Experimental Study of the Hydrodynamics and Cluster Formation in a Circulating Fluidized Bed

1990 Annual Report

**M. Gautam
E. Johnson**

January 1991

Work Performed Under Contract No.: DE-FC21-87MC24207

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
Morgantown, West Virginia**

**By
West Virginia University
Mechanical & Aerospace Engineering
Morgantown, West Virginia**

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615)576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

**Experimental Study of the Hydrodynamics and
Cluster Formation in a Circulating Fluidized Bed**

1990 Annual Report

**M. Gautam
E. Johnson**

Work Performed Under Contract No.: DE-FC21-87MC24207

**For
U.S. Department of Energy
Office of Fossil Energy
Morgantown Energy Technology Center
P.O. Box 880
Morgantown, West Virginia 26507-0880**

**By
West Virginia University
Mechanical & Aerospace Engineering
Morgantown, West Virginia 26506**

January 1991

SUMMARY

A novel non-invasive gas-solid flow measuring technique is being developed and tested for studying the hydrodynamics inside the riser of a Circulating Fluidized Bed (CFB). First of the two aims of the overall program, namely, design, development and testing of the the technique to characterize the particle and gas velocities in two-phase flows was accomplished in the past year. The second objective, that of making detailed measurements of gas and solid phases in the rises of a cold CFB model to investigate the phenomena of clusters and streamers for different bed operating parameters will be accomplished in the remaining phases of the program.

The "fringe-mode" laser Doppler anemometry concept has been modified and extended by using particles coated with a fluorescent dye and introducing a narrow band pass filter in the receiving optics. The technique permits optical discrimination between the scattered light (laser wavelength from undyed particles) and the fluorescence emission (longer wavelength). Results from extensive testing of various dye-solvent combinations, counter processor settings, signal-to noise optimization and subsequent flow measurements in the test section have shown that the technique can effectively discriminate between two classes of particles --the smaller seed particles for the gas phase data and the larger bed particles. Use of a two-watt Argon-Ion laser assisted in the non-

intrusive probing of the gas-solid flow and in enhancing the signal-to-noise ratio. An uncertainty analysis of LDA measurements is presented. Design of the cold flow CFB model, presently under fabrication, is outlined in this report. The Plexiglas CFB model will be employed for the riser core-annular flow studies using the fluorescence-emission based laser-Doppler anemometry. The results from this study will present a unique detailed description of the complex gas-solid behavior in the CFB riser.

Table of Contents

Chapter 1	Introduction	1
Chapter 2	Literature Review	4
2.1	Circulating Fluidized Bed	4
2.2	Velocity Measurement Techniques in Two-Phase Flow	11
Chapter 3	Experimental Equipment and Procedures	19
3.1	Experimental Equipment	19
3.1.1	Horizontal Test Section	19
3.1.2	Laser Doppler Anemometer	23
3.1.3	Laser-Induced Fluorescence Emission Based LDA	28
3.1.4	Flow Seeding	30
3.1.5	Data Acquisition System	34
3.2	Experimental Procedures	36
3.2.1	LDA Velocity Measurements	36
3.2.2	Uncertainties in LDA Measurements	42
3.2.3	Dye Optimization	45
3.2.4	Particle Dying Procedure	46
3.2.5	Calibration Techniques	47
Chapter 4	Design of the Experimental Circulating Fluidized Bed	50
4.1	Design of the Distributor	52
4.2	Design of the Riser	52
4.2.1	Diameter of the Riser	52
4.2.2	Height of the Riser	54
4.3	Design of the Cyclone	55
4.3.1	Dimensions of the Cyclone	55

4.3.2	Calculation of the Pressure Drop	57
4.4	Design of the Hopper	58
4.5	Design of the L-Valve	58
Chapter 5	Results	62
5.1	Dye Optimization	62
5.2	Calibration	63
5.2.1	Calibration Using the Undyed Titanium Dioxide in the Horizontal Test Section	63
5.2.2	Using the Calibration Wheel	64
5.2.3	Sensitivity Tests	65
5.2.4	Calibration Using Dyed/Undyed Glass Shot in the Horizontal Test Section	66
Bibliography		104
Appendix		110

List of Figures

Fig. 2.1	Typical Signals from (a) Solid Phase Particle and (b) from Seeding Particle	13
Fig. 3.1	Schematic of the Test Section for Technique Optimization	20
Fig. 3.2	Schematic of the Test Loop Support	22
Fig. 3.3	Schematic of One-Component LDA System without Frequency Shift	26
Fig. 3.4	Ray Diagram for the Axial Velocity Component Measurements	27
Fig. 3.5	Laser Doppler Anemometer Measuring Volume	29
Fig. 3.6	Fluidized Bed Feeder	33
Fig. 3.7	Schematic of the Data Acquisition System	35
Fig. 3.8	Logic Print of the Master Computer Interface Unit	37
Fig. 3.9	Absorption and Emission Spectra of Rhodamine 6-G	39
Fig. 4.1	Circulating Fluidized Bed	51
Fig. 4.2	Distributor Plate Flow Characteristics (MOTT POROUS MEDIA)	53
Fig. 4.3	Cyclone	56
Fig. 4.4	Schematic of the Particle Hopper	59
Fig. 4.5	Schematic of the L-Valve	61

CHAPTER 1

INTRODUCTION

There is increasing interest in operating fluidized beds at high gas velocities where gas-solids contacting may be much improved. In the form of a circulating fluidized bed, it has been recognized as a key to efficient gas-solid processing. The several advantages offered by CFB's over the conventional fluidized bed systems such as uniform bed temperature, reduced aggregation and agglomeration have resulted in a recent vote of confidence by the U.S. utility companies.

To date, the understanding of the CFB's and fundamental research into the underlying phenomena of high-velocity fluid beds and systematic compilation of design data is at best sketchy and even the most rudimentary model and correlation which would permit design are lacking. There are three different flow regimes: bubbling, turbulent, and fast fluidization. In the bubbling regime, gas crosses a horizontal section through a fluidized bed by the following mechanisms:

- (i) translation of bubble voids, often called visible bubble flow;
- (ii) flow through the bubbles relative to them, often called the through flow component;
- (iii) interstitial flow relative to the particles in the dense phase;
- (iv) net flux of interstitial voids moving with particles.

Lanneau (1960) was the first to recognize the transition from bubbling to turbulent fluidization and the potential advantages of operating in the turbulent regime. What Kehoe and Davidson (1971) saw as the velocity of the gas flowing through narrow beds of fine powders was a breakdown of the slugging regime into a state of continuous coalescence - virtually a channelling state with "tongues" of fluid darting in zigzag fashion through the bed. Kehoe and Davidson (1971) coined the word "turbulent" to describe this state. They reported that this transition to the turbulent fluidization occurred at a velocity equal to three times the terminal velocity of particles belonging to the smallest cut. The transition from bubbling to turbulent fluidization is gradual and spans a range of gas velocities. Clusters also exist in this stage.

The transport velocity may be regarded as the boundary which divides vertical gas-solid flow into two groups of states. Below it lie the bubbling and the turbulent fluid beds. The bed in general experiences no net flow and remains at the bottom of the holding vessel. Above, lie the transport regimes which encompass a wide range of states from dilute-phase flow to the fast bed condition. This occurs at twenty times the terminal velocity.

The fast bed condition is marked by relatively high solid concentrations, aggregation of the particles in clusters and strands which break apart and reform in rapid succession, extensive backmixing of solid, and slip velocities of the individual particles. A way to create the dense suspension is to circulate the very solid emerging from the top of the reactor to its bottom.

Currently, the published work in circulating fluidized beds falls short of answering the questions on the intimately interacting gas-solid flow fields and their influence on each other at a localized level in the riser. Therefore, there is little information available to design engineers for use in optimizing fuels, improving reaction rates of increasing combustion efficiencies. The object of the study of the air-solid two-phase flow is to clarify the flow mechanism resulting from interaction between gaseous and solid phases in the riser.

To study the hydrodynamics and cluster formations in a circulating fluidized bed riser, a non-invasive gas-solid flow measuring technique has been developed. This technique utilizes a Laser Doppler Anemometer (LDA) system and is based upon the fluorescence-emission from doped particles which allow differentiation between particle size and obtain velocity measurements. This report presents results from the investigation of using fluorescence-emission based LDA technique for gas-solid flow measurements. Detailed measurements of gas and solid flows in the riser of a cold CFB will be taken at different operating parameters to study the phenomena of clusters and streamers.

This report outlines the tasks accomplished in the first year of the project. A detailed literature review in Chapter 2 is followed by a chapter on the experimental equipment, procedures and various analyses of the techniques adopted for the project. Chapter 4 describes the design of the components of a CFB (a transport cold model) which is currently being fabricated to study the flows in the riser.

CHAPTER 2

LITERATURE REVIEW

A review of the published literature has revealed several works on the flow behavior in circulating fluidized beds. Presented here are only the recent investigations into the hydrodynamics of CFB's and the cluster phenomena in the risers.

2.1 Circulating Fluidized Bed Hydrodynamics

Yoshioka et al. (1987) found that the velocity of the fluidized particles could be determined by measuring the deflection of a spring plate inserted into the bed. The bubbles were detected with the aid of a light transmitting probe. The probe detected bubbles by the intensity of the light being transmitted between the two elements of the probe. Yoshioka developed profiles of the velocity ratio of the fluidized particles, of the bubble fraction, and of the ratio of tracer concentration. He found that the bubbles moved upward away from the center of the bed whereas the particles move upward along the center of the bed but downward near the wall with a circulatory motion.

Drahos et al. (1988) identified three basic flow regimes when the gas velocity was decreased at the given solid feed rate, namely: uniform dilute flow, with particles flowing upwards in a uniform dispersion; dense flow, characterized by the presence of clouds of particles and voids free of solids; and bubbling dense bed, with the accumulation of solids in the bottom part of the column, forming there a dense bed with the distinct upper surface

level. These regimes were found by introducing pressure fluctuations.

Berruti and Kalogerakis (1989) developed a mathematical model capable of predicting the two-phase flow characteristics and required only the experimental average voidage profile along the riser and the net solids circulation rate. The model has been tested in different regimes, and the model predictions compared well with experimental results.

Rhodes and Geldart (1989) formulated pressure losses in the riser, primary cyclone, solids control valve, and slow bed. Their model enabled axial density profiles to be predicted. The terms of entrainment from bubbling beds and choking in pneumatic conveying were the basis for this mathematical model.

Kato et al. (1989) measured the axial particle holdup and the axial pressure drop in a fast fluidized bed. They concluded that the superficial circulation rate of particles, tube diameter, particle Reynolds number, and axial distance from distributor affected the particle holdup. An empirical equation for the location of the inflection point between the dense and dilute region of particles and an empirical equation for particle holdup in a fast fluidized bed were obtained.

Biswas et al. (1987) checked the validity of published choking correlations. By controlling and measuring gas and solid flowrates independently, it was shown that it was possible to delineate the limiting operating flowrates for the fast-fluid bed regime and to obtain a quantitative flow regime defining the limits of fast fluidization. The transition gas velocity was defined as the upper

critical gas velocity. For a given solid flux, the upper critical gas velocity represents the highest gas velocity for operation in the fast fluidization mode. The Yousfi and Gau (1974) correlation underpredicts the upper critical velocity by between 15 and 25%, depending on the magnitude of the solid gas flux. The transition from lean-phase conveying to fast fluidization was found to be analogous to the so-called choking transition in pneumatic conveying.

Carey (1987) goes over the early work of Richardson and Zaki (1954) which gave a relation between concentration and the settling velocity of suspended spherical particles. He also derived equations to define the n term in the Richardson and Zaki equation.

Dry (1986) developed an experimental technique to examine radial gas concentration profiles. Solids were found to appear to congregate on the outside of the lift pipe - fast bed bend. He found the distance above the grid the gas-only radial profile is fairly flat. He also found that at gas velocities between 2 m/s and 4 m/s, the core/annulus distribution is maintained, but at 6 m/s the lean core migrates across the tube to the outer wall. Also, Dry (1987) found that at higher velocities, the coarse particles tend to concentrate along the wall region. The coarse particles were observed to move from the top of the bed toward the bottom.

Horio et al. (1989) developed scaling laws for circulating fluidized beds. His theory was based on the clustering annular flow model. Experiments were performed using two geometrically similar CFB cold models. Similarity was assumed since the voidage

distributions and the annular flow structures were similar and so were the cluster voidages.

Salem and Gibbs (1987) investigated the feasibility of a circulating system, where the driving force for transporting particles is provided by jet pumps. The jets would enable and even distribution of the circulating solids and could also be used to provide a multi-location feeding and withdrawal system. The jets could also be computer controlled to compensate for changes. Salem and Gibbs found that large particles were easier to circulate with jets.

Fox et al. (1989) studied the circulation of particles between two fluidized beds for an open-loop circulation. They developed equations to calculate the driving and resisting forces. The authors found that the most efficient way to control the circulation rate of solids was by varying the valve of the vertical resisting force in the downflowing compartment. This adjusts the state of de-fluidization.

Knowlton et al. (1986) discussed the design of lockhoppers which transfer solids from a high-pressure vessel to atmospheric pressure. They found that a restricted pipe discharge system can lower capital cost, giving continuous discharge of solids, and result in a much lower valve maintenance cost. Additionally, the gas requirements were found to be less.

Mountzaris and Jackson (1986) investigated the effects of aeration in standpipes. Their model was based on differential continuity and momentum balances for a system which consisted of a mass flow hopper, a vertical aerated standpipe and a flow

restricting device at its lower end. The authors developed equations for the design of each of the above components. With one aeration point, they obtained and discussed twelve flow regimes.

Shingles and Silverman (1986) studied the pressure profile in a stand pipe. Their results showed that the gas compression effect going down the standpipe of the reactor is limited. Sufficient entrapped aeration from the hopper entered the top of the standpipes to enable a fluidized dense-flow regime to exist over the entire length of the standpipe.

Extensive reviews of circulating fluidized bed research are presented by Yerushalmi et al. (1979). They concluded that the transition from bubbling to turbulent fluidization is represented by the fluctuations of dynamic pressure at any point across the bed and the pressure drop across the bed. This transition is characterized by velocities U_c and U_k . U_c is the velocity at the peak pressure fluctuations and U_k is the velocity at which pressure fluctuations level off marking the turbulent regime. Both velocities increase with particle size and density.

The turbulent regime has two interacting phases, dense phase and lean phase, which result in the bed having properties of both individual particles and clusters. Dense phase consists of closely packed clusters and streamers of particles with downward motion. Lean phase is characterized by individual particles and small clusters with upward motion. Yerushalmi et al. (1978) also concluded that the fast bed condition is characterized by high solid concentration, large cluster formations, backmixing of solids, and slip velocities greater than freefall velocities of

individual particles by an order of magnitude.

Bader et al. (1989) conducted tests in the riser of a CFB with FCC catalyst to determine the degree of gas/solid contacting the fast fluidized bed regime using an intrusive sampling probe and helium tracer technique. They concluded that the solid distribution in the riser is of a core-annulus flow type which high velocity dilute phase core is surrounded by slower, denser solid annulus. The solids flux profile in the riser was determined to be parabolic. The solids flux core was 3 to 5 times the average solids flux and the wall flux flows downward 6 to 8 times the average flux in the riser. The radial particle velocity distribution in the riser was found to also be parabolic through the use of a pitot tube. The application of a pitot tube for this purpose is open to question. It was also concluded that there was substantial backmixing of solids in the riser.

A quantitative discussion and comparison was done by Neale et al. (1972) exploring possible solutions to the problem of creeping flow relative to an isolated permeable sphere. They suggested the most satisfactory solution is based upon a generalized Brinkman's extension of Darcy's Law. It was concluded that internal permeation within a high porosity permeable particle usually cannot be neglected.

Jackson's (1963) linear stability analysis of dense beds of solid particles operating near minimum fluidization was extended by Grace and Tuot (1979) to apply to more dilute systems. They postulate the origins of particle clusters which occur due to the instability of uniform dispersions of particles in a gas.

Guilin et al. (1984) studied the characteristics of gas mixing a fast fluidized bed which was 8 m high, 115 mm inside diameter, and had a 100 mm inside diameter downcomer. The bed material was spherical silica-gel particles with a diameter of 0.22 mm. They concluded that the bed could be divided into two regions; the variable voidage zone (4 m from the bottom) and the constant voidage zone. The constant voidage zone is characterized by a constant pressure drop and a uniform axial average voidage. It was revealed that the axial mixing could be neglected.

Yerushalmi et al. (1978) studied the extent of gas backmixing in a catalyst fluidized bed at gas velocities spanning the bubbling, turbulent, and fast bed regimes. The regimes were characterized with high backmixing in bubbling, diminishing backmixing in the turbulent regime, and plug flow in the fast regime.

Lean phase properties were explained with equations for cluster size and terminal velocity by Subbarao (1986). Slack (1963) studied the sedimentation of clusters composed of a few particles in a viscous medium.

The effects of hydrodynamic aggregate size, shape, and porosity have upon settling velocity was analyzed by Hamdullhpur et al. (1989). The slip velocity ratio (U_s/U_p) was found to increase as more particles were incorporated within the aggregate. Hydrodynamic aggregates undergo internal circulation since there are no forces holding particles in position. The forces holding the aggregate together are small and therefore making deformation and disruption easy. They concluded that the relative motion

between the aggregate and the fluid results in the fluid passing through or around the aggregate; however, this does not affect the drag coefficient except at high porosities (> 0.85).

Sutherland and Tan (1970) applied Stoke's solution for flow around a solid sphere to creeping flow outside a permeable sphere and applied Darcy's Law to describe the internal flow. This was in an attempt to obtain limits on permeability for any size aggregate beyond which internal flows may be neglected.

The concept of continuity wave and cluster formation was used to derive a relationship for choking in vertical pneumatic flow by Yang (1983). These relationships were used by Yang (1984) to develop mechanistic models to predict the transitions between the different regimes of fluidization for fine particles. The continuity wave equation was used to predict the transition between bubbling and turbulent regimes. The transition between dilute phase and fast fluidization regimes was approximated using the choking correlations (Yang, 1984).

The computation of bed-solid circulation rates and patterns induced by a central jet and slug motion was performed by Kececiloglu (1989). The experiment measured profiles of tracer particles concentrated inside a fluidized bed.

2.2 Velocity Measurement Techniques in Two-Phase Flows

Yianneskis (1987) and Gautam et al. (1987) have reviewed recent developments in optical and unobtrusive techniques based on laser Doppler anemometry that permit the measurement of the velocities and/or of the sizes of particles.

Durst (1982) reported on some techniques in laser Doppler

anemometry with emphasis on combined systems which permit simultaneous measurements of particle velocities, size distributions and concentrations. The blocking of the incident and the scattered light by the suspensions in two-phase flows along with the complexities involved in separating the information from the two-phase remains a major research area.

Several researcher have used LDA in two-phase flows for making velocity, concentration and particle size measurements (Durst and Zare, 1975; Durst and Umhauer, 1975; Birchenough and Mason, 1976; Yule et al., 1977). Levy and Lockwood (1983), Modaress et al. (1982) and Yianneskis and Whitelaw (1984) measured both the gas and the solid phase velocities. Figure 2.1 shows a typical output signal from the photomultiplier tube and I_p and I_p' are the pedestal amplitudes of the dispersed and the continuous phases, respectively. Discrimination between the light scattered by large particles (mainly from the solid phase) and from the small particles (mainly from the gas phase) was accomplished by setting a variable threshold level on the photomultiplier output. However, they did not account for the trajectory ambiguity which originates from the inherent non-uniformity of illumination in optical measuring volume (Farmer, 1972). Durst and Umhauer (1975) attempted to by-pass this problem by employing a second optical system, designed for particle sizing, which was focused around the same measuring volume. Lee and Srinivasan (1978) suppressed the ambiguity due to non-uniform distribution of incident light inside the measuring volume by electronically isolating the effective measuring volume to the central core portion of the original

Figure 2.1 Typical Signals from (a) Solid Phase Particle and (b) from a Seeding Particle

measuring volume. Lee and Durst (1982) employed a technique reported by Durst (1975) to carry out local velocity measurements in particulate two-phase flows. By combining the use of automatic filterbanks with amplitude discriminators and photodiodes, they were able to minimize the trajectory ambiguity and record signals from the two-phases. Maeda et al. (1980) separated the signals by taking the wave number into account in addition to the pedestal amplitude, and measured gas-solid two-phase flow in a vertical pipe. Tsuji and Morikawa (1982) employed an amplitude validation circuit and set threshold values for the pedestal and Doppler components of the Doppler signal by which simultaneous measurements of the gas and solid phases could be made. Modares and Tan (1983) employed a two color LDA with two overlapping measuring volumes of different diameters. The Doppler signals from the smaller volume yielded the velocity information of the gas phase and the discrimination between the two-phases was effected on the basis of the pedestal amplitudes of the signals from the larger volume. The velocity of the particles was obtained by reducing the photomultiplier sensitivity. Stevenson et al. (1975,1977) investigated the concept of laser-induced fluorescence coupled with an LDV system for particle size and discrimination in aerosol droplets and velocity measurements. Their "fringe mode" fluorescence velocimetry concept was investigated by adding fluorescent dyes to various solvents. The scope traces of the fluorescence signals showed that the quantum yield and the attainable dye concentration are strongly dependent on the solvent. Particle fluorescence was induced with 0.01 molar solution of

Rhodamine 6-G in ethanol (Stevenson et al., 1975) and Rhodamine 6-G in a 50-50 volumetric mixture of benzyl alcohol and ethylene glycol (1977). They suggested that further studies were required to determine the optimum dye-solvent combinations that will permit high dye concentrations to be attained without reducing the quantum yield.

Patrose and Caram (1982) made measurements of particle velocities in a transparent two-dimensional bed. The transit timing type optical consisted of five fibers located inside a hypodermic needle which in turn, was introduced into the bed from the top. They used an LDA system also to make particle velocity measurements. They observed good agreement between the two techniques leading them to conclude that their probe could be used for particle velocity measurements in fluidized beds. All of these measurements were made at the distribution grid orifices and they have mapped the particle flow field for bed heights of 43.2 mm and 184 mm. However, they did not measure the fluid velocities.

Johnston et al. (1975) used an LDA in a fixed bed of transparent spheres to measure the local velocity of liquid whose refractive index matched liquid-solid fluidized bed flow system and made detailed LDA measurements of particle velocity in its interior. But, the refractive index matching requirement limits the use of this technique to a few liquid-solid systems. They did not make any fluid velocity measurements inside the bubbles. Durrett et al. (1985) designed a corrective lens for use with an LDV system. The lens negates many of the aberrations caused by the cylindrical wall when LDV measurements are made off the plane of

symmetry. Durrett et al. (1988) experimentally mapped the flow field of an axi-symmetric sudden expansion air flow using an LDV with a correction lens system. The implementation of the correction lens eliminated the optical aberrations thus allowing measurement of the axial and radial velocity components. The mean velocities, turbulence intensities, turbulent kinetic energy, and Reynolds stresses were measured and/or derived.

Lai and Faeth (1987) describe a combined LDA and LIF system to simultaneously measure gas velocities and concentrations at a point. Turbulent mixing between two streams and turbulent transport from surfaces can be studied using this system. The extremely expensive LDA/LIF system has good spatial resolution and frequency response, operated in particle-containing environments and near surfaces, and performs acceptably at high turbulence intensities.

Lourenco et al. (1986) presented a new technique for two-dimensional flow visualization and measurement of instantaneous velocity and vorticity fields. The Particle Image Displacement Velocimetry (PIDV) involves taking multiple photographs of an illuminated plane (created with a ruby or a NdYg laser or a continuous wave laser with shutter device) while the seeded particles pass through. A moving pattern is created by the light scattered from the seeded plane. The relative information is then obtained from an analysis of the photograph. It is well suited for the study of unsteady or complex flowfields.

A laser velocimeter based on a combination of a crossed beam laser velocimeter (LDV) and laser-induced fluorescence is proposed

by Keefer (1987). The system, laser fluorescence velocimeter (LFV), utilizes the temporal and spatial characteristics of the fluorescence induced by a crossed-beam interference region to determine flow velocity. The advantages of the system are: applications to both strong and weak accelerated flows, no particles are required, discrimination against undesirable particle scattering and background radiation due to the spectral shift of fluorescence, and the continuous LFV signal has its own advantages in signal processing.

LDA based diagnostics have been employed by some investigators to measure the elutriation rates in the freeboard region where the particle loading is low, thus producing less interference. Levy and Lockwood (1983) used an LDA to measure gas-phase velocities above a bed in which 400 to 1000 micron sand was fluidized. They used a rectangular channel 0.6 m x 0.3 m x 2.4 m (height) with 19 mm thick float glass to enable clear passage to the laser beams.

Kale and Eaton (1985) used a single component LDA to make gas phase velocity measurements in the freeboard region. Using a fluidized bed with a 150 mm square cross section and a variable-angle diffuser in the freeboard region, they showed that a particle loading of as low as 2% by weight significantly alters the freeboard fluid mechanics.

The literature review shows several pioneering works on the hydrodynamics of circulating fluidized beds but experimental studies have been performed only under limited conditions. Specifically, there is no detailed experimental data available on the flow field inside the riser in circulating fluidized beds. The

gas-solid flow structure is of paramount importance in reactor modelling. The absence of experimental data is due partly to the lack of appropriate experimental techniques. Therefore, a test facility was constructed and a non-intrusive technique was developed for measuring the velocity of fluid and particles flowing through the riser. Details of the experimental apparatus and the procedures adopted are given in the following chapter.

CHAPTER 3

EXPERIMENTAL EQUIPMENT AND PROCEDURE

The research program involves two major aspects. First, is the modification of the conventional Laser Doppler anemometry technique by employing the laser-induced fluorescence emission phenomena in order to effectively probe polydisperse gas-solid flows. The second aspect is to apply this technique to study the gas-solid flow structure and clusters in the riser of a circulating fluidized bed. This chapter describes the equipment and instrumentation designed and built to achieve the above goals. A description of the experimental procedures adopted to-date is given in the second half of this chapter.

3.1 Experimental Equipment

The equipment and the instrumentation used in this research program are described in the following order:

- i) Horizontal Test Section
- ii) Laser Doppler Anemometer
- iii) Flow Seeding
- iv) Data Acquisition System

3.1.1 Horizontal Test Section

The 13 ft. horizontal section consists of two pieces of 5 ft. long clear, cast acrylic tubing and a clear Pyrex glass section 4 ft. long (see Figure 3.1.). Both the acrylic and glass sections have an outer diameter of 2 in. and an inner diameter of 1.95 in. The sections of tubing are fastened together using a rubber

Figure 3.1 Schematic of the Test Section for Technique Optimization

coupling which provides an airtight seal at the joint. The test section is made of clear Pyrex because, unlike Plexiglas, it is resistant to scratches and surface marring caused by the abrasive seeding particles thus providing unrestricted optical access to the internal pipe flow. The condition of transparency is necessary when using the LDA system to ensure reliable measurements.

The lightweight supports for the tubing are 8 in. lengths of angle iron welded to a stand (see Figure 3.2). The stand is bolted to a wooden support which is in turn clamped to the table. The tubing rests on the supports and is secured with ring clamps. There are two supports for each section of tubing (6 in all) to ensure stability. The set up has been aligned and leveled. Particles exit the glass section and are fed to the pre-filter and HEPA filter via flexible driver hose 3 in. in diameter. The HEPA filter is a Flanders double nipple HEPA filter (part 007-4-03-02-IU-N2N2) capable of handling 35 cfm with an efficiency of 99.9% of 0.3 μm particles. The pre-filter (Flanders # BFDL2) is constructed of a polyester media and is supported by a lightweight frame.

Downstream from the filters is the 2 Hp Baldor centrifugal air blower (Model VM3155) connected with flexible dryer hose 4 in. in diameter. The flow rate through the system can be controlled using a Reliance AC motor controller connected to the blower. The flowrate is checked against readings from a pitot-static tube installed in the system. The exhaust from the blower flows to a hood through flexible dryer hose 3 in. in diameter. This hose does not collapse under maximum suction of the blower and is sufficient

Figure 3.2 Schematic of the Test Loop Support

for use throughout the setup.

3.1.2 Laser Doppler Anemometer

Pointwise measurements of the gas-solid flow are being made using an Argon-Ion (514.5nm) gased laser Doppler anemometer (LDA). The objectives of this program demand the use of a non-intrusive fluorescence-emission based LDA technique. The unique advantages offered by LDA's over other fluid flow instrumentation are listed below:

- a. The measurement is non-invasive in nature hence it retains all the flow field characteristics.
- b. No calibration is required. It has a linear response to fluid velocity.
- c. Measures the desired component of velocity directly in any complex flow field. The quantity measured by the LDA is the projection of the velocity vector on the measuring direction defined by the optical system.
- d. A very high dynamic range--can measure velocities ranging from microns/sec to hypersonic speeds.
- e. In addition the high spatial and temporal resolution, combined acousto-optical and electronic shifting allows measurement of reversing flows (flows which change direction).

The only requirements for LDA application are (i) the fluid must be reasonably transparent to the laser light and that there must be a clear optical access through a window to the measuring point, and (ii) presence of seed particles (light scattering

sources) in the field.

The performance of the LDA is described by some important parameters. They relate the calibration constant, the dimensions of the measuring volume and the number and separation of interference fringe lines in the measuring volume to input parameters such as laser wavelength, beam waist parameters, LDA beam separation, beam expansion and measuring distance. The important parameters are:

$$\text{Doppler Frequency} \quad f_d = \frac{2u_x}{\lambda} \sin \left\{ \frac{\theta}{2} \right\}$$

$$\text{Fringe Spacing} \quad \delta_f = \frac{\lambda}{2 \sin \left\{ \frac{\theta}{2} \right\}}$$

$$\text{Diameter of Focused Laser Beam} \quad d_f = \frac{4 f \lambda}{\pi E d_i}$$

$$\begin{aligned} \text{Measuring Volume Dimensions} \quad d_x &= \frac{d_i}{\cos \left\{ \frac{\theta}{2} \right\}} & d_y &= d_i \\ d_z &= \frac{d_i}{\sin \left\{ \frac{\theta}{2} \right\}} \end{aligned}$$

$$\text{Calibration Factor} \quad C = \frac{\lambda}{2 \sin \left\{ \frac{\theta}{2} \right\}}$$

where:

λ Laser wavelength
E Beam expansion factor
d Diameter of laser beam waist before expansion
d Diameter of focused laser beam
D Beam separation before expansion
 θ Beam intersection angle
f Focal length of optics
 $\bar{u}$ Velocity component in measuring direction

A block diagram of the system with and without frequency shift is shown in Figure 3.3. Currently, no frequency shift is being employed. The light source is a 2 watt LEXEL Argon-Ion laser emitting a single line at 514.5 nm. The laser can emit only a single laser line as a result of the insertion of a second cavity, etalon, in the laser cavity. This adds to the stability of the laser and reduces the noise. The system is configured in a dual beam forward-scatter mode. A DANTEC type 55x190a Counter Processor is being used and the future tasks in this year's work plan will involve use of DANTEC type 55n10 Frequency Shifter along with a Bragg Cell (acousto-optic cell) will be used. The system is interfaced with a dedicated PDP-11 laboratory computer which is used for acquiring and analyzing the data. A ray diagram of the optical set-up is shown in Figure 3.4.

1	Cover and Retarder
2	Support
3	Beamsplitter Neutral
4	Beam Displacer
5	Backscatter Section
6	Lens Mounting Ring
7	Front Lens Achromatic (600 mm)
8	PM Optics
9	Interference Filter 514.5 nm
10	PM Section
11	Mounting Bench

Figure 3.3 Schematic of One-Component LDA System Without Frequency Shift

Figure 3.4 Ray Diagram for the Axial Velocity Component Measurements

3.1.3 Laser-Induced Fluorescence Emission Based LDA

Conventional LDA systems are generally operated in the fringe mode as shown in Figure 3.5. Two coherent, monochromatic equal-intensity Gaussian beams intersect at their waists and form a standing electromagnetic wave distribution in the intersection zone, the measuring volume, which may be visualized as a set of planar fringes perpendicular to the plane of the two beams and parallel to their bisector. The generation of Doppler signals is explained by the time-varying intensity of the light scattered by a particle passing through the fringe pattern. The modulation frequency under the Gaussian envelope is the Doppler frequency as given above.

The detection process is basically incoherent, since the intensity fluctuation is the measured quantity. This allows for modification of the conventional LDA in which the standing electromagnetic field induces a time-varying fluorescent emission from particles treated with a dye. The wavelength difference between the incident beams and the detected fluorescent emission resulting from the use of fluorescence emission based LDA system. Fluorescent emission, being spatially isotropic and unpolarized eliminates any reduction in signal modulation due to light of unequal amplitude and polarization interfering at the photo-tube (Durst et al., 1973). Thus large aperture receiving optics will be very effective especially when large input beam angles are used. The fluorescence emission based LDA permits discrimination between different sized particles as well as between phases in multiphase flows.

Figure 3.5 Laser Doppler Anemometer Measuring Volume

3.1.4 Flow Seeding

Investigations of the permissible size of a single seeding particle have been carried out by Melling and Whitelaw (1973). In this investigation, titanium oxide powder was used as seeding material for gas phase measurements. However, the titanium dioxide particles are not spherical enough to impart a high scattered light intensity which is necessary to obtain the best LDA signal. Titanium dioxide particles also performed poorly in the fluorescent dyeing procedure. The adsorption of the dye solution proved to be somewhat less than expected.

The behavior of dilute concentrations of particles in a turbulent fluid has been investigated (Tchen, 1947) by considering the equation of motion, the Basset-Boussinesq-Oseen equation, for a spherical particle in a fluid:

$$\begin{aligned} \frac{\pi}{6} d_p^3 \rho_p \frac{du_p}{dt} - 3 \pi \mu d_p (u_f - u_p) + \pi d_p \rho_f \frac{du_f}{dt} + \frac{1}{2} \cdot \frac{\pi}{6} d_p^3 \rho_f \left[\frac{du_f}{dt} - \frac{du_f}{dt} \right] + \\ + \frac{3}{2} d_p^3 \rho_f \sqrt{\pi \nu} \int_0^t d\xi \left[\frac{du_f}{d\xi} - \frac{du_p}{d\xi} \right] / \sqrt{t - \xi} \end{aligned} \quad (3.1.1)$$

where, the origin and meaning of individual terms of the equation is described in detail elsewhere (Hinze, 1959; Hjelmfelt and Mockros, 1966).

Equation 3.1.1 may be divided by the particle mass and rewritten as:

$$\begin{aligned} \frac{du_p}{dt} = & 36 \frac{\nu}{d_p^2 (2\rho_p/\rho_f + 1)} (u'_f - u_p) + \frac{3}{(2\rho_p/\rho_f + 1)} \frac{du_f}{dt} + \\ & + \frac{18}{d_p (2\rho_p/\rho_f + 1)} \sqrt{\nu/\pi} \int_0^t \frac{(du'_f/dt - du_p/dt)}{t - \xi} d\xi \end{aligned} \quad (3.1.2)$$

Neglecting the history and added mass terms in addition to the pressure gradient effect gives:

$$\frac{du_p}{dt} = \frac{36\nu}{d_p^2 (2\rho_p/\rho_f + 1)} (u'_f - u_p) \quad (3.1.3)$$

Particle relaxation time is defined as:

$$\tau_p = \frac{d_p^2 (2\rho_p/\rho_f + 1)}{36\nu} \quad (3.1.4)$$

Substituting Equation 3.1.4 in Equation 3.1.3 gives:

$$\frac{du_p}{dt} = \frac{1}{\tau_p} (u_p - u'_r) \quad (3.1.5)$$

Equation 3.1.5 indicates that the system behaves as a first order system with a relaxation time, τ_p . The amplitude response of such a system is given by:

$$A_p(\omega) = \frac{1}{\sqrt{1 + (\tau_p \omega)^2}} \quad (3.1.6)$$

Applying Equation 3.1.6 to seed particles (typically less than 2 microns) yields a frequency response of 430 Hz at an amplitude ratio (A_p/A_r) = 99% and a response of 6030 Hz at an amplitude ratio 50%.

Fine powders and glass beads mixed with larger beads in fluidized bed feeders have been successfully used by several investigators (Jurewicz et al., 1975; Durst et al., 1982; Kale and Eaton, 1985; Gautam, 1989) and have not had problems with smaller particles agglomerating on the glass beads such as to remove all of them from the flow.

The seeding material is provided by a fluidized bed feeder (See Figure 3.6) consisting of a cylindrical tube, 43 cm long and 3.5 cm in diameter with a cone shaped distributor for uniform supply of compressed air. To enhance uniform fluidization 1 mm to 1.5 mm

Figure 3.6 Fluidized Bed Feeder

glass beads were introduced in the vessel. The vessel walls were periodically tapped to prevent particles from clinging to it. The seeding material is injected through rubber tubing to a nozzle. The nozzle is mounted in the center of the acrylic tubing at the beginning of the horizontal section using a vertical stand and clamp.

3.1.5 Data Acquisition System

The data acquisition system for this investigation is controlled by PDP-11 microcomputer manufactured by Digital Electronics Corporation. The DANTEC type 55x190a LDA Counter Processor is interfaced to the computer. The schematic of the entire data acquisition system for velocity measurements is shown in Figure 3.7.

Software was developed in FORTRAN and PDP-11 MACRO Assembly Language to sequentially start the data acquisition via the LDA system and reduce the data. The software developed for this purpose is user friendly and provides complete automation. PDP-11 micro is able to accept data at a maximum rate of 10 KHz while the LDA Counter Processor is able to give data at a rate of up to 1 Mhz. In the absence of a Direct Memory Access (DMA) link, data recording at a rate fast enough so as not to affect the operation of the experiment is not possible. During the bed operation, the data is stored in arrays in the memory and processed at the end of each run. At the end of each run, the raw data (on velocity and sample interval time) is analyzed and stored on the 20 MB hard disk. The post-test data from the PDP-11 computer is uploaded to

Figure 3.7 Schematic of the Data Acquisition System

the mainframe computer systems for further reduction and analysis. The data is plotted using SAS and the downloaded to a MacIntosh computer to obtain a hard copy of the graph. The custom built interface unit (Gautam, 1989) services the test facility during the flow field measurements with the LDA. The logic diagram is shown in Fig. 3.8.

3.2 Experimental Procedures

A description of the experimental procedures adopted is given in this section. The major tasks have been divided as follows:

- i) LDA signals
- ii) uncertainty in LDA measurements
- iii) optimization of the dye strength
- iv) particle dying procedure, and
- v) calibration technique.

3.2.1 LDA Velocity Measurements

The utility of LDA in measurement of single phase flows has been demonstrated beyond question. However, the use of LDA in gas-solid multiphase flows is still in a developmental stage. New instrumentation such as the Phase Doppler Particle Analyzer and the transit-time type of devices from INSITEC are now on the market but they are severely limited in their capabilities and yet very expensive. For monodispersed and lightly loaded flows, the light scattered from seed particles small enough to follow complex fluid motions, including turbulence, is converted into velocity information. For flows with higher particulate loading or with

polydispersed flows, other LDA techniques using amplitude and frequency discrimination are required to distinguish between fluid and particle velocity fields. However, these techniques have severe limitations of their own (Gautam et al., 1987). The velocity measurements were carried out using the LDA in the forward scatter mode. The receiving optics were placed at an angle of 30 degrees off of the central axis of the transmitting optics to avoid the light reflected from the glass faces from entering the receiving optics and with consequent improvement in the signal-to-noise ratio. All of the axial component measurements were made along the horizontal plane at three radial locations. However, passage of the laser beams through the media of different indices of refraction, air-glass-air, resulted in spatial displacement of the measuring volume. This displacement of the measuring volume was calculated and the necessary corrections were made. Lee and Srinivasan (1978) and Gautam (1989) employed amplitude discrimination to distinguish between gas phase and particle phase velocity information. The laser-induced fluorescence emission based LDA technique in combination with amplitude discrimination will yield velocity information in a multisolid flow. Seed particles or any one particular group of solids coated with a fluorescent dye, such as the Rhodamine 6-G (Stevenson et al., 1977) scatter light at wavelengths in the range 520 nm-660 nm (see Figure 3.9). Weak scattered light at 514.5 nm wavelength is also present. However, by using a narrow band pass filter with a central wavelength, as dictated by the spectrum in Figure 3.9, of 560 nm, scattered light (the strong scatter from

Figure 3.9 Absorption and Emission Spectra of Rhodamine 6G

undyed particles and the weak scattered light from the coated particles) at 514.5 nm wavelength is prevented from entering the photomultiplier tube. Small quantities of coated 2 micron diameter seed particles in the flow field provide velocity information on the gas phase. This technique in tandem with amplitude discrimination eliminates the problem of trajectory ambiguity which, as stated earlier, results due to inherent non-uniform illumination in the measuring volume. By coating the larger sized bed material (glass beads of 300 micron mean diameter) information on the particulate velocity flow field will be obtained. Preliminary testing of this technique has been conducted in a horizontal co-current gas-solid pipe flow first using single mean sized particles (2 microns mean diameter and later 300 microns mean diameter) and second with particle groups of varied sizes (2 microns, 300 microns and 500 microns mean diameter) will be mixed together in the flow with the 300 microns diameter particles coated with the dye.

In the absence of DMA link, data recording is slow; hence, an alternate software based system of storing the incoming data had to be employed given the limitations of the PDP-11 such as data acceptance and storage. The incoming data is reduced and stored in arrays while velocity and sample interval time data are stored on the hard disk.

Fluid velocity data is obtained from light scattered by the seed particles. Amplitude discrimination is being employed in addition to the fluorescence-emission to discriminate signals originating from larger particles and the seeding material. Hence,

the large particles selected had a mean diameter greater than 300 micron rendering signal discrimination tractable. The threshold settings on the counter processor are set to discard signals from larger particles, i.e. signals with a larger pedestal or the larger d.c. component. The threshold settings were determined prior to running the experiments. Larger particles passing through the measuring volume scatter more light and produce a larger intensity response from the PM tube (called the pedestal) than the smaller particles. Thus, when the threshold level of the signal is set above that for the smaller particle signal only small or large particle signals are processed, and the velocity of the two phases could be separated. The difficulty encountered with this approach lies in the inability to accurately distinguish between the signals from small particles passing through the center of the measuring volume and the signals of large particles crossing near the edges of the measuring volume. Since laser beams have Gaussian light intensities both signals may have similar pedestals. This inability to separate large and small particle signals is referred to as trajectory ambiguity.

In this phase of the research program only the axial components of the velocity vector were measured at five cross-sectional planes in the glass test section. Measurements in each cross-sectional plane were made along the centerline. Measurements very close to the wall will also be attempted. In the past, with conventional LDA's measurements close to the wall were quite difficult because of a low signal-to-noise ratio due to scattering from the walls.

Typically, one thousand data points were required at each

location to obtain statistically accurate velocity information. The standard derivation and ninety-five percent confidence interval, based on Student-t distribution, was calculated. Velocity bias was eliminated using the incremental times and weighing each sample. The mean velocity and turbulent intensity at each data location was determined.

3.2.2 Uncertainties in LDA Measurements

The procedure outlined by Kline and McClintock (1953) has been used to calculate the uncertainty of a given parameter in the current study. The uncertainty interval of a measurement is generally stated at specified odds; typically, odds of 20 to 1 (corresponding to 95% level of confidence) are used.

The uncertainty of a measured quantity is expressed as:

$$R \pm u_R \quad (20 \text{ to } 1)$$

where, R is the mean value of the variable and u_R the uncertainty interval.

Consider a variable, N which is a function of n independent variables,

$$N = f(u_1, u_2, u_3, \dots, u_n)$$

Then the uncertainty in N is given by:

$$u_N = \left[\left(\frac{\partial N}{\partial u_1} \Delta u_1 \right)^2 + \left(\frac{\partial N}{\partial u_2} \Delta u_2 \right)^2 + \dots + \left(\frac{\partial N}{\partial u_n} \Delta u_n \right)^2 \right]^{1/2}$$

In a dual beam fringe mode LDA system the particle velocity is given by the following relation:

$$\bar{u} = \delta_f \cdot f_d$$

where,

$\bar{u}$ = Particle velocity

δ_f = Fringe spacing

f_d = Doppler frequency

The fringe spacing is a function of the laser light wavelength and the beam intersection angle:

$$\delta_f = \frac{\lambda}{2 \sin(\alpha)}$$

where,

λ = Laser wavelength (514.5 nm)

α = Half of the intersection angle(θ)

For small value of θ , $\sin \theta = \tan \theta = a/F$, where $2a$ is the beam spacing at beam splitter and F is the focal length of transmitting lens:

$$\alpha_f = \frac{\lambda \cdot F}{2 \cdot a}$$

Using uncertainty estimates (Kline and McClintock, 1953) :

$$\delta(\delta_f^2) = \left[\left(\frac{\partial \delta_f}{\partial F} \delta F \right)^2 + \left(\frac{\partial \delta_f}{\partial a} \delta a \right)^2 \right]$$

$$\delta(\delta_f) = \frac{\lambda}{2} \left[\left(\frac{1}{a} \delta F \right)^2 + \left(\frac{F}{a^2} \delta a \right)^2 \right]^{1/2}$$

$$\delta(\delta_f) = \frac{\lambda}{2a} \left[(\delta F)^2 + \left(\frac{F}{a} \delta a \right)^2 \right]^{1/2}$$

$$= \frac{\lambda}{2a} \left[\left(\frac{\delta F}{F} \right)^2 + \left(\frac{\delta a}{a} \right)^2 \right]^{1/2} \cdot \frac{2a \cdot d_{fr}}{\lambda}$$

where,

$$F = \frac{2a\delta_f}{\lambda}$$

$$\frac{\delta(\delta_f)}{\delta_f} = \left[\left(\frac{\delta F}{F} \right)^2 + \left(\frac{\delta a}{a} \right)^2 \right]^{1/2}$$

The uncertainty is a function of $\delta F/F$ and $\delta a/a$ only. By allowing the beams to hit a distant screen, the relative magnitudes of these uncertainties can be reduced. Here, $\delta F/F$ is denoted by $\delta F'/F'$ and $\delta a/a$ by $\delta a'/a'$, where $2a'$ is the beam separation at a plane distance F' from the measuring volume. The corresponding uncertainties were $\delta F' = 0.2$ cm and $\delta a' = 0.1$ cm thus, yielding $\delta(\delta_f)/\delta f = 0.50\%$ as the uncertainty in the calibration constant, the fringe spacing, δ_f .

However, data show that scatter in the measurements is larger than the uncertainty calculated above. The observed variations are dominated by statistical uncertainties in the measurement process.

3.2.3 Dye Optimization

The fluorescent dye consists of Rhodamine 6-G in a solution of 50-50% by volume of ethylene glycol and benzyl alcohol. Several solution strengths were tested for the optimum LDA signal. Solutions with molar concentrations ranging from 0.0200 M to 0.0292 M (approximately 10 - 14 g. of Rhodamine 6-G per liter of solution) were prepared. The solutions were then tested to select the dye strengths that provided the best signals.

Strands of 38 gage (100 microns) Nichrome wire were immersed in solution for a period of 24 hours in an attempt to attain a fluorescent coating. When removed from the solution, they were allowed to dry for approximately 1.5 hours. When removed from the solution, the wires had an oxidized film and did not retain the fluorescent coating of the dye. Signal quality was very poor from the dyed wire. Human hairs proved to be better suited to the

dying procedure and were substituted for the wires.

Once the hairs were dyed, each was attached to a calibration wheel and tested with the LDA system. The calibration wheel consists of a Plexiglas disc attached to a variable DC motor. The speed of the wheel is verified using a strobe. A hair is attached to the outer edge of the wheel so that it passes through the measuring volume once per revolution of the wheel; thereby simulating a particle crossing the fringes. The speed of the wheel was measured using both the LDA and a strobe. The results from both were in good agreement. Those solutions providing the best signals were chosen for the particle dying procedure.

3.2.4 Particle Dying Procedure

In the particle dying procedure, the optimum dye solution was prepared as mentioned previously. Particles of titanium dioxide were mixed with the solution. The mixture was then agitated for several hours using a wrist-action shaker. Several methods of removal of the dyed particles from solution were employed.

First, the unseparated mixture was heated in a drying oven in an attempt to drive off the excess moisture. After the particles were in the oven an appropriate amount of time, they were placed in a desiccator to prevent the further absorption of moisture from the air. The time necessary for the evaporation of the excess dye took as long as four days. This process was too slow and the particles emerged from the oven caked together.

The second method attempted to separate the dyed particles from the excess solution before placing it in the drying oven.

This was done by filtration, centrifuging, and decanting. The particles formed a "colloid-like" suspension which did not filter well. This process was also slow and messy and proved to be inefficient due to the small amount of particles retrieved from the solution.

The third method increased the amount of particles mixed per milliliter of dye solution. Since less dye was used, the excess was small and the time needed for drying decreased to one day. This method was the most effective and is used in all further dying procedures.

Because titanium dioxide particles emerged from the oven caked together, running them through a grinder and then through a ultrasonic separator was required to ensure the retention of the 2 micron sizing. Also, the absorption of the fluorescent dye by the titanium dioxide was poor. The particles did not retain the fluorescent orange color of the dye. Instead, they were purple when removed from the drying oven. Due to these problems and that of particle sphericity mentioned earlier, glass shot was substituted. The fluorescent dye solution coated the glass shot well and retained its orange color. The glass shot did not dry in "cakes" and retained its size and shape.

3.2.5 Calibration Techniques

A series of calibration tests were conducted in the horizontal test section using 2 micron undyed titanium dioxide as the seeding particle. The velocity measurements were taken at several different flowrates and at several positions along the center axis

using the LDA with the PM optics in forward scatter mode. The data taken by the LDA was then compared to the velocity calculated from the pressure differential measured using a pitot tube upstream from the LDA apparatus. These results were in good agreement.

The calibration wheel, as mentioned earlier, was then used to test the dyed and undyed glass shot and the 560 nm narrow bandwidth filter. The first test used 500 micron undyed glass shot attached to the Plexiglas disc on the calibration wheel so that the particles passed through the measuring volume with each revolution of the disc. The PM optics were placed in backscatter mode and no optical filter was used. Velocity measurements were taken and compared to those calculated from rpm measured by the strobe. The data was in good agreement with the calculated values.

Next, 500 micron glass shot coated with the fluorescent dye was placed on the calibration wheel. Data was taken and was in good agreement with the calculated values. The 560 nm bandwidth filter was then placed on the PM optics. Data was taken and was in good agreement with the calculated values.

The undyed glass shot was again placed on the calibration wheel and the 560 nm optical filter was placed on the PM optics. Because the glass shot was undyed, the 560 nm filter prevented the 514.4 nm scattered light from passing. Data was only able to be taken when the gain, PM tube voltage, and threshold settings were extremely high. And then, the measured velocities did not correspond to the calculated values using the strobe. When the gain and threshold settings were kept at levels used with the dyed particles, no data was able to be taken.

Tests were conducted to measure the instrumentation's sensitivity to gain, PM tube voltage, and threshold by varying only one quantity at a time. Tolerance levels for signal to noise ratio were established. The range of gain necessary to obtain a good signal and accurate velocity measurements was found.

Velocity measurements were then taken in the horizontal test section using 300 micron shot. Velocity measurements were taken undyed glass shot and the 514.4 nm optical filter was placed on the PM optics which operated in forward scatter mode. Measurements were taken at three different flowrates and at five different locations along the center axis. The velocity measurements were comparable to calculated values using the measured pressure differential upstream.

The 560 nm optical filter was then added to the PM optics and 300 micron glass shot coated with the fluorescent dye was used. Velocity measurements were taken at the same three flowrates and at the same five positions along the center axis. The velocity measurements were in good agreement with those taken with the undyed glass shot and the 514.4 nm optical filter.

CHAPTER 4

CFB EXPERIMENTAL FACILITY

A Circulating Fluidized Bed (CFB) experimental set-up has been designed (see Figure 4.1) to provide maximum versatility in investigating particle cluster formation in the CFB riser using LDA, optic fiber probes, and other probes. The cold-flow CFB model currently under fabrication is 6 m high and constructed mainly out of Plexiglas. Two stage cyclones are employed to capture the particles exhausted from the riser. The baghouse connected to the outlet of the secondary cyclone prevents fines from being exhausted to the atmosphere. The riser is made of Plexiglas tube with an inside diameter of 200 mm, wall thickness of 8 mm, and consists of 6 jointed sections in order to enhance the versatility of the experimental set-up.

Under normal operating conditions the fluidizing velocity in the CFB varies from 8 m/s to a maximum of 12 m/s. Design air flowrate is 0.25 m³/s. Circulation of particles varies from 50 kg/m²s to 200 kg/m²s. At maximum fluidizing velocity, the entrainment capacity of air is 138 kg/m³, and the mean voidage at outlet of riser is 0.94.

In order to observe the quality of fluidization and the flow patterns, the riser is made of Plexiglas. Transparent bed wall provides clear access for observing and videotaping gas bubbles, particle clusters, etc., and help in the adjustment of parameters controlling the flow patterns and fluidization.

The CFB experimental set-up was designed as a cold-flow model;

however, studies at temperatures above ambient can be performed. The fluidizing air can be heated with electrical heaters up to 100 degrees Celsius. This will be very helpful in studying the formation of clusters as a function of temperature.

Design details of each component of the cold-flow CFB system are given below:

4.1 Design of the Distributor

Published literature has presented ample evidence showing that the quality of fluidization is strongly influenced by the type of gas distributor used. For few air inlet openings the bed density fluctuates appreciably at all flow rates, though more severely at higher flow rates. For more air inlet openings the fluctuation in bed density is negligible at low air flow rate. Bed density is more uniform throughout. Since the mean diameters of particle is 50 μm , the orifice of the distributor must be small enough to maintain the particle. Considering the distributor size, the pressure drop and fluidizing velocity, a sintered stainless steel porous plate manufactured by MOTT POROUS MEDIA will be used as the distributor. The distributor plate flow characteristics are shown in Figure 4.2. At the operating condition the pressure drop across the distributor is 4.2 KPa.

4.2 Design of the Riser

4.2.1 The Diameter of the Riser

Most of the previous investigations (van Zoonen, 1962; Hartage et al. 1986) with a few exceptions (Bader, Findlay, and Knowlton,

Figure 4.2 Distributor Plate Flow Characteristics
(MOTT POROUS MEDIA)

1989) employed a small diameter riser (50 mm to 100 mm). Experimental results obtained from both the large and the small diameter test units have shown that the flow in the riser of circulating fluidized beds is of a core-annulus type.

The solid and gas interaction between the core and the annulus is an important consideration in the evaluation of risers since the amount of interaction affects the solid and gas residence times. Therefore, tests should be conducted in a unit with suitable size riser in order to determine the mass flux and particle velocity distributions as a function of riser radius and also axial riser position.

The results of experiments conducted by Bader, Findlay, and Knowlton (1989) have shown that the radial solids flux profile in the riser is parabolic. At a location 9.1 m above the solids entry point, the net mass flux rate decreased with riser radial position to a value of zero at about 25 mm from the wall, and the particle velocity profile is also similar to the mass flux profile. Voidage profile is smoother than both the mass flux and particle velocity profiles. Taking the wall effects and particle-particle interaction into consideration, a riser with a diameter of 200 mm was selected which 2 times the width of the particle flux region.

4.2.2 Height of the Riser

Bader, Findlay, and Knowlton (1989) have shown that, the mass flux and voidage profiles at positions of 9.1 and 4.0 m are nearly the same except for the quantity of mass flux and voidage. So, the height of the riser was selected as 4.5 m and divided into 6

sections. From bottom to top, the various sections are 700 mm, 800 mm, 800 mm, 800 mm, 800 mm. and 600 mm, respectively in length.

4.3 Design of the Cyclones

Circulating fluidized beds are characterized by particle circulation. The circulation of particles depends mainly on the fluidizing velocity and the quantity of particles captured from exhausted gas. If the particles captured from the exhaust gas are much smaller than those in the exhaust gas then a stable circulation cannot be maintained. Hence, provisions are made to improve the collection of exhausted particles using a multistage cyclone, baghouse, electrical filters and so on. Considering the actual situation, two stage cyclones are inserted in the experimental set-up and the design details are given below:

4.3.1 Dimensions of the Cyclones

Two similar cyclones are employed in the test unit in order to capture the particles exhausted from the riser as shown in Figure 4.3. The outside diameters of both the cyclones are 300 mm. Diameter of the outlet is 150 mm. Height of the primary cyclone is 600 mm and that of the secondary cyclone is 400 mm. Other dimensions of both of the cyclones are as follows:

Primary Cyclone

D = 300 mm, A = 1200 mm
B = 600 mm, C = 600 mm
E = 75 mm, F = 188 mm
L = 75 mm, K = 150 mm

Secondary Cyclone

D = 300 mm, A = 1200 mm
B = 600 mm, C = 600 mm
E = 75 mm, F = 188 mm
L = 75 mm, K = 150 mm

Figure 4.3 Cyclone

$$M = 150 \text{ mm}, N = 38 \text{ mm}$$

$$M = 150 \text{ mm}, N = 38 \text{ mm}$$

The inlet velocity of both cyclones is 18.8 m/s and the outlet velocity of both is 11.9 m/s.

4.3.2 Calculation of Pressure Drop

The air flowrate is 2.5 m³/s and the inlet velocity V_i of the cyclone is 18.8 m/s. The number of cyclone inlet heads p_i :

$$\begin{aligned} P_i &= k_o KL/M^2 = 16.0 \times 150 \times 75/150^2 \\ &= 8.0 \end{aligned}$$

here k_o is a constant, for the following conditions, $k_o = 16.0$

$$\begin{aligned} L/D &= 1/12 - 1/4 \\ K/D &= 1/4 - 1/2 \\ M/D &= 1/4 - 1/2 \end{aligned}$$

The velocity head (in H₂O):

$$h_v = 0.05 \times \rho v_c^2 = 0.05 \times 1.2 \times 18.8^2 = 21.2 \text{ mm H}_2\text{O}$$

The total pressure drop across cyclone:

$$p = p_i \times h_v = 8.0 \times 21.2 \text{ mm H}_2\text{O} = 169.6 \text{ mm H}_2\text{O}$$

The minimum particle size:

$$D_{p \text{ min}} = \left[\frac{9\mu D}{\pi N V_i (\rho_s - \rho)} \right]^{1/2} = \sqrt{\frac{9 \times 1.2 \times 10^{-5} \times 0.3}{3.14 \times 5 \times 18.8 (2000 - 1.2)}} = 7.6 \times 10^{-6} \text{ m}$$

Here V_i is the inlet velocity, μ is the viscosity, N is the number of turns, $N=5$

The cut size:

$$D_{pc} = \sqrt{\frac{9 \mu D}{2 \pi N V_c (\rho_s - \rho_g)}} = \sqrt{\frac{9 \times 1.2 \times 0.3 \times 10^{-5}}{2 \times 3.14 \times 5 \times 18.8 (2000 - 1.2)}} = 5.2 \mu m$$

The separation efficiencies are:

d_p	3 μm	10 μm	15 μm	20 μm
efficiency	22%	80%	90.5%	99.5%

4.4 Design of the Hopper

A schematic of the particle hopper employed in the experiment unit is shown in Figure 4.4. Since the maximum mass flux rate is 25 kg/s in the test unit, there should be enough room to store the circulating particles in the loop to maintain a stable circulation.

Considering the particle circulation to be stable and the time required for each complete circulation in the CFB to be 5 seconds, the quantity of particles passing a given section in the stand pipe, W , is 125 kg per circulation. The hopper was designed to store at least twice this amount. The volume of the hopper, V is $V = 2W/\rho_p = 2 \times 125 / 2500 = 0.1 \text{ m}^3$, at least assuming the density of particles, ρ_p , is 2500 kg/m³.

4.5 Design of the L-Valve

Several types of non-mechanical valves are in use today to transfer the particles from the standpipe to the riser. Notable amongst them are L-valves and U-valves. Importance of a well designed L-valve cannot be overstressed. Depending on the particle characteristics, two types of flows can exist in the non-mechanical valves, namely aerated flow and stick-slip flow. If stick-slip

Figure 4.4 Schematic of the Particle Hopper

flow exists, it is necessary to determine whether there exists a positive pressure difference (pressure at the top is lower than the pressure at the bottom).

From the operating conditions and the particles employed in the test, it is apparent that a stick-slip flow exists in this test. The ideal seal height (where there is a net zero gas flow rate) and the height (where the solids in the leg flow continuously downward) are determined. In the experimental unit, an L-valve is employed and its dimensions are shown in Figure 4.5.

A = 75 mm, B = 500 mm, C = 500 mm

Figure 4.5 Schematic of the L-Valve

CHAPTER 5

RESULTS AND DISCUSSION

This chapter presents and discusses the results of the dye optimization and calibration procedures as given in Chapter 3. All velocity measurements have corresponding velocity histogram plots. Each plot represents the final velocity distribution of 1000 points of raw data taken at one horizontal location at a set flowrate and manipulated using the statistical programs listed in the Appendix.

5.1 Dye Optimization

The fluorescent dye, consisting of Rhodamine 6-G in a solution of ethylene glycol and benzyl alcohol (50-50% by volume), was prepared in molar concentrations ranging from 0.0200 M to 0.0292 M (approximately 10-14 g of Rhodamine 6-G per liter of solution). The dyes were then tested to select the dye strengths that provide the best signals following the procedure described in Sections 3.2.3 and 3.2.4.

The dyes were tested with human hairs which had been coated with the solution and placed on the calibration wheel. The gain, PM tube voltage, threshold, and high and low pass filters were manipulated to obtain the best signal. This was done using undyed hairs first and the green 514.5 nm filter on the receiving optics. Once the levels were set, they remained constant throughout the experiment.

The results showed little differentiation between the dye molarity but rather varied according to the amount of dye on the hairs. This proved to be especially apparent in later tests where the particles were dyed showing that in addition to dye strength the amount of dye absorbed by the particles/hairs is equally important. The 0.02 M solution was found to yield the best signals and was therefore used for dying particles.

5.2 Calibration

Several calibration tests were performed to check the LDA output following the procedure in Section 3.2.5. These tests were performed using undyed titanium dioxide, undyed glass shot, and dyed glass shot in combination with the green and orange filters. Three techniques were used to calibrate the instrumentation. First, the undyed 2 micron titanium dioxide was used as the seeding particle in the horizontal test and the green filter was placed on the PM tube receiving optics. The second employed the use of the calibration wheel with the dyed and undyed glass shot and the two filters. The third was performed in the horizontal test section using undyed titanium dioxide and dyed and undyed glass shot and the two filters.

5.2.1 Calibration Using the Undyed Titanium Dioxide in the Horizontal Test Section

A series of calibration tests were conducted in the horizontal test section using undyed 2 micron titanium dioxide as the seeding particle and the 514.5 nm green optical filter on the PM tube

receiving optics as described in Section 3.2.5. Velocity measurements were taken at three different speeds of the blower yielding a calculated velocity of 9.69 m/s, 13.41 m/s, and 15.66 m/s at: 10 cm, 12.5 cm, 15 cm, 17.5 cm, and 19.5 cm from the coupling. Velocity histograms of the final data set (after statistical averaging) are given in Graphs: 5.1 - 5.15.

The data presented in these graphs is a result of statistical averaging and rejection of spurious "noisy" data. Mean, rms, and standard deviation values of the velocity data were calculated using standard statistical methods. Velocity histograms were re-plotted after the tails were deleted and new mean and standard deviation values were calculated. The highly restrictive criteria used for eliminating the noisy data involved retaining the data with ± 2 standard deviations of the mean velocities. This resulted in a fairly high percentage of the data being rejected. However, future data reduction will retain values within 2.56 standard deviations of the mean velocities. For the data presented in the graphs, velocity bias corrections were not applied to the calculated statistical averages. An inspection of the histograms of statistically reduced data provided more insight into the nature and aim of this study. In test runs where the histograms did not follow the required distribution, the run could be rejected completely.

5.2.2 Using Calibration Wheel

In the first test, no optical filter was placed on the calibration wheel. The undyed 500 micron glass shot was attached

to the wheel and velocity measurements were taken. The data from the LDA had a final (after running through statistical averaging programs) velocity average of 4.304 m/s. The velocity calculated from the strobe at 1580 rpm is 4.63 m/s (see Graph 5.16). Next, dyed 500 micron glass shot was placed on the wheel and velocity measurements were taken. The data from the LDA had a final velocity average of 4.496 m/s and that calculated from the strobe was again 4.63 m/s (see Graph 5.17).

Next, the 560 nm orange filter was placed on the receiving optics. Dyed (0.02 M) 500 micron glass shot was attached to the calibration wheel and two sets of data were taken. The final velocity average obtained was 5.135 m/s and 4.594 m/s with a velocity calculated from the strobe to be 4.63 m/s (see Graph 5.18 and 5.19). The dyed glass shot was removed from the wheel and replaced with undyed 500 micron glass shot. With the gain, threshold, PM tube voltage, and high and low pass filter settings the same as for the dyed particles with the filter, the data rate was zero, that is, no data could be acquired. This result was as expected. This leads to the conclusion that when dyed and undyed particles are present together in a flow stream, a narrow bandpass filter in the optical train will permit discrimination between the two types of particles and yield velocity information from the fluorescent particles.

5.2.3 Sensitivity Tests

Tests were conducted with the dyed particles on the calibration wheel and the narrow bandpass optical filter (orange

filter, centered at 560 nm) on the PM tube receiving optics. The instrumentation's sensitivity to gain, PM tube voltage, and threshold were tested. Each variable was tested while the others were held constant.

The output was relatively insensitive to small changes in threshold. The signal and the velocity measurements remained consistent throughout the test. The output was highly sensitive to small changes in the PM tube voltage. Small changes in voltage were undiscernible on the voltmeter reading but resulted in large variations in the velocity measurement. The gain showed some sensitivity to large changes but after reaching a certain level the velocity measurements were consistent for small changes in gain.

5.2.4 Calibration using Dyed/Undyed Particles in the Horizontal Test Section

A series of calibration tests were conducted in the horizontal test section using undyed and dyed 300 micron glass shot as the seeding particle and the 514.5 nm green optical filter and the 560 nm orange optical filter on the PM tube receiving optics as described in Section 3.2.5. Velocity measurements were taken at three different speeds of the blower yielding a calculated velocity of 8.57 m/s, 13.41 m/s, and 15.66 m/s. Measurements were taken at five different locations along the center axis at: 10 cm, 12.5 cm, 15 cm, 17.5 cm, and 19.5 cm from the coupling.

The first data set was taken with undyed 300 micron glass shot and the 514.5 nm green optical filter on the PM tube receiving

optics. Velocity measurements were taken at the three blower speeds and five axial location mentioned above. Velocity histograms of the final data set (after statistical averaging) are given in Graphs: 5.20 - 5.35. The second data set was taken with dyed 300 micron glass shot and the 560 nm orange optical filter on the PM tube receiving optics. Considerable volume of data acquired towards the end of the year is currently being processed. It will be included in the upcoming monthly reports.

The adopted technique permitted optical discrimination between the scattered light and fluorescence emission. The Laser Doppler Anemometer used in this effort was configured in the differential Doppler or fringe mode. This utilizes the scattered light when a particle passes through the point of intersection of the Gaussian beams. The scattered intensity varies with time and the modulation frequency under the gaussian envelope is given by

$$f_d = \frac{2 U_x}{\lambda} \sin \frac{\theta}{2}$$

The detection process, being essentially incoherent permitted the introduction of fluorescent particles in the flow such that the standing electromagnetic field, in the intersection region, could induce a time varying fluorescent emission (Stevenson et al., 1975). Hence, by using a narrow band pass filter in the receiving optics, signals from the two classes of particles (dyed and undyed) were effectively discriminated.

The optical filter allowed the fluorescence emission to reach the PM tube and blocked out the scattered light. Fluorescence emission eliminates the dependence of the signal modulator on the aperture geometry of the PM receiving optics primarily because fluorescence is spatially isotropic and unpolarized (Stevenson et al., 1975).

Although the signal amplitude from fluorescent particles was considerably less than the scattered light signals (without the optical filter), a careful adjustment of the gain and PM tube voltage yielded fairly satisfactory velocity data. The signal to noise ratio from the fluorescence emission was not comparable to the scattered light signals; however, the subsequent statistical data reduction eliminated the noise.

Use of an optical filter to allow the passage of only the longer fluorescence emission along with the use of a powerful laser (a 2.0 W Ar-ion laser with .8 W in the 515.5 nm line was employed) will permit non-intrusive probing of the core-annulus flow in a CFB riser. Given the difference in the characteristics of fluorescence emission and scattered light, measurements closer to the riser wall are highly possible. Reflected light would not permit measurements near the wall.

VELOCITY HISTOGRAMS Particle Size = 2 microns Pipe Diameter = 2.5 cm

Graph 5.1 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS
Particle Size = 2 microns
Pipe Diameter = 2.5 cm

**Graph 5.2 Horizontal Test with Undyed Titanium Dioxide
 Using 514.5 nm Green Filter**

VELOCITY HISTOGRAMS Particle Size = 2 microns Pipe Diameter = 2.5 cm

Graph 5.3 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS
Particle Size = 2 microns
Pipe Diameter = 2.5 cm

**Graph 5.4 Horizontal Test with Undyed Titanium Dioxide
 Using 514.5 nm Green Filter**

VELOCITY HISTOGRAMS **Particle Size = 2 microns** **Pipe Diameter = 2.5 cm**

**Graph 5.3 Horizontal Test with Undyed Titanium Dioxide
 Using 514.5 nm Green Filter**

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

Graph 5.6 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

Graph 5.7 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

VELOCITY (m/s)

Graph 5.8 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

Graph 5.9 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

VELOCITY (m/s)

Graph 5.10 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS
Particle Size = 2 microns
Pipe Diameter = 2.5 cm

Graph 5.11 Horizontal Test with Undyed Titanium Dioxide
 Using 514.5 nm Green Filter

Pipe Diameter = 2.5 cm

Graph 5.12 Horizontal Test with Undyed Titanium Dioxide Using 514.5 nm Green Filter

VELOCITY HISTOGRAM Particle Size = 2 microns Pipe Diameter = 2.5 cm

VELOCITY (m/s)

Graph 5.13 Horizontal Test with Undyed Titanium Dioxide
 Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

Graph 5.14 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns
Pipe Diameter = 2.5 cm

Graph 5.15 Horizontal Test with Undyed Titanium Dioxide
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

PARTICLE SIZE = 500 microns
CALIBRATION WHEEL
UNDYED, NO FILTER

VELOCITY (m/s)

Graph 5.16 Calibration Wheel with Undyed Glass Shot without Filter

VELOCITY HISTOGRAMS
PARTICLE SIZE = 500 microns
CALIBRATION WHEEL
DYED, NO FILTER

VELOCITY (m/s)

Graph 5.17 Calibration Wheel with Dyed Glass Shot without Filter

VELOCITY HISTOGRAMS
PARTICLE SIZE = 500 microns
CALIBRATION WHEEL
DYED, ORANGE FILTER

Graph 5.18 Calibration Wheel with Dyed Glass Shot and 560 nm Filter

VELOCITY HISTOGRAMS
PARTICLE SIZE = 500 microns
CALIBRATION WHEEL
DYED, ORANGE FILTER

Graph 3.19 Calibration Wheel with Dyed Glass shot and 560 nm Filter

VELOCITY HISTOGRAMS

Particle Size = 300 micron
Pipe Diameter = 2.5 cm

VELOCITY (m/s)

Graph 5.20 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 300 micron

Pipe Diameter = 2.5 cm

VELOCITY (m/s)

Graph 5.21 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 300 micron

Pipe Diameter = 2.5 cm

VELOCITY m/s

Graph 5.22 Horizontal Test with Undyed glass shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns

Pipe Diameter = 2.5 cm

Graph 5.23 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.24 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.25 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.26 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 3.27 Horizontal Test With Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.28 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.29 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.30 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 3.31 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.32 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAM

Particle Size = 300 microns
Pipe Diameter = 2.5 cm

Graph 5.33 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS

Particle Size = 2 microns

Pipe Diameter = 2.5 cm

VELOCITY (m/s)

Graph 5.34 Horizontal Test with Undyed Glass Shot
Using 514.5 nm Green Filter

VELOCITY HISTOGRAMS Particle Size = 300 micron Pipe Diameter = 2.5 cm

VELOCITY m/s

Graph 5.35 Horizontal Test with Undyed Glass Shot Using 514.5 nm Green Filter

BIBLIOGRAPHY

Bader, R., Findlay, J. and Knowlton, T.M., (1989), "Gas/Solids Flow Patterns in a 30.5cm Diameter Circulating Fluidized Bed", Institute of Gas Technology, Sept. 25, 1989.

Bernard, J.M., Wang, C.P. and Lee, R.M., (1981), "Measurement of Fluid Velocity in the Interior of a Transparent Fluidized Bed with a Laser Doppler Anemometer", AIChE Symp Ser, Vol. 77, No. 205, pp. 37-50.

Berruti, F. and Kalogerakis, N., (1989), "Modelling the Internal Flow Structure of Circulating Fluidized Beds", Can J Chem Eng, Vol. 67, No. 6, pp. 1010-1014.

Birchenough, A. and Mason, J.S., (1976), "Local Particle Velocity Measurements with a Laser Anemometer in an Upward Flowing Gas-Solid Suspension", Powder Tech, Vol. 14, p. 139.

Biswas, J. and Leung, L.S., (1987), "Applicability of Choking Correlations for Fast-Fluid Bed Operation", Powder Tech, Vol. 51, No. 2, pp. 179-180.

Carey, V.P., (1987), "Dependence of Settling Velocity on Particle Concentration in a Fluidized Bed of Spherical Particles", Int J Multiphase Flow, Vol. 13, No. 3, pp. 429-431.

Drahos, J., Cermak, J., Guardani, R. and Schugerl, K., (1988), "Characterization of Flow Regime Transitions in a Circulating Fluidized Bed", Powder Tech, Vol. 56, No. 1, pp. 41-48.

Dry, R.J., (1986), "Radial Concentrating Profile in a Fast-Fluidized Bed", Powder Tech, Vol. 49, No. 1, pp. 37-44.

Dry, R.J., (1987), "Radial Particle Size Segregation in a Fast-Fluidized Bed", Powder Tech, Vol. 52, No. 1, pp. 7-16.

Durrett, R.P., Gould, R.D., Stevenson, W.H., and Thompson, H.D., (1985), "A Correction Lens for Laser Doppler Velocimeter Measurements in a Cylindrical Tube", AIAA J, Vol. 23, No. 9, pp. 1387-1391.

Durrett, R.P., Stevenson, W.H., and Thompson, H.D., (1988), "Radial and Axial Turbulent Flow Measurement with an LDV in an Axisymmetric Sudden Expansion Air Flow", J Fluids Eng, Vol. 110, pp. 367-372.

Durst, F., (1982), "Review-Combined Measurements of Particle Velocities, Size Distributions and Concentrations", Trans ASME, Vol. 104, pp. 284-296.

Durst, F. and Umhauer, H., (1975), "Local Measurements of Particle Velocity, Size Distribution, and Concentration with a Combined Laser Doppler Particle Sizing System", Proc LDA Symp, Copenhagen, p. 430.

Durst, F. and Zare, M., (1975), "Laser Doppler Measurements in Two-Phase Flows", Proc LDA Symp, Copenhagen.

Farmer, W.M., (1972), "Dynamic Particle Size and Number Analysis Using a Laser Doppler Velocity Meter", Applied Optics, Vol. 11, p. 2603.

Fox, C., Molodtsov, Y. and Large, J.F., (1989), "Control Mechanisms of Fluidized Solids Circulation Between Adjacent Vessels", AIChE J, Vol. 35, No. 12, pp. 1933-1941.

Gautam, M., Bocanegra, L., Jurewicz, J.T. and Morris, G. J., (1987), "A Review of LDV Measurements in Gas-Solid Flows", Int'l Symp Multiphase Flows, eds., C.T. Crowe and Z.Q. Fan, Hangzhou, China.

Gautam, M., (1989), "An Experimental Study of the Hydrodynamics Inside Fluidized Bed Bubbles", Ph.D. Dissertation, Dept. of Mech. and Aero. Engg., West Virginia University, Morgantown.

Grace, J.R. and Tuot, J., (1979), "A Theory for Cluster Formation in Vertically Conveyed Suspensions of Intermediate Density", Trans I ChemE, Vol. 57, pp. 49-54.

Guilin, Y., Zhe, H. and Lianzhong, Z., (1984), "Radial Gas Dispersion in a Fast-Fluidized Bed", Fluidization, IV, pp. 145-152.

Hamdullhpur, F., Al Taweel, A.M., Militzer, J. and Kan, M., (1989), "Motion of Hydrodynamic Aggregates", Powder Tech, Vol. 59, pp. 1973-1981.

Hartage, E., Li, Y., and Werther, J., (1986) "Analysis of the Local Structure of the Two-Phase Flow in a Fast Fluidized Bed", Circulating Fluidized Bed Technology, Pergamon Press, NY.

Hinze, J.O., (1959), Turbulence, McGraw Hill Book Co., New York.

Hjelmfelt, A.T. Jr. and Mokros, L.F., (1966), "Motion of Discrete Particles in a Turbulent Fluid", App Sci Res, Vol. 16, pp. 149-161.

Horio, M., Ishii, H., Kobukai, Y. and Yamanishi, N., (1989), "Scaling Law for Circulating Fluidized Beds", J Chem Eng Jpn, Vol. 22, No. 6, pp. 587-592.

Jackson, R., (1963), "The Mechanics of Fluidized Beds, Part II", Trans Instn Chem Engrs, Vol. 41, pp. 22-28.

Johnston, W., Dybbs, A. and Edwards, R., (1975), "Measurement of Fluid Velocity Inside Porous Media with a Laser Anemometer", The Physics of Fluids, Vol. 18, pp. 913-914.

Jurewicz, J.T., Stock, D.E., Crowe, C.T. and Eschbach, J.E., (1975), "Measurement of Both Gas and Particle Velocities in Turbulent Two Phase Flow", Proc of the Fourth Symposium of Turbulence in Liquids, Rolla, Missouri.

Kale, S.R. and Eaton, J.K., (1985), "An Experimental Investigation of Gas-Particle Flows Through Diffusers in the Freeboard Region of Fluidized Beds", Int'l J of Multiphase Flows, Vol. 11, No. 5, pp. 659-674.

Kato, K., Shibasaki, Tamura, Anta, Wang and Takarada, (1989), "Particle Holdup in a Fast-Fluidized Bed", J Chem Eng Jpn, Vol. 22, No. 2, pp. 130-136.

Kececioğlu, I. and Keairns, D.L., (1989), "Computation of Solid Circulation Rates in a Fluidized Bed From Tracer Particle Concentration Distributions", Can J of Chem Eng, Vol. 67, pp. 290-300.

Keefer, D. (1987), "Laser Fluorescence Velocimeter", Applied Optics, Vol. 26, No.1, pp. 91-94.

Kehoe, P.K.W and Davidson, J.F., (1971), "Continuously Slugging Fluidized Beds", Inst Chem Eng Symp Ser, Vol. 33, pp. 97.

Kline, S.J. and McClintok, F.A., (1953), "Describing Uncertainties in Single Sample Experiments", Mech Eng, pp. 3-6.

Knowlton, T., Findlay, J., Sishtla, C. and Chan, I., (1986), "Solids Pressure Reduction Without Lockhoppers: The Restricted Pipe Discharge System", AIChE Symp Ser, Vol. 83, No. 255, pp. 64-73.

Lai, M.C. and Faeth, G.M., (1987), "A Combined Laser Doppler Anemometer/Laser Induced Fluorescence System for Turbulent Transport Measurements", J Heat Transfer, Vol 109, pp. 254-256.

Lanneau, K.P., (1960), "Gas-Solid Contacting in Fluidized Beds", Trans Inst Chem Engrs, Vol. 38, pp. 25.

Lee, S.L. and Durst, F., (1982), "On the Motion of Particles in Turbulent Duct Flows", Int'l J Multiphase Flow, Vol. 8, No. 2, pp. 125-145.

Lee, S.L. and Srinivasan, J., (1978), "Measurement of Local Size and Velocity Probability Density Distributions in Two-Phase Suspension Flows by Laser Doppler Technique", Int'l J of Multiphase Flow, Vol. 4, pp. 141-155.

Levy, Y. and Lockwood, F.C., (1983), "Velocity Measurements in a Particle Laden Turbulent Free Jet", Combustion and Flame, Vol. 40, pp. 333-339.

Lourenco, L., Krothapalli, A., Buchlin, J.M., and Riethmuller, M.L., (1986), "Noninvasive Experimental Technique for the Measurement of Unsteady Velocity Fields", AIAA J, Vol. 24, No. 10, pp. 1715-1716.

Maeda, M., Hishida, K. and Furutani, T., (1980), "Velocity Distributions of Air-Solid Suspension in Upward Pipe Flow (Effect of Particles on Air Velocity Distribution)", Trans Japan Soc Mech Engrs, 46, p. 2313.

Melling, A. and Whitelaw, J.H., (1973), "Seeding of Gas Flows for Laser Anemometry", DISA Information, 15, p. 5.

Meyers, J.F., (1988), "Laser Velocimeter Data Acquisition and Real Time Processing Using Microcomputer", Int'l Symposium on Application of Laser Anemometry to Fluid Mechanics, Lisbon, Portugal.

Modaress, D., Wuerer, J. and Elgobashi, S., (1982), Proc AIAA/ASME 3rd Joint Thermophysics, Fluids, Plasma, and Heat Transfer Conf., June 7-11, 1982, St. Louis, Paper AIAA - 82-0964.

Modaress, D. and Tan, H., (1983), "Two-Component LDA Measurement in a Two-Phase Turbulent Jet", AIAA J, 21st Aerospace Science Meeting, Jan. 10-13, Reno, NV.

Mountzaris, T.J. and Jackson, R., (1986), "The Effects of Aeration on the Gravity Flow of Particulate Materials in Vertical Standpipes", AIChE Symp Ser, Vol. 83, No. 255, pp. 10-22.

Neale, G., Epstein, N. and Nader, W., (1972), "Creeping Flow Relative to Permeable Spheres", Chem Eng Sci, Vol. 28, pp. 1865-1874.

Patrose, B. and Caram, H.S., (1982), "Optical Fiber Probe Transit Anemometer for Particle Velocity Measurements in Fluidized Beds", AIChE J, Vol. 28, No. 4, pp. 604-609.

Rhodes, M.J. and Geldart, D., (1989), "The Upward Flow of Gas/Solid Suspensions", Chem Eng Res Des, Vol. 67, No. 1, pp. 20-29.

Richardson, J.F. and Zaki, W.M., (1954), "Sedimentation and Fluidization: Part I", Trans Inst Chem Eng, Vol. 32, p. 35.

Salem, T.F., and Gibbs, B.M. (1987), "Solid Circulation Between Fluidized Beds Using Jet Pumps", Powder Tech, Vol. 52, No. 2, pp. 107-116.

Shingles, T. and Silverman, R.W., (1986), "Determination of Standpipe Pressure Profiles and Slide Valve Orifice Discharge Coefficients of Synthol Circulating Fluidized Bed Reactors", Powder Tech, Vol. 47, No. 2, pp. 129-136.

Slack, G.W., (1963), "Sedimentation of Compact Clusters of Uniform Spheres", Nature, Vol. 200, pp. 466-467.

Slack, G.W., Jayaweera, K.O.L.F. and Mason, B.J., (1963), "The Behaviour of Clusters of Spheres Falling in a Viscous Fluid: Part 1", J of Fluid Mech, Vol. 20, pp. 121-128.

Stevenson, W.H. and dos Santos, R., (1977), "Aerosol Sizing by Means of Laser-induced Fluorescence", Appl Phys Lett, Vol. 30, No. 5, pp. 236-237.

Stevenson, W.H., dos Santos, R. and Mettler, S., (1975), "A Laser Velocimeter Utilizing Laser-Induced Fluorescence", App Phys Lett, Vol. 27, No. 7, pp. 395-396.

Subbarao, D., (1986), "Clusters and Lean-Phase Behavior", Powder Tech, Vol. 46, pp. 101-107.

Sutherland, K.S. and Tan, H., (1970), "Sedimentation of a Porous Sphere", Chem Eng Sci, Vol. 25, pp. 1948-1950.

Tchen, C.M., (1947), "Mean Value and Correlation Problems Connected with the Motion of Small Particles Suspended in a Turbulent Fluid", Ph.D. Dissertation, Delft, Martinz Nyhoff, the Hague.

Tsuji, Y. and Morikawa, Y., (1982), "LDV Measurements of an Air-Solid Two-Phase Flow in a Horizontal Pipe", J Fluid Mech, Vol. 120, pp. 385-409.

Van Zoonen, D., (1962), "Measurement of Diffusional Phenomena and Velocity Profiles in a Vertical Riser", Proc Symp Interaction Between Fluid and Particles, Inst Chem Eng, pp. 64-17.

Yang, W., (1983), "Criteria for Choking in Vertical Pneumatic Conveying Lines", Powder Tech, Vol. 35, pp. 143-150.

Yang, W., (1984), "Mechanistic Models for Transitions Between Regimes of Fluidization", AIChE J, Vol. 30, No. 6, pp. 1025-1027.

Yerushalmi, J. and Cankurt, N.T., (1978), "Gas Backmixing in High Velocity Fluidized Beds", Fluidization, Cambridge Univ. Press, pp. 387-393.

Yerushalmi, J. and Cankurt, N.T., (1979), "Further Studies of the Regimes of Fluidization", Powder Tech, vol. 24, pp. 187-205.

Yianneskis, M., (1987), "Velocity, Particle Sizing and Concentration Measurement Techniques for Multiphase Flow", Powder Tech, Vol. 49, pp. 261-269.

Yianneskis, M. and Whitelaw, J.H., (1984), Proc Symp on Liquid-Solid Flow and Erosion Wear in Industrial Equipment, ASME Fluids Engineering Conference, New Orleans, Feb. 11-17.

Yoshioka, S., Miyamoto, T., Tomura, J., Hirato, M., Kiuchi, N., and Ishiboshi, Y., (1987), "Circulatory Flow of Particles in a 0.96-m-diameter Fluidized Bed", Int Chem Eng, Vol. 27, No. 2, pp. 281-287.

Yousfi, Y. and Gau, G., (1974), "Aerodynamique de L'ecoulement Vertical de Suspensions Concentrees Gaz-Solides - I. Regimes D'ecoulement et Stabilite Aerodynamic", Chem Eng Sci, Vol. 29, p. 139.

Yule, A.J., Chigier, N.A., Atakan, S. and Ungut, A., (1977), "Particle Size and Velocity Measurement by Laser Anemometry", J Energy, Vol. 1, No. 4, pp. 220-228.

APPENDIX

This FORTRAN program calculates the velocity from the data brought in from the counter processor using an assembly language subroutine.

```

C   TEST PROGRAM: LDA COUNTER PROCESSOR TO COMPUTER
      DIMENSION LDADAT(1000),LDATIM(1000)
      THETA=7.25
      PII=4.0* ATAN(1.0)
      RDCRV= 180.0/PII
      WRITE (7,150)
150    FORMAT (1X, 21HINPUT FREQUENCY SHIFT)
      ACCEPT*,F
      WRITE (7,200)
200    FORMAT (1X,32HINPUT NUMBER OF SAMPLES REQUIRED)
      ACCEPT*,N
      CALL LDAFQ(N,LDADAT(1),LDATIM(1))
      WRITE(7,1001)

1          0          0          1
FORMAT(3X,1HI,3X,9HLDADAT(I),5X,4HFREQ,11X,3HVEL,12X,5HOMEGA,
& ,10X,4HTIME)
      WRITE (7,300)
300    FORMAT(/)
      VELSUM= 0.0
      DO 10 I= 1, N
        DM= FLOAT(LDADAT(I).AND.255)
        IDX= (LDADAT(I).AND.3840)/256
        D=DM*2.**IDX
        FD=14.96*D-F
        VEL= FD*(514.5E-9)/(2.*SIN(THETA/(2.*RDCRV)))
        OMEGA= VEL*60./(6.83E-2*2.*PII)
        TM= FLOAT(LDATIM(I).AND.255)
        ITX=(LDATIM(I).AND.3840)/256
        T=TM*2.**ITX *1.E-7
        VELSUM= VEL + VELSUM
      WRITE(7,1000) I,LDADAT(I),FD,VEL,OMEGA,T
      WRITE(9,2000) I,FD,VEL
C      WRITE(9,1000) I,LDADAT(I),FD,VEL,OMEGA,T
10     CONTINUE
      VELAVE= VELSUM/N
      WRITE(7,1050) VELAVE
1000   FORMAT(1X,I4,2X,I7,4X,E12.4,3X,E12.4,3X,E12.4,3X,E12.4)
1050   FORMAT(1X,18HAVERAGE VELOCITY =,3X,E12.4)
2000   FORMAT(1X,I3,4X,E12.4,4X,E12.4)
      STOP
      END

```

This assembly language (PDP-11 MAC) subroutine brings in data from the counter processor.

```

DRVIN    = 167774
DRVOUT    = 167772
ZERO      =      0
CLDRF     =     40
GOVAL     =     34
GOVAL1    =     74
GOVAL01   =     35
;GOVAL03  =     37

```

```

LDAFQ::  MOV  #ZERO, @#DRVOUT          ; CLEAR DATA READY FLOP
        MOV  #CLDRF, @#DRVOUT
        MOV  #ZERO, @#DRVOUT

        MOV  (R5)+, R0                ; GET NUMBER OF ARGUMENTS IN
                                      ; R0

        MOV  @ (R5)+, R1              ; GET COUNT, N , IN R1
        MOV  (R5)+, R2                ; GET ADR OF THE FIRST ELEMENT
                                      ; OF ARRAY

        MOV  (R5) , R3                ; INTO R2
                                      ; GET ADR OF FIRST ELEMENT OF
                                      ; 2ND ARRAY

        MOV  #GOVAL, @#DRVOUT         ; ARM LDA COUNTER, SET S1 AND
                                      ; S0, AND
                                      ; MUX ADR TO ZERO

                                      ; VALIDATION ROUTINE
1$:      MOV  @#DRVIN, R4              ; GET LDA DATA INTO R3. BRANCH
        BMI  1$                      ; BACK IF BIT 15 IS SET
        MOV  R4, (R2)+                ; STORE LDA DATA BY R2 AND
                                      ; INCREMENT

                                      ; IF GOVAL01 IS DESABLE, TIME
                                      ; INTERVAL
                                      ; WON'T BE SOTRE
        MOV  #GOVAL01, @#DRVOUT       ; SET MUX TO 01 (TIME
                                      ; INTERVAL)
        ;MOV  #GOVAL03, @#DRVOUT      ; SET MUX TO 03 (NUMBER OF
                                      ; FRINGES)
        MOV  @#DRVIN, (R3)+           ; STORE TIME INTERVAL OR
                                      ; NUMBER OF
                                      ; FRINGES IN R3

        MOV  #GOVAL1, @#DRVOUT        ; TOGGLE BIT 5 TO CLEAR THE
                                      ; DATA
        MOV  #GOVAL, @#DRVOUT         ; READY FLOP
        DEC  R1                      ; DECREMENT THE NUMBER OF
                                      ; SAMPLES

```


BNE 1\$

MOV #ZERO,@#DRVOUT

RTS PC

.END

; BRANCH BACK IF MORE DATA

; DISARM LDA COUNTER AND CLEAR
; ALL
; OUTPUT BITS

This FORTRAN program calculates the statistically reduces the raw data by eliminating all data above or below +/- two standard deviations from the mean. Data is run through the elimination loops three times.

```

C PROGRAM TO ELIMINATE DATA NOT WITHIN THE RANGE OF 2 STANDARD
DEVIATIONS
C THIS PROGRAM WILL RUN THROUGH THIS CALC. TWICE AND STORE DATA IN
FILE\
C TKELLY.DAT
C23456789
      DIMENSION NO(1000),FD(1000),FREQ(1000),VEL(1000),VEL1(1000)
C ASSIGN THE OLD DATA FILE
      TYPE *, 'ENTER THE OUTPUT FILE NAME (OLD DATA FILE)'
      READ(7,100) RESEAR
      OPEN(UNIT=9,NAME=RESEAR,TYPE='OLD')
C ASSIGN THE NEW DATA FILE
100  FORMAT(A10)
      TYPE *, 'ENTER THE INPUT FILE NAME (NEW DATA FILE)'
      READ(7,100) OUTPUT
      OPEN(UNIT=8,NAME=OUTPUT,TYPE='NEW')
C ENTER THE NUMBER OF DATA POINTS
      WRITE(7,*) 'ENTER NUMBER OF DATA POINTS'
      READ(7,*) N
      VELSUM=0.0
      SQMN=0.0
C READ DATA FROM FILE AND SUM VELOCITY
      DO 10 I=1,N
      READ(9,1000) NO(I),FD(I),VEL(I)
      VELSUM=VEL(I)+VELSUM
10   CONTINUE
C CALCULATE MEAN VELOCITY
      AVG=VELSUM/FLOAT(N)
      WRITE(7,11) AVG
11   FORMAT(1X,'AVG.VEL.1 IS',1X,E12.4)
C TAKE DIFFERENCE OF VEL(I) AND MEAN, SQUARE DIFFERENCE, SUM RESULT
      DO 20 I=1,N
      SQMN=((VEL(I)-AVG)**2)+SQMN
20   CONTINUE
C CALCULATE STANDARD DEVIATION
      STDDEV=(SQMN/(FLOAT(N)-1))**.5
      WRITE(7,21) STDDEV
21   FORMAT(1X,'ST.DEV.1 IS ',E12.4)
C CALCULATE LIMITS OF +/- 2*STANDARD DEVIATION
      HIGH=AVG+2*STDDEV
      SLOW=AVG-2*STDDEV
      WRITE(7,22) HIGH
      WRITE(7,24) SLOW
22   FORMAT(1X,'HIGH.1 IS ',E12.4)
24   FORMAT(1X,'LOW.1 IS ',E12.4)
      J=0
      VELSUM=0.0
C ELIMINATE DATA ABOVE AND BELOW AVE +/- 2*STDDEV, STORE REST IN

```

```

NEW ARRAY
  DO 30 I=1,N
    IF (VEL(I) .LE. HIGH .AND. VEL(I) .GE. SLOW) GO TO 25
    GO TO 30
25    J=J+1
      FREQ(J)=FD(I)
      VEL1(J)=VEL(I)
      VELSUM=VEL1(J)+VELSUM
C      WRITE(8,1000) J, FREQ(I), VEL1(I)
30    CONTINUE
C CALCULATE NEW MEAN
  AVG=VELSUM/FLOAT(J)
  WRITE(7,42) J
  WRITE(7,41) AVG
41    FORMAT(1X,'AVG.VEL.2 IS ',E12.4)
42    FORMAT(1X,'N.2 IS ',I3)
  SQMN=0.0
  L=J
C CALCULATE NEW STANDARD DEVIATION
  DO 50 J=1,L
    SQMN=((VEL1(J)-AVG)**2)+SQMN
50    CONTINUE
  STDDEV=(SQMN/(FLOAT(L)-1))**0.5
  WRITE(7,51) STDDEV
51    FORMAT(1X,'STD.DEV.2 IS ',E12.4)
C CALCULATE NEW LIMITS
  HIGH=AVG+2*STDDEV
  WRITE(7,52) HIGH
52    FORMAT(1X,'HIGH.2 IS ',E12.4)
  SLOW=AVG-2*STDDEV
  WRITE(7,53) SLOW
53    FORMAT(1X,'LOW.2 IS ',E12.4)
  K=0
  VELSUM=0.0
C ELIMINATE DATA OUTSIDE LIMITS AND STORE REST IN NEW DATA FILE
  DO 60 J=1,L
    IF (VEL1(J) .LE. HIGH .AND. VEL1(J) .GE. SLOW) GO TO 55
    GO TO 60
55    K=K+1
      WRITE(8,1000) K, FREQ(J), VEL1(J)
      VELSUM=VEL1(J)+VELSUM
60    CONTINUE
  WRITE(7,64) K
  AVG=VELSUM/FLOAT(K)
  WRITE(7,63) AVG
64    FORMAT(1X,'N.3 IS ',I3)
65    FORMAT(1X,'THE FINAL AVERAGE IS ',E12.4)
1000  FORMAT(1X,I3,4X,E12.4,4X,E12.4)
  CLOSE(UNIT=8)
  CLOSE(UNIT=9)
  STOP
  END

```

This FORTRAN program sorts the statistically reduced data in ascending order, counts the frequency of occurrence of the velocity data and prepares the data for use in the SAS program to produce velocity histograms.

C23456789

```

      DIMENSION N(1000), F(1000), V(1000),V1(1000),T(1000)
      LOGICAL DONE, FINI
      WRITE(5,10)
10     FORMAT(1X,'ENTER THE NAME OF THE FILE TO BE SORTED')
      READ(5,12) RESEAR
12     FORMAT(A10)
      OPEN(UNIT=15,FILE=RESEAR,STATUS='OLD')
      WRITE(5,15)
15     FORMAT(1X,'ENTER THE NAME OF THE NEW FILE')
      READ(5,16) SFILE
16     FORMAT(A10)
      OPEN(UNIT=14,FILE=SFILE,STATUS='NEW')
      WRITE(5,18)
18     FORMAT(1X,'ENTER THE NUMBER OF DATA POINTS')
      READ(5,*) K
      DO 30 I = 1, K
        READ(15,*) N(I), F(I), V(I)
30     CONTINUE
      PAIRS=K-1
      DONE=.FALSE.
35     IF (.NOT. DONE) THEN
        DONE=.TRUE.
        DO 40 I=1, PAIRS
          IF (V(I) .GT. V(I + 1)) THEN
            TEMP = V(I)
            V(I) = V(I + 1)
            V(I + 1) = TEMP
            DONE=.FALSE.
          END IF
          WRITE(5,39) I, V(I)
          FORMAT(1X,I3,4X,E12.4)
40     CONTINUE
      PAIRS=PAIRS-1
      GO TO 35
    END IF
    L=0
    J=0
    DO 50 I=1,K
      L=L+1
      IF (V(I) .NE. V(I+1)) THEN
        J=J+1
        WRITE(5,95) J, V(I), L, 1
        WRITE(14,95) J, V(I), L, 1
        L=0
95     FORMAT(1X,I3,4X,E12.4,4X,I3,4X,I1)
      END IF
50     CONTINUE
    END

```

This program produces the velocity histograms of the statistically reduced data using SAS on the VAX system.

```
FILENAME DATA 'DISK04:KEL.DAT';  
DATA;  
INFILE KEL;  
INPUT N V F A$;  
PROC GPLOT;  
PLOT F*V=A/VAXIS=0 TO 25 by 5.0 HAXIS=0.0 to 15.0 BY 0.5 OVERLAY;  
SYMBOL1 I=NEEDLE V=STAR;  
TITLE1 H=1 F=NONE 'VELOCITY HISTOGRAMS';  
TITLE 2 H=1 F=NONE 'AXIAL CENTERLINE VELOCITY';  
TITLE3 H=1 F=NONE 'PARTICLE SIZE = 500 microns';  
TITLE4 H=1 F=NONE 'PIPE DIAMETER = 2.5 cm';  
LABEL F='FREQUENCY';  
LABEL V='VELOCITY';  
GOPTIONS BAUD=2400;  
RUN;
```

END

**DATE
FILMED**

12 / 16 / 92