CLASSIFICATION

UNCLASSIFIED

DOCUMENT IDENTIFICATION NO.

BNWL-SA-1767

BATTELLE NORTHWEST
BATTELLE MEMORIAL INSTITUTE PACIFIC NORTHWEST LABORATORY
POST OFFICE BOX 999 / RICHLAND, WASHINGTON 99352

**RECORD
COPY**

COPY AND SERIES NO.

1-

DATE

April 9, 1968

TITLE AND AUTHOR

MASS TRANSFER AT THE SOLID-LIQUID INTERFACE FOR CLIMBING
FILM FLOW IN AN ANNULAR DUCT

AM SUTLEY, JG KNUDSEN

CONTRACT

☐ - 1830
☐ - 1831

PROJECT NO.

RESERVED FOR TECHNICAL INFO. USE

REFERENCE COPY

D I S T R I B U T I O N

NAME

COMPANY

LOCATION

NAME

COMPANY

LOCATION

ROUTE TO

PAYROLL NO.

COMPANY

LOCATION

FILES ROUTE
DATE

SIGNATURE AND DATE

UNCLASSIFIED

CLASSIFICATION

MASTER *Se*

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

ABSTRACT

A method utilizing a diffusion controlled electrochemical reaction was used to measure average and instantaneous mass transfer coefficients at the solid-liquid interface in upward gas-liquid climbing film flow in a vertical annular duct. These measurements give some indication of the mechanics of flow of the film, the extent of turbulence at the inner wall, and the effect of film thickness and wave motion on the mass transfer process at the inner wall. Predictions of incipient downflow of the film, shear stress at the inner wall, and interfacial shear stress were obtained from these measurements. Fluctuations in the velocity gradient at the inner wall were also studied. Results of this study are in fair agreement with previous work and with theoretical predictions based on simplified momentum balance concepts.

MASS TRANSFER AT THE SOLID-LIQUID INTERFACE FOR CLIMBING FILM FLOW IN AN ANNULAR DUCT

by
A. M. Sutey
J. G. Knudsen

INTRODUCTION

Climbing film flow is but one of the various regimes of upward two-phase (gas-liquid) flow. In climbing film flow the liquid moves upward as a film on the surface of the duct as the faster moving gas stream flows upward adjacent to the liquid film. Due to the momentum transfer at the gas-liquid interface, the liquid film is transported upward at the expense of the pressure energy of the gas stream. As a result, the liquid film is characterized by complex wave and entrainment phenomena. This type of flow is of particular interest since it exists over a rather wide range of gas and liquid flow rates and is commonly encountered in process equipment.

A knowledge of the mechanics of climbing film flow is essential to predict and understand the momentum, heat, and mass transfer processes which occur in the process. However, the difficulties involved in determining the fluid dynamics of the climbing film are considerable, primarily, since it is nearly impossible to probe the very thin film without disturbing it. Theoretical models of the climbing film can be tested better by means of accurate local measurements than by the total liquid flow approach which has been employed in many investigations.

In the present study, the liquid flows as a film up the concentric inner core of an annulus while air flows upward in the annular space,

the outer wall of the annulus remaining dry. Such an arrangement permits direct observation of the climbing film through a transparent outer tube and simplifies the measurement of pressure gradients, air velocity profiles and film structure.

An electrochemical method utilizing a diffusion controlled ferro-ferricyanide redox couple was used to measure average and instantaneous mass transfer coefficients at the solid-liquid film interface. This method has been used extensively in various geometrical systems by many investigators (1, 2, 6, 8, 15-17, 19-23), but has been restricted to oxygen-free systems. A preliminary study was performed by the authors (25, 26) in a pipe flow system to measure the actual effect of dissolved oxygen on the measured mass transfer coefficient. It was found that the electrochemical technique can be applied in the presence of air if certain precautions are taken.

This study demonstrates the advantage of local instantaneous measurements in describing climbing film phenomena. Further studies of this type will lead to a more basic understanding of the processes of heat, mass, and momentum transfer which occur in two-phase gas-liquid film flow.

BACKGROUND THEORY

Detailed theory relating to the measurement of mass transfer coefficients by the electrochemical method is given in references (25) and (26). The simplified current equation is:

$$\frac{i}{An F} = \bar{k}_c (C_b - C_w) \quad (1)$$

At the limiting current the interfacial concentration c_w becomes zero, and the rate of mass transfer is expressed as:

$$\frac{i_L}{An F} = \bar{k}_c C_b \quad (2)$$

where $\bar{k}_c$ is the mass transfer coefficient and is a function of Reynolds number, Schmidt number and geometry. Typical polarization curves for the ferro-ferricyanide system are shown in Figure 5. Limiting current is obtained at the flat portion of the curve. The occurrence of a limiting current confirms that the reaction is diffusion controlled. In this manner, experimental mass transfer coefficients can be determined from Equation 2. It should be noted that this development doesn't require the existence of any special type of fluid dynamics near the electrode surface.

Momentum Transfer in Climbing Film Flow -- In this investigation the liquid film flows upward on the inner concentric core of an annulus as shown in Figure 1. The simplified steady state equations of continuity and momentum for the climbing film flow system are:

$$\frac{\rho u}{g_c} \frac{\partial u}{\partial x} = \frac{-\partial P}{\partial x} + \frac{1}{r} \frac{\partial}{\partial r} (r\tau) - \frac{\rho g}{g_c} \quad (3)$$

$$0 = \frac{\partial P}{\partial r} \quad (4)$$

$$0 = \frac{\partial u}{\partial x} + \frac{1}{r} \frac{\partial (r\tau)}{\partial r} \quad (5)$$

Assuming: (1) $\frac{\partial P}{\partial x}$ is constant; (2) the liquid film is of uniform thickness, r_1 ; (3) no mass transfer occurs between the gas and the liquid either by diffusion or entrainment; and (4) physical properties are constant, one may obtain the following expressions:

$$\frac{dP}{dx} \int_1^2 r dr + \frac{\rho g}{g_c} \int_1^2 r dr + \frac{\rho}{g_c} \int_1^2 u \frac{du}{dx} r dr = \left[r\tau \right]_1^2$$

$$\frac{dP}{dx} + \frac{\rho g}{g_c} + \frac{(\rho/g_c)}{(r_2^2 - r_1^2)} \frac{d}{dx} \int_1^2 u^2 r dr = \frac{2 \left[r\tau \right]_1^2}{(r_2^2 - r_1^2)} \quad (6)$$

the usual equation

Applying equation (6) to various regions of the annulus, one may obtain the following shear stress relationships assuming kinetic energy effects are negligible compared to the other terms.

$$\tau_1 = \frac{1}{r_1} \left[r_1 \tau_1 - a \frac{(r_2^2 - r_1^2)}{2} \right] \quad (7)$$

$$\tau_1 = \tau_2 \frac{r_2}{r_1} \frac{R_1}{R_2} \quad (8)$$

$$\tau_2 = \beta \frac{(r_m^2 - r_2^2)}{2r_2} \quad (9)$$

where $a = \left(\frac{dP}{dx} + \frac{\rho_L g}{g_c} \right)$ and $\beta = \frac{dP}{dx} + \frac{\rho_G g}{g_c}$

If the pressure gradient, point of maximum velocity, film thickness and shear stress at the outer wall are known, the shear stress at the solid-liquid interface (τ_1) may be calculated and compared with values obtained via independent measurements.

Equations (7) and (8) may also be obtained via a simplified laminar film analysis of equation (3) using the aforementioned assumptions and the following boundary conditions:

$$\begin{array}{ll} \text{at } r=r_1 & u = 0 \\ \text{at } r=r_2 & \frac{du}{dr} = \frac{r_2 g_c}{\mu} \end{array}$$

Therefore, the laminar climbing film analysis has merit in that it reduces to the proper limits when considering shear stress distribution.

Generally, entrainment is present for most two phase gas-liquid film flows. Equations (6) through (9) may still be used to estimate two phase flow parameters if the density of the gas core is available from entrainment data. For such a case

$$\frac{1}{\rho} = X \left(\frac{1}{\rho_G} \right) + (1-X) \left(\frac{1}{\rho_L} \right) \quad (10)$$

where X is the quality (weight fraction) of the gas phase. Since entrainment data is not available for the present system, no relation involving the density of the gas core was used for calculations in this work.

Mass Transfer at the Solid-Liquid Interface -- Consider the liquid film as shown in Figure 2 flowing over a smooth test electrode under the following conditions: (1) the liquid properties are constant; (2) the surface concentration is uniform ($c_w = 0$); (3) the undisturbed liquid bulk concentration is c_b ; (4) mass transfer is due to diffusion alone; (5) curvature is neglected; (6) the test electrode is short (for small values of y $\partial^2 c / \partial x^2 \ll \partial^2 c / \partial y^2$); (7) the concentration boundary layer is within the laminar sublayer which is fully developed; (8) the thickness of the concentration boundary layer is small compared to the mean film thickness; and (9) the velocity of the liquid near the wall is $u = \frac{\bar{a}}{y}$, $u = \bar{a}y$, $v = 0$, $w = 0$.

This boundary value problem was solved by Leveque (14). The average mass transfer coefficient over a length L is:

$$\bar{k}_c = 1.68 D_{AB} \left(\frac{\bar{a}}{9 D_{AB} L} \right)^{1/3} \quad (11)$$

Using this relation one can estimate the momentum transfer to the inner core wall by means of experimental mass transfer data. This analysis is applicable to both laminar and turbulent liquid film flows provided the concentration boundary layer does not greatly exceed the region of linear velocity gradient near the wall.

Velocity Gradient and Shear Stress at the Solid-Liquid Film Interface --

Rearrangement of Equation (11) gives the following expression for the velocity gradient in the region of the wall

$$\bar{a} = 1.898 D_{AB} L \left(\frac{\bar{k}_c}{D_{AB}} \right)^3 \quad (12)$$

If very short sections are considered, all mass transfer may occur within a relatively thin laminar layer of fluid near the wall. In such a case the concentration boundary layer would not extend beyond the so called laminar sublayer. Mass transfer coefficient measurements for short electrodes of different sizes are used to determine $\bar{a}$. If values for $\bar{a}$ for the different electrodes remain essentially constant under the same gas-liquid flow conditions, then the concentration boundary layer is within the laminar sublayer. In this case shear stresses at the inner wall may be calculated as follows:

$$\tau_1 = \frac{\mu}{g_c} \left(\frac{du}{dy} \right)_{y=0} = \frac{\mu \bar{a}}{g_c} \quad (13)$$

and

$$\tau_1 = \frac{1.898 \mu D_{AB} L}{g_c} \left(\frac{\bar{K}_c}{D_{AB}} \right)^3 \quad (14)$$

Therefore shear stresses at the inner wall may be determined from electrode length, physical properties and experimental mass transfer coefficients calculated from Equation (2).

Estimation of Mean Interfacial Shear Stress -- Equation (7) gives:

$$\tau_i = \frac{1}{r_i} \left[r_i \tau_1 - a \left(\frac{r_i^2 - r_1^2}{2} \right) \right]$$

where τ_i is the mean interfacial shear stress which consists both of viscous drag and form drag on the air-liquid interface. Substitution of τ_1 from Equation (14) gives:

$$\tau_i = \frac{1}{r_i} \left[\frac{1.898 \mu D L r_i}{g_c} \left(\frac{\bar{K}_c}{D_{AB}} \right)^3 - a \left(\frac{r_i^2 - r_1^2}{2} \right) \right] \quad (15)$$

If the pressure gradient, film thickness, and mass transfer coefficient are known, τ_i may be determined.

The mean interfacial shear stress may also be determined using Equation (8) if the film thickness, point of maximum air velocity, and shear stress at the outer wall are known.

Estimation of Incipient Downflow -- At very low gas flow rates insufficient momentum is transferred from the gas phase to the liquid film to maintain climbing film flow. Near the inner core wall the liquid film may be flowing downward even though the net flow of the film may be upward. Downflow begins when the shear stress at the solid-liquid interface is zero. From Equations (7) and (3):

$$0 = 2R_1 r_2 \tau_2 - c R_2 (r_1^2 - r_i^2) \quad (16)$$

If the pressure gradient, point of maximum velocity, film thickness, and shear stress at the outer wall are known, downflow conditions may be estimated and compared with downflow results determined from experimental mass transfer measurements. It should be noted that Equation (16) may also be obtained from the laminar climbing film model.

EXPERIMENTAL APPARATUS AND PROCEDURE

Two Phase Flow System -- A detailed sketch of the test section is presented in Figure 3. Cooled, metered air was supplied to the system by a blower rated at 550 cfm at 9 psig. The vertical annular column was 35 feet long including a 20 foot long annular test section. The test section consisted of a 3-inch I. D. plexiglass tube with a 1-inch O. D. stainless-steel concentric inner core which was supported laterally by sets of streamlined stainless-steel centering screws.

The liquid supply was kept in a 15 gallon stainless-steel, steam jacketed vessel and maintained under a nitrogen atmosphere. Liquid was pumped into the inner core of the annular column and entered the test section by a liquid injection section which consisted of a 1-inch O. D. stainless-steel porous tube 2 inches long and 3/64-inch thick. Liquid was transported upwards as a thin film on the inner tube by means of momentum transferred from the air stream. The mass transfer measurement location was approximately 11 feet above the liquid injector. At this location the liquid film temperature was also measured by means of a calibrated temperature probe. At the end of the column the air and liquid were completely separated by means of a reducing section and a subsequent cyclone arrangement, and the liquid was subsequently discarded to drain.

The following ranges of air and liquid flow conditions were covered: air flow rates 140-385 cfm at 68°F and one atm, and liquid flow rates 0.2-1.46 lb / min.

Electrochemical Systems -- All experimental mass transfer data were obtained at limiting current which was determined from a plot of average current versus potential similar to the curve in Figure 3. Limiting current was obtained at the flat portion of the curve. A potential was applied between the anode and the cathode, and the current in the circuit was measured. Adjustment of a rheostat in the circuit permitted the determination of the entire polarization curve.

Fluctuations in the electrochemical circuit current were recorded as voltage variations across standard resistors either by a Honeywell Model 1508 Visicorder or by a Tektronix type 545A oscilloscope. A Tektronix type 122 AC-coupled preamplifier with differential input was used in the circuit to amplify the voltage signal from the standard resistor. The common mode rejection ratio of this amplifier was used to eliminate the DC-component. Adjustment of the high and low frequency response

positions of the amplifier and subsequent observation of the oscilloscope trace allowed one to determine the approximate frequency range of the signal.

The test electrodes were of two types--ring electrodes and wire electrodes. Both types of electrode assemblies constituted a portion of the inner core of the annular test section.

For the ring-type electrode, Figure 4 the electrochemical reaction was carried out between a large nickel ring (anode) and the small nickel ring (cathode) mounted flush to the inner core wall. The one-inch long anode was sufficiently large so that the current was not limited in any way. Thus, all concentration polarization effects were due only to the reaction at the cathode. The cathodes varied in length from approximately $1/16$ to $1/8$ -inch long. The primary purpose of this ring-type electrode assembly was to measure average mass transfer coefficients as a function of liquid and gas flow rates.

The electrode rings were mounted concentrically onto an approximately one-inch outside diameter plexiglass rod which had been machined and threaded on each end to $5/8$ -inch outside diameter. A $1/2$ -inch long plexiglass spacer separated the electrodes. Epoxy cement was applied to the electrodes and spacer; immediately afterwards, a $1/2$ -inch long plexiglass spacer was screwed firmly against the anode to hold the electrodes in place. This spacer also insulated the anode from the upper section of the inner core. Each electrode assembly was constructed so that a minimum of three inches of smooth plexiglass preceded the test electrode (cathode) in order to eliminate disturbing the flow field near the core wall. The entire electrode assembly was machined in one operation to the dimensions of the inner core and polished smooth with rouge paper.

Prior to the installation of the electrodes in the system, they were cleaned with carbon tetrachloride. Each electrode remained in the system for a series of experiments. Before each experimental run the electrodes were cathodically cleaned in 5% NaOH solution at a current density of 20 ma for 12-15 minutes to minimize chemical polarization effects (6,19). Following each run the cell was inspected to ascertain if adverse corrosion deposits had formed on the electrode surface during the experiment. In general, no such deposits were formed during the experimental runs if the aforementioned cleaning procedure was followed. Failure to properly clean the electrodes causes erroneous mass transfer results (26). Care was also taken to operate the cell no longer than three hours without recleaning the electrodes.

The wire-type electrode assembly was essentially the same as the ring-type assembly except for the cathode design. Thus, only the cathode is shown for the wire-type electrode in Figure 4. The cathode was a 0.064-inch diameter nickel wire mounted flush to the inner core wall. The wire was inserted into the plexiglass spacer separating it from the anode and was held in place with epoxy cement. The entire electrode assembly was machined and polished to its proper dimensions after all components had been assembled. This type of electrode arrangement was utilized to obtain velocity gradient fluctuations at the solid-liquid film interface.

For all climbing film flow experiments the electrolyte used was a 0.025-equimolar solution of potassium ferricyanide and potassium ferrocyanide in 2N NaOH. The sodium hydroxide acted as an indifferent electrolyte to eliminate any migration due to ionic transference effects. The solutions were prepared just prior to the runs using distilled water which had been purged with nitrogen to eliminate dissolved oxygen. Precautions were taken to keep the test solution away from light.

EFFECT OF DISSOLVED OXYGEN

In a preliminary study (25, 26) suitable dissolved oxygen limits were established for the electrochemical measurement of mass transfer coefficients in the presence of air. This study showed that if the test solution is first saturated with nitrogen, future exposure to air for a short period of time does not greatly affect the mass transfer data.

In the climbing film flow study the electrolyte was completely saturated with nitrogen prior to its injection into the annular test section. The solution in the liquid reservoir was maintained at approximately ten per cent saturation. The percentage of dissolved oxygen in the redox solution increased as it flowed upward through the two phase system. The dissolved oxygen content of the climbing film was measured about six inches above the test electrodes, and for the liquid and gas flow rates studied the percent saturation of dissolved oxygen at this location varied between 30-50%. Based on previous results (25, 26) the effect of dissolved oxygen on the mass transfer coefficient in climbing film flow is less than 2%. All dissolved oxygen content measurements were obtained via a Beckman Oxygen Analyzer model 777.

EXPERIMENTAL RESULTS

Mass Transfer Coefficients at the Solid-Liquid Film Interface --

Figures 6 and 8 summarize the experimental data for the 1/8-inch and 1/16-inch electrodes. Figures 6 and 7 present $\bar{K}_c$ as a function of air flow rate with liquid flow rate as parameter, whereas, Figure 8 presents $\bar{k}_c$ as a function of liquid flow rate with air flow rate as parameter. The data is plotted in this manner in order to examine the relative effects of air and liquid flow rates on the mass transfer process. The experimental mass transfer coefficients are considered accurate to within $\pm 5\%$.

As shown by Figures 6 and 7 the mass transfer data of the two electrodes are in qualitative agreement. However, the data of the 1/16-inch electrode are more extensive than those of the 1/8-inch electrode; hence, reference will be made primarily to the data of the shorter electrode.

Figure 7 shows the dependence of $\bar{k}_c$ on gas flow rate. The mass transfer coefficient decreases rapidly as the air flow rate is decreased at constant liquid flow rate. As the gas flow rate decreases the film thickness increases, and the film velocity decreases; thus, $\bar{k}_c$ decreases. At very low gas flow rates $\bar{k}_c$ exhibits a minimum value which corresponds to incipient downflow within the film. Although the shear stress at the inner wall is zero at incipient downflow, $\bar{k}_c$ has a finite value. Since the film is very agitated at this point, $\bar{k}_c$ is probably much greater than it would be under stagnant conditions. As flooding is approached $\bar{k}_c$ increases slightly due to increased downflow and agitation within the film.

Figure 8 shows the effect of liquid flow rate on $\bar{k}_c$. Except for the lowest gas flow case, the nature of the relationship between $\bar{k}_c$ and liquid flow is qualitatively the same regardless of gas flow rate. The mass transfer coefficient decreases slightly as liquid flow rate is decreased. At low liquid flow rates, $\bar{k}_c$ increases sharply just before the minimum wetting rate is reached. The rise in $\bar{k}_c$ just prior to the minimum wetting rate is caused not only by a decrease in film thickness but also by turbulence developed in the film during the groping and reforming periods. A similar rise in heat transfer coefficient near the minimum wetting rate region was measured by Norman and McIntyre (18) for a falling liquid film on a vertical surface.

The lowest gas flow rate in Figure 8 corresponds to the downflow region. In this low film velocity region the film tends to maintain its

identity at lower liquid rates and the minimum wetting rate is lowered. Therefore, no rise in $\bar{K}_c$ was noted in the low liquid flow range.

A comparison of Figures 7 and 8 shows the mass transfer coefficient is much more dependent on air flow rate than on liquid flow rate primarily because film velocity, film thickness and film stability are strongly dependent on the gas flow rate.

Fluctuations in Rate of Mass Transfer to a Wire Electrode --

Visicorder traces of the fluctuations in the rate of mass transfer to a small wire electrode are shown for various flow conditions in Figure 9. The frequencies of the fluctuations are mostly in the 0.2-100 cps range although a power spectrum density analysis is required to describe in detail the frequency domain of the signals. The intensity of the fluctuations increases as the gas flow rate is decreased. At downflow conditions the fluctuations increase considerably indicating a transition in the flow field near the electrode. For the same gas flow rate the film is more stable at low liquid flow rates than at high liquid flow rates. Since more momentum transfer from the air stream is required to maintain high liquid flow films, this result is to be expected.

The present data indicate that mass transfer at the solid-liquid wall may be influenced by the wave structure of the climbing film. The visicorder traces for downflow reflect to a considerable degree the observed pulse-like nature of the climbing film under downflow conditions. Similar results have been shown by Chand and Rosson (3) who demonstrated the importance of wave motion on the heat transfer process within a falling film. Further instantaneous local measurements are required: (1) to study the quantitative effect of the air-liquid interface on the rate of mass transfer to the inner wall, and (2) to classify flow regimes which occur in climbing film flow. (3).

Velocity Gradients at the Solid-Liquid Interface

A comparison of the velocity gradients at the solid-liquid film interface calculated from experimental mass transfer data of the 1/16-inch and 1/8-inch electrodes for the same air and liquid flow was made. The average calculated value of $\bar{a}_1/\bar{a}_2$ was 1.35. If the ratio $\bar{a}_1/\bar{a}_2$ is approximately 1.0, all mass transfer measurements are assumed to occur within a region of uniform velocity gradient close to the inner wall. This comparison between $\bar{a}_1$ and $\bar{a}_2$ is reasonably good and well within experimental error. Since $\bar{a}_1/\bar{a}_2$ is dependent on $(D_2/D_1)^2 (\bar{k}_{c1}/\bar{k}_{c2})^3$ a small error in the values of $\bar{k}_c$ and D could cause a large error in the calculated value of $\bar{a}_1/\bar{a}_2$. To further ensure that all mass transfer measurements were obtained within a laminar-flow region near the wall, only the experimental data of the 1/16-inch electrode were used to calculate other quantities based on the Leveque model.

Based on the classical film model ($\delta = D/\bar{k}_c$), the concentration boundary layer thickness was determined from mass transfer coefficient data for the 1/16-inch electrode. The estimated concentration boundary layer thickness was 4 to 9% of the experimental liquid film thickness for liquid flows of 0.48 to 0.79 lb/min and gas flows of 198 to 379 cfm. Thus, under these conditions, the Leveque model is applicable.

Shear Stress at the Inner Wall--The shear stress at the solid-liquid interface was calculated from Equation 14 by means of experimental mass transfer data for the 1/16-inch electrode. The accuracy of τ_1 is estimated to be within $\pm 20\%$. In Figure 10, τ_1 is presented as a function of gas flow rate with liquid flow rate as parameter and as would be expected exhibits a character similar to $\bar{k}_c$.

The minimum value of τ_1 in Figure 10 corresponds to incipient downflow within the film even though τ_1 is not zero. This results since K_c is finite at incipient downflow. Also, since K_c is always positive, only positive τ_1 values are predicted. Nevertheless, the minimum value of τ_1 indicates a transition in the velocity gradient at the wall. For gas flow rates less than 180 cm, the actual shear stresses were obtained by extrapolation of the lines shown in Figure 11. It is noted that zero shear stress occurs in the region 155 to 165 cm. Values of τ_1 were also calculated from Equations 7 and 8. Film thicknesses, shear stresses at the outer wall, and radii of maximum air velocity obtained by KLM (12,13) were used with pressure gradients from the present work. These results are also presented in Figure 11 and are within 25 to 60% of those obtained using K_c data. The discrepancy between τ_1 values predicted by the two sets of data may be attributed in part to errors in mean thickness as reported by KLM (12,13). Errors in mean film thickness cause appreciable errors in values of τ_1 calculated from Equations 7 and 8. The greatest deviation in predicted τ_1 values occurs in the low air flow rate region where the data of KLM are minimal. Additional accurate film thickness data are required in the low air flow rate region to explain these differences. In the low air flow rate region, τ_1 values calculated from K_c data are considered most reliable since Figure 12 shows these values approach the proper downflow limit of zero. Also, these predictions of incipient downflow compare well with those determined via experimental pressure drop measurements which will be subsequently discussed.

Pressure Gradient and Entrainment -- Typical pressure gradients are presented in Figure 12 as a function of air flow rate with liquid flow rate as parameter. In reference (25), pressure gradient data were reported both at equilibrium and minimum entrainment conditions.

Comparison of the data showed that entrainment increases at low air flow rates as downflow and flooding is approached especially at high liquid flow rates. Entrainment reaches a minimum in the moderate gas flow range. Except at very low air flow rates, the effect of entrainment on the pressure gradient is negligible for the flow rates studied.

At very low air flow rates, the pressure gradient reaches a minimum value which closely corresponds in terms of air and liquid flow rates to incipient downflow as shown by $\bar{k}_c$ data in Figure 7. Under downflow conditions the air-liquid interface is very rough and unstable requiring more energy to be transferred from the air to maintain the climbing film. Thus, the pressure gradient increases as flooding is approached.

Shear Stress at the Air-Liquid Interface -- The shear stress (τ_i) at the air-liquid film interface was calculated from Equation 7 using τ_1 and α values determined in the present study and mean film thickness data of Kim (12, 15).

In Figure 13 τ_i is presented as a function of gas flow rate with liquid flow rate as parameter. The interfacial shear stress decreases as gas flow rate decreases. For a liquid flow rate of 0.48 lb/min for which film thickness data is available, τ_i exhibits a minimum value at a gas flow rate of 224 cfm, whereas, downflow occurs at 158 cfm based on $\bar{k}_c$ data. This behavior of τ_i may initiate the gradual change of the velocity gradient at the inner wall from positive to negative. Further study in light of additional film thickness data is required to explain the behavior of τ_i .

Values of τ_i were also calculated from Equation 8. Film thickness, shear stresses at the outer wall, and radii of maximum air velocity obtained by Kim (12,13) were used. These results are also presented in Figure 13 and compare within 20 to 40% of those obtained using $\bar{k}_c$ and α data.

DISCUSSION OF RESULTS

The instantaneous local measurements of mass transfer at the solid-liquid interface permit better understanding of the nature of climbing film flow. In their studies of electrochemical mass transfer to a small electrode on a pipe wall, Reiss and Hanratty (20) recorded no fluctuations in the rate of mass transfer to the electrode in the laminar flow regime. At a Reynolds number of 2,140 a slight wavy disturbance was noted. These disturbances increased in the transition region and were observed to greatly increase in frequency and intensity as the Reynolds number further increased to fully developed turbulent flow conditions. Based on these observations of Reiss and Hanratty and the traces in Figure 9 climbing film flow is considered turbulent for the gas and liquid flows studied. The climbing film is relatively stable at high gas flow rates but becomes increasingly turbulent as the gas flow rate is decreased at a constant liquid flow rate. Turbulence is more characteristic of climbing films formed from high liquid flow rates than those formed from low liquid flow rates.

On the basis of the fluctuating mass transfer data obtained in this study, surface renewal models (4,9,11,27) are considered as possible explanations of the exchange of heat, mass, and momentum transfer from the climbing film to the inner wall. Surface renewal parameters may be determined from the mass transfer results of this work and used to predict preferably heat transfer results for the climbing film system. Since no convective heat transfer results are presently available for this system, surface renewal models were not tested.

Under downflow conditions flow adjacent to the inner wall is downward even though the net flow of the film may be upward. At incipient downflow the shear stress at the inner wall is zero. The air and liquid flow conditions at incipient downflow are estimated at the minimum values of the mass transfer coefficient and pressure gradient. These values are presented in Table I and show excellent agreement with each other. Table I shows that incipient downflow occurs at progressively higher air flow rates as the liquid flow rate increases since more momentum transfer from the air is required to maintain the higher liquid film flows. Predictions of incipient downflow by means of local mass transfer coefficient data are considered the most reliable and do not depend on subjective visual observations of the film.

Downflow may also be measured by the occurrence of high intensity fluctuations in the local instantaneous rate of mass transfer to a wire electrode as shown in Figure 9. However, insufficient data is presently available over a wide range of liquid flows to use this method.

Downflow was also observed by Willis (28), and Hewitt, et al. (10) in upward annular air-water flow in a vertical tube. Curves of pressure gradient versus gas flow rate at constant liquid flow exhibited minimum values which corresponded to zero wall shear stress. Fair agreement was obtained between measured minimum pressure gradients and those predicted using laminar film flow theory.

Table I
Air Flow Rates at Incipient Downflow

Liquid Flow Rate lb/min	$\Delta P/\Delta x$ Minimum Entrainment	$\Delta P/\Delta x$ Equilibrium Entrainment	τ_1 From Mass Transfer Measurements	τ_1 Film-Knudsen
Air Flow Rate (cfm) - at 60°F and 1 atm				
0.20			156	
0.34	158	165	157	
0.48	158	160	158	202
0.79	164	168	161	
1.10	172	185	163	
1.30	170		164	
1.46			164	

The shear distribution within the film is described by Figure 14 in which the ratio of the interfacial shear to the shear stress at the inner wall is presented. At very low gas rates τ_i/τ_1 , approaches infinity as downflow is approached. At high gas rates this ratio becomes independent of liquid flow rate and approaches unity; i. e. the

shear stress is constant across the film. Shearer and Nedderman (24) have also reported $\tau_w = \tau_i$ (to a 1% accuracy) for the small ripple wave regime in annular climbing-film flow. Additional film structure data is required to study the shear stress distribution over a wide range of liquid and gas flow conditions.

The variation of τ_i/τ_1 with flow conditions, Figure 14 is closely related to that of mean film thickness with flow conditions as shown in Figure 15. At very low gas rates the film thickness approaches infinity as downflow and flooding is approached. As the gas flow rate increases the film thickness decreases rapidly up to a flow rate of 240 cfm after which it decreases more slowly becoming nearly independent of liquid flow rate at the highest air flow studied. The similar behavior of τ_i/τ_1 and film thickness with flow conditions demonstrates the dependence of the velocity profile on film thickness.

The results of this study indicate the variation in the velocity profile of the climbing film as a function of air and liquid flow rates. The possible velocity profiles in the liquid film are shown in Figure 16 in the order of increasing gas flow rate.

CONCLUSIONS

The results of this study are as follows:

(1) At constant liquid flow rate the mass transfer coefficient decreases rapidly as air flow rate decreases and at very low gas flow rates exhibits a minimum value which corresponds to incipient downflow within the climbing film.

(2) At constant gas flow rate the mass transfer coefficient decreases slightly as liquid flow rate is decreased and at very low liquid flow rates increases sharply just prior to the minimum wetting rate.

(3) Based on the fluctuations in the rate of mass transfer to the inner core wall, the climbing film flow is considered turbulent for the gas and liquid flows studied. The climbing film is relatively stable at high gas flow rates but becomes increasingly turbulent as downflow is approached.

(4) The shear stress at the inner wall was calculated from the Leveque Theory for climbing film flow using experimental mass transfer data of a short electrode. Results compare well with independent values calculated from previous work.

(5) At constant liquid flow rate the pressure gradient decreases rapidly as the air flow rate decreases and at very low air flow rates reaches a minimum value which closely corresponds in terms of air and liquid flow rates to incipient downflow as indicated by the mass transfer coefficient data.

(6) Interfacial shear stresses were calculated from two separate relationships each using independent experimental data and the results compare well with each other.

(7) At very low gas rates the shear stress ratio τ_i/τ_1 approaches infinity as downflow is approached. At high gas rates this ratio becomes independent of liquid flow rate and approaches unity. The similar behavior of τ_i/τ_1 and film thickness as affected by flow conditions demonstrates the dependence of the velocity profile on film thickness.

NOMENCLATURE

<u>Symbol</u>	<u>Definition</u>	<u>Dimensions</u>
$\bar{a}$	velocity gradient at the electrode wall	1/sec
A	surface area of working electrode	cm ²
c_b	bulk concentration of ferricyanide ions	moles/cc
c_w	interfacial (solid-liquid) concentration	moles/cc
D, D _{AB}	diffusivity of ferricyanide ions	cm ² /sec
F	Faraday (96,500)	coulomb equivalent
g	acceleration of gravity	ft/sec ²
g_c	force-mass conversion factor (32.17)	$\frac{\text{lb}}{\text{m ft}} \text{sec}^2$ lb _f sec ²
i	current	amperes
i_L	limiting current	amperes
$\bar{k}_c$	average mass transfer coefficient	cm/sec
L	length of electrode	inch
n	number of electrons involved in electrode reaction	
P	pressure	lb _f /ft ²
$\Delta P/\Delta x$	pressure gradient	lb _f /ft ³
r	direction co-ordinate	inch
r_1	inner core radius	inch

<u>Symbol</u>	<u>Definition</u>	<u>Dimensions</u>
r_2	outer tube radius	inch
r_i	interface (liquid film-air) radius	inch
r_m	radius of maximum air velocity	inch
R_1	$(r_m^2 - r_i^2) / (r_2^2 - r_1^2)$	dimensionless
R_2	$(r_2^2 - r_m^2) / (r_2^2 - r_1^2)$	dimensionless
R_L	$(r_i^2 - r_1^2) / (r_2^2 - r_1^2)$	dimensionless
R_G	$(r_2^2 - r_i^2) / (r_2^2 - r_1^2)$	dimensionless
u	local velocity in the x direction	ft/sec
v	local velocity in r (or y) direction	ft/sec
x, y	distance co-ordinate	inch
α	$(\Delta P / \Delta x + \rho_L g / \bar{s}_c)$	$\text{lb}_m / \text{ft}^3$
β	$(\Delta P / \Delta x + \rho_G g / \bar{s}_c)$	$\text{lb}_m / \text{ft}^3$
μ	viscosity	$\text{lb}_m / \text{ft-sec}$
ρ_L	density of liquid (electrolyte)	$\text{lb}_m / \text{ft}^3$
ρ_G	density of gas (air)	$\text{lb}_m / \text{ft}^3$
τ	shear stress	$\text{lb}_f / \text{ft}^2$
τ_1	shear stress at solid-liquid film interface (at inner core wall)	$\text{lb}_f / \text{ft}^2$
τ_2	shear stress at outer tube wall	$\text{lb}_f / \text{ft}^2$
τ_i	interfacial (air-liquid film) shear stress	$\text{lb}_f / \text{ft}^2$
X	quality (weight fraction) of the gas phase	dimensionless

BIBLIOGRAPHY

1. Bazan, J. C. and A. J. Arvia. Ionic mass transfer in flowing solutions. Electrochemical reactions under ionic mass-transfer rate control on cylindrical electrodes. *Electrochimica Acta* 9:667-684, 1964
2. _____ The diffusion of ferro-ferricyanide ions in aqueous solutions of sodium hydroxide. *Electrochimica Acta* 10:1025-1032. 1965.
3. Chand, R. and H. F. Rosson. Local heat flux to a water film flowing down a vertical surface. *Industrial and Engineering Chemistry Fundamentals* 4:356-359. 1965.
4. Danckwerts, P. V. Significance of Liquid Film Coefficients in Gas Absorption. *Industrial and Engineering Chemistry Fundamentals* 43:1460-1466. 1951.
5. Dukler, A. E. and M. G. Hubbard. The characterization of flow regimes for horizontal two-phase flow: I. Statistical analysis of wall pressure fluctuations. In: *Proceedings of the 1966 Heat Transfer and Fluid Mechanics Institute*, University of Santa Clara, June, 1966. Stanford, Stanford University Press, 1966. p. 100-121.
6. Eisenberg, M., C. W. Tobias and C. R. Wilke. Ionic mass transfer and concentration polarization at rotating electrodes. *Transactions of the Electrochemical Society* 101:306-320. 1954.
7. Glasstone, S. *Introduction to electrochemistry*. New York, Van Nostrand, 1942. 557p.
8. Grassman, P. Electrochemische Messung von Stoffübergangszahlen. *Chemie Ingenieur Technik* 8:529-533. 1961.
9. Hanratty, T. J. Turbulent Exchange of Mass and Momentum with a Boundary. *Journal of the American Institute of Chemical Engineers* 7:488-497, 1961.

10. Hewitt, G. F., P. M. C. Lacey, and B. Nicholls. Transitions in Film Flow in a Vertical Tube. Harwell, Berkshire, England, 1965. 35p. (United Kingdom Atomic Energy Authority. AERE-R-4614)
11. Higbie, R. The Rate of Absorption of a Pure Gas into a Still Liquid during Short Periods of Exposure. Transactions of the American Institute of Chemical Engineers 31:365-389. 1935.
12. Kim, D. H. Momentum Transfer in Climbing Film Flow in an Annular Duct. Ph. D. thesis. Corvallis, Oregon State University, 1965. 148 numb. leaves.
13. Kim, D. H. and J. G. Knudsen. Momentum transfer in climbing film flow in an annular duct, Journal of the American Institute of Chemical Engineers, Vol
14. Knudsen, J. G. and D. L. Katz. Fluid dynamics and heat transfer. New York, McGraw-Hill, 1958. 576p.
15. Kolthoff, I. M. and E. A. Pearson. Stability of potassium ferrocyanide solutions. Industrial and Engineering Chemistry, Analytical Edition 3:381-382. 1931.
16. Lin, C. S., E. B. Denton, N. S. Gaskill and G. L. Putnam. Diffusion controlled electrode reactions. Industrial and Engineering Chemistry 43:2136-2143. 1951.
17. Mitchell, J. E. and T. J. Hanratty. A study of turbulence at a wall using an electrochemical wall shear-stress meter. Journal of Fluid Mechanics 26:199-221. 1966.
18. Norman, W. S. and V. McIntyre. Heat transfer to a liquid film on a vertical surface. Transactions of the Institution of Chemical Engineers, London 38:301-307. 1960.
19. Petrocelli, J. V. and A. A. Paolucci. Overvoltage at oxidation-reduction electrodes. Journal of the Electrochemical Society 98:291-295. 1951.
20. Reiss, L. P. and T. J. Hanratty. Measurement of instantaneous rates of mass transfer to a small sink on a wall. Journal of the American Institute of Chemical Engineers 8:245-247. 1962.
21. _____ An experimental study of the unsteady nature of the viscous sublayer. Journal of the American Institute of Chemical Engineers 9:154-160. 1963.

22. Shaw, P. V. and T. J. Hanratty. Fluctuations in the local rate of turbulent mass transfer to a pipe wall. *Journal of the American Institute of Chemical Engineers* 10:475-482. 1964.
23. Shaw, P. V., L. P. Reiss and T. J. Hanratty. Rates of turbulent transfer to a pipe wall in the mass transfer region. *Journal of the American Institute of Chemical Engineers* 9: 362-364. 1963.
24. Shearer, C. J. and R. M. Nedderman. Pressure gradient and liquid film thickness in co-current upwards flow of gas-liquid mixtures. Application to film cooler design. *Chemical Engineering Science* 20:671-683. 1965.
25. Sutey, A. M. Mass transfer at the solid-liquid interface for climbing film flow in an annular duct. Ph. D. Thesis. Oregon State University, Corvallis, Oregon. June 1967.
26. Sutey, A. M. and J. G. Knudsen. Effect of dissolved oxygen on the redox method for the measurement of mass transfer coefficients. *Industrial and Engineering Chemistry Fundamentals*, Vol. 6, Page 132, Feb. 1967.
27. Toor, H. L. and J. M. Marchello. Film-penetration for mass and Heat Transfer. *Journal of the American Institute of Chemical Engineers* 4: 97-101. 1958.
28. Willis, I. J. Upwards Annular Two-Phase Air-Water Flow in Vertical Tubes. *Chemical Engineering Science* 20: 895-902. 1965.

SECTION OF ANNULAR DUCT SHOWING CLIMBING FILM

FIGURE (1)

MASS TRANSFER AT THE SOLID-LIQUID INTERFACE

Figure (2)

TWO PHASE FLOW COLUMN

Figure (3)

ELECTRODES

Figure (4)

LIMITING CURRENT CURVES IN CLIMBING FILM FLOW

1/16-INCH RING ELECTRODE

LIQUID FLOW = 0.48 LB/MIN

VOLTAGE (VOLTS)

MASS TRANSFER COEFFICIENT VS AIR FLOW RATE

Figure (6)

MASS TRANSFER COEFFICIENT VS AIR FLOW RATE

Figure (7)

MASS TRANSFER COEFFICIENT VS LIQUID FLOW RATE

Figure (8)

FLUCTUATIONS IN THE RATE OF MASS TRANSFER AT THE SOLID-LIQUID FILM INTERFACE

Figure (9)

Figure (10) Shear Stress at the Solid-Liquid Film Interface

SHEAR STRESS AT THE SOLID-LIQUID FILM INTERFACE AT DOWNFLOW

Figure (11)

PRESSURE GRADIENT VS AIR FLOW RATE AT MINIMUM ENTRAINMENT

Figure (12)

INTERFACIAL SHEAR STRESS VS AIR FLOW RATE

Figure (13)

SHEAR STRESS DISTRIBUTION VS AIR FLOW RATE

Figure (14)

FILM THICKNESS VS AIR FLOW RATE

Figure (15)