Fiber

SP-100 PROGRAM

Technical Information Report

SP-100 Attitude Control Pathfinder Study

Fidelis O. Eke
Stephen H. Graff
Robert A. Laskin
Peter A. Swan

March 1984

National Aeronautics and
Space Administration

JPL

Jet Propulsion Laboratory
California Institute of Technology
Pasadena, California

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

SP-100 PROGRAM

Technical Information Report SP-100 Attitude Control Pathfinder Study

Fidelis O. Eke
Stephen H. Graff
Robert A. Laskin
Peter A. Swan

March 1984

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

National Aeronautics and
Space Administration

JPL

Jet Propulsion Laboratory
California Institute of Technology
Pasadena, California

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SP-100 PROGRAM

Department of Defense
Defense Advanced Research Projects Agency
Arlington, Virginia

Department of Energy
Office of Nuclear Energy
Washington, D.C

National Aeronautics and Space Administration
Office of Aeronautics and Space Technology
Washington, D.C.

Jet Propulsion Laboratory
California Institute of Technology
Pasadena, California

SP-100 ATTITUDE CONTROL PATHFINDER STUDY

F. O. Eke, S. H. Graff, R. A. Laskin, P. A. Swan

ABSTRACT

This report delineates the scope of Jet Propulsion Laboratory's FY'83 effort in the attitude control area in support of the SP-100 program. Dynamic modeling of the baseline beam configuration has been conducted and is presented herein. As a first cut, the beam is treated as rigid. Its inherent flexibility is then integrated via the hybrid coordinates method. Using the resulting dynamical equations, a preliminary look at attitude control is taken. Only one axis of rotation and one flexible mode are included. An alternative to the beam configuration is one that envisions connecting basebody to user via a long, lightweight, flexible tether. A literature search has been conducted in this area and the resulting bibliography is presented. The tether option is not considered viable near term. However, it offers several potentially significant advantages and thus deserves serious consideration for the next generation space power system.

This report also treats attitude control constraints imposed by the high temperature and radiation environment and addresses the issue of hardware requirements and availability.

Recommendations for FY'84 tasks include assembling and exercising a simulation program for the beam configuration dynamic model and conducting a technology assessment in the area of tether dynamics and control.

CONTENTS

I	Introduction	3
II	Beam Dynamics and Control	4
	A. Rigid Body Formulation	4
	1. General Configuration	4
	2. Symmetric Configuration	7
	B. Flexibility Considerations	7
	1. Model Description	7
	2. Appendage Equations	9
	3. Vehicle Equations	11
	4. Modal Truncation	12
	C. Effects of Rotating and/or Reciprocating Machinery	13
	1. Rigid Formulation	13
	2. Flexible Body Formulation	13
	D. Control System	14
	E. Findings	17
III	Tether Configuration	18
IV	Commonality	22
V	Conclusion	24
VI	References	26
VII	Bibliography	27

Figures

1.	SP-100 System	5
2.	Flexible Beam Model	8
3.	Block Diagram (Closed Loop System)	16
4.	Tether Radiation Attenuation	20

Table

1.	Control Implementation	23
----	----------------------------------	----

I. INTRODUCTION

Abundant electrical power is a vital ingredient in our progress in space. This power is needed for large communication and navigation satellites, space stations, and exploration of the solar system.

The SP-100 nuclear space power system is nominally a 100 kW_e power source for applications which require high power and long life. The preliminary set of requirements calls for continuous power delivery for a period of seven years.

SP-100 requires an attitude control development to insure proper utilization of the current and future technology. Total integration of all the system components by JPL requires a design concept for each sub-system which can be used to compare, critique, and assess contractor inputs. The SP-100 challenges and opportunities for attitude control analysis include high reliability, high radiation levels, large temperature variations, long lifetimes, unusual vibrations from rotating and reciprocating machinery, and unique user requirements.

This study assessed the technology available for the baseline in the areas of articulation and deployment and dynamics and control of beams (with beam baseline of 25 meters), attitude control constraints, and finally the hardware commonality. An additional look at the concept of tethers, as a potential technology for the future, enables the program office to better assess the proposals of the contractors. The final conclusions and recommendations fill out the study with ideas and rationale for the future program office efforts.

II. BEAM DYNAMICS AND CONTROL

The SP-100 system may be visualized, as shown in Fig. 1, as two bodies B_1 and B_2 connected by a flexible truss B_3 , and in orbit around the earth. B_1 is the power generating unit and may or may not be more massive than B_2 . Depending on the precise type of power generation system adopted, B_1 may carry rotating or reciprocating machinery as well as working fluids.

The aim of the study reported here is to develop an acceptable mathematical model for the SP-100 system and to identify potential problems related to the attitude dynamics and control of the system.

II.A. Rigid Body Formulation

II.A.1 General Configuration

As a first step in the modeling of the SP-100, the system will be assumed to comprise two rigid bodies B_1 and B_2 connected by a rigid rod B_3 , as shown in Fig. 1. m_i and I_i represent respectively the mass of body B_i , and the inertia dyadic of body B_i for its center of mass C_i .

The angular momentum of the system may be written as

$$\underline{H} = (\underline{I}_1 + \underline{I}_2 + \underline{I}_3) \cdot \underline{\omega} + \sum m_i \underline{r}_i \times (\underline{\omega} \times \underline{r}_i) \quad (1)$$

where $\underline{\omega}$ is the angular velocity of any of the bodies, and $\underline{r}_i$ is the position vector of C_i with respect to the center of mass C of the whole system. If one lets

$$\underline{I} = \underline{I}_1 + \underline{I}_2 + \underline{I}_3 \quad (2)$$

then

$$\underline{H} = \underline{I} \cdot \underline{\omega} + \sum m_i \underline{r}_i \times (\underline{\omega} \times \underline{r}_i) \quad (3)$$

and

$$\dot{\underline{H}} = \underline{I} \cdot \dot{\underline{\omega}} + \underline{\omega} \times \underline{I} \cdot \underline{\omega} + \sum \{m_i \underline{r}_i \times (\dot{\underline{\omega}} \times \underline{r}_i) + m_i \underline{r}_i \times [\underline{\omega} \times (\underline{\omega} \times \underline{r}_i)]\} \quad (4)$$

or

$$\dot{\underline{H}} = \underline{I} \cdot \dot{\underline{\omega}} + \underline{\omega} \times \underline{I} \cdot \underline{\omega} + \sum m_i \{-\underline{r}_i \times (\underline{r}_i \times \dot{\underline{\omega}}) - \underline{\omega} \times [\underline{r}_i \times (\underline{r}_i \times \underline{\omega})]\} \quad (5)$$

If matrix formulation is desired, the unit vectors $\underline{e}_1, \underline{e}_2, \underline{e}_3$, are written as a vector array

FIGURE 1: SP-100 System

$$\{e\} = \begin{bmatrix} e_x \\ e_y \\ e_z \end{bmatrix} \quad (6)$$

and matrices $\dot{H}$, ω , r_i , and I_i are defined as follows:

$$\underline{H} = \{e_x \ e_y \ e_z\} \begin{bmatrix} H_x \\ H_y \\ H_z \end{bmatrix} = \{e\}^T \dot{H} \quad (7)$$

$$\underline{\omega} = \{e_x \ e_y \ e_z\} \begin{bmatrix} \omega_x \\ \omega_y \\ \omega_z \end{bmatrix} = \{e\}^T \omega \quad (8)$$

$$\underline{r}_i = \{e_x \ e_y \ e_z\} \begin{bmatrix} r_{ix} \\ r_{iy} \\ r_{iz} \end{bmatrix} = \{e\}^T r_i \quad (9)$$

and

$$I_i = \begin{bmatrix} I_{ix} & I_{ixy} & I_{ixz} \\ I_{ixy} & I_{iy} & I_{iyz} \\ I_{ixz} & I_{iyz} & I_{zz} \end{bmatrix} \quad (10)$$

The matrix equivalent of equation (5) then becomes

$$\dot{H} = I\dot{\omega} + \tilde{\omega}I\omega + \sum m_i (-\tilde{r}_i\tilde{r}_i\omega - \tilde{\omega}\tilde{r}_i\tilde{r}_i\omega) \quad (11)$$

where the tilde ($\sim$) sign implies the cross operator; for example

$$\tilde{\omega} = \begin{bmatrix} 0 & -\omega_z & \omega_y \\ \omega_z & 0 & -\omega_x \\ -\omega_y & \omega_x & 0 \end{bmatrix}$$

Defining

$$I'_i = I_i - m_i \tilde{r}_i \tilde{r}_i \quad (12)$$

and

$$I' = I'_1 + I'_2 + I'_3 \quad (13)$$

Eq. (11) could be written in the more compact and familiar form

$$\underline{H} = I'\omega + \tilde{\omega}I'\omega = M \quad (14)$$

where M is a column vector whose elements are the components of the moment about the system mass center C of the resultant force on the system. Equation (14), supplemented with appropriate kinematical equations and control equations, may be used for the simulation of the motion of the

system.

II.A.2 Symmetric Configuration

Real engineering systems of this type usually possess some amount of symmetry. In the specific case of SP-100, it is not unreasonable to assume, for example, that the axis of the rod B_3 passes through all mass centers, and that lines parallel to e_1 , e_2 , and e_3 are centroidal principal axes for each of the bodies. The equations of motion in this case still have the form of equation (14), however, the expression for I' is much simpler. For three axis stabilized systems, like the SP-100, it is customary and reasonable to further assume that ω is small so that the $\mathcal{O}(I'\omega)$ term in equation (14) drops out, leading to the simple decoupled equations

$$\begin{aligned}\dot{\omega}_x &= M_x/I_x \\ \dot{\omega}_y &= M_y/I_y \\ \dot{\omega}_z &= M_z/I_z\end{aligned}\tag{15}$$

II.B Flexibility Considerations

II.B.1 Model Description

Once the rigidity assumption of the previous section is discarded, one immediately runs into the difficulty of modeling a system which now includes a flexible beam between two rigid bodies. Several approaches to the analysis of flexible vehicles are treated in references [2] through [5]. When the ultimate aim is to arrive at equations of motion for computer simulation, the dynamical equations must be amenable to a form (through appropriate coordinate transformation) that facilitates coordinate truncation so that system deformation may be represented by a finite number of "modal" coordinates.

The approach adopted in this study is the hybrid coordinate method of Likins [2]. This method is most useful when portions of an otherwise rigid vehicle undergo deformations that may be reasonably assumed to remain "small." For an efficient use of the above method, the SP-100 is modeled, as shown in Fig. 2, as a rigid body B_1 with a linearly elastic flexible appendage A. B_1 is taken to be the more massive of the two end masses of the real system, and the other end mass together with the flexible beam

FIGURE 2: Flexible Beam Model

constitute the appendage A. Should B_2 be the larger mass, then it would be regarded as rigid and the remainder of the system considered as a flexible appendage. The next step is the derivation of equations of motion for the system just described, and this will be done by deriving the equations of motion for each appendage and then supplementing these with the equations of motion of the whole system viewed as a unit.

II.B.2 Appendage Equations

Consider the system in some general configuration depicted in Fig. 2. The appendage A undergoes "small" deformations relative to the base B_1 , while the motion of B_1 is arbitrary. A is now idealized as a collection of n elastically interconnected discrete rigid sub-bodies, A_s being one such sub-body. Damping is ignored at this point; it will be incorporated in the model at a later stage with the introduction of modal coordinates. The dotted lines in Fig. 2 show the position of A before deformation; point 0 is fixed in inertial space, S^* is the system mass center, and $0'$ is the location of S^* when the system was undeformed, and is therefore fixed in B_1 .

For the sub-body A_s ,

$$\underline{F}_s = m_s \ddot{\underline{p}}_s \quad (16)$$

where $\underline{F}_s$ is the resultant force on A_s , m_s is its mass, and $\underline{p}_s$ is the position vector of the center of mass of A_s relative to 0. On the other hand, it is clear from the figure that

$$\underline{p}_s = \underline{X} + \underline{C} + \underline{R} + \underline{r}_s + \underline{u}_s \quad (17)$$

where

$\underline{X}$ is the vector from 0 to S^*

$\underline{C}$ is the position vector of $0'$ relative to S^*

$\underline{R}$ is the vector from $0'$ to a point Q fixed in B_1

$\underline{r}_s$ vector goes from Q to the location of the mass center of A_s in the undeformed configuration, and

$\underline{u}_s$ is the position vector of the mass center of A_s relative to its location in the undeformed configuration.

Hence

$$\underline{F}_s = m_s (\ddot{\underline{X}} + \ddot{\underline{C}} + \ddot{\underline{R}} + \ddot{\underline{r}}_s + \ddot{\underline{u}}_s) \quad (18)$$

Column matrices $\underline{X}$, $\underline{C}$, $\underline{R}$, $\underline{r}_s$, and $\underline{u}_s$ are now defined as follows

$$\underline{X} = \{\underline{i}_1 \ \underline{i}_2 \ \underline{i}_3\} \begin{bmatrix} X_1 \\ X_2 \\ X_3 \end{bmatrix} = \{\underline{i}\}^T \underline{X} \quad (19)$$

$$\underline{C} = \{\underline{b}_1 \ \underline{b}_2 \ \underline{b}_3\} \begin{bmatrix} C_1 \\ C_2 \\ C_3 \end{bmatrix} = \{\underline{b}\}^T \underline{C} \quad (20)$$

$$\underline{R} = \{\underline{b}_1 \ \underline{b}_2 \ \underline{b}_3\} \begin{bmatrix} R_1 \\ R_2 \\ R_3 \end{bmatrix} = \{\underline{b}\}^T \underline{R} \quad (21)$$

$$\underline{r}_s = \{\underline{b}_1 \ \underline{b}_2 \ \underline{b}_3\} \begin{bmatrix} r_{s1} \\ r_{s2} \\ r_{s3} \end{bmatrix} = \{\underline{b}\}^T \underline{r}_s \quad (22)$$

$$\underline{u}_s = \{\underline{b}_1 \ \underline{b}_2 \ \underline{b}_3\} \begin{bmatrix} u_{s1} \\ u_{s2} \\ u_{s3} \end{bmatrix} = \{\underline{b}\}^T \underline{u}_s \quad (23)$$

It then becomes possible to write Eq. 18 in matrix form as

$$\begin{aligned} F_s = m_s [\oplus \ddot{\underline{X}} + \ddot{\underline{C}} + 2\tilde{\omega} \dot{\underline{C}} + \tilde{\omega} \tilde{\omega} (\underline{C} + \underline{R}) - (\tilde{\underline{C}} + \tilde{\underline{R}}) \dot{\omega} - (\underline{r}_s + \underline{u}_s) \dot{\omega} + \tilde{\omega} \tilde{\omega} (\underline{r}_s + \underline{u}_s) \\ + 2\tilde{\omega} \underline{u}_s + \ddot{\underline{u}}_s] \end{aligned} \quad (24)$$

where $\oplus$ is the transformation matrix between the $\underline{i}$ and $\underline{b}$ bases given by

$$\{\underline{i}\}^T = \{\underline{b}\}^T \oplus \quad (25)$$

The matrix $\underline{C}$ represents the motion of the system mass center in B_1 , and may be shown to be given by

$$\underline{C} = - \sum \mu_s \underline{u}_s \quad (27)$$

$$\text{where } \mu_s = m_s / (\sum m_s) \quad (28)$$

Equation (27) and its time derivatives may be substituted into equation (24) to give

$$\begin{aligned} F_s = m_s [\oplus \ddot{\underline{X}} + \ddot{\underline{u}}_s - \sum \mu_k \ddot{\underline{u}}_k + 2\tilde{\omega} (\underline{u}_s - \sum \mu_k \underline{u}_k) - (\tilde{\underline{R}} + \tilde{\underline{r}}_s) \dot{\omega} + \tilde{\omega} (\underline{u}_s - \sum \mu_k \underline{u}_k) \\ + \tilde{\omega} \tilde{\omega} (\underline{R} + \underline{r}_s + \underline{u}_s - \sum \mu_k \underline{u}_k)] \end{aligned} \quad (29)$$

The equations of rotational motion of A_s are obtained by equating the resultant external torque on A_s to the time rate of change of its inertial angular momentum. Since the rotation of A_s relative to B_1 is due only to "small" structural deformations, this rotation can be represented by the vector

$$\underline{\beta}_s = \beta_{s1} \underline{b}_1 + \beta_{s2} \underline{b}_2 + \beta_{s3} \underline{b}_3 \quad (30)$$

where $\beta_{s1}, \beta_{s2}, \beta_{s3}$ are three angles of rotation about the orthogonal axes b_1, b_2, b_3 . Hence, the angular velocity matrix ω_s of A_s takes the form

$$\omega_s = \omega + \{b\}^T \dot{\beta}_s \quad (31)$$

Finally, the equations of attitude motion of A_s can be put in the form

$$T_s = I_s(\dot{\omega} + \ddot{\beta}_s) + [I_s\tilde{\omega} + \tilde{\omega}I_s - (\widetilde{I_s\omega})]\dot{\beta}_s + \tilde{\omega}I_s\omega + [I_s\tilde{\omega} - (\widetilde{I_s\dot{\omega}}) - \tilde{\omega}(\widetilde{I_s\omega}) + \tilde{\omega}I_s\tilde{\omega}]\beta_s \quad (32)$$

where

T_s is the resultant torque matrix

and I_s is the centroidal inertia matrix of A_s .

For a three-axis stabilized system, equations (29) and (32) may be linearized in ω , they then reduce respectively to

$$m_s(\ddot{u}_s - \sum \mu_k \ddot{u}_k) = -m_s \oplus \ddot{X} + (\tilde{R} + \tilde{T}_s)\dot{\omega} + F_s \quad (33)$$

and

$$I_s \ddot{\beta}_s = -I_s \dot{\omega} + T_s \quad (34)$$

II.B.3 Vehicle Equations

Equations (33) and (34) are not sufficient for the complete description of the motions of our system. They will now be supplemented with the dynamical equations of the whole vehicle.

The vehicle translational equation is

$$F = m \underline{a}^{s*} \quad (35)$$

where F is the resultant external force on the whole vehicle, m is the total mass, and $\underline{a}^{s*}$ is the acceleration of the system mass center. The matrix form of equation (35) is

$$F = m \oplus \ddot{X} \quad (36)$$

and the rotational equations for small ω can be written in the compact form

$$T = I^* \dot{\omega} + R \sum m_s \ddot{u}_s + \sum \tilde{r}_s m_s \ddot{u}_s + \sum I_s \ddot{\beta}_s \quad (37)$$

where I^* is the inertia matrix of the undeformed vehicle for the point O' of Figure 3. A comparison of Equations (15) and (37) indicates that the effects of beam flexibility are contained in the last three terms on the right hand side of Equation (37). Equations (33), (34), (36), and (37) form a set of $6n+6$ scalar equations with $X, \oplus, \omega, u_s$ and β_s ($6n+9$ in number) as unknowns. And together with a set of kinematical equations relating $\oplus$ and ω , and control equations, they are sufficient for the simulation of the motions of the system.

II.B.4 Modal Truncation

The difficulty with the equations mentioned above is simply their dimension due mainly to the appendage equations whose number is directly proportional to n . The objective in this subsection is to attempt a reduction of the dimension of the equations of motion through some type of coordinate truncation. This naturally involves the introduction of a linear transformation for at least some of the variables, and this transformation must give rise to decoupled equations so as to permit valid truncation. Here, such a transformation is applied to the appendage deformation coordinates only. First, the appendage deformation coordinates are organized into a coordinate matrix q defined as

$$q = [u_1^1 \ u_2^1 \ u_3^1 \ \beta_1^1 \ \beta_2^1 \ \beta_3^1 \ u_1^2 \ u_2^2 \ u_3^2 \ \beta_1^2 \ \beta_2^2 \ \beta_3^2 \ \dots \ \beta_3^N]^T \quad (38)$$

Because the appendage equations (33) and (34) are linearized in the deformation coordinates u_s and β_s , these equations can be written in matrix form as

$$M'\ddot{q} + D'\dot{q} + K'q = L' \quad (39)$$

By inspection of equations (33) and (34), it becomes evident that M' is a constant symmetric matrix. F_s and T_s in equations (33) and (34) include structural interaction forces and torques between neighboring sub-bodies of A. These interactions may be visualized as linearly elastic and viscous forces and torques that are proportional to the deformation and deformation rates. Hence D' and K' are also constant matrices; all the damping coefficients go into D' and all the stiffnesses go into K' . L' depends on $\ddot{\Theta}$, $\ddot{X}$, and the external applied forces and torques that may appear in F_s and T_s .

Classical modal analysis techniques can be applied to our system by first ignoring damping and considering

$$M'\ddot{q} + K'q = L' \quad (40)$$

This leads to the choice of the normal-mode transformation

$$q = \phi\eta \quad (41)$$

which in turn transforms equation (39) into

$$\ddot{\eta} + 2\zeta\sigma\dot{\eta} + \sigma^2\eta = \phi^T L' \quad (42)$$

where η is the column matrix of modal coordinates, σ and ζ are diagonal matrices of natural frequencies and damping ratio, and ϕ is the modal matrix.

Equations (42) are now decoupled and may be truncated to a convenient size. If $\bar{\eta}$ is the truncated form of η , the appendage equations now take the form

$$\ddot{\bar{\eta}} + 2\dot{\zeta}\dot{\bar{\eta}} + \sigma^2\bar{\eta} = \phi^T L' \quad (43)$$

Depending on the number of "modes" retained, this truncated form of the appendage equations, together with the vehicle equations could constitute a much smaller set of dynamical equations, and therefore much cheaper to integrate on a computer.

II.C Effects of Rotating and/or Reciprocating Machinery

II.C.1 Rigid Formulation

The addition of a rotating element to one of the main bodies of the system introduces a slight change in the equations of attitude motion. For example, let us examine the case of Fig. 1 where the connecting rod between B_1 and B_2 is assumed to be rigid, and body B_1 contains a rotor. If this added rotor is axisymmetric, then B_1 is a gyrostat and the system angular momentum is augmented by a term h which represents the angular momentum of the rotor relative to the basebody B_1 . Equation (15) then has the matrix form

$$T = I\dot{\omega} + \dot{h} - \hat{h}\omega \quad (44)$$

which now includes a "gyroscopic stiffness" term. Hence, the motion of an axisymmetric rotor in B_1 does affect vehicle motion. The importance of this effect depends on the inertia of the rotor, and its spin rate relative to the basebody B_1 . If the rotor mass center is offset from the spin axis, the system's dynamics is further complicated by the appearance of new terms involving this offset.

II.C.2 Flexible Body Formulation

In the case of a flexible beam, the presence of a rotor on body B_1 can affect both the appendage equations and the vehicle equations. The appendage equations can only be affected through the column vector C (see Eq. (24)) which represents the motion of the system mass center in body B_1 . If the rotor is axisymmetric, then the location of the system mass center is not modified by the motion of the rotor, and hence, the appendage equations remain unchanged. This means that the procedure and results of the

coordinate matrix truncation are unaffected by the motion of a symmetric rotor in B_1 . However, the vehicle equations change slightly because the expression for the angular momentum of the system is modified by the presence of the rotor. The vehicle equation of rotational motion becomes

$$T = I^* \dot{\omega} + \dot{h} - \tilde{h}\omega + \tilde{R} \sum m_s \ddot{u}_s + \sum I_s \ddot{\beta}_s + \sum \tilde{r}_s m_s \ddot{u}_s \quad (45)$$

The first term on the right hand side of Eq. (45) is the rigid body term. It is the only term that would remain if the whole system were one rigid body. The second and third terms are due to the presence of the rotor, and the last three terms are contributions from the system's flexibility.

If the rotor mass center is not located on the spin axis, the rotor's motion will affect the location of the system mass center. That is, the appendage equations will be impacted through the C matrix, and the modal analysis technique used above breaks down because D' and K' are no longer constant matrices.

II.D Control System

Since our system is three-axis stabilized, the elements of the matrix ω are small, and we can let

$$\omega = \dot{\theta} \quad (46)$$

$$\text{where } \theta = [\theta_1 \ \theta_2 \ \theta_3]^T \quad (47)$$

and $\theta_1, \theta_2, \theta_3$ are vehicle rotation angles. If our interest, from controls point of view, is limited to θ , it will be necessary to display clearly the relationship between the control torque T and the rotation angle θ . As a simple example, we consider the case of negligible external force and torque on the appendage. System equations may then be reduced to

$$T = I^* \ddot{\theta} - \delta T \ddot{\eta} \quad (48)$$

$$\text{and } \ddot{\eta} + 2\zeta\sigma\dot{\eta} + \alpha^2\eta = \delta\ddot{\theta} \quad (49)$$

The Laplace transform of these equations yields

$$T(s) = s^2 I^* \theta(s) - \delta T s^2 \eta(s) \quad (50)$$

$$\text{and } s^2 \eta(s) + 2s\zeta\sigma\eta(s) + \sigma^2 \eta(s) = s^2 \delta \theta(s) \quad (51)$$

Equations (50) and (51) can be combined to give

$$\theta(s) = [sI^* - s^4 \delta T D \delta]^{-1} T(s) \quad (52)$$

where D is a diagonal matrix given by

$$D = \begin{bmatrix} \frac{1}{s^2+2\zeta_1\sigma_1s+\sigma_1^2} & 0 \\ 0 & \frac{1}{s^2+2\zeta_2\sigma_2s+\sigma_2^2} \\ 0 & \frac{1}{s^2+2\zeta_N\sigma_Ns+\sigma_N^2} \end{bmatrix} \quad (53)$$

In the special case when the coordinate truncation is carried down to a single modal coordinate, Eq. (52) becomes

$$\Theta(s) = \frac{1}{s^2} [I^* - s^2 \delta_1 T \delta_1] \left(\frac{1}{s^2+2\zeta_1\sigma_1s+\sigma_1^2} \right)^{-1} T(s) \quad (54)$$

A block diagram representation of this control system is shown in Fig. 3. If it is further assumed that dynamic response in this single mode representation influences vehicle response about one axis only, and that the inertia matrix I^* is diagonal, then the dynamics block of Fig. 3 can be expressed as

$$G(s) = \left[I_a^* s^2 - \frac{s^4 (\delta_a^1)^2}{(s^2+2\zeta_1\sigma_1s+\sigma_1^2)} \right]^{-1} \quad (55)$$

where a is the single axis considered. This expression can eventually be put in the form

$$G(s) = \frac{s^2+2\zeta_1\sigma_1s+\sigma_1^2}{I_a^* s^2 (s^2 E + 2\zeta_1\sigma_1s+\sigma_1^2)} \quad (56)$$

$$\text{where } E = 1 - \frac{(\delta_a^1)^2}{I_a^*} \quad (57)$$

In the case of simple gain control,

$$H(s) = K \text{ (constant)} \quad (58)$$

and the characteristic equation becomes

$$s^4 (I_a^* E) + s^3 (2I_a^* \zeta_1 \sigma_1) + s^2 (I_a^* \sigma_1^2 + K) + s (2K \zeta_1 \sigma_1) + K \sigma_1^2 = 0$$

An examination of the Routhian array for this system indicates asymptotic stability for positive K .

FIGURE 3: Block Diagram

II.E Findings

The formulation of equations of motion for the SP-100 system could be described as complete. If the connecting structure of the system is assumed to be rigid, the equations of motion are very simple and decoupled. When the flexibility of the structure is taken into account, the system is modeled as a main rigid body with an attached flexible appendage, the other rigid body being assimilated into the appendage. Furthermore, the appendage is modeled as a system of elastically interconnected rigid sub-bodies. The complete dynamical equations of the system are then composed of the appendage equations together with the complete vehicle equations. Truncation of these equations is achieved through modal analysis of the appendage equations. These reduced dynamical equations can then be completed with kinematical and control equations for the purposes of vehicle motion simulation.

When the basebody contains a perfectly axisymmetric rotating or reciprocating sub-body, the effects of the motion of such a rotor are easily accommodated in the analyses presented because they are decoupled from flexibility effects.

A preliminary analysis of the control system using the extreme example of single axis response of an appendage represented by a single modal coordinate, with simple gain control, reveals asymptotic stability in every case.

III. TETHER CONFIGURATION

The SP-100 program has two major areas for potential benefit and two areas of smaller potential for future utilization of tether technology. The major aspects of tether technology that apply to SP-100 are 1) radiation attenuation and 2) disturbance isolation. The two ancillary aspects of the tether technology are 1) the ability to provide gravitational fields and 2) the adjustment capability for attitude control without the use of propellants. These benefits will be discussed further. The concept of tethers and their applications in space have recently identified potential applications to both Earth and interplanetary missions. Notably, tethers can provide unique techniques for scientific measurements. By using a constellation of tethered satellites, simultaneous sampling and multiple measurements of electromagnetic and atmospheric characteristics at stereographic observations, sample retrieval of low altitude atmospheric gases of a planet, such as Jupiter, or a fly-by comet can be easily accomplished across multiple locations. Tethers also provide the option of using less fuel for maneuvers such as spacecraft insertion, orbit adjust, and science probe injection towards planets.

Extensive work has been done in the dynamics and control of space vehicles; however, the addition of long (in excess of 80 km) tethers creates new and unusual aspects to the calculations. The initial efforts by NASA in the early days of Gemini studied the dynamics and control of short tethers (order of 100 m) to provide gravity gradient stabilization and spin induced gravity. These activities were accomplished both in orbit and in simulations. Recent efforts have surfaced with emphasis on the uses of long tethers mainly due to the better understanding of the dynamics pioneered by Professor Colombo of the Smithsonian Astrophysical Observatory. These efforts have initiated interest in many universities and laboratories to better understand the simulations. The recent emphasis has centered around the new missions that have become better understood since the new dynamical modeling has been discussed in the literature.

Currently, NASA is pushing the concepts of tethers that relate to the Earth resources or Earth oriented activities. The new ideas of gravity gradient induced gravitational forces for manned activities (about .1 g's), of "free" altitude additions from "spare" masses provided to the shuttle orbits, and of scientific measurements in the upper atmosphere from medium orbits of the orbiters have created much interest in the earth resources and space sciences community.

Two joint U.S.-Italian missions scheduled for 1987 and 1988 will demonstrate the feasibility and benefits of tethered satellite systems deployed from the shuttle orbiter. The tether will be a flexible metallic or synthetic line, 1-2 mm in diameter and 100 Km or more in length, carrying a total payload mass of 500 Kg. Because of the differences in environmental parameters at the outer planets, (such as gravity and aerodrag) the requirements and characteristics of tethers will vary from the above Earth oriented missions. Furthermore, current work on tether dynamics and controls are relatively immature. It is timely now to verify the tether concept for applications to future planetary, earth resources, and military missions.

Several representatives of the SP-100 project attended the NASA sponsored Tether Workshop in Williamsburg, Virginia in June 1983. Their participation in the Tethers Workshop resulted in a better understanding of the current technology and programmatic paths. The emphasis was related to Earth oriented activities and rarely investigated the possibilities of interplanetary activities. A major conclusion from this Tether Workshop was that the modeling of the dynamics and control of orbiting tethers must be investigated thoroughly. The current models vary in assumptions, in structure, and sometimes in conclusions.

The support of SP-100 conducted a basic reference research effort with the compiling of many articles and books pertaining to tether systems (see attached bibliography). The initial assessment of the dynamics and control of tether satellite systems has shown that there are four potential benefits.

- (a) Radiation Attenuation: Figure 4 shows a generic case of a nuclear power system with the length of the tether varying from 25 meters (baseline) to 500 meters. This increase in distance (r) decreases the amount of

z (M)	(DEG)*	SHIELD RADIUS (M)	SHIELD ₂ AREA (M ²)
25	84.2	10	314
50	78.7	5	78.5
75	73.3	3.3	34.9
100	68.2	2.5	19.6
250	45	1.0	3.14
500	26.6	.5	.79

SHIELD AREA $\propto$ MASS

* θ 's FOR 500 METER DIAMETER "SAFE" ZONE

FIGURE 4: Tether Radiation Attenuation

- shield area to protect a satellite safety zone by a rate of $1/r^2$. A tether on the order of 10 km might render shielding totally unnecessary.
- (b) **Vibration Isolation:** A tether system will provide the ability to attenuate vibrations through the use of a tether with no (very small) transmission of shear forces. This provides a protection from vibration that must be studied to quantify the effect.
 - (c) **Gravity Field:** The stable tether system will rotate once during each orbit. This slow rotation and long tether length (moment arm) will provide a small amount of artificial gravity through centrifigual force. This could have significant safety implications for the reactor.
 - (d) **Attitude Adjustment:** By placing the center of mass around the attachment point, fine adjustments can be achieved of the attitude of the satellite. This can be accomplished with electromechanical devices instead of costly propellant usage.

IV. COMMONALITY

Several attitude control constraints and hardware uses are common to the two configurations. The SP-100 attitude control subsystem has both temperature and radiation constraints. The radiation limit for the Galileo project which is 5×10^9 protons/cm² and 1×10^6 neutrons/cm² with design margin of 2, was selected for the electronics. Off-the-shelf electromechanical devices such as resolvers reaction wheels, gyros and motors have a limit of 250 to 500 krads due to lubrication and insulation breakdown. These electromotive devices can be designed for even higher radiation levels. Presently, sun sensors can tolerate up to 150 krads, however, star sensors are not radiation hardened and therefore present a problem. Earth sensors radiation hardened to greater than 500 krad are currently available.

When the reactor is operational the radiator temperature may be as high as 900° K. When the reactor is shut down, the electronics will need heaters. The electronics temperature range which has been selected for now is the same as for the Galileo Project which is from 273° to 328° K with qualification limits at 253° to 348°K.

The extreme temperature range leads to consideration of heaters and insulation for the propulsion system. The Jet Propulsion Laboratory's limits for Hydrazine with Shell 405 catalyst are from 275° K to 322° K, although an upper limit 340°K is possible. This yields an Isp of 233 seconds at 300 psia for an expansion ratio of 50. To prevent propellant line freezing, line heaters are required. Viking and Galileo Projects selected dinitrogen tetroxide (NTO) and monomethyl hydrazine (MMH) which has a temperature range from 221° K to 361° K with an Isp of 349 seconds at 140 psia for an expansion ratio of 40. Unfortunately, unburned NTO and MMH leaves solid particle residue. Chlorine pentafluoride (CPF) and MMH has a temperature range from 221° K to 338° K with an Isp of 363 seconds at 150 psia for an expansion ratio of 40. For a lower freezing point with Mixed Hydrazine Fuel 3 (MHF-3) which has a range from 208° K to 338° K and an Isp of 342.1 seconds at 150 psia and an expansion ratio of 40. CPF has a higher Isp, higher density, lower freezing point (170° K), higher combustion efficiency and lower plume contamination than Hydrazine or NTO and MMH. The CPF technology is widely available and it

has been burned in test bed engines at the Air Force Rocket Propulsion Laboratory, Rocketdyne, Aerojet General, Thiokol Reaction Motors, TRW, and the Jet Propulsion Laboratory. While CPF is corrosive, it has been stored for up to ten years safely. Therefore CPF with MMH or MHF-3 has been recommended for SP-100.

The potential of propellant line freezing combined with the propellant line deployment has led to the decision that each subsatellite, whether deployed by a beam or tether, should have its own set of propellant tanks and lines with one attitude control system for the thrusters.

To reduce the high temperature and high radiation impacts on the user's subsystem the user will be remote from the reactors. This led to the beam and tether configurations, both of which require various sensors and actuators to handle the attitude control considerations.

Since large amounts of electrical power are available, attitude control should emphasize reaction wheels, control moment gyros, magnetic torquers, rather than thrusters as primary devices. Table 1 shows the possible primary effectors and sensors for various mission orbits and trajectories. Magnetic torquers and gravity gradient are viable contenders for the primary system only in low planetary orbits. The exact choice of effectors and sensors depends on mission requirements and further investigation of the SP-100 design.

TABLE 1: Control Implementation

	HIGHLY			
	LOW ORBIT	HIGH ORBIT	ELLIPTICAL ORBIT	INTERPLANETARY
THRUSTERS	X	X	X	X
GRAVITY GRADIENT	X			
MAGNETIC TORQUERS	X			
CONTROL MOMENT GYRO	X	X	X	X
REACTION WHEEL	X	X	X	X
MOMENTUM WHEEL	X	X	X	X
SUN SENSOR	X	X	X	X
STAR SENSOR	X	X	X	X
EARTH SENSOR	X	X	X	X

V. CONCLUSION

The deployable beam configuration uses an off-the-shelf item with a 20:1 expansion ratio. Thus a 24 meter beam uses slightly more than one meter of shuttle cargo bay length. The dynamics are well understood, although the power and AACS cable deployment with the beam is a concern. This is a good conservative approach for today.

Tethers offer a low radiation user environment and vibration isolation. There are many advantages for applications of tethers which are harder to achieve with the beam configuration: radiation isolation, artificial gravity, and vibration isolation are three. While tether materials and fabrication needs further study, this is a good approach for future space power applications. Tethers should not be proposed as the baseline system at the present time; however, the study effort should continue to insure that the benefits could be incorporated if they fulfill their potential.

The attitude control pathfinder study is a good start, but without adequate mission requirements or tools, the design options cannot be fully assessed. Therefore, the following is recommended:

In the beam dynamics area, the dynamics model should be put into a computer simulation. Further, modeling and subsequent incorporation into the simulation program is required to quantify:

1. the effects of fluid motion in the basebody on the dynamic behavior of the system;
2. the effects of rotating or reciprocating machinery in the base body, particularly when the rotating body is non-axisymmetric. This may lead to a strong coupling between the motion of the rotor and appendage deformations.

The controls work presented in this report is very preliminary in the sense that the final results were restricted to a single mode representation and a single axis control. A generalization to several modes and three axes control is needed. Furthermore, a decision on the exact location of sensors and effectors in the light of the existing constraints still has to be made; and this will have an impact on the final form of the control equations.

In the tether area, using the extensive bibliography, tether dynamics and controls should be investigated further at JPL with an eye toward application to the next generation SP-100.

VI. REFERENCES

1. SP-100 Functional Requirements - Nuclear Space Power Systems, SP-100-1, 19 January 1982.
2. Likins, P. W., "Dynamics and Control of Flexible Space Vehicles," JPL Technical Report 32-1329, 15 January 1970.
3. Likins, P. W., and Fleischer, G. E., "Results of Flexible Spacecraft Attitude Control Studies Utilizing Hybrid Coordinates," AIAA Journal of Spacecraft, Vol. 8, No. 3, 1971.
4. Williams, C.J.H., "Dynamics Modeling and Formulation Techniques for Non-Rigid Spacecraft," Proceedings of a Symposium on Dynamics and Control of Non-Rigid Spacecraft, Frascati, Italy, 24-26 May 1976.
5. Kane, T. R., Likins, P. W., and Levinson, D. A., Spacecraft Dynamics, McGraw Hill Book Company, 1983.
6. Bekey, Ivan, "Tethers Open New Space Options," NASA Office of Space Flight Report, 1983, also in Astronautics and Aeronautics, April 1983, pp 32-40.
7. Graff, S., "TASP Environmental Limits on Attitude Control," JPL IOM 343-83-183, 4 March 1983.

VII. BIBLIOGRAPHY

- ALL-1 Allias, E. and S. Bergamaschi, "Dynamics of Tethered Satellites Two Alternative Concepts for Retrieval", MECCANICA, June 1979, p. 103-111.
- ALL-2 Allias, E. and C. Tomadini, "Position and Attitude Control of a Satellite Tethered to the Shuttle," 18th International Scientific Conference on Space, Rome, Italy, March 15-16, 1978.
- AND-1 Anderson, W.W., ON LATERAL CABLE OSCILLATIONS OF CABLE-CONNECTED SPACE STATIONS. NASA TN 5107, Langley Research Center.
- BAI-1 Bainum, P.M. and V.K. Kumar, "Optimal Control of the Shuttle-Tethered System", ACTA ASTRONAUTICA, Vol. 7, May 80, p. 1333-1348. (also presented at the 30th Congress of International Federation, Munich, Germany. #IAF-79-190 Sept 16-22, 1979).
- BAI-2 Bainum, Peter M., R.E. Harkness and Willem Stuiver, "Attitude Stability and Damping of a Tethered Orbiting Interferometer Satellite System", JOURNAL OF ASTRONAUTICAL SCIENCES, Vol. XIX, No. 5, p. 364-389, Mar-Apr. 1972.
- BAI-3 Bainum, P.M., and K.S. Evans, "Three Dimensional Motion and Stability of Two Rotating Cable-Connected Bodies," JOURNAL OF SPACECRAFT AND ROCKETS, 12 (1975), 242-250.
- BAI-4 Bainum, P.M., A.S.S.R. Reddy and R. Krishna, "On the Controllability and Control Law Design for an Orbiting Large Flexible Antenna System," 34th Congress of the International Astronautical Federation at Budapest Hungary, Oct 10-15, 1983.
- BAK-1 Baker, W., J.A. Dunkin, Z.J. Galaboff, K.D. Johnson, R.R. Kissel, M.H. Rheinfurth and M.P.L. Siebel, TETHERED SUBSATELLITE STUDY, NASA TM X-73314, Marshall Space Flight Center, March 1976.
- BAN-1 Banerjee, A.K. and T.R. Kane, "Tethered Satellite Retrieval with Thruster Augmented Control", AIAA/AAS ASTRODYNAMICS CONFERENCE, San Diego Calif, 1982. #AIAA 82-1-21.
- BAN-2 Banerjee, Arun K. and Thomas R. Kane, "Tether Deployment Dynamics", JOURNAL OF ASTRONAUTICAL SCIENCES, Vol. XXX, No. 4, pp. 347-365, Oct-Dec 1982.
- BAR-1 Barkin, A., "Calculation of Characteristic Exponents of Poincare Periodic Solutions, and the Stability of Rotational Motions of Celestial Bodies by Cassini's Laws," PIS'MA V ASTRONOMICHESKII

ZHURNAL, Vol. 5, Feb. 1979. p. 100-105.

BAR-2 Barkin, A., "On Cassini's Laws -- Satellite Rotation,"
ASTRONOMICHESKII ZHURNAL, Vol. 55, No. 1, 1978, p. 113-122.

BEK-1 Bekey, Ivan, TETHERS OPEN NEW SPACE OPTIONS, NASA Office
of Space-Flight Report, April 1983.

BEL-1 Beletskii, V.V. and E.M. Levin, "Mechanics of an Orbital
Cable System", Translated from Kosmicheskie Issledovaniya, Vol.
18, No. 5, pp. 678-688, Sept-Oct 1980.

BEL-2 Beletskii, V.V. and E.M. Levin, "Dynamics of Space
Cable Systems," IFAC AUTOMATIC CONTROL IN SPACE, Noordwijkerhout,
The Netherlands, 1982.

BEL-3 Beletskii, V.V., "Resonance Rotation of Celestial Bodies
and Cassini's Laws," CELESTIAL MECHANICS, Vol. 6, Nov. 1972,
p. 356-378.

BEL-4 Beletskii, V.V. and E.M. Levin, "Dynamics of the
Orbital Cable System," 34th Congress of the International Astro-
nautical Federation at Budapest Hungary, Oct. 10-15, 1983.

BER-1 Bergamaschi, Silvio, "Tether Motion after Failure",
JOURNAL OF ASTRONAUTICAL SCIENCES, Vol. XXX, No. 1, pp. 49-59,
Jan-Mar 1982.

BIR-1 Birch, Paul, "Orbital Ring Systems and Jacob's
Ladders-1", JOURNAL OF BRITISH INTERPLANETARY SOCIETY, Vol. 35,
No. 11, Nov 82, p. 474-497.

BIR-2 Birch, Paul, "Orbital Ring Systems and Jacob's
Ladders-2", JOURNAL OF BRITISH INTERPLANETARY SOCIETY, Vol. 36,
No. 3, Dec 82, p. 115-128.

BLI-1 Blitzer, L. and J.D. Anderson, "Theory of Satellite
Orbit-Orbit Resonance," CELESTIAL MECHANICS, Vol. 25, Sept. 81,
p. 65-78.

BLI-2 Blitzer, L., "Application of Spin-Orbit Theory to a
Class of Orbit-Orbit Resonances, The Case of Titan-Hyperion,"
CELESTIAL MECHANICS, Vol. 16, Sept. 1977, p. 87-95.

BLI-3 Blitzer, L., "Dynamics of Orbit-Orbit and Spin-Orbit
Resonances: Similarities and Differences," NATURAL AND ARTIFICIAL
SATELLITE MOTION, Nacozy, P. and S. Ferraz-Mello, eds., Univ.
of Texas Press, Austin, Texas, 1979, p. 221-230.

BOE-1 Boevkin, V.I., Y.N. Pavlov, and V.M. Nedashkovskii,
"Rotational Motion of a Gravitational Stabilization System,"
COSMIC RES. Vol. 11, 6 Nov 1973, p. 770-773.

BOL-1 Bolotina, N.E. and V.G. Vilke, "Stability of the

Equilibrium Positions of a Flexible, Heavy Fiber Attached to a Satellite in a Circular Orbit," COSMIC RESEARCH, Vol. 16, No. 4, Jan. 1979, p. 506-510.

BOW-1 Bowden, M.L., "A Gravity Gradient Stabilized Solar Power Satellite Design," AIAA 19th AEROSPACE SCIENCES MEETING, St. Louis, Missouri, January 12-15, 1981 (AIAA-81-0362).

BRA-1 Braginskii, V.B. and A. Polnarev, "Relativistic Spin-quadrupole gravitational Effect," ZHETF PIS'MA V. REDAKTSIIU, Vol. 31, Apr. 20, 1978, p. 444-447.

BRE-1 Brereton, R.C., "Stability of Planar Librations of a Dumbbell Satellite in an Elliptic Orbit," Royal Aeronautical Society Journal, 70:1098-1102. December 1966.

BSC-1 Bschorr, D., "Controlling Short-Tethered Satellites," ACTA ASTRONAUT, Vol. 7, 4-5 May 1980, p. 567-573 (30th IAF)

BUC-1 Buckens, F., "On the Motion Stability of Tethered Satellites Configuration", PROCEEDINGS OF THE 12TH INTERNATIONAL SYMPOSIUM ON SPACE TECHNOLOGY AND SCIENCE, Editor: H. Nagasu, AGNE Publishing, Inc., 1977, Tokyo, pp. 351-358.

CHO-1 Chobotov, V., "Gravity-gradient Excitation of a Rotating Cable-Counterweight Space Station in Orbit", JOURNAL OF APPLIED MECHANICS, Vol. 30, p. 547-554.

CHO-2 Chobotov, V.A., "A Synchronous Satellite At Less Than Synchronous Altitude," An Aerospace Corporation Memorandum.

CLA-1 Clarke, Arthur C., THE SPACE ELEVATOR: "THOUGHT EXPERIMENT" OR KEY TO THE UNIVERSE, Address to the XXXth Astronautical Congress, Munich, 20 Sept 1979.

COL-1 Colombo, G. et al. "Shuttle-Borne "Skyhook": A New Tool for Low-Orbital-Altitude Research", Smithsonian Astrophysical Observatory Report, Sept 1974.

COL-2 Colombo, G., STUDY OF CERTAIN LAUNCHING TECHNIQUES USING LONG ORBITING TETHERS, NASA-CR-164060, Smithsonian Institution Astrophysical Observatory, March 1981.

COL-3 Colombo, G., S. Bergamaschi, And F. Bevilacqua, "The Italian Participation to the Tethered Satellite System", XXXII Congress of the International Astronautical Federation, IAF-81-33, Sept 1981.

COL-4 Colombo, G., E.M. Gaposchkin, M.D. Grossi, and G.C. Weiffenbach, "The 'Skyhook': A Shuttle-Borne Tool for Low Orbital Altitude Research", MECCANICA, March 1975.

COL-5 Colombo, G., et al., "Use of Tethers for Payload Orbital Transfer", Smithsonian Astrophysical Observatory, NAS 8-33691, Mar

1982.

COL-6 Colombo, G., "Study of Tethered Satellite Active Attitude Control", SAO NASA Contract NAS 8-33691, Oct. 1982

COL-7 Colombo, G., D.A. Arnold, N. Lanham and G. Nystrom, "System Noise Analysis of the Dumb-bell Tethered Satellite for Gravity-Gradient Measurements," Smithsonian Astrophysical Observatory, Cambridge, Mass., NSG 8063, October 1979.

COL-8 Colombo, G., M.D. Grossi, D. Arnold and M. M. Sanchez, "Continuation of Investigation of Electrodynamic Stabilization and Control of Long Orbiting Tethers," Final Report, NAS8-33691, SAO Report, March 1983.

COL-9 Colombo, G., "Study of Certain Tether Safety Issues and The Use of Tethers for Payload Orbital Transfer," NAS8-33691, SAO Report, August 1981.

CRO-1 Crouch, Donald S., "Shuttle Tethered Satellite System Program Overview", APPLICATIONS OF TETHERS IN SPACE WORKSHOP, Williamsburg, Va., June 15, 1983.

DEL-1 Deleeuw, J.H. and D.R. Taeusch, "Interaction of a Tethered Satellite with the Atmosphere and the Resultant Environment," UAH/NASA Workshop on the Use of a Tethered Satellite System, p. 106-110.

DIA-1 Diarra, Cheick Modibo, "The Effects of Tether Mass on the Stability and the Controllability of the Shuttle-Tethered Subsatellite System", XXXIII Congress of the International Astronautical Federation, IAF 82-06, Paris, France, Sept 1982.

DIC-1 Dickstein, D.H., "Capture of a Passively Stabilized Satellite by Earth's Gravity Field," AIAA JOURNAL 1:2399-401, October 1963.

DOB-1 Dobrowolny, M., G. Colombo and M.D. Grossi, "Electrodynamics of Long Conducting Tethers in the Near Earth Environment," Interim Report NASA Contract #NAS 8-31678. Jan 5, 1976.

DOB-2 Dobrowolny, M., D.A. Arnold, G. Colombo, and M. Grossi, "Investigation of Electrodynamic Stabilization and Control of Long Orbiting Tethers", Interim Report NASA Contract #NAS8-33691. 28 February 1981.

EAD-1 Eads, J.B. and Walf, H., "Tethered Body Problems and Relative Motion Orbit Determination", NAS-5-21453, Analytical Mechanics Association, Inc., Aug 1972.

EFI-1 Efimenko, G.G. and N.V. Krivonosova, "The Stability of Motion of a Flexible Cable with Loads in a Newtonian Force Field," IZVESTIYA MEKHANIKA TVERDOGO TELA, Sept-Oct. 1982, pp. 22-27.

ETK-1 Etkin, B., "Dynamics of Gravity-Oriented Orbiting Systems with Applications to Passive Stabilization," AIAA JOURNAL 2:1008-14, June 1964.

FRY-1 Frye, W.E. and E.V.B. Stearns, "Stabilization and Attitude Control of Satellite Vehicles," AMERICAN ROCKET SOCIETY JOURNAL 29:927-31, December 1959.

GAR-1 Garber, T.B., "A Preliminary Investigation of the Motion of a Long, Flexible Wire in Orbit," Rand Report -RM-2705-ARPA, March 23, 1961.

GAR-2 Garber, T.B., "Influence of Constant Disturbing Torques on the Motion of Gravity-Gradient Stabilized Satellites," AIAA JOURNAL 1:968-969, April 1963.

GLA-1 Glaese, J.R. and Pastrick, H.L., "Modal Synthesis Simulation of the Shuttle Orbiter Tethered Satellite System", AIAA/AAS ASTRODYNAMICS CONFERENCE, San Diego, AIAA-82-1424, 1982.

GRA-1 Grasshoff, L.H., "Influence of Gravity on Satellite Spin Axis Attitude," AMERICAN ROCKET SOCIETY JOURNAL 30:1174-1175, December 1960.

GRE-1 Gresham, L.L. and C.C. Rupp, "Effects of Tether Attachments on the Shuttle/Tethered Satellite Systems Dynamics," AAS Guidance and Control Conference, Keystone, Colorado, February 24-28, 1979. (AAS 79-033)

GUT-1 Gutman, A.S., "Active Damping Concept for Gravity Gradient Satellite Attitude Control," JOURNAL OF SPACECRAFT AND ROCKETS, 4:953-5, July 1967.

HAB-1 Hablani, H.B. and S.K. Shrivastava, "Equilibrium and Liapunov Stability of Flexible Damped Gravity Oriented Satellites," AIAA 16th AEROSPACE SCIENCES MEETING, Huntsville, Ala, January 1978 (AIAA-78-53).

HAG-1 Hagedorn, P. and S. Otterbein, "Some Remarks on the Control of Variable Length Tethered Satellites with Attitude Orbit Coupling", Institut Fur Mechanik, T. H. Darmstadt, Darmstadt, Federal Republic of Germany.

HAR-1 Hara, Michio, "Effects of Magnetic and Gravitational Torques on Spinning Satellite Attitude," AIAA JOURNAL, Vol. 11, 12 Dec. 1973, p. 1737-1742.

HER-1 Herzberg, R.J., K.F. Johansen, and R.C. Stroud, "Dynamics and Control of Large Satellites," ASTRONAUT AERNAUT, Vol. 16, 10 Oct. 1978, p. 35-39.

HUL-1 Hultquist, P.F., "Gravitational Torque Impulse on a Stabilized Satellite," AMERICAN ROCKET SOCIETY JOURNAL, 31:1506-

1509, November 1961.

HUN-1 Hunter, M.W., "Near Earth Transportation Options and High Payoff Choices", AIAA INTERNATIONAL ANNUAL MEETING, Baltimore, Md, May 1982.

KAL-1 - Kalaghan, P.M. et al., "Study of the Dynamics of a Tethered Satellite System(Skyhook)", Final Report NAS 8-32199, Smithsonian Astrophysical Observatory, Cambridge, Mass., March 1978.

KAN-1 Kane, T.R. and A.K. Banerjee, "A Conservation Theorem for Homogeneous Simple Nonholonomic Systems," AIAA DYNAMICS CONFERENCE, Lake Placid, New York, Sept. 1983.

KAN-2 Kane, T.R. and T.R. Robe, "Gravity Torque Effects," AIAA JOURNAL, 4:1454-5, August 1966.

KAR-1 Karr, G.R., "Aerodynamics Effects," UAH/NASA WORKSHOP ON THE USE OF A TETHERED SATELITE SYSTEM, p. 151-155.

KER-1 Kershner, R.B., "Gravity-Gradient Stabilization of Satellites," A & A Engr., 1:18-22, September 1963.

KIR-1 Kirschner, L.R., "The Skyhook Program: A Software Package for a Tethered Satellite System, Including Electrodynamic Interactions", NASA Technical Report Contract NAS 8-33691, May 80.

KDH-1 Kohler, P., W. Maag, R. Wehrli, R. Weber, and H. Brauchi, "Dynamics of a System of Two Satellites Connected by a Deployable and Extensible Tether of Finite Mass", ESTEC Contract #2992/76/NL/AK(SC), Vol 1 and 2, 1978.

KRY-1 Kyrias, G.M., "Tethered Satellite Control Mechanism," NASA Report N83 24882.

KUL-1 Kulla, P., "Stabilization of Tethered Satellites", ESTEC Report TMM/78-07/PK/AVS, 1977.

KUL-2 Kulla, P., "Dynamics of Tethered Satellites", PROCEEDINGS OF THE SYMPOSIUM ON DYNAMICS AND CONTROL OF NON-RIGID SPACECRAFT, Frascati, Italy, pp. 349-334, 1976.

LAN-1 Lang, D.L. and Nolting, R.K., "Operations with Tethered Space Vehicles", NASA SP-138, Gemini Summary Conference 1967.

LAU-1 Laue, Jay H., "Tethered Satellite System-Project Overview", Briefing given NASA/MSFC/PF17, Jan 19, 1983.

LAU-2 Laue, J.H and F. Manarini, "The Tethered Retrievable Platform Concept and Utilization", PROCEEDINGS OF THE 33RD CONGRESS OF THE INTERNATIONAL ASTRONAUTICAL FEDERATION, Sept-Oct 1982, Paris France, IAF-82-13.

LIK-1 Likins, P.W. and D.L. Mingori, "Liapunov Stability Analysis of Freely Spinning Systems," 18th IAF Congress, Yugoslavia, September 1967.

LIP-1 Lips, K.W. and V.J. Modi, "General Dynamics of a Large Class of Flexible Satellite Systems", ACTA ASTRONAUTICA, Vol. 7, 1980, pp. 1349-1360.

LIP-1 Lips, K.W., and V.J. Modi, "Transient Attitude Dynamics of Satellites with Deploying Flexible Appendages," ACTA ASTRONAUTICA, Vol. 5, Oct. 1978, p. 797-815.

MAI-1 Maierov, V.A., V.I. Popov, and I.O. Yanov, "Analysis of the Dynamics of a System Using Gravitational-Gradient and Gyroscopic Principles of Stabilization," COSMIC RES., Vol. 18, 4 Jul-Aug 1980, p. 348-356.

MAN-1 Manarini, G. and F. Mariani, "The Tethered Satellite System Technical Aspects and Prospective Science Missions", Riena, Atti 22 Convegno Intele Sullo Spazio, Roma 1982.

MAR-1 Mariani, F., "Science by Tethered Satellites", Dipartimento di Fisica, Universita di Roma "La Sapienza", Piazzale Aldo Moro, 2-00185, Roma, Italy.

MAR-10 Martinex-Sanchez, M., "The Use of Long Tethers for Payload Orbital Transfer," 34th CONGRESS OF THE INTERNATIONAL ASTRONAUTICAL FEDERATION at Budapest, Hungary, 10-15 October 1983.

MAY-1 Mayer, H.L., SWARMS: OPTIMUM AGGREGATIONS OF SPACECRAFT, ATR-80(7734)-1, NASA Contract NAS W-3160 with Aerospace Corp., 29 Feb 1980.

MAY-2 Mayer, H.L., "Structures Matching the Space Environment: Bridges or Spider Webs", Proceedings of the American Astronautical Society 1980. AAS 80-276.

MIC-1 Michelson, I., "Coupling Effects of Gravity Gradient Satellite Motions," ARS JOURNAL, 32:1735, November 1962.

MIC-2 Michelson, I., "Equilibrium Orientations of Gravity-Gradient Satellites," AIAA JOURNAL, 1:493, February 1963.

MIC-3 Michelson, I., "Euler Angles for Libration Analysis," AIAA JOURNAL, 2:1469-70, August 1964.

MIC-4 Michelson, I., "Librational Dynamic Response Limits of Gravity Gradient Satellites," AIAA JOURNAL, 1:216, Jan 63.

MIC-5 Michelson, I., "Orbit-Resonance of Satellites in Librational Motion," AIAA JOURNAL, 1:489-90, February 1963.

MIN-1 Mingori, D.L., "Gravity Torque on a Spinning Satellite Body," Master's Thesis for the University of California at Los

Angeles, August 1962.

MIN-2 Mingori, D.L., "Gravity Torques," Class Notes for University of California at Los Angeles class on Advanced Satellite Dynamics.

MIN-3 - Mingori, D.L. and P.W. Likins, "Liapunov Stability Analysis of Freely Spinning Systems," EIGHTEENTH IAF CONGRESS, Belgrade, Yugoslavia, September 1967.

MIS-1 Misra, A.K. and Modi, V.J., "A General Dynamical Model for the Space Shuttle Based Tethered Subsatellite System", ADVANCES IN THE ASTRONAUTICAL SCIENCES, 40, 537-557, 1979.

MIS-2 Misra, A.K. and Modi, V.J., "Deployment and Retrieval of a Subsatellite Connected by a Tether to the Space Shuttle", AIAA/AAS ASTRODYNAMICS CONFERENCE, Danvers, Mass., AIAA-80-1693.

MIS-3 Misra, A.K. and V.J. Modi, "Dynamics and Control of Tether Connected Two-Body Systems - A Brief Review", 33rd Congress of International Astronautical Federation, Paris, France, Sept 27-Oct 2, 1982.

MIS-4 Misra, A.K., D.M. Xu, and V.J. Modi, "Non-Linear Vibrations of Orbiting Tethers," AAS/AIAA Astrodynamics Specialist Conference, #83-300, Lake Placid, N.Y., Aug 22-25, 1983.

MIS-5 Misra, A.K. and V.J. Modi, "The Influence of Satellite Flexibility on Orbital Motion," CELESTIAL MECHANICS, Vol. 17, Feb. 1978, p. 145-165.

MOD-1 Modi, V.J., G. Chang-fu, and A.K. Misra, "Effects of Damping on the Control Dynamics of the Space Shuttle Based Tether System", AAS/AIAA ASTRODYNAMICS CONFERENCE, Lake Tahoe, AAS-81-143.

MOD-2 Modi, V.J., G. Chang-fu, A.K. Misra and D.M. Xu, "On the Control of the Space Shuttle Based Tether System", 32nd CONGRESS OF INTERNATIONAL ASTRONAUTICAL FEDERATION, Rome, Italy, 1981.

MOD-3 Modi, V.J. and A.K. Misra, "Deployment Dynamics and Control of Tethered Satellite Systems", AIAA/AAS ASTRODYNAMICS CONFERENCE, Palo Alto, Calif, Aug 1978. AIAA/AAS 78-1398.

MOD-4 Modi, V.J. and A.K. Misra, "Orbital Perturbations of Tethered Satellite Systems," JOURNAL OF ASTRONAUTICAL SCIENCES, Vol. 25, July-Sept. 1977, p. 271-278.

MOD-5 Modi, V.J. and S.C. Sharma, "Structural Dynamics and Configuration Control of Spinning and Gravity Oriented Multi-body Systems," DYNAMICS OF MULTIBODY SYSTEMS: PROCEEDINGS OF THE SYMPOSIUM, Munich, West Germany, August 29-September 3, 1977, p. 245-259. (A79-14201 03-70)

MOD-6 Modi, V.J. and A.K. Misra, "On the Deployment Dynamics of Tether Connected Two-Body Systems," INTERNATIONAL ASTRONAUTICAL FEDERATION CONGRESS, Yugoslavia, 1978. (IAF 78-104)

MOD-7 Modi, V.J. and R.C. Brereton, "Planar Librational Stability of a Flexible Satellite," AIAA JOURNAL, 6:511-17, March 1968.

MOH-1 Mohan, S.N., ORBITAL PERTURBATIONS DUE TO ATTITUDE LIBRATION OF AN ARBITRARY RIGID BODY MOVING IN A CENTRAL NEWTONIAN FIELD, Stanford University Report SUDAAR # 410 for Air Force Avionics Laboratory, WPAFB Ohio, Aug 1970.

MOR-1 Moran, J.P., "Effects of Plane Librations on the Orbital Motion of a Dumbbell Satellite, ARS JOURNAL, 31:1089-1096, August 1961.

NAS-1 NASA-JPL Tether Users Briefing, 1983.

NEW-1 Newton, R.R., "Damping of a Gravitationally Stabilized Satellite," AIAA JOURNAL, 2:20-25, January 1964.

NEW-10 Newton, J.K. and J.L. Farrell, "Natural Frequencies of a Flexible Gravity-Gradient Satellite," JOURNAL OF SPACE-CRAFT AND ROCKETS, 5:560-569, May 1968.

PAU-1 Paul, B., "Planar Librations of an Extensible Dumbell Satellite," AIAA JOURNAL, February 1963, 411-418.

PEA-1 Pearson, Jerome, "Anchored Lunar Satellites for Cislunar Transportation and Communication", Report from USAF Flight Dynamics Laboratory, WPAFB, Ohio.

PEA-2 Pearson, Jerome, "The Orbital Tower: A Spacecraft Launcher Using the Earth's Rotational Energy", Acta Astronautica, Vol. 2, pp. 785-799. 1975.

PEA-10 Peale, S.J., "Rotation of Solid Bodies in the Solar System," REVIEWS OF GEOPHYSICS AND SPACE PHYSICS, Vol. 11, Nov. 1973, p. 767-783.

PEA-11 Peale, S.J., "Generalized Cassini's Laws," ASTRONOMICAL JOURNAL, Vol. 74, p. 483-489.

PEL-1 Peller, J.B., W.B. Fouts, W.T. Schleich, J.A. Jansen, and D.A. Johnson, "Space Shuttle Guidance and Control Overview," Papers from the 1982 Guidance and Control Conference, San Diego, California, 9-11 August 1982.

PEN-1 Pengelley, G.D., "Preliminary Survey of Dynamic Stability of a Cable-Connected Spinning Space Station," JOURNAL OF SPACECRAFT AND ROCKETS, Oct 1966, 1456-62.

PER-1 Perrine, B.S., "A Method for Soft Tethered Station

Keeping", NASA TMX-53643, Marshall Space Flight Center, July 31, 1967.

PRI-1 Pringle R., "Exploration of Nonlinear Resonance in Damping an Elastic Dumb-Bell Satellite", AIAA Journal, 1968, N. 7, 1217-1222.

RIC-1 Richards, W.R., "The Space Anchor", JET PROPULSION LABORATORY INTEROFFICE MEMO, 28 July 1977.

ROW-1 Rowell, L.N. and M.C. Smith, "Effect of Geometrical Libration on the Damped Motion of an Earth Satellite, ARS JOURNAL, 31:361-364, March 1961.

RUP-1 Rupp, C.C. and J.H. Laue, "Shuttle/Tethered Satellite System", JOURNAL OF THE ASTRONAUTICAL SCIENCES, Vol. 26, No. 1, Jan 1978, p. 1-17.

RUP-2 Rupp, C.C., "A Tether Tension Control Law for Tethered Satellites Deployed Along the Local Vertical", NASA TMX-64963, 1975.

RUP-3 Rupp, C.C. and L.L. Gresham, "A Preliminary Study of the Attitude Control for the Shuttle Tether Satellite System", IEEE Journal, 1979.

RUP-4 Rupp, C.C. and L.L. Gresham, "Investigating the Attitude Control of the Shuttle/Tether Satellite System," PROCEEDINGS OF THE ELEVENTH ANNUAL SOUTHEASTERN SYMPOSIUM ON SYSTEM THEORY, Clemson University, So. Carolina, Mar. 79.

RUS-1 Rushing, F.C., A.B. Simon and C.I. Denton, "Unbendable Booms for Gravity Gradient Systems," SPACE/AERONAUTICS, 50:76-7, August 1968.

SAE-1 Saeed, I., and W. Stuver, "Periodic Boom Forces in Dumb-Bell Type Satellites Moving in a Circular Orbit," AIAA JOURNAL, 12(1974), 423-4.

SAD-1 Smithsonian Astrophysical Observatory Software Questionnaire - Draft, 15 June 1983.

SAR-1 Sarychev, V.A., "On the Dynamics of Tether-Connected Two-Body Systems", 33rd Congress of International Astronautical Federation, Paris France, IAF-82-316, Sept 27-Oct 2, 1982.

SAR-2 Sarychev, V.A. and V.V. Sazonov, "Gravity Gradient Stabilization of the Salyut-Soyuz Orbital Complex, 34th INTERNATIONAL ASTRONAUTICAL FEDERATION at Budapest Hungary, 10-15 Oct. 1983.

SCH-1 Schechter, H.B., "Dumbbell Librations in Elliptic Orbits," AIAA JOURNAL, 2:1000-3, June 1964.

SEL-1 Sellappan, R.G., "Some Dynamical Design Considerations for Momentum Biased Spacecraft," 34th INTERNATIONAL ASTRONAUTICAL FEDERATION at Budapest Hungary, 10-15 October 1983.

SHA-1 Sharma, S.C. and W. Stuiver, "Boom Forces in Librating Dumb-Bell Type Satellites," AIAA JOURNAL, 12(1974), 425-6.

SIN-1 Singh, R.B., "Three Dimensional Motion of a System of Two Cable-Connected Satellites in Orbit", ASTRONAUTICA ACTA, Vol. 18, 1973, pp. 301-308.

SNO-1 Snoddy, W.C., "Scientific and Technical Applications of a Tethered Satellite System", 175th AIAA AEROSPACE SCIENCES MEETING, New Orleans, La., Jan 15-17, 1979.

SPE-1 Spencer, T.M., "Atmospheric Perturbation and Control of a Shuttle/Tether Satellite", AUTOMATIC CONTROL IN SPACE PROCEEDINGS OF THE 8TH SYMPOSIUM. Oxford, England July 2-6, 1979, p. 101-108.

STR-1 Strachan, R.L., "The Effect of Eccentricity on Planar Librations of a Gravity Gradient Stabilized Satellite," AIAA/AAS ASTRODYNAMICS CONFERENCE, Danvers, Mass., August 11-13, 1980.

STU-1 Stuiver, W., "Lagrange Configurations in Space System Dynamics", Journal of the Astronautical Sciences, 25(1977), p. 91-106.

STU-2 Stuiver, Willem and Peter M. Bainum, "A Study of Planar Deployment Control and Libration Damping of a Tethered Orbiting Interferometer Satellite", JOURNAL OF ASTRONAUTICAL SCIENCES, Vol. XX, No. 6, pp. 321-346, May-June 1973.

STU-3 Stuiver, W., "Dynamics and Configuration Control of a Two-Body Satellite System," JOURNAL OF SPACECRAFT AND ROCKETS, 11(1974), 545-546.

STU-4 Stuiver, W. and P.M. Bainum, "Deployment Control and Libration Damping of a Tethered Orbiting Interferometer Satellite," 20TH CONGRESS OF THE INTERNATIONAL ASTRONAUTICAL FEDERATION, Mar del Plata, Argentina, October 5-11, 1969.

SWE-1 Swet, C.J. and J.M. Whisnant, "Deployment of a Tethered Orbiting Interferometer", JOURNAL OF ASTRONAUTICAL SCIENCES, Vol. XVII, No. 1, pp. 44-59, July-Aug 1969.

SYN-1 Synge, J.L., "On the Behaviour, According to Newtonian Theory, of a Plumb Line or Pendulum Attached to an Artificial Satellite", PROCEEDINGS OF THE ROYAL IRISH ACADEMY, Vol. 60, Sec A, 1-6, 1959.

TSI-1 Tsiolkovsky, K.E., GREZY O. ZEMIE I NEBE (I) NA VESTE (Speculations between earth and sky, and on Vesta; science fiction works), Moscow, izd-vo AN SSSR, 1959.

UPH-1 Uphoff, C., "Tethered Lunar Satellite", JET PROPULSION LABORATORY INTEROFFICE MEMO, June 15, 1982.

VAL-1 Vallerani, E., G. Manarini and E. Lorenzini, "Prospective of Tethered System in Space Station Operations," 34th CONGRESS OF THE INTERNATIONAL ASTRONAUTICAL FEDERATION, 10-15 October 1983.

VAN-1 Van der Ha, J.C., "Orbital and Relative Motion of a Tethred Satellite System," 34th CONGRESS OF THE INTERNATIONAL ASTRONAUTICAL FEDERATION at Budapest Hungary, 10-15 Oct. 1983.

WAR-1 Ward, W.R., "Tidal Friction and Generalized Cassini's Laws in the Solar System for Planetary Spin Axis Rotation," ASTRONOMICAL JOURNAL, Vol. 80, Jan. 1976, p. 64-70.

WAR-2 Ward, W.R., "Tidal Friction and Generalized Cassini's Laws in the Solar System," PhD Dissertation, California Institute of Technology, 1973.

WEB-1 Weber, R. and H. Brauchli, "Dynamics of a System of Two Satellites Connected by a Deployable and Extensible Tether of Finite Mass", Vol 1 & 2. ESTEC Contract #2992/76/NL/AR(SC). October 1978.

WEI-1 Weiffenbach, G.C., "A Study of the Electrodynamics of Long Conducting Tethers in the Near Earth Environment", Smithsonian Institution Contract with NASA-NAS8-31678.

WOL-1 Wolfe, R.R., J.M. Corgan and P.B. Teets, "Energy Requirements for Satellite Stabilization of the Gravitational Gradient," ARS JOURNAL, 31:836-838, June 1961.

XU-1 Xu, D.M., A.K. Misra, and V.J. Modi, "Three Dimensional Control of the Shuttle Supported Tether Satellite Systems During Deployment and Retrieval", PROCEEDINGS OF THE 3rd VPISU/AIAA SYMPOSIUM ON DYNAMICS AND CONTROL OF LARGE FLEXIBLE SPACECRAFT, Blacksburg, Va., 1981.

XU-2 Xu, D.M., A.K. Misra, and V.J. Modi, "On Vibration Control of Tethered Satellite Systems," PROCEEDINGS OF THE WORKSHOP ON APPLICATIONS OF DISTRIBUTED SYSTEM THEORY TO THE CONTROL OF LARGE SPACE STRUCTURES, G. Rodriguez, ed., JPL PUB. 83-46, July 1, 1983, pp. 317-327.

YAS-1 Yasaka, Tetsuo, "The Structural Feasibility of a Gravity Stabilized Antenna," 31st CONGRESS OF THE INTERNATIONAL ASTRONAUTICAL FEDERATION, Tokyo, Japan, September 21-28, 1980. (IAF 80-A-28)

YOD-1 Yoder, C.F., "Diagrammatic Theory of Transition of Pendulum Like Systems --- Orbit-Orbit and Spin-Orbit Gravitational Resonance Interactions," CELESTIAL MECHANICS, Vol. 19,

January 1979, p. 3-29.

YOD-2 Yoder, C.F., "Effects of the SPIN-SPIN Interaction and the Inelastic Tidal Deformation on the Lunar Physical Librations," NATURAL AND ARTIFICIAL SATELLITE MOTION, Nacozy, P. and S. Ferraz-Mello, ed's., University of Texas Press, Austin, Texas, 1979, p. 211-221.

YU-1 Yu, E.Y., "Long-Term Coupling Effects Between Librational and Orbital Motions of a Satellite," AIAA JOURNAL, 2:553-555, March 1964.

ZAJ-1 Zajac, E.E., "Damping of a Gravitationally Oriented Two-Body Satellite," ARS JOURNAL, 32:1871-1875, December 1962.

BOOKS AND MANUALS

AME-1 Ames Research Center, SYMPOSIUM ON PASSIVE GRAVITY-GRADIENT STABILIZATION, NASA SP-107, Moffett Field, California, May 10-11, 1965.

ARN-1 Arnold, J.R. ed, REPORT ON THE UTILIZATION OF THE EXTERNAL TANKS OF THE SPACE TRANSPORTATION SYSTEM, A Workshop Held at the Univ. of California in San Diego, California Space Institute, NASA Contract NAS8-35037, April 1983.

ATH-1 Athans, M. and P.L. Falb, OPTIMAL CONTROL, Mc-Graw Hill Book Company, St. Louis, Mo., 1966.

BAT-1 Bates, R.R., D.D. Mueller and J.E. White, FUNDAMENTALS OF ASTRODYNAMICS, Dover Publications, Inc., New York, 1971.

BRO-1 Brogan, William L., MODERN CONTROL THEORY, Quantum Publishers Inc., New York, 1974

BRY-1 Bryson, A.E. Jr. and Yu-Chi Ho, APPLIED OPTIMAL CONTROL, Hemisphere Pub. Corp., New York, 1975.

CAN-1 Canon, M.D., C.D. Cullum Jr. and E. Polak, THEORY OF OPTIMAL CONTROL AND MATHEMATICAL PROGRAMMING, Mc-Graw-Hill, Inc., New York, 1970.

DAZ-1 D'Azzo, J.J. and C.H. Houpis, LINEAR CONTROL SYSTEM ANALYSIS AND DESIGN, Mc-Graw-Hill Inc., New York, 1981.

EKE-1 Eke, F.O., "Comments on the Definition of Angular Momentum," Draft Jet Propulsion Laboratory Engineering Memorandum, April 2, 1982.

GRE-1 Greenwood, D.T., PRINCIPLES OF DYNAMICS, Prentice-Hall Inc., Englewood Cliffs, New Jersey, 1965.

KAN-1 Kane, T.R., DYNAMICS, Holt, Reinhart and Winston, Inc., New York, 1968.

KAN-2 Kane, T.R., P.W. Likins and D.A. Levinson, SPACECRAFT DYNAMICS, McGraw Hill, Inc., New York, 1983.

KAP-1 Kaplan, M.H., MODERN SPACECRAFT DYNAMICS AND CONTROL, John Wiley and Sons, 1976.

KIR-1 Kirk, D.E., OPTIMAL CONTROL THEORY, Prentice-Hall Inc., Englewood Cliffs New Jersey, 1970.

KWA-1 Kwakernaak, H. and R. Sivan, LINEAR OPTIMAL CONTROL SYSTEMS, John Wiley and Sons, Inc., 1972.

LIK-1 Likins, P.W., ELEMENTS OF ENGINEERING MECHANICS, McGraw Hill Book Company, 1972.

NAC-1 Nacozy, P.E. and S. Fezzaz-Mello, Editors, NATURAL AND ARTIFICIAL SATELLITE MOTION, University of Texas Press, Austin, Texas, 1979.

NEW-1 Newton, Isaac, PRINCIPIA MATHEMATICA, F. Cajori translator and revisor, University of California Press, Berkeley, 1934.

SAG-1 Sagan, Carl, COSMOS, Random House, New York, 1980.

SYM-1 SYMPOSIUM ON PASSIVE GRAVITY-GRADIENT STABILIZATION, Ames Research Center, Moffett Field, Ca., NASA, 1966.

SP-100 Program Distribution List

SP-100 PROGRAM OFFICE

LCDR William E. Wright, Director
Delbert F. Bunch, Deputy Director for Nuclear Technology
Judith H. Ambrus, Deputy Director for Aerospace Technology

DARPA
DOE HQ
NASA HQ

SP-100 PROJECT OFFICE

Vincent C. Truscello, Project Manager
Herbert S. Davis, Assistant Manager
John E. Hanson, Deputy Manager for Nuclear Technology
Jack F. Mondt, Deputy Manager for Aerospace Technology
James R. French, System Definition Manager
Richard A. Wallace, Mission Analysis and Requirements Manager
Kirk G. Gerbracht, Administration and Operations Manager
R. Joseph Sovle, Manager, SP-100 Office

JPL
JPL
Los Alamos
JPL
JPL
JPL
JPL
LeRC

CIVIL MISSIONS ADVISORY GROUP

PROJECT REVIEW BOARD

SAFETY ADVISORY COMMITTEE

AIR FORCE

Len Caveny	Bolling AFB
Lt. Jason Feig	AF/RPL
Lt. Efren Fornoles	Kirtland AFB
Lt. Steven Hooser	Space Division
Lt. Col. James Lee	Kirtland AFB
Capt. David Perkins	AF/RPL
Jim Reams	Wright-Patterson AFB
Col. Frank J. Redd	Kirtland AFB

ARGONNE NATIONAL LABORATORY

Richard Lewis

BROOKHAVEN NATIONAL LABORATORY

Herb Kouts

DEPARTMENT OF ENERGY

Dyer Kenney	DOE/HQ
Ehsan Khan	DOE/HQ
Stephen Lanes	DOE/HQ
Lt. Col. Robert Smith	DOE/HQ
Walter Von Flue	DOE/SAN
Earl Wahlquist	DOE/HQ

HEDL

C. M. Cox

INEL

John A. Dearlen

SP-100 Program Distribution List (Continued)

JOHNSON SPACE CENTER

Will Ellis
J. Gary Rankin

JPL

Internal Distribution

LANGLEY RESEARCH CENTER

Ray Hook

LAWRENCE LIVERMORE NATIONAL
LABORATORY

Carl Walter

LEWIS RESEARCH CENTER

Henry Slone
Ronald Thomas

LOS ALAMOS NATIONAL LABORATORY

Jay Boudreau
Kaye D. Lathrop

NASA

Wayne Hudson
Jerome P. Mullin
Frederick Bowen Jr.

Resident Office, Kirtland AFB
Headquarters
Resident Office, JPL

NAVY

Cdr. Larry Burgess
LCDR William Mohr
Bill Schmidt
Jim Severance

NAVELEX
NAVELEX
Office of Naval Research
Naval Research Laboratory

OAK RIDGE NATIONAL LABORATORY

William Harms

SANDIA NATIONAL LABORATORY

Lou Cropp