FAST EXCITATION WIGGLER FIELD
MEASUREMENT RESULTS

J. Armendariz, J. Gallardo, T. Romano
A. van Steenberg

August 1992

Received OSTI
NOV 02 1992

NATIONAL SYNCHROTRON LIGHT SOURCE

BROOKHAVEN NATIONAL LABORATORY
ASSOCIATED UNIVERSITIES, INC.

Under Contract No. DE-AC02-76CH00016 with the
UNITED STATES DEPARTMENT OF ENERGY

MASTER

ck
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency, contractor or subcontractor thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency, contractor or subcontractor thereof.

FAST EXCITATION WIGGLER FIELD MEASUREMENT RESULTS

J. Armendariz, J. Gallardo,
T. Romano, A. van Steenbergen

NSLS and Physics Department

Brookhaven National Laboratory

Upton, New York 11973

As part of the program of Inverse Free Electron Laser (IFEL) Accelerator Development, the development of fast excitation, planar wigglers with high K magnitude has been pursued. This paper discusses the observed characteristics of a variable period length, tapered, wiggler as well as the procedures of measurement. The behaviour of a constant period length magnet with varying Vanadium Permendur (VaP) and field reflector thickness is also discussed.

INTRODUCTION

The IFEL accelerator[1], as parameterized, makes use of a quasi sinusoidal magnetic field with a variable period length. The tapered wiggler described in this paper has varying period lengths (λ) from approximately 2.98 to 5.04 cm. It is comprised of easily stackable, geometrically alternating substacks of Vanadium Permendur (VaP) laminations, a ferromagnetic material which is driven in a fast excitation mode and

makes use of interleaving conductive, nonmagnetic, Copper (Cu) laminations, which act as eddy current induced "field reflectors." The VaP laminations for this wiggler design have been studied by means of two dimensional mesh computations (POISSON) and by means of actual short wiggler model measurements. These laminations are assembled in substacks and separated by the nonmagnetic, Cu laminations. Tie rods, running from end to end through the laminations, hold the magnet compressed and in place. Four straight current conductors, parallel to the axis of the composite assembly and interconnected only at the ends outside the magnet body, constitute the single current excitation loop for the wiggler. Two pictorial views of the magnet can be seen in Fig. 1 and Fig. 2.

For the IFEL objective the maximum magnetic field of the wiggler is required to have a field magnitude of $B=12.5$ kG. The field reflectors are essential in order to obtain this field strength within the 4 mm gap through which the electron and laser beams will pass. The quasi sinusoidal characteristic of the magnetic field is produced by alternating the polarity of adjacent poles within the magnet. This is accomplished by simply rotating the substacks of VaP through 180° , every half period ($\frac{\lambda}{2}$).

TECHNICAL DESCRIPTION AND EXPERIMENTAL OBSERVATIONS

A single loop of Cu wire with an approximate area of $A=0.2258$ cm² constitutes the probe used for field measurements. Calibration of the probe was done on a "C" magnet of known magnetic field strength. The current signal produced within the probe by the magnetic field is integrated and amplified by a factor of approximately 10:1 and then routed to an oscilloscope where the signal can then be measured by means of a digital current peak meter. The probe is housed within a strip of compressed phenolic material approximately the size of the magnet gap. A mylar strip is placed within the magnet to provide a snug fit and insure a consistent path of travel

for the probe; therefore, it is essential to always pull the probe through the length of the magnet, to avoid inconsistent field readings.

A. TAPERED WIGGLER

Preliminary data obtained from a tapered wiggler model with varying period lengths from approximately 2.98 to 5.04 cm, in which the ratio of VaP to Cu was kept constant, indicated that the magnetic field on axis rises linearly with increasing period length. Measurements of the field were taken for current values ranging from 1 to 7.7 kA. In all cases the linearity of the field vs. longitudinal coordinate was evident; and the slope of the peaks of the magnetic field is a function of current. The slopes ranged from 3×10^{-3} to 4×10^{-2} kG/cm and the intercepts from 2.3 to 15.8 kG. The full field measurement at 6 kA can be seen in Fig. 3 and the corresponding peak values of the field in Figs. 4-5. It was previously assumed that the peak magnetic field was a function of period length only, but as a result of the experimental observations, it is now concluded that it is also dependent upon the ratio of VaP stack thickness to period length. Figs. 6-7 are the plots of the slope vs. current and the intercepts vs. current, respectively. The saturation effects can be seen in Fig. 7 as the current increases. In Fig. 6 an almost quadratic increase is observed among the slope values. Further analysis is described below.

B. CONSTANT PERIOD WIGGLER

In a constant period wiggler with a constant ratio of VaP to Cu, experimental results indicated that the maximum magnetic field on axis is essentially constant, excluding end effects, throughout the length of the magnet as shown in Fig. 8. Again, field measurements were taken for current values ranging from 1 to 7.7 kA producing slopes from 3.7×10^{-4} to 1.8×10^{-3} kG/cm and intercepts from 2.3 to 16.6 kG. The

slopes in this case are, however, small and can be attributed to, exclusively, the end effects of the magnet. A symmetry about the center of the magnet is observed, and can be seen in Figs. 9-10. With closer evaluation of the peak values of the magnetic field an "elbowing" of the points about the center becomes evident. It is thought that this elbowing is a result of the end effects of the magnet and that only about the center, do the magnetic poles behave as if part of an infinitely long magnet. In all cases, the slopes of best fit lines calculated through the peak points leading up to the center of the magnet are of opposite sign to those leading away from the center of the magnet.

C. SHORT WIGGLER MODELS

A constant period wiggler magnet with a varying ratio of VaP to $\frac{\lambda}{2}$ was configured and measured along with a tapered wiggler which kept the VaP constant and varied the Cu reflectors. The full field measurements for these configurations at 6 kA can be seen in Figs. 11-12 respectively. As can be seen in Figs. 13-14, a linearity is evident in the peak values of the magnetic field of the magnet with constant period and varying ratio of VaP to $\frac{\lambda}{2}$. Although this was a shorter wiggler model, the increase in slope with respect to current for this magnet shows the same behaviour as noted earlier for the varying period length, constant VaP to Cu ratio, wiggler magnet; as can be seen in Fig. 15. This evidence tends to support the conjecture that a term dependent upon the ratio of VaP thickness to ($\frac{\lambda}{2}$) is necessary in order to be able to describe the magnetic field properly, since the only common factor between the two magnets is the increasing amount of VaP. In previous experiments it was observed that the optimum ratio of VaP to Cu was 4 to 1. When this optimum setting is exceeded the smooth sinusoidal shape of the field is compromised. The "shouldering" effect observed in the field of Fig. 12, depicts this effect.

To analyze the data, several fortran programs were written. These programs consisted of routines which solved for the peak values of the fields and which would then fit a polynomial to these points. Also utilized extensively for this purpose was the IMSL library. PV Wave, a graphics package on the Vax cluster at the Brookhaven National Laboratory, was used to provide the hard copy output of our data.

SUMMARY OF RESULTS

Through measurement of the fields of four wiggler configurations a relationship between the wiggler's magnetic field and the longitudinal coordinate has been developed. For current values less than 4 kA, below the onset of saturation, the magnetic field can be described by:

$$\frac{B(z)}{(NI)} = 2.517 + [0.604(\frac{dr}{dz}) + 0.128(\frac{d\lambda}{dz})]z \quad [\frac{kG}{A}] \quad (1)$$

where NI is the number of ampere turns, $\frac{dr}{dz}$ is rate of change of the ratio of VaP to $\frac{\lambda}{2}$ with respect to z , and $\frac{d\lambda}{dz}$ is the rate of change of the period with respect to z . In the design of tapered wigglers, it is convenient to maintain a constant value of r , thus giving $\frac{dr}{dz}=0$. For λ values greater than 3.2 cm, the empirical relationship

$$\frac{B(z)}{(NI)} = 2.517 + 0.128(\frac{d\lambda}{dz})z \quad [\frac{kG}{A}] \quad (2)$$

is then established. Table I shows the dimensions of the individual wiggler models, the ratio of VaP to $(\frac{\lambda}{2})$ and taper of the several wiggler models assembled and measured and subject of this report.

CONCLUSION

Fast excitation driven, laminated Vanadium Permendur, wigglers with periodic interleaving of conductive copper field reflectors, can provide state of the art wigglers. It is evident from the preceding that the constant period wiggler satisfy FEL objec-

tives. It is further observed, that IFEL accelerator requirements can be fulfilled with the tapered wiggler model.

ACKNOWLEDGEMENT

One of the authors (JA), participant in the Summer Research Program, gratefully acknowledge support from the Department of Energy, Office of Educational Programs. This work was supported by the U.S. Department of Energy under Contract No. DE-ACO2-76-CH00016.

REFERENCES

- ¹ E. Courant, A. Fisher, J. Gallardo, C. Pellegrini, J. Rogers, J. Sandweiss, J. Sheehan, A. van Steenbergen, S. Ulc, M. Woodle, *Inverse Free-Electron Laser Accelerator Development*, The Accelerator Test Facility Users' Meeting, October 15-16, 1991, BNL Report **BNL-47000**, **CAP #81**, **ATF-91P**.

TABLES

TABLE I. Table of wiggler dimensions. WLi and Wle constitute the first and last halves, respectively, of the magnet of Fig. 3. WII, WIII and WIV are the dimensions of the magnets in Figs. 11, 12 and 8, respectively. Data is normalized to $L_w=24$ cm and $I_{exc}=4$ kA

$\frac{dB}{dz}$ [kG/cm]	λ [cm]	W_p [cm]	$(r)^a$	$(B_i)^b$ [kG]	$(B_e)^c$ [kG]	$\frac{dB}{dz}$ [kG/cm]	$\frac{dr}{dz}$ [1/cm]
WLi	2.98	1.19	0.798	9.57	—	0.0168 ^d	≈ 0
var. λ ; const r	4.29	1.73	0.806	—	9.97	—	—
Wle	4.29	1.73	0.806	9.97	—	0.0168 ^d	≈ 0
var. λ ; const r	5.04	1.98	0.786	—	10.37	—	—
WII	3.96	1.07	0.540	10.05	—	0.0168 ^d	0.006
const λ	3.96	1.37	0.692	—	10.45	—	—
WIII	3.25	1.02	0.628	10.11	—	0.0072	-0.006
const W_p	4.27	1.02	0.478	—	10.28	—	—
WIVi	3.76	1.52	0.808	10.06	—	$\pm 0.0068^e$	≈ 0
const λ, r	3.76	1.52	0.808	—	9.89	—	—

^a $r = \frac{W_p}{(\lambda/2)}$, W_p denotes the thickness of the VaP

^b $B_i = B(z = 0)$ except for WIV where $B_i = B(z = 24)$

^c $B_e = B(z = 24)$ except for WIV where $B_e = B(z = 0)$

^d without partial saturation, 0.0145

^e end effects

FIG. 1. Pictorial of Fast Excitation Wiggler with field reflection.

FIG. 2. Pictorial of Wiggler with a front view of the VaP laminations and approximate positioning of the current conductors.

FIG. 3. Full field measurement of Tapered Wiggler with varying period lengths, and a constant VaP to Cu ratio.

FIG. 4. Positive peak values of magnetic field in Fig. 3.

FIG. 5. Negative peak values of magnetic field in Fig. 3.

FIG. 6. Plot of slope vs. current for different current settings of the Tapered Wiggler with varying period lengths and constant VaP to Cu ratio.

FIG. 7. Plot of intercepts vs. current for different current settings of the Tapered Wiggler with varying period lengths and constant VaP to Cu ratio.

FIG. 8. Full field measurement of Wiggler with constant period length and constant VaP to Cu ratio.

FIG. 9. Positive Peak values of magnetic field in Fig. 8.

FIG. 10. Negative Peak values of magnetic field in Fig. 8.

FIG. 11. Full field measurement of Short Constant Period Wiggler with varying VaP to $\frac{\lambda}{2}$ ratio.

FIG. 12. Full field measurement of Short Constant VaP Wiggler with varying Cu.

FIG. 13. Positive peak values of magnetic field in Fig. 11.

FIG. 14. Negative peak values of magnetic field in Fig. 11.

FIG. 15. Plot of slope vs. current for different current settings of the Short Constant Period Wiggler with varying ratio of V_{aP} to $\frac{\lambda}{2}$.

**DATE
FILMED
01/10/93**