1 of 1

Report No. ERA-NRE-93-055

Date: July 1993

RECEIVED
NOV 15 1993
OSTI

INTERNAL TECHNICAL REPORT

Title: MEASURED THERMAL AND FAST NEUTRON FLUENCE RATES
ATR CYCLE 100-BC 4/23/93 THRU 5/13/93

Organization: Radiation Measurements and Development

Author: L. D. Smith, R. K. Murray, JW Rogers

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Checked By: *Jerry D Smith*

Approved By: *JW Rogers*

MASTER

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

~~THIS DOCUMENT HAS NOT BEEN REVIEWED FOR DISSEMINATION~~
~~CONTAINING UNCLASSIFIED INFORMATION~~

MEASURED THERMAL AND FAST NEUTRON FLUENCE RATES
ATR CYCLE 100-BC
4/23/93 Thru 5/13/93

L. D. Smith, R. K. Murray and JW Rogers

This report contains the thermal (2200 m/s) and fast ($E > 1\text{MeV}$) neutron fluence rate data for ATR Cycle 100-BC which were measured by the Radiation Measurements Laboratory (RML) as requested by the Power Reactor Programs (ATR Experiments) Radiation Measurements Work Order.

This report contains fluence rate values corresponding to the particular elevations (relative to the 80 ft. core elevation) where the measurements were taken. The data in this report consists of (1) a table of the ATR power history and distribution, (2) a hard copy listing of all thermal and fast neutron fluence rates, (3) plots of both the thermal and fast neutron fluence rates, and (4) a magnetic record (3.5 inch diskette) containing a listing of only the fast neutron fluence rates, their assigned elevations and proper header identification of all monitor positions contained herein.

did not accompany this report, ds

The fluence rates reported are for the average power levels given in the table of power history and distribution.

All "H" holder monitor wires for this cycle are 54 inches long.

All "SR" holder monitor wires for this cycle are 55 inches long. This length allows measurement of the full core region and makes the first count elevation 24.73 inches above core midplane.

Due to the safety rod problems in the west lobe, "BR" holders were used in the W-1, 2, 3, and 4 positions. All "BR" holder monitor wires for this cycle are 56.25 inches long.

The distance from the end of the wires to the first count position was 4.25 inches for all wires counted from this cycle.

The results from the measurements in the W-1, 2, 3, 4 monitor positions indicate that the safety rod followers were rotated to a different azimuthal orientation relative to the normal orientation. The results indicate that the rotation was counterclockwise from their normal orientation. This is the same condition observed starting with Cycle 99-B.

DEFINITIONS OF REPORTED INFORMATION

ON PRINTED PAGES

1. CYCLE: The identification code given to a specific period of operation of the ATR for which the data in this report applies.
2. POSITION: The identification code given to a specific location in the ATR core area where neutron monitors were located and for which the data associated with the code apply. The letter code identifies the lobe and the number code identifies a monitor position.
3. MONITOR ID: The identification code given to a specific neutron monitor holder. The code is stamped on the holder. The letter code identifies the type of holder and the number is unique to allow tracking of the neutron monitors and their data.
4. EFPD: The acronym for, "Effective Full Power Days" which is the effective number of days the ATR operated at the average total core power level of the cycle. This value is obtained from the ATR power history and distribution.
5. AVERAGE MW: The average power level (in megawatts) at which the ATR lobe operated during the cycle. The values used for NW, NE, C, SW, and SE lobes are obtained from the ATR power history and distribution. The values used for the other lobes and core positions are determined as follows:

$$\begin{aligned}N &= (NE + NW + C)/3 \\E &= (NE + SE + C)/3 \\S &= (SE + SW + C)/3 \\W &= (NW + SW + C)/3\end{aligned}$$

$$\begin{aligned}A1 \text{ through } A8 &= C \\A9 &= NE \\A10 &= SE \\A11 &= SW \\A12 &= NW\end{aligned}$$

$$\begin{aligned}B1 \text{ or } B2 &= NE \\B3 \text{ or } B4 &= SE \\B5 \text{ or } B6 &= SW \\B7 \text{ or } B8 &= NW\end{aligned}$$

$$\begin{aligned}B9 &= N \\B10 &= E \\B11 &= S \\B12 &= W\end{aligned}$$

6. DATE: The calendar dates corresponding to the outage and operating time of the cycle. These dates include the forced outage time associated with the cycle as well as the operating time.

7. ELEVATION: The vertical position associated with the neutron fluence rate measurement value relative to the 80 ft. elevation of the ATR core. The elevation values are in inches and negative values are below the 80 ft. elevation (commonly referred to as centerline). The elevation values are established reference elevation points specified as follows:

<u>Holder Type</u>	<u>Reference Elevation</u>	<u>Drawing Numbers</u>
H	77.948 ft.	424852
SR	77.768 ft.	417424
BR-WEST POSITIONS	81.771 ft.	035561

Using the dimensions of the monitor holders, the location of the monitor wire in the holder, the length of the wire and the distance between the measurements along the wire an elevation value for each fluence rate value is determined. An evaluation of the elevation tolerances is listed as follows:

	<u>SR & BR Holders</u>	<u>H Holders</u>
Holder Fabrication	± 0.11 inch	± 0.11 inch
Cutting the Monitor Wire to Length	± 0.01 inch	± 0.01 inch
Wire Alignment in the Holder	± 0.13 inch	± 0.06 inch
Mounting the Wire to the Scanner	± 0.13 inch	± 0.13 inch
Scanning Control	± 0.01 inch	± 0.01 inch
Scanner Home Positioning	± 0.06 inch	± 0.06 inch
Stackup of the Safety Rod Components (estimated)	± 0.33 inch*	
Position of the Safety Rod Relative to 80 ft. (core centerline) during Operation	± 0.75 inch**	
95% Confidence Bound	± 0.78 inch	± 0.19 inch
Maximum Error	± 1.53 inch	± 0.38 inch

These elevation tolerances include only what are considered to be random errors. Systematic errors or biases may also occur due to information input. However, procedural controls are used to minimize this information input error.

*This estimate will be revised after an actual measurement is made.

**This estimate does not include variations due to thermal and hydraulic effects.

8. "THERMAL": The equivalent 2200 m/s (0.025 eV) neutron fluence rate assuming a Maxwellian distribution for the thermalized neutrons at 20.40C. The fluence rate is determined from the Co-59 (n,c)Co-60 reaction rate assuming a 37 barn 2200 m/s cross section for the reaction. Corrections for the epithermal reaction rate are made based on cadmium ratio measurements at each position of the fluence rate measurement. All fluence rate values are in units of neutrons per sqcm per second.
9. "FAST": The equivalent >1 MeV fission neutron energy fluence rate assuming a pure U-235 fission spectrum neutron energy distribution. The fluence rate is determined from the Ni-58(n,p)Co-58 reaction rate assuming a 0.092 barn fission spectrum averaged cross section for the reaction and a fission spectrum fraction of 0.692 for >1 MeV neutrons. Corrections for the burnout of the Co-58 isomers are made based on the measured 2200 m/s fluence rate, the exposure duration and the burnout cross sections of the isomers [1650 barns (71 days), 1.7 E+5 barns (9.1 hours)] at each position of the fluence rate measurement.
10. CENTERLINE FLU. RATE: The neutron fluence rate at the elevation assignment nearest to the ATR core centerline elevation (0.0).
11. AVG. MAX. FLU. RATE: The average of the highest three adjacent values.
12. MAX. FLU. RATE/MW (AVG.): The average maximum fluence rate divided by the average power level (MW) of the lobe or position.
13. K FACTOR: The conversion factor determined from the neutron monitor activity for converting the net count rate at each elevation to the absolute reaction product (60Co or 58Co) radioactivity per unit mass of the monitor material (d/s/mg).
14. RESONANCE CORRECTION: The fractional correction factor used to correct the Co-59(n,c)Co-60 reaction rate for the epithermal neutron response at the position where the neutron monitor was located during irradiation. This correction factor was determined from cobalt "cadmium ratio" measurements at the same spatial location for the monitor geometry and atom density.
15. C/L BURNOUT CORRECTION: The correction factor for the burnout (transmutation) of the reaction products (Co-60, Co-58, Co-58m) of the neutron monitors during the cycle irradiation at the centerline fluence rate elevation. The burnout correction factors for other elevation assignments will vary (nonlinearly) depending on the "thermal" neutron fluence rates and cycle durations.
16. BACKGROUND (counts/sec.): The whole scanner detector background environment counting rate at the time the neutron monitor wires were scanned.

17. CHECK SOURCE (counts/sec.)

Date Hour : The wire scanner detector check source count rate on the day the neutron monitor wires were scanned. The check source is a radioactive (^{60}Co) cobalt-aluminum wire mounted in a fixture which reproducibly positions it over the detector collimator. This check source is used to test counting functions (gain and stability) of the scanner counting system. The count rate is corrected for background and decay corrected to 05/01/88, 12:00.

ON PLOTS

18. REACTOR: Identification of the reactor with which the data are associated (normally ATR).

19. CYCLE POWER: The total megawatt days of power produced during the reactor cycle. This value is normally obtained from the ATR power history and distribution information supplied by PRP.

20. MATERIAL: The element name of the neutron monitor material. The "thermal" neutron monitor material is normally an alloy (CoAl) of cobalt (Co) and aluminum (Al) where the weight percent is given preceding the percent (%) symbol.

21. EXPERIMENT: The identification code given to the experiment located in the loop. This information is provided by PRP.

POWER HISTORY AND DISTRIBUTION

CYCLE 100-BC
4/23/93 TO 5/13/93

	<u>NW</u>	<u>NE</u>	<u>C</u>	<u>SW</u>	<u>SE</u>	<u>TOTAL MWD</u>
Mwd	41	43	81	88	105	357
EFPD	2.78					
Eff. Te.	0.932	0.977	1.841	2.000	2.386	
PF	0.335	0.352	0.662	0.719	0.858	
Average Power Level in MW	14.6	15.4	29.1	31.6	37.7	

Total Full Power 128.4 MW

Due to significant down time during this cyle, the following power history was used for fluence rate determinations:

0.4875 days @ 29.4 MW = 0.2290 P.F.
0.1958 days @ 43 MW = 0.3350 P.F.
5.6 days @ 0 MW = 0.0 P.F.
0.2750 days @ 29.3 MW = 0.2280 P.F.
0.2167 days @ 45.7 MW = 0.3560 P.F.
0.1215 days @ 99 MW = 0.7710 P.F.
1.1944 days @ 129 MW = 1.0040 P.F.
0.8611 days @ 137.8 MW = 1.0730 P.F.
0.1563 days @ 156.5 MW = 1.2190 P.F.
0.0229 days @ 202.5 MW = 1.5770 P.F.
41 days @ 0 MW = 0.0 P.F.

ATR NEUTRON MONITOR RESULTS

PAGE: 1

CYCLE: 100-BC
EFPD: 2.8POSITION: N-1
AVERAGE MW: 19.7MONITOR ID: SR-486
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.03E+13	1.30E+13
22.75	1.83E+13	2.03E+13
20.75	4.66E+13	3.07E+13
18.75	7.38E+13	3.77E+13
16.75	9.79E+13	4.56E+13
14.75	1.14E+14	5.19E+13
12.75	1.25E+14	5.69E+13
10.75	1.37E+14	6.09E+13
8.75	1.42E+14	6.31E+13
6.75	1.49E+14	6.33E+13
4.75	1.51E+14	6.41E+13
2.75	1.58E+14	6.58E+13
0.75	1.56E+14	6.06E+13
-1.25	1.58E+14	6.78E+13
-3.25	1.52E+14	6.76E+13
-5.25	1.51E+14	6.61E+13
-7.25	1.45E+14	6.08E+13
-9.25	1.39E+14	5.88E+13
-11.25	1.32E+14	5.76E+13
-13.25	1.21E+14	5.14E+13
-15.25	1.07E+14	4.79E+13
-17.25	9.21E+13	4.25E+13
-19.25	7.59E+13	3.51E+13
-21.25	5.89E+13	2.51E+13
-23.25	4.92E+13	1.61E+13
-25.25	3.27E+13	8.56E+12

CENTER LINE FLU. RATE	1.56E+14	6.06E+13
AVG. MAX. FLU. RATE	1.58E+14	6.72E+13
MAX. FLU. RATE/MW (AVG.)	8.00E+12	3.41E+12
K FACTOR	274.14	3370.35
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.173
BACKGROUND (COUNTS/SEC.)	1.54	1.54
CHECK SOURCE (COUNTS/SEC.)		
06/10/93 09:24	1760.	1760.

ATR NEUTRON MONITOR RESULTS

PAGE: 2

CYCLE: 100-BC
EFPD: 2.8POSITION: N-3
AVERAGE MW: 19.7MONITOR ID: SR-487
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.20E+13	2.18E+13
22.75	1.98E+13	3.46E+13
20.75	4.96E+13	5.07E+13
18.75	7.90E+13	5.95E+13
16.75	1.03E+14	7.15E+13
14.75	1.18E+14	7.69E+13
12.75	1.30E+14	8.44E+13
10.75	1.36E+14	8.75E+13
8.75	1.46E+14	9.14E+13
6.75	1.50E+14	9.19E+13
4.75	1.54E+14	9.44E+13
2.75	1.60E+14	9.21E+13
0.75	1.62E+14	9.24E+13
-1.25	1.64E+14	8.84E+13
-3.25	1.62E+14	9.56E+13
-5.25	1.53E+14	9.41E+13
-7.25	1.47E+14	9.41E+13
-9.25	1.43E+14	8.56E+13
-11.25	1.35E+14	8.29E+13
-13.25	1.22E+14	8.02E+13
-15.25	1.09E+14	7.26E+13
-17.25	9.62E+13	6.62E+13
-19.25	8.02E+13	5.29E+13
-21.25	6.43E+13	4.13E+13
-23.25	5.36E+13	2.63E+13
-25.25	4.03E+13	1.21E+13

CENTER LINE FLU. RATE	1.62E+14	9.24E+13
AVG. MAX. FLU. RATE	1.63E+14	9.46E+13
MAX. FLU. RATE/MW (AVG.)	8.25E+12	4.80E+12
K FACTOR	275.02	3496.48
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.178
BACKGROUND (COUNTS/SEC.)	1.29	1.29
CHECK SOURCE (COUNTS/SEC.)		
05/28/93 08:25	1786.	1786.

ATR NEUTRON MONITOR RESULTS

PAGE: 3

CYCLE: 100-BC
EFPD: 2.8

POSITION: N-4
AVERAGE MW: 19.7

MONITOR ID: SR-488
DATE: 04/23/93 to 05/13/93

ELEVATION from core CL (inches)	"THERMAL" 2200 m/s CO (n/cm**2/sec)	"FAST" >1 MeV NI (n/cm**2/sec)
24.73	8.52E+12	9.49E+12
22.75	1.54E+13	1.40E+13
20.75	4.14E+13	2.07E+13
18.75	7.07E+13	2.51E+13
16.75	9.57E+13	2.87E+13
14.75	1.10E+14	2.96E+13
12.75	1.22E+14	3.66E+13
10.75	1.31E+14	3.67E+13
8.75	1.36E+14	3.84E+13
6.75	1.42E+14	3.83E+13
4.75	1.46E+14	4.06E+13
2.75	1.47E+14	4.04E+13
0.75	1.49E+14	4.17E+13
-1.25	1.48E+14	3.81E+13
-3.25	1.49E+14	4.17E+13
-5.25	1.46E+14	4.11E+13
-7.25	1.43E+14	3.99E+13
-9.25	1.37E+14	3.84E+13
-11.25	1.29E+14	3.60E+13
-13.25	1.20E+14	3.46E+13
-15.25	1.07E+14	3.21E+13
-17.25	9.44E+13	2.69E+13
-19.25	7.80E+13	2.16E+13
-21.25	6.16E+13	1.82E+13
-23.25	4.68E+13	1.23E+13
-25.25	3.02E+13	7.29E+12

CENTER LINE FLU. RATE	1.49E+14	4.17E+13
AVG. MAX. FLU. RATE	1.49E+14	4.09E+13
MAX. FLU. RATE/MW (AVG.)	7.55E+12	2.08E+12
K FACTOR	272.01	3359.97
RESONANCE CORRECTION	0.81	NA
C/L. BURNOUT CORRECTION	1.000	1.167
BACKGROUND (COUNTS/SEC.)	1.34	1.34
CHECK SOURCE (COUNTS/SEC.)		1785.
06/02/93 09:22	1785.	

ATR NEUTRON MONITOR RESULTS

PAGE: 4

CYCLE: 100-BC
EFPD: 2.8POSITION: E-1
AVERAGE MW: 27.4MONITOR ID: SR-489
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.15E+13	1.24E+13
22.75	2.25E+13	1.89E+13
20.75	6.34E+13	2.87E+13
18.75	1.09E+14	3.62E+13
16.75	1.44E+14	4.30E+13
14.75	1.72E+14	4.84E+13
12.75	1.92E+14	5.37E+13
10.75	2.10E+14	5.94E+13
8.75	2.27E+14	6.14E+13
6.75	2.42E+14	6.43E+13
4.75	2.50E+14	6.53E+13
2.75	2.59E+14	7.00E+13
0.75	2.55E+14	7.06E+13
-1.25	2.53E+14	7.00E+13
-3.25	2.45E+14	6.77E+13
-5.25	2.37E+14	6.72E+13
-7.25	2.29E+14	6.43E+13
-9.25	2.16E+14	6.06E+13
-11.25	1.97E+14	5.77E+13
-13.25	1.76E+14	5.32E+13
-15.25	1.55E+14	4.90E+13
-17.25	1.37E+14	4.06E+13
-19.25	1.14E+14	3.36E+13
-21.25	8.78E+13	2.49E+13
-23.25	6.57E+13	1.86E+13
-25.25	4.20E+13	1.06E+13

CENTER LINE FLU. RATE	2.55E+14	7.06E+13
AVG. MAX. FLU. RATE	2.56E+14	7.02E+13
MAX. FLU. RATE/MW (AVG.)	9.34E+12	2.56E+12
K FACTOR	277.90	3369.61
RESONANCE CORRECTION	0.81	NA
C/L. BURNOUT CORRECTION	1.000	1.249
BACKGROUND (COUNTS/SEC.)	1.88	1.88
CHECK SOURCE (COUNTS/SEC.)		
06/02/93 09:22	1785.	1785.

ATR NEUTRON MONITOR RESULTS

PAGE: 5

CYCLE: 100-BC
EFPD: 2.8POSITION: E-2
AVERAGE MW: 27.4MONITOR ID: SR-490
DATE: 04/23/93 to 05/13/93

ELEVATION from core CL (inches)	"THERMAL" 2200 m/s CO (n/cm**2/sec)	"FAST" >1 MeV NI (n/cm**2/sec)
24.73	1.68E+13	2.50E+13
22.75	2.84E+13	4.05E+13
20.75	7.66E+13	5.89E+13
18.75	1.23E+14	7.91E+13
16.75	1.67E+14	9.28E+13
14.75	1.91E+14	1.10E+14
12.75	2.15E+14	1.24E+14
10.75	2.36E+14	1.34E+14
8.75	2.49E+14	1.45E+14
6.75	2.67E+14	1.52E+14
4.75	2.76E+14	1.62E+14
2.75	2.79E+14	1.65E+14
0.75	2.79E+14	1.61E+14
-1.25	2.79E+14	1.62E+14
-3.25	2.78E+14	1.56E+14
-5.25	2.64E+14	1.51E+14
-7.25	2.53E+14	1.50E+14
-9.25	2.36E+14	1.44E+14
-11.25	2.23E+14	1.31E+14
-13.25	1.98E+14	1.14E+14
-15.25	1.74E+14	1.04E+14
-17.25	1.47E+14	9.12E+13
-19.25	1.22E+14	7.34E+13
-21.25	9.29E+13	5.19E+13
-23.25	7.29E+13	3.33E+13
-25.25	5.34E+13	1.67E+13

CENTER LINE FLU. RATE	2.79E+14	1.61E+14
AVG. MAX. FLU. RATE	2.79E+14	1.62E+14
MAX. FLU. RATE/MW (AVG.)	1.02E+13	5.93E+12
K FACTOR	280.23	3382.00
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.265
BACKGROUND (COUNTS/SEC.)	1.36	1.36
CHECK SOURCE (COUNTS/SEC.)		
06/16/93 09:06	1751.	1751.

ATR NEUTRON MONITOR RESULTS

PAGE: 6

CYCLE: 100-BC
EFPD: 2.8POSITION: E-3
AVERAGE MW: 27.4MONITOR ID: SR-491
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.72E+13	3.24E+13
22.75	2.89E+13	5.46E+13
20.75	7.29E+13	7.71E+13
18.75	1.15E+14	1.01E+14
16.75	1.52E+14	1.20E+14
14.75	1.77E+14	1.40E+14
12.75	2.02E+14	1.54E+14
10.75	2.14E+14	1.70E+14
8.75	2.30E+14	1.78E+14
6.75	2.39E+14	1.85E+14
4.75	2.52E+14	1.94E+14
2.75	2.61E+14	1.90E+14
0.75	2.63E+14	2.01E+14
-1.25	2.61E+14	1.98E+14
-3.25	2.55E+14	1.89E+14
-5.25	2.38E+14	1.91E+14
-7.25	2.26E+14	1.72E+14
-9.25	2.16E+14	1.64E+14
-11.25	2.05E+14	1.54E+14
-13.25	1.85E+14	1.38E+14
-15.25	1.62E+14	1.24E+14
-17.25	1.39E+14	1.00E+14
-19.25	1.13E+14	8.53E+13
-21.25	8.93E+13	6.70E+13
-23.25	7.64E+13	4.12E+13
-25.25	6.23E+13	2.09E+13

CENTER LINE FLU. RATE	2.63E+14	2.01E+14
AVG. MAX. FLU. RATE	2.62E+14	1.97E+14
MAX. FLU. RATE/MW (AVG.)	9.55E+12	7.17E+12
K FACTOR	279.22	3333.64
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.254
BACKGROUND (COUNTS/SEC.)	1.19	1.19
CHECK SOURCE (COUNTS/SEC.)		
06/09/93 07:01	1757.	1757.

ATR NEUTRON MONITOR RESULTS

PAGE: 7

CYCLE: 100-BC
EFPD: 2.8POSITION: E-4
AVERAGE MW: 27.4MONITOR ID: SR-492
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.47E+13	2.51E+13
22.75	2.45E+13	3.85E+13
20.75	6.42E+13	5.84E+13
18.75	9.97E+13	7.54E+13
16.75	1.34E+14	9.06E+13
14.75	1.58E+14	1.00E+14
12.75	1.78E+14	1.04E+14
10.75	1.94E+14	1.14E+14
8.75	2.05E+14	1.18E+14
6.75	2.09E+14	1.20E+14
4.75	2.20E+14	1.30E+14
2.75	2.28E+14	1.30E+14
0.75	2.26E+14	1.29E+14
-1.25	2.31E+14	1.29E+14
-3.25	2.26E+14	1.31E+14
-5.25	2.10E+14	1.26E+14
-7.25	1.99E+14	1.22E+14
-9.25	1.88E+14	1.18E+14
-11.25	1.75E+14	1.11E+14
-13.25	1.61E+14	9.79E+13
-15.25	1.42E+14	9.13E+13
-17.25	1.21E+14	8.20E+13
-19.25	9.86E+13	6.82E+13
-21.25	7.72E+13	4.57E+13
-23.25	6.35E+13	2.88E+13
-25.25	4.91E+13	1.31E+13

CENTER LINE FLU. RATE	2.26E+14	1.29E+14
AVG. MAX. FLU. RATE	2.28E+14	1.30E+14
MAX. FLU. RATE/MW (AVG.)	8.32E+12	4.74E+12
K FACTOR	282.29	3412.42
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.228
BACKGROUND (COUNTS/SEC.)	1.97	1.97
CHECK SOURCE (COUNTS/SEC.)		
06/07/93 09:51	1772.	1772.

ATR NEUTRON MONITOR RESULTS

PAGE: 8

CYCLE: 100-BC
EFPD: 2.8POSITION: SE-1
AVERAGE MW: 37.7MONITOR ID: SR-493
DATE: 04/23/93 to 05/13/93

ELEVATION from core CL (inches) -----	"THERMAL" 2200 m/s CO (n/cm**2/sec) -----	"FAST" >1 MeV NI (n/cm**2/sec) -----
24.73	1.73E+13	3.14E+13
22.75	3.09E+13	5.22E+13
20.75	8.55E+13	8.34E+13
18.75	1.40E+14	1.13E+14
16.75	1.93E+14	1.43E+14
14.75	2.27E+14	1.67E+14
12.75	2.60E+14	1.85E+14
10.75	2.82E+14	1.97E+14
8.75	3.01E+14	2.15E+14
6.75	3.17E+14	2.23E+14
4.75	3.29E+14	2.31E+14
2.75	3.45E+14	2.39E+14
0.75	3.49E+14	2.43E+14
-1.25	3.51E+14	2.30E+14
-3.25	3.44E+14	2.35E+14
-5.25	3.33E+14	2.27E+14
-7.25	3.19E+14	2.17E+14
-9.25	3.00E+14	2.01E+14
-11.25	2.78E+14	1.89E+14
-13.25	2.54E+14	1.70E+14
-15.25	2.25E+14	1.45E+14
-17.25	1.93E+14	1.22E+14
-19.25	1.53E+14	9.41E+13
-21.25	1.18E+14	7.05E+13
-23.25	9.41E+13	4.37E+13
-25.25	7.21E+13	2.02E+13

CENTER LINE FLU. RATE	3.49E+14	2.43E+14
AVG. MAX. FLU. RATE	3.48E+14	2.38E+14
MAX. FLU. RATE/MW (AVG.)	9.24E+12	6.31E+12
K FACTOR	278.50	3334.09
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.309
BACKGROUND (COUNTS/SEC.)	1.65	1.65
CHECK SOURCE (COUNTS/SEC.)		
05/28/93 08:25	1786.	1786.

ATR NEUTRON MONITOR RESULTS

PAGE: 9

CYCLE: 100-BC
EFPD: 2.8POSITION: SE-2
AVERAGE MW: 37.7MONITOR ID: SR-494
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.76E+13	3.21E+13
22.75	3.11E+13	5.32E+13
20.75	8.56E+13	8.68E+13
18.75	1.40E+14	1.14E+14
16.75	1.91E+14	1.42E+14
14.75	2.27E+14	1.66E+14
12.75	2.59E+14	1.91E+14
10.75	2.82E+14	2.00E+14
8.75	3.03E+14	2.19E+14
6.75	3.23E+14	2.24E+14
4.75	3.37E+14	2.45E+14
2.75	3.45E+14	2.46E+14
0.75	3.51E+14	2.48E+14
-1.25	3.54E+14	2.46E+14
-3.25	3.45E+14	2.45E+14
-5.25	3.37E+14	2.39E+14
-7.25	3.23E+14	2.29E+14
-9.25	3.06E+14	2.10E+14
-11.25	2.83E+14	1.97E+14
-13.25	2.52E+14	1.72E+14
-15.25	2.26E+14	1.52E+14
-17.25	1.91E+14	1.27E+14
-19.25	1.54E+14	1.01E+14
-21.25	1.19E+14	7.49E+13
-23.25	9.53E+13	4.47E+13
-25.25	7.10E+13	1.73E+13

CENTER LINE FLU. RATE	3.51E+14	2.48E+14
AVG. MAX. FLU. RATE	3.50E+14	2.47E+14
MAX. FLU. RATE/MW (AVG.)	9.28E+12	6.54E+12
K FACTOR	282.19	3474.89
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.310
BACKGROUND (COUNTS/SEC.)	1.41	1.41
CHECK SOURCE (COUNTS/SEC.)		
06/09/93 07:01	1757.	1757.

ATR NEUTRON MONITOR RESULTS

PAGE: 10

CYCLE: 100-BC
EFPD: 2.8

POSITION: SE-3
AVERAGE MW: 37.7

MONITOR ID: SR-495
DATE: 04/23/93 to 05/13/93

ELEVATION from core CL (inches)	"THERMAL" 2200 m/s CO (n/cm**2/sec)	"FAST" >1 MeV NI (n/cm**2/sec)
24.73	1.81E+13	3.42E+13
22.75	3.19E+13	5.51E+13
20.75	9.23E+13	8.62E+13
18.75	1.49E+14	1.17E+14
16.75	2.01E+14	1.44E+14
14.75	2.41E+14	1.70E+14
12.75	2.71E+14	1.93E+14
10.75	2.94E+14	2.07E+14
8.75	3.14E+14	2.23E+14
6.75	3.34E+14	2.32E+14
4.75	3.45E+14	2.38E+14
2.75	3.62E+14	2.53E+14
0.75	3.67E+14	2.56E+14
-1.25	3.66E+14	2.47E+14
-3.25	3.57E+14	2.51E+14
-5.25	3.45E+14	2.38E+14
-7.25	3.30E+14	2.32E+14
-9.25	3.07E+14	2.15E+14
-11.25	2.88E+14	1.98E+14
-13.25	2.60E+14	1.81E+14
-15.25	2.27E+14	1.52E+14
-17.25	1.96E+14	1.33E+14
-19.25	1.60E+14	1.03E+14
-21.25	1.26E+14	7.57E+13
-23.25	1.01E+14	5.13E+13
-25.25	7.45E+13	2.31E+13

CENTER LINE FLU. RATE	3.67E+14	2.56E+14
AVG. MAX. FLU. RATE	3.65E+14	2.52E+14
MAX. FLU. RATE/MW (AVG.)	9.68E+12	6.68E+12
K FACTOR	275.78	3367.63
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.320
BACKGROUND (COUNTS/SEC.)	1.11	1.11
CHECK SOURCE (COUNTS/SEC.)		1786.
05/28/93 08:25	1786.	

ATR NEUTRON MONITOR RESULTS

PAGE: 11

CYCLE: 100-BC
EFPD: 2.8POSITION: SE-4
AVERAGE MW: 37.7MONITOR ID: SR-496
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.85E+13	2.90E+13
22.75	3.14E+13	5.26E+13
20.75	8.94E+13	7.66E+13
18.75	1.51E+14	1.02E+14
16.75	2.05E+14	1.24E+14
14.75	2.43E+14	1.46E+14
12.75	2.78E+14	1.69E+14
10.75	3.01E+14	1.77E+14
8.75	3.21E+14	1.98E+14
6.75	3.39E+14	2.03E+14
4.75	3.52E+14	2.11E+14
2.75	3.67E+14	2.18E+14
0.75	3.74E+14	2.29E+14
-1.25	3.75E+14	2.31E+14
-3.25	3.66E+14	2.25E+14
-5.25	3.53E+14	2.18E+14
-7.25	3.35E+14	2.08E+14
-9.25	3.14E+14	1.97E+14
-11.25	2.91E+14	1.79E+14
-13.25	2.67E+14	1.57E+14
-15.25	2.36E+14	1.45E+14
-17.25	2.03E+14	1.20E+14
-19.25	1.65E+14	9.88E+13
-21.25	1.33E+14	7.42E+13
-23.25	1.08E+14	4.63E+13
-25.25	8.06E+13	2.53E+13

CENTER LINE FLU. RATE	3.74E+14	2.29E+14
AVG. MAX. FLU. RATE	3.72E+14	2.29E+14
MAX. FLU. RATE/MW (AVG.)	9.86E+12	6.06E+12
K FACTOR	277.07	3341.63
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.324
BACKGROUND (COUNTS/SEC.)	1.40	1.40
CHECK SOURCE (COUNTS/SEC.)		
06/02/93 09:22	1785.	1785.

ATR NEUTRON MONITOR RESULTS

PAGE: 12

CYCLE: 100-BC
EFPD: 2.8POSITION: S-1
AVERAGE MW: 32.8MONITOR ID: SR-497
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.86E+13	3.22E+13
22.75	3.21E+13	5.41E+13
20.75	8.36E+13	8.79E+13
18.75	1.34E+14	1.09E+14
16.75	1.84E+14	1.38E+14
14.75	2.14E+14	1.56E+14
12.75	2.37E+14	1.78E+14
10.75	2.54E+14	1.97E+14
8.75	2.76E+14	2.09E+14
6.75	2.85E+14	2.27E+14
4.75	2.96E+14	2.29E+14
2.75	3.12E+14	2.34E+14
0.75	3.12E+14	2.37E+14
-1.25	3.16E+14	2.30E+14
-3.25	3.08E+14	2.31E+14
-5.25	2.98E+14	2.21E+14
-7.25	2.85E+14	2.18E+14
-9.25	2.68E+14	2.14E+14
-11.25	2.47E+14	1.92E+14
-13.25	2.24E+14	1.80E+14
-15.25	1.98E+14	1.60E+14
-17.25	1.71E+14	1.32E+14
-19.25	1.42E+14	1.10E+14
-21.25	1.09E+14	7.72E+13
-23.25	9.28E+13	5.06E+13
-25.25	7.82E+13	2.40E+13

CENTER LINE FLU. RATE	3.12E+14	2.37E+14
AVG. MAX. FLU. RATE	3.13E+14	2.34E+14
MAX. FLU. RATE/MW (AVG.)	9.55E+12	7.12E+12
K FACTOR	285.11	3420.37
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.286
BACKGROUND (COUNTS/SEC.)	1.59	1.59
CHECK SOURCE (COUNTS/SEC.)		
06/09/93 07:01	1757.	1757.

ATR NEUTRON MONITOR RESULTS

PAGE: 13

CYCLE: 100-BC
EFPD: 2.8POSITION: S-2
AVERAGE MW: 32.8MONITOR ID: SR-498
DATE: 04/23/93 to 05/13/93

ELEVATION from core CL (inches)	"THERMAL" 2200 m/s CO (n/cm**2/sec)	"FAST" >1 MeV NI (n/cm**2/sec)
24.73	1.48E+13	1.84E+13
22.75	3.08E+13	2.70E+13
20.75	9.56E+13	3.99E+13
18.75	1.59E+14	5.28E+13
16.75	2.10E+14	6.48E+13
14.75	2.39E+14	7.73E+13
12.75	2.58E+14	8.64E+13
10.75	2.79E+14	9.16E+13
8.75	3.02E+14	1.01E+14
6.75	3.19E+14	1.09E+14
4.75	3.25E+14	1.04E+14
2.75	3.27E+14	1.16E+14
0.75	3.29E+14	1.17E+14
-1.25	3.30E+14	1.17E+14
-3.25	3.24E+14	1.19E+14
-5.25	3.17E+14	1.12E+14
-7.25	3.09E+14	1.08E+14
-9.25	2.93E+14	1.00E+14
-11.25	2.75E+14	9.21E+13
-13.25	2.56E+14	8.84E+13
-15.25	2.25E+14	7.52E+13
-17.25	1.96E+14	6.63E+13
-19.25	1.62E+14	5.39E+13
-21.25	1.25E+14	3.71E+13
-23.25	9.04E+13	2.32E+13
-25.25	6.05E+13	1.39E+13

CENTER LINE FLU. RATE	3.29E+14	1.17E+14
AVG. MAX. FLU. RATE	3.28E+14	1.18E+14
MAX. FLU. RATE/MW (AVG.)	1.00E+13	3.59E+12
K FACTOR	278.53	3301.19
RESONANCE CORRECTION	0.81	NA
C/L. BURNOUT CORRECTION	1.000	1.297
BACKGROUND (COUNTS/SEC.)	1.31	1.31
CHECK SOURCE (COUNTS/SEC.)		
06/10/93 09:24	1760.	1760.

ATR NEUTRON MONITOR RESULTS

PAGE: 14

CYCLE: 100-BC
EFPD: 2.8POSITION: S-3
AVERAGE MW: 32.8MONITOR ID: SR-499
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.57E+13	2.44E+13
22.75	2.90E+13	3.86E+13
20.75	8.52E+13	5.62E+13
18.75	1.40E+14	7.58E+13
16.75	1.85E+14	8.84E+13
14.75	2.14E+14	1.05E+14
12.75	2.35E+14	1.19E+14
10.75	2.53E+14	1.31E+14
8.75	2.65E+14	1.35E+14
6.75	2.83E+14	1.41E+14
4.75	2.91E+14	1.44E+14
2.75	3.06E+14	1.50E+14
0.75	3.13E+14	1.49E+14
-1.25	3.10E+14	1.49E+14
-3.25	3.12E+14	1.45E+14
-5.25	3.04E+14	1.45E+14
-7.25	2.92E+14	1.44E+14
-9.25	2.80E+14	1.37E+14
-11.25	2.58E+14	1.26E+14
-13.25	2.36E+14	1.13E+14
-15.25	2.06E+14	1.00E+14
-17.25	1.79E+14	7.87E+13
-19.25	1.40E+14	6.51E+13
-21.25	1.11E+14	4.94E+13
-23.25	8.73E+13	3.37E+13
-25.25	6.17E+13	1.76E+13

CENTER LINE FLU. RATE	3.13E+14	1.49E+14
AVG. MAX. FLU. RATE	3.12E+14	1.49E+14
MAX. FLU. RATE/MW (AVG.)	9.51E+12	4.55E+12
K FACTOR	277.28	3445.84
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.287
BACKGROUND (COUNTS/SEC.)	1.16	1.16
CHECK SOURCE (COUNTS/SEC.)		
06/16/93 09:06	1751.	1751.

ATR NEUTRON MONITOR RESULTS

PAGE: 15

CYCLE: 100-BC
EFPD: 2.8POSITION: S-4
AVERAGE MW: 32.8MONITOR ID: SR-500
DATE: 04/23/93 to 05/13/93

ELEVATION from core CL (inches)	"THERMAL" 2200 m/s CO (n/cm**2/sec)	"FAST" >1 MeV NI (n/cm**2/sec)
24.73	1.91E+13	3.44E+13
22.75	3.08E+13	5.96E+13
20.75	7.88E+13	8.54E+13
18.75	1.29E+14	1.16E+14
16.75	1.76E+14	1.38E+14
14.75	2.03E+14	1.63E+14
12.75	2.26E+14	1.75E+14
10.75	2.45E+14	1.82E+14
8.75	2.61E+14	2.12E+14
6.75	2.77E+14	2.16E+14
4.75	2.88E+14	2.30E+14
2.75	2.95E+14	2.35E+14
0.75	2.98E+14	2.32E+14
-1.25	3.01E+14	2.36E+14
-3.25	2.96E+14	2.32E+14
-5.25	2.87E+14	2.25E+14
-7.25	2.74E+14	2.14E+14
-9.25	2.60E+14	2.01E+14
-11.25	2.47E+14	1.95E+14
-13.25	2.31E+14	1.77E+14
-15.25	2.01E+14	1.57E+14
-17.25	1.74E+14	1.36E+14
-19.25	1.42E+14	1.11E+14
-21.25	1.10E+14	7.95E+13
-23.25	9.30E+13	4.89E+13
-25.25	7.98E+13	2.52E+13

CENTER LINE FLU. RATE	2.98E+14	2.32E+14
AVG. MAX. FLU. RATE	2.99E+14	2.34E+14
MAX. FLU. RATE/MW (AVG.)	9.11E+12	7.15E+12
K FACTOR	276.03	3351.97
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.278
BACKGROUND (COUNTS/SEC.)	1.36	1.36
CHECK SOURCE (COUNTS/SEC.)		
06/14/93 10:16	1763.	1763.
06/14/93 10:26	1761.	1761.

ATR NEUTRON MONITOR RESULTS

PAGE: 16

CYCLE: 100-BC
EFPD: 2.8POSITION: SW-1
AVERAGE MW: 31.6MONITOR ID: SR-501
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	2.02E+13	3.28E+13
22.75	3.38E+13	5.55E+13
20.75	8.89E+13	8.00E+13
18.75	1.41E+14	1.01E+14
16.75	1.86E+14	1.24E+14
14.75	2.16E+14	1.38E+14
12.75	2.38E+14	1.55E+14
10.75	2.47E+14	1.67E+14
8.75	2.59E+14	1.78E+14
6.75	2.69E+14	1.84E+14
4.75	2.86E+14	1.88E+14
2.75	3.03E+14	1.91E+14
0.75	3.17E+14	1.94E+14
-1.25	3.16E+14	1.95E+14
-3.25	3.14E+14	1.91E+14
-5.25	3.08E+14	1.87E+14
-7.25	2.94E+14	1.81E+14
-9.25	2.78E+14	1.74E+14
-11.25	2.58E+14	1.65E+14
-13.25	2.40E+14	1.46E+14
-15.25	2.11E+14	1.34E+14
-17.25	1.79E+14	1.10E+14
-19.25	1.49E+14	8.71E+13
-21.25	1.18E+14	6.84E+13
-23.25	9.55E+13	4.04E+13
-25.25	7.13E+13	2.28E+13

CENTER LINE FLU. RATE	3.17E+14	1.94E+14
AVG. MAX. FLU. RATE	3.16E+14	1.93E+14
MAX. FLU. RATE/MW (AVG.)	1.00E+13	6.12E+12
K FACTOR	277.27	3476.11
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.290
BACKGROUND (COUNTS/SEC.)	1.38	1.38
CHECK SOURCE (COUNTS/SEC.)		
06/09/93 07:01	1757.	1757.

ATR NEUTRON MONITOR RESULTS

PAGE: 17

CYCLE: 100-BC
EFPD: 2.8POSITION: SW-2
AVERAGE MW: 31.6MONITOR ID: SR-502
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.64E+13	2.67E+13
22.75	2.95E+13	4.82E+13
20.75	7.76E+13	7.60E+13
18.75	1.26E+14	1.00E+14
16.75	1.71E+14	1.17E+14
14.75	1.95E+14	1.32E+14
12.75	2.14E+14	1.50E+14
10.75	2.20E+14	1.66E+14
8.75	2.24E+14	1.79E+14
6.75	2.39E+14	1.83E+14
4.75	2.58E+14	1.94E+14
2.75	2.84E+14	1.88E+14
0.75	2.88E+14	1.96E+14
-1.25	2.91E+14	2.02E+14
-3.25	2.95E+14	1.99E+14
-5.25	2.79E+14	1.89E+14
-7.25	2.76E+14	1.92E+14
-9.25	2.62E+14	1.75E+14
-11.25	2.42E+14	1.64E+14
-13.25	2.18E+14	1.53E+14
-15.25	1.93E+14	1.37E+14
-17.25	1.68E+14	1.11E+14
-19.25	1.40E+14	9.08E+13
-21.25	1.07E+14	5.96E+13
-23.25	8.51E+13	3.75E+13
-25.25	6.38E+13	1.64E+13

CENTER LINE FLU. RATE	2.88E+14	1.96E+14
AVG. MAX. FLU. RATE	2.92E+14	1.99E+14
MAX. FLU. RATE/MW (AVG.)	9.23E+12	6.30E+12
K FACTOR	282.69	3381.44
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.271
BACKGROUND (COUNTS/SEC.)	1.71	1.71
CHECK SOURCE (COUNTS/SEC.)		
06/14/93 10:16	1763.	1763.
06/14/93 10:26	1761.	1761.

ATR NEUTRON MONITOR RESULTS

PAGE: 18

CYCLE: 100-BC
EFPD: 2.8POSITION: SW-3
AVERAGE MW: 31.6MONITOR ID: SR-503
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.54E+13	2.31E+13
22.75	2.70E+13	4.10E+13
20.75	6.98E+13	6.56E+13
18.75	1.15E+14	8.83E+13
16.75	1.58E+14	1.11E+14
14.75	1.82E+14	1.30E+14
12.75	1.98E+14	1.42E+14
10.75	2.07E+14	1.57E+14
8.75	2.14E+14	1.68E+14
6.75	2.29E+14	1.82E+14
4.75	2.43E+14	1.91E+14
2.75	2.65E+14	1.96E+14
0.75	2.77E+14	1.99E+14
-1.25	2.78E+14	1.98E+14
-3.25	2.79E+14	1.98E+14
-5.25	2.72E+14	1.94E+14
-7.25	2.64E+14	1.86E+14
-9.25	2.48E+14	1.74E+14
-11.25	2.32E+14	1.59E+14
-13.25	2.10E+14	1.45E+14
-15.25	1.86E+14	1.31E+14
-17.25	1.62E+14	1.14E+14
-19.25	1.35E+14	9.10E+13
-21.25	1.04E+14	6.12E+13
-23.25	8.17E+13	4.32E+13
-25.25	6.27E+13	1.85E+13

CENTER LINE FLU. RATE	2.77E+14	1.99E+14
AVG. MAX. FLU. RATE	2.78E+14	1.99E+14
MAX. FLU. RATE/MW (AVG.)	8.80E+12	6.29E+12
K FACTOR	284.97	3377.78
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.264
BACKGROUND (COUNTS/SEC.)	1.50	1.50
CHECK SOURCE (COUNTS/SEC.)		
06/02/93 09:22	1785.	1785.

ATR NEUTRON MONITOR RESULTS

PAGE: 19

CYCLE: 100-BC
EFPD: 2.8POSITION: SW-4
AVERAGE MW: 31.6MONITOR ID: SR-504
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

24.73	1.77E+13	2.99E+13
22.75	3.06E+13	5.20E+13
20.75	8.18E+13	7.49E+13
18.75	1.29E+14	9.81E+13
16.75	1.74E+14	1.20E+14
14.75	2.01E+14	1.34E+14
12.75	2.19E+14	1.48E+14
10.75	2.24E+14	1.55E+14
8.75	2.32E+14	1.70E+14
6.75	2.46E+14	1.73E+14
4.75	2.68E+14	1.77E+14
2.75	2.84E+14	1.84E+14
0.75	2.94E+14	1.90E+14
-1.25	3.03E+14	1.91E+14
-3.25	2.98E+14	1.80E+14
-5.25	2.88E+14	1.76E+14
-7.25	2.77E+14	1.80E+14
-9.25	2.61E+14	1.58E+14
-11.25	2.47E+14	1.56E+14
-13.25	2.23E+14	1.44E+14
-15.25	1.98E+14	1.21E+14
-17.25	1.68E+14	1.03E+14
-19.25	1.39E+14	8.94E+13
-21.25	1.08E+14	6.42E+13
-23.25	8.83E+13	4.39E+13
-25.25	6.77E+13	2.00E+13

CENTER LINE FLU. RATE	2.94E+14	1.90E+14
AVG. MAX. FLU. RATE	2.98E+14	1.88E+14
MAX. FLU. RATE/MW (AVG.)	9.44E+12	5.96E+12
K FACTOR	279.39	3348.94
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.275
BACKGROUND (COUNTS/SEC.)	1.80	1.80
CHECK SOURCE (COUNTS/SEC.)		
06/07/93 09:51	1772.	1772.

ATR NEUTRON MONITOR RESULTS

PAGE: 20

CYCLE: 100-BC
EFPD: 2.8

POSITION: W-1
AVERAGE MW: 25.1

MONITOR ID: BR-505
DATE: 04/23/93 to 05/13/93

ELEVATION
from core CL
(inches)

"THERMAL"
2200 m/s CO
(n/cm**2/sec)

"FAST"
>1 MeV NI
(n/cm**2/sec)

20.50	9.06E+13	5.97E+13
19.50	1.02E+14	6.79E+13
17.50	1.32E+14	8.16E+13
15.50	1.59E+14	9.59E+13
13.50	1.78E+14	1.00E+14
11.50	1.95E+14	1.10E+14
9.50	2.07E+14	1.19E+14
7.50	2.19E+14	1.24E+14
5.50	2.30E+14	1.29E+14
3.50	2.38E+14	1.29E+14
1.50	2.58E+14	1.32E+14
-0.50	2.54E+14	1.34E+14
-2.50	2.43E+14	1.28E+14
-4.50	2.37E+14	1.31E+14
-6.50	2.30E+14	1.30E+14
-8.50	2.20E+14	1.21E+14
-10.50	2.09E+14	1.20E+14
-12.50	1.97E+14	1.16E+14
-14.50	1.76E+14	1.08E+14
-16.50	1.47E+14	9.80E+13
-18.50	1.26E+14	8.55E+13
-20.50	1.02E+14	7.07E+13
-22.50	7.84E+13	5.15E+13
-24.50	6.84E+13	2.85E+13
-26.50	4.42E+13	1.30E+13
-28.50	2.21E+13	5.74E+12
-30.48	1.02E+13	3.09E+12

CENTER LINE FLU. RATE	2.54E+14	1.34E+14
AVG. MAX. FLU. RATE	2.52E+14	1.32E+14
MAX. FLU. RATE/MW (AVG.)	1.00E+13	5.25E+12
K FACTOR	273.60	3378.64
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.248
BACKGROUND (COUNTS/SEC.)	1.63	1.63
CHECK SOURCE (COUNTS/SEC.)		1777.
06/21/93 08:24	1777.	

ATR NEUTRON MONITOR RESULTS

PAGE: 21

CYCLE: 100-BC
EFPD: 2.8

POSITION: W-2
AVERAGE MW: 25.1

MONITOR ID: BR-506
DATE: 04/23/93 to 05/13/93

ELEVATION
from core CL
(inches)

"THERMAL"
2200 m/s CO
(n/cm**2/sec)

"FAST"
>1 MeV NI
(n/cm**2/sec)

20.50	9.82E+13	6.96E+13
19.50	1.10E+14	8.45E+13
17.50	1.43E+14	1.03E+14
15.50	1.75E+14	1.20E+14
13.50	1.94E+14	1.34E+14
11.50	2.18E+14	1.43E+14
9.50	2.33E+14	1.58E+14
7.50	2.42E+14	1.66E+14
5.50	2.49E+14	1.71E+14
3.50	2.69E+14	1.72E+14
1.50	2.91E+14	1.77E+14
-0.50	2.88E+14	1.80E+14
-2.50	2.81E+14	1.79E+14
-4.50	2.69E+14	1.74E+14
-6.50	2.59E+14	1.72E+14
-8.50	2.51E+14	1.68E+14
-10.50	2.40E+14	1.62E+14
-12.50	2.22E+14	1.51E+14
-14.50	2.00E+14	1.38E+14
-16.50	1.68E+14	1.21E+14
-18.50	1.39E+14	1.04E+14
-20.50	1.11E+14	8.46E+13
-22.50	8.82E+13	6.14E+13
-24.50	7.85E+13	3.33E+13
-26.50	4.97E+13	1.54E+13
-28.50	2.55E+13	5.96E+12
-30.48	1.10E+13	2.96E+12

CENTER LINE FLU. RATE	2.88E+14	1.80E+14
AVG. MAX. FLU. RATE	2.87E+14	1.79E+14
MAX. FLU. RATE/MW (AVG.)	1.14E+13	7.12E+12
K FACTOR	282.20	3324.04
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.271
BACKGROUND (COUNTS/SEC.)	1.55	1.55
CHECK SOURCE (COUNTS/SEC.)		1777.
06/21/93 08:24	1777.	

ATR NEUTRON MONITOR RESULTS

PAGE: 22

CYCLE: 100-BC
EFPD: 2.8POSITION: W-3
AVERAGE MW: 25.1MONITOR ID: BR-507
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

20.50	1.00E+14	3.67E+13
19.50	1.16E+14	4.22E+13
17.50	1.51E+14	5.22E+13
15.50	1.81E+14	5.71E+13
13.50	2.04E+14	6.83E+13
11.50	2.28E+14	7.08E+13
9.50	2.45E+14	7.94E+13
7.50	2.60E+14	8.21E+13
5.50	2.64E+14	8.54E+13
3.50	2.75E+14	8.74E+13
1.50	2.94E+14	8.93E+13
-0.50	2.92E+14	8.98E+13
-2.50	2.91E+14	9.13E+13
-4.50	2.80E+14	9.01E+13
-6.50	2.73E+14	8.84E+13
-8.50	2.66E+14	8.11E+13
-10.50	2.53E+14	8.21E+13
-12.50	2.34E+14	7.10E+13
-14.50	2.12E+14	6.98E+13
-16.50	1.85E+14	6.31E+13
-18.50	1.54E+14	5.37E+13
-20.50	1.22E+14	4.17E+13
-22.50	9.23E+13	3.21E+13
-24.50	6.78E+13	1.95E+13
-26.50	3.94E+13	1.02E+13
-28.50	2.16E+13	4.67E+12
-30.48	1.13E+13	2.50E+12

CENTER LINE FLU. RATE	2.92E+14	8.98E+13
AVG. MAX. FLU. RATE	2.92E+14	9.04E+13
MAX. FLU. RATE/MW (AVG.)	1.16E+13	3.60E+12
K FACTOR	277.69	3381.61
RESONANCE CORRECTION	0.81	NA
C/L. BURNOUT CORRECTION	1.000	1.273
BACKGROUND (COUNTS/SEC.)	1.53	1.53
CHECK SOURCE (COUNTS/SEC.)		
06/21/93 08:24	1777.	1777.

ATR NEUTRON MONITOR RESULTS

PAGE: 23

CYCLE: 100-BC
EFPD: 2.8POSITION: W-4
AVERAGE MW: 25.1MONITOR ID: BR-508
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

20.50	8.54E+13	2.93E+13
19.50	9.46E+13	3.45E+13
17.50	1.22E+14	4.10E+13
15.50	1.47E+14	5.00E+13
13.50	1.68E+14	5.47E+13
11.50	1.85E+14	5.92E+13
9.50	1.95E+14	6.03E+13
7.50	2.05E+14	6.43E+13
5.50	2.10E+14	6.40E+13
3.50	2.20E+14	6.70E+13
1.50	2.33E+14	6.37E+13
-0.50	2.34E+14	6.72E+13
-2.50	2.25E+14	6.88E+13
-4.50	2.22E+14	6.54E+13
-6.50	2.18E+14	6.78E+13
-8.50	2.12E+14	6.27E+13
-10.50	1.99E+14	6.34E+13
-12.50	1.86E+14	5.84E+13
-14.50	1.67E+14	5.71E+13
-16.50	1.45E+14	5.05E+13
-18.50	1.21E+14	4.52E+13
-20.50	9.85E+13	3.67E+13
-22.50	7.44E+13	2.70E+13
-24.50	5.41E+13	1.60E+13
-26.50	3.17E+13	8.31E+12
-28.50	1.76E+13	4.13E+12
-30.48	9.00E+12	2.00E+12

CENTER LINE FLU. RATE	2.34E+14	6.72E+13
AVG. MAX. FLU. RATE	2.31E+14	6.73E+13
MAX. FLU. RATE/MW (AVG.)	9.19E+12	2.68E+12
K FACTOR	273.02	3343.71
RESONANCE CORRECTION	0.76	NA
C/L. BURNOUT CORRECTION	1.000	1.234
BACKGROUND (COUNTS/SEC.)	1.41	1.41
CHECK SOURCE (COUNTS/SEC.)		
06/17/93 09:03	1754.	1754.

ATR NEUTRON MONITOR RESULTS

PAGE: 24

CYCLE: 100-BC
EFPD: 2.8POSITION: H-2
AVERAGE MW: 29.1MONITOR ID: H-202
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

25.23	6.03E+13	2.30E+13
23.25	6.69E+13	3.61E+13
21.25	8.06E+13	5.48E+13
19.25	1.01E+14	7.03E+13
17.25	1.26E+14	8.43E+13
15.25	1.48E+14	9.50E+13
13.25	1.65E+14	1.04E+14
11.25	1.81E+14	1.16E+14
9.25	1.92E+14	1.20E+14
7.25	2.03E+14	1.23E+14
5.25	2.03E+14	1.27E+14
3.25	2.09E+14	1.30E+14
1.25	2.09E+14	1.34E+14
-0.75	2.10E+14	1.34E+14
-2.75	2.07E+14	1.37E+14
-4.75	2.08E+14	1.33E+14
-6.75	2.05E+14	1.23E+14
-8.75	1.98E+14	1.24E+14
-10.75	1.82E+14	1.21E+14
-12.75	1.68E+14	1.11E+14
-14.75	1.51E+14	9.98E+13
-16.75	1.29E+14	8.91E+13
-18.75	1.12E+14	7.40E+13
-20.75	9.04E+13	5.62E+13
-22.75	7.70E+13	4.39E+13
-23.75	7.42E+13	3.35E+13

CENTER LINE FLU. RATE	2.10E+14	1.34E+14
AVG. MAX. FLU. RATE	2.09E+14	1.35E+14
MAX. FLU. RATE/MW (AVG.)	7.19E+12	4.64E+12
K FACTOR	280.44	3421.42
RESONANCE CORRECTION	0.75	NA
C/L. BURNOUT CORRECTION	1.000	1.216
BACKGROUND (COUNTS/SEC.)	1.51	1.51
CHECK SOURCE (COUNTS/SEC.)		
06/17/93 09:03	1754.	1754.

ATR NEUTRON MONITOR RESULTS

PAGE: 25

CYCLE: 100-BC
EFPD: 2.8POSITION: H-10
AVERAGE MW: 29.1MONITOR ID: H-203
DATE: 04/23/93 to 05/13/93ELEVATION
from core CL
(inches)
-----"THERMAL"
2200 m/s CO
(n/cm**2/sec)
-----"FAST"
>1 MeV NI
(n/cm**2/sec)

25.23	6.60E+13	2.89E+13
23.25	6.69E+13	4.56E+13
21.25	8.15E+13	7.47E+13
19.25	1.05E+14	9.54E+13
17.25	1.26E+14	1.18E+14
15.25	1.50E+14	1.35E+14
13.25	1.61E+14	1.54E+14
11.25	1.82E+14	1.70E+14
9.25	1.92E+14	1.79E+14
7.25	2.07E+14	1.87E+14
5.25	2.15E+14	1.93E+14
3.25	2.20E+14	2.03E+14
1.25	2.23E+14	2.06E+14
-0.75	2.20E+14	2.07E+14
-2.75	2.22E+14	1.99E+14
-4.75	2.17E+14	1.84E+14
-6.75	2.13E+14	1.82E+14
-8.75	2.02E+14	1.76E+14
-10.75	1.86E+14	1.72E+14
-12.75	1.72E+14	1.58E+14
-14.75	1.56E+14	1.46E+14
-16.75	1.38E+14	1.25E+14
-18.75	1.17E+14	1.06E+14
-20.75	9.20E+13	8.20E+13
-22.75	8.13E+13	5.86E+13
-23.75	7.85E+13	4.52E+13

CENTER LINE FLU. RATE	2.20E+14	2.07E+14
AVG. MAX. FLU. RATE	2.22E+14	2.05E+14
MAX. FLU. RATE/MW (AVG.)	7.62E+12	7.05E+12
K FACTOR	274.68	3398.21
RESONANCE CORRECTION	0.75	NA
C/L. BURNOUT CORRECTION	1.000	1.223
BACKGROUND (COUNTS/SEC.)	1.28	1.28
CHECK SOURCE (COUNTS/SEC.)		
06/17/93 09:03	1754.	1754.

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-486

POSITION : N-1

MATERIAL : 0.4970 %COAL

EXPERIMENT : 1D-N

AVG. MAX. FLUENCE RATE : $1.58\text{E}+14$

26
AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-486

POSITION: N-1

MATERIAL: NICKEL

EXPERIMENT: 1D-N

AVG. MAX. FLUENCE RATE: $6.72\text{E}+13$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-487

POSITION : N-3

MATERIAL : 0.4970 %COAL

EXPERIMENT : 1D-N

AVG. MAX. FLUENCE RATE : $1.63\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-487

POSITION : N-3

MATERIAL : NICKEL

EXPERIMENT : 1D-N

AVG. MAX. FLUENCE RATE : $9.46\text{E}+13$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-488

POSITION: N-4

MATERIAL: 0.4970 %COAL

EXPERIMENT: 1D-N

AVG. MAX. FLUENCE RATE: $1.49\text{E}+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-488

POSITION : N-4

MATERIAL : NICKEL

EXPERIMENT : 1D-N

AVG. MAX. FLUENCE RATE : $4.09\text{E}+13$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-489

POSITION : E-1

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2C-E

AVG. MAX. FLUENCE RATE : 2.56×10^{14}

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-489

POSITION : E-1

MATERIAL : NICKEL

EXPERIMENT : 2C-E

AVG. MAX. FLUENCE RATE : $7.02\text{E}+13$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-490

POSITION : E-2

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2C-E

AVG. MAX. FLUENCE RATE : $2.79\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-490

POSITION: E-2

MATERIAL: NICKEL

EXPERIMENT: 2C-E

AVG. MAX. FLUENCE RATE: $1.62\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-491

POSITION: E-3

MATERIAL: 0.4970 %COAL

EXPERIMENT: 2C-E

AVG. MAX. FLUENCE RATE: $2.62\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-491

POSITION: E-3

MATERIAL: NICKEL

EXPERIMENT: 2C-E

AVG. MAX. FLUENCE RATE: $1.97\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mw

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-492

POSITION : E-4

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2C-E

AVG. MAX. FLUENCE RATE : $2.28\text{E}+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mw

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-492

POSITION: E-4

MATERIAL: NICKEL

EXPERIMENT: 2C-E

AVG. MAX. FLUENCE RATE: $1.30E+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-493

POSITION : SE-1

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2B-SE

AVG. MAX. FLUENCE RATE : $3.48\text{E}+14$

40
AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-493

POSITION : SE-1

MATERIAL : NICKEL

EXPERIMENT : 2B-SE

AVG. MAX. FLUENCE RATE : $2.38\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-494

POSITION: SE-2

MATERIAL: 0.4970 %COAL

EXPERIMENT: 2B-SE

AVG. MAX. FLUENCE RATE: $3.50\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-494

POSITION: SE-2

MATERIAL: NICKEL

EXPERIMENT: 2B-SE

AVG. MAX. FLUENCE RATE: $2.47\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-495

POSITION : SE-3

MATERIAL : 0.4970 %COAL

EXPERIMENT : 28-SE

AVG. MAX. FLUENCE RATE : $3.65\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-495

POSITION : SE-3

MATERIAL : NICKEL

EXPERIMENT : 2B-SE

AVG. MAX. FLUENCE RATE : $2.52E+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-496

POSITION : SE-4

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2B-SE

AVG. MAX. FLUENCE RATE : $3.72\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-496

POSITION: SE-4

MATERIAL: NICKEL

EXPERIMENT: 2B-SE

AVG. MAX. FLUENCE RATE: $2.29\text{E}+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-497

POSITION : S-1

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2C-S

AVG. MAX. FLUENCE RATE : $3.13\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-497

POSITION: S-1

MATERIAL: NICKEL

EXPERIMENT: 2C-S

AVG. MAX. FLUENCE RATE: $2.34\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-498

POSITION : S-2

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2C-S

AVG. MAX. FLUENCE RATE : $3.28\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-498

POSITION: S-2

MATERIAL: NICKEL

EXPERIMENT: 2C-S

AVG. MAX. FLUENCE RATE: $1.18\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-499

POSITION : S-3

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2C-S

AVG. MAX. FLUENCE RATE : $3.12\text{E}+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-499

POSITION : S-3

MATERIAL : NICKEL

EXPERIMENT : 2C-S

AVG. MAX. FLUENCE RATE : $1.49\text{E}+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-500

POSITION: S-4

MATERIAL: 0.4970 %COAL

EXPERIMENT: 2C-S

AVG. MAX. FLUENCE RATE: $2.99\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mw

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-500

POSITION : S-4

MATERIAL : NICKEL

EXPERIMENT : 2C-S

AVG. MAX. FLUENCE RATE : $2.34E+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-501

POSITION: SW-1

MATERIAL: 0.4970 %COAL

EXPERIMENT: 2D-SW

AVG. MAX. FLUENCE RATE: $3.16E+14$

95
AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-501

POSITION : SW-1

MATERIAL : NICKEL

EXPERIMENT : 2D-SW

AVG. MAX. FLUENCE RATE : $1.93E+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mw

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-502

POSITION : SW-2

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2D-SW

AVG. MAX. FLUENCE RATE : 2.92×10^{14}

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mw

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-502

POSITION: SW-2

MATERIAL: NICKEL

EXPERIMENT: 2D-SW

AVG. MAX. FLUENCE RATE: $1.99\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-503

POSITION : SW-3

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2D-SW

AVG. MAX. FLUENCE RATE : $2.78\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-503

POSITION: SW-3

MATERIAL: NICKEL

EXPERIMENT: 2D-SW

AVG. MAX. FLUENCE RATE: $1.99\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mw

DATE : 04/23/93 - 05/13/93

MONITOR NO. : SR-504

POSITION : SW-4

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2D-SW

AVG. MAX. FLUENCE RATE : 2.98×10^{14}

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: SR-504

POSITION: SW-4

MATERIAL: NICKEL

EXPERIMENT: 2D-SW

AVG. MAX. FLUENCE RATE: $1.88\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: BR-505

POSITION: W-1

MATERIAL: 0.4970 %COAL

EXPERIMENT: 1C-W

AVG. MAX. FLUENCE RATE: $2.52\text{E}+14$

64
AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: BR-505

POSITION: W-1

MATERIAL: NICKEL

EXPERIMENT: 1C-W

AVG. MAX. FLUENCE RATE: $1.32\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : BR-506

POSITION : W-2

MATERIAL : 0.4970 %COAL

EXPERIMENT : 1C-W

AVG. MAX. FLUENCE RATE : $2.87\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : BR-506

POSITION : W-2

MATERIAL : NICKEL

EXPERIMENT : 1C-W

AVG. MAX. FLUENCE RATE : $1.79E+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : BR-507

POSITION : W-3

MATERIAL : 0.4970 %COAL

EXPERIMENT : 1C-W

AVG. MAX. FLUENCE RATE : $2.92\text{E}+14$

89
AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: BR-507

POSITION: W-3

MATERIAL: NICKEL

EXPERIMENT: 1C-W

AVG. MAX. FLUENCE RATE: $9.04\text{E}+13$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: BR-508

POSITION: W-4

MATERIAL: 0.4970 %COAL

EXPERIMENT: 1C-W

AVG. MAX. FLUENCE RATE: $2.31\text{E}+14$

AVERAGED VALUES OVER 2.8 DAYS REACTOR OPERATIONS AT 128.4 MW

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : BR-508

POSITION : W-4

MATERIAL : NICKEL

EXPERIMENT : 1C-W

AVG. MAX. FLUENCE RATE : $6.73\text{E}+13$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : H-202

POSITION : H-2

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2A-C

AVG. MAX. FLUENCE RATE : $2.09\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : H-202

POSITION : H-2

MATERIAL : NICKEL

EXPERIMENT : 2A-C

AVG. MAX. FLUENCE RATE : $1.35\text{E}+14$

THERMAL NEUTRON FLUENCE RATE (2200 m/s)

REACTOR : ATR

CYCLE : 100-BC

CYCLE POWER : 359.5 Mwd

DATE : 04/23/93 - 05/13/93

MONITOR NO. : H-203

POSITION : H-10

MATERIAL : 0.4970 %COAL

EXPERIMENT : 2A-C

AVG. MAX. FLUENCE RATE : $2.22\text{E}+14$

FAST NEUTRON FLUENCE RATE (> 1 MeV)

REACTOR: ATR

CYCLE: 100-BC

CYCLE POWER: 359.5 Mwd

DATE: 04/23/93 - 05/13/93

MONITOR NO.: H-203

POSITION: H-10

MATERIAL: NICKEL

EXPERIMENT: 2A-C

AVG. MAX. FLUENCE RATE: $2.05\text{E}+14$

DATE

FILMED

1 / 7 / 94

END