AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

DOE/PC/90180--T 11

RECEIVED
DOE/PETC
QUARTERLY REPORT
(03/01/94 to 06/30/94)

94 JUL -1 PM 3:22
ACQUISITION & ASSISTANCE DIV.

20/94

NUMERICAL STUDY OF THE FLOW OF GRANULAR MATERIALS DOWN AN INCLINED PLANE

Project Director : K. R. Rajagopal
Department of Mechanical Engineering
University of Pittsburgh
Pittsburgh, PA 15261

Contract No : DE-AC22-91PC90180

Contract Period : 12/13/1990 - 12/13/1994

Student(s) and the degree for which they are registered : Mr. R. Gudhe, (Ph.D)

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

870

SUMMARY

In the previous report the governing equations for the flow of granular materials down an inclined plane using the continuum model proposed by Rajagopal and Massoudi [cf. Goodman and Cowin (1971, 1972), Rajagopal and Massoudi (1990)] were derived. We studied the effect of the various forms of the materials parameters (β 's) on the velocity, volume fraction and temperature fields. In this report, we derive the governing equations for the flow of granular materials down an inclined plane using the kinetic theory based model proposed by Boyle and Massoudi (1990).

INTRODUCTION

A study indicated that the commercial and large-scale solids-processing plants have an average operating reliability of 63%, compared to 84% for large-scale plants using only liquids and gases [cf. Plasynski et al. (1992)]. Granular materials have both the properties of a solid and a fluid, as they can take the shape of the vessel containing them, thereby exhibiting fluid like characteristics, or they can be heaped, thereby behaving like a solid. Also, granular materials can sustain shear stresses in the absence of any deformation, and the critical stress at which shearing begins depends on the normal stress.

Due to their complexity, the modeling of granular materials would require a fusion of the ideas from solid, fluid and soil mechanics. Also granular materials, like non-Newtonian fluids and non-linearly elastic solids exhibit normal-stress differences in simple shear flow. Thus modeling granular materials and slurries is very complex, and has to draw upon experiences from non-linear fluid and solid theories. One approach used in modeling the mechanics of granular materials is the **continuum approach** and the other is the **kinetic theory approach**. Several models are proposed based on the continuum theory approach [cf. Goodman and Cowin (1971, 1972), Cowin (1974a, b), Massoudi and Boyle (1987), Passman et al. (1980), Ahmadi (1982a, b) and Rajagopal and Massoudi (1990)]. The key reason behind using a kinetic theory approach for granular materials is the analogy between a *grain* and a *molecule*. So as a first approximation, both gas molecules and granular materials can be considered single-sized hard spheres. If the flow of granular materials is rapid, it can be characterized by an average or continuum velocity about which the velocities of the individual grains change because of random collisions. Since such motion closely resembles a flowing gas, the ideas incorporated into the kinetic theory of gases have been applied to the rapid flow of granular material. However, the analogy between a gas and granular materials is not exact because the collisions between gas particles are energy conserving, whereas those between grains of material are energy dissipating. But the inelasticity of granular collisions prevents the theoretical methods developed for hard sphere gases from being directly applied to flowing granular materials. In order to calculate the macroscopic behavior of a flowing gas, only the probability of any two particles simultaneously occupying two given positions and exhibiting two specified velocities is needed; furthermore, if the fluid is dilute enough, all that is needed is the probability of any one particle being at a given position with a specified velocity. These ideas are more fully explained by utilizing the concept of a phase space [cf. McQuarrie (1976)]. Several

models have been proposed by various investigators using ideas of kinetic theory [cf. Ogawa et al. (1980), Jenkins and Savage (1983), Lun et al. (1984), Ahmadi and Shahinpoor (1984), Jenkins and Richman (1985), Boyle and Massoudi (1989)].

GOVERNING EQUATIONS

Boyle and Massoudi (1990) proposed a model which can exhibit normal-stress effects by including the effects of the gradient of the volume distribution function, which is the noticeable difference between the model proposed by Lun, Savage and co-workers (1984). The granular stress tensor $\mathbf{T}$ is the sum of the two terms, reflecting that momentum can be transported by the uninterrupted streaming of granules $\mathbf{T}_k$ and by the essentially instantaneous transport from one center to another during a collision $\mathbf{T}_c$. The granular stress tensor $\mathbf{T}$ follows from that of Lun et al. (1984), but there is an additional contribution to $\mathbf{T}$ from $\mathbf{M}$ (or $\mathbf{T}_m$) that is given by

$$\mathbf{T}_m = \frac{4}{5} \eta g_0 \rho \theta v \frac{V_0^{*2} d^2}{(1 - v V_0^*)^2} (2 \mathbf{M} + tr \mathbf{M} \mathbf{1}) \quad (1)$$

The stress tensor for a rapidly sheared granular material is found by summing the above individual contributions, which is given by

$$\begin{aligned} \mathbf{T} = & \left\{ \rho \theta (1 + 4 \eta v g_0) + \left(\frac{2 \mu}{3 \eta (2 - \eta) g_0} (1 + \frac{8}{5} \eta v g_0) \right. \right. \\ & \left. \left. \left\{ 1 + \frac{8}{5} \eta (3 \eta - 2) v g_0 \right\} - \frac{3}{5} \mu_b \eta \right) \nabla \cdot \mathbf{u} \right. \\ & \left. + \frac{4}{5} \eta v g_0 \rho \theta \frac{V_0^{*2} \bar{\sigma}^2}{(1 - v V_0^*)^2} tr \mathbf{M} \right\} \mathbf{1} \\ & - \left\{ \frac{2 \mu}{\eta (2 - \eta) g_0} (1 + \frac{8}{5} \eta v g_0) \left[1 + \frac{8}{5} \eta (3 \eta - 2) v g_0 \right] + \frac{6}{5} \mu_b \eta \right\} \mathbf{D} \\ & + \frac{8}{5} \eta g_0 \rho \theta v \frac{V_0^{*2} \bar{\sigma}^2}{(1 - v V_0^*)^2} \mathbf{M} \end{aligned} \quad (2)$$

$$\text{where, } \mu_b = \frac{256 \mu v^2 g_0}{5 \pi}; \quad \mu = \frac{5 m (\theta/\pi)^{1/2}}{16 d^2}$$

$$V_0^* = \frac{6 V_0}{\pi d^3}$$

$$\mathbf{M} = \nabla \mathbf{v} \otimes \nabla \mathbf{v}$$

where V_0 represents the volume per neighboring particle, θ is the granular temperature, v is the volume fraction, d is the diameter of the particle, m is the mass of the granule and g_0 is a function of volume fraction.

The conservation of mass is given by:

$$\frac{\partial \rho}{\partial t} + \text{div}(\rho \mathbf{u}) = 0, \quad (3)$$

where $\frac{\partial}{\partial t}$ is the partial derivative with respect to time. The balance of linear momentum is:

$$\rho \frac{D\mathbf{v}}{Dt} = \text{div} \mathbf{T} + \rho \mathbf{b}, \quad (4)$$

where $\frac{D}{Dt}$ is the material time derivative, $\mathbf{b}$ is the body force and $\mathbf{T}$ is the Cauchy stress tensor. The balance of angular momentum (in the absence of couple stresses) yields the result that the Cauchy stress is symmetric:

$$\mathbf{T} = \mathbf{T}^T \quad (5)$$

The pseudo-energy equation in its general form is given by [cf. Richman and Marciniec (1990)]

$$\text{tr}(\mathbf{T} \mathbf{D}) - \text{div} \mathbf{Q}_a - \gamma_a = \frac{3}{2} \rho \frac{d\theta}{dt}, \quad (6)$$

where $\mathbf{Q}_a$ is the flux of fluctuation energy, γ_a is the collisional rate per unit volume of energy dissipation. Here, for the problem under consideration, we assume [cf. Jenkins and Richman (1985)]

$$\mathbf{Q}_a = -\frac{5\mu}{2} M \nabla \theta \quad (7)$$

$$\gamma_a = \frac{15\mu(1-e)\theta}{d^2} \quad (8)$$

$$\text{where,} \quad M = 1 + \frac{9\pi}{32} \left(1 + \frac{5}{12G}\right)^2$$

$$G(v) = \frac{v(2-v)}{2(1-v)^3}$$

$$\mu = \frac{8 d \rho G \theta^{1/2}}{5 \pi^{1/2}}$$

Consider the flow of granular materials down an inclined plane modeled by the kinetic theory based model proposed by Boyle and Massoudi (1990) [cf. Figure 1] due to the action of gravity. The flow of granular materials down an inclined plane has been studied by several authors [cf. Goodman and Cowin (1971), Savage (1979), Hutter, Szidarovszky, and Yakowitz (1986a, b), Johnson and Jackson (1987)]. In this problem, we consider steady one-dimensional flow of incompressible granular materials (i.e., $\gamma = \text{constant}$) down an inclined plane, where the angle of inclination is α . Here, we assume the flow is a fully developed steady flow. The constitutive equation for the stress tensor is given by equation (2), and volume fraction, velocity, and granular temperature fields are assumed to be of the form

$$\begin{aligned} v &= v(y) \\ u &= U(y)i \\ \theta &= \theta(y) \end{aligned} \tag{9}$$

With the above assumptions, the conservation of mass is identically satisfied and the balance of linear momentum and the pseudo-energy in the non-dimensionalized form reduces to

$$\frac{d}{dy} \left(\beta_3 \sqrt{\bar{\theta}} \frac{d\bar{U}}{dy} \right) = -2 \left\{ \frac{h}{d} \right\}^{3/2} \sin \alpha \quad (10)$$

$$\frac{d}{dy} \left(\beta_0 \bar{\theta} + \left\{ \frac{d}{h} \right\}^2 \beta_{14} \bar{\theta} \left\{ \frac{dv}{dy} \right\}^2 \right) = -\frac{h}{d} \cos \alpha \quad (11)$$

$$\frac{d}{dy} \left(K \sqrt{\bar{\theta}} \frac{d\bar{\theta}}{dy} \right) = \left\{ \frac{h}{d} \right\}^2 \bar{\gamma}_a \bar{\theta}^{3/2} - \frac{1}{2} \left\{ \frac{h}{d} \right\} \beta_3 \sqrt{\bar{\theta}} \left\{ \frac{d\bar{U}}{dy} \right\}^2 \quad (12)$$

subject to the boundary conditions

$$\bar{U} = 0 \quad \text{at } \bar{y} = 0 \text{ (on the inclined plane)} \quad (13)$$

$$A_f = \int_0^1 v \, d\bar{y} \quad (\text{Value specified}) \quad (14)$$

and,

$$\frac{d\bar{U}}{d\bar{y}} = 0$$

$$\beta_0 \bar{\theta} + \left\{ \frac{d}{h} \right\}^2 \beta_{14} \theta \left\{ \frac{dv}{d\bar{y}} \right\}^2 = \bar{P}_s \left\{ \frac{h}{d} \right\}$$

$$\frac{d\bar{\theta}}{d\bar{y}} = 0 \quad \text{at } \bar{y} = 1 \text{ (on the free surface)} \quad (15)$$

$$\bar{\theta} = \bar{\theta}_f \quad (\text{Value specified})$$

$$\text{with,} \quad \bar{y} = \frac{y}{h}; \quad \bar{U} = \frac{U}{\sqrt{gh}}; \quad \bar{\theta} = \frac{\theta}{dg}; \quad \bar{P}_s = \frac{P_s}{\rho_p g h} \quad (16)$$

where h is a characteristic length (flow thickness), d stands for the diameter of the particle, P_s is the surface environmental pressure. Also, the coefficients depend upon the volume fraction which are given below

$$\beta_0 = (1 + 4\eta v g_0) v$$

$$\beta_{14} = \frac{12\eta g_0 V_0^{*2}}{5(1-V_0^*v)^2} v^2$$

$$\beta_3 = \frac{5\pi^{1/2}}{48\eta(2-\eta)g_0} \left\{ 1 + \frac{8}{5}\eta v g_0 \right\} \left\{ 1 + \frac{8}{5}\eta(3\eta-2)g_0 v \right\} + \frac{8}{5}\pi^{-1/2}\eta g_0 v^2$$

$$K = \frac{25\pi^{1/2}}{192} \left\{ 1 + \frac{\pi}{32} \left(1 + \frac{5(1-v)^3}{6v(2-v)} \right)^2 \right\}$$

$$\bar{\gamma}_a = \frac{48}{\pi^{1/2}} \eta(1-\eta)g_0 v^2 \quad (17)$$

$$\text{with,} \quad g_0 = \frac{V_0^*}{4(1-V_0^*v)}$$

$$\eta = \frac{1}{2} (1+e)$$

where, e is the co-efficient of restitution.

Numerical Results

The system of equations (10), (11), and (12) subject to the boundary conditions (13) through (15) are being solved numerically. The numerical results for the above governing equations will be presented in the next report.

Figure 1 Flow Down An Inclined Plane

REFERENCES

1. **Ahmadi, G. and M. Shahinpoor** "A Kinetic Model for Rapid Flows of Granular Materials," *Int. J. of Non-Linear Mech.*, 19: 177-186, 1984.
2. **Ahmadi, G.** "A Continuum Theory of Smectic Liquid Crystals," *J. Rheology*, 26: 535-566, 1982a.
3. **Ahmadi, G.** "A Generalized Continuum theory for Granular Materials," *Int. J. Non-Linear Mech.*, 17: 21-33, 1982b.
4. **Boyle, E.J. and M. Massoudi** "A Kinetic Theory Derivation of the Stress Tensor for Granular Material That Includes Normal Stress Effects," Technical Note, DOE/METC-90/4093, 1989.
5. **Boyle, E.J. and M. Massoudi** "A Theory for Granular Materials Exhibiting Normal Stress Effects Based on Enskog's Dense Gas Theory," *Int. J. of Engng. Sci.*, 28: 1261-1275, 1990.
6. **Cowin, S.C.** "A Theory for the Flow of Granular Material," *Powder Tech.*, 9: 61-69, 1974a.
7. **Cowin, S.C.** "Constitutive Relations that imply a Generalized Mohr-Coulomb Criterion," *Acta Mechanica*, 20: 41-46, 1974b.
8. **Goodman, M.A. and S.C. Cowin** "Two Problems in the Gravity Flow of Granular Materials," *J. Fluid Mech.*, 45: 321-339, 1971.
9. **Goodman, M.A. and S.C. Cowin** "A continuum Theory for Granular Materials," *Arch. Rat. Mech. and Anal.*, 44: 249-266, 1972.
10. **Hutter, K., F. Szidarovszky, S. Yakowitz** "Plane Steady Shear Flow of a Cohesionless Granular Material Down an Inclined Plane: A Model for Flow Avalanches Part-I: Theory," *Acta Mechanica*, 63: 87-112, 1986a.
11. **Hutter, K., F. Szidarovszky, S. Yakowitz** "Plane Steady Shear Flow of a Cohesionless Granular Material Down an Inclined Plane: A Model for Flow Avalanches Part-II: Numerical Results," *Acta Mechanica*, 65: 239-261, 1986b.
12. **Jenkins, J.T. and S.B. Savage** "A Theory for the Rapid Flow of Identical, Smooth, Nearly Elastic, Spherical Particles," *J. Fluid Mech.*, 130: 187-202, 1983.
13. **Jenkins, J.T. and M.W. Richman** "Grad's 13-Moment System for a Dense Gas of Inelastic Spheres," *Arch. Rat. Mech. and Anal.*, 87: 355- 377, 1985.
14. **Johnson, P.C., and R. Jackson** "Frictional-Collisional Constitutive Relations for Granular Materials with Application to Plane Shearing," *J. Fluid Mech.*, 176: 67-93, 1987.
15. **Lun, C.K.K., S.B. Savage, D.J. Jeffrey and N. Chepurnity** "Kinetic Theories for Granular Flow: Inelastic Particles in Couette Flow and Slightly Inelastic Particles in a General Flow Field," *J. Fluid Mech.*, 140: 223-256, 1984.

16. **Massoudi, M., and E.J. Boyle** "Continuum Theories of Granular Materials with applications to fluidized beds," Technical Report, U.S. Department of Energy Report, DOE/METC-88/4077, 1987.
17. **McQuarrie, V.V.** *Statistical Mechanics*, Haper and Row, New York, 1976.
18. **Ogawa, S., A. Umemura and N. Oshima** "On the Equations of Fully Fluidized Granular Materials," *J. Appl. Math. and Physics*, 31: 483-493, 1980.
19. **Passman, S.L., J.W. Nunziato, P.B. Bailey and J.P. Thomas, Jr.** "Shearing Flows of Granular Materials," *J. Engrg. Mech. Div.*, ASCE, 106: 773-783, 1980.
20. **Plasynski, S.I., W.C. Peters, and S.L. Passman** "The Department of Energy Solids Transport, Multiphase Flow Program," *Proceedings of the NSF-DOE Joint workshop on Flow of Particulates and Fluids*, Gaithersburg, September 16-18, 1992.
21. **Rajagopal, K.R. and M. Massoudi** "A Method for Measuring Material Moduli of Granular Materials: Flow in an Orthogonal Rheometer," DOE/PETC/ TR-90/3, 1990.
22. **Richman, M.W., and R.P. Marciniec** "Gravity-Driven Granular Flows of Smooth, Inelastic Spheres Down Bumpy Inclines," *Transactions of ASME*, 57: 1036-1043, 1990.
23. **Savage, S.B.** "Gravity Flow of Cohesionless Granular Materials in Chutes and Channels," *J. Fluid Mech.*, 92: 53-96, 1979.

DATE

FILMED

10 / 5 / 94

END