DECLASSIFIED

HW-55269

Undocumented

copy!

DISTRIBUTION

~~RESTRICTED DATA~~

~~This document contains restricted data as defined in the Atomic Energy Act of 1954. Its transmission or the disclosure of its contents in any manner to an unauthorized person is prohibited.~~

1. J. M. Batch
2. J. L. Benson
3. R. E. Hall
4. G. M. Hesson/D. E. Fitzsimmons
5. L. H. McEwen
6. R. W. Reid
7. R. H. Gay
8. K. G. Toyoda/W. L. Thorne
9. F. W. Van Wormer
10. E. D. Waters
11. R. E. Trumble
- 12-14 Extra
15. Record Center
16. File Copy

This document classified by

J. M. Batch
J. M. Batch

Classification Cancelled and Changed To

DECLASSIFIED

March 7, 1958

By Authority of CG-PR-2

DS LEWIS 12-15-92

By Am Eck 4-26-94

Verified By J. H. Wells 4-26-94

LABORATORY PRESSURE DROP DATA FOR SUPPORT CHARGES USING PIERCED-SOLID DUMMY SLUGS - ALL REACTORS

E. D. Waters

INTRODUCTION AND PURPOSE

This report presents Hydraulics Laboratory data of the pressure drop characteristics for various combinations of 'pierced-solid' dummy slugs in the support charges in the three normal reactor process tubes. 'Pierced-solid' slugs are regular solid aluminum dummy slugs which have been concentrically drilled so that mating against an I & E slug would not block the hole flow channel. ✓

SUMMARY

Dummy section pressure drop comparisons are presented on Figures 1, 2, and 3 for K, BDF, and C reactors, respectively. 'Pierced-solid aluminum dummy slugs (1.438" O.D. by 0.51" I.D. by 8" long) were used in various combinations to produce an increased pressure drop across the dummy charge. No operating peculiarities were observed while using 'pierced-solids' in the support charge.

DISCUSSION OF RESULTS

Tests were conducted using standard process tubes and outlet assemblies. Data were first obtained for standard downstream dummy (support) charges consisting of the following pieces front to rear:

K

3 - 8" expendable perfs
9 - 8" tubulars
2 - 5" expendable perfs

BDF and C

3 - 8" expendable perfs
9 - 8" tubulars
1 - 5" expendable perf
2 - 8" expendable perfs

MASTER

DECLASSIFIED

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, make any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

DECLASSIFIED

HW-55269
Undocumented

(In the actual tests, the total length of the tubulars was adjusted by a few inches in order to adjust the uranium-to-dummy junction to fit existing pressure taps. Slight changes of the tubular charge length does not cause a detectable change in pressure drop as determined by previous tests.)

Static pressures were measured at the EOAS (end-of-active-section) and at the RNB (rear nozzle barrel).

Pressure drop data are shown on Figures 1, 2, and 3 for the various combinations of dummy charge. The charge and the water temperature are shown for each curve on the figures. There is no known explanation for the pressure drop being higher with a standard C dummy than for either a BDF or K dummy except that reproducibility of these low ΔP data is known to be poor from one charge to another. The RNB tap on a C rear nozzle is at a point where there is flow past the pressure tap whereas there is no flow past the RNB pressure tap on the K and BDF tubes. The velocity head (due to kinetic energy of the fluid) would amount to about 0.57 psi at 60 gpm for the C tube; applying this correction would help bring the curve for a standard C dummy nearer to the curves for K and BDF, but the C curve would still be slightly higher than expected.

The pressure drop for the various new dummy charge combinations are about what might be expected; K tube gives lowest ΔP with C tube slightly higher and the BDF tube the highest ΔP . For charges where a 'pierced-solid' is against the tubular section, the ΔP curve is unpredictable as shown on Figure 1 by +. A 'pierced-solid' at the downstream end of the tubulars showed data near curve E in one case and when recharged at a different time showed data near curve D. This is not surprising, however, since some degree of interjunction flow is involved. It has been demonstrated in I & E slug plugging studies that interjunction flow is quite unpredictable.

Figure 4 illustrates two special effects which were investigated. Curves D and E represent the difference in ΔP when two 'pierced-solid' slugs are separated from each other and from tubulars by first one and then three perfs, respectively, in a C tube.

Comparison of curves A and B for a K tube or curves C and D for a C tube shows the effect of temperature on the dummy section pressure drop. The temperature effect would be about the same for the BDF tube. For the case of a standard dummy charge, the ΔP is about 1 psi less (at 50 gpm) for hot (110°C) than for cold (15°C) water flow.

E.D. Waters, Engineer
Thermal Hydraulics Operation
HANFORD LABORATORIES OPERATION

ED Waters:sjl

DECLASSIFIED

DECLASSIFIED

Undocumented

Dummy Section Pressure Drop K Tube

Basis: I & W Slugs-Cold Isothermal Flow

DECLASSIFIED

DECLASSIFIED

MM-55269
Undocumented

Figure 2

Dummy Section Pressure Drop RDP Tube

Notes: I & E Slugs-Cold Isothermal Flow

DECLASSIFIED

DECLASSIFIED

NW-10210

Undocumented

Figure 3

Dummy Section Pressure Drop C Tube

Basis: I & E Slugs-Cold Isothermal Flow

DECLASSIFIED

DECLASSIFIED

NW-55269
Undocumented

Figure 4

Special Effects

DECLASSIFIED