Savannah River Site Environmental Report for 1991 (U)

Margaret W. Arnett *Margaret W. Arnett*
Linda K. Karapatakis *L. Karapatakis*
Albert R. Mamatey *Albert R. Mamatey*
James L. Todd *James L. Todd*

UNCLASSIFIED

DOES NOT CONTAIN
UNCLASSIFIED CONTROLLED
NUCLEAR INFORMATION

ADC &
Reviewing
Official:

Official:

Date:

C. Banick, Asst. Chief of
(Name and Title)
6/30/92

The monitoring data in this report are certified as valid for the 1991 calendar year, and the report has been approved for publication by the following officials:

J.D. Heffner
J.D. Heffner, Manager
Environmental Monitoring Section

Robert Lorenz
R. Lorenz, Manager
Environmental Publications and Data Evaluation
Environmental Monitoring Section

Prepared for the U.S. Department of Energy under contract No. DE-ACO9-89SR18035
Westinghouse Savannah River Company, Environmental Monitoring Section,
Environmental Protection Department
Savannah River Site, Aiken, SC 29808

MASTER

EP

Acknowledgements

- ◆ Acknowledgement is given to Radiological Assessments Corporation for the role it played in preparing the *Savannah River Site Environmental Report for 1991*. The authors specifically acknowledge the support of John Till, Susan Rope, Larry Bell, Duane Schmidt, Marilyn Case, Lisa Stetar, Kathleen Meyer, Paul Voillequé, and George Killough. Their professional support in the areas of data interpretation, graphical presentation of data, monitoring design, dose assessment, and public communication, continues to improve the quality of this report.
- ◆ The authors appreciate the efforts of the following individuals and groups who contributed technical data and information for specific chapters in the report.
  - Gail Jernigan and Celest Mooney (Chapter 2, "Environmental Compliance")
  - Bill Carlton and Walt Marter (Chapter 6, "Calculating Radiation Doses")
  - Robert Turner (Chapter 7, "Air Pathways," and Chapter 8, "Water Pathways")
  - Academy of Natural Sciences of Philadelphia (Chapter 11, "Special Surveys")
- ◆ Listed below are other individuals who provided expert printing, reproduction, design, and layout support.

Stephanie Doestch (design, printing)	Wanda Dunn (offsite printing)
Ed Landry (illustrating)	Tom Huckabee (reproduction)
Don Lechner (genographics)	Carol Attaway
Helena Thomas	
- ◆ The review and approval process requires dedication and support within both WSRC and DOE-SR. A special thanks to Dan Zweifel for coordinating the DOE-SR review and approval process. In addition, the persons listed below gave extra time and effort to ensure the report was reviewed and approved for release.

Cy Banick, WSRC	Mina Perrin, DOE-SR
Jack Duschinski, WSRC	
- ◆ A text team reviewed each chapter of the report to verify the technical and programmatic accuracy of the information presented. Text team members included the following:

Larry Eldridge	Craig Hetrick	Bill Littrell
Carol Cummins	Natalie Park	
- ◆ Thank you to the following individuals who provided data and reviewed the data tables:

Bob Henderson	Lynne Geary	Bill Carlton
Larry Eldridge	Craig Hetrick	Brian Crandall
Dave Filler	Moheb Khalil	Walt Marter
Pete Fledderman	Robin Young	Roger Wong
- ◆ Thank you to Dawn Haygood of WSRC Public Relations, Environmental Outreach, for updating the external distribution list and conducting a business reply mail-out to improve report distribution.
- ◆ A special thanks to Chris Wickham for providing computer support.

Preface

The *Savannah River Site Environmental Report for 1991* documents environmental activities conducted on and in the vicinity of the Savannah River Site (SRS) in Aiken, S.C., from Jan. 1 to Dec. 31, 1991, with an update on compliance activities through April 1, 1992. The 300-square-mile site is a Department of Energy (DOE) facility managed by the Westinghouse Savannah River Company (WSRC), which was the site's primary contractor during 1991.

SRS conducts environmental surveillance and effluent monitoring to meet requirements of DOE Orders and to comply with state and federal environmental regulations. Chapter III of DOE Order 5400.1 requires the publication of an annual environmental report by June 1 of each year to inform the public of the impact of facility operations on the environment and public health.

BACKGROUND

SRS has had an extensive environmental surveillance program in place since 1951 (before startup). At that time, data generated by the onsite surveillance program were reported in site documents. Beginning in 1959, data from offsite environmental monitoring activities were presented in reports issued for public dissemination. Separate reporting of SRS's onsite and offsite environmental monitoring activities continued until 1985, when data from both surveillance programs were merged into a single publication.

REPORT FORMAT

The present *Savannah River Site Environmental Report for 1991* is a single volume with a separate summary pamphlet highlighting the major findings for 1991. The report is divided into an executive summary and 14 chapters containing information on environmental compliance issues, environmental monitoring methods and programs, and environmental research activities for 1991, as well as historical data from previous years. Analytical results, figures, charts, and data tables relevant to the environmental monitoring program for 1991 at SRS are included.

Organization of chapters

The first three chapters present an overview of SRS's location and operations, discuss environmental compliance at the site from Jan. 1, 1991, through April 1, 1992, and integrate the objectives and rationale of the SRS environmental monitoring program with information on the important radionuclides and key pathways for releases from SRS.

The next three chapters cover monitoring methods of the SRS environmental monitoring program, such as collection and analysis of environmental samples and interpretation of data from those analyses; quality assurance and quality control measures within the monitoring program; and an explanation of how offsite radiation doses to the public resulting from SRS operations are calculated.

Actual monitoring details, located in the next five chapters, are organized by environmental pathways to better integrate the results from different environmental media. With this approach, the monitoring of air, rainwater, soil, penetrating radiation, vegetation, and food products is included as subsections of Chapter 7, "Air Pathways." Chapter 8, "Water Pathways," includes monitoring details for surface water, sediment, drinking water, and groundwater in four major subsections. Monitoring results, data tables, and figures relevant to both air and water pathways are located here. Chapter 9 contains material on wildlife monitoring surveys conducted during the year, and Chapters 10 and 11 focus on nonroutine occurrences and special surveys.

The last three chapters of the report offer an inside look at environmental research conducted by various WSRC organizations at the Savannah River Laboratory (SRL), by the University of Georgia at the Savannah River Ecology Laboratory (SREL), and by the U.S. Forest Service at the Savannah River Forest Station (SRFS).

How to read the report

Each chapter in the report begins with a short, boxed listing of major topics and accompanying page numbers, followed by a section listing chapter

highlights. Special boxed summaries within the text, called "sidebars," add auxiliary information for the reader that is pertinent to the chapter topics. All monitoring data relevant to the chapter topics are listed as "Tables" at the end of each chapter. Data listed within the text are presented in "Charts." Figures, which are also contained within the text, depict graphic illustrations of sample locations, data, and/or other text information.

In addition, the 1991 SRS environmental report includes several supplementary sections in the front and back that provide extra detail and information. Acronyms used in the report are listed behind the Table of Contents. The appendices in the back of the report contain a listing of SRS environmental permits, radionuclide and chemical nomenclature, federal drinking water standards, SRS environmental highlights since site startup, and a section stating errata for the 1990 report. The final appendix lists the 1991 distribution list, which includes government officials, members of congress, DOE facilities and headquarters personnel, universities, environmental and civic groups, and the media. A glossary of technical terms and an index located in the back conclude this report.

The tables present summaries of the types of data listed as follows:

- federal and state standards and guides applicable to SRS operations
- information on sample aliquots and lower limits of detection for specific analyses
- concentrations of radioactivity in environmental media
- quantities of radioactivity released to the environment from SRS operations
- calculated offsite radiation doses which result from SRS operations
- measurements of physical properties, chemicals, and metals concentrations in environmental media

- interlaboratory comparisons of various analytical results

The figures and tables in this report contain information about the routine environmental monitoring program at SRS unless otherwise indicated. No attempt has been made to include all data from environmental research programs.

Variations in the report's content from year to year reflect changes in the routine environmental monitoring program or the inability to obtain certain samples from a specific location.

The following items will aid the reader in interpreting the data in this report:

- The uncertainty term is reported with up to—but no more than—three significant figures. The result is reported with up to three significant figures, with the last significant figure determined by the quantification of the uncertainty term. EMS attempted to report the appropriate confidence in the result with the correct number of significant figures.
- The reported uncertainty reflects only the counting error—not other components of random and systematic error present in the measurement process. For this reason, some results may imply a greater confidence than the determination would suggest.
- Uncertainties quoted with means represent the deviation of measurements about the mean value. This number is calculated from the results themselves, not from the uncertainties of the individual results.
- For gamma-emitting radionuclides, less-than-detectable values are represented as "<" the lower limit of detection (LLD) for that measurement. For all other analyses, a value is reported although it may be below the LLD for that analysis. Negative values are also reported. Tables 4-2 through 4-6 provide the LLDs for analyses performed by EMS.
- Averages were calculated using both positive and negative results. However, results reported as <LLD (gamma-emitting radionuclides) were not considered in the averages.

Contents

List of Charts	vii
List of Figures	ix
List of Tables	xv
Acronyms	xxv
Executive Summary	xxvii
Chapter 1. Site and Operations Overview	1
Description of the Savannah River Site	1
Description of SRS Operations and Facilities	3
Description of Environmental Monitoring Programs	8
Description of Environmental Research and Service	8
Environmental Program Information	9
Chapter 2. Environmental Compliance	13
Introduction	13
Compliance Status	13
Environmental Permits	21
Appraisals and Surveillances of Environmental Programs	21
Current Issues and Actions	22
Compliance Summary for Jan. 1 to April 1, 1992	25
Chapter 3. Environmental Monitoring Perspectives, Objectives, Rationale	29
Introduction	29
Program Basis	29
Objectives	29
Design Criteria	31
Perspectives on Radiation Exposures	39
Perspectives on Chemical Exposures	41
Chapter 4. Sample Collection, Analytical Procedures, and Data Interpretation	43
Introduction	43
Program Changes in 1991	44
Radiological Monitoring	45
Radiological Sample Collection and Analytical Procedures	47
Interpretation of Reported Radiological Monitoring Data	55
Nonradiological Sample Collection and Analysis	59

Chapter 5. Quality Assurance/Quality Control	73
Introduction	73
EMS QA/QC Program Guidelines	73
QA/QC Results for EMS Laboratories	75
QA/QC Results for Subcontracted Laboratories	77
Chapter 6. Calculating Radiation Doses	101
Introduction	101
Radiation Dose Terminology: Definitions and Units	101
Applicable Dose Standards	105
SRS Offsite Dose Calculations	106
Dose Calculation Models	107
Chapter 7. Air Pathways	125
Introduction	125
Radiological Air Monitoring	126
Nonradiological Air Monitoring	132
Rainwater	133
Soil	135
Penetrating Radiation	136
Vegetation	138
Food Products	140
Chapter 8. Water Pathways	199
Introduction	199
Surface Water	200
Nonradiological Water Monitoring	211
Sediment	214
Drinking Water	216
Groundwater	221
Chapter 9. Wildlife Monitoring	443
Introduction	443
Radiological Monitoring	443
Doses to the Public from Wildlife Consumption	448
Doses to Native Aquatic Animal Organisms	449
Nonradiological Monitoring	449
Chapter 10. Nonroutine Occurrences	469
Introduction	469
772-F Contamination – April 1991	470
Twin Lakes Dam Failure – Aug. 1-2, 1991	470
H-Area Waste Management Facilities – Sept. 23-30, 1991	471
K-Reactor Tritium Release – Dec. 22-25, 1991	472

Chapter 11. Special Surveys	479
Introduction	479
Radiological Monitoring Surveys	479
Nonradiological Surveys	486
Chapter 12. Savannah River Laboratory	527
Introduction	527
Environmental Research Projects	527
Seismic and Geoscience Research Projects	531
Operations Support Projects	534
Chapter 13. Savannah River Ecology Laboratory	535
Introduction	535
Biogeochemical Ecology	536
Wildlife Ecology and Toxicology	537
Wetlands Ecology	539
Environmental Outreach and Education	540
Chapter 14. Savannah River Forest Station	541
Introduction	541
Natural Resource Management Planning and Operations	541
Southeastern Forest Experiment Station Studies	544
National Environmental Research Park Activities	544
References	545
Glossary	551
Appendix A: SRS Environmental Permits	A-1
Appendix B: Radionuclide and Chemical Nomenclature	B-1
Appendix C: Drinking Water Standards	C-1
Appendix D: Environmental Monitoring Reports	D-1
Appendix E: SRS Environmental Highlights	E-1
Appendix F: Errata	F-1
Appendix G: Distribution List for the SRS Environmental Report	G-1
Index	i

List of Charts

Chart 2-1.	Key Federal Regulations that SRS Must Follow	14
Chart 2-2.	Waste Units Undergoing RCRA Closure during 1991	15
Chart 2-3.	SRS Construction and Operating Permits	21
Chart 3-1.	Radionuclides Released to Air from SRS during 1986-1990	32
Chart 3-2.	Radionuclides Entering the Savannah River during 1986-1990	34
Chart 3-3.	Properties of Most Important Radionuclides Released from SRS between 1986 and 1990	36
Chart 3-4.	Comparison and Description of Various Radiation Dose Levels	42
Chart 5-1.	Elements of the ANSI/ASME NQA-1 QA Program Requirements for Nuclear Facilities	74
Chart 5-2.	Conductivity and pH Measurements	77
Chart 5-3.	Laboratories Subcontracted to EMS in 1991	78
Chart 5-4.	EPA Water Pollution Study for 1991	79
Chart 6-1.	Hypothetical Calculation of Committed Effective Dose Equivalent	103
Chart 6-2.	Internal Dose Factors for an Adult	104
Chart 6-3.	Radiation Dose Limits for Exposure of the Public to Releases from DOE Facilities	105
Chart 6-4.	Offsite Dose Calculations for SRS Releases: Receptors and Assumptions	106
Chart 7-1.	1991 Atmospheric Releases, Calculated Concentrations at Site Boundary, and Derived Concentration Guides	128
Chart 7-2.	Calculated Maximum Individual Dose Commitment from SRS Atmospheric Releases in 1991	129
Chart 7-3.	Average 1989, 1990, and 1991 Gross Alpha and Nonvolatile Beta Measured in Air	131
Chart 7-4.	1987-1991 SRS Atmospheric Tritium Releases and Average Measured Tritium Concentrations in Air	132
Chart 7-5.	SRS Power Plant Boiler Capacities	132
Chart 7-6.	Nonradiological Air Emissions Standards	133
Chart 7-7.	Nonradiological Air Emissions for 1991	133
Chart 7-8.	Average 1989, 1990, and 1991 Gross Alpha and Nonvolatile Beta in Rainwater Deposition ..	135
Chart 7-9.	Comparison of 1990 and 1991 TLD Environmental Penetrating Radiation Measurements ...	139
Chart 7-10.	Maximum and Minimum Tritium Concentrations in Vegetation	139
Chart 7-11.	Monitoring Data for Milk	144
Chart 8-1.	1991 Direct Discharges of Radioactive Liquid Effluents by Source	200
Chart 8-2.	Radioactive Liquid Releases from SRS and Comparison of Downriver Concentrations to DOE-Derived Concentration Guides	204
Chart 8-3.	Calculated Maximum Individual Dose Commitment from SRS Liquid Releases in 1991	205
Chart 8-4.	Average Concentration of Radioactivity in Offsite and SRS Stream Water	209
Chart 8-5.	South Carolina Water Quality Standards (Class B Waters)	213

List of Charts

Chart 8-6.	EPA Drinking Water Standards for Radionuclides	218
Chart 8-7.	Average Gross Alpha and Nonvolatile Beta Activities in Drinking Water	218
Chart 8-8.	EPA Drinking Water Standards for Nonradiological Contaminants	220
Chart 8-9.	Comprehensive Analyses Constituents	226
Chart 9-1.	Radioactivity in Fish and Seafood	445
Chart 9-2.	Mercury in Fish	450
Chart 11-1.	Sampling Location and Rationale for Four Mile Creek Survey	486
Chart 11-2.	Maximum Levels of Radioactivity Measured during Four Mile Creek Survey	487
Chart 11-3.	ANSP Cursory Surveys in 1991	488

List of Figures

Figure 1-1.	SRS, approximately 300 square miles in area, is located about 25 miles southeast of Augusta, Ga., and 20 miles south of Aiken, S.C.	3
Figure 1-2.	SRS includes six major production areas, the Savannah River Ecology Laboratory, and the Savannah River Laboratory	5
Figure 1-3.	Pathways of atmospheric and liquid releases from SRS Areas	7
Figure 3-1.	Compliance with regulations and responding to public concern are two main reasons for environmental monitoring at SRS	30
Figure 3-2.	Importance of radionuclides to dose from atmospheric releases to the maximally exposed adult located on the SRS boundary.	33
Figure 3-3.	Importance of radionuclides to dose from liquid releases to a maximally exposed adult and the population during 1986-90	35
Figure 3-4.	Importance of pathways to maximum individual dose from airborne SRS releases.	37
Figure 3-5.	Average annual effective dose equivalent to people living in the CSRA	41
Figure 4-1.	EMCAP is EMS's new computer-based sample tracking system	44
Figure 4-2.	Environmental samples are measured for radioactivity through the general process shown ..	47
Figure 4-3.	SRS collects air samples in three different ways: with filter paper, a charcoal cartridge, and silica gel.	48
Figure 4-4.	The Isco sampler consists of a microprocessor-controlled peristaltic pump in weatherproof housing.	50
Figure 5-1.	Environmental monitoring system model quality assurance program	75
Figure 5-2.	EMS quality assessment program for monitoring performance of subcontracted laboratories	76
Figure 5-3.	Subcontracted analytical laboratories participated in quality control analyses comparison each quarter	80
Figure 6-1.	How SRS uses internal dose factors to calculate doses based on the intake of a radionuclide.	104
Figure 6-2.	Comparisons between mathematical models of radionuclide movement and actual measurements	108
Figure 6-3.	Radioactive materials in the air enter the human body through pathways ranging from direct radiation to food consumption	109

Figure 6-4.	Graph shows percentage of time wind blows toward each directional sector at SRS	110
Figure 6-5.	Wind speed and direction in the vicinity of SRS	111
Figure 6-6.	The primary SRL WIND System atmospheric transport model	112
Figure 6-7.	Radioactivity in streams, rivers, and groundwater can enter the human body through various pathways and relationships	113
Figure 7-1.	Location of air monitoring stations within 25 miles of SRS	130
Figure 7-2.	TLD measurements provide a quick and reliable method for determining penetrating radiation doses to the population within an 8,000-square-mile area of SRS	137
Figure 7-3.	Vegetation sampling locations inside the Solid Waste Disposal Facility	141
Figure 7-4.	Vegetation sampling locations outside the Solid Waste Disposal Facility	141
Figure 7-5.	Technicians collect milk and food samples from local dairies and farms within a 25-mile radius of SRS	142
Figure 7-6.	Measurements of tritium concentrations over a five-year period from locally collected milk reflect changes in atmospheric releases	143
Figure 8-1.	Direct releases of tritium to site streams	201
Figure 8-2.	Tritium migration from seepage basins to site streams	201
Figure 8-3.	Total tritium releases (direct and migration combined)	201
Figure 8-4.	Radionuclide migration from seepage basins to streams	202
Figure 8-5.	SRS monitors site streams and the Savannah River for radioactivity at selected locations . .	206
Figure 8-6.	Tritium accounts for 89.4 percent of the liquid dose downriver at two water treatment plants	207
Figure 8-7.	Tritium release summary, 1960-1991	211
Figure 8-8.	SRS streams and the Savannah River are monitored for water quality	212
Figure 8-9.	Sediment sampling locations	215
Figure 8-10.	SRS collects drinking water samples from 35 onsite facilities and 16 surrounding towns and cities	217
Figure 8-11.	Comparison of 1990 and 1991 tritium concentrations measured at downriver water treatment facilities (Beaufort-Jasper and Port Wentworth) versus those measured at North Augusta	219
Figure 8-12.	Facilities monitored by the SRS monitoring well network, with areas that have constituents exceeding DWS detected in 1991	265
Figure 8-13.	Potentiometric surface and horizontal groundwater flow directions of the Congaree-Four Mile zone at SRS during the first quarter of 1991	267

Figure 8-14.	Potentiometric surface and horizontal ground flow directions of the Cretaceous zone at SRS during the first quarter of 1991	268
Figure 8-15.	Construction diagram for water table and deeper zone monitoring wells	269
Figure 8-16.	Correlation chart for hydrostratigraphic and geologic units at SRS	270
Figure 8-17.	Geologic cross-section of Coastal Plain sediments at SRS	271
Figure 8-18.	Potentiometric map of the principal aquifer of Late Cretaceous age, October 1954, in the vicinity of SRS (after Siple, 1967, Plate 6)	272
Figure 8-19.	Contoured elevation of the water table at the Separations and Waste Management areas, February 1991	273
Figure 8-20.	Generalized hydrostratigraphic cross-section through the F-Area seepage basins	273
Figure 8-21.	Vertical gradient relationships between the Congaree-Four Mile and Cretaceous zones at SRS during the first quarter of 1991	274
Figure 8-22.	Areas and locations monitored for groundwater quality at SRS	275
Figure 8-23.	Groundwater monitoring at A and M areas and Silverton Road Waste Site	276
Figure 8-24.	Groundwater monitoring at A and M areas	277
Figure 8-25.	General extent of trichloroethylene in groundwater at A and M areas	278
Figure 8-26.	Groundwater monitoring at C Area	279
Figure 8-27.	Groundwater monitoring at K Area	280
Figure 8-28.	Groundwater monitoring at L Area	281
Figure 8-29.	Groundwater monitoring at P Area	282
Figure 8-30.	Groundwater monitoring at R Area	283
Figure 8-31.	Separations and waste management areas and nearby wells monitored for groundwater quality at SRS	284
Figure 8-32.	Groundwater monitoring near F-Area Canyon Building and F-Area Tank Farm	285
Figure 8-33.	Groundwater monitoring near F-Area seepage basins and F-Area Tank Farm	286
Figure 8-34.	Groundwater monitoring at the central part of H Area	287
Figure 8-35.	Groundwater monitoring near the Radioactive Waste Burial Grounds and H-Area seepage basins	288
Figure 8-36.	Groundwater monitoring at S Area, Y Area, Z Area, and nearby locations	289
Figure 8-37.	Groundwater monitoring at the northern part of E Area and the Radioactive Waste Burial Grounds	290

Figure 8-38.	Groundwater monitoring at Central Shops Area	291
Figure 8-39.	Groundwater monitoring at D Area	292
Figure 8-40.	Groundwater monitoring at the Chemicals, Metals, and Pesticides Pits	293
Figure 8-41.	Groundwater monitoring at Interim Waste Technology Site B	294
Figure 8-42.	Groundwater monitoring at Interim Waste Technology Sites P and Q and the Kato Road and Lower Kato Road Sewage Sludge Application sites	295
Figure 8-43.	Groundwater monitoring at Par Pond	296
Figure 8-44.	Groundwater monitoring at the Road A Chemical Basin and the 40-Acre Hardwood Sewage Sludge Application Site	297
Figure 8-45.	Groundwater monitoring at the Sanitary Landfill and the Orangeburg Sewage Sludge Application Site	298
Figure 8-46.	Groundwater monitoring at Road F and Sandy (Lucy) Sewage Sludge Application sites. . .	299
Figure 8-47.	Trichloroethylene concentrations at the water table beneath TNX Area	300
Figure 8-48.	Cut-away view of trichloroethylene plume beneath TNX Area, showing extent of plume above 0.05 mg/L in the upper saturated zone and Congaree-Four Mile zone beneath TNX Area	301
Figure 8-49.	Groundwater monitoring at TNX Area	302
Figure 9-1.	SRS collects fish along the Savannah River above the site, adjacent to the site, and at the river mouth	444
Figure 9-2.	SRS has compared Cs-137 in deer from the SCCP hunting camp since 1968.	447
Figure 10-1.	If a nonroutine release is suspected, SRS follows a specific sampling and analysis regime	470
Figure 10-2.	Map shows the locations where samples were taken following the September 1991 liquid release of cesium and strontium at the H-Area waste management facilities	471
Figure 10-3.	Map shows path followed by tritium from K Area to the Savannah River estuary after December 1991 release	473
Figure 11-1.	Map shows air and land monitoring locations established for a special sampling program conducted during the 1991 drawdown of Par Pond	481
Figure 11-2.	Radioactivity released from SRS operations contaminated the Savannah River Swamp between Steel Creek and Little Hell Landing during the 1960s	482
Figure 11-3.	The Environmental Monitoring Section conducted a first-ever comprehensive survey of Four Mile Creek in 1990 to characterize the radiological condition of the stream and stream valley	485

Figure 11-4.	The Academy of Natural Sciences of Philadelphia has established specific sampling locations for surveys of the Savannah River	488
Figure 12-1.	Map pinpoints location of Pen Branch fault and other Savannah River Site basement faults	533

List of Tables

Table 1-1.	Onsite Operating Areas	12
Table 4-1.	General Radiological Sampling and Analysis Schedule	62
Table 4-2.	Lower Limits of Detection for Radiological Detection Instruments	64
Table 4-3.	Lower Limits of Detection for HPGE Gamma Analysis of Air Filters	65
Table 4-4.	Lower Limits of Detection for HPGE Gamma Analysis of River, Stream, and Rain Ion Columns	66
Table 4-5.	Lower Limits of Detection for HPGE Gamma Analysis of Water and Milk Samples	67
Table 4-6.	Lower Limits of Detection for HPGE Gamma Analysis of Vegetation, Soil, Wildlife, and Foods	68
Table 4-7.	Counting Geometries for Analysis of Gamma-Emitting Radionuclides	69
Table 4-8.	Sample Media Data	70
Table 4-9.	General Nonradiological Sampling and Analysis Schedule	71
Table 5-1.	Blind Sample Results for Conductivity Field Measurements	81
Table 5-2.	Blind Sample Results for pH Field Measurements	82
Table 5-3.	EMS Blind Sample Results for Tritium	83
Table 5-4.	EMS Blind Sample Results for Gamma-Emitting Radionuclides	84
Table 5-5.	EMS Blind Sample Results for Gross Alpha and Beta	85
Table 5-6.	QAD Interlaboratory Comparison of Analytical Results	86
Table 5-7.	QAP Interlaboratory Comparison of Analytical Results	88
Table 5-8.	NPDES Blind Sample Results	90
Table 5-9.	NPDES Duplicate Sample Results	91
Table 5-10.	Interlaboratory Quality Assessment Program	97

List of Tables

Table 5-11.	Results of Metals Analysis on Split Quarterly Composites	99
Table 5-12.	Results of Metals Analysis on Split Duplicate and Blind Quarterly Composites	100
Table 6-1.	Adult Intake and Usage Parameters for Atmospheric Dose Calculations	115
Table 6-2.	Adult Intake and Usage Parameters for Liquid Dose Calculations	116
Table 6-3.	50-Mile-Radius (80 km) Milk, Meat, and Vegetation Production Around SRS	117
Table 6-4.	50-Mile-Radius (80 km) Population Distribution Around SRS	119
Table 6-5.	Input Parameters for Atmospheric Transport Model	120
Table 6-6.	Meteorological Data for 1982-1986	121
Table 6-7.	Site Parameters Used in Liquid Dose Calculations	123
Table 7-1.	1991 Atmospheric Releases by Source	145
Table 7-2.	Maximum Individual Committed Dose at Site Perimeter from Atmospheric Releases with Consumption of Cow Milk	146
Table 7-3.	Maximum Individual Committed Dose at Site Perimeter from Atmospheric Releases with Consumption of Goat Milk	147
Table 7-4.	Average Individual Committed Dose at Site Perimeter from Atmospheric Releases with Consumption of Cow Milk	148
Table 7-5.	50-Mile (80-km) Collective Committed Dose from Atmospheric Releases	149
Table 7-6.	1991 NESHAP Report Data–CAP88 Compared With MAXIGASP	150
Table 7-7.	1991 NESHAP Report Data–CAP88 Compared With POPGASP	151
Table 7-8.	Radioactivity in Air	152
Table 7-9.	Tritium in Atmospheric Moisture	156
Table 7-10.	Rainwater Deposition of Radionuclides	158
Table 7-11.	Tritium in Rainwater	161
Table 7-12.	Radioactivity in Soil	162
Table 7-13.	Onsite TLD Environmental Gamma Radiation Measurements	163
Table 7-14.	Site Perimeter TLD Environmental Gamma Radiation Measurements	167
Table 7-15.	Concentric Ring TLD Environmental Gamma Radiation Measurements	173

Table 7-16.	South Carolina TLD Environmental Gamma Radiation Measurements	175
Table 7-17.	Georgia TLD Environmental Gamma Radiation Measurements	178
Table 7-18.	Radioactivity in Vegetation	180
Table 7-19.	Radioactivity in Seepage and Retention Basin Vegetation	185
Table 7-20.	Radioactivity in Vegetation inside the Solid Waste Disposal Facility Fences	186
Table 7-21.	Radioactivity in Vegetation outside the Solid Waste Disposal Facility Fences	188
Table 7-22.	Radioactivity in Milk	190
Table 7-23.	Radioactivity in Food	191
Table 8-1.	Estimated Tritium Releases in SRS Streams and the Savannah River	303
Table 8-2.	Calculated Migration of Radioactivity from Seepage Basins	305
Table 8-3.	Radioactivity in Transport at Sample Points on Four Mile Creek	306
Table 8-4.	Maximum Individual Committed Dose from Liquid Releases	307
Table 8-5.	Individual Committed Dose from Public Water Supplies at Beaufort-Jasper	308
Table 8-6.	Individual Committed Dose from Public Water Supplies at Port Wentworth	309
Table 8-7.	Collective Dose from Liquid Releases	310
Table 8-8.	Potential Doses from Irrigation Pathway	311
Table 8-9.	Radioactivity in Savannah River Water	312
Table 8-10.	Radioactivity in SRS Stream Water	315
Table 8-11.	Radioactivity in Seepage Basin Water	322
Table 8-12.	Tritium Releases Summary, 1960-1991	323
Table 8-13.	NPDES Sampling Points and Effluent Composition for Permit SC 0000175	324
Table 8-14.	NPDES Sampling Points and Effluent Composition for Permit SC 0044903	329
Table 8-15.	National Pollutant Discharge Elimination System Monitoring Data	330
Table 8-16.	NPDES Exceedances During 1991	343
Table 8-17.	Savannah River Water Quality	344
Table 8-18.	Fecal Coliform Bacteria in SRS Streams and the Savannah River	347

Table 8-19.	SRS Stream Water Quality: Herbicides and Volatile Organics	348
Table 8-20.	SRS Stream Water Quality	349
Table 8-21.	Herbicides in Stream and River Water	358
Table 8-22.	Temperature Profile Surveys on Beaver Dam Creek and Steel Creek	361
Table 8-23.	Radioactivity in River and Stream Sediment	362
Table 8-24.	Herbicides in Stream and River Sediment	365
Table 8-25.	Radioactivity in Drinking Water	368
Table 8-26.	Drinking Water Analysis Results for Residual Chlorine and Total Coliform	375
Table 8-27.	Chlorocarbon Monitoring Results from A-Administration Area Wells	376
Table 8-28.	SRS Drinking Water Chlorocarbon Monitoring Results	377
Table 8-29.	Maximum Volatile Organic Compound and Unregulated Organic Compound Levels in SRS Drinking Water	378
Table 8-30.	SCDHEC Chemical Analysis Results for SRS Drinking Water	379
Table 8-31.	Surface Water Treatment Plant Self-Monitoring Results for 400-D Area	381
Table 8-32.	Comprehensive Analyses Results for SRS Drinking Water Systems	382
Table 8-33.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the A-Area Burning Rubble Pits	397
Table 8-34.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the A-Area Coal Pile Runoff Containment Basin	397
Table 8-35.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the A-Area Metals Burning Pit	398
Table 8-36.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the M-Area Hazardous Waste Management Facility	399
Table 8-37.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Metallurgical Laboratory Seepage Basin	400
Table 8-38.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Miscellaneous Chemical Basin	400
Table 8-39.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Motor Shop Oil Basin	401
Table 8-40.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the A- and M-Areas Plume Definition Wells	402

Table 8-41.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Savannah River Laboratory Seepage Basins	403
Table 8-42.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Silverton Road Waste Site	403
Table 8-43.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the C-Area Burning/Rubble Pit	404
Table 8-44.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the C-Area Disassembly Basin	404
Table 8-45.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the C-Area Reactor Seepage Basins	405
Table 8-46.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Acid/Caustic Basin	405
Table 8-47.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Ash Basin	406
Table 8-48.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Burning/Rubble Pit	406
Table 8-49.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Coal Pile Runoff Containment Basin	406
Table 8-50.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Disassembly Basin	407
Table 8-51.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Reactor Seepage Basin	407
Table 8-52.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Acid/Caustic Basin	408
Table 8-53.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Disassembly Basin	408
Table 8-54.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Oil and Chemical Basin	409
Table 8-55.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Reactor Seepage Basin	409
Table 8-56.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Research Wells	410
Table 8-57.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Acid/Caustic Basin	410
Table 8-58.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Burning/Rubble Pit	410

List of Tables

Table 8-59.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Coal Pile Runoff Containment Basin	411
Table 8-60.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Disassembly Basin	411
Table 8-61.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Reactor Seepage Basins	412
Table 8-62.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the R-Area Burning/Rubble Pits	412
Table 8-63.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the R-Area Disassembly Basin	412
Table 8-64.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the R-Area Reactor Seepage Basins	413
Table 8-65.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Acid/Caustic Basin	413
Table 8-66.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Burma Road Rubble Pit	414
Table 8-67.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Burning/Rubble Pits	414
Table 8-68.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Canyon Building and A-Line Uranium Recovery Facility	415
Table 8-69.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Coal Pile Runoff Containment Basin	416
Table 8-70.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Seepage Basins	416
Table 8-71.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Sludge Land Application Site	418
Table 8-72.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Tank Farm	418
Table 8-73.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Acid/Caustic Basin	418
Table 8-74.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Auxiliary Pump Pit	419
Table 8-75.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Canyon Building	419
Table 8-76.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Coal Pile Runoff Containment Basin	420

Table 8-77.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Retention Basins	420
Table 8-78.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Seepage Basins	421
Table 8-79.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Sludge Land Application Site	422
Table 8-80.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Tank Farm	423
Table 8-81.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the M-Area Waste Disposal Facility (Y Area)	423
Table 8-82.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Old F-Area Seepage Basin	424
Table 8-83.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Radioactive Waste Burial Grounds	424
Table 8-84.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the S-Area Defense Waste Processing Facility	427
Table 8-85.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the S-Area Vitrification Building	428
Table 8-86.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Z and ZW Wells	428
Table 8-87.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Z-Area Low Point Drain Tank	428
Table 8-88.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Central Shops Burning/Rubble Pit South of the Ford Building Seepage Basin	429
Table 8-89.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Central Shops Diesel Spill	429
Table 8-90.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Ford Building Seepage Basin	429
Table 8-91.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the D-Area Burning/Rubble Pits	430
Table 8-92.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the D-Area Coal Pile Runoff Containment Basin and Ash Basins	430
Table 8-93.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the D-Area Oil Disposal Basin	431
Table 8-94.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Chemicals, Metals, and Pesticide Pits	431

Table 8-95.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Interim Waste Technology Sites	432
Table 8-96.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-28 Well Cluster in F Area	433
Table 8-97.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Potential New Production Reactor Site Characterization Wells	433
Table 8-98.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Road A Chemical Basin (Baxley Road)	433
Table 8-99.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Sanitary Landfill	434
Table 8-100.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Sewage Sludge Application Sites	435
Table 8-101.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the New TNX Seepage Basin	435
Table 8-102.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the Old TNX Seepage Basin	436
Table 8-103.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the TNX-Area Assessment Wells	437
Table 8-104.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the TNX-Area Background Wells	437
Table 8-105.	Maximum Constituents Results Exceeding Applicable Standards for Wells at the TNX Burying Ground	438
Table 8-106.	EPA Primary Drinking Water Standards used for the Groundwater Monitoring Program ...	439
Table 9-1.	Radioactivity in Fish and Seafood	451
Table 9-2.	Summary of Cesium-137 in Fish	455
Table 9-3.	Comparison of Field and Laboratory Cesium-137 Measurements in Deer and Hogs	456
Table 9-4.	Summary of Cesium-137 in Deer	460
Table 9-5.	Summary of Strontium in Deer and Hog	461
Table 9-6.	Iodine-129 and Cesium-137 in Deer Thyroids and Muscle	462
Table 9-7.	Calculated Doses to Aquatic Biota from SRS Releases	464
Table 9-8.	Mercury in Fish	465
Table 10-1.	Radioactivity in Upper Three Runs Creek at U3R-2	474

Table 10-2.	Radioactivity in Upper Three Runs Creek at U3R-3	475
Table 10-3.	Twin Lakes Special Sampling Summary	476
Table 10-4.	Sample Analysis Summary for the H-Area Tank Farm Release	477
Table 10-5.	Perspectives on the December 1991 Tritium Release from K Reactor	478
Table 11-1.	Par Pond Sampling Summary	491
Table 11-2.	Air Monitoring Results for Par Pond	492
Table 11-3.	Radioactivity in Par Pond Sediment	493
Table 11-4.	Radioactivity in Pond C Sediment	498
Table 11-5.	Strontium in Par Pond and Pond C	499
Table 11-6.	Par Pond Penetrating Radiation Measurements	500
Table 11-7.	Mercury in Par Pond and Pond C Sediment	501
Table 11-8.	Radioactivity in Biological Media	502
Table 11-9.	Radioactivity in Savannah River Swamp Soil – 1990	503
Table 11-10.	Radioactivity in Savannah River Swamp Vegetation – 1990	507
Table 11-11.	Savannah River Swamp MicroR Measurements – 1990	509
Table 11-12.	Savannah River Swamp TLD Exposure Measurements – 1990	517
Table 11-13.	Comparison of TLD and MicroR Measurements in the Savannah River Swamp – 1990	519
Table 11-14.	Radioactivity in Savannah River Swamp Soil – 1991	520
Table 11-15.	Radioactivity in Savannah River Swamp Vegetation – 1991	521
Table 11-16.	Savannah River Swamp TLD Exposure Measurements – 1991	522
Table 11-17.	Plutonium Results from Four Mile Creek Survey	523

Acronyms

AEC	Atomic Energy Commission (now the Department of Energy and Nuclear Regulatory Commission)	EA	Environmental Assessment
ALARA	as low as reasonably achievable	EDE	effective dose equivalent
AMS	Aerial Monitoring System	EIS	Environmental Impact Statement
ANSP	Academy of Natural Sciences of Philadelphia	EMS	Environmental Monitoring Section (WSRC-EPD)
APHA	American Public Health Association	EML	Environmental Measurements Laboratory (DOE)
BDC	Beaver Dam Creek	EMSL-LV	Environmental Monitoring Systems Laboratory/Las Vegas (EPA)
BF	bioaccumulation factor	EOC	Emergency Operating Center
BSRI	Bechtel Savannah River Inc.	EPA	U.S. Environmental Protection Agency
CAA	Clean Air Act (federal)	EPCRA	Emergency Planning and Community-Right-to-Know Act
CAAC	Clean Air Act Code (federal)	EPD	Environmental Protection Department (WSRC)
CEPEP	Comprehensive Environmental Protection Evaluation Program (federal)	ERA	Environmental Resource Associates
CEQ	Council on Environmental Quality	ESAC	Earth Science Advisory Committee
CERCLA	Comprehensive Environmental Response, Compensation, and Liability Act (Superfund) (federal)	ES&H	Environment, Safety, and Health (DOE-HQ)
CFR	Code of Federal Regulations	ETF	Effluent Treatment Facility
CL	confidence level	ETI	Environmental Testing Inc.
CLP	Contract Laboratory Program (EPA)	FDA	Food and Drug Administration (federal)
CSRA	Central Savannah River Area	FFCA	Federal Facility Compliance Agreement
CT ERR	counting error	FMC	Four Mile Creek
CWA	Clean Water Act (federal)	FONSI	Finding of No Significant Impact
DCG	derived concentration guides	GDNR	Georgia Department of Natural Resources
DBE	Design Basis Earthquake	GIS	Geographic Information System
DEL	deleted version	HEPA	high-efficiency particulate air filter
DM	dry monitoring (wells)	HPGe	high-purity germanium detector
DOE	U.S. Department of Energy	HWMW	Hazardous Waste/Mixed Waste Disposal Facility (WSRC)
DOE-HQ	U.S. Department of Energy- Headquarters	ICP/MS	inductively coupled plasma-mass spectrometer
DOE-SR	U.S. Department of Energy- Savannah River Operations Office	ICRP	International Commission on Radiological Protection
DOE-SR/ED	U.S. Department of Energy Savannah River Operations Office Environmental Division	IGB	Indian Grave Branch
DOM	dissolved organic matter	IMPACTS	Issue Management Processing Action and Commitment Tracking System
DOT	U.S. Department of Transportation	ITP	in-tank precipitation
DRF	dose reduction factor	LDR	land disposal restrictions
DWPF	Defense Waste Processing Facility (WSRC)	LEPC	local emergency planning commission
DWS	Drinking Water Standards (EPA)		

LET	linear energy transfer	RCRA	Resource Conservation and Recovery Act (federal)
LETF	Liquid Effluent Treatment Facility	RFI	RCRA Facility Investigation
LLD	lower limit of detection	RFI/RI	RCRA Facility Investigation/ Remedial Investigation
LSC	liquid scintillation counter	ROD	Record of Decision
L3R	Lower Three Runs Creek	RQ	reportable quantity
MRD	mean relative difference	RTF	Replacement Tritium Facility (WSRC)
MCL	maximum contaminant level	RBOF	Receiving Basin for Offsite Fuel
MDC	minimum detectable concentration	SARA	Superfund Amendments and Reauthorization Act
MSS	multispectral scanner	SCCP	South Carolina Coastal Plain
MTF	Memorandum-to-File	SCDHEC	South Carolina Department of Health and Environmental Control
MWMF	Mixed Waste Management Facility (WSRC)	SDWA	Safe Drinking Water Act (federal)
NAAQS	National Ambient Air Quality Standards	SEA	Special Environmental Analysis
NCRP	National Council on Radiation Protection and Measurements	SEFES	Southeastern Forest Experimental Station
NEPA	National Environmental Policy Act	SI	International System of Units
NESHAP	National Emission Standards for Hazardous Air Pollutants	SIRIM	Site Item Reportable Issue Management
NIST	National Institute of Standards and Technology	SPOT	Satellite Pour l'Observation de la Terre (Earth Observation Satellite)
NOI	Notice of Intent	SREL	Savannah River Ecology Laboratory (University of Georgia)
NOV	Notice of Violation	SRFS	Savannah River Forest Station (USFS)
NPDES	National Pollutants Discharge Elimination System	SRL	Savannah River Laboratory (WSRC)
NPL	National Priority List (CERCLA)	SRS	Savannah River Site
NPR	New Production Reactor	SWDF	Solid Waste Disposal Facility
NRC	Nuclear Regulatory Commission (federal)	SWMU	solid waste management unit
NRDC	Natural Resources Defense Council	TB	Tims Branch
OSHA	Occupational Safety and Health Administration	TI	Teledyne Isotopes
ORA	Operations Recreational Association	TIMS	Thermal Ionization Mass Spectrometer
PB	Pen Branch	TLD	thermoluminescent dosimeter
PBF	Pen Branch Fault	TRAC	Tracking Radioactive Atmosphere Contaminants
PEIS	Programmatic Environmental Impact Statement	TSCA	Toxic Substance Control Act
PCB	polychlorinated biphenyl	USFS	U.S. Forest Service
PE	performance evaluation samples (EPA)	USGS	U.S. Geological Survey
PHA	pulse height analysis	U3R	Upper Three Runs Creek
PIP	Public Involvement Plan	WIND	Weather INformation and Display
PWA	process waste assessment	WMT	Waste Management Technology (WSRC)
QA	quality assurance	WSRC	Westinghouse Savannah River Company
QAD	Quality Assurance Division (EPA)		
QAP	Quality Assurance Program (DOE)		
QC	quality control		

Executive Summary

INTRODUCTION

The Savannah River Site (SRS), one of 16 facilities in the U.S. Department of Energy (DOE) complex, produces plutonium, tritium, and other special nuclear materials for national defense, other government programs, and some civilian purposes. Environmental monitoring, environmental research, and environmental compliance share equal importance at SRS. Each program consists of specific activities conducted to meet federal and state regulations and guidelines which ensure that past, present, and future site operations do not adversely affect the environment or public health.

In 1991, environmental monitoring was conducted within a 30,000-square-mile area around SRS including neighboring cities, towns, and counties in Georgia and South Carolina. Thousands of samples of air, surface water, groundwater, food and drinking water, wildlife, rainwater, soil, sediment, and vegetation were collected and analyzed for radioactive constituents. In addition, penetrating radiation levels were measured with thermoluminescent dosimeters (TLDs) at 462 locations.

This executive summary centers primarily on the estimated offsite radiation doses to the public from radionuclide releases, and on the nonradiological monitoring program. Brief reviews of various environmental and compliance activities focus on the

major issues of each program. All five SRS reactors were inoperative during 1991. However, maintenance operations in the reactor areas, as well as operations in the separations and waste management areas, resulted in atmospheric and liquid releases of radionuclides to the environment.

DOSE ESTIMATES TO OFFSITE POPULATION

Applicable Dose Standards

SRS is required to maintain radiation doses to the public within the limits specified in DOE Order 5400.5. The dose limits established in DOE Order 5400.5 include all exposure pathways from all DOE activities, including atmospheric releases and releases to surface waters. These limits, summarized in Chart ES-1, are used for comparison in the sections that follow. In addition to meeting these limits, SRS is also required to ensure that doses to the public are as low as reasonably achievable (ALARA).

Doses from Atmospheric Releases

As shown in Figure ES-1, the maximum effective dose equivalent (EDE) from atmospheric releases of radioactive materials was 0.12 mrem (0.0012 mSv). This estimated dose, based on a hypothetical individual residing at the SRS boundary, is 1.2 percent of the 10 mrem/yr (0.1mSv/yr) limit for exposure to airborne releases from DOE facilities. The average individual dose at the SRS perimeter was estimated to be 0.06 mrem (0.0006 mSv) in 1991.

The collective EDE to the 555,100 persons living within 50 miles (80 km) of the center of the site was 7.1 person-rem (0.071 person-Sv). Tritium was the most important radionuclide, comprising over 90 percent of the estimated doses from SRS atmospheric releases.

Doses from Liquid Releases

The EDE to the maximally exposed individual from liquid releases of radioactivity to the Savannah River was 0.34 mrem (0.0034 mSv). Approximately seventy

Figure ES-1 Maximum contributions from SRS releases versus other sources of radiation.

Chart ES-1
DOE Radiation Dose Limits for Exposure to the Public from Releases from DOE Facilities^a

Mode of Public Exposure	Effective Dose Equivalent	
	mrem/year	mSv/year
All sources and pathways from routine DOE operations ^b	100	1
Airborne effluents (40 CFR 61, Subpart H) ^c	10	0.1
Drinking water pathway (40 CFR 141) ^d	4	0.04

a All the limits listed are given in DOE Order 5400.5, Feb. 8, 1990, "Radiation Protection of the Public and Environment."

b "Routine DOE Operations" means normal planned operations and does not include nonroutine releases.

c The standard for airborne effluents applies to the sum of the doses from all airborne pathways: inhalation, submersion in a plume, exposure to radionuclides deposited on the ground surface, and consumption of foods contaminated as a result of the deposition of radionuclides.

d The drinking water standard applies to public community drinking water systems and drinking water supplies operated by DOE or DOE contractors.

percent of this calculated dose resulted primarily from the intake of Cs-137, found in Savannah River fish and shellfish.

Offsite doses were calculated for persons receiving drinking water from two water treatment plants approximately 100 miles downriver from SRS in Hardeeville (Beaufort-Jasper), S.C., and Port Wentworth, Ga. The maximum committed EDEs were .081 mrem (0.0008 mSv) at Beaufort-Jasper and .099 mrem (0.0010 mSv) at Port Wentworth. These estimated doses are based on an individual who consumes 2 liters per day of drinking water from the Savannah River. These doses are 2.0 percent and 2.5 percent, respectively, of the DOE and Environmental Protection Agency (EPA) drinking water standard of 4 mrem/yr (0.04 mSv/yr). Liquid tritium releases accounted for approximately 90 percent of the offsite doses from SRS at Hardeeville and Port Wentworth.

The 1991 collective EDE from liquid releases was 3.2 person-rem (0.032 person-Sv).

As shown in Chart ES-2, all estimated doses attributed to SRS were below required standards. These doses can also be compared to other sources of radiation, including naturally occurring and man-made. A person living in the Central Savannah River Area (CSRA) receives an annual radiation dose of about 380 mrem (3.8 mSv) from sources such as radon in homes,

medical x-rays, terrestrial and cosmic radiation, and consumer products. Doses contributed by SRS in 1991 were less than 1 percent of the annual radiation dose a CSRA resident received from natural sources.

AIR PATHWAYS

Air

During 1991, SRS monitored effluents (points of release) and the environment to determine the concentrations of radioactive materials in the air. Tritium was the primary radionuclide released to the atmosphere (200,000 Ci) in 1991. Tritium was released primarily from the reactors, separations, and heavy water reprocessing areas.

Concentrations of tritium were routinely detected in the air, with concentrations decreasing with increasing distance from the site. The average tritium concentration measured at the site perimeter was 2.1×10^{-11} $\mu\text{Ci/mL}$, while the average concentrations measured offsite at the 100-mile locations were 2-3 times lower. The concentrations of all measured radionuclides, including tritium, were below the derived concentration guides (DCGs) of DOE Order 5400.5, "Radiation Protection of the Public and the Environment."

During 1991, after assessing the need for nonradiological ambient-air monitoring, SRS terminated the operation of all onsite ambient-air monitoring stations. South Carolina and Georgia continue to monitor air

quality as part of the network associated with the Clean Air Act (CAA).

Nonradioactive emissions of SO₂, NO_x, CO, and total particulate matter less than 10 microns (PM₁₀) released from SRS stacks were within applicable South Carolina Department of Health and Environmental Control (SCDHEC) standards.

Penetrating Radiation

An extensive, 8,000-square-mile surveillance network covers SRS and the surrounding areas. Within the network, TLDs are used to measure environmental penetrating radiation levels from terrestrial and cosmic components of background radiation and from SRS operations. In 1991, penetrating radiation measurements taken at fences around various SRS facilities, including the Solid Waste Disposal Facility (SWDF), H Area, and Central Shops were higher than offsite measurements, with a maximum at the SWDF of 480 mrem/yr. Penetrating radiation measurements taken offsite and at other onsite locations were similar to values reported for Augusta, Ga. (84 mrem), by the Environmental Protection Agency (EPA).

Other Air Pathways

SRS analyzes samples from other segments of the environment that may be affected by SRS atmospheric releases and provide a pathway of radiation exposure to

the public. These include samples of milk, food, rainwater, soils, and vegetation.

Tritium in milk is attributed to releases from SRS. Milk from all dairies showed detectable concentrations of tritium at some point during 1991. Over the past six years, concentrations of tritium in milk generally reflected changes in the atmospheric source term.

In 1991, concentrations of Pu-238 and Pu-239 in soil around F and H Areas were greater than concentrations measured at the 100-mile locations. These higher onsite concentrations reflect past F- and H-Area releases and 1991 releases of 2.64E-04 Ci of Pu-238 and 3.25E-04 Ci of Pu-239.

WATER PATHWAYS

Surface and Drinking Water

In 1991, over 99 percent of the total radioactivity introduced to the Savannah River by SRS occurred from tritium releases. Of the 27,400 Ci of tritium released from the site, 59 percent was attributed to migration from seepage basins; the remaining 41 percent resulted from direct tritium releases to onsite streams by the Reactors, Separations, and Heavy Water Reprocessing areas. The total tritium directly released to onsite streams was over four times higher than the 1990 releases because of the December 1991 tritium release from K Area and increased operations at the Effluent Treatment Facility (ETF) in H Area.

Chart ES-2

Comparison of Calculated Maximum Doses from SRS Releases with Applicable Standards and Natural Background Radiation

Exposure Pathway	Maximum Dose ^a from SRS Releases	Applicable Standard ^b	% of Standard	% of Natural Background ^c
Airborne effluents	0.12 mrem	10 mrem	1.2 ^d	0.04
Drinking water ^e	0.10 mrem	4 mrem	2.5	0.03
All pathways ^f	0.46 mrem	100 mrem	0.46	0.15

a Effective dose equivalent.

b See Chart ES-1.

c Site-specific estimate of average dose received from natural background radiation is 315 mrem/yr

d This calculated EDE comparison is not intended to show NESHAP compliance because the dose was not calculated with CAP88 (Chapters 6 and 7).

e This calculated maximum individual EDE is for the population served by the Port Wentworth, Ga., Water Treatment Plant.

f Exposure pathways are added in order to compare maximum calculated doses from SRS releases with the DOE "all pathways" standard. However, it is impossible for any individual to receive the maximum dose from each pathway. This total includes the maximum airborne EDE of 0.12 mrem and the maximum liquid EDE of 0.34 mrem.

"Maximally Exposed Individual"

When calculating doses to the public from atmospheric and liquid releases, scientists use the concept of the "maximally exposed individual." No such person is known to exist.

For atmospheric releases: Someone who lives at the SRS boundary 365 days per year and consumes milk, meat, and vegetables produced at that location.

For liquid releases: Someone who lives immediately downriver from SRS 365 days per year, drinks one liter of water per day from the Savannah River, consumes a large amount of fish, and spends the majority of time on the river.

Downriver from SRS at sampling location River 10A, tritium concentrations averaged $3.25\text{E-}06$ $\mu\text{Ci/mL}$, which is below the $2\text{E-}05$ $\mu\text{Ci/mL}$ EPA drinking water standard. Low levels of Cs-137, Sr-89,90, and Pu-239 were also measured in the Savannah River, but concentrations of these radionuclides were below EPA drinking water standards.

Nonradiological liquid effluents are regulated under the National Pollutant Discharge Elimination System (NPDES). Seventy-eight permitted outfalls were monitored in 1991. Seven exceedances from six outfalls were identified from the 8,329 analyses performed.

The Savannah River and onsite streams, classified as Class B waters, are also monitored to determine water quality. In 1991, analytical results for all parameters were within standards required for Class B waters.

Sediments

The 1991 river and onsite stream sediment results reflect current and previous contributions of radioactivity from SRS liquid releases. During 1991, as in past years, maximum radionuclide concentrations were measured in sediment samples collected from Four Mile Creek, a stream that receives effluents and groundwater migration from C, F, and H areas. During the past three years, average concentrations of Cs-137, Pu-239 and Pu-238 measured in Four Mile Creek sediments were 130, 70, and 30 times higher, respectively, than average concentrations in Savannah River sediment collected downriver from SRS at

Highway 301. These higher onsite concentrations reflect historical releases from the separations areas.

In the nonradiological monitoring program for 23 herbicides, none were detected in either the Savannah River or stream sediment samples in 1991.

Groundwater

SRS monitors groundwater quality for hundreds of radioactive and nonradioactive constituents from about 1,400 wells at more than 90 locations to identify contamination that may occur due to site operations. Four new wells series, representing 41 wells, were added to the program in 1991; 196 new wells added to existing well series were monitored for the first time.

Over 210 wells monitor the volatile organic plume beneath A and M Areas. In 1991, trichloroethylene and tetrachloroethylene exceeded standards in 117 and 82 wells, respectively, in these areas. Samples from one well near the M-Area Hazardous Waste Management Facility (HWMF) yielded a dense nonaqueous-phase liquid consisting primarily of these organics.

Concentrations of tritium and chlorinated volatile organics in wells near the K-Area seepage basins, which were quite high in 1990, returned to lower historic levels at SRS in 1991. Wells in D Area, the location of a large coal-fired power plant and the inactive heavy water facilities, had the highest levels of sulfate and chromium of any monitored locations at SRS this year. The highest levels were 175 times greater than the EPA drinking water standards. Tritium, total radium, gross alpha, nonvolatile beta, lead, trichloroethylene, and tetrachloroethylene exceeded standards in a majority of wells at all locations onsite.

Groundwater downgradient from the F- and H-Area seepage basins has become progressively cleaner since the basins were closed in 1988. During the years 1983-1991, the site's groundwater remediation program had removed approximately 260,000 lb of volatile organic compounds from over 1.3 billion gallons of groundwater beneath A and M areas.

WILDLIFE

The maximum concentration of Cs-137 measured in fish downriver from SRS was 0.25 pCi/g. Since 1979, concentrations of Cs-137 in fish from site streams and ponds have remained fairly constant. The consumption of fish comprised 71 percent of the total maximum committed EDE from liquid releases, with the majority of dose attributed to Cs-137. Some fraction of the Cs-137 in fish is due to worldwide fallout; however, that component is difficult to determine and is not

subtracted from the total. Thus, the calculated dose from consumption of Cs-137 in fish is an overestimate of that contributed from SRS releases.

In SRS deer and hogs, the laboratory analysis of muscle samples collected from 124 animals indicated that the maximum concentration of Cs-137 in deer muscle was 13.7 pCi/g compared to the field maximum of 21 pCi/g. The committed EDE to an individual who consumed one 8-oz. steak of deer meat with 21 pCi/g of Cs-137 would be 0.24mrem (0.0024 mSv). If the same person were to eat one 8-oz. deer steak, which contained a concentration of 21 pCi/g of Cs-137, every day for one year, he/she would receive a committed EDE that is 87 percent of the DOE annual dose limit and 23 percent of the average CSRA resident's average annual dose from naturally-occurring radioactivity.

NONROUTINE OCCURRENCES

Four nonroutine occurrences contributed to unplanned releases of radioactive materials to the environment from SRS operations in 1991. These are listed below:

- April 25, 1991: Ground contamination was discovered near F-Area laboratory buildings 772-F and 772-1F during a routine survey. Analytical results of run-off water from the affected area indicated that the released activity was primarily Sr-89,90, with some Cs-137. Although operations and water run-off have released activity from this location to the stream bed over the years, no routine sediment sampling has been done, and thus no background samples are available for comparisons. No estimate of the total activity released could be made because of the lack of flow measurements at this run-off discharge point.
- Aug. 1-2, 1991: The dam on Twin Lakes, which drains to Four Mile Creek above Road A-7, failed. Special sampling of water and sediment began on Aug. 7.
- Sept. 23-30, 1991: The H-Area Tank Farm retention basins released 0.011 Ci of Cs-137 and 0.012 Ci of Sr-89,90 to Four Mile Creek. The maximum EDE to an individual offsite was estimated at 0.0047 mrem (drinking water plus fish consumption).
- Dec. 22-25, 1991: Approximately 5,700 Ci of tritium in 150 gallons of heavy water leaked from a K-Reactor heat exchanger. The maximum dose to an individual offsite was calculated as 0.035 mrem (0.9 percent of the EPA drinking water standard of 4 mrem/year). The maximum doses to individuals consuming water from the Beaufort-Jasper and Port Wentworth water systems were 0.0096 (0.2

percent of the EPA standard) and 0.030 mrem (0.8 percent of the EPA standard), respectively. The reason for the difference is that Beaufort-Jasper stopped pumping until the plume passed, while Port Wentworth switched to a pumping cycle associated with tidal changes to minimize the intake of tritium.

When sufficient information was available, release values from nonroutine occurrences were incorporated into final offsite dose determinations (Chart ES-2).

SPECIAL SURVEYS

In 1991, a special radiological survey of Par Pond was performed during the water drawdown for a safety investigation of Par Pond dam. Sediments of Pond C and Par Pond contained elevated concentrations of Cs-137, up to 140 pCi/g, compared to background levels of about 1 pCi/g. Air sampling during the investigation indicated no detectable increase in airborne radioactivity from wind erosion of sediments.

Results from a comprehensive survey of the Savannah River swamp conducted in 1990, along with results from a 1991 cursory survey of the area, are reported. The levels of contamination were consistent with results from previous surveys. Core samples of soils show the expected decrease in concentrations with increasing depth, with contamination extending to depths of at least 9-12 inches.

In 1990, a Four Mile Creek survey characterized the creek for the presence of various radionuclides, including Cs-137, Sr-89,90, and tritium, that enter the area as a result of operations in C, F, and H areas. The Pu-238,239 results for soil samples collected during the 1990 survey are reported this year. Increased activity is seen downstream of F and H Areas.

The 1991 surveys by the Academy of Natural Sciences of Philadelphia (ANSP), which study the effects of SRS effluent discharges on general river health, indicated deteriorating water quality downstream of Lower Three Runs Creek. In September, ANSP conducted the sixth comprehensive biological survey in the vicinity of the Georgia Power Company's Vogtle Electric Generating Plant on the Savannah River. The 1991 data show that the operation of Plant Vogtle had no adverse effect on the water quality of the Savannah River.

ENVIRONMENTAL RESEARCH AND MANAGEMENT PROJECTS

Environmental research projects at the site covered a variety of sciences. Groups participating included the

Three Separate Groups Conduct Research at SRS during 1991

- SRL** • activities to meet permit or environmental impact statement requirements
- fate and effects of pollutants from SRS
- environmental dosimetry
- atmospheric and stream effluent studies
- seismic studies
- emergency response
- SREL** • geochemistry of uranium and other metals
- radionuclide cycling
- endangered and threatened species
- biodiversity
- biological communities in natural and disturbed wetlands
- SRFS** • timber management and reforestation
- wildlife management
- secondary road management
- fire management

Savannah River Laboratory, the Savannah River Ecology Laboratory, and the U.S. Forest Service Savannah River Forest Station. Studies in 1991 are summarized above.

ENVIRONMENTAL COMPLIANCE

Environmental compliance activities and issues at SRS in 1991 ranged from the site's compliance status with state and federally regulated programs—such as the Resource Conservation and Recovery Act (RCRA), the Clean Water Act (CWA), and the CAA—to dealing with a tritium release from K Reactor during pre-startup testing. Three major environmental compliance issues received attention during 1991. In March 1991, a Federal Facilities Compliance Agreement (FFCA) was signed between the DOE-Savannah River Operations Office (DOE-SR) and EPA Region IV to address SRS mixed-waste compliance with land disposal restrictions (LDRs) established by the 1984 amendments to RCRA. A draft Federal Facilities Agreement (FFA) between EPA and SCDHEC to integrate RCRA and Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) regulatory require-

ments was released Dec. 17 for a 60-day public comment period. This document represents an agreement between the three agencies directing the comprehensive remediation of SRS.

An alternative radiological monitoring system package, sent to EPA April 1 in response to new National Emissions Standards of Hazardous Air Pollutants (NESHAP) requirements (40 CFR 61, Subpart H), was denied. SRS signed an interim FFCA June 28, 1991, and a final one Oct. 31. The final FFCA allows SRS to continue operating facilities while installing upgraded sampling and air monitoring instrumentation and requires a sitewide air emissions inventory by the end of 1993.

In other activities, 10 hazardous-waste units under RCRA control were closed and certified during 1991. Closure plan approval for the Metallurgical Laboratory Seepage Basin, contaminated with organic chemicals, was obtained in September. During 1991, there were four tritium releases reported under CERCLA, seven exceedances with NPDES permit requirements, and one notice of violation during SCDHEC inspections of air emission sources for exceeding the authorized opacity limit for a permitted diesel engine in K Area. A DOE-SR appraisal identified 31 deficiencies with potable water systems at SRS, which provide drinking water to its employees. In 1991, SRS instituted bacteriological compliance monitoring at all SRS area drinking water systems to comply with state drinking water regulations. Because of operating problems, the water in D Area is no longer used for drinking. A deficiency in the polychlorinated biphenyls (PCBs) program, regulated under the Toxic Control Substances Act (TSCA), involved reporting the fraction of PCBs in PCB-containing transformers.

The draft Environmental Impact Statement (EIS) for the New Production Reactor (NPR) was issued in April for public comment. Several public hearings were held in May in Aiken, S.C., and Augusta and Savannah, Ga.

Current issues at SRS include the drawdown of Par Pond by 19 feet to investigate the structural integrity of the dam. Alternatives are being evaluated for the repairing, refilling, or draining of the reservoir. Finally, SCDHEC, the Georgia Department of Natural Resources (GDNR), and downstream water consumers were notified of the accidental release during pre-startup testing of 150 gallons of heavy water containing approximately 5,700 Ci of tritium from K Reactor in late December. The predicted radiation dose from this release was well below the EPA drinking water limit of 4 mrem per year.

To Learn About:	Turn to page:
♦ Water resources on and around the site	2
♦ The six major production areas	3
♦ Waste minimization efforts at SRS	9
♦ SRS's "Environmental Outreach" program	10

Site and Operations Overview

1991 HIGHLIGHTS

- ♦ Although all five SRS reactors were inoperative in 1991, initial steps to restart K Reactor began in December. During the K-Reactors startup, a leak from one of the heat exchangers resulted in a liquid release of approximately 5,700 Ci of tritium. The spill, which occurred Dec. 22-25, was one of the largest liquid releases of tritium in recent years and is discussed in detail in Chapter 10, "Nonroutine Occurrences."
- ♦ Construction of the Replacement Tritium Facility (RTF), a one-acre underground facility in H Area, was suspended temporarily in May due to a lack of financial and administrative controls. Designed to reduce waste generation and minimize tritium losses to the environment, the RTF is scheduled to begin operation in 1993.
- ♦ In July 1991, the Nuclear Materials Processing Division restarted the HB Line in the H-Area canyon for Pu-238 production. Shipments of the Pu-238 to Los Alamos National Laboratory for encapsulation into fuel for the space program began in August. The fuel will power two upcoming space probes in the mid-1990s: Cassini (to the planet Saturn) and CRAF (Comet Rendezvous Asteroid Fly By).
- ♦ The Z-Area Saltstone Facility is designed to process and dispose of decontaminated salt solutions from the storage tanks located in F and H Areas, and from the Effluent Treatment Facility located on the south side of H Area. The decontaminated salt solutions are immobilized in a cement-based grout and disposed of in above-ground concrete vaults. Since its startup in June 1990, the Saltstone Facility has processed approximately 12,000 tons of salts.
- ♦ Public meetings were held throughout 1991 to address public concerns about environmental issues at SRS. They included meetings to address concerns about the tritium in the Savannah River, a public workshop to discuss the SRS priority system for cleanup and waste management, and public meetings to present the updated Site Specific Plan and the Environmental Restoration and Waste Management Five-Year Plan. Also, SRS began a series of public meetings called the Environmental Forums.

DESCRIPTION OF THE SAVANNAH RIVER SITE

Location

The Savannah River Site (SRS) occupies an area of approximately 300 square miles adjacent to the Savannah River, principally in Aiken and Barnwell counties of South Carolina.

The site is approximately 25 miles southeast of Augusta, Ga., and 20 miles south of Aiken, S.C.

(Figure 1-1). The average population density in the counties surrounding SRS ranges from 23 to 560 people per square mile, with the largest concentration in the Augusta metropolitan area. Based on 1980 unextrapolated census data, the population within a 50-mile radius (80 km) of SRS is approximately 555,100. Required census data for 1990 has not been made available by the Census Bureau.

Various industrial, manufacturing, medical, and farming operations are conducted in areas surrounding

Typical Climate at SRS

- ◆ **Summer**
Hot and humid
Temperatures reach upper 90s (°F)
33 percent of annual rainfall
- ◆ **Fall**
Cool mornings, warm afternoons
Temperatures range 50 to 76 °F
19 percent of annual rainfall
- ◆ **Winter**
Mild; lasting November through March
Temperatures normally above 32 °F
21 percent of annual rainfall
- ◆ **Spring**
Most variable; cold snap often in March
Temperatures average 65 °F
27 percent of annual rainfall

the site. Major industrial and manufacturing facilities in the area include textile mills; plants producing polystyrene foam and paper products; chemical processing plants; and a commercial nuclear power plant. Farming is diversified in the region and includes crops such as cotton, soybeans, corn, and small grains.

Climate

The SRS climate is mild, with an average frost-free season of approximately 246 days. The average annual rainfall at SRS, about 48 inches, is fairly evenly distributed throughout the year. There is no strongly prevailing wind direction. However, there is a relatively high frequency of east and northeast winds during the summer and fall. During the late fall, winter, and spring months, there is a relatively high frequency of south through northwest winds [Hunter, 1990]. More detailed information about winds and atmospheric dispersion from SRS can be found in Chapter 6, "Calculating Radiation Doses." With the exception of the Savannah River, no unusual topographic features exert significant influences on the general climatology.

Water Resources

SRS is bounded on its southwestern border for about 20 miles by the Savannah River, approximately 160 river

miles from the Atlantic Ocean. Five major streams at SRS feed into the Savannah River: Upper Three Runs Creek, Four Mile Creek, Pen Branch, Steel Creek, and Lower Three Runs Creek (Figure 1-2). These streams, which receive effluents from various onsite operations, are not used as commercial sources of water.

The Savannah River is used as a drinking water supply for approximately 65,000 persons downriver in Port Wentworth, Ga., and near Hardeeville, S.C. (Beaufort and Jasper counties) [Hamby, 1991]. The Port Wentworth Water Treatment Plant intake is located approximately 130 river miles from SRS, and the Beaufort-Jasper facility intake is approximately 120 river miles from SRS. The Savannah River also is used for commercial and sport fishing, boating, and other recreational activities downriver from SRS. There is no known use of the Savannah River for irrigation by farming operations located downstream of SRS [Hamby, 1991].

SRS uses water from the Savannah River for site operations. River water is used to supply cooling water for reactors when they are operating. Until August 1990, the drinking water system in D Area was supplied with treated surface water taken from the Savannah River. D Area now uses bottled drinking water (Chapter 8, "Water Pathways").

Geology and Hydrology

SRS is situated on the Upper Coastal Plain of South Carolina. The Coastal Plain at SRS consists of 500 to 1,400 feet of sands, clays, and limestones of Tertiary and Cretaceous age. These sediments are underlain by sandstones of Triassic age and older metamorphic and igneous rocks.

The sandy sediments of the Coastal Plain contain several productive aquifers—separated by clay-rich units—that drain to the Savannah River, its tributaries, and the Savannah River Swamp.

The older, underlying rocks are nearly impermeable and do not constitute a major water source. Detailed information on the geology and hydrology at SRS can be found in Chapter 8.

Land Resources

The SRS region is part of a wetlands area called the Southern Bottomland Hardwood Swamp region. The main features are river swamps, rarely more than five miles wide, which occur on the Coastal Plain that extends from Virginia south to Florida and west along the Gulf of Mexico to the Mississippi River drainage basin.

Figure 1-1 SRS, approximately 300 square miles in area, is located about 25 miles southeast of Augusta, Ga., and 20 miles south of Aiken, S.C.

Most of the site's environs are rural, with approximately 40 percent of the countryside forested with longleaf and loblolly pines and with sweet gum, maple, birch, and various oak-hickory hardwood trees.

Major plant communities on SRS include cypress-gum and lowland hardwood swamps, sandhills, and old agricultural fields, as well as aquatic and semiaquatic areas. These habitats range from very sandy, dry hilltops to continually flooded swamps.

SRS is populated with more than 50 species of mammals, including deer, feral hogs, beavers, rabbits, foxes, raccoons, and opossums. The site also is home to more than 100 species of reptiles and amphibians (including turtles, alligators, lizards, snakes, frogs, and salamanders) and more than 200 species of birds.

The site provides refuge for three endangered and threatened species: the red-cockaded woodpecker, the southern bald eagle, and the wood stork. Many research projects conducted at the site are designed to protect and increase the populations of these species (Chapters 13 and 14, "Savannah River Ecology Laboratory" and "Savannah River Forest Station," respectively).

SRS maintains a forest management program to contribute to environmental protection and research. Additional information about SRS and the surrounding

area can be found in *The Savannah River Plant Environment* [Dukes, 1984].

DESCRIPTION OF SRS OPERATIONS AND FACILITIES

SRS, one of 16 facilities in the U.S. Department of Energy (DOE) complex, is operated by Westinghouse Savannah River Company (WSRC). SRS produces plutonium, tritium, and other special nuclear materials for national defense; however, nuclear materials produced at the site also are used for other government programs and for some civilian purposes. For example, SRS-produced Pu-238 is used as an energy source in the U.S. space program.

SRS consists of six major production areas: reactor areas (C, K, L, P, and R areas); separations areas (F and H areas); waste management areas (E, G, S, Y, and Z areas); the heavy water reprocessing area (D Area); the reactor materials area (M Area); and the administration area (A Area).

Each group has a specific function for the site. The following sections provide brief descriptions of the primary operations conducted within each area. Table 1-1, at the end of this chapter, summarizes the major SRS production groups, the facilities within each area, the radionuclides released during 1991, and the operating periods for these facilities.

Figure 1-2 shows the various operating areas at SRS, and Figure 1-3 details the environmental release pathways of each area.

Reactor Areas

Five nuclear production reactors are located at SRS—one in each of the C, K, L, P, and R areas. All five SRS reactors were inoperative during 1991. R Reactor was shut down permanently in 1964, and C Reactor was placed in cold-standby in 1987, when cracking was observed in the reactor vessel. K, L, and P Reactors were shut down for maintenance and safety upgrades in 1988. DOE announced in February 1991 that P Reactor would be shut down permanently, but would continue to provide spare parts for both L and K Reactors. In December 1991, DOE announced that L Reactor would be put on standby status and not restarted for at least three years.

Initial steps to restart K Reactor began in December 1991. During the K-Reactor startup, a leak from one of the heat exchangers resulted in a liquid release of approximately 5,700 Ci of tritium. The spill, which occurred Dec. 22-25, was one of the largest liquid releases of tritium in recent years and is discussed in detail in Chapter 10, "Nonroutine Occurrences."

When SRS reactors operate, plutonium and tritium are created by uranium and lithium absorption of neutrons. The release of nuclear particles (neutrons, photons, etc.) and heat from fissioning atoms within the reactors produces enormous amounts of energy.

Heavy water is circulated in a closed system through heat exchangers to moderate and cool the reactors. Water from the Savannah River and Par Pond, a man-made cooling water impoundment covering 2,640 acres, provides coolant for the heat exchangers.

Heat exchanger cooling water does not pass directly through the reactors; therefore, it is not subject to direct neutron activation. The heat exchanger cooling water from P Reactor is returned to Par Pond, which overflows to Lower Three Runs Creek. The L and K reactors use Savannah River water as a heat exchanger coolant. L-Reactor heat exchanger cooling water is discharged to L Lake, which overflows to Steel Creek. K-Reactor heat exchanger cooling water is discharged to Pen Branch; however, a cooling tower being constructed in K Area is scheduled for completion in June 1992, with tie-in planned for December 1992.

Although the reactors did not operate during 1991, various maintenance operations ongoing in the reactor

areas resulted in atmospheric and liquid releases (Table 1-1).

Reactor Materials Area

The Reactor Materials Area (M Area) consists of a fuel and target fabrication facility, three analytical laboratories, and an effluent treatment facility.

The fuel fabrication facility produces fuel and target elements to be used in the reactors. Control rods and other reactor components also are manufactured within the facility.

Three laboratory facilities in M Area provide analytical support for reactor facilities, heavy water facilities, fuel fabrication facilities, and the liquid effluent treatment facilities.

The Liquid Effluent Treatment Facility (LETf) in M Area treats wastewater generated by various M-Area processes for discharge to Tims Branch, which feeds into Upper Three Runs Creek. It also consolidates low radioactivity residues from M-Area processes for eventual disposal in Y Area, to be located within the boundaries of Z Area.

Separations and Waste Management Areas

Reactor-generated products are processed in the separations areas in F and H areas (Table 1-1). Operations in the separations areas also include tritium processing and receipt of offsite fuel. Waste management and storage activities also are performed in E, G, S, Y, and Z areas. E Area is a newly designated area between F and H areas that eventually will include all the site's disposal and storage facilities. Locations not within areas designated for specific purposes are called G Area, or General Area.

Complex chemical and physical processes in the F- and H-area canyon buildings separate uranium, plutonium, and fission products. The separated plutonium and uranium are transferred to other facilities in F and H areas and processed into solid form. Fission products are stored in high-level waste tanks in F and H areas.

Two primary tritium facilities located in H Area extract and separate tritium from targets irradiated in SRS reactors. The tritium is processed and packaged for shipment to other DOE facilities.

The Replacement Tritium Facility (RTF), a one-acre underground facility under construction in H Area, is scheduled to begin operation in 1993. This project originally was scheduled to be completed in 1992, but construction was temporarily suspended in May because of a lack of financial and administrative

Figure 1-2 SRS Includes six major production areas, the Savannah River Ecology Laboratory, and the Savannah River Laboratory.

controls. The RTF will replace gas separation and loading operations now performed in one of the existing tritium facilities. The RTF is designed to minimize tritium losses to the environment and to reduce waste generation. The RTF and the existing tritium facility will operate concurrently for approximately one year.

Production control laboratories, located in F Area, provide analytical support for F- and H-area separations processes, waste management, and reactor materials activities.

Offsite fuel that will be processed in the H-Area canyon building is stored and packaged in the Receiving Basin for Offsite Fuel (RBOF). Other operations conducted at RBOF include cleaning lithium-aluminum targets for processing in the tritium facilities and processing deionizers used in the reactor areas. Most radioactive waste generated from RBOF operations is contained in liquid waste that is transferred to the high-level waste storage tanks located in F and H areas.

In July 1991, the Nuclear Materials Processing Division restarted the HB Line (chemical processing) in the H-Area canyon for Pu-238 separation. Shipments of the Pu-238 to Los Alamos National Laboratory for encapsulation into fuel for the space program began in August. The fuel will power two upcoming space probes in the mid- 1990s: Cassini (to the planet Saturn) and CRAF (Comet Rendezvous Asteroid Fly By).

Facilities located in the separations and waste management areas are designed to store or treat wastes generated from onsite operations. These facilities include the F- and H-area Effluent Treatment Facility (ETF), the Defense Waste Processing Facility (DWPF), the high-level waste tank farms, the Y- and Z-area Saltstone Facilities, and the Solid Waste Disposal Facility (SWDF), formerly the Radioactive Waste Burial Grounds.

The ETF, located on the south side of H Area, collects and treats routine process wastewater, contaminated canyon facility cooling water, and tank farm storm water from F and H areas. The ETF removes radioactive and nonradioactive contaminants, except tritium, from process effluents, allowing the water to be discharged to Upper Three Runs Creek.

The DWPF, the nation's first high-level radioactive waste vitrification plant, is located in S Area. When

operational, the DWPF will accept high-level radioactive waste stored in the F- and H-area waste tanks and mix the waste with glass frit. The mixture is heated and cooled to form a solid inert glass form suitable for storage in offsite geologic repositories. The glass form and the geologic repository will effectively isolate the nuclear waste from the environment. Nonradioactive integrated water runs (water used as feed) began in the spring of 1991. Cold chemical runs, simulated nonradioactive feed, are scheduled to start in the fall of 1992. The scheduled start for radioactive runs at DWPF is the spring of 1994.

The F- and H-area tank farms consist of large underground storage tanks that store high-level aqueous radioactive waste and evaporated saltcake. The wastes, contained in 29 tanks in H Area and 22 tanks in F Area, eventually will be removed and processed in the DWPF.

Another waste storage area, the Z-Area Saltstone Facility, is designed to process and dispose of the decontaminated salt solution supernates from the storage tanks in F and H Areas and from ETF concentrate. Since its startup in June 1990, the Saltstone Facility has processed approximately one million gallons of salt solution into 12,000 tons of salts. Similarly, Y Area will process sludges generated from the Reactor Materials Area. The decontaminated salt solution, or sludge, is immobilized with solidifying agents such as slag, fly ash, or cement, and disposed of in concrete vaults.

Solid radioactive wastes generated at SRS and other DOE facilities are buried in the SWDF—located in E Area between F and H areas. The SWDF consists of separate trenches for wastes with high-level radioactivity and wastes with low-level radioactivity. Types of waste buried in the SWDF include contaminated equipment, waste from laboratory operations (e.g., gloves, beakers), and scrap and tools used in the reactor areas.

Heavy Water Reprocessing Area

A heavy water production plant, located in D Area, began operation in 1953 to produce heavy water to moderate and cool the site's reactors. The facility stopped processes in 1981 because of a sufficient supply of heavy water. The facilities currently operating in D Area include a heavy water reprocessing facility, a coal-fired power plant, and a laboratory facility that analyzes process effluent samples.

Figure 1-3 Pathways of Atmospheric and Liquid Releases from SRS Areas. Broken lines indicate that discharges to these seepage basins have been discontinued.

Administration Area

The Administration Area (A Area) contains organizations that provide direct support for SRS operations. DOE's Savannah River Operations Office (DOE-SR) and WSRC administrative offices are based in A Area. The Savannah River Laboratory (SRL) performs research and development activities and provides analytical support for onsite operations, and the University of Georgia's Savannah River Ecology Laboratory (SREL) conducts independent environmental research projects.

Other Areas

Other facilities that support SRS operations are located onsite and offsite. The onsite areas include training facilities (B Area), central shops (CS Area), and the U.S. Savannah River Forest Station (SRFS) headquarters. Many administrative activities are conducted offsite, with offices based in Aiken and North Augusta, S.C., and in Augusta.

DESCRIPTION OF ENVIRONMENTAL MONITORING PROGRAMS

SRS conducts an extensive environmental monitoring program consisting of radiological and nonradiological monitoring at and around the site. The Environmental Monitoring Section (EMS) of the Environmental Protection Department (EPD) conducts most radiological and nonradiological environmental monitoring programs for SRS. However, other groups onsite including SREL, SRL, and WSRC Power Department also conduct various environmental monitoring activities for SRS. Detailed information about the radiological and nonradiological monitoring programs is provided in later chapters of this report.

DESCRIPTION OF ENVIRONMENTAL RESEARCH AND SERVICE

DOE designated SRS as the first National Environmental Research Park in 1972. Since then, scientists from universities and other organizations have used the site as an outdoor laboratory to study the impact of human activities on the environment. The protected boundaries of the site provide land suitable for long-term research projects. In addition, almost 12,000 acres (5 percent) of SRS land is specifically protected for research. These areas, designated as set-aside areas, provide undisturbed land for comparison with areas affected by SRS operations and forest management.

As a result of the research park program, scientists have compiled detailed information on many aspects of the

SRS environment, including soil development and inventories of plant and animal species.

The 40th anniversary for research conducted by SREL at SRS was celebrated in 1991. Also, SREL's faculty, technicians, students, and visiting scientists published three books and approximately 100 research articles in conjunction with the Research Park program.

National Environmental Research Park activities are coordinated through SRL's Savannah River Research Center, SREL, or SRFS. In 1991, each of these groups conducted research activities under the Research Park program. This research is summarized in Chapters 12 ("Savannah River Laboratory"), 13, and 14 of this report.

Other research programs, in addition to Research Parks programs, are conducted each year at SRS by various onsite groups, including SRL, SREL, and SRFS.

Environmental Exchange

In an effort to improve and update the environmental monitoring and research programs, SRS has opened several avenues of exchange with other scientists.

Technical Information Exchange

The DOE-SR Environmental Restoration Division hosted a Technical Information Exchange (TIE) Workshop Nov. 17-20 in Augusta. More than 120 DOE contractor representatives from across the United States shared environmental technologies and experiences in support of DOE's mission to clean up the environment. This first-ever TIE grew from a suggestion by a DOE area technology representative team as a method to enhance the exchange of technical information among DOE sites.

Environmental Advisory Committee

The Environmental Advisory Committee, which consists of seven nationally recognized consultants from the fields of biology, ecology, hydrogeology, health physics, environmental restoration, and economics, meets quarterly to review environmental programs and make recommendations for those programs.

Data Exchange Program

Representatives from the South Carolina Department of Health and Environmental Control (SCDHEC), Georgia Department of Natural Resources (GDNR), Georgia Power Company, Chem-Nuclear Systems, DOE, and WSRC have met quarterly since 1987 in a Data Exchange Program to share technical environ-

A cooling tower under construction in K Area is scheduled for completion in June 1992.

mental program information and data from environmental radioactivity sampling. These meetings provide an open forum to review and possibly improve each organization's monitoring program.

The Data Exchange Committee held one meeting in 1991. At this meeting, the *Savannah River Site Environmental Report for 1990* was presented to the Data Exchange members, along with a summary of analytical results and laboratory techniques from the intercomparison study that began in 1990.

ENVIRONMENTAL PROGRAM INFORMATION

Waste Minimization Program

SRS is actively developing and implementing waste reduction and minimization programs to decrease the amount of solid waste generated by site operations. These efforts are coordinated by the site Waste Action Team and Waste Minimization Group, which not only assist site operating groups in setting goals and reducing waste generation, but provide guidance and document results.

A sitewide Waste Minimization Plan was published in 1989 to identify objectives, goals, and activities for the programs. All SRS facilities prepared facility-specific waste minimization plans during 1991. An expanded activity of the facility-specific plans is the process waste assessment (PWA). Through the PWA, each facility identifies the origins of its waste streams and systematically determines which streams and methods to target for minimization.

Implementation of a recycling program continued to be a major focus in 1991. Recycling of antifreeze, lathe coolants, solvents, paints, solvent-contaminated rags, and silver from photographic solvents is concentrated in one area at SRS. Aluminum cans are being recycled across the site, and plans for programs to recycle paper, cardboard, plastic, and glass are in progress. Security concerns and funding requirements prohibited the awarding of a recycling contract in 1991. However, several site groups are re-evaluating the recycling program, and a new bid contract should be prepared during the coming year.

A cardboard recycling program is being explored to parallel the paper recycling effort. Cardboard does not carry security concerns, yet it accounts for a large

percentage of the landfill's total waste. SRS is looking into establishing a contract with a local recycling firm to accept cardboard from bins in high-generation areas of the site.

An affirmative procurement program is being developed onsite to encourage the purchase of products made from recycled or reclaimed materials. The program is aimed at educating consumers, buyers, and vendors.

Environmental Awareness Day

Environmental Awareness Day, initiated in 1988, is observed with displays and presentations across the site by WSRC, SREL, SRFS, and other organizations to show personnel the importance of protection of natural resources in daily living. The 1991 program—"Our Natural Resources: A Legacy for the Future...?"—included planting trees in Augusta and preparing resource kits for local schoolchildren.

Public Information

State and federal regulations require SRS to notify the public about various environmental activities. For this reason, SRS's Environmental Protection and Public Relations departments started a newsletter, *Environmental Bulletin*, in 1990 to notify the public about ongoing environmental issues at SRS. The bulletin was published monthly in 1991 to provide information on such items as public hearings on Environmental Impact Statements (EIS) and Resource Conservation and Recovery Act (RCRA) permit modifications.

SRS's fiscal year 1992 Site Specific Plan (SSP) for environmental restoration and waste management was completed in 1990. The SSP supports DOE's five-year plan to eliminate or reduce the risks to human health, safety, and the environment at nuclear-related waste sites by the year 2019. During the year, SRS staff discussed the SSP with the public in Aiken and Columbia, S.C., and Savannah, Ga.

Environmental Outreach

WSRC's Environmental Protection and Public Affairs departments and the DOE Office of External Affairs inform the public about environmental issues through a program called "Environmental Outreach." The outreach program, begun in 1988, offers site tours and stewardship talks about environmental activities to the general public, including elected officials, environmental groups, school groups, the media, and civic organizations. SRS conducts environmental training

programs to increase employee awareness of environmental activities as well.

In an ongoing effort to address public concerns about environmental issues at SRS, the site held several public meetings in 1991. Sessions were held in the Savannah-Beaufort-Hilton Head Island, S.C., region to address concerns about tritium in the Savannah River. SRS officials met with civic groups and government agencies in the area.

A public workshop was held in March to discuss the SRS priority system for cleanup and waste management. After the SSP was updated and the Environmental Restoration and Waste Management Five-Year Plan was released, public meetings were held in October in Savannah, Columbia, and Aiken.

In 1991, SRS began a series of public meetings called Environmental Forums to address local community concerns. An advisory committee from the Barnwell County area helped prepare the agenda for the first forum. Additional forums are planned for Aiken, Columbia, Augusta, Savannah, and Hilton Head Island.

Many of these environmental outreach activities resulted from interviews with local citizens in 1990. The Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) requires a site to write a community relations plan once it is placed on the National Priority List (Superfund cleanup). SRS was placed on the National Priority List (NPL) in December 1989. In 1990, 85 local citizens were interviewed for their ideas on how and when they wanted information from SRS. The SRS plan, called the Public Involvement Plan (PIP), goes a step beyond CERCLA to include public involvement opportunities for other environmental regulations. The PIP was released Dec. 17, 1991, for a 60-day public comment period.

Many other environmental outreach activities were held throughout 1991, including environmental tours for the public and environmental presentations to civic clubs, churches, and schools.

Environmental Training Programs

SRS provides environmental training programs to enhance knowledge and qualifications for personnel performing tasks associated with environmental assessment, planning, and restoration at the site. This training, mandated by various environmental laws and regulations, is designed to achieve compliance with all applicable requirements for the affected SRS personnel. A multi-faceted approach has been used to provide

a comprehensive training program flexible enough to meet the needs of the site population. The program includes both onsite and offsite classroom instruction, on-the-job training, seminars and video conferences, and specialized workshops and courses. A summary of the environmental training activities conducted or prepared by SRS during 1991 includes:

- Hazardous Waste Site Worker Training
- Hazardous Waste Site Manager/Supervisor Training
- RCRA Training for Treatment, Storage, and Disposal Facility Workers
- National Environmental Policy Act (NEPA) Orientation Training
- Environmental Laws and Regulations Training
- Water/Wastewater Treatment Certification Training
- Westinghouse/DOE Environmental School of Excellence

Table 1-1
Onsite Operating Areas

Area	Radionuclides Released in 1991 ^a		Periods of Operation
	Atmospheric	Liquid	
Reactor areas	Tritium, ^{89,90} Sr, ¹³¹ I, ²³⁹ Pu	Tritium, ⁹⁰ Sr, ²³⁹ Pu	
• Reactors (C, L, K, P, and R)			None
Reactor Materials Area	^{89,90} Sr, ^{235,238} U	⁹⁰ Sr, ^{235,238} U, ²³⁹ Pu	
• Fuel Fabrication Facility			Jan-Dec 1991
• Analytical laboratory facilities			Jan-Dec 1991
• Liquid Effluent Treatment Facility			Jan-Dec 1991
Separations Areas	Tritium, ¹⁴ C, ⁸⁵ Kr, ¹²⁹ I, ¹³¹ I, ⁶⁰ Co, ^{89,90} Sr, ¹⁰⁶ Ru, ¹²⁵ Sb, ¹³⁴ Cs, ¹³⁷ Cs, ¹⁴⁴ Ce, ^{235,238} U, ²³⁸ Pu, ²³⁹ Pu, ^{241,243} Am, ^{242,244} Cm	Tritium, ⁹⁰ Sr, ¹³⁷ Cs, ¹⁴⁷ Pm, ^{235,238} U, ²³⁹ Pu	
• Canyon facilities (F Area)			15% of the year
• Canyon facility (H Area)			10% of the year
• Effluent Treatment Facility (H Area)			Jan-Dec 1991
• Receiving Basin for Offsite Fuel (H Area)			Jan-Dec 1991
• Tritium facilities (H Area)			Jan-Dec 1991
• Tank farms (F Area)			Jan-Dec 1991
• Tank farms (H Area)			Jan-Dec 1991
Waste Management Areas	None	None	
• Defense Waste Processing Facility			Cold runs Jan-Dec 1991
• Saltstone facility			Jan-Dec 1991
• Solid Waste Disposal Facility			Jan-Dec 1991
Heavy Water Reprocessing Area	Tritium, ^{89,90} Sr, ²³⁹ Pu	Tritium, ⁹⁰ Sr, ²³⁹ Pu	
• Coal-fired power plant			Jan-Dec 1991
• Analytical laboratory facility			Jan-Dec 1991
• Heavy water rework facility			50% of the year
Administration Area			
• Savannah River Laboratory	¹³¹ I, ¹³³ I, ⁶⁰ Co, ^{89,90} Sr, ¹³⁷ Cs, ²³⁹ Pu	Tritium, ⁹⁰ Sr, ²³⁹ Pu	Jan-Dec 1991

^a The radionuclides released are listed in no particular order.

To Learn About:	Turn to page:
♦ Waste unit closures	15
♦ Mixed-waste disposal compliance	15
♦ NEPA compliance issues	17
♦ SRS PCB program	20
♦ DOE-SR appraisal reports for 1991	21
♦ Tritium release from K Reactor	25

Compiled by Patricia J. West
Environmental Protection Department

Environmental Compliance

1991 HIGHLIGHTS

- ♦ The closure plan for the Metallurgical Laboratory Seepage Basin was approved in September, and construction is 30 percent complete.
- ♦ WSRC removed three tanks and abandoned five tanks in place as part of a program begun in 1989 to abandon or remove all regulated single-wall underground storage tanks at SRS by 1998.
- ♦ Under the National Environmental Policy Act, WSRC conducted approximately 340 reviews for proposed federal actions at SRS. One of these activities included an Environmental Assessment on the impacts of Pu-238 processing and fabrication at SRS with a Finding of No Significant Impact published in the *Federal Register* in July.
- ♦ During a DOE appraisal of the polychlorinated bipheynyl (PCB) program conducted in November, three noteworthy practices and one deficiency were cited. Noteworthy practices included preparing a draft PCB Management Manual and writing comments on proposed PCB regulations. The deficiency concerned the reporting of the weight of the PCB fraction in transformer oil, rather than the entire weight of the oil. The deficiency will be corrected.
- ♦ On April 1, SRS submitted an alternative radiological monitoring system package to EPA, as required by 40 CFR 61, the National Emission Standards for Hazardous Air Pollutants. Because EPA did not approve the alternative package, an interim Federal Facilities Compliance Agreement was approved June 30, and a final one was signed Oct. 31.

INTRODUCTION

Compliance with environmental regulations and U.S. Department of Energy (DOE) Orders relating to environmental protection is an important part of the Savannah River Site (SRS) program. Management of the environmental programs is a major task; more than 1,000 people are devoted full-time to environmental activities at SRS. Chart 2-1 lists some of the key regulations and relevant information regarding them.

All activities at SRS are overseen by one or more regulators, such as the South Carolina Department of Health and Environmental Control (SCDHEC) and the Environmental Protection Agency (EPA). Over the last few years, the number of regulations affecting

site operations has increased dramatically. Considerable effort in recent years has gone toward bringing all SRS facilities and operations into compliance with the appropriate regulations.

COMPLIANCE STATUS

Resource Conservation and Recovery Act

The federal Resource Conservation and Recovery Act (RCRA) was passed in 1976 to address the problem of how to deal with the country's huge volume of solid waste. The law requires the EPA to regulate the management of hazardous waste, which includes solvents, batteries, petroleum products, and many other substances deemed to be harmful to human health and the environment. RCRA also regulates

Chart 2-1
Key Federal Regulations that SRS Must Follow

Legislation	What It Regulates/SRS Compliance Posture
RCRA Resource Conservation and Recovery Act	◆ Management of hazardous, nonhazardous, and medical waste and underground storage tanks containing hazardous substances and petroleum products.
CERCLA; SARA Comprehensive Environmental Response, Compensation, and Liability Act; Superfund Amendments and Reauthorization Act	◆ Establish liability, compensation, cleanup, and emergency response for hazardous substances released to the environment. ◆ SRS was placed on National Priority List (NPL) in December 1989.
CERCLA (TITLE III); EPCRA Emergency Planning and Community Right-to-Know Act	◆ Requires that hazardous substances used onsite be reported to state and local planning units.
CWA; NPDES Clean Water Act; National Pollutant Discharge Elimination System	◆ Regulates liquid discharges at the end of each conveyance (e.g., drain or pipe) that carries effluents to streams.
CAA; NESHAP Clean Air Act; National Emission Standards for Hazardous Air Pollutants	◆ Sets air quality standards for hazardous air emissions, such as radionuclides and benzene.
TSCA Toxic Substances Control Act	◆ Regulates polychlorinated biphenyls (PCBs) use and disposal. ◆ Since there currently is no disposal facility in the country, radioactive PCBs generated at SRS are stored onsite.
NEPA National Environmental Policy Act	◆ Evaluates potential environmental impacts of federal activities and alternatives. In 1991, WSRC conducted 340 reviews for proposed activities.

some nonhazardous waste, the nonradioactive portion of mixed waste, underground storage tanks, and medical waste.

RCRA addresses the production, treatment, storage, and disposal of hazardous waste; this is referred to as "cradle to grave" control. Generators of hazardous waste, such as SRS, must follow very specific requirements for handling these wastes. RCRA requires that owners and operators of hazardous-waste management facilities obtain operating or post-clo-

sure care permits for many waste management activities. Chart 2-2 summarizes SRS closure activities conducted during 1991 under RCRA.

EPA has authority for all hazardous-waste regulations. However, the agency can delegate this authority to a state when the state passes laws and regulations that meet or exceed EPA regulations, and the state plan is approved by EPA. SCDHEC has authority for all aspects of RCRA except the 1984 Hazardous and Solid Waste Act Amendments to RCRA.

Chart 2-2
Waste Units Undergoing RCRA Closure During 1991

Waste Units	Contamination	Status In 1991
F-Area seepage basins (three basins)	Low-level mixed waste	◆ Closed in January 1991; certified in April 1991 ◆ Post-closure plan submitted to SCDHEC in December 1990
H-Area seepage basins (four basins)	Low-level mixed waste	◆ Closed in May 1991; certified in October 1991 ◆ Post-closure plan submitted to SCDHEC in December 1990
M-Area Settling Basin	Degreasing solvents and low-level uranium	◆ Closed in January 1991; certified in April 1991
Mixed Waste Management Facility (58 acres of the existing 195-acre Low-level Waste Disposal Facility)	Mixed waste	◆ Closed in December 1990; certified in April 1991
Underground Storage Tank 105-C	Corrosive	◆ Closed in September 1991; certified in December 1991
Acid/caustic basins in F, H, K, and P areas	Dilute sulfuric acid and sodium hydroxide	◆ Closure plan under SCDHEC review
Metallurgical Laboratory Seepage Basin (a Carolina bay will be part of this closure)	Organic chemicals	◆ Closure plan approved September 1991 ◆ Construction started, 30 percent complete

Land Disposal Restrictions

The 1984 amendments to RCRA established what are known as the land disposal restrictions (LDRs), often referred to as "land ban." These regulations allow storage of hazardous wastes for a limited time and prohibit the disposal of untreated waste in land disposal units. The amendments require that all wastes meet treatment standards based on the best available technology prior to land disposal.

The same restrictions apply to mixed waste, that is, waste composed of a mixture of radioactive and hazardous waste. SRS maintains that LDRs applicable to mixed wastes require regulatory agreements in order to achieve compliance. Therefore, a Federal

Facilities Compliance Agreement (FFCA) was negotiated between the DOE-Savannah River Operations Office (DOE-SR) and EPA Region IV (Alabama, Florida, Georgia, Kentucky, Mississippi, North Carolina, South Carolina, and Tennessee) to address SRS mixed-waste compliance with LDRs. This agreement was signed in March 1991.

The LDR FFCA, however, does not address some mixed wastes, which could become prohibited from land disposal May 8, 1992. At this time, SRS is designing treatment and disposal facilities for these mixed wastes. If the site continues to generate the prohibited mixed-waste streams, it must store them until the facilities are complete.

SRS has identified 17 major waste streams that could become prohibited from land disposal May 8, 1992. To reduce the impact of the potential prohibition on site operations, negotiations to modify the LDR FFCA will begin in January 1992, with a goal of having the document signed by the prohibition date. In addition, the site included all 17 waste streams in the DOE Comprehensive Case-By-Case Extension request, recently submitted to EPA. Finally, SRS is preparing treatability variances for a certain number of the mixed-waste streams.

Treatability variances are an option available to facilities for particular waste streams that either cannot be treated at the level specified in the regulations, or where the treatment technology is inappropriate for the waste. The variance petitions are reviewed either by EPA in Washington, D.C., or by Region IV, depending on the type of waste and whether the variance request is site specific or generic. SRS has identified six mixed-waste streams that are potential candidates for a treatability variance. One variance, for in-tank precipitation filters, has been prepared and will be submitted to EPA Region IV in early 1992 for review. A second variance, for cadmium-containing safety and control rods, is being prepared. These variances, depending on the alternate technology proposed, may eliminate some of the storage prohibition problem.

Underground Storage Tanks

Underground storage tanks at SRS store petroleum products, such as gasoline, diesel fuel, and hazardous substances, as defined by the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA). All of these tanks are regulated under Subtitle I of RCRA.

DOE-SR requested in 1989 that Westinghouse Savannah River Company (WSRC) begin a program to abandon or remove all regulated single-wall storage tanks at SRS by 1998. In 1991, WSRC removed three tanks and abandoned five tanks in place. In addition, 14 tanks associated with former municipal or military areas that had been abandoned prior to 1974 were removed. Tightness testing using approved methodology was performed on 15 tanks as required by SCDHEC regulations.

In areas where underground tanks are still needed, WSRC will replace the tanks with double-walled tanks having leak detection systems. To complete this project, removal or abandonment is required for 30 additional tanks.

RCRA Hazardous-Waste Facilities Location Standards

Location standards regulations for RCRA hazardous-waste facilities became effective in South Carolina in February 1991. Under the new regulations, existing permitted hazardous-waste facilities were required to submit a compliance demonstration within 180 days (Aug. 21, 1991) of the effective date, while new facilities must meet certain conditions before they are built. The Hazardous Waste Storage Facility was the only facility for which a compliance demonstration was required by the Aug. 21 deadline, as it was the only SCDHEC-permitted facility. The demonstration was submitted on time. In addition, SRS submitted compliance demonstrations to SCDHEC for five other facilities with Part B permit applications. Part B permits allow for the treatment, storage, and disposal of hazardous wastes. These facilities are under "interim" status, which means that SRS has applied for permits, but SCDHEC has not acted on the applications yet. In anticipation of future need, the compliance demonstrations for seven interim-status facilities without Part B permit applications submitted to SCDHEC were completed and will be submitted when the Part B permit applications for these facilities are completed. For two proposed facilities, compliance demonstrations were completed as far as design information would allow.

Location standards demonstrations are ongoing for other expanding and interim-status facilities and will be completed as required.

RCRA Facility Investigation Program

The Hazardous Waste Permit issued to SRS in September 1987 requires that the site institute a program for investigating solid-waste management units (SWMUs). The RCRA Facility Investigation Program (RFI) plan requires the investigation and remediation (if necessary) of releases of hazardous waste/constituents from SWMUs.

SRS submitted to SCDHEC and the EPA Region IV program an RFI plan—approved in 1989—that specified the generic methods and procedures to be used for each unit-specific investigation. The plan is being updated to incorporate requirements of the pending Federal Facilities Agreement (FFA) and new CERCLA guidance and regulations.

During 1991, 15 Revision 0 work plans were submitted to EPA/SCDHEC, and 13 more (Revision 1) were submitted to EPA/SCDHEC incorporating EPA's comments. Finally, two proposed work plans

were sent to EPA/SCDHEC. None of the plans received final approval during 1991.

Comprehensive Environmental Response, Compensation, and Liability Act

SRS is subject to the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA), also known as Superfund. SRS was placed on the nation's CERCLA National Priority List in December 1989. CERCLA establishes a response program for releases or potential releases of hazardous substances to the environment, as well as a mechanism for remediation. RCRA addresses hazardous waste, whereas CERCLA addresses all hazardous substances, including radionuclides. All releases to the environment must be evaluated under the CERCLA program, which encompasses the entire site, including 102 waste units now being investigated for remediation. The program also includes more than 300 sites being evaluated to determine if there is a need for further investigation.

Remediation under CERCLA imposes requirements in addition to existing RCRA requirements. For example, additional training may be necessary for those people involved in activities on any RCRA/CERCLA units. Furthermore, all documentation of the remedial process must now be available to the public.

The RFI Program plan under RCRA was expanded to address CERCLA hazardous substances and was renamed the RFI/Remedial Investigation Program Plan. Integration of RCRA and CERCLA regulatory requirements will provide a more cost-effective and focused investigation and remediation process.

CERCLA-Reportable Releases

CERCLA requires that the National Response Center (operated by the U.S. Coast Guard) be notified in the event of a non-federally permitted release of a reportable quantity (RQ) of a hazardous substance, including radionuclides. The center then alerts appropriate federal and state emergency response personnel so they can evaluate whether government response is appropriate.

During 1991, four releases from SRS were reported to the center. Each involved a tritium release that exceeded the RQ of 100 Ci. The releases were reported in compliance with EPA's broad definition of a release and DOE's interpretation that unplanned

releases of a radionuclide in excess of an RQ are not federally permitted under the Atomic Energy Act.

Federal Facilities Agreement

In accordance with Section 120 of CERCLA, DOE negotiated with EPA Region IV and the SCDHEC to prepare a FFA in 1991. A draft FFA for SRS was released on Dec. 17 for a 60-day public comment period. This document represents an agreement between the three agencies directing the comprehensive remediation of SRS. The agreement is expected to be signed in 1992.

Public Involvement Plan

A Public Involvement Plan (PIP) has been reviewed by both EPA Region IV and SCDHEC. Public comment was sought during the same period as for the draft FFA. SRS, EPA Region IV, and SCDHEC are preparing responses to those comments. A Responsiveness Summary will be prepared by the three parties and released to the public. The PIP list provides for four information repositories: The DOE Public Reading Room, University of South Carolina at Aiken; the Thomas Cooper Library, Government Documents Department, University of South Carolina, Columbia; the Reese Library, Augusta College, Augusta, Ga.; and the Asa H. Gordon Library, Savannah State College, Savannah, Ga.

The PIP, which fulfills the CERCLA requirement for a community relations plan, was expanded by SRS to cover requirements of other laws and regulations, in addition to DOE guidance. Development of the plan is based on community interviews and other relevant information specifying the community relations activities that SRS, EPA, and SCDHEC expect to undertake during the remediation of SRS.

National Environmental Policy Act

The National Environmental Policy Act of 1969 (NEPA) provides a means to evaluate potential environmental impacts of proposed federal activities and examine alternatives to those actions. At SRS, a NEPA compliance group directs the level of NEPA review of a proposed action and supports preparation of documentation supporting DOE compliance with NEPA. In 1991, the NEPA team conducted approximately 340 reviews for proposed federal actions at SRS and formally documented these reviews through Categorical Exclusions, Special Environmental Analyses, or Environmental Assessments (EAs). WSRC also provided technical support to DOE-SR for the preparation of Environmental Impact Statements (EISs).

NEPA activities conducted during 1991 included the following:

- An EA on the Soil Stabilization Project for the restart of K Reactor was finalized and made available in August. This project was part of the NEPA documentation necessary for implementing the reactor restart program.
- A draft EA on the Operation of the Uranium Solidification Facility in Building 221-H was submitted to DOE-SR in May. The draft document is undergoing revisions per comments from DOE Headquarters (DOE-HQ).
- A final EA on the Radioisotope Heat Source Fuel Processing Fabrication operation was made available to the public by DOE in July. The Finding of No Significant Impact (FONSI) was published in the *Federal Register* later in July. This document reviewed the impacts of Pu-238 processing and fabrication at SRS and Los Alamos National Laboratory near Los Alamos, N.M.
- A Supplement Analysis, which supplements an EA, was prepared to assess the impacts resulting from the project-specific design of the proposed M-Area Waste Disposal Facility (Y Area).
- The draft EA on the Consolidated Incineration Facility was in the review-and-comment stage at DOE-HQ for most of the 1991 calendar year. The document was in the final revision stage in December and was sent to the South Carolina and Georgia governments for review prior to issuance.
- The draft EA on the proposed upgrade of both the Plantwide Fire Protection System and related Domestic Water Supply System was finalized—and the FONSI issued—in December. The proposed project would upgrade both systems on a sitewide basis.
- A preliminary draft EA on the proposed New Whole Body Counter Facility in B Area was submitted to DOE-SR for review and comment in December. This project will enable the site to meet increasing needs for monitoring employees for internal radionuclides.
- A Special Environmental Analysis was prepared by DOE-SR in August to assess the potential environmental impacts associated with management, maintenance, and repair activities on the Par Pond Dam. This document fulfilled a commitment made by DOE-HQ to the President's Council on Environmental Quality (CEQ) regarding the Par Pond issue.
- A preliminary draft EA on the Hazardous Low-Level Waste Processing Tanks facility in H Area was submitted to DOE-SR in November. This project will enable the site to comply with the Federal Facilities Agreement regarding the interim storage and processing of low-level waste.
- The draft EIS for the Siting, Construction, and Operation of New Production Reactor (NPR) Capacity was issued in April for public comment. Because of Secretary of Energy James D. Watkins' announcement to incorporate the siting and technology of the NPR into the EIS on the nuclear weapons complex reconfiguration, the final EIS was not issued. The NPR information will be included in the Weapons Reconfiguration Programmatic Environmental Impact Statement (PEIS), which will be finalized in August 1993.

Other NEPA documents completed during 1991 included a draft EA on 105-K Grouting Phase II; a draft EA on Storage of Plutonium Metal in Building 247-F Vault; an analysis of the Environmental impacts Resulting from the Modifications in the Defense Waste Processing Facility; and a draft EA on Natural Resources Management Activities at SRS.

A total of 323 Categorical Exclusion recommendations was forwarded to DOE-SR during the 1991 calendar year. Discussions have been undertaken by SRS regarding implementation of the final DOE regulation (10 CFR 1021) concerning NEPA compliance within the DOE Complex.

Safe Drinking Water Act

The Safe Drinking Water Act (SDWA) was enacted in 1974 to protect public drinking water systems, then amended in 1980 and 1986. SRS provides drinking water to its employees through 14 major treatment/distribution systems.

In 1991, SRS instituted bacteriological (total coliform) compliance monitoring at all SRS area drinking water systems to comply with state drinking water regulations. This is part of a major effort to upgrade the site's drinking water systems. During October 1991, SRS and SCDHEC officials identified appropriate system modifications and developed a project timetable, with completion targeted for 1997.

Clean Water Act

The Clean Water Act (CWA) of 1972 created the National Pollutant Discharge Elimination System (NPDES) program. This program, regulated by SCDHEC under EPA authority, is intended to protect surface waters by limiting all nonradiological releases

of effluents into streams, reservoirs, and other wetlands. Discharge limits are set for each facility to ensure that SRS operations do not impact aquatic life adversely or decrease water quality.

An SRS NPDES permit (SC0000175) regulated 78 active NPDES outfalls onsite during 1991. Five additional NPDES outfalls under Permit SC0044903, effective Dec. 1, 1990, will allow discharge from the K-Reactor cooling tower, but these are not yet operational. All of the active permitted outfalls were sampled in 1991.

SRS NPDES permit compliance has steadily improved during the past eight years. The compliance rate for 1991 was 99.99 percent, based on 7,033 analyses. Only seven analyses exceeded NPDES permit limits. These exceedances occurred at six different locations. A table of exceedances (Table 8-16), including the location, probable cause, and corrective action, appears at the end of Chapter 8, "Water Pathways."

Emergency Planning and Community Right-To-Know Act (SARA Title III)

The Emergency Planning and Community Right-to-Know Act (EPCRA) of 1986 was enacted as a provision to the Superfund Amendments and Reauthorization Act (SARA). This statute requires businesses to notify state and local emergency planning units of the hazardous substances used at their facilities, including inventories of these substances. Industries also must report all planned and unplanned releases, such as CERCLA-reportable releases.

Under Section 312 of EPCRA, an annual Tier II Inventory Report must be filed by SRS every year by March 1 for all hazardous materials stored or used onsite in excess of specified quantities during the previous calendar year. Hazardous-chemical storage and use occurring in 1990 was submitted in March 1991. The Tier II report listed approximately 208 chemicals for 1990. Inventory data for 1991 is being collected for the March 1992 reporting date.

Under Section 313 of EPCRA, SRS must file an annual Toxic Chemical Release Inventory Report by July 1. SRS must calculate releases of regulated chemicals to air, land, water, and underground injection, and report aggregate quantities for each regulated chemical that exceeds established threshold amounts. In June 1991, SRS reported such releases occurring during the 1990 reporting year. Eleven

chemicals, with releases totaling 98,505 pounds, were reported.

The Pollution Prevention Act of 1990 will add additional reporting requirements for the July 1992 report. The act will require SRS to determine the quantity of a chemical that would enter a waste stream prior to treatment, recycling, or disposal. It also will require reporting amounts treated and recycled, source reduction activities, one-time events, and quantities of chemicals expected to enter a waste stream or be recycled in future years. The impact on operations from source reduction and recycling conducted during the previous calendar year will be evaluated and reported.

Clean Air Act

The federal Clean Air Act (CAA) establishes air quality and emission limits throughout the United States. SRS has 13 air quality permits covering 134 point sources for air emissions. SCDHEC conducted 21 inspections at SRS during 1991, and the site received one Notice of Violation (NOV) for exceeding the authorized opacity limit for a permitted diesel engine in K Area. The permit reflecting the diesel's operating parameters was corrected to reflect the permissible emissions rate, and the NOV was dismissed.

National Emission Standards for Hazardous Air Pollutants

The National Emission Standards for Hazardous Air Pollutants (NESHAP) is one section of the CAA; it sets air quality standards for air emissions containing hazardous constituents such as radionuclides and asbestos.

NESHAP Radionuclide Program

The SRS NESHAP radionuclide program is being revised to meet a Dec. 15, 1989, EPA revision of 40 CFR 61, Subpart H. The revision involves a change in dose standard to an offsite member of the public from 25 mrem per year to 10 mrem per year from airborne pathways. Although SRS monitoring systems indicate that SRS is below the current 10-mrem standard at the site boundary, the site monitoring approach differs from those specified in Subpart H of the regulations. However, the regulations allow EPA to approve alternate methods that essentially accomplish the results expected of the prescribed methods that have been used.

On April 1, 1991, SRS submitted an alternative radiological monitoring system package to EPA,

which requested that EPA approve an alternative overall monitoring approach under Subpart A. Although the overall application was denied, EPA did accept some of the SRS monitoring methods. Because the application was denied, it became necessary for SRS to negotiate with EPA an FFCA that allows SRS to continue to operate facilities while installing upgraded sampling and monitoring instrumentation. An interim FFCA was signed June 30, 1991. The interim FFCA was required to allow continued operation until the final FFCA could be executed. The final FFCA, signed Oct. 31, 1991, outlines a number of requirements for the air program, including upgrades of some site monitoring systems. It also requires that a comprehensive air emissions inventory for the site be completed by Dec. 31, 1993.

NESHAP Asbestos Removal Program

In the early 1950s, when SRS was under construction, asbestos insulation was among the top boiler and piping insulators and thus is present in older buildings on the site. The dangers of airborne asbestos fibers, which are carcinogenic, were unknown at the time.

The NESHAP standard does not set a numerical threshold for asbestos fiber emissions. Instead, it requires persons conducting asbestos-related activities, such as demolition and renovation, to notify SCDHEC of removal activities, to follow approved procedures, and to adopt specific work practices to prevent releases of asbestos to the air.

SRS has contracted certified instructors to teach employees the correct way to perform asbestos abatement projects. More than 800 employees are trained in the proper methods of asbestos removal, and two trained professionals coordinate permitting and approvals from SCDHEC. Asbestos is removed during maintenance and renovations of equipment and buildings. During 1991, SRS removed 10,034 linear feet and 84,686 square feet of asbestos-containing material and continued a program to identify friable asbestos—a form that can be crumbled or pulverized with hand pressure when dry.

Toxic Substances Control Act

Polychlorinated biphenyls (PCBs) are regulated under the Toxic Substances Control Act (TSCA) and have been used in the past in various equipment on the site. SRS has a well-structured PCB program for complying with TSCA regulations. During a DOE appraisal conducted in November 1991, the preliminary report from DOE cited three noteworthy

practices and one deficiency about the overall PCB program. These practices include: preparation of a PCB Management Manual (draft); preparation of comments on proposed PCB regulations to minimize the potential impact to SRS; and formation of a PCB task team, which is actively and comprehensively addressing all aspects of PCB management at SRS. The deficiency in the program concerned the reporting of PCBs in the PCB transformer oil on the PCB Annual Document Log. SRS was reporting the weight of the PCB fraction in the transformer oil as opposed to the entire weight of the oil. In light of the new information, the deficiency will be corrected to comply with EPA guidance.

SRS has some PCBs—radioactively contaminated during a spill—that have been stored onsite since 1978. Although TSCA regulations call for annual disposal of PCB waste, there is insufficient capacity for disposal of radioactive PCB waste offsite. Therefore, these wastes will continue to be stored onsite until a form of treatment is identified. A survey of DOE facilities for availability of treatment and/or treatment capacity is being conducted. An FFCA is expected to be prepared in 1992.

Federal Insecticide, Fungicide, and Rodenticide Act

The Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA) restricts the application of pesticides through a certification program. The SRS pesticide procedure controls pesticide use onsite and requires that certified applicators oversee the application of these substances. The 1990 DOE "Tiger Team" assessment approved the current SRS program with a recommendation that WSRC develop a database to track the use and location of pesticides at SRS. The site's pesticide procedure is being revised to require additional applications data. A more detailed explanation of the Tiger Team assessment appears later in this chapter.

Endangered Species Act

The Endangered Species Act of 1973, as amended, provides for the designation and protection of wildlife, fish, and plants in danger of becoming extinct. The act also conserves the ecosystems on which such species depend.

Several endangered species of wildlife exist at SRS. The site conducts research on several species, including the wood stork, the red-cockaded woodpecker, and others. Programs designed to enhance habitat are also in place. Details on these programs

can be found in Chapter 13, "Savannah River Ecology Laboratory," and Chapter 14, "Savannah River Forest Station." No new compliance issues were identified in 1991 at SRS.

National Historic Preservation Act

The National Historic Preservation Act of 1966, Section 106, governs the protection of archaeological and historical resources. SRS ensures that the site is in compliance with this act through the site use process. All sites being considered for activities such as construction are evaluated by the University of South Carolina's archaeology group to ensure that archaeological or historic sites are not impacted. No new compliance issues were identified in 1991 at SRS.

Executive Order 11988, "Floodplain Management"

Executive Order 11988, "Floodplain Management," was established to avoid long- and short-term impacts associated with the occupancy and modification of floodplains. Evaluation of impact to SRS floodplains is ensured through the NEPA Evaluation Checklist and the site use system. Site use applications are reviewed by WSRC, DOE-SR, the Savannah River Forest Station (SRFS), and the University of Georgia's Savannah River Ecology Laboratory (SREL), as well as by professionals from other organizations for potential impacts. No new compliance issues were identified in 1991 at SRS.

Executive Order 11990, "Protection of Wetlands"

Executive Order 11990, "Protection of Wetlands," was established to mitigate adverse impacts to wetlands caused by destruction and modification of wetlands and to avoid new construction in wetlands wherever possible. Avoidance of impact to SRS wetlands is ensured through the site use process as well as project reviews by the wetlands task force at SRS. Many groups and individuals including scientists at the Savannah River Laboratory (SRL) and SREL review site use forms to ensure that proposed projects do not impact wetlands. No new compliance issues were identified in 1991 at SRS.

ENVIRONMENTAL PERMITS

SRS has 452 construction and operating permits that specify operating levels for each permitted source. Chart 2-3 summarizes the permits held by SRS. Appendix A provides a comprehensive list of the permits, including the permit number, type of permit, and permitted source. SRS also has a Part A and Part B

Chart 2-3
SRS Construction and Operating Permits

<i>Type of Permit</i>	<i>Number of Permits</i>	
	<u>1990</u>	<u>1991</u>
Air	160	133
Domestic water	88	110
Industrial solid waste	8	6
Industrial wastewater	82	79
Maintenance dredging	2	1
Sanitary wastewater	105	112
Underground storage tank	2	11

permit (SCI-89-0008989) and two NPDES permits (SC0000175 and SC0044903).

APPRAISALS AND SURVEILLANCES OF ENVIRONMENTAL PROGRAMS

The SRS environmental program is overseen by a number of organizations, both inside and outside the DOE complex. Each year, this supervision involves many appraisals and surveillances of the programs. In 1991, 27 appraisals and 116 surveillances were conducted that focused on compliance-related issues. The appraisals, which are formal evaluations of environmental programs, included one SCDHEC Compliance Monitoring Evaluation of WSRC compliance with RCRA requirements for hazardous wastes, one DOE-SR Production Office review of environmental compliance with selected continued operation of the K and P Reactors, 14 WSRC appraisals, and 13 DOE-SR appraisals.

Appraisals

The 27 appraisals conducted by DOE-SR and WSRC assessed SRS's environmental programs and compliance with environmental regulations. Examples of some programs evaluated during 1991 included NEPA, quarterly hazardous waste reporting, wastewater construction permitting, laundry facilities, waste minimization, recycling, ecology and wildlife, EPCRA, release monitoring in the separations areas,

and a management appraisal. All deficiencies noted are logged into the Issue Management Processing Action and Commitment Tracking System (IMPACTS) and will be tracked until corrected to the satisfaction of DOE-SR and WSRC.

Surveillances

The 116 surveillances were conducted by DOE-SR to investigate compliance-related concerns associated with emergencies, to randomly evaluate site programs and facilities, and to supplement and follow up on DOE-SR's Comprehensive Environmental Protection Evaluation Program (CEPEP) evaluations. DOE-SR performs two types of surveillances: initial and follow-up. An initial surveillance determines whether a facility complies with specific regulations. A follow-up surveillance verifies whether a finding has been rectified. The surveillances were conducted on spills and releases, drinking water systems, water treatment systems, and waste handling and storage.

SRS Environmental Tiger Team Assessment

In 1989, Secretary Watkins announced a plan to strengthen Environmental, Safety, and Health (ES&H) activities within the DOE complex. The concept of Tiger Team assessments was developed to assess all DOE facilities for compliance with ES&H requirements. The assessment of SRS—conducted from January to March 1990—covered environmental, safety, health, and management areas and was designed to determine the site's compliance with applicable federal (including DOE), state, and local requirements.

The EA subteam concentrated on 10 areas: air, soils and sediments, surface water, hydrogeology, waste management, toxic and chemical materials, quality assurance, radiation, inactive waste sites, and NEPA. The subteam identified four key findings representing potential compliance issues related to federal and state regulations or DOE orders:

- Deficiencies in the waste management program
- Failure to meet state water pollution control requirements
- Inadequate monitoring of radiological releases
- Deficiencies within SRS quality assurance activities

WSRC, which prepared a Tiger Team Action Plan to address the findings from all areas evaluated, initially identified 211 actions required to correct these

findings. Seventy of the actions were completed in 1990 and 90 more were completed in 1991. Some of the closures resulted in the need for additional actions, boosting the total number of actions required to 234. As of Dec. 31, 1991, 829 of 1,089 actions had been completed. Of those, 261 had been validated by DOE-SR. WSRC is completing actions on schedule. More information on specific findings of the Tiger Team Assessment, and plans to correct the findings, can be found in the following publications: *Tiger Team Assessment of the Savannah River Site Environment, Safety, and Health* [DOE, 1990] and *Savannah River Site Action Plan in Response to the Department of Energy Environmental Health and Safety Compliance Assessment of the Savannah River Site* [WSRC, 1990].

Comprehensive Environmental Protection Evaluation Program

The DOE-SR Environmental Division (DOE-SR/ED) evaluates specific areas within environmental programs under the recently revised CEPEP.

Highlights of some of the appraisal reports issued by DOE-SR/ED in 1991 appear on page 23. Only Laundry Facilities Discharges and the SRS Recycle Program appraisals were not included in the highlights.

Compliance Inspections

The SCDHEC Air Compliance Inspection included a surveillance of all SRS air sources. The site received one NOV for exceeding the authorized opacity limit for a permitted diesel engine in K Area.

During the 1991 calendar year, SCDHEC conducted two inspections for NPDES programs. Inspection results indicated SRS was in compliance with the NPDES permit. The SCDHEC inspection team noted that SRS has one of South Carolina's best compliance programs.

CURRENT ISSUES AND ACTIONS

Par Pond Drawdown

On March 14, 1991, a small depression was discovered in the dam of Par Pond, a 2,640-acre reservoir constructed in 1958 to serve as a recirculating cooling reservoir for P and R Reactors. As a safety precaution to downstream populations, the water level in the pond was lowered about 19 feet during the period June 28-Sept. 19, 1991.

1991 DOE-SR Environmental Division Appraisal Results Highlights

Appraisal Report (Date Issued)	Summary of Deficiencies and Noteworthy Practices (Examples in Parentheses)	
Potable water systems at SRS (3/1/91)	31 deficiencies	(operating problems at D-Area Surface Water Drinking Plant)
	3 noteworthy practices	(potable water supply at SRS generally found acceptable)
Radiological sample analysis (3/18/91)	9 deficiencies	(certain critical functions performed only by key personnel)
Prior air emission issues (3/22/91)	4 deficiencies	(sampling methods comparing source emissions to downwind data)
Underground storage tanks (3/22/91)	11 deficiencies	(lack of procedures, records, and formal training)
	3 noteworthy practices	(updating Environmental Compliance manual)
Asbestos abatement (3/29/91)	11 deficiencies	(adherence to sitewide procedures, air sample turnaround time)
	4 noteworthy practices	(Draft Asbestos Management Plan a foundation for asbestos abatement program)
Sanitary wastewater systems (5/17/91)	10 deficiencies	(quality control of onsite lab testing procedures)
	3 noteworthy practices	(excellent effluent quality, good maintenance)
Wastewater construction onsite (7/31/91)	2 deficiencies	(no operating permits for some facilities built before 1988)
	3 noteworthy practices	(Environmental Permitting Procedures – "HOW" Manual – a model for other sites)
Hazardous-waste quarterly reporting program (9/3/91)	5 deficiencies	(lack of uniform reporting of waste quantities and volumes)
	3 noteworthy practices	(issuance of sitewide environmental procedures manual)
Emergency planning and community right-to-know (10/23/91)	6 deficiencies	(no sitewide Facility Emergency Coordinator; halon release Aug. 6 not reported to SCDHEC)
	2 noteworthy practices	(accessibility of information enhanced by computerization of records)
SRS wetlands protection (11/1/91)	4 deficiencies	(storm water runoff from Burial Grounds at F Area, causing erosion)
	3 noteworthy practices	(first sitewide appraisal of wetlands)
H-Area radiological liquid effluent monitoring (12/1/91)	3 deficiencies	(liquid effluents from H Area not characterized isotopically; liquid effluents not sampled at tritium facility; alarms at the Canyon and Tank Farm storm drains not tested adequately)
	2 noteworthy practices	(DCG fractions calculated by F/H personnel for each release prior to offsite release)

As the drawdown and structural investigation proceeded, regulatory agencies and the public were notified and apprised of studies being conducted and management alternatives being evaluated. Several concurrent radiological and nonradiological sampling studies by WSRC's Environmental Monitoring Section (EMS), SRL, and SREL, including water, sediment, atmosphere, and biota (e.g. fish, feral hog, vegetation), continued to be conducted in Par Pond and in Lower Three Funs Creek during and after drawdown to assess the potential impacts on human health and the ecosystem.

Studies of the radiological data indicated that radiological impacts from drawdown were relatively minor. The estimated maximum offsite dose from the liquid releases was 0.05 mrem, calculated using the LADTAP II program. The estimated maximum offsite dose from airborne releases, which was modeled as resuspension of sediment into the atmosphere, was 0.012 mrem, calculated using the EPA CAP88 code. These potential offsite doses are equivalent to less than three hours of exposure to natural background radiation.

At this time, three alternatives are being evaluated relative to the future of the reservoir. The first is to repair the dam and refill the pond. The second is to repair the dam and leave the reservoir at the current 181-foot elevation. The third is to breach the dam and drain the reservoir. The regulatory and ecological impacts of all three actions have been evaluated, and a decision on the selected action is expected in 1992.

K-Reactor Lawsuit

On June 11, 1990, the Natural Resources Defense Council and the Energy Research Foundation filed a lawsuit in the U.S. District Court of South Carolina, requesting that K Reactor not be restarted without a cooling tower in place to prevent thermal effluents from being discharged into the environment in excess of the NPDES permit.

In 1984, the State of South Carolina and DOE entered into a consent order that allows operation of K Reactor without a cooling tower, with the understanding that the cooling tower must be completed by Dec. 31, 1992. The cooling tower will reduce the temperature of the discharges to less than 90 °F, as required by the NPDES permit. For an update on the status of the cooling tower, refer to the compliance summary for Jan. 1 to April 1, 1992, at the end of this chapter.

The U.S. District Court in Aiken ruled Aug. 15, 1991, that the requested injunction against DOE would not be in the public interest, and that the plaintiff citizens groups lacked sufficient standing in the matter. Attorneys for the two environmental groups filed an appeal of the ruling in the U.S. Fourth Circuit Court of Appeals in Richmond, Va., Oct. 23, 1991. A hearing on the merits of reactor operation took place before that court Dec. 5, 1991.

On Dec. 13, 1991, the Fourth Circuit Court of Appeals remanded the suit to the District Court in Aiken for a hearing on the standing issue and, if necessary, a trial on the merits. At that time, the District Court sustained the lower court's denial of the request for the preliminary injunction, and DOE then announced that steps would be taken to restart K Reactor.

Special Fish Sampling Program

In October 1990, the Georgia Department of Natural Resources (GDNR) identified—in fish caught in the Savannah River near the mouth of Four Mile Creek—elevated levels of radioactive contaminants in concentrations greater than previously reported by SRS. On June, 19, 1991, WSRC and GDNR met in Atlanta to pinpoint the cause of differences in SRS and GDNR data and to agree on appropriate follow-up. A second meeting was held July 31 to continue discussions on assessment of the public health risks associated with the contaminated fish. A Sept. 9 meeting continued previous discussions and had as its primary purpose the presentation of the 1988 GDNR creek survey and the establishment of SRS field sampling methods.

Correspondence continues between representatives of WSRC, EPA, GDNR and SCDHEC regarding the sampling/analysis plan for radioisotopes in fish from the Savannah River.

Tritium in Georgia Wells

GDNR notified SRS in 1991 that five of 70 wells tested in Georgia had confirmed elevated levels of tritium. The levels ranged from 500 to 1,500 pCi/L. The EPA drinking water standard is an annual average of 20,000 pCi/L.

All currently available data suggest that atmospheric transport is responsible for the tritium in the Georgia groundwater. Tritium has been released in safe quantities to the atmosphere during the past 40 years of SRS operations. Tritium released to the atmosphere comes to the earth in the form of rain, which slowly infiltrates the ground and seeps into the underlying aquifers.

The measured amounts—consistent with the overall trend in the SRS area—are within the typical range for Savannah River water and lower than amounts historically found in the area's rainwater.

The State of Georgia has expressed concerns that the tritium was the result of migration through aquifers. SRS contends that geologic conditions would not allow such migrations to occur. A Memorandum of Agreement between DOE and the U.S. Geological Survey (USGS) to conduct a study of the regional groundwater flow patterns was signed in the mid-1980s, and work on drilling these wells was initiated in 1991. Also, DOE agreed to fund a study by the State of Georgia to determine the environmental route of the tritium.

Tritium Release from K Reactor

In early December 1991, final approval was given to restart K Reactor to resume the production of tritium. After the lengthy shutdown, an extensive pre-startup test was conducted to ensure that all equipment was operating properly. During the testing on Dec. 22, a leak developed in a tube in one of the reactor's 12 heat exchangers. This allowed heavy water containing tritium to slowly leak into the Savannah River via Pen Branch. The leak was discovered Dec. 25 through routine monitoring.

SCDHEC and downstream water consumers were notified of the leak and the estimated time it would reach them. Sampling of the river was increased to determine the amount of tritium released and its progression downstream.

It was determined that 150 gallons of heavy water containing approximately 5,700 Ci of tritium leaked from K Reactor before the source of the leak was identified and isolated. The calculated maximum dose to an offsite individual was 0.04 mrem, well below the 40 CFR 141 limit of 4 mrem per year.

The leaking heat exchanger was replaced, and corrective actions were taken to ensure that a similar release could be detected promptly. Chapter 10, "Nonroutine Occurrences," discusses this release in greater detail.

COMPLIANCE SUMMARY FOR JAN. 1 TO APRIL 1, 1992

Background

SRS strives to protect the environment by complying with various environmental regulations; compliance and settlement agreements; and DOE, executive, and

court orders. Below is a summary of SRS compliance status with major environmental statutes for the period Jan. 1 to April 1, 1992.

Compliance Status

Resource Conservation and Recovery Act

Waste Unit Closures

The closure plan for the acid/caustic basins in F, H, K, and P areas, which was submitted in June 1989, is still under review by SCDHEC. Additional information, requested in January 1992, was supplied by SRS on Feb. 7.

Comprehensive Environmental Response, Compensation, and Liability Act

Federal Facilities Agreement

The 60-day public comment period for SRS's draft FFA was completed Feb. 14, 1992. This document represents an agreement between EPA-Region IV, SCDHEC, and DOE to direct the comprehensive remediation of SRS.

The three parties have begun meeting regularly to review the comments and prepare a responsiveness summary addressing them. The FFA will be revised, if necessary, when the summary is completed. DOE-HQ then will review the document, and all parties will sign the final agreement.

Public Involvement Plan

The 60-day PIP public comment period also was completed Feb. 14. This CERCLA-required document outlines the site's public participation program.

CERCLA-Reportable Releases

With the exception of several leaks of ethylene glycol (antifreeze), no CERCLA-reportable releases occurred during the Jan. 1-April 1, 1992, period. Ethylene glycol only recently was added to the CERCLA RQ list, when amendments to the Clean Air Act added 45 air toxins. Because EPA has not yet developed specific RQs for these substances, the default quantity of one pound automatically applies. Therefore, a spill or leak of one pound of ethylene glycol (about a quart of motor vehicle coolant) must be reported to the National Response Center.

Through March 31, seven leaks of one RQ or more of antifreeze were reported to the National Response Center. The leaks occurred in private and government vehicles.

National Environmental Policy Act

The following NEPA activities were conducted from Jan. 1 to April 1, 1992:

- A draft EA on the proposed New Whole Body Counter Facility in B Area was submitted to DOE-HQ in January. This project will enable the site to meet increasing needs for monitoring employees for internal radionuclides.
- A preliminary draft summary supplement to the Par Pond Special Environmental Analysis (SEA) was prepared by DOE-SR to document the environmental impacts observed between August 1991 and February 1992.
- A Notice of Intent (NOI) was issued in March 1992 for the preparation of an EIS on the F/H Canyon Exhaust System upgrade and operation activities. The proposed action is to replace the exhaust systems that maintain the desired pressure differentials between various sections in the two canyon buildings.

Safe Drinking Water Act

The D-Area drinking water problem has not been resolved, and employees there continue to use bottled water. However, approval was issued in 1992 for the installation of two groundwater monitoring wells for that area as part of a project upgrading the area from a surface water treatment system to a groundwater-based treatment system. The project is slated for completion by July 1, 1993.

EPCRA (SARA Title III) Reporting Requirements

Under Section 312 of EPCRA, an annual Tier II inventory report must be filed by March 1 for all hazardous materials stored and used onsite in excess of specified quantities for the previous calendar year. The Tier II report for 1991 was submitted Feb. 27, 1992, by Industrial Hygiene.

Issues and Actions

Par Pond Drawdown

A health-based risk assessment conducted for Par Pond indicates that the reservoir is now a higher CERCLA priority. A focused feasibility study is being prepared to evaluate possible remediation alternatives against nine CERCLA criteria.

Three scenarios are under consideration:

- Repair the dam and refill the pond.
- Repair the dam and leave the reservoir at the current 181-foot elevation.
- Breach the dam and drain the reservoir.

The regulatory and ecological impacts of all three actions have been evaluated, and SRS is working with EPA to determine the best alternative. A decision is expected this year.

K-Reactor Lawsuit

On June 11, 1990, the Natural Resources Defense Council and the Energy Research Foundation filed a lawsuit in the U.S. District Court of South Carolina, requesting that K Reactor not be restarted without a cooling tower in place.

The U.S. District Court in Aiken ruled Aug. 15, 1991, that the requested injunction against DOE would not be in the public interest, and that the plaintiff citizens groups lacked sufficient standing in the matter. The two environmental groups appealed the ruling in the U.S. Fourth Circuit Court of Appeals in Richmond, Va., Oct. 23, 1991. A hearing on the merits of reactor operation took place before that court Dec. 5, 1991.

On Dec. 13, 1991, the Fourth Circuit Court of Appeals remanded the suit to the District Court in Aiken for a hearing on the standing issue and, if necessary, a trial on the merits. At that time, the District Court sustained the lower court's denial of the request for the preliminary injunction, and DOE announced that steps would be taken to restart K Reactor. The power ascension limit of 30 percent power for a period of three months should have little impact on Pen Branch, as opposed to expected one-year operation at 100 percent power when the lawsuit was filed.

On Jan. 23, 1992, the Court of Appeals issued a written opinion setting forth the rationale for its Dec. 13 order. The District Court has not yet rescheduled a hearing.

Meanwhile, the cooling tower subcontractor met the contractual commitment for a mechanically complete cooling tower March 31, 1992. This is the original milestone date included in the contract awarded in October 1989. Subject to the availability of sufficient funds, construction of plant tie-ins is scheduled to begin once the Power Ascension Test Program is completed in July. This will allow all project construction to be finished by Dec. 31, 1992, in compliance with the Consent Order between DOE and SCDHEC.

Tritium Release from K Reactor

As a result of the Dec. 22-25 tritium release from K Reactor, SCDHEC issued an NOV Feb. 26, 1992, contending that tritium was not listed on the NPDES permit and that the release, therefore, constituted a

discharge of an unpermitted pollutant into the environment. SCDHEC also requested that a report be prepared explaining the incident and what corrective

actions have been taken. DOE furnished the requested report while maintaining that tritium cannot be regulated under an NPDES permit.

Chapter 3

To Learn About:	Turn to page:
♦ Why SRS maintains an environmental monitoring program	29
♦ Important radionuclides at SRS	32
♦ Important environmental pathways at SRS	36
♦ Monitoring program changes in 1991	38
♦ Perspectives on radiation exposure	39
♦ Perspectives on chemical exposure	41

Compiled by
Radiological Assessments Corporation

Environmental Monitoring Perspectives, Objectives, Rationale

1991 HIGHLIGHTS

- ♦ A comprehensive review of the environmental monitoring program began in 1990 with the initiation of an Environmental Monitoring Plan. This plan, required by DOE Order 5400.1, General Environmental Protection Program, was approved by DOE-SR in November 1991. The plan documents the effluent monitoring and environmental surveillance activities conducted at SRS.
- ♦ EMS changed the frequency of tritium determination in air moisture from bimonthly to weekly because of high humidity experienced in the summer months. Also, paddlewheel and piston pump samplers at several existing surface water monitoring locations were replaced with flow-proportional composite samplers to improve sample efficiency.
- ♦ In 1991, EMS reviewed its radioactive surface-water monitoring locations for compliance with DOE Order 5400.5, Radiation Protection of the Public and the Environment. This order requires monitoring at the point of discharge for liquid waste released to surface waters. As a result of the review, several monitoring sites will be moved in 1992 from downstream of the effluent outfall to the point of discharge.
- ♦ Because of the relative importance of Sr-90 and Cs-137 from liquid pathways to offsite dose calculations, SRS is evaluating the design of the fish monitoring program to provide the most useful data for dose assessment and trend analysis.

INTRODUCTION

This chapter discusses the objectives and rationale for Savannah River Site's (SRS) environmental monitoring program and analyzes how the important radionuclides and pathways for releases from SRS affect the design of the program. The latter sections of the chapter provide perspectives for judging exposures associated with releases of radioactive and nonradioactive contaminants from SRS.

PROGRAM BASIS

The two major reasons why SRS maintains the environmental monitoring program are to comply with

environmental regulations and to address specific areas of public concern (Figure 3-1). Implicit in the environmental regulations are a number of objectives relating to protection of the environment as well as human health.

OBJECTIVES

The objectives of the SRS environmental monitoring program incorporate recommendations of the International Commission on Radiological Protection [ICRP 1985], as well as requirements of the U.S. Department of Energy (DOE) Order 5400.1 and the Environmental Regulatory Guide for Radiological Effluent Monitoring and Environmental Surveillance [DOE, 1991]:

Monitoring is Required for Compliance ...

Various environmental regulations and DOE orders impose requirements that call for monitoring. Many of the laws governing waste management and releases of materials to the environment have specific monitoring requirements to show compliance with the law.

For example, the National Pollutant Discharge Elimination System (NPDES) regulates operational effluents through outfalls by permit. The NPDES permits specify applicable standards and monitoring, for which sampling and analysis must be performed.

Monitoring Responds to Public Concerns ...

The decision to perform specific environmental monitoring may be motivated by public concern. Such concern may arise when any radioactive or nonradioactive contaminant is released and may

be transported toward residences or schools. Concern may also exist for releases of long-lived radionuclides that will remain in the environment for many years.

Figure 3-1 Compliance with regulations and responding to public concern are two main reasons for environmental monitoring at SRS.

- To assess actual or potential exposures to critical groups and populations from the presence of radioactive and nonradioactive materials from normal site operations and from accidents.
- To demonstrate compliance with authorized limits, regulatory requirements, and environmental commitments made under the National Environmental Policy Act (NEPA) or other official documents.
- To verify the adequacy of the facility containment of radioactivity and the effectiveness of effluent treatments and controls.
- To notify the proper officials of unusual or unforeseen conditions and, where appropriate, to implement a special environmental monitoring program.
- To communicate accurately and effectively the re-

sults of the monitoring program to DOE, other government agencies, and the general public.

- To maintain an accurate and continuous record of the effects of SRS operations on the environment.
- To determine concentrations of radioactive and nonradioactive contaminants in environmental media to assess the immediate and long-term consequences of normal and accidental releases.
- To distinguish between contributions to environmental contamination and environmental effects from the operation of SRS and contributions from other sources.
- To evaluate and revise the environmental monitoring program in response to changing conditions in releases, transfer pathways, and regulatory orders.
- To provide site-specific data for risk assessment and uncertainty analysis for human populations in the vicinity of SRS.
- To conduct scientific studies of the transfer pathways of radioactive and nonradioactive contaminants in the environment.
- To assess the validity and effectiveness of models to predict the concentration of pollutants in the environment.
- To determine the long-term buildup and prediction of environmental trends from site-released contaminants.
- To establish baselines of environmental quality, so that trends in the physical, chemical, and biological condition of environmental media can be characterized.
- To identify and quantify new or existing environmental quality problems and evaluate the need for remedial actions or mitigation measures.
- To support operating and construction permit revision and/or re-issuance.

Later chapters in this report, beginning with Chapter 4, "Sample Collection, Analytical Procedures, and Data Interpretation," describe how SRS meets these objectives by implementing a comprehensive environmental monitoring program. Not all these objectives are addressed in the annual environmental report. For example, special research reports, NEPA documents, and environmental bulletins and other publications also address these objectives and communicate the results.

DESIGN CRITERIA

To meet the objectives of the SRS environmental monitoring program, approximately 50,000 samples are collected and analyzed annually for radioactive and nonradioactive contaminants. In designing the monitoring program, it is important to justify that the samples and their analyses will help SRS achieve the monitoring objectives. The justification of planned sampling locations, sample media, sampling frequencies, and analyses is sometimes called the rationale for monitoring.

Nonradiological Monitoring

Because SRS is involved in the production of plutonium, tritium, and other special nuclear materials, much of the environmental monitoring effort is directed toward collecting and analyzing samples for radioactive materials. However, extensive environmental monitoring also is conducted for nonradioactive contaminants. The nonradiological monitoring program is designed to ensure that the physical and chemical properties of atmospheric and liquid discharges are in compliance with state and federal standards.

Nonradioactive constituents in SRS liquid discharges are regulated by the South Carolina Department of Health and Environmental Control (SCDHEC) under the National Pollutant Discharges Elimination System (NPDES) Program. SRS has two NPDES permits that specify discharge limits and monitoring requirements for each of the site's 78 outfalls. The monitoring requirements vary from one outfall to another, depending on the type of facility (i.e., the types of materials that potentially are present) and the known characteristics of the wastewater. In addition to monitoring liquid effluents, SRS collects and analyzes samples from the site streams and the Savannah River. This nonradiological monitoring is designed to provide verification of the outfall sampling and to ensure that materials that could adversely affect the environment are detected and characterized.

Monitoring of nonradioactive constituents in SRS atmospheric releases is designed to ensure compliance with permits issued by SCDHEC. The major nonradiological emissions of concern from SRS stacks include sulfur dioxide, oxides of nitrogen, and total particulate matter. In the past, SRS conducted ambient-air-quality monitoring at five onsite locations. However, this monitoring, which is not required by the regulations, was discontinued in 1991, after SRS re-evaluated its usefulness. Ambient-air quality near

Chart 3-1
Radionuclides Released to Air from SRS during 1986-1990

Radionuclide Category	Activity (Ci) Released to the Atmosphere				
	1986	1987	1988	1989	1990
Hydrogen, Carbon, Iodine					
Tritium as water vapor	2.9 E+5	2.7 E+5	2.9 E+5	2.2 E+5	1.8 E+5
Tritium as hydrogen gas	1.4 E+5	3.2 E+5	1.7 E+5	9.2 E+4	7.8 E+4
Total tritium (H-3)	4.3 E+5	5.9 E+5	4.6 E+5	3.1 E+5	2.5 E+5
Carbon-14	5.6 E+1	4.1 E+1	2.4 E+1	1.8 E+1	6.7 E-1
Iodine-129	8.7 E-2	7.2 E-2	6.3 E-2	5.2 E-2	1.3 E-2
Iodine-131	2.6 E-2	1.3 E-2	5.0 E-4	3.6 E-4	1.2 E-4
Noble Gases					
Argon-41	8.3 E+4	8.8 E+4	3.0 E+4	0.0 E+0	0.0 E+0
Krypton-85	7.1 E+5	4.0 E+5	2.4 E+5	4.2 E+4	3.0 E+3
Short-lived krypton and xenon isotopes	1.9 E+4	1.4 E+4	1.4 E+4	0.0 E+0	0.0 E+0
Particulates					
Fission and activation products	9.3 E-2	1.2 E+0	4.3 E-2	6.4 E-3	1.2 E-2
Uranium	1.6 E-3	8.5 E-3	1.5 E-3	5.1 E-3	5.2 E-3
Transuranic elements	2.5 E-3	2.9 E-3	1.5 E-3	2.4 E-3	3.5 E-3

SRS is monitored by South Carolina and Georgia as part of a network associated with the Clean Air Act (CAA).

Radiological Monitoring

Demonstrating compliance with the regulations is also an objective of the radiological monitoring program. Radioactive materials, like nonradioactive contaminants, are regulated at the point of discharge. However, the regulations for radioactive materials, unlike those for nonradioactive contaminants, also specify limits for exposures, or doses, to the public. As discussed in Chapter 6, "Calculating Radiation Doses," SRS uses mathematical models to determine the transport of radioactive contaminants in the environment and to estimate the resulting exposures to the offsite population. Therefore, the environmental monitoring program must provide the data needed to effectively develop and use these models.

In addition to demonstrating compliance with radiation dose limits, SRS also uses models to optimize the existing radiological monitoring program. For example, predictions of models can be very beneficial in placing measuring devices at the best locations in the environment and in identifying important pathways and contaminants that should be given priority in a monitoring scheme. Modeling can contribute to the best use of resources available for sampling and analysis and can verify that a sampling network will perform adequately.

Although many different radionuclides are released from SRS facilities during a particular year, a relatively small number of them are important contributors to the radiation dose to persons in the vicinity of SRS. Information from the 1986-90 environmental reports was examined to determine which radionuclides and pathways have been most important in terms of the quantity of radionuclides released, the dose to the maximally exposed individual, and the collective dose to the population. This type of analysis, called a critical pathways analysis, provides an indication of the important radionuclides and pathways for a particular site. Critical pathways analyses have been used throughout the history of SRS to provide input to monitoring design.

The following sections summarize the results of critical pathways analysis for the previous five years of SRS operations. The analysis was done for radionuclide releases to the atmosphere and to surface water, the principal media that carry radioactivity offsite. The properties and environmental behavior of the important radionuclides, as well as implications for the environmental monitoring program, are discussed.

Important Radionuclides Released to Air

Releases of radionuclides to the atmosphere at SRS depend upon which facilities are in operation during the course of the year. Chart 3-1, which contains the amounts of radionuclides in airborne effluents during

Figure 3-2 Importance of radionuclides to dose from atmospheric releases to the maximally exposed adult located on the SRS boundary.

the five-year period considered, illustrates this fact. There were no releases of argon-41 (Ar-41) or short-lived isotopes of krypton and xenon during 1989 and 1990, when the reactors were not operating. Overall, the largest releases during the period were of tritium (H-3) and the noble gas krypton-85 (Kr-85). The chart shows that releases of radionuclides in particulate form have been much lower than those in gaseous form.

Fission products include the nuclides strontium-90 (Sr-90), cesium-137 (Cs-137), ruthenium-106 (Ru-106), and cerium-144 (Ce-144). Activation products include cobalt-60 (Co-60) and manganese-54 (Mn-54). There are three naturally occurring uranium nuclides, U-234, U-235, and U-238. A primary transuranic element is plutonium, with isotopes Pu-238, and the pair Pu-239,240, which usually are

reported together because they cannot be separated by alpha spectroscopy. Also in that group are isotopes of americium and curium. The total particulate release exceeded 0.1 Ci in only one of the five years (1987). That year, the release was composed primarily of Cs-137.

Figure 3-2 examines the contributions of these nuclides to the committed effective dose equivalent (EDE) to the maximally exposed adult. (Technical dosimetry terms and the methods of dose calculation are discussed in Chapter 6). This person is presumed to be located on the SRS boundary where the maximum concentrations of radionuclides are present during the course of the year. The habits and food supply of the individual are presumed to be those that maximize his/her radiation exposure.

Chart 3-2
Radionuclides Entering the Savannah River during 1986-1990

Radionuclide Category	Activity (Ci) in Releases to the Savannah River				
	1986	1987	1988	1989	1990
Hydrogen, Carbon, Iodine					
Total tritium (H-3)	2.8 E+4	2.3 E+4	1.9 E+4	1.7 E+4	1.6 E+4
Iodine-129	2.2 E-2	2.2 E-2	2.2 E-2	2.2 E-2	2.2 E-2
Particulates					
Fission and activation products	4.7 E-1	7.8 E-1	9.6 E-1	5.0 E-1	5.5 E-1
Uranium	4.4 E-2	5.5 E-3	5.5 E-3	4.3 E-4	1.4 E-3
Transuranic elements	8.5 E-3	1.8 E-2	5.5 E-3	1.4 E-2	2.3 E-2

To give a clear picture of the effect of reactor operations on releases, the data in Figure 3-2 are divided into two time periods: 1986-1987 and 1989-1990. Several reactors operated during only parts of 1988, so this year is not included in the graph. Tritium has been the radionuclide that contributes most to the committed EDE for this hypothetical individual. During years of reactor operation, Ar-41 made the next largest contribution. Throughout the period, I-129 was estimated to contribute 4 to 17 percent, and C-14 contributed 0.2 to 6 percent of the total committed EDE. In 1987, the particulate fission product Cs-137 was an important contributor (12 percent of the committed EDE), due to a nonroutine release of about 1 Ci of Cs-137 from an H-Area evaporator in the waste management facilities [Mikol et al., 1988]. During reactor operations, the relatively large releases of the noble gas isotopes of krypton and xenon contributed less than 3 percent of the committed EDE to the maximally exposed person. Without reactor operations, these nuclides are even less important. The increased relative importance of transuranic elements in 1989-1990 compared to 1986-1987 is due to several factors:

- higher releases of transuranics (about 65 percent increase)
- lower releases of noble gases and tritium (about 75 percent decrease)
- an increase in the dose conversion factor for ingestion of plutonium (Chapter 6) [DOE, 1988]

Similar conclusions about radionuclide importance can be drawn when the collective dose to the population is examined. However, the contribution of tritium to the collective committed EDE is even larger than its

contribution to that of the maximally exposed individual. Despite the large release quantities of krypton and xenon isotopes, particularly during reactor operation, those nuclides were not major contributors to collective dose. Noble gases, as a class, contributed about 15 percent to the collective committed EDE when reactors were operating, but less during other years. The long-lived carbon and iodine isotopes were responsible for 2-17 percent of the committed EDE to the population during these years. With the exception of 1987, when the release of Cs-137 accounted for nearly 20 percent of the collective committed EDE, particulate radionuclides accounted for less than 5 percent of the total.

Important Radionuclides Released to Surface Water

Pathways analysis also can be used for evaluation of the monitoring program for liquid releases from SRS. In this section, radionuclides that are carried offsite by surface water into the Savannah River are examined, both in terms of the total amounts of radioactivity and the contributions to doses to the public. Chart 3-2 shows the quantities of radionuclides from SRS entering the Savannah River from 1986 to 1990. The releases of tritium, some of which are due to groundwater migration from seepage basins, are by far the largest of any nuclide. Releases of fission and activation products, primarily Sr-90 and Cs-137, ranged from about 0.5 to 1 Ci during the period. The estimated release of I-129 was even lower, about 0.02 Ci. Releases of uranium and the transuranic nuclides were both lower than that of I-129. The only transuranic nuclides for which a release was reported were Pu-239,240.

Figure 3-3 contains the contributions of these releases of radionuclides to the dose to a hypothetical adult who resides just downstream from SRS as well as the collective dose to the population. The hypothetical individual's habits are assumed to include a large consumption of fish caught from the river. The radionuclide that contributes most of that person's committed EDE is Cs-137, primarily due to the assumed consumption of fish. As discussed further in Chapter 9, "Wildlife Monitoring," the importance of Cs-137 in fish is overestimated because no attempt is made to subtract background Cs-137, which is widespread in the environment from past weapons testing. Tritium is the second most important contributor to the individual's committed EDE.

The collective dose from liquid releases includes doses to people who are more than 80 km from the center of SRS. At Beaufort-Jasper, S.C., and Port Wentworth, Ga., water is taken from the Savannah River for public

drinking water supplies. Consumption of tritium in the water typically accounts for more than 60 percent of the collective dose attributable to SRS releases (Figure 3-3).

Summary of Important Radionuclides

The list of nuclides of particular interest with regard to doses from SRS operational releases is shown in Chart 3-3. Also shown are some of the properties of these radionuclides that are related to their potential to produce doses to individuals and the population. With the exception of Ar-41, the nuclides have relatively long half-lives. The types of radiations emitted are variable from one nuclide to the next. The predominance of beta and alpha emitters shows the importance of internal exposures due to ingestion or inhalation of radionuclides. [See table on the inside back cover of this report for a description of the properties of alpha, beta, and gamma radiation.s.]

Figure 3-3 Importance of radionuclides to dose from liquid releases to a maximally exposed adult and the population during 1986-90.

Chart 3-3 Properties of Most Important Radionuclides, in Terms of Offsite Dose to People, Released from SRS between 1986 and 1990

Radionuclide	Half-Life	Primary radiation emissions	Importance of food pathways
Tritium (Hydrogen-3)	12.4 years	β	High
Carbon-14	5730 years	β	High
Iodine-129	16 million years	β	High
Argon-41	1.83 hours	γ	Low
Cesium-137	30.2 years	β, γ	High
Plutonium-238	87.7 years	α	Low
Plutonium-239	24,100 years	α	Low
Plutonium-240	6,570 years	α	Low

Important Pathways for Releases of Radionuclides from SRS

The most important pathways from SRS atmospheric releases to an individual at the site perimeter were through inhalation, external exposure from radionuclides in the plume, consumption of vegetables, and milk consumption (Figure 3-4). Because the largest airborne contributor to dose is tritium, which permeates all environmental media, the predominance of inhalation and food pathways is not surprising. Exposure to radionuclides deposited on the ground is a relatively unimportant pathway at SRS.

Four of the radionuclides are relatively mobile in food chains (Chart 3-3). Hydrogen and carbon are important nutrients, and iodine is an important trace element. Cs-137 behaves similarly to potassium, which is important to human metabolism. In contrast, Ar-41 and the plutonium isotopes have low mobility in food chains. The former is important only as a source of external exposure from the plume of noble gases released during reactor operation. The alpha-emitting plutonium nuclides enter the body primarily by direct inhalation of air or ingestion of water. Their concentration in human food chains is not an important exposure pathway. However, for the other four nuclides, food pathways are important contributors to human exposure.

Two comparisons illustrate the importance of food chain pathways for biologically active radionuclides. I-129 released to the atmosphere can deposit on leafy vegetation, such as lettuce, or on pasture grass that is consumed by cattle. This process and the subsequent

transfer of the radioiodine to meat and milk can lead to much higher exposures than would be received if inhalation were the only route of exposure. An I-129 air concentration of 1 pCi/m³ can lead to concentrations of 1,200, 1,600, and 2,900 pCi/kg of that isotope in milk, meat, and leafy vegetables produced at the same location. Typical doses for consumption of foods containing I-129 can be 80 to 280 times greater than the doses that would have been received from inhalation alone. The ratio varies with age; food chain pathways for I-129 are more important for young children than for adults [NCRP, 1983].

Food chain pathways can be especially important for some radionuclides released in liquid effluents. The bioaccumulation factor (BF) is used to compare the radionuclide content in aquatic organisms with that in the water. For example, the site-specific estimate of the BF for Cs-137 in fresh water fish is 3,000 L/kg. This means that if the Cs-137 concentration in water is 1 pCi/L, then the concentration of Cs-137 in fish living in the water will be approximately 3,000 pCi/kg. Consumption of 225 grams (about 8 ounces) of this fish will lead to a Cs-137 intake of about 675 pCi. That amount is larger than the total intake from drinking three 8-ounce glasses of the water each day for an entire year. It is apparent that fish consumption can easily be a more important source of Cs-137 than drinking water in which the fish live.

Actual values of bioaccumulation factors for Cs-137 and other nuclides depend upon the species of fish, the concentrations of other elements in the water, and other site-specific factors. The uptake of airborne nuclides into food products is similarly dependent upon local

conditions. These examples simply show the potential importance of food chain pathways for radionuclides with high biological activity.

Implications of Pathways Analysis for Environmental Monitoring

Based on potential offsite doses, the pathways analysis indicates the need for directing environmental monitoring efforts toward contaminants in air, vegetation, and milk. These media can be monitored with air sampling stations, environmental thermoluminescent dosimeters (TLDs), and analyses of food product samples. Based on the same modeling analysis, the principal radionuclides to monitor were identified (Chart 3-3).

In terms of the liquid pathways, tritium in drinking water and Cs-137 in fish are the most important radionuclides/media to monitor. In addition, sediments may absorb certain radionuclides and some nonradioactive contaminants from surface water. Thus,

sediments may represent long-term indicators of environmental quality for some contaminants, and consequently are monitored regularly. As examples, cerium, cesium, and plutonium typically accumulate in sediments, whereas tritium and C-14 typically remain in the water.

The environmental monitoring program incorporates information obtained from the liquid pathways models (Chapter 6) to determine what analyses are performed on sediment and surface water samples. As part of the monitoring program, surface water samples are analyzed for concentrations of tritium, gross alpha, nonvolatile beta, and gamma-emitting radionuclides. Sediment samples, on the other hand, are analyzed specifically for Cs-137, Sr-90, Pu-238, and Pu-239,240.

Groundwater modeling is useful in identifying the best location for monitoring wells and for predicting which contaminants are mobile and how fast they migrate. However, because groundwater flow is not as well

Reactors Operating 1986 - 1987

Reactors Shut Down 1989 - 1990

Figure 3-4 Importance of pathways to maximum individual dose from airborne SRS releases.

defined as stream flow and cannot be observed as easily, groundwater models are considered less precise than models of stream water behavior.

A groundwater monitoring program should focus on contaminants that are the best indicators of leakage or contaminant movement. Tritium is the most mobile radionuclide. Other mobile radionuclides are C-14, Tc-99, and I-129. Many volatile organic compounds, such as the solvent trichloroethylene, and inorganic compounds, such as sodium nitrate, also are very mobile in groundwater.

At SRS, tritium oxide (tritium in the form of water) is the most abundant groundwater source-term radionuclide. Sources of tritium in groundwater include liquid discharges to streams and basins, as well as rainfall removal of atmospheric tritium releases. Monitoring-well samples are analyzed routinely for tritium oxide, which is used as the primary indicator of groundwater movement. Samples also are analyzed for other contaminants that may originate from the specific site being monitored.

Measurement Capabilities

Many of the radioactive and nonradioactive materials released from SRS exist in such low concentrations in the environment that they are not readily measured. Thus, the measurement capabilities become determining factors in the rationale for monitoring certain materials. In these cases, it is still important to determine the quantities of the substances in the environment.

One way to determine small quantities of these substances is to monitor the source of the contamination (i.e., at the stack or outfall), where higher concentrations may be more readily obtained. Environmental modeling can then be used to calculate the expected concentrations of contaminants in various environmental media. Smaller numbers of environmental samples may be obtained to verify the accuracy of the modeling. The noble gases, as well as I-129 and C-14, are more difficult to measure in the environment than some other radionuclides. Consequently, SRS has elected to use modeling to estimate downwind concentrations for the purposes of dose calculations.

Monitoring Program Changes in 1991

The types, frequencies, and locations of environmental measurements are reviewed routinely to determine if a need for monitoring remains. If a clear rationale for a measurement no longer exists, it is deleted from the program. Likewise, the environmental monitoring

program is expanded as new methods for environmental monitoring evolve. Important factors that affect this rationale include program evaluation, environmental regulations, public concern, measurement capabilities, and environmental modeling.

A comprehensive review of the environmental monitoring program began in 1990 with the initiation of an Environmental Monitoring Plan. This plan, required by DOE Order 5400.1, General Environmental Protection Program, was approved by DOE's Savannah River Operations (DOE-SR) in November 1991. It documents the effluent monitoring and environmental surveillance activities conducted at SRS by identifying the rationale and design criteria for the monitoring program, the frequency of monitoring and analysis, specific analytical and sampling procedures, quality assurance requirements, and guidance on preparing and distributing reports. The Environmental Monitoring Plan, which will be revised yearly and updated at least every three years, will provide documentation of, and guidance for, SRS monitoring activities.

Program changes implemented in 1991 are discussed in Chapters 6-10 of this report. The changes included the following:

- Onsite ambient air had been monitored for sulfur dioxide, oxides of nitrogen, ozone, and particulate matter at five monitoring stations. The usefulness of this monitoring was reevaluated, and EMS determined that this monitoring is not required by any regulations, including those of the Environmental Protection Agency (EPA) and SCDHEC. In addition, since the stations were located within SRS, they were not useful for determining concentrations of these pollutants in offsite ambient air, where members of the public could have access. Thus, the monitoring was determined to be unnecessary and was terminated in June 1991.
- SRS's Environmental Monitoring Section (EMS) changed the frequency of tritium determination in air moisture from bi-monthly to weekly because of the effects of high humidity experienced in the summer months. Paddlewheel and piston pump samplers at some existing surface water monitoring locations were replaced with flow-proportional composite samplers to improve sample efficiency.
- In 1991, EMS reviewed its radioactive surface water monitoring locations for compliance with DOE Order 5400.5, Radiation Protection of the Public and the Environment. This order requires monitoring at the point of discharge for liquid waste released to surface waters. As a result of the review, several monitoring sites will be moved in 1992

from downstream of the effluent outfall to the point of discharge.

- In support of the annual SRS deer hunts, new, more reliable monitors and National Institute of Standards and Technology (NIST) traceable calibration sources were purchased. As required by DOE Order 5400.5, a new confiscation limit was adopted; it is based on the cumulative EDE of the hunter, rather than the cesium concentration in the deer. This was implemented through a computerized database, which was developed for calculating and tracking each hunter's EDE.
- The K-Reactor restart effort was supported by the addition of a composite sampler in K Canal and weekly sampling at the K-011 outfall. Also, in response to Par Pond drawdown activities (conducted to allow inspection of Par Pond Dam and repair of seepage areas in the dam), four temporary air monitoring stations were installed and the L3R-1A sampling location was relocated to L3R-1B to obtain a more representative sample. More information on the Par Pond drawdown can be found in Chapter 11, "Special Surveys."
- Because of the relative importance of Sr-90 and Cs-137 in fish to offsite dose from the liquid pathways, SRS is evaluating the design of the fish monitoring program to determine what changes can be made to make the data more useful for dose assessment and trend analysis.

PERSPECTIVES ON RADIATION EXPOSURES

This section gives basic information on the sources of exposure to radiation and compares various levels of radiation dose. This information will help provide a perspective for judging radiation doses associated with releases of radionuclides from SRS. Chapter 6 provides detailed definitions of the terms and units for expressing radiation doses.

Natural Background Radiation

The major source of radiation exposure to the public is attributed to radiation from naturally occurring radioactive materials in the environment. Exposure from this radiation occurs from sources both external and internal to the body. This naturally occurring radiation often is referred to as natural background radiation. The amount of radiation exposure an individual receives varies according to location.

Cosmic Radiation

Energetically charged particles from outer space continuously hit the earth's atmosphere. These particles and the secondary particles and photons they

Dose Quantities and Units: How are they related?

Dose - refers to the radiation energy actually absorbed in a material or tissue (rad or gray).

Dose Equivalent - dose multiplied by a quality factor to allow for the different effectiveness of different types of radiation (rem or sievert).

Effective Dose Equivalent (EDE) - the sum of all organ or tissue doses, after each has been multiplied by a weighting factor. The EDE is designed to reflect the total risk associated with the exposure (rem or sievert).

(Chapter 6 contains detailed definitions)

create are ionizing radiation called cosmic radiation. Because the atmosphere provides some shielding against cosmic radiation, the intensity of this radiation increases with altitude above sea level. The average annual dose to people in the United States from cosmic radiation is about 27 mrem [NCRP, 1987a].

A report published by EPA gives an outdoor cosmic radiation dose for Augusta, Ga., of about 41 mrem [Oakley, 1972]. When shielding and the time spent indoors are considered, the annual average cosmic radiation dose for the local population is about 33 mrem.

Terrestrial Radiation

Terrestrial radiation refers to radiation emitted from radioactive materials, primarily potassium (K-40), isotopes of thorium (Th), and isotopes of uranium (U), in the earth's rocks and soils. The average annual dose from terrestrial gamma radiation is about 28 mrem in the United States, but varies geographically across the United States [NCRP, 1987a]. Typical reported values are about 16 mrem at the Atlantic and Gulf coastal plains and about 63 mrem at the eastern slopes of the Rocky Mountains. Values from the SRS vicinity include 43 mrem for Augusta, 23 mrem for Charleston, S.C., and 68 mrem for Columbia, S.C. [Oakley, 1972].

Internal Radiation

Natural radionuclides in the environment enter the body by inhalation and by ingestion of foods, milk, and water. These radionuclides are metabolized in the body similarly to nonradioactive elements, although each

element is metabolized differently. Natural radionuclides in the body include isotopes of uranium, thorium, radium, radon, polonium, bismuth, and lead in the U-238 and Th-232 decay series. In addition, the body contains isotopes of potassium (K-40), rubidium (Rb-87), and carbon (C-14).

The major contributors to the annual dose equivalent for internal radionuclides are the short-lived decay products of radon (mostly Rn-222), which contribute an average dose of about 200 mrem per year. This dose estimate is based on an average radon concentration of about 1 pCi/L [NCRP, 1987a]. The results of long-term measurements in living areas of about 30,000 homes in the United States suggest that the mean radon concentration levels are about 3.6 pCi/L for the U.S. population and about 1 pCi/L for South Carolina [Alter and Oswald, 1988]. If these results are verified by a nationwide EPA survey, the average dose estimate for the U.S. population will increase, and the estimate for South Carolina will remain about 200 mrem. It is expected that the EPA survey will be published in 1992.

The average dose from other internal radionuclides is about 39 mrem per year, which is predominantly attributed to the naturally occurring radioactive isotope of potassium, K-40. The concentration of radioactive potassium in human tissues is similar in all parts of the world [NCRP, 1987a].

Man-Made Sources of Radiation

In addition to the natural background, there are a number of man-made sources of radiation to which most people are exposed. The categories of consumer products, medical sources, and other minor sources are discussed below. In addition, about one half of one percent of the U.S. population performs radiation work. A comprehensive EPA report [Kumazawa et al., 1984] projected an average occupational dose to monitored radiation workers in medicine, industry, the nuclear fuel cycle, government, and miscellaneous industries to be 105 mrem/year for 1985, down slightly from 110 mrem/year in 1980.

Consumer Products

Many consumer products also are sources of ionizing radiation. In some of these products, like smoke detectors and airport X-ray baggage inspection systems, the radiation is essential to the performance of the device. In other products, such as televisions and tobacco products, the radiation occurs incidentally to the product function. The U.S. average annual dose to

an individual from consumer products is about 10 mrem [NCRP, 1987a].

Medical Diagnosis and Therapy

Radiation is an important tool of diagnostic medicine and cancer treatment. Exposure to patients is deliberate and directly beneficial to the patients exposed. In general, medical exposures from diagnostic or therapeutic X-rays result from radiation beams directed to specific areas of the body. Thus, all body organs normally are not irradiated uniformly.

Nuclear medicine examinations involve the internal administration of radioactive materials or radionuclides to the patient. However, the radionuclides used for specific tests are not distributed uniformly throughout the body. In these cases, the concept of EDE, which relates exposure of organs or body parts to one effective whole-body dose, is useful in making comparisons. The average annual EDE to all individuals from medical examinations is 53 mrem (about 39 mrem for diagnostic X-rays and 14 mrem for nuclear medicine procedures) [NCRP, 1989]. The actual doses to individuals who receive such medical exams are much higher than these values, but not everyone receives such exams each year [NCRP, 1989].

Other Sources

There are a few additional sources of radiation that contribute minor doses to individuals in the United States. The dose to the general public from nuclear fuel cycle facilities, such as uranium mines, mills, fuel processing plants, nuclear power plants, and transportation routes, has been estimated at less than 1 mrem per year [NCRP, 1987a].

Small doses to individuals occur as a result of radioactive fallout from atmospheric atomic bomb tests, which have now been suspended; emissions of radioactive materials from other nuclear facilities, such as DOE facilities; emissions from certain mineral extraction facilities; and transportation of radioactive materials. The combination of these sources contributes less than one mrem per year to the average dose to an individual [NCRP, 1987a].

Comparison of Various Levels of Radiation Dose

On the average, a person living in the Central Savannah River Area (CSRA) receives an annual radiation dose of about 380 mrem. Figure 3-5 shows the contributions of various radiation sources to this average dose to an individual.

Chart 3-4 presents a scale of radiation dose levels, with an example of the type of exposure that may cause such a dose, or the special significance of such a dose. This information is intended to help the reader become familiar with a range of radiation doses that various individuals may receive.

PERSPECTIVES ON CHEMICAL EXPOSURES

Just as all humans are exposed to radiation in their normal daily lives, humans also are exposed to hazardous chemicals. However, unlike radiation exposures, there is no natural background for many chemicals to which people can be exposed.

Some hazardous chemicals do exist in the natural environment. In many areas of the country, soils contain naturally elevated concentrations of metals, such as selenium, arsenic, or molybdenum, that may be hazardous to humans and animals. However, exposures to many more hazardous chemicals result directly or indirectly from human actions. Materials used for

building homes may contain chemicals such as formaldehyde (in some insulation materials), asbestos (formerly used in insulation and ceiling tiles), and lead (formerly used in paints).

Personal uses of automobiles involve potential exposure to many hazardous chemicals. Gasoline fumes, which contain the hydrocarbons heptane and octane, benzene, and tetraethyl lead (being phased out), may be inhaled while refueling. Used motor oils, air conditioner refrigerants, and combustion exhaust gases also may be encountered. Many hazardous chemicals are used or produced in manufacturing facilities, including cleaning-material solvents (such as toluene, xylene, or trichloroethylene), fine particles of many metals (from mechanical processing), and acids and other organic compounds used in chemical reactions. Thus, people are exposed to these chemicals in their everyday lives. At SRS, some chemicals are monitored in the nonradiological monitoring program to ensure that their levels in atmospheric and liquid discharges are in compliance with state and federal regulations.

Figure 3-5 Average Annual Effective Dose Equivalent to People Living in the CSRA. The total dose of about 380 mrem is broken into categories by radiation source. Occupational exposures are not included.

Chart 3-4 Comparison and Description of Various Radiation Dose Levels

Dose level	Description
1 mrem	Approximate daily dose from natural background radiation, including that due to radon.
2.5 mrem	Cosmic radiation dose to a person on a one-way airplane flight from New York to Los Angeles.
10 mrem	Typical dose from one chest X-ray using modern equipment.
10 mrem	Annual exposure limit, set by EPA, for exposures from airborne emissions from operations of nuclear fuel cycle facilities, including power plants, uranium mines, and mills.
33 mrem	Average yearly dose from cosmic radiation to people in the Central Savannah River Area.
66 mrem	Average yearly dose to people in the United States from man-made sources.
60-80 mrem	Average yearly dose from cosmic radiation to people in the Rocky Mountain states.
83 mrem	Estimate of the largest dose any offsite person could have received from the March 28, 1979, Three Mile Island nuclear accident.
100 mrem	Annual limit of radiation dose from all DOE facilities to a member of the public who is not a radiation worker.
110 mrem	Average occupational dose received by U.S. commercial radiation workers in 1980.
170 mrem	Average yearly dose to an airline flight crew member from cosmic radiation.
300 mrem	Average yearly dose to people in the United States from all sources of natural background radiation.
900 mrem	Average dose from a lower-intestine diagnostic X-ray series.
1-5 rem	EPA's Protective Action Guidelines state that public officials should take emergency action when the dose to a member of the public from a nuclear accident will likely reach this range.
5 rem	Annual limit for occupational exposure of radiation workers set by the NRC and DOE.
10 rem	The BEIR V report estimated that an acute dose at this level would result in a lifetime excess risk of death from cancer, caused by the radiation, of 0.8 percent.
25 rem	EPA guideline for voluntary maximum dose to emergency workers for non-lifesaving work during an emergency.
75 rem	EPA guideline for maximum dose to emergency workers volunteering for lifesaving work.
50-600 rem	Doses in this range received over a short period of time will produce radiation sickness in varying degrees. At the lower end of this range, people are expected to recover completely, given proper medical attention. At the top of this range, most people will die within 60 days.

To Learn About:	Turn to page:
♦ Measuring radioactivity in environmental samples	45
♦ Radiological analysis:	
Penetrating radiation	47
Air samples	48
Surface water	49
Drinking water	53
Wildlife	53
Soil and sediments, vegetation	54
♦ Uncertainties, errors, detection limits	56
♦ Nonradiological analysis:	
Air samples, liquid effluents	59
Surface water, ...	59
Drinking water	61

Compiled by Jason H. Chappell
Environmental Protection Department

Sample Collection, Analytical Procedures, and Data Interpretation

1991 HIGHLIGHTS

- ♦ Deer and hogs collected during onsite controlled hunts were monitored in the field for Cs-137. Muscle tissue was collected from a random 10 percent of the animals and analyzed for Cs-137 and Sr-90.
- ♦ After reassessing the need for nonradiological onsite ambient air monitoring, operation of the five ambient air monitoring stations was terminated in June.
- ♦ When new contracts for laboratory analysis of groundwater samples were awarded in 1991, an expanded data format was implemented to collect more complete information about each analysis.
- ♦ To ensure proper sample control, EMS laboratories implemented the Environmental Monitoring Computer Automation Project (EMCAP)—a sophisticated, computer-based sample tracking system for effluent and environmental samples.

INTRODUCTION

The environmental monitoring program at Savannah River Site (SRS) includes radiological and nonradiological monitoring that encompasses a 30,000-square-mile area on and around the site. This chapter summarizes how environmental samples are collected and prepared, as well as the analytical techniques used to determine the concentrations of radioactive and nonradioactive contaminants within the samples. Chapters 7, 8, and 9, "Air Pathways," "Water Pathways," and "Wildlife Monitoring," respectively, provide tables and figures that identify sampling stations and locations.

In 1991, approximately 105,000 radiological analyses were performed on about 27,000 air, water (process, stream, river, rain, and groundwater), soil, sediment, vegetation, milk, food, and wildlife samples. These represent the critical media through which radiological contaminants can be transported to the public and the environment. Penetrating radiation levels were monitored at 462 locations.

The nonradiological monitoring program concentrates primarily on the Savannah River, onsite streams, and groundwater. These are the primary pathways for nonradiological contaminants to reach the public and environment. In 1991, more than 20,000 nonradiological analyses were performed on more than 7,000

Figure 4-1 EMCAP is EMS's new computer-based sample tracking system, which maintains chain-of-custody from sample collection through analysis.

samples of surface water, soil, sediment, and fish to determine the concentrations of nonradioactive contaminants. In addition, approximately 400,000 analyses were performed on groundwater samples collected from more than 1,200 monitoring wells. Ambient air quality was continuously monitored at five stations within the site boundary until June 1991.

The Environmental Monitoring Section (EMS) of the Environmental Protection Department (EPD) manages the SRS environmental monitoring program, which consists of sample collection and preparation, chemical analysis, radioanalytical counting, and data management, interpretation, and reporting. In addition, commercial subcontractors provide support to EMS for a number of monitoring activities in the radiological and nonradiological monitoring programs.

PROGRAM CHANGES IN 1991

Sample Identification and Tracking

Samples must be tracked to ensure that the results generated can be associated with the appropriate sample. Without proper sample control, the analytical results are meaningless.

In 1991, EMS implemented a sophisticated, computer-based sample tracking system for effluent and environmental samples, called the Environmental Monitoring Computer Automation Project (EMCAP). Figure 4-1 shows how EMCAP is used to track samples and maintain the chain-of-custody of the samples from collection, through sample preparation and analysis, to analysis results.

EMCAP is used for all radiological and nonradiological effluent and environmental samples. However, since

many nonradiological samples involve offsite analyses by subcontracted laboratories, nonradiological samples may have fewer entries made into EMCAP. The contracted laboratories are required to maintain chain-of-custody for all samples shipped by SRS for analysis.

Termination of Nonradiological Ambient Air Monitoring

Onsite ambient air had been monitored for sulfur dioxide (SO₂), oxides of nitrogen (NO_x), ozone (O₃) and particulate matter of size less than 10 microns (PM₁₀), at five monitoring stations. Because of increasing maintenance costs due to the age of the equipment used, this aspect of the nonradiological air monitoring program was reassessed. EMS determined that this monitoring is not required by any regulations, including those of the U.S. Environmental Protection Agency (EPA) and the South Carolina Department of Health and Environmental Control (SCDHEC). In addition, since the stations were located within SRS, they were not useful for determining concentrations of these pollutants in offsite ambient air, where members of the public could have access. Thus, this monitoring was determined to be unnecessary, and EMS terminated the operation of the monitoring stations in June 1991.

Expansion of Groundwater Data Format

When EMS awarded new contracts for laboratory analysis of groundwater samples in 1991, a new data format was implemented to collect more information about each analysis. The information now provided to EPD/EMS includes the well name, chain-of-custody number, sample date, date laboratory received the sample, extraction date, analysis date, test name, analysis method, detection limits, batch number, and results qualifiers for each analysis.

RADIOLOGICAL MONITORING

The objectives and rationale for the environmental monitoring program are discussed in Chapter 3, "Environmental Perspectives, Objectives, Rationale." To achieve these objectives, EMS has established a routine radiological sampling and analysis program, which is summarized in Table 4-1.

Processing Samples with EMCAP

After samples are collected, EMS personnel log the samples into EMCAP. The samples are logged in by entering the sample location, the medium, and the collection date. The computer system then assigns a

unique identification number to each sample. After the samples are logged in, analysts working in the chemistry laboratories collect the samples for their labs from the collections room. The lab supervisor maintains a schedule that documents when samples are collected and designates what samples are to be analyzed in each of the chemistry labs.

To maintain chain-of-custody, the chemistry lab analysts log all samples into the lab through EMCAP. When they have completed the sample preparation and analysis, they take the samples to the counting room. After the samples have left the lab, the analysts log them out of the lab, and the counting room analysts log them into the counting room through EMCAP. Throughout the different sample preparations and analyses, the original sample—and each aliquot created from that sample—maintains its identification number. When the analyses are complete, the data are entered into EMCAP, thus ending the chain-of-custody.

Labs contracted to SRS for environmental sample analysis are required to maintain chain-of-custody for all samples shipped by SRS for analysis.

Radioactivity Measuring Techniques

In the monitoring program, three types of radiation are monitored—alpha particles, beta particles, and gamma rays. The back cover of this report depicts these types of radiation. The type and energy of radiation emitted are used to identify specific radionuclides. It is possible to determine most radionuclides with little or no sample preparation. In other cases, the radionuclide of interest in a sample usually can be determined only after it has been concentrated and chemically separated from the sample medium and the other radionuclides in the sample.

Measuring the low levels of radioactivity typically found in environmental samples presents a special problem. The sample counting rate usually is not much larger than the background (blank) counting rate from naturally occurring radionuclides and cosmic radiation throughout the environment. As a result, the difference between the two counting rates is small (sometimes zero or negative), with a statistical error that is large relative to the measurement.

To mitigate these measurement difficulties, extensive chemical separation, purification, and concentration techniques, as well as sensitive counting instruments, are used to detect any radioactivity present in a sample. The quantity or concentration of the radionuclide measured in the sample usually is expressed in units of

radioactivity per unit mass or volume (e.g., $\mu\text{Ci/g}$ and $\mu\text{Ci/mL}$).

Instrumentation

Measuring radioactivity in environmental samples requires instruments that can detect alpha, beta, or gamma radiation. Since no one detector is applicable in all situations, EMS uses four different types of instruments in its counting laboratory. Each requires that the sample be prepared in a particular form, volume, and container. This set of conditions, together with the position of the sample container on the detector, is called the sample counting geometry. A fixed and reproducible sample geometry is necessary for accurate analysis of radioactivity.

When radioactivity is being measured in a prepared sample, the instrument detects and counts a fraction of the photons or particles emitted during radioactive disintegrations. An instrument's detection efficiency for a given set of measurement conditions is the fraction of radiation that the instrument records during the counting interval. Because the instrument does not record all radioactive emissions from the sample, its absolute detection efficiency is always less than 100 percent. Therefore, the instrument must be calibrated to relate the counting efficiency to each detector, the sample type, and geometry.

A detection instrument is calibrated by counting a standard calibration source of known activity that is prepared in the same counting geometry as the sample. The calibration source contains known quantities of specific radionuclides that are traceable to the National Institute of Standards and Technology (NIST) or other international standards of measurement. For a given set of measurement conditions, the calibration determines the detection efficiency, which is computed as the measured counts divided by the known activity for the calibration source.

The count of the unknown sample then is divided by the detection efficiency and by the sample volume to give the total activity per unit mass or volume of sample. Other factors influencing detection efficiencies include chemical yield, decay corrections, and radionuclide abundance.

Tables 4-2 through 4-6 list the instruments and detectors used by EMS in the laboratory to measure radioactivity. They also list the radionuclides measured with each instrument and provide the lower limits of detection for these instruments under a given set of measurement conditions.

Other types of radiation detection instruments are used in the field to measure radioactivity. Thermoluminescent dosimeters (TLDs) measure penetrating radiation. MicroR meters are portable survey instruments used to measure low-level gamma exposure rates. The instrument is a 1-in.-by-1-in. NaI(Tl) crystal connected to a pulse rate meter. It is used to measure exposure rates from background to 2,500 $\mu\text{R/hr}$. The microR meter is used by EMS during special surveys and incident responses. Portable sodium iodide [NaI(Tl)] detectors are used in the field to monitor wildlife for gamma-emitting radionuclides.

Sample Counting Geometries for Gamma-Emitting Radionuclide Analysis

The gamma spectroscopy system is a versatile radioanalytical instrument that can measure a variety of sample types, sometimes with little or no sample preparation. Counting geometries of the calibration standards are chosen to match the sample type and its physical configuration as closely as possible.

When selecting sample counting geometries, the goal is to ensure the highest accuracy while providing the best counting efficiency with minimum sample preparation. It is not always practical, however, to have a counting geometry that exactly matches every sample type. After chemical preparation, many of the samples analyzed have densities similar to water; therefore, many calibration standards are prepared as though they were water samples.

In 1991, one new air geometry—a composite of twelve 4.7-CM glass fiber filters—was added as part of the analysis regimen. This new calibration geometry was added to more closely match the sample geometry being analyzed.

The standard sample counting geometries summarized in Table 4-7 are used to determine gamma-emitting radionuclides in environmental samples.

General Measurement Processes

Although the procedures used for specific analyses are complex, EMS follows general steps for environmental sample collection, preparation, and analysis. Figure 4-2 depicts the general measurement process used for environmental and effluent samples.

Analytical procedures summarized in the following section are based on EPA or other accepted procedures [EPA, 1980; Beaufait, 1952; NAS, 1960]. Table 4-8 presents sample preparation data for specific media. Typical counting times for each counting instrument are offered in Tables 4-2 through 4-6.

Figure 4-2 Environmental samples are measured for radioactivity through the general process shown above.

RADIOLOGICAL SAMPLE COLLECTION AND ANALYTICAL PROCEDURES

Penetrating Radiation

TLDs are used on and around SRS to measure penetrating radiation levels. In 1991, more than 8,700 TLD badges were placed at 462 locations within an 8,000-square-mile area of the site. These areas included stations onsite, at the site perimeter, and in nearby South Carolina and Georgia towns.

Each TLD used at the site includes two thallium-activated calcium sulfate crystals ($\text{CaSO}_4:\text{Tl}$). The dosimeters are annealed, placed in plastic holders, and stored inside heat-sealed plastic bags before being taken to the field.

A set of control TLDs, some of which are irradiated to a known exposure, accompanies the field TLDs to correct for systematic errors that occur when exposing and reading the dosimeters. The nonirradiated control

TLDs accompany the field TLDs, but are kept in shielded storage for the complete 90-day field cycle to correct for dose accumulated during transportation to and from the field and any natural thermoluminescence exhibited by the crystals.

Five TLDs are placed side by side at each monitoring location. The TLDs can be used to provide incremental dose rates during nonroutine releases, and they also offer increased precision in the routine monitoring program. The field and control TLDs are collected and analyzed quarterly to determine penetrating radiation exposure. The exposure is measured by determining the average response of the two calcium sulfate crystals in the dosimeter.

The TLDs measure exposures in units of milliroentgens (mR). However, the dose equivalent in millirem (mrem) reported in Tables 7-13 through 7-17 was calculated by multiplying the exposure measurement by an "f-factor" (1 for muscle) and a quality factor (1 for gamma radiation). Therefore, the exposure level

measured is approximately equal numerically to the dose equivalent [Sorenson, 1987].

Air

Sample Collection

Air is sampled continuously at air monitoring stations located onsite, at the site perimeter, and at 25- and 100-mile radius locations. At each monitoring station, airborne radioactivity is sampled by continuously drawing air through three types of sampling media—a high-efficiency glass fiber filter that traps particulates, an activated charcoal cartridge for radioiodines, and a silica gel tritium absorber.

The volumetric rate of air passing through the high-efficiency glass fiber filter is approximately 70 L/min (2.5 ft³/min). Air flow and the total sampling time are recorded to calculate the radioactivity per unit volume of air. The glass fiber filters are analyzed for gross alpha, nonvolatile beta, gamma-emitting radionuclides, and radioactive isotopes of strontium and plutonium.

The activated charcoal cartridge is located down-line from the high-efficiency glass fiber filter. Air is drawn through the activated charcoal at 70L/min, and the charcoal is analyzed for gamma-emitting radionuclides on a high-purity germanium (HPGe) detector.

The tritium sampler collects moisture from the atmosphere by drawing air through the silica gel at a continuous rate of 150 mL/min (0.005 ft³/min). The

primary column contains non-indicating silica gel. This is followed by a secondary column of indicating silica gel. If moisture saturates the primary silica gel column during the sampling period, the moisture will reach the secondary column and cause a color change in the moisture-indicating silica gel. When this occurs, the samples are flagged and the secondary column is changed. The moisture collected by the primary silica gel is analyzed for tritium oxide content. Beginning in June, both indicating and non-indicating columns were collected on a weekly basis. The silica gel from both columns was composited into a single sample and analyzed for tritium oxide content.

Glass fiber filters, silica gel, and activated charcoal cartridges are collected weekly from all 35 monitoring stations for analyses. Figure 4-3 represents a typical air monitoring station.

Analytical Procedures

Air samples are collected for analysis of gross alpha, nonvolatile beta, gamma-emitting radionuclides, tritium, and radioactive isotopes of strontium and plutonium.

Gross Alpha and Nonvolatile Beta

Gross analyses of airborne particulates on the air filters are performed as a screening technique for information on worldwide fallout or SRS releases. This analysis technique determines to what extent alpha-particle and beta-particle emitters are present in the sample, but does not identify specific radionuclides. Gross alpha-

Figure 4-3 SRS collects air samples in three different ways: with filter paper, a charcoal cartridge, and silica gel.

and nonvolatile beta-emitting radionuclides are analyzed simultaneously with a gas-flow proportional counter by a direct count of individual particulate filters.

Gamma-Emitting Radionuclides

After the gross alpha and nonvolatile beta analysis, onsite weekly filters are composited monthly by location, while offsite filters are composited weekly into site perimeter, 25-mile, and 100-mile samples. The composites are analyzed for gamma-emitting radionuclides, using an HPGe detector. Air filters do not require chemical processing for this analysis.

After gamma analysis, each filter composite is cut into sections; one-half is used for plutonium analysis, 40 percent is used for strontium analysis, and 10 percent is composited quarterly and analyzed by the Savannah River Laboratory (SRL) for specific analytes.

For areas that have the potential to release I-131, radioactivity is measured on an HPGe detector by a direct count of a charcoal cartridge. The HPGe detector distinguishes the I-131 gamma energy from other radionuclides with high spectral resolution.

Tritium

For tritium analysis, water is removed by distilling the non-indicating silica gel over low heat. The distillate represents the total moisture content in the air sampled. The distillate then is mixed in a liquid scintillation cocktail. The concentration of tritium oxide in the moisture is determined with a liquid scintillation counter.

Strontium

A single chemical separation method is used to measure total radioactive strontium (Sr-89,90). For Sr-89,90 analysis of air filter samples, a known amount of stable (nonradioactive) strontium is added to the sample as a carrier. The stable carrier and the radioactive isotopes of strontium are separated from other elements by precipitation with fuming nitric acid.

Barium then is removed from the strontium isotopes by precipitating barium chromate in an acetate buffer solution. It is necessary to remove the barium because it interferes as a fission product and with weight recovery of strontium.

The strontium carrier and the radionuclides of strontium are precipitated as strontium carbonate. The

strontium carbonate then is dried, weighed to determine recovery of the carrier, and counted in a gas-flow proportional counter. The total radioactive strontium is calculated from a single count.

Plutonium

Air filters collected at monitoring stations are spiked with Pu-242, ashed, and leached with acid during preparation for plutonium (Pu-238 and Pu-239) analysis. The leached solution is evaporated, dissolved in an acid solution, and passed through an anion exchange resin, which extracts and holds the plutonium. The extracted plutonium then is chemically removed from the resin column, evaporated to dryness, and redissolved in a sulfate solution. The sulfate medium containing the plutonium is electrodeposited on a stainless steel disk and counted on a silicon surface barrier detector. The Pu-242 spike recovery is used to verify the purity of the chemical separation and to quantify the amount of Pu-238 and Pu-239 present in the sample.

Streams

Sample Collection

Site streams are sampled continuously using three primary systems—paddlewheel samplers, Brailsford motor pumps, and Isco samplers. The paddlewheel sampler consists of a Lexan® paddlewheel suspended on two pontoons. The floating sampler, anchored in the stream, collects samples in a small cup attached to the paddlewheel. The cup holds approximately 0.5 mL of water. As the stream velocity rotates the paddlewheel, water is collected in the cup and emptied into a collection trough. The water sample flows by gravity from the trough, through a connecting tube, and into a polyethylene jug attached to the sampler.

The Brailsford pump system consists of an all-plastic, variable speed, valveless piston driven by a Brailsford AG fractional watt motor. The pump samples stream water at a rate of 2.84 L/day. Approximately six gallons of water are routinely collected with both the paddlewheel and Brailsford pump sampling systems. Sampling jugs for both systems are emptied weekly.

The Isco sampler (Figure 4-4) consists of a microprocessor-controlled peristaltic pump in a weatherproof housing. The sampler performs a sample line purge before and after each aliquot is collected to minimize aliquot cross contamination. The sample aliquot size, as well as sampling frequency, is adjustable by the user. The sampler can be attached to a flow meter to provide a flow proportional sample. The

Figure 4-4 The Isco sampler consists of a microprocessor-controlled peristaltic pump in weatherproof housing.

Isco sampler will collect from 7.57 to 15.14 L, depending on model and bottle configuration.

Analytical Procedures

Water samples from site streams are analyzed for gamma-emitting radionuclides, gross alpha, nonvolatile beta, tritium, uranium/plutonium, and radioactive isotopes of strontium.

Gamma-Emitting Radionuclides

Gamma-emitting radionuclides are directly analyzed on an HPGe detector by counting a 500- or 1,000-mL water sample.

Gross Alpha and Nonvolatile Beta

Gross alpha- and nonvolatile beta-emitting radionuclides are measured by a direct count of the residue remaining after evaporating a 1-L aliquot of the water sample. The sample residue is transferred to a two-inch stainless steel planchet. The planchet is flamed to remove residual moisture and volatile material, which might absorb the alpha and beta radiation. The sample then is counted on a gas-flow proportional counter.

Tritium

Tritium is measured in a 5-mL undistilled portion of sample by liquid scintillation counting.

Uranium/Plutonium

Alpha-emitting radionuclides are extracted from 1-L samples with triisooctylamine (TIOA) in xylene. Both uranium and plutonium are stripped from the TIOA with hydrochloric acid (HCl). The acid solution then is evaporated to dryness to remove the HCl. The residue is dissolved in nitric acid, transferred to a stainless steel planchet, and evaporated prior to final counting on a gas-flow proportional counter. The result is the total radioactivity due to plutonium and uranium, without specific isotopic analysis.

Strontium

Total radioactive strontium (Sr-89,90) concentrations are measured by the same procedure used for air filter samples.

To determine Sr-90 concentrations, the beta emissions of Sr-89,90 are resolved by observing the decay of Sr-89 and ingrowth of Y-90 (a daughter product of Sr-90) with at least two counting intervals in the gas-flow proportional counter, over a 7-to-14-day period. These results then are used to solve two

simultaneous equations for the individual count rates of Sr-89 and Sr-90.

Savannah River

Sample Collection

The Savannah River is sampled continuously by paddlewheel samplers equipped with 26-L polyethylene jugs. River sampling jugs are emptied weekly.

SRL also samples the Savannah River at two locations—upriver near Shell Bluff (River 2) and downriver at Highway 301 (River 10) with continuous samplers that typically process 300 to 500 L of water per week through an ion exchange column to concentrate the radionuclides. SRL collects ion exchange samples biweekly to perform low-level analysis of gamma-emitting radionuclides.

Analytical Procedures

Savannah River samples are analyzed to determine concentrations of gross alpha, nonvolatile beta, gamma-emitting radionuclides, tritium, and radioactive isotopes of strontium and plutonium.

Gross Alpha and Nonvolatile Beta

Gross alpha- and nonvolatile beta-emitting radionuclides are determined with the same analytical procedure described for streams, except for samples collected at River 2 and River 10. To remove large particulates, these samples are filtered prior to analysis. Both the precipitates and the filtrates then are analyzed using the stream procedure.

Gamma-Emitting Radionuclides

River samples are prepared for analysis by passing from 8 to 24 L of the sample through a cation-anion exchange column. This process increases analytical sensitivity by concentrating the radionuclides that are present. The column is counted with an HPGe detector and radionuclides then are eluted from the resin column with nitric acid for subsequent analyses of strontium and plutonium.

For the low-level analysis of gamma-emitting radionuclides performed by SRL, the radionuclides concentrated on the ion exchange material are counted for approximately 16 hours on an HPGe detector in a low-background counting facility. This sensitive procedure enables SRL to measure lower levels of gamma-emitting radionuclides than the EMS procedure allows. The concentrations of Cs-137 presented in

this report for Savannah River water at River 2 and River 10 were measured by SRL.

Tritium

Tritium is determined by performing liquid scintillation counting of a 5-mL portion of the distilled sample.

Strontium

Total strontium (Sr-89,90) is determined from a portion of the column eluate by the same procedure used for air samples. Sr-90 then is measured using the same procedure described for stream samples.

Plutonium

Plutonium (Pu-238,239) concentrations are determined from a portion of the eluate taken from the ion exchange column used for the gamma-emitting radionuclides analysis. The analytical procedure is the same procedure used for air filters.

Seepage Basins

A 2-L grab sample is collected quarterly from seepage basins in A, C, L, and P areas and monthly from the TNX Seepage Basin and Solid Waste Disposal Facility (SWDF) Settling Basin. These samples are analyzed for gross alpha, nonvolatile beta, tritium, strontium, uranium/plutonium, and gamma-emitting radionuclides, following the procedures for stream samples.

Groundwater

Sample Collection and Analysis

Groundwater samples are obtained in various ways from monitoring wells at SRS. Most are collected using submersible pumps installed in the wells; some are collected using bailers lowered into the wells, and a few are collected from continuously pumping wells. Criteria that determine which wells will have analyses conducted on their samples are: the nature of the site being monitored; the past history of monitoring at the site; and special needs of the well. Gamma emitters, tritium, gross alpha, nonvolatile beta, total radium, Sr-89 and Sr-90 and are determined for all new wells the first year they are sampled, and thereafter once every two years. Specific radionuclides are determined for selected samples. Groundwater samples are analyzed by subcontracted laboratories using EPA methods, except for determinations that do not have EPA methods. For details concerning the analytical methods used, refer to Chapter 8.

Milk

Sample Collection

One-half gallon (1.89 L) of fresh raw milk is collected every two weeks from each of five local dairies and a

SRS personnel obtain water samples from the Savannah River.

local major distributor. An additional 1.5 gallons (5.68 L) is collected from each location quarterly.

Analytical Procedures

The half gallons of milk collected every two weeks are analyzed for gamma-emitting radionuclides (primarily I-131 and Cs-137) and tritium. The 1.5 gallons collected quarterly are analyzed for Sr-90.

Gamma-Emitting Radionuclides

Concentrations of gamma-emitting radionuclides are determined by direct count of a 1-L sample aliquot on a high-purity germanium (HPGe) detector. The HPGe detector uses diffused junctions generated by the application of a high voltage across a semiconductor material to detect photon radiation.

Tritium

Milk solids are separated from the liquid by distillation to reduce quenching interferences. A 5-mL portion of the distilled liquid then is analyzed with a liquid scintillation counter to determine the concentration of tritium oxide.

Strontium

A cation exchange resin is used to separate strontium and Y-90 from the milk as chlorides. The separated chlorides are evaporated to dryness and the residue is dissolved in hydrochloric acid. To begin the Y-90 ingrowth, Y-90 is removed from the strontium using 2-di-ethylhexyl phosphoric acid in toluene. Equilibrium of Y-90 with Sr-90 is approached over a 15-day period, after which the short-lived Y-90 daughter is removed once again. The yttrium is transferred to a stainless steel planchet and counted in a gas-flow proportional counter. The amount of Sr-90 is calculated by relating the Y-90 buildup to the original Sr-90 concentration.

Food

Sample Collection

Local foods, including fruit, small grains, corn, eggs, chicken, beef, and pork, are obtained from private farms located within a 25-mile radius of SRS. Collards are collected as control samples from Columbia, S.C. All food samples are collected annually with the exception of eggs, which are collected quarterly.

Analytical Procedures

Analysts prepare food samples for analysis by separating and discarding the inedible portions, except for grains that contain both grain and husks. The samples are chopped or blended and then dried or ashed. A portion of the original sample is retained for tritium analysis before drying. The residue is dissolved in a hydrochloric acid solution.

The prepared food samples are analyzed for gamma-emitting radionuclides, Sr-90, uranium/plutonium, Pu-238, Pu-239, and tritium.

Gamma-Emitting Radionuclides

Gamma-emitting radionuclides are determined with an HPGe detector by a direct count of the hydrochloric acid solution.

Strontium

The procedure for Sr-90 analysis is the same as described for stream samples.

Uranium/Plutonium

Uranium/plutonium is measured in foods following the same procedure described for stream samples.

Plutonium

Concentrations of Pu-238 and Pu-239 are determined by the same procedure described for air filter samples.

Fish are taken from onsite streams, ponds, and the Savannah River so that concentrations of radionuclides present in the aquatic environment can be measured.

Tritium

Tritium is measured in the free water obtained by freeze-drying a portion of the original sample. The water is counted in a liquid scintillation counter.

Drinking Water

Sample collection

Drinking water samples are collected at onsite sampling locations and in communities surrounding SRS. Samples are collected from faucets and drinking fountains. Some onsite samples are collected monthly, while others are collected quarterly.

Offsite samples are collected semiannually except from water treatment plants, where raw and finished drinking water samples are collected daily, composited, and analyzed monthly.

Analytical Procedures

All drinking water samples are analyzed for gross alpha, nonvolatile beta, and tritium. Once a year, an additional sample is collected from each location for Sr-90 analysis. Analytical procedures for drinking

water are the same as the procedures used for stream samples.

Wildlife

Sample Collection and Analysis

The South Carolina Wildlife and Marine Resources Department issued permit number F-91-22, which authorized EMS to collect fish specimens during 1991.

Fish and Shellfish

Fish are caught onsite and offsite—and shellfish offsite—in traps or by hook and line. Both are liquified (blended and decanted), placed into a sample bottle, and analyzed for gamma-emitting radionuclides on an HPGe detector. Gross alpha- and nonvolatile beta-emitting radionuclides are measured by a direct count of residue remaining from the evaporation of acid solutions of a blended sample. The residue is placed on a 2-in. stainless steel planchet and counted in a gas-flow proportional counter.

Deer and Hogs

Deer and hogs are monitored onsite annually through controlled hunts during the November and December hunting season. EMS performs a field analysis of

Cs-137 on deer and hogs at the hunt site with portable 2-by-2-in. sodium iodide [NaI(Tl)] detectors. The portable detectors are calibrated so that Cs-137 concentrations in flesh may be calculated from the field measurements.

Accuracy of the calibrations is verified by analyzing muscle tissue from a random 10 percent of the total animals harvested from each hunt—and bone from 20 percent of the animals sampled for muscle. The muscle tissue is analyzed for gamma-emitting radionuclides and Sr-90 in the laboratory. The muscle tissue is analyzed by an HPGe detector and the analytical procedures described for stream samples and food samples, respectively. Muscle samples also are collected from all deer and hogs having Cs-137 field measurements greater than 25 pCi/g for laboratory analysis.

Bone samples from these randomly selected animals are analyzed for Sr-90, using the same analytical procedures described for stream samples.

Turkeys

The South Carolina Game Management Division traps turkeys on SRS for repopulation of other South Carolina game areas. Turkeys are monitored for concentrations of Cs-137 with a portable 2-by-2-in. [NaI(Tl)] detector before removing them from the site.

Turtles

The Savannah River Ecology Laboratory (SREL) traps turtles both onsite and offsite as part of an ongoing study to learn about the animal's migratory behavior. Trapped turtles are aged, sexed, and monitored for radioactivity with a G-M detector (Thyac).

Rainwater

Sample Collection

Radioactivity in rainwater and deposition is determined from monthly rainfall samples. Rainwater is collected in a 2-by-2-foot metal pan located atop each of 35 air monitoring stations. At stations equipped with ion exchange columns, the water passes through the column and into a polyethylene jug. At stations not equipped with ion exchange columns, the water collects in the pan and drains directly into the jug.

Analytical Procedures

Rainwater samples are analyzed for gross alpha, nonvolatile beta, radioactive isotopes of strontium and plutonium, and gamma-emitting radionuclides to

determine deposition. Tritium is measured directly in the rainwater.

Gross alpha, nonvolatile beta, plutonium, strontium

Analyses are determined from the eluate of the ion exchange column obtained after analysis for the gamma-emitting radionuclides. The analytical procedures for these analyses are the same as those described for stream and river samples.

Gamma-Emitting Radionuclides

The ion exchange columns are counted directly for gamma-emitting radionuclides on an HPGe detector. The column is eluted and the eluate is used for subsequent analyses.

Tritium

Since tritium does not collect on the rain ion exchange column, tritium concentrations are determined by liquid scintillation counting of the rainwater collected in the jugs.

Soil and Sediment

Sample Collection

Soil samples are collected annually from four locations around F and H areas, from four locations in S Area, and from four locations around Z Area. Samples also are collected at four site perimeter and two 100-mile-radius locations. Ten soil plugs, each 8 cm deep, are taken 30 cm apart in a straight line at each sampling location.

EMS collects sediment samples annually from SRS streams and Savannah River sampling locations. Sediment collection techniques for streams and rivers are designed to obtain samples from the top 8 cm of sediment in areas where fine sediment accumulates. The samples are not intended to be representative of the entire stream bed.

Analytical Procedures

After collection, the 10 soil plugs are combined into composites by location. The sediment samples and composited soil samples are dried, sieved, and pulverized before being analyzed for gamma-emitting radionuclides and radioactive isotopes of strontium and plutonium.

Gamma-Emitting Radionuclides

For analysis of gamma-emitting radionuclides, a portion of the prepared sample is placed in a 500-mL plastic bottle and counted on an HPGe detector.

Strontium

For Sr-90 analysis, a portion of the prepared sample is leached with ammonium acetate, and the solution is evaporated to dryness. The residue is dissolved in nitric acid, and the sample is analyzed using the same method described for stream samples.

Plutonium

A portion of each prepared soil and sediment sample is analyzed for Pu-238 and Pu-239 following the procedure described for air filters.

Vegetation

Sample Collection

EMS collects vegetation (grass) samples at onsite locations, at the site perimeter, and within a 25- and 100-mile radius of SRS. Vegetation samples are collected annually from retention/seepage basins and inside the SWDF (formerly referred to as the Burial Ground) fence and quarterly at all other onsite and offsite locations.

Analytical Procedures

Vegetation samples are analyzed for gross alpha, nonvolatile beta, gamma-emitting radionuclides, tritium, and total radioactive strontium. Before the samples are analyzed for radioactivity, the vegetation is oven dried for approximately 24 hours at 80 to 90 °C. A portion of the original sample is retained for tritium analysis before drying.

Gross Alpha and Nonvolatile Beta

To determine gross alpha- and nonvolatile beta-emitting radionuclides, a portion of dried and ashed vegetation is dissolved in nitric acid and transferred to a stainless steel planchet and dried for counting in a gas-flow proportional counter.

Gamma-Emitting Radionuclides

Gamma-emitting radionuclides are determined by counting dried and milled vegetation in a 1-L Marinelli beaker on an HPGe detector.

Tritium

Tritium is measured by liquid scintillation counting of the free water, which is obtained by freeze-drying a portion of the vegetation.

Strontium

Dried vegetation samples are milled before strontium analysis. Total strontium (Sr-89,90) then is determined using the same procedure described for air samples.

INTERPRETATION OF REPORTED RADIOLOGICAL MONITORING DATA

A product of an efficient and thorough monitoring program is a report that contains reliable data. This section describes how EMS reports data, the significance of the data, and the techniques used to interpret the reported values. Quality assurance and quality control program goals and procedures are discussed in Chapter 5, "Quality Assurance/Quality Control."

Overview

Reporting radiological measurement data is subject to the following criteria:

- Measurement results must be reported with the proper units and the appropriate number of significant figures. Additional specifications, such as how the sample was collected or how it was composited, are necessary to understand and interpret the results.
- A reported value must include an assessment of its uncertainty. The uncertainty value must be based on as complete an assessment as possible, taking into account errors such as random errors, systematic errors, and rounding errors, so that sufficient information is conveyed. Both precision and accuracy of the results should be estimated and addressed, and the meaning of the presented uncertainties should be unambiguous.
- The lower limit of detection (LLD) under a given set of practical conditions should be estimated and reported for low-level environmental measurements (Tables 4-2 through 4-6).

A complete discussion of the theoretical basis and procedures for data reduction and interpretation of environmental monitoring measurements is beyond the scope of this report. Detailed discussion of these topics can be found in the following references: Bevington, 1969; Corley, 1961; NCRP, 1988; Natrella, 1966; and Watson, 1980.

Interpretation of Reported Data

Nomenclature

Text and data tables in this report refer to various radionuclides and chemicals using specific scientific

nomenclature. Appendix B interprets the nomenclature used in this report.

Presentation of Units

Most radiological data are presented as activity concentrations by volume or mass [e.g., $\mu\text{Ci/L}$ (microcuries per liter) or $\mu\text{Ci/g}$ (microcuries per gram)]. Data in this report are presented in the units required by U.S. Department of Energy (DOE) Order 5400.1. Although picocurie (pCi) was the most common activity unit used in previous reports, activity now is presented in microcuries (μCi). To put this change into perspective, one microcurie is equal to one million picocuries. Scientific notation also is used (i.e., $150 \mu\text{Ci/g} = 1.5\text{E}+02 \mu\text{Ci/g}$). Fractions and multiples of units, as well as conversion tables, are shown on the inside front cover of this report.

Table 4-8 shows typical sample sizes and aliquots. The dimensional units and other necessary information for the reported values are provided in the data tables or within the text. Statistical uncertainties are not presented with data reported in the text except in cases where measurements are characteristically subject to large uncertainties (e.g., wildlife monitoring).

Radionuclides Reported

This report follows the practice, common in environmental monitoring literature, of reporting gross alpha and gross nonvolatile beta measurements. These measurements provide no information on the identity of the radionuclides present in the sample. However, the counting instruments are usually calibrated to a single radionuclide. This unavoidable difference, between the calibration radionuclide and the unknown radionuclides in the samples, results in additional uncertainty in the results of these gross alpha and nonvolatile beta measurements. The results of these gross measurements were calculated based on the use of Po-210 for the gross alpha calibration and Sr-90 for the nonvolatile beta calibration.

Care must be taken in interpreting gross alpha and nonvolatile beta results. Gross measurements should not be used to make conclusions about dosimetric significance or environmental behavior of the unknown radionuclides in the samples. Rather, gross measurement results are more suited to showing trends in concentrations and determining whether radionuclide-specific analyses should be performed.

Some data tables quote activities of some naturally occurring radionuclides (e.g., K-40, Be-7) and radionuclides that may arise from fallout from previous nuclear weapons testing (e.g., Sr-90, Cs-137, and Pu-239).

EMS measures concentrations of other specific radionuclides in the environment that possibly are contributed by SRS operations. Some of these analyses include tritium, strontium, plutonium, cesium, and other gamma-emitting radionuclides.

For analysis of gamma-emitting radionuclides, the only specific radionuclides reported are those detected in the sample. Radionuclides not listed in the data tables were below the detection limits given in Tables 4-2 through 4-6.

Measurement Difficulties

Environmental samples often contain low levels of radioactivity, and the difference between the sample count and the background count (i.e., radioactivity count taken with no sample present) consequently is small. Since all measurements involve statistical variations, the net, measured sample counts, after the background has been subtracted, are sometimes negative (i.e., less than zero). All of the counting instruments except the gamma analysis system produce a net sample count, even if the result is small or less than zero. Although negative results have no physical meaning, the data remain statistically valid and are reported and included in yearly and composite averages.

The gamma analysis system produces a net sample count only if the value is above the detection limit and is not negative or accompanied by a large uncertainty. However, if these conditions are not met, the gamma analysis system calculates an estimated LLD. The LLD is the smallest concentration of a material that can be reliably detected in a sample (see Tables 4-2 through 4-6).

Interpretation of Reported Uncertainties

The absolute error or uncertainty of a reported value (the deviation from the true value) cannot be known because the true value is not known exactly. However, the limits of this uncertainty can be inferred and estimated from the measurement process itself. This uncertainty assessment includes an incumbent risk of being incorrect, which is called the confidence limit. The absolute uncertainty of a measurement is composed of illegitimate (gross), random, and systematic errors.

Illegitimate Errors

Illegitimate or gross errors are those errors that are so serious that to obtain an adequate measurement, a new sample must be collected or new measurement performed. Normally, such errors are easily recognized and corrected.

Random Errors

Random errors affect the precision of a measured value (i.e., the reproducibility of a set of successive, independent measurements). These errors result from random variations at all stages of the sample collection, sample preparation, and measurement processes. The overall random uncertainty of a measurement is assessed by calculating the standard deviation of the mean (average) of numerous replicate determinations. However, replicate measurements of environmental samples are uncommon and usually not feasible, due to time and cost constraints.

Because radioactive decay follows the Poisson statistical distribution, the standard deviation can be estimated from the number of counts obtained for a single measurement. This counting error takes into consideration only uncertainties arising from the random nature of the radioactive decay process itself. Ideally, random uncertainties arising from every major step or component of the measurement process should be independently assessed. This approach, however, usually is not feasible and is uncommon for reporting environmental data. Sampling and analytical procedures are designed to minimize random errors that are not included in the counting-error assessment.

Systematic Errors

Systematic errors affect the accuracy of a measured value (i.e., the proximity to the true value). These errors arise from bias introduced by improperly calibrated instruments, errors in reagents and calibration standards, and imperfect analytical technique and experimental design. This bias affects each measurement in the same way. Assessing systematic uncertainties is complex and subjective. Therefore, they are not included in the uncertainties for measured values in this report.

To ensure the accuracy of the reported data and to reduce systematic errors, EMS participates in EPA and DOE laboratory intercomparison programs. These interlaboratory programs and their results are discussed in Chapter 5. To further minimize systematic errors, EMS uses defined quality assurance and quality control procedures, conducts periodic training sessions for

analysts, performs frequent reviews of experimental designs and measurement procedures, and uses standard reference materials traceable to NIST or other international standards of measurement for all calibrations.

Reported Uncertainties

Uncertainties quoted in this report for individual measurements, such as the maximum or minimum of a range of values, are counting uncertainties only, calculated with assumptions of a Poisson distribution, and are the limits of a 95 percent confidence interval. The uncertainties quoted for mean values are the uncertainties of the mean, given as the limits of a 95 percent confidence interval. The total uncertainties of a result, which include random and systematic errors, are higher than the reported counting uncertainties.

Lower Limits of Detection

Numerous expressions and definitions of "detection limits" frequently are encountered. Their meanings often are ambiguous and incorrectly interpreted. The terms "lower limit of detection" (LLD) and "minimum detectable concentration" (MDC) are used interchangeably in this report.

The LLD corresponds to an *a priori* limit above which the level of activity is reliably estimated using a given instrument, method, and sample type. It depends not only on the instrument and sample characteristics, but on many other specific factors involved in the measurement process, such as length of the counting interval, chemical yield, sample geometry and density, decay time, and other radionuclides present in the sample.

Since all these factors can influence the value of the LLD, it must be emphasized that the MDC or LLD is not a limit below which radioactivity is undetectable. Rather, under a given set of practical conditions, it is a limit above which there is a high probability of detecting radioactivity present in a sample and a low probability of reporting a false positive. The LLD is one useful parameter often evaluated in comparisons of alternative measurement procedures.

The LLD values in this report were calculated with the formula listed below [Watson, 1980]:

$$LLD = K(k^2 + 2k\sqrt{2s}) = K(2.71 + 4.65s)$$

where:

$k=1.645$ (95% confidence level)

s =standard deviation of the background count

K =proportionality constant which relates counts to the

activity concentration for a given set of measurement conditions

Tables 4-2 through 4-6 list estimated lower limits of detection for each instrument and various sample types under typical measurement conditions.

Evaluation of Groundwater Data

Data Preparation

EPD/EMS receives analytical results and field measurements as reports and as ASCII computer files that are loaded onto a mainframe computer at SRS. Log books track receipt and transfer of data to the mainframe database, and computer programs provide data in a format that can be validated.

Quality control practices include the following:

- Verification of correct well names and sample dates for field and analytical data
- Verification that all analyses requested on the chain-of-custody forms are complete for each laboratory
- Identification of data entry problems (e.g., duplicate records, incorrect units)
- Comparison of analytical data to historical analytical data and review of the data for transcript, instrument, or calculation errors
- Comparison of blind replicates and laboratory in-house replicates for inconsistencies
- Identification of laboratory blanks and blind blanks with elevated concentrations

Possible transcription errors and suspect results are documented and submitted to the appropriate laboratory for verification or correction. No changes are made to the database until the laboratory documents the problem and solution. Changes to the database are recorded in a log book.

EPD/EMS publishes quarterly reports that identify samples that have been analyzed after their expiration dates, suspect results that have been verified by the laboratory, and the analyses of blanks with elevated results.

Statistical Treatment

The mean relative difference (MRD) index is used to evaluate intralaboratory and interlaboratory reproducibility of identical chemical analyses. The MRD is defined as follows:

$$MRD = \left\{ \frac{\sum_{i=1}^n |x_i - y_i| / [(x_i + y_i) / 2]}{n} \right\} \times 100$$

where x_i and y_i represent two results for a constituent in a water sample for the i^{th} analysis, and n represents the number of result pairs for a constituent. Generally, the closer the original results and their replicate or duplicate results are to each other, the lower the MRD.

There are two types of intralaboratory comparisons: inhouse duplicate and blind replicate. For the in-house duplicate comparisons, the quantities x_i and y_i represent the original result and the in-house duplicate rerun, respectively. For the blind replicate comparisons, x_i and y_i represent the results for the known sample and the EPD/EMS blind replicate, respectively.

For both intralaboratory comparisons, the MRD is calculated as the average absolute difference between an original sample and its duplicate or blind replicate expressed as a percentage of the mean of those two samples. The intralaboratory MRD indexes for General Engineering and IT Analytical Services (first quarter only) are listed in the "Quality Control Samples" chapter of *The Savannah River Site's Groundwater Monitoring Program, First Quarter 1991* (ESH-EMS-910087); *The Savannah River Site's Groundwater Monitoring Program, Second Quarter 1991* (ESH-EMS-910088); *The Savannah River Site's Groundwater Monitoring Program, Third Quarter 1991* (ESH-EMS-910089); and *The Savannah River Site's Groundwater Monitoring Program, Fourth Quarter 1991* (ESH-EMS-910090).

For interlaboratory comparisons, x_i and y_i represent the mean analyte results for the original sample and all replicates or duplicates for the i^{th} analysis; x_i represents the mean result from one laboratory, and y_i represents the mean result from the other laboratory. The values x_i and y_i are calculated from the known sample results and the EPD/EMS blind replicate results. The MRD is calculated as the average absolute difference between laboratories for the i^{th} analysis expressed as a percentage of the mean of both laboratories.

A reference detection limit (RDL) for each analyte is determined for calculating the intralaboratory and interlaboratory MRD. Because some detection limits may be anomalously high (e.g., due to dilution or other effects), the RDL for an analyte is chosen as the value that is greater than or equal to at least 90 percent of the detection limit values from both laboratories. All of the detection limit values less than the RDL are adjusted to

the new RDL value. Analyses where constituents are not detected and where the detection limits are greater than the RDL are eliminated from the MRD index comparison and from subsequent statistical tests.

In addition to the interlaboratory MRD calculations, paired t-tests are performed to see if the difference between the mean concentrations of an analyte from the same well reported by each laboratory is significant. The t-test tests the null hypothesis that there is no significant difference in the concentrations given by the two laboratories. The MRD and t-test results of the interlaboratory comparison for the analytes with at least one result above the RDL are listed in the "Quality Control Samples" chapter of *The Savannah River Site's Groundwater Monitoring Program, First Quarter 1991* (ESH-EMS-910087). Since only one laboratory conducted analyses during second, third, and fourth quarters, the interlaboratory comparisons could not be conducted during these quarters.

NONRADIOLOGICAL SAMPLE COLLECTION AND ANALYSIS

Nonradiological surveillance at SRS began in 1951 with a water quality monitoring program on the Savannah River. Since that time, the nonradiological monitoring program has expanded to include monitoring for specific chemicals, metals, dissolved ions, and organic constituents in SRS liquid effluents, site streams, the Savannah River, groundwater, drinking water, air, and fish.

Table 4-9 lists the general nonradiological sampling and analysis schedule for specific environmental media. Collection, preservation, and analytical procedures for samples in the nonradiological monitoring program follow recommended guidelines in *Methods for Chemical Analysis of Water and Wastes* [EPA, 1979], *Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater* [EPA, 1982M], and *Standard Methods for the Examination of Water and Wastewater* [APHA, 1981].

Air

Five onsite ambient air-monitoring stations house instruments that continuously monitor for sulfur dioxide, oxides of nitrogen, and ozone. Particulate matter less than 10 microns is monitored every six days over a 24-hour period. Oxides of nitrogen and particulates are measured at every monitoring station; sulfur dioxide is measured at three stations; and ozone is measured at two stations. One monitoring station

contains two adjacent particulate samplers for quality assurance purposes. Sampling and analyses are performed in accordance with EPA requirements (40 CFR 58, Appendix B) and SCDHEC guidelines.

As discussed in the "Program Changes in 1991" section of this chapter, the operation of these five ambient air-monitoring stations was determined to be unnecessary, and they were shut down in June 1991. The stations are not required by the EPA or SCDHEC.

Liquid Effluents (NPDES)

Sample Collection

SRS wastewater effluent discharges, regulated by SCDHEC under two National Pollutant Discharge Elimination System (NPDES) program permits, are sampled according to procedures consistent with EPA methods (40 CFR Part 136). The sampling frequency varies with the outfall location and the parameters required by the NPDES permits.

Analytical Procedures

The types of analyses performed also vary with each permitted outfall. However, temperature, pH, total nonfilterable residue (suspended solids), and oil and grease are determined routinely at most outfalls. Certain outfall samples also are analyzed for metals, fecal coliform, nutrients, herbicides, and organic chemicals. All analyses are performed using accepted procedures in 40 CFR Part 136.

Offsite subcontracted laboratories perform all NPDES analyses except fecal coliform and field measurements (dissolved oxygen, chlorine, flow, temperature, and pH), which are performed onsite.

Streams and River

Sample Collection

Eight stream locations are sampled continuously by paddlewheel samplers for metal analyses. EMS collects the water samples weekly and preserves them according to requirements in 40 CFR Part 136. The samples are composited quarterly for metals analyses.

EMS collects grab samples from eight stream locations and three Savannah River locations monthly for nonmetals analyses. These samples are preserved according to EPA procedures (40 CFR Part 136). Composited samples are not used for nonmetals analyses because of short EPA-recommended holding times and restrictive preservation requirements.

Additional grab water samples are collected annually at seven stream locations and two Savannah River

The Savannah River and SRS streams are monitored for chemicals, metals, and physical and biological properties to ensure that SRS materials do not contaminate the aquatic environment.

locations for analysis of herbicides. These sites monitor the herbicides introduced into the Savannah River from SRS and provide information on the state of the Savannah River with respect to the herbicides analyzed. The monitored herbicides in stream and river water are listed in Chapter 8 and Table 8-24.

Analytical Procedures

Water quality in site streams and the Savannah River is monitored by analyzing samples for chemicals, metals, and physical and biological properties. All analyses are performed in accordance with EPA-approved methods contained in 40 CFR Part 136.

Field measurements of pH, dissolved oxygen, conductivity, and temperature are taken weekly at all river sampling locations and monthly at all stream sampling locations by EMS collections personnel.

Fish

In 1991, a total of 181 fish from 13 onsite and offsite locations were analyzed for mercury. The fish chosen for analysis represent the most common edible species in the SRS area.

Analytical Procedures

Concentrations of mercury (Hg) in units of $\mu\text{g/L}$ are calculated from a single curve produced by the collective absorbance data of known standard concentrations. A constant weight of 0.3 grams of flesh (muscle) is used for each analysis.

Groundwater

Groundwater samples were collected from more than 1,400 monitoring wells at SRS (Chapter 8). Samples are analyzed by subcontracted laboratories for metals, organic compounds, and other constituents. Most are collected using submersible pumps installed in the wells; some are collected using bailers lowered into the wells; and a few are collected from continuously pumping wells. Criteria that determine which wells will have analyses conducted on their samples are the nature of the site being monitored; the past history of monitoring at the site; and special needs of the well. Some samples are analyzed for chlorinated volatile organic chemicals by an SRS laboratory in M Area. Almost all determinations are made using EPA analytical procedures.

Drinking Water

The Power Operations Department operates 26 separate drinking water systems at SRS, and the Defense Waste Processing Facility (DWPF) operates one system in S Area. Most of the larger drinking water systems draw water from the Pee Dee, Black Creek, or Middendorf formations. Most of the smaller systems use shallow wells that draw water from the Congaree or Four Mile formations.

Chlorine is added to the water at each facility for bacteriological control. The larger systems are pH-adjusted by adding sodium hydroxide or soda ash to the systems. Polyphosphates are added to three systems for iron and corrosion control. All systems are monitored daily to determine the concentration of chemicals added to the water. Bacteriological samples are collected at frequencies ranging from daily to monthly, depending upon the size and type of the system.

A SCDHEC-certified offsite laboratory collects samples from all site drinking water systems every 12 to 16 months. The samples are analyzed for an

extensive list of chemical and physical attributes and contaminants to ensure that all systems meet SCDHEC and EPA drinking water standards.

SCDHEC collects samples for bacteriological and chemical analyses from the 14 larger systems onsite for regulatory checks. The frequency of sampling depends upon the analyte being measured.

SCDHEC also analyzes the drinking water samples for eight volatile organics that currently are regulated under South Carolina Primary Drinking Water Regulation R-61-58.

Sediment

Sediment samples are collected annually at seven stream locations and two Savannah River locations. In 1991, a 1-L grab sample was taken at each location, shipped to an offsite subcontracted laboratory, and analyzed for herbicides, using EPA methods 608 and 615. SRS has conducted this program since 1976, in conjunction with stream and river water sampling, to determine concentrations of these materials in SRS streams and in Savannah River sediments.

Table 4-1
General Radiological Sampling and Analysis Schedule

Sample Type	Sampling Frequency	Frequency of Analysis ^a
Air		
Filters	Continuous	Weekly Alpha, beta, Monthly Gamma emitters, ²³⁸ Pu, ²³⁹ Pu, and ^{89,90} Sr
Charcoal	Continuous	Weekly ¹³¹ I
Silica gel	Continuous	Weekly Tritium
Thermoluminescent dosimeters	Continuous	Quarterly Penetrating radiation
Streams	Continuous	Weekly Alpha, beta, tritium, and U/Pu Monthly ^{89,90} Sr, ⁹⁰ Sr, and gamma emitters
Savannah River	Continuous	Weekly Alpha, beta, tritium, and gamma emitters, Monthly ^{89,90} Sr, ⁹⁰ Sr, ²³⁸ Pu, and ²³⁹ Pu
Seepage basins	Quarterly	Alpha, beta, tritium, gamma emitters, ^{89,90} Sr, and U/Pu
Groundwater ^b	Requirements vary with location	
Milk	Biweekly	Gamma emitters and tritium
	Quarterly	⁹⁰ Sr
Food	Annually	Tritium, gamma emitters, ⁹⁰ Sr, U/Pu, ²³⁸ Pu, and ²³⁹ Pu
Eggs	Quarterly	Tritium, gamma emitters, ⁹⁰ Sr, U/Pu, ²³⁸ Pu, and ²³⁹ Pu
Drinking water		
Onsite	Monthly or quarterly	Alpha, beta, and tritium
Offsite	Semiannually	Alpha, beta, and tritium
Water treatment plants	Daily sampling Monthly analysis	Alpha, beta, and tritium
All locations	Annually	⁹⁰ Sr

^a Analysis frequencies not listed in this column follow the sampling frequency for that medium.

^b Sample collection and analytical procedures for groundwater monitoring are discussed in the quarterly groundwater reports.

Table 4-1
General Radiological Sampling and Analysis Schedule, Cont'd.

Sample Type	Sampling Frequency	Frequency of Analysis ^a
Rainwater	Continuous sampling	Monthly or quarterly Alpha, beta, tritium, gamma emitters, ²³⁸ Pu, ²³⁹ Pu, ^{89,90} Sr, and ⁹⁰ Sr
Soil and sediments	Annually	Gamma emitters, ⁹⁰ Sr, ²³⁸ Pu, and ²³⁹ Pu
Vegetation		Alpha, beta, tritium, ^{89,90} Sr, and gamma emitters
F, H, S, and Z Areas	Quarterly	
Outside Burial Ground fence	Quarterly	
Inside Burial Ground fence	Annually	
Seepage/Retention basins	Annually	
Offsite	Quarterly	

^a Analysis frequencies not listed in this column follow the sampling frequency for that medium.

Table 4-2
Lower Limits of Detection for Radiological Detection Instruments

Alpha Spectrometer Analysis of Plutonium

Sample:	Lower Limit of Detection:
Air filter	2.4E-17 $\mu\text{Ci/mL}$
Rain ion columns	2.8E-7 $\mu\text{Ci/m}^2$
River water	4.3E-15 $\mu\text{Ci/mL}$
Soil and sediment	8.6E-10 $\mu\text{Ci/g}$
Foodstuff	8.6E-11 $\mu\text{Ci/g}$

NOTE: These LLD values for the **alpha spectrometer** were calculated at the 95% confidence level using the formula given in the section, "Lower Limits of Detection," in Chapter 4. The air filter value is for one half of a single filter (2.5 CFM for one week). The sample aliquot was 2 L for river water, 10 g for soils, 100 g for foodstuff, and 0.031 m² per collection area for rain water. The typical recovery was 42%; the typical counting efficiency was 27%. The LLD for the actual samples are variable because of the effects of sample preparation, sample size, chemical recovery, counting efficiency, and radioactive decay. The sample counting time is 5000 minutes.

Gas-Flow Proportional Counters

Nuclide:	Lower Limit of Detection:
Gross alpha	6.8E-7 $\mu\text{Ci/sample}$
Nonvolatile beta	1.52E-6 $\mu\text{Ci/sample}$
Sr-89,90	2.38E-6 $\mu\text{Ci/sample}$
Sr-90	1.89E-6 $\mu\text{Ci/sample}$

NOTE: The instrument LLD values for the **gas-flow proportional counter** were calculated at the 95% confidence level using the formula given in the section, "Lower Limits of Detection," in Chapter 4. The counting efficiencies were 28% for alpha, and 40% for beta, ⁹⁰Sr, and ^{89,90}Sr. The LLD for the actual sample is variable because of the effects of sample aliquot size, sample preparation, chemical recovery, counting efficiency, and radioactive decay. The sample counting time was 20 minutes.

Liquid Scintillation Analyses for Weak Beta Emitters

Sample:	Lower Limit of Detection:
Tritium ^a	1.3E-6 $\mu\text{Ci/mL}$
Tritium ^b	4.7E-7 $\mu\text{Ci/mL}$
Phosphorus-32	6.2E-9 $\mu\text{Ci/mL}$
Promethium-147	8.6E-9 $\mu\text{Ci/mL}$
Sulfur-35	3.7E-9 $\mu\text{Ci/mL}$

NOTE: Instrumental LLD values for the liquid scintillation counter were calculated at the 95% confidence level using the formula given in the section, "Lower Limits of Detection," in Chapter 4. The average counting efficiencies were 37% for tritium, 79% for ³²P, 88% for ¹⁴⁷Pm, and 88% for ³⁵S. The LLD for the actual sample is variable because of the effects of sample preparation, sample aliquot size, chemical recovery, counting efficiency, counting time, and radioactive decay.

- a Routine environmental samples (e.g. stream samples and silica gels) are analyzed for tritium using a 20-minute count.
 b Environmental samples such as drinking water, foodstuff, and rainwater are analyzed using a 150-minute count.

Table 4-3
Lower Limits of Detection for High Purity Germanium (HPGe) Detector
Gamma Analysis of Air Filters

Nuclide	LLD (E-15 $\mu\text{Ci/mL}$)
	Air Filters
Ce-141	149
Ce-144	310
Co-58	55
Co-60	44
Cr-51	858
Cs-134	49
Cs-137	49
I-131	58
Mn-54	45
Nb-95	94
Ru-103	77
Ru-106	433
Sb-125	126
Zn-65	108
Zr-95	116

NOTE: The calculations were performed using a typical flow volume of 713.7 m³. Iodine-131 was collected on a charcoal cartridge. The typical counting interval used for particulate filters was 83 minutes and for charcoal cartridges, 2.8 hours. The typical decay time used for filters was five weeks, and for cartridges, two weeks. The chemical recovery is assumed to be 100%. The LLD values are based on a background measurement and calculated at the 95% confidence level using Canberra Industries APOGEE gamma analysis software.

Table 4-4
Lower Limits of Detection for High Purity Germanium (HPGe) Detector
Gamma Analysis of River, Stream, and Rain Ion Columns

Nuclide	LLD (E-09 $\mu\text{Ci/mL}$)		LLD (pCi/m^2)
	River	Stream	Rain
Ce-141	3.0	11	246
Ce-144	11	35	585
Co-58	2	5	99
Co-60	2	5	85
Cr-51	18	60	1,380
Cs-134	2	6	93
Cs-137	2	6	94
I-131	5	17	914
Mn-54	2	5	85
Nb-95	2	7	156
Ru-103	2	6	131
Ru-106	15	49	819
Sb-125	4	15	240
Zn-65	4	12	202
Zr-95	3	11	207

NOTE: The calculations were performed using a typical counting interval of 83 minutes. The typical sample decay times used were two weeks for river and stream waters, and four weeks for rain water. The sample volume (passed through the column) was 20 L for river water and 6 L for stream water. The rain deposition area was 4 ft². The chemical recovery is assumed to be 100%. The LLD values are based upon a background measurement and calculated at the 95% confidence level using Canberra Industries APOGEE gamma analysis software.

Table 4-5
Lower Limits of Detection for High Purity Germanium (HPGe) Detector
Gamma Analysis of Water and Milk Samples

Nuclide	LLD pCi/L		
	Water (1 L)	Water (500 mL)	Milk (1 L)
Ce-141	13	47	4
Ce-144	54	198	16
Co-58	11	39	4
Co-60	13	43	4
Cr-51	115	418	32
Cs-134	13	45	3
Cs-137	14	49	4
I-131	20	73	6
Mn-54	15	53	4
Nb-95	15	52	4
Ru-103	12	42	4
Ru-106	128	452	30
Sb-125	26	95	9
Zn-65	25	87	8
Zr-95	20	71	7

NOTE: The calculations were performed using a counting interval of 83 minutes for water, or 14 hours for milk, and a sample decay time of one week. The chemical recovery is assumed to be 100%. The LLD values are based upon a background measurement and calculated at the 95% confidence level using Canberra Industries APOGEE gamma analysis software.

Table 4-6
Lower Limits of Detection for High Purity Germanium (HPGe) Detector
Gamma Analysis of Vegetation, Soil, Wildlife, and Foods

Nuclide	LLD E-3 (pCi/g)			
	Vegetation	Soil	Seafood/ Wildlife	Foods
Ce-141	680	152	33	22
Ce-144	2,100	362	113	59
Co-58	322	61	21	11
Co-60	314	53	24	11
Cr-51	3,620	856	205	144
Cs-134	340	57	21	10
Cs-137	350	58	23	11
I-131	1,020	567	61	100
Mn-54	308	53	23	11
Nb-95	441	97	28	17
Ru-103	381	81	24	15
Ru-106	2,970	508	199	96
Sb-125	883	149	54	27
Zn-65	723	125	47	22
Zr-95	660	128	41	22

NOTE: The calculations were performed using a typical counting interval of 83 minutes for vegetation and soil, and 8.3 hours for seafood/wildlife and foods. The sample weights used were 100g vegetation, 600g soil, 250g seafood/wildlife, and 1,000g foods. Typical decay times used were two weeks for vegetation and seafood/wildlife, and four weeks for soil and foods. The chemical recovery is assumed to be 100%. The LLD values are based upon a background measurement and calculated at the 95% confidence level using Canberra Industries APOGEE gamma analysis software.

Table 4-7
Counting Geometries for Analysis of Gamma-Emitting Radionuclides

---

Water Geometries

Seven geometries are used to count samples having densities similar to water. All water, milk, wildlife, and vegetation samples are counted using one of the following water geometries:

- 1 L of water in a 1-L polyethylene Marinelli beaker
- 500 mL of water in a 1-L polyethylene Marinelli beaker
- 500 mL of water in a 500-mL polyethylene bottle
- 200 mL of water in a 500-mL polyethylene bottle
- 100 mL of water in a 500-mL polyethylene bottle
- 20 mL of water in a liquid scintillation vial
- 10 mL of water in a liquid scintillation vial

Air Filter Geometries

Filters used to collect air particulates are counted in one of the following geometries:

- 7.6-cm glass fiber filter in a Caplug® plastic holder
- 4.7-cm glass fiber filter in a Caplug® plastic holder (composite of 12 filters)

Charcoal Geometries

Charcoal samples are counted in the following geometries for volatile iodines:

- 1 L of charcoal in a 1-L polyethylene Marinelli beaker
- 3 × 2 in. triethylenediamine (TEDA)-impregnated charcoal cartridge
- 2.5-in. Mine Safety Appliance charcoal cartridge

Soil Geometry

Soil and sediment samples are counted using one geometry:

- 500 mL of soil in a 500-mL polyethylene bottle

Ion Exchange Column Geometry

Ionic forms of radionuclides in large volume water samples and rainwater samples are collected and concentrated on an ion exchange column. The ion exchange resin is then counted in the following geometry:

- 1.5 × 4 in.-Teflon® column containing an ion exchange resin

Table 4-8
Sample Media Data

Sample Matrix or Media	Sample Size	Representative Allquot
Gross alpha:		
Water	1 L	1 L
Vegetation	1–2 kg	1–5 g
Rain (collection pan)	0.37 m ²	0.093 m ² (1/4 total sample)
Air	whole filter	800 m ³
Nonvolatile beta:		
Water	1 L	1 L
Vegetation	1–2 kg	2 g
Air	whole filter	800 m ³
Strontium-89,90:		
River water	7 L	1 L
Rain	0.37 m ²	0.031 m ² (1/12 total sample)
Streams	1 L	1 L
Air composites		
site perimeter	20,000 m ³	4,200 m ³
25-mile radius	18,000 m ³	3,600 m ³
100-mile radius	6,000 m ³	1,200 m ³
Strontium-90:		
River water	7 L	7 L
Streams	6 L	3 L (duplicates)
Milk	0.5 L	0.5 L
Food	20 g	20 g
Rain	0.37 m ²	0.031 m ² (1/12 total sample)

Table 4-9
General Nonradiological Sampling and Analysis Schedule

Environmental Medium	Frequency	Analysis
Air	Continuously ^a	SO ₂ , NO _x , and O ₃
	Six-day intervals	Particulate Matter (PM ₁₀)
Liquid effluents (NPDES)	Varies with permit requirements	
Savannah River	Continuously	Quarterly Metals (monthly composites)
	Monthly	Water quality parameters ^b , temperature, pH, dissolved oxygen, conductivity and fecal coliform
	Annually	Herbicides
Streams	Weekly	Quarterly Metals (weekly composites)
	Monthly	Water quality parameters, organics, pH, dissolved oxygen, temperature, conductivity, and fecal coliform
Drinking water		
Primary systems	Annually	Chemicals, metals, and organics
Smaller systems	Varies with use	Chemicals, metals, and organics
All systems	Varies with use	Total coliform and residual chlorine
Wildlife (fish)	Monthly	Mercury
Sediments	Annually	Herbicides

a Ambient air stations were shut down in June 1991.

b Water quality parameters are given in Table 4-2.

To Learn About:	Turn to page:
♦ EMS QA/QC program guidelines	73
♦ Model QA program	74
♦ QA/QC results for EMS laboratories	75
♦ QA/QC results of subcontracted laboratories ...	77
♦ Nonradiological liquid effluents	78
♦ Stream and river water	79
♦ Groundwater monitoring	79

Compiled by G. Tim Jannik
Environmental Protection Department

Quality Assurance/Quality Control

1991 HIGHLIGHTS

- ♦ In nationwide QA programs conducted by DOE and EPA, environmental samples were provided to EMS for analysis. Conclusions from the 1991 program indicated that 93 of the 115 results (81 percent) reported by EMS fell within ± 20 percent of the EPA and DOE values, the acceptable range for all participating laboratories.
- ♦ When EMS analyzed 11 blind samples for tritium, 10 of the results (91 percent) were within the acceptance range for accuracy (± 20 percent).
- ♦ TMA/Eberline Inc. (formerly Normandeau Associates Inc.), subcontractor for the NPDES monitoring program, analyzed samples for the EPA Discharge Monitoring Report QA assessment program and received a 93 percent proficiency rating during 1991.
- ♦ A model QA program was developed for environmental monitoring to incorporate state and federal guidelines, as well as WSRC QA/QC requirements.

INTRODUCTION

The Environmental Monitoring Section (EMS) at Savannah River Site (SRS) maintains a quality assurance/quality control (QA/QC) program to verify the integrity of data generated within its environmental monitoring program. Each aspect of the monitoring program, from sample collection to data reporting, must address quality assurance, quality control, and quality assessment standards defined in the QA/QC program.

This chapter defines the guidelines and applicable standards for the environmental monitoring QA/QC program. The QA/QC program results for the EMS laboratory and subcontracted laboratories also are presented and discussed.

EMS QA/QC PROGRAM GUIDELINES

The EMS QA/QC program defines the quality-related activities and the quality assurance requirements necessary to ensure the validity and integrity of

monitoring data obtained from the analytical work performed or directed by EMS.

In addition, EMS's analytical program is designed to meet or exceed laboratory certification standards established by the Environmental Protection Agency (EPA) and the state of South Carolina.

For a complete description of the EMS QA/QC program, refer to the SRS Environmental Monitoring Plan (WSRC-3Q1-2-1000).

Applicable Standards

U.S. Department of Energy (DOE) Order 5700.6C and state and federal regulations establish requirements and guidelines for the Westinghouse Savannah River Company (WSRC) quality assurance program at SRS.

The *Westinghouse Savannah River Company Quality Assurance Plan* (WSRC 1-05) provides overall quality requirements for environmental surveillance programs. The requirements of WSRC 1-05 are

implemented in the *Westinghouse Savannah River Company Quality Assurance Manual* (WSRC 1Q).

WSRC 1Q is written not only to address the requirements of WSRC 1-05, but also the 18 quality assurance requirements of the national standard, American National Standards Institute (ANSI)/American Society of Mechanical Engineers (ASME) NQA-1 (Quality Assurance Program Requirements for Nuclear Facilities). These elements are listed in Chart 5-1.

The EMS QA Plan (WSRC-3Q1-2-8000) was developed as a mechanism for applying the quality assurance requirements of WSRC 1Q to the environmental monitoring program. *The Environmental Permitting Manual* (WSRC-1M-91-69) is a site document used as a reference for incorporating the applicable analytical requirements.

The National Emissions Standards for Hazardous Air Pollutants (NESHAP) defines specific QA requirements for monitoring radiological air emissions [EPA, 1989a]. A NESHAP-required sample tracking system was placed in operation during 1991. This computer-based system, entitled Environmental Monitoring Computer Automation Project (EMCAP), tracks all samples handled by the EMS laboratory. Refer to Chapter 4, "Sample Collection, Analytical Procedures, and Data Interpretation," for more information on EMCAP.

Records and data generated by the monitoring program are maintained in accordance with the requirements of DOE Order 1324.2A, "Records Disposition," and WSRC 1Q to ensure valid and defensible monitoring data.

QA records generated within environmental monitoring include sampling and analytical procedure manuals, logbooks, chain-of-custody forms, calibration and training records, analytical notebooks, control charts, validated laboratory data, and environmental reports. These records are maintained and stored according to requirements specified in HP-1, "Health Protection Record Retention Schedule."

Model QA Program

To implement an effective QA program, a model was developed that uses the following six tools described below. Figure 5-1 shows the relationship of these tools to the model QA program.

QA Training

All EMS personnel complete QA training designed for the group. Special emphasis is placed on regulations that govern the environmental monitoring program.

Data Tracking System

The EMS QA/QC data tracking system automatically retrieves and reports QA/QC sample data for surveillances. The system compares values to historical data and control limits and performs trending analysis as required by DOE orders. If control limits are exceeded, routine samples are flagged and reported immediately, thus reducing the response time to potential analytical problems.

Data Validation

The statistical data validation computer program reviews concentrations of both effluent and environmental samples. The results are compared to historical

Chart 5-1
Elements of the ANSI/ASME NQA-1 QA Program Requirements for Nuclear Facilities

♦ Organization	♦ Inspection
♦ Quality Assurance Program	♦ Test Control
♦ Design Control	♦ Control of Measuring and Test Equipment
♦ Procurement Document Control	♦ Handling, Storage and Shipping
♦ Instructions, Procedures and Drawings	♦ Inspection, Test and Operating Status
♦ Document Control	♦ Control of Nonconforming Items
♦ Control of Purchased Items and Services	♦ Corrective Actions
♦ Identification and Control of Items	♦ QA Records
♦ Control of Processes	♦ Audits

Figure 5-1 Environmental Monitoring System Model Quality Assurance Program

levels, established limits, and control locations. Statistical tools—including goodness-of-fit tests, control charting, probability plotting, and numerical and graphical summaries—are used to alert management of potential changes in the environmental baseline.

Quality Indicators

The concept of quality indicators includes developing a set of measurable indicators for each work group and visually displaying and monitoring these indicators against a quality goal.

Customized QA Activities

Customized QA activities include internal audits, control charts, control samples, blind samples, and trending.

Quality Assessment Program for Subcontracted Laboratories

The Quality Assessment Program (QAP) for monitoring subcontracted laboratory performance consists of

three types of evaluations (Figure 5-2). The Mean Relative Difference (MRD) statistical evaluation is the cornerstone of the QAP program. This statistic identifies the differences between laboratory duplicate and blind-sample results for intralaboratory comparisons. It also identifies the differences in split-sample results for interlaboratory comparisons. Refer to Chapter 4 for additional information on the MRD statistic.

QA/QC RESULTS FOR EMS LABORATORIES

Field Blind-Sample Program

As part of the nonradiological monitoring program, EMS routinely conducts a blind-sample program for field measurements of pH and conductivity to assess the quality and reliability of field data measurements.

During 1991, blind pH field measurements were taken for 44 samples, and blind conductivity field measurements were taken for 40 samples. The results from the blind-sample program are presented in Tables 5-1 and 5-2. The accuracy of these measurements was evaluated by calculating the percent difference for each

Figure 5-2 EMS Quality Assessment Program for Monitoring Performance of Subcontracted Laboratories.

pair of measurement values. The percent difference is the absolute value of the difference between the actual and reported measurements, divided by the actual, with the quantity multiplied by 100. Both accuracy and precision were further characterized by using the statistical method known as the 95 percent confidence interval [Steel and Torrie, 1980] for the percent difference.

Chart 5-2 provides the upper and lower 95 percent confidence limits for the mean value of the percent difference in the conductivity and pH measurements. (There is a 95 percent probability that the true percent difference is between the upper and lower confidence limits.)

Data for both pH and conductivity demonstrated skewed distributions. Using the method of Quantile (Q-Q) plots, the logarithms of these data more clearly satisfied the statistical assumption of normality. Therefore, the confidence intervals were calculated on the logarithms of pH and conductivity. The anti-logs of the mean (i.e., geometric mean) and the upper and lower confidence limits are reported.

Field measurements for chlorine, dissolved oxygen, and temperature also are performed by EMS personnel. However, due to the changing physical nature of these

parameters, they do not lend themselves to a blind-sample program. Instrumentation calibration is relied upon for quality control of these analyses, per Procedure Manual WSRC-3Q1.

Penetrating Radiation Measurements

Thermoluminescent dosimeters and hand-held survey meters used for penetrating radiation measurements are calibrated prior to use per Procedure Manual WSRC-3Q1. No additional QA/QC programs have been developed for these parameters.

Laboratory Comparison Programs

Analysis of Control Samples

One method of monitoring radiological laboratory performance within EMS is by using quality control samples. Air filter or water samples are prepared with known levels of radionuclides typically found in routine samples. Whenever possible, quality control samples are prepared from National Institute of Standards and Technology (NIST)-traceable material or standardized against NIST material. The quality control samples are labeled as "QC Blind" to aid in data retrieval. They are not true blind samples; however, their radionuclide composition is unknown to the analysts. "QC Blind" samples are analyzed and the results reported to the QA/QC coordinator. The

Chart 5-2
Conductivity and pH Measurements

	Lower 95% CL ^a	GM ^b	Upper 95% CL
Conductivity	2.16	2.85	3.76
pH	1.23	1.67	2.28

a Confidence level

b Geometric mean

compiled data verify that the laboratory maintains procedural controls. Approximately 31 percent of the EMS sampling and analysis load is devoted to QC activities. Control samples account for 15 percent, blanks account for 10 percent, duplicates account for 5 percent, and re-runs account for 1 percent.

During 1991, control samples were analyzed for tritium, gross alpha and beta, and gamma-emitting radionuclides as part of the blind sample program. The internal blind sample program's results are presented in Tables 5-3, 5-4, and 5-5. The acceptance ratio for accuracy is ± 20 percent (0.8 to 1.2) between measured and actual values. In 1991, all detectable measurements for gamma-emitting radionuclides were within the acceptance range; 10 tritium analyses of 11 fell within the acceptance range; and four of six gross alpha and beta analyses fell within the acceptance range.

The gross alpha and beta results show a bias in that all measured values are lower than the actual value. This bias is a result of EMS gross alpha and beta counters being calibrated with NIST standards. The NIST standards have a different geometry (electroplated near massless point sources) and radionuclide composition (Sr-90/Y-90) than do the blind samples. Sample self-absorption is corrected for, but random geometry and differing radionuclides will cause an unavoidable bias.

Interlaboratory Comparison Programs

In addition to the internal blind-sample program, the EMS laboratory routinely participates in two interlaboratory comparison programs to track performance accuracy. Under both programs, a variety of samples is sent to participating laboratories at intervals throughout the year, and results from the laboratories are compared. These comparisons not only test the accuracy of procedures, but compare SRS nationwide

with other laboratories. Below are descriptions of the two interlaboratory comparisons conducted in 1991.

DOE's QAP, an external quality assurance program, tests the quality of environmental data reported to DOE by its contractors. Reference samples for this program—including samples of soil, water, vegetation, animal tissues, and air filters—are prepared by the DOE Environmental Measurements Laboratory (EML) and sent to the participating laboratories. Analytical results are reported to EML within 90 days and compared with the test results of other laboratories. EML evaluates the results and distributes them to the participating laboratories.

The second program is administered by the Quality Assurance Division (QAD) of the EPA Environmental Monitoring System Laboratory-Las Vegas (EMSL-LV). This division is responsible for quality control of environmental radiological measurements. EPA provides participating laboratories with water, air, milk, and food samples that contain a variety of radionuclides with activity concentrations near environmental levels. The QAD program enables the EMS laboratory to document the accuracy of radiological analysis data, identify instrument and procedural problems, and compare analysis performance with other participating laboratories.

Sample results and performance ratings for the QAD and QAP programs are presented in Tables 5-6 and 5-7. The results reported by EMS in the QAD and QAP programs fell generally within ± 20 percent (0.8-1.2) of the EPA or DOE values. In the QAD program, 20 percent (12 of 60) of the year's results fell outside the acceptance ratio, while 18 percent (10 of 55) fell beyond the acceptance range for the QAP program.

The QAD and QAP programs identified that analyses for Sr-90 and Pu-239 were the main problem areas in the EMS laboratory. These two analytical procedures have been reviewed and revised and should show improved performance ratings in the future.

QA/QC RESULTS FOR SUBCONTRACTED LABORATORIES

Subcontracted Laboratory Guidelines

Subcontracted laboratories providing analytical services must have a documented QA/QC program and meet the same quality requirements defined in WSRC 1Q and WSRC 1-05. Subcontracted laboratories primarily perform nonradiological analyses. Chart 5-3 lists the subcontracted laboratories used during 1991 and the analytical programs in which they were involved.

Chart 5-3
Laboratories Subcontracted to EMS in 1991

Subcontracted Laboratory	Analytical Program
General Engineering Laboratories	Groundwater
IT Analytical Services	Groundwater
TMA/Eberline Inc.	Nonradiological liquid effluents (NPDES)
(Formerly Normandeau Associates Inc.)	River and stream water quality
	Sediments
J.H. Carr and Associates	QA laboratory for:
	NPDES
	Stream water
	River water
	Miscellaneous

To ensure that subcontracted laboratories have applied QA/QC requirements specific to their program, the performance of subcontracted laboratories is evaluated routinely through laboratory performance evaluations with the EPA Water Pollution Study, interlaboratory comparisons using EPA quality control samples, and laboratory evaluations at subcontractor facilities.

Nonradiological Liquid Effluents

Nonradiological liquid effluent samples are collected at each permitted SRS outfall according to requirements in the National Pollutant Discharge Elimination System (NPDES) permit, which is regulated by the South Carolina Department of Health and Environmental Control (SCDHEC). Effluent samples are analyzed by onsite laboratories for fecal coliform and biochemical oxygen demand, and by a subcontracted laboratory for other constituents, such as metals, organics, and oil and grease.

In 1991, the primary subcontractor for the NPDES program was TMA/Eberline Inc. (formerly Normandeau Associates Inc.). J. H. Carr and Associates acted as the QA laboratory for the interlaboratory comparison program in 1991. TMA/Eberline was involved in three separate laboratory comparison studies during the year—one intralaboratory comparison and two interlaboratory comparisons.

Intralaboratory Comparison Program

The intralaboratory program is used to compare performance within a laboratory by analyzing duplicate samples (10-15 percent) and blind samples

throughout the year. TMA/Eberline analyzed 191 duplicate samples for various parameters during 1991. Thirty-six of these analyses showed a difference of greater than ± 20 percent, which is the acceptance range. Thirty-four of the exceeding analyses were either biochemical oxygen demand (BOD), total suspended solids (TSS), or oil and grease. TMA/Eberline also analyzed 19 blind samples submitted by EMS. Only two of the 19 results (one TSS and one BOD) had ratios of accuracy outside the acceptable range of ± 20 percent (0.8-1.2).

Results of blind sample and duplicate analyses completed during 1991 are presented in Tables 5-8 and 5-9.

Interlaboratory Comparison Program

Interlaboratory comparison studies are used to compare performance between laboratories by submitting duplicate blind and spiked samples and EPA performance samples to different laboratories. During 1991, TMA/Eberline was involved in two interlaboratory comparison studies—one conducted by EPA and the second by EMS.

All subcontracted labs analyzing NPDES samples must participate in the EPA Discharge Monitoring Report Quality Assurance assessment program. EPA sends performance samples that contain constituents normally found in industrial and municipal wastewaters to participating laboratories.

These water samples have known chemical parameters, such as chemical oxygen demand, and contain

Chart 5-4
EPA Water Pollution Study for 1991

Laboratory	Number of Analyses	Acceptable Results	Non-Acceptable Results	Rating
TMA/Eberline	144	139	5	97%
J.H. Carr	142	137	5	96%

known concentrations of constituents, such as total suspended solids, oil and grease, and certain trace metals. EPA provides a final comprehensive report to the program participants. The report contains a statistical analysis of all data and documentation of the "true" sample value, with stated "acceptance limits" and "warning limits." In 1991, TMA/Eberline received a 93 percent proficiency rating. All its results were within acceptance limits; however, 7 percent of the results were outside the warning limits, which are used to indicate possible analytical problems before a sample result becomes unacceptable.

EMS conducted the second interlaboratory comparison between TMA/Eberline and J. H. Carr as an additional QA check. EMS sent each laboratory identical samples with known concentrations for analysis. The reported analytical data were compared to the known value, the range of acceptable values, and the other laboratory's reported values. Each laboratory was rated for proficiency by calculating the ratio of results within acceptable ranges to the number of analyses performed. The acceptable limits of proficiency were 80-100 percent.

The 1991 results demonstrated that both TMA/Eberline and J.H. Carr performed within the acceptable levels of proficiency (80-100 percent). Both laboratories received an 89 percent proficiency rating. The EMS interlaboratory comparison results are presented in Table 5-10.

Stream and River Water

Metals analyses for SRS streams and the Savannah River also are performed by a subcontracted laboratory. In 1991, TMA/Eberline was the primary subcontractor for the water quality program, and J.H. Carr acted as the QA laboratory for interlaboratory comparisons.

Interlaboratory Comparison Program

The water quality QA/QC program requires duplicate analyses of 10 percent of the samples to verify the

analytical results. In 1991, duplicate samples for metals analysis were split between two laboratories, TMA/Eberline and J.H. Carr.

TMA/Eberline received samples quarterly from each of the 11 water quality monitoring locations. Split-sample aliquots from two locations, Steel Creek at Highway 125 (SC-4) and near Shell Bluff (River 2), were distributed to J.H. Carr each quarter. Because of changes in the TMA/Eberline contract, fourth-quarter results are not available. Both laboratories determined the concentrations of 13 metals. The comparison of analytical data submitted by the two laboratories is provided in Table 5-11. The mean relative difference was used to evaluate these data. In addition, a split duplicate sample and a blind quarterly composite sample were analyzed by each laboratory. The results of these analyses is given in Table 5-12. Evaluation of the quarterly splits indicated that the results between the two laboratories were comparable, with the exception of aluminum and iron in the River 2 samples. The cause of the difference in values is not known.

Also in 1991, TMA/Eberline and J.H. Carr participated in the EPA Water Pollution Study. EPA provided the laboratories with samples spiked with known concentrations for analysis of trace metals (aluminum, cadmium, chromium, copper, iron, lead, manganese, nickel, and zinc), nutrients (nitrate-nitrogen and total phosphorus), volatile organics, biochemical oxygen demand, and miscellaneous constituents, such as pH, oil and grease, and total suspended solids.

During the 1991 study, both laboratories received ratings within the EPA acceptance criteria of 80-100 percent. The results are summarized in Chart 5-4.

Groundwater Monitoring

Groundwater analyses at SRS also are performed by subcontracted labs. During 1991, General Engineering Laboratories and IT Analytical Services were the primary subcontractors.

EMS personnel perform an annual evaluation of each subcontracted laboratory to ensure that the laboratories

Figure 5-3 Subcontracted analytical laboratories participated in quality control analyses comparison each quarter—General Engineering for four quarters and IT Analytical Services for one quarter. Both laboratories analyzed for Appendix IX constituents, priority pollutants, and routinely analyzed constituents.

maintain technical competence and follow the required QA programs. Each evaluation includes sample receipt, calibration procedures, analytical procedures, data verification, data reports, records management, nonconformance and corrective actions, and preventive maintenance. EMS provides reports of the findings and recommendations to each laboratory and conducts follow-up evaluations as necessary.

Interlaboratory Comparison Program

During the first quarter of 1991, split samples, representing 5 percent of the samples sent to each laboratory, were submitted for analysis to General Engineering, IT Analytical Services, the EMS laboratory, and the M-Area laboratory. A second portion of each split sample was sent to a different laboratory, and the results were used for interlaboratory comparisons.

Blind replicates, representing 5 percent of the samples sent to each laboratory, were submitted to General Engineering, IT Analytical Services, the EMS laboratory, and the M-Area laboratory for analysis each quarter. The results were used for intralaboratory and interlaboratory comparisons.

Trip blanks, representing 5 percent of the samples sent to each laboratory, were submitted to General Engineering, IT Analytical Services, and the EMS laboratory for analysis each quarter. The results were

used for intralaboratory and interlaboratory comparisons.

Equipment blanks, collected every day that a metal analysis sample was collected, were sent to General Engineering and IT Analytical Services for analysis during the first quarter and to General Engineering only for the remaining three quarters. The results were used for intralaboratory and interlaboratory comparisons.

Certified environmental quality control samples purchased from Environmental Resource Associates were sent to General Engineering and IT Analytical Services for analysis during the first quarter and to General Engineering only for the remaining three quarters. Each laboratory analyzed for EPA Appendix IX constituents, priority pollutants, and other routinely analyzed constituents. The results were compared based upon the percentage of results within the acceptable concentration range of the certified values.

For all three types of analyses, both laboratories received ratings within the EPA acceptance range of 80-100 percent. The comparison between the two laboratories is shown in Figure 5-3.

Intralaboratory Comparison Program

In addition to the blind replicate, trip blank, and equipment blank programs already described, field blanks representing 5 percent of the total M-Area samples were analyzed by the M-Area laboratory for intralaboratory comparisons.

Table 5-1
Blind Sample Results for Conductivity Field Measurements

Sample Identification	(μmhos/cm)		% Difference
	Measured Value	Actual Value	
BC-01-1	128	128	0.00%
BC-01-2	147	161	8.70%
BC-01-2	170	171	0.58%
BC-01-4	153	159	3.77%
BC-02-1	162	167	2.99%
BC-02-2	125	129	3.10%
BC-02-3	153	158	3.16%
BC-02-4	105	108	2.78%
BC-03-3	160	153	4.58%
BC-03-4	149	157	5.09%
BC-04-2	151	157	3.82%
BC-04-3	105	103	1.94%
BC-04-4	187	192	2.60%
BC-05-1	102	103	0.97%
BC-05-2	159	158	0.63%
BC-05-3	125	125	0.00%
BC-05-4	105	109	3.67%
BC-06-1	153	149	2.68%
BC-06-2	102	119	14.29%
BC-06-3	179	187	4.28%
BC-07-1	165	161	2.48%
BC-07-2	129	128	0.78%
BC-07-3	113	118	4.24%
BC-07-4	138	136	1.47%
BC-08-1	149	145	2.76%
BC-08-2	140	123	13.82%
BC-08-3	133	129	3.10%
BC-09-1	138	146	5.48%
BC-09-2	126	126	0.00%
BC-09-3	159	160	0.63%
BC-09-4	122	124	1.61%
BC-10-1	145	134	8.20%
BC-10-2	130	133	2.25%
BC-10-3	120	126	4.76%
BC-11-1	114	111	2.70%
BC-11-2	140	133	5.26%
BC-11-3	120	129	6.98%
BC-12-1	111	112	0.89%
BC-12-2	125	132	5.30%
BC-12-3	128	127	0.79%

Table 5-2
Blind Sample Results for pH Field Measurements

Sample Identification	pH Units		Difference
	Measured Value	Actual Value	
BpH-01-1	4.30	4.33	0.03units
BpH-01-2	6.96	6.98	0.02 units
BpH-01-3	7.00	6.77	0.23 units
BpH-01-4	7.04	7.01	0.03 units
BpH-01-5	6.30	6.30	0.00 units
BpH-02-1	5.08	4.80	0.28 units
BpH-02-2	5.74	5.65	0.09 units
BpH-02-3	4.08	3.71	0.37 units
BpH-02-4	7.28	6.99	0.29 units
BpH-03-1	7.10	7.02	0.08 units
BpH-03-2	6.70	6.52	0.18 units
BpH-03-3	4.35	4.42	0.07 units
BpH-03-4	5.60	5.35	0.25 units
BpH-04-1	6.81	7.02	0.21 units
BpH-04-3	6.05	5.93	0.12 units
BpH-04-4	4.72	4.58	0.14 units
BpH-05-1	4.47	4.52	0.05 units
BpH-05-2	6.70	7.00	0.30 units
BpH-05-3	7.04	6.86	0.18 units
BpH-05-4	6.75	7.08	0.33 units
BpH-06-1	3.86	4.03	0.17 units
BpH-06-2	7.44	7.40	0.04 units
BpH-06-3	10.50	9.58	0.92 units
BpH-07-1	4.99	4.95	0.04 units
BpH-07-2	7.10	7.04	0.06 units
BpH-07-3	9.18	9.00	0.18 units
BpH-07-4	6.95	6.99	0.04 units
BpH-07-5	6.95	6.99	0.04 units
BpH-08-1	6.68	6.62	0.06 units
BpH-08-2	8.04	8.34	0.30 units
BpH-08-3	7.47	7.53	0.06 units
BpH-09-1	6.74	6.70	0.04 units
BpH-09-2	7.53	7.60	0.07 units
BpH-09-3	8.20	8.21	0.01 units
BpH-09-4	6.40	6.82	0.42 units
BpH-10-1	6.70	6.82	0.12 units
BpH-10-2	7.30	7.38	0.08 units
BpH-10-3	7.80	7.78	0.02 units
BpH-11-1	7.20	6.95	0.25 units
BpH-11-2	4.20	4.11	0.09 units
BpH-11-3	7.50	7.34	0.16 units
BpH-12-1	6.87	6.96	0.09 units
BpH-12-2	4.50	4.39	0.11 units
BpH-12-3	7.60	7.22	0.38 units

Table 5-3
EMS Blind Sample Results for Tritium

Date	pCi/ml		Ratio
	Measured Value	Actual Value	
01-15-91	2.42 ± 0.80	2.71	0.89
02-15-91	1.51 ± 0.80	1.79	0.84
03-25-91	4.49 ± 0.82	4.53	0.99
04-26-91	2.83 ± 0.84	3.04	0.93
06-11-91	8.75 ± 0.55	8.85	0.99
07-17-91	5.38 ± 0.50	5.84	0.92
08-13-91	6.13 ± 1.00	6.33	0.97
09-10-91	5.18 ± 0.91	4.33	1.20
10-24-91	3.61 ± 0.47	3.08	1.17
11-18-91	3.57 ± 0.89	3.05	1.17
12-09-91	1.66 ± 0.80	1.27	1.31

Table 5-4
EMS Blind Sample Results for Gamma-Emitting Radionuclides

Sample Number	Nuclide	pCi/L		Ratio
		Measured Value	Actual Value	
82	Ba-133	53.0 ± 9.5	61.4 ± 5.5	0.86 ± 0.17
	Cs-137	16.0 ± 7.0	15.4 ± 2.0	1.04 ± 0.47
85	Ba-133	80.6 ± 14.5	95.6 ± 7.4	0.84 ± 0.16
	Co-60	35.0 ± 9.0	29.8 ± 3.0	1.17 ± 0.32

Table 5-5
EMS Blind Sample Results for Gross Alpha and Beta

Sample Number	Nuclide	pCi/L		Ratio
		Measured Value	Actual Value	
75	Gross Alpha	16.8 ± 3.6	21.0 ± 6.6	0.80 ± 0.30
	Gross Beta	37.9 ± 4.7	44.7 ± 7.7	0.85 ± 0.18
78	Gross Alpha	3.8 ± 2.1	5.7 ± 1.8	0.67 ± 0.42
	Gross Beta	4.5 ± 1.8	6.3 ± 1.5	0.71 ± 0.33
83	Gross Alpha	17.4 ± 4.1	21.0 ± 6.6	0.83 ± 0.32
	Gross Beta	41.5 ± 5.1	44.7 ± 7.7	0.93 ± 0.20

Table 5-6
QAD Interlaboratory Comparison of Analytical Results

Sample Date	Nuclide	SRS Value		QAD Value ^a		SRS/ QAD Ratio	No. of Labs	Mean Value of Labs		% Labs within 2 σ of QAD Value ^b
Water Samples (pCi/L)										
01-25-91	Alpha	3	$\pm$ 1.4	5	$\pm$ 5	0.6	168	5.69 $\pm$ 1.79		98%
04-16-91	Alpha	37	$\pm$ 6	54	$\pm$ 14	0.7	131	49.7 $\pm$ 11.4		90%
05-17-91	Alpha	13	$\pm$ 2.5	24	$\pm$ 6	0.5	173	21 $\pm$ 6.6		84%
09-20-91	Alpha	4.7	$\pm$ 1.5	10	$\pm$ 5	0.5	169	10.36 $\pm$ 3.15		95%
10-22-91	Alpha	70	$\pm$ 11	82	$\pm$ 21	0.9	140	76 $\pm$ 18		93%
02-08-91	Ba-133	80	$\pm$ 4	75	$\pm$ 8	1.1	135	74.1 $\pm$ 5.86		90%
06-07-91	Ba-133	59	$\pm$ 8	62	$\pm$ 6	1.0	138	61.37 $\pm$ 5.48		87%
10-04-91	Ba-133	96	$\pm$ 3.1	98	$\pm$ 10	1.0	131	96 $\pm$ 7.4		90%
01-25-91	Beta	5	$\pm$ 1.4	5	$\pm$ 5	1.0	167	6.3 $\pm$ 1.51		96%
04-16-91	Beta	166	$\pm$ 12	115	$\pm$ 17	1.4	128	108.6 $\pm$ 13.9		82%
05-17-91	Beta	33	$\pm$ 4.5	46	$\pm$ 5	0.7	176	44.7 $\pm$ 7.73		74%
09-20-91	Beta	18.7	$\pm$ 3.1	20	$\pm$ 5	0.9	166	20.3 $\pm$ 3.68		93%
10-22-91	Beta	43	$\pm$ 7	65	$\pm$ 10	0.7	142	56 $\pm$ 8		82%
02-08-91	Co-60	40	$\pm$ 2	40	$\pm$ 5	1.0	138	40.04 $\pm$ 2.87		90%
06-07-91	Co-60	11	$\pm$ 3	10	$\pm$ 5	1.1	137	10.7 $\pm$ 2.32		96%
10-04-91	Co-60	29.33 $\pm$ 2.4		29.0 $\pm$ 5.0		1.0	133	29.8 $\pm$ 3.0		96%
10-22-91	Co-60	21	$\pm$ 2	20	$\pm$ 5	1.1	99	20 $\pm$ 2.1		95%
02-08-91	Cs-134	7	$\pm$ 0.5	8	$\pm$ 5	0.9	135	8.09 $\pm$ 1.98		98%
04-16-91	Cs-134	26	$\pm$ 3	24	$\pm$ 5	1.1	103	22.96 $\pm$ 2.06		90%
06-07-91	Cs-134	15	$\pm$ 2	15	$\pm$ 5	1.0	137	14.2 $\pm$ 2.02		98%
10-04-91	Cs-134	8.7 $\pm$ 1.5		10 $\pm$ 5		0.9	133	9.9 $\pm$ 1.8		98%
10-22-91	Cs-134	8.3 $\pm$ 1.0		10 $\pm$ 5		0.8	97	9.6 $\pm$ 1.2		97%
02-08-91	Cs-137	9 $\pm$ 0.5		8 $\pm$ 5		1.1	133	9.06 $\pm$ 1.59		98%
04-16-91	Cs-137	25 $\pm$ 5		25 $\pm$ 5		1.0	104	25.5 $\pm$ 2.41		90%
06-07-91	Cs-137	15 $\pm$ 4		14 $\pm$ 5		1.1	137	15.37 $\pm$ 1.96		97%
10-04-91	Cs-137	9.7 $\pm$ 1.5		10 $\pm$ 5		1.0	133	10.9 $\pm$ 1.8		96%
10-22-91	Cs-137	12.3 $\pm$ 2.0		11 $\pm$ 5		1.1	99	12.4 $\pm$ 1.6		96%
02-22-91	H-3	4363 $\pm$ 250		4418 $\pm$ 442		1.0	128	4438 $\pm$ 333		92%
06-21-91	H-3	11500 $\pm$ 260		12480 $\pm$ 1248		0.9	137	12435 $\pm$ 941		91%
01-18-91	Pu-239	2.6 $\pm$ 0.3		3.3 $\pm$ 0.3		0.8	43	3.23 $\pm$ .36		77%
08-23-91	Pu-239	18.6 $\pm$ 0.6		19.4 $\pm$ 1.9		1.0	45	19.22 $\pm$ 4.62		83%
01-04-91	Ru-106	190 $\pm$ 22		199 $\pm$ 20		1.0	133	194 $\pm$ 21		86%
02-08-91	Ru-106	191 $\pm$ 15		186 $\pm$ 19		1.0	134	191.8 $\pm$ 19.9		85%
06-07-91	Ru-106	146 $\pm$ 30		149 $\pm$ 15		1.0	135	141.4 $\pm$ 14.1		84%
01-11-91	Sr-89	1 $\pm$ 2.6		5 $\pm$ 5		0.2	71	5.23 $\pm$ 1.6		100%
04-16-91	Sr-89	19 $\pm$ 9		28 $\pm$ 5		0.7	70	25.7 $\pm$ 6.45		81%
05-10-91	Sr-89	40 $\pm$ 8		39 $\pm$ 5		1.0	81	37.4 $\pm$ 8.27		76%

a Environmental Protection Agency Quality Assurance Division (QAD).

b Percentage of participating laboratories that had results falling within 2 σ of QAD value.

Table 5-6
QAD Interlaboratory Comparison of Analytical Results, Cont'd.

Sample Date	Nuclide	SRS Value	QAD Value ^a	SRS/QAD Ratio	No. of Labs	Mean Value of Labs	% Labs within 2 σ of QAD Value ^b
10-22-91	Sr-89	6 $\pm$ 4	10 $\pm$ 5	0.6	71	9.8 $\pm$ 2.5	96%
01-11-91	Sr-90	5 $\pm$ 1.7	5 $\pm$ 5	1.0	77	4.85 $\pm$ 1.01	99%
04-16-91	Sr-90	21 $\pm$ 5	26 $\pm$ 5	0.8	75	23.6 $\pm$ 3.27	89%
05-10-91	Sr-90	18 $\pm$ 4	24 $\pm$ 5	0.8	88	23.85 $\pm$ 3.02	93%
10-22-91	Sr-90	9 $\pm$ 3	10 $\pm$ 5	0.9	76	10 $\pm$ 2	98%
03-15-91	U nat	22.0 $\pm$ 7	7.6 $\pm$ 3	2.9	98	7.3 $\pm$ 1.36	96%
04-16-91	U nat	31.0 $\pm$ .65	29.8 $\pm$ 3.0	1.0	92	28.88 $\pm$ 3.42	77%
07-19-91	U nat	14.8 $\pm$ .20	14.2 $\pm$ 3.0	1.0	107	13.38 $\pm$ 2.00	91%
01-04-91	Zn-65	78.3 $\pm$ 8.0	73.0 $\pm$ 7.0	1.1	133	74.6 $\pm$ 6.6	89%
02-08-91	Zn-65	162 $\pm$ 13	149 $\pm$ 15	1.1	136	149.7 $\pm$ 10.7	90%
06-07-91	Zn-65	112 $\pm$ 12	108 $\pm$ 11	1.0	136	109.5 $\pm$ 8.13	93%

Air Filter Samples (pCi/filter)

03-29-91	Alpha	29 $\pm$ 3.1	25 $\pm$ 6	1.2	131	29.73 $\pm$ 5.93	77%
08-30-91	Alpha	30.7 $\pm$ 3.3	25.0 $\pm$ 6.0	1.2	131	28.3 $\pm$ 5.0	88%
03-29-91	Beta	108 $\pm$ 6	124 $\pm$ 6	0.9	134	130.1 $\pm$ 13.6	63%
08-30-91	Beta	95 $\pm$ 4.5	92 $\pm$ 10	1.0	133	95.5 $\pm$ 9.0	86%
08-30-91	Cs-137	31 $\pm$ 2.8	30.0 $\pm$ 5.0	1.0	125	32.5 $\pm$ 5.4	85%

Milk Samples (pCi/L)

04-26-91	Cs-137	53 $\pm$ 8	49 $\pm$ 5	1.1	87	51.3 $\pm$ 3.73	90%
09-27-91	Cs-137	34 $\pm$ 2.9	30.0 $\pm$ 5.0	1.1	79	31.3 $\pm$ 2.3	96%
04-26-91	K mg/mL	1840 $\pm$ 240	1650 $\pm$ 83	1.1	73	1653 $\pm$ 162	77%
09-27-91	K mg/mL	1888 $\pm$ 33	1740 $\pm$ 87	1.1	67	1667 $\pm$ 121	64%
04-26-91	Sr-90	30 $\pm$ 6	32 $\pm$ 5	0.9	47	28.02 $\pm$ 5.14	77%
09-27-91	Sr-90	26 $\pm$ 8	25 $\pm$ 5	1.0	48	21.2 $\pm$ 4.2	83%

^a Environmental Protection Agency Quality Assurance Division (QAD).

^b Percentage of participating laboratories that had results falling within 2 σ of QAD value.

Table 5-7
QAP Interlaboratory Comparison of Analytical Results

March-June 1991

Nuclide	SRS Value		QAP Value ^a	SRS/ QAP Ratio	No. of Labs	Mean Value of Labs	Labs 20% QAP Value ^b
Air (pCi/filter)							
Be-7	54.0	± 3.2	53.0	1.02	44	53.5	90
Ce-144	60.0	± 2.2	52.2	1.15	45	57.3	84
Co-57	6.6	± 0.3	5.82	1.13	45	5.95	84
Co-60	5.5	± 0.2	5.14	1.07	45	5.11	88
Cs-137	5.4	± 0.3	4.53	1.19	45	5.05	75
Mn-54	5.4	± 0.3	4.80	1.13	45	5.21	77
Pu-239	0.276	± 0.0150	0.154	1.79	29	0.149	75
Sr-90	0.08	± 0.09	0.079	1.01	15	0.076	28
U	2.485	± 0.0350	2.760	0.90	9	2.55	70
Soil (pCi/g)							
Cs-137	166.	± 8.	150.	1.11	45	163.	67
K-40	405.	± 20.	374.	1.08	39	384.	60
Pu238	11.011	± 0.370	11.500	0.96	26	10.400	77
Pu239	3.406	± 0.185	3.400	1.00	26	3.460	74
Sr-90	5.00	± 2.15	9.20	0.54	17	10.00	35
Vegetation (pCi/g)							
Cs-137	79.6	± 4.0	67.6	1.18	39	72.1	52
K-40	1334.	± 67.	1150.	1.16	32	1220.	61
Pu-238	3.47	± 0.157	4.060	0.85	20	3.560	90
Pu-239	0.898	± 0.080	1.400	0.64	22	1.040	13
Sr-90	134.3	± 26.6	186.0	0.72	19	162.0	7 ^c
Water (pCi/L)							
Am-241	1.38	± 1.22	1.19	1.16	25	1.09	61
Co-57	246.	± 9.	230.	1.07	48	235.	93
Co-60	204.	± 6.	201.	1.01	47	202.	95
Cs-137	184.	± 9.	169.	1.09	47	183.	85
H-3	363.	± 22.	361.	1.01	33	347.	83
Mn-54	232.	± 11.	213.	1.09	49	231.	89
Pu-239	0.706	± 0.050	0.773	0.91	34	0.688	85
Sr-90	6.510	± 1.550	8.630	0.75	25	8.930	76
U (Bq)	0.015	± 0.0002	0.017	0.88	17	0.016	73

a Quality Assessment Program (QAP) conducted by the DOE Environmental Measurements Laboratory (EML).

b Percentage of participating laboratories that had results falling between the $\pm 20\%$ acceptance range.

Table 5-7
QAP Interlaboratory Comparison of Analytical Results, Cont'd.

September-December 1991

Nuclide	SRS Value			QAP Value ^a	SRS/ QAP Ratio	No. of Labs	Mean Value of Labs	Labs 20% QAP Value ^b
Air (pCi/filter)								
Be-7	55.	±	3.	53.8	1.02	43	53.7	93%
Ce-144	53.1	±	2.5	50.8	1.05	45	49.1	86%
Co-57	18.3	±	1.1	16.6	1.10	43	17.	82%
Co-60	22.9	±	1.4	23.	1.00	45	22.3	91%
Cs-137	28.7	±	1.1	28.	1.02	45	27.7	91%
Mn-54	25.1	±	1.5	24.3	1.03	43	23.9	91%
Pu-239	0.0418	±	0.0076	0.084	0.50	29	0.084	76%
Sr-90	0.28	±	0.17	0.58	0.48	16	0.665	47%
U nat	3.02	±	0.08	3.08	0.98	10	3.33	36%
Soli (pCi/g)								
Cs-137	370.	±	19.	312.	1.19	41	350.	55%
K-40	492.	±	30.	430.	1.14	32	448.	70%
Pu-239	7.872	±	0.926	7.35	1.07	29	8.23	61%
Sr-90	1.2	±	2.7	3.78	0.32	12	3.75	15%
Vegetation (pCi/g)								
Cs-137	28.3	±	0.8	27.1	1.04	36	30.3	71%
K-40	1046.	±	49.	992.	1.05	34	1090.	83%
Pu-239	0.348	±	0.037	0.365	0.95	19	0.397	47%
Sr-90	267.	±	3.	439.	0.61	18	359.	57%
Water (pCi/L)								
Am-241	0.19	±	0.08	0.57	0.33	26	0.588	75%
Ce-144	230.	±	37.	226.	1.02	43	236.	77%
Co-57	183.	±	20.	166.	1.10	48	174.	91%
Co-60	307.	±	10.	291.	1.05	48	305.	93%
Cs-137	49.4	±	3.1	46.	1.07	48	49.2	83%
H-3	101.	±	22.	100.	1.01	32	100.	77%
Mn-54	105.	±	5.6	103.	1.02	47	106.	91%
Pu-239	0.478	±	0.0296	0.51	0.94	38	0.499	86%
Sr-90	10.2	±	2.2	10.9	0.94	26	10.8	72%
U nat	0.034	±	0.001	0.037	0.92	14	0.04	75%

a Quality Assessment Program (QAP) conducted by the DOE Environmental Measurements Laboratory (EML).

b Percentage of participating laboratories that had results falling between the $\pm 20\%$ acceptance range.

Table 5-8
NPDES Blind Sample Results

First Quarter

NPDES Site	Parameter Sampled	Unit	NPDES Result	Blind Sample Result	Difference
D-003	Total suspended solids	mg/L	8	6	2
D-003	Oil and grease	mg/L	<1	<1	<1
F-003	Biochemical oxygen demand	mg/L	5.1	1.1	4.0
H-016	Copper	mg/L	<0.01	<0.01	<0.01
H-016	Lead	mg/L	<0.003	<0.003	<0.003
H-016	Zinc	mg/L	<0.01	<0.01	<0.01
A-005	Perclene	µg/L	<1	<1	<1
A-005	Triclene	µg/L	<1	<1	<1
A-005	1,1,1 - Trichloroethane	µg/L	<1	<1	<1
A-003	Chromium	mg/L	<0.02	<0.02	<0.02
P-007	Aluminum	mg/L	0.447	0.556	0.109
P-007	Aluminum	mg/L	0.243	0.292	0.049

Third Quarter

NPDES Site	Parameter Sampled	Unit	NPDES Result	Blind Sample Result	Difference
M-004	Nitrates	mgN/L	142	131	11
M-004	Nickel	mg/L	<0.005	<0.005	<0.005
A-011	Oil and grease	mg/L	<1	<1	<1
A-011	Total suspended solids	mg/L	<1	<1	<1
A-001	Total suspended solids	mg/L	<1	<1	<1
X-008	Iron	mg/L	0.972	0.974	0.002
X-008	Aluminum	mg/L	0.159	0.158	0.001

Table 5-9
NPDES Duplicate Sample Results

First Quarter

Sample	Analyte	Result 1	Result 2	Difference
H-016	Ammonia , mgN/L	0.049	0.040	0.009
H-016	Zinc, mg/L	<0.01	<0.01	<0.01
A-001	Total suspended solids, mg/L	<1	<1	<1
A-001	Biochemical oxygen demand, mg/L	<1	<1	<1
A-001	Oil and grease, mg/L	<1	1.3	>0.3
A-003	Total suspended solids, mg/L	<1	<1	<1
A-003	Oil and grease, mg/L	1.2	1.3	0.1
A-003	Chromium, mg/L	<0.02	<0.02	<0.02
A-003	Chromium, mg/L	<0.02	<0.02	<0.02
A-003	Nitrate,mgN/L	<0.02	<0.02	<0.02
A-005	Total suspended solids, mg/L	<1	<1	<1
A-005	Oil and grease, mg/L	1.4	1.8	0.4
A-005	Fecal coliform, colonies/100 mL	<2	<2	<2
A-005	Perclene, µg/L	<2	<2	<2
A-005	Perclene, µg/L	<1	<1	<1
A-005	Triclene, µg/L	<2	<2	<2
A-005	Triclene, µg/L	<1	<1	<1
A-005	1,1,1-Trichloroethane, µg/L	<2	<2	<2
A-005	1,1,1-Trichloroethane, µg/L	<1	<1	<1
A-011	Total suspended solids, mg/L	<1	<1	<1
A-011	Oil and grease, mg/L	<1	<1	<1
M-004	Phosphate, mgP/L	0.064	0.058	0.006
D-001	Total suspended solids, mg/L	11	10	1
D-001	Oil and grease, mg/L	<1	<1	<1
H-016	Nitrate, mgN/L	32.5	31.4	1.1
D-006	Fecal coliform, colonies/100 mL	120	108	12
H-016	Copper, mg/L	<0.01	<0.01	<0.01
H-016	Copper, mg/L	<0.01	<0.01	<0.01
H-016	Lead, mg/L	<0.003	<0.003	<0.003
D-1C	Total suspended solids, mg/L	6	5	1
D-1C	Oil and grease, mg/L	<1	<1	<1
C-001	Oil and grease, mg/L	<1	<1	<1
C-001	Total suspended solids, mg/L	1	1	0
C-003	Oil and grease, mg/L	<1	<1	<1
C-003	Total suspended solids, mg/L	<1	<1	<1
C-004	Oil and grease, mg/L	<1	<1	<1
C-004	Total suspended solids, mg/L	4	4	0
A-014	Oil and grease, mg/L	<1	<1	<1
A-014	Biochemical oxygen demand, mg/L	1.1	<1	<1.1
A-014	Total suspended solids, mg/L	<1	<1	<1
F-001	Oil and grease, mg/L	1.0	1.2	0.2
F-002	Oil and grease, mg/L	1.7	2.4	0.7
F-003	Oil and grease, mg/L	3.0	<1	>2
F-003	Biochemical oxygen demand, mg/L	5.1	1.0	4.1
F-003	Total suspended solids, mg/L	4	2	2
F-001	Total suspended solids, mg/L	4	2	2
F-002	Total suspended solids, mg/L	1	2	1
D-003	Total suspended solids, mg/L	8	5	3
D-003	Oil and grease, mg/L	<1	<1	<1

Table 5-9
NPDES Duplicate Sample Results, Cont'd.

First Quarter, Cont'd.

Sample	Analyte	Result 1	Result 2	Difference
D-006	Total suspended solids, mg/L	18	19	1
D-006	Oil and grease, mg/L	<1	<1	<1
P-007	Aluminum, mg/L	0.243	0.316	0.073
P-007	Iron, mg/L	0.477	0.502	0.025

Table 5-9
NPDES Duplicate Sample Results, Cont'd.

Second Quarter

Sample	Analyte	Result1	Result 2	Difference
X-014	Bezene, µg/L	<1	<1	<1
M-004	Nitrate, mg/L	1030	1040	10
M-004	Phosphate, mgP/L	4.65	4.82	0.17
F-005	Total suspended solids, mg/L	3	3	0
F-005	Oil and grease, mg/L	1.1	1.3	0.2
F-008	Total suspended solids, mg/L	3	3	0
F-008	Oil and grease, mg/L	<1	1.3	>0.3
H-016	Mercury, mg/L	<0.0001	<0.0001	<0.0001
H-002	Total suspended solids, mg/L	2	2	0
H-002	Oil and grease, mg/L	<1	<1	<1
H-004	Total suspended solids, mg/L	2	2	0
H-004	Oil and grease, mg/L	<1	<1	<1
H-008	Total suspended solids, mg/L	8	8	0
H-008	Oil and grease, mg/L	<1	1.3	<1.3
A-003	Chromium, mg/L	<0.02	<0.02	<0.02
A-003	Chromium, mg/L	<0.02	<0.03	>0.01
K-011	Total suspended solids, mg/L	5	5	0
K-011	Total suspended solids, mg/L	5	9	4
K-011	Total suspended solids, mg/L	5	8	3
K-011	Oil and grease, mg/L	<1	<1	<1
K-011	Oil and grease, mg/L	<1	<5	>4
K-011	Oil and grease, mg/L	<1	<5	>4
DW-002	Oil and grease, mg/L	<1	<1	<1
SC-004	Phosphate, mgP/L	0.032	0.030	0.002
SC-004	Phosphate, mgP/L	0.032	<0.05	<0.018
SC-004	Phosphate, mgP/L	0.032	<0.05	<0.018
SC-004	Cadmium, mg/L	<0.01	<0.01	<0.01
SC-004	Cadmium, mg/L	<0.01	<0.01	<0.01
SC-004	Cadmium, mg/L	<0.01	<0.01	<0.01
K-006	Total suspended solids, mg/L	2	2	0
K-006	Oil and grease, mg/L	<1	<1	<1
P-013	Total suspended solids, mg/L	1	1	0
P-013	Oil and grease, mg/L	<1	<1	<1
P-019	Total suspended solids, mg/L	2	2	0
P-019	Oil and grease, mg/L	<1	<1	<1
SC-004	Lead, mg/L	0.0047	0.011	0.0063
SC-004	Lead, mg/L	0.0047	<0.005	<0.0003
SC-004	Lead, mg/L	0.0047	<0.005	<0.0003
L-008	Total suspended solids, mg/L	2	3	1
L-008	Oil and grease, mg/L	<1	<1	<1
M-004	Oil and grease, mg/L	<1	<1	<1
M-005	Perclene, µg/L	<2	<2	<2
M-005	1,1,1-Trichloroethane, µg/L	<2	<2	<2
M-005	Triclene, µg/L	<2	<2	<2
H-016	Total suspended solids, mg/L	<1	<1	<1
H-016	Biochemical oxygen demand, mg/L	1.7	1.5	0.2

Table 5-9
NPDES Duplicate Sample Results, Cont'd.

Second Quarter, Cont'd.

Sample	Analyte	Result 1	Result 2	Difference
H-016	Biochemical oxygen demand, mg/L	2.8	3.2	0.4
H-016	Zinc, mg/L	0.013	0.01	0.003
H-016	Oil and grease, mg/L	<1	<1	<1
X-008	Aluminum, mg/L	<0.05	<0.05	<0.05
X-008	Aluminum, mg/L	<0.05	<0.05	<0.05
X-008	Aluminum, mg/L	<0.05	<0.05	<0.05
X-008	Iron, mg/L	1.19	1.21	0.02
X-008	Iron, mg/L	1.19	1.10	0.08
X-008	Iron, mg/L	1.19	1.12	0.07

Table 5-9
NPDES Duplicate Sample Results, Cont'd.

Third Quarter

Sample	Analyte	Result 1	Result 2	Difference
X-014	Biochemical oxygen demand, mg/L	1.3	1.9	0.6
X-008	Total suspended solids, mg/L	1	<1	<1
X-014	Total organic carbon, mg/L	3.89	2.31	1.58
X-014	Total suspended solids, mg/L	1	1	0
X-004	Oil and grease, mg/L	1.3	1.2	0.1
X-004	Total suspended solids, mg/L	1	1	0
X-008	Oil and grease, mg/L	<1	3.5	>2.5
X-014	Oil and grease, mg/L	<1	<1	<1
SC-004	Nitrate, mgN/L	0.03	0.04	0.01
SC-004	Phosphate, mgP/L	0.070	0.042	0.028
SC-004	Silver, mg/L	<0.0005	<0.0005	<0.0005
A-001	Biochemical oxygen demand, mg/L	<1	3.5	>2.5
A-001	Oil and grease, mg/L	<1	<1	<1
X-008	Aluminum, mg/L	0.159	0.164	0.005
X-008	Iron, mg/L	0.972	0.954	0.018
M-004	Total suspended solids, mg/L	4	3	1
F-001	Total suspended solids, mg/L	1	<1	<1
F-001	Oil and grease, mg/L	<1	<1	<1
M-004	Phosphate, mgP/L	8.58	8.50	0.08
M-004	Nickel, mg/L	<0.05	<0.1	>0.05
M-004	Oil and grease, mg/L	1.3	1.2	0.1
C-001	Total suspended solids, mg/L	1	2	1
C-001	Total suspended solids, mg/L	<1	<1	<1
C-001	Oil and grease, mg/L	<1	<1	<1
C-001	Oil and grease, mg/L	<1	<1	<1
C-004	Total suspended solids, mg/L	3	1	2
C-004	Oil and grease, mg/L	3.2	2	1.2
A-014	Oil and grease, mg/L	<1	<1	<1
A-014	Total suspended solids, mg/L	<1	<1	<1
H-016	Total suspended solids, mg/L	2	2	0
H-016	Oil and grease, mg/L	<1	<1	<1
A-003	Total suspended solids, mg/L	<1	<1	<1
A-003	Oil and grease, mg/L	1.8	4.5	2.7
A-003	Chromium, mg/L	<0.02	<0.02	<0.02
D-001	Total suspended solids, mg/L	2	2	0
D-001	Oil and grease, mg/L	2.6	1.0	1.6
D-006	Total suspended solids, mg/L	8	8	0
D-006	Fecal coliform, colonies/100mL	154	74	80
M-005	1,1,1-Trichloroethane, µg/L	<2	<2	<2
M-005	Perchlene, µg/L	<2	<2	<2
M-005	Triclene, µg/L	<2	<2	<2

Table 5-9
NPDES Duplicate Sample Results, Cont'd.

Fourth Quarter

Sample	Analyte	Result 1	Result 2	Difference
A-005	Fecal coliform, colonies/100 mL	<2	<2	<2
X-008	Aluminum, mg/L	<0.05	<0.05	<0.05
X-008	Iron, mg/L	1.44	1.24	0.2
H-002	Total suspended solids, mg/L	3	4	1
H-002	Oil and grease, mg/L	<1	3	>2
A-005	Perclene, µg/L	<2	<2	<2
A-005	Triclene, µg/L	<2	<2	<2
A-005	1,1,1-Trichloroethane, µg/L	<2	<2	<2
X-014	Biochemical oxygen demand, mg/L	1.5	1.4	0.1
F-002	Total suspended solids, mg/L	2	2	0
F-002	Oil and grease, mg/L	2.8	4.5	1.7
F-003	Total suspended solids, mg/L	11	2	9
F-003	Oil and grease, mg/L	2.1	2.1	0
F-005	Total suspended solids, mg/L	3	2	1
F-005	Oil and grease, mg/L	1.6	1.1	0.5
F-008	Total suspended solids, mg/L	36	35	1
F-008	Oil and grease, mg/L	1.3	1.9	0.6
D-006	Fecal coliform, colonies/100 mL	46	36	10
D-001	Total suspended solids, mg/L	8	8	0
D-001	Oil and grease, mg/L	<1	1.4	>0.4
F-001	Total suspended solids, mg/L	3	5	2
F-001	Oil and grease, mg/L	18	<1	>17
A-014	Oil and grease, mg/L	<1	<1	<1
A-014	Perclene, µg/L	<2	<2	<2
A-014	Triclene, µg/L	<2	<2	<2
A-014	1,1,1-Trichloroethane, µg/L	<2	<1	>1
H-004	Total suspended solids, mg/L	3	<1	>2
H-004	Oil and grease, mg/L	<1	2.5	>1.5
H-008	Total suspended solids, mg/L	1	1	0
H-008	Oil and grease, mg/L	8.7	6.8	1.9
SC-004	Nitrate, mgN/L	0.03	0.03	0
SC-004	Phosphate, mgP/L	0.016	0.033	0.017
SC-004	Selenium, mg/L	<0.006	<0.006	<0.006
SC-004	Selenium, mg/L	<0.006	<0.006	<0.006
SC-004	Arsenic, mg/L	<0.003	<0.003	<0.003
SC-004	Chromium, mg/L	<0.02	<0.02	<0.02
H-016	Biochemical oxygen demand, mg/L	2.4	2.4	0
H-016	Zinc, mg/L	0.014	0.094	0.08
L-008	Total suspended solids, mg/L	3	3	0
L-008	Oil and grease, mg/L	<1	5.5	>4.5
P-013	Total suspended solids, mg/L	1	2	1
P-013	Oil and grease, mg/L	<1	11.1	>10.1

Table 5-10
Interlaboratory Quality Assessment Program

Parameters	Theoretical Value	Acceptance Result Range	Carr Result	TMA/Eberline Result
Minerals (mg/L)				
pH	9.1	[8.9-9.3]	9.0	9.14
Sulfate	92	[79-105]	360**	85.6
Chloride	293	[272-314]	284	296
Fluoride	7.4	[6.6-8.2]	6.5	7.27
Alkalinity as CaCO ₃	160	[147-173]	126**	161
Conductivity (μmhos/cm)	1340	[1210-1470]	1375	1510**
Dissolved Solids	1060	[920-1200]	968	977
Grease and oil	29.3	[22-37]	27.4	28.7
Demand (mg/L)				
Biochemical oxygen demand	78.4	[60-99]	119**	54.4**
Chemical oxygen demand	131	[111-151]	120	120
Total organic carbon	51.4	[44-59]	61**	51.7
Kjeldahl nitrogen as N	6.13	[5.0-7.2]	5.7	5.62
Nutrients (mg/L)				
Ammonia as Nitrogen	3.85	[3.2-4.5]	4.3	4.39
Nitrate as Nitrogen	8.83	[7.8-9.8]	8.4	8.56
Phosphate as Phosphorous	10.6	[9.0-12]	10.1	10.3
Trace Metals (μg/L)				
Aluminum	626	[513-739]	570	647
Arsenic	131	[98-154]	111	123
Barium	356	[291-420]	314	359
Boron	197	[161-232]	208	247**
Calcium	0	[0]	0	0
Cadmium	164	[134-194]	162.6	167
Chromium	437	[358-516]	435	464
Copper	414	[339-488]	399	430
Iron	621	[509-773]	596	661
Lead	261	[214-308]	266	258
Manganese	379	[311-447]	356	393
Magnesium	0	[0]	0	0
Mercury	5.7	[4.2-7.2]	5.22	7.17
Nickel	485	[398-572]	460	517
Zinc	449	[368-530]	460	476

Table 5-10
Interlaboratory Quality Assessment Program, Cont'd.

Parameters	Theoretical Value	Acceptance Result Range	Carr Result	TMA/Eberline Result
Organics (µg/L)				
gamma-BHC (Lindane)	2.11	[0.61-2.9]	1.86	0.87
Endrin	0.629	[0.19-0.92]	0.60	0.27
Methoxychlor	1.34	[0.40-2.1]	1.11	1.46
2,4-D	1.85	[0.55-2.4]	1.57	0.55
2,4,5-TP Silvex	1.33	[0.40-1.7]	1.03	0.48
Pesticides (µg/L)				
Aldrin	0.606	[0.25-0.74]	0.510	0.24**
alpha-BHC	0.270	[0.10-0.36]	0.260	0.10
Endrin	1.25	[0.38-1.8]	1.09	0.53
heptachlor Epoxide	0.690	[0.25-0.98]	0.60	0.26
PCBs (µg/L)				
Aroclor 1260	8.39	[2.6-11]	0	0
Acceptance Level^a		85 – 100%	89%	89%

a The acceptance level is a percentage rating which is based on the ratio of acceptable results versus total determinations requested. The percent range of acceptance for EMS is based on standard laboratory and best management practices.

** outside the range of the acceptance level.

Table 5-11
Results of Metals Analysis on Split Quarterly Composites

Parameter	SC-4 (mg/L)			River 2 (mg/L)		
	Carr	TMA/Eberline	MRD ^a	Carr	TMA/Eberline	MRD ^a
FIRST QUARTER						
Aluminum	<0.05	<0.05	-	0.310	1.58	134
Cadmium	<0.01	<0.01	-	<0.01	<0.01	-
Calcium	3.2	3.01	6	3.76	3.61	4
Chromium	<0.05	<0.02	-	<0.05	<0.02	-
Copper	<0.05	0.01	-	<0.05	<0.01	-
Iron	0.17	0.182	7	0.98	2.65	92
Lead	<0.005	0.0048	-	<0.005	0.0041	-
Magnesium	1.06	0.933	13	1.29	1.20	7
Manganese	<0.05	0.0134	-	0.14	0.139	0.7
Mercury		<0.0001	-	0.00023	<0.0001	-
Nickel	<0.05	<0.05	-	<0.05	<0.05	-
Sodium	6.89	6.12	12	7.24	7.24	2
Zinc	<0.05	<0.01	-	<0.05	0.011	-
SECOND QUARTER						
Aluminum	<0.05	0.10	-	0.220	0.833	116
Cadmium	<0.01	<0.01	-	<0.01	<0.01	-
Calcium	1.92	b	-	3.7	b	-
Chromium	<0.05	<0.02	-	<0.05	<0.02	-
Copper	<0.05	<0.01	-	<0.05	<0.01	-
Iron	0.19	0.213	11	0.74	1.39	61
Lead	<0.005	0.0032	-	<0.005	<0.003	-
Magnesium	1.16	b	-	1.45	b	-
Manganese	<0.05	b	-	0.11	b	-
Mercury	0.0002	<0.0001	-	<0.0002	<0.0001	-
Nickel	<0.05	<0.05	-	<0.05	<0.05	-
Sodium	6.44	6.64	3	6.49	6.68	3
Zinc	<0.05	<0.01	-	0.05	<0.01	-
THIRD QUARTER						
Aluminum	<0.05	0.53	-	0.09	0.332	115
Cadmium	<0.01	<0.01	-	<0.01	<0.01	-
Calcium	1.97	c	-	3.65	c	-
Chromium	<0.05	<0.02	-	<0.05	<0.02	-
Copper	<0.05	<0.01	-	<0.05	<0.01	-
Iron	0.16	0.173	8	0.51	0.727	32
Lead	<0.005	<0.003	-	<0.005	<0.003	-
Magnesium	0.96	c	-	1.36	c	-
Manganese	0.05	c	-	0.12	c	-
Mercury	<0.0002	<0.0001	-	<0.0002	<0.0001	-
Nickel	<0.05	<0.05	-	<0.05	<0.05	-
Sodium	5.2	5.43	4	7.15	7.58	6
Zinc	<0.05	<0.01	-	<0.05	0.012	-
FOURTH QUARTER^c						

a The mean relative difference (MRD) was calculated by dividing the difference between the reported values by the average values multiplied by 100. The MRD will be inflated for result differences as the result approaches the detection limit.

b Not tested.

c Due to expiration of contract, fourth quarter results and some third quarter results are not available.

Table 5-12
Results of Metals Analysis on Split Duplicate and Blind Quarterly Composites

Parameter	(mg/L)			(mg/L)		
	Carr	Duplicate Sample	Blind Sample	TMA/Eberline	Duplicate Sample	Blind Sample
FIRST QUARTER						
Aluminum	0.320	0.320	0.30	0.194	0.204	0.155
Cadmium	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Calcium	2.8	2.78	2.76	2.65	2.77	2.6
Chromium	<0.05	<0.05	<0.05	<0.02	<0.02	<0.02
Copper	<0.05	<0.05	<0.05	0.027	0.031	0.025
Iron	0.42	0.42	0.41	0.486	0.534	0.441
Lead	0.0005	0.0006	<0.0005	0.0094	0.0116	0.0059
Magnesium	0.78	0.77	0.76	0.676	0.690	0.668
Manganese	<0.05	<0.05	<0.05	0.016	0.0172	0.0138
Mercury	0.00026	0.00023	0.00023	<0.0001	<0.0001	<0.0001
Nickel	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Sodium	5.0	4.9	2.76	4.41	4.51	4.52
Zinc	<0.05	<0.05	<0.05	<0.01	0.013	<0.01
SECOND QUARTER						
Aluminum	0.10	<0.05	0.01	0.141	0.069	0.175
Cadmium	<0.01	<0.01	0.01	<0.01	<0.01	<0.01
Calcium	0.35	16.6	0.40	a	a	a
Chromium	<0.05	<0.05	<0.05	<0.02	<0.02	<0.02
Copper	<0.05	<0.05	<0.05	<0.01	<0.01	<0.01
Iron	0.26	0.12	0.27	0.369	0.228	0.414
Lead	<0.0005	<0.0005	<0.0005	<0.003	<0.003	<0.003
Magnesium	0.28	0.66	0.31	a	a	a
Manganese	<0.05	<0.05	<0.05	a	a	a
Mercury	<0.0002	0.0002	<0.0002	<0.0001	<0.0001	<0.0001
Nickel	<0.05	<0.05	0.05	<0.05	<0.05	<0.05
Sodium	1.15	2.19	1.15	1.38	2.05	1.55
Zinc	<0.05	<0.05	<0.05	<0.01	<0.01	<0.01
THIRD QUARTER						
Aluminum	<0.05	<0.05	0.01	0.098	0.112	0.129
Cadmium	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01
Calcium	4.11	4.08	4.02	b	b	b
Chromium	<0.05	<0.05	<0.05	<0.02	<0.02	<0.02
Copper	<0.06	0.06	<0.05	0.062	0.067	0.065
Iron	0.65	0.66	0.65	0.688	0.702	0.665
Lead	<0.0005	<0.0005	<0.0005	<0.003	<0.003	<0.003
Magnesium	0.79	0.79	0.78	b	b	b
Manganese	<0.05	<0.05	<0.05	b	b	b
Mercury	0.00029	<0.0002	<0.0002	<0.0001	<0.0001	<0.0001
Nickel	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05
Sodium	4.77	4.65	4.77	4.9	4.6	4.55
Zinc	<0.05	<0.05	<0.05	0.039	0.024	0.028
FOURTH QUARTER^b						

a Not tested

b Due to expiration of contract, fourth quarter results and some third quarter results are not available.

To Learn About:	Turn to page:
♦ Radiation dose definitions	101
♦ Radiation dose standards and limits	105
♦ Representative scenarios for offsite dose calculations	106
♦ Dose calculation models	107
♦ CAP88 computer code for NESHAP compliance ..	108
♦ Modeling atmospheric radioactive releases	109
♦ Modeling transport of liquid radioactive releases ..	112

Compiled by G. Tim Jannik
Environmental Protection Department

Calculating Radiation Doses

1991 HIGHLIGHTS

- ♦ Most radioactive materials released from SRS have such low concentrations when dispersed in the environment that standard monitoring procedures cannot detect the materials. Therefore, mathematical models are used to estimate the doses to offsite populations. These models calculate radiation doses using known environmental transport mechanisms and known pathways of exposure to man. Measured concentrations of radioactive materials in environmental media are used to validate the dispersion calculations in the atmospheric model and to adjust some parameters and input data in the liquid model.
- ♦ SRS uses the MAXIGASP, POPGASP, and LADTAPII radiation transport and dose model codes. These computer codes were developed for the commercial nuclear industry. MAXIGASP calculates the maximum and average offsite doses to individuals from atmospheric releases. POPGASP calculates the collective dose from atmospheric releases. LADTAPII calculates the maximum and average individual and collective doses from liquid releases.
- ♦ The CAP88 computer code (updated version of AIRDOS/RAD RISK) is required, under the Clean Air Act regulations (40 CFR 61), to be used to calculate offsite doses from atmospheric releases from existing and proposed facilities to show compliance with NESHAP. This code is not used for other routine dose calculations at SRS because it cannot handle certain site-specific factors. However, doses calculated by the CAP88 and MAXIGASP codes are in reasonably close agreement.
- ♦ Occasionally a nonroutine occurrence at SRS results in an atmospheric release of radioactivity over a relatively short period of time. For these releases, atmospheric transport models, available on the Weather Information and Display (WIND) System, are used to calculate offsite doses in real time. During 1991, there were no such occurrences at SRS.

INTRODUCTION

This chapter discusses radiation dose terminology and describes how offsite doses are calculated from releases of radioactive materials to the atmosphere and surface water.

Estimated doses for atmospheric and liquid releases from Savannah River Site (SRS) are presented in the Executive Summary, Chapter 7, "Air Pathways," and Chapter 8, "Water Pathways." In addition, doses

calculated from measured concentrations in milk, food, and wildlife are presented in Chapter 7 and Chapter 9, "Wildlife Monitoring."

RADIATION DOSE TERMINOLOGY: DEFINITIONS AND UNITS

In considering radiation exposures and possible consequences to exposed individuals, the term "radiation dose" is commonly used. This general term may refer to one of the more precisely defined quantities discussed below.

Internal and External Radiation Doses

An individual's radiation dose from an external source is received only while the individual is exposed to the source. However, in the case of an intake of radioactive materials into the body, the dose will continue even after the intake has ceased. Radioactive materials can be taken into the body by three primary modes:

- ingestion of the radioactive material in food or drinking water
- inhalation of airborne radioactive particulates or vapors
- absorption of the radionuclide through the skin

Following an intake, the radioactive material is distributed and retained within the body's organs according to each organ's metabolism of that particular element or compound. Therefore, after the intake of radioactive material ends, the organs will continue to absorb energy emitted by the retained radionuclides.

The dose rate to the organs will diminish over time because radioactive materials are removed by biological processes and by radioactive decay. Since some materials, such as tritium, are rapidly eliminated from the body, exposure to their emissions is brief. Similarly, some radionuclides have short half-lives (their radioactivity decreases rapidly), and the dose rate to the organs from those materials also diminishes rapidly.

Other radioactive materials, such as plutonium, are radiologically long-lived and firmly retained within the body. These types of radioactive sources may remain in the body and emit radiation for months or years. As a result, the dose to the organs continues to accumulate after the intake ceases. The continued irradiation and accumulation of dose to an organ depends on the type of intake and the radiological and biological properties of the radioactive material taken into the body.

Absorbed Dose and Dose Equivalent

The measure of radiation exposure to an organ or tissue is the absorbed dose, which is defined as the quantity of radiation energy absorbed by the organ divided by the organ's mass. The International System of Units (SI) unit for absorbed dose is the gray (Gy). An organ receives an absorbed dose of 1 Gy when it absorbs 1 joule of radiation energy per kilogram of its mass. The conventional unit of absorbed dose is the rad (100 rad = 1 Gy). Absorbed doses from facility releases are more commonly expressed using a smaller unit, the millirad (mrad), where 1 mrad = 0.001 rad.

Absorbed dose depends only on the radiation energy absorbed by the organ, not on the radiation type (alpha particles, beta particles, gamma rays, or neutrons). But for a given absorbed dose, the degree and kinds of biological effects that may occur as a result of the organ's irradiation depend on the radiation type. For this reason, absorbed dose is inadequate for predicting health effects associated with radiation exposure.

The dose equivalent to an organ exposed to a source of ionizing radiation is defined as the absorbed dose to the organ multiplied by a quality factor. This quality factor takes the radiation type into account. The International Commission on Radiological Protection (ICRP) has recommended specific quality factors for the radiation types of most concern in this report. The U.S. Department of Energy (DOE) has adopted these quality factors, which are listed below, in DOE Order 5400.5:

Gamma rays	1
Beta particles, other electrons	1
Alpha particles	20

The committed dose equivalent is the predicted total dose equivalent to a tissue or organ over a 50-year period after a known intake of a radionuclide into the body. Fifty years is the approximate residual life expectancy of a young adult. The 50-year time span tends to overestimate the life-time dose to older individuals but may, in some cases, underestimate radiation doses to young children.

The SI unit of dose equivalent and committed dose equivalent is the sievert (Sv). The conventional unit, used in this report, is the rem (100 rem = 1 Sv). However, for environmental levels of radioactivity, the smaller unit—millirem (mrem)—is more convenient. One millirem is one thousandth of a rem (1 mrem = 0.001 rem).

Effective Dose Equivalent and Committed Effective Dose Equivalent

The effective dose equivalent (EDE) combines the dose equivalents received by all organs of the body into a single weighted sum. The EDE is defined as the sum of all organ dose equivalents after each one has been multiplied by an appropriate weighting factor. The weighting factors, which were developed by the ICRP, express the fractional risk of a stochastic health effect associated with the dose equivalent to that organ. The ICRP weighting factors (W_T), which have been adopted by DOE in DOE Order 5400.5, are shown in Chart 6-1. The Environmental Protection Agency (EPA) has accepted these factors for calculation of

Chart 6-1
Hypothetical Calculation of Committed Effective Dose Equivalent

Organ or Tissue	ICRP Risk Weighting Factor (W_T) ^a	Committed Dose Equivalent (H_T), mrem	Committed Effective Dose Equivalent ($W_T \times H_T$), mrem
Gonads	0.25	0.4	0.10
Breast	0.15	0.5	0.075
Red marrow	0.12	0.6	0.072
Lung	0.12	0.8	0.096
Thyroid	0.03	1.2	0.036
Bone surfaces	0.03	4.3	0.13
Remainder			
Liver	0.06	0.6	0.036
Kidneys	0.06	0.5	0.030
Spleen	0.06	0.4	0.024
Pancreas	0.06	0.4	0.024
Adrenal	0.06	0.3	0.018
Committed EDE =			0.64 mrem

a Source: ICRP Publication 26.

EDE under the Clean Air Act (40 CFR 61, Subpart H) [EPA, 1989a].

The EDE combines the individual organ or tissue dose equivalents into a single risk-weighted sum. EDEs can be added to determine the total risk from exposure to several radionuclides. When external radiation sources, such as an airborne plume, expose the whole body uniformly, the external EDE is added to the EDE from internal exposures. If the external exposure is non-uniform, the organ and tissue doses are weighted individually, as shown in Chart 6-1.

The committed effective dose equivalent refers to the total EDE that will be accumulated over a 50-year period following an intake. The committed EDE is defined as the sum of all committed organ dose equivalents after each one has been multiplied by the appropriate weighting factor. The committed EDE refers to an individual's committed effective dose from a specified intake.

Chart 6-1 provides a sample calculation of the committed EDE, where the six specified organs or tissues and the five remaining organs or tissues receiving the highest dose are considered. The committed dose equivalent (H_T) to each organ or tissue is multiplied by the appropriate risk weighting factor (W_T). The sum of these products is the committed EDE. The calculation in Chart 6-1 is a hypothetical

example for simultaneous exposures to more than one radionuclide.

Collective Effective Dose Equivalent

The term collective dose refers to the sum of individual doses received by all members of a population. In this report, the EDE (average individual dose) is used to calculate the collective dose for the population within a 50-mile radius of a hypothetical release point centrally located within SRS.

The unit of collective EDE is the person-rem or person-sievert (person-Sv). For example, if each individual in the Central Savannah River Area (CSRA) population (555,100) receives an EDE of 1 mrem (0.01 mSv) each year, the annual collective EDE commitment to the population is calculated using the following method:

$$\begin{aligned}
 &555,100 \text{ persons} \\
 &\times 1 \text{ mrem} \\
 &\times 0.001 \text{ rem per mrem} \\
 &= 555.1 \text{ person-rem}
 \end{aligned}$$

Internal Dose Factors

Internal dose factors are used to calculate the committed dose equivalent to an organ and the committed effective dose equivalent to an individual. These factors are specific to the radionuclide and to the intake mode (inhalation or ingestion). Internal dose

factors express the 50-year committed dose that would result from the intake of a unit quantity of radioactivity, normally 1 picocurie (1 pCi). The units of the factors may be, for example, mrem/pCi. Chart 6-2 shows internal dose factors for several radionuclides in determining the committed EDE to an adult. Figure 6-1 shows a sample calculation using these factors.

The intake of a radionuclide by ingestion depends on the concentration of the radionuclide in foods and drinking water and on the individual's consumption patterns. The estimated intake of a radionuclide is multiplied by the appropriate ingestion dose factor to provide the estimate of committed EDE resulting from the intake.

The estimates of radiation doses presented in this report were calculated using the dose factors provided by DOE [DOE, 1988b]. These dose factors are based on ICRP 30 [ICRP, 1979], with modifications from ICRP 48 [ICRP, 1986] for plutonium and other related elements

In the following example, the average tritium oxide concentration measured at the site perimeter during 1991 was used to calculate the annual intake of tritium:

$$\begin{array}{l} \text{Concentration of} \quad \text{duration of exposure} \\ \text{tritium oxide in} \quad \text{(365 days per year)} \\ \text{air (pCi/m}^3\text{)} \end{array} \quad \begin{array}{l} \text{breathing rate during} \\ \text{exposure (m}^3\text{/day)} \end{array}$$

$$21 \times 22 \times 365 = 168,630$$

$$\begin{array}{l} \text{Annual intake of} \\ \text{tritium oxide by} \\ \text{inhalation (pCi)} \end{array}$$

The calculated intake is then converted to a committed effective dose equivalent using the appropriate ICRP internal dose factor from Chart 6-2:

$$\begin{array}{l} \text{Annual intake of} \quad \text{committed effective} \\ \text{tritium oxide by} \quad \text{dose equivalent from} \\ \text{inhalation (pCi)} \quad \text{tritium oxide (mrem)} \end{array}$$

$$168,630 \times 9.5 \times 10^{-8} = 0.016$$

$$\begin{array}{l} \text{internal dose} \\ \text{factor (mrem/pCi)} \end{array}$$

Figure 6-1 How SRS uses internal dose factors to calculate doses based on the intake of a radionuclide.

**Chart 6-2
Internal Dose Factors for an Adult**

Radionuclide	(mrem/pCi Intake) ^a	
	Inhalation	Ingestion
Tritium oxide	9.5E-08 ^b	6.3E-08
Strontium-90	1.3E-03	1.3E-04
Iodine-131	3.2E-05	5.3E-05
Cesium-137	3.2E-05	5.0E-05
Plutonium-239	5.1E-01	4.3E-03

a Source: DOE, 1988b.

b Includes allowance for skin absorption.

SRS dose calculations are based on dose conversion factors for adults. Although age-specific dose factors are available for 12 elements, including hydrogen,

carbon, strontium, iodine, cesium, and plutonium—in ICRP 56 [ICRP, 1989], these have not been adopted for DOE operations. The dose factors are being evaluated and, once accepted, will be incorporated into future reports.

SRS uses adult consumption rates for food and drinking water to estimate intakes of radionuclides for all members of the population. Intake rates for food and drinking water consumption appear in Tables 6-1 and 6-2. These intake values were developed specifically for SRS based on an updated survey [Hamby, 1991]. This report includes data on agricultural production, meat and milk production (Table 6-3), consumption rates for food products (Table 6-1), and use of the Savannah River for drinking water and recreational purposes (Table 6-2). Use of these survey data allows more site-specific environmental assessments for SRS operations.

Extended Intakes: Environmental Dose Commitment

When radioactive materials are released from a facility to the environment, only a small fraction reaches the public, and that fraction is delayed as it moves through the environment. Particulate radioactive materials released to the atmosphere are deposited on exposed surfaces, such as the ground and vegetative cover. Materials deposited on the ground can be a source of external exposure until they decay or are carried away by weathering processes. They also are a source of future exposure to people through the consumption of vegetative crops, which are exposed through their root

systems. Materials deposited directly on vegetation are available for human or animal consumption only during the time the crops are exposed. Thus, radioactive particulate materials deposited on the ground can be a source of future radiation exposure, limited by radioactive decay and weathering.

Most gaseous radioactive materials, like tritium, C-14 (as carbon dioxide), and nonreactive noble gases (Ar-41 and radioisotopes of krypton and xenon), have a relatively short residence time in the local environment and do not contribute much to exposure in future years. An exception to this is I-129, which is released as a reactive vapor and has a long radioactive half-life. It remains in the soil for many years. Thus, particulate radioactive materials and I-129 vapor may contribute to exposure in future years through internal and external exposure pathways. The magnitude of this future source of exposure can be evaluated by calculating the environmental dose commitment (EDC). At SRS, the EDC to the population is calculated for a period extending 100 years after the time of release of radioactive materials to the environment.

The radioactive materials released from SRS to the atmosphere that contribute to EDC typically are

released in very small quantities and are a minor contributor to the overall dose to the population.

APPLICABLE DOSE STANDARDS

DOE radiation standards for protection of the public in the SRS vicinity are specified in DOE Order 5400.5, Chapter 2, "Environmental Compliance." In addition to specifying limits for radiation exposures, this Order also sets forth an objective "that potential exposures to members of the public be as far below the limits as is reasonably achievable." This is better known as the as low as reasonably achievable (ALARA) process.

The standards in DOE Order 5400.5 are based on recommendations of the ICRP and the National Council on Radiation Protection and Measurements (NCRP), and also incorporate regulations promulgated by EPA. Chart 6-3 provides the dose standards and limits for atmospheric and liquid pathways referenced in this report.

EPA limits for the atmospheric pathways contained in 40 CFR Part 61, Subpart H [EPA, 1989a] also are included in DOE Order 5400.5.

Dose limits for drinking water consumed from DOE drinking water systems, community drinking water systems, and downriver water treatment plants are

Chart 6-3
Radiation Dose Limits for Exposure of the Public to Releases from DOE Facilities^a

Mode of Public Exposure	Effective Dose Equivalent	
	mrem/year	mSv/year
All effluents and pathways from routine DOE operations ^b	100	1
Airborne effluents ^c	10	0.1
Drinking water pathway ^d	4	0.04

- a All of the limits listed have been incorporated into DOE Order 5400.5, Feb. 8, 1990, "Radiation Protection of the Public and Environment."
- b "Routine DOE Operations" means normal planned operations and does not include nonroutine releases.
- c The standard for airborne effluents applies to the sum of the doses from all airborne pathways: inhalation, submersion in a plume, exposure to radionuclides deposited on the ground surface, and consumption of foods contaminated as a result of deposition (40 CFR 61, Subpart H).
- d The drinking water standard applies to public community drinking water systems and drinking water supplies operated by DOE or DOE contractors (40 CFR 141).

Chart 6-4
Offsite Dose Calculations for SRS Releases: Receptors and Assumptions

Description	Assumptions about Receptors
	Airborne Effluents ^a
Maximum Site Boundary	◆ Lives at site boundary where highest air concentrations occur. ◆ Maximum exposure and consumption rates of food produced at residence.
Average Site Boundary	◆ Lives at a location of average boundary air concentration^b. ◆ Average exposure and consumption rates.
Whole Population	◆ Actual distribution of population within 50 miles of center of SRS. ◆ Average exposure and consumption rates for all pathways.
	Waterborne Effluents ^a
Maximum Exposure Case #1	◆ Lives on shore of Savannah River. ◆ Average consumption rate of river water. ◆ Maximum consumption rate of fish.
Maximum Exposure Case #2	◆ Maximum consumption of water from downriver water treatment plants.
Average Exposure	◆ Average consumption of water from downriver water treatment plants.
Whole Population	◆ Average consumption of water from downriver water treatment plants. ◆ Average consumption of fish from Savannah River. ◆ River recreational activity exposure based on survey data.

a See Tables 6-1 and 6-2 for specific values of the maximum and average consumption rates for adults used in the calculations.

b Determined by averaging the predicted concentrations at 320 locations equidistantly spaced at the site perimeter.

consistent with the criteria in 40 CFR 141, "National Interim Primary Drinking Water Regulations" [EPA, 1975]. Under these regulations, persons consuming drinking water shall not receive an annual whole body dose (DOE Order 5400.5 interprets this as effective dose equivalent) of more than 4 mrem (0.04 mSv). This dose limit is based on a maximum consumption of 2 liters of water per day. The SRS dose estimates, which are based on this criterion, can be compared with the EPA dose standard.

SRS OFFSITE DOSE CALCULATIONS

In this report, offsite doses from SRS releases of radioactive materials (atmospheric and liquid) are calculated for the scenarios listed in Chart 6-4 for adults residing near SRS or at downriver locations.

Since DOE has adopted dose factors for adults only, SRS calculates collective doses as if the entire population consists of adults.

Collective doses are calculated for the population within a 50-mile (80-km) radius of SRS (555,100 persons). This collective dose is calculated by determining the dispersion of atmospheric releases (and subsequent individual doses) to each of 80 radial segments around SRS. These sectors are defined by 16 directions and five distances from SRS, up to 50 miles (80 km) from a hypothetical release point located near the center of SRS. The average individual EDE (in rem) in each radial segment is multiplied by the population in that segment to obtain the collective EDE (in person-rem) for that segment. The distribution of population with distance and direction around SRS is shown in Table 6-4.

Data from the 1990 census has not been used in this report because the breakdown of the CSRA population distribution has not yet been made available by the Census Bureau.

The collective EDE within the 50-mile radius is determined and reported in Chapter 7 and the Executive Summary of this report.

Collective doses are also calculated for the population served by the Cherokee Hill Water Treatment Plant at Port Wentworth, Ga., near Savannah, Ga. (15,000 persons), and the population served by the Beaufort-Jasper Water Treatment Plant near Beaufort, S.C. (50,000 persons). These collective doses are reported in Chapter 8 and the Executive Summary.

The individual and collective committed effective dose equivalents for SRS releases in 1991, calculated by the methods described in this chapter, are compared with doses from natural background and medical sources in the Executive Summary of this report. A discussion of radiation from natural, medical, and other sources is provided in Chapter 3, "Environmental Monitoring Perspectives, Objectives, Rationale."

Relative Effects of Different Chemical Forms of Tritium

The dosimetry and environmental behavior of tritium are discussed in this section. Tritium regularly accounts for a larger fraction of the offsite collective dose than all other radionuclides released from SRS (Chapter 3).

Atmospheric tritium (abbreviated as T) releases from SRS operations are primarily in two chemical forms: tritium oxide (water vapor-HTO and T₂O) and elemental tritium (gas-HT and T₂). Atmospheric tritium releases are identified by chemical form, and doses from each form are calculated separately for the following reasons:

- Human intake and metabolism for exposure to tritium in air differ greatly (by four orders of magnitude) for the oxide and the elemental forms.
- The oxide and elemental forms of tritium behave differently in the environment.

The different ways in which tritium is metabolized are considered in dose calculations. Tritium oxide is readily absorbed by the body when tritiated water vapor is inhaled or when tritium oxide is ingested with drinking water or food. To account for this efficient uptake of tritium oxide, the doses for tritium oxide are calculated from a mathematical model that assumes all of the ingested or inhaled tritium oxide is instantly

neously absorbed into the body fluids. A third mode of intake, absorption through the skin, also is important for tritium oxide. An individual exposed to airborne tritiated water vapor normally absorbs about half as much tritium through the skin as by inhalation [ICRP, 1979]. The EDE factor corresponding to intake by inhalation has been calculated to account for this uptake of tritium oxide through the skin. All dose factors for tritium oxide are based on the assumption that tritium oxide assimilated by the body is eliminated at the same rate as body water.

Elemental tritium is not assimilated efficiently by the human body. Of the elemental tritium gas inhaled, only about 0.004 percent is converted to the oxide form and retained as free water [NCRP, 1979]. The need for limiting exposure to elemental tritium in air is governed by the dose to the lung while the gas is in the airways.

DOSE CALCULATION MODELS

Most of the radioactive materials released from SRS are present in such low concentrations when dispersed in the environment that standard monitoring procedures cannot detect them. Therefore, radiation doses to offsite populations are calculated with mathematical models. Figure 6-2 shows how models can be used to calculate concentrations that are too small to measure. These models use known transport mechanisms for atmospheric and liquid releases and known major pathways of exposure to man.

Environmental measurements of tritium oxide released during routine operations are used to verify atmospheric dispersion in the transport models [Marter, 1984].

To calculate annual offsite doses, SRS uses radiation transport and dose models developed for the commercial nuclear industry [NRC, 1977]. The models are implemented at SRS in the following computer programs:

- MAXIGASP: calculates maximum and average doses to offsite individuals from atmospheric releases.
- POPGASP: calculates collective doses from atmospheric releases.
- LADTAPII: calculates both maximum and average doses to offsite individuals and the population from liquid releases.
- CAP88: calculates doses to offsite individuals from atmospheric releases to demonstrate compliance with the Clean Air Act.

MAXIGASP and POPGASP are SRL-combined versions of the Nuclear Regulatory Commission

Figure 6-2 Comparisons between mathematical models of radionuclide movement and actual measurements.

(NRC) computer programs called XOQDOQ (atmospheric transport) and GASPARG (exposure pathway). The modifications incorporate the input of required physical and biological data specific to SRS. The program also allows input for multiple release points. However, the radionuclide transport and dose calculations in the XOQDOQ and GASPARG programs were not modified. LADTAPII is an unmodified version of the NRC computer program of the same name. Details on these environmental models and computer programs are available in the following referenced documents [NRC, 1973; NRC, 1977, Eckerman et al., 1980; Simpson and McGill, 1980].

The CAP88 computer code is required under 40 CFR 61 to calculate offsite doses from atmospheric releases from existing and proposed facilities [EPA, 1989a]. Calculations with CAP88 are used to demonstrate compliance with the National Emission Standards for Hazardous Air Pollutants (NESHAP). SRS uses the CAP88 dose estimates to show NESHAP compliance, but not for routine dose calculations.

The major difference between the CAP88 and MAXIGASP dose calculation methodology is the handling of dose from tritium in foods. Both codes assume that the tritium concentration in food moisture approaches the tritium concentration in air moisture. The concentration of tritium in air moisture depends on the amount of tritium released to the atmosphere and the moisture content (absolute humidity) of the air. The resulting concentration of tritium in air moisture will be higher if the humidity is low. The CAP88 code uses a "built in" average absolute humidity of 8 g H₂O/m³ of air, whereas the MAXIGASP code allows input of a site-specific average absolute humidity of 11 g H₂O/m³ of air (as determined from weather records for SRS and

Augusta, Ga.). The use of the humidity value 8 g H₂O/m³ of air by CAP88 underestimates the actual humidity and thus overestimates dose from vegetative food crops. Since animals consume vegetative food crops, this also causes an overestimate of dose from consumption of meat and milk. The EPA has now approved the use of a site-specific average absolute humidity of 11 g H₂O/m³ of air, and this value was incorporated in the CAP88 computer code for calculating the offsite NESHAP dose from 1991 SRS operations.

The other factor that affects calculation of dose from tritium in foods is the degree of equilibrium reached between tritium concentration in food moisture and the tritium concentration in air moisture. The CAP88 code uses the assumption that the tritium concentration in food moisture will equal the tritium concentration in air moisture, which is 100 percent equilibrium. The MAXIGASP code uses the assumption that the tritium concentration in food moisture will be 50 percent of the tritium concentration in air moisture, or 50 percent equilibrium, which is the recommended value in NRC, 1977. In the SRS area, limited data indicate that the average tritium content of foods approaches, but does not reach, equilibrium with atmospheric moisture [Murphy, 1990]. In studies at SRS over the period 1974 to 1987, the annual average concentration of tritium in vegetation moisture was shown to vary from 50 percent to 250 percent of the annual average concentration of the atmospheric moisture. The average over the five-year period 1982 to 1986 was 73 percent. Thus, it appears that the CAP88 code may overestimate dose from tritium in foods, while MAXIGASP may underestimate the dose, with the true dose being somewhere in between.

Figure 6-3 Radioactive materials in the air enter the human body through pathways ranging from direct radiation to food consumption.

Both the CAP88 and the MAXIGASP codes use modeling based on NRC Regulatory Guide 1.109 [NRC, 1977]. Differences in the implementation of the Regulatory Guide tritium-in-food model in the codes are responsible for most of the differences in the calculated doses. Even with these differences, the doses calculated by the two computer codes are in reasonable agreement. This comparison is shown in Chapter 7. Additional studies are needed to determine the most appropriate degree of equilibrium between tritium concentration in food moisture and the tritium concentration in air moisture in the SRS area for use in both the computer codes.

Modeling the Dispersion of Atmospheric Radioactive Releases

Radioactive materials released to the atmosphere are mixed and dispersed within the air mass as they are carried by the prevailing wind. Airborne radionuclides can cause internal exposures to people by the inhalation pathway; airborne gamma-emitting radionuclides can cause external exposures to people by the immersion (direct radiation) pathway. Radionuclides gradually are removed from the air by radioactive decay and by physical processes that deposit them on the ground, where some radionuclides may continue to be sources of external radiation. The deposited radionuclides

subsequently move through various pathways to man. A simplified representation of the important atmospheric transport pathways is given in Figure 6-3.

Atmospheric transport models simulate airborne movement, radioactive decay, and radionuclide deposition to predict concentrations in the air near ground level and on the ground surface at specified downwind locations. These concentrations are used to estimate radiation doses to individuals at those locations. These concentrations also are used to predict deposition on food crops, pastures, and agricultural soil for some exposure pathways.

Meteorological Database

Dose estimates in this report incorporate atmospheric transport and deposition calculations based on meteorological measurements made over a five-year period (1982-1986). Comparisons of this database with other databases collected at SRS since 1966 show very little change in dispersion conditions in this time period. The meteorological measurements include all dispersion conditions observed over the five-year period, ranging from unstable (much turbulence, which leads to good dispersion) to very stable (very little turbulence, which produces a narrow plume exhibiting poor dispersion). The measurements, collected from the meteorological tower located near the center of

SRS in H Area, are presented in Table 6-6. The SRS meteorological data for 1982-1986, also in Table 6-6, indicate that this area experiences stable conditions (atmospheric stability classes E, F, G) about 26 percent of the time.

It is typical in this section of South Carolina that there is not one strongly prevailing wind direction. Figure 6-4 shows the percentage of time that the wind blows toward a sector. The percentage of time blowing toward each of the 16 sectors is less than 10 percent, with a slight prevalence of winds blowing toward the southwest. Figure 6-5 shows wind speed and direction for the period 1982-1986.

Meteorological data are used as input for the atmospheric transport models, which calculate the radionuclide concentration in air (χ), per unit release rate (Q), at prescribed ground-level positions near the point of release.

At SRS, the χ/Q s are calculated based on releases from five separate points. The input parameters for these points are shown in Table 6-5. The atmospheric transport model calculates the χ/Q at 320 locations along the site perimeter for each of the five release points. Data from these calculations are used to

determine the location of—and calculate the dose to—the maximally exposed offsite individual. These data also are used to calculate the average dose at the site perimeter.

These atmospheric transport models are based on methods widely used in the nuclear industry [NRC, 1973]. The versions used for assessing routine releases from SRS are implemented in the computer program XOQDOQ [Sagendorf and Goll, 1977]. Measured annual average concentrations of tritium oxide in the atmosphere and in other environmental media are compared with concentrations calculated with XOQDOQ [Marter, 1984]. Although this comparison is strictly valid only for the dispersion of water vapor and effluents that behave similarly, it also is indicative of the model's ability to estimate transport and diffusion of releases of other gases and particulate material. The comparisons of measured and predicted tritium concentrations in offsite air are published annually in this report (Chapter 7).

Dose Calculations for Atmospheric Releases

Effective dose equivalents to offsite individuals and the population from atmospheric releases of radioactivity are calculated by using the MAXIGASP and

Figure 6-4 Graph shows percentage of time wind blows toward each directional sector at SRS.

Windrose for SRS (1982-1986) Tower H-62

Figure 6-5 Wind speed and direction in the vicinity of SRS.

POPGASP programs. These programs use the following data to calculate doses:

- measured and calculated annual radioactivity releases (Chapter 7)
- population distribution
- production data for vegetables, crops, milk, and meat

Intakes of radioactivity by individuals and populations are based on population distribution and adult inhalation and consumption rates for food, air, and water. Tables 6-1, 6-2, and 6-7 provide the parameters used for these calculations.

Radioactive intakes by offsite populations are converted to committed dose with the DOE internal effective dose equivalent factors. These effective dose

equivalent factors provide estimates of a 50-year committed dose for intake of a unit quantity of radioactivity.

The term environmental dose commitment, as explained previously, refers to collective (population) dose calculated to account for the continued contribution of internal and external radiation dose to the population near SRS. This dose is calculated exclusively as the result of radioactivity in the environment due to SRS operations. The calculated collective doses in this report include an estimate of environmental dose commitment for a 100-year period following the release of radioactivity.

Occasionally, a nonroutine occurrence at SRS results in an atmospheric release of radioactivity over a relatively short period of time. For these releases, atmospheric transport models available on the Weather Information

Models of the dispersion of airborne radioactivity are usually of the **Gaussian puff** or **Gaussian plume** type.

Puff models generally represent releases of relatively short duration. Plume models are more appropriate for averaging a release over a longer period.

The models incorporate radioactive decay, and they usually account for wet and dry deposition processes that deplete the puff or plume over time and leave some of the radioactivity on the ground surface.

Both models account for the downwind movement and vertical and horizontal dispersion of the released radioactivity.

Figure 6-6 The primary SRL WIND System atmospheric transport model is a Gaussian Puff/Plume (PF/PL) model. The PF/PL model transports the release along a series of downwind straight-line segments determined from hourly averages.

and Display (WIND) System are used to calculate offsite doses in real time. The WIND System transport models use real-time observed meteorological data from the onsite meteorological network and forecast data from the National Weather Service to predict the transport of a radioactive puff or plume through the atmosphere. To calculate internal dose estimates, the models combine the DOE 50-year committed EDE factors based on ICRP 30 with the breathing rate of an active adult.

The primary WIND System atmospheric transport model is a Gaussian Puff/Plume (PF/PL) model (Figure 6-6) that assumes that the ambient concentrations of the material released form a Gaussian (normal) distribution about a centerline as the material is dispersed throughout the atmosphere. The PF/PL model transports the release along a series of downwind straight-line segments determined from hourly averaged observed and forecasted wind data.

Modeling the Dispersion and Transport of Liquid Radioactive Releases

Radioactive materials released to SRS streams flow to the Savannah River. Although many of the radionuclides are measurable at the point of release, most fall below minimum detectable concentrations after dilution with river water. Only tritium oxide and trace amounts of Sr-90 and Cs-137 are routinely detected in the river. Doses from these radionuclides are calculated from measured concentrations in river water and downriver drinking water. For those radionuclides which may be present at levels below minimum detectable concentrations, it is necessary to use a mathematical model to account for the offsite doses from measured SRS releases to the streams.

A simplified representation of the more important transport pathways of radioactive materials in surface water or groundwater is shown in Figure 6-7 [ICRP, 1965]. Radioactive materials released into streams are dispersed and diluted in the water, transported by the current, and deposited into sand and sediments on the bottom of the stream. The radioactive materials enter the aquatic food chain as they are taken up directly from the water or sediments by aquatic plants and animals. Radioactivity in drinking water taken from the streams exposes people directly. Stream water used for irrigation or for watering animals may introduce radionuclides into food crops and animal products that people ultimately consume.

Mathematical models of aquatic radionuclide transport quantify these pathways and estimate concentrations of radioactivity in food and drinking water by simulating

Figure 6-7 Radioactivity in streams, rivers, and groundwater can enter the human body through the various pathways and relationships shown above.

the movement of the released radioactivity through the water, its transfer to aquatic organisms, and its uptake by terrestrial crops and agricultural animals.

Doses from the irrigation water pathway are not included in dose summaries in this report based on a survey questionnaire completed by county farm agents in the SRS area regarding Savannah River use [Hamby, 1991]. This survey revealed no known use of river water for irrigation downriver from SRS. However, since irrigation along the river by a farming operation is possible, potential doses from this pathway also are calculated. Detailed results of these calculations are presented in Chapter 8.

Flow-Rate Data

The amount of dilution of radioactive materials in the Savannah River is dependent on the flow rate of the river. Annual average flow rates change from year to year, depending on the amount of rainfall in the watershed of the river and the quantity of water released by Thurmond Lake Dam.

The United States Geological Survey (USGS) makes continuous flow-rate measurements at a number of locations on the river. At river mile 120 (Highway 301 Bridge), the average measured flow rate in 1991 was 11,598 cubic feet/second, which is 4 percent lower than the average flow rate of 12,064 cubic feet/second in 1990. Monthly average flow rates in 1991 ranged from

a minimum of 6,334 cubic feet/second (October) to a maximum of 19,220 cubic feet/second (August).

Since daily and monthly flow rates fluctuate widely (i.e., short-term dilution varies from day to day and month to month), an "effective" flow rate is calculated and used in liquid dose model calculations. The effective annual flow rate is based on continuously measured releases of tritium and measured concentrations of tritium in river water and at downstream water treatment plants. The use of effective flow rates accounts for the effect of widely varying short-term flow rates and for additional dilution of river water with other non-river water sources at the downstream water treatment plants.

Dose Calculations for Liquid Releases

Calculation of offsite individual and collective

committed effective doses from liquid releases of radioactivity at SRS are provided by the LADTAPII program. The LADTAPII program uses the following data to calculate doses [Hamby, 1991]:

- annual measured and calculated releases of radioactivity to the river
- average river flow rates
- population data
- sports and commercial fish-harvests data
- community water consumption data
- recreational use of the river data

The data used in these calculations, as well as human consumption rates for water and fish, are shown in Tables 6-2 and 6-7.

Table 6-1
Adult Intake and Usage Parameters for Atmospheric Dose Calculations^a

Pathway	Average Individual	Maximum Individual	Population
Fruits, vegetables, and grains (kg/yr)	163	276	163
Leafy vegetables (kg/yr)	21	43	21
Milk (L/yr)	120	230	120
Meat (beef) (kg/yr)	43	81	43
Inhalation (m ³ /yr)	8,000	8,000	8,000
Fraction of dose received after taking structural shielding into account	0.7	0.7	0.5

^a Values developed by SRL for the Savannah River Site [Hamby, 1991]

Table 6-2
Adult Intake and Usage Parameters for Liquid Dose Calculations^a

Pathway	Average Individual	Maximum Individual	Population
Water consumption (L/yr)		370	370
Fish consumption (kg/yr)		19	9
Marine invertebrates (kg/yr)		8	2
Boating ^b		21	1,100,000
Swimming ^b		8.9	160,000
Shoreline recreation ^b		23	960,000
Water Treatment Plants^c			
Water consumption (L/yr)	370	730	370

^a Values developed by SRL for the Savannah River Site [Hamby, 1991].

^b Maximum individual values are in units of hours/year; population values are in units of person-hours.

^c Dose is calculated for the average individual, maximum individual, and population through the drinking water pathway from the downstream public water supplies at Beaufort-Jasper and Port Wentworth.

Table 6-3
50-Mile-Radius (80 km) Milk, Meat, and Vegetation Production Around SRS

Site Annual Milk Production (L)

Dir (miles)	0.0-5.	5.-10.	10.-20.	20.-30.	30.-40.	40.-50.	Total
N	0.0	0.0	4.200E+04	6.900E+04	1.000E+06	5.300E+06	6.411E+06
NNE	0.0	0.0	4.200E+04	6.900E+04	2.100E+05	5.000E+05	8.210E+05
NE	0.0	0.0	3.200E+04	1.000E+06	2.700E+06	2.000E+06	5.732E+06
ENE	0.0	0.0	2.500E+04	1.200E+06	4.400E+06	5.200E+06	1.083E+07
E	0.0	0.0	2.500E+04	1.400E+06	3.900E+06	4.900E+06	1.023E+07
ESE	0.0	0.0	2.500E+04	5.600E+05	3.000E+04	4.900E+05	1.105E+06
SE	0.0	0.0	2.500E+04	0.000E+00	0.000E+00	0.000E+00	2.500E+03
SSE	0.0	0.0	4.800E+05	8.600E+05	1.200E+06	1.200E+06	3.740E+06
S	0.0	0.0	1.000E+06	2.100E+06	3.000E+06	3.500E+06	9.600E+06
SSW	0.0	0.0	9.900E+05	3.800E+06	7.400E+06	7.600E+06	1.979E+07
SW	0.0	0.0	9.900E+05	2.200E+06	5.800E+06	4.800E+06	1.379E+07
WSW	0.0	0.0	9.900E+05	1.700E+06	2.400E+06	3.500E+06	8.590E+06
W	0.0	0.0	6.700E+05	1.300E+06	2.200E+06	3.600E+06	7.770E+06
WNW	0.0	0.0	2.300E+05	1.100E+06	1.200E+06	2.000E+06	4.530E+06
NW	0.0	0.0	4.200E+04	3.800E+05	1.400E+06	1.000E+06	2.822E+06
NNW	0.0	0.0	4.200E+04	6.900E+04	1.700E+06	3.400E+06	5.211E+06
TOTAL	0.0	0.0	5.628E+06	1.781E+07	3.854E+07	4.899E+07	1.110E+08

Site Annual Meat Production (kg)

Dir (miles)	0.0-5.	5.-10.	10.-20.	20.-30.	30.-40.	40.-50.	Total
N	0.0	0.0	5.300E+04	8.800E+04	2.500E+05	9.800E+05	1.371E+06
NNE	0.0	0.0	5.300E+04	8.800E+04	2.000E+05	4.100E+05	7.510E+05
NE	0.0	0.0	7.100E+04	1.700E+05	3.500E+05	4.500E+05	1.041E+06
ENE	0.0	0.0	8.300E+04	2.000E+05	4.600E+05	5.700E+05	1.313E+06
E	0.0	0.0	8.300E+04	1.900E+05	3.400E+05	5.100E+05	1.123E+06
ESE	0.0	0.0	8.300E+04	1.900E+05	2.200E+05	2.500E+05	7.430E+05
SE	0.0	0.0	1.200E+05	2.100E+05	2.600E+05	3.000E+05	8.900E+05
SSE	0.0	0.0	1.100E+05	1.900E+05	2.600E+05	2.900E+05	8.500E+05
S	0.0	0.0	9.400E+04	1.500E+05	2.000E+05	2.700E+05	7.140E+05
SSW	0.0	0.0	9.500E+04	1.800E+05	2.900E+05	3.900E+05	9.550E+05
SW	0.0	0.0	9.500E+04	1.700E+05	2.700E+05	3.200E+05	8.550E+05
WSW	0.0	0.0	9.500E+04	1.600E+05	2.300E+05	4.000E+05	8.850E+05
W	0.0	0.0	5.800E+04	1.000E+05	2.100E+05	4.100E+05	7.780E+05
WNW	0.0	0.0	4.800E+04	6.200E+04	1.300E+05	2.900E+05	5.300E+05
NW	0.0	0.0	5.300E+04	8.000E+04	2.800E+05	2.700E+05	6.830E+05
NNW	0.0	0.0	5.300E+04	8.800E+04	3.300E+05	6.200E+05	1.091E+06
TOTAL	0.0	0.0	1.247E+06	2.316E+06	4.280E+06	6.730E+06	1.457E+07

Table 6-3
50-Mile-Radius (80 km) Milk, Meat, and Vegetation Production Around SRS,
Cont'd.

Site Annual Vegetation Production (kg)

Dir (miles)	0.0-5.	5.-10.	10.-20.	20.-30.	30.-40.	40.-50.	Total
N	0.0	0.0	3.600E+05	6.000E+05	8.400E+05	8.700E+05	2.670E+06
NNE	0.0	0.0	3.600E+05	6.000E+05	5.100E+05	6.300E+03	1.476E+06
NE	0.0	0.0	3.600E+05	6.900E+05	1.000E+06	5.000E+05	2.550E+06
ENE	0.0	0.0	3.600E+05	6.600E+05	1.200E+06	1.500E+06	3.270E+06
E	0.0	0.0	3.600E+05	5.900E+05	8.500E+05	1.400E+06	3.200E+06
ESE	0.0	0.0	3.600E+05	2.200E+06	1.900E+06	1.100E+06	5.560E+06
SE	0.0	0.0	2.500E+06	4.500E+06	3.000E+06	1.100E+06	1.110E+07
SSE	0.0	0.0	1.700E+06	2.900E+06	3.600E+06	1.100E+06	9.300E+06
S	0.0	0.0	7.200E+04	5.400E+05	8.400E+05	9.700E+05	2.422E+06
SSW	0.0	0.0	3.500E+02	1.200E+05	2.500E+05	1.100E+05	4.804E+05
SW	0.0	0.0	3.500E+02	7.800E+02	2.200E+03	3.100E+05	3.133E+05
WSW	0.0	0.0	3.500E+02	5.800E+02	9.900E+02	2.900E+03	4.820E+03
W	0.0	0.0	4.500E+04	2.300E+04	1.700E+04	5.200E+04	1.370E+05
WNW	0.0	0.0	2.600E+05	3.800E+04	4.500E+05	1.100E+06	1.848E+06
NW	0.0	0.0	3.600E+05	4.300E+05	8.400E+05	1.100E+06	2.730E+06
NNW	0.0	0.0	3.600E+05	6.000E+05	8.400E+05	1.100E+06	2.900E+06
TOTAL	0.0	0.0	7.458E+06	1.449E+07	1.614E+07	1.232E+07	5.041E+07

Table 6-4
50-Mile-Radius (80 km) Population Distribution Around SRS

Dir (miles)	0.0–5.	5.–10.	10.–20.	20.–30.	30.–40.	40.–50.	Total
N	0.0	2.000E+00	3.710E+03	8.271E+03	4.849E+03	1.262E+04	2.945E+04
NNE	0.0	1.000E+00	6.900E+02	1.516E+03	3.811E+03	9.080E+03	1.510E+04
NE	0.0	0.000E+00	4.372E+03	2.792E+03	4.795E+03	9.303E+03	2.126E+04
ENE	0.0	2.000E+00	1.135E+03	5.779E+03	5.108E+03	4.009E+04	5.212E+04
E	0.0	1.000E+00	7.548E+03	6.346E+03	7.832E+03	4.802E+03	2.653E+04
ESE	0.0	3.500E+01	1.666E+03	1.946E+03	2.368E+03	2.455E+03	8.469E+03
SE	0.0	4.300E+01	6.490E+02	5.704E+03	5.736E+03	7.555E+03	1.969E+04
SSE	0.0	4.200E+01	4.130E+02	1.070E+03	1.069E+03	3.294E+03	5.888E+03
S	0.0	6.000E+00	4.940E+02	1.341E+03	6.692E+03	3.377E+03	1.191E+04
SSW	0.0	0.000E+00	1.064E+03	2.145E+03	6.139E+03	2.917E+03	1.227E+04
SW	0.0	0.000E+00	9.280E+02	1.851E+03	2.037E+03	2.734E+03	7.550E+03
WSW	0.0	0.000E+00	8.680E+02	7.283E+03	1.481E+03	7.775E+03	1.741E+04
W	0.0	6.000E+01	6.430E+02	7.720E+03	2.539E+03	7.116E+03	1.808E+04
WNW	0.0	2.800E+02	2.201E+03	1.035E+05	3.447E+04	9.114E+03	1.495E+05
NW	0.0	1.050E+02	5.596E+03	8.813E+04	1.477E+04	1.578E+03	1.102E+05
NNW	0.0	3.010E+02	9.582E+03	2.691E+04	6.324E+03	6.644E+03	4.976E+04
TOTAL	0.0	8.770E+02	4.156E+04	2.723E+05	1.100E+05	1.305E+05	5.552E+05

Non-extrapolated 1980 census data. Detailed 1990 data was not yet available.

Table 6-5
Input Parameters for Atmospheric Transport Model

Release Locations for 1991 Maximum and Average Individuals

	Release Source Area				Diffuse and Fugitive
	F,H,P,K,C	M	D	SRL	
Release height (m)	61	0	16	31	0
Release location (site coord.)					
East	58000	50041	20938	51863	58000
North	62000	104828	65284	106670	62000

Note: Operating period for maximum individual and average individual taken as 74 years, i.e., two times actual operating period.

Note: Operating period for population dose taken to be 201 years, i.e., 100-year environmental dose commitment.

Table 6-6
Meteorological Data for 1982-1986

USNRC Computer Code-XOQDOQ, Version 2.0 Run Data: 87.072 (SRL 6/29/83 VERSION)
 38193 Wind Stats H-Area 60 minute 62M 82-86 Stability from Sigma A
 Release Height = 200 ft (61 m)

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class A
Extremely Unstable Conditions

(M/S)																	
UMAX	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
2.00	0.372	0.317	0.356	0.372	0.361	0.249	0.275	0.275	0.296	0.306	0.351	0.374	0.382	0.388	0.335	0.291	5.299
4.00	0.450	0.589	0.751	0.783	0.728	0.573	0.482	0.495	0.521	0.636	0.780	1.008	0.825	0.683	0.466	0.382	10.154
6.00	0.105	0.094	0.126	0.181	0.128	0.136	0.071	0.099	0.110	0.162	0.217	0.241	0.249	0.160	0.134	0.097	2.309
8.00	0.008	0.010	0.003	0.008	0.008	0.003	0.008	0.016	0.013	0.008	0.026	0.010	0.029	0.013	0.018	0.016	0.196
12.00	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.005	0.003	0.010	0.003	0.000	0.005	0.005	0.000	0.003	0.034
14.10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.003	0.003	0.003	0.000	0.000	0.008
TOTAL	0.93	1.01	1.24	1.34	1.23	0.96	0.84	0.89	0.94	1.12	1.38	1.64	1.49	1.25	0.95	0.79	18.00

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class B
Moderately Unstable Conditions

(M/S)																	
UMAX	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
2.00	0.055	0.071	0.065	0.094	0.055	0.055	0.058	0.050	0.058	0.097	0.073	0.092	0.094	0.081	0.079	0.073	1.149
4.00	0.178	0.291	0.390	0.450	0.312	0.272	0.230	0.199	0.325	0.278	0.414	0.602	0.419	0.330	0.189	0.141	5.019
6.00	0.115	0.162	0.330	0.278	0.152	0.128	0.102	0.073	0.170	0.217	0.278	0.422	0.377	0.233	0.110	0.086	3.234
8.00	0.016	0.000	0.018	0.010	0.003	0.010	0.010	0.010	0.024	0.026	0.047	0.034	0.097	0.084	0.071	0.016	0.477
12.00	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.008	0.000	0.003	0.013	0.013	0.008	0.010	0.055
14.10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
TOTAL	0.36	0.52	0.80	0.83	0.52	0.47	0.40	0.33	0.58	0.63	0.81	1.15	1.00	0.74	0.46	0.23	9.93

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class C
Slightly Unstable Conditions

(M/S)																	
UMAX	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
2.00	0.073	0.076	0.113	0.162	0.065	0.050	0.052	0.055	0.063	0.102	0.126	0.123	0.115	0.144	0.071	0.063	1.453
4.00	0.285	0.539	0.817	0.791	0.479	0.374	0.319	0.356	0.429	0.474	0.597	0.681	0.566	0.458	0.319	0.202	7.687
6.00	0.173	0.471	0.966	0.542	0.306	0.241	0.225	0.223	0.388	0.537	0.490	0.649	0.566	0.424	0.244	0.144	6.588
8.00	0.050	0.079	0.207	0.052	0.037	0.031	0.037	0.034	0.079	0.170	0.157	0.204	0.319	0.275	0.084	0.092	1.906
12.00	0.003	0.003	0.005	0.003	0.000	0.000	0.008	0.010	0.016	0.016	0.018	0.081	0.110	0.126	0.024	0.021	0.442
TOTAL	0.58	1.17	2.11	1.55	0.89	0.70	0.64	0.68	0.97	1.30	1.39	1.74	1.68	1.43	0.74	0.52	18.08

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class D
Neutral Conditions

(M/S)																	
UMAX	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
2.00	0.068	0.071	0.086	0.063	0.060	0.045	0.031	0.063	0.079	0.089	0.079	0.102	0.183	0.102	0.060	0.047	1.228
4.00	0.380	0.631	1.136	0.940	0.717	0.600	0.513	0.683	0.712	0.717	0.728	0.723	0.751	0.626	0.361	0.322	10.541
6.00	0.304	0.741	1.351	0.785	0.547	0.505	0.644	0.869	0.945	0.859	0.780	0.861	0.961	1.089	0.442	0.244	11.929
8.00	0.110	0.178	0.278	0.123	0.050	0.139	0.186	0.249	0.317	0.270	0.207	0.267	0.432	0.364	0.152	0.065	3.385
12.00	0.031	0.031	0.042	0.000	0.005	0.013	0.058	0.050	0.029	0.050	0.071	0.115	0.202	0.165	0.034	0.013	0.909
14.10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.003	0.000	0.000	0.003	0.003	0.000	0.000	0.008
TOTAL	0.89	1.65	2.89	1.91	1.38	1.30	1.43	1.91	2.08	1.99	1.86	2.07	2.53	2.35	1.05	0.69	28.00

Table 6-6
Meteorological Data for 1982-1986, Cont'd.

USNRC Computer Code— XOQDOQ, Version 2.0 Run Data: 87.072 (SRL 6/29/83 VERSION)
 38193 Wind Stats H-Area 60 minute 62M 82-86 Stability from Sigma A
 Release Height = 200 ft (61 m)

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class E
Slightly Stable Conditions

(M/S)	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
UMAX																	
2.00	0.031	0.026	0.050	0.037	0.021	0.037	0.042	0.068	0.047	0.047	0.050	0.050	0.063	0.050	0.042	0.050	0.710
4.00	0.262	0.333	0.503	0.469	0.442	0.437	0.495	0.634	0.529	0.442	0.463	0.372	0.461	0.327	0.304	0.191	6.664
6.00	0.372	0.655	1.089	0.851	0.702	0.552	0.833	1.066	1.060	0.940	1.050	0.827	0.751	0.702	0.385	0.223	12.057
8.00	0.029	0.052	0.058	0.063	0.071	0.055	0.029	0.060	0.141	0.120	0.123	0.152	0.081	0.039	0.018	0.018	1.110
12.00	0.000	0.000	0.000	0.000	0.000	0.005	0.000	0.000	0.000	0.003	0.000	0.000	0.000	0.000	0.000	0.000	0.008
14.10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
TOTAL	0.69	1.07	1.70	1.42	1.24	1.09	1.40	1.83	1.78	1.55	1.69	1.40	1.36	1.12	0.75	0.48	20.55

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class F
Moderately Stable Conditions

(M/S)	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
UMAX																	
2.00	0.003	0.008	0.008	0.000	0.003	0.003	0.005	0.042	0.013	0.024	0.010	0.005	0.005	0.003	0.010	0.013	0.154
4.00	0.037	0.063	0.084	0.052	0.050	0.089	0.071	0.126	0.086	0.097	0.073	0.052	0.034	0.045	0.016	0.045	1.019
6.00	0.194	0.372	0.374	0.317	0.204	0.173	0.144	0.293	0.275	0.259	0.301	0.275	0.131	0.063	0.063	0.071	3.508
8.00	0.005	0.037	0.042	0.063	0.058	0.037	0.016	0.031	0.055	0.037	0.034	0.042	0.024	0.008	0.000	0.003	0.490
12.00	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
14.10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
TOTAL	0.24	0.48	0.51	0.43	0.31	0.30	0.24	0.49	0.43	0.42	0.42	0.37	0.19	0.12	0.09	0.13	5.17

Joint Frequency Distribution of Wind Speed and Direction:

Atmospheric Stability Class G
Very Stable Conditions

(M/S)	N	NNE	NE	ENE	E	ESE	SE	SSE	S	SSW	SW	WSW	W	WNW	NW	NNW	TOTAL
UMAX																	
2.00	0.000	0.005	0.016	0.000	0.003	0.010	0.000	0.005	0.013	0.005	0.005	0.005	0.000	0.000	0.000	0.005	0.073
4.00	0.008	0.000	0.003	0.000	0.003	0.003	0.003	0.000	0.005	0.000	0.000	0.003	0.003	0.000	0.000	0.003	0.031
6.00	0.000	0.034	0.029	0.008	0.008	0.005	0.008	0.013	0.003	0.008	0.010	0.005	0.005	0.000	0.000	0.000	0.136
8.00	0.000	0.003	0.003	0.005	0.003	0.003	0.000	0.003	0.000	0.000	0.005	0.003	0.000	0.000	0.000	0.000	0.026
12.00	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
14.10	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
TOTAL	0.01	0.04	0.05	0.01	0.02	0.02	0.01	0.02	0.02	0.01	0.02	0.02	0.01	0.00	0.00	0.001	0.27

Table 6-7
Site Parameters Used in Liquid Dose Calculations

River flow rate at SRS for 1991 (cfs)	11,852 ft. ³ /sec.
River dilution in estuary	3
Transit time from process areas to river (hr)	24
Transit time from SRS to water treatment plants (hr)	72
Water treatment time (hr)	24
Edible aquatic food harvest (kg/yr)	
Fish – sport	35,000 ^a
Fish – commercial	2,700 ^a
Invertebrates – saltwater	390,000 ^a
Irrigation ^a	None ^a
Shore width factor	0.2
Fish bioaccumulation factor for cesium	3,000

^a Values developed by SRL for the Savannah River Site [Hamby, 1991]

To Learn About:	Turn to page:
♦ Radiological Air Monitoring	126
♦ Nonradiological Air Monitoring	132
♦ Rainwater	133
♦ Soil	135
♦ Penetrating Radiation	136
♦ Vegetation	138
♦ Food Products	140

Compiled by Jason H. Chappell,
G. Tim Jannik, and George A. Taylor
Environmental Protection Department

Air Pathways

1991 HIGHLIGHTS

- ♦ Approximately 200,000 Ci of tritium were released from SRS to the atmosphere, compared to approximately 253,000 Ci released in 1990. The average tritium concentration measured at the site perimeter was $2.1\text{E-}11$ $\mu\text{Ci/mL}$. The average tritium concentration at the 100-mile-radius station was $8.5\text{E-}12$ $\mu\text{Ci/mL}$. In the last five years, the largest quantity of tritium released to the atmosphere was 595,000 Ci in 1987.
- ♦ For 1991 radioactive atmospheric releases, the EDE to the average individual at the site perimeter was 0.056 mrem; the EDE to the maximally exposed person was 0.12 mrem. The major pathways contributing to these doses were from inhalation and vegetation.
- ♦ This was the first year that SRS included an estimate of radionuclide releases from unmonitored diffuse and fugitive sources. These unmonitored sources can include ponds, contaminated land areas, and structures without ventilation or with ventilation that does not result in a well-defined release point. As a result of this assessment, six particulate radionuclides were added to the list of radionuclides released to air from SRS operations. The dose to an offsite individual from those six radionuclides was <0.0001 percent of the total dose from all radionuclides, indicating that diffuse and fugitive sources were unimportant contributors to offsite dose. Diffuse and fugitive sources contributed 0.02 percent to the total tritium source term.
- ♦ Penetrating radiation levels are continuously measured with 462 TLDs at and within an 8,000-square-mile area of SRS. During 1991, the maximum onsite measurement was 480 mrem/year around the SWDF, where radioactive waste is buried. Offsite measurements made in 1991 were comparable to those made in previous years. The maximum measurements at site perimeter and 25- and 100-mile radius stations were 146 mrem/year, 79 mrem/year, and 96 mrem/year, respectively. Penetrating radiation levels averaged 78 mrem/year in Georgia and 76 mrem/year in South Carolina.

INTRODUCTION

In the Savannah River Site (SRS) region, airborne radionuclides originate from natural sources (terrestrial or cosmic), worldwide fallout, and atmospheric emissions from SRS and the neighboring Vogtle Electric Generating Plant.

The site maintains an extensive network of air monitoring stations to determine the concentrations of radioac-

tive particulates and gases in the air. In addition, rainwater, soil, vegetation, and food products, which are all part of the airborne radioactivity pathway to humans, are routinely sampled and analyzed for radioactivity (Chapter 6, "Calculating Radiation Doses").

Penetrating radiation exposures, which occur from sources such as cosmic radiation, naturally occurring terrestrial radionuclides, worldwide fallout, and SRS

facilities and operations are extensively monitored using thermoluminescent dosimeters (TLDs).

In addition to ambient radiological conditions, radioactive and nonradioactive airborne emissions originating at SRS facilities are monitored (by a combination of direct measurement, sample extraction and measurement, or process knowledge) at their points of discharge.

Air monitoring verifies that all emissions, ambient concentrations, and radiation doses are within applicable regulatory standards. It also provides verification that emission estimates and dose calculation models are proper and conservative.

RADIOLOGICAL AIR MONITORING

1991 Effluent Releases to the Atmosphere

Description of Effluent Monitoring Program

Each process-area discharge stack that releases (or has the potential to release) radioactive materials is continuously checked by applicable on-line sampling and/or monitoring systems. Most air effluent particulate samples are collected weekly and analyzed for environmental release calculations. Tritium is monitored with continuous "real time" instrumentation to determine instantaneous and cumulative releases.

Applicable Regulations

U.S. Department of Energy (DOE) Order 5400.1, "General Environmental Protection Program," requires that effluent monitoring be conducted at all DOE sites.

Effluent Monitoring Results

Data obtained from monitored air effluent release points are used in conjunction with calculated release estimates of unmonitored radionuclides (C-14 and Kr-85) in order to quantify the total amount of radioactive material released to the environment. 1991 was the first year that SRS has included an estimate of radionuclide releases from unmonitored diffuse and fugitive sources. These unmonitored sources include ponds, contaminated land areas, and structures without ventilation or with ventilation that does not result in a well-defined release point. The specific sources and methods used to estimate these emissions are described in *Calculated Release Levels from Phase III Installations* [Blunt, 1992]. As a result of this unmonitored-sources assessment, six particulate radionuclides were added to the list of radionuclides released to air from

SRS operations. The dose to an offsite individual from these six radionuclides was less than 0.0001 percent of the the total dose from all radionuclides.

The total SRS atmospheric releases for 1991 are shown by source in Table 7-1, following the text of this chapter.

Calculated Radionuclide Concentrations in Air

Average concentrations of radionuclides in air at the site boundary are calculated from the atmospheric release quantities. Calculation is required because the concentration of SRS-released radionuclides (except tritium) at the site boundary cannot be detected above background concentration levels. These calculations are performed using computer codes, which employ standard meteorological dispersion equations and site meteorology (Chapter 6). MAXIGASP is the name of the computer code used to calculate concentrations of radionuclides and radiation doses from airborne releases at SRS.

Applicable Regulations

Concentration guides for radionuclides in air, called Derived Concentration Guides (DCGs), are given in DOE Order 5400.5. These guides, based on recommendations in the International Commission on Radiological Protection (ICRP) Publications 26 and 30 [ICRP, 1977 and ICRP, 1979], are used as reference concentrations for conducting environmental protection programs and for making dose estimates.

The DCGs are defined as the air concentration of a radionuclide that will give a 50-year committed effective dose equivalent (EDE) of 100 mrem under conditions of continuous exposure for one year.

Calculated Concentrations

Chart 7-1 shows atmospheric releases and the MAXIGASP-computer-code-calculated concentrations of radionuclides in air at the site perimeter.

Average annual radionuclide concentrations are compared to DCGs to determine if effluent treatment systems are effective. Included in Chart 7-1 is a comparison of the DCGs to the calculated site boundary concentration of radionuclides released from SRS in 1991.

Since tritium was the only monitored radionuclide of SRS origin routinely detected in offsite air, measured tritium concentrations were used to confirm the calculated concentrations of other radionuclides at the site perimeter.

The average tritium oxide concentration measured at the site perimeter monitoring stations, $2.1\text{E-}11$ $\mu\text{Ci/mL}$, is about 50 percent of the $4.2\text{E-}11$ $\mu\text{Ci/mL}$ value calculated using MAXIGASP and the $4.3\text{E-}11$ $\mu\text{Ci/mL}$ calculated with the CAP88 (40 CFR 61, Subpart H) computer code. The calculated concentrations for 1991 were a conservative estimate of the offsite effects from onsite releases of radioactive materials. The maximum concentration of tritium measured at the site boundary was $3.8\text{E-}11$ $\mu\text{Ci/mL}$. This is 46 percent lower than the $7.1\text{E-}11$ $\mu\text{Ci/mL}$ value calculated using MAXIGASP, and 38 percent lower than the $6.1\text{E-}11$ $\mu\text{Ci/mL}$ calculated with the CAP88 code.

Calculated Offsite Radiation Doses from Atmospheric Releases

During 1991, offsite EDEs from SRS atmospheric releases were calculated for individuals living at the site perimeter and for the population within 50 miles (80 km) of the center of the site. Computer codes implemented models for the various pathways of exposure in calculating radiation doses. Chapter 6 contains the descriptions of these models and codes. The calculated individual and collective doses from 1991 atmospheric releases are presented in Tables 7-2 through 7-7.

Applicable Regulations

DOE Order 5400.5, "Radiation Protection of the Public and Environment," includes the dose limit from 40 CFR 61, Subpart H [National Emission Standards for Hazardous Air Pollutants (NESHAP)] for airborne radionuclides [EPA, 1989a]. The standard states that air emissions of radionuclides from normal operations at DOE facilities shall not result in an EDE greater than 10 mrem/year to any member of the public.

Maximum Individual EDE

Table 7-2 presents the calculated EDE by pathway and by radionuclide to a hypothetical individual located at the site perimeter, which is considered the point of maximum offsite exposure. The MAXIGASP computer code was used to calculate this EDE. The parameters used for the calculations and a description of EDE are provided in Chapter 6.

In 1991, using an assumed average dietary intake, the EDE to the maximally exposed individual was 0.093 mrem (0.00093 mSv). If maximum intake of all types of food (cow milk, meat, and vegetables) was assumed, the EDE was calculated to be 0.12 mrem (0.0012 mSv), or 1.2 percent of the DOE Order 5400.5 standard of 10 mrem/year (Chart 7-2).

During 1991, in response to public concerns, additional calculations of the maximum individual EDE were performed substituting a goat milk pathway for the normal cow milk pathway. The results of these calculations are given in Table 7-3. The maximum EDE using the maximum-consumption goat milk pathway was 0.14 mrem (0.0014 mSv), which is 15 percent higher than the cow milk pathway EDE.

Average Individual EDE

Table 7-4 shows the calculated EDE to the average individual at the site perimeter by pathway and radionuclide. The parameters used for the calculations are provided in Chapter 6. These EDEs, based on 1991 atmospheric releases, were calculated for persons with normal living habits residing at 320 locations equidistantly spaced along the site perimeter. These EDEs were then averaged over the 320 locations to give the values shown in the table. MAXIGASP was the computer code used for these calculations.

In 1991, the major pathways contributing to average individual doses from atmospheric releases were from inhalation (61 percent) and consumption of vegetation (27 percent). An EDE of 0.056 mrem (0.00056 mSv) was calculated for the average individual at the site perimeter assuming average dietary intake and inhalation.

Collective EDE

Doses were also calculated using the POPGASP computer code for the population residing within 50 miles (80 km) of the center of SRS. The calculated collective EDEs are shown in Table 7-5. In 1991, the collective EDE was estimated to be 7.10 person-rem (0.071 person-Sv). This dose is less than 1 percent of the collective EDE received from natural sources of radiation (approximately 195,000 person-rem). Refer to Chapter 6 for a description of collective EDE.

NESHAP Compliance

To demonstrate compliance with NESHAP (Clean Air Act, 40 CFR 61, Subpart H) regulations, maximum individual and collective EDEs were calculated using the CAP88 computer code and are presented in Tables 7-6 and 7-7, respectively. The maximum EDE calculated with CAP88 was 0.22 mrem, which is 2.2 percent of the 10 mrem/yr NESHAP standard as shown in Chart 7-2. The CAP88 collective EDE was estimated to be 21 person-rem (0.21 person-Sv).

A side-by-side comparison of the maximum individual EDEs calculated using CAP88 and MAXIGASP is shown in Table 7-6. Additionally, a side-by-side com-

Chart 7-1
1991 Atmospheric Releases, Calculated Concentrations at Site Boundary, and Derived Concentration Guides

Radionuclide	Ci Released at Emission Source	(μCi/mL)	
		Calculated Average Concentrations at Site Perimeter	Derived Concentration Guides ^a
GASES AND VAPORS			
H-3 (oxide)	1.37E+05	4.21E-11	1E-07
H-3 (elemental)	6.29E+04	1.93E-11	2E-02
H-3 Total	2.00E+05	6.14E-11	1E-07
C-14	6.20E-01	1.89E-15	6E-09
Kr-85	1.04E+04	3.18E-12	3E-06
I-129	1.01E-02	2.80E-18	7E-11
I-131	2.98E-05	3.25E-20	4E-10
I-133	7.92E-05	8.49E-20	2E-09
PARTICULATES			
Cr-51	5.52E-07	2.71E-22	6E-08
Co-60	3.48E-06	1.57E-21	8E-11
Zn-65	1.46E-16	7.19E-32	6E-10
Sr-89,90 ^b	3.97E-03	1.54E-18	9E-12
Zr-95	1.11E-07	5.46E-23	9E-10
Nb-95	1.55E-15	7.62E-31	3E-09
Ru-106	4.44E-04	1.23E-19	3E-11
Sb-125	8.54E-08	2.36E-23	1E-09
Cs-134	6.68E-06	1.91E-21	2E-10
Cs-137	3.32E-04	9.87E-20	4E-10
Ce-144	1.03E-06	3.66E-22	3E-11
Pm-147	5.35E-15	2.64E-30	3E-10
Eu-154	3.44E-13	1.69E-28	5E-11
Eu-155	7.46E-14	3.68E-29	3E-10
U-235,238	2.69E-03	8.87E-19	1E-13
Pu-238	2.64E-04	7.32E-20	3E-14
Pu-239 ^c	4.71E-04	1.82E-19	2E-14
Am-241,243	1.51E-04	4.18E-20	2E-14
Cm-242,244	4.25E-05	1.18E-20	4E-14

^a Source: DOE Order 5400.5. In cases where different chemical forms have different DCGs, the lowest DCG for the radionuclide is given. These DCGs are defined as the air concentration of that radionuclide that will give a 50-year committed dose of 100 mrem under conditions of continuous exposure for one year.

^b Includes unidentified beta-gamma.

^c Includes unidentified alpha.

Chart 7-2
Calculated Maximum Individual Dose Commitment from SRS Atmospheric Releases in 1991

Maximum Individual EDE	Standard	Percent of Standard
Calculated EDE Using MAXIGASP		
0.12 mrem	10 mrem ^a	1.2
Calculated EDE Using CAP88 (NESHAP)		
0.22 mrem	10 mrem ^b	2.2
^a DOE: DOE Order 5400.5, Feb. 8, 1990. ^b EPA: (NESHAP) 40 CFR 61 Subpart H, Dec. 15, 1989.		

parison of the collective EDEs calculated using CAP88 and POPGASP is given in Table 7-7. As can be seen from these tables, the CAP88 code estimates a higher dose from tritium, via the food pathway, than do the MAXIGASP and POPGASP codes. This is because CAP88 assumes a 100 percent equilibrium between tritium concentrations in air and tritium concentrations in vegetation. MAXIGASP and POPGASP assume a 50 percent equilibrium between the two concentrations. Refer to Chapter 6 for a complete explanation of the differences in these dose modeling computer codes.

Measured Radionuclide Concentrations in Air

Description of Monitoring Program

Concentrations of radioactive materials in the air were monitored at five monitoring stations on the site, 14 monitoring stations at the site perimeter, and 12 monitoring stations at distances of approximately 25 miles from the center of the site (called 25-mile-radius stations). The Burial Ground North onsite location, out of service and not sampled in 1990 because of power supply problems, was placed back into service in 1991. The monitoring stations at the site perimeter and the 25-mile-radius stations are strategically located to permit continuous sampling within each approximate 30° sector around SRS.

The locations of the monitoring stations were selected to optimize the probability of detecting any routine or nonroutine release of airborne radioactivity from SRS regardless of wind direction. Air monitoring station locations are shown in Figure 7-1.

Additional air monitoring stations are located in Savannah and Macon, Ga., and in Columbia and Greenville, S.C. (100-mile-radius stations). These stations serve as reference points for background radioactivity concentrations from natural sources and worldwide fallout.

At all monitoring stations, airborne radioactive materials are measured by drawing air samples through the appropriate air media—filter paper, charcoal cartridges, and silica gel. Filter papers and charcoal cartridges are collected and replaced weekly; the silica gel, which is used to analyze for tritium in atmospheric moisture, is also changed every week. The collection media are then analyzed for radionuclide content. A complete discussion of sample collection and analytical procedures is found in Chapter 4, "Sample Collection, Analytical Procedures, and Data Interpretation."

Radioactive noble gases I-129 and C-14 are not routinely monitored at air monitoring stations because of sampling and analysis complexity. However, calculated maximum doses from these radionuclides are relatively small.

Applicable Standards

DOE Order 5400.1, "General Environmental Protection Program," requires that environmental surveillance be conducted at all DOE sites in order to monitor the effects, if any, of DOE activities on the surrounding environment.

Monitoring Results

Radioactivity in environmental air monitoring results are presented in Tables 7-8 and 7-9. Tritium was the

Figure 7-1 Location of air monitoring stations within 25 miles of SRS. Also, four stations are positioned approximately 100 miles from the site.

only radionuclide of site origin that had offsite concentrations in air that could be routinely detected above background (control) concentrations. The annual average concentrations of all measurable particulate radioactivity and tritium were only small percentages of the DCGs for air.

Gross Alpha and Nonvolatile Beta

Because they provide no specific radionuclide information, total gross alpha and nonvolatile beta measurements are used only for screening purposes. However, they do provide trending information and give an indication if radionuclide-specific measurements are needed.

In 1991, small amounts of particulate alpha and beta-gamma radioactivity were released to the atmosphere from SRS operations, primarily from F- and H-Area facilities (Table 7-1). However, because of atmospheric dispersion, these small radioactive releases generally were not detectable at the site perimeter above background contributions from worldwide fallout and natural radioactivity.

During 1991, average gross alpha and nonvolatile beta concentrations measured in onsite air were similar to the average concentrations measured in offsite air. The average alpha and beta concentrations in air for the years 1989, 1990, and 1991 are shown in Chart 7-3. Also given in Chart 7-3 is a comparison of the average beta-concentrations-in-air data for the years 1989 and 1990 from the Environmental Protection Agency (EPA) monitoring stations at Columbia and Barnwell, S.C. [EPA, 1989, 1990]. As can be seen from the chart, the EPA-measured data for average beta concentrations in air was lower than the SRS-measured concentrations in 1989, but higher at the Columbus station in 1990. However, overall analytical results are close.

Average gross alpha concentrations in air for all monitored locations in 1991 were approximately twice the 1989 and 1990 concentrations. A similar trend was seen in the average gross alpha deposition from rainwater (Chart 7-8). This increase was independent of SRS activities (alpha radioactivity releases from SRS were lower in 1991 than in previous years). An explanation for this increase is not known at this time.

The maximum onsite gross alpha activity, $1.1\text{E-}14$ $\mu\text{Ci/mL}$, was measured in a sample from A Area. The

Chart 7-3
Average 1989, 1990, and 1991 Gross Alpha and Nonvolatile Beta Measured in Air

Locations	No. of Locations	Average Gross Alpha ($\mu\text{Ci}/\text{ml}$)			Average Nonvolatile Beta ($\mu\text{Ci}/\text{ml}$)		
		1989	1990	1991	1989	1990	1991
Onsite	(5)	1.4E-15	1.3E-15	2.5E-15	1.8E-14	1.8E-14	1.8E-14
Site Perimeter	(14)	1.1E-15	1.1E-15	2.6E-15	1.7E-14	1.8E-14	1.8E-14
25-mile radius	(12)	1.1E-15	1.0E-15	2.5E-15	1.7E-14	1.8E-14	1.8E-14
100-mile radius	(4)	1.6E-15	1.3E-15	2.6E-15	1.7E-14	1.9E-14	1.8E-14
Columbia ^a	(1)	N/A	N/A	N/A	1.4E-14	2.4E-14 ^b	^c
Barnwell ^a	(1)	N/A	N/A	N/A	0.9E-14	1.9E-14 ^b	^c

a Measured by the U.S. Environmental Protection Agency (EPA).

b 1990 data are for the first nine months

c 1991 data were not available

N/A - Not analyzed by EPA

maximum nonvolatile beta activity, 4.7E-14 $\mu\text{Ci}/\text{mL}$, was detected in an air sample from H Area.

Plutonium and Strontium

Plutonium and strontium are released in small amounts from SRS, primarily from facilities in the separations areas (Table 7-1). Concentrations of Pu-238, Pu-239, and Sr-89,90 measured at the site perimeter were similar to those measured at the 100-mile radius stations (Table 7-8).

Slightly higher concentrations of Pu-238 and Pu-239 were measured at the onsite monitoring stations, near the points of discharge, than at the offsite stations. There were no significant differences in the onsite and offsite Sr-89,90 concentrations.

The maximum Pu-239 concentration measured onsite was $(2.02 \pm 0.24)\text{E-16 } \mu\text{Ci}/\text{mL}$ at the Burial Ground North monitoring station. The maximum onsite concentration of Pu-238 was $(4.20 \pm 0.18)\text{E-16 } \mu\text{Ci}/\text{mL}$, which was measured at the F-Area monitoring station.

Gamma-Emitting Radionuclides

During 1991, only naturally occurring radionuclides, such as Be-7 and K-40, were detectable in the ambient air. In past years, Cs-137 had been detected in onsite samples; however, none was detected in 1991. All other man-made gamma-emitting radionuclides were also

below detection limits. Refer to Chapter 4 for a description of the analytical lower limits of detection.

Tritium

Because tritium is a form of hydrogen, and hydrogen (H) is an integral part of water (H_2O), SRS monitors for tritium in atmospheric moisture. The 1991 measured concentrations of tritium in atmospheric moisture are shown in Table 7-9. The average measured concentration of tritium in air was determined by multiplying the measured tritium concentration in atmospheric moisture by a generic SRS absolute humidity value of 11 g water/ m^3 air. Use of this generic value was required because the specific humidity at each monitoring location was not monitored, nor was the weight of the captured atmospheric moisture determined. Improvements in the quantification of atmospheric moisture will be made by the Environmental Monitoring Section (EMS) in 1992.

The average measured tritium concentrations in air for the years 1987 through 1991 are shown in Chart 7-4. Also shown in Chart 7-4 are the total atmospheric tritium releases from SRS for the same years. As can be seen, there is nearly a direct correlation between the quantity of tritium released and the measured concentration of tritium in air at all monitoring locations.

The average tritium concentration in air at the site perimeter in 1991 was $2.1\text{E-11 } \mu\text{Ci}/\text{mL}$. This value compared favorably with the MAXIGASP and CAP88

Chart 7-4
1987-1991 SRS Atmospheric Tritium Releases and Average Measured Tritium Concentrations in Air

Year	Total Atmospheric Tritium Released (Ci)	Average Measured Tritium Concentrations in Air			
		Onsite (5 sites) ($\mu\text{Ci/mL}$)	Site Perimeter (14 sites) ($\mu\text{Ci/mL}$)	25-mile (12 sites) ($\mu\text{Ci/mL}$)	100-mile (4 sites) ($\mu\text{Ci/mL}$)
1987	595,000	10.00E-10	8.10E-11	2.50E-11	9.90E-12
1988	462,000	8.40E-10	5.40E-11	1.70E-11	12.00E-12
1989	309,000	6.40E-10	3.70E-11	1.40E-11	9.00E-12
1990	253,000	4.30E-10	3.20E-11	1.20E-11	8.80E-12
1991	200,000	2.50E-10	2.10E-11	1.10E-11	8.50E-12

computer code calculated values of 4.2E-11 $\mu\text{Ci/mL}$ and 4.3E-11 $\mu\text{Ci/mL}$, respectively. The maximum tritium concentration in air at the site perimeter was 3.8E-11 $\mu\text{Ci/mL}$, which occurred at the D-Area location. This value also compared favorably with the MAXIGASP and CAP88 computer code calculated values for the maximum site perimeter concentration of 7.1E-11 $\mu\text{Ci/mL}$ and 6.1E-11 $\mu\text{Ci/mL}$, respectively.

NONRADIOLOGICAL AIR MONITORING

1991 Nonradioactive Effluent Releases to the Atmosphere

Major nonradiological emissions of concern from stacks at SRS facilities include sulfur dioxide (SO_2), carbon monoxide (CO), oxides of nitrogen (NO_x), and total particulate matter less than 10 microns (PM_{10}). Stacks that have such emissions at SRS include both powerhouse stacks and process stacks.

Three coal-fired power plants located at SRS burned a total of 201,007 tons of coal in 1991. This is lower than the 242,731 tons of coal burned in 1990. The four D-Area boilers use pulverized coal; all other boilers are stoker fed. The D-Area boilers also burn waste oil. The location, number of boilers, and capacity of each boiler for these plants are listed in Chart 7-5.

Six additional onsite process stacks also release nonradioactive materials, including SO_2 , NO_x , and PM_{10} . The coal-fired power plants at K Area and P Area are no longer in operation.

Description of Monitoring Program

Each power plant stack is monitored for nonradioactive emissions. Six process stacks also are monitored, in-

cluding four stacks in M Area and one each in F and H areas.

Compliance with the SO_2 emissions standard at power plants is determined by the analysis of coal to be burned. The determination of expected SO_2 emissions is made using results of analyses of the coal for sulfur, carbon, ash, water, and BTU output.

The day-to-day control of PM_{10} is maintained with opacity meters in all SRS powerhouse stacks. Air compliance tests also are used to determine compliance with standards for PM_{10} and NO_x . These air compliance tests are performed every two years for each boiler by air emissions specialists under contract to SRS.

Applicable Standards

Permits issued by the South Carolina Department of Health and Environmental Control (SCDHEC) regulate nonradioactive emissions from SRS stacks. Specific permits for operating facilities are listed in Appendix A.

SCDHEC air emissions standards are listed in Chart 7-6. All SRS process stacks, including three M-Area

Chart 7-5
SRS Power Plant Boiler Capacities

Location	No. of Boilers	Capacity (BTU/hr)
A Area	2	7.17E+07
D Area	4	3.96E+08
H Area	3	7.17E+07

stacks and the 291-F stack, are subject to the 40 percent opacity limit.

Monitoring Results

Chart 7-7 shows the 1991 atmospheric emissions of SO₂, NO_x, CO, and PM₁₀ from power plants at SRS, all of which were within applicable SCDHEC standards.

These emissions numbers are based upon the area coal usage. SO₂ is calculated using the average sulfur content of the coal, and assumes 100 percent liberation of sulfur and 100 percent conversion to SO₂. Particulates, NO_x, and CO are based upon the multipliers provided in the EPA Pollutant Emission Factors AP-42 for Industrial Boilers.

The sulfur content of coal burned at SRS in 1991 averaged 1.2 percent for pulverizer coal and 0.9 percent for stoker coal, which are both less than the 2 percent SCDHEC standard.

The site received one Notice of Violation (NOV) for exceeding the authorized opacity limit for a permitted diesel engine in K Area.

Ambient Air Quality

After reassessing the need for nonradiological onsite ambient air monitoring, SRS terminated operation of the five ambient air quality monitoring stations in 1991. See Chapter 4 for the reason behind this decision.

The states of South Carolina and Georgia continue to monitor ambient air quality near SRS as part of the network associated with the Clean Air Act.

RAINWATER

Description of Monitoring Program

Rainwater monitoring is performed because rainwater deposition of radionuclides from atmospheric releases

**Chart 7-7
Nonradiological Air Emissions for 1991**

A-Area Bollers	
Sulfur dioxide	325 tons
Particulates	547 tons
NO _x	135 tons
Carbon monoxide	49 tons
H-Area Bollers	
Sulfur dioxide	325 tons
Particulates	542 tons
NO _x	127 tons
Carbon monoxide	45 tons
D-Area Bollers	
Sulfur dioxide	3924 tons
Particulates	692 tons
NO _x	1226 tons
Carbon monoxide	49 tons

may be a source of dose to persons, through the grass-to-cow-to-milk-to-person pathway. For this reason, SRS maintains a network of rainwater sampling stations to measure deposition from worldwide fallout and emissions from the site. The rainwater monitoring program consists of only radiological analyses.

Rainwater collection pans are located on top of each air monitoring station. The locations of these stations are shown in Figure 7-1. The majority of the rainwater samples collected are not analyzed, because they are collected for post-accident analysis only.

Monthly samples are analyzed from the H-Area onsite station, the Darkhorse and Barnwell Gate site perimeter stations, and at the Olar, S.C., 25-mile-radius station. The H-Area location was chosen for analysis because it is centrally located on SRS. The Barnwell Gate, Dark Horse, and Olar locations were chosen because they are located in an east-by-southeast direction from SRS, which is the direction most major weather patterns follow in the SRS area. Quarterly samples are collected and analyzed from the four 100-mile-radius control site stations (at Columbia and Greenville, S.C.; and Macon and Savannah, Ga.).

In general, rainwater samples are analyzed for gross alpha, nonvolatile beta, gamma-emitting radionuclides, Pu-238, Pu-239, tritium, and strontium.

**Chart 7-6
Nonradiological Air Emissions Standards^a**

Sulfur dioxide	3.5 lb/10 ⁶ BTU
Total suspended particulates	0.6 lb/10 ⁶ BTU
Opacity ^a	40%

^a Applicable for process stacks in existence prior to Jan. 1, 1986, and power house stacks built before Feb. 11, 1971, when this standard became effective. The standard is 20 percent for stacks on line after these dates.

For a complete description of the sampling and analytical procedures used for rainwater, refer to Chapter 4.

Monitoring Results

Rainwater depositions for 100-mile-radius locations are difficult to compare with the other locations monitored because of differences in sampling frequency. Samples at the 100-mile-radius locations are collected quarterly, whereas samples are collected monthly from onsite, site perimeter, and 25-mile-radius locations.

Because the ion column remains at the 100-mile-radius monitoring stations for a longer period of time, more activity collects on the ion column and is thus measured in the sample. Sampling frequency is not accounted for in the deposition calculation. Therefore, levels of radioactivity are higher at the 100-mile-radius locations compared to the onsite, site perimeter, and 25-mile-radius locations. Table 7-10 presents the rainwater deposition results for 1991. Table 7-11 presents the tritium measured in rainwater.

Gross Alpha and Nonvolatile Beta

Gross alpha and nonvolatile beta analyses are used to screen for radioactivity; however, these analyses provide no information on specific radionuclides which

may be present in the sample. In 1991, the maximum gross alpha depositions onsite, at the site perimeter, and at 25-mile-radius stations ranged from 19 ± 6.2 pCi/m² to 58 ± 7.7 pCi/m². The maximum nonvolatile beta depositions at the same locations ranged from 210 ± 11 pCi/m² to 540 ± 19 pCi/m². The maximum nonvolatile beta deposition was measured in a sample from the 25-mile radius location at Olar.

The average deposition for gross alpha and nonvolatile beta in rainwater for the years 1989, 1990, and 1991 is shown in Chart 7-8. Also shown are the nonvolatile beta data for 1989 and the first three quarters of 1990 for the EPA rainwater monitoring location in Columbia. These data were obtained from EPA's National Air and Radiation Environmental Laboratory Quarterly Reports 58 through 63 [EPA, 1989,1990,1991]. EPA monitors for nonvolatile beta in rainwater on a monthly basis, which provides a better control than the quarterly 100-mile-radius samples.

Gamma-Emitting Radionuclides

No man-made, gamma-emitting radionuclides were detected in the rainwater samples from any of the monitoring locations. Be-7 (a naturally occurring radionuclide) was detected in samples from each location. Pb-214, which also is a naturally occurring radionu-

Two-foot-by-two-foot rainwater collection pans are installed on top of each air monitoring station.

Chart 7-8
Average 1989, 1990, and 1991 Gross Alpha and Nonvolatile Beta in Rainwater Deposition

Locations	No. of Locations	Average Gross Alpha Deposition (pCi/m ²)			Average Beta Deposition (pCi/m ²)		
		1989	1990	1991	1989	1990	1991
H Area	1	6	6	10	150	78	158
Site perimeter	2	8	4	7	150	88	138
25-mile radius	1	7	3	3	150	74	132
100-mile radius ^a	4	32	5	12	350	152	351
EPA Environmental Data Station—Columbia	1	N/A	N/A	N/A	127	111 ^b	b

^a Deposition period is three months for the 100-mile-radius locations; for all other locations it is one month.

^b 1990 data are for the first nine months; 1991 data were not available.

clide, was detected in four samples from offsite locations, but not in any of the samples from H Area. The results for naturally occurring radionuclides are not presented in Table 7-10.

Tritium

During 1991, only samples from the 100-mile locations and the Darkhorse site perimeter location were analyzed for tritium.

The maximum concentration of tritium in rainwater at Darkhorse was $(4.3 \pm 0.1) \times 10^{-6}$ $\mu\text{Ci/mL}$. The maximum concentration at the Columbia 100-mile radius location was $(5.2 \pm 1.1) \times 10^{-7}$ $\mu\text{Ci/mL}$. The higher tritium levels in rainwater at the site perimeter are attributed to the atmospheric tritium releases from SRS.

Strontium

The maximum measured deposition of Sr-89,90 in rainwater was 7.2 ± 3.3 pCi/m², measured at the onsite H-Area location. Most of the other measurements of Sr-89,90 in rainwater were less-than-detectable (i.e., the measurement estimate was negative, or less than the uncertainty). Some deposition samples were also specifically analyzed for Sr-90. All these results were less than detectable.

Plutonium

The maximum measured deposition of Pu-238 was 1.1 ± 0.2 pCi/m², which occurred at the onsite H-Area location. The maximum measured deposition of Pu-239 was 1.5 ± 0.2 pCi/m², which also occurred at H Area. These measured depositions reflect the rainout of plutonium atmospheric releases from the Separations

Area. The measurements of Pu-238 and Pu-239 at the other locations were less than detectable, with the exception of the maximum Pu-239 measurement at Greenville, S.C., which was 0.17 ± 0.06 pCi/m².

SOIL

Description of Monitoring Program

Soil samples from uncultivated areas can provide a measure of the quantity of suspended or re-suspended radioactivity deposited from the atmosphere. Samples are collected annually from F, H, S, and Z areas and around the site perimeter. Two control locations (Clinton, S.C., and Savannah) approximately 100 miles from SRS also are sampled.

The concentrations of radionuclides in soil vary significantly among locations because of differences in rainfall patterns and in the mechanics of radionuclide retention and transport in different types of soil. Rates of migration in soil also vary significantly from one radionuclide to another. For example, strontium tends to migrate through soil more freely than cesium or plutonium.

Local concentrations of radionuclides in soils often are spatially nonuniform. The chemical separation of radionuclides in soil samples in the laboratory is complicated by the nonhomogeneity of the soil and by the difficulty in stripping ions from the soil. Therefore, individual measurements of radionuclides in soil samples may not be representative of large areas. An average concentration of multiple samples from a defined area provides a better measure of soil radionuclide concentrations.

Monitoring Results

Measurements of radionuclides in soil for 1991 are presented in Table 7-12.

Strontium

Maximum concentrations of Sr-90 in soil at the site perimeter and the 100-mile radius locations were 0.037 ± 0.016 pCi/g and 0.032 ± 0.015 pCi/g, respectively. The Sr-90 concentrations measured in soils at the site perimeter and offsite were similar to concentrations observed over the last several years and resulted primarily from worldwide fallout from nuclear weapons tests.

Higher concentrations of Sr-90 were measured onsite in H and F areas, reflecting releases from the Separations Area. The maximum detectable concentrations measured were 0.044 ± 0.002 pCi/g in H Area and 0.088 ± 0.017 pCi/g in F Area.

Cesium-137

Cesium-137 was detected at all locations sampled. Detectable Cs-137 concentrations onsite ranged from a minimum of 0.098 ± 0.021 pCi/g around Z Area to a maximum of 1.84 ± 0.07 pCi/g around H Area. Maximum concentrations of Cs-137 at the site perimeter and at the 100-mile-radius locations were 0.98 ± 0.05 pCi/g and 0.64 ± 0.05 pCi/g, respectively. Concentrations of Cs-137 from onsite and offsite locations were similar to concentrations observed in previous years.

Plutonium

In 1991, concentrations of Pu-239 around F and H areas were somewhat greater than those detected at S and Z areas and at the site perimeter, reflecting releases from the Separations Area.

Atmospheric plutonium releases from the Separations Area from 1955 through 1991 total 0.7 Ci Pu-238 and 3 Ci Pu-239.

The majority of these releases occurred in earlier years of SRS operation. Releases for 1991 were 0.264 mCi of Pu-238 and 0.325 mCi of Pu-239. Concentrations of Pu-238 and Pu-239 measured in soil at the SRS boundary and at the 100-mile radius sampling locations during 1991 ranged from near the lower limit of detection of 0.0008 pCi/g to 0.033 pCi/g.

PENETRATING RADIATION

TLDs have been used at SRS since 1965 for monitoring penetrating radiation (X-rays, gamma rays, energetic

beta particles, and neutrons). The inside back cover of this report illustrates some properties of the different types of radiation.

Description of Monitoring Program

Penetrating radiation levels at and around SRS are continuously measured at 462 locations with TLDs. The TLDs also provide a quick and reliable method to determine radiation doses to population groups within an 8,000-square-mile area of SRS in the event of an unplanned release of radioactivity.

The TLD monitoring stations are located onsite, at the site perimeter, at 25- and 100-mile radii, and in South Carolina and Georgia cities and towns within a 50-mile radius of the site. The breakdown is as follows:

- Onsite, 134 TLD stations
- Site perimeter, 184 TLD stations
- 25-mile radius, 12 TLD stations
- 100-mile radius, eight TLD stations
- South Carolina cities and towns, 80 TLD stations
- Georgia cities and towns, 44 TLD stations

In the South Carolina and Georgia cities and towns, half the TLDs are inside buildings, with the other half located outside the buildings. The TLDs at the remaining locations are outdoors. Two TLDs are placed at each indoor location, and five TLDs are placed at each outdoor location. The TLDs placed indoors provide an indication of the external dose equivalent received by individuals inside shielding structures.

Every three months, the TLDs are collected for analysis and replaced. Control sets of TLDs also accompany the field TLDs to evaluate systematic and transport uncertainties. Monitoring locations are shown in Figure 7-2. More information on TLD collection and analytical procedures is found in Chapter 4.

Monitoring Results

Chart 7-9 compares offsite 1991 TLD results with offsite TLD results for 1990. Summaries of all TLD data are presented in Tables 7-13 through 7-17.

Penetrating radiation fields vary significantly from one location to another because of differences in the terrestrial and cosmic components of natural background radiation. For example, varying concentrations of the decay products of radium and thorium in the soil result in different measured radiation levels. In Augusta, Ga., the EPA estimates an average

Figure 7-2 TLD measurements provide a quick and reliable method for determining penetrating radiation doses to the population within an 8,000-square-mile area of SRS.

outdoor dose equivalent of 84 mrem per year from cosmic and terrestrial radiation [Oakley, 1972].

In 1991, dose measurements outdoors in Georgia cities and towns averaged 78 mrem/yr, while measurements in South Carolina cities and towns averaged 76 mrem/yr. At the 100-mile radius stations, the average dose measurement was 71 mrem/yr.

Onsite measurements were taken at fences around the various SRS operating facilities. Some onsite radiation levels were above offsite background levels, including the Solid Waste Disposal Facility (SWDF), H Area, and Central Shops. During 1991, the maximum penetrating radiation level was 480 mrem/yr, measured near the SWDF, an area where radioactive waste is buried. Direct gamma radiation from waste shipments or other waste storage activities cause higher penetrating radiation levels.

Measurements at other onsite facilities and around the site perimeter were similar to those levels determined by EPA.

Expansion of Monitoring Network

The installation and testing of 12 site perimeter continuous monitoring stations continued in 1991. These stations, in addition to the existing TLD and air monitoring stations, will supplement the site's emergency response capability by continuously measuring and periodically reporting penetrating radiation levels from each 30° sector around SRS. The radiation monitors are capable of detecting exposure rates from 10 μ R/hr to 1 R/hr.

The monitors are housed in temperature-controlled buildings. Each monitoring station is currently transmitting data at least once a day through a U.S. Geological Survey (USGS) satellite telemetry system. Should an emergency occur, the monitors will transmit data at 5- to 10-minute intervals. In 1991, EMS completed testing on new equipment that will improve the reliability, sensitivity, and accuracy of the measurements. The ability of the monitors to withstand varying environmental conditions will also improve with the new equipment. When the project is complete, the data from the monitors will be transferred to the WIND

TLDs have been used at SRS since 1965 for monitoring penetrating radiation levels.

(Weather INformation and Display) system and integrated into the emergency response system.

VEGETATION

Description of Monitoring Program

Radioactive contamination of growing plants may result from transfer of radioactive materials from the soil or from radioactivity deposited on the surface of the plant from the atmosphere.

Vegetation samples are collected at onsite, site perimeter, 25-mile-radius, and 100-mile-radius locations. Onsite samples are collected around seepage and retention basins, inside and around the SWDF, around the Defense Waste Processing Facility (DWPF) in S Area, and around the Saltstone Facility in Z Area.

Grass is analyzed routinely for radioactivity; Bermuda grass is preferred because of its importance as a pasture grass for dairy herds and its year-round availability. Grass also provides an indication of fallout due to exposure of the grass blades' relatively large surface area in the environment.

Monitoring Results

Measurements of radioactivity in vegetation, based on dry weight, are presented in Table 7-18.

Gross Alpha and Nonvolatile Beta

The maximum gross alpha activity detected in onsite vegetation was 5.71 ± 1.90 pCi/g in a vegetation sample from Z Area. The maximum gross alpha activity detected from an offsite vegetation sample was 1.5 ± 0.66 pCi/g taken in Macon, Ga.

Maximum nonvolatile beta activities ranged from 11.7 ± 1.9 pCi/g to 87.9 ± 4.1 pCi/g onsite; 10.4 ± 1.3 pCi/g to 47.9 ± 2.8 pCi/g at the site perimeter; 12.3 ± 1.4 pCi/g to 47.5 ± 2.7 pCi/g at the 25-mile-radius locations; and 14.0 ± 1.6 pCi/g to 42.2 ± 2.2 pCi/g at the 100-mile-radius locations. Variations in worldwide fallout patterns and in concentrations of naturally occurring radionuclides in the soil contribute to differences in nonvolatile beta concentrations in vegetation.

Gamma-Emitting Radionuclides

Concentrations of Cs-137 were detected in composited vegetation samples from F, S, and Z areas, the site perimeter locations, the 25-mile radius locations, and the

Chart 7-9
Comparison of 1990 and 1991 TLD Environmental Penetrating Radiation Measurements^a

Locations	No. of Locations	Max (mrem/yr)		Min (mrem/yr)		Avg (mrem/yr)	
		1991	1990	1991	1990	1991	1990
Site perimeter	184	146±26	104±19	21±4	21±4	42±11	45±11
25-mile radius	12	79±14	61±11	28±5	29±5	52±14	52±15
100-mile radius	8	96±17	95±17	35±6	37±7	71±21	69±19
South Carolina							
Inside buildings	40	161±29	163±29	23±4	25±5	80±30	83±31
Outside buildings	40	128±23	132±24	8±2	34±6	76±18	79±19
Georgia							
Inside buildings	22	159±29	224±40	36±7	37±7	86±25	91±31
Outside buildings	22	179±32	142±26	35±6	36±7	78±23	77±21

^a Maximums and minimums were determined by selecting the highest and lowest dose equivalent from a particular location (e.g., site perimeter). Average measurements were calculated from the average of each location in a particular group. The ± expresses the total analytical uncertainty (random and systematic) associated with each measurement. Contributing factors to the total uncertainty included dosimeter fading, calibration, energy-directional dependence, and reproducibility. Uncertainties for the average measurements are one standard deviation from the mean of all locations.

100-mile radius locations. The maximum activities for Cs-137 measured at these locations were 2.5 ± 0.12 pCi/g in F Area; 0.27 ± 0.35 pCi/g in H Area; 0.42 ± 0.05 pCi/g in S Area; 0.66 ± 0.07 pCi/g in Z Area; 0.08 ± 0.02 pCi/g at the site perimeter locations; 0.11 ± 0.02 pCi/g at the 25-mile radius locations; and 0.066 ± 0.02 pCi/g at the 100-mile-radius locations.

Tritium

Tritium concentration in vegetation is measured by analyzing the free water which has been extracted from the sample by freeze drying. Onsite and site perimeter tritium concentrations were generally higher than concentrations in vegetation samples collected from the 25-mile-radius and 100-mile-radius locations. Chart 7-10 compares the maximum and minimum concentrations of tritium onsite, at the site perimeter, at the 25-mile radius, and at the 100-mile radius.

Higher concentrations onsite and at the site perimeter are attributed to atmospheric tritium releases from SRS.

Strontium

The maximum concentrations of Sr-89,90 in vegetation were 3.39 ± 0.22 pCi/g in F Area; 0.81 ± 0.1 pCi/g in H Area; 0.84 ± 0.1 pCi/g at the site perimeter; 0.37 ± 0.1 pCi/g at the 25-mile radius; and 0.24 ± 0.1 pCi/g at the

100-mile radius. The 1991 average Sr-89,90 concentration was 0.6 pCi/g onsite and 0.13 pCi/g at the 100-mile radius.

Seepage and Retention Basins

In addition to the onsite, site perimeter, 25-mile-radius, and 100-mile-radius locations mentioned previously, vegetation samples are collected around seepage and retention basins located near the Reactor and Separations areas. Samples from four to eight locations outside the fence of each basin are composited for

Chart 7-10
Maximum and Minimum Tritium Concentrations in Vegetation

Location ^a	(pCi/g)	
	Maximum	Minimum
Onsite (16)	5.42E+01	5.25E-01
Site Perimeter (14)	8.45E+00	1.23E-01
25-Mile Radius (4)	1.85E+00	1.88E-02
100-Mile Radius (4)	1.00E+00	<LLD

^a Number in parentheses is number of locations.

measurements of gross alpha, nonvolatile beta, and gamma-emitting radionuclides, as well as Sr-89,90.

Gross alpha activities were not detectable except at two locations. Maximum concentrations at these areas were 1.17 ± 0.53 pCi/g at the F-Area seepage basin and 2.53 ± 0.66 pCi/g at the H-Area seepage basin. This compares with 0.14 pCi/g at the F-Area basin in 1990. The H-Area basin was closed in 1990.

Nonvolatile beta activities at the seepage and retention basins were near the levels observed offsite and slightly higher than those measured in 1990. In 1991, the maximum nonvolatile beta activity (71.1 ± 3.1 pCi/g) in vegetation samples from the A-Area basin was higher than the 1990 measurement of 31 pCi/g. The concentration of Sr-90 at the A-Area Basin in 1991 was 2.37 ± 0.07 pCi/g, and the Cs-137 concentration was 0.91 ± 0.08 pCi/g. In the C-Area basin vegetation sample, the 1991 nonvolatile beta activity (24.5 ± 1.4 pCi/g) was higher than the 1990 measurement of 1.1 pCi/g.

Seepage and retention basin vegetation monitoring results are presented in Table 7-19.

Solid Waste Disposal Facility

Vegetation samples are also collected inside the SWDF to determine whether uptake of radioactivity has occurred by vegetation from buried waste. The SWDF samples are analyzed for gross alpha, nonvolatile beta, and gamma-emitting radionuclides. Sample locations are shown in Figure 7-3. Data are presented in Table 7-20.

In 1991, six locations—3A, 4, 15, 31, 33, and 36—inside SWDF showed higher levels of nonvolatile beta activities than in 1990. Generally, differences in concentrations between 1990 and 1991 at these locations were negligible. Cs-137 was detected at all locations. The maximum concentration, 1.6 ± 0.1 pCi/g, was detected at Location 3. Results from all locations were similar to those measured in 1990.

Vegetation samples are also collected quarterly outside SWDF fences. Vegetation sampling locations outside the SWDF are shown in Figure 7-4. Monitoring data are shown in Table 7-21.

The maximum gross alpha and nonvolatile beta activities in vegetation outside the SWDF fence were 8.4 ± 4.0 pCi/g and 48.2 ± 3.5 pCi/g, respectively. The average alpha and nonvolatile beta activity for 1991 was similar to that reported in 1990. The maximum concentration of Cs-137 detected in vegetation outside

SWDF was 0.69 ± 0.07 pCi/g. This sample was taken from Location 9.

Concentrations of radionuclides measured in samples collected outside the SWDF indicate control practices at the SWDF have been effective in preventing the spread of contamination from the facility.

FOOD PRODUCTS

Monitoring the concentrations of radionuclides in milk and food products is an important element of the site's environmental monitoring program because radioactive materials can be transported to man through consumption of these media. For this reason, EMS collects and analyzes milk and food samples to determine the concentrations of radionuclides contributed by SRS operations and worldwide fallout.

A complete discussion of sample collection and analytical procedures for these media is found in Chapter 4.

Milk

Description of Monitoring Program

Milk samples are collected every two weeks at six dairies within a 25-mile radius of SRS and from locally produced inventories of a major distributor. Sampling locations are shown in Figure 7-5.

Milk samples are analyzed for tritium and gamma-emitting radionuclides, primarily Cs-137 and I-131. Additional milk samples are collected quarterly and analyzed for Sr-90.

Monitoring Results

Chart 7-11 shows a comparison of radionuclide concentrations in milk over the past three years. Comprehensive monitoring data for 1991 are presented in Table 7-22.

Strontium-90

All results of 1991 measurements of Sr-90 concentrations in milk samples were at, or at less than, detectable levels. The minimum detectable activity, $8.0\text{E-}09$ mCi/mL, was calculated using the variable counting instrumentation parameters inherent to the procedure.

Gamma-Emitting Radionuclides

Cesium-137 was the only man-made gamma-emitting radionuclide detected in milk samples during 1991. Measured concentrations ranged from $(2.0 \pm 0.6)\text{E-}09$ $\mu\text{Ci/mL}$ to $(8.3 \pm 0.8)\text{E-}09$ $\mu\text{Ci/mL}$. The average concentration of $3.4\text{E-}09$ $\mu\text{Ci/mL}$ for 1991 was similar to the average concentration calculated in 1990 (Chart

Figure 7-3 Vegetation sampling locations inside the Solid Waste Disposal Facility

Figure 7-4 Squares, triangles, circles indicate vegetation sampling locations outside SWDF.

7-11), but higher than the concentration for 1989 because only detectable concentrations—a conservative method—were used in 1990 and 1991 to calculate averages. In 1989, the average was calculated with zeros added for non-detectable results.

For the period 1986 to 1991, there is not a direct relationship between the amount of Cs-137 released to the atmosphere from SRS and the concentrations in milk. Even in 1987, when the atmospheric release of Cs-137 was over 500 times higher than the amount released in the other five years, the maximum and average concentrations of Cs-137 in milk are similar to those measured in the other five years [Mikol et al., 1988]. This indicates that other sources are more significant contributors to Cs-137 in milk than atmospheric releases from SRS.

Concentrations of I-131 were not detected in any milk samples in 1991. Because of its short physical half-life (eight days), I-131 generally is not detected, except shortly after tests of nuclear weapons or in the wake of events such as the Chernobyl incident. There were no

announced atmospheric nuclear weapons tests or other major nuclear incidents in 1991.

Tritium

Tritium in milk is attributed to releases from SRS. Milk from all dairies showed detectable concentrations of tritium at some point during 1991. The maximum concentration (2.32 ± 0.08)E-06 $\mu\text{Ci/mL}$ was observed at the Girard, Ga., location. Concentrations in milk during the past six years generally reflect changes in the atmospheric source term (Figure 7-6).

Foodstuffs

Description of Monitoring Program

Farm products including vegetables, fruit, grain, poultry, and meat are collected annually from 14 locations within the six counties surrounding SRS. Six locations are near the site perimeter and eight locations are approximately 25 miles from SRS. Eggs are collected quarterly from these locations. Collards collected annually from Columbia are used as a control sample. Figure 7-5 shows food sampling locations.

Figure 7-5 Technicians collect milk and food samples from local dairies and farms within a 25-mile radius of SRS. Milk samples are collected every two weeks. Food samples are collected annually, with the exception of eggs, which are collected quarterly.

Food samples are analyzed for gamma-emitting radionuclides, tritium, Sr-90, uranium and plutonium (non-specific), Pu-238, and Pu-239.

Monitoring Results

Food monitoring data are presented in Table 7-23. In 1991, the concentrations of radionuclides measured in foods were near or below levels measured in the control sample (collards) from Columbia.

Gamma-Emitting Radionuclides

The only man-made gamma-emitting radionuclide detected in food was Cs-137. The maximum Cs-137 concentration, 0.023 ± 0.003 pCi/g, was measured in grain and was similar to concentrations measured in previous years. Concentrations of Cs-137 were not detected in the control sample.

Strontium-90

With the exception of collards, all concentrations in foodstuffs were less than concentrations measured in the control sample collected from Columbia. Sr-90 concentrations in food ranged from $(-0.95 \pm 4.3)E-04$ pCi/g (corn) to 0.53 ± 0.33 pCi/g (collards). The Sr-90 concentration in the control sample was $0.13 \pm .03$ pCi/g.

g. Sr-90 concentrations for all media were within ranges observed in past years.

Uranium/Plutonium

Most concentrations of total uranium and plutonium (U/Pu) in food samples were not detectable. The highest concentration was $(6.5 \pm 5.6)E-03$ pCi/g in corn samples.

Concentrations of Pu-238 ranged from $-7.3E-05$ pCi/g in a grain sample to $(1.5 \pm 0.8)E-04$ pCi/g in a beef sample. Pu-239 concentrations in food ranged from $-7.7E-05$ pCi/g to $(6 \pm 3)E-05$ pCi/g in beef samples. Measurements in food were similar to 1990 maximum levels of $2.7E-03$ pCi/g for Pu-238 and $7.0E-04$ pCi/g for Pu-239.

Tritium

Concentrations of tritium ranged from $6.1E-03$ pCi/g in beef to 2.7 pCi/g in fruit. In the control sample, the tritium concentration was $4.7E-01$ pCi/g.

Doses from Consumption

DOE has established a radiation dose limit of 100 mrem (1 mSv) EDE for individual members of the public. This limit, incorporated into DOE Order 5400.5, "Radiation Protection of the Public and Environment," applies to all individual members of the public and

Figure 7-6 Tritium concentrations are attributed to releases from SRS. Measurements over a five-year period from locally collected milk reflect changes in atmospheric releases.

Chart 7-11
Monitoring Data for Milk

Analysis	E-09 $\mu\text{Ci/mL}$					
	1989		1990		1991	
	Max	Avg	Max	Avg	Max	Avg
Strontium-90	8.0	3.2	7.2	0.25	8.4	^a
Cesium-137 ^b	5.1	1.6	5.7	3.2 ^b	8.3	3.4
Tritium	1,670.0	300.0	1,190.0	272.0	2,320.0	479.0

^a All results of 1991 measurements of Sr-90 concentrations in milk samples were at, or at less than, detectable levels. The minimum detectable activity, $8.0\text{E-}09 \mu\text{Ci/mL}$, was calculated using the variable counting instrumentation parameters inherent to the procedure.

^b Cs-137 averages for 1990 and 1991 were calculated using only detectable concentrations determined by the EMS gamma spectroscopy software. The reported average in 1989 was calculated using zeros if the result was not above the detection limit.

includes the dose a person receives as a consequence of DOE operations through all pathways. Specific pathways include the consumption of milk and food containing radioactivity as a result of SRS emissions.

Also contained in DOE Order 5400.5 is the EPA dose limit of 10 mrem EDE/yr from atmospheric emissions (40 CFR 61, Subpart H) from DOE facilities. Air emissions from SRS can contribute to the food pathways.

Milk Consumption

The tritium concentrations in milk that are attributed to SRS releases do not correspond to large radiation doses when compared to dose limits. For example, the 50-year committed EDE from drinking 0.5 L of milk per day for a year, with a tritium concentration of $2.32\text{E-}06 \mu\text{Ci/mL}$ (maximum in 1991), is approximately 0.027 mrem (0.00027 mSv). This dose is 0.27 percent of the EPA 10 mrem standard.

If a person were to drink 0.5 L of milk with a Cs-137 concentration of $8.3\text{E-}09 \mu\text{Ci/mL}$ (maximum in 1991) every day for a year, that person would receive a committed EDE of 0.076 mrem (0.00076 mSv), which is 0.76 percent of the EPA 10 mrem limit. Drinking milk

with a maximum concentration of Sr-90 ($8.4\text{E-}09 \mu\text{Ci/mL}$) would result in a committed EDE of 0.20 mrem (0.002 mSv), or 2.0 percent of the EPA limit..

Food Consumption

Doses are calculated for food consumption based on the intake of collards, which are broad, leafy vegetables considered a typical part of the dietary intake of the SRS area population. The radiation dose from eating foods containing tritium, attributable to SRS operations, is a small fraction of the annual DOE dose limit. If a person consumed collards at a maximum rate of 43 kg/year (95 lb/yr), the 50-year committed EDE would be $1.3\text{E-}03 \text{ mrem}$ ($1.3\text{E-}05 \text{ mSv}$) for tritium (maximum of 0.47 pCi/g in 1991), which is less than 1 percent of the 10 mrem EPA annual dose limit.

Eating collards with a maximum Cs-137 concentration of 0.023 pCi/g at a rate of 43 kg/yr would result in a committed EDE of 0.05 mrem (0.0005 mSv), which is less than 1 percent of the EPA 10 mrem limit. Using the same scenario for concentrations of Sr-90 in collards, the dose would be 3.0 mrem, or 30 percent, of the EPA limit.

Table 7-1
1991 Atmospheric Releases by Source

Radio-nuclide	Curies						
	Reactors	Separations	Reactor Materials	Heavy Water	SRL	Diffuse and Fugitive ^a	Total
GASES AND VAPORS							
H-3 (oxide)	7.47E+04	6.21E+04		1.69E+02		2.55E+01	1.37E+05
H-3 (elem.)		6.29E+04					6.29E+04
H-3 Total	7.47E+04	1.25E+05		1.69E+02			2.00E+05
C-14		6.20E-01				4.00E-08	6.20E-01
Kr-85		1.04E+04					1.04E+04
I-129		1.01E-02					1.01E-02
I-131	1.04E-07	2.34E-08			2.96E-05	1.16E-07	2.98E-05
I-133					7.92E-05		7.92E-05
PARTICULATES							
Cr-51						5.52E-07	5.52E-07
Co-60		1.71E-06			3.78E-07	1.39E-06	3.48E-06
Zn-65						1.46E-16	1.46E-16
Sr-89,90 ^b	2.97E-04	2.75E-03	2.21E-04	1.52E-05	3.84E-05	6.50E-04	3.97E-03
Zr-95						1.11E-07	1.11E-07
Nb-95						1.55E-15	1.55E-15
Ru-106		4.44E-04				4.97E-12	4.44E-04
Sb-125		8.54E-08				7.27E-15	8.54E-08
Cs-134		6.40E-06				2.82E-07	6.68E-06
Cs-137		3.20E-04			6.73E-06	5.48E-06	3.32E-04
Ce-144		6.48E-07				3.78E-07	1.03E-06
Pm-147						5.35E-15	5.35E-15
Eu-154						3.44E-13	3.44E-13
Eu-155						7.46E-14	7.46E-14
U-235,238		2.56E-03	1.25E-04			1.44E-15	2.69E-03
Pu-238		2.64E-04				3.18E-07	2.64E-04
Pu-239 ^c	3.04E-05	3.48E-04		7.89E-07	5.24E-05	3.95E-05	4.71E-04
Am-241,243		1.51E-04				8.86E-13	1.51E-04
Cm-242,244		4.25E-05				7.32E-12	4.25E-05

a Estimated releases from minor unmonitored diffuse and fugitive sources.

b Includes unidentified beta-gamma.

c Includes unidentified alpha.

Table 7-2
Maximum Individual Committed Dose at Site Perimeter from
Atmospheric Releases with Consumption of Cow Milk

By Pathway

Pathway	Average Consumption		Maximum Consumption	
	Individual Dose, mrem ^a	Percent of Total Dose	Individual Dose, mrem ^a	Percent of Total Dose
Plume	4.11E-05	0.04	4.11E-05	0.03
Ground	1.71E-04	0.18	1.71E-04	0.14
Inhalation	5.65E-02	60.47	5.65E-02	46.09
Vegetation	2.51E-02	26.86	4.37E-02	35.65
Cow Milk	8.20E-03	8.78	1.57E-02	12.81
Meat	3.43E-03	3.67	6.47E-03	5.28
Total	9.34E-02		1.23E-01	

By Radionuclide

Radionuclide	Average Consumption		Maximum Consumption	
	Individual Dose, mrem ^a	Percent of Total Dose	Individual Dose, mrem ^a	Percent of Total Dose
Gases and Vapors				
H-3	8.62E-02	92.27	1.12E-01	91.37
C-14	1.22E-04	0.13	2.21E-04	0.18
Kr-85	4.11E-05	0.04	4.11E-05	0.03
I-129	3.13E-03	3.35	5.49E-03	4.48
I-131	4.35E-08	0.00005	8.49E-08	0.0001
Particulates				
Sr-90	1.41E-04	0.15	2.30E-04	0.19
Ru-106	6.93E-06	0.01	1.15E-05	0.01
Cs-134, 137	3.17E-05	0.03	3.50E-05	0.03
U-235, 238	1.37E-03	1.47	1.46E-03	1.19
Pu-238	6.27E-04	0.67	7.62E-04	0.62
Pu-239	1.28E-03	1.37	1.56E-03	1.27
Am-241, 243	4.11E-04	0.44	5.03E-04	0.41
Cm-242, 244	5.98E-05	0.06	7.30E-05	0.06
Total	9.34E-02		1.23E-01	

^a Effective dose equivalent.

Table 7-3
Maximum Individual Committed Dose at Site Perimeter from
Atmospheric Releases with Consumption of Goat Milk

By Pathway

Pathway	Average Consumption		Maximum Consumption	
	Individual Dose, mrem ^a	Percent of Total Dose	Individual Dose, mrem ^a	Percent of Total Dose
Plume	4.11E-05	0.04	4.11E-05	0.03
Ground	1.71E-04	0.16	1.71E-04	0.12
Inhalation	5.65E-02	54.40	5.65E-02	39.65
Vegetation	2.51E-02	24.17	4.37E-02	30.67
Goat Milk	1.86E-02	17.91	3.56E-02	24.99
Meat	3.44E-03	3.31	6.47E-03	4.54
Total	1.04E-01		1.42E-01	

By Radionuclide

Radionuclide	Average Consumption		Maximum Consumption	
	Individual Dose, mrem ^a	Percent of Total Dose	Individual Dose, mrem ^a	Percent of Total Dose

Gases and Vapors

H-3	9.65E-02		1.32E-01	92.64
C-14	1.26E-04	0.12	2.29E-04	0.16
Kr-85	4.11E-05	0.04	4.11E-05	0.03
I-129	3.20E-03	3.08	5.63E-03	3.95
I-131	4.91E-08	0.00	9.56E-08	0.00007

Particulates

Sr-90	1.44E-04	0.14	2.35E-04	0.16
Ru-106	6.93E-06	0.01	1.15E-05	0.01
Cs-134, 137	3.35E-05	0.03	3.86E-05	0.03
U-235, 238	1.37E-03	1.32	1.46E-03	1.02
Pu-238	6.27E-04	0.60	7.62E-04	0.53
Pu-239	1.28E-03	1.23	1.56E-03	1.09
Am-241, 243	4.11E-04	0.40	5.03E-04	0.35
Cm-242, 244	5.97E-05	0.06	7.30E-05	0.05
Total	1.04E-01		1.42E-01	

^a Effective dose equivalent.

Table 7-4
Average Individual Committed Dose at Site Perimeter from Atmospheric Releases with Consumption of Cow Milk

By Pathway

Pathway	Individual Dose, mrem^a	Percent of Total Dose
Plume	2.49E-05	0.04
Ground	1.18E-04	0.21
Inhalation	3.40E-02	60.52
Vegetation	1.51E-02	26.88
Cow Milk	4.89E-03	8.70
Meat	2.05E-03	3.65
Total	5.62E-02	

By Radionuclide

Radionuclide	Individual Dose, mrem^a	Percent of Total Dose
Gases and Vapors		
H-3	5.14E-02	91.49
C-14	7.37E-05	0.13
Kr-85	2.49E-05	0.04
I-129	1.93E-03	3.44
I-131	2.61E-07	0.0005
Particulates		
Sr-90	1.01E-04	0.18
Ru-106	4.28E-06	0.01
Cs-134,137	2.10E-05	0.04
U-235,238	1.01E-03	1.80
Pu-238	3.82E-04	0.68
Pu-239	1.06E-03	1.89
Am-241,243	2.51E-04	0.45
Cm-242,244	3.64E-05	0.06
Total	5.62E-02	

^a Effective dose equivalent.

Table 7-5
50-Mile (80-km) Collective Committed Dose from Atmospheric Releases

By Pathway

Pathway	Population Dose person-rem^a	Percent of Total Dose
Plume	2.72E-03	0.04
Ground	2.95E-02	0.42
Inhalation	5.10E+00	71.88
Vegetation	1.19E+00	16.77
Cow Milk	6.12E-01	8.63
Meat	1.61E-01	2.27
Total	7.10E+00	

By Radionuclide

Radionuclide	Population Dose person-mrem^a	Percent of Total Dose
Gases and Vapors		
H-3	6.61E+00	93.16
C-14	6.66E-03	0.09
Kr-85	2.72E-03	0.04
I-129	1.74E-01	2.45
I-131	9.39E-06	0.0001
Particulates		
Sr-90	6.90E-03	0.10
Ru-106	3.66E-04	0.01
Cs-134,137	3.14E-03	0.04
U-235,238	1.22E-01	1.72
Pu-238	4.53E-02	0.64
Pu-239	9.00E-02	1.27
Am-241,243	2.97E-02	0.42
Cm-242,244	4.31E-03	0.06
Total	7.10E+00	

^a Effective dose equivalent.

Table 7-6
1991 NESHAP Report Data—CAP88 Compared With MAXIGASP

Maximum Individual Dose Commitment at Site Boundary from Atmospheric Releases

	CAP88 CODE		MAXIGASP CODE	
	Max. Ind. mrem^a	Percent of Dose	Max. Ind. mrem^a	Percent of Dose
By Pathway				
Plume	5.10E-05	0.02	4.11E-05	0.03
Ground	1.47E-04	0.07	1.71E-04	0.14
Inhalation	6.36E-02	28.80	5.65E-02	46.09
Food ^b	1.57E-01	71.11	6.59E-02	53.74
Total	2.21E-01		1.23E-01	
By Radionuclide				
Gases and Vapors				
H-3 ^c	2.18E-01	98.43	1.12E-01	91.37
C-14	4.74E-05	0.02	2.21E-04	0.18
Kr-85	7.58E-05	0.03	4.11E-05	0.03
I-129	7.63E-04	0.34	5.49E-03	4.48
I-131	1.81E-08	0.00001	8.49E-08	0.0001
Particulates				
Sr-90	6.16E-05	0.03	2.30E-04	0.19
Ru-106	9.93E-06	0.004	1.15E-05	0.01
Cs-134,137	2.01E-04	0.01	3.50E-05	0.03
U-235,238	1.23E-03	0.56	1.46E-03	1.19
Pu-238	3.13E-04	0.14	7.62E-04	0.62
Pu-239	6.28E-04	0.28	1.56E-03	1.27
Am-241,243	2.92E-04	0.13	5.03E-04	0.41
Cm-242,244	4.34E-04	0.02	7.30E-05	0.06
Total	2.21E-01		1.23E-01	

a Effective dose equivalent.

b Meat, milk, and vegetation.

c Dose from tritium in foods calculated with absolute humidity of 11 g water per cubic meter of air.

Table 7-7
1991 NESHAP Report Data—CAP88 Compared With POPGASP

Collective Committed Dose from Atmospheric Releases

	CAP88 Code		POPGASP Code	
	Person rem ^a	Percent of Dose	Person rem ^a	Percent of Dose
By Pathway				
Plume	5.66E-03	0.03	2.73E-03	0.04
Ground	1.79E-02	0.08	2.95E-02	0.42
Inhalation	7.02E+00	33.05	5.10E+00	71.88
Food ^b	1.42E+01	66.84	1.96E+00	27.67
Total	2.12E+01		7.10E+00	
By Radionuclide				
Gases and Vapors				
H-3 ^c	2.09E+01	98.61	6.61E+00	93.16
C-14	4.37E-03	0.02	6.66E-03	0.09
Kr, Xe isotopes	8.40E-03	0.04	2.72E-03	0.04
I-129	3.63E-02	0.17	1.74E-01	2.45
I-131	7.08E-07	0.000003	9.39E-06	0.0001
Particulates				
Sr-90	5.40E-03	0.03	6.90E-03	0.10
Ru-106	1.60E-03	0.01	3.66E-04	0.01
Cs-134,137	3.35E-03	0.02	3.14E-03	0.04
U-235,238	1.18E-01	0.56	1.22E-01	1.72
Pu-238	2.90E-02	0.14	4.53E-02	0.64
Pu-239	5.73E-02	0.27	9.00E-02	1.27
Am-241,243	2.74E-02	0.13	2.97E-02	0.42
Cm-242,244	4.07E-03	0.02	4.31E-03	0.06
Total	2.12E+01		7.10E+00	

^a Effective dose equivalent.

^b Meat, milk, and vegetation.

^c Dose from tritium in foods calculated with absolute humidity of 11 g water per cubic meter of air.

Table 7-8
Radioactivity in Air

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha ($\mu\text{Ci/mL}$)				
Onsite				
A Area	49	$1.05 \pm 0.13 \text{ E-14}$	$0.41 \pm 2.37 \text{ E-16}$	$2.79 \pm 1.92 \text{ E-15}$
Burial Ground North	25	$5.04 \pm 0.78 \text{ E-15}$	$1.24 \pm 0.47 \text{ E-15}$	$2.55 \pm 0.99 \text{ E-15}$
Burial Ground South	50	$6.92 \pm 1.04 \text{ E-15}$	$6.31 \pm 3.08 \text{ E-16}$	$2.34 \pm 1.39 \text{ E-15}$
F Area	49	$6.97 \pm 1.05 \text{ E-15}$	$5.48 \pm 3.44 \text{ E-16}$	$2.33 \pm 1.18 \text{ E-15}$
H Area	48	$8.12 \pm 1.14 \text{ E-15}$	$3.63 \pm 4.30 \text{ E-16}$	$2.45 \pm 1.47 \text{ E-15}$
Site Perimeter				
Allendale Gate	51	$8.81 \pm 1.01 \text{ E-15}$	$3.71 \pm 3.11 \text{ E-16}$	$2.43 \pm 1.62 \text{ E-15}$
Barnwell Gate	50	$9.58 \pm 1.08 \text{ E-15}$	$2.67 \pm 3.49 \text{ E-16}$	$2.68 \pm 1.78 \text{ E-15}$
D Area	50	$8.44 \pm 0.99 \text{ E-15}$	$0.13 \pm 2.40 \text{ E-16}$	$2.55 \pm 1.68 \text{ E-15}$
Darkhorse	51	$7.81 \pm 0.98 \text{ E-15}$	$1.22 \pm 2.65 \text{ E-16}$	$2.47 \pm 1.66 \text{ E-15}$
East Talatha	49	$8.88 \pm 1.09 \text{ E-15}$	$0.96 \pm 2.40 \text{ E-16}$	$2.77 \pm 1.88 \text{ E-15}$
Greenpond	50	$8.74 \pm 1.23 \text{ E-15}$	$2.71 \pm 2.88 \text{ E-16}$	$2.54 \pm 1.77 \text{ E-15}$
Highway 39	52	$1.02 \pm 0.11 \text{ E-14}$	$2.75 \pm 2.32 \text{ E-16}$	$2.62 \pm 1.85 \text{ E-15}$
Highways 21 & 167	50	$1.00 \pm 0.11 \text{ E-14}$	$0.08 \pm 4.18 \text{ E-16}$	$2.64 \pm 1.87 \text{ E-15}$
Jackson, SC	51	$7.22 \pm 0.92 \text{ E-15}$	$3.33 \pm 3.05 \text{ E-16}$	$2.51 \pm 1.64 \text{ E-15}$
Patterson Mill Rd	51	$1.07 \pm 0.12 \text{ E-14}$	$5.27 \pm 3.40 \text{ E-16}$	$2.65 \pm 1.86 \text{ E-15}$
Road A14	52	$7.82 \pm 1.11 \text{ E-15}$	$2.17 \pm 2.88 \text{ E-16}$	$2.60 \pm 1.68 \text{ E-15}$
Talatha Gate	49	$6.28 \pm 0.87 \text{ E-15}$	$2.81 \pm 2.92 \text{ E-16}$	$2.45 \pm 1.41 \text{ E-15}$
West Jackson	49	$9.57 \pm 1.12 \text{ E-15}$	$1.90 \pm 6.34 \text{ E-16}$	$2.84 \pm 1.79 \text{ E-15}$
Windsor Road	49	$8.20 \pm 1.12 \text{ E-15}$	$1.70 \pm 2.19 \text{ E-16}$	$2.82 \pm 1.70 \text{ E-15}$
25-mile Radius				
Aiken Airport	51	$6.90 \pm 0.95 \text{ E-15}$	$0.44 \pm 2.41 \text{ E-16}$	$2.25 \pm 1.28 \text{ E-15}$
Aiken State Park	48	$9.40 \pm 1.04 \text{ E-15}$	$3.61 \pm 3.07 \text{ E-16}$	$2.91 \pm 1.98 \text{ E-15}$
Allendale, SC	52	$7.61 \pm 0.99 \text{ E-15}$	$3.63 \pm 3.09 \text{ E-16}$	$2.28 \pm 1.47 \text{ E-15}$
Augusta, GA	48	$5.51 \pm 0.80 \text{ E-15}$	$6.61 \pm 3.63 \text{ E-16}$	$2.53 \pm 1.23 \text{ E-15}$
Highway 301	43	$7.40 \pm 0.93 \text{ E-15}$	$1.51 \pm 3.07 \text{ E-16}$	$2.29 \pm 1.51 \text{ E-15}$
Langley, SC	50	$7.97 \pm 1.17 \text{ E-15}$	$5.69 \pm 3.46 \text{ E-16}$	$2.57 \pm 1.50 \text{ E-15}$
Lees, SC	46	$7.83 \pm 0.35 \text{ E-15}$	$-0.73 \pm 2.14 \text{ E-16}$	$2.06 \pm 1.30 \text{ E-15}$
Olar, SC	54	$8.76 \pm 1.01 \text{ E-15}$	$3.17 \pm 2.50 \text{ E-16}$	$2.58 \pm 1.81 \text{ E-15}$
Perkins, GA	49	$9.07 \pm 1.03 \text{ E-15}$	$3.39 \pm 3.09 \text{ E-16}$	$2.66 \pm 1.91 \text{ E-15}$
South Richmond, GA	46	$1.01 \pm 0.12 \text{ E-14}$	$3.65 \pm 3.09 \text{ E-16}$	$2.64 \pm 1.75 \text{ E-15}$
Springfield, SC	51	$7.04 \pm 0.93 \text{ E-15}$	$6.57 \pm 3.61 \text{ E-16}$	$2.56 \pm 1.54 \text{ E-15}$

Table 7-8
Radioactivity in Air, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Waynesboro, GA	51	$7.98 \pm 0.97 \text{ E-15}$	$3.52 \pm 3.07 \text{ E-16}$	$2.37 \pm 1.34 \text{ E-15}$
100-mile Radius				
Columbia, SC	46	$8.41 \pm 1.04 \text{ E-15}$	$2.85 \pm 3.22 \text{ E-16}$	$2.74 \pm 1.60 \text{ E-15}$
Greenville, SC	40	$7.85 \pm 1.08 \text{ E-15}$	$2.43 \pm 2.69 \text{ E-16}$	$2.86 \pm 1.85 \text{ E-15}$
Macon, GA	44	$9.31 \pm 1.54 \text{ E-15}$	$3.15 \pm 3.45 \text{ E-16}$	$2.40 \pm 1.70 \text{ E-15}$
Savannah, GA	50	$6.28 \pm 0.84 \text{ E-15}$	$2.40 \pm 2.82 \text{ E-16}$	$2.38 \pm 1.41 \text{ E-15}$
Nonvolatile Beta ($\mu\text{Ci/mL}$)				
Onsite				
A Area	49	$4.28 \pm 0.20 \text{ E-14}$	$8.50 \pm 0.91 \text{ E-15}$	$1.91 \pm 0.79 \text{ E-14}$
Burial Ground North	25	$3.70 \pm 0.16 \text{ E-14}$	$1.15 \pm 0.11 \text{ E-14}$	$1.95 \pm 0.71 \text{ E-14}$
Burial Ground South	50	$4.57 \pm 0.21 \text{ E-14}$	$6.52 \pm 0.82 \text{ E-15}$	$1.77 \pm 0.81 \text{ E-14}$
F Area	49	$4.56 \pm 0.21 \text{ E-14}$	$8.16 \pm 0.89 \text{ E-15}$	$1.76 \pm 0.74 \text{ E-14}$
H Area	48	$4.71 \pm 0.22 \text{ E-14}$	$7.84 \pm 0.87 \text{ E-15}$	$1.75 \pm 0.76 \text{ E-14}$
Site Perimeter				
Allendale Gate	51	$4.32 \pm 0.18 \text{ E-14}$	$5.47 \pm 0.79 \text{ E-15}$	$1.77 \pm 0.77 \text{ E-14}$
Barnwell Gate	50	$4.34 \pm 0.18 \text{ E-14}$	$7.99 \pm 1.07 \text{ E-15}$	$1.83 \pm 0.76 \text{ E-14}$
D Area	50	$3.80 \pm 0.17 \text{ E-14}$	$7.62 \pm 0.87 \text{ E-15}$	$1.67 \pm 0.70 \text{ E-14}$
Darkhorse	51	$3.93 \pm 0.17 \text{ E-14}$	$6.86 \pm 0.84 \text{ E-15}$	$1.71 \pm 0.72 \text{ E-14}$
East Talatha	49	$4.09 \pm 0.18 \text{ E-14}$	$2.65 \pm 0.65 \text{ E-15}$	$1.91 \pm 0.81 \text{ E-14}$
Greenpond	50	$4.63 \pm 0.22 \text{ E-14}$	$6.24 \pm 0.80 \text{ E-15}$	$1.76 \pm 0.79 \text{ E-14}$
Highway 39	52	$3.86 \pm 0.18 \text{ E-14}$	$1.44 \pm 0.46 \text{ E-15}$	$1.72 \pm 0.76 \text{ E-14}$
Highways 21 & 167	50	$4.18 \pm 0.18 \text{ E-14}$	$9.01 \pm 0.94 \text{ E-15}$	$1.88 \pm 0.71 \text{ E-14}$
Jackson, SC	50	$4.03 \pm 0.19 \text{ E-14}$	$7.65 \pm 0.88 \text{ E-15}$	$1.65 \pm 0.71 \text{ E-14}$
Patterson Mill Rd	51	$4.62 \pm 0.19 \text{ E-14}$	$9.23 \pm 0.94 \text{ E-15}$	$1.83 \pm 0.77 \text{ E-14}$
Road A14	52	$4.54 \pm 0.21 \text{ E-14}$	$7.91 \pm 0.98 \text{ E-15}$	$1.79 \pm 0.76 \text{ E-14}$
Talatha Gate	49	$3.71 \pm 0.17 \text{ E-14}$	$5.32 \pm 1.26 \text{ E-15}$	$1.69 \pm 0.72 \text{ E-14}$
West Jackson	49	$4.41 \pm 0.19 \text{ E-14}$	$4.76 \pm 0.34 \text{ E-15}$	$1.85 \pm 0.80 \text{ E-14}$
Windsor Road	49	$3.78 \pm 0.19 \text{ E-14}$	$7.91 \pm 0.91 \text{ E-15}$	$1.86 \pm 0.68 \text{ E-14}$
25-mile Radius				
Aiken Airport	51	$3.15 \pm 0.16 \text{ E-14}$	$7.70 \pm 0.88 \text{ E-15}$	$1.66 \pm 0.58 \text{ E-14}$
Aiken State Park	48	$3.66 \pm 0.16 \text{ E-14}$	$8.38 \pm 1.00 \text{ E-15}$	$1.92 \pm 0.71 \text{ E-14}$
Allendale, SC	52	$3.63 \pm 0.17 \text{ E-14}$	$8.42 \pm 0.90 \text{ E-15}$	$1.68 \pm 0.67 \text{ E-14}$
Augusta, GA	48	$5.08 \pm 0.32 \text{ E-14}$	$9.91 \pm 1.03 \text{ E-15}$	$1.92 \pm 0.80 \text{ E-14}$
Highway 301	43	$3.81 \pm 0.17 \text{ E-14}$	$5.88 \pm 0.89 \text{ E-15}$	$1.67 \pm 0.67 \text{ E-14}$

Table 7-8
Radioactivity in Air, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Langley, SC	50	$4.86 \pm 0.23 \text{ E-14}$	$8.86 \pm 1.03 \text{ E-15}$	$1.87 \pm 0.72 \text{ E-14}$
Lees, SC	46	$3.64 \pm 0.16 \text{ E-14}$	$2.12 \pm 0.18 \text{ E-17}$	$1.62 \pm 0.66 \text{ E-14}$
Olar, SC	51	$4.39 \pm 0.22 \text{ E-14}$	$7.43 \pm 0.86 \text{ E-15}$	$1.78 \pm 0.79 \text{ E-14}$
Perkins, GA	49	$4.81 \pm 0.20 \text{ E-14}$	$6.89 \pm 0.87 \text{ E-15}$	$1.85 \pm 0.84 \text{ E-14}$
South Richmond, GA	46	$4.21 \pm 0.20 \text{ E-14}$	$6.56 \pm 0.82 \text{ E-15}$	$1.82 \pm 0.73 \text{ E-14}$
Springfield, SC	51	$4.10 \pm 0.18 \text{ E-14}$	$8.99 \pm 0.84 \text{ E-15}$	$1.81 \pm 0.72 \text{ E-14}$
Waynesboro, GA	51	$3.34 \pm 0.16 \text{ E-14}$	$7.65 \pm 0.87 \text{ E-15}$	$1.72 \pm 0.63 \text{ E-14}$
100-mile Radius				
Columbia, SC	46	$3.36 \pm 0.16 \text{ E-14}$	$6.35 \pm 0.79 \text{ E-15}$	$1.64 \pm 0.61 \text{ E-14}$
Greenville, SC	40	$5.26 \pm 0.24 \text{ E-14}$	$6.59 \pm 0.83 \text{ E-15}$	$2.00 \pm 0.92 \text{ E-14}$
Macon, GA	44	$4.88 \pm 0.20 \text{ E-14}$	$6.57 \pm 0.79 \text{ E-15}$	$1.73 \pm 0.78 \text{ E-14}$
Savannah, GA	50	$4.23 \pm 0.19 \text{ E-14}$	$7.51 \pm 0.99 \text{ E-15}$	$1.68 \pm 0.80 \text{ E-14}$
Sr-89,90 ($\mu\text{Ci/mL}$)				
Monthly Composite				
A Area	10	$1.37 \pm 0.36 \text{ E-15}$	$-4.71 \pm 2.51 \text{ E-16}$	$2.36 \pm 5.05 \text{ E-16}$
Burial Ground North	6	$1.06 \pm 0.79 \text{ E-15}$	$-2.32 \pm 4.48 \text{ E-16}$	$2.88 \pm 4.60 \text{ E-16}$
Burial Ground South	11	$4.48 \pm 3.55 \text{ E-16}$	$-3.10 \pm 3.32 \text{ E-16}$	$1.76 \pm 2.18 \text{ E-16}$
F Area	11	$7.63 \pm 8.40 \text{ E-16}$	$-4.64 \pm 1.92 \text{ E-16}$	$1.69 \pm 3.82 \text{ E-16}$
H Area	11	$5.49 \pm 3.56 \text{ E-16}$	$-1.11 \pm 0.68 \text{ E-15}$	$0.22 \pm 4.47 \text{ E-16}$
Site Perimeter	46	$5.11 \pm 2.91 \text{ E-16}$	$-3.58 \pm 1.33 \text{ E-16}$	$0.49 \pm 1.49 \text{ E-16}$
25-mile Radius	48	$3.10 \pm 1.87 \text{ E-16}$	$-4.74 \pm 5.20 \text{ E-16}$	$0.44 \pm 1.45 \text{ E-16}$
100-mile Radius	48	$2.08 \pm 0.45 \text{ E-15}$	$-2.22 \pm 0.81 \text{ E-15}$	$2.00 \pm 6.12 \text{ E-16}$
Cs-137 ($\mu\text{Ci/mL}$)				
Monthly Composite				
Onsite				
A Area	13 / 0 ^a			
Burial Ground North	6 / 0			
Burial Ground South	12 / 0			
F Area	12 / 0			
H Area	12 / 0			

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-8
Radioactivity in Air, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Site Perimeter	50 / 0 ^a			
25-mile Radius	51 / 0			
100-mile Radius	52 / 0			
Pu-238 ($\mu\text{Ci/mL}$)				
Monthly Composite				
A Area	9	$3.45 \pm 1.52 \text{ E-18}$	$-3.48 \pm 3.01 \text{ E-18}$	$-0.13 \pm 1.86 \text{ E-18}$
Burial Ground North	6	$1.32 \pm 0.32 \text{ E-17}$	$5.36 \pm 2.05 \text{ E-18}$	$8.45 \pm 3.46 \text{ E-18}$
Burial Ground South	10	$5.99 \pm 0.88 \text{ E-17}$	$-5.36 \pm 6.10 \text{ E-19}$	$1.29 \pm 1.75 \text{ E-17}$
F Area	11	$4.20 \pm 0.18 \text{ E-16}$	$1.76 \pm 0.67 \text{ E-18}$	$0.77 \pm 1.25 \text{ E-16}$
H Area	12	$2.92 \pm 0.93 \text{ E-17}$	$1.84 \pm 1.33 \text{ E-18}$	$6.79 \pm 7.50 \text{ E-18}$
Site Perimeter	46	$1.94 \pm 0.22 \text{ E-17}$	$-2.88 \pm 1.47 \text{ E-18}$	$1.22 \pm 3.65 \text{ E-18}$
25-mile Radius	44	$4.61 \pm 1.26 \text{ E-18}$	$-3.98 \pm 0.69 \text{ E-18}$	$0.03 \pm 1.24 \text{ E-18}$
100-mile Radius	43	$2.39 \pm 0.68 \text{ E-17}$	$-4.78 \pm 3.59 \text{ E-18}$	$1.44 \pm 3.59 \text{ E-18}$
Pu-239 ($\mu\text{Ci/mL}$)				
Monthly Composite				
A Area	9	$1.19 \pm 0.88 \text{ E-18}$	$-4.44 \pm 4.45 \text{ E-18}$	$-0.15 \pm 1.66 \text{ E-18}$
Burial Ground North	6	$2.02 \pm 0.24 \text{ E-16}$	$1.29 \pm 0.91 \text{ E-18}$	$3.82 \pm 8.03 \text{ E-17}$
Burial Ground South	10	$9.09 \pm 4.81 \text{ E-18}$	$0.00 \pm 1.56 \text{ E-18}$	$2.93 \pm 2.75 \text{ E-18}$
F Area	11	$8.46 \pm 0.80 \text{ E-17}$	$6.02 \pm 3.48 \text{ E-19}$	$1.94 \pm 2.38 \text{ E-17}$
H Area	12	$7.31 \pm 1.03 \text{ E-17}$	$0.76 \pm 1.32 \text{ E-18}$	$1.32 \pm 2.22 \text{ E-17}$
Site Perimeter	46	$5.40 \pm 0.70 \text{ E-17}$	$-2.68 \pm 1.55 \text{ E-18}$	$2.11 \pm 8.07 \text{ E-18}$
25-mile Radius	44	$1.06 \pm 0.18 \text{ E-17}$	$-1.01 \pm 0.18 \text{ E-17}$	$0.79 \pm 1.73 \text{ E-18}$
100-mile Radius	43	$0.54 \pm 2.22 \text{ E-17}$	$-3.75 \pm 2.17 \text{ E-18}$	$0.61 \pm 1.75 \text{ E-18}$

a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-9
Tritium in Atmospheric Moisture

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Tritium ($\mu\text{Ci/mL}$)				
Onsite				
A Area	40	$4.6 \pm 0.97 \text{ E-06}$	$1.80 \pm 8.20 \text{ E-06}$	$1.92 \pm 1.01 \text{ E-06}$
Burial Ground North	22	$5.05 \pm 0.17 \text{ E-05}$	$2.10 \pm 0.86 \text{ E-06}$	$1.76 \pm 1.07 \text{ E-05}$
Burial Ground South	41	$8.21 \pm 0.31 \text{ E-05}$	$7.34 \pm 0.31 \text{ E-06}$	$3.99 \pm 1.85 \text{ E-05}$
F Area	37	$1.85 \pm 0.04 \text{ E-05}$	$1.24 \pm 0.65 \text{ E-06}$	$6.74 \pm 3.16 \text{ E-06}$
H Area	38	$1.94 \pm 0.01 \text{ E-04}$	$2.33 \pm 0.68 \text{ E-06}$	$4.65 \pm 4.26 \text{ E-05}$
Site Perimeter				
Allendale Gate	39	$3.60 \pm 0.17 \text{ E-06}$	$2.60 \pm 2.30 \text{ E-07}$	$1.43 \pm 0.80 \text{ E-06}$
Barnwell Gate	36	$4.55 \pm 2.06 \text{ E-06}$	$-2.20 \pm 6.30 \text{ E-07}$	$1.65 \pm 1.03 \text{ E-06}$
D Area	41	$6.44 \pm 0.29 \text{ E-06}$	$1.90 \pm 6.60 \text{ E-07}$	$3.43 \pm 1.36 \text{ E-06}$
Darkhorse	43	$4.51 \pm 0.36 \text{ E-06}$	$-3.80 \pm 6.90 \text{ E-07}$	$1.85 \pm 1.06 \text{ E-07}$
East Talatha	39	$1.23 \pm 0.12 \text{ E-05}$	$-0.10 \pm 6.40 \text{ E-07}$	$2.30 \pm 2.22 \text{ E-06}$
Greenpond	40	$4.00 \pm 0.92 \text{ E-06}$	$4.80 \pm 6.70 \text{ E-07}$	$1.59 \pm 0.80 \text{ E-06}$
Highway 39	38	$5.28 \pm 0.38 \text{ E-06}$	$2.80 \pm 5.20 \text{ E-07}$	$2.04 \pm 1.27 \text{ E-06}$
Highways 21 & 167	39	$3.49 \pm 0.60 \text{ E-06}$	$4.80 \pm 2.30 \text{ E-07}$	$1.69 \pm 0.70 \text{ E-06}$
Jackson, SC	39	$3.57 \pm 0.67 \text{ E-06}$	$2.20 \pm 2.00 \text{ E-07}$	$1.62 \pm 0.80 \text{ E-06}$
Patterson Mill Rd	41	$4.67 \pm 0.25 \text{ E-06}$	$2.10 \pm 6.40 \text{ E-07}$	$1.56 \pm 0.94 \text{ E-06}$
Road A14	40	$1.50 \pm 0.14 \text{ E-05}$	$5.10 \pm 2.40 \text{ E-07}$	$2.55 \pm 2.34 \text{ E-06}$
Talatha Gate	37	$3.84 \pm 0.92 \text{ E-06}$	$0.00 \pm 6.10 \text{ E-07}$	$1.94 \pm 0.94 \text{ E-06}$
West Jackson	41	$6.86 \pm 0.67 \text{ E-06}$	$4.90 \pm 2.40 \text{ E-07}$	$1.91 \pm 1.12 \text{ E-06}$
Windsor Road	41	$3.49 \pm 0.24 \text{ E-06}$	$1.90 \pm 2.30 \text{ E-07}$	$1.90 \pm 2.30 \text{ E-07}$
25-mile Radius				
Aiken Airport	40	$1.25 \pm 0.06 \text{ E-05}$	$-4.30 \pm 6.90 \text{ E-07}$	$1.41 \pm 1.97 \text{ E-06}$
Aiken State Park	41	$3.08 \pm 0.90 \text{ E-06}$	$-2.90 \pm 6.90 \text{ E-07}$	$9.77 \pm 5.66 \text{ E-07}$
Allendale, SC	41	$3.92 \pm 0.94 \text{ E-06}$	$0.00 \pm 6.60 \text{ E-06}$	$9.17 \pm 6.93 \text{ E-07}$
Augusta, GA	40	$2.73 \pm 0.88 \text{ E-06}$	$1.00 \pm 2.40 \text{ E-07}$	$9.33 \pm 6.13 \text{ E-07}$
Highway 301	39	$3.48 \pm 0.89 \text{ E-06}$	$-1.30 \pm 7.00 \text{ E-07}$	$1.02 \pm 0.76 \text{ E-06}$
Langley, SC	41	$4.04 \pm 0.94 \text{ E-06}$	$-5.90 \pm 6.80 \text{ E-07}$	$1.03 \pm 0.85 \text{ E-06}$
Lees, SC	40	$5.03 \pm 0.98 \text{ E-06}$	$-2.20 \pm 6.90 \text{ E-07}$	$9.56 \pm 8.19 \text{ E-07}$
Olar, SC	39	$5.10 \pm 0.37 \text{ E-06}$	$-4.10 \pm 6.90 \text{ E-07}$	$1.00 \pm 1.02 \text{ E-06}$
Perkins, GA	40	$2.82 \pm 0.87 \text{ E-06}$	$-1.00 \pm 2.30 \text{ E-07}$	$8.76 \pm 6.74 \text{ E-07}$
South Richmond, GA	38	$2.29 \pm 0.86 \text{ E-06}$	$1.60 \pm 2.40 \text{ E-07}$	$9.52 \pm 5.03 \text{ E-07}$
Springfield, SC	41	$3.09 \pm 0.89 \text{ E-06}$	$-2.90 \pm 6.90 \text{ E-07}$	$1.10 \pm 0.76 \text{ E-06}$

Table 7-9
Tritium in Atmospheric Moisture, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Waynesboro, GA	41	$2.53 \pm 0.88 \text{ E-06}$	$-0.20 \pm 2.40 \text{ E-08}$	$9.87 \pm 5.97 \text{ E-07}$
100-mile Radius				
Columbia, SC	5	$1.76 \pm 0.22 \text{ E-06}$	$4.40 \pm 8.10 \text{ E-07}$	$8.00 \pm 5.32 \text{ E-07}$
Greenville, SC	4	$1.80 \pm 0.88 \text{ E-06}$	$-0.40 \pm 1.90 \text{ E-08}$	$7.73 \pm 7.83 \text{ E-07}$
Macon, GA	4	$1.16 \pm 0.85 \text{ E-06}$	$-0.20 \pm 1.80 \text{ E-08}$	$5.83 \pm 5.71 \text{ E-07}$
Savannah, GA	4	$1.71 \pm 0.85 \text{ E-06}$	$5.60 \pm 2.00 \text{ E-07}$	$1.08 \pm 0.52 \text{ E-06}$

Table 7-10
Rainwater Deposition of Radionuclides

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha (pCi/sq m)				
Onsite				
H Area	12	4.21 $\pm$ 0.68 E+01	0.01 $\pm$ 1.90 E+00	1.01 $\pm$ 1.13 E+01
Site Perimeter				
Barnwell Gate	12	1.92 $\pm$ 0.45 E+01	-1.10 $\pm$ 1.69 E+00	6.33 $\pm$ 6.74 E+00
Darkhorse	11	5.82 $\pm$ 0.77 E+01	-2.13 $\pm$ 1.40 E+00	0.81 $\pm$ 1.73 E+01
25-mile Radius				
Olar, SC	12	1.89 $\pm$ 0.62 E+01	-1.97 $\pm$ 1.33 E+00	3.12 $\pm$ 5.83 E+00
100-mile Radius				
Columbia, SC	3	1.94 $\pm$ 0.77 E+01	1.14 $\pm$ 0.67 E+01	1.65 $\pm$ 0.44 E+01
Greenville, SC	3	1.69 $\pm$ 0.66 E+01	-0.43 $\pm$ 4.01 E+00	7.99 $\pm$ 8.65 E+00
Macon, GA	4	5.41 $\pm$ 1.14 E+01	0.05 $\pm$ 3.96 E+00	1.93 $\pm$ 2.52 E+01
Savannah, GA	2	1.00 $\pm$ 0.79 E+01	1.92 $\pm$ 4.35 E+00	5.97 $\pm$ 5.73 E+00
Nonvolatile Beta (pCi/sq m)				
Onsite				
H Area	12	5.01 $\pm$ 0.18 E+02	5.63 $\pm$ 4.85 E+00	1.58 $\pm$ 1.34 E+02
Site Perimeter				
Barnwell Gate	12	2.11 $\pm$ 0.11 E+02	6.11 $\pm$ 4.51 E+00	1.11 $\pm$ 0.74 E+02
Darkhorse	11	4.07 $\pm$ 0.16 E+02	1.66 $\pm$ 0.54 E+01	1.65 $\pm$ 1.44 E+02
25-mile Radius				
Olar, SC	12	5.37 $\pm$ 0.19 E+02	-0.33 $\pm$ 3.93 E+00	1.32 $\pm$ 1.55 E+02
100-mile Radius				
Columbia, SC	3	7.51 $\pm$ 0.31 E+02	3.54 $\pm$ 0.22 E+02	4.92 $\pm$ 2.25 E+02
Greenville, SC	3	3.30 $\pm$ 0.21 E+02	1.02 $\pm$ 0.14 E+02	1.92 $\pm$ 1.21 E+02
Macon, GA	4	7.51 $\pm$ 0.32 E+02	2.63 $\pm$ 1.05 E+01	3.28 $\pm$ 3.05 E+02
Savannah, GA	2	7.51 $\pm$ 0.33 E+02	3.50 $\pm$ 1.07 E+01	3.93 $\pm$ 5.07 E+02
Sr-89,90 (pCi/sq m)				
Onsite				
H Area	2	7.23 $\pm$ 3.29 E+00	-0.27 $\pm$ 5.44 E+00	3.48 $\pm$ 5.30 E+00
Site Perimeter				
Barnwell Gate	2	3.36 $\pm$ 5.84 E+00	-1.39 $\pm$ 6.06 E+00	0.99 $\pm$ 3.36 E+00
Darkhorse	3	3.65 $\pm$ 6.62 E+00	-0.54 $\pm$ 6.04 E+00	1.53 $\pm$ 2.10 E+00
25-mile Radius				
Olar, SC	3	5.37 $\pm$ 5.08 E+00	-6.87 $\pm$ 8.38 E+00	-0.67 $\pm$ 6.12 E+00

Table 7-10
Rainwater Deposition of Radionuclides, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Sr-90 (pCi/sq m)				
Onsite				
H Area	1	0.69 $\pm$ 4.02 E+01	0.69 $\pm$ 4.02 E+01	0.69 $\pm$ 4.02 E+01
Site Perimeter				
Barnwell Gate	1	0.35 $\pm$ 7.54 E+01	0.35 $\pm$ 7.54 E+01	0.35 $\pm$ 7.54 E+01
Darkhorse	1	-0.01 $\pm$ 5.82 E+01	-0.01 $\pm$ 5.82 E+01	-0.01 $\pm$ 5.82 E+01
25-mile Radius				
Olar, SC	1	0.00 $\pm$ 7.45 E+01	0.00 $\pm$ 7.45 E+01	0.00 $\pm$ 7.45 E+01
100-mile Radius				
Columbia, SC	1	0.00 $\pm$ 1.66 E+02	0.00 $\pm$ 1.66 E+02	0.00 $\pm$ 1.66 E+02
Greenville, SC	2	0.03 $\pm$ 1.43 E+02	-0.25 $\pm$ 5.01 E+01	0.50 $\pm$ 4.22 E+00
Macon, GA	2	0.11 $\pm$ 1.06 E+02	0.07 $\pm$ 1.84 E+02	8.82 $\pm$ 2.49 E+00
Savannah, GA	1	-0.32 $\pm$ 6.56 E+01	-0.32 $\pm$ 6.56 E+01	-0.32 $\pm$ 6.56 E+01
Cs-137 (pCi/sq m)				
Onsite				
H Area	9 / 0 ^a			
Site Perimeter				
Barnwell Gate	13 / 0			
Darkhorse	13 / 0			
25-mile Radius				
Olar, SC	11 / 0			
100-mile Radius				
Columbia, SC	3 / 0			
Greenville, SC	4 / 0			
Macon, GA	4 / 0			
Savannah, GA	4 / 0			

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-10
Rainwater Deposition of Radionuclides, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Pu-238 (pCi/sq m)				
Onsite				
H Area	4	1.08 $\pm$ 0.16 E+00	-0.25 $\pm$ 4.93 E-01	2.62 $\pm$ 5.46 E-01
Site Perimeter				
Darkhorse	3	9.79 $\pm$ 5.95 E-02	-5.14 $\pm$ 6.80 E-02	0.69 $\pm$ 7.98 E-02
25-mile Radius				
Olar, SC	4	1.14 $\pm$ 0.72 E-01	-3.08 $\pm$ 4.22 E-02	4.55 $\pm$ 6.31 E-02
100-mile Radius				
Columbia, SC	1	-9.40 $\pm$ 4.39 E-02	-9.40 $\pm$ 4.39 E-02	-9.40 $\pm$ 4.39 E-02
Greenville, SC	2	2.33 $\pm$ 0.76 E-01	-5.14 $\pm$ 8.10 E-02	0.91 $\pm$ 2.01 E-01
Macon, GA	2	1.20 $\pm$ 1.30 E-01	5.67 $\pm$ 5.30 E-02	8.84 $\pm$ 4.48 E-02
Savannah, GA	1	-1.04 $\pm$ 0.53 E-01	-1.04 $\pm$ 0.53 E-01	-1.04 $\pm$ 0.53 E-01
Pu-239 (pCi/sq m)				
Onsite				
H Area	4	1.51 $\pm$ 0.18 E+00	-0.61 $\pm$ 1.06 E-01	4.36 $\pm$ 7.30 E-01
Site Perimeter				
Darkhorse	3	9.40 $\pm$ 9.40 E-02	0.00 $\pm$ 2.02 E-02	3.99 $\pm$ 4.86 E-02
25-mile Radius				
Olar, SC	4	9.47 $\pm$ 5.80 E-02	-1.82 $\pm$ 3.15 E-02	2.84 $\pm$ 4.98 E-02
100-mile Radius				
Columbia, SC	1	4.26 $\pm$ 7.35 E-02	4.26 $\pm$ 7.35 E-02	4.26 $\pm$ 7.35 E-02
Greenville, SC	2	1.70 $\pm$ 0.63 E-01	-7.99 $\pm$ 8.00 E-02	0.45 $\pm$ 1.77 E-01
Macon, GA	2	1.14 $\pm$ 0.81 E-01	1.75 $\pm$ 3.91 E-02	6.57 $\pm$ 6.82 E-02
Savannah, GA	1	1.48 $\pm$ 0.74 E-01	1.48 $\pm$ 0.74 E-01	1.48 $\pm$ 0.74 E-01

Table 7-11
Tritium in Rainwater

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Tritium ($\mu\text{Ci/mL}$)				
Site Perimeter				
Darkhorse	22	$4.34 \pm 0.12 \text{ E-06}$	$3.94 \pm 0.67 \text{ E-08}$	$9.46 \pm 9.44 \text{ E-07}$
100-mile Radius				
Columbia, SC	4	$5.23 \pm 1.06 \text{ E-07}$	$0.28 \pm 1.30 \text{ E-07}$	$2.50 \pm 2.30 \text{ E-07}$
Greenville, SC	1	$2.42 \pm 1.46 \text{ E-07}$	$2.42 \pm 1.46 \text{ E-07}$	$2.42 \pm 1.46 \text{ E-07}$
Macon, GA	2	$0.80 \pm 4.10 \text{ E-07}$	$-1.69 \pm 0.98 \text{ E-07}$	$-0.45 \pm 1.76 \text{ E-07}$
Savannah, GA	2	$0.25 \pm 1.30 \text{ E-07}$	$-1.22 \pm 1.21 \text{ E-07}$	$-0.48 \pm 1.03 \text{ E-07}$

Table 7-12
Radioactivity in Soil

Location	pCi/g $\pm$ σ ; dry weight; 0-8 cm depth			
	Sr-90	Cs-137	Pu-238	Pu-239
F Area				
2,000 ft. East	$2.54 \pm 1.98 \text{ E-02}$	$9.59 \pm 0.49 \text{ E-01}$	$4.43 \pm 0.51 \text{ E-02}$	$2.98 \pm 0.13 \text{ E-01}$
2,000 ft. West	$1.33 \pm 1.74 \text{ E-02}$	$8.01 \pm 0.42 \text{ E-01}$	*	*
2,000 ft. North	$-0.20 \pm 1.81 \text{ E-02}$	—	$7.03 \pm 1.81 \text{ E-03}$	$4.96 \pm 1.62 \text{ E-03}$
2,000 ft. South	$8.79 \pm 1.72 \text{ E-02}$	*		
H Area				
2,000 ft. East	$1.52 \pm 0.17 \text{ E-02}$	$4.30 \pm 0.29 \text{ E-01}$	$1.42 \pm 0.19 \text{ E-02}$	$4.61 \pm 0.32 \text{ E-02}$
2,000 ft. West	$-1.90 \pm 0.15 \text{ E-02}$	$9.73 \pm 0.49 \text{ E-01}$	$3.62 \pm 0.33 \text{ E-02}$	$1.01 \pm 0.05 \text{ E-01}$
2,000 ft. North	$1.01 \pm 0.14 \text{ E-02}$	$3.52 \pm 0.27 \text{ E-01}$	*	*
2,000 ft. South	$4.40 \pm 0.17 \text{ E-02}$	$1.84 \pm 0.07 \text{ E+00}$	$4.41 \pm 0.24 \text{ E-02}$	$1.04 \pm 0.04 \text{ E-01}$
S Area				
#1	$-1.12 \pm 0.09 \text{ E-02}$	$7.80 \pm 0.43 \text{ E-01}$	$8.58 \pm 0.53 \text{ E-03}$	$3.94 \pm 0.11 \text{ E-02}$
#2	$0.73 \pm 1.04 \text{ E-03}$	—	$1.92 \pm 1.39 \text{ E-03}$	$2.92 \pm 1.81 \text{ E-03}$
#3	$-4.73 \pm 0.81 \text{ E-03}$	$1.95 \pm 0.23 \text{ E-01}$	$3.89 \pm 0.13 \text{ E-02}$	$6.32 \pm 0.17 \text{ E-02}$
#4	$-8.58 \pm 0.83 \text{ E-03}$	—	$1.24 \pm 0.07 \text{ E-02}$	$6.70 \pm 0.50 \text{ E-03}$
Z Area				
#1	$-7.01 \pm 1.12 \text{ E-03}$	—	$2.61 \pm 0.39 \text{ E-03}$	$3.49 \pm 0.42 \text{ E-03}$
#3	$-4.24 \pm 1.06 \text{ E-03}$	—	$6.70 \pm 4.31 \text{ E-04}$	$2.61 \pm 0.58 \text{ E-03}$
#5	$-6.42 \pm 0.93 \text{ E-03}$	$9.76 \pm 2.14 \text{ E-02}$	$1.05 \pm 0.28 \text{ E-03}$	$2.52 \pm 0.39 \text{ E-03}$
#7	$-9.39 \pm 1.00 \text{ E-03}$	—	$6.40 \pm 0.56 \text{ E-03}$	$3.92 \pm 0.43 \text{ E-03}$
Site Perimeter				
NE Quadrant	$3.67 \pm 1.61 \text{ E-02}$	$6.74 \pm 0.39 \text{ E-01}$	$2.39 \pm 0.78 \text{ E-03}$	$3.26 \pm 0.28 \text{ E-02}$
NW Quadrant	$-0.09 \pm 1.43 \text{ E-02}$	$9.81 \pm 0.51 \text{ E-01}$	*	*
SE Quadrant	$-1.42 \pm 1.34 \text{ E-02}$	$4.79 \pm 0.39 \text{ E-01}$	*	*
SW Quadrant	$0.47 \pm 1.45 \text{ E-02}$	$5.99 \pm 0.47 \text{ E-01}$	$1.66 \pm 0.45 \text{ E-03}$	$2.10 \pm 0.15 \text{ E-02}$
100-mile Radius				
Clinton, SC	$3.32 \pm 1.54 \text{ E-02}$	$4.02 \pm 0.39 \text{ E-01}$	$2.72 \pm 1.46 \text{ E-04}$	$8.53 \pm 0.57 \text{ E-03}$
Savannah, GA	$-0.04 \pm 1.40 \text{ E-02}$	$6.39 \pm 0.47 \text{ E-01}$	$5.45 \pm 1.51 \text{ E-04}$	$1.09 \pm 0.05 \text{ E-02}$

* No samples counted.

— No quantifiable activity.

Table 7-13
Onsite TLD Penetrating Radiation Measurements

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
100-C AREA							
C-AREA CORNER 1	4	43	± 8	36	± 6	40	-
C-AREA CORNER 2	4	48	± 9	41	± 7	45	-
C-AREA CORNER 3	4	50	± 9	44	± 8	47	-
C-AREA CORNER 4	4	50	± 9	44	± 8	47	-
100-K AREA							
K-AREA CORNER 1	4	67	± 12	60	± 11	63	-
K-AREA CORNER 2	4	46	± 8	40	± 7	42	-
K-AREA CORNER 3	4	80	± 14	72	± 13	77	-
K-AREA CORNER 4	4	60	± 11	49	± 9	55	-
100-L AREA							
L-AREA CORNER 1	4	56	± 10	48	± 9	51	-
L-AREA CORNER 2	4	54	± 10	45	± 8	49	-
L-AREA CORNER 3	4	54	± 10	47	± 8	51	-
L-AREA CORNER 4	4	62	± 11	54	± 10	58	-
100-P AREA							
P-AREA CORNER 1	4	62	± 11	54	± 10	57	-
P-AREA CORNER 2	4	48	± 9	41	± 7	45	-
P-AREA CORNER 3	4	56	± 10	49	± 9	54	-
P-AREA CORNER 4	4	60	± 11	52	± 9	57	-
100-R AREA							
R-AREA CORNER 1	4	56	± 10	43	± 8	50	-
R-AREA CORNER 2	4	66	± 12	55	± 10	61	-
R-AREA CORNER 3	4	42	± 8	37	± 7	39	-
R-AREA CORNER 4	4	60	± 11	52	± 9	57	-
R-AREA CORNER 5	4	53	± 10	46	± 8	50	-
R-AREA CORNER 6	4	52	± 9	42	± 8	46	-
R-AREA CORNER 7	4	54	± 10	46	± 8	50	-
200-F AREA							
F-AREA CORNER 1	4	63	± 11	47	± 9	55	-
F-AREA CORNER 2	4	68	± 12	51	± 9	63	-
F-AREA CORNER 3	4	73	± 13	59	± 11	68	-
F-AREA CORNER 4	4	72	± 13	57	± 10	66	-
F-AREA CORNER 5	4	132	± 24	108	± 19	123	-
F-AREA CORNER 6	4	86	± 15	69	± 12	80	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-13
Onsite TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
200-H AREA							
H-AREA CORNER 1	4	71	± 13	59	± 11	66	-
H-AREA CORNER 2	4	104	± 19	70	± 13	87	-
H-AREA CORNER 3	4	67	± 12	56	± 10	61	-
H-AREA CORNER 4	4	146	± 26	121	± 22	138	-
H-AREA CORNER 5	3	155	± 28	132	± 24	147	-
H-AREA CORNER 6	4	74	± 13	60	± 11	69	-
H-AREA CORNER 7	4	66	± 12	54	± 10	62	-
H-AREA CORNER 8	4	74	± 13	61	± 11	71	-
200-Z AREA							
Z-AREA TLD 1	4	51	± 9	41	± 7	47	-
Z-AREA TLD 2	4	50	± 9	38	± 7	43	-
Z-AREA TLD 3	4	50	± 9	40	± 7	45	-
Z-AREA TLD 4	4	48	± 9	42	± 7	44	-
300-M AREA							
M-AREA CORNER 1	4	81	± 15	60	± 11	72	-
M-AREA CORNER 2	4	50	± 9	40	± 7	46	-
M-AREA CORNER 3	4	95	± 17	80	± 14	88	-
M-AREA CORNER 4	4	59	± 11	44	± 8	53	-
M-AREA CORNER 5	4	75	± 14	52	± 9	64	-
M-AREA CORNER 6	4	50	± 9	40	± 7	47	-
M-AREA CORNER 7	4	77	± 14	60	± 11	71	-
M-AREA CORNER 8	4	101	± 18	72	± 13	90	-
400-D AREA							
D-AREA CORNER 1	4	55	± 10	41	± 7	48	-
D-AREA CORNER 2	4	46	± 8	37	± 7	40	-
D-AREA CORNER 3	4	61	± 11	46	± 8	55	-
D-AREA CORNER 4	4	68	± 12	52	± 10	61	-
D-AREA CORNER 5	4	52	± 9	38	± 7	45	-
D-AREA CORNER 6	4	37	± 7	12	± 2	24	-
CENTRAL SHOPS							
CENTRAL SHOPS 1	4	93	± 17	76	± 14	82	-
CENTRAL SHOPS 2	4	80	± 14	67	± 12	76	-
CENTRAL SHOPS 3	4	50	± 9	42	± 8	46	-
CENTRAL SHOPS 4	4	116	± 21	97	± 17	109	-
CENTRAL SHOPS 5	4	425	± 77	342	± 61	395	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-13
Onsite TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
CLASSIFICATION							
618-G 1	4	54	± 10	45	± 8	50	-
618-G 2	4	48	± 9	39	± 7	43	-
618-G 3	4	54	± 10	48	± 9	50	-
618-G 4	4	42	± 8	37	± 7	40	-
DWPF							
DEFENSE WASTE 1	4	71	± 13	61	± 11	65	-
DEFENSE WASTE 2	4	101	± 18	88	± 16	97	-
DEFENSE WASTE 3	4	92	± 17	79	± 14	88	-
DEFENSE WASTE 4	4	82	± 15	62	± 11	70	-
NPR							
NPR N	1	37	± 7	37	± 7	37	-
NPR NE	1	73	± 15	73	± 15	73	-
NPR E	1	66	± 11	66	± 11	66	-
NPR SE	1	73	± 15	73	± 15	73	-
NPR S	1	33	± 7	33	± 7	33	-
NPR SW	1	84	± 15	84	± 15	84	-
NPR W	1	37	± 7	37	± 7	37	-
NPR NW	1	80	± 15	80	± 15	80	-
GEORGIA POWER							
POWER 1 HIGH	4	34	± 6	29	± 5	31	-
POWER 1 LOW	4	37	± 7	28	± 5	33	-
POWER 2 HIGH	4	42	± 8	34	± 6	39	-
POWER 2 LOW	4	44	± 8	34	± 6	40	-
POWER 3 HIGH	4	42	± 8	35	± 6	40	-
POWER 3 LOW	4	41	± 7	35	± 6	38	-
POWER 4 HIGH	4	40	± 7	35	± 6	38	-
POWER 4 LOW	4	41	± 7	32	± 6	38	-
POWER 5 HIGH	4	38	± 7	24	± 4	32	-
POWER 5 LOW	4	35	± 6	30	± 5	33	-
PLANT VOGTLE							
VOGTLE LOCATION 1	4	65	± 12	26	± 5	44	-
VOGTLE LOCATION 2	4	47	± 9	5	± 1	25	-
VOGTLE LOCATION 3	4	49	± 9	5	± 1	28	-
VOGTLE LOCATION 4	4	55	± 10	12	± 2	33	-
VOGTLE LOCATION 5	4	80	± 14	38	± 7	59	-
VOGTLE LOCATION 6	4	57	± 10	16	± 3	36	-
VOGTLE LOCATION 7	4	54	± 10	10	± 2	32	-
VOGTLE LOCATION 8	4	53	± 10	10	± 2	32	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-13
Onsite TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
RAILROAD AT ROAD F							
ROAD E & F 1	4	65	± 12	52	± 9	60	-
ROAD E & F 2	4	67	± 12	55	± 10	63	-
SOLID WASTE DISPOSAL FACILITY							
643-7G 1	4	247	± 44	65	± 12	178	-
643-7G 2	4	74	± 13	62	± 11	70	-
643-7G 3	4	121	± 22	88	± 16	103	-
643-7G 4	3	428	± 77	338	± 61	381	-
643-G 1	4	59	± 11	50	± 9	54	-
643-G 2	4	87	± 16	67	± 12	80	-
643-G 3	4	480	± 86	419	± 75	459	-
643-G 4	4	104	± 19	94	± 17	100	-
TECHNICAL AREA							
TECHNICAL AREA 1	4	66	± 12	42	± 8	56	-
TECHNICAL AREA 2	4	89	± 16	65	± 12	80	-
TECHNICAL AREA 3	4	67	± 12	53	± 10	62	-
TECHNICAL AREA 4	4	81	± 14	66	± 12	76	-
TECHNICAL AREA 5	4	72	± 13	53	± 10	65	-
TECHNICAL AREA 6	4	68	± 12	60	± 11	65	-
TECHNICAL AREA 7	4	71	± 13	64	± 11	68	-
TECHNICAL AREA 8	4	60	± 11	51	± 9	57	-
TNX AREA							
TNX AREA 1	4	42	± 8	26	± 5	34	-
TNX AREA 2	4	100	± 18	57	± 10	74	-
TNX AREA 3	4	62	± 11	50	± 9	57	-
TNX AREA 4	4	95	± 17	81	± 15	89	-
TRAINING CENTER							
TRAINING CENTER 1	4	286	± 51	235	± 42	267	-
TRAINING CENTER 2	4	54	± 10	44	± 8	51	-
TRAINING CENTER 3	4	50	± 9	43	± 8	48	-
TRAINING CENTER 4	4	53	± 10	45	± 8	49	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-14
Site Perimeter TLD Penetrating Radiation Measurements

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
NEAR ALLIED GENERAL							
ALLIED GENERAL 1	4	60	± 11	36	± 7	48	-
ALLIED GENERAL 2	4	48	± 9	25	± 4	33	-
ALLIED GENERAL 3	4	54	± 10	29	± 5	38	-
ALLIED GENERAL 4	4	51	± 9	24	± 4	34	-
NEAR PLANT VOGTLE							
PUMPHOUSE ROAD 1		54	± 10	44	± 8	50	-
PUMPHOUSE ROAD 2	4	52	± 9	42	± 8	47	-
PUMPHOUSE ROAD 3	4	29	± 5	26	± 5	28	-
PUMPHOUSE ROAD 4	4	35	± 6	30	± 5	32	-
PUMPHOUSE ROAD 5	4	60	± 11	49	± 9	55	-
PUMPHOUSE ROAD 6	4	51	± 9	43	± 8	47	-
SITE PERIMETER							
SITE PERIMETER 1.00	4	38	± 7	28	± 5	33	-
SITE PERIMETER 1.25	4	40	± 7	34	± 6	37	-
SITE PERIMETER 1.50	4	41	± 7	36	± 6	39	-
SITE PERIMETER 1.75	4	34	± 6	28	± 5	32	-
SITE PERIMETER 2.00	4	69	± 12	57	± 10	64	-
SITE PERIMETER 2.25	4	48	± 9	40	± 7	45	-
SITE PERIMETER 2.50	4	42	± 8	36	± 6	40	-
SITE PERIMETER 2.75	4	35	± 6	30	± 5	34	-
SITE PERIMETER 3.00	4	39	± 7	33	± 6	37	-
SITE PERIMETER 3.25	4	37	± 7	30	± 5	35	-
SITE PERIMETER 3.50	4	37	± 7	30	± 5	35	-
SITE PERIMETER 3.75	4	55	± 10	48	± 9	52	-
SITE PERIMETER 4.00	4	53	± 10	43	± 8	49	-
SITE PERIMETER 4.25	4	40	± 7	35	± 6	37	-
SITE PERIMETER 4.50	4	43	± 8	35	± 6	39	-
SITE PERIMETER 4.75	4	40	± 7	30	± 5	37	-
SITE PERIMETER 5.00	4	51	± 9	44	± 8	49	-
SITE PERIMETER 5.25	4	51	± 9	40	± 7	46	-
SITE PERIMETER 5.50	4	58	± 11	46	± 8	54	-
SITE PERIMETER 5.75	4	72	± 13	55	± 10	64	-
SITE PERIMETER 6.00	4	75	± 13	62	± 11	70	-
SITE PERIMETER 6.25	4	80	± 14	66	± 12	72	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-14
Site Perimeter TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SITE PERIMETER, CONT'D.							
SITE PERIMETER 6.50	4	55	± 10	45	± 8	51	-
SITE PERIMETER 6.75	4	38	± 7	29	± 5	34	-
SITE PERIMETER 7.00	4	55	± 10	43	± 8	49	-
SITE PERIMETER 7.25	4	64	± 11	49	± 9	56	-
SITE PERIMETER 7.50	4	49	± 9	43	± 8	45	-
SITE PERIMETER 7.75	4	69	± 12	43	± 8	52	-
SITE PERIMETER 8.00	4	43	± 8	36	± 7	40	-
SITE PERIMETER 8.25	4	55	± 10	46	± 8	51	-
SITE PERIMETER 8.50	4	52	± 9	45	± 8	49	-
SITE PERIMETER 8.75	4	49	± 9	41	± 7	45	-
SITE PERIMETER 9.00	4	51	± 9	41	± 7	47	-
SITE PERIMETER 9.25	4	40	± 7	31	± 6	35	-
SITE PERIMETER 9.50	4	41	± 7	34	± 6	37	-
SITE PERIMETER 9.75	4	40	± 7	33	± 6	36	-
SITE PERIMETER 10.00	4	33	± 6	28	± 5	30	-
SITE PERIMETER 11.00	4	37	± 7	34	± 6	35	-
SITE PERIMETER 12.00	4	40	± 7	33	± 6	36	-
SITE PERIMETER 13.00	4	36	± 6	29	± 5	32	-
SITE PERIMETER 14.00	4	44	± 8	37	± 7	41	-
SITE PERIMETER 15.00	4	58	± 10	42	± 8	47	-
SITE PERIMETER 16.00	4	60	± 11	50	± 9	56	-
SITE PERIMETER 17.00	4	64	± 11	55	± 10	61	-
SITE PERIMETER 18.00	4	49	± 9	36	± 7	44	-
SITE PERIMETER 19.00	4	48	± 9	40	± 7	45	-
SITE PERIMETER 20.00	4	91	± 16	74	± 13	79	-
SITE PERIMETER 21.00	4	56	± 10	33	± 6	41	-
SITE PERIMETER 22.00	4	61	± 11	37	± 7	46	-
SITE PERIMETER 23.00	3	64	± 11	42	± 8	51	-
SITE PERIMETER 24.00	4	58	± 10	36	± 7	43	-
SITE PERIMETER 25.00	4	55	± 10	34	± 6	40	-
SITE PERIMETER 26.00	4	53	± 9	28	± 5	37	-
SITE PERIMETER 27.00	4	62	± 11	37	± 7	46	-
SITE PERIMETER 28.00	4	59	± 11	36	± 7	45	-
SITE PERIMETER 29.00	4	49	± 9	25	± 5	35	-
SITE PERIMETER 30.00	4	65	12	43	± 8	49	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-14
Site Perimeter TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SITE PERIMETER, CONT'D.							
SITE PERIMETER 31.00	3	146	± 26	37	± 7	73	-
SITE PERIMETER 32.00	4	58	± 10	35	± 6	43	-
SITE PERIMETER 33.00	4	58	± 10	34	± 6	45	-
SITE PERIMETER 34.00	4	61	± 11	37	± 7	46	-
SITE PERIMETER 35.00	4	54	± 10	30	± 5	40	-
SITE PERIMETER 36.00	4	67	± 12	44	± 8	52	-
SITE PERIMETER 37.00	4	62	± 11	38	± 7	49	-
SITE PERIMETER 38.00	4	73	± 13	50	± 9	59	-
SITE PERIMETER 39.00	4	47	± 8	42	± 7	44	-
SITE PERIMETER 40.00	4	37	± 7	33	± 6	35	-
SITE PERIMETER 41.00	4	40	± 7	33	± 6	36	-
SITE PERIMETER 42.00	4	51	± 9	41	± 7	45	-
SITE PERIMETER 43.00	4	56	± 10	50	± 9	54	-
SITE PERIMETER 44.00	4	43	± 8	37	± 7	39	-
SITE PERIMETER 45.00	4	38	± 7	35	± 6	37	-
SITE PERIMETER 46.00	4	46	± 8	41	± 7	43	-
SITE PERIMETER 47.00	4	46	± 8	38	± 7	41	-
SITE PERIMETER 48.00	4	43	± 8	36	± 6	39	-
SITE PERIMETER 49.00	4	77	± 14	66	± 12	71	-
SITE PERIMETER 50.00	4	40	± 7	32	± 6	36	-
SITE PERIMETER 51.00	4	44	± 8	36	± 7	39	-
SITE PERIMETER 52.00	4	46	± 8	41	± 7	44	-
SITE PERIMETER 53.00	4	39	± 7	31	± 6	34	-
SITE PERIMETER 54.00	4	32	± 6	25	± 5	29	-
SITE PERIMETER 55.00	4	27	± 5	23	± 4	24	-
SITE PERIMETER 56.00	4	31	± 6	27	± 5	28	-
SITE PERIMETER 57.00	4	33	± 6	28	± 5	30	-
SITE PERIMETER 57.25	4	40	± 7	33	± 6	36	-
SITE PERIMETER 57.50	4	40	± 7	29	± 5	33	-
SITE PERIMETER 57.75	4	37	± 7	32	± 6	35	-
SITE PERIMETER 58.00	4	53	± 9	47	± 9	48	-
SITE PERIMETER 58.25	4	40	± 7	34	± 6	37	-
SITE PERIMETER 58.50	4	39	± 7	31	± 6	35	-
SITE PERIMETER 58.75	4	44	± 8	38	± 7	40	-
SITE PERIMETER 59.00	4	39	± 7	32	± 6	35	-
SITE PERIMETER 59.25	4	43	± 8	37	± 7	40	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-14
Site Perimeter TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SITE PERIMETER, CONT'D.							
SITE PERIMETER 59.50	4	57	± 10	48	± 9	52	-
SITE PERIMETER 59.75	4	46	± 8	38	± 7	41	-
SITE PERIMETER 60.00	4	52	± 9	45	± 8	47	-
SITE PERIMETER 60.25	4	36	± 7	31	± 5	33	-
SITE PERIMETER 60.50	4	49	± 9	28	± 5	34	-
SITE PERIMETER 60.75	4	38	± 7	31	± 6	33	-
SITE PERIMETER 61.00	4	42	± 8	33	± 6	37	-
SITE PERIMETER 61.25	4	45	± 8	37	± 7	40	-
SITE PERIMETER 61.50	4	38	± 7	30	± 5	34	-
SITE PERIMETER 61.75	4	40	± 7	26	± 5	34	-
SITE PERIMETER 62.00	4	38	± 7	35	± 6	36	-
SITE PERIMETER 62.25	4	31	± 6	30	± 5	30	-
SITE PERIMETER 62.50	4	44	± 8	38	± 7	41	-
SITE PERIMETER 62.75	4	62	± 11	56	± 10	59	-
SITE PERIMETER 63.00	4	47	± 8	31	± 6	39	-
SITE PERIMETER 63.25	4	36	± 7	30	± 5	34	-
SITE PERIMETER 63.50	4	48	± 9	32	± 6	40	-
SITE PERIMETER 63.75	4	35	± 6	30	± 5	33	-
SITE PERIMETER 64.00	4	39	± 7	28	± 5	34	-
SITE PERIMETER 64.25	4	33	± 6	28	± 5	30	-
SITE PERIMETER 64.50	4	37	± 7	31	± 6	33	-
SITE PERIMETER 64.75	4	37	± 7	28	± 5	33	-
SITE PERIMETER 65.00	4	43	± 8	34	± 6	40	-
SITE PERIMETER 65.25	4	57	± 10	45	± 8	51	-
SITE PERIMETER 65.50	4	75	± 13	55	± 10	66	-
SITE PERIMETER 65.75	4	55	± 10	47	± 8	51	-
SITE PERIMETER 66.00	4	77	± 14	54	± 10	66	-
SITE PERIMETER 66.25	4	77	± 14	54	± 10	66	-
SITE PERIMETER 66.50	4	75	± 14	58	± 10	68	-
SITE PERIMETER 66.75	4	53	± 10	39	± 7	47	-
SITE PERIMETER 67.00	4	43	± 8	32	± 6	38	-
SITE PERIMETER 67.25	4	52	± 9	41	± 7	47	-
SITE PERIMETER 67.50	4	56	± 10	40	± 7	48	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-14
Site Perimeter TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SITE PERIMETER, CONT'D.							
SITE PERIMETER 67.75	4	36	± 6	26	± 5	31	-
SITE PERIMETER 68.00	4	36	± 7	28	± 5	33	-
SITE PERIMETER 68.25	4	34	± 6	29	± 5	32	-
SITE PERIMETER 68.50	4	51	± 9	37	± 7	44	-
SITE PERIMETER 68.75	4	53	± 9	44	± 8	49	-
SITE PERIMETER 69.00	4	69	± 13	48	± 9	60	-
SITE PERIMETER 69.25	4	38	± 7	27	± 5	33	-
SITE PERIMETER 69.50	4	45	± 8	32	± 6	39	-
SITE PERIMETER 69.75	4	51	± 9	35	± 6	44	-
SITE PERIMETER 70.00	4	45	± 8	32	± 6	39	-
SITE PERIMETER 70.25	4	33	± 6	27	± 5	30	-
SITE PERIMETER 70.50	4	37	± 7	32	± 6	35	-
SITE PERIMETER 70.75	4	50	± 9	40	± 7	45	-
SITE PERIMETER 71.00	4	43	± 8	29	± 5	37	-
SITE PERIMETER 71.25	4	56	± 10	41	± 7	50	-
SITE PERIMETER 71.50	4	49	± 9	38	± 7	44	-
SITE PERIMETER 71.75	4	53	± 10	40	± 7	47	-
SITE PERIMETER 72.00	4	48	± 9	34	± 6	41	-
SITE PERIMETER 72.25	4	41	± 7	31	± 6	36	-
SITE PERIMETER 72.50	4	41	± 7	33	± 6	37	-
SITE PERIMETER 72.75	4	41	± 7	32	± 6	36	-
SITE PERIMETER 73.00	4	38	± 7	28	± 5	33	-
SITE PERIMETER 73.25	4	44	± 8	34	± 6	39	-
SITE PERIMETER 73.50	4	47	± 8	33	± 6	40	-
SITE PERIMETER 73.75	4	37	± 7	32	± 6	34	-
SITE PERIMETER 74.00	4	38	± 7	28	± 5	33	-
SITE PERIMETER 74.25	4	31	± 6	26	± 5	28	-
SITE PERIMETER 74.50	4	29	± 5	22	± 4	25	-
SITE PERIMETER 74.75	4	34	± 6	26	± 5	30	-
SITE PERIMETER 75.00	4	35	± 6	24	± 4	30	-
SITE PERIMETER 75.25	4	37	± 7	30	± 5	33	-
SITE PERIMETER 75.50	4	27	± 5	21	± 4	24	-
SITE PERIMETER 75.75	4	31	± 6	23	± 4	27	-
SITE PERIMETER 76.00	4	34	± 6	26	± 5	30	-
SITE PERIMETER 76.25	4	40	± 7	34	± 6	37	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-14
Site Perimeter TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SITE PERIMETER, CONT'D.							
SITE PERIMETER 76.50	4	39	± 7	26	± 5	32	-
SITE PERIMETER 76.75	4	36	± 6	27	± 5	32	-
SITE PERIMETER 77.00	4	38	± 7	32	± 6	35	-
SITE PERIMETER 78.00	4	46	± 8	34	± 6	39	-
SITE PERIMETER 79.00	2	43	± 8	36	± 7	39	-
SITE PERIMETER 79.25	4	45	± 8	35	± 6	40	-
SITE PERIMETER 79.50	4	51	± 9	38	± 7	45	-
SITE PERIMETER 79.75	4	55	± 10	46	± 8	51	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-15
Concentric Ring TLD Penetrating Radiation Measurements

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
ONSITE							
BURIAL GROUND N	4	95	± 17	79	± 14	87	-
BURIAL GROUND S	4	59	± 11	52	± 9	56	-
F AREA	4	87	± 16	77	± 14	82	-
H AREA	4	77	± 14	56	± 10	69	-
SITE PERIMETER							
A AREA	4	65	± 12	54	± 10	60	-
ALLENDALE GATE	4	30	± 5	24	± 4	27	-
BARNWELL GATE	4	49	± 9	43	± 8	47	-
D AREA	4	46	± 8	39	± 7	43	-
DARKHORSE	4	51	± 9	38	± 7	44	-
EAST TALATHA	4	37	± 7	29	± 5	34	-
GREENPOND	4	43	± 8	32	± 6	38	-
HIGHWAY 39	4	44	± 8	36	± 6	42	-
HIGHWAYS 21 & 167	4	71	± 13	59	± 11	67	-
JACKSON, SC	4	53	± 10	42	± 8	48	-
PATTERSON MILL RD	3	126	± 23	38	± 7	68	-
ROAD A14	4	44	± 8	36	± 7	41	-
TALATHA GATE	4	52	± 9	42	± 8	47	-
WEST JACKSON	4	65	± 12	53	± 10	60	-
WINDSOR ROAD	4	42	± 8	33	± 6	39	-
25-MILE RADIUS							
AIKEN AIRPORT	4	50	± 9	44	± 8	48	-
AIKEN STATE PARK	4	35	± 6	28	± 5	33	-
ALLENDALE, SC	4	49	± 9	39	± 7	44	-
AUGUSTA, GA	4	61	± 11	52	± 9	57	-
HIGHWAY 301	4	66	± 12	50	± 9	59	-
LANGLEY, SC	4	70	± 13	60	± 11	67	-
LEES, SC	4	38	± 7	28	± 5	33	-
OLAR, SC	4	42	± 8	35	± 6	38	-
PERKINS, SC	4	42	± 8	36	± 6	40	-
SOUTH RICHMOND	4	71	± 13	64	± 12	68	-
SPRINGFIELD, GA	4	79	± 14	66	± 12	74	-
WAYNESBORO, GA	3	58	± 10	55	± 10	57	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-15
Concentric Ring TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
100-MILE RADIUS							
COLUMBIA, SC	4	77	± 14	62	± 11	68	-
COLUMBIA II	4	79	± 14	59	± 11	70	-
GREENVILLE, SC	4	96	± 17	83	± 15	91	-
GREENVILLE II	4	96	± 17	84	± 15	91	-
MACON, GA	4	95	± 17	62	± 11	82	-
MACON II	4	96	± 17	72	± 13	83	-
SAVANNAH, GA	4	43	± 8	37	± 7	41	-
SAVANNAH II	4	40	± 7	35	± 6	38	-

- Insufficient data; standard deviation not calculated for <5 samples.

Table 7-16
South Carolina TLD Penetrating Radiation Measurements

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SOUTH CAROLINA CITIES AND TOWNS							
AIKEN							
LAURENS ST I	4	111	± 20	83	± 15	100	-
LAURENS ST O	4	69	± 12	60	± 11	66	-
SILVER BLUFF RD I	4	77	± 14	58	± 11	69	-
SILVER BLUFF RD O	4	81	± 15	61	± 11	72	-
ALLENDALE I	4	60	± 11	44	± 8	53	-
ALLENDALE O	4	44	± 8	40	± 7	42	-
BARNWELL I	4	60	± 11	52	± 9	57	-
BARNWELL O	4	82	± 15	71	± 13	78	-
BATESBURG I	4	85	± 15	71	± 13	77	-
BATESBURG O	4	101	± 18	74	± 13	93	-
BEECH ISLAND I	4	72	± 13	60	± 11	67	-
BEECH ISLAND O	4	93	± 17	79	± 14	86	-
BLACKVILLE I	4	32	± 6	23	± 4	28	-
BLACKVILLE O	4	73	± 13	64	± 12	69	-
COLUMBIA							
ATLAS ST I	4	133	± 24	102	± 18	114	-
ATLAS ST O	4	91	± 16	67	± 12	76	-
DENTSVILLE I	4	93	± 17	76	± 14	84	-
DENTSVILLE O	4	104	± 19	80	± 14	88	-
EAU CLAIRE I	4	119	± 21	89	± 16	99	-
EAU CLAIRE O	4	88	± 16	68	± 12	75	-
FIRE HDQTRS I	4	135	± 24	119	± 21	124	-
FIRE HDQTRS O	4	94	± 17	77	± 14	83	-
HARDEN ST I	4	120	± 22	100	± 18	108	-
HARDEN ST O	4	97	± 17	78	± 14	84	-
INDUSTRIAL PARK I	4	135	± 24	113	± 20	122	-
INDUSTRIAL PARK O	4	90	± 16	69	± 12	80	-
NORTH COLUMBIA I	4	161	± 29	145	± 26	154	-
NORTH COLUMBIA O	4	83	± 15	62	± 11	70	-
SHANDON ST I	4	82	± 15	59	± 11	68	-
SHANDON ST O	4	81	± 15	66	± 12	71	-
ST ANDREWS I	4	100	± 18	72	± 13	82	-
ST ANDREWS O	4	91	± 16	72	± 13	80	-

- Insufficient data; standard deviation not calculated for <5 samples.
I Represents measurements taken from TLDs placed inside of buildings.
O Represents measurements taken from TLDs placed outside of buildings.

Table 7-16
South Carolina TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SOUTH CAROLINA CITIES AND TOWNS, CONT'D.							
COUCHTON I	4	59	± 11	44	± 8	53	-
COUCHTON O	4	108	± 19	72	± 13	85	-
EDGEFIELD I	4	75	± 13	45	± 8	58	-
EDGEFIELD O	4	72	± 13	57	± 10	63	-
ESTILL I	4	63	± 11	53	± 10	58	-
ESTILL O	4	81	± 15	70	± 13	76	-
GRANITEVILLE I	4	71	± 13	51	± 9	62	-
GRANITEVILLE O	4	63	± 11	55	± 10	60	-
HAMPTON I	4	86	± 15	62	± 11	73	-
HAMPTON O	4	88	± 16	81	± 15	83	-
JACKSON I	4	63	± 11	50	± 9	56	-
JACKSON O	4	62	± 11	53	± 9	58	-
JOHNSTON I	4	67	± 12	52	± 9	60	-
JOHNSTON O	4	95	± 17	78	± 14	80	-
LEXINGTON I	4	133	± 24	108	± 19	119	-
LEXINGTON O	4	66	± 12	47	± 8	55	-
MARTIN I	4	32	± 6	28	± 5	29	-
MARTIN O	4	42	± 8	34	± 6	37	-
MCCORMICK I	4	82	± 15	68	± 12	77	-
MCCORMICK O	4	69	± 12	56	± 10	63	-
NEW ELLENTON I	4	111	± 20	93	± 17	104	-
NEW ELLENTON O	4	70	± 13	64	± 12	68	-
NORTH AUGUSTA I	4	108	± 19	96	± 17	103	-
NORTH AUGUSTA O	4	110	± 20	87	± 16	100	-
NORTH I	4	112	± 20	86	± 16	100	-
NORTH O	3	89	± 16	79	± 14	82	-
OLAR I	3	71	± 13	63	± 11	69	-
OLAR O	3	94	± 17	84	± 15	91	-
ORANGEBURG I	4	99	± 18	84	± 15	89	-
ORANGEBURG O	4	106	± 19	86	± 15	93	-

- Insufficient data; standard deviation not calculated for <5 samples.
 I Represents measurements taken from TLDs placed inside of buildings.
 O Represents measurements taken from TLDs placed outside of buildings.

Table 7-16
South Carolina TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
SOUTH CAROLINA CITIES AND TOWNS, CONT'D.							
SALUDA I	4	161	± 29	133	± 24	150	-
SALUDA O	4	117	± 21	101	± 18	112	-
SMOAKS I	3	65	± 12	55	± 10	59	-
SMOAKS O	3	60	± 11	54	± 10	56	-
SPRINGFIELD I	4	64	± 11	45	± 8	56	-
SPRINGFIELD O	4	84	± 15	8	± 2	61	-
ST MATTHEWS I	4	65	± 12	55	± 10	60	-
ST MATTHEWS O	4	98	± 18	90	± 16	94	-
SWANSEA I	4	60	± 11	53	± 9	57	-
SWANSEA O	4	112	± 20	95	± 17	104	-
WAGENER I	4	86	± 15	66	± 12	77	-
WAGENER O	4	70	± 13	49	± 9	56	-
WEST COLUMBIA I	4	121	± 22	101	± 18	108	-
WEST COLUMBIA O	4	128	± 23	104	± 19	112	-
WILLISTON I	4	93	± 17	76	± 14	81	-
WILLISTON O	4	90	± 16	78	± 14	84	-
WINDSOR I	4	49	± 9	28	± 5	35	-
WINDSOR O	4	45	± 8	36	± 7	41	-

- Insufficient data; standard deviation not calculated for <5 samples.
 I Represents measurements taken from TLDs placed inside of buildings.
 O Represents measurements taken from TLDs placed outside of buildings.

Table 7-17
Georgia TLD Penetrating Radiation Measurements

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
GEORGIA CITIES AND TOWNS							
ALEXANDER I	2	40	± 7	36	± 7	38	-
ALEXANDER O	4	41	± 7	35	± 6	39	-
AUGUSTA							
CENTRAL&TROUPE I	4	105	± 19	85	± 15	99	-
CENTRAL&TROUPE O	4	70	± 13	54	± 10	65	-
CENTRAL AVE I	4	97	± 17	70	± 13	86	-
CENTRAL AVE O	4	69	± 12	57	± 10	65	-
EVE & ELLIS I	3	114	± 20	92	± 16	104	-
EVE & ELLIS O	4	68	± 12	48	± 9	60	-
MILLEDGEVILLE RD I	4	102	± 18	81	± 15	92	-
MILLEDGEVILLE RD O	4	65	± 12	48	± 9	58	-
REYNOLD ST I	4	113	± 20	91	± 16	104	-
REYNOLD ST O	4	98	± 18	84	± 15	93	-
WALTON WAY I	4	91	± 16	68	± 12	79	-
WALTON WAY O	4	133	± 24	99	± 18	119	-
WATKINS ST I	4	101	± 18	85	± 15	93	-
WATKINS ST O	1	67	± 12	67	± 12	67	-
GIRARD I	4	106	± 19	85	± 15	95	-
GIRARD O	4	88	± 16	73	± 13	82	-
HEPHZIBAH I	4	53	± 9	48	± 9	50	-
HEPHZIBAH O	4	43	± 8	38	± 7	41	-
LINCOLNTON I	4	132	± 24	105	± 19	120	-
LINCOLNTON O	4	84	± 15	72	± 13	78	-
LOUISVILLE I	4	96	± 17	67	± 12	84	-
LOUISVILLE O	3	125	± 23	118	± 21	122	-
MCBEAN I	4	95	± 17	72	± 13	85	-
MCBEAN O	3	179	± 32	67	± 12	110	-
MILLEN I	4	55	± 10	40	± 7	48	-
MILLEN O	4	68	± 12	52	± 9	61	-
NEWINGTON I	4	118	± 21	85	± 15	103	-
NEWINGTON O	4	99	± 18	76	± 14	90	-

- Insufficient data; standard deviation not calculated for <5 samples.
 I Represents measurements taken from TLDs placed inside of buildings.
 O Represents measurements taken from TLDs placed outside of buildings.

Table 7-17
Georgia TLD Penetrating Radiation Measurements, Cont'd.

Location	No. of Samples	Maximum	CT ERR 2 σ or LLD	Minimum	CT ERR 2 σ or LLD	Arithmetic Mean	2 Std Dev
Dose, mrem/year							
GEORGIA CITIES AND TOWNS, CONT'D.							
SARDIS I	4	77	± 14	61	± 11	71	-
SARDIS O	4	81	± 15	63	± 11	76	-
STATESBORO I	4	74	± 13	59	± 11	69	-
STATESBORO O	4	77	± 14	48	± 9	62	-
SYLVANIA I	4	159	± 29	123	± 22	145	-
SYLVANIA O	4	87	± 16	70	± 13	80	-
THOMSON I	3	96	± 17	95	± 17	95	-
THOMSON O	4	115	± 21	98	± 18	108	-
WADLEY I	4	80	± 14	66	± 12	76	-
WADLEY O	4	103	± 19	89	± 16	97	-
WAYNESBORO I	4	53	± 10	46	± 8	50	-
WAYNESBORO O	3	66	± 12	56	± 10	62	-
WRENS I	4	117	± 21	98	± 18	109	-
WRENS O	4	82	± 15	64	± 12	73	-

- Insufficient data; standard deviation not calculated for <5 samples.
- I Represents measurements taken from TLDs placed inside of buildings.
- O Represents measurements taken from TLDs placed outside of buildings.

Table 7-18
Radioactivity in Vegetation

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha (pCi/g; dry weight)				
F-Area Veg. Site #13	4	7.95 $\pm$ 4.93 E-01	-0.46 $\pm$ 4.35 E-01	3.53 $\pm$ 3.54 E-01
F-Area Veg. Site #21	4	3.84 $\pm$ 3.95 E-01	-2.49 $\pm$ 3.60 E-01	0.84 $\pm$ 2.79 E-01
H-Area Veg. Site #10	4	1.20 $\pm$ 0.67 E+00	1.86 $\pm$ 4.96 E-01	4.74 $\pm$ 4.86 E-01
H-Area Veg. Site #22	4	4.59 $\pm$ 4.61 E-01	-2.20 $\pm$ 3.60 E-01	1.28 $\pm$ 3.07 E-01
S-Area Veg. Site #1	4	1.82 $\pm$ 0.80 E+00	-0.02 $\pm$ 3.67 E-01	5.59 $\pm$ 8.58 E-01
S-Area Veg. Site #2	4	1.07 $\pm$ 0.60 E+00	-0.12 $\pm$ 3.43 E-01	4.88 $\pm$ 4.64 E-01
S-Area Veg. Site #3	4	1.65 $\pm$ 1.02 E+00	1.36 $\pm$ 3.81 E-01	5.35 $\pm$ 7.41 E-01
S-Area Veg. Site #4	3	1.41 $\pm$ 0.94 E+00	-7.41 $\pm$ 5.18 E-01	0.34 $\pm$ 1.07 E+00
Z-Area Veg. Site #1	4	5.50 $\pm$ 1.64 E+00	-1.35 $\pm$ 5.18 E-01	1.71 $\pm$ 2.60 E+00
Z-Area Veg. Site #2	4	1.90 $\pm$ 0.76 E+00	-0.26 $\pm$ 4.45 E-01	1.12 $\pm$ 0.86 E+00
Z-Area Veg. Site #3	4	1.33 $\pm$ 0.82 E+00	-3.01 $\pm$ 4.37 E-01	2.89 $\pm$ 7.47 E-01
Z-Area Veg. Site #4	4	1.01 $\pm$ 0.73 E+00	-1.34 $\pm$ 5.63 E-01	3.56 $\pm$ 4.80 E-01
Z-Area Veg. Site #5	4	5.71 $\pm$ 1.90 E+00	1.79 $\pm$ 4.84 E-01	2.26 $\pm$ 2.45 E+00
Z-Area Veg. Site #6	4	8.24 $\pm$ 5.96 E-01	-0.46 $\pm$ 4.51 E-01	3.35 $\pm$ 3.71 E-01
Z-Area Veg. Site #7	4	1.31 $\pm$ 0.64 E+00	-5.73 $\pm$ 3.81 E-01	1.85 $\pm$ 8.86 E-01
Z-Area Veg. Site #8	4	4.18 $\pm$ 5.67 E-01	-1.28 $\pm$ 4.28 E-01	0.81 $\pm$ 2.38 E-01
Allendale Gate	4	3.62 $\pm$ 3.86 E-01	-2.58 $\pm$ 3.61 E-01	0.64 $\pm$ 2.66 E-01
Barnwell Gate	4	3.73 $\pm$ 4.78 E-01	-1.03 $\pm$ 4.77 E-01	1.04 $\pm$ 2.35 E-01
D Area	4	1.41 $\pm$ 0.80 E+00	1.50 $\pm$ 3.78 E-01	7.48 $\pm$ 5.87 E-01
Darkhorse	4	1.01 $\pm$ 0.77 E+00	-2.20 $\pm$ 3.20 E-01	2.26 $\pm$ 5.42 E-01
East Talatha	4	5.38 $\pm$ 5.70 E-01	1.40 $\pm$ 3.70 E-01	3.38 $\pm$ 2.18 E-01
Greenpond	4	1.04 $\pm$ 0.65 E+00	4.11 $\pm$ 5.25 E-01	6.66 $\pm$ 2.73 E-01
Highway 39	4	7.51 $\pm$ 4.78 E-01	-3.59 $\pm$ 3.92 E-01	0.80 $\pm$ 4.73 E-01
Highways 21 & 167	4	5.51 $\pm$ 4.26 E-01	-5.22 $\pm$ 3.00 E-01	1.06 $\pm$ 4.51 E-01
Jackson, SC	4	1.41 $\pm$ 0.68 E+00	-0.42 $\pm$ 4.36 E-01	5.32 $\pm$ 6.97 E-01
Patterson Mill Rd	4	6.96 $\pm$ 5.40 E-01	-1.03 $\pm$ 7.63 E-01	1.77 $\pm$ 3.65 E-01
Road A14	4	9.33 $\pm$ 5.76 E-01	-1.58 $\pm$ 4.69 E-01	2.91 $\pm$ 4.60 E-01
Talatha Gate	3	4.11 $\pm$ 4.62 E-01	-4.53 $\pm$ 2.96 E-01	-0.14 $\pm$ 4.32 E-01
West Jackson	3	7.27 $\pm$ 5.50 E-01	1.65 $\pm$ 4.36 E-01	4.92 $\pm$ 2.92 E-01
Windsor Road	4	6.42 $\pm$ 6.33 E-01	-0.46 $\pm$ 2.83 E-01	2.36 $\pm$ 3.32 E-01
Allendale, SC	4	3.76 $\pm$ 4.05 E-01	-2.14 $\pm$ 3.38 E-0	1.38 $\pm$ 2.52 E-01
Langley, SC	4	7.68 $\pm$ 5.49 E-01	-4.20 $\pm$ 6.29 E-01	0.81 $\pm$ 5.30 E-01
Springfield, SC	4	7.41 $\pm$ 6.09 E-01	-4.01 $\pm$ 2.74 E-01	-0.65 $\pm$ 5.40 E-01

Table 7-18
Radioactivity in Vegetation, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Waynesboro, GA	4	6.59 $\pm$ 5.36 E-01	-3.73 $\pm$ 3.94 E-01	1.16 $\pm$ 4.33 E-01
Columbia, SC	4	6.54 $\pm$ 5.43 E-01	-6.31 $\pm$ 3.47 E-04	4.70 $\pm$ 3.15 E-01
Greenville, SC	4	4.29 $\pm$ 5.90 E-01	-2.91 $\pm$ 3.76 E-01	1.65 $\pm$ 3.26 E-01
Macon, GA	4	1.50 $\pm$ 0.66 E+00	-6.59 $\pm$ 3.88 E-01	2.36 $\pm$ 9.11 E-01
Savannah, GA	4	1.64 $\pm$ 3.12 E-01	-0.43 $\pm$ 1.66 E-01	1.41 $\pm$ 9.99 E-02
Nonvolatile Beta (pCi/g; dry weight)				
F-Area Veg. Site #13	4	1.87 $\pm$ 0.22 E+01	4.13 $\pm$ 1.21 E+00	1.18 $\pm$ 0.67 E+01
F-Area Veg. Site #21	4	1.32 $\pm$ 0.19 E+01	7.73 $\pm$ 1.16 E+00	1.12 $\pm$ 0.24 E+01
H-Area Veg. Site #10	4	2.88 $\pm$ 0.26 E+01	1.32 $\pm$ 0.16 E+01	1.88 $\pm$ 0.70 E+01
H-Area Veg. Site #22	4	1.17 $\pm$ 0.19 E+01	5.55 $\pm$ 1.22 E+00	8.16 $\pm$ 2.94 E+00
S-Area Veg. Site #1	4	8.79 $\pm$ 0.41 E+01	1.05 $\pm$ 0.14 E+01	3.42 $\pm$ 3.60 E+01
S-Area Veg. Site #2	4	1.91 $\pm$ 0.16 E+01	5.09 $\pm$ 1.12 E+00	1.27 $\pm$ 0.74 E+01
S-Area Veg. Site #3	4	6.76 $\pm$ 0.37 E+01	7.51 $\pm$ 1.24 E+00	2.87 $\pm$ 2.70 E+01
S-Area Veg. Site #4	3	3.82 $\pm$ 0.29 E+01	5.00 $\pm$ 1.08 E+00	2.27 $\pm$ 1.67 E+01
Z-Area Veg. Site #1	4	3.99 $\pm$ 0.29 E+01	8.86 $\pm$ 1.21 E+00	1.82 $\pm$ 1.46 E+01
Z-Area Veg. Site #2	4	2.09 $\pm$ 0.23 E+01	8.65 $\pm$ 1.30 E+00	1.23 $\pm$ 0.58 E+01
Z-Area Veg. Site #3	4	1.90 $\pm$ 0.25 E+01	8.38 $\pm$ 1.19 E+00	1.32 $\pm$ 0.44 E+01
Z-Area Veg. Site #4	4	3.70 $\pm$ 0.28 E+01	4.90 $\pm$ 1.02 E+00	1.59 $\pm$ 1.44 E+01
Z-Area Veg. Site #5	4	2.66 $\pm$ 0.28 E+01	1.22 $\pm$ 0.14 E+01	1.92 $\pm$ 0.64 E+01
Z-Area Veg. Site #6	4	1.83 $\pm$ 0.22 E+01	6.43 $\pm$ 1.18 E+00	1.19 $\pm$ 0.52 E+01
Z-Area Veg. Site #7	4	4.64 $\pm$ 0.31 E+01	1.22 $\pm$ 0.15 E+01	2.24 $\pm$ 1.61 E+01
Z-Area Veg. Site #8	4	3.33 $\pm$ 0.27 E+01	1.13 $\pm$ 0.13 E+01	2.14 $\pm$ 1.06 E+01
Allendale Gate	4	1.12 $\pm$ 0.13 E+01	5.43 $\pm$ 1.12 E+00	8.79 $\pm$ 2.79 E+00
Barnwell Gate	4	2.40 $\pm$ 0.17 E+01	7.68 $\pm$ 1.23 E+00	1.42 $\pm$ 0.72 E+01
D Area	4	3.02 $\pm$ 0.23 E+01	7.68 $\pm$ 1.24 E+00	2.09 $\pm$ 0.95 E+01
Darkhorse	4	2.31 $\pm$ 0.17 E+01	5.01 $\pm$ 1.20 E+00	1.55 $\pm$ 0.87 E+01
East Talatha	4	2.36 $\pm$ 0.18 E+01	1.76 $\pm$ 0.17 E+01	2.09 $\pm$ 0.31 E+01
Greenpond	4	1.92 $\pm$ 0.17 E+01	4.36 $\pm$ 1.16 E+00	1.10 $\pm$ 0.62 E+01
Highway 39	4	1.87 $\pm$ 0.18 E+01	7.68 $\pm$ 1.23 E+00	1.36 $\pm$ 0.46 E+01
Highways 21 & 167	4	1.95 $\pm$ 0.19 E+01	7.68 $\pm$ 1.23 E+00	1.29 $\pm$ 0.50 E+01
Jackson, SC	4	2.69 $\pm$ 0.21 E+01	7.05 $\pm$ 1.30 E+00	1.41 $\pm$ 0.94 E+01
Patterson Mill Rd	4	4.79 $\pm$ 0.28 E+01	8.23 $\pm$ 1.25 E+00	2.18 $\pm$ 1.78 E+01
Road A14	4	2.26 $\pm$ 0.19 E+01	1.04 $\pm$ 0.13 E+01	1.61 $\pm$ 0.62 E+01
Talatha Gate	3	1.70 $\pm$ 0.15 E+01	-3.02 $\pm$ 0.58 E-03	8.46 $\pm$ 8.52 E+00

Table 7-18
Radioactivity in Vegetation, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
West Jackson	3	1.04 $\pm$ 0.13 E+01	9.17 $\pm$ 1.47 E+00	9.99 $\pm$ 0.71 E+00
Windsor Road	4	1.57 $\pm$ 0.15 E+01	7.47 $\pm$ 1.24 E+00	1.12 $\pm$ 0.36 E+01
Allendale, SC	4	1.23 $\pm$ 0.14 E+01	7.13 $\pm$ 1.21 E+00	9.79 $\pm$ 2.52 E+00
Langley, SC	4	4.75 $\pm$ 0.27 E+01	9.78 $\pm$ 8.25 E-01	1.85 $\pm$ 2.02 E+01
Springfield, SC	4	2.07 $\pm$ 0.17 E+01	4.34 $\pm$ 1.08 E+00	1.33 $\pm$ 0.71 E+01
Waynesboro, GA	4	2.23 $\pm$ 0.20 E+01	9.88 $\pm$ 1.33 E+00	1.81 $\pm$ 0.56 E+01
Columbia, SC	4	2.80 $\pm$ 0.25 E+01	-8.51 $\pm$ 0.81 E-03	1.62 $\pm$ 1.20 E+01
Greenville, SC	4	4.22 $\pm$ 0.22 E+01	1.63 $\pm$ 0.17 E+01	2.50 $\pm$ 1.17 E+01
Macon, GA	4	3.25 $\pm$ 0.20 E+01	1.23 $\pm$ 0.13 E+01	2.13 $\pm$ 0.88 E+01
Savannah, GA	4	1.40 $\pm$ 0.16 E+01	9.08 $\pm$ 1.21 E+00	1.12 $\pm$ 0.24 E+01
Tritium (pCi/g; wet weight)				
F-Area Veg. Site #13	2	3.96 $\pm$ 0.09 E+00	2.11 $\pm$ 0.02 E+00	3.03 $\pm$ 1.31 E+00
F-Area Veg. Site #21	3	3.33 $\pm$ 0.06 E+01	5.81 $\pm$ 0.17 E-01	1.19 $\pm$ 1.86 E+01
H-Area Veg. Site #10	3	2.15 $\pm$ 0.17 E+00	5.25 $\pm$ 0.12 E-01	1.54 $\pm$ 0.88 E+00
H-Area Veg. Site #22	3	5.42 $\pm$ 0.08 E+01	2.39 $\pm$ 0.03 E+00	2.26 $\pm$ 2.77 E+01
S-Area Veg. Site #1	3	3.92 $\pm$ 0.06 E+01	6.14 $\pm$ 0.06 E+00	1.77 $\pm$ 1.86 E+01
S-Area Veg. Site #2	3	9.57 $\pm$ 0.16 E+00	4.33 $\pm$ 0.07 E+00	6.41 $\pm$ 2.78 E+00
S-Area Veg. Site #3	3	1.39 $\pm$ 0.02 E+01	1.03 $\pm$ 0.01 E+00	6.81 $\pm$ 6.53 E+00
S-Area Veg. Site #4	3	2.36 $\pm$ 0.04 E+01	2.61 $\pm$ 0.02 E+00	1.24 $\pm$ 1.06 E+01
Z-Area Veg. Site #1	3	2.10 $\pm$ 0.03 E+01	6.58 $\pm$ 0.13 E+00	1.37 $\pm$ 0.72 E+01
Z-Area Veg. Site #2	2	2.33 $\pm$ 0.04 E+01	8.22 $\pm$ 0.15 E+00	1.57 $\pm$ 1.06 E+01
Z-Area Veg. Site #3	2	1.92 $\pm$ 0.03 E+01	4.37 $\pm$ 0.09 E+00	1.18 $\pm$ 1.05 E+01
Z-Area Veg. Site #4	1	1.75 $\pm$ 0.03 E+01	1.75 $\pm$ 0.03 E+01	1.75 $\pm$ 0.03 E+01
Z-Area Veg. Site #5	3	3.62 $\pm$ 0.06 E+01	1.94 $\pm$ 0.03 E+00	1.89 $\pm$ 1.71 E+01
Z-Area Veg. Site #6	3	4.67 $\pm$ 0.05 E+01	1.74 $\pm$ 0.03 E+00	1.81 $\pm$ 2.48 E+01
Z-Area Veg. Site #7	3	2.67 $\pm$ 0.04 E+01	7.92 $\pm$ 0.11 E+00	1.86 $\pm$ 0.96 E+01
Z-Area Veg. Site #8	3	2.97 $\pm$ 0.05 E+01	6.26 $\pm$ 0.10 E+00	1.42 $\pm$ 1.34 E+01
Allendale Gate	3	4.30 $\pm$ 1.55 E-01	1.45 $\pm$ 0.24 E-01	2.55 $\pm$ 1.53 E-01
Barnwell Gate	3	1.75 $\pm$ 0.12 E+00	2.06 $\pm$ 0.30 E-01	7.56 $\pm$ 8.60 E-01
D Area	2	3.26 $\pm$ 0.21 E+00	8.85 $\pm$ 0.90 E-01	2.07 $\pm$ 1.68 E+00
Darkhorse	3	1.81 $\pm$ 0.06 E+00	1.36 $\pm$ 0.21 E-01	9.24 $\pm$ 8.43 E-01
East Talatha	2	8.45 $\pm$ 0.24 E+00	5.66 $\pm$ 0.28 E-01	4.51 $\pm$ 5.58 E+00
Greenpond	3	2.98 $\pm$ 0.05 E+00	4.43 $\pm$ 0.50 E-01	1.44 $\pm$ 1.36 E+00
Highway 39	2	5.82 $\pm$ 1.56 E-01	1.74 $\pm$ 0.26 E-01	3.78 $\pm$ 2.88 E-01

Table 7-18
Radioactivity in Vegetation, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Highways 21 & 167	3	1.78 $\pm$ 0.16 E+00	1.54 $\pm$ 0.46 E-01	7.82 $\pm$ 8.75 E-01
Jackson, SC	3	1.25 $\pm$ 0.16 E+00	3.59 $\pm$ 0.32 E-01	7.66 $\pm$ 4.49 E-01
Patterson Mill Rd	2	5.90 $\pm$ 1.01 E-01	1.27 $\pm$ 0.26 E-01	3.58 $\pm$ 3.28 E-01
Road A14	3	2.72 $\pm$ 0.17 E+00	2.32 $\pm$ 0.22 E-01	1.53 $\pm$ 1.25 E+00
Talatha Gate	1	5.78 $\pm$ 0.27 E-01	5.78 $\pm$ 0.27 E-01	5.78 $\pm$ 0.27 E-01
West Jackson	1	1.08 $\pm$ 0.08 E+00	1.08 $\pm$ 0.08 E+00	1.08 $\pm$ 0.08 E+00
Windsor Road	3	3.81 $\pm$ 0.25 E+00	1.23 $\pm$ 0.21 E-01	1.93 $\pm$ 1.85 E+00
Allendale, SC	2	1.85 $\pm$ 0.14 E+00	1.07 $\pm$ 0.18 E-01	0.98 $\pm$ 1.24 E+00
Langley, SC	2	2.73 $\pm$ 1.36 E-01	1.88 $\pm$ 0.89 E-02	1.46 $\pm$ 1.80 E-01
Springfield, SC	2	1.51 $\pm$ 0.14 E+00	7.54 $\pm$ 2.15 E-02	0.79 $\pm$ 1.02 E+00
Waynesboro, GA	2	3.44 $\pm$ 0.22 E-01	3.33 $\pm$ 1.35 E-01	3.39 $\pm$ 0.08 E-01
Columbia, SC	3	1.00 $\pm$ 0.15 E+00	2.86 $\pm$ 1.08 E-02	4.48 $\pm$ 4.99 E-01
Greenville, SC	2	1.81 $\pm$ 1.60 E-02	-0.12 $\pm$ 1.27 E-01	0.30 $\pm$ 2.15 E-02
Macon, GA	2	4.63 $\pm$ 2.45 E-02	-0.27 $\pm$ 1.28 E-01	0.98 $\pm$ 5.16 E-02
Savannah, GA	2	6.17 $\pm$ 1.28 E-02	-0.45 $\pm$ 1.32 E-01	0.83 $\pm$ 7.55 E-02
Sr-89, 90 (pCi/g; dry weight)				
F Area	4	3.39 $\pm$ 0.22 E+00	4.02 $\pm$ 1.03 E-01	1.24 $\pm$ 1.43 E+00
H Area	4	8.12 $\pm$ 0.97 E-01	2.49 $\pm$ 0.67 E-01	5.16 $\pm$ 2.62 E-01
Site Perimeter	4	8.36 $\pm$ 0.99 E-01	2.66 $\pm$ 0.77 E-01	5.06 $\pm$ 2.76 E-01
25-mile Radius	4	3.70 $\pm$ 0.93 E-01	1.17 $\pm$ 0.71 E-01	2.06 $\pm$ 1.13 E-01
100-mile Radius	4	2.39 $\pm$ 0.96 E-01	4.76 $\pm$ 3.10 E-02	1.30 $\pm$ 0.81 E-01
S-Area Veg. Site #1	4	6.46 $\pm$ 0.91 E-01	1.51 $\pm$ 0.70 E-01	3.68 $\pm$ 2.10 E-01
Z-Area Veg. Site #1	4	8.41 $\pm$ 0.98 E-01	1.66 $\pm$ 0.64 E-01	3.85 $\pm$ 3.09 E-01
Cs-137 (pCi/g; dry weight)				
F Area	4 / 4 ^a	2.55 $\pm$ 0.12 E+00	4.37 $\pm$ 0.48 E-01	1.11 $\pm$ 0.97 E+00
H Area	4 / 3	2.68 $\pm$ 0.35 E-01	1.57 $\pm$ 0.21 E-01	2.05 $\pm$ 0.57 E-01
Site Perimeter	7 / 1	8.36 $\pm$ 2.26 E-02	8.36 $\pm$ 2.26 E-02	8.36 $\pm$ 2.26 E-02
25-mile Radius	4 / 1	1.12 $\pm$ 0.23 E-01	1.12 $\pm$ 0.23 E-01	1.12 $\pm$ 0.23 E-01
100-mile Radius	4 / 1	6.63 $\pm$ 1.69 E-02	6.63 $\pm$ 1.69 E-02	6.63 $\pm$ 1.69 E-02
S-Area Veg. Site #1	4 / 1	1.57 $\pm$ 0.28 E-01	1.57 $\pm$ 0.28 E-01	1.57 $\pm$ 0.28 E-01

a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-18
Radioactivity in Vegetation, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
S-Area Veg. Site #2	4 / 0 ^a			
S-Area Veg. Site #3	4 / 0			
S-Area Veg. Site #4	4 / 2	4.16 $\pm$ 0.49 E-01	2.40 $\pm$ 0.30 E-01	3.28 $\pm$ 1.24 E-01
Z-Area Veg. Site #1	4 / 0			
Z-Area Veg. Site #2	4 / 0			
Z-Area Veg. Site #3	4 / 3	4.63 $\pm$ 0.51 E-01	1.35 $\pm$ 0.30 E-01	2.54 $\pm$ 1.82 E-01
Z-Area Veg. Site #4	4 / 0			
Z-Area Veg. Site #5	4 / 1	1.85 $\pm$ 0.44 E-01	1.85 $\pm$ 0.44 E-01	1.85 $\pm$ 0.44 E-01
Z-Area Veg. Site #6	4 / 0			
Z-Area Veg. Site #7	4 / 3	6.64 $\pm$ 0.74 E-01	4.25 $\pm$ 0.45 E-01	5.49 $\pm$ 1.20 E-01
Z-Area Veg. Site #8	4 / 1	1.32 $\pm$ 0.29 E-01	1.32 $\pm$ 0.29 E-01	1.32 $\pm$ 0.29 E-01

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-19
Radioactivity in Seepage and Retention Basin Vegetation

Location	pCi/g $\pm$ σ (dry weight)		
	Gross Alpha	Nonvolatile Beta	Sr-90
700-A Seepage Basin Composite (4 Locations)	4.17 $\pm$ 6.18 E-01	7.11 $\pm$ 0.31 E+01	2.37 $\pm$ 0.07 E+00
100-C Seepage Basin Composite (8 Locations)	2.29 $\pm$ 3.50 E-01	2.45 $\pm$ 0.14 E+01	8.88 $\pm$ 0.12 E+00
100-K Seepage Basin Composite (4 Locations)	0.84 $\pm$ 3.30 E-01	7.51 $\pm$ 0.95 E+00	2.93 $\pm$ 0.34 E-01
100-L Seepage Basin Composite (4 Locations)	5.68 $\pm$ 4.04 E-01	1.14 $\pm$ 0.11 E+01	5.15 $\pm$ 0.27 E-01
100-L Chemical Basin Composite (4 Locations)	-1.94 $\pm$ 2.93 E-01	1.72 $\pm$ 0.12 E+01	4.71 $\pm$ 0.36 E-01
100-P Seepage Basin Composite (4 Locations)	-0.05 $\pm$ 2.92 E-01	4.69 $\pm$ 0.84 E+00	3.86 $\pm$ 0.30 E-01
100-R Seepage Basin Composite (8 Locations)	8.67 $\pm$ 4.33 E-01	1.28 $\pm$ 0.11 E+01	1.89 $\pm$ 0.06 E+00
200-F Seepage Basin Composite (8 Locations)	1.17 $\pm$ 0.53 E+00	1.98 $\pm$ 0.13 E+01	6.15 $\pm$ 0.40 E-01
200-F Retention Basin Composite (6 Locations)	-0.07 $\pm$ 3.46 E-01	1.46 $\pm$ 0.12 E+01	5.15 $\pm$ 0.32 E-01
200-H Seepage Basin Composite (8 Locations)	2.53 $\pm$ 0.66 E+00	1.27 $\pm$ 0.11 E+01	5.77 $\pm$ 0.31 E-01
200-H Retention Basin Composite (8 Locations)	3.26 $\pm$ 4.18 E-01	5.85 $\pm$ 0.20 E+01	1.78 $\pm$ 0.01 E+01
Location	pCi/g $\pm$ σ (dry weight)		
	K-40	Cs-137	
700-A Seepage Basin Composite (4 Locations)	6.76 $\pm$ 0.91 E+00	9.10 $\pm$ 0.80 E-01	
100-C Seepage Basin Composite (8 Locations)	—	—	
100-K Seepage Basin Composite (4 Locations)	3.37 $\pm$ 0.68 E+00	2.75 $\pm$ 0.43 E-01	
100-L Seepage Basin Composite (4 Locations)	—	—	
100-L Chemical Basin Composite (4 Locations)	9.35 $\pm$ 0.87 E+00	—	
100-P Seepage Basin Composite (4 Locations)	4.15 $\pm$ 0.46 E+00	—	
100-R Seepage Basin Composite (8 Locations)	—	—	
200-F Seepage Basin Composite (8 Locations)	1.24 $\pm$ 0.18 E+01	—	
200-F Retention Basin Composite (6 Locations)	7.65 $\pm$ 0.84 E+00	—	
200-H Seepage Basin Composite (8 Locations)	1.06 $\pm$ 0.10 E+01	—	
200-H Retention Basin Composite (8 Locations)	7.70 $\pm$ 0.67 E+00	6.21 $\pm$ 0.23 E+00	

— No quantifiable activity.

Table 7-20
Radioactivity in Vegetation
inside the Solid Waste Disposal Facility Fences

Location	Gross Alpha*	Nonvolatile Beta*	K-40*	Cs-137*
1	$-0.42 \pm 4.08 \text{ E-01}$	$1.37 \pm 0.15 \text{ E+01}$	—	—
1A	$8.18 \pm 6.07 \text{ E-01}$	$1.49 \pm 0.16 \text{ E+01}$	$1.13 \pm 0.09 \text{ E+01}$	$2.61 \pm 0.34 \text{ E-01}$
2	$3.80 \pm 4.82 \text{ E-01}$	$8.12 \pm 1.28 \text{ E+00}$	$4.07 \pm 0.85 \text{ E+00}$	—
3	$2.02 \pm 0.82 \text{ E+00}$	$1.35 \pm 0.15 \text{ E+01}$	—	$1.60 \pm 0.10 \text{ E+00}$
3A	$2.97 \pm 5.17 \text{ E-01}$	$3.41 \pm 0.22 \text{ E+01}$	—	—
4	$-2.38 \pm 3.37 \text{ E-01}$	$1.32 \pm 0.15 \text{ E+01}$	$1.91 \pm 0.12 \text{ E+01}$	$2.52 \pm 0.35 \text{ E-01}$
5	$1.05 \pm 4.97 \text{ E-01}$	$3.09 \pm 0.21 \text{ E+01}$		
6	$-4.83 \pm 2.98 \text{ E-01}$	$1.44 \pm 0.16 \text{ E+01}$	$1.40 \pm 0.09 \text{ E+01}$	$1.29 \pm 0.25 \text{ E-01}$
7	$6.28 \pm 5.81 \text{ E-01}$	$5.13 \pm 0.26 \text{ E+01}$	—	—
8	$4.24 \pm 5.66 \text{ E-01}$	$1.34 \pm 0.15 \text{ E+01}$	$1.67 \pm 0.13 \text{ E+01}$	$2.45 \pm 0.40 \text{ E-01}$
8A	$-4.64 \pm 2.88 \text{ E-01}$	$1.35 \pm 0.15 \text{ E+01}$	$1.32 \pm 0.14 \text{ E+01}$	$5.40 \pm 0.72 \text{ E-01}$
10	$3.92 \pm 4.84 \text{ E-01}$	$5.42 \pm 1.16 \text{ E+00}$	—	—
11	$7.21 \pm 3.76 \text{ E-01}$	$9.70 \pm 0.92 \text{ E+00}$	$7.06 \pm 0.71 \text{ E+00}$	$1.68 \pm 0.28 \text{ E-01}$
12	$-2.42 \pm 3.58 \text{ E-01}$	$1.09 \pm 0.14 \text{ E+01}$	$7.45 \pm 1.13 \text{ E+00}$	$8.08 \pm 0.79 \text{ E-01}$
13	$-5.13 \pm 3.05 \text{ E-01}$	$1.88 \pm 0.17 \text{ E+01}$	$1.38 \pm 0.14 \text{ E+01}$	$4.06 \pm 0.59 \text{ E-01}$
14	$-0.34 \pm 2.76 \text{ E-01}$	$1.25 \pm 0.14 \text{ E+01}$	$1.32 \pm 0.13 \text{ E+01}$	$3.22 \pm 0.53 \text{ E-01}$
15	$6.54 \pm 5.59 \text{ E-01}$	$2.74 \pm 0.19 \text{ E+01}$	—	—
16	$8.77 \pm 6.55 \text{ E-01}$	$1.65 \pm 0.17 \text{ E+01}$	$1.38 \pm 0.13 \text{ E+01}$	—
17	$5.73 \pm 5.75 \text{ E-01}$	$2.34 \pm 0.19 \text{ E+01}$	—	—
18	$1.09 \pm 0.67 \text{ E+00}$	$1.32 \pm 0.15 \text{ E+01}$	$1.16 \pm 0.13 \text{ E+01}$	—
19	$-4.42 \pm 2.82 \text{ E-01}$	$1.04 \pm 0.14 \text{ E+01}$	$1.20 \pm 0.12 \text{ E+01}$	—
19A	$-4.42 \pm 2.86 \text{ E-01}$	$9.19 \pm 1.34 \text{ E+00}$	$1.31 \pm 0.14 \text{ E+01}$	—
20	$1.31 \pm 5.12 \text{ E-01}$	$2.61 \pm 0.20 \text{ E+01}$	—	—
20A	$3.70 \pm 3.81 \text{ E-01}$	$7.46 \pm 1.15 \text{ E+00}$	—	—
21	$-4.74 \pm 2.93 \text{ E-01}$	$1.41 \pm 0.15 \text{ E+01}$	$1.77 \pm 0.16 \text{ E+01}$	$1.55 \pm 0.44 \text{ E-01}$
22	$-2.53 \pm 3.56 \text{ E-01}$	$1.38 \pm 0.15 \text{ E+01}$	$1.13 \pm 0.12 \text{ E+01}$	—
23	$9.51 \pm 5.18 \text{ E-01}$	$1.19 \pm 0.13 \text{ E+01}$	$1.54 \pm 0.10 \text{ E+01}$	—
23A	$1.77 \pm 0.78 \text{ E+00}$	$1.27 \pm 0.15 \text{ E+01}$	$1.16 \pm 0.10 \text{ E+01}$	—
24	$1.15 \pm 0.55 \text{ E+00}$	$8.81 \pm 1.21 \text{ E+00}$	$9.58 \pm 0.78 \text{ E+00}$	—
25	$1.95 \pm 4.94 \text{ E-01}$	$1.03 \pm 0.14 \text{ E+01}$	—	—
26	$2.10 \pm 5.01 \text{ E-01}$	$7.53 \pm 1.29 \text{ E+00}$	$1.08 \pm 0.10 \text{ E+01}$	—

* pCi/g $\pm \sigma$; dry weight
 — No quantifiable activity.

Table 7-20
Radioactivity in Vegetation
inside the Solid Waste Disposal Facility Fences, Cont'd.

Location	Gross Alpha*	Nonvolatile Beta*	K-40*	Cs-137*
27	$-2.35 \pm 3.46 \text{ E-01}$	$1.09 \pm 0.14 \text{ E+01}$	$1.83 \pm 0.17 \text{ E+01}$	—
28	$-2.25 \pm 1.86 \text{ E-01}$	$1.14 \pm 0.13 \text{ E+01}$	$1.40 \pm 0.14 \text{ E+01}$	—
29	$-0.31 \pm 2.71 \text{ E-01}$	$1.20 \pm 0.13 \text{ E+01}$	$9.84 \pm 0.81 \text{ E+00}$	—
30	$5.95 \pm 4.68 \text{ E-01}$	$1.39 \pm 0.14 \text{ E+01}$	—	—
31	$-4.56 \pm 2.83 \text{ E-01}$	$1.36 \pm 0.15 \text{ E+01}$	*	*
32	$-0.30 \pm 2.71 \text{ E-01}$	$1.17 \pm 0.13 \text{ E+01}$	—	—
33	$1.52 \pm 3.45 \text{ E-01}$	$1.72 \pm 0.15 \text{ E+01}$	—	—
34	$1.69 \pm 3.25 \text{ E-01}$	$9.51 \pm 1.23 \text{ E+00}$	—	—
35	$5.78 \pm 4.54 \text{ E-01}$	$1.37 \pm 0.14 \text{ E+01}$	$1.16 \pm 0.07 \text{ E+01}$	—
36	$1.46 \pm 0.81 \text{ E+00}$	$2.03 \pm 0.18 \text{ E+01}$	$1.53 \pm 0.10 \text{ E+01}$	—
37	$3.70 \pm 4.17 \text{ E-01}$	$1.72 \pm 0.15 \text{ E+01}$	$1.55 \pm 0.15 \text{ E+01}$	—
38	$3.74 \pm 3.83 \text{ E-01}$	$7.08 \pm 1.13 \text{ E+00}$	—	—
39	$-0.36 \pm 2.74 \text{ E-01}$	$1.32 \pm 0.14 \text{ E+01}$	—	—
40	$-0.59 \pm 3.31 \text{ E-01}$	$1.73 \pm 0.15 \text{ E+01}$	—	—
41	$3.66 \pm 3.95 \text{ E-01}$	$1.27 \pm 0.14 \text{ E+01}$	—	$1.41 \pm 0.19 \text{ E-01}$
42	$1.38 \pm 0.86 \text{ E+00}$	$1.61 \pm 0.17 \text{ E+01}$	—	—

* pCi/g $\pm$ σ ; dry weight
 — No quantifiable activity.

Table 7-21
Radioactivity in Vegetation
outside the Solid Waste Disposal Facility Fences

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha (pCi/g; dry weight)				
Location 1	4	8.38 $\pm$ 3.95 E+00	-4.27 $\pm$ 3.25 E-01	2.57 $\pm$ 3.94 E+00
Location 2	4	1.87 $\pm$ 1.16 E+00	3.32 $\pm$ 6.90 E-01	1.04 $\pm$ 0.72 E+00
Location 3	4	8.22 $\pm$ 4.61 E-01	-1.98 $\pm$ 7.63 E-01	2.42 $\pm$ 4.25 E-01
Location 4	4	6.10 $\pm$ 1.72 E+00	-0.38 $\pm$ 4.62 E-01	2.86 $\pm$ 2.89 E+00
Location 5	4	1.19 $\pm$ 0.90 E+00	2.08 $\pm$ 5.27 E-01	8.55 $\pm$ 4.43 E-01
Location 6	4	3.32 $\pm$ 7.52 E-01	-0.59 $\pm$ 5.63 E-01	1.62 $\pm$ 1.63 E-01
Location 7	4	2.85 $\pm$ 1.27 E+00	-4.68 $\pm$ 3.35 E-01	0.69 $\pm$ 1.52 E+00
Location 8	4	1.83 $\pm$ 1.03 E+00	-2.85 $\pm$ 4.12 E-01	0.61 $\pm$ 1.05 E+00
Location 9	4	2.72 $\pm$ 0.57 E+00	-2.69 $\pm$ 2.02 E-01	0.72 $\pm$ 1.36 E+00
Location 10	4	7.95 $\pm$ 7.70 E-01	-2.75 $\pm$ 2.13 E-01	0.51 $\pm$ 5.04 E-01
Location 11	3	1.97 $\pm$ 5.17 E-01	-4.41 $\pm$ 3.45 E-01	-1.06 $\pm$ 3.20 E-01
Location 12	4	1.62 $\pm$ 0.84 E+00	1.52 $\pm$ 4.98 E-01	7.50 $\pm$ 6.21 E-01
Location 13	4	2.31 $\pm$ 1.24 E+00	-0.80 $\pm$ 2.99 E-01	0.68 $\pm$ 1.10 E+00
Nonvolatile Beta (pCi/g; dry weight)				
Location 1	4	4.35 $\pm$ 0.23 E+01	9.84 $\pm$ 1.45 E+00	2.55 $\pm$ 1.42 E+01
Location 2	4	2.26 $\pm$ 0.24 E+01	4.50 $\pm$ 1.01 E+00	1.41 $\pm$ 0.75 E+01
Location 3	4	4.82 $\pm$ 0.35 E+01	1.05 $\pm$ 0.15 E+01	2.94 $\pm$ 1.70 E+01
Location 4	4	4.54 $\pm$ 0.31 E+01	1.07 $\pm$ 0.21 E+01	2.36 $\pm$ 1.59 E+01
Location 5	4	2.57 $\pm$ 0.25 E+01	1.11 $\pm$ 0.15 E+01	1.63 $\pm$ 0.65 E+01
Location 6	4	2.94 $\pm$ 0.26 E+01	1.12 $\pm$ 0.15 E+01	2.19 $\pm$ 0.77 E+01
Location 7	4	3.81 $\pm$ 0.32 E+01	9.78 $\pm$ 1.43 E+00	2.53 $\pm$ 1.41 E+01
Location 8	4	3.66 $\pm$ 0.28 E+01	1.01 $\pm$ 0.14 E+01	2.03 $\pm$ 1.18 E+01
Location 9	4	2.33 $\pm$ 0.24 E+01	6.82 $\pm$ 1.23 E+00	1.43 $\pm$ 0.76 E+01
Location 10	4	2.45 $\pm$ 0.24 E+01	1.02 $\pm$ 0.14 E+01	1.80 $\pm$ 0.63 E+01
Location 11	3	2.55 $\pm$ 0.25 E+01	1.24 $\pm$ 0.16 E+01	1.97 $\pm$ 0.67 E+01
Location 12	4	3.84 $\pm$ 0.22 E+01	8.01 $\pm$ 1.35 E+00	2.51 $\pm$ 1.37 E+01
Location 13	4	2.41 $\pm$ 0.17 E+01	8.39 $\pm$ 1.36 E+00	1.52 $\pm$ 0.69 E+01

Table 7-21
Radioactivity in Vegetation
outside the Solid Waste Disposal Facility Fences, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
K-40 (pCi/g; dry weight)				
Location 1	4 / 4 ^a	2.37 $\pm$ 0.14 E+01	7.16 $\pm$ 0.70 E+00	1.52 $\pm$ 0.79 E+01
Location 2	4 / 3	1.13 $\pm$ 0.08 E+01	1.01 $\pm$ 0.13 E+01	1.06 $\pm$ 0.06 E+01
Location 3	4 / 3	2.46 $\pm$ 0.13 E+01	6.94 $\pm$ 0.57 E+00	1.53 $\pm$ 0.88 E+01
Location 4	4 / 3	3.96 $\pm$ 0.18 E+01	6.89 $\pm$ 0.61 E+00	2.70 $\pm$ 1.76 E+01
Location 5	4 / 3	7.94 $\pm$ 0.78 E+00	5.34 $\pm$ 0.66 E+00	6.91 $\pm$ 1.38 E+00
Location 6	4 / 3	2.07 $\pm$ 0.13 E+01	5.93 $\pm$ 0.53 E+00	1.28 $\pm$ 0.74 E+01
Location 7	4 / 3	1.49 $\pm$ 0.12 E+01	8.90 $\pm$ 0.88 E+00	1.22 $\pm$ 0.30 E+01
Location 8	4 / 3	1.99 $\pm$ 0.12 E+01	1.27 $\pm$ 0.09 E+01	1.52 $\pm$ 0.41 E+01
Location 9	4 / 3	1.20 $\pm$ 0.10 E+01	5.13 $\pm$ 0.86 E+00	8.26 $\pm$ 3.48 E+00
Location 10	3 / 3	1.16 $\pm$ 0.09 E+01	6.20 $\pm$ 0.75 E+00	9.31 $\pm$ 2.77 E+00
Location 11	2 / 1	1.57 $\pm$ 0.09 E+01	1.57 $\pm$ 0.09 E+01	1.57 $\pm$ 0.09 E+01
Location 12	4 / 3	3.12 $\pm$ 0.17 E+01	1.05 $\pm$ 0.08 E+01	2.05 $\pm$ 1.04 E+01
Location 13	3 / 3	1.57 $\pm$ 0.08 E+01	8.32 $\pm$ 0.81 E+00	1.27 $\pm$ 0.39 E+01
Cs-137 (pCi/g; dry weight)				
Location 1	4 / 1	2.28 $\pm$ 0.31 E-01	2.28 $\pm$ 0.31 E-01	2.28 $\pm$ 0.31 E-01
Location 2	4 / 0			
Location 3	4 / 1	7.56 $\pm$ 1.78 E-02	7.56 $\pm$ 1.78 E-02	7.56 $\pm$ 1.78 E-02
Location 4	4 / 1	3.15 $\pm$ 0.37 E-01	3.15 $\pm$ 0.37 E-01	3.15 $\pm$ 0.37 E-01
Location 5	4 / 0			
Location 6	4 / 1	2.12 $\pm$ 0.24 E-01	2.12 $\pm$ 0.24 E-01	2.12 $\pm$ 0.24 E-01
Location 7	4 / 3	2.91 $\pm$ 0.35 E-01	2.16 $\pm$ 0.36 E-01	2.65 $\pm$ 0.43 E-01
Location 8	4 / 3	1.58 $\pm$ 0.27 E-01	1.07 $\pm$ 0.22 E-01	1.29 $\pm$ 0.26 E-01
Location 9	4 / 3	6.85 $\pm$ 0.73 E-01	2.63 $\pm$ 0.34 E-01	4.59 $\pm$ 2.12 E-01
Location 10	3 / 3	3.01 $\pm$ 0.37 E-01	1.86 $\pm$ 0.30 E-01	2.26 $\pm$ 0.66 E-01
Location 11	2 / 0			
Location 12	4 / 2	3.15 $\pm$ 0.35 E-01	2.34 $\pm$ 0.31 E-01	2.75 $\pm$ 0.57 E-01
Location 13	3 / 2	2.21 $\pm$ 0.34 E-01	1.29 $\pm$ 4.01 E-01	1.75 $\pm$ 0.65 E-01

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-22
Radioactivity in Milk

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Tritium ($\mu\text{Ci/mL}$)				
Denmark, SC	18	$6.80 \pm 1.50 \text{ E-07}$	$1.26 \pm 1.02 \text{ E-07}$	$3.59 \pm 1.85 \text{ E-07}$
Girard, GA	26	$2.32 \pm 0.08 \text{ E-06}$	$-0.11 \pm 1.16 \text{ E-07}$	$5.33 \pm 4.46 \text{ E-07}$
Gracewood, GA	21	$8.26 \pm 1.56 \text{ E-07}$	$0.18 \pm 1.16 \text{ E-07}$	$3.60 \pm 2.17 \text{ E-07}$
Jackson, SC	26	$1.42 \pm 0.16 \text{ E-06}$	$4.25 \pm 1.05 \text{ E-07}$	$8.62 \pm 3.23 \text{ E-07}$
Waynesboro, GA	25	$8.65 \pm 1.51 \text{ E-07}$	$-0.26 \pm 1.08 \text{ E-07}$	$3.44 \pm 2.52 \text{ E-07}$
Williston, SC	26	$9.59 \pm 1.71 \text{ E-07}$	$1.35 \pm 1.02 \text{ E-07}$	$5.48 \pm 2.59 \text{ E-07}$
Major Distributor	25	$6.86 \pm 1.50 \text{ E-07}$	$-0.56 \pm 1.00 \text{ E-07}$	$2.96 \pm 2.33 \text{ E-07}$
Sr-90 ($\mu\text{Ci/mL}$)				
Denmark, SC	2	$2.25 \pm 2.16 \text{ E-09}$	$0.04 \pm 1.12 \text{ E-08}$	$1.32 \pm 1.31 \text{ E-09}$
Girard, GA	2	$0.55 \pm 1.34 \text{ E-08}$	$4.37 \pm 2.39 \text{ E-09}$	$4.93 \pm 0.80 \text{ E-09}$
Gracewood, GA	2	$0.57 \pm 1.38 \text{ E-08}$	$5.35 \pm 4.75 \text{ E-09}$	$5.53 \pm 0.26 \text{ E-09}$
Jackson, SC	2	$2.17 \pm 2.31 \text{ E-09}$	$-0.24 \pm 1.15 \text{ E-08}$	$-0.13 \pm 3.25 \text{ E-09}$
Waynesboro, GA	2	$0.84 \pm 1.74 \text{ E-08}$	$3.99 \pm 3.54 \text{ E-09}$	$6.19 \pm 3.11 \text{ E-09}$
Williston, SC	2	$8.26 \pm 5.72 \text{ E-09}$	$-0.34 \pm 1.13 \text{ E-08}$	$2.44 \pm 8.22 \text{ E-09}$
Major Distributor	2	$-0.01 \pm 1.59 \text{ E-09}$	$-2.90 \pm 9.18 \text{ E-09}$	$-1.46 \pm 2.05 \text{ E-09}$
Cs-137 ($\mu\text{Ci/mL}$)				
Denmark, SC	19	$2.83 \pm 0.61 \text{ E-09}$	$1.97 \pm 0.56 \text{ E-09}$	$2.40 \pm 0.61 \text{ E-09}$
Girard, GA	24	$6.36 \pm 0.83 \text{ E-09}$	$2.33 \pm 0.57 \text{ E-09}$	$3.48 \pm 1.93 \text{ E-09}$
Gracewood, GA	20	$3.54 \pm 0.62 \text{ E-09}$	$2.49 \pm 0.57 \text{ E-09}$	$2.91 \pm 0.39 \text{ E-09}$
Jackson, SC	24	$2.89 \pm 0.60 \text{ E-09}$	$2.50 \pm 0.59 \text{ E-09}$	$2.72 \pm 0.20 \text{ E-09}$
Waynesboro, GA	22	$3.55 \pm 0.60 \text{ E-09}$	$2.17 \pm 0.77 \text{ E-09}$	$2.68 \pm 0.52 \text{ E-09}$
Williston, SC	19	$8.32 \pm 0.79 \text{ E-09}$	$2.75 \pm 0.59 \text{ E-09}$	$4.31 \pm 1.62 \text{ E-09}$
Major Distributor	24	$6.49 \pm 0.80 \text{ E-09}$	$3.01 \pm 0.58 \text{ E-09}$	$3.86 \pm 1.48 \text{ E-09}$
I-131 ($\mu\text{Ci/mL}$)				
Denmark, SC	19 / 0 ^a			
Girard, GA	24 / 0			
Gracewood, GA	20 / 0			
Jackson, SC	24 / 0			
Waynesboro, GA	22 / 0			
Williston, SC	19 / 0			
Major Distributor	24 / 0			

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 7-23
Radioactivity in Food

Location	Sr-90 (pCi/g $\pm$ σ) ^a	K-40 (pCi/g $\pm$ σ) ^a	Cs-137 (pCi/g $\pm$ σ) ^a	H-3 (pCi/g $\pm$ σ) ^b
Collards (15 locations)				
FS-1	1.2 $\pm$ 0.36 E-01	4.2 $\pm$ 0.15 E+0	—	1.8 $\pm$ 0.11 E-01
FS-2	5.3 $\pm$ 3.3 E-01	2.7 $\pm$ 0.14 E+0	—	1.3 $\pm$ 0.21 E-01
FS-3	1.8 $\pm$ 0.28 E-01	4.0 $\pm$ 0.17 E+0	—	6.4 $\pm$ 0.80 E-02
FS-4	1.4 $\pm$ 0.28 E-01	7.7 $\pm$ 0.26 E+0	1.4 $\pm$ 0.27 E-02	8.1 $\pm$ 1.2 E-02
FS-5	0.34 $\pm$ 4.6 E-02	—	—	3.8 $\pm$ 0.90 E-02
FS-6	2.0 $\pm$ 0.40 E-01	3.2 $\pm$ 0.13 E+0	2.0 $\pm$ 0.42 E-02	1.4 $\pm$ 0.14 E-01
FS-7	2.8 $\pm$ 3.1 E-02	3.8 $\pm$ 0.15 E+0	—	4.3 $\pm$ 1.2 E-02
FS-8	1.4 $\pm$ 0.37 E-01	3.4 $\pm$ 0.17 E+0	2.1 $\pm$ 0.36 E-02	3.6 $\pm$ 0.76 E-02
FS-9	4.9 $\pm$ 3.2 E-02	5.3 $\pm$ 0.23 E+0	—	9.8 $\pm$ 1.5 E-02
FS-10	3.5 $\pm$ 2.9 E-02	—	—	1.0 $\pm$ 0.10 E-01
FS-11	1.3 $\pm$ 0.37 E-01	3.5 $\pm$ 0.13 E+0	1.2 $\pm$ 0.33 E-02	1.5 $\pm$ 0.19 E-01
FS-12	1.4 $\pm$ 0.37 E-01	3.7 $\pm$ 0.15 E+0	1.1 $\pm$ 0.37 E-02	2.6 $\pm$ 0.81 E-02
FS-13	2.5 $\pm$ 0.42 E-01	3.6 $\pm$ 0.14 E+0	—	7.3 $\pm$ 1.1 E-02
FS-14	6.8 $\pm$ 3.4 E-02	3.6 $\pm$ 0.17 E+0	—	9.8 $\pm$ 0.86 E-02
FS-15 control	1.3 $\pm$ 0.34 E-01	—	—	4.7 $\pm$ 0.51 E-01
	U/Pu (pCi/g $\pm$ σ)^a	Pu-239 (pCi/g $\pm$ σ)^a	Pu-238 (pCi/g $\pm$ σ)^a	
FS-1	*	*	*	
FS-2	0.10 $\pm$ 3.2 E-03	*	*	
FS-3	-1.5 $\pm$ 2.8 E-03	*	*	
FS-4	*	8.6 $\pm$ 7.2 E-06	-6.9 $\pm$ 8.3 E-06	
FS-5	1.8 $\pm$ 3.6 E-03	*	*	
FS-6	3.4 $\pm$ 4.0 E-03	2.1 $\pm$ 1.6 E-05	-3.0 $\pm$ 1.3 E-05	
FS-7	1.8 $\pm$ 3.6 E-03	*	*	
FS-8	3.4 $\pm$ 4.0 E-03	*	*	
FS-9	-1.5 $\pm$ 2.8 E-03	*	*	
FS-10	0.09 $\pm$ 3.2 E-03	6.5 $\pm$ 7.3 E-06	0.83 $\pm$ 1.3 E-05	
FS-11	3.4 $\pm$ 4.0 E-03	*	*	
FS-12	*	*	*	
FS-13	-1.4 $\pm$ 2.8 E-03	*	*	
FS-14	3.4 $\pm$ 4.0 E-03	-8.4 $\pm$ 6.2 E-06	-2.9 $\pm$ 0.8 E-05	
FS-15 control	-1.5 $\pm$ 2.8 E-03	*	*	

* No samples counted.
— No quantifiable activity.

a. dry weight
b. wet weight

Table 7-23
Radioactivity in Food, Cont'd.

Location	Sr-90 (pCi/g $\pm \sigma$) ^a	K-40 (pCi/g $\pm \sigma$) ^a	Cs-137 (pCi/g $\pm \sigma$) ^a	H-3 (pCi/g $\pm \sigma$) ^b
CORN (14 locations)				
FS-1	$-2.3 \pm 4.1 \text{ E-04}$	$3.1 \pm 0.11 \text{ E+0}$	$7.3 \pm 2.2 \text{ E-03}$	*
FS-2	$-2.7 \pm 7.2 \text{ E-04}$	$1.7 \pm 0.07 \text{ E+0}$	$7.3 \pm 1.2 \text{ E-03}$	*
FS-3	$2.5 \pm 0.45 \text{ E-03}$	$3.0 \pm 0.12 \text{ E+0}$	—	*
FS-4	$1.9 \pm 6.2 \text{ E-04}$	$2.8 \pm 0.10 \text{ E+0}$	—	*
FS-5	$-6.9 \pm 8.6 \text{ E-04}$	$2.5 \pm 0.11 \text{ E+0}$	$7.7 \pm 1.6 \text{ E-03}$	*
FS-6	$-3.4 \pm 5.3 \text{ E-04}$	$3.0 \pm 0.12 \text{ E+0}$	$1.7 \pm 0.22 \text{ E-02}$	*
FS-7	$3.0 \pm 0.46 \text{ E-03}$	$2.9 \pm 0.12 \text{ E+0}$	—	*
FS-8	$3.5 \pm 0.61 \text{ E-03}$	$2.6 \pm 0.11 \text{ E+0}$	—	*
FS-9	$-3.6 \pm 4.7 \text{ E-04}$	$2.9 \pm 0.10 \text{ E+0}$	—	*
FS-10	$2.3 \pm 5.9 \text{ E-04}$	$3.4 \pm 0.13 \text{ E+0}$	—	*
FS-11	$-0.95 \pm 4.3 \text{ E-04}$	$2.8 \pm 0.12 \text{ E+0}$	$1.3 \pm 0.21 \text{ E-02}$	*
FS-12	$-0.58 \pm 6.0 \text{ E-04}$	—	—	*
FS-13	$3.3 \pm 0.49 \text{ E-03}$	—	—	*
FS-14	$-0.35 \pm 4.4 \text{ E-04}$	$2.4 \pm 0.10 \text{ E+0}$	—	*
	U/Pu (pCi/g $\pm \sigma$)^a	Pu-239 (pCi/g $\pm \sigma$)^a	Pu-238 (pCi/g $\pm \sigma$)^a	
FS-1	$0.09 \pm 4.2 \text{ E-03}$	*	*	
FS-2	$0.12 \pm 4.2 \text{ E-03}$	*	*	
FS-3	$-2.0 \pm 3.6 \text{ E-03}$	*	*	
FS-4	$2.2 \pm 4.7 \text{ E-03}$	$1.2 \pm 1.2 \text{ E-05}$	$-0.40 \pm 1.2 \text{ E-05}$	
FS-5	*	*	*	
FS-6	$-4.2 \pm 3.0 \text{ E-03}$	*	*	
FS-7	$-2.1 \pm 3.6 \text{ E-03}$	*	*	
FS-8	$6.5 \pm 5.6 \text{ E-03}$	*	*	
FS-9	$-4.2 \pm 3.0 \text{ E-03}$	*	*	
FS-10	$-0.42 \pm 3.0 \text{ E-02}$	$-2.4 \pm 1.7 \text{ E-05}$	$-0.40 \pm 2.1 \text{ E-05}$	
FS-11	$-2.0 \pm 3.6 \text{ E-03}$	*	*	
FS-12	$0.09 \pm 4.2 \text{ E-03}$	$0.0 \pm 6.2 \text{ E-05}$	$0.30 \pm 1.2 \text{ E-04}$	
FS-13	$-4.2 \pm 3.0 \text{ E-03}$	*	*	
FS-14	$-4.2 \pm 3.0 \text{ E-03}$	*	*	

* No samples counted.
 — No quantifiable activity.

a. dry weight
 b. wet weight

Table 7-23
Radioactivity in Food, Cont'd.

Location	Sr-90 (pCi/g $\pm \sigma$) ^a	K-40 (pCi/g $\pm \sigma$) ^a	Cs-137 (pCi/g $\pm \sigma$) ^a	H-3 (pCi/g $\pm \sigma$) ^b
GRAIN (14 locations)				
FS-1	$-1.2 \pm 0.12 \text{ E-02}$	$3.7 \pm 0.14 \text{ E+0}$	—	*
FS-2	$-7.4 \pm 1.5 \text{ E-03}$	$3.2 \pm 0.11 \text{ E+0}$	$5.6 \pm 2.1 \text{ E-03}$	*
FS-3	$6.0 \pm 2.2 \text{ E-03}$	$4.3 \pm 0.14 \text{ E+0}$	—	*
FS-4	$3.1 \pm 0.19 \text{ E-02}$	$3.3 \pm 0.14 \text{ E+0}$	—	*
FS-5	$5.0 \pm 0.17 \text{ E-02}$	$3.3 \pm 0.14 \text{ E+0}$	—	*
FS-6	$-1.3 \pm 0.20 \text{ E-02}$	—	—	*
FS-7	$-2.4 \pm 1.8 \text{ E-03}$	—	—	*
FS-8	$-1.1 \pm 0.14 \text{ E-02}$	$3.7 \pm 0.14 \text{ E+0}$	$2.3 \pm 0.26 \text{ E-02}$	*
FS-9	$1.0 \pm 0.26 \text{ E-02}$	$4.4 \pm 0.14 \text{ E+0}$	—	*
FS-10	$5.2 \pm 0.17 \text{ E-02}$	$3.5 \pm 0.14 \text{ E+0}$	—	*
FS-11	$4.5 \pm 1.2 \text{ E-03}$	$3.0 \pm 0.11 \text{ E+0}$	—	*
FS-12	$3.0 \pm 0.14 \text{ E-02}$	$3.6 \pm 0.12 \text{ E+0}$	—	*
FS-13	$1.4 \pm 0.13 \text{ E-02}$	$2.8 \pm 0.12 \text{ E+0}$	—	*
FS-14	$1.2 \pm 0.15 \text{ E-02}$	$3.2 \pm 0.13 \text{ E+0}$	—	*
	U/Pu (pCi/g $\pm \sigma$)^a	Pu-239 (pCi/g $\pm \sigma$)^a	Pu-238 (pCi/g $\pm \sigma$)^a	
FS-1	$-1.6 \pm 2.9 \text{ E-03}$	*	*	
FS-2	$-3.3 \pm 2.3 \text{ E-03}$	$0.33 \pm 2.8 \text{ E-05}$	$1.5 \pm 5.0 \text{ E-05}$	
FS-3	$-1.6 \pm 2.9 \text{ E-03}$	$-1.3 \pm 1.2 \text{ E-05}$	$0.09 \pm 1.2 \text{ E-05}$	
FS-4	$-1.6 \pm 2.9 \text{ E-03}$	$-2.4 \pm 2.2 \text{ E-05}$	$-7.3 \pm 4.2 \text{ E-05}$	
FS-5	$0.04 \pm 3.3 \text{ E-03}$	*	*	
FS-6	$0.05 \pm 3.3 \text{ E-03}$	*	*	
FS-7	$-1.6 \pm 2.9 \text{ E-03}$	$-2.0 \pm 3.5 \text{ E-05}$	$-1.1 \pm 3.7 \text{ E-05}$	
FS-8	$1.7 \pm 3.7 \text{ E-03}$	*	*	
FS-9	$0.07 \pm 3.3 \text{ E-03}$	*	*	
FS-10	$-3.3 \pm 2.3 \text{ E-03}$	$-2.7 \pm 3.4 \text{ E-05}$	$4.8 \pm 6.2 \text{ E-05}$	
FS-11	$-3.3 \pm 2.3 \text{ E-03}$	*	*	
FS-12	$3.4 \pm 4.1 \text{ E-03}$	*	*	
FS-13	$-3.3 \pm 2.3 \text{ E-03}$	*	*	
FS-14	$-3.3 \pm 2.3 \text{ E-03}$	*	*	

* No samples counted.
 — No quantifiable activity.

a. dry weight
 b. wet weight

Table 7-23
Radioactivity in Food, Cont'd.

Location	Sr-90 (pCi/g $\pm$ σ) ^a	K-40 (pCi/g $\pm$ σ) ^a	Cs-137 (pCi/g $\pm$ σ) ^a	H-3 (pCi/g $\pm$ σ) ^b
FRUIT (12 locations)				
FS-1	2.0 $\pm$ 0.24 E-02	1.8 $\pm$ 0.09 E+01	—	1.4 $\pm$ 0.67 E-01
FS-2	-3.9 $\pm$ 1.4 E-03	1.8 $\pm$ 0.08 E+0	—	1.5 $\pm$ 0.55 E-01
FS-3	2.6 $\pm$ 2.9 E-02	1.9 $\pm$ 0.08 E+01	—	*
FS-4	2.9 $\pm$ 3.3 E-02	2.3 $\pm$ 0.09 E+01	—	2.8 $\pm$ 0.33 E-01
FS-6	2.9 $\pm$ 2.7 E-02	2.5 $\pm$ 0.09 E+01	—	6.3 $\pm$ 0.81 E-01
FS-7	7.4 $\pm$ 3.4 E-02	1.8 $\pm$ 0.09 E+01	—	2.0 $\pm$ 0.83 E-01
FS-9	-1.8 $\pm$ 0.14 E-02	1.9 $\pm$ 0.08 E+0	—	8.0 $\pm$ 2.6 E-02
FS-10	3.7 $\pm$ 2.8 E-02	1.9 $\pm$ 0.09 E+01	—	3.7 $\pm$ 1.2 E-01
FS-11	-3.7 $\pm$ 0.14 E-02	1.8 $\pm$ 0.08 E+0	—	3.3 $\pm$ 1.0 E-01
FS-12	0.62 $\pm$ 2.2 E-02	2.3 $\pm$ 0.09 E+01	—	2.7 $\pm$ 0.09 E-0
FS-13	1.6 $\pm$ 0.15 E-02	1.9 $\pm$ 0.09 E+0	—	*
FS-14	0.72 $\pm$ 1.4 E-03	1.9 $\pm$ 0.09 E+0	—	2.8 $\pm$ 0.99 E-01
	U/Pu (pCi/g $\pm$ σ)^a	Pu-239 (pCi/g $\pm$ σ)^a	Pu-238 (pCi/g $\pm$ σ)^a	
FS-1	-3.3 $\pm$ 2.3 E-03	*	*	
FS-2	-3.2 $\pm$ 2.3 E-03	0.0 $\pm$ 1.2 E-05	-2.3 $\pm$ 0.80 E-05	
FS-3	-3.3 $\pm$ 2.3 E-03	*	*	
FS-4	-1.6 $\pm$ 2.9 E-03	*	*	
FS-6	1.8 $\pm$ 3.8 E-03	*	*	
FS-7	-1.6 $\pm$ 2.9 E-03	*	*	
FS-9	0.14 $\pm$ 3.4 E-03	1.6 $\pm$ 2.3 E-05	-0.63 $\pm$ 1.9 E-05	
FS-10	-1.5 $\pm$ 2.9 E-03	*	*	
FS-11	-3.3 $\pm$ 2.3 E-03	1.3 $\pm$ 1.7 E-05	3.0 $\pm$ 2.1 E-05	
FS-12	-1.6 $\pm$ 2.9 E-03	*	*	
FS-13	-3.3 $\pm$ 2.3 E-03	*	*	
FS-14	-3.3 $\pm$ 2.3 E-03	-2.7 $\pm$ 1.8 E-05	-3.6 $\pm$ 1.5 E-05	

* No samples counted.
 — No quantifiable activity.

a. dry weight
 b. wet weight

Table 7-23
Radioactivity in Food, Cont'd.

Location	Sr-90 (pCi/g $\pm$ σ) ^a	K-40 (pCi/g $\pm$ σ) ^a	Cs-137 (pCi/g $\pm$ σ) ^a	H-3 (pCi/g $\pm$ σ) ^b
CHICKEN (4 locations)				
FS-1	$-6.0 \pm 1.2 \text{ E-03}$	—	—	$1.8 \pm 0.30 \text{ E-01}$
FS-4	$7.1 \pm 1.1 \text{ E-03}$	—	—	$1.8 \pm 0.27 \text{ E-01}$
FS-8	$5.3 \pm 1.4 \text{ E-03}$	$3.3 \pm 0.13 \text{ E+0}$	$9.1 \pm 3.9 \text{ E-03}$	$2.1 \pm 0.37 \text{ E-01}$
FS-10	$-1.4 \pm 1.2 \text{ E-03}$	—	—	$5.7 \pm 2.9 \text{ E-02}$
	U/Pu (pCi/g $\pm$ σ) ^a	Pu-239 (pCi/g $\pm$ σ) ^a	Pu-238 (pCi/g $\pm$ σ) ^a	
FS-1	$3.4 \pm 3.3 \text{ E-03}$	$-1.5 \pm 0.97 \text{ E-05}$	$4.9 \pm 2.6 \text{ E-05}$	
FS-4	$0.07 \pm 2.3 \text{ E-03}$	$8.9 \pm 9.1 \text{ E-06}$	$-4.5 \pm 2.1 \text{ E-05}$	
FS-8	$-1.6 \pm 1.6 \text{ E-03}$	$0.17 \pm 1.0 \text{ E-05}$	$-1.4 \pm 2.0 \text{ E-05}$	
FS-10	$0.05 \pm 2.3 \text{ E-03}$	*	*	
BEEF (4 locations)				
	Sr-90 (pCi/g $\pm$ σ) ^a	K-40 (pCi/g $\pm$ σ) ^a	Cs-137 (pCi/g $\pm$ σ) ^a	H-3 (pCi/g $\pm$ σ) ^b
FS-3	$2.9 \pm 1.4 \text{ E-03}$	—	—	$2.4 \pm 0.42 \text{ E-01}$
FS-7	$1.6 \pm 1.1 \text{ E-03}$	$2.1 \pm 0.21 \text{ E+0}$	—	$6.8 \pm 3.2 \text{ E-02}$
FS-9	$-1.6 \pm 0.11 \text{ E-02}$	$2.9 \pm 0.10 \text{ E-0}$	—	$0.61 \pm 1.7 \text{ E-02}$
FS-13	$0.32 \pm 1.6 \text{ E-03}$	—	—	$7.9 \pm 1.5 \text{ E-02}$
	U/Pu (pCi/g $\pm$ σ) ^a	Pu-239 (pCi/g $\pm$ σ) ^a	Pu-238 (pCi/g $\pm$ σ) ^a	
FS-3	$-3.1 \pm 2.2 \text{ E-02}$	*	*	
FS-7	$-1.5 \pm 2.8 \text{ E-03}$	$-7.7 \pm 7.7 \text{ E-05}$	$0.61 \pm 1.1 \text{ E-04}$	
FS-9	$-3.1 \pm 2.2 \text{ E-03}$	$6.0 \pm 3.4 \text{ E-05}$	$-3.4 \pm 4.3 \text{ E-05}$	
FS-13	$-3.1 \pm 2.2 \text{ E-03}$	$-4.2 \pm 4.2 \text{ E-05}$	$1.5 \pm 0.85 \text{ E-04}$	

* No samples counted.

— No quantifiable activity.

a. dry weight

b. wet weight

Table 7-23
Radioactivity in Food, Cont'd.

Location	Sr-90 (pCi/g $\pm \sigma$) ^a	K-40 (pCi/g $\pm \sigma$) ^a	Cs-137 (pCi/g $\pm \sigma$) ^a	H-3 (pCi/g $\pm \sigma$) ^b
PORK (4 locations)				
FS-3	$4.2 \pm 1.1 \text{ E-03}$	$3.2 \pm 0.25 \text{ E+0}$	–	$4.6 \pm 2.2 \text{ E-01}$
FS-7	$8.0 \pm 1.2 \text{ E-03}$	$3.0 \pm 0.13 \text{ E+0}$	–	$3.8 \pm 2.2 \text{ E-01}$
FS-9	$-1.8 \pm 1.1 \text{ E-03}$	–	–	$1.6 \pm 2.1 \text{ E-01}$
FS-13	$1.1 \pm 0.12 \text{ E-02}$	$2.8 \pm 0.21 \text{ E+0}$	$1.5 \pm 0.35 \text{ E-02}$	*
	U/Pu (pCi/g $\pm \sigma$) ^a	Pu-239 (pCi/g $\pm \sigma$) ^a	Pu-238 (pCi/g $\pm \sigma$) ^a	
FS-3	*	$9.9 \pm 8.6 \text{ E-06}$	$3.7 \pm 1.5 \text{ E-05}$	
FS-7	*	$1.0 \pm 0.68 \text{ E-05}$	$-1.2 \pm 0.73 \text{ E-05}$	
FS-9	*	$0.0 \pm 1.7 \text{ E-05}$	$-2.3 \pm 0.83 \text{ E-05}$	
FS-13	$5.6 \pm 9.8 \text{ E-06}$	$5.6 \pm 9.8 \text{ E-06}$	$-0.64 \pm 1.6 \text{ E-05}$	

* No samples counted.
 – No quantifiable activity.

a. dry weight
 b. wet weight

Table 7-23
Radioactivity in Food, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
EGGS (8 locations)				
Sr-90 (pCi/g; dry weight)				
FS-2	1	$3.7 \pm 0.13 \text{ E-02}$	$3.7 \pm 0.13 \text{ E-02}$	$3.7 \pm 0.13 \text{ E-02}$
FS-3	1	$3.1 \pm 1.4 \text{ E-03}$	$3.1 \pm 1.4 \text{ E-03}$	$3.1 \pm 1.4 \text{ E-03}$
FS-4	1	$7.1 \pm 1.2 \text{ E-03}$	$7.1 \pm 1.2 \text{ E-03}$	$7.1 \pm 1.2 \text{ E-03}$
FS-5	4	$4.9 \pm 0.12 \text{ E-02}$	$4.6 \pm 1.4 \text{ E-03}$	$2.2 \pm 2.1 \text{ E-02}$
FS-6	1	$1.6 \pm 0.13 \text{ E-02}$	$1.6 \pm 0.13 \text{ E-02}$	$1.6 \pm 0.13 \text{ E-02}$
FS-8	3	$5.9 \pm 2.9 \text{ E-02}$	$-1.0 \pm 0.13 \text{ E-02}$	$2.1 \pm 3.5 \text{ E-02}$
FS-10	4	$1.5 \pm 0.11 \text{ E-02}$	$-1.9 \pm 0.14 \text{ E-02}$	$-0.07 \pm 1.7 \text{ E-02}$
FS-13	1	$0.72 \pm 2.6 \text{ E-02}$	$0.72 \pm 2.6 \text{ E-02}$	$0.72 \pm 2.6 \text{ E-02}$
U/Pu (pCi/g; dry weight)				
FS-2	1	$0.08 \pm 2.3 \text{ E-03}$	$0.08 \pm 2.3 \text{ E-03}$	$0.08 \pm 2.3 \text{ E-03}$
FS-3	1	$-2.8 \pm 5.1 \text{ E-03}$	$-2.8 \pm 5.1 \text{ E-03}$	$-2.8 \pm 5.1 \text{ E-03}$
FS-4	1	$0.06 \pm 2.3 \text{ E-03}$	$0.06 \pm 2.3 \text{ E-03}$	$0.06 \pm 2.3 \text{ E-03}$
FS-5	4	$3.4 \pm 3.3 \text{ E-03}$	$-2.8 \pm 5.1 \text{ E-03}$	$0.01 \pm 2.6 \text{ E-03}$
FS-6	1	$-2.8 \pm 5.1 \text{ E-03}$	$-2.8 \pm 5.1 \text{ E-03}$	$-2.8 \pm 5.1 \text{ E-03}$
FS-8	3	$-1.5 \pm 8.5 \text{ E-03}$	$-5.8 \pm 4.1 \text{ E-03}$	$-4.4 \pm 2.5 \text{ E-03}$
FS-10	4	$-1.6 \pm 1.6 \text{ E-03}$	$-5.9 \pm 4.1 \text{ E-03}$	$-3.7 \pm 2.4 \text{ E-03}$
FS-13	1	$-3.7 \pm 3.2 \text{ E-03}$	$-3.7 \pm 3.2 \text{ E-03}$	$-3.7 \pm 3.2 \text{ E-03}$
H-3 (pCi/g; wet weight)				
FS-2	1	$2.2 \pm 0.58 \text{ E-01}$	$2.2 \pm 0.58 \text{ E-01}$	$2.2 \pm 0.58 \text{ E-01}$
FS-3	0			
FS-4	1	$2.2 \pm 0.44 \text{ E-01}$	$2.2 \pm 0.44 \text{ E-01}$	$2.2 \pm 0.44 \text{ E-01}$
FS-5	2	$4.2 \pm 0.82 \text{ E-01}$	$8.8 \pm 1.6 \text{ E-02}$	$2.5 \pm 2.4 \text{ E-01}$
FS-6	1	$4.4 \pm 1.4 \text{ E-02}$	$4.4 \pm 1.4 \text{ E-02}$	$4.4 \pm 1.4 \text{ E-02}$
FS-8	2	$2.1 \pm 0.37 \text{ E-01}$	$1.2 \pm 0.15 \text{ E-01}$	$1.6 \pm 0.64 \text{ E-01}$
FS-10	4	$2.7 \pm 0.38 \text{ E-01}$	$3.7 \pm 1.6 \text{ E-02}$	$1.2 \pm 1.1 \text{ E-01}$
FS-13	1	$1.8 \pm 0.13 \text{ E+0}$	$1.8 \pm 0.13 \text{ E+0}$	$1.8 \pm 0.13 \text{ E+0}$

Table 7-23
Radioactivity in Food, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
EGGS (8 locations)				
K-40 (pCi/g; dry weight)				
FS-2	1 / 0 ^a			
FS-3	1 / 1	1.4 $\pm$ 0.07 E+0	1.4 $\pm$ 0.07 E+0	1.4 $\pm$ 0.07 E+0
FS-4	1 / 1	1.2 $\pm$ 0.05 E+0	1.2 $\pm$ 0.05 E+0	1.2 $\pm$ 0.05 E+0
FS-5	4 / 4	1.3 $\pm$ 0.05 E+0	1.1 $\pm$ 0.07 E+0	1.2 $\pm$ 0.09 E+0
FS-6	1 / 1	1.4 $\pm$ 0.07 E+0	1.4 $\pm$ 0.07 E+0	1.4 $\pm$ 0.07 E+0
FS-8	3 / 3	1.3 $\pm$ 0.07 E+0	1.2 $\pm$ 0.06 E+0	1.2 $\pm$ 0.08 E+0
FS-10	4 / 4	1.2 $\pm$ 0.07 E+0	1.1 $\pm$ 0.07 E+0	1.2 $\pm$ 0.07 E+0
FS-13	1 / 1	1.2 $\pm$ 0.06 E+0	1.2 $\pm$ 0.06 E+0	1.2 $\pm$ 0.06 E+0
Cs-137 (pCi/g; dry weight)				
FS-2	1 / 0			
FS-3	1 / 0			
FS-4	1 / 0			
FS-5	4 / 0			
FS-6	1 / 0			
FS-8	3 / 0			
FS-10	4 / 1	2.7 $\pm$ 0.87 E-03	2.7 $\pm$ 0.87 E-03	2.7 $\pm$ 0.87 E-03
FS-13	1 / 0			

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

To Learn About:	Turn to page:
♦ Surface Water	
Radiological Water Monitoring	200
Nonradiological Water Monitoring	211
♦ Sediment	214
♦ Drinking Water	216
♦ Groundwater	221

Compiled by
G. Tim Jannik and George A. Taylor
Environmental Protection Department

Linda L. Basinger
Exploration Resources

Water Pathways

1991 HIGHLIGHTS

- ♦ The radiation dose to the maximally exposed individual from SRS releases of radioactivity to the Savannah River was 0.34 mrem (0.0034 mSv), which is 0.34 percent of the 100 mrem DOE limit for annual exposure. This dose results primarily from Cs-137 and the consumption of fish.
- ♦ Total releases of tritium from SRS (including direct releases and migration) were 27,400 Ci. This was 70 percent higher than the 1990 total of 16,100 Ci. This increase is partially due to the K-Area tritium release in December 1991 (Chapter 10, "Nonroutine Occurrences") and increased migration from site seepage basins.
- ♦ SRS had a 99.92 percent NPDES compliance rate in 1991. Of the 8,329 analyses performed, only seven exceeded the permit limits. Four outfall sample points in D, P, S, and Y Areas were removed from the permit Nov. 4, 1991.
- ♦ Tritium in drinking water downriver is attributed to SRS operations and represents 89.5 percent of the dose received by individuals at the downriver water treatment plants. The maximum dose to persons receiving water from either Beaufort-Jasper or Port Wentworth in 1991 was 0.099 mrem (.00099mSv), based on maximum consumption. This dose is 2.5 percent of the EPA and DOE standard of 4 mrem per year.
- ♦ The SRS Groundwater Monitoring Program included analyses for several hundred radioactive and nonradioactive constituents from approximately 1,400 wells at more than 90 locations. Four new well series, representing 41 wells, were added to the program during the year, and 196 new wells added to existing well series were monitored for the first time.

INTRODUCTION

Water pathway monitoring at Savannah River Site (SRS) encompasses the sampling and analysis of liquid effluents, surface waters, groundwater, drinking water, seepage basin water, and sediment.

Extensive monitoring is performed on the Savannah River, which flows along a 20-mile border of the site; on the six onsite streams; and on the SRS region's groundwater and drinking water.

Monitoring activities are performed by the Environmental Protection Department's Environmental Monitoring Section (EPD/EMS) and the Savannah River

Laboratory (SRL). The Savannah River is also monitored by other groups including the South Carolina Department of Health and Environmental Control (SCDHEC) and the Georgia Department of Natural Resources (GDNR). A complete description of the sample collection and analytical procedures used for surface waters and groundwater can be found in Chapter 4, "Sample Collection, Analytical Procedures, and Data Interpretation."

Water pathway monitoring verifies that ambient concentrations and radiation doses from SRS liquid releases are within applicable regulatory standards. It

also provides verification that dose calculation models are appropriate and conservative.

SURFACE WATER

Radiological Water Monitoring

1991 Releases of Radioactivity to Surface Water

Each process area liquid effluent discharge point that releases (or has the potential to release) radioactive materials is routinely sampled and analyzed for radioactivity. Refer to Chapter 4 for a description of the analytical procedures used for water samples.

Site streams also are sampled upgradient and downgradient of seepage basins in order to calculate the amount of radioactivity migrating from the basins. These results are important in calculating the total levels of radioactivity released to the Savannah River as a result of SRS operations.

Applicable Regulations

U.S. Department of Energy (DOE) Order 5400.1, "General Environmental Protection Program," requires that liquid effluent monitoring be conducted at all DOE sites [DOE, 1988a].

Effluent Monitoring Results

Direct releases of radioactive materials to onsite streams in 1991 are shown by source in Chart 8-1. Tritium was the major radionuclide released in the liquid effluents. The total tritium directly released in

1991 was 11,300 Ci, which was over four times higher than the 1990 release of 2,620 Ci. This increase was due partially to the December 1991 tritium release from K Area (Chapter 10, "Nonroutine Occurrences") and partially to increased operations at the Separations Area Effluent Treatment Facility and at the Heavy Water Rework Facility in D Area. Table 8-1 shows the direct releases of tritium to site streams for the years 1987 through 1991. Figure 8-1 presents this same data in graphical form.

Seepage Basin Migration Results

To incorporate the migration of radioactivity to site streams into total radioactive release quantities, EMS monitors and quantifies the migration of radioactivity from site seepage basins. During 1991, only tritium and Sr-90 were detectable in seepage basin migration. Results of these calculations are presented in Table 8-2.

The continuation page of Table 8-1 shows the releases of tritium via migration to site streams for the years 1987 through 1991. Figure 8-2 gives a graphical representation of this same data. The total quantity of tritium released from the seepage basins through migration was 16,100 Ci in 1991, compared with a release of 13,500 Ci in 1990.

Figure 8-3 shows the total combined tritium releases from direct discharges and seepage basin migration for the years 1986 through 1991. The tritium migrating from seepage basins in 1991 represented 59

Chart 8-1
1991 Direct Discharges of Radioactive Liquid Effluents by Source

Nuclide	(Ci)					Total
	Reactors	Separations	Reactor Materials	Heavy Water	SRL/TNX	
H-3	7.51E+03	3.09E+03	0.00E+00	6.81E+02	2.25E-01	1.13E+04
Sr-90 ^a	3.57E-02	3.90E-02	5.74E-03	7.32E-03	1.32E-03	8.90E-02
Cs-137	0.00E+00	2.64E-02	0.00E+00	0.00E+00	0.00E+00	2.64E-02
Pm-147	0.00E+00	6.63E-03	0.00E+00	0.00E+00	0.00E+00	6.63E-03
U-235,236	0.00E+00	2.22E-05	3.22E-03	0.00E+00	0.00E+00	3.24E-03
Pu-239 ^b	1.24E-03	1.58E-02	0.00E+00	2.56E-04	2.85E-03	2.01E-02

a Includes unidentified beta-gamma.

b Includes unidentified alpha.

Figure 8-1 Direct releases of tritium to site streams.

Figure 8-2 Tritium migration from seepage basins to site streams.

Figure 8-3 Total tritium releases (direct and migration combined).

percent of the total amount of tritium released to site streams.

Figure 8-4 presents a sketch of how radionuclides can physically migrate from seepage basins and then outcrop into streams. Refer to Chapter 2, "Environmental Compliance," for a discussion on SRS seepage basin closures.

Migration of Radioactivity from the K-Area Drain Field and Seepage Basin

Liquid purges from the K-Area disassembly basin were released to the K-Area seepage basin in 1959 and 1960. Since 1960, purges from the K-Area disassembly basin have been discharged to a drainage field located below the K-Area retention basin. A total tritium migration of 2160 Ci was calculated from weekly flow measurements and tritium concentrations measured in Indian Grave Branch (a tributary of Pen Branch) during 1991. This migration represents a 39% decrease from 1990.

Migration of Radioactivity from F- and H-Area Seepage Basins

Although seepage basins in F and H areas are no longer used, radioactivity previously deposited in them continues to migrate via the groundwater and outcrop into Four Mile Creek. Migration of radioactivity from F- and H-Area seepage basins was

measured with continuous samplers and flow recorders in Four Mile Creek. Groundwater from the F-Area seepage basins enters Four Mile Creek between sampling locations FMC-3A, FMC-2B, and FMC-A7. Four Mile Creek sampling locations are shown in Figure 8-5.

Most of the outcropping from H-Area seepage basins 1, 2, and 3 occurs between FMC-1C and FMC-2B. Additional outcropping from H-Area seepage basin 4 and the Solid Waste Disposal Facility (SWDF) occurs between FMC-3 and FMC-3A.

Radioactivity from the H-Area seepage basins and the SWDF mixes during groundwater migration to Four Mile Creek. Therefore, radioactivity from the two sources cannot be distinguished at the outcrop point.

As shown in Table 8-1 and Table 8-2, measured migration of tritium from F-Area seepage basins was 5750 Ci in 1991, a 61 percent increase over 1990. The measured migration from H-Area seepage basin 4 and the SWDF was 6420 Ci, which was a 50 percent increase over 1990. Reasons for these increases are being investigated. The measured migration from H-Area seepage basins 1, 2, and 3 was 1810 Ci (a 5 percent decrease from 1990.)

In 1991, the amount of Sr-90 entering Four Mile Creek was 460 mCi from F-Area seepage basins and 54 mCi from H-Area seepage basins. This was an increase of 138 percent over the 1990 releases. The reason for this

Figure 8-4 Radionuclide migration from seepage basins to streams.

increase is not known at this time. In 1991, there was no Cs-137 migration detected from the F- or H-area seepage basins. Also, desorption of Cs-137 from sediments in the Four Mile Creek bed could not be distinguished from the direct Cs-137 releases into the stream.

A comparison of the radioactivity measured in transport at sample points on Four Mile Creek for 1990 and 1991 is shown in Table 8-3.

Migration from P- and C-Area Seepage Basins

Liquid purges from the P-, L- and C-area disassembly basins have been released to their respective seepage basins since 1978. Purge water is released to the seepage basins to allow a significant part of the tritium to decay before the water outcrops to surface streams and flows into the Savannah River. The delaying action of the basins reduces the dose that users of water at downriver water treatment plants receive from SRS tritium releases. Although the seepage basins were used for purging the disassembly basins from the 1950s until 1970, disassembly basin purge water was released directly to SRS streams between 1970 and 1978. The earlier experience with seepage basins indicated that the extent of radioactive decay during the holdup was sufficient to recommend that the basins be used again in P, L, and C areas.

Results of samples taken from Twin Lakes and Castor Creek near C Area indicated that no radionuclide migration could be attributed to the C-Area seepage basin in 1991. The failure of the Twin Lakes Dam in 1991 has made the determination of migration more difficult in this area (Chapter 10). Results from a sampler installed on Steel Creek above L Lake indicated 364 Ci of tritium migrated from the P-Area seepage basin during 1991, which was an increase of 63 percent over 1990. Migration of radionuclides from the L-Area seepage basin has not been detected in site streams. The continuation page of Table 8-1 shows the releases of tritium from the P- and C-Area seepage basins for the years 1987 through 1991.

Radionuclide Concentrations in Water

The average concentrations of specific radionuclides in offsite water are either calculated or directly measured at three locations: in the Savannah River just below SRS; in Beaufort-Jasper drinking water; and in Port Wentworth drinking water. The water treatment plants at Beaufort-Jasper, S.C., and Port Wentworth, Ga., are approximately 100 miles downriver from SRS. Concentration values are used to

estimate offsite doses and to verify that SRS liquid effluents are within applicable standards.

Applicable Regulations

Concentration guides for radionuclides in water, called Derived Concentration Guides (DCGs), are given in DOE Order 5400.5 (DOE, 1990a). These guides, based on recommendations in the International Commission on Radiological Protection (ICRP) Publications 26 and 30 [ICRP, 1977, and ICRP, 1979], are used as screening values for considering best available technology (BAT) for treatment of liquid effluents and for making dose estimates. DOE exempts tritium from BAT requirements.

The DCGs are defined as the concentration of a radionuclide in water that will give a 50-year committed dose of 100 mrem under conditions of continuous exposure for one year.

Calculated and Measured Concentration Results

Chart 8-2 provides a comparison of the total quantities of radioactivity released from SRS to the subsequent concentrations downriver from SRS and to the specific radionuclide DCGs. The majority of the concentrations shown in Chart 8-2 were calculated, rather than measured, because most radionuclide concentrations in the Savannah River are below detectable levels. The 1991 average river flow rate was 11,598 ft³/sec, which was measured at the United States Geological Survey (USGS) station located at River 10 (River Mile 120). Measured concentrations are shown for tritium, Sr-90, and Cs-137.

The total-release quantities shown were determined by adding the total direct releases to site streams (Chart 8-1) to any measured migration from seepage basins (or the SWDF), desorption from stream beds, and any lake or pond overflows (Table 8-2).

As shown in Chart 8-2, the maximum offsite concentration of radionuclides occurs in the Savannah River just below SRS. As to be expected, tritium had the highest concentration of all radionuclides at all locations. Concentrations of all radionuclides at each location were well below Environmental Protection Agency (EPA) drinking water standards [EPA, 1975, and EPA, 1977], and the DCGs.

Offsite Radiation Doses from Releases to Surface Waters

During 1991, offsite effective dose equivalents (EDEs) from SRS liquid releases were calculated for individuals living at the site perimeter and for the pop-

Chart 8-2
Radioactive Liquid Releases from SRS and Comparison of Downriver Concentrations to DOE-Derived Concentration Guides

Nuclide	Ci Released	Concentration ($\mu\text{Ci/mL}$)			
		DCG ^a	Below SRS ^b	Beaufort-Jasper ^c	Port Wentworth ^d
H-3 ^e	2.74E+04	2.0E-03	3.2E-06 ^f	1.6E-06 ^f	1.9E-06 ^f
Sr-90 ^e	6.03E-01	1.0E-06	1.4E-10 ^f	3.5E-11	4.2E-11
I-129 ^e	2.20E-02	5.0E-07	2.3E-12	1.3E-12	1.5E-12
Cs-137	2.64E-02	3.0E-06	4.9E-11 ^f	1.5E-12	1.8E-12
Pm-147	6.63E-03	1.0E-04	7.1E-13	3.8E-13	4.6E-13
U-235,238	3.24E-03	6.0E-07	3.5E-13	1.9E-13	2.3E-13
Pu-239	2.01E-02	3.0E-08	2.1E-12	1.2E-12	1.4E-12

a Source: DOE Order 5400.5. DCGs are defined as the ingested water concentration of a radionuclide that would result in a 50-year committed dose of 100 mrem under conditions of continuous exposure for year. This assumes a person ingests 730 liters of drinking water a year, or two liters per day.

b Savannah River just downriver from SRS.

c Beaufort-Jasper, S.C., drinking water.

d Port Wentworth, Ga., drinking water.

e Includes releases to streams and groundwater migration from seepage basins.

f Measured concentrations. All other concentrations were calculated using models verified with tritium measurements.

ulation served by the water treatment plants at Beaufort-Jasper and Port Wentworth. The calculated individual and collective doses from 1991 liquid releases are presented in Tables 8-4 through 8-7.

The liquid source terms (total Ci released by radionuclide) used for dose calculations are shown in Chart 8-2. For dose calculations, releases of unidentified beta-gamma emitters were summed with Sr-90 releases and releases of unidentified alpha emitters were summed with releases of Pu-239. The LADTAPII computer code (Chapter 6, "Calculating Radiation Doses") is used at SRS for dose calculations.

Offsite doses from liquid releases vary each year with the amount of radionuclides released and the amount of dilution (flow rate) in the Savannah River. Although flow rates are recorded at USGS gauging stations at the SRS Boat Dock and at River 10 (River Mile 120), these data are not used in dose calculations. Instead, flow rates for dose calculations are calculated from measured tritium releases and measured tritium concentrations in river water. The measured flow rates are used to verify the calculated flow rates.

The calculated flow rates used for Beaufort-Jasper and Port Wentworth are "effective" flow rates that account for additional dilution in the water treatment

plants' pumping systems. The calculated flow at River 10 is used in calculating maximum individual doses, collective doses, and potential doses from irrigation with river water.

Applicable Regulations

EPA drinking water standards for radionuclides and dose limits apply at the water treatment plants serving Beaufort and Jasper counties in South Carolina and Port Wentworth in Georgia [EPA, 1975]. Drinking water standards for specific radionuclides are listed in Appendix C.

DOE Order 5400.5, "Radiation Protection of the Public and Environment," incorporates the dose limit from the EPA drinking water standards (DOE, 1990a). The Order states that normal operations at DOE facilities shall not result in an EDE from drinking water greater than 4 mrem/year to any member of the public. In addition, the all-pathway individual EDE shall be limited to 100 mrem/year.

Maximum Individual EDE

Table 8-4 gives the maximum calculated offsite EDE to a hypothetical individual from SRS releases of radioactivity to the Savannah River. The parameters used for calculating maximum offsite doses to the

Chart 8-3
Calculated Maximum Individual Dose Commitment from SRS Liquid Releases in 1991

	Committed EDE	Applicable Standard	Percent of Standard
Maximally Exposed Individual at			
Site Boundary (“fence post” individual)	0.34 mrem	100 mrem ^a	0.34
Beaufort-Jasper (public water supply only)	0.081 mrem	4 mrem ^b	2.0
Port Wentworth (public water supply only)	0.099 mrem	4 mrem ^b	2.5

a All-Pathway Standard: 100 mrem/year. [DOE Order 5400.5]

b Drinking Water Pathway Standard: 4 mrem/year. [DOE Order 5400.5 and EPA, 1975 (40 CFR 141)]

hypothetical (“fence post”) individual from liquid releases can be found in Chapter 6.

The highest potential EDE to the maximally exposed individual from liquid releases in 1991 was 0.34 mrem (0.0034 mSv). This dose is 0.34 percent of the 100 mrem DOE dose limit for annual exposure and just 0.11 percent of the annual dose received by persons living in the Central Savannah River Area (CSRA) from natural sources of radioactivity.

Chart 8-3 shows the calculated maximum committed EDE to individuals from releases to surface waters, with a comparison to applicable standards.

The 1991 maximum EDE of 0.34 mrem was 100 percent higher than the 1990 maximum EDE of 0.17 mrem. This relatively large increase is primarily due to a 130 percent increase in the radiation dose from consumption of Cs-137 in fish. In addition, the K-Area tritium release in December 1991 (Chapter 10) and increased tritium releases from seepage basin migration contributed to a 70 percent increase in total tritium releases from SRS in 1991.

As can be seen in Table 8-4, the EDE to the maximally exposed individual at the site perimeter results primarily from Cs-137. The major dose pathway for the maximally exposed individual at the site perimeter is from the consumption of fish, which readily bioaccumulate Cs-137. Refer to Chapter 9, “Wildlife Monitoring,” for a description of the SRS fish monitoring program results.

During 1991, measured concentrations of Cs-137 in fish were calculated to have been caused by Cs-137 releases that were over 25 times higher than the actual measured direct releases of Cs-137 from SRS. This indicates either migration of fish from SRS streams to the main channel of the river, inconsistencies in the fish sampling and monitoring program (Chapter 9), or a significant source of release to the river other than measured direct liquid effluents. As a check on this, the average measured concentration of Cs-137 at River 10 ($4.93\text{E-}11$ $\mu\text{Ci/mL}$) was compared with the calculated concentration at River 10 ($2.81\text{E-}12$ $\mu\text{Ci/mL}$), based on measured effluent releases and flow rates. The ratio of measured concentration to calculated concentration of 17.5 seems to confirm an additional unmonitored source of Cs-137, possibly from streambed and swamp desorption and/or migration. This phenomenon is seen every year, but the ratio has never been larger than in 1991. Since 1985, the largest ratio of measured/calculated concentrations was 8.4 in 1986.

Maximum and Average EDE from Public Drinking Water Supplies

Table 8-5 and Table 8-6 show calculated committed EDEs to individuals whose entire daily intake of water is supplied by the Beaufort-Jasper and Port Wentworth water treatment plants, downriver of SRS.

The committed EDE for average water consumption (1 L/day for a year) was 0.041 mrem (0.00041 mSv)

Figure 8-5 SRS monitors site streams and the Savannah River for radioactivity at selected locations.

from Beaufort-Jasper and 0.050 mrem (0.00050 mSv) from Port Wentworth water supplies.

At the Beaufort-Jasper Water Treatment Plant, the committed EDE for maximum water consumption rates (2 L/day for a year) was 0.081 mrem (0.00081 mSv). At the Port Wentworth Water Treatment Plant, the committed EDE for maximum water consumption rate (2 L/day for a year) was 0.099 mrem (0.00099 mSv). As can be seen from Chart 8-3, the maximum committed EDE of 0.099 mrem is 2.5 percent of the

DOE and EPA standard of 4 mrem/yr from public water supplies.

As shown in Figure 8-6, tritium accounts for over 89 percent of the drinking water dose at the two public water supply locations.

Collective EDE

Collective doses were also calculated using the LADTAPII computer code; the results are shown in Table 8-7. In 1991, the collective dose from SRS liquid releases was 3.23 person-rem (0.0323 person-

Figure 8-6 Tritium accounts for 89.4 percent of the liquid dose downriver at two water treatment plants.

Sv). This was 37 percent higher than the 1990 dose of 2.35 person-rem.

The collective EDE from water consumption occurs to the discrete population groups at Beaufort-Jasper and Port Wentworth. The collective EDE from other pathways occurs to a diffuse population that cannot be described as being in a specific geographical location.

Potential EDE from Irrigation

The 1990 update of the land and water use parameters [Hamby, 1991] revealed that there is no known use of river water withdrawn downstream from SRS for irrigation purposes. However, the potential maximum offsite dose from this source is 0.17 mrem (0.0017 mSv) as shown in Table 8-8.

Surface Water Monitoring

Description of Monitoring Program

Savannah River

Paddlewheel samplers at locations upriver from, adjacent to, and downriver from SRS continuously sample the Savannah River. A monitoring location upriver from SRS provides background analytical data (i.e., data from comparable waterways unlikely to have been directly influenced by SRS operations). In 1991, the river was sampled at the six locations shown in Figure 8-5.

Sampling locations on the river provide measurements to determine the amount of radioactivity released to the Savannah River from SRS operations.

River flow is measured using USGS flow recorders at two sampling stations: River 2 upriver from SRS and River 10 downriver from SRS.

In most cases, river water samples are collected weekly for analyses of gross alpha, nonvolatile beta, tritium, and a variety of specific radionuclides. The frequency and type of analyses, which vary from location to location, are based upon the potential quantity and specific radionuclides likely to be present at a sampling location. Changes in SRS operations and variations in radiological conditions may create sampling changes as well. There were no changes in the river sampling program during 1991.

SRL monitors the Savannah River for Cs-137 with ultra-low-level analysis techniques (Chapter 4). SRL samples are collected every two weeks from upriver at the River 2 station and downriver at the River 10 station.

Site Streams

Five SRS streams—Upper Three Runs Creek, Four Mile Creek, Pen Branch, Steel Creek, and Lower Three Runs Creek—feed into the Savannah River. A sixth stream, Beaver Dam Creek, receives effluents from D Area. These six streams are sampled continuously at 34 locations to monitor radioactivity released from SRS facilities. The 34 sampling locations include effluent monitoring points and points downstream of effluents. Samples are also collected on all major streams near Road A (Highway 125), which is near the SRS boundary. Figure 8-5 shows all stream sampling locations. Stream flows are determined by USGS flow recorders at most of the sampling locations.

One change to the site stream program was the monitoring at sample point PP-2, which was discontinued during 1991 because the Par Pond drawdown eliminated flow at this point (Chapter 10).

Continuous water samples from streams are generally collected weekly and analyzed for gross alpha, nonvolatile beta, tritium, and other specific types of radionuclides. The frequency and types of analyses performed on each sample are based on the potential quantity and type of radionuclides likely to be present at the sampling location (Chapter 4).

Offsite Surface Water

Offsite surface water also is sampled to provide background data. The Edisto River, a small river in

South Carolina, is the selected offsite control location because it is a surface water system similar to SRS streams and, except for atmospheric tritium releases, is not directly affected by SRS operations.

Seepage Basins

Seepage basins are shallow, earthen excavations that receive wastewater containing chemicals and radionuclides. Some of the wastewater (approximately 30 percent of the discharged volume) evaporates to the atmosphere. The remaining wastewater seeps downward through the sides and floor of a basin to the groundwater. After mixing with the groundwater, the contaminants generally flow slowly in a horizontal direction, eventually outcropping into a surface stream (Figure 8-4). During its slow travel through the soil, the wastewater loses some of its contamination by precipitation, filtration, adsorption, ion exchange, and radioactive decay [Stone, 1983].

EMS collects water samples quarterly at three seepage basin locations (C, L, and P areas) and monthly at two locations (SWDF and TNX Area) to determine radionuclide concentrations and inventory in the basin water. Use of seepage basins in F and H areas was discontinued in 1989 and sampling was also discontinued in 1989 after the basins were dry and capped.

As discussed previously, streams also are sampled downgradient of the basins to calculate the amount of radioactivity migrating from the seepage basins. These results are important in calculating the total levels of radioactivity released to the Savannah River as a result of SRS operations.

Applicable Standards

DOE Order 5400.1, "General Environmental Protection Program," requires that environmental surveillances be conducted at all DOE sites in order to monitor the effects, if any, of DOE activities on the surrounding environment. [DOE, 1988a].

Monitoring Results

Savannah River

In 1991, EMS measured no statistically significant differences between upriver and downriver gross alpha, nonvolatile beta, Sr-90, Cs-137, Pu-238, and Pu-239 activities. The river monitoring data are presented in Table 8-9.

Table 8-9 includes Cs-137 concentrations measured by the ultra-low-level SRL analytical procedure for river samples from River 2 and River 10. The average

concentration of Cs-137 at River 10 was $(4.93 \pm 2.20)E-11$ $\mu\text{Ci/mL}$, which is over four times greater than the River 2 average concentration of $(1.12 \pm 0.65)E-11$ $\mu\text{Ci/mL}$.

As shown in Table 8-9, the average tritium concentrations measured at River 2 were $(4.1 \pm 3.1)E-07$ $\mu\text{Ci/mL}$, and the average concentration at River 10 was $(3.2 \pm 4.6)E-06$ $\mu\text{Ci/mL}$. This equated to a total of 26,300 Ci of tritium added to the Savannah River by SRS operations during 1991 (refer to the continuation page of Table 8-1).

Site Streams

Detailed site stream monitoring data are presented in Table 8-10. The average concentration of gross alpha, nonvolatile beta, and tritium at locations near the mouths of the streams are listed in Chart 8-4 and compared to the Edisto River control results. The stream locations compared to the Edisto River in this table are downstream of all liquid effluent discharge points, where adequate mixing has taken place.

Tims Branch, a tributary of Upper Three Runs Creek, receives effluents from M Area and SRL. In 1991, M-Area effluents contained small quantities of uranium, and SRL releases contained tritium and small quantities of strontium and plutonium (Chart 8-1). Releases to Tims Branch eventually flow downstream and enter Upper Three Runs Creek. Samples are analyzed for gross alpha, nonvolatile beta, and tritium. Samples monitoring the M-Area effluent also are analyzed for non-specific uranium and plutonium.

As can be seen in Chart 8-4, gross alpha and nonvolatile beta activities entering Upper Three Runs Creek from Tims Branch (TB-5) are comparable to the Edisto River control samples.

Upper Three Runs Creek receives liquid discharges from the Effluent Treatment Facility (ETF), flow from Tims Branch, and storm-water runoff from parts of F and H areas. The ETF, located in H Area, is the largest contributor of radioactivity to Upper Three Runs Creek (U3R-2A).

The maximum gross alpha activity and nonvolatile beta activity ($(8.34 \pm 0.90)E-09$ $\mu\text{Ci/mL}$ and $(5.26 \pm 0.14)E-07$ $\mu\text{Ci/mL}$, respectively) found in Upper Three Runs Creek were measured at U3R-2, the effluent monitoring point for the F-Area storm sewer. (This monitoring point was incorrectly called U3R-2F in the 1990 report.) This sampling location receives storm water from various locations in F Area. Maximum and average values were both higher at this location during 1991 than they were during 1990. A

Chart 8-4
Average Concentration of Radioactivity in Offsite and SRS Stream Water

Location ^a	Alpha ($\mu\text{Ci/mL}$)	Beta ($\mu\text{Ci/mL}$)	Tritium ($\mu\text{Ci/mL}$)
Tims Branch-5	$(1.29 \pm 0.56)\text{E-09}$	$(3.03 \pm 0.87)\text{E-09}$	$(1.32 \pm 0.59)\text{E-06}$
Upper Three Runs-4	$(1.54 \pm 0.88)\text{E-09}$	$(1.73 \pm 0.57)\text{E-09}$	$(1.74 \pm 2.36)\text{E-05}$
Beaver Dam Creek	$(0.46 \pm 3.23)\text{E-10}$	$(2.31 \pm 0.94)\text{E-09}$	$(1.75 \pm 3.90)\text{E-05}$
Four Mile Creek-6	$(3.17 \pm 3.11)\text{E-10}$	$(2.15 \pm 0.43)\text{E-08}$	$(2.86 \pm 0.63)\text{E-04}$
Indian Grave Branch-21	$(1.71 \pm 2.12)\text{E-10}$	$(1.30 \pm 0.53)\text{E-09}$	$(2.58 \pm 0.80)\text{E-03}$
Pen Branch-3	$(1.43 \pm 2.36)\text{E-10}$	$(2.25 \pm 0.55)\text{E-09}$	$(5.07 \pm 7.30)\text{E-05}$
Steel Creek-4	$(-0.33 \pm 1.25)\text{E-10}$	$(2.03 \pm 0.49)\text{E-09}$	$(5.37 \pm 0.97)\text{E-06}$
Lower Three Runs-3	$(1.91 \pm 1.55)\text{E-10}$	$(3.77 \pm 0.53)\text{E-09}$	$(1.20 \pm 0.58)\text{E-06}$
Control			
Edisto River	$(1.31 \pm 0.58)\text{E-09}$	$(2.19 \pm 0.77)\text{E-09}$	$(5.53 \pm 4.46)\text{E-07}$

^a Locations are near mouth of streams.

major reason for the increase was the strontium release from the F-Area lab facility in September (Chapter 11, "Special Surveys").

Due to increased operations at the ETF, the average and maximum concentrations of tritium ($(5.04 \pm 8.08)\text{E-02 } \mu\text{Ci/mL}$ and $(3.68 \pm 0.06)\text{E-01 } \mu\text{Ci/mL}$, respectively) measured at the U3R-2A discharge point were higher in 1991 than in 1990. These concentrations also are greater than the DOE-DCG standard of $2.0\text{E-03 } \mu\text{Ci/mL}$ (Chart 8-2). DOE, however, exempts tritium from BAT requirements. The ETF process cannot and, therefore, does not remove tritium from the effluents released to the stream. The average concentration of tritium at U3R-4, near the mouth of the creek, was $(1.74 \pm 2.36)\text{E-05 } \mu\text{Ci/mL}$, which is well below the DOE-DCG standard.

Beaver Dam Creek receives effluents from the heavy water rework, powerhouse, and laboratory facilities located in D Area. During 1991, tritium was the principal radionuclide released in the D-Area effluents.

Average gross alpha and nonvolatile beta activities in Beaver Dam Creek for 1991 were within the ranges observed in the Edisto River control samples.

During 1991, the average concentration of tritium in Beaver Dam Creek was $(1.75 \pm 3.90)\text{E-05 } \mu\text{Ci/mL}$, which was slightly greater than the 1990 concentrations. However, this concentration is much lower than the DOE-DCG standard.

Four Mile Creek receives effluents from F, H, and C areas. Four Mile Creek also receives tritium and Sr-90 migration from the F- and H-area seepage basins and the SWDF.

Nonvolatile beta activities in Four Mile Creek were above those at the control location mainly due to the migration from the F- and H-Area seepage basins. Table 8-2 shows that the calculated migration of strontium to Four Mile Creek during 1991 was 0.51 Ci, an increase of 138 percent over the 1990 level. The reason for this increase is being investigated, but is not known at this time.

During 1991, Cs-137 was detected in only one of the 26 samples taken at FMC-6. Gross alpha and U/Pu concentrations levels were not significantly different than control samples.

The majority of the tritium found in Four Mile Creek comes from seepage basin migration. During 1991, 13,980 Ci of tritium were calculated to have migrated into Four Mile Creek (Table 8-2). This was 43 percent greater than the 1990 total of 9,757 Ci. The reason for

this increase is being investigated, but is not known at this time.

C Reactor, which has not operated since 1985, released 13 Ci of tritium to Four Mile Creek through the C-Area process sewer in 1991. F and H areas released a total of 20 Ci of tritium to Four Mile Creek in 1991. The highest average concentration of tritium measured in Four Mile Creek during 1991 was $(2.57 \pm 0.77)\text{E-03 } \mu\text{Ci/mL}$ at location FMC-3A, which monitors releases from F Area and migration from F-Area seepage basins. This was the only location on Four Mile Creek that exceeded the DOE-DCG standard of $2.0\text{E-03 } \mu\text{Ci/mL}$. The average concentration of tritium at FMC-6 (downstream from effluents to Four Mile Creek) during 1991 was $(2.86 \pm 0.63)\text{E-04 } \mu\text{Ci/mL}$, which is 14 percent of the DOE-DCG for tritium.

Pen Branch receives heat exchanger cooling water from K Area and flow from Indian Grave Branch (IGB). Tritium migration from the K-Area drain field and seepage basin outcrops into IGB.

During 1991, the average concentration of tritium in IGB was $(2.58 \pm 0.80)\text{E-03 } \mu\text{Ci/mL}$ at sampling location IGB-21, which is downgradient from the K-Area drain field and seepage basin. This was 57 percent lower than the 1990 level but was still greater than the 2.0E-03 DOE-DCG standard. After dilution, the average tritium concentration measured in Pen Branch at Road A (PB-3) was $(5.07 \pm 7.30)\text{E-05 } \mu\text{Ci/mL}$.

As shown in Chart 8-4, gross alpha and nonvolatile beta activities at PB-3 measured at or near background levels. No gamma-emitting radionuclides were detected in samples analyzed from Pen Branch.

Steel Creek receives releases from L-Area effluents and tritium migration from the P-Area seepage basins. These releases enter L Lake, which overflows into Steel Creek near Road A. Most concentrations of radionuclides in Steel Creek below L Lake represent notable decreases from their 1985 levels when construction of L Lake was completed. The decreases likely resulted from the increased flow of river water used in L Reactor and from dilution by L Lake.

In 1991, tritium migration from the P-Area seepage basin increased 63 percent over the 1990 level (see Table 8-2). The average level measured at SC-2A was $(7.52 \pm 5.64)\text{E-05 } \mu\text{Ci/mL}$, which is well below the DOE-DCG standard. All other radionuclide con-

centrations were comparable to control location concentrations.

Lower Three Runs Creek receives overflow from Par Pond, which receives P-Reactor heat exchanger cooling water and other effluents from P Area. Par Pond also receives discharges from all storm sewer outfalls from the deactivated R Area and from a few storm sewers in P Area.

As shown in Chart 8-4, gross alpha and nonvolatile beta activities in Lower Three Runs Creek measured at or near background levels. No gamma-emitting radionuclides were detected in samples analyzed from Lower Three Runs Creek.

The average tritium concentration detected in P-Area effluent during 1991 was $(2.56 \pm 1.89)\text{E-06 } \mu\text{Ci/mL}$, and the average at L3R-1A was $(2.92 \pm 0.75)\text{E-06 } \mu\text{Ci/mL}$ which are both well below the DOE-DCG standard.

Refer to Chapter 11 for a description of the effects the 1991 Par Pond drawdown had on radionuclide activity levels.

TNX Area average radionuclide concentrations, as measured in the TNX effluent samples, were at or below control point concentration levels during 1991.

Offsite Surface Water

Table 8-10 includes the radionuclide concentrations measured in the Edisto River, which does not receive water from any stream on SRS. Chart 8-4 also compares the average concentrations of radioactivity for site streams and the Edisto River.

Seepage Basins

Water samples collected from seepage basins located in C, L, P, and TNX areas and near the SWDF generally reflect concentrations observed in the wastewater released to the basins. Monitoring results of seepage basin water are presented in Table 8-11.

Tritium Release Transport in Streams and River

Releases of tritium from SRS to the Savannah River are estimated by using stream and river flow rates and the three different sets of measurements listed here:

- concentrations at effluent release points and just upstream and downstream from migration release points
- concentrations in SRS streams at the last sampling point before entry into the river (stream transport)

- concentrations in the Savannah River downriver from SRS (river transport) minus the concentrations measured upriver of SRS

A release summary showing the stream and river transport of tritium for the years 1987 through 1991 is presented in Table 8-1.

Results showed that 1991 point-of-release and stream transport estimates agreed within 3 percent and that the point-of-release estimates were within 5 percent of the river transport estimates. The differences between the release estimates can be attributed to a number of factors, including random and systematic uncertainties associated with the measurements. Point-of-release values, considered the best and most conservative release estimates, are used for annual dose calculations.

The tritium release summary for the years 1960 to 1991 is presented in Table 8-12. Figure 8-7 compares the calculated releases of tritium based on the three alternative methods for each year since 1960.

As described in the 1991 Releases of Radioactivity to Surface Water section of this chapter, the 1991 releases of tritium were at their highest level since

1986. Total tritium releases in 1991 (27,400 Ci) were over 70 percent higher than they were in 1990 (16,100 Ci).

NONRADIOLOGICAL WATER MONITORING

Surface water was monitored for nonradioactive contaminants at 78 effluent outfalls from site facilities, at locations along six site streams, and at three locations on the Savannah River.

Monitoring the streams and river serves as a backup to outfall monitoring to ensure that materials that could adversely affect the environment are characterized if released.

Liquid Effluent Monitoring (NPDES)

Description of Monitoring Program

The physical properties and concentrations of chemicals and metals in SRS effluents are regulated by SCDHEC under the National Pollutant Discharge Elimination System (NPDES) program.

Tables 8-13 and 8-14 list the NPDES outfall locations and the sources of the wastewater contained in each effluent.

Figure 8-7 Tritium Release Summary by Calculation Method, 1960-1991.

Applicable Standards

Standards applicable to nonradioactive constituents and physical properties in SRS wastewater discharges from all outfalls are contained in the site's two NPDES permits. These permits, SC 0000175 and SC 0044903, are administered by SCDHEC. Monitoring requirements and standards, as listed in the permit, vary from one outfall to another based upon the materials released from the facility (Chapter 2).

Monitoring Results

A summary of monitoring results is presented in Table 8-15. SRS had a 99.92 percent NPDES compliance rate in 1991. Of the 8,329 analyses performed, seven exceeded permit limits. These seven exceedances occurred at six different outfalls during the year. Table 8-16 summarizes the limits exceeded, the outfall locations, the possible cause of noncompliance, and the corrective action taken.

Savannah River

Description of Monitoring Program

The Savannah River is monitored at four locations for organic and inorganic contaminants. These sampling sites are located upriver and downriver from the site to provide a means of comparing SRS contribution of pollutants with "background" levels of chemicals from natural sources and from contaminants produced by industrial sewage plants, medical facilities, or other industrial facilities upriver from the site. Sampling locations on the Savannah River are shown in Figure 8-8.

Included in these background levels, in addition to natural sources, are contaminants produced by industrial sewage plants, medical facilities, or other industrial facilities upriver from SRS.

Field measurements for conductivity, dissolved oxygen, pH, and temperature are also taken in the Savannah River monthly to monitor the river water quality. Laboratory analyses are conducted for other

Figure 8-8 SRS streams and the Savannah River are monitored for water quality in a process that includes laboratory analyses for organic and inorganic contaminants and metals.

Chart 8-5 South Carolina Water Quality Standards (Class B Waters)

Fecal coliform. The count is not to exceed a geometric mean of 1,000 colonies/100 mL, based on five consecutive samples during any 30-day period; not to exceed 2,000 colonies/100 mL in more than 20 percent of the samples examined during such period.

pH. Range between 6.0 and 8.5, except that specified waters may range from a pH of 5.0 to 8.5, due to natural conditions.

Temperature. The water temperature for all Class B free-flowing waters shall not exceed a maximum temperature of 90°F (32.2 °C) after adequate mixing as a result of heated liquid, nor shall a temperature climb of more than 5 °F (2.8 °C) above temperatures existing under natural conditions be allowed as a result of the discharge of heated liquids unless an appropriate temperature criterion or mixing zone has been established.

Dissolved oxygen. Daily average not less than 5.0 mg/L with a low of 4.0 mg/L, except that specified waters may have an average of 4 mg/L due to natural conditions.

water quality parameters such as metals, chemicals, and physical and biological properties.

In addition, the Academy of Natural Sciences of Philadelphia (ANSP) conducts special environmental surveys on the Savannah River through a program that began in 1951. Savannah River water quality surveys by ANSP consisted of diatom monitoring and biological cursory surveys during 1991. Preliminary results of these surveys are discussed in Chapter 11.

Applicable Standards

The South Carolina Water Quality Standards for Class B waters define the chemical and biological standards for the Savannah River. The standards define Class B waters as: "Freshwaters suitable for secondary contact recreation, and as a source for drinking water supply after conventional treatment in accordance with requirements of the department (SCDHEC); suitable for fishing and the survival and propagation of a balanced indigenous aquatic community of fauna and flora; suitable also for industrial and agricultural uses." [SCDHEC, 1981] Standards for Class B waters are summarized in Chart 8-5.

Monitoring Results

A comparison of Savannah River water quality analyses upriver and downriver of SRS showed no significant differences. Measurements for fecal coliform were within Class B standards in 1991. This may be attributed to the fact that much of the water discharged to the river from SRS has undergone

treatment processes so that the water can be used for various purposes (e.g., drinking water).

These treatment processes remove coliform from the water before it is released to the river. In 1991, the maximum measurements were 1,300 colonies/100mL upriver from SRS and 1,600 colonies/mL downriver from SRS. The averages of the monthly geometric mean of measurements for fecal coliform were 84 colonies/100 mL upriver and 53 colonies/100 mL downriver from SRS.

Temperature, dissolved oxygen, and pH field measurements were within the standards required for Class B waters. Analytical results for chemicals and metals were within the ranges observed in previous years. Savannah River water quality data are presented in Tables 8-17 and 8-18.

SRS Streams

Description of Monitoring Program

EMS monitors site streams monthly for chemicals, metals, and physical and biological properties. The stream nonradiological monitoring program helps detect materials that may be inadvertently released from sources other than routine release points.

The six principal streams on SRS receive water primarily from the D-Area powerhouse. D Area also contains heavy-water rework facilities and a process control laboratory. Each stream on SRS receives varying amounts of wastewater and rainwater runoff

from SRS facilities. Sampling locations are shown in Figure 8-8.

In addition to SRS monitoring, SCDHEC collects duplicate monthly samples from Tims Branch near Road C, Upper Three Runs Creek at Road A, Four Mile Creek at Road A-7, and Steel Creek at Road A. SCDHEC performs this monitoring to ensure that materials released from SRS are not contaminating the Savannah River.

Applicable Standards

South Carolina water quality standards for Class B waters, shown in Chart 8-5, also apply to SRS streams.

Monitoring Results

All analyses of SRS stream samples and measurements in SRS streams met the South Carolina standards for Class B waters.

In previous years, temperatures in Pen Branch exceeded the Class B water standard due to thermal discharges from K Reactor. However, due to the shutdown of K Reactor in 1988, the maximum temperature in Pen Branch was 29.4 °C (84.9 °F) in 1991, which was within the Class B water quality standards.

Analytical results for chemicals and metals were within the ranges observed in previous years. Tables 8-18, 8-19, and 8-20 summarize stream water quality data.

Monitoring for Herbicides

Description of Monitoring Program

Herbicides have been monitored since 1976 to assess their concentrations in surface water from SRS streams and the Savannah River. Water samples from seven stream locations and two river locations were analyzed for 23 herbicides during 1991.

Monitoring Results

Concentrations of all herbicides analyzed in river and stream water were less than minimum detectable concentrations during 1991. Herbicide data for stream and river water are presented in Table 8-21.

River and Stream Temperature Surveys

Description of Monitoring Program

Temperature profile surveys are conducted on the Savannah River and several SRS streams as required

by Consent Order 84-4-W to determine the thermal effects of SRS operations upon the waters of South Carolina. These studies also provide baseline seasonal temperatures of the creek mouths before a reactor startup. These surveys are conducted quarterly when the reactors are operating and at least annually if the reactors are shutdown. In 1991, none of the reactors were operating.

Consent Order 84-4-W between SCDHEC and DOE sets temperature limits for Steel Creek and Beaver Dam Creek. This Order states that the downstream river temperatures outside the mixing zone should not be in excess of 2.8°C above the ambient temperature. The mixing zone shall not exceed 25% of the cross sectional area and over 33% of the surface area of the river.

Measurements in the creek mouths are taken at 2-ft. intervals across the creeks. At each interval, stream temperatures are measured at 1-ft. depths from the surface of the creek to the bottom. River measurements are taken at 10 intervals from the South Carolina bank to the Georgia bank. At each of these intervals, temperature measurements are taken at 1-ft. depths from the river surface to the bottom.

The reference ambient temperature, which is used as a control temperature, for the river and SRS streams is determined from a temperature profile 100 yards upriver from Beaver Dam Creek. In addition to temperature profile surveys conducted by SRS, stations established by USGS continuously collect temperature measurements at the mouth of each SRS stream.

Monitoring Results

Two temperature profile surveys were performed in the mouths and upriver from Beaver Dam Creek and Steel Creek during 1991. Temperature measurements in both Beaver Dam Creek and Steel Creek exceeded the ambient temperatures but were within the limits set by Consent Order 84-4-W. Table 8-22 summarizes the 1991 temperature profile results.

SEDIMENT

Radiological Monitoring Program

Description of Monitoring Program

Radiological analysis of sediment samples serves to determine the deposition and accumulation of long-lived radionuclides in the SRS streambeds and in the Savannah River riverbed.

Sediment samples are collected annually at six locations on the Savannah River upriver from,

Figure 8-9 Sediment sampling locations.

adjacent to, and downriver from SRS, and at nine site stream locations. The samples are collected at locations where maximum accumulation of radioactivity in the river and stream beds is expected. These locations are shown in Figure 8-9.

Sediment is analyzed for gamma-emitting radionuclides, Sr-90, Pu-238, and Pu-239. Refer to Chapter 4 for a description of the sediment sampling and analysis procedures.

During 1991, sediment samples were also analyzed from Par Pond, Savannah River Swamp, and Four

Mile Creek as part of special surveys. The results of these surveys are discussed in Chapter 11.

Monitoring Results

Concentrations of radionuclides in sediment may vary from year to year because the exact collection point in the streambeds may vary. The shifting and resuspension of sediment also may cause variations in radionuclide concentrations. Therefore, the sediment analytical results are more appropriately used as long-term trending indicators, as opposed to year-to-year effluent release indicators.

The 1991 river and onsite stream sediment results reflect current and previous contributions of radioactivity from SRS liquid releases. A tabulation of results from 1989 to 1991 for both river and stream sediment samples is presented in Table 8-23.

During 1991, as in past years, maximum radionuclide concentrations were measured in samples collected from Four Mile Creek. This stream receives effluents from F, H, and C areas as well as radionuclide migration from the F- and H-area seepage basins and the SWDF.

Gamma-Emitting Radionuclides

Cs-137 was the only man-made gamma-emitting radionuclide routinely detected in river sediment. The maximum 1991 Cs-137 concentration detected in river sediment was $(7.21 \pm 0.56)\text{E-01 pCi/g}$, which occurred at River Mile 129.5 (above Lower Three Runs). This location has had the highest Cs-137 concentration during each of the past four years.

As to be expected, higher concentrations of Cs-137 were measured in stream sediments than in the river sediments. A maximum Cs-137 concentration of $(5.14 \pm 0.15)\text{E+01 pCi/g}$ was measured in Four Mile Creek at Road A-7A (in a beaver pond).

During 1991, Co-60 also was detected in stream sediment from Four Mile Creek, Pen Branch, and Steel Creek. The maximum, $(1.15 \pm 0.05)\text{E+00 pCi/g}$, was detected in sediment from the Steel Creek/Pen Branch mouth.

Strontium

The maximum river sediment Sr-90 concentration was $(3.85 \pm 2.06)\text{E-02 pCi/g}$, which occurred at River Mile 129.5 (above Lower Three Runs Creek).

The maximum stream sediment Sr-90 concentration was $(9.11 \pm 0.53)\text{E-01 pCi/g}$, which occurred at Four Mile Creek at Road A-7A (in a beaver pond).

Plutonium

During 1991, the maximum concentration of Pu-238 detected in river sediment was $(2.89 \pm 4.20)\text{E-03 pCi/g}$, which occurred at River Mile 150.2 (below Four Mile Creek). The maximum concentration of Pu-239 detected in river sediment was $(2.32 \pm 0.23)\text{E-03 pCi/g}$, which occurred at River Mile 129.5 (above Lower Three Runs Creek).

The maximum concentrations of Pu-238 and Pu-239 $(1.18 \pm 0.01)\text{E+00 pCi/g}$, and $(3.73 \pm 0.06)\text{E-01}$

pCi/g, respectively) in onsite stream sediment were measured at FMC A-7A (in a beaver pond).

Nonradiological Monitoring Program

Description of Monitoring Program

The nonradiological monitoring program focuses on monitoring herbicides to assess their concentrations in sediment from SRS streams and the Savannah River. Sediment samples from two Savannah River and seven stream locations were analyzed for 23 herbicides during 1991.

Monitoring Results

No herbicides were detected in either the Savannah River or stream sediment samples in 1991. All sample results were below the detection limits of the EPA analytical procedures used. The herbicide analytical results for stream and river sediment samples are presented in Table 8-24.

DRINKING WATER

A major pathway for radiation dose to man is through drinking water consumption. Drinking water systems onsite, in surrounding communities, and downriver of SRS have to be routinely monitored to quantify levels of contaminants consumed by individuals either residing or working in these areas. SRS processes have the potential to adversely affect the site's potable water supply, in addition to the potable water supplies of individuals and communities located downstream of SRS.

EMS conducts routine monitoring to quantify levels of radionuclide contaminants in the 28 drinking water systems onsite and at drinking water systems in surrounding communities.

A discussion of sample collection and analytical procedures for drinking water appears in Chapter 4.

Radiological Monitoring Program

Description of Monitoring Program

EMS collects drinking water samples from 35 onsite facilities and 16 surrounding towns and cities. The frequency of sample collection varies depending on the use of the drinking water system. Most onsite systems are sampled either monthly or quarterly. Samples from surrounding towns are collected semi-annually. The offsite public drinking water locations are shown in Figure 8-10.

Samples are also collected and analyzed at two water treatment plants downriver from SRS that supply

treated Savannah River water to Beaufort-Jasper and Port Wentworth consumers.

The Port Wentworth Water Treatment Plant has been treating Savannah River water during the entire period of SRS operation. Treated water from this plant is used primarily for industrial and manufacturing purposes in an industrial complex near Savannah, Ga. This treatment plant serves about 15,000 people—primarily adults working in industrial facilities.

The Beaufort-Jasper Water Treatment Plant near Hardeeville, S.C., has been in operation since 1965. It serves approximately 50,000 people living in Beaufort and Jasper counties.

Samples from a water treatment plant in North Augusta, S.C., also are collected for analysis. The North Augusta Water Treatment Plant is upriver from SRS and not directly affected by liquid releases from SRS operations. This location provides a control for comparison of results from the other treatment plants.

Raw and finished water samples from the three offsite water treatment plants are collected daily by treatment plant personnel and composited for monthly analysis by SRS.

All drinking water samples are analyzed for concentrations of gross alpha, nonvolatile beta, and tritium. A total strontium (Sr-89, 90) analysis is performed annually for samples collected onsite and in surrounding communities.

Applicable Standards

SRS drinking water systems must meet the water quality criteria mandated by the South Carolina Primary Drinking Water Regulations (R61-58). Included in these regulations are compliance requirements for radionuclides based on EPA drinking water standards. The drinking water standards, given as maximum contaminant levels (MCL), are based on an annual whole body dose of 4 mrem for the consumption of 2 L of water per day (40 CFR 141). Chart 8-6 lists the EPA drinking water standards for radionuclides analyzed in the monitoring program.

G92G009.01L

Figure 8-10 SRS collects drinking water samples from 35 onsite facilities and 16 surrounding towns and cities. Offsite samples are collected semiannually.

Chart 8-6
EPA Drinking Water Standards
for Radionuclides

Gross alpha	1.5E-08 $\mu\text{Ci}/\text{mL}$
Nonvolatile beta	5.0E-08 $\mu\text{Ci}/\text{mL}$
Tritium	2.0E-05 $\mu\text{Ci}/\text{mL}$
Strontium-89	2.0E-08 $\mu\text{Ci}/\text{mL}$
Strontium-90	8.0E-09 $\mu\text{Ci}/\text{mL}$

These EPA drinking water standards also apply to offsite public drinking water systems.

Monitoring Results

Radioactivity monitoring data for drinking water, presented in Table 8-25, are discussed in the following sections.

Gross Alpha and Nonvolatile Beta

Gross alpha and nonvolatile beta activities in drinking water collected onsite and from surrounding towns measured within ranges attributed to naturally occurring radium and thorium [Mikol, 1980]. Measurements from all locations were below the EPA drinking water standards for gross alpha and nonvolatile beta.

Gross alpha and nonvolatile beta results for finished water samples collected from both the Beaufort-Jasper and Port Wentworth water treatment plants were comparable to concentrations observed at the water treatment plant in North Augusta. These results are summarized in Chart 8-7.

Tritium

Small but measurable concentrations of tritium were occasionally detected in onsite drinking water samples collected in operating areas. The maximum onsite tritium concentration was $(4.0 \pm 0.1)\text{E-}06$ $\mu\text{Ci}/\text{mL}$ (400D, raw), or 20 percent of the EPA-derived MCL of $2.0\text{E-}05$ $\mu\text{Ci}/\text{mL}$.

In 1987, SRL conducted a special study to determine whether tritium was present in the Black Creek-Middendorf formations. The study indicated that trace levels of tritium detected in onsite drinking water samples are introduced after sample collection (during chemical treatment or through exposure to atmospheric tritium) and do not reflect contamination in the aquifer [Mikol, 1988].

The maximum tritium concentration in drinking water supplies from surrounding towns was $(9.9 \pm 1.5)\text{E-}07$ $\mu\text{Ci}/\text{mL}$ (Jackson, S.C.), or 5 percent of the EPA-derived MCL of $2.0\text{E-}05$ $\mu\text{Ci}/\text{mL}$.

Increased concentrations of tritium are the only measurable SRS impact on drinking water at downriver water treatment plants. Tritium is attributed to SRS releases when present in water supplies using Savannah River water. Measurable tritium concentrations in surface water result from direct liquid releases and seepage basin migration releases to SRS streams and from the exchange of tritium from SRS atmospheric releases with hydrogen in rainwater and surface water. Figure 8-11 summarizes and compares the maximum and average tritium concentrations in samples collected from the water treatment plants.

Strontium

Onsite and offsite (surrounding towns) drinking water samples are also analyzed for Sr-90. The maximum onsite strontium concentration, $(2.3 \pm 1.4)\text{E-}09$ $\mu\text{Ci}/\text{mL}$, was measured at Par Pond Laboratory. This result is 29 percent of the EPA-derived maximum contaminant level of $8.0\text{E-}09$ $\mu\text{Ci}/\text{mL}$. For offsite locations, maximum Sr-90 concentration was $(1.7 \pm 1.1)\text{E-}09$ $\mu\text{Ci}/\text{mL}$ (Barnwell, S.C.), or 21 percent of the EPA standard.

Doses from Drinking Water Consumption

Persons downriver from SRS may receive a radiation dose by consuming drinking water which contains radioactivity as a result of liquid releases from SRS. EPA has established a 4 mrem dose limit for the consumption of 2 L of water per day (40 CFR 141).

Tritium present in drinking water downriver is attributed to SRS operations and represents the majority of dose (89.5 percent) received by persons at

Chart 8-7
Average Gross Alpha and Nonvolatile Beta
Activities in Drinking Water^a

Location	$(\mu\text{Ci}/\text{mL})$	
	Alpha	Beta
Beaufort-Jasper	9.2E-11	1.9E-09
Port Wentworth	-8.6E-11	2.3E-09
North Augusta	2.7E-11	2.0E-09

^a Finished water samples

Figure 8-11 Graph shows comparison of 1990 and 1991 tritium concentrations measured at downriver water treatment facilities (Beaufort-Jasper and Port Wentworth) versus those measured at North Augusta.

downriver water treatment plants (Table 8-5). In 1991, the maximum dose from tritium to persons receiving water from either Beaufort-Jasper or Port Wentworth was 0.073 mrem, based on consumption of 2 L of water per day. The maximum committed dose for all radionuclides in drinking water at the water treatment plants was 0.099 mrem (0.00099 mSv). This dose is equivalent to 2.5 percent of the EPA drinking water standard of 4 mrem/yr. A detailed discussion of doses from drinking water consumption downriver from SRS is found in Chapter 6.

Nonradiological Monitoring Program

Description of Monitoring Program

The 28 separate onsite drinking water systems are monitored by the SRS Power Operations Department. Most of the larger systems draw water from wells installed in the Black Creek-Middendorf formations. The smaller systems utilize shallow wells that draw water from the Congaree or McBean formations.

The drinking water is disinfected with chlorine to ensure that bacteriological concentrations are maintained below state and federal limits. Sodium hydroxide or soda ash is added to water in larger systems to maintain a pH within acceptable limits. Polyphosphates also are added to three onsite systems for iron and corrosion control. The concentrations of chemicals added to the water are monitored daily at all 28 systems.

Samples from all drinking water supplies are routinely analyzed for residual chlorine and total coliform bacteria. The sampling frequency depends upon the potential for contamination and the amount of use of the water supply.

In addition, all drinking water supplies are analyzed for a comprehensive list of chemicals and other water quality parameters on a 12- to 16-month basis. Samples from the 28 drinking water systems were collected in December 1991.

SCDHEC drinking water regulations require chemical samples to be collected and analyzed once every three years. This includes all SRS drinking water systems.

Chlorocarbons in drinking water are monitored at six domestic water wells and at two process water wells in the A and M areas. Monitoring frequency depends on use. Chlorocarbons are also measured at all drinking water systems on a semiannual basis.

In 1981, groundwater in the vicinity of M Area was found to be contaminated with metal degreasing solvents. Follow-up sampling indicated the presence of trichloroethylene and tetrachloroethylene (chlorocarbons) in wells 20A and 53A in A-Area wells. These wells were removed from service and well 82A replaced these two wells to supply drinking water. Water from wells 20A and 53A are now restricted to process water applications.

Applicable Standards

SRS drinking water systems must meet the water quality criteria mandated by South Carolina Primary Drinking Water Regulations (R61-58). SCDHEC implements drinking water standards for South Carolina that are at least as stringent as the federal standards. Many of these regulations apply only to community drinking water systems.

Although the site is considered a non-community drinking water system, SRS uses SCDHEC MCLs and

recommended guidelines to ensure safe drinking water at SRS. Chart 8-8 summarizes the standards used at SRS. Drinking water standards for specific contaminants also are listed in Appendix C.

Monitoring Results

Total coliform bacteria was present in four samples collected by SRS personnel from the A- and F-Area domestic water systems during the period April 4-11, 1991. These positive sample results exceeded SCDHEC bacteriological water quality limits. Twenty-two repeat samples were collected from the A- and F-Area domestic water systems by SRS and SCDHEC personnel during the period April 12-15, 1991. All of these samples tested free from total coliform bacteria.

A routine sample collected from F Area April 10, 1991, tested positive for total coliform bacteria. One of the repeat samples also tested positive, resulting in a second exceedance of the SCDHEC water quality limits. Additional repeat samples were collected on April 13, 1991; all were negative for total coliform bacteria. Analytical results are presented in Table 8-26.

SRS believes that the positive sample results were not actually caused by coliform bacteria in the drinking water. These water supplies are chlorinated for bacteriological control, and adequate free chlorine residuals were present in all samples collected. It is more likely that these positive results were caused by sampling or laboratory technique or contaminated sample bags.

Positive concentrations of trichloroethylene were detected by SRS and subcontracted laboratory personnel in domestic water samples from Wells 68A and from service water in A Area. Service water sample analyses results exceeded the EPA standard (5 µg/L); however, this water is currently being used as process (non-drinking) water.

Process water wells 20A and 53A (non-drinking water) continued to show elevated chlorocarbon concentrations as a result of the contamination identified in 1981. In 1991, the maximum concentration in these process wells was 200 µg/L trichloroethylene, measured in well 53A.

No positive chlorocarbon concentrations were detected in drinking water samples collected semi-annually from SRS drinking water systems. Monitoring results for chlorocarbons in SRS drinking water are presented in Tables 8-27 and 8-28.

Chart 8-8
EPA Drinking Water Standards for
Nonradiological Contaminants^{a,b}

Total trihalomethanes	100 µg/L
Tetrachloroethylene	5 µg/L
Trichloroethylene	5 µg/L
1,1,1-trichloroethane	200 µg/L
Total coliform bacteria	1 positive per month per drinking water system

a SCDHEC-recommended guidelines call for a minimum of 0.2 mg/L (ppm) chlorine at all parts of the water system. There are no maximum contaminant levels for chlorine.

b Drinking water standards not shown are given in Appendix C.

Table 8-29 summarizes the 1991 maximum concentrations of organics measured in SRS drinking water for samples collected and analyzed as required by the Safe Drinking Water Act. Samples collected from D Area contained positive concentrations of bromodichloromethane and chloroform. The source of these positive concentrations could not be identified.

Elevated sodium concentrations (28 mg/L) were detected in samples from A Area. Federal regulations set an optimal limit in drinking water of 20 mg/L; however, SCDHEC suggests that the public need not be notified unless sodium levels exceed 75 mg/L. The analytical results for chemicals in SRS drinking water are presented in Table 8-30.

Self-monitoring results for total coliform bacteria and turbidity at the D-Area surface water treatment plant are presented in Table 8-31. Because of operating problems, water in D-Area is no longer used for drinking.

A comprehensive analysis of SRS drinking water systems appears in Table 8-32. SCDHEC secondary MCLs were exceeded at some of the systems. However, such levels are imposed on parameters that relate only to aesthetic qualities of drinking water.

GROUNDWATER

The Groundwater Monitoring Program at SRS, conducted by EPD/EMS, gathers information to determine the effect of SRS operations on groundwater quality in compliance with state and federal regulations. SRS operations use and produce radioactive and chemical constituents that could adversely affect the quality of groundwater.

SRS is located on the western Upper Coastal Plain of South Carolina. Groundwater beneath 5 to 10 percent of the area has been contaminated by either industrial solvents, tritium, metals, other radionuclides and constituents, or a combination of these materials used or generated by operations at SRS (Figure 8-12). Contaminated groundwater in areas indicated on Figure 8-12 contains one or more of these constituents at or above the levels of EPA Primary Drinking Water Standards (DWS) (Table 8-106).

Groundwater beneath the site flows slowly, at rates ranging from inches per year to several hundred feet per year, toward streams and swamps onsite, and into the Savannah River. Figures 8-13 and 8-14 illustrate the horizontal flow directions of two regional aquifers monitored beneath SRS. Horizontal flow directions of

groundwater within these aquifers are indicated by bold arrows perpendicular to potentiometric contours. In both aquifers, the direction of flow beneath monitored waste sites is generally toward the Savannah River, the Savannah River Swamp, Upper Three Runs Creek, or Lower Three Runs Creek. Surface water in the swamp and creeks eventually flows into the Savannah River.

To identify the extent of contamination in groundwater and to predict the possible fate of the contaminants, scientists must determine the location and movement of groundwater. To make this determination, an understanding of how groundwater moves, in general, and an understanding of how that movement will be influenced by the specific geologic setting at SRS, are required.

Groundwater Hydrology

When rain falls, a portion of the rainwater accumulates as groundwater by soaking into the ground, infiltrating soil and rock. The accumulation of groundwater in pore spaces of sediments creates sources of usable water. This groundwater generally continues to flow in response to external forces. Groundwater eventually reappears at the surface in springs, swamps, stream and river beds, or pumped wells. Thus, groundwater is a reservoir whose primary input is recharge from rainwater infiltrating the soil and whose output is through discharge to springs, swamps, rivers, and wells.

Water from the surface moving down into the soil makes its way by percolating downward through the pore spaces between sediment grains. The smaller the pore spaces, the slower the flow of water through the sediment. The physical property that describes the ease with which water may move through the pore spaces and cracks in a solid is called permeability, and it is largely determined by the volume and size of pore spaces in the solid.

As water infiltrates the earth, it travels down through the vadose or unsaturated zone; here the pore spaces are partly filled with water and partly filled with air. Water moving down through the unsaturated zone will eventually reach the saturated zone; here the pore spaces are completely filled with water. The boundary between the unsaturated and the saturated zones is known as the water table. The water table generally follows, in subtle form, the contour of the surface topography. Springs, swamps, and beds of streams and rivers are the outcrops of the water table, where groundwater is discharged to the surface.

The flow of groundwater and the position of the water table may be complicated by variations in the permeability of the subsurface. Because the permeability of the earth varies greatly, groundwater flowing through subsurface strata does not travel at a constant rate or without impediment. Strata that transmit water easily (such as those composed primarily of sand) are called aquifers, and strata that restrict water movement (such as clay layers) are called aquitards. An aquifer with an aquitard lying above and beneath it is termed a confined aquifer. Groundwater moves through aquifers toward natural exits, or discharge points, to reappear at the surface.

The direction of groundwater flow through an aquifer system is determined by the permeability of the strata containing the aquifer and the hydraulic gradient, which is a measure of the difference in hydraulic head over a specified distance. Differences in hydraulic head are the driving force for groundwater movement through the saturated zone. The hydraulic head at any given point in an aquifer is a function of the energy associated with the water's elevation above sea level and the pressures exerted on it by surrounding water. Because hydraulic head is not just a function of elevation, downgradient is not necessarily synonymous with downhill. The downgradient direction will have a horizontal and vertical component, just as a household drain moves wastewater both vertically and horizontally seeking the lowest point of exit. Aquitards deflect groundwater movement just as drain-pipe walls control the direction of wastewater movement. In an aquifer constrained by aquitards such as horizontal clay layers, the downgradient direction tends to be more horizontal than vertical.

The strategy that underlies the placement of wells at SRS is complex, but the theory behind their placement is simple. Rainwater moves soluble substances downward through the unsaturated zone to the water table. The water then flows downgradient toward the discharge point. Monitoring wells are generally located to determine the effect of a specific site on groundwater quality near the site. Wells placed to intercept the groundwater flowing away from a site are called downgradient wells. Wells placed to intercept groundwater before it flows under a site are called upgradient wells. Wells sampling groundwater flowing next to a site are called sidegradient wells. Any contamination of the downgradient wells not present in the upgradient wells of a site is assumed to be a product of that site.

Wells are drilled to various depths in the saturated zone below the area to be monitored. At the screen zone, the well casing is perforated to allow water to enter the well. Thus, the screen zone refers to the zone of subsurface strata whose water is being sampled by the well. Figure 8-15 illustrates the construction of a monitoring well and the relationship between screen zone and water elevation for wells screened below the water table. The water rises in the well casing to equilibrate with the hydraulic head of the water surrounding the well's screen zone. The elevation of this water in the well is measured to determine the hydraulic head of the water in the zone monitored. By comparing the water levels in adjacent wells screened in the same zone, the hydraulic gradient can be determined, and the horizontal direction of groundwater flow can be predicted. Only wells screened in the same zones are considered when determining the horizontal gradient; wells screened above and below an aquitard can have different hydraulic heads, thus defining a vertical gradient.

The vertical direction of groundwater movement is controlled by the permeability of the aquitards and the relative difference in hydraulic head of the water on either side of an aquitard. Vertical gradients can be determined by comparing the water levels between adjacent wells screened on either side of an aquitard. If the water levels in deeper wells are higher than those in shallower wells, the vertical component of flow is upward.

The implications of the above discussions for SRS are clear. Substances placed in the soil may be dissolved in rainwater and transported into the saturated zone. Groundwater aquifers are the primary pathways by which a potentially hazardous substance may enter nearby streams and eventually the Savannah River. Vertical and horizontal groundwater flow directions are in part determined by the permeability and continuity of geologic strata. In order to monitor the movement of groundwater effectively, and any hazardous constituents it may contain, researchers at SRS have undertaken many detailed studies of the geology of strata beneath the site.

Geological and Hydrogeological Setting at SRS

SRS is located on the Upper Atlantic Coastal Plain, approximately 20 miles southeast of the Fall Line, which separates the Piedmont and Coastal Plain provinces. The site is on the Aiken Plateau, a relatively flat area that slopes southeastward and is dissected by several tributaries of the Savannah River.

SRS is underlain by a 700- to 1,200-ft-thick, seaward-thickening wedge of Coastal Plain sediment composed of unconsolidated sands, clayey sands, sandy clays, and lesser amounts of calcareous sediment. These layers are underlain by dense crystalline igneous and metamorphic rock or consolidated sediments of the Triassic Period. The Triassic formations and older igneous and metamorphic rocks are hydrologically isolated from the overlying Coastal Plain sediments by a regional aquitard (Figures 8-16 and 8-17). Within the Coastal Plain sediments, the sandy strata are generally porous and permeable and may form aquifers. Strata rich in clays are made less porous by the presence of tiny pore-filling clay particles. Clayey strata, therefore, are less permeable than sandy strata and tend to be aquitards.

For the purposes of this report, we will discuss three major water-bearing zones in Coastal Plain sediments divided by regional aquitards. In ascending order, these are the Cretaceous zone, the Congaree-Four Mile zone, and the upper saturated zone, including the water table in most areas. (These terms are informal: for correlation with regional aquifers and SRS regulatory hydrostratigraphic nomenclature, see Figure 8-16.) Monitoring wells at SRS primarily sample water from these zones. A simplified description of the sediments, beginning with the deeper and ending with the shallower formations, follows and is presented graphically in Figure 8-16.

The deepest aquifer monitored at SRS occurs in sediments of geologic formations of Cretaceous age. These Cretaceous sediments are largely permeable quartz sands and sandy clays capable of yielding abundant water; they constitute a regionally important aquifer. Overlying the Cretaceous zone is a regional aquitard composed of sandy-clay and clay sediments in formations of Paleocene age.

The Paleocene aquitard separates the deep Cretaceous zone from the overlying intermediate-depth Congaree-Four Mile zone, which occurs in sediments of early Eocene age. The Congaree-Four Mile zone is a locally important source of groundwater, occurring in moderately- to well-sorted sand and interbedded sandy-clay sediments capable of yielding several hundred gallons of water per minute. A local aquitard, composed predominantly of clay and identified in SRS literature as "Green Clay," overlies the intermediate-depth Congaree-Four Mile zone, separating it from the upper saturated zone in shallow formations of middle to late Eocene age and post

Eocene age. (In the Savannah River Valley between SRS and Georgia, this aquitard and the sediments of the underlying Congaree-Four Mile zone have been eroded by river channel migration and incision.) Sediments of the upper saturated zone are predominantly sandy clay and calcareous sediments and generally yield low amounts of water. Numerous discontinuous clay-rich layers (including the "Tan Clay" of SRS literature) in these middle to late Eocene-age formations create local aquitards in the upper saturated zone, resulting in locally complex patterns of groundwater flow.

At SRS, the horizontal direction of groundwater movement is largely governed by the depths of incisions of the creeks and streams where water is discharged to the surface. The valleys of the smaller perennial streams allow discharge from the upper saturated formations. The valleys of major tributaries of the Savannah River drain formations of intermediate depth, and the valley of the Savannah River drains deep formations. Generally, groundwater in the deep Cretaceous zone flows toward and discharges into the Savannah River. Flow in this zone from both the Georgia and South Carolina sides of the river is indicated by the potentiometric contours in Figure 8-18 [Siple, 1967]. Groundwater in intermediate depth lower Eocene-age formations (the Congaree-Four Mile zone) flows toward and discharges into Upper Three Runs Creek or the Savannah River, depending on proximity. Groundwater in younger sediments (the upper saturated zone) generally flows toward and discharges into the nearest perennial stream, swamp, or river.

The role of stream valleys in determining groundwater flow directions and hydraulic gradients at SRS is shown in Figures 8-19 and 8-20. Figure 8-19 is a contour map of the water table at the separations and waste management areas, based on water elevation measurements at several hundred wells in that vicinity during February 1991. Upper Three Runs Creek and Four Mile Creek, shown in blue, flow to the southwest along the upper and lower margins of the map, respectively. Minor perennial streams are also shown. Water table contours in stream valleys tend to be a subdued expression of surface topographic contours. Horizontal flow directions (shown by red arrows) are perpendicular to the water table contours and are controlled by the depth and orientation of stream valleys.

Figure 8-20 is a simplified hydrogeologic cross section looking to the southwest along the line A-A' in Figure 8-19. Horizontal flow directions in the

uppermost saturated zone and the Congaree-Four Mile zone are shown with red arrows following the slope of the potentiometric surfaces of these two water-bearing zones. Groundwater in the upper saturated zone may flow toward discharge points along either Four Mile Creek or Upper Three Runs Creek or downward into the Congaree-Four Mile zone. Once groundwater enters the Congaree-Four Mile zone, horizontal flow is toward discharge points along Upper Three Runs Creek. Downward flow from the Congaree-Four Mile zone into the Cretaceous zone is restricted by the clay-rich sediments of the Paleocene aquitard and by a loss of hydrostatic head in the Congaree-Four Mile zone resulting from discharge into Upper Three Runs Creek.

Few aquitards are continuous across SRS. Generally, in the northwestern part of SRS (near A and M areas; Figure 8-21), aquitards are less continuous, permitting vertical flow of groundwater. Where aquitards are more continuous, as they are in the southeastern portion of SRS, groundwater movement is predominantly horizontal. Along the Pen Branch fault (Figure 8-17), aquitards (and transmissive zones) are offset, making the aquitards effectively discontinuous and increasing the likelihood of vertical interchange of water from one transmissive zone to another.

Beneath much of SRS, hydraulic head decreases with depth, so the vertical component of groundwater flow is downward. This is the case in A and M areas, where discontinuous aquitards and downward-decreasing hydraulic head allow the downward movement of water from the water table to deeper zones. This type of area is called an aquifer recharge zone (Figure 8-21). However, because of the discharge of intermediate depth Eocene groundwater to the valleys of Upper Three Runs Creek and the Savannah River, the hydraulic head in sediments above the Paleocene aquitard is less than the hydraulic head in sediments below the Paleocene aquitard. Thus, the vertical hydraulic gradient is upward, from the lower to the upper sediments in some areas (Figure 8-21). This upward flow occurs, for example, in the separations and waste management areas, where both the Paleocene aquitard and an upward hydraulic gradient restrict downward flow of groundwater from Eocene into Cretaceous-age sediments. This upward flow component beneath the separations and waste management areas prevents the downward migration of hazardous substances from overlying zones at this site into the Cretaceous zone.

Groundwater at SRS is monitored in three major zones: the Cretaceous zone, the Congaree-Four Mile zone, and the upper saturated zone in formations overlying the sediments constituting the Congaree-Four Mile zone. At local monitored sites, these zones may be further subdivided to account for variations in sediment types and groundwater flow. Vertical and horizontal flow directions in these zones are controlled by hydraulic head, the permeability of sediments forming aquifers and aquitards, and proximity to discharge points. Local flow patterns may be very complex; nevertheless, all groundwater in these zones eventually exits the subsurface and flows from springs or streams into the Savannah River.

Uses of Groundwater in the Vicinity of SRS

Groundwater is used as a domestic, municipal, and industrial water supply throughout the Upper Coastal Plain. Most municipal and industrial water supplies in Aiken County are developed from the Cretaceous zone. Domestic water supplies are primarily developed from the Congaree-Four Mile zone and the upper saturated zone. In Barnwell and Allendale counties, some municipal users are supplied from the Congaree-Four Mile zone and overlying units that thicken to the southeast. At SRS, most groundwater production is from the Cretaceous zone with a few lower-capacity wells pumping from the Congaree-Four Mile zone. Every major operating area at SRS has groundwater production wells. Total groundwater production at SRS is from 9 to 12 million gal/day, similar to the volume pumped for industrial and municipal production within 10 miles of SRS.

Groundwater Monitoring Program at SRS

The Groundwater Monitoring Program at SRS gathers data to quantify the effect of SRS facilities on groundwater quality. The program is designed to accomplish the following:

- assist SRS in complying with environmental regulations and DOE directives
- provide data to identify and monitor constituents in the groundwater
- permit characterization of new facility locations to ensure they are well suited to house the intended facilities
- support basic research projects

The Groundwater Monitoring Program at SRS is performed by the Groundwater Monitoring Group (GMG) of EMS. GMG provides the services for

installing monitoring wells, collecting and analyzing samples, and reporting results to assist the operating departments in meeting their responsibilities.

The current EPD/EMS Groundwater Monitoring Program monitors for radioactive and nonradioactive constituents. The radioactive constituents primarily include gross alpha, nonvolatile beta, gamma emitters, Sr-89,90, total radium, and tritium. The nonradioactive constituents include volatile organics, herbicides, pesticides, metals, major ions, and numerous other constituents.

Sample Scheduling and Collection

EPD/EMS schedules groundwater sampling either in response to specific requests from SRS personnel or as part of the ongoing EPD/EMS Groundwater Monitoring Program. These groundwater samples provide data for reports required by federal and state regulations and for internal reports and research projects. The ongoing EPD/EMS Groundwater Monitoring Program schedules wells to be sampled semiannually, annually, or biennially. Groundwater monitoring requests by personnel outside of EPD/EMS typically require samples to be collected monthly, quarterly, semiannually, or annually; however, other time periods may be requested. Sampling and shipping procedures are consistent with EPA, SCDHEC, and U.S. Department of Transportation (DOT) methods.

New wells added to the EPD/EMS program are sampled for four consecutive quarters to analyze for a comprehensive list of constituents (Chart 8-9). Except for several old wells not constructed properly for collecting samples for all analyses, these comprehensive analyses are conducted for all active EPD/EMS monitoring wells every two years to identify any new constituents. Wells with constituent concentrations above certain limits are identified and are subsequently sampled either annually or semiannually, depending on the concentrations of the constituents. Field measurements of pH, temperature, specific conductance, alkalinity (as CaCO_3), and water level are taken quarterly at all active EPD/EMS monitoring wells. Groundwater samples are collected from monitoring wells with either dedicated pumps or bailers. The pumped samples and some bailed samples are collected only after four well volumes have been purged to assure that the pH and specific conductance have stabilized, indicating that the stagnant well water has been removed. Wells that are bailed have dedicated bailers to prevent cross-contamination among wells.

EPA-recommended preservatives and sample handling techniques are used during sample storage and transportation to both onsite and offsite analytical laboratories. Sample bottles and shipping coolers are tested and approved using DOT standards [CFR, 1991a]. Potentially radioactive samples are screened for total activity prior to shipment to determine appropriate packaging requirements.

Deviations from the routine sampling and analysis schedule for 1991 are published quarterly in the SRS groundwater monitoring reports [Environmental Monitoring, 1991, 1991a, 1991b, 1991c].

Analytical Procedures

In 1991, General Engineering Laboratories of Charleston, S.C., performed most of the groundwater analyses. IT Analytical Services of St. Louis, Mo., performed groundwater analyses for the first quarter of 1991. The EPD/EMS radiological laboratory at SRS analyzed samples for gross alpha, nonvolatile beta, gamma emitters, tritium, Sr-89, 90, and uranium/plutonium for first quarter 1991; for the remainder of the year, this laboratory only analyzed radiological samples for K-Area wells and screened potentially radioactive samples for total activity prior to shipment. During second quarter, Ecotek Laboratory Services, Inc., of Atlanta, Ga., performed specific radionuclide analyses previously done by IT Analytical Services and EPD/EMS. During third and fourth quarters, Teledyne Isotopes of Northbrook, Illinois, performed the same radiological analyses that were previously done by Ecotek. The M-Area laboratory at SRS analyzed samples for six specific volatile organic compounds in 1991. The D-Area laboratory at SRS analyzed samples from K-Area Reactor Seepage Basin for deuterium and gross alpha/beta/gamma in 1991. The contracted laboratories are certified by SCDHEC.

A representative list of nonradioactive and radioactive analytes and the corresponding EPA-approved analytical methods and laboratory detection limits are given in the SRS groundwater quarterly reports as referenced above. In 1991, comprehensive analyses (Chart 8-9) were performed on active wells during first quarter and on new or previously unsampled wells as described in the Sample Scheduling and Collection section.

Analytical results, submitted to EPD/EMS on computer disks by each laboratory, are screened for entry into a computer database. Once in the database, the groundwater data are prepared for publication in formal periodic reports to regulatory agencies, for

**Chart 8-9
Comprehensive Analyses Constituents**

Arsenic	Nonvolatile beta
Barium	Pesticides/herbicides ^b
Cadmium	Phenols
Chloride	Selenium
Chromium	Silver
Fluoride	Sodium
Gross alpha	Specific conductance
Iron	Sulfate
Lead	Total dissolved solids
Major ions ^a	Total organic carbon
Manganese	Total organic halogens
Mercury	Total phosphates (as P)
Nitrate as nitrogen	Total radium
	Tritium

a Major ions include the following: calcium, alkalinity (field measurements), magnesium, potassium, and silica.

b Pesticide/herbicide analyses, conducted the first quarter of the initial four quarters of comprehensive analyses, are part of the regular biennial comprehensive analyses. The pesticide/herbicide analyses include the following: 2,4-dichlorophenoxyacetic acid, endrin, lindane, methoxychlor, toxaphene, and 2,4,5-TP (silvex).

publication in the SRS annual environmental report, for publication in internal documents, and for use in research studies.

Evaluation of Groundwater Data

EPD/EMS receives analytical results and field measurements as reports and as ASCII computer files that are loaded onto a mainframe computer at SRS. Logbooks track receipt and transfer of data to the mainframe database, and computer programs provide data in a format that can be validated.

Quality control practices include the following:

- verification of correct well names and sample dates for field and analytical data
- verification that all analyses requested on the chain-of-custody forms are complete for each laboratory
- identification of data entry problems (e.g., duplicate records, incorrect units)

- comparison of analytical data to historical analytical data and review of the data for transcript, instrument, or calculation errors
- comparison of blind replicates and laboratory in-house replicates for inconsistencies
- identification of laboratory blanks and blind blanks with elevated concentrations

Possible transcription errors and suspect results are documented and submitted to the appropriate laboratory for verification or correction. No changes are made to the database until the laboratory documents the problem and solution. Changes to the database are recorded in a logbook.

EPD/EMS publishes quarterly reports that identify samples that have been analyzed after their expiration dates, suspect results that have been verified by the laboratory, and the analyses of blanks with elevated results.

Changes to the Groundwater Monitoring Program During 1991

Four new well series were added to the Groundwater Monitoring Program in 1991:

- Seventeen wells of the BGX series monitored the site of the future E-Area Vaults.
- Four wells of the HMD series monitored the site of the future Hazardous Waste/Mixed Waste Disposal Facility.
- Four wells of the LAW series monitored the L-Area Oil and Chemical Basin.
- Sixteen wells of the NPM series monitored the Potential New Production Reactor Site.

The following 196 new wells were added to existing well series and monitored for the first time in 1991:

- Nine wells of the AMB series monitored the Metallurgical Laboratory Seepage Basin.
- Five wells of the ASB series monitored the Savannah River Laboratory (SRL) Seepage Basins.
- In the BGO series, 7 replacement wells monitored the Burial Grounds and Mixed Waste Management Facility (MWMF), 5 new wells monitored the Burial Grounds, and 21 new wells monitored the MWMF.
- One replacement well of the FCA series monitored the F-Area Canyon Building.
- Five replacement wells and 25 new assessment wells of the FSB series monitored the F-Area Seepage Basins.

- Twenty-five assessment wells of the HSB series monitored the H-Area Seepage Basins.
- Two wells of the HXB series monitored the Ford Building Seepage Basin.
- Two wells of the IDB series monitored Site B of the Interim Waste Technology Site.
- Two wells of the IDQ series monitored Site Q of the Interim Waste Technology Site.
- Four wells of the KRB series monitored the K-Area Retention Basin.
- One new well of the KSB series monitored the K-Area Seepage Basins.
- Twenty-six wells of the LFW series monitored the Sanitary Landfill.
- In the MSB series, 36 point-of-compliance wells monitored the M-Area Hazardous Waste Management Facility (HWMF) and 14 plume definition wells monitored M Area.
- Six wells of the SCA series monitored the S-Area Vittrification Building

The following 13 wells were abandoned in 1991:

- One well (AMB 4) in the Metallurgical Laboratory Seepage Basin was abandoned because it was too close to the edge of the basin and would have been covered when the basin was closed.
- Wells in the F-Area Seepage Basins (FSB 94D, 95C, 95D, 96A, 98A, and 105D) and H-Area Seepage Basins (HSB124A) were replaced because they were contaminated with grout or they consistently purged dry, producing no water for analytical results.
- Wells in the K-Area Retention Basin (KRB 1, 8, 13, 14, and 15) were abandoned because construction activities while inserting a liner in the basin re-contoured the basin walls and ruined the monitoring well system.

When EPD/EMS awarded new laboratory contracts in 1991, a new data format was implemented to collect more information about each analysis. The information now provided to EPD/EMS includes the well name, chain-of-custody number, sample date, date the laboratory received the sample, extraction date, analysis date, test name, analysis method, detection limit, batch number, and result qualifiers for each analysis.

The following groundwater reports are public documents: *The Savannah River Site's Groundwater Monitoring Program, First Quarter 1991* (ESH-

EMS-910087), *The Savannah River Site's Groundwater Monitoring Program, Second Quarter 1991* (ESH-EMS-910088), *The Savannah River Site's Groundwater Monitoring Program, Third Quarter 1991* (ESH-EMS-910089), *The Savannah River Site's Groundwater Monitoring Program, Fourth Quarter 1991* (ESH-EMS-910090), and *Environmental Protection Department's Well Inventory* (ESH-EMS-910092). The analytical results for all analyses conducted in 1991 are given in the quarterly reports and will not be found in this report.

Applicable Monitoring Standards

The analytical results of samples taken from the SRS monitoring wells that exceed federal primary drinking water standards are discussed in this section. Aquifers at SRS are classified as potentially acceptable drinking water sources. South Carolina has established a policy to maintain the quality of these waters suitable for drinking water [SCDHEC, 1985]. Federal and state primary drinking water standards would apply if groundwater beneath the monitored locations was used for drinking water. Federal secondary drinking water standards are not addressed in this section because they are primarily aesthetic guidelines relating to public acceptance of drinking water [CFR, 1991b]. Federal primary drinking water standards for radioactive and nonradioactive constituents are given in Table 8-106. Some standards have not been formally accepted and are not addressed in this section because they may change before they are made final.

Four constituents without drinking water standards are discussed in the text when their values exceed certain levels. These constituents are specific conductance at values equal to or greater than 100 $\mu\text{S}/\text{cm}$, alkalinity (as CaCO_3) at values equal to or greater than 100 mg/L , total dissolved solids (TDS) at values equal to or greater than 200 mg/L , and pH at values equal to or below 4.0 or equal to or above 8.5. The selection of these values as standards for comparison is somewhat arbitrary; however, these values exceed levels usually found in background wells at SRS. The occurrence of elevated alkalinity (as CaCO_3), specific conductance, and pH within a single well may indicate leaching of the grouting material used in well construction.

Waste Sites Common To Several Areas

There are five waste sites within SRS that are common to several areas. The descriptions for these waste sites are as follows:

Acid/Caustic Basins

The acid/caustic basins in F, H, K, L, P, and R areas are unlined earthen pits (approximately 50 ft by 50 ft by 7 ft deep) that received dilute sulfuric acid and sodium hydroxide solutions used to regenerate ion-exchange units in the water-purification processes at the reactor and separations areas in the center of SRS. Other wastes discharged to the basins included water rinses from the ion-exchange units, steam condensate, and runoff from the spill containment enclosures for the storage tanks. The basins allowed mixing and neutralization of the dilute solutions before their discharge to nearby streams.

The basins were constructed between 1952 and 1954. The R-Area basin was abandoned in 1964, the L-Area basin in 1968, and the H-Area basin in 1985. The other basins remained in service until new neutralization facilities became operational in 1982. The basins are uncovered and most are dry except during periods of prolonged precipitation. The basins are part of the Resource Conservation and Recovery Act (RCRA) Facility Investigation/Remedial Investigation (RFI/RI) program. Presently, the basins in F, H, K, and P areas are also RCRA sites. An Interim Status Closure Plan was submitted to SCDHEC on Feb. 7, 1992, proposing the clean closure of these basins. A work plan for characterization work for the L- and R-Area acid/caustic basins has been submitted to EPA Region IV and SCDHEC as part of the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) process. This work plan defines a program for determining the extent of contamination at these basins.

Burning/Rubble Pits

From 1951 to 1973, burnable wastes such as paper, wood, plastics, rubber, oil, degreasers, and drummed solvents were received and burned monthly in one or more of the burning/rubble pits in A, C, Central Shops, D, F, K, L, P, and R areas. In 1973, the burning of waste stopped, and the pits were covered with a layer of soil. Rubble wastes, including paper, wood, concrete, empty galvanized-steel barrels and drums, and cans were then disposed of in the pits until they reached capacity and were covered with soil. All burning/rubble pits were inactive by 1981, and all are covered except the R-Area pit (131-1R), which has not been backfilled. These pits are part of the RFI/RI program. In addition, work plans to fully characterize the extent of contamination at all the burning/rubble pits have been submitted to EPA and SCDHEC.

Coal Pile Runoff Containment Basins

Electricity and steam at SRS are generated by burning coal, which is stored in open piles. The coal is generally moderate-to-low sulfur coal (1–2 percent), which is received by rail, placed on a hopper, sprayed with water to control dust, and loaded onto piles. Coal piles originally existed in A, C, D, F, H, K, L, P, and R areas. The coal pile in R Area was removed in 1964, the L-Area coal pile was removed in 1968, and the coal piles in C and F areas were removed in 1985. In 1991, the K-Area coal pile was removed down to a 2-in. base, and 75 percent of the P-Area coal pile was also removed.

The facilities generally contain a 90-day reserve of coal, which is not rotated, resulting in long-term exposure to the environment. This weathering results in the formation of sulfuric acid, which is produced by the chemical and biological oxidation of sulfur compounds in the coal.

To achieve compliance with the NPDES permit issued in 1977, coal pile runoff containment basins in A and D areas were completed in October 1978, and basins in C, F, H, K, and P areas were completed in March 1981.

Currently, rainwater runoff from the remaining coal piles in A, D, H, K, and P areas flows into the coal pile runoff containment basins via gravity flow ditches and sewers. The basins allow mixing of the runoff and its seepage into the subsurface, thus preventing the entry of large surges of low pH runoff into surface streams. All of the basins are active including those in C and F areas, which still collect runoff although no coal remains at either location. All of these basins are part of the RFI/RI program.

Disassembly Basins

The disassembly basins were constructed adjacent to each reactor at SRS to store irradiated assemblies (reactor fuel and target rods) prior to their shipment to the separations areas. The disassembly basins are concrete-lined tanks containing water. The irradiated assemblies are rinsed before being placed in the basins, but some radioactivity is transferred from these assemblies to the basin water. Radionuclides enter the disassembly basin water as a film of liquid on the irradiated components as they are discharged from the reactor tank to the disassembly basin, in the oxide corrosion film on the irradiated components, and, infrequently, from leaks in porous components. Sand filters are used to remove radioactive particulates from the disassembly basin water. The filtered basin

water is circulated through deionizers to remove additional constituents and is periodically purged through regenerated deionizers to the reactor seepage basins. The disassembly basin is then filled with clean water. Purging is carried out to reduce radiation exposure to operating personnel from the accumulation of tritium in the basin.

Reactor Seepage Basins

Since 1957, active reactor seepage basins have received low-level radioactive purge water from the disassembly basins. This water purge is necessary to keep the tritium concentration in the disassembly basin water within safe levels for operating personnel. Although many radionuclides have been discharged to the basins, almost all of the radioactivity is due to tritium and small amounts of Sr-90, Cs-137, and Co-60.

Before the use of mixed-bed deionizers and sand filters began in the 1960s, purge water was pumped directly from the disassembly basins to the seepage basins. From 1970 to 1978, the seepage basins for active reactors were bypassed, and the filtered, deionized purge water was discharged directly into nearby streams. In 1978, the seepage basins for C, L, and P reactors were reactivated. The K-Area Reactor Seepage Basin was used from 1957 to 1960 only. Since that time, water has been purged from the K-Area Disassembly Basin to the K-Area Retention Basin. The R-Area Seepage Basins have been filled and covered with asphalt. The K- and R-Area Reactor Seepage Basins are part of the CERCLA RI program.

Groundwater Monitoring Results

The following section describes the groundwater monitoring results for approximately 100 locations (Figure 8-12) within designated areas at the SRS. The areas are grouped by their functions in the following order: administration and manufacturing, reactor, separations and waste management, and other areas. The discussions of recent trends in the data are based on results presented in the groundwater monitoring chapters of the SRS annual environmental reports from 1986 through 1991. The applicable standards referred to in these discussions and elsewhere throughout the section are the EPA primary drinking water standards given in Table 8-106 and the standards presented for specific conductance, alkalinity (as CaCO_3), TDS, and pH in the Applicable Monitoring Standards section of this section. Wells that could not be sampled during the year are listed as inaccessible, suffering mechanical failure, or contain-

ing insufficient water. Geographical descriptions in the text are based on true north rather than SRS grid coordinates. Figures 8-23, 8-24, 8-26 through 8-46, and 8-49 are oriented by SRS grid coordinates.

Administration and Manufacturing Areas

The administration and manufacturing areas, A and M areas, are located in the northwest portion of SRS (Figure 8-22). A Area houses administrative and research facilities. The latter includes the SRL, which conducts environmental research and management projects. M Area produces nuclear fuels, targets, and other reactor components. Surface elevations across these areas range from approximately 350 to 380 ft mean sea level (msl). Surface drainage is toward Tims Branch, approximately 5,000 ft to the east, and toward valleys to the northwest and southwest that lead to the Savannah River. The nearest SRS boundary is approximately one-half mile to the northwest.

The water table beneath A and M areas slopes radically to the southeast, south, and southwest toward Tims Branch and other discharge points. Geohydrologic information from these areas indicates that most of the water of the upper saturated zone migrates downward into lower water-bearing zones.

In 1991, groundwater was monitored at the following locations in A and M areas:

A-Area Burning/Rubble Pits

The A-Area Burning/Rubble Pits (731-A and 731-1A) and A-Area Ash Pile (788-2A) are approximately 800 ft west of Road D and 1,000 ft north of the A-Area Metals Burning Pit (Figure 8-23). Although the pits are backfilled and inactive, A-Area Ash Pile 788-2A, which is currently active, is near pits 731-A and 731-1A. See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pits were monitored by the four wells of the ARP series in 1991. Well ARP 1A was sampled but provided no water-elevation data. Horizontal groundwater flow beneath the pits is to the west toward the Savannah River Swamp. Relative to the pits, wells ARP 2 and 3 are upgradient, well ARP 1A is downgradient, and well ARP 4 is sidegradient.

As in the past, no radioactive constituents were detected above DWS in 1991. Lead was detected at the DWS in the downgradient well ARP 1A (Table 8-33). Trichloroethylene concentrations exceeding the DWS were detected in wells ARP 1A and 3. Well ARP 3 had levels of tetrachloroethylene above the DWS.

A-Area Coal Pile Runoff Containment Basin

The A-Area Coal Pile Runoff Containment Basin (788-3A) is east of Road D and approximately 535 ft southeast of the A-Area coal pile (Figure 8-24). See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins.

The basin was monitored in 1991 by the four water-table wells of the ACB series. Horizontal gradients are very low beneath the site, which appears to sit above a water-table divide between Tims Branch and the Savannah River Swamp. As a result, horizontal flow directions are difficult to determine. It appears that all four wells are downgradient to sidegradient of the basin.

As in the past, wells ACB 3A and 4A show concentrations of total radium above the DWS and elevated specific conductance (Table 8-34). Well ACB 4A had a single analysis of gross alpha above the DWS.

A-Area Metals Burning Pit

The A-Area Metals Burning Pit (731-4A), placed in service about 1952, is west of Road D and south of the A-Area Burning/Rubble Pits (Figure 8-23). Lithium-aluminum alloy, aluminum pieces, plastic pipe, metal drums, and other metal scraps were deposited in the pit and burned periodically. In 1974, the solid materials remaining in the pit were covered with soil, and the pit was regraded. The pit is currently inactive and part of the RCRA RFI/RI program.

Twelve wells of the ABP series monitored the pit in 1991. Wells ABP 1DD, 2DD, 4DD, 6D, 7D, and 8D provided water-level data only and were not sampled. Well ABP 3 is screened at the water table, and wells ABP 1A, 2A, 3C, 4, and 8C monitor the lower portion of the upper saturated zone and the Congaree-Four Mile zone. Horizontal groundwater flow in the monitored zones is generally to the southwest toward the Savannah River Swamp. Relative to the pit, well ABP 1A appears to be upgradient, well ABP 8C appears to be sidegradient, wells ABP 2A, 3, and 3C appear to be upgradient to sidegradient, and well ABP 4 appears to be downgradient to sidegradient. Water-level measurements from the ABP wells show a downward vertical gradient that might result in downward migration of groundwater from the water table into the Congaree-Four Mile zone.

Concentrations of chlorinated volatile organics were detected above DWS in wells ABP 2A, 3, 3C, and 4

(Table 8-35). Results from well ABP 8C showed activities of total radium, nonvolatile beta, and tritium (single analysis) and concentrations of antimony and lead above DWS. Elevated levels of alkalinity (as CaCO_3), pH, TDS, and specific conductance in well ABP 8C indicate possible leaching of well grout. Except for lead concentrations and tritium activity, results above applicable standards are similar to those of past years.

M-Area Hazardous Waste Management Facility

The M-Area HWMF consists of the M-Area Settling Basin (904-51G), which is south of M Area and west of Road D, and Lost Lake (904-112G) (Figure 8-24). The unlined basin, in operation from 1958 until 1985, received wastewater containing metal-cleaning solvents, depleted uranium, and other chemicals and metals from fuel fabrication processes in M Area. Water from the settling basin flowed through an overflow ditch to Lost Lake, a shallow upland depression. A seepage area formed adjacent to the ditch and Lost Lake. A closure cap was completed on the basin during 1989. The closure was certified by RCRA on February 11, 1991, and accepted by SCDHEC on April 26, 1991. The basin is the first SRS hazardous waste unit to be closed under RCRA.

In the early 1980s, 11 wells (MSB 1A, 2A, 3A, 4A, 5A, 6A, 7A, 8A, 13A, 13B, and 13C) were installed and approved by SCDHEC as the original point-of-compliance (POC) groundwater monitoring wells at the M-Area HWMF. An additional well, MSB 22, was approved as a POC well in 1988. In 1990, sampling at five of these early POC wells (MSB 1A, 2A, 3A, 4A, and 13C) was discontinued due to declining water levels at the M-Area HWMF that resulted from basin closure and continued operation of the recovery system (see Plume Definition Wells in this section). These wells were then replaced by 36 new POC wells (MSB 1B, 1C, 1CC, 1D, 2B, 2C, 2D, 3B, 3C, 3D, 4B, 4C, 4D, 5B, 5C, 6B, 6C, 7B, 7C, 8B, 8C, 13CC, 13D, 57D, 58D, 59D, 60D, 62B, 62C, 62D, 63B, 63C, 63D, 64B, 64C, and 64D) as part of the M-Area Phase IV Drilling Program at the M-Area HWMF.

In 1991, the M-Area HWMF was monitored by the following POC wells: MSB 1B, 1C, 1CC, 1D, 2B, 2C, 2D, 3B, 3C, 3D, 4B, 4C, 4D, 13A, 13B, 13CC, 13D, 22, 57D, 58D, 59D, 60D, and well clusters MSB 5, 6, 7, 8, 62, 63, and 64. Well MSB 8A was dry. Wells MSB 29A, 29B, 29C, 29D, 29TA, 43A, 43B, 43D, and 43TA are designated background wells for the facility. These wells monitor the upper saturated zone, the Congaree-Four Mile zone, sandy beds within the regional Paleocene aquitard, and the Cretaceous zone

beneath the facility. Horizontal flow direction in all zones is generally to the southeast toward the Savannah River. The pumping of water in the groundwater remediation program (see Plume Definition Wells in this section) has altered hydraulic gradients beneath the facility, making upgradient and downgradient designations inappropriate. Downward vertical gradients exist from the water table to the Cretaceous zone. However, groundwater flow in the Congaree-Four Mile and Cretaceous zones beneath the facility appears to be predominantly horizontal.

As in the past, the trichloroethylene and tetrachloroethylene plume affects groundwater in numerous wells monitoring this facility (Table 8-36); the highest concentrations exceeding DWS are found in wells surrounding the M-Area Settling Basin. A dense non-aqueous liquid (DNAPL), consisting primarily of trichloroethylene and tetrachloroethylene, was found at the bottom of well MSB 3D during routine sampling events, and the well is now part of the DNAPL Contamination Assessment Study. Concentrations of nitrate above the DWS continue to be found in more than half of the facility's wells, with the highest levels detected in the vicinity of Lost Lake. Concentrations of 1,1-dichloroethylene exceeding the DWS were detected in nine MSB wells, and several other chlorinated volatile organics were reported in one to two wells each. Concentrations of lead above the DWS were reported for several wells. Nonvolatile beta and total radium were detected above DWS in several of the POC wells, and total radium was above the DWS in one of the facility's designated background wells. Uranium and U-234 were reported above DWS in one and two wells, respectively. Thallium levels above the DWS were reported for two wells. In addition, several wells had elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS, which indicate the probable influence of well grout.

Since the beginning of the full-scale recovery system for the groundwater remediation program in April of 1985, pumping has markedly changed groundwater flow near this facility. As a result, changes in concentrations of analytes in groundwater through time in this area are difficult to interpret accurately.

Metallurgical Laboratory Seepage Basin

The Metallurgical Laboratory Seepage Basin (904-110G) at the east edge of A Area (Figure 8-24) received wastewater effluent from the Metallurgical Laboratory Building (723-A) from 1956 until 1985. Wastewater released to the basin consisted of small

quantities of laboratory wastes from metallographic sample preparation (degreasing, cleaning, etching) and corrosion testing of stainless steel and nickel-based alloys. The wastewater volume discharged from the laboratory was small (5 to 10 gal/day) and consisted mostly of rinsewater. Noncontact cooling water (approximately 900 gal/day) was also discharged. The basin is currently inactive and contains rainwater. Revision V of the closure plan was approved by SCDHEC on September 17, 1991. The construction phase of the project was implemented on December 9, 1991. The basin has been de-watered, backfilled, and capped with low-permeable clay. A revised RCRA Part B Post-Closure Care Permit application was submitted to SCDHEC on December 31, 1991. The basin closure is scheduled to be completed by May 14, 1992.

The basin was monitored by the 19 wells of the AMB series in 1991. Five of these wells were added in 1989 to monitor the shallow bay-like depression adjacent to the basin. In 1991, nine wells, those with an "A" or "B" suffix, were added to provide additional analytical information and to monitor the Congaree-Four Mile zone in response to SCDHEC's comments about the RCRA Part B Post-Closure Care Permit (initially submitted in July 1989). Horizontal groundwater flow in the upper saturated zone is generally to the northwest. Relative to the facility, well AMB 11D is upgradient; wells AMB 5, 6, 8D, and 9D are downgradient; wells AMB 7 and 12D are upgradient to sidegradient; well AMB 4D is immediately adjacent to the basin; and, due to the irregular shape of the bay-like depression, well AMB 10D is upgradient to one portion of the facility and downgradient to another. Well AMB 10DD monitors a perched water-bearing zone in the southern portion of the facility. Horizontal groundwater flow within the Congaree-Four Mile zone is to the southeast. Water elevations of AMB wells that monitor this deeper zone show a downward vertical groundwater flow gradient, which implies the potential for downward migration of groundwater from the water table into the Congaree-Four Mile zone.

Analytical results for the AMB wells are similar to previous years' results except that prior to 1991 there were no AMB wells monitoring the Congaree-Four Mile zone. Single analyses of gross alpha exceeding the DWS were reported for wells AMB 7, 12D, and 13AR (Table 8-37). Total radium above the DWS was detected in well AMB 5 and in single analyses for wells AMB 4D, 9D, and 11B. Lead and antimony exceeded DWS in wells AMB 4 and 4D, respectively.

Elevated specific conductance and concentrations of chlorinated volatile organics above DWS were detected in several upgradient and downgradient wells monitoring the upper saturated zone and in several Congaree-Four Mile zone wells. Wells AMB 10A and 11D showed elevated alkalinity (as CaCO_3), specific conductance, and pH, and AMB 10A showed elevated TDS, suggesting that water from these wells may be affected by well grout. In addition, well AMB 4A had elevated pH.

Miscellaneous Chemical Basin

The Miscellaneous Chemical Basin (731-5A) is west of Road D near the A-Area Metals Burning Pit (Figure 8-23). The basin, in operation by 1956, was closed and graded in 1974. There are no records of the materials disposed of at this location. However, soil gas investigations revealed volatile organics in the near-surface soils at the basin. This basin is currently inactive and is part of the RFI/RI program.

The basin was monitored by the nine wells of the MCB series in 1991. Wells MCB 8D and 9D provided water-level data only and were not sampled. Wells MCB 5C, 6C, and 7C monitor groundwater in the Congaree-Four Mile zone. The remainder of the wells in this series are screened in the upper saturated zone. The horizontal flow within the upper saturated zone appears to be to the north-northeast toward Tims Branch. Relative to the basin, wells MCB 2 and 5 appear to be upgradient, well MCB 4 appears to be upgradient to sidegradient, and well MCB 6 appears to be downgradient to sidegradient. Horizontal flow in the Congaree-Four Mile zone is to the south toward Upper Three Runs Creek. A downward vertical gradient exists between the upper saturated zone and the Congaree-Four Mile zone. This condition implies the potential for downward migration of groundwater from the surface into the Congaree-Four Mile zone.

Analytical results for the MCB wells in 1991 are similar to those of recent years. Congaree-Four Mile zone well MCB 5C had concentrations above DWS for lead, nonvolatile beta, total radium, and for a single analysis of tritium (Table 8-38). Total radium was also detected above the DWS in single analyses for wells MCB 6C and 7C. Concentrations of chlorinated volatile organics above DWS were reported for several upgradient wells and one downgradient well monitoring the upper saturated zone and for two wells screened in the Congaree-Four Mile zone. Elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS in wells MCB 5C and 7C

suggest that water from these wells may be affected by leaching of well grout.

Motor Shop Oil Basin

The 716-A Motor Shop Oil Basin (904-101G) is at the south edge of A Area (Figure 8-24), near the 716-A Motor Shop and the NPDES Outfall A-14, a known source of volatile organics. This unlined basin was placed in service in 1977 to receive liquid effluent from the Motor Shop, which included trace quantities of engine oil, grease, kerosene, ethylene glycol, and soap. All waste passed through an oil skimmer prior to discharge into the basin. In August 1983, all discharges to the basin were terminated. This basin is currently inactive but collects rainwater during periods of heavy precipitation. The basin is part of the RFI/RI program.

The basin was monitored by the three water-table wells of the AOB series in 1991. Horizontal groundwater flow beneath this basin is to the southwest toward the Savannah River Swamp. Relative to the basin, wells AOB 1 and 2 are downgradient, and well AOB 3 is upgradient to sidegradient.

In well AOB 3, one analysis of total radium activity slightly exceeded the DWS (Table 8-39). As in the past, well AOB 1 had concentrations of chlorinated volatile organics above DWS.

Plume Definition Wells

Besides the groundwater monitoring conducted at specific locations in A and M areas, groundwater is also monitored for volatile organics by numerous plume definition wells. The first plume definition wells were installed in 1981, after discovery of the contamination in June 1981. Presently, approximately 280 plume definition wells are located within a 5-square-mile area.

Progress has been made in assessing the extent of the contamination, and a groundwater remediation program is under way. In February 1983, a 20-gal/min air stripper began operation, and in January 1984 two recovery wells were installed along with a 50-gal/min air stripper. A full-scale recovery system consisting of 11 recovery wells and a 400 gal/min air stripper replaced the previous air strippers in April 1985. In January 1990, Westinghouse Savannah River Company petitioned SCDHEC to allow an increase in flow to the stripper. This request was granted by SCDHEC in March 1990. The stripper has operated at between 450–500 gal/min since April 1990. Through December 1991, 260,000 lb of volatile organics have

been removed from over 1.3 billion gal of groundwater.

In 1991, the extent of the contaminant plume beneath A and M areas was monitored by the following plume definition wells: ABW 1; AC 1A, 1B, 2A, 2B, 3A, and 3B; well clusters ASB 8 and 9; and approximately 250 MSB wells that are not POC wells (Figures 8-23 and 8-24). Wells MSB 11E, 12D, 13C, 14C, 23, 25, 26, 34C, 35D, 38D, 40C, 40D, 41D, and 55D went dry during sampling or provided field data only. Wells MSB 17C, 42D, 45C, 46B, 46C, and 83A either were dry or could not be sampled.

The three major water-bearing zones that are monitored beneath and in the vicinity of M Area are the upper saturated zone, the Congaree-Four Mile zone, and the Cretaceous zone. In addition, some wells are screened in sandy beds within the regional Paleocene aquitard in order to better understand groundwater flow between the Congaree-Four Mile and Cretaceous zones. A downward vertical gradient exists across all zones. Horizontal flow directions within the upper saturated zone are locally variable, but are generally radial, toward Tims Branch from the eastern portions of the area, and to the south and southwest respectively from the southern and western portions of the area. Low horizontal gradients in the central and western portions of the area indicate that most groundwater movement in this zone is downward into the Congaree-Four Mile zone. Exact flow directions in the upper saturated zone in the region immediately north of A Area are not clear. Horizontal flow in deeper zones is generally to the south and southwest toward the Savannah River and its swamp and tributaries.

Groundwater flow below the upper saturated zone is predominantly horizontal under much of the area. The clays of the regional Paleocene aquitard support hydraulic head under much of the monitored region, restricting downward groundwater flow from the Congaree-Four Mile zone into the Cretaceous zone. However, studies of vertical and horizontal gradients and contaminant transport in the vicinity of well cluster ASB 8 indicate downward flow from the water table into the Cretaceous zone, which is an exception to this trend in the region beneath the SRL Seepage Basins.

As in the past, the groundwater plume beneath A and M areas is characterized by chlorinated solvent concentrations at or above DWS (primarily trichloroethylene, with lesser amounts of tetrachloroethylene and other chlorinated solvents; Table 8-40). The

plume definition well network extends from the region north of SRL, between Road 1 and the SRS boundary, south to wells near the Miscellaneous Chemical Basin and the Metals Burning Pit, and from Tims Branch in the east to the west toward the Silverton Road Waste Site. The known extent of the plume encompasses approximately three square miles. In 1991, as in 1990, chlorinated solvents were reported above DWS in wells MSB 48B, 48C, and 85C. These wells are in the vicinity of known sources of volatile organic solvents. These well clusters are located approximately 2,000 feet from the nearest SRS boundary.

The highest concentrations of chlorinated solvents detected were found in the vicinity of known point sources in A and M areas, in the upper saturated zone, and in the Congaree-Four Mile zone. Chlorinated solvent concentrations above DWS were detected in many upper saturated zone and Congaree-Four Mile zone wells. Fewer wells monitor groundwater in the locally sandy beds of the regional Paleocene aquitard and in the Cretaceous zone than in upper zones; however, solvent concentrations above DWS in these two lower units are not as widespread as in the two upper zones. Solvent concentrations exceeding DWS in the Cretaceous zone appear to be restricted to the region directly beneath and downgradient of the SRL Seepage Basins.

In addition to chlorinated solvents, several metals and radionuclides exceeded DWS in plume definition wells. Total radium and nitrate exceeded DWS in certain wells near the M-Area HWMF, and tritium activity exceeded the DWS in five wells north of the SRL Seepage Basins.

Figure 8-25 illustrates the general extent of the trichloroethylene plume in groundwater in the vicinity of A and M areas. The distribution of trichloroethylene in groundwater is generally linked to proximity to point sources and hydraulic gradients. Low horizontal gradients in the upper saturated zone and downward vertical gradients from the water table to the Cretaceous zone have resulted in the downward transport of trichloroethylene into lower zones. Horizontal flow in the Congaree-Four Mile zone to the south and southwest has resulted in the transport of trichloroethylene into regions in this zone downgradient of surface point sources.

Savannah River Laboratory Seepage Basins

The SRL Seepage Basins (904-53G1, 904-53G2, 904-54G, and 904-55G) are east of Road A-1 across from SRL (Figure 8-24). These four basins,

constructed between 1954 and 1960, received low-level radioactive wastewater through underground drains from laboratories in Buildings 735-A and 773-A.

Basins 1 (904-53G1) and 2 (904-53G2) were placed in operation in 1954. Basins 3 (904-54G) and 4 (904-55G) were added in 1958 and 1960, respectively, to provide additional holding capacity. Wastewater flowed sequentially from Basin 1 to Basin 4 (west to east) in cascade via overflow channels. Basin 4 has no overflow or outlet. When the basins were in operation, only wastewater with radioactivity less than 100 dpm/mL alpha and/or 50 dpm/mL beta-gamma was discharged to the basins. An exception to this practice was made in 1971 when 0.68 Ci of curium from a leaking separator pit in Building 776-A was disposed of in the basins. Approximately 34 million gal of wastewater were discharged to the basins during their operating life. The basins were taken out of service in October 1982. A waste-site assessment report and a groundwater quality assessment/corrective action feasibility plan have been submitted to SCDHEC for review. These basins are part of the RFI/RI program.

The basins were monitored by 13 wells of the ASB series in 1991. Horizontal groundwater flow beneath the basins is to the west. Relative to the basins, the six water-table wells are characterized as follows: wells ASB 2A and 3A are upgradient; well ASB 5A is downgradient to sidegradient; well ASB 6A is downgradient; wells ASB 1A and 4 are sidegradient. Wells ASB 2C, 3C, 6C, 7, and 10C monitor the lower portion of the upper saturated zone and the upper portion of the Congaree-Four Mile zone. Well ASB 6AA monitors groundwater quality in sandy beds within the Paleocene aquitard. Well ASB 6TA monitors the Cretaceous zone. Downward vertical gradients between the water table and the Cretaceous zone indicate the potential for downward groundwater flow from the upper saturated zone into the Cretaceous zone below this site.

Activities above DWS for tritium, total radium, Am-241, Ra-226, Ra-228, U-235, and U-238 (Table 8-41) were detected in several upgradient and downgradient wells monitoring the upper saturated zone and in numerous wells monitoring lower zones. Several of these radionuclides were not reported above the DWS before 1991. Sampling for I-131 was performed for the first time in 1991, with activity above the DWS detected in well ASB 3C. I-131 has a half-life of eight days, which makes this result from a groundwater sample questionable. As in the past,

concentrations of chlorinated volatile organics above DWS were reported for sidegradient wells and one downgradient well of the upper saturated zone and for several wells of lower zones. Concentrations of chromium exceeding DWS were reported in the new well ASB 6TA. Continued elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS in wells ASB 3C, 6AA and 6TA suggest that water from these wells may be affected by leaching of well grout.

Silverton Road Waste Site

The Silverton Road Waste Site (731-3A), southwest of Road C-1.1 (Figure 8-23), was used for disposal of metal shavings, construction debris, tires, drums, tanks, and miscellaneous items. The startup date is unknown, and no records of waste disposal activities were kept. Operations at this location ceased in 1974, and the waste material is presently covered with soil and vegetation. This site is part of the RFI/RI program.

In 1991, groundwater beneath this site was monitored by the 30 wells of the SRW series. Wells SRW 1, 2, 4, 5, 6, 7, 8, 9, 10, 11, 12C, 13C, 15C, and 16C monitored the water table; the remaining wells monitored the upper and lower portions of the Congaree-Four Mile zone. Vertical hydraulic gradients at this site are very low; the predominant direction of flow is probably horizontal. Wells SRW 10 and 14C were dry every time they were visited during the year. Horizontal flow in all the monitored zones is generally to the southwest toward the Savannah River Swamp. Relative to the waste site, the wells are characterized as follows: wells SRW 1, 2, and 3A are upgradient; wells SRW 4, 5, 6, 7, and 8 are downgradient; well SRW 15 and well cluster SRW 14 are sidegradient; well cluster SRW 16 is upgradient to sidegradient; well SRW 11 and well clusters SRW 9, 12, and 13 are downgradient to sidegradient.

Unlike recent years, no radioactive constituents were reported above DWS during 1991. As in the past, several chlorinated volatile organics were detected above DWS (Table 8-42) in downgradient wells monitoring the upper saturated zone and in one upgradient and two sidegradient wells monitoring the Congaree-Four Mile zone. Lead concentrations exceeded DWS in 10 SRW wells, most of which are downgradient.

Reactor Areas

C Area, located near the central part of SRS (Figure 8-22), contains C Reactor, which was shut down for repairs in 1985. Surface elevations across the area

range from approximately 250 to 290 ft msl. Surface drainage is predominantly to the west toward a tributary of Four Mile Creek. The nearest SRS boundary is approximately 5.5 miles to the west. Several incised tributaries and streams exist between C Area and the SRS boundary and are regions of groundwater discharge.

In 1991, groundwater was monitored at the following locations in C Area:

C-Area Burning/Rubble Pit

The C-Area Burning/Rubble Pit (131-C) is approximately 1,000 ft west of C Area (Figure 8-26) on a gentle, westward slope. See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pit was monitored by the four wells of the CRP series in 1991. Horizontal flow at the water table is toward Four Mile Creek to the west. Well CRP 1 is upgradient, wells CRP 2 and 4 are sidegradient, and well CRP 3 is downgradient, relative to the pit.

As in past years, tritium was detected above the DWS in wells CRP 1 and 2 (Table 8-43). Trichloroethylene (up to 21.0 mg/L) and tetrachloroethylene (up to 0.034 mg/L) were detected above DWS in all of the CRP wells in 1991. Concentrations of chloroethene (vinyl chloride) and 1,1-dichloroethylene above DWS were reported in downgradient well CRP 3 for the first time. Concentrations above DWS for chromium and lead were also found in well CRP 3. Elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS suggest possible leaching of well grout in well CRP 3. Similar results were reported in previous years.

C-Area Coal Pile Runoff Containment Basin

The C-Area Coal Pile Runoff Containment Basin (189-C) is southeast of C Area (Figure 8-26), approximately 650 ft southeast of the former location of the C-Area coal pile. See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins.

This basin is monitored by the four water-table wells of the CCB series. Horizontal flow at the water table beneath this basin is to the west toward Four Mile Creek. Relative to the basin, wells CCB 1 and 2 are downgradient, and wells CCB 3 and 4 are upgradient.

Lead concentrations slightly exceeding the DWS were reported for the first time in well CCB 3, with a maximum level of 0.016 mg/L. As in the past, no other

radioactive or chemical constituents were detected above DWS in 1991.

C-Area Disassembly Basin

The C-Area Disassembly Basin is located in the C-Area reactor building (105-C) (Figure 8-26). See the Waste Sites Common to Several Areas section for a discussion of SRS disassembly basins.

This basin was monitored by the two wells of the CDB series during 1991. There was insufficient information to precisely determine groundwater gradients at this location. However, horizontal flow at the water table appears to be generally southwestward, and both wells are probably downgradient of the basin.

As in recent years, both CDB wells showed tritium activity exceeding the DWS (Table 8-44). Lead in well CDB 1 exceeded the DWS, with similar results to those of years past. Specific conductance was slightly elevated in well CDB 2 for the first time.

C-Area Reactor Seepage Basins

The three C-Area Reactor Seepage Basins (904-66G, 904-67G, and 904-68G), located about 650 ft west of the reactor building (Figure 8-26), are currently active and periodically receive purge water when the C-Area reactor is operating. The basins are connected in series, with water entering Basin 1, then moving to Basins 2 and 3. See the Waste Sites Common to Several Areas section for a discussion of SRS reactor seepage basins.

Groundwater beneath the basins was monitored by the six water-table wells of the CSB series in 1991. Horizontal flow in the water table is generally southwestward toward Four Mile Creek. Relative to the basins, well CSB 1A is upgradient, well CSB 2A is sidegradient, wells CSB 4A and 5A are downgradient, and wells CSB 3A and 6A are sidegradient to downgradient.

Tritium activity was above the DWS in most of the wells (Table 8-45) in 1991, as in recent years. Concentrations slightly above DWS for chlorinated volatile organics were detected in downgradient and sidegradient wells. Tritium activity and concentrations of chlorinated volatile organics have decreased in the last few years. Well CSB 1A had concentrations above DWS for lead and 1,2-dichloroethane. Well CSB 2A showed levels of copper and lead above DWS. Wells CSB 1A and 5A had elevated pH. Well CSB 1A also showed elevated alkalinity (as CaCO_3) and specific conductance, which may indicate leaching of well grout. Well CSB 6A had elevated specific conductance.

K Area is located in the south-central part of SRS (Figure 8-22). This area contains K Reactor, which was shut down in 1988 for maintenance and safety upgrades. Preparations for reactor restart were under way in 1991. The ground surface elevation near the central part of K Area is approximately 280 ft msl and slopes gently to the west toward Indian Grave Branch and to the east toward Pen Branch. The nearest SRS boundary is approximately 5 miles to the west.

The dissection of Pen Branch and Indian Grave Branch isolates the groundwater in this portion of the Dry Branch/Santee formations from other groundwater in these formations. Horizontal groundwater flow in the Congaree Formation is toward the Savannah River.

In 1991, groundwater was monitored at the following locations in K Area:

K-Area Acid/Caustic Basin

The K-Area Acid/Caustic Basin (904-80G) is on the east side of K Area (Figure 8-27) near a tributary of Pen Branch. See the Waste Sites Common to Several Areas section for a discussion of SRS acid/caustic basins.

The basin was monitored by the seven wells of the KAC series in 1991. Groundwater flow is to the southwest toward Indian Grave Branch. Relative to the basin, wells KAC 3 and 5 are upgradient, wells KAC 4 and 7 are sidegradient, wells KAC 1 and 6 are downgradient, and well KAC 2 is upgradient to sidegradient.

In contrast to recent years, no radiological constituents were reported above DWS during 1991. Lead in well KAC 7 and sulfate in wells KAC 1 and 7 were the only chemical constituents reported above DWS during 1991 (Table 8-46). As in the past, specific conductance was elevated in most of the KAC wells. Elevated TDS was reported in wells KAC 1, 2, and 7.

K-Area Ash Basin

The K-Area Ash Basin (188-K) is southwest of K Area (Figure 8-27), about 330 ft south of the K-Area coal pile. The basin receives ash sluice water from the powerhouse in K Area and has been in service since 1951.

The basin was monitored by the four wells of the KAB series in 1991. Groundwater flow is generally to the southwest toward Indian Grave Branch. Relative to the basin, wells KAB 1 and 2 are upgradient, well

KAB 3 is sidegradient, and well KAB 4 is downgradient.

Results for radioactive and chemical analyses during 1991 were similar to recent years. Total radium activity above the DWS was reported for wells KAB 1 and 4 (Table 8-47). Elevated alkalinity (as CaCO_3) and TDS were reported in well KAB 4, and specific conductance was elevated in wells KAB 1, 3, and 4.

K-Area Burning/Rubble Pit

The K-Area Burning/Rubble Pit (131-K) is approximately 900 ft northeast of K Area (Figure 8-27). See the Waste Sites Common to Several Areas section for a discussion of the SRS burning/rubble pits.

The pit was monitored by the four wells of the KRP series in 1991. Horizontal flow varied between southward and southwestward directions during the year, generally toward Indian Grave Branch. Well KRP 2 is upgradient relative to the pit, wells KRP 1 and 3 are sidegradient, and well KRP 4 is downgradient.

No radioactive analyses were reported above DWS during 1991. Trichloroethylene exceeded the DWS in well KRP 4 (Table 8-48). Tetrachloroethylene exceeded the DWS in well KRP 4 and in a single analysis in well KRP 1. Lead was detected above the DWS in well KRP 2. These results are similar to those reported in recent years.

K-Area Coal Pile Runoff Containment Basin

The K-Area Coal Pile Runoff Containment Basin (189-K) is west of K Area (Figure 8-27), between the K-Area Ash Basin and Reactor Seepage Basin. See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins.

The basin was monitored by the four water-table wells of the KCB series in 1991. Groundwater flow is generally to the southwest toward Indian Grave Branch. Wells KCB 1 and 2 are upgradient relative to the basin, and wells KCB 3 and 4 are downgradient.

Analytical results during 1991 for radiological constituents and indicator parameters were similar to recent years. Tritium activity was slightly above the DWS in both upgradient wells (Table 8-49). Total radium activity exceeding the DWS was reported in wells KCB 2 and 3. Well KCB 3 showed gross alpha activity above the DWS. Elevated alkalinity (as CaCO_3) and specific conductance were reported for well KCB 4. Specific conductance was also elevated

in wells KCB 1 and 3. Well KCB 3 had elevated TDS and low pH.

K-Area Diesel Tank Spill

The K-Area Diesel Tank Spill is monitored by well KDT 1D, which is located in the center of K Area north of the K-Area Disassembly Basin (Figure 8-27). This well was installed after a valve in a buried diesel supply line leaked. Most of the diesel-contaminated soil was removed from the area, except where continued excavation would have jeopardized the structural integrity of an underground storage tank. Because some of the diesel-contaminated soil was left in place, SCDHEC required the installation of a monitoring well.

Horizontal groundwater flow beneath this location is to the southwest. Well KDT 1D appears to be downgradient of the spill site.

Like last year, when the spill site was first sampled, tritium activity remained above the DWS (up to $7.8\text{E-}04$ $\mu\text{Ci/mL}$) during 1991. No other radiological or chemical constituents were detected above DWS.

K-Area Disassembly Basin

The K-Area Disassembly Basin is located in the K-Area reactor building (105-K; Figure 8-27). See the Waste Sites Common to Several Areas section for a discussion of SRS disassembly basins.

Wells KDB 1, 2, and 3 monitored the basin in 1991. Groundwater flow in the upper saturated zone is generally to the southwest. Wells KDB 1 and 3 are sidegradient, and well KDB 2 is downgradient, relative to the basin.

Analytical results for 1991 were similar to recent years. Tritium activity above DWS was detected in all wells at every sampling event during 1991 (Table 8-50). Total radium activity exceeded the DWS in wells KDB 1 and 3. Concentrations of lead, tetrachloroethylene, and trichloroethylene exceeded DWS in two wells each. Specific conductance was elevated in wells KDB 1 and 3. Well KDB 3 also had elevated alkalinity (as CaCO_3) and TDS.

K-Area Reactor Seepage Basin

The K-Area Reactor Seepage Basin (904-65G), in service from 1959 through 1960, is west of K Area (Figure 8-27). See the Waste Sites Common to Several Areas section for a discussion of SRS reactor seepage basins.

The basin was monitored by the four wells of the KSB series and by well K 301P in 1991. Horizontal gradients are low beneath this location, making horizontal flow directions difficult to determine. However, horizontal flow in the upper saturated zone is generally to the southwest toward Indian Grave Branch. Wells KSB 1 and 4A are generally upgradient of the basin, wells KSB 2 and 3 are generally downgradient of the basin, and well K 301P appears to be sidegradient.

As in the past, tritium activity was detected above the DWS in all of the KSB wells and in well K 301P at every sampling event (Table 8-51), although activity decreases from first to fourth quarters during 1991. Nonvolatile beta activity was detected above the DWS in a single analysis in well KSB 2. Trichloroethylene concentrations remained elevated in wells KSB 1 and 4A. No other chemical constituents were detected above DWS during the year. Well K 301P had elevated alkalinity (as CaCO_3) and specific conductance.

K-Area Retention Basin

The K-Area Retention Basin (904-88G) is north of K Area, about 330 ft from the perimeter fence (Figure 8-27). The basin has been used since 1965 for disposal of purge water from the K-Area Disassembly Basin.

During 1990, the KRB wells monitoring groundwater in the vicinity of the K-Area Retention Basin were abandoned because construction for the new K-Area Retention Basin liner left the downgradient wells on the slope of the new basin wall. However, during fourth quarter 1991, four new wells of the KRB series were installed to continue groundwater monitoring of the retention basin. The wells, all of which are screened in the water table, were sampled for the first time during fourth quarter 1991. Horizontal groundwater flow beneath the retention basin appears to be to the west-northwest toward Indian Grave Branch. Relative to the basin, well KRB 16D appears to be upgradient, wells KRB 17D and 18D appear to be sidegradient, and well KRB 19D appears to be downgradient to sidegradient.

Tritium activity exceeded the DWS (up to $7.9\text{E-}02$ $\mu\text{Ci/mL}$) in all wells during 1991. No other radioactive or chemical constituents were detected above DWS during the year. Comparison of 1991 analytical results to those of recent years is not applicable because all of the present KRB wells were installed in 1991 and are screened slightly below the wells they replaced.

K-Area Sludge Land Application Site

The K-Area Sludge Land Application Site (761-4G; formerly the K-Area Borrow Pit) covers 17 acres southeast of K Area and is located on the west bank of Pen Branch (Figure 8-27) above its confluence with Indian Grave Branch. In 1989, this location was declared part of the RFI/RI program because of the presence of chlordane in the lagoon sludge applied to the site. See the Sewage Sludge Application Sites discussion under the General Areas section.

In 1991, this location was monitored by the three water-table wells of the KSS series. Groundwater flow in the upper saturated zone is to the south toward Pen Branch. Well KSS 1D is upgradient of the site, well KSS 2D is within the sludge application area, and well KSS 3D is downgradient of the sludge application area.

Lead exceeded the DWS (up to 0.033 mg/L) in well KSS 1D in 1991. No other radioactive or chemical constituent exceeded DWS during the year.

L Area is in the south-central part of SRS (Figure 8-22). This area contains L Reactor, which was shut down in 1988 for maintenance and safety upgrades. Surface elevations across L Area range from approximately 230 to 260 ft msl and decrease toward Steel Creek, approximately 2,500 ft to the southeast. Several small tributaries of Steel Creek receive surface drainage from L Area. The nearest SRS boundary is approximately 5.5 miles to the southeast.

The upper saturated zone beneath L-Area discharges to Steel Creek and Pen Branch. The incision of the Aiken Plateau by Pen Branch to the northwest and by Steel Creek to the southeast isolates groundwater in this portion of the upper saturated zone from groundwater of this zone in other areas.

In 1991, groundwater was monitored at the following locations in L Area:

L-Area Acid/Caustic Basin

The L-Area Acid/Caustic Basin (904-79G) is south of L Area and to the east of the L-Area Oil and Chemical Basin (904-83G) (Figure 8-28) on a slope leading to Steel Creek. See the Waste Sites Common to Several Areas section for a discussion of SRS acid/caustic basins.

During 1991, groundwater beneath the L-Area Acid/Caustic Basin was monitored by the four water-table wells of the LAC series. Horizontal gradients at this site are low, and the water-table

surface is undulatory, making horizontal flow directions difficult to determine. At this site, horizontal flow in the upper saturated zone is generally to the southwest toward L Lake. Wells LAC 1, 2, and 4 are probably sidegradient to upgradient, and well LAC 3 is probably sidegradient to downgradient.

No radioactive constituents were detected above DWS during 1991. Concentrations of lead and trichloroethylene exceeding DWS were reported for wells LAC 1 and 2 (Table 8-52). Tetrachloroethylene above the DWS was detected in well LAC 3. As in the past, elevated alkalinity (as CaCO_3), pH, and specific conductance in well LAC 3 suggest that water from this well may be affected by well grout. Specific conductance was also elevated in well LAC 4. These results are similar to those reported in previous years.

L-Area Burning/Rubble Pit

The L-Area Burning/Rubble Pit (131-L) is approximately 1,200 ft northwest of L Area, near the intersection of Road 7 and Road 6-4.2 (Figure 8-28). See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

Groundwater beneath the pit was monitored by the four water-table wells of the LRP series. Horizontal groundwater flow was generally to the west toward Pen Branch during 1991. Relative to the pit, well LRP 2 is upgradient, LRP 1 is sidegradient, and wells LRP 3 and 4 are downgradient. An anomalously low water elevation observation was recorded for well LRP 2 during the year's first quarter; this was probably an erroneous reading and was not considered in horizontal flow interpretation.

As in the past, no radioactive constituents exceeded DWS during 1991. Lead concentrations continued to exceed the DWS (up to 0.14 mg/L) in wells LRP 2 and 3. No other chemical constituents exceeded DWS during the year.

L-Area Disassembly Basin

The L-Area Disassembly Basin is located in the L-Area reactor building (105-L) (Figure 8-28). See the Waste Sites Common to Several Areas section for a discussion of SRS disassembly basins.

Groundwater beneath the basin was monitored during 1991 by the two water-table wells of the LDB series. The two wells are located near an apparent water-table divide between Pen Branch and L Lake. Information was insufficient to determine the precise horizontal flow directions of groundwater beneath the basin.

However, there appears to be a component of flow in the water table to the west toward Pen Branch, making well LDB 2 sidegradient to upgradient, and well LDB 1 sidegradient to downgradient, relative to the basin.

No radioactive constituents were reported above DWS in 1991. Lead was detected above DWS in both LDB wells (Table 8-53). Tetrachloroethylene concentrations in well LDB 1 were at the DWS. These results are similar to those of recent years.

L-Area Oil and Chemical Basin

The L-Area Oil and Chemical Basin (904-83G) is southeast of L Area, between the L-Area Reactor Seepage Basin (904-64G) and Acid/Caustic Basin (904-79G) (Figure 8-22). From 1961 to 1979, the basin received small quantities of radioactive oil and chemical waste from throughout SRS that were not appropriate for discharge to effluent streams, regular seepage basins, or the 200-Areas waste management systems. The waste came primarily from Building 717-G and was delivered to the basin via a pipeline. The basin has been inactive since 1979. Because the basin is a radiologically controlled area, vegetation inside and outside the basin perimeter is removed periodically. The basin is part of the RFI/RI program.

During 1991, groundwater beneath this basin was monitored by the four water-table wells of the LCO series. Horizontal gradients in the vicinity of the basin are low, and the water-table surface is undulatory, making determination of horizontal groundwater flow directions difficult. Groundwater flow in the upper saturated zone beneath the basin appears to range between southeastward and southward toward L Lake. Wells LCO 2 and 3 are generally upgradient, and wells LCO 1 and 4 are generally downgradient to sidegradient, relative to the basin.

Analytical results for radiological and chemical constituents were similar to those reported in recent years. Tritium activity in wells LCO 1 and 4, a single analysis of total radium activity in well LCO 4, and nonvolatile beta activity in well LCO 1 were above DWS during 1991 (Table 8-54). Lead concentrations exceeded the DWS in well LCO 2. Sulfate observations for well LCO 4 remained elevated, although only one analysis exceeded the DWS. Chlorinated volatile organics above DWS and elevated specific conductance and TDS were detected in wells LCO 3 and 4. Well LCO 3 also had elevated alkalinity (as CaCO_3) and pH, suggesting that the water from this well may be affected by well grout.

L-Area Reactor Seepage Basin

The L-Area Reactor Seepage Basin (904-64G) is southeast of L Area adjacent to the L-Area Oil and Chemical Basin (Figure 8-28). The L-Area Reactor Seepage Basin was used from 1958 until 1969 and from 1985 to the present. See the Waste Sites Common to Several Areas section for a discussion of SRS reactor seepage basins.

The basin was monitored by the four water-table wells of the LSB series during 1991. Horizontal groundwater flow in the upper saturated zone directly beneath the basin is to the east-southeast. Wells LSB 3 and 4 are generally upgradient, well LSB 1 is downgradient, and well LSB 2 is downgradient to sidegradient, relative to the basin.

Single analyses of gross alpha and nonvolatile beta exceeding DWS from well LSB 4 (Table 8-55) are considered suspect because they are not supported by other analyses of these constituents during 1991 or in recent years. During 1991 as in the past, tritium activity and lead concentrations exceeded DWS in all of the LSB wells except LSB 2. No other analytes exceeded DWS during the year.

L-Area Research Wells

L Area is also monitored by three LAW series research wells, located north of L Lake and south of L Reactor, surrounding the L-Area waste sites (Figure 8-28). These wells monitor groundwater quality of the Congaree-Four Mile zone. Local water elevation measurements show a downward vertical gradient from the water table into the Congaree-Four Mile zone, indicating the potential for downward migration of groundwater into the Congaree-Four Mile zone. Because of variable flow directions in the upper saturated zone, the LAW wells appear to be sidegradient to downgradient of monitored facilities in the southern half of L Area. Horizontal flow of the Congaree-Four Mile zone is to the southwest toward the Savannah River.

No chemical or radiological constituents were detected above DWS in the LAW wells during 1991. Elevated alkalinity (as CaCO_3), specific conductance, and pH in wells LAW 2B and 3B (Table 8-56) suggest the influence of well grout.

P Area, located in the south-central part of SRS (Figure 8-22), houses P Reactor, which was shut down in 1988 for maintenance and safety improvements. Surface elevations across P Area range from approximately 310 to 330 ft msl. The nearest SRS

boundary is approximately 5 miles to the east on the opposite side of Lower Three Runs Creek.

Lower Three Runs Creek (to the east), Steel Creek (to the southwest), and Meyers Branch (to the south and east) isolate the groundwater in the upper saturated zone in P Area from other locations of groundwater in this zone. The horizontal hydraulic gradients vary across P Area and increase near a tributary to Par Pond, approximately 1,000 ft to the northeast. The horizontal gradients also increase near a tributary to Steel Creek to the southwest.

In 1991, groundwater was monitored at the following locations in P Area:

P-Area Acid/Caustic Basin

The P-Area Acid/Caustic Basin (904-78G) is east of P Area and Road F (Figure 8-29) on a slope that leads to a tributary of Par Pond. See the Waste Sites Common to Several Areas section for a discussion of SRS acid/caustic basins.

The basin was monitored by the six water-table wells of the PAC series in 1991. Horizontal groundwater flow beneath the basin is to the northeast toward an adjacent unnamed stream flowing into Par Pond. Well PAC 4 is upgradient relative to the basin, wells PAC 3, 5, and 6 are downgradient, well PAC 1 is generally upgradient to sidegradient, and well PAC 2 is generally downgradient to sidegradient.

In contrast to recent years, no radioactive constituents were reported above DWS. No chemical constituents were detected above DWS either, in keeping with the trend of recent years. Alkalinity (as CaCO_3), specific conductance, and TDS were elevated in wells PAC 5 and 6 (Table 8-57). Wells PAC 3 and 4 also showed elevated specific conductance, and well PAC 3 had elevated TDS. Values of 47,000 and 41,000 mg/L for TDS in well PAC 2 for the same sample date are considered anomalous; other analyses for TDS during 1991 considerably lower values.

P-Area Burning/Rubble Pit

The P-Area Burning/Rubble Pit (131-P) is approximately 1,200 ft west of P Area (Figure 8-29). See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pit was monitored in 1991 by the four water-table wells of the PRP series. Horizontal groundwater flow beneath the basin shifted from a west-northwestward direction toward Pen Branch in the first quarter of 1991 to a southwestward direction toward Steel Creek

in the second quarter. This minor change in flow direction could have been caused by a variation in precipitation. However, there are only four water-table wells in the vicinity, which limits the data that are available for determining flow direction at this location. Relative to the pit, well PRP 4 is upgradient, well PRP 2 appears to be sidegradient to upgradient, and PRP 1A and 3 are generally sidegradient to downgradient.

Analytical results for 1991 are similar to those of previous years. Tritium, detected above the DWS in well PRP 1A, was the only radioactive constituent to exceed DWS during 1991 (Table 8-58). Lead in concentrations exceeding the DWS was detected in wells PRP 1A and 3. Several chlorinated volatile organics exceeded DWS in well PRP 3. Trichloroethylene was also reported in concentrations exceeding the DWS in well PRP 1A.

P-Area Coal Pile Runoff Containment Basin

The P-Area Coal Pile Runoff Containment Basin (189-P) is southeast of the coal pile and south of P Area (Figure 8-29). See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins.

The basin was monitored by the four water-table wells of the PCB series in 1991. Horizontal groundwater flow appears to vary throughout the year between northeastward and southeastward directions. The water-table surface beneath the basin is undulatory, making relative gradient characterizations of each well difficult to assign. Generally, well PCB 3A is upgradient, well PCB 2A is downgradient, and wells PCB 1A and 4A vary between downgradient and upgradient, relative to the basin.

Total radium and a single analysis of gross alpha exceeded DWS in well PCB 4A (Table 8-59). Sulfate concentrations above the DWS, elevated specific conductance and TDS, and low pH were detected in wells PCB 1A, 3A, and 4A. A value of 23,400 mg/L reported for sulfate in well PCB 4A is inconsistent with other analyses for the same well and analyses corresponding to the same sample date. Cadmium for well PCB 3A was above the DWS. Nickel exceeded the DWS in well PCB 4A. Wells PCB 3A and 4A also had concentrations of lead exceeding the DWS. Results for 1991 are similar to those of past years.

P-Area Disassembly Basin

The P-Area Disassembly Basin is located in the P-Area reactor building (105-P) (Figure 8-29). See the Waste Sites Common to Several Areas section for a discussion of SRS disassembly basins.

In 1991, the two wells of the PDB series monitored the groundwater beneath the basin. There was insufficient information to determine the direction of horizontal groundwater flow. Both wells are screened below the water-table surface, preventing detailed correlation of these water elevations with adjacent water-table elevations. However, correlation with trends throughout P Area suggests a northwestward flow. Therefore, relative to the basin, well PDB 3 is probably upgradient to sidegradient, and well PDB 2 is probably downgradient to sidegradient.

Tritium activity and lead concentrations in both PDB wells exceeded DWS during 1991 (Table 8-60). Potassium-40, sampled for the first time this year, was detected above the DWS in well PDB 3. Specific conductance in well PDB 2 was slightly elevated.

P-Area Reactor Seepage Basins

The P-Area Reactor Seepage Basins (904-61G, 904-62G, and 904-63G) are southwest of the reactor building (Figure 8-29). The basins are connected in series, with water entering Basin 1, then flowing to Basins 2 and 3. See the Waste Sites Common to Several Areas section for a discussion of SRS reactor seepage basins.

In 1991, the seven water-table wells of the PSB series monitored the three seepage basins. Horizontal groundwater flow is to the west-northwest toward Pen Branch and the headwaters of Steel Creek. There are no wells assigned to monitor the P-Area Retention Basin, although it should be noted that all of the PSB wells are upgradient to sidegradient of this unit. Well PSB 5A is upgradient of Basin 3. Well PSB 6A is upgradient of Basin 2 and downgradient of Basin 1. Well PSB 3A is downgradient of all three seepage basins. Well PSB 2A is downgradient of Basins 1 and 2. Well PSB 1A is downgradient of Basin 1. Well PSB 7A is upgradient to sidegradient of Basin 1. Well PSB 4A is downgradient to sidegradient of Basin 3.

Analytical results for 1991 are similar to those of recent years. Tritium activity exceeded the DWS in all of the PSB wells during 1991 (Table 8-61). Sr-89, 90, which was not requested for analysis in previous years, exceeded the DWS in well PSB 2A. Nitrate concentrations exceeding the DWS and elevated specific conductance were also reported for well PSB 2A. Lead was detected above the DWS in wells PSB 3A, 4A, and 5A, and to a lesser extent in wells PSB 6A and 7A.

R Area, located in the east-central part of SRS (Figure 8-22), houses R Reactor, which was permanently shut down in 1964. This area is on a topographic divide where surface elevations range from approximately 280 to 330 ft msl. Surface drainage is to the northwest and northeast toward Mill Creek and Pond A and to the southeast and southwest toward tributaries of Pond 4 and Pond 2. The nearest SRS boundary is approximately 4.8 miles to the east.

Incised tributaries, streams, and Par Pond separate R Area from the SRS site boundary. R Area is near a groundwater divide between Mill Creek and Par Pond. The groundwater just north of R Area naturally discharges to Mill Creek, approximately 1,000 ft to the northwest, and to the R-Area Canal of Pond A to the northeast. The groundwater from the southern part of R Area naturally discharges to a tributary of Pond 4, approximately 1,800 ft south of R Area.

In 1991, groundwater was monitored at the following locations in R Area:

R-Area Acid/Caustic Basin

The R-Area Acid/Caustic Basin (904-77G) is south of R Area, just south of Road G (Figure 8-30). See the Waste Sites Common to Several Areas section for a discussion of SRS acid/caustic basins.

The basin was monitored by the four wells of the RAC series in 1991. Horizontal groundwater flow beneath the basin is to the southeast. Well RAC 1 is upgradient relative to the basin, well RAC 3 is sidegradient, and wells RAC 2 and 4 are downgradient to sidegradient. Well RAC 4 is screened about 5 ft below the water-table surface.

Unlike analyses of recent years, no radioactive constituent was above DWS in 1991. Lead continued to exceed the DWS (up to 0.033 mg/L) in well RAC 2 and in a single analysis of RAC 3. No other chemical constituent exceeded DWS during the year.

R-Area Burning/Rubble Pits

The R-Area Burning/Rubble Pits (131-R and 131-1R) are approximately 900 ft southeast of R Area, southeast of Road G (Figure 8-30). See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pits were monitored by the four water-table wells of the RRP series in 1991. Horizontal groundwater flow direction varied throughout the year between south and southwest toward Pond 5 and Pond 2, respectively, making relative gradient characteriza-

tions of each well difficult to assign. Relative to both pits, well RRP 2 is probably upgradient, well RRP 3 is probably sidegradient, well RRP 1 is probably upgradient to sidegradient, and well RRP 4 is probably downgradient to sidegradient.

As in the past, no radioactive constituent was detected above DWS in 1991. Lead concentrations exceeded the DWS in well RRP 1 (Table 8-62) at levels similar to recent years. Chloroethene (vinyl chloride) was reported above the DWS for well RRP 2 for the first time.

R-Area Disassembly Basin

The R-Area Disassembly Basin is located in the west end of the R-Area reactor building (105-R), which is in the center of R Area (Figure 8-30). See the Waste Sites Common to Several Areas section for a discussion of SRS disassembly basins.

The basin was monitored by the three water-table wells of the RDB series in 1991. Horizontal groundwater flow is to the east. Relative to the basin, wells RDB 2D and 3D are downgradient, and well RDB 1D is upgradient to sidegradient.

Tritium activity above the DWS was detected in well RDB 2D (Table 8-63), as it was last year, the first year the RDB wells were sampled. Specific conductance remained elevated in all three wells, and alkalinity (as CaCO_3) was elevated for the first time in both downgradient wells.

R-Area Reactor Seepage Basins

The six R-Area Reactor Seepage Basins (904-103G, 904-104G, and 904-57G through 904-60G) are just outside the perimeter fence northwest of R Area (Figure 8-30). The basins received purge water from the R-Area Disassembly Basin from 1957 until 1964. Overflow was sequential via overflow channels from Basin 1 to Basin 2, to Basin 3, to Basin 4. Basin 5 received water directly from the disassembly basin. Basin 6 received water pumped from Basins 2, 3, and 4 and then was used for receiving water directly from the disassembly basin.

On Nov. 8, 1957, an experimental fuel element failed during a calorimeter test in the emergency section of the R-Area Disassembly Basin. Following this incident, the seepage basins received approximately 2,700 Ci of nonvolatile beta activity, including Sr-90 and Cs-137. About half of the Sr-90 and Cs-137 has decayed since the accident. Much of the released radioactivity was contained in Basin 1, which was

backfilled in December 1957. Basins 2 through 6 were placed in operation in 1957 and 1958 to assist in containing the radioactivity.

In 1960, Basins 2 through 5 were closed and backfilled. The ground surface above Basins 1 through 5 was treated with herbicide and covered with asphalt. In addition, a kaolinite cap and dike (down to a clay layer) was constructed over and around Basin 1 and the northwest end of Basin 3 to minimize lateral movement of the radioactive contamination. Basin 6, which was active until 1964, was backfilled in 1977.

In 1975, a substantial increase in Sr-90 activity ($3.4\text{E-}06 \mu\text{Ci/mL}$) occurred in groundwater monitoring well RSE 13 on the southeast side of Basin 1 outside the clay dike. Investigations revealed that the contamination was migrating through a sewer line that had been abandoned after completion of R-Reactor construction. Subsequently, eight groundwater monitoring wells (RSD 4 through RSD 11) were installed downgradient of well RSE 13 on three parallel lines, approximately 50, 150, and 300 ft south of well RSE 13.

In 1991, the basins were monitored by 4 wells of the RSA series, 3 wells of the RSB series, 9 wells of the RSC series, 13 wells of the RSD series, 21 wells of the RSE series, and 3 wells of the RSF series. Well RSE 12 could not be sampled during the year. Water-table gradients vary greatly in the vicinity of the six seepage basins. Basin 1 is located near a water-table divide. Generally, beneath Basin 1 horizontal flow in the upper saturated zone appears to be in a southeastward direction. Beneath Basins 2, 3, 4, 5, and 6 horizontal flow in the upper saturated zone appears to vary between northward and northwestward directions.

Nonvolatile beta activity and to a lesser extent gross alpha activity and cadmium concentrations above DWS were reported for numerous wells (Table 8-64). These constituents are generally restricted in extent to the area south and southeast of Basin 1 and the area surrounding the confluence of Basins 3 and 4. Several wells had elevated specific conductance. As in the past, a single analysis of total radium activity above the DWS was reported for well RSA 10, and tritium was detected above the DWS in two wells located northwest of Basin 3. Specific conductance and pH remained elevated in well RSF 1, suggesting the possibility of well grout in the groundwater sample.

Separations and Waste Management Areas

The separations and waste management areas (E, F, H, S, Y, and Z areas) are located in the central part of

SRS, six miles west of the nearest SRS boundary (Figures 8-22 and 8-31). The Radioactive Waste Burial Grounds lie between F and H areas. S Area is located just north of H Area, and Z Area is north of S Area. Y Area is located within the boundaries of Z Area. Reactor-produced materials are processed in the chemical separations plants located in F and H areas. Uranium, Pu-238, and Pu-239 are separated from each other and from fission products. These areas also have facilities for eventual purifying and packaging of tritium and for storing fission wastes. S-, Y-, and Z-Area facilities are currently under development. S Area will solidify high-level radioactive waste, currently stored in F and H areas, into a solid, inert glass form for eventual storage in an offsite geologic repository. Y Area will process mixed-waste sludge from H and M areas in grout and store it in vaults that will be buried onsite. Z Area will process and dispose of low-level radioactive salt supernate from F and H areas.

Surface elevations across the separations and waste management areas range from approximately 250 to 320 ft msl. Surface drainage is to Four Mile Creek to the south and Upper Three Runs Creek and its tributaries, McQueen Branch and Crouch Branch, to the north and west.

F Area, H Area, and the Radioactive Waste Burial Grounds are located on the groundwater divide between Four Mile Creek and Upper Three Runs Creek. Near-surface groundwater in the southern portions of these areas discharges to Four Mile Creek and its tributaries 500 to 2,000 ft to the south. Near-surface groundwater in the northern portions of these areas discharges to Upper Three Runs Creek and its tributaries 1,500 to 4,000 ft to the north. S, Y, and Z areas are located north of H Area on the groundwater divide between Upper Three Runs Creek and its tributaries—McQueen Branch to the east and Crouch Branch to the west.

In 1991, groundwater was monitored at the following locations in the separations and waste management areas:

F-Area Acid/Caustic Basin

The F-Area Acid/Caustic Basin (904-74G) is east of F Area (Figure 8-32) on a slope that leads to an unnamed tributary of Upper Three Runs Creek. See the Waste Sites Common to Several Areas section for a discussion of SRS acid/caustic basins.

The basin was monitored by the six water-table wells of the FAC series in 1991. The surface of the water table in the vicinity of the basin is undulatory, making horizontal groundwater flow directions difficult to interpret. Generally, flow appears to be to the southwest toward an unnamed tributary of Four Mile Creek. Relative to the basin, well FAC 8 appears to be upgradient, wells FAC 4 and 5 appear to be sidegradient, wells FAC 6 and 7 appear to be downgradient, and well FAC 3 appears to be upgradient to sidegradient.

Total radium activity in wells FAC 3 and 4 and gross alpha activity in well FAC 4 continued to exceed DWS in 1991 (Table 8-65). Single analyses of tetrachloroethylene and trichloroethylene were reported above DWS for wells FAC 3 and 4; these results are inconsistent with past results and other 1991 determinations for these constituents. As in the past, all of the FAC wells showed elevated specific conductance. TDS and pH also remained elevated in well FAC 3, indicating that water from this well may be affected by well grout.

F-Area Burma Road Rubble Pit

The F-Area Burma Road Rubble Pit (231-4F) is located south of the Burma Road and Road C intersection, approximately 2,800 ft southwest of the F-Area Canyon Building (Figure 8-33). This location consists of two excavated earthen pits that may contain paint cans, fluorescent light fixtures, metal, concrete, lumber, poles, and glass. Unknown quantities of refuse were deposited here from approximately 1973 through 1983. The pit is presently inactive and is in the RFI/RI program.

The pit was monitored by the five water-table wells of the BRR series in 1991. Horizontal groundwater flow beneath the pit is to the west toward Upper Three Runs Creek. Relative to the pit, well BRR 1D is upgradient and the remaining wells are downgradient.

Three downgradient wells had tritium activity above the DWS and elevated specific conductance (Table 8-66), as last year when the pit was first sampled. Single analyses of lead and total radium slightly exceeded DWS in well BRR 3D.

F-Area Burning/Rubble Pits and Rubble Pit

The F-Area Burning/Rubble Pits (231-F and 231-1F) and Rubble Pit (231-2F) are north of the intersection of Road C and the F-Area entrance road, approximately 2,300 ft west of F Area (Figure 8-32). See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pits were monitored by the four wells of the FBP series in 1991. These wells are screened below the water-table surface, making interpretation of horizontal flow directions difficult; however, flow beneath this location appears to be to the west-southwest. Relative to the pits, well FBP 4 appears to be upgradient, wells FBP 1A and 3A appear to be sidegradient, and well FBP 2A appears to be downgradient.

Analytical results for 1991 were similar to those of past years. Nonvolatile beta activity and trichloroethylene concentrations were detected slightly above DWS in well FBP 1A (Table 8-67). Well FBP 2A had concentrations above DWS for tetrachloroethylene and trichloroethylene and for a single analysis of carbon tetrachloride. Wells FBP 1A and 2A both showed elevated specific conductance.

F-Area Canyon Building and A-Line Uranium Recovery Facility

The F-Area Canyon Building (221-F) is in the center of F Area, and the A-Line Uranium Recovery Facility (221-1F) is east of the south end of the Canyon Building (Figure 8-32). At the Canyon Building, material from the reactors is dissolved using nitric acid, and the desired radionuclides are separated from fission products. At the A-Line Building, uranium oxide is produced from uranyl nitrate.

The groundwater at the F-Area Canyon Building, the A-Line Uranium Recovery Facility, and the surrounding area was monitored by 2 wells of the FAL series, 15 wells of the FCA series, and 5 wells of the NBG series. Eight of the FCA series wells monitor a perched water-bearing zone in the vicinity of the Canyon Building. Perched zone wells FCA 9B, 10B, and 16T were dry during every sampling period in 1991. Well FCA 9C could not be accessed for sampling. The Canyon Building is near the crest of a water-table divide between Upper Three Runs Creek and Four Mile Creek. The water table is undulatory and irregular beneath this area, possibly due to preferential local recharge from the overlying perched zone. Horizontal flow beneath the southern end of the Canyon Building and the A-Line Facility is locally to the south. Beneath the northern half of the Canyon Building horizontal flow is northwest and north of the facility, toward Upper Three Runs Creek. Horizontal flow beneath the Naval Fuels Building is generally to the north toward upper Three Runs Creek. All FCA wells and the two FAL wells are sidegradient to downgradient of the Canyon Building. Well FAL 1 appears to be downgradient and FAL 2 sidegradient to

downgradient of the A-Line Facility. The five NBG wells are upgradient to sidegradient of the Naval Fuels Building and downgradient to sidegradient of the Canyon Building.

Activities of gross alpha, nonvolatile beta, and total radium and concentrations of trichloroethylene and nitrate exceeded DWS in several wells surrounding the facilities (Table 8-68). In addition, activities of Sr-89, 90, U-235, K-40, and tritium and concentrations of lead, 1,2-dichloroethane, and tetrachloroethylene were reported above DWS in at least one well each. Specific conductance was elevated in numerous wells; elevated TDS and alkalinity (as CaCO_3), and low pH were detected in one or two wells each. These results are similar to those of recent years, with the exception that total radium and some of the less prevalent radionuclides reported for 1991 were absent from results exceeding DWS in recent years; also, K-40 has not previously been requested for analysis.

F-Area Coal Pile Runoff Containment Basin

The F-Area Coal Pile Runoff Containment Basin (289-F) is southeast of F Area (Figure 8-32). See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins.

The basin was monitored by the six water-table wells of the FCB series in 1991. Well FCB 7 was dry every time it was sampled during the year. Horizontal gradients at this location are low, and the water-table surface is undulatory, making interpretation of flow directions difficult. Horizontal groundwater flow is radially distributed to the west, southwest, and southeast. The predominant flow is to the south-southwest toward Four Mile Creek. Relative to the basin, wells FCB 2 and 4 appear to be downgradient to sidegradient, and wells FCB 3, 5, and 6 are downgradient.

In 1991, for the first time, gross alpha and nonvolatile beta activities were reported above DWS for one sampling event in well FCB 3 (Table 8-69). Total radium activity was above the DWS in every FCB well at least once during 1991. A single lead analysis, slightly above the DWS, was reported for well FCB 5. As in the past, specific conductance was elevated in well FCB 6.

F-Area Effluent Treatment Cooling Water Basin

The F-Area Effluent Treatment Cooling Water Basin (241-97F) is located in the southwest portion of F Area (Figures 8-32 and 8-33). The basin will receive diverted cooling water from the separations processes, which then will be sent to the F/H Effluent Treatment

Facility (ETF) if contaminated or to a permitted outfall if uncontaminated. The ETF was placed in service in 1988 to treat wastewater formerly sent to the F- and H-Area Seepage Basins.

In 1991, the basin was monitored by the four water-table wells of the FET series. Horizontal groundwater flow is to the southwest toward Four Mile Creek. Relative to the basin, well FET 1D is upgradient, and wells FET 2D, 3D, and 4D are downgradient.

A single analysis of gross alpha was reported above the DWS for well FET 2D with a maximum level of $1.8\text{E-}08 \mu\text{Ci/mL}$. No other chemical or radioactive constituents were reported above DWS in 1991.

F-Area Seepage Basins

The F-Area Seepage Basins (904-41G, 904-42G, and 904-43G) are on both sides of Road C-4, southwest of Road C (Figures 8-32 and 8-33). Beginning in 1955, the basins received wastewater from F Area containing low-level radioactivity and chemicals, including nitric acid, mercury, and sodium hydroxide. The basins operated under RCRA interim status from 1980 until they were taken out of service in the fourth quarter of 1988. The basins are inactive RCRA hazardous waste management facilities. A RCRA Part B Post-Closure Care Permit application was submitted to SCDHEC on December 3, 1990. The closure cap was certified as closed by RCRA on February 26, 1991. SCDHEC accepted the closure certification on April 26, 1991.

In 1991, groundwater beneath and in the vicinity of the F-Area Seepage Basins was monitored by 90 wells of the FSB series and five wells of the F series. FSB wells with the "A" or "B" suffix monitor the Congaree-Four Mile zone. The remainder of the FSB wells and the F-series wells monitor the upper saturated zone. Well FSB 1TA is a production well. Well FSB 87D was dry at every sampling attempt during the year. Wells FSB 94D, 95C, 95D, 96A, and 105D could not be sampled during the year for various reasons.

Horizontal groundwater flow within the upper saturated zone beneath the facility is to the south toward Four Mile Creek. Relative to the basins, the wells and well clusters monitoring the upper saturated zone are characterized as follows: well clusters FSB 76 and 99 and wells FSB 108D and 109D are upgradient; well clusters FSB 78, 79, 89, 90, 91, 93, 94, 95, 97, 104, 106, 110 and wells FSB 77, 92D,

103C, 117D, 119D, and F 14 and 16 are downgradient. The remaining wells screened in these zones are sidegradient or sidegradient to downgradient of the basins. Well FSB 76, while technically upgradient of the basins, is near a process sewer line known to have collapsed in the past; therefore, the quality of water monitored by this well is comparable to that of a downgradient well.

Water elevations in adjacent wells screened in the Cretaceous zone show an upward vertical gradient from the Cretaceous into the Congaree-Four Mile zone. As indicated in Figure 8-13, groundwater in the upper saturated zone beneath the basins may follow one of two distinct flow paths—south toward Four Mile Creek or down into the Congaree-Four Mile zone. Downward flow into the Congaree-Four Mile zone dominates southward horizontal flow with increasing distance north from Four Mile Creek. Flow in the Congaree-Four Mile zone is probably mostly horizontal toward Upper Three Runs Creek, constrained by the regional Paleocene aquitard and by an upward vertical gradient from the Cretaceous zone.

During 1991, as in the past, the contaminant plume in the vicinity of the F-Area Seepage Basins was characterized by low pH and high nitrate concentrations and by high tritium, gross alpha, nonvolatile beta, and total radium activities (Table 8-70). Specific conductance levels were generally elevated. In addition, other radionuclides, metals, chlorinated solvents, and inorganic constituents were above DWS in one or more wells each. Generally, tritium and nitrate were the most widespread contaminants; metals and transuranic radionuclides exceeding DWS were typically found in portions of the plume closer to the basins. The upper saturated zone wells nearest the basins show generally declining tritium activities and nitrate concentrations during the period from 1989 to 1991.

Wells of the FSB series monitoring the plume in the upper saturated zone define an area of approximately one-half square mile surrounding the basins, extending toward Four Mile Creek to the south, and including clusters FSB 115 and 116 south of Four Mile Creek. Contamination in the Congaree-Four Mile zone is less extensive than in the upper saturated zone. Tritium activity exceeded the DWS in 11 wells monitoring the Congaree-Four Mile zone; in addition, other radionuclides, nitrate, and antimony exceeded DWS in at least one well each. The lateral extent of contamination extends slightly farther to the north toward Upper Three Runs Creek in the Congaree-Four Mile zone (downgradient in this zone) than in the

upper saturated zone. Elevated specific conductance and TDS levels for certain wells monitoring the Congaree-Four Mile zone may result from the natural occurrence of soluble calcium carbonate minerals in the Congaree and associated formations. Elevated pH, TDS, and alkalinity (as CaCO_3) in some wells indicate that leaching of well grout may be affecting the water quality in these wells.

F-Area Sludge Land Application Site

The F-Area Sludge Land Application Site covers 8 acres southeast of F Area, south of Road E (Figures 8-32 and 8-33). Sludge from SRS's sanitary wastewater treatment plants has been disposed of at this location since 1987. See the Sewage Sludge Application Sites discussion under the General Areas section.

The site was monitored by the four water-table wells of the FSS series in 1991. Horizontal groundwater flow is to the southwest toward Four Mile Creek.

Analytical results were similar to those of recent years. Tritium exceeded the DWS in wells FSS 2D and 3D and in a single analysis of well FSS 4D (Table 8-71). Well FSS 3D had concentrations of lead above the DWS. Single analyses of total radium exceeded the DWS for wells FSS 1D and 2D in 1991; elevated specific conductance was also observed in these wells.

F-Area Tank Farm

The F-Area Tank Farm (241-F), at the southwest edge of F Area (Figures 8-32 and 8-33), comprises 22 subsurface tanks containing aqueous radioactive wastes. These wastes consist of sludges, supernatant liquid of varying salt concentrations, and salt cake. The sludges are primarily a mixture of oxides and hydroxides of manganese, iron, and aluminum; small amounts of uranium, plutonium, and mercury; and almost all of the fission products originally in the irradiated fuel except cesium. The supernate is primarily a solution of sodium nitrate, sodium nitrite, sodium hydroxide, sodium aluminate, and most of the soluble fission products, including the major cesium isotopes. The solution volume is reduced in the tank farm evaporators, then stored in tanks to precipitate the sodium nitrate and sodium nitrite. This precipitate forms the salt cake. In 1961, Tank 8 was overfilled, causing soil contamination and possible groundwater contamination in the tank farm area.

The tank farm was monitored by the 27 water-table wells of the FTF series in 1991. Wells FTF 1, 8, and 14 could not be sampled during the year. The wells surround tank groups and monitor for leaks from the adjacent tanks. Groundwater flow in the upper saturated zone beneath the facility is to the north and west toward Upper Three Runs Creek and to the south toward Four Mile Creek. Horizontal gradients in the area are low and variable from quarter to quarter, making horizontal flow directions near each tank difficult to determine.

Gross alpha and total radium activities exceeded DWS in most of the FTF wells in 1991 (Table 8-72). Nonvolatile beta activity was detected above the DWS in nine wells, and tritium activity exceeded the DWS in two wells. No chemical constituents were detected above DWS during the year. Numerous wells had elevated specific conductance; wells FTF 7, 12, 13, and 21 also showed elevated pH, indicating that leaching of well grout may be affecting the water quality in these wells. These results are similar to those reported in recent years.

H-Area Acid/Caustic Basin

The H-Area Acid/Caustic Basin (904-75G) is southwest of H-Area Canyon Building near the H-Area Tank Farm (Figure 8-34). The basin was excavated in a relatively flat area at an elevation of approximately 285 ft msl. In addition to the acid/caustic solutions that were discontinued in 1982, the basin received steam condensate from a hose box and drainage from a chemical pad until 1985. See the Waste Sites Common to Several Areas section for a discussion of SRS acid/caustic basins.

The basin was monitored by the four water-table wells of the HAC series in 1991. Horizontal groundwater flow is to the northwest toward Crouch Branch. Relative to the basin, well HAC 4 is upgradient, well HAC 2 is downgradient, well HAC 1 is upgradient to sidegradient, and well HAC 3 is downgradient to sidegradient.

As in recent years, tritium activity exceeded the DWS in all wells in 1991 (Table 8-73). Total radium was detected above the DWS in well HAC 2 at one sampling event. Sulfate observations above the DWS (up to 4,280 mg/L) in wells HAC 1 and 2 are inconsistent with other sulfate results for these wells. As in the past, elevated TDS was reported in well HAC 2 and in a single analysis of well HAC 3. Specific conductance remained elevated in wells HAC 1, 2, and 3.

H-Area Auxiliary Pump Pit

The H-Area Auxiliary Pump Pit (241-10H) is at the east end of H Area (Figure 8-34). The facility will pump a high-level radioactive sludge and precipitate from the H-Area Tank Farm to the S-Area Low Point Pump Pit. When the pumps are shut down, this facility will collect the solution in a temporary holding tank via gravity flow lines.

The pit was monitored by the two wells of the HAP series in 1991. Information was insufficient to determine horizontal groundwater flow direction beneath the pit, although nearby wells show a general trend to the northeast toward McQueen Branch. Relative to the pit, well HAP 1 appears to be sidegradient, and well HAP 2 appears to be downgradient. Both wells appear to be upgradient to sidegradient of the H-Area Coal Pile Runoff Containment Basin.

No chemical or radioactive constituents were reported above DWS for the HAP wells in 1991 (Table 8-74). Elevated specific conductance and a single elevated result of alkalinity (as CaCO_3) were reported for well HAP 1, as in the past.

H-Area Canyon Building

The H-Area Canyon Building (221-H) is in the northeast part of H Area (Figure 8-34). At this building, materials from the reactors are dissolved using nitric acid, and the desired radionuclides are separated from waste products.

In 1991, the Canyon Building was monitored by the four water-table wells of the HCA series. The building is near the crest of a water-table divide, making relative gradient characterizations for each well difficult to assess. Groundwater beneath the southeastern half of the building appears to flow to the northeast toward McQueen Branch, and flow beneath the northwestern half appears to be to the north-northwest toward Crouch Branch. Thus, relative to the building, well HCA 2 appears to be upgradient, wells HCA 1 and 3 appear to be downgradient, and well HCA 4 appears to be downgradient to sidegradient.

As in the past, tritium activity exceeded DWS in all wells in 1991 (Table 8-75). Uranium-238 activity was reported, for the first time, in wells HCA 3 and 4. Total radium activity above the DWS was detected in well HCA 2 and in a single analysis of well HCA 3. Tetrachloroethylene, trichloroethylene, and lead

exceeded DWS, as in the past, in well HCA 4. Lead also exceeded the DWS in well HCA 1. Specific conductance remained elevated in wells HCA 2, 3, and 4.

H-Area Coal Pile Runoff Containment Basin

The H-Area Coal Pile Runoff Containment Basin (289-H) is east of H Area, approximately 1,000 ft east-northeast of the H-Area coal pile (Figure 8-34). See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins.

In 1991, the basin was monitored by the four water-table wells of the HCB series. Horizontal groundwater flow is to the northeast toward McQueen Branch. Relative to the basin, wells HCB 2 and 3 are upgradient and wells HCB 1 and 4 are downgradient.

Analytical results for 1991 were similar to those of recent years. Tritium activity exceeded the DWS in all wells (Table 8-76). Total radium activity and a single analysis of gross alpha exceeded DWS in well HCB 2. Concentrations of lead above the DWS were reported for the two upgradient wells and for one downgradient well. Elevated specific conductance, low pH, and concentrations of sulfate above the DWS were detected in wells HCB 2 and 4. Specific conductance was also elevated in well HCB 1, and TDS was elevated in well HCB 2.

H-Area Effluent Treatment Cooling Water Basin

The H-Area Effluent Treatment Cooling Water Basin (241-103H) is southwest of H Area (Figure 8-34). The basin will receive diverted cooling water from the separations processes, which will be sent to the F/H ETF if contaminated or to a permitted outfall if uncontaminated. The ETF was placed in service in 1988 to treat the wastewater formerly sent to the F- and H-Area Seepage Basins.

The basin was monitored by the four water-table wells of the HET well series in 1991. Horizontal groundwater flow is to the southwest toward Four Mile Creek. Relative to the basin, well HET 1D is upgradient and wells HET 2D, 3D, and 4D are downgradient.

As in recent years, all of the HET series wells had tritium activity exceeding the DWS (up to $3.7\text{E-}05$ $\mu\text{Ci/mL}$) in 1991. No other radioactive or chemical constituents were detected above DWS during the year.

H-Area Retention Basins

The H-Area Retention Basins (281-3H and 281-8H) are southeast of the intersection of Road 4 and Road E (Figure 8-34). A small, unlined earthen retention basin (281-3H) was used from 1955 to 1973 to provide temporary emergency storage for cooling water from the chemical separations process that contained radionuclides and possibly trace quantities of chemicals. Basin 281-3H presently is open but inactive and part of the CERCLA Remedial Investigation (RI) program. A larger, rubber-lined retention basin (281-8H) replaced the original basin in 1973 and is still in use for receipt of diverted cooling water or stormwater. The basins are adjacent, and any contamination in the groundwater is probably due to the unlined 281-3H basin.

In 1991, the basins were monitored by the two wells of the HR3 well series and the four wells of the HR8 well series. Well HR8 14 could not be sampled during the year. These wells are screened below the water-table surface, making determination of horizontal groundwater flow directions difficult. However, flow appears to be to the southwest toward Four Mile Creek. Relative to the basins, wells HR3 11 and 13 appear to be upgradient, well HR8 11 appears to be sidegradient, and wells HR8 12 and 13 appear to be downgradient.

As in recent years, tritium activity exceeded the DWS in all wells during 1991 (Table 8-77). Single analyses of total radium and lead slightly exceeded DWS in well HR8 12. In 1991, no other radioactive or chemical constituents were reported above DWS.

H-Area Seepage Basins

The H-Area Seepage Basins (904-44G, 904-45G, 904-46G, and 904-56G) are southwest of H Area, southwest of the intersection of Road E and Road 4 (Figure 8-35). Starting in 1955, the basins received wastewater from H Area containing low-level radioactivity and chemicals, including nitric acid, mercury, and sodium hydroxide. Basin 3 has been inactive since 1962. Basins 1, 2, and 4 operated under RCRA interim status from 1980 until taken out of service in the fourth quarter of 1988. The basins are inactive RCRA hazardous waste management facilities. A RCRA Part B Post-Closure Care Permit application was submitted to SCDHEC on December 3, 1990. The closure cap was certified as closed by RCRA on July 22, 1991. SCDHEC accepted the closure certification on November 30, 1991.

In 1991, the basins were monitored by six wells of the H series and by 129 wells of the HSB series. Well HSB 146A could not be sampled during the year.

The H series wells and the HSB series wells with no suffix or a suffix of "B," "C," "D," or "E," monitor the upper saturated zone. HSB wells with an "A" suffix monitor the Congaree-Four Mile zone. Well HSB 1TB is a production well. Relative to the basins, upper saturated zone well cluster HSB 65 and well HSB 66 are upgradient. The remaining wells in the upper saturated zone are downgradient to sidegradient, relative to the basin.

Horizontal groundwater flow within the upper saturated zone is generally south to southeast toward Four Mile Creek and an unnamed tributary. Horizontal flow in the Congaree-Four Mile zone is generally to the north and northeast, toward Upper Three Runs Creek.

Water elevations in adjacent wells screened in the Cretaceous zone show an upward vertical gradient from the Cretaceous into the Congaree-Four Mile zone. Vertical and horizontal gradients and flow directions beneath the H-Area Seepage Basins are generally similar to gradients and flow directions in the vicinity of the F-Area Seepage Basins. Beneath the H-Area Seepage Basins, as beneath the F-Area Seepage Basins, groundwater in the upper saturated zone may follow one of two distinct flow paths—south toward Four Mile Creek or down into the Congaree-Four Mile zone. Downward flow into the Congaree-Four Mile zone dominates southward horizontal flow with increasing distance north from Four Mile Creek. Flow in the Congaree-Four Mile zone is probably mostly horizontal toward Upper Three Runs Creek, constrained by the regional Paleocene aquitard and by an upward vertical gradient from the Cretaceous zone.

During 1991, as in the past, the contaminant plume in the vicinity of the H-Area Seepage Basins was characterized by tritium, gross alpha, nonvolatile beta, and total radium activities above DWS, low pH, and nitrate concentrations above the DWS. Specific conductance levels were generally elevated (Table 8-78). In addition, numerous other radionuclides, metals, chlorinated solvents, and other constituents were above DWS in one or more wells each. Generally, tritium was the most widespread contaminant, being found in most wells around the border of the HSB well network; metals and transuranic radionuclides exceeding DWS were typically found in portions of the plume closer to the basins. However, gross alpha, nonvolatile beta, and total radium

activities exceeded DWS in several sidegradient HSB well clusters to the west and east of the basins. As noted in 1990, upper saturated zone wells nearest the basins show generally declining tritium activities and nitrate concentrations during the period of 1989 to 1991.

Wells of the HSB series monitoring the plume in the upper saturated zone define an area of approximately one square mile surrounding the basins and extending toward Four Mile Creek to the south, including clusters HSB 130, 131, 140, and 148, south of Four Mile Creek. Contamination in the Congaree-Four Mile zone is less extensive than in the upper saturated zone. Tritium activity exceeded the DWS in five wells monitoring the Congaree-Four Mile zone; in addition, other radionuclides and chlorinated solvents exceeded DWS in at least one well each. The lateral extent of contamination extends slightly farther to the north toward Upper Three Runs Creek in the Congaree-Four Mile zone (downgradient in this zone) than in the upper saturated zone. Radionuclide activity in the Congaree-Four Mile zone is highest in the immediate vicinity of the basins. Elevated specific conductance and TDS levels for certain wells monitoring the Congaree-Four Mile zone may result from the natural occurrence of soluble calcium carbonate minerals in the Congaree and associated formations. Elevated pH, TDS, and alkalinity (as CaCO_3) in some wells may show the influence of well grout.

H-Area Sludge Land Application Site

The H-Area Sludge Land Application Site covers 13 acres southeast of H Area, south of Road E (Figure 8-31). Sewage sludge has been disposed of at this location since November 1990. See the Sewage Sludge Application Sites discussion under the General Areas section.

This location was monitored by the three wells of the HSS series in 1991. Wells HSS 1D and 2D are screened about 15 ft below the water-table surface, and their water-level observations appear to be unrepresentatively low. Because of this and because the wells are arranged almost in a line, horizontal groundwater flow directions are difficult to interpret. However, flow appears to be to the south or southeast toward Four Mile Creek.

A single analysis of total radium was detected above the DWS in well HSS 2D in 1991 (Table 8-79). Lead concentrations remained above the DWS in well HSS 3D.

H-Area Tank Farm

The H-Area Tank Farm (241-H), at the south end of H Area (Figure 8-34), comprises 29 subsurface tanks containing aqueous radioactive wastes. These wastes consist of sludges, supernatant liquid of varying salt concentrations, and salt cake. The sludges are primarily a mixture of oxides and hydroxides of manganese, iron, and aluminum; small amounts of uranium, plutonium, and mercury; and almost all of the fission products originally in the irradiated fuel except cesium. The supernatant is primarily a solution of sodium nitrate, sodium nitrite, sodium hydroxide, sodium aluminate, and most of the fission products, including the major cesium isotopes. The solution volume is reduced in the tank farm evaporators, then stored in tanks to precipitate the sodium nitrate and sodium nitrite. This precipitate forms the salt cake. Tank 16 leaked prior to the removal of the waste from that tank in 1972; this tank is in the RFI/RI program. A spill occurred at Tank 13 in 1983.

In 1991, the tank farm was monitored by the 32 wells of the HTF series and by well 241-H. Wells HTF 5, 6, 8, and 34 could not be sampled during the year. The wells surround tank groups and monitor for leaks from the adjacent tanks. The wells are screened at the water table or in the upper portion of the saturated zone. This location is on a groundwater divide between Four Mile Creek to the south and Upper Three Runs Creek to the north. Generally, beneath the northwestern portion of the tank farm, horizontal groundwater flow is to the north toward McQueen Branch; beneath the southwest portion of the tank farm, the horizontal flow is to the south toward Four Mile Creek. Beneath the eastern portion of the facility, horizontal flow is generally to the northeast toward Upper Three Runs Creek and McQueen Branch. Horizontal gradients in the area are low, making relative gradient characterizations for each well difficult to determine.

Analytical results for 1991 are similar to those of recent years. Tritium activity, found above the DWS in numerous HTF wells (Table 8-80), has its highest levels in wells surrounding tanks 21 through 24. Activities of gross alpha and, to a lesser extent, nonvolatile beta were detected above DWS in several wells in the central and western portions of the tank farm area. Total radium activity above the DWS was found in several wells distributed across the site. Lead and cadmium concentrations exceeded DWS in numerous wells, most of which are located in the central and western portions of the area. Mercury was detected in concentrations exceeding the DWS in wells HTF 9 and 17. Well HTF 27 had nitrate

concentrations above the DWS. In addition, specific conductance was elevated in several HTF wells.

M-Area Waste Disposal Facility (Y Area)

The M-Area Waste Disposal Facility (Y Area; Figure 8-36) will process mixed-waste sludge (off-gas blowdown) from the Consolidated Incineration Facility, to be built in H Area, and mixed-waste electroplating sludge from M Area. The waste will be solidified and stored in disposal vaults in Y Area.

This location was monitored by the eight wells of the YSC series in 1991. Wells YSC 1D and 2D are water-table wells; wells YSC 1C and 4C monitor the lower portion of the upper saturated zone; and wells YSC 1A, 2A, 4A, and 5A monitor the Congaree-Four Mile zone. Well YSC 1A could not be sampled during the year. Information was insufficient to determine precisely the horizontal flow directions in either the upper saturated zone or the Congaree-Four Mile zone; however, water elevation data from nearby S and Z areas indicate flow in the upper saturated zone is to the north and northeast toward McQueen Branch and Upper Three Runs Creek, and in the Congaree-Four Mile zone flow is to the north toward Upper Three Runs Creek. All of the YSC wells are located within the facility, with the exception of YSC 5A, located approximately 2,500 ft southeast of the facility.

This site was monitored for the first time in 1990. Total radium activity was detected again above the DWS in well YSC 2A (Table 8-81). Tritium activity was detected above the DWS for the first time in well YSC 1C. Alkalinity (as CaCO_3), specific conductance, pH, and TDS remained elevated in wells YSC 2A and 5A, suggesting that water from these wells may be affected by the leaching of well grout.

Old F-Area Seepage Basin

The Old F-Area Seepage Basin (904-49G), the first seepage basin constructed in the area, is north of the F-Area perimeter security fence and the F-Area Canyon Building (221-F) (Figure 8-32). This basin was used for disposal of wastewater from the Canyon Building from November 1954 until mid-May 1955, when it was abandoned in place. For three months in 1969, spent nitric acid solutions used to etch depleted uranium (from Building 313-M operations) were discharged to the basin. During operation, the seepage basin received a variety of wastewaters, including evaporator overheads, laundry wastewater, and an unknown amount of chemicals. Currently the basin contains some rainwater and is inactive. Official

waste-site closure has not been completed. This basin is part of the RFI/RI program.

The basin was monitored by the four water-table wells of the FNB series in 1991. Horizontal groundwater flow in the upper saturated zone beneath the basin is to the north-northeast toward Upper Three Runs Creek. Relative to the basin, wells FNB 1 and 4 are sidegradient, well FNB 2 is downgradient, and well FNB 3 is downgradient to sidegradient.

Analytical results for the FNB wells during 1991 were similar to those of recent years. Activities of nonvolatile beta, total radium, tritium, and U-238 above DWS (Table 8-82) and elevated specific conductance were reported for wells FNB 2 and 3; tritium activity also exceeded the DWS in well FNB 1. Well FNB also had elevated U-233, 244 activity. Well FNB 2 also had gross alpha activity and nitrate concentrations exceeding DWS and low pH. Trichloroethylene was reported above the DWS in wells FNB 1 and 2.

Radioactive Waste Burial Grounds

The Radioactive Waste Burial Grounds are in E Area between F and H areas (Figures 8-22 and 8-31), approximately 6 miles east of the nearest SRS boundary. This location is used for storage of radioactive solid waste produced at SRS and shipped from other DOE facilities. The original area (643-E) began receiving waste in 1952 and was filled in 1972. Operations then shifted to the adjacent 643-7E Burial Ground. The Mixed Waste Management Facility (MWMF; 643-28E), an area within 643-7E, was defined in 1986 (Figure 8-35). Closure of the 643-28E facility has been completed and was certified by SCDHEC under RCRA on March 28, 1991. Burial Ground 643-7E, the Low Level Radioactive Waste Disposal Facility (LLRWDF), is undergoing assessment and feasibility studies for closure under RCRA. All facilities within the Burial Grounds have been designated the Burial Ground Complex (BGC) and are undergoing a combined and comprehensive RFI/RI characterization and assessment.

The Radioactive Waste Burial Grounds are used for disposal of transuranic (TRU) alpha waste, low-level alpha and beta-gamma waste, intermediate-level beta-gamma waste, and waste generated offsite. Until 1965, TRU waste was placed in plastic bags and cardboard boxes and buried in earthen trenches. Between 1965 and 1974, TRU waste was segregated into two categories. Waste containing less than 0.1 Ci per package was buried unencapsulated in trenches. Waste containing greater than 0.1 Ci per package was

buried in retrievable concrete containers or encapsulated in concrete. Since 1974, TRU wastes contaminated with greater than $1\text{E-}02 \mu\text{Ci TRU/g}$ have been stored in water-tight containers that can be retrieved intact up to 20 years from the time of storage. Containers are stored on a concrete pad with a monitoring sump. Some bulky wastes are stored directly in shallow burial trenches. Since mid-1984, newly generated low-level waste has been placed in metal boxes or metal drums and is currently stored in engineered, low-level trenches and covered with at least 4 ft of soil.

Mixed wastes (low-level radioactive waste and hazardous waste) stored within 643-E and 643-28E include lead (used for shielding), cadmium (from control rods, safety rods, and shielding), tritiated pump oil, and mercury. Some of the waste is contained in welded stainless steel containers or metal drums and stored within concrete cylinders. Degraded solvents and tritiated pump oil were stored in tanks installed in 1975; a program is under way to incinerate these wastes. The tritiated pump oil from Tank S-32 was removed and either incinerated or stored in Building 643-29E. Tank S-32 was formally closed under RCRA. In March 1986, disposal operations for radioactive waste containing lead or other hazardous wastes were discontinued. A plan was implemented to ensure that all other wastes were certified to be free of hazardous materials.

The Burial Grounds were monitored by the BG and BGO well series and by well cluster HSB 85. The MGA, MGC, MGE, and MGG series wells (grid wells) monitored the upper saturated zone beneath Burial Ground 643-E and are located within this facility. The wells in these series are monitored by both EPD and SRL as part of ongoing research projects. Wells BG 91, 92, 93, 94, 95, 96, 101, 103, 104, 107, 108, 109, 110, 121, 122, and 125 are the SRL Burial Grounds Site Characterization Wells. Forty-seven of the BGO wells at the perimeter of Burial Ground 643-7E are RCRA compliance wells. Wells MGA 36; MGC 11 and 23; MGE 21; MGG 15, 19, and 28; BGO 5C, 5D, 8A, 12C, 17D, 19D, and 42C; well cluster BGO 46; and well BGX 6D could not be sampled during the year. Well BG 125 was dry.

In 1991, the upper saturated zone was monitored by wells of the BGO series whose cluster numbers are suffixed by "C" and "D," wells HSB 85B and C, and all of the BG wells. Groundwater in the Congaree-Four Mile zone was monitored by wells of the BGO series suffixed by an "A" and by well HSB 85A.

A groundwater divide extends east-west in the upper saturated zone beneath the Burial Grounds. Horizontal flow is generally radial to the southwestern, western, and northwestern directions from the southeastern corner of the Burial Grounds. From the northeastern corner of this area, horizontal groundwater flow in the upper saturated zone is to the north-northeast toward Crouch Branch. From the northwest corner of the area, flow in the upper saturated zone is generally to the west toward Upper Three Runs Creek. From the southwest corner of the area, the upper saturated zone generally flows to the south toward Four Mile Creek.

A downward vertical gradient exists between the water table and the Congaree-Four Mile zone, indicating the potential for downward transport of contaminant-bearing groundwater. Gradient relationships between the Congaree-Four Mile zone and the Cretaceous zone indicate predominantly horizontal transport in the Congaree-Four Mile zone; flow is to the north toward Upper Three Runs Creek.

Relative to the Burial Grounds, wells HSB 85B and 85C, BG 110, and BGO 1D are upgradient, and all other wells monitoring the facility are downgradient to sidegradient.

During 1991, the area located on E Road between F and H Areas was designated as E Area (Figure 8-38). Included in this area are the Old Burial Grounds, the Burial Ground Expansion (now called the E-Area Vaults), and the Landfill Monitoring Building. E Area will include projects for the Hazardous/Mixed Waste Vaults, the Transuranic Waste Facility, and the Waste Preparation Facility.

The 17 wells of the BGX series were installed in 1991 to monitor the E-Area Vaults near the Burial Grounds. Sampling of the wells began during third quarter 1991. Well BGX 6D could not be sampled during the year. Horizontal groundwater flow directions in the upper saturated zone are variable throughout this area. Generally, horizontal flow from the southeastern portion of the E-Area Vaults is to the north-northeast toward Crouch Branch, and horizontal flow from the western portion of the vaults is to the northwest toward Upper Three Runs Creek. Relative to the E-Area Vaults, wells BGX 2D, 3D, and 4D are upgradient, well BGX 5D appears to be sidegradient, and wells BGX 9D, 10D, and 12D are downgradient. The remainder of the wells monitor the lower portion of the upper saturated zone and the Congaree-Four Mile zone. Horizontal flow in the Congaree-Four Mile zone is generally to the north-northwest toward Upper Three Runs Creek. Vertical gradients from the water

table to the Congaree-Four Mile zone indicate the potential for downward groundwater flow beneath the facility.

The four HMD series water-table wells (Figure 8-38) were installed in 1991 to provide background data for the HWMF (not in operation in 1991) and to assess quality of groundwater flowing from the MWMF toward Upper Three Runs Creek. Horizontal groundwater flow beneath the HWMF is to the north. All four wells are downgradient of the MWMF.

During 1991, as in previous years, tritium and chlorinated volatile organics were the primary analytes above DWS in groundwater below these facilities (Table 8-83). Most wells monitoring the upper saturated zone had tritium activities at or above the DWS; chlorinated volatile organic solvents in many upper-saturated-zone wells exceeded DWS. In 1991, the extent and location of tritium and chlorinated solvent plumes changed little from previous years. Total radium and other radionuclide activities, as well as metals, nitrate, nitrite, and several pesticides exceeded DWS in one or more wells each.

The highest tritium activity was recorded in samples from wells near the southwestern and southeastern ends of Facility 643-E, the Old Burial Ground. High tritium activities were also reported for wells monitoring the region north of Facility 643-7E. Most elevated total radium activities were reported for perimeter wells BGO 32D to BG 61, located along the south-central fence of the Old Burial Ground.

Most elevated concentrations of chlorinated organic solvents (chiefly trichloroethylene and lesser amounts of tetrachloroethylene and other compounds) were reported for wells along the southwestern edge of the Old Burial Ground and at the northern margin of Facility 643-7E.

In the Congaree-Four Mile zone, trichloroethylene concentrations above the DWS were reported for six wells; elevated tetrachloroethylene concentrations were reported for two wells. Tritium activities above the DWS were reported for four wells in the Congaree-Four Mile zone. In addition, other radionuclide activities and metal concentrations exceeded DWS in several wells monitoring this zone. Elevated tritium activities and chlorinated solvent concentrations were generally found near or downgradient from upper saturated zone contaminant plumes.

The BGX wells, sampled for the first time in 1991, showed tritium activity detected above the DWS in several downgradient and upgradient wells, including Congaree-Four Mile zone well BGX 1A. Concentrations of lead above the DWS and activities exceeding DWS for total radium, gross alpha, and nonvolatile beta were reported for well BGX 1A. Total radium activity was also reported above the DWS in well BGX 10D, and gross alpha activity was detected above the DWS in well BGX 5D. Chlorinated volatile organic concentrations exceeded DWS in two wells. Elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS in wells BGX 1A, 1C, and 2B suggest that water from these wells may be affected by well grout. Elevated alkalinity (as CaCO_3) was detected in well BGX 4A. Specific conductance was also elevated in wells BGX 1D, 4A and 4C.

The HMD wells were monitored for the first time in 1991. A single analysis of total radium activity was reported at the DWS for well HMD 4D. A single analysis of tetrachloroethylene above the DWS and elevated specific conductance were reported for well HMD 1D.

S-Area Defense Waste Processing Facility

The S-Area Defense Waste Processing Facility (DWPF) (Figure 8-36) will solidify high-level radioactive waste into a solid, inert glass form for eventual storage in an offsite geologic repository.

The six wells of the SBG series were installed as background wells at the DWPF and are screened below the water-table surface, making correlations between these water elevations and adjacent water-table elevations difficult. Horizontal groundwater flow is to the north and northeast toward Upper Three Runs and McQueen Branch, respectively. Relative to the facility, wells SBG 5 and 6 are upgradient, well SBG 1 is sidegradient, and wells SBG 2, 3, and 4 are downgradient.

Tritium exceeded the DWS in wells SBG 1 and 4 (Table 8-84). Total radium above the DWS and elevated TDS were reported for well SBG 6. Well SBG 4 had concentrations of chlorinated volatile organics above DWS. These results are similar to those of recent years.

S-Area Low Point Pump Pit

The S-Area Low Point Pump Pit (511-S) is at the south end of S Area (Figure 8-36). The facility will pump high-level radioactive sludge and precipitate from the H-Area Tank Farm to the DWPF Vitrification Building (221-S). When the pumps are shut down, the

sludge and precipitate remaining in the line will drain back into a temporary holding tank via gravity flow lines.

The pump pit was monitored in 1991 by the two wells of the SLP series. Both are water table wells, although well SLP 2 is screened below the top of the water table. Horizontal groundwater flow is to the northeast toward McQueen Branch. Relative to the pit, well SLP 2 is downgradient, and well SLP 1 is downgradient to sidegradient.

No chemical or radiological constituents were detected above DWS in the SLP wells during 1991.

S-Area Vittrification Building

The S-Area Vittrification Building (221-S), also known as the S-Area Canyon Building, is located in the northern portion of S Area (Figure 8-36). The Vittrification Building will contain process and auxiliary equipment and personnel facilities to incorporate radioactive waste into leach-resistant glass. The glass will be cast in metal canisters and stored in an interim facility within S Area.

The S-Area Vittrification Building was monitored by 10 wells of the SCA series in 1991. Well SCA 1A were dry every time they were sampled during the year. Wells SCA 2A, 3A, and 4A are screened in a perched water-bearing zone, and well SCA 2A was dry every time it was sampled in 1991. The water-table surface in the immediate vicinity of the Vittrification Building is undulatory, and there is no clear horizontal flow pattern at the water table immediately beneath the site. This may be the result of local recharge of the upper saturated zone from the perched water-bearing zone beneath the site. Horizontal flow in the upper saturated zone in the general vicinity of S Area is to the north and northeast, toward Upper Three Runs Creek and McQueen Branch, respectively. Hydraulic gradients immediately beneath the site indicate possible local westward flow as well. Relative to the building, wells SCA 4 and 6 are probably upgradient; wells SCA 3 and 5 are probably downgradient; and wells SCA 1 and 2 are located within the building.

Total radium activity was detected above the DWS in three of the SCA wells (Table 8-85); tritium activity exceeded the DWS in four wells, including two wells monitoring a perched water-bearing zone beneath the site. These radioactive constituents were detected above DWS for the first time at this location. Elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS were detected in several wells, indicating that

leaching of well grout may be affecting the water quality of wells SCA 3A and 6.

Z and ZW Wells

The Z and ZW wells (Figures 8-31 through 8-33) were installed in the separations areas in 1951 and 1952. These wells, which range from approximately 15 to 90 ft deep, measure water-table elevations and monitor for radioactive constituents in the groundwater in and around F and H areas.

Results for 1991 were similar to those of recent years. Tritium activity exceeded the DWS in wells ZW 2, 5, 7, 9, and 10 (Table 8-86). Samples from these wells were not tested for chemical constituents. Specific conductance was elevated in wells ZW 2, 4, 5, 6, 7, 8, and 17. Elevated pH was reported in wells Z 8 and 18 and in well ZW 7.

Z-Area Low Point Drain Tank

The Z-Area Low Point Drain Tank (551-Z) is southeast of S Area (Figure 8-36). The facility will receive low-level radioactive salt solution from the H-Area Tank Farm and pump it to the Z-Area Salt Solution Holding Tank (201-Z). When the H-Area pump is shut down, the low point drain tank has sufficient capacity to collect the solution still remaining in the lines via gravity flow.

The two wells of the ZDT series monitored the drain tank in 1991. Information was insufficient to determine the direction of horizontal groundwater flow at this site. However, other wells nearby indicate a flow to the northeast toward McQueen Branch. Well ZDT 1 is probably downgradient, and well ZDT 2 is probably downgradient to sidegradient, relative to the tank.

As in the past, tritium activity above the DWS was detected in both wells (Table 8-87). No other chemical or radiological constituents were reported above DWS. Specific conductance was elevated in well ZDT 1.

Z-Area Saltstone Facility

The Z-Area Saltstone Facility (Figure 8-36) will process and dispose of low-level radioactive salt supernatant from F and H areas.

Three wells of the ZBG series were installed to obtain background data at this facility and to monitor the Z-Area Saltstone Facility vault after startup. In 1991, wells ZBG 1 and 2 monitored the water table, and ZBG 1A monitored a perched water-bearing zone between 276 and 281 ft msl. Information was

insufficient to determine the direction of horizontal groundwater flow beneath the facility, although data from nearby wells indicate flow to the northeast toward McQueen Branch, a tributary of Upper Three Runs Creek. Relative to the vault areas, well ZBG 1 is probably sidegradient, and well ZBG 2, located within the facility, is probably downgradient.

No chemical or radiological constituents were reported above DWS in the ZBG wells during 1991. Levels of Ra-226, 228 were elevated during 1990, but none were reported for 1989 or 1988.

Other Areas

Central Shops Area, located in the central part of SRS (Figures 8-22 and 8-38), provides supply, maintenance, and other services for SRS. Surface elevations across the area range from approximately 280 to 300 ft msl. Surface drainage is to tributaries of Four Mile Creek to the north, west, and south and to tributaries of Pen Branch to the east. The nearest SRS boundary is approximately 6.5 miles to the west-southwest. Four Mile Creek, Upper Three Runs Creek, and several other incised creeks are located between Central Shops Area and the SRS boundary and are areas of groundwater discharge.

In 1991, groundwater was monitored at the following locations in Central Shops Area:

Central Shops Burning/Rubble Pits

The Central Shops Burning/Rubble Pits (631-1G, 631-3G, and 631-5G) are about 600 ft north of Central Shops Area (Figure 8-38). The exact boundaries of the pits are unknown. See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

In 1991, the pits (631-1G and 631-3G) were monitored by the four wells of the CSR series. Horizontal groundwater flow is to the southwest toward Four Mile Creek. Well CSR 2 appears to be upgradient, wells CSR 3 and 4 appear to be sidegradient, and well CSR 1 appears to be downgradient to sidegradient, relative to the pits. Pit 631-5G has no monitoring wells at present.

During 1991, lead concentrations in well CSR 1 exceeded the DWS (up to 0.049 mg/L) for the first time. No other chemical or radioactive constituents were reported above DWS.

Central Shops Burning/Rubble Pit South of the Ford Building Seepage Basin

The Central Shops Burning/Rubble Pit South of the Ford Building Seepage Basin (631-6G) is about 1 mile southeast of the Central Shops Burning/Rubble Pits 631-1G, 631-3G, and 631-5G (Figure 8-38). See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pit was monitored by the three wells of the CBR series in 1991. Horizontal gradients in the vicinity of the pit are very low, and the pit is near a water-table divide between Pen Branch and Four Mile Creek, making the interpretation of horizontal groundwater flow directions difficult. However, flow appears to be to the south toward Pen Branch. The exact boundaries of the pit are unknown. Well CBR 1D appears to be upgradient, and wells CBR 2D and 3D appear to be sidegradient, relative to the pit.

No chemical or radiological constituents were detected above DWS in 1990, when the wells were first sampled. Total radium activity above the DWS was reported in the two sidegradient wells in 1991 (Table 8-88). Tritium activity slightly exceeded the DWS in well CBR 2D. Single analyses of tetrachloroethylene, trichloroethylene, and mercury from sidegradient wells exceeded DWS.

Central Shops Diesel Spill

The CSD series wells are located southeast of the Hazardous Waste Storage Facility and northwest of the Fire Department Training Facility in Central Shops Area (Figure 8-38). These wells monitor for diesel fuel in the water table beneath this area because leaking tanks are buried at the Diesel Fuel Storage Facility.

In 1991, the nine wells of the CSD series monitored the diesel fuel plume. Horizontal flow in the upper saturated zone is to the southwest toward a tributary of Four Mile Creek. Well CSD 1D is upgradient, well CSD 2D is sidegradient to upgradient, and the remaining wells are downgradient to sidegradient of the spill.

Total radium slightly exceeded the DWS in the upgradient well, as it did in 1990, when wells at the spill site were first sampled. Nitrite concentrations were reported above the DWS for the first time in well CSD 12D (Table 8-89). Replicate analyses of this sample by a different laboratory did not confirm the presence of nitrite. Trichloroethylene concentrations up to the DWS were reported in well CSD 13D as they

were last year. Elevated alkalinity (as CaCO_3) and specific conductance in wells CSD 4D and 11D as well as elevated pH in well CSD 4D suggest possible leaching of well grout.

Fire Department Training Facility

The Fire Department Training Facility (904-113G), also known as the Central Shops Burnable Oil Basin, is at the southeast end of Central Shops Area near the Ford Building Seepage Basin (Figure 8-38). This facility, a shallow pit surrounded by an 18-in.-high asphalt dike, was used from 1979 to 1982 by the SRS Fire Department to train personnel to use firefighting equipment. After this time, the area was excavated and backfilled.

The two wells of the CSO series monitored the facility in 1991. There was insufficient information to determine precisely the direction of horizontal groundwater flow beneath the facility. Well CSO 2 is screened below the top of the water table and may produce unrepresentative water table elevation data. However, well data from other nearby wells suggest flow to the southwest toward an unnamed tributary of Four Mile Creek. Well CSO 1 is probably sidegradient, and well CSO 2 is probably upgradient to sidegradient.

No radioactive or chemical constituents exceeding DWS were reported for the CSO well series in 1991. In recent years, tritium activity has exceeded the DWS.

Ford Building Seepage Basin

The Ford Building Seepage Basin (904-91G) lies southeast of the Fire Department Training Facility in the southeast portion of Central Shops Area (Figure 8-38). The basin received low-level radioactive wastewater from Ford Building operations (repairing heat exchangers) from 1964 to January 1984. The basin is currently inactive and is part of the RFI/RI program.

In 1991, the five wells of the HXB series monitored the basin. Horizontal gradients are very low in the immediate vicinity of the basin, located near a water table divide between Pen Branch and Four Mile Creek. Determination of horizontal flow directions is difficult; however, the dominant flow in the vicinity of the basin appears to be to the west-southwest toward an unnamed tributary of Four Mile Creek. Well HXB 4D appears to be upgradient relative to the basin, well HXB 1 appears to be sidegradient, wells HXB 2 and 3

appear to be upgradient to sidegradient, and HXB 5D appears to be downgradient to sidegradient.

Tritium activity was detected above the DWS in well HXB 5D and in a single analysis in well HXB 1 (Table 8-90). Tritium activity has not been detected above the DWS in these wells in recent years. A single analysis of total radium above the DWS and elevated specific conductance were reported for well HXB 4D.

Hazardous Waste Storage Facility

The Hazardous Waste Storage Facility (709-G, 709-2G, and 709-4G) is northwest of Central Shops Area (Figure 8-38). Building 709-G has been in service since 1983, 709-2G since 1987, and 709-4G since 1984. Building 709-2G contains a mixture of low-level radioactive waste and hazardous waste. Wastes are stored inside the buildings in drums placed on diked concrete floors designed to contain liquid spills. This facility, which is currently active, is inspected weekly for container leakage.

The facility was monitored by the two wells of the HWS series in 1991. Information from these wells is insufficient to determine horizontal groundwater flow directions, though the dominant flow beneath much of the overall Central Shops Area is to the southwest toward an unnamed tributary of Four Mile Creek. Relative to the facility, well HWS 2 is probably upgradient, and well HWS 1A is probably upgradient to sidegradient.

The concentration of lead in well HWS 1A was above the DWS (up to 0.022 mg/L). No other radioactive or chemical constituents were reported above DWS during 1991.

Hydrofluoric Acid Spill

The Hydrofluoric Acid Spill (631-4G) is at the south end of Central Shops Area near Road 3 (Figure 8-38). It is uncertain whether a spill occurred at this site or if contaminated soil or containers are buried there. The spill or burial occurred prior to 1970, and an identification sign is the only evidence that material was released there. This location is part of the CERCLA RI program.

The four water-table wells of the CSA series monitored the spill area in 1991. Horizontal groundwater flow is to the south-southwest toward an unnamed tributary of Four Mile Creek. The exact confines of the spill or burial are unknown. However, well CSA 2 appears to be upgradient relative to the spill area, wells CSA 1 and 3 appear to be sidegradient, and well CSA 4 appears to be downgradient to sidegradient.

A pesticide, lindane, was detected slightly above the DWS (up to 0.00041 mg/L) for the first time in the upgradient well. No other chemical or radiological constituents were reported above DWS during 1991.

D Area, located in the southwest part of SRS (Figure 8-22), includes a large coal-fired power plant and the inactive heavy water facilities. Surface elevations across D Area range from approximately 100 to 150 ft msl, decreasing to the west-southwest toward the Savannah River. The nearest SRS boundary is the Savannah River, approximately 0.75 miles to the west. The water table discharges to the Savannah River and to a nearby swamp.

In 1991, groundwater was monitored at the following locations in D Area:

D-Area Burning/Rubble Pits

The D-Area Burning/Rubble Pits (431-D and 431-1D) are approximately 1,000 ft west of D Area (Figure 8-39). See the Waste Sites Common to Several Areas section for a discussion of SRS burning/rubble pits.

The pits were monitored by the four water-table wells of the DBP series in 1991. Horizontal groundwater flow is to the south-southwest toward the Savannah River. Relative to pits 431-D and 431-1D, wells DBP 1 and 3 are upgradient and well DBP 2 is downgradient. Well DBP 4 is downgradient to sidegradient of pit 431-D and upgradient to sidegradient of pit 431-1D. Wells DBP 2, 3, and 4 are screened below the top of the water table.

As in the past, no chemical or radiological constituents were detected above DWS in the DBP wells during 1991. However, wells DBP 2 and 4 showed elevated specific conductance (Table 8-91). A value for TDS of 1,140 mg/L reported for well DBP 2 is considered anomalous due to its inconsistency with other analyses of the same sample and with other TDS values for the same well.

D-Area Coal Pile Runoff Containment Basin and Ash Basins

The D-Area Coal Pile Runoff Containment Basin (489-D) is south of D Area (Figure 8-39). See the Waste Sites Common to Several Areas section for a discussion of SRS coal pile runoff containment basins. The D-Area Ash Basins are southwest of the D-Area perimeter fence on a northwest-trending slope. Ash sluice water from the D-Area powerhouse has been discharged to the D-Area Ash Basins since 1951. The

annual ash disposal rate into the D-Area Ash Basins was approximately 50,000 yd³/yr until 1983 and has been approximately 65,000 yd³/yr since 1983.

These basins were monitored by 15 water-table wells of the DCB series in 1991. Horizontal groundwater flow is radially patterned across this area, flowing generally to the southwest beneath the coal pile runoff containment basin and the southernmost ash basin and generally to the west and northwest beneath the three northern ash basins. Flow beneath these units is toward the Savannah River and the Savannah River Swamp. Water-elevation data from well DCB 11 is unusually high relative to other wells in its vicinity. Because this may be a reflection of local recharge of the water table at that specific location, those data were omitted when calculating flow patterns across the area. With respect to the coal pile runoff containment basin, the DCB series wells were characterized as follows—wells DCB 2A, 7, and 8 are upgradient; wells DCB 1A, 4A, 5A, 10, 13, 15, and 16 are downgradient; well DCB 6 is sidegradient; wells DCB 9, 12, and 14 are downgradient to sidegradient. With respect to the ash basins, wells DCB 1A, 2A, 4A, 5A, 6, 7, 8, 9, 10, and 13 are upgradient; wells DCB 12, 15, and 16 are downgradient; well DCB 3A is upgradient to sidegradient; well DCB 14 is downgradient to sidegradient.

Activities of tritium, total radium, nonvolatile beta, and gross alpha were detected above DWS in several DCB wells situated downgradient of the coal pile and its runoff containment basin (Table 8-92). Lead concentrations exceeding the DWS were reported for upgradient well DCB 2A. Also detected in these wells were elevated alkalinity (as CaCO₃), specific conductance, and TDS. Low pH and concentrations exceeding DWS of several metals, sulfate, and chlorinated volatile organics were also reported. Well DCB 16 and to a lesser extent DCB 15 had elevated pH, alkalinity (as CaCO₃), TDS, and specific conductance, indicating that leaching of well grout may be affecting the water quality of these wells. Except for the absence of high levels of fluoride during 1991, most of the analytical results for the year are consistent with those of recent years.

D-Area Oil Disposal Basin

The D-Area Oil Disposal Basin (631-G) is north of D Area near the intersection of Road A-4 and Road 3 (Figure 8-39). The basin was constructed in 1952 and received waste oil products from D Area that were unacceptable for incineration in the powerhouse boilers. These waste oils may have contained

hydrogen sulfide, chlorinated organics, or other chemicals. In 1975, the oil basin was removed from service and backfilled with soil. This basin is part of the RFI/RI program.

The basin was monitored by four wells of the DOB series in 1991. Groundwater flow direction was variable during the year, though generally heading to the south or southwest toward the Savannah River. Relative to the basin, well DOB 3 is upgradient, well DOB 2 is downgradient, well DOB 4 is upgradient to sidegradient, and well DOB 1 is downgradient to sidegradient.

Concentrations of tetrachloroethylene and trichloroethylene above DWS were detected in well DOB 1 (Table 8-93). A single analysis of tetrachloroethylene slightly exceeded the DWS in well DOB 4. Specific conductance was elevated in well DOB 1. Analytical results for the DOB series wells were similar to past years.

General Areas are those sections of SRS outside areas designated for specific purposes. In 1991, groundwater was monitored at the following locations in the General Areas:

Background Well Near Hawthorne Fire Tower

The Background Well Near Hawthorne Fire Tower is in the north-central part of SRS between Upper Three Runs Creek and Tinker Creek (Figure 8-22). Well GBW 1 was installed at this location to provide background groundwater quality information.

During 1991 as in the past, no results for radioactive or chemical constituents exceeded DWS in well GBW 1.

Chemicals, Metals, and Pesticides Pits

The Chemicals, Metals, and Pesticides (CMP) Pits (080-17G, 080-17.1G, 080-18G, 080-18.1G, 080-18.2G, 080-18.3G, and 080-19G) are west of Road C (Figure 8-40) at the top of a hill near the head of Pen Branch. Surface elevations across this location range from 290 to 330 ft msl. Surface drainage is toward the north to Pen Branch and toward the south to a tributary of Pen Branch. The nearest SRS boundary is about 7 miles to the southeast. The CMP Pits were used to dispose of waste from 1971 through 1979. The waste consisted of drummed oil, organic solvents, and small amounts of pesticides and metals. In 1984, the pits were excavated to form two trenches, backfilled, and capped. During excavation, much of the liquid waste was recovered in the original burial drums. These pits are part of the RFI/RI program.

In 1991, the pits were monitored by 20 wells of the CMP series. Wells with no modifier or a "C" suffix after the well cluster number monitored the water table, wells with a "B" suffix are screened at deeper levels in the upper saturated zone, and wells with an "A" suffix are screened in the Congaree-Four Mile zone. Well CMP 16C, located between the pits, was dry every time it was sampled during the year. Flow in the upper part of the upper saturated zone is generally to the north toward Pen Branch. Relative to the pits, well CMP 10 appears to be upgradient, well CMP 11 appears to be upgradient to sidegradient, well CMP 13 appears to be downgradient to sidegradient, and the remaining water table wells appear to be sidegradient. Horizontal groundwater flow in the lower portion of the upper saturated zone is to the north-northwest toward Pen Branch. Relative to the pits, wells CMP 11B and 16B are upgradient; wells CMP 8B and 13B are downgradient; and wells CMP 10B and 15B are upgradient to sidegradient. Horizontal flow in the Congaree-Four Mile zone is generally to the west beneath the pits. A downward vertical gradient exists between the water-table surface and the Congaree-Four Mile zone, which indicates the potential for downward migration of groundwater from surface elevations into the Congaree-Four Mile zone.

Unlike recent years, during 1991 no radioactive constituents were detected above DWS in any CMP well. As in the past, lead and three chlorinated organic solvents were reported above DWS in several CMP wells (Table 8-94). Alkalinity (as CaCO_3), pH, and especially specific conductance remained elevated in numerous lower zone wells, probably due to the presence of naturally occurring carbonate rock.

Interim Waste Technology Sites

The Interim Waste Technology Site Characterization Wells are located on sites B, P, and Q, each covering approximately 300 acres. These wells were installed by SRL to characterize potential locations for new waste management facilities. Site B is located in the north-central part of SRS, approximately 2 miles northeast of H Area near the intersection of Road E-2 and Monroe Owens Road (Figure 8-41). It lies south of Tinker Creek, west of Mill Creek, and east of McQueen Branch between two gently sloping ridges. Surface elevations at this location range from 290 to 320 ft msl and surface drainage is to the northeast toward Mill Creek and to the southwest toward McQueen Branch. The nearest SRS boundary is approximately 6 miles to the north.

Sites P and Q are adjacent to each other and are located east of Road 2 and west-southwest of the Kato and Lower Kato Road Sewage Sludge Application Sites (Figure 8-42). The sites occupy the eastward facing slope of a ridge separating the Savannah River floodplain from Upper Three Runs Creek. Surface elevations across Site P range from 250 to 280 ft msl, and across Site Q from 200 to 260 ft msl. Surface drainage from both sites is southeast toward Upper Three Runs Creek. The nearest SRS boundary is approximately 2.5 miles to the west.

In 1991, 14 wells of the IDB series, 13 wells of the IDP series, and 14 wells of the IDQ series monitored Sites B, P, and Q, respectively. Wells IDP 3D and 10 and well IDQ 1 were dry during 1991.

Ten of the IDB wells monitored the upper saturated zone, and the remaining four wells of the series monitored deeper zones in 1991. Horizontal flow of the water table is to the northeast toward Mill Creek. Water elevations in wells monitoring deeper zones show a downward vertical gradient from the water table surface into the Congaree-Four Mile zone (approximately 235 to 116 ft msl) but an upward vertical gradient between the Congaree-Four Mile zone and the Cretaceous zone. This condition indicates the potential for local downward flow of groundwater into the Congaree-Four Mile zone. Groundwater flow in the lower zones is probably predominantly horizontal toward upper Three Runs Creek to the north in the Congaree-Four Mile zone, and toward the Savannah River to the southwest in the Cretaceous zone.

In 1991, 11 of the IDP wells monitored the upper saturated zone, and two wells monitored deeper zones. Horizontal flow in the upper saturated zone beneath this location is to the southeast toward Upper Three Runs Creek. Wells IDP 3B and 3A monitor, respectively, the Congaree-Four Mile zone and the Cretaceous zone. Water elevations in these wells indicate the potential for downward flow of groundwater from the water-table surface into the Congaree-Four Mile zone. An upward vertical gradient exists between the Cretaceous and the Congaree-Four Mile zones; the predominant flow direction in each of these zones is probably horizontal, south towards Upper Three Runs Creek in the Congaree-Four Mile zone and southwest toward the Savannah River in the Cretaceous zone. Groundwater transport within these lower zones is probably horizontal, most likely to the southwest toward the Savannah River.

Eleven wells of the IDQ series monitored the upper saturated zone in 1991. Of these, two wells, IDQ 1 and 2, have no screen zone data, and only IDQ 2 has water-elevation observations, so their final classifications are contingent on additional well data. Three wells monitored deeper zones. Horizontal flow in the upper saturated zone is to the south toward Upper Three Runs Creek. Gradient relationships between zones and flow directions in the Congaree-Four Mile and Cretaceous zones are similar to gradients and flow directions indicated by the adjacent IDP wells.

Activities above DWS for Ra-226, U-238, and to a lesser extent U-235 were detected in several IDB wells during 1991 (Table 8-95). These radioactive constituents were not analyzed for in 1990, when sampling for chemical and radiological constituents began. Antimony concentrations exceeded the DWS in well IDB 1B, as they did last year. Lead was detected above the DWS for the first time in well IDB 3. Continued elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS in wells IDB 1A, 1B, 2B, 2C, and 3 suggest that water from these wells was affected by well grout; well IDB 9 may also have been affected similarly.

U-238 activity, not analyzed for in 1990 for the IDP series wells, was detected above the DWS during 1991 in several IDP wells. U-235 activity was detected above the DWS for the first time in well IDP 6. No chemical constituents were detected above DWS. Elevated alkalinity (as CaCO_3), specific conductance, and pH in wells IDP 3B and 3C indicate possible effect of well grout. Well IDP 4 also reported a single analysis of elevated specific conductance; this result is considered suspect because it is not supported by other analyses during the year.

U-235 activity above the DWS was reported for well IDQ 8; U-238 activity exceeded the DWS in wells IDQ 4, 5, 7, 10, and 12; Ra-226 activity was detected above the DWS in wells IDQ 6 and 12; and K-40 activity was detected above the DWS in well IDQ 11. Sampling for these radioactive constituents was not performed prior to 1991 for the IDQ well series. No chemical constituents were detected above DWS. Alkalinity (as CaCO_3), specific conductance, and pH remained elevated in wells IDQ 3B and 6, suggesting that water from these wells may be affected by well grout. Wells IDQ 4, 7, and 10 also had varying elevated levels of alkalinity (as CaCO_3), specific conductance, and pH.

Par Pond Sludge Land Application Site

The Par Pond Sludge Land Application Site (formerly the Par Pond Borrow Pit Site; 761-5G) covers 22 acres south of Par Pond and is approximately 1.3 miles north-northeast of the intersection of Roads B and F (Figure 8-43). Surface elevations across this area range from 210 to 230 ft msl. Surface water drains to the north toward Par Pond and to the south toward a tributary of Lower Three Runs Creek. The nearest SRS boundary is about 2 miles to the east. In 1989, the site became part of the RFI/RI program because of the presence of chlordane in the lagoon sludge applied to the site. See the Sewage Sludge Application Sites discussion under the General Areas section.

This location was monitored by the three wells of the PSS series and by well SSS 17. All of the PSS series wells are screened slightly below the top of the water table; no screen zone data are available for well SSS 17. Horizontal groundwater flow appears to be to the southwest toward an unnamed tributary of Lower Three Runs Creek. Wells PSS 1D and SSS 17 are upgradient, and wells PSS 2D and 3D are downgradient of the application site.

Although total radium and gross alpha activities exceeding DWS have been reported in recent years, no radioactive or chemical constituents were detected above DWS in the PSS wells nor in well SSS 17 during 1991.

P 14 Well Cluster

The P 14 well cluster is adjacent to SRS Road E-2, near the proposed Sanitary Landfill (Figure 8-41). Analyses from these wells are used to support the Nuclear Weapons Complex Reconfiguration Site Environmental Impact Statement. No radiological or chemical constituents exceeded DWS in this cluster during 1991. Specific conductance (at 160 $\mu\text{S}/\text{cm}$) was elevated in well P 14C.

P 28 Well Cluster in F Area

Three wells of the P 28 well cluster are used for microbiology research on bioremediation of SRS groundwater in F Area (Figure 8-32). No results for radioactive or chemical constituents exceeded DWS in the P 28 well cluster during 1991. Elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS in well P 28TC (Table 8-96) suggest that water from this well may be affected by well grout.

P 29 Well Cluster in B Area

Three wells of the P 29 well cluster are used for microbiology research on bioremediation of SRS groundwater in B Area (Figure 8-42). Benzene was detected above the DWS in well P 29C (up to 0.052 mg/L) consistently in 1991. The elevated benzene could be the result of old underground gas or diesel storage tanks. EMS has inspected the area and believes there are two possible underground storage tanks north of well P 29C. The predominant groundwater gradient in the area is south toward Upper Three Runs Creek. The first suspected tank appears to be at an abandoned gas station on the south side of the intersection of Road C-2 and the road perpendicular to and adjoining Roads 2 and C-2. The second suspected tank appears to be an old diesel tank in front of Building 772-7B, which is located on the road perpendicular to and adjoining Roads 2 and C-2. No other radioactive or chemical constituents were detected above DWS in the P 29 well cluster.

Potential New Production Reactor Site Characterization Wells

The NPM series wells are situated north of the intersection of Roads C and 6, approximately 4,500 ft northeast of Central Shops Area (Figure 8-31). They were installed as characterization wells for preliminary hydrogeologic evaluation of a new production reactor location.

The 16 wells of the NPM series were monitored for the first time during fourth quarter 1991. Wells NPM 1A, 19E, and 34E monitor the Congaree-Four Mile zone. The remainder of the wells monitor the upper saturated zone and a perched water-bearing zone beneath the reference location. The wells are near a water-table divide between Four Mile Creek and Pen Branch. Water in the upper saturated zone flows to the northwest toward Four Mile Creek from the northwestern part of the area and to the southeast from the southern part of the area, toward Pen Branch. Water elevations in well clusters NPM 1, 4, 19, and 34 show a potential for downward flow of groundwater from the upper saturated zone into the Congaree-Four Mile zone. Horizontal flow in the Congaree-Four Mile zone beneath the area is generally to the west, toward the Savannah River and Upper Three Runs Creek.

No radiological or chemical constituents were detected above DWS in the NPM wells. Several wells had elevated alkalinity (as CaCO_3), specific conductance, pH, and TDS (Table 8-97), indicating that water from these wells may be affected by well grout.

Road A Chemical Basin (Baxley Road)

The Road A Chemical Basin (Baxley Road: 904-111G) is approximately 2,600 ft west of the intersection of Road A and Road 6 (Figure 8-44) and about 2 miles southeast of the D-Area Powerhouse. Surface elevations across this location range from 190 to 220 ft msl, with surface drainage toward the southwest to the Savannah River Swamp. The nearest SRS boundary is about 3.5 miles to the west. The basin is reported to have received miscellaneous radioactive and chemical aqueous waste, but no records of the materials disposed of at the basin are available. The basin was closed and backfilled in 1973. It is currently part of the RFI/RI program.

The basin was monitored in 1991 by the five wells of the BRD series. Well BRD 3 was dry. Well BRD 4 is screened below the water table. Horizontal groundwater flow is to the west toward the Savannah River Swamp. Relative to the basin, well BRD 2 is sidegradient, wells BRD 1 and 5D are downgradient, and well BRD 4 is downgradient to sidegradient.

Total radium activity slightly above the DWS was detected in wells BRD 2 and 4 for the first time (Table 8-98). As in the past, well BRD 2 had concentrations of lead above the DWS during 1991. Concentrations of trichloroethylene and tetrachloroethylene reported above DWS in one and three wells, respectively, are considered anomalous; all of these results shared the same sampling date, and other analyses during the year for these same wells do not support such high values.

Sanitary Landfill

The Sanitary Landfill (740-G), opened in 1973, is southwest of Road C (Figure 8-45) about midway down the slope from the Aiken Plateau to Upper Three Runs Creek. Surface elevations across the landfill range from 170 to 220 ft msl, with surface drainage toward the southeast to Upper Three Runs Creek. The nearest SRS boundary is about 3.5 miles to the west. At the landfill, materials such as paper, plastics, rubber, wood, cardboard, rags, pesticide bags, empty cans, putrescible wastes, and asbestos in bags are placed in trenches, which are covered daily with soil. The landfill receives approximately 15,000 to 20,000 tons of waste per year. The landfill is operated under South Carolina Domestic Waste Permit No. 87A; it is part of the RFI/RI program.

Groundwater beneath the landfill was monitored by the 57 wells of the LFW series in 1991; 14 of these

wells monitored either the lower portion of the upper saturated zone or the Congaree-Four Mile zone. The remaining wells monitored the water table. Horizontal groundwater flow in the upper saturated zone and the Congaree-Four Mile zone is generally to the south toward Upper Three Runs Creek. Relative to the landfill, wells LFW 24, 25, 26, 27, 28, 29, 30, 31, 42 and well cluster 43 are upgradient. Wells LFW 6, 8, 19, 32, 33, 34, 36, 37, 38, 39, 40, 41, 44D, 45D, 46D, 56D, 58D, 60D, and clusters 47, 48, 55, 57, 59, 61, and 62 are downgradient, relative to the landfill. All other wells are located within the confines of the landfill. The vertical hydraulic gradient between the water table and the monitored portion of the Congaree-Four Mile zone is small to negligible indicating that horizontal flow toward Upper Three Runs Creek is dominant over vertical groundwater flow beneath the facility.

Activities of total radium and tritium and concentrations of chlorinated volatile organics, metals, and benzene exceeded DWS in numerous wells (Table 8-99), generally concentrating in the central and eastern portions of the landfill. Elevated alkalinity (as CaCO_3), specific conductance, and, to a lesser extent, TDS and concentrations above the DWS of fluoride were detected in these same wells. In addition, chlorinated volatile organics, particularly trichloroethylene, were present in levels exceeding DWS in many of the LFW wells monitoring the southern portion of the facility. Well LFW 59B had low pH.

Sewage Sludge Application Sites

The Sewage Sludge Application Sites were originally the subject of a research program using domestic sewage sludge to reclaim borrow pits and to enhance forest productivity at SRS beginning in 1980. After sludge was applied to the sites, hardwoods and pines were planted to identify the amount of wood biomass that could be produced using the sludge as a fertilizer and soil conditioner. Nine sites were permitted by SCDHEC for sludge application.

The following nine sites had sludge applied in 1980: the 40-Acre Hardwood Site, the K-Area Borrow Pit, the Kato Road Site, the Lower Kato Road Site, the Orangeburg Site, the Par Pond Borrow Pit, the Road F Site, the Sandy (Lucy) Site, and the Second Par Pond Borrow Pit. In 1988, the Central Shops Sanitary Sewage Sludge Lagoon was closed, and the lagoon sludge was applied to the K-Area and Par Pond Borrow Pits.

The Sewage Sludge Application Sites were monitored by 33 SSS series wells until 1988. New wells were

installed in F, H, and K Areas and at the Par Pond site in 1988, replacing 12 of the SSS wells. Descriptions of these new well series (FSS, HSS, KSS, and PSS) are provided under the F-Area, H-Area, K-Area, and General Areas sections, respectively. The F- and H-Area sites are the only remaining active sludge application sites. Sludge was disposed of at the F-Area site until third quarter 1990. Sludge is currently disposed of at the H-Area Sludge Land Application Site. The remaining Sewage Sludge Application Sites are located throughout SRS.

The 40-Acre Hardwood Sewage Sludge Application Site, located in the southwestern portion of SRS, is 1,500 ft south of the Road A Chemical Basin (Baxley Road) on the southwest side of Road A (Figure 8-44). Surface elevations across the site range from 160 to 200 ft msl, and surface drainage is toward the southwest to the Savannah River Swamp. The nearest SRS boundary is approximately 3.5 miles to the west.

The Kato Road Sewage Sludge Application Site lies in the western portion of SRS, 1,200 ft east of Road 2 and just southeast of Road C-2 (Figure 8-42). Surface elevations across the site range from 220 to 280 ft msl, with drainage toward the southeast to Upper Three Runs Creek. The nearest SRS boundary is approximately 3 miles to the west.

The Lower Kato Road Sewage Sludge Application Site, located in the western portion of SRS, is 1,800 ft east of Road 2 and adjacent to the Kato Road Sewage Sludge Application Site, which is to the north (Figure 8-42). Surface elevations across the site range from 220 to 250 ft msl. Surface drainage is toward the southeast to Upper Three Runs Creek. The nearest SRS boundary is about 3 miles to the west.

The Orangeburg Sewage Sludge Application Site is in the western portion of SRS, 3,000 ft south of Road C and 1,200 ft southwest of the Sanitary Landfill (Figure 8-45). Surface elevations across the site range from 200 to 220 ft msl, and surface drainage is toward the southeast to Upper Three Runs Creek. The nearest SRS boundary is about 4 miles to the west.

The Road F Sewage Sludge Application Site, in the northern portion of SRS, lies immediately north of the Road F and Road F-1 intersection (Figure 8-46). Surface elevations across the site range from 290 to 300 ft msl, with surface drainage toward Upper Three Runs Creek to the southeast. The nearest SRS boundary lies about 3.5 miles to the northwest.

The Sandy (Lucy) Sewage Sludge Application Site lies in the northwestern portion of SRS between Road 2 and Road F and southwest of the Road F Sewage Sludge Application Site (Figure 8-46). Surface elevations across the site range from 290 to 310 ft msl, and surface drainage is toward the south to Upper Three Runs Creek. The nearest SRS boundary is approximately 3 miles to the northwest.

The Second Par Pond Borrow Pit Sewage Sludge Application Site, located in the eastern portion of SRS, lies on the eastern edge of Par Pond 500 ft north of Road B (Figure 8-43). Surface elevations across the site range from 200 to 220 ft msl, with surface drainage toward the west to Par Pond and toward the south to Lower Three Runs Creek. The nearest SRS boundary is about 0.5 miles to the east.

These Sewage Sludge Application Sites were monitored in 1991 by wells of the SSS series. Wells SSS 7, 8, 9, and 11 were dry every time they were sampled during the year. Horizontal groundwater flow beneath the 40-Acre Hardwood Site (wells SSS 1, 2, and 3) is to the west. Groundwater flow beneath the Kato Road Site (wells SSS 19, 20, and 21) appears to be to the east-southeast. Groundwater flow beneath the Lower Kato Road Site (wells SSS 4, 5, and 6) appears to be to the southeast. There was insufficient data to determine accurately the horizontal groundwater flow direction at the Second Par Pond Borrow Pit Site (wells SSS 25, 26, and 27). No data were available to determine horizontal flow at the Orangeburg Site (wells SSS 7, 8, and 9), although other nearby measurements indicate a general southward flow. Insufficient data were available to determine precisely the direction of horizontal flow beneath either the Sandy (Lucy) Site (wells SSS 10, 11, and 12) or the Road F Site (wells SSS 22, 23, and 24); however, the horizontal flow in the upper saturated zone beneath the sites appears to be toward Upper Three Runs Creek to the south and southeast, respectively.

Total radium activity exceeded the DWS in well SSS 1 at the 40-Acre Hardwood Site in 1991 (Table 8-100); no radioactive or chemical constituents have been reported above DWS at this location during the previous three years. At the Lower Kato Road Site, gross alpha activity above the DWS was detected in well SSS 6, and total radium activity exceeded the DWS in wells SSS 5 and 6. Well SSS 6 also had concentrations of lead above the DWS, and well SSS 4 had elevated specific conductance. Total radium activity exceeded the DWS in well SSS 5 during 1988 and 1990; no chemical constituents have previously

been reported above DWS at this location. Wells monitoring the Orangeburg Site were dry at every sampling event during 1991. No radioactive or chemical constituents were detected above DWS during 1991 or in recent years at the Sandy (Lucy) Site; however, specific conductance remained elevated in well SSS 10. Activities of gross alpha and total radium exceeded DWS, for the first time in recent years, in well SSS 20 at the Kato Road Site during 1991. As in the past, no chemical constituents were detected above DWS at this location. No results for radioactive or chemical constituents exceeded DWS at the Road F Site; total radium activity exceeded the DWS in 1990 and was the only such result in recent years. Total radium activity exceeded the DWS in all three wells at the Second Par Pond Borrow Pit Site in 1991. In the past, gross alpha and total radium activities were detected above DWS in well SSS 27; no chemical constituents have exceeded DWS in recent years. Alkalinity (as CaCO_3) was elevated for the first time in well SSS 25, and specific conductance remained elevated in the same well.

TNX Area, located in the southwest part of SRS (Figure 8-22), is operated by SRL to test equipment prior to installation and to develop new designs. Surface elevations across TNX Area range from approximately 120 to 150 ft msl, decreasing to the west-southwest toward the Savannah River. The nearest SRS boundary is the Savannah River, approximately 0.25 miles to the west. The water table discharges to the Savannah River and to the nearby swamp. Figures 8-47 and 8-48 indicate the extent of the trichloroethylene plume beneath TNX Area.

In 1991, groundwater was monitored at the following locations in TNX Area:

New TNX Seepage Basin

The New TNX Seepage Basin (904-102T), located in the east section of the TNX facility and across River Road from the TNX process area (Figure 8-49), replaced the Old TNX Seepage Basin and operated from 1980 to 1988. This basin is part of the RFI/RI program. A waste-site assessment report and a groundwater quality assessment/corrective action feasibility plan have been submitted to SCDHEC for review.

The basin was monitored by the four wells of the YSB series in 1991. Horizontal groundwater flow beneath the basin is to the west toward the Savannah River Swamp. Relative to the basin, well YSB 2A is upgradient, well YSB 4A is downgradient, well YSB

3A is upgradient to sidegradient, and well YSB 1A is sidegradient to downgradient.

Total radium activity was reported above the DWS for the first time for wells YSB 3A and 4A (Table 8-101). As in the past, specific conductance was elevated in wells YSB 3A and 4A, and TDS remained elevated in well YSB 3A. No chemical constituents were detected above DWS during 1991.

Old TNX Seepage Basin

The Old TNX Seepage Basin (904-76T), in the southwest corner of the TNX facility (Figure 8-49), was in operation from 1958 to 1980 and received waste from pilot-scale tests conducted at TNX. In 1981, the basin wall was breached, and the impounded water was drained into the adjacent wetlands. The basin was then backfilled with a sand and clay mixture and the top capped with clay. This basin is part of the RFI/RI program.

The basin was monitored in 1991 by the seven wells of the XSB series. Wells XSB 1D, 2D, 3A, 4D, and 5A are water-table wells; well XSB 1B, screened between 75 and 65 ft msl, monitors the lower portion of the upper saturated zone; well XSB 1A, screened between 54 and 44 ft msl, monitors the Congaree-Four Mile zone. Horizontal flow at the water table beneath the basin is generally to the southwest toward the Savannah River Swamp. Relative to the basin, well XSB 1D is sidegradient, well XSB 3A is sidegradient to downgradient, and wells XSB 2D, 4D, and 5A are downgradient. Horizontal flow in the lower portion of the upper saturated zone and in the Congaree-Four Mile zone is probably southwest toward the Savannah River Swamp. A head reversal between the lower and upper portions of the upper saturated zone (wells XSB 1D and 1B) makes downward vertical flow of groundwater within this zone unlikely beneath this site and indicates horizontal flow toward the river and swamp to be the dominant flow direction in this zone. A downward vertical gradient exists between the lower portion of the upper saturated zone and the Congaree-Four Mile zone.

Monitoring results for 1991 are similar to those of past years. Total radium, radium isotopes, and Sr-90 were reported above DWS in at least one well (Table 8-102). Concentrations of chlorinated volatile organics, particularly trichloroethylene, were detected above DWS in all of the XSB wells screened at the water table. Mercury and nitrate were detected above DWS in one and two downgradient wells, respectively. Specific conductance was elevated in several wells, including the Congaree-Four Mile zone

well, which also had a single analysis of Ra-226 activity above the DWS. Elevated specific conductance, pH, and TDS in well XSB 2D suggest that water from the well may be affected by the leaching of well grout.

TNX-Area Assessment Wells

The TNX series wells are located west of River Road in TNX Area (Figure 8-49). These wells were installed to assess the lateral extent of the plume, primarily volatile organics, resulting from operations in TNX Area.

In 1991, 12 water-table wells of the TNX series monitored groundwater beneath TNX Area. The surface of the water table in this area is locally undulatory; however, horizontal flow is generally to the west toward the Savannah River Swamp. Wells TNX 1D, 8D, 9D, 10D, 11D, and 12D are downgradient of TNX Area. Wells TNX 6D and 7D are sidegradient of the area. Wells TNX 4D and 5D are downgradient of the New TNX Seepage Basin and upgradient of the Old TNX Seepage Basin. Well TNX 3D is centrally located and thus is downgradient of the TNX Burying Ground and downgradient to sidegradient of the New TNX Seepage Basin. Well TNX 2D is downgradient to sidegradient of the New TNX Seepage Basin and the TNX Burying Ground.

Activities exceeding DWS of numerous radioactive constituents, concentrations of chlorinated volatile organics and nitrate above DWS, and elevated specific conductance were reported for several centrally-located TNX wells (Table 8-103). Many of the same constituents also affected groundwater in downgradient wells located in the Savannah River Swamp to the southwest, although generally to a lesser extent. These downgradient wells also show consistent levels of trichloroethylene above the DWS. The pesticides, lindane and endrin, were not requested for analysis in 1990 when the TNX wells were first sampled but were detected above DWS in most wells in 1991. Elevated TDS was reported in well TNX 3D. These results are similar to those of last year.

TNX-Area Background Wells

In 1991, three wells of the P 26 well cluster provided background groundwater quality data for TNX Area. These wells are located near TNX Area, approximately 200 ft north of the intersection of River Road and Road 3 (Figure 8-49).

In 1991, the P 26 well cluster monitored groundwater from three zones. Well P 26A, screened between 31

and 21 ft msl, monitored the Congaree-Four Mile zone; well P 26B, screened between 81 and 71 ft msl, monitored the lower part of the upper saturated zone; and well P 26D, a water-table well, is screened between 121 and 101 ft msl. In all three zones, horizontal flow appears to be to the southwest toward the Savannah River Swamp. The cluster is generally sidegradient to upgradient of TNX Area. A head reversal exists between the Congaree-Four Mile zone and the lowermost upper saturated zone, reducing the potential for downward flow of groundwater into the Congaree-Four Mile zone in this vicinity.

Activities of Ra-226 and U-238 were detected above DWS in well P 26D (Table 8-104). Total radium activity exceeded the DWS in well P 26A, and Am-241 exceeded the DWS in wells P 26A and 26B. Total radium and U-238 activities were not reported above DWS in the P 26 well cluster in 1990, when the cluster was first sampled.

TNX Burying Ground

The TNX Burying Ground (643-5T) was built within the TNX operating fence to dispose of debris from an experimental evaporator that exploded at TNX in 1953 (Figure 8-49). The buried material included contaminated conduit, tin, drums, structural steel, and depleted uranium. Although most of this material was excavated and sent to the Radioactive Waste Burial Grounds between 1980 and 1984, an estimated 27 kg of uranyl nitrate remains buried at this location. The TNX Burying Ground is part of the CERCLA RI program.

In 1991, six wells of the TBG series monitored the water table beneath this facility. Well TBG 5A monitors the Congaree-Four Mile zone, and TBG 5B monitors the lower portion of the upper saturated zone. The water table here generally flows to the west. Relative to the burying ground, well TBG 7 is upgradient, and wells TBG 1 and 6 are downgradient. Wells TBG 3, 4, and 5 are within the boundaries of the facility. Water elevations from wells TBG 5 and 5B indicate an upward vertical gradient from the lower portion of the upper saturated zone to the water-table surface. This reduces the potential for vertical migration of groundwater into the deeper zones and suggests a predominantly horizontal movement within the upper saturated zone toward the Savannah River Swamp.

During 1991, as in previous years, total radium activity and concentrations of chlorinated volatile organics and nitrate were detected above DWS in

several wells (Table 8-105) located either within the facility or downgradient of the facility. Specific conductance was elevated for these same wells. Gross alpha activity exceeding the DWS was absent from this location in 1991, although it has been consistently reported in recent years. Radium-226 activity

continued to exceed the DWS in two wells during 1991; Ra-228 above the DWS also was reported for two wells, one of which monitors the lower portion of the upper saturated zone. As in the past, well TBG 4 had mercury concentrations exceeding the DWS and low pH.

Figure 8-12 Facilities monitored by the SRS monitoring well network, with areas that have constituents exceeding DWS detected in 1991.

KEY FOR Figure 8-12

Administration And Manufacturing Areas

1. A-Area Burning/Rubble Pits
2. A-Area Coal Pile Runoff Containment Basin
3. A-Area Metals Burning Pit
4. M-Area Hazardous Waste Management Facility
5. Metallurgical Laboratory Seepage Basin
6. Miscellaneous Chemical Basin
7. Motor Shop Oil Basin
8. Savannah River Laboratory Seepage Basins
9. Silverton Road Waste Site

Reactor Areas

C Area

10. C-Area Burning/Rubble Pit
11. C-Area Coal Pile Runoff Containment Basin
12. C-Area Disassembly Basin
13. C-Area Reactor Seepage Basins

K Area

14. K-Area Acid/Caustic Basin
15. K-Area Ash Basin
16. K-Area Burning/Rubble Pit
17. K-Area Coal Pile Runoff Containment Basin
18. K-Area Diesel Tank Spill
19. K-Area Disassembly Basin
20. K-Area Reactor Seepage Basin
21. K-Area Retention Basin
22. K-Area Sludge Land Application Site

L Area

23. L-Area Acid/Caustic Basin
24. L-Area Burning/Rubble Pit
25. L-Area Disassembly Basin
26. L-Area Oil and Chemical Basin
27. L-Area Reactor Seepage Basin

P Area

28. P-Area Acid/Caustic Basin
29. P-Area Burning/Rubble Pit
30. P-Area Coal Pile Runoff Containment Basin
31. P-Area Disassembly Basin
32. P-Area Reactor Seepage Basins

R Area

33. R-Area Acid/Caustic Basin
34. R-Area Burning/Rubble Pits
35. R-Area Disassembly Basin
36. R-Area Reactor Seepage Basins

Separations And Waste Management Areas

37. F-Area Acid/Caustic Basin
38. F-Area Burma Road Rubble Pit
39. F-Area Burning/Rubble Pits
40. F-Area Canyon Building and A-Line Uranium Recovery Facility
41. F-Area Coal Pile Runoff Containment Basin
42. F-Area Effluent Treatment Cooling Water Basin
43. F-Area Seepage Basins
44. F-Area Sludge Land Application Site
45. F-Area Tank Farm
46. H-Area Acid/Caustic Basin
47. H-Area Auxiliary Pump Pit
48. H-Area Canyon Building
49. H-Area Coal Pile Runoff Containment Basin
50. H-Area Effluent Treatment Cooling Water Basin

51. H-Area Retention Basins
52. H-Area Seepage Basins
53. H-Area Sludge Land Application Site
54. H-Area Tank Farm
55. M-Area Waste Disposal Facility (Y Area)
56. Old F-Area Seepage Basin
57. Radioactive Waste Burial Grounds
58. S-Area Defense Waste Processing Facility
59. S-Area Low Point Pump Pit
60. S-Area Vitrification Building
61. Z-Area Low Point Drain Tank
62. Z-Area Saltstone Facility

Other Areas

Central Shops Area

63. Central Shops Burning/Rubble Pits
64. Central Shops Burning/Rubble Pit South of the Ford Building Seepage Basin
65. Central Shops Diesel Spill
66. Fire Department Training Facility
67. Ford Building Seepage Basin
68. Hazardous Waste Storage Facility
69. Hydrofluoric Acid Spill

D Area

70. D-Area Burning/Rubble Pits
71. D-Area Coal Pile Runoff Containment Basin and Ash Basins
72. D-Area Oil Disposal Basin

General Areas

73. Chemicals, Metals, and Pesticides Pits
74. Interim Waste Technology Site B
75. Interim Waste Technology Site P
76. Interim Waste Technology Site Q
77. Par Pond Sludge Land Application Site
78. Road A Chemical Basin (Baxley Road)
79. P 29 Well Cluster in B Area
80. Potential New Production Reactor Site Characterization Wells (NPM)
81. Sanitary Landfill
82. Sewage Sludge Application Site, 40-Acre Hardwood
83. Sewage Sludge Application Site, Kato Road
84. Sewage Sludge Application Site, Lower Kato Road
85. Sewage Sludge Application Site, Orangeburg
86. Sewage Sludge Application Site, Road F
87. Sewage Sludge Application Site, Sandy (Lucy)
88. Sewage Sludge Application Site, Second Par Pond Borrow Pit

TNX Area

89. New TNX Seepage Basin
90. Old TNX Seepage Basin
91. TNX Burying Ground

Note: This key follows the order of the text descriptions in the Groundwater Monitoring Results section, with the following exceptions: the L-Area Research Wells, the P 14 Well Cluster, the P 28 Well Cluster, the Plume Definition Wells, the Z and ZW Wells, the Background Well Near Hawthorne Fire Tower, the TNX-Area Assessment Wells, and the TNX-Area Background Wells. These wells are not identified on Figure 8-12 and thus are omitted from the key. The shaded areas of the figure are the approximate limits of groundwater with constituents exceeding federal primary drinking water standards. Major constituents are given for selected sites.

Figure 8-13 Potentiometric surface and horizontal groundwater flow directions of the Congaree-Four Mile zone at SRS during the first quarter of 1991.

Figure 8-14 Potentiometric surface and horizontal ground flow directions of the Cretaceous zone at SRS during the first quarter of 1991.

Figure 8-15 Construction diagram for water table and deeper zone monitoring wells.

Figure 8-16 Correlation chart for hydrostratigraphic and geologic units at SRS.

Figure 8-17 Geologic cross section of Coastal Plain sediments at SRS.

Figure 8-18 Potentiometric map of the principal aquifer of Late Cretaceous age, October 1954, in the vicinity of SRS (after Siple, 1967, Plate 6).

Figure 8-19 Contoured elevation of the water table at the Separations and Waste Management areas, February 1991.

Figure 8-20 Generalized hydrostratigraphic cross section through the F-Area Seepage Basins (A-A' in Figure 8-19), showing general flow directions within and between the monitored zones.

Figure 8-21 Vertical gradient relationships between the Congaree-Four Mile and Cretaceous zones at SRS during the first quarter of 1991.

Figure 8-22 Areas and locations monitored for groundwater quality at SRS.

Figure 8-23 Groundwater monitoring at A and M areas and Silverton Road Waste Site.

Figure 8-25 General extent of trichloroethylene in groundwater at A and M areas. *Top*) Trichloroethylene concentrations above 1 mg/L beneath A and M areas. *Bottom*) Cut-away view of the trichloroethylene plume. The boundary between the light and dark blue regions represents the extent of trichloroethylene concentrations above DWS (0.005 mg/L). Prepared by WSRC Environmental Sciences Section.

Figure 8-26 Groundwater monitoring at C Area.

Figure 8-27 Groundwater monitoring at K Area.

Figure 8-28 Groundwater monitoring at L Area.

Figure 8-29 Groundwater monitoring at P Area.

Figure 8-30 Groundwater monitoring at R Area.

Figure 8-31 Separations and waste management areas and nearby wells monitored for groundwater quality at SRS.

Figure 8-32 Groundwater monitoring near F-Area Canyon Building and F-Area Tank Farm.

Figure 8-33 Groundwater monitoring near F-Area Seepage Basins and F-Area Tank Farm.

Figure 8-34 Groundwater monitoring at the central part of H Area.

Figure 8-35 Groundwater monitoring near the Radioactive Waste Burial Grounds and H-Area Seepage Basins.

Figure 8-36 Groundwater monitoring at S Area, Y Area, Z Area, and nearby locations.

Figure 8-37 Groundwater monitoring at the northern part of E Area and the Radioactive Waste Burial Grounds.

Figure 8-38 Groundwater monitoring at Central Shops Area.

Figure 8-39 Groundwater monitoring at D Area.

Figure 8-40 Groundwater monitoring at the Chemicals, Metals, and Pesticides Pits.

Figure 8-41 Groundwater monitoring at Interim Waste Technology Site B.

Figure 8-42 Groundwater monitoring at Interim Waste Technology Sites P and Q and the Kato Road and Lower Kato Road Sewage Sludge Application sites.

Figure 8-43 Groundwater monitoring at Par Pond.

Figure 8-44 Groundwater monitoring at the Road A Chemical Basin and the 40-Acre Hardwood Sewage Sludge Application Site.

Figure 8-45 Groundwater monitoring at the Sanitary Landfill and the Orangeburg Sewage Sludge Application Site.

Figure 8-46 Groundwater monitoring at Road F and Sandy (Lucy) Sewage Sludge Application sites.

Figure 8-47 Trichloroethylene concentrations at the water table beneath TNX Area. (a) Block diagram of TNX Area showing topography, water table elevations, and trichloroethylene concentrations in the Savannah River Swamp. (b) Trichloroethylene concentrations at the water table beneath TNX Area. The boundary between blue and green shading represents the extent of trichloroethylene above DWS.

Figure 8-48 Cut-away view of trichloroethylene plume beneath TNX Area, showing extent of plume above 0.05 mg/L in the upper saturated zone and Congaree-Four Mile zone beneath TNX Area.

Figure 8-49 Groundwater monitoring at TNX Area.

Table 8-1
Estimated Tritium Releases in SRS Streams and the Savannah River

DIRECT RELEASES (CURIES)							% of Total to River in 1991
Area	Release Point	1987	1988	1989	1990	1991	
Reactor							
100 P	Par Pond overflow to Lower-Three Runs Creek	490	327	(321) ^a	(207) ^a	221	
	Process sewer to Par Pond			164	67	(43) ^a	
	Reactor heat exchanger cooling water to Par Pond			464	125	(67) ^a	
100 L	L-Lake overflow to Steel Creek	520	502	(556) ^a	(358) ^a	723	
	Process sewer to L Lake			24	27	(11) ^a	
	Reactor heat exchanger coolingwater to L Lake			98	72	(112) ^a	
100 K	Process sewer to Pen Branch	68	264	100	169	74	
	Reactor heat exchanger coolingwater to Pen Branch		2,470	112	249	6,470 ^b	
	K—area secondary effluent					6	
100 C	Process Sewer to Four Mile Creek	4	11	16	1	13	
	Subtotal	2,722	3,570	978	710	7,510	27
Separations							
200 F	Effluent to Four Mile Creek	13	14	8	327	6	
	Effluent to Upper Three Runs			2	0	0	
200 H	Effluent to Four Mile Creek	204	12	20	22	14	
	Effluent to Upper Three Runs			1	4	5	
	Effluent Treatment Facility		101	2,070	1,200	3,070	
	Subtotal	217	127	3,100	1,550	3,090	11
400 D							
400 D	Process sewer to Beaver Dam Creek	1,380	1,740	562	358	681	
	Subtotal	1,380	1.7	562	358	681	2
Total Direct Releases		4,319	5,440	3,640	2,620	11,300	41

NOTE: Because of rounding, the sum of individual columns might not equal totals.

a Not used in totals because release has been counted elsewhere.

b Includes heat exchanger leak of Dec. 22-25, 1991.

Table 8-1
Estimated Tritium Releases in SRS Streams and the Savannah River, Cont'd.

MIGRATION (CURIES)							% of Total To River in 1991
Area	Release Point	1987	1988	1989	1990	1991	
200 F&H	Solid Waste Disposal Facility and H-Area seepage basin to Four Mile Creek	6,150	3,670	3,600	4,280	6,420	
	200-F seepage basin to Four Mile Creek	2,760	3,330	4,440	3,570	5,750	
	200-H seepage basin to Four Mile Creek	5,630	3,980	3,310	1,900	1,810	
100 C	Seepage basin to Four Mile Creek				7		
100 K	904-88G to Indian Grave Branch	3,600	2,780	2,220	3,560	2,160	
100 P	Seepage basin to Steel Creek	130	133	137	224	(364) ^a	
	Subtotal	18,270	13,900	13,700	13,500	16,100	59
	Total Direct Releases and Migration	22,589	19,300	17,300	16,100	27,400	100

STREAM TRANSPORT (CURIES)							% of Total To River in 1991
Area	Release Point	1987	1988	1989	1990	1991	
400 D	Beaver Dam Creek at swamp	1,270	2,510	879	756	801	3
200 F&H	Four Mile Creek at Road A13	12,960	11,200	11,200	9,370	13,300	50
100 K	Pen Branch at Road A	4,450	3,220	2,700	2,510	7,100	27
100 L	Steel Creek at Road A	640	502	556	358	723	3
100 P	Lower Three Runs at Road B	490	327	321	207	221	1
ETF	Upper Three Runs at Road A	720	535	2,160	2,380	4,410	16
	Subtotal	20,530	18,300	17,800	15,600	26,600	97

NOTE: Because of rounding, the sum of individual columns might not equal totals.

RIVER TRANSPORT (CURIES)							% of Total To River in 1991
Area	Release Point	1987	1988	1989	1990	1991	
	Tritium measured in the Savannah River below SRS			17,110	16,570	28,700	
	Tritium measured in the Savannah River above SRS			1,480	2,080	2,420	
	Tritium measured in the Savannah River below SRS (downriver minus upriver)	26,150	14,600	15,600	14,490	26,300	96

^a Not used in totals because release has been counted elsewhere.

Table 8-2
Calculated Migration of Radioactivity from Seepage Basins

Location	Source Description	Tritium (Curies)		% Difference 1990 to 1991
		1990	1991	
FMA7-(FM3A+FM2B)	200-F seepage basins to Four Mile Creek	3570	5750	+61%
FM2B-FM1C	200-H seepage basins to Four Mile Creek	1900	1810	-5%
FM3A-FM3	200-H Seepage Basin #4 and Solid Waste Disposal Facility to Four Mile Creek	4280	6420	+50%
IGB21	K-Area Retention Basin to Indian Grave Branch	3560	2160	-39%
SC2A	100-P Seepage Basin to Steel Creek	224	364	+63%
Twin Lakes	100-C Seepage Basin to Four Mile Creek	7	a	—

Location	Source Description	Total Strontium (Millicuries)		% Difference 1990 to 1991
		1990	1991	
FMA7-(FM3A+FM2B)	200-F seepage basins to Four Mile Creek	163	460	+182%
FM2B-FM1C	200-H seepage basins to Four Mile Creek	53	54	+2%

a Dam failure in August 1991 caused destruction of the Twin Lakes Flow Station.

— Not calculated.

Table 8-3
Radioactivity in Transport at Sample Points on Four Mile Creek

Location	Tritium (Curies)		Ratio 1990/1991
	1990	1991	
FM3	327	6	54.5 ^a
FM1C	18	11	1.64
FM1B	8	5	1.60
FM2	476	456	1.04
FM2B	1920	1820	1.05
FM3A	4610	6430	0.72
FMA7	10100	14000	0.72
FM6	9370	13300	0.70

Location	Total Strontium (Millicuries)		Ratio 1990/1991
	1990	1991	
FM3	4	4	1.00
FM1C	1	3	0.33
FM1B	1	1	1.00
FM2	18	51	0.35
FM2B	54	83	0.65
FM3A	4	4	1.00
FMA7	221	547	0.40
FM6	192	377	0.51

Location	Cesium-137 (Millicuries) ^b		Ratio 1990/1991
	1990	1991	
FM3	2	1	2.00
FM1C	15	6	2.50
FM1B	25	2	12.5
FM2	71	44	1.61
FM2B	71	60	1.18

a The tritium source term attributed to FM3 in 1990 was high in part because of a suspect sample that appeared to be switched with FM3A, whose average tritium concentration is much higher.

b Cesium-137, which EMS labs can routinely detect at 20 pCi/L per typical sample aliquot and counting time, was not detected at sample locations FM3A, FMA7, and FM6 in 1991. The results shown reflect only positive detectable values.

Table 8-4
Maximum Individual Committed Dose from Liquid Releases

By Pathway

Pathway	Individual Dose, mrem^a	Percent of Total Dose
Fish	2.40E-01	71.31
Invertebrate	1.88E-02	5.59
Water	7.70E-02	22.88
Shoreline	7.79E-04	0.23
Swimming	5.14E-07	0.0002
Boating	6.07E-07	0.0002
Total	3.37E-01	

By Radionuclide

Radionuclide	Individual Dose, mrem^a	Percent of Total Dose
H-3	7.32E-02	21.74
Sr-90	1.46E-02	4.35
I-129	4.60E-04	0.14
Cs-137	2.36E-01	70.07
Pm-147	5.97E-06	0.00
U-235,238	7.10E-05	0.02
Pu-239	1.15E-02	3.41
Total	3.37E-01	

^a Effective dose equivalent.

Table 8-5
Individual Committed Dose from Public Water Supplies at Beaufort-Jasper

Average Consumption

Radionuclide	Individual Dose, mrem^a	Percent of Total Dose
H-3	3.68E-02	89.40
Sr-90	1.67E-03	4.06
I-129	1.31E-04	0.32
Cs-137	7.13E-04	1.73
Pm-147	1.34E-07	0.0003
U-235,238	1.59E-05	0.04
Pu-239	1.85E-03	4.48
Total	4.12E-02	

Maximum Consumption

Radionuclide	Individual Dose, mrem^a	Percent of Total Dose
H-3	7.26E-02	89.40
Sr-90	3.30E-03	4.06
I-129	2.59E-04	0.32
Cs-137	1.40E-03	1.73
Pm-147	2.65E-07	0.0003
U-235,238	3.13E-05	0.04
Pu-239	3.64E-03	4.48
Total	8.12E-02	

^a Committed effective dose equivalent.

Table 8-6
Individual Committed Dose from Public Water Supplies at Port Wentworth

Average Consumption

Radionuclide	Individual Dose, mrem^a	Percent of Total Dose
H-3	4.47E-02	89.40
Sr-90	2.03E-03	4.06
I-129	1.60E-04	0.32
Cs-137	8.65E-04	1.73
Pm-147	1.63E-07	0.0003
U-235,238	1.93E-05	0.04
Pu-239	2.24E-03	4.48
Total	5.00E-02	

Maximum Consumption

Radionuclide	Individual Dose, mrem^a	Percent of Total Dose
H-3	8.82E-02	89.40
Sr-90	4.01E-03	4.06
I-129	3.15E-04	0.32
Cs-137	1.71E-03	1.73
Pm-147	3.22E-07	0.0003
U-235,238	3.81E-05	0.04
Pu-239	4.42E-03	4.48
Total	9.87E-02	

^a Committed effective dose equivalent.

Table 8-7
Collective Dose from Liquid Releases

By Pathway

Pathway	Collective Dose person-rem^a	Percent of Total Dose
Sport fish	3.87E-01	11.98
Commercial fishing	3.39E-03	0.10
Beaufort-Jasper	2.06E+00	63.79
Port Wentworth	7.50E-01	23.22
Salt water inversion	2.52E-04	0.01
Recreation-Savannah River	2.88E-02	0.89
Total	3.23E+00	

By Radionuclide

Radionuclide	Collective Dose person-rem^a	Percent of Total Dose
H-3	2.52E+00	77.95
Sr-90	1.23E-01	3.80
I-129	9.36E-03	0.29
Cs-137	4.52E-01	13.99
Pm-147	9.79E-06	0.0003
U-235,238	1.09E-03	0.03
Pu-239	1.27E-01	3.94
Total	3.23E+00	

^a Effective dose equivalent.

Table 8-8
Potential Doses from Irrigation Pathway

Effective Dose Equivalent

Food Type	Maximum Individual Dose mrem	Collective Dose person-rem^a
Vegetation	9.35E-02	5.83E+00
Leafy vegetable	1.46E-02	3.76E-01
Milk	4.72E-02	6.43E+00
Meat	1.55E-02	8.31E-01
Total	1.71E-01	1.35E+01

---

a Acreage for each food type is assumed to be 1,000 acres.

Table 8-9
Radioactivity in Savannah River Water

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha ($\mu\text{Ci/mL}$)				
Control				
GDNR R2	12	$3.03 \pm 2.25 \text{ E-10}$	$-1.36 \pm 2.03 \text{ E-10}$	$0.24 \pm 1.68 \text{ E-10}$
River 2	49	$4.32 \pm 3.08 \text{ E-10}$	$-2.39 \pm 1.63 \text{ E-10}$	$0.07 \pm 1.74 \text{ E-10}$
Savannah River				
GDNR R3B	13	$5.86 \pm 3.14 \text{ E-10}$	$-1.14 \pm 1.89 \text{ E-10}$	$0.89 \pm 1.96 \text{ E-10}$
River 10A	51	$5.16 \pm 2.72 \text{ E-10}$	$-2.34 \pm 1.49 \text{ E-10}$	$0.04 \pm 1.65 \text{ E-10}$
River 10B	47	$6.62 \pm 3.12 \text{ E-10}$	$-2.35 \pm 1.58 \text{ E-10}$	$0.89 \pm 2.11 \text{ E-10}$
River 3A above Vogtle	48	$6.97 \pm 3.29 \text{ E-10}$	$-2.47 \pm 1.67 \text{ E-10}$	$-0.23 \pm 2.00 \text{ E-10}$
River 3B below Vogtle	48	$7.24 \pm 3.51 \text{ E-10}$	$-2.32 \pm 1.55 \text{ E-10}$	$0.87 \pm 2.23 \text{ E-10}$
River 8A below Steel Creek	24	$4.33 \pm 2.63 \text{ E-10}$	$-2.12 \pm 1.37 \text{ E-10}$	$-0.16 \pm 1.35 \text{ E-10}$
River 8B below Steel Creek	24	$5.20 \pm 2.72 \text{ E-10}$	$-2.38 \pm 1.49 \text{ E-10}$	$0.16 \pm 1.95 \text{ E-10}$
River 8C below Little Hell Landing	24	$1.05 \pm 0.10 \text{ E-08}$	$-2.45 \pm 1.67 \text{ E-10}$	$0.48 \pm 2.14 \text{ E-09}$
Nonvolatile Beta ($\mu\text{Ci/mL}$)				
Control				
GDNR R2	12	$3.03 \pm 0.57 \text{ E-09}$	$1.52 \pm 0.53 \text{ E-09}$	$2.10 \pm 0.39 \text{ E-09}$
River 2	49	$4.68 \pm 0.64 \text{ E-09}$	$7.75 \pm 4.44 \text{ E-10}$	$2.16 \pm 0.77 \text{ E-09}$
Savannah River				
GDNR R3B	13	$2.92 \pm 0.40 \text{ E-09}$	$1.04 \pm 0.44 \text{ E-09}$	$2.02 \pm 0.52 \text{ E-09}$
River 10A	51	$4.65 \pm 1.02 \text{ E-09}$	$5.81 \pm 4.11 \text{ E-10}$	$2.05 \pm 0.68 \text{ E-09}$
River 10B	47	$3.40 \pm 0.57 \text{ E-09}$	$1.13 \pm 0.47 \text{ E-09}$	$2.18 \pm 0.55 \text{ E-09}$
River 3A above Vogtle	48	$4.53 \pm 1.01 \text{ E-09}$	$-2.34 \pm 3.51 \text{ E-10}$	$1.99 \pm 0.75 \text{ E-09}$
River 3B below Vogtle	48	$5.46 \pm 1.06 \text{ E-09}$	$1.14 \pm 0.48 \text{ E-09}$	$2.23 \pm 0.70 \text{ E-09}$
River 8A below Steel Creek	24	$4.03 \pm 0.99 \text{ E-09}$	$1.04 \pm 0.44 \text{ E-09}$	$1.94 \pm 0.60 \text{ E-09}$
River 8B	24	$2.95 \pm 0.57 \text{ E-09}$	$1.19 \pm 0.48 \text{ E-09}$	$2.00 \pm 0.55 \text{ E-09}$
River 8C below Little Hell Landing	24	$3.11 \pm 0.94 \text{ E-09}$	$7.84 \pm 4.25 \text{ E-10}$	$1.95 \pm 0.62 \text{ E-09}$

Table 8-9
Radioactivity in Savannah River Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Tritium ($\mu\text{Ci/mL}$)				
Control				
GDNR R2	12	$1.03 \pm 0.18 \text{ E-06}$	$-0.57 \pm 1.03 \text{ E-07}$	$4.24 \pm 3.20 \text{ E-07}$
River 2	52	$1.07 \pm 0.15 \text{ E-06}$	$-4.71 \pm 9.12 \text{ E-08}$	$4.06 \pm 3.11 \text{ E-07}$
Savannah River				
GDNR R3B	13	$1.57 \pm 0.15 \text{ E-06}$	$2.72 \pm 1.06 \text{ E-07}$	$7.87 \pm 3.65 \text{ E-07}$
River 10A	53	$3.15 \pm 0.03 \text{ E-05}$	$5.53 \pm 0.96 \text{ E-07}$	$3.25 \pm 4.61 \text{ E-06}$
River 10B	51	$3.15 \pm 0.03 \text{ E-05}$	$3.96 \pm 0.95 \text{ E-07}$	$3.07 \pm 4.21 \text{ E-06}$
River 3A above Vogtle	51	$4.50 \pm 0.18 \text{ E-06}$	$1.26 \pm 0.20 \text{ E-07}$	$1.05 \pm 0.87 \text{ E-06}$
River 3B below Vogtle	52	$4.68 \pm 0.13 \text{ E-06}$	$4.36 \pm 9.31 \text{ E-08}$	$1.15 \pm 1.02 \text{ E-06}$
River 8A below Steel Creek	26	$4.08 \pm 0.18 \text{ E-06}$	$4.71 \pm 1.15 \text{ E-07}$	$1.90 \pm 0.85 \text{ E-06}$
River 8C below Little Hell Landing	26	$4.76 \pm 0.18 \text{ E-06}$	$6.00 \pm 0.30 \text{ E-07}$	$2.33 \pm 1.05 \text{ E-06}$
Sr-89,90 ($\mu\text{Ci/mL}$)				
Savannah River				
River 8A below Steel Creek	9	$1.07 \pm 0.88 \text{ E-09}$	$-2.00 \pm 4.07 \text{ E-10}$	$4.04 \pm 4.27 \text{ E-10}$
River 8B below Steel Creek	8	$1.13 \pm 0.54 \text{ E-09}$	$0.14 \pm 6.20 \text{ E-10}$	$5.05 \pm 3.23 \text{ E-10}$
River 8C below Little Hell Landing	7	$5.66 \pm 4.93 \text{ E-10}$	$-2.15 \pm 5.49 \text{ E-10}$	$1.21 \pm 2.92 \text{ E-10}$
Sr-90 ($\mu\text{Ci/mL}$)				
Control				
GDNR R2	12	$5.91 \pm 0.23 \text{ E-10}$	$-1.18 \pm 1.29 \text{ E-11}$	$1.63 \pm 1.75 \text{ E-10}$
Savannah River				
River 10A	12	$3.20 \pm 0.26 \text{ E-10}$	$2.23 \pm 0.96 \text{ E-11}$	$1.37 \pm 0.90 \text{ E-10}$
River 3A above Vogtle	12	$2.50 \pm 1.00 \text{ E-10}$	$-1.38 \pm 0.21 \text{ E-10}$	$1.14 \pm 1.04 \text{ E-10}$
River 3B below Vogtle	12	$2.40 \pm 0.13 \text{ E-10}$	$2.35 \pm 0.48 \text{ E-11}$	$1.22 \pm 0.73 \text{ E-10}$

Table 8-9
Radioactivity in Savannah River Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Cs-137 ($\mu\text{Ci/mL}$)				
Control				
River 2	46 / 0 ^a			
Savannah River				
River 2 ^b	18 / 18	$3.00 \pm 4.00 \text{ E-11}$	$4.00 \pm 2.00 \text{ E-12}$	$1.12 \pm 0.65 \text{ E-11}$
River 10 ^b	33 / 33	$8.40 \pm 1.75 \text{ E-11}$	$1.10 \pm 0.12 \text{ E-11}$	$4.93 \pm 2.20 \text{ E-11}$
River 3A above Vogtle	46 / 0			
River 3B below Vogtle	48 / 0			
River 10 (Highway 301)	46 / 0			
Pu-238 ($\mu\text{Ci/mL}$)				
Control				
River 2	11	$1.39 \pm 0.22 \text{ E-11}$	$-1.23 \pm 1.17 \text{ E-09}$	$-1.10 \pm 3.71 \text{ E-10}$
Savannah River				
River 10A	10	$3.63 \pm 2.19 \text{ E-12}$	$-7.96 \pm 8.40 \text{ E-13}$	$0.28 \pm 1.26 \text{ E-12}$
River 3A above Vogtle	9	$9.88 \pm 2.20 \text{ E-12}$	$-2.35 \pm 0.91 \text{ E-12}$	$1.02 \pm 3.68 \text{ E-12}$
River 3B below Vogtle	10	$1.57 \pm 1.22 \text{ E-12}$	$-1.40 \pm 1.61 \text{ E-12}$	$-2.04 \pm 9.42 \text{ E-13}$
Pu-239 ($\mu\text{Ci/mL}$)				
Control				
River 2	11	$7.79 \pm 1.91 \text{ E-12}$	$-0.35 \pm 1.05 \text{ E-12}$	$1.03 \pm 2.29 \text{ E-12}$
Savannah River				
River 10A	10	$3.08 \pm 1.26 \text{ E-12}$	$-3.46 \pm 6.00 \text{ E-13}$	$0.70 \pm 1.05 \text{ E-12}$
River 3A above Vogtle	9	$4.05 \pm 1.33 \text{ E-12}$	$-7.38 \pm 7.38 \text{ E-13}$	$0.64 \pm 1.58 \text{ E-12}$
River 3B below Vogtle	10	$5.97 \pm 3.45 \text{ E-12}$	$-6.17 \pm 3.56 \text{ E-13}$	$1.08 \pm 2.07 \text{ E-12}$

- ^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.
- ^b Samples counted by SRL.

Table 8-10
Radioactivity in SRS Stream Water

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha ($\mu\text{Ci/mL}$)				
Background				
U3R-1A	50	$7.80 \pm 0.86 \text{ E-09}$	$0.02 \pm 1.18 \text{ E-10}$	$3.26 \pm 1.30 \text{ E-09}$
Edisto River	46	$2.53 \pm 0.51 \text{ E-09}$	$3.73 \pm 2.27 \text{ E-10}$	$1.31 \pm 0.58 \text{ E-09}$
Four Mile Creek				
FMC-1B	49	$2.42 \pm 0.54 \text{ E-09}$	$0.81 \pm 2.82 \text{ E-10}$	$1.06 \pm 0.61 \text{ E-09}$
FMC-1C	49	$4.78 \pm 0.72 \text{ E-09}$	$-1.32 \pm 2.31 \text{ E-10}$	$1.65 \pm 1.02 \text{ E-09}$
FMC-2B	25	$1.53 \pm 0.48 \text{ E-09}$	$-3.59 \pm 1.44 \text{ E-10}$	$3.25 \pm 5.21 \text{ E-10}$
FMC-2	25	$1.90 \pm 0.47 \text{ E-09}$	$-0.06 \pm 2.44 \text{ E-10}$	$5.33 \pm 4.10 \text{ E-10}$
FMC-3A	20	$1.69 \pm 0.49 \text{ E-09}$	$-0.21 \pm 1.88 \text{ E-10}$	$7.00 \pm 4.56 \text{ E-10}$
FMC-3	48	$4.25 \pm 0.70 \text{ E-09}$	$0.91 \pm 2.73 \text{ E-10}$	$1.43 \pm 1.07 \text{ E-09}$
FMC-6	27	$1.16 \pm 0.39 \text{ E-09}$	$-1.08 \pm 2.10 \text{ E-10}$	$3.17 \pm 3.11 \text{ E-10}$
FMC-A7	20	$1.66 \pm 0.46 \text{ E-09}$	$-1.81 \pm 2.07 \text{ E-10}$	$5.96 \pm 4.85 \text{ E-10}$
HP-50	27	$5.32 \pm 0.74 \text{ E-09}$	$8.86 \pm 3.36 \text{ E-10}$	$2.93 \pm 1.21 \text{ E-09}$
HP-52	24	$5.44 \pm 0.82 \text{ E-09}$	$2.65 \pm 2.55 \text{ E-10}$	$2.80 \pm 1.32 \text{ E-09}$
Indian Grave Branch				
IGB-21	4	$3.95 \pm 2.76 \text{ E-10}$	$-0.85 \pm 1.51 \text{ E-10}$	$1.71 \pm 2.12 \text{ E-10}$
Lower Three Runs Creek				
L3R-1A	14	$2.84 \pm 2.16 \text{ E-10}$	$-2.00 \pm 1.28 \text{ E-10}$	$0.56 \pm 1.41 \text{ E-10}$
L3R-2	25	$5.72 \pm 3.13 \text{ E-10}$	$-2.08 \pm 1.35 \text{ E-10}$	$0.80 \pm 2.30 \text{ E-10}$
L3R-3	12	$5.10 \pm 3.09 \text{ E-10}$	$-0.04 \pm 1.83 \text{ E-10}$	$1.91 \pm 1.55 \text{ E-10}$
Beaver Dam Creek				
400-D	43	$7.35 \pm 4.49 \text{ E-10}$	$-4.28 \pm 2.96 \text{ E-10}$	$0.46 \pm 3.23 \text{ E-10}$
Par Pond				
100-R Effluent	52	$1.08 \pm 0.35 \text{ E-09}$	$-2.83 \pm 1.54 \text{ E-10}$	$1.61 \pm 2.66 \text{ E-10}$
Pen Branch				
K-10	51	$6.32 \pm 2.97 \text{ E-10}$	$-2.70 \pm 2.46 \text{ E-10}$	$0.80 \pm 1.90 \text{ E-10}$
Pen Branch #3	21	$7.68 \pm 3.05 \text{ E-10}$	$-1.10 \pm 1.90 \text{ E-10}$	$1.43 \pm 2.36 \text{ E-10}$
Savannah River Swamp				
TNX ETP	27	$2.78 \pm 0.82 \text{ E-09}$	$-1.98 \pm 1.90 \text{ E-10}$	$8.47 \pm 7.14 \text{ E-10}$
Steel Creek				
SC-2A	21	$1.42 \pm 0.40 \text{ E-09}$	$-0.12 \pm 2.34 \text{ E-10}$	$4.31 \pm 3.93 \text{ E-10}$
SC-4	22	$3.06 \pm 2.27 \text{ E-10}$	$-1.97 \pm 1.26 \text{ E-10}$	$-0.33 \pm 1.25 \text{ E-10}$

Table 8-10
Radioactivity in SRS Stream Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Tims Branch				
TB-2	51	$1.68 \pm 0.53 \text{ E-09}$	$0.02 \pm 2.00 \text{ E-10}$	$5.85 \pm 3.66 \text{ E-10}$
TB-3 (ISCO)	32	$2.40 \pm 0.89 \text{ E-09}$	$-4.16 \pm 4.81 \text{ E-10}$	$6.31 \pm 6.15 \text{ E-10}$
TB-3 (Trebler)	14	$3.27 \pm 0.91 \text{ E-09}$	$1.21 \pm 0.72 \text{ E-09}$	$2.35 \pm 0.59 \text{ E-09}$
TB-5	27	$2.76 \pm 0.55 \text{ E-09}$	$4.25 \pm 2.97 \text{ E-10}$	$1.29 \pm 0.56 \text{ E-09}$
U3R				
Crouch Branch	26	$2.03 \pm 0.70 \text{ E-09}$	$-3.74 \pm 2.60 \text{ E-10}$	$4.96 \pm 6.07 \text{ E-10}$
HP-15	49	$3.68 \pm 0.71 \text{ E-09}$	$-1.41 \pm 0.39 \text{ E-09}$	$1.26 \pm 0.93 \text{ E-09}$
McQueens Branch	22	$1.36 \pm 0.41 \text{ E-09}$	$0.79 \pm 2.03 \text{ E-10}$	$5.84 \pm 3.60 \text{ E-10}$
U3R-2A	50	$1.01 \pm 0.50 \text{ E-08}$	$-4.50 \pm 2.93 \text{ E-09}$	$-0.65 \pm 2.65 \text{ E-09}$
U3R-2	51	$8.34 \pm 0.90 \text{ E-09}$	$4.46 \pm 2.76 \text{ E-10}$	$2.09 \pm 1.35 \text{ E-09}$
U3R-3	26	$3.92 \pm 0.61 \text{ E-09}$	$8.73 \pm 3.02 \text{ E-10}$	$2.09 \pm 0.78 \text{ E-09}$
U3R-4	26	$3.41 \pm 0.57 \text{ E-09}$	$2.72 \pm 2.40 \text{ E-10}$	$1.54 \pm 0.88 \text{ E-09}$
U3R-F3	50	$5.68 \pm 1.51 \text{ E-09}$	$-3.99 \pm 5.75 \text{ E-10}$	$1.31 \pm 1.23 \text{ E-09}$
Nonvolatile Beta ($\mu\text{Ci/mL}$)				
Background				
U3R-1A	50	$4.92 \pm 0.65 \text{ E-09}$	$2.27 \pm 3.95 \text{ E-10}$	$2.63 \pm 0.89 \text{ E-09}$
Edisto River	46	$4.46 \pm 0.61 \text{ E-09}$	$8.51 \pm 4.61 \text{ E-10}$	$2.19 \pm 0.77 \text{ E-09}$
Four Mile Creek				
FMC-1B	49	$2.72 \pm 0.14 \text{ E-08}$	$5.56 \pm 0.72 \text{ E-09}$	$1.43 \pm 0.46 \text{ E-08}$
FMC-1C	49	$4.95 \pm 0.05 \text{ E-07}$	$5.16 \pm 0.67 \text{ E-09}$	$2.79 \pm 7.22 \text{ E-08}$
FMC-2B	25	$8.13 \pm 0.23 \text{ E-08}$	$2.22 \pm 0.12 \text{ E-08}$	$4.10 \pm 1.59 \text{ E-08}$
FMC-2	25	$9.08 \pm 0.22 \text{ E-08}$	$8.86 \pm 0.78 \text{ E-09}$	$2.64 \pm 1.87 \text{ E-08}$
FMC-3A	20	$4.41 \pm 0.16 \text{ E-08}$	$3.73 \pm 0.60 \text{ E-09}$	$8.99 \pm 8.75 \text{ E-09}$
FMC-3	48	$1.42 \pm 0.02 \text{ E-07}$	$3.05 \pm 0.55 \text{ E-09}$	$1.17 \pm 2.00 \text{ E-08}$
FMC-6	27	$3.12 \pm 0.14 \text{ E-08}$	$1.36 \pm 0.09 \text{ E-08}$	$2.15 \pm 0.43 \text{ E-08}$
FMC-A7	20	$6.57 \pm 0.21 \text{ E-08}$	$2.95 \pm 0.13 \text{ E-08}$	$4.26 \pm 0.99 \text{ E-08}$
HP-50	27	$8.76 \pm 0.78 \text{ E-09}$	$1.85 \pm 0.50 \text{ E-09}$	$5.03 \pm 1.54 \text{ E-09}$
HP-52	24	$6.49 \pm 0.19 \text{ E-08}$	$7.53 \pm 0.77 \text{ E-09}$	$2.05 \pm 1.29 \text{ E-08}$
Indian Grave Branch				
IGB-21	4	$1.74 \pm 0.50 \text{ E-09}$	$5.78 \pm 4.21 \text{ E-10}$	$1.30 \pm 0.53 \text{ E-09}$
Lower Three Runs Creek				
L3R-1A	14	$5.92 \pm 0.71 \text{ E-09}$	$2.29 \pm 0.52 \text{ E-09}$	$3.86 \pm 1.06 \text{ E-09}$

Table 8-10
Radioactivity in SRS Stream Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
L3R-2	25	5.14 $\pm$ 0.76 E-09	8.35 $\pm$ 4.26 E-10	3.38 $\pm$ 0.99 E-09
L3R-3	12	4.70 $\pm$ 0.64 E-09	2.70 $\pm$ 0.54 E-09	3.77 $\pm$ 0.53 E-09
Beaver Dam Creek				
400-D	43	4.61 $\pm$ 1.03 E-09	-2.66 $\pm$ 7.47 E-10	2.31 $\pm$ 0.94 E-09
Par Pond				
100-R Effluent	52	2.04 $\pm$ 0.11 E-08	6.73 $\pm$ 0.71 E-09	1.16 $\pm$ 0.38 E-08
Pen Branch				
K-10	26	5.59 $\pm$ 0.69 E-09	-1.62 $\pm$ 0.49 E-09	2.22 $\pm$ 0.80 E-09
Pen Branch #3	21	3.02 $\pm$ 0.60 E-09	1.10 $\pm$ 0.51 E-09	2.25 $\pm$ 0.55 E-09
Savannah River Swamp				
TNX Effluent	27	7.95 $\pm$ 1.20 E-09	1.96 $\pm$ 0.50 E-09	4.65 $\pm$ 1.43 E-09
Steel Creek				
SC-2A	21	8.57 $\pm$ 0.80 E-09	2.44 $\pm$ 0.55 E-09	5.04 $\pm$ 1.69 E-09
SC-4	22	3.16 $\pm$ 0.56 E-09	9.97 $\pm$ 4.51 E-10	2.03 $\pm$ 0.49 E-09
Tims Branch				
TB-2	51	2.91 $\pm$ 0.56 E-09	2.56 $\pm$ 3.93 E-10	1.36 $\pm$ 0.52 E-09
TB-3 (ISCO)	32	8.05 $\pm$ 1.56 E-09	-0.88 $\pm$ 1.14 E-09	2.96 $\pm$ 1.95 E-09
TB-3 (Trebler)	14	6.73 $\pm$ 1.49 E-09	2.07 $\pm$ 1.17 E-09	4.53 $\pm$ 1.32 E-09
TB-5	27	4.59 $\pm$ 0.63 E-09	1.41 $\pm$ 0.48 E-09	3.03 $\pm$ 0.87 E-09
U3R				
Crouch Branch	26	6.16 $\pm$ 1.12 E-09	1.16 $\pm$ 0.82 E-09	2.87 $\pm$ 1.34 E-09
HP-15	49	5.22 $\pm$ 0.65 E-09	-2.70 $\pm$ 0.53 E-09	2.85 $\pm$ 1.32 E-09
McQueens Branch	22	3.40 $\pm$ 0.61 E-09	9.84 $\pm$ 4.49 E-10	2.07 $\pm$ 0.59 E-09
U3R-2A	50	2.08 $\pm$ 0.16 E-07	-1.19 $\pm$ 0.75 E-08	1.88 $\pm$ 3.77 E-08
U3R-2	51	5.26 $\pm$ 0.14 E-07	2.59 $\pm$ 0.55 E-09	3.03 $\pm$ 7.59 E-08
U3R-3	26	3.11 $\pm$ 0.56 E-09	1.09 $\pm$ 0.45 E-09	2.07 $\pm$ 0.54 E-09
U3R-4	26	3.08 $\pm$ 0.55 E-09	8.76 $\pm$ 4.41 E-10	1.73 $\pm$ 0.57 E-09
U3R-F3	50	4.67 $\pm$ 0.37 E-08	0.50 $\pm$ 1.31 E-09	6.82 $\pm$ 6.70 E-09
Tritium (μCl/mL)				
Background				
U3R-1A	51	1.57 $\pm$ 0.45 E-06	0.34 $\pm$ 2.67 E-07	9.18 $\pm$ 3.65 E-07
Edisto River	52	3.17 $\pm$ 3.46 E-06	0.68 $\pm$ 1.05 E-07	5.53 $\pm$ 4.46 E-07

Table 8-10
Radioactivity in SRS Stream Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Four Mile Creek				
FMC-1B	52	$1.13 \pm 0.05 \text{ E-05}$	$1.79 \pm 0.42 \text{ E-06}$	$5.71 \pm 2.63 \text{ E-06}$
FMC-1C	52	$5.00 \pm 0.11 \text{ E-05}$	$3.15 \pm 0.45 \text{ E-06}$	$1.54 \pm 1.07 \text{ E-05}$
FMC-2	27	$1.17 \pm 0.02 \text{ E-04}$	$1.68 \pm 0.06 \text{ E-05}$	$5.55 \pm 2.56 \text{ E-05}$
FMC-2B	27	$4.11 \pm 0.07 \text{ E-04}$	$1.48 \pm 0.07 \text{ E-04}$	$2.51 \pm 0.62 \text{ E-04}$
FMC-3	52	$9.12 \pm 0.54 \text{ E-06}$	$4.69 \pm 2.77 \text{ E-07}$	$2.98 \pm 1.65 \text{ E-06}$
FMC-3A	27	$4.91 \pm 0.08 \text{ E-03}$	$1.42 \pm 0.01 \text{ E-03}$	$2.57 \pm 0.77 \text{ E-03}$
FMC-6	27	$3.86 \pm 0.06 \text{ E-04}$	$1.19 \pm 0.02 \text{ E-04}$	$2.86 \pm 0.63 \text{ E-04}$
FMC-A7	27	$9.67 \pm 0.18 \text{ E-04}$	$3.31 \pm 0.09 \text{ E-04}$	$6.59 \pm 1.68 \text{ E-04}$
HP-50	26	$7.39 \pm 0.14 \text{ E-05}$	$5.39 \pm 0.37 \text{ E-06}$	$2.23 \pm 1.88 \text{ E-05}$
HP-52	27	$2.43 \pm 0.07 \text{ E-05}$	$7.26 \pm 2.71 \text{ E-07}$	$5.71 \pm 5.59 \text{ E-06}$
Twin Lakes	50	$2.54 \pm 0.06 \text{ E-05}$	$1.07 \pm 0.05 \text{ E-05}$	$1.96 \pm 0.30 \text{ E-05}$
Caster Creek	50	$6.08 \pm 0.49 \text{ E-06}$	$2.40 \pm 0.46 \text{ E-06}$	$4.69 \pm 0.66 \text{ E-06}$
Indian Grave Branch				
IGB-21	53	$4.21 \pm 0.02 \text{ E-03}$	$1.95 \pm 0.33 \text{ E-05}$	$2.58 \pm 0.80 \text{ E-03}$
Lower Three Runs Creek				
L3R-1A	15	$4.39 \pm 0.34 \text{ E-06}$	$1.76 \pm 0.37 \text{ E-06}$	$2.92 \pm 0.75 \text{ E-06}$
L3R-2	26	$2.40 \pm 0.29 \text{ E-06}$	$4.32 \pm 2.67 \text{ E-07}$	$1.68 \pm 0.55 \text{ E-06}$
L3R-3	12	$2.07 \pm 0.44 \text{ E-06}$	$0.23 \pm 3.44 \text{ E-07}$	$1.20 \pm 0.58 \text{ E-06}$
Beaver Dam Creek				
400-D	52	$2.75 \pm 0.00 \text{ E-04}$	$1.19 \pm 0.42 \text{ E-06}$	$1.75 \pm 3.90 \text{ E-05}$
Par Pond				
100-R Effluent	53	$9.69 \pm 0.20 \text{ E-05}$	$2.28 \pm 0.35 \text{ E-06}$	$1.40 \pm 1.52 \text{ E-05}$
P-area Effluent	53	$1.25 \pm 0.06 \text{ E-05}$	$6.88 \pm 3.24 \text{ E-07}$	$2.56 \pm 1.89 \text{ E-06}$
Pen Branch				
K-10	53	$9.15 \pm 0.11 \text{ E-05}$	$4.08 \pm 4.12 \text{ E-07}$	$0.59 \pm 1.28 \text{ E-05}$
Pen Branch #3	27	$3.83 \pm 0.02 \text{ E-04}$	$8.62 \pm 0.53 \text{ E-06}$	$5.07 \pm 7.30 \text{ E-05}$
Savannah River Swamp				
TNX Effluent	27	$7.17 \pm 4.12 \text{ E-07}$	$-2.68 \pm 3.29 \text{ E-07}$	$1.94 \pm 3.03 \text{ E-07}$
Steel Creek				
SC-2A	26	$1.65 \pm 0.03 \text{ E-04}$	$4.23 \pm 0.49 \text{ E-06}$	$7.52 \pm 5.64 \text{ E-05}$
SC-4	27	$7.59 \pm 0.52 \text{ E-06}$	$3.89 \pm 0.40 \text{ E-06}$	$5.37 \pm 0.97 \text{ E-06}$

Table 8-10
Radioactivity in SRS Stream Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Tims Branch				
TB-2	52	$1.38 \pm 0.43 \text{ E-06}$	$-5.20 \pm 2.91 \text{ E-07}$	$2.78 \pm 4.39 \text{ E-07}$
TB-5	26	$2.62 \pm 0.46 \text{ E-06}$	$-4.60 \pm 2.06 \text{ E-07}$	$1.32 \pm 0.59 \text{ E-06}$
U3R				
Crouch Branch	27	$4.41 \pm 0.08 \text{ E-05}$	$8.26 \pm 0.46 \text{ E-06}$	$1.86 \pm 0.82 \text{ E-05}$
HP-15	52	$7.30 \pm 0.15 \text{ E-05}$	$2.02 \pm 0.43 \text{ E-06}$	$2.09 \pm 1.59 \text{ E-05}$
McQueens Branch	27	$1.49 \pm 0.05 \text{ E-05}$	$5.64 \pm 0.35 \text{ E-06}$	$1.16 \pm 0.20 \text{ E-05}$
U3R-2A	51	$3.68 \pm 0.06 \text{ E-01}$	$2.56 \pm 0.06 \text{ E-03}$	$5.04 \pm 8.08 \text{ E-02}$
U3R-2	52	$6.79 \pm 0.38 \text{ E-06}$	$2.04 \pm 3.96 \text{ E-07}$	$1.92 \pm 1.28 \text{ E-06}$
U3R-3	26	$7.81 \pm 0.11 \text{ E-04}$	$2.23 \pm 0.31 \text{ E-06}$	$0.70 \pm 1.78 \text{ E-04}$
U3R-4	27	$9.88 \pm 0.18 \text{ E-05}$	$2.33 \pm 0.30 \text{ E-06}$	$1.74 \pm 2.36 \text{ E-05}$
U3R-F3	52	$1.06 \pm 0.04 \text{ E-05}$	$0.00 \pm 3.98 \text{ E-07}$	$2.83 \pm 2.02 \text{ E-06}$
Sr-89,90 ($\mu\text{Ci/mL}$)				
Four Mile Creek				
FMC-1B	12	$4.24 \pm 0.89 \text{ E-09}$	$3.34 \pm 6.31 \text{ E-10}$	$2.01 \pm 1.16 \text{ E-09}$
FMC-1C	12	$3.07 \pm 0.15 \text{ E-08}$	$6.14 \pm 4.87 \text{ E-10}$	$5.73 \pm 8.34 \text{ E-09}$
FMC-2	12	$2.80 \pm 0.15 \text{ E-08}$	$1.20 \pm 0.71 \text{ E-09}$	$6.68 \pm 8.26 \text{ E-09}$
FMC-2B	12	$2.76 \pm 0.14 \text{ E-08}$	$6.78 \pm 1.44 \text{ E-09}$	$1.34 \pm 0.70 \text{ E-08}$
FMC-3	12	$1.01 \pm 0.09 \text{ E-08}$	$0.21 \pm 5.14 \text{ E-10}$	$2.44 \pm 2.77 \text{ E-09}$
FMC-3A	12	$6.57 \pm 0.78 \text{ E-09}$	$2.80 \pm 5.12 \text{ E-10}$	$1.65 \pm 1.77 \text{ E-09}$
FMC-A7	12	$2.91 \pm 0.12 \text{ E-08}$	$1.09 \pm 0.08 \text{ E-08}$	$1.84 \pm 0.54 \text{ E-08}$
HP-52	12	$5.62 \pm 0.76 \text{ E-09}$	$-3.47 \pm 4.34 \text{ E-10}$	$1.47 \pm 1.54 \text{ E-09}$
Indian Grave Branch				
IGB-21	4	$1.64 \pm 3.78 \text{ E-10}$	$-2.74 \pm 4.27 \text{ E-10}$	$0.13 \pm 2.03 \text{ E-10}$
Lower Three Runs Creek				
L3R-1A	7	$8.72 \pm 8.49 \text{ E-10}$	$-2.39 \pm 4.56 \text{ E-10}$	$2.60 \pm 3.91 \text{ E-10}$
L3R-3	11	$7.63 \pm 3.44 \text{ E-10}$	$1.30 \pm 7.01 \text{ E-10}$	$4.06 \pm 1.90 \text{ E-10}$
Steel Creek				
SC-2A	12	$8.27 \pm 4.71 \text{ E-10}$	$-4.24 \pm 7.10 \text{ E-10}$	$2.66 \pm 3.87 \text{ E-10}$
U3R				
HP-15	12	$8.87 \pm 3.52 \text{ E-10}$	$-4.28 \pm 3.93 \text{ E-10}$	$1.57 \pm 4.11 \text{ E-10}$
McQueens Branch (discontinued at the end of 1990)				
U3R-2A	51	$2.01 \pm 0.39 \text{ E-08}$	$-3.66 \pm 3.16 \text{ E-09}$	$3.82 \pm 3.79 \text{ E-09}$

Table 8-10
Radioactivity in SRS Stream Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
U3R-2	12	$4.84 \pm 0.18 \text{ E-08}$	$8.52 \pm 7.20 \text{ E-10}$	$0.80 \pm 1.35 \text{ E-08}$
U3R-3	11	$6.06 \pm 5.53 \text{ E-10}$	$-3.41 \pm 4.13 \text{ E-10}$	$2.15 \pm 2.91 \text{ E-10}$
U3R-F3	12	$1.60 \pm 0.82 \text{ E-09}$	$-2.31 \pm 4.36 \text{ E-10}$	$2.93 \pm 5.24 \text{ E-10}$
Sr-90 ($\mu\text{Ci/mL}$)				
Four Mile Creek				
FMC-6	11	$9.28 \pm 0.22 \text{ E-09}$	$5.38 \pm 0.16 \text{ E-09}$	$7.14 \pm 1.42 \text{ E-09}$
Lower Three Runs Creek				
L3R-2	11	$5.57 \pm 0.63 \text{ E-10}$	$7.91 \pm 6.91 \text{ E-11}$	$3.22 \pm 1.66 \text{ E-10}$
Pen Branch				
Pen Branch #3	11	$4.00 \pm 0.85 \text{ E-10}$	$1.78 \pm 5.72 \text{ E-11}$	$1.64 \pm 1.09 \text{ E-10}$
Steel Creek				
SC-4	10	$6.13 \pm 0.81 \text{ E-10}$	$-8.50 \pm 6.67 \text{ E-11}$	$1.41 \pm 1.96 \text{ E-10}$
U/Pu ($\mu\text{Ci/mL}$)				
Four Mile Creek				
FMC-6	26	$1.90 \pm 2.26 \text{ E-10}$	$-3.12 \pm 2.22 \text{ E-10}$	$-0.32 \pm 1.28 \text{ E-10}$
Lower Three Runs Creek				
L3R-2 (Dip)	48	$4.86 \pm 4.76 \text{ E-10}$	$-5.56 \pm 3.84 \text{ E-10}$	$-0.50 \pm 2.05 \text{ E-10}$
L3R-2 (Composite)	24	$2.88 \pm 3.42 \text{ E-10}$	$-4.02 \pm 2.81 \text{ E-10}$	$-0.69 \pm 1.68 \text{ E-10}$
Pen Branch				
Pen Branch #3	27	$2.96 \pm 2.84 \text{ E-10}$	$-2.17 \pm 1.49 \text{ E-10}$	$-0.44 \pm 1.16 \text{ E-10}$
Savannah River Swamp				
TNX Effluent	27	$3.23 \pm 3.84 \text{ E-10}$	$-3.16 \pm 2.22 \text{ E-10}$	$-0.35 \pm 1.65 \text{ E-10}$
Tims Branch				
TB-2	50	$1.56 \pm 0.44 \text{ E-09}$	$-3.81 \pm 2.61 \text{ E-10}$	$0.37 \pm 3.00 \text{ E-10}$
TB-3 (ISCO)	37	$8.42 \pm 7.17 \text{ E-09}$	$-5.12 \pm 3.56 \text{ E-09}$	$0.67 \pm 3.55 \text{ E-09}$
TB-3 (Treble)	14	$5.89 \pm 7.44 \text{ E-09}$	$-5.83 \pm 5.82 \text{ E-09}$	$-0.42 \pm 3.64 \text{ E-09}$
U3R				
U3R-2	52	$1.30 \pm 0.14 \text{ E-08}$	$4.76 \pm 4.19 \text{ E-10}$	$2.96 \pm 2.16 \text{ E-09}$
U3R-4	27	$4.19 \pm 2.19 \text{ E-10}$	$-3.54 \pm 2.54 \text{ E-10}$	$-0.05 \pm 1.75 \text{ E-10}$
U3R-F3	52	$1.92 \pm 0.61 \text{ E-09}$	$-1.38 \pm 2.41 \text{ E-10}$	$4.33 \pm 4.65 \text{ E-10}$

Table 8-10
Radioactivity in SRS Stream Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Cs-137 ($\mu\text{Ci/mL}$)				
Four Mile Creek				
FMC-6	26 / 1 ^a	6.44 $\pm$ 2.24 E-09	6.44 $\pm$ 2.24 E-09	6.44 $\pm$ 2.24 E-09
Lower Three Runs Creek				
L3R-2	25 / 0			
Pen Branch				
Pen Branch #3	26 / 0			
Steel Creek				
SC-4 Road A	27 / 0			

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 8-11
Radioactivity in Seepage Basin Water

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha ($\mu\text{Ci/mL}$)				
SWDF Seepage Basin	6	$1.50 \pm 0.50 \text{ E-09}$	$7.24 \pm 4.70 \text{ E-10}$	$1.07 \pm 0.31 \text{ E-09}$
C Seepage Basin	3	$0.68 \pm 1.42 \text{ E-09}$	$-0.09 \pm 1.61 \text{ E-09}$	$3.66 \pm 4.07 \text{ E-10}$
L Seepage Basin	3	$4.14 \pm 2.20 \text{ E-09}$	$-0.10 \pm 1.70 \text{ E-09}$	$1.35 \pm 2.41 \text{ E-09}$
P Seepage Basin	3	$1.54 \pm 1.65 \text{ E-09}$	$0.71 \pm 1.81 \text{ E-09}$	$1.22 \pm 0.45 \text{ E-09}$
TNX 904-102G	9	$1.96 \pm 3.32 \text{ E-09}$	$-3.47 \pm 2.46 \text{ E-09}$	$-0.38 \pm 1.77 \text{ E-09}$
Nonvolatile Beta ($\mu\text{Ci/mL}$)				
SWDF Seepage Basin	6	$3.51 \pm 0.05 \text{ E-07}$	$1.67 \pm 0.11 \text{ E-08}$	$0.94 \pm 1.27 \text{ E-07}$
C Seepage Basin	3	$6.70 \pm 0.69 \text{ E-08}$	$4.08 \pm 0.58 \text{ E-08}$	$5.58 \pm 1.35 \text{ E-08}$
L Seepage Basin	3	$3.27 \pm 0.55 \text{ E-08}$	$1.45 \pm 0.46 \text{ E-08}$	$2.22 \pm 0.94 \text{ E-08}$
P Seepage Basin	3	$5.78 \pm 0.65 \text{ E-08}$	$4.51 \pm 0.60 \text{ E-08}$	$5.29 \pm 0.68 \text{ E-08}$
TNX 904-102G	9	$2.58 \pm 0.90 \text{ E-08}$	$-0.61 \pm 7.68 \text{ E-09}$	$1.43 \pm 1.02 \text{ E-08}$
Tritium ($\mu\text{Ci/mL}$)				
A Area 1	1	$6.92 \pm 0.43 \text{ E-06}$	$6.92 \pm 0.43 \text{ E-06}$	$6.92 \pm 0.43 \text{ E-06}$
SWDF Seepage Basin	10	$1.27 \pm 0.00 \text{ E-03}$	$6.93 \pm 0.15 \text{ E-05}$	$3.62 \pm 3.52 \text{ E-04}$
C Seepage Basin	4	$3.11 \pm 0.39 \text{ E-05}$	$3.21 \pm 0.37 \text{ E-06}$	$1.28 \pm 1.25 \text{ E-05}$
L Seepage Basin	4	$1.39 \pm 0.02 \text{ E-03}$	$4.73 \pm 3.25 \text{ E-07}$	$4.34 \pm 6.56 \text{ E-04}$
P Seepage Basin	4	$8.29 \pm 0.21 \text{ E-03}$	$1.08 \pm 0.34 \text{ E-06}$	$2.95 \pm 3.87 \text{ E-03}$
TNX Seepage Basin	12	$2.50 \pm 0.45 \text{ E-06}$	$9.04 \pm 4.55 \text{ E-07}$	$1.76 \pm 0.55 \text{ E-06}$
Cs-137 ($\mu\text{Ci/mL}$)				
C Seepage Basin	3 / 0 ^a			
L Seepage Basin	3 / 0			
P Seepage Basin	2 / 1	$7.80 \pm 1.27 \text{ E-08}$	$7.80 \pm 1.27 \text{ E-08}$	$7.80 \pm 1.27 \text{ E-08}$

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 8-12
Tritium Releases Summary, 1960-1991

Year	Estimated Tritium Release (Ci)		
	Based on Point-of-Release Concentrations and Flow Rates ^a	Based on Stream Concentrations and Flow Rates	Based on Savannah River Concentrations and Flow Rates
1960	64,000 ^b	69,600	73,700
1961	69,000 ^b	83,000	77,000
1962	58,000 ^b	64,000	63,000
1963	97,000 ^b	96,900	122,800
1964	111,000 ^b	131,600	143,000
1965	108,400	109,200	100,200
1966	84,900	97,800	78,300
1967	70,600	77,000	68,500
1968	63,800	67,200	61,800
1969	64,600	64,000	58,100
1970	36,900	43,200	31,800
1971	38,200	44,700	39,100
1972	46,800	47,300	45,300
1973	71,100	62,800	61,100
1974	59,900	54,600	46,000
1975	55,600	50,000	49,500
1976	59,600	47,400	51,100
1977	43,800	39,700	42,500
1978	37,600	35,300	36,600
1979	29,400	27,100	30,600
1980	24,900	28,800	30,700
1981	23,900	22,100	25,100
1982	32,200	31,300	30,600
1983	34,200	33,000	33,000
1984	32,800	32,600	33,200
1985	25,000	22,300	24,100
1986	27,800	22,300	22,100
1987	22,700	20,500	26,200
1988	19,300	18,300	14,600
1989	17,300	17,800	15,600
1990	16,100	15,600	14,500
1991	27,400	26,600	26,300

a Includes direct releases to streams and migration from F-, H-, K-, and P-Area seepage basins and the Solid Waste Disposal Facility to streams.

b Includes heat exchanger cooling water released from P Area (of Par Pond origin) to Steel Creek.

Table 8-13
NPDES Sampling Points and Effluent Composition for Permit SC 0000175

A AREA

Sample Point: A-001

Effluent consists of the following types of wastewater:

- a) cooling water
- b) steam condensate
- c) laboratory drain water

Sample Point: A-003

Effluent consists of the following types of wastewater:

- a) cooling water
- b) steam condensate

Sample Point: A-005

Effluent consists of the following types of wastewater:

- a) wastewater from animal holding area
- b) steam condensate
- c) steam cleaning wastewater
- d) cooling water

Sample Point: A-011

Effluent consists of the following types of wastewater:

- a) cooling water

Sample Point: A-014

Effluent consists of the following types of wastewater:

- a) air stripper wastewater
- b) non-contact cooling water

Sample Point: A-015

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

C AREA

Sample Point: C-001

Effluent consists of the following types of wastewater:

- a) cooling water

Sample Point: C-003

Effluent consists of the following types of wastewater:

- a) cooling water

- b) powerhouse wastewater
- c) water treatment wastewater

Sample Point: C-004

Effluent consists of the following types of wastewater:

- a) neutralization water
- b) service wastewater
- c) C-Reactor cooling water

Sample Point: C-004A

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

D AREA

Sample Point: D-001

Effluent consists of the following types of wastewater:

- a) cooling water
- b) neutralization water
- b) heavy water

Sample Point: D-001A

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: D-001B

Effluent consists of the following types of wastewater:

- a) coal pile runoff

Sample Point: D-001C

Effluent consists of the following types of wastewater:

- a) ash basin discharge

Sample Point: D-003

Effluent consists of the following types of wastewater:

- a) Powerhouse washdown water
- b) water treatment plant wastewater

Sample Point: D-005

Effluent consists of the following types of wastewater:

- a) water filter backwash overflow

Table 8-13
NPDES Sampling Points and Effluent Composition for Permit SC 0000175, Cont'd.

D AREA, CONT'D.

Sample Point: D-006

Effluent consists of the following types of wastewater:

- a) cooling water
- b) powerhouse washdown
- c) heavy water process water

Sample Point: DW-001*

Effluent consists of the following types of wastewater:

- a) washdown water from concrete transit mixer trucks
- b) wastewater from concrete batch plant

* Removed from Permit SC0000175 November 4, 1991

Sample Point: DW-002

Effluent consists of the following types of wastewater:

- a) Steam cleaning wastewater
- b) Storm water runoff
- c) Equipment wash water

Sample Point: DW-003

Effluent consists of the following types of wastewater:

- a) sanitary wastewater from DWPF (S area)

Sample Point: DW-004

Effluent consists of the following types of wastewater:

- a) neutralization
- b) cooling water
- c) steam condensate
- d) sanitary wastewater

F AREA

Sample Point: F-001

Effluent consists of the following types of wastewater:

- a) non-process cooling water

Sample Point: F-002

Effluent consists of the following types of wastewater:

- a) non-process cooling water

Sample Point: F-003

Effluent consists of the following types of wastewater:

- a) cooling water and steam condensate

Sample Point: F-003A

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: F-005

Effluent consists of the following types of wastewater:

- a) cooling water and steam condensate

Sample Point: F-007

Effluent consists of the following types of wastewater:

- a) ash basin discharge

Sample Point: F-008

Effluent consists of the following types of wastewater:

- a) neutralization
- b) cooling water
- c) steam condensate
- d) process wastewater
- e) Outfall F-012 and Outfall F-013

Sample Point: F-008A

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: F-012

Effluent consists of the following types of wastewater:

- a) stormwater run-off retention basin effluent.

Sample Point: F-013

Effluent consists of the following types of wastewater:

- a) cooling water retention basin effluent.

Sample Point: FS-001

Effluent consists of the following types of wastewater:

- a) cooling water
- b) greenhouse wastewater

Sample Point: FS-002

Effluent consists of the following types of wastewater:

- a) cooling water
- b) greenhouse wastewater

H AREA

Sample Point: H-002

Effluent consists of the following types of wastewater:

- a) non-process cooling water

Table 8-13

NPDES Sampling Points and Effluent Composition for Permit SC 0000175, Cont'd.

H AREA, CONT'D.**Sample Point: H-003**

Effluent consists of the following types of wastewater:

- a) stormwater

Sample Point: H-004

Effluent consists of the following types of wastewater:

- a) non-process cooling water

Sample Point: H-006

Effluent consists of the following types of wastewater:

- a) stormwater

Sample Point: H-007

Effluent consists of the following types of wastewater:

- a) cooling tower blowdown
- b) air compressor cooling water
- c) freeze protection purge from a water tank filling line

Sample Point: H-008

Effluent consists of the following types of wastewater:

- a) cooling water
- b) steam condensate
- c) neutralization wastewater
- d) powerhouse wastewater

Sample Point: H-008A

Effluent consists of the following types of wastewater:

- a) ash basin discharge

Sample Point: H-012

Effluent consists of the following types of wastewater:

- a) cooling and steam condensate,
- b) replacement tritium facilities decontamination showers
- c) floor drains
- d) Outfall H-017
- e) Outfall H-018

Sample Point: H-013

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: H-015*

Effluent consists of the following types of wastewater:

- a) non-contact cooling water

- b) steam condensate

- c) cooling tower blowdown

*Facility not in service but point still on permit.

Sample Point: H-016

Effluent consists of the following types of wastewater:

- a) process water
- b) cooling water
- c) stormwater

Sample Point: H-017

Effluent consists of the following types of wastewater:

- a) storm water run-off retention basin effluent

Sample Point: H-018

Effluent consists of the following types of wastewater:

- a) cooling water retention basin effluent

K AREA**Sample Point: K-001**

Effluent consists of the following types of wastewater:

- a) cooling water

Sample Point: K-006

Effluent consists of the following types of wastewater:

- a) non-process cooling water
- b) ash sluice leakage
- c) powerhouse wastewater

Sample Point: K-008

Effluent consists of the following types of wastewater:

- a) non-process cooling water

Sample Point: K-010

Effluent consists of the following types of wastewater:

- a) non-process cooling water

Sample Point: K-011

Effluent consists of the following types of wastewater:

- a) neutralization wastewater
- b) K-Reactor cooling water treatment
- c) reservoir wastewater

Sample Point: K-012

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Table 8-13
NPDES Sampling Points and Effluent Composition for Permit SC 0000175, Cont'd.

L AREA

Sample Point: L-007

Effluent consists of the following types of wastewater:

- a) treated low activity wastewater
- b) treated sanitary and neutralization tank waste
- c) reactor cooling water
- d) water treatment plant backflush
- e) reservoir overflow

Sample Point: L-007A

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: L-008

Effluent consists of the following types of wastewater:

- a) non- process cooling water
- b) water reservoir sump wastewater

Sample Point: L-010

Effluent consists of the following types of wastewater:

- a) stormwater

M AREA

Sample Point: M-004

Effluent consists of the following types of wastewater:

- a) Liquid Effluent Treatment Facility

Sample Point: M-005

Effluent consists of the following types of wastewater:

- a) air stripper

P AREA

Sample Point: P-005*

Effluent consists of the following types of wastewater:

- a) ash basin discharge

*Removed from Permit SC0000175 November 4, 1991

Sample Point: P-007

Effluent consists of the following types of wastewater:

- a) Powerhouse wastewater
- b) non-process cooling water

Sample Point: P-013

Effluent consists of the following types of wastewater:

- a) neutralization
- b) reactor process
- c) cooling water

Sample Point: P-019

Effluent consists of the following types of wastewater:

- a) P-Reactor cooling water

Sample Point: P-020

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: PP-001

Effluent consists of the following types of wastewater:

- a) storm water

S AREA

Sample Point: S-002

Effluent consists of the following types of wastewater:

- a) automotive shop
- b) cooling wastewater

Sample Point: S-008*

Effluent consists of the following types of wastewater:

- a) stormwater runoff
- b) cooling wastewater

*Removed from Permit SC0000175 November 4, 1991

Sample Point: S-011

Effluent consists of the following types of wastewater:

- a) sanitary wastewater from Central Shops AreaWWTP

Sample Point: S-014

Effluent consists of the following types of wastewater:

- a) stormwater

Sample Point: SC-004

Effluent consists of the following types of wastewater:

- a) Steel Creek water monitoring below the dam at Road A

Table 8-13
NPDES Sampling Points and Effluent Composition for Permit SC 0000175, Cont'd.

B AREA

Sample Point: T-001

Effluent consists of the following types of wastewater:

- a) artificial stream water

Sample Point: T-005

Effluent consists of the following types of wastewater:

- a) cooling water
- b) boiler blowdown
- c) neutralized acid solutions

Sample Point: T-007

Effluent consists of the following types of wastewater:

- a) sanitary wastewater from B Area

TNX AREA

Sample Point: X-004

Effluent consists of the following types of wastewater:

- a) cooling water

Sample Point: X-008

Effluent consists of the following types of wastewater:

- a) cooling water

- b) cooling tower blowdown

- c) domestic water overflow

Sample Point: X-011

Effluent consists of the following types of wastewater:

- a) cooling water
- b) cooling tower blowdown
- c) domestic water overflow

Sample Point: X-013

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Sample Point: X-014

Effluent consists of the following types of wastewater:

- a) treated wastewater from TNX-ETP

Y AREA

Sample Point: Y-001*

Effluent consists of the following types of wastewater:

- a) cooling water
- b) locomotive washwater

*Removed from Permit SC0000175 November 4, 1991

Table 8-14
NPDES Sampling Points and Effluent Composition for Permit SC 0044903

Sample Point: A-001A

Effluent consists of the following types of wastewater;

- a) air stripper effluent

- a) well flush water

- b) tank overflow

Sample Point: A-028

Effluent consists of the following types of wastewater:

- a) Powerhouse wastewater
- b) water from floor drains
- c) cooling water
- d) well flush water

Sample Point: K-018

Effluent consists of the following types of wastewater:

- a) neutralization
- b) K-Reactor cooling tower blowdown
- c) reservoir wastewater

Sample Point: A-029

Effluent consists of the following types of wastewater:

Sample Point: X-008A

Effluent consists of the following types of wastewater:

- a) sanitary wastewater

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall A-001					
Flow	MGD	15	0.576	0.360	0.427
pH	pH	15	8.6	6.8	
Temperature	°F	15	81	73	77
Total nonfilterable residue	mg/L	15	2.0	<1	<1
Oil and grease	mg/L	15	5.7	<1	1.1
Biochemical oxygen demand	mg/L	15	12	<1	1.4
Tetrachloroethylene	µg/L	5	<2	<2	<2
Trichloroethylene	µg/L	5	<2	<2	<2
1,1,1-Trichloroethane	µg/L	5	<2	<2	<2
Outfall A-003					
pH	pH	15	8.1	6.6	
Temperature	°F	15	80	55	71
Total nonfilterable residue	mg/L	15	2.0	<1	<1
Oil and grease	mg/L	15	12	<1	1.5
Tetrachloroethylene	µg/L	3	<2	<2	<2
Trichloroethylene	µg/L	3	<2	<2	<2
1,1,1-Trichloroethane	µg/L	3	<2	<2	<2
Chromium	mg/L	23	<0.02	<0.02	<0.02
Outfall A-005					
Flow	MGD	12	0.216	0.072	0.145
pH	pH	15	7.9	7.0	
Temperature	°F	15	79	63	71
Fecal coliform	#/100	15	11700	1.0	790
Total nonfilterable residue	mg/L	15	3.0	<1	1.1
Oil and grease	mg/L	15	4.9	<1	1.4
Biochemical oxygen demand	mg/L	15	4.5	<1	1.2
Tetrachloroethylene	µg/L	15	<2	<2	<2
Trichloroethylene	µg/L	15	<2	<2	<2
1,1,1-Trichloroethane	µg/L	15	<2	<2	<2
Outfall A-011					
pH	pH	15	8.1	7.1	
Temperature	°F	14	83	64	75
Total nonfilterable residue	mg/L	15	2.0	<1	<1
Oil and grease	mg/L	15	6.8	<1	1.4
Biochemical oxygen demand	mg/L	15	5.1	<1	4.2
Tetrachloroethylene	µg/L	6	<2	<2	<2
Trichloroethylene	µg/L	6	<2	<2	<2
1,1,1-Trichloroethane	µg/L	65	<2	<2	<2

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall A-014					
Flow	MGD	12	2.84	1.56	1.81
pH	pH	24	7.9	6.2	
Temperature	°F	14	75	64	70
Total nonfilterable residue	mg/L	15	5.0	<1	1.4
Oil and grease	mg/L	15	5.5	<1	1.0
Biochemical oxygen demand	mg/L	14	6.7	<1	2.0
Tetrachloroethylene	µg/L	15	<2	<2	<2
Trichloroethylene	µg/L	15	<2	<2	<2
1,1,1-Trichloroethane	µg/L	15	<2	<2	<2
Outfall A-015					
Flow	MGD	12	0.181	0.105	0.138
pH	pH	15	8.0	6.5	
Fecal coliform	#/100mL	18	<2	<2	<2
Total nonfilterable residue	mg/L	15	11	<1	4.6
Biochemical oxygen demand	mg/L	15	10	<1	3.8
Outfall C-001					
pH	pH	14	7.8	6.4	
Temperature	°F	14	79	48	65
Total nonfilterable residue	mg/L	14	3.6	<1	1.3
Oil and grease	mg/L	14	3.6	<1	1.1
Outfall C-003					
pH	pH	14	8.0	6.2	
Temperature	°F	14	73	67	70
Total nonfilterable residue	mg/L	14	2.0	<1	<1
Oil and grease	mg/L	14	2.3	<1	<1
Outfall C-004					
pH	pH	10	7.8	6.9	
Temperature	°F	10	85	63	72
Total nonfilterable residue	mg/L	10	6.0	<1	2.9
Oil and grease	mg/L	10	8.8	<1	2.4
Outfall C-004A					
Flow	MGD	12	0.045	0.02	0.031
pH	pH	14	8.4	6.8	
Fecal coliform	#/100mL	16	3.0	1.0	1.0
Total nonfilterable residue	mg/L	14	8.0	1.0	3.4
Biochemical oxygen demand	mg/L	14	6.4	<1	3.7

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall D-001					
pH	pH	16	7.8	6.3	
Temperature	°F	16	82	54	71
Total nonfilterable residue	mg/L	17	67	8.0	16
Oil and grease	mg/L	16	6.2	<1	1.3
Outfall D-001A					
Flow	MGD	12	0.022	0.007	0.013
pH	pH	15	8.1	6.8	
Fecal coliform	#/100mL	16	10	<2	2.2
Total nonfilterable residue	mg/L	15	5.0	1.0	2.9
Biochemical oxygen demand	mg/L	15	4.7	<1	2.5
Outfall D-001B					
Flow	MGD	4	0.432	0.432	0.432
pH	pH	4	6.8	6.4	
Total nonfilterable residue	mg/L	4	4.0	1.0	2.0
Aluminum	mg/L	2	29	27	28
Iron	mg/L	2	52	47	50
Sulfate	mg/L	2	582	544	563
Outfall D-001C					
Flow	MGD	15	5.73	4.64	5.02
pH	pH	16	7.6	6.5	
Total nonfilterable residue	mg/L	16	8.0	1.0	3.3
Oil and grease	mg/L	16	3.9	<1	1.1
Outfall D-003					
pH	pH	16	7.8	6.5	
Total nonfilterable residue	mg/L	16	31	<1	4.9
Oil and grease	mg/L	16	6.2	<1	<1
Outfall D-005					
Flow	MGD	12		no flow	
Outfall D-006					
pH	pH	16	7.8	6.3	
Temperature	°F	12	84	57	72
Fecal coliform	#/100mL	16	1,152	14	160
Total nonfilterable residue	mg/L	16	21	2.0	6.2
Oil and grease	mg/L	16	7.1	<1	1.5

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall DW-001					
Flow	MGD	6	0.507	0.252	0.387
pH	pH	6	8.8	6.9	
Total nonfilterable residue	mg/L	6	28	4.0	14
Outfall DW-002					
Flow	MGD	17	0.022	0.007	0.015
pH	pH	15	7.8	6.3	
Oil and grease	mg/L	21	16	<1	2.5
Outfall DW-003					
Flow	MGD	11	0.026	0.017	0.022
pH	pH	14	7.4	6.4	
Fecal coliform	#/100mL	16	10	<2	<2
Total nonfilterable residue	mg/L	14	22	3.0	8.9
Biochemical oxygen demand	mg/L	15	8.4	<1	4.6
Outfall DW-004					
Flow	MGD	7	0.180	0.108	0.149
pH	pH	6	7.6	6.7	
Temperature	°F	5	72	60	67
Total nonfilterable residue	mg/L	6	9.0	2.0	4.0
Oil and grease	mg/L	6	8.3	<1	2.7
Biochemical oxygen demand	mg/L	6	30	<1	6.1
Outfall F-001					
Flow	MGD	15	0.216	0.108	0.18
pH	pH	17	9.3	7.2	
Temperature	°F	15	88	71	79
Total nonfilterable residue	mg/L	16	14	<1	2.7
Oil and grease	mg/L	16	3.8	<1	1.1
Outfall F-002					
Flow	MGD	15	0.086	0.022	0.048
pH	pH	16	7.9	6.4	
Temperature	°F	15	78	51	66
Total nonfilterable residue	mg/L	16	4.0	<1	1.5
Oil and grease	mg/L	16	2.8	<1	<1
Outfall F-003					
Flow	MGD	15	0.108	0.058	0.074
pH	pH	16	8.5	6.7	
Temperature	°F	15	87	69	76
Total nonfilterable residue	mg/L	16	11	<1	3.2
Oil and grease	mg/L	16	6.0	<1	<1
Biochemical oxygen demand	mg/L	16	5.1	<1	1.3

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall F-003A					
Flow	MGD	12	0.022	0.004	0.01
pH	pH	14	8.6	6.9	
Fecal coliform	#/100mL	14	5.0	<2	<2
Total nonfilterable residue	mg/L	14	31	2.0	7.9
Biochemical oxygen demand	mg/L	14	2.9	<1	1.6
Outfall F-005					
Flow	MGD	15	0.115	0.029	0.059
pH	pH	17	9.2	7.0	
Temperature	°F	15	79	69	75
Total nonfilterable residue	mg/L	16	4.0	1.0	2.3
Oil and grease	mg/L	16	14	<1	1.8
Outfall F-007					
Flow	MGD	12		no flow	
Outfall F-008					
pH	pH	16	7.9	7.2	
Temperature	°F	15	89	70	80
Total nonfilterable residue	mg/L	16	36	2.0	5.7
Oil and grease	mg/L	16	3.8	<1	1.3
Outfall F-008A					
Flow	MGD	12	0.115	0.007	0.073
pH	pH	14	8.5	7.0	
Fecal coliform	#/100mL	16	2.0	<2	<2
Total nonfilterable residue	mg/L	14	5.0	1.0	2.8
Biochemical oxygen demand	mg/L	14	4.7	<1	1.7
Outfall F-012					
Flow	MGD	18	1.18	1.01	1.11
pH	pH	18	8.8	6.8	
Nitrate	mg/L	18	0.35	0.01	0.06
Ammonia	mg/L	18	0.11	0.02	0.12
Total nonfilterable residue	mg/L	18	10	2.0	6.9
Manganese	mg/L	18	0.012	<0.005	0.006
Uranium	mg/L	18	<0.02	<0.02	<0.02
Lead	mg/L	18	0.016	<0.003	<0.003
Nickel	mg/L	18	<0.05	<0.05	<0.05
Silver	mg/L	18	0.0014	<0.0005	<0.0005
Chromium	mg/L	18	<0.02	<0.02	<0.02
Aluminum	mg/L	18	0.30	0.13	0.19
Copper	mg/L	18	<0.01	<0.01	<0.01
Mercury	µg/L	18	<0.0001	<0.0001	<0.0001
Zinc	mg/L	18	0.23	0.02	0.07

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall F-013					
Flow	MGD	5	1.15	0.086	0.527
pH	pH	5	8.9	5.8	
Nitrate	mg/L	5	0.08	0.02	0.04
Ammonia	mg/L	5	0.05	0.02	0.03
Total nonfilterable residue	mg/L	5	13	2.0	5.6
Manganese	mg/L	5	0.03	0.008	0.01
Uranium	mg/L	5	<0.02	<0.02	<0.02
Lead	mg/L	5	0.013	<0.003	0.006
Nickel	mg/L	5	<0.05	<0.05	<0.05
Chromium	mg/L	5	<0.02	<0.02	<0.02
Aluminum	mg/L	5	0.25	0.11	0.20
Copper	mg/L	5	<0.01	<0.01	<0.01
Mercury	µg/L	5	<0.0001	<0.0001	<0.0001
Zinc	mg/L	5	0.13	0.03	0.07
Outfall FS-001					
Flow	MGD	12		no flow	
Outfall FS-002					
Flow	MGD	12		no flow	
Outfall H-002					
Flow	MGD	16	0.115	0.043	0.098
pH	pH	16	7.4	5.5	
Temperature	°F	15	82	59	73
Total nonfilterable residue	mg/L	15	9.0	<1	3.2
Oil and grease	mg/L	16	8.3	<1	1.2
Outfall H-004					
Flow	MGD	15	0.0584	0.014	0.043
pH	pH	15	7.7	6.2	
Temperature	°F	14	82	57	70
Total nonfilterable residue	mg/L	15	13	<1	3.2
Oil and grease	mg/L	15	2.4	<1	<1
Outfall H-006					
Flow	MGD	9		no flow	
Outfall H-007					
Flow	MGD	15	0.115	0.022	0.074
pH	pH	16	7.4	5.8	
Temperature	°F	15	80	51	69
Total nonfilterable residue	mg/L	16	6.0	2.0	3.9
Oil and grease	mg/L	17	19	<1	2.1
Residual chlorine	mg/L	15	<0.1	<0.1	<0.1

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall H-008					
pH	pH	16	7.6	6.2	
Temperature	°F	15	82	54	69
Total nonfilterable residue	mg/L	16	10	1.0	3.8
Oil and grease	mg/L	16	8.7	<1	1.5
Outfall H-008A					
Flow	MGD	15	1.41	0.063	0.444
pH	pH	16	7.2	5.3	
Total nonfilterable residue	mg/L	15	4.0	1.0	1.9
Oil and grease	mg/L	15	4.2	<1	1.0
Outfall H-012					
Flow	MGD	12	46	0.362	5.49
pH	pH	16	7.4	6.8	
Temperature	°F	14	85	55	76
Total nonfilterable residue	mg/L	16	8.0	<1	2.8
Oil and grease	mg/L	16	4.7	<1	1.3
Sulfate	mg/L	8	14	1.9	10
Outfall H-013					
Flow	MGD	12	0.114	0.058	0.071
pH	pH	14	7.6	6.6	
Fecal coliform	#/100mL	15	<2	<2	<2
Total nonfilterable residue	mg/L	14	19	1.0	6.7
Biochemical oxygen demand	mg/L	14	7.4	<1	4.2
Outfall H-016					
Temperature	°F	53	84	57	72
Biochemical oxygen demand	mg/L	53	6.4	<1	1.6
Nitrate	mg/L	53	53	1.6	16
Ammonia	mg/L	53	<0.5	<0.5	<0.5
Total nonfilterable residue	mg/L	53	1.0	<1	<1
Oil and grease	mg/L	53	11	<1	1.3
Uranium	mg/L	13	<0.02	<0.02	<0.02
Lead	mg/L	53	0.02	<0.003	<0.003
Nickel	mg/L	13	<0.05	<0.05	<0.05
Mercury	µg/L	53	0.0008	<0.0001	<0.0001
Chromium	mg/L	53	<0.02	<0.02	<0.02
Aluminum	mg/L	13	<0.05	<0.05	<0.05
Copper	mg/L	53	0.015	<0.01	<0.01
Zinc	mg/L	53	3.0	<0.01	0.02
Manganese	mg/L	53	0.012	<0.005	<0.005
Total Chlorine	mg/L	13	0.5	<0.01	0.16

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall H-017					
Flow	MGD	27	1.19	0.43	0.921
pH	pH	27	9.6	5.6	
Nitrate	mg/L	27	7.9	0.01	0.38
Ammonia	mg/L	27	0.24	<0.05	<0.05
Total nonfilterable residue	mg/L	27	26	4.0	10
Manganese	mg/L	27	<1	<1	<1
Uranium	mg/L	27	<0.02	<0.02	<0.02
Lead	mg/L	27	0.066	<0.003	0.007
Nickel	mg/L	27	<0.05	<0.05	<0.05
Chromium	mg/L	27	<0.02	<0.02	<0.02
Aluminum	mg/L	27	0.61	<0.05	0.29
Copper	mg/L	27	0.01	<0.01	<0.01
Mercury	µg/L	27	<0.0001	<0.0001	<0.0001
Zinc	mg/L	27	0.28	0.05	0.15
Outfall H-018					
Flow	MGD	6	1.15	0.086	0.92
pH	pH	6	8.9	6.4	
Nitrate	mg/L	6	0.24	0.01	0.10
Manganese	mg/L	6	0.006	<0.005	<0.005
Total nonfilterable residue	mg/L	6	18	<1	4.8
Ammonia	mg/L	6	<0.5	<0.5	<0.5
Uranium	mg/L	6	<0.02	<0.02	<0.02
Lead	mg/L	6	0.006	<0.003	<0.003
Nickel	mg/L	6	<0.05	<0.05	<0.05
Silver	mg/L	6	<0.0005	<0.0005	<0.0005
Chromium	mg/L	6	<0.02	<0.02	<0.02
Aluminum	mg/L	6	0.09	0.07	0.08
Copper	mg/L	6	<0.01	<0.01	<0.01
Mercury	µg/L	6	<0.0001	<0.0001	<0.0001
Zinc	mg/L	6	0.11	0.02	0.07
Outfall K-001					
Flow	MGD	14	0.022	0.007	0.015
pH	pH	15	7.5	6.4	
Temperature	°F	12	86	61	76
Total nonfilterable residue	mg/L	14	32	<1	4.6
Oil and grease	mg/L	14	15	<1	2.5
Sulfate	mg/L	4	10	9.4	9.7
Outfall K-006					
Flow	MGD	13	0.36	0.007	0.26
pH	pH	15	7.7	6.1	
Temperature	°F	13	84	61	69
Total nonfilterable residue	mg/L	15	1,790	<1	121
Oil and grease	mg/L	14	6.5	<1	1.1

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall K-008					
Flow	MGD	16	0.576	0.007	0.235
pH	pH	15	7.8	6.4	
Temperature	°F	14	89	54	69
Total nonfilterable residue	mg/L	16	50	2.0	8.4
Oil and grease	mg/L	14	120	<1	9.5
Outfall K-010					
Flow	MGD	15	0.432	0.072	0.221
pH	pH	16	7.8	6.4	
Temperature	°F	16	87	61	73
Total nonfilterable residue	mg/L	17	45	2.0	7.9
Oil and grease	mg/L	15	12	<1	1.4
Outfall K-011					
pH	pH	15	7.8	6.6	
Temperature	°F	12	83	56	71
Total nonfilterable residue	mg/L	16	49	2.0	8.6
Oil and grease	mg/L	15	7.0	<1	1.1
Outfall K-012					
pH	pH	14	8.0	6.9	
Fecal coliform	#/100mL	16	<2	<2	<2
Total nonfilterable residue	mg/L	14	18	1.0	7.2
Biochemical oxygen demand	mg/L	15	10	<1	3.9
Outfall L-007					
pH	pH	14	7.5	6.7	
Temperature	°F	12	86	55	71
Total nonfilterable residue	mg/L	14	17	3.0	6.3
Oil and grease	mg/L	14	2.3	<1	<1
Outfall L-007A					
Flow	MGD	12	0.58	0.006	0.060
pH	pH	13	8.6	6.6	
Fecal coliform	#/100mL	14	<2	<2	<2
Total nonfilterable residue	mg/L	13	4.0	1.0	2.1
Biochemical oxygen demand	mg/L	13	5.3	<1	2.6
Outfall L-008					
Flow	MGD	15	0.072	0.006	0.434
pH	pH	15	7.7	6.9	
Temperature	°F	15	85	58	73
Total nonfilterable residue	mg/L	15	9.0	2.0	3.4
Oil and grease	mg/L	15	6.8	<1	<1
Outfall L-010					
Flow	MGD	1		no flow	

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall M-004					
Flow	MGD	34	0.014	0.007	0.010
pH	pH	24	7.7	6.8	
Nitrate	mg/L	13	1,540	229	796
Phosphate	mg/L	13	17	0.06	6.5
Total nonfilterable residue	mg/L	34	6.0	1.0	2.8
Oil and grease	mg/L	34	12	<1	1.3
Uranium	mg/L	34	0.12	<0.02	<0.02
Lead	mg/L	34	0.02	<0.003	<0.003
Nickel	mg/L	34	<0.1	<0.05	<0.05
Silver	mg/L	4	<0.0005	<0.0005	<0.0005
Chromium	mg/L	4	<0.02	<0.02	<0.02
Aluminum	mg/L	34	1.3	<0.05	0.23
Copper	mg/L	34	<0.01	<0.01	<0.01
Cyanide	mg/L	4	<0.005	<0.005	<0.005
Cadmium	mg/L	4	<0.01	<0.01	<0.01
Zinc	mg/L	4	0.06	0.02	0.04
Outfall M-005					
Flow	MGD	51	0.73	0.63	0.64
pH	pH	29	8.0	6.1	
Tetrachloroethylene	µg/L	51	<2	<2	<2
Trichloroethylene	µg/L	51	<2	<2	<2
1,1,1-Trichloroethane	µg/L	51	<2	<2	<2
Outfall P-005					
Flow	MGD	8	0.014	0.002	0.009
pH	pH	9	7.2	6.4	
Total nonfilterable residue	mg/L	9	15	3.0	7.7
Oil and grease	mg/L	9	5.5	<1	1.8
Outfall P-007					
pH	pH	11	8.0	6.4	
Temperature	°F	11	84	59	74
Total nonfilterable residue	mg/L	11	4.0	<1	1.8
Oil and grease	mg/L	11	2.6	<1	1.1
Aluminum	mg/L	11	0.44	<0.05	0.12
Iron	mg/L	11	0.83	0.10	0.35
Outfall P-013					
pH	ph	14	7.9	6.5	
Temperature	°F	12	87	60	73
Total nonfilterable residue	mg/L	14	4.0	<1	1.9
Oil and grease	mg/L	14	3.4	<1	<1

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall P-019					
pH	pH	6	7.9	6.8	
Temperature	°F	6	82	52	68
Total nonfilterable residue	mg/L	6	3.0	<1	1.7
Oil and grease	mg/L	6	1.9	<1	1.1
Outfall P-020					
pH	pH	15	8.6	6.9	
Fecal coliform	#/100mL	15	<2	<2	<2
Total nonfilterable residue	mg/L	15	12	<1	4.5
Biochemical oxygen demand	mg/L	15	5.0	<1	2.0
Outfall PP-001					
Flow	MGD	6	0.144	0.022	0.013
Oil and grease	mg/L	6	8.8	<1	2.1
Outfall S-002					
Flow	MGD	21	0.036	0.007	0.024
pH	pH	11	7.5	6.2	
Temperature	°F	11	79	50	65
Total nonfilterable residue	mg/L	11	23	1.0	7.1
Oil and grease	mg/L	19	2.9	<1	1.1
Biochemical oxygen demand	mg/L	11	7.0	<1	2.0
Aluminum	mg/L	11	1.0	0.21	0.44
Iron	mg/L	11	2.6	0.36	0.12
Outfall S-008					
Flow	MGD	12		no flow	
Outfall S-011					
Flow	MGD	12	0.084	0.049	0.069
pH	pH	14	8.0	6.7	
Fecal coliform	#/100mL	15	<2	<2	<2
Total nonfilterable residue	mg/L	14	8.0	3.0	4.6
Biochemical oxygen demand	mg/L	14	5.2	<1	1.7
Outfall S-014					
Flow	MGD	12		no flow	

MGD=Million gallons per day
 - Insufficient data

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall SC-004					
pH	pH	12	7.8	6.5	
Arsenic	mg/L	12	<0.003	<0.003	<0.003
Chromium	mg/L	12	<0.02	<0.02	<0.02
Lead	mg/L	12	0.014	<0.003	0.004
Mercury	µg/L	12	<0.0001	<0.0001	<0.0001
Selenium	mg/L	12	<0.006	<0.006	<0.006
Cadmium	mg/L	12	<0.01	<0.01	<0.01
Silver	mg/L	12	<0.0005	<0.0005	<0.0005
Barium	mg/L	12	0.016	0.001	0.011
Nitrate	mg/L	12	0.36	0.03	0.10
Phosphate	mg/L	12	0.27	0.02	0.12
Outfall T-001					
Flow	MGD	12		no flow	
Outfall T-005					
Flow	MGD	12		no flow	
Outfall T-007					
pH	pH	24	7.8	7.0	
Fecal coliform	#/100mL	24	2.5	<2	<2
Total nonfilterable residue	mg/L	24	8.0	<1	2.5
Biochemical oxygen demand	mg/L	24	7.6	<1	2.1
Outfall X-004					
pH	pH	15	7.9	6.8	
Temperature	°F	14	82	70	75
Total nonfilterable residue	mg/L	14	4.0	<1	1.9
Oil and grease	mg/L	14	7.3	<1	2.1
Outfall X-008					
Flow	MGD	14	0.36	0.09	0.22
pH	pH	15	7.9	6.4	
Temperature	°F	14	95	68	80
Total nonfilterable residue	mg/L	15	12	<1	3.6
Oil and grease	mg/L	15	5.7	<1	1.7
Aluminum	mg/L	15	0.16	<0.05	0.04
Iron	mg/L	15	5.0	0.55	1.6
Outfall X-011					
Flow	MGD	6	0.001	0.001	0.001

MGD=Million gallons per day

Table 8-15
National Pollutant Discharge Elimination System Monitoring Data, Cont'd.

Measurement	Units	Freq/Year	Maximum	Minimum	Average
Outfall X-013					
pH	pH	14	8.2	6.8	
Fecal coliform	#/100mL	17	<2	<2	<2
Total nonfilterable residue	mg/L	14	17	2.0	6.3
Biochemical oxygen demand	mg/L	14	27	0.5	3.9
Outfall X-014					
Biochemical oxygen demand	mg/L	53	28	<1	4.8
Total suspended solids	mg/L	53	62	2.0	9.4
Oil and grease	mg/L	53	11	<1	1.4
Total organic carbon	mg/L	55	42	<1	4.1
Benzene	µg/L	55	2.2	<1	<1
Phenol	mg/L	55	0.02	<0.002	0.004
Mercury	µg/L	54	0.32	<0.1	0.13
Outfall Y-001					
Flow	MGD	10		no flow	

MGD=Million gallons per day

Table 8-16
NPDES Exceedances During 1991

Department	Location	Date	Analysis	Possible Cause ^a	Corrective Action ^a
Separations	F-001 F-Area	6/06/91	pH (Max)	Unknown	None
Separations	F-005 F-Area	6/06/91	pH (Max)	Unknown	None
CSWE	A-005 A-Area	6/10/91	Fecal (Max)	Unconfirmed. Possible contamination from animal pens	Disinfection installed in pen drains
Construction	DW-002 S-Area	7/9/91	O & G (Max)	Hydraulic overload from rainfall	Separator roof repaired
DWPF	DW-004 S-Area	8/01/91	BOD	Failure to monitor	Administrative procedures Implemented
DWPF	DW-004	8/01/91	Flow	Failure to monitor	Administrative procedures Implemented
Power	K-006 K-Area	8/05/91	TSS (Max)	Construction activities	Construction crews reminded that all activities must be coordinated with site environmental groups

a Each exceedance was reported as presented above to the South Carolina Department of Health and Environmental Control in a monthly Discharge Monitoring Report.

b Biological Oxygen Demand.

Table 8-17
Savannah River Water Quality

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic		
					Mean		Std Dev
River-3B (Below Plant Vogtle) ^a							
Water volume	L		9.76E+12 (total)				
Temperature ^b	°C	12	24	12	18	±	4.3
pH ^b	pH	12	7.8	6.2			
Dissolved oxygen ^b	mg/L	12	10	7.1	8.7	±	0.92
Alkalinity	mg/L	12	23	8.0	17	±	4.4
Conductivity ^b	µmhos/cm	12	100	56	79	±	14
Turbidity	NTU	12	78	2.8	14	±	22
Suspended solids	mg/L	12	98	4.0	18	±	26
Volatile solids	mg/L	12	15	1.0	3.0	±	3.9
Total dissolved solids	mg/L	12	97	18	64	±	11
Total solids	mg/L	12	162	63	83	±	28
Fixed residue	mg/L	12	83	3.0	16	±	22
Chemical oxygen demand	mg/L	12	26	4.0	11	±	5.7
Chloride	mg/L	12	10	4.0	7.1	±	2.2
Nitrogen (as NO ₂ /NO ₃)	mg/L	12	1.2	0.08	0.34	±	0.28
Sulfate	mg/L	12	11	5.1	7.4	±	1.6
Phosphorus (as PO ₄)	mg/L	12	0.14	0.03	0.07	±	0.03
Aluminum	mg/L	4	1.2	0.12	-		-
Nitrogen (as NH ₃)	mg/L	12	0.20	0.01	0.12	±	0.06
Calcium	mg/L	2	4.0	3.7	-		-
Copper	mg/L	4	<0.01	<0.01	-		-
Cadmium	mg/L	4	<0.01	<0.01	-		-
Magnesium	mg/L	2	1.4	1.2	-		-
Manganese	mg/L	2	0.15	0.07	-		-
Mercury	µg/L	4	<0.05	<0.0001	-		-
Nickel	mg/L	4	<0.05	<0.01	-		-
Sodium	mg/L	4	10	6.6	-		-
Iron	mg/L	4	2.5	0.36	-		-
Lead	mg/L	4	0.01	<0.003	-		-
Chromium	mg/L	4	<0.02	<0.01	-		-
Zinc	mg/L	4	0.03	0.02	-		-

^a Metals are analyzed quarterly from a continuous flow composite.

^b Field measurement.

- Insufficient data; mean not calculated for <5 samples.

Table 8-17
Savannah River Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic		
					Mean		Std Dev
River-2 (Above SRS) ^a							
Water volume	L		8.869E+12 (total)				
Temperature ^b	°C	12	24	11	18	±	4.2
pH ^b	pH	12	7.3	6.2			
Dissolved oxygen ^b	mg/L	12	10	7.6	8.7	±	0.80
Alkalinity	mg/L	12	25	7.0	17	±	5.0
Conductivity ^b	µmhos/cm	12	92	53	74	±	14
Turbidity	NTU	12	83	2.6	15	±	23
Suspended solids	mg/L	12	108	4.0	20	±	29
Volatile solids	mg/L	12	16	0	3.3	±	4.1
Total dissolved solids	mg/L	12	88	43	59	±	11
Total solids	mg/L	12	169	52	79	±	32
Fixed residue	mg/L	12	92	3.0	17	±	25
Chemical oxygen demand	mg/L	12	24	7.0	12	±	4.7
Chloride	mg/L	12	9.4	3.5	6.0	±	1.7
Nitrogen (as NO ₂ /NO ₃)	mg/L	12	0.84	0.07	0.30	±	0.20
Sulfate	mg/L	12	11	5.0	7.4	±	1.7
Phosphorus (as PO ₄)	mg/L	12	0.10	0.02	0.05	±	0.02
Aluminum	mg/L	4	1.6	0.13	-		-
Nitrogen (as NH ₃)	mg/L	12	0.84	0.04	0.19	±	0.22
Calcium	mg/L	2	3.8	3.6	-		-
Copper	mg/L	4	<0.01	<0.01	-		-
Cadmium	mg/L	4	<0.01	<0.01	-		-
Magnesium	mg/L	2	1.5	1.2	-		-
Manganese	mg/L	2	0.14	0.08	-		-
Mercury	µg/L	4	<0.50	<0.0001	-		-
Nickel	mg/L	4	<0.05	<0.01	-		-
Sodium	mg/L	4	9.6	6.7	-		-
Iron	mg/L	4	2.6	0.32	-		-
Lead	mg/L	4	<0.01	0.003	-		-
Chromium	mg/L	4	<0.02	<0.01	-		-
Zinc	mg/L	4	0.01	<0.01	-		-

a Metals are analyzed quarterly from a continuous flow composite.

b Field measurement.

- Insufficient data; mean not calculated for <5 samples.

Table 8-17
Savannah River Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic		
					Mean		Std Dev
River-10 (Below SRS) ^a							
Water volume	L		1.06E+13 (total)				
Temperature ^b	°C	12	25	11	18	±	4.5
pH ^b	pH	12	7.5	6.0			
Dissolved oxygen ^b	mg/L	12	9.6	5.8	7.8	±	1.1
Alkalinity	mg/L	12	26	11	18	+	4.7
Conductivity ^b	µmhos/cm	12	101	60	81	±	14
Turbidity	NTU	12	38	2.9	10	±	11
Suspended solids	mg/L	12	64	4.0	16	±	17
Volatile solids	mg/L	12	11	1.0	2.8	±	2.8
Total dissolved solids	mg/L	12	80	51	64	±	7.9
Total solids	mg/L	12	131	65	81	±	21
Fixed residue	mg/L	12	53	2.5	14	±	14
Chemical oxygen demand	mg/L	12	26	7.0	14	±	6.5
Chloride	mg/L	12	9.7	4.2	7.2	±	1.7
Nitrogen (as NO ₂ /NO ₃)	mg/L	12	0.76	0.11	0.25	±	0.18
Sulfate	mg/L	12	13	6.0	7.8	±	1.9
Phosphorus (as PO ₄)	mg/L	12	0.39	0.04	0.09	±	0.09
Aluminum	mg/L	4	0.79	0.16	-		-
Nitrogen (as NH ₃)	mg/L	12	0.30	0.01	0.12	±	0.07
Calcium	mg/L	2	4.4	4.0	-		-
Copper	mg/L	4	<0.01	<0.01	-		-
Cadmium	mg/L	4	<0.01	<0.01	-		-
Magnesium	mg/L	2	1.4	1.2	-		-
Manganese	mg/L	2	0.13	0.07	-		-
Mercury	µg/L	4	<0.05	<0.0001	-		-
Nickel	mg/L	4	<0.05	<0.01	-		-
Sodium	mg/L	4	10	7.5	-		-
Iron	mg/L	4	1.8	0.51	-		-
Lead	mg/L	4	0.01	<0.003	-		-
Chromium	mg/L	4	<0.02	<0.01	-		-
Zinc	mg/L	4	<0.01	<0.01	-		-

a Metals are analyzed quarterly from a continuous flow composite.

b Field measurement.

- Insufficient data; mean not calculated for <5 samples.

Table 8-18
Fecal Coliform Bacteria in SRS Streams and the Savannah River

Location	Number of Samples	Result (Colonies/100mL)				
		Weekly Values		Monthly Geometric Mean ^a		
		Maximum	Minimum	Maximum	Minimum	Average
River 2, above SRS	52	1300	3	258	13	84
River 3B, Plant Vogtle Discharge	52	1290	10	209	34	80
River 10, below SRS	52	1600	3	180	9	53
Upper Three Runs Creek at Road F	52	750	30	246	45	101
Upper Three Runs Creek at Road A	52	727	11	170	46	98
Beaver Dam Creek near Swamp	52	1200	3	128	17	50
Four Mile Creek at Road A	52	200	8	102	17	48
Pen Branch at Road A	52	1100	5	127	22	50
Steel Creek at Road A	12	31	<2	31	<2	16
Lower Three Runs Creek at Road A	52	990	<2	279	30	119
Lower Three Runs Creek at Tabernacle Church Road	52	560	15	159	41	100

^a Maximum, minimum, and average of monthly geometric mean of weekly values. The standard for South Carolina states that the fecal coliform count should not exceed a geometric mean of 1,000 colonies/100 mL based on five consecutive samples during any 30-day period, nor exceed 2,000 colonies/100 mL in more than 20% of the samples examined during such period (not applicable during or following periods of rainfall).

Table 8-19
SRS Stream Water Quality: Herbicides and Volatile Organics

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic	
					Mean	2 Std Dev
Tims Branch-5						
2, 4-D	µg/L	12	<0.2	<0.2	-	-
Silvex	µg/L	12	<0.05	<0.05	-	-
Methoxychlor	µg/L	12	<0.02	<0.02	-	-
Toxaphene	µg/L	12	<2.5	<2.5	-	-
Lindane	µg/L	12	<0.05	<0.05	-	-
Endrin	µg/L	12	<0.05	<0.05	-	-
Tetrachloroethylene	µg/L	12	<2.0	<2.0	-	-
Trichloroethylene	µg/L	12	<2.0	<2.0	-	-
1,1,1-Trichloroethane	µg/L	12	<2.0	<2.0	-	-
Four Mile Creek-A7						
2, 4-D	µg/L	12	<0.2	<0.2	-	-
Silvex	µg/L	12	<0.05	<0.05	-	-
Methoxychlor	µg/L	12	<0.02	<0.02	-	-
Toxaphene	µg/L	12	<2.5	<2.5	-	-
Lindane	µg/L	12	<0.05	<0.05	-	-
Endrin	µg/L	12	<0.05	<0.05	-	-
Tetrachloroethylene	µg/L	12	<2.0	<2.0	-	-
Trichloroethylene	µg/L	12	<2.0	<2.0	-	-
1,1,1-Trichloroethane	µg/L	12	<2.0	<2.0	-	-
Steel Creek-4						
2, 4-D	µg/L	12	<0.2	<0.2	-	-
Silvex	µg/L	12	<0.05	<0.05	-	-
Methoxychlor	µg/L	12	<0.02	<0.02	-	-
Toxaphene	µg/L	12	<2.5	<2.5	-	-
Lindane	µg/L	12	<0.05	<0.05	-	-
Endrin	µg/L	12	<0.05	<0.05	-	-
Tetrachloroethylene	µg/L	12	<2.0	<2.0	-	-
Trichloroethylene	µg/L	12	<2.0	<2.0	-	-
1,1,1-Trichloroethane	µg/L	12	<2.0	<2.0	-	-
Upper Three Runs Creek-4						
2, 4-D	µg/L	12	<0.2	<0.2	-	-
Silvex	µg/L	12	<0.05	<0.05	-	-
Methoxychlor	µg/L	12	<0.02	<0.02	-	-
Toxaphene	µg/L	12	<2.5	<2.5	-	-
Lindane	µg/L	12	<0.05	<0.05	-	-
Endrin	µg/L	12	<0.05	<0.05	-	-
Tetrachloroethylene	µg/L	12	<2.0	<2.0	-	-
Trichloroethylene	µg/L	12	<2.0	<2.0	-	-
1,1,1-Trichloroethane	µg/L	12	<2.0	<2.0	-	-

- Mean not calculated; all measurements were less than detection limits.

Table 8-20
SRS Stream Water Quality

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Tims Branch 5^a					
Water volume	L		6.21E+09 (total)		
Temperature ^b	°C	12	22.1	7.7	15.3 $\pm$ 4.73
pH ^b	pH	12	7.5	6.3	6.8 $\pm$ 0.35
Dissolved oxygen ^b	mg/L	12	11.8	8.1	9.86 $\pm$ 1.18
Alkalinity	mg/L	12	18	8	13.25 $\pm$ 3.36
Conductivity ^b	μ mhos/cm	12	84	46.8	58.8 $\pm$ 10.4
Total organic carbon	mg/L	12	8.24	1.89	3.9 $\pm$ 2.03
Turbidity	NTU	12	21.7	4.27	9.43 $\pm$ 5.6
Suspended solids	mg/L	12	21	5	9.1 $\pm$ 4.25
Volatile solids	mg/L	12	5	1	3.25 $\pm$ 1.35
Total dissolved solids	mg/L	12	62	39	48.75 $\pm$ 7.93
Total solids	mg/L	12	70	47	57.5 $\pm$ 8.6
Fixed residue	mg/L	12	16	3	5.75 $\pm$ 3.5
Chemical oxygen demand	mg/L	12	22	4	8.6 $\pm$ 4.9
Organic nitrogen	mg/L	12	0.4	0.21	0.3 $\pm$ 0.067
Chloride	mg/L	12	4.77	2.61	3.6 $\pm$ 0.64
Nitrogen (NO ₂ /NO ₃)	mg/L	12	2.44	0.13	0.81 $\pm$ 0.65
Sulfate	mg/L	12	6	2.98	4.29 $\pm$ 1.05
Phosphorus (as PO ₄)	mg/L	12	0.89	0.03	0.13 $\pm$ 0.24
Aluminum	mg/L	4	0.45	0.16	—
Nitrogen (as NH ₃)	mg/L	12	1.36	0.02	0.18 $\pm$ 0.37
Calcium	mg/L	2	1.101	1.1	—
Copper	mg/L	4	<0.01	<0.01	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	0.5	0.42	—
Manganese	mg/L	2	0.1	0.05	—
Mercury	μ g/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	10.4	7.93	—
Iron	mg/L	4	2.2	1.41	—
Lead	mg/L	4	0.009	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	<0.01	<0.01	—
Steel Creek at Road A^a					
Water volume	L		1.24E+11 (total)		
Temperature ^b	°C	12	28.2	8.7	18.9 $\pm$ 6.92
pH ^b	pH	12	7.7	6.3	6.95 $\pm$ 0.47
Dissolved oxygen ^b	mg/L	12	11.2	6.1	8.3 $\pm$ 1.7
Alkalinity	mg/L	12	13	8	10.9 $\pm$ 1.8
Conductivity ^b	μ mhos/cm	12	67.8	46.2	59.7 $\pm$ 6.2
Total organic carbon	mg/L	12	6.3	2.9	3.9 $\pm$ 1.1
Turbidity	NTU	12	2.14	0.93	1.47 $\pm$ 0.37
Suspended solids	mg/L	12	8	2	4.14 $\pm$ 1.8
Volatile solids	mg/L	12	4	1	2 $\pm$ 1

a Metals are analyzed quarterly from a monthly grab composite.

b Field measurements.

Table 8-20
SRS Stream Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Steel Creek at Road A, Cont'd^a					
Total dissolved solids	mg/L	12	51	36	43.6 $\pm$ 5
Total solids	mg/L	12	59	40	47.9 $\pm$ 5.8
Fixed residue	mg/L	12	6	1	2.6 $\pm$ 1.6
Chemical oxygen demand	mg/L	12	15	4	9 $\pm$ 3.6
Organic nitrogen	mg/L	12	0.35	0.23	0.29 $\pm$ 0.044
Chloride	mg/L	12	7.03	4	5.6 $\pm$ 0.95
Nitrogen (NO ₂ /NO ₃)	mg/L	12	0.21	0.02	0.08 $\pm$ 0.06
Sulfate	mg/L	12	8	3	5.6 $\pm$ 1.6
Phosphorus (as PO ₄)	mg/L	12	0.05	0.01	0.023 $\pm$ 0.013
Aluminum	mg/L	4	0.1	<0.05	—
Nitrogen (as NH ₃)	mg/L	12	0.25	0.04	0.11 $\pm$ 0.07
Calcium	mg/L	2	3.01	2.27	—
Copper	mg/L	4	0.023	<0.01	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	1.11	0.93	—
Manganese	mg/L	2	0.017	0.01	—
Mercury	μg/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	8.3	5.43	—
Iron	mg/L	4	0.213	0.135	—
Lead	mg/L	4	0.003	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	<0.01	<0.01	—
Upper Three Runs at Road A^a					
Water volume	L		2.52E+11 (total)		
Temperature ^b	°C	12	23.3	8.9	16 $\pm$ 5.11
pH ^b	pH	12	7.5	6.1	6.7 $\pm$ 0.5
Dissolved oxygen ^b	mg/L	12	11.14	6.9	8.6 $\pm$ 1.4
Alkalinity	mg/L	12	5	1	3.1 $\pm$ 1.4
Conductivity ^b	μmhos/cm	12	40.2	11.3	24.3 $\pm$ 6.6
Total organic carbon	mg/L	12	9.38	2.59	4.98 $\pm$ 2.45
Turbidity	NTU	12	5.39	1.98	3.6 $\pm$ 1.23
Suspended solids	mg/L	12	19	3	7.8 $\pm$ 4.4
Volatile solids	mg/L	12	7	1	3.25 $\pm$ 1.71
Total dissolved solids	mg/L	12	43	26	33.75 $\pm$ 6.22
Total solids	mg/L	12	56	32	41.6 $\pm$ 7.5
Fixed residue	mg/L	12	13	2	4.75 $\pm$ 3.16
Chemical oxygen demand	mg/L	12	30	3	13.6 $\pm$ 7.7
Organic nitrogen	mg/L	12	1.03	0.23	0.43 $\pm$ 0.3
Chloride	mg/L	12	2.79	1.12	2.1 $\pm$ 0.51
Nitrogen (NO ₂ /NO ₃)	mg/L	12	0.4	0.02	0.123 $\pm$ 0.096
Sulfate	mg/L	12	4.98	2	3.36 $\pm$ 0.95
Phosphorus (as PO ₄)	mg/L	12	0.05	0.01	0.027 $\pm$ 0.012
Aluminum	mg/L	4	0.243	0.14	—
Nitrogen (as NH ₃)	mg/L	12	0.39	0	0.086 $\pm$ 0.11

a Metals are analyzed quarterly from a monthly grab composite.

b Field measurements.

Table 8-20
SRS Stream Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Upper Three Runs at Road A, Cont'd.^a					
Calcium	mg/L	2	1.65	1.598	—
Copper	mg/L	4	0.021	0.01	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	0.39	0.3	—
Manganese	mg/L	2	0.014	0.01	—
Mercury	µg/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	1.6	1.27	—
Iron	mg/L	4	0.966	0.37	—
Lead	mg/L	4	0.01	<0.003	—
Chromium	mg/L	4	<0.01	<0.01	—
Zinc	mg/L	4	<0.01	<0.01	—
Four Mile Creek Road at A-7^a					
Water volume	L		2.46E+10 (total)		
Temperature ^b	°C	12	2.4	7.4	16.16 $\pm$ 5.82
pH ^b	pH	12	7.4	6.2	6.8 $\pm$ 0.44
Dissolved oxygen ^b	mg/L	12	11.6	5	8.5 $\pm$ 2.14
Alkalinity	mg/L	12	15	2	8.33 $\pm$ 3.65
Conductivity ^b	µmhos/cm	12	97.5	49	64.6 $\pm$ 14.2
Total organic carbon	mg/L	12	9.04	1.65	3.75 $\pm$ 2.36
Turbidity	NTU	12	9.03	1.41	4.38 $\pm$ 2.66
Suspended solids	mg/L	12	15	2	6.91 $\pm$ 3.75
Volatile solids	mg/L	12	5	1	2.75 $\pm$ 1.28
Total dissolved solids	mg/L	12	68	42	53.9 $\pm$ 7.7
Total solids	mg/L	12	76	51	60.8 $\pm$ 7.7
Fixed residue	mg/L	12	10	1	4.81 $\pm$ 2.75
Chemical oxygen demand	mg/L	12	26	1	10.25 $\pm$ 7.9
Organic nitrogen	mg/L	12	0.51	0.22	0.32 $\pm$ 0.09
Chloride	mg/L	12	15	2	8.33 $\pm$ 3.65
Nitrogen (NO ₂ /NO ₃)	mg/L	12	3.47	1.35	2.17 $\pm$ 0.72
Sulfate	mg/L	12	17	4	6.6 $\pm$ 3.45
Phosphorus (as PO ₄)	mg/L	12	0.04	0.02	0.02 $\pm$ 0.006
Aluminum	mg/L	4	0.374	0.057	—
Nitrogen (as NH ₃)	mg/L	12	0.42	0.02	0.122 $\pm$ 0.1
Calcium	mg/L	2	3.47	3.36	—
Copper	mg/L	4	<0.01	<0.01	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	0.65	0.64	—
Manganese	mg/L	2	0.21	0.19	—
Mercury	µg/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	9.218	6.62	—
Iron	mg/L	4	1.71	0.703	—
Lead	mg/L	4	0.01	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	0.01	<0.01	—

^a Metals are analyzed quarterly from a monthly grab composite.

^b Field measurements.

Table 8-20
SRS Stream Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Crouch Branch					
Water volume	L		6.11E+07 (total)		
Temperature ^b	°C	12	25.8	8.3	17.08 $\pm$ 5.98
pH ^b	pH	12	7.56	5.8	6.74 $\pm$ 0.6
Dissolved oxygen ^b	mg/L	12	8.2	2.6	5.73 $\pm$ 1.95
Turbidity	NTU	12	83.5	5.05	31.58 $\pm$ 24.8
Suspended solids	mg/L	12	22	2	10.3 $\pm$ 6.23
Lower Three Runs at Patterson Mill^a					
Water volume	L		1.25E+11 (total)		
Temperature ^b	°C	12	24.8	8.3	17.1 $\pm$ 5.6
pH ^b	pH	12	7.75	6.3	7.03 $\pm$ 0.41
Dissolved oxygen ^b	mg/L	12	10.4	6.15	8.13 $\pm$ 1.45
Alkalinity	mg/L	12	51	14	25.6 $\pm$ 10.6
Conductivity ^b	μ mhos/cm	12	93	64	74.6 $\pm$ 8.4
Turbidity	NTU	12	2.89	0.91	1.42 $\pm$ 0.53
Suspended solids	mg/L	12	8	1	3.18 $\pm$ 1.94
Volatile solids	mg/L	12	4	1	1.72 $\pm$ 1.1
Total dissolved solids	mg/L	12	69	48	56.4 $\pm$ 6.34
Total solids	mg/L	12	73	50	59.3 $\pm$ 6.78
Fixed residue	mg/L	12	5	1	1.72 $\pm$ 1.27
Chemical oxygen demand	mg/L	12	16	7	11.25 $\pm$ 2.86
Chloride	mg/L	12	5.4	2.67	3.8 $\pm$ 0.8
Nitrogen (NO ₂ /NO ₃)	mg/L	12	0.13	0.02	0.07 $\pm$ 0.035
Sulfate	mg/L	12	9	3	4.52 $\pm$ 1.6
Phosphorus (as PO ₄)	mg/L	12	0.06	0.01	0.03 $\pm$ 0.013
Aluminum	mg/L	4	0.184	0.023	—
Nitrogen (as NH ₃)	mg/L	12	1.41	0.03	0.19 $\pm$ 0.38
Calcium	mg/L	2	9	7.83	—
Copper	mg/L	4	0.016	0.013	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	0.81	0.7	—
Manganese	mg/L	2	0.03	0.022	—
Mercury	μ g/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	5.1	3.097	—
Iron	mg/L	4	0.423	0.266	—
Lead	mg/L	4	0.003	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	<0.01	<0.01	—
McQueen Branch					
Water volume	L		9.93E+08 (total)		
Temperature	°C	12	23.8	9.7	16.08 $\pm$ 4.87
pH	pH	12	7.9	6	7.02 $\pm$ 0.57
Dissolved oxygen	mg/L	12	10.5	7.7	9.3 $\pm$ 1.01
Turbidity	NTU	12	11.54	2.88	6.97 $\pm$ 2.37
Suspended solids	mg/L	12	9	1	4.5 $\pm$ 2.57

a Metals are analyzed quarterly from a monthly grab composite.

b Field measurements.

Table 8-20
SRS Stream Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Pen Branch Road at A-17^a					
Water volume	L		1.71E+11 (total)		
Temperature ^b	°C	12	29.4	9.8	19.06 $\pm$ 6.31
pH ^b	pH	12	7.85	6.41	7.24 $\pm$ 0.41
Dissolved oxygen ^b	mg/L	12	10.9	7.08	9.13 $\pm$ 1.24
Alkalinity	mg/L	12	21	4	15 $\pm$ 4.91
Conductivity ^b	μ mhos/cm	12	88	28	65.8 $\pm$ 16.5
Turbidity	NTU	12	54.1	3.65	10.7 $\pm$ 14
Suspended solids	mg/L	12	42	5	11.08 $\pm$ 10
Volatile solids	mg/L	12	10	1	2.9 $\pm$ 2.4
Total dissolved solids	mg/L	12	70	52	59 $\pm$ 5.11
Total solids	mg/L	12	112	59	70 $\pm$ 14
Fixed residue	mg/L	12	32	3	8.25 $\pm$ 7.8
Chemical oxygen demand	mg/L	12	21	9	14 $\pm$ 3.3
Chloride	mg/L	12	7.59	3.66	5.8 $\pm$ 1.5
Nitrogen (NO ₂ /NO ₃)	mg/L	12	0.38	0.1	0.21 $\pm$ 0.083
Sulfate	mg/L	12	11	5	6.73 $\pm$ 1.71
Phosphorus (as PO ₄)	mg/L	12	0.15	0.02	0.075 $\pm$ 0.04
Aluminum	mg/L	4	0.31	0.125	—
Nitrogen (as NH ₃)	mg/L	12	0.23	0.03	0.1 $\pm$ 0.06
Calcium	mg/L	2	4.04	4	—
Copper	mg/L	4	0.312	0.143	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	1.26	0.92	—
Manganese	mg/L	2	0.06	0.04	—
Mercury	μ g/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	9.39	5.77	—
Iron	mg/L	4	0.75	0.34	—
Lead	mg/L	4	<0.003	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	0.012	0.01	—
Four Mile Creek at Road A^a					
Water volume	L		5.13E+10 (total)		
Temperature ^b	°C	12	28.6	9	18.32 $\pm$ 6.96
pH ^b	pH	12	8.5	6.4	7.33 $\pm$ 0.54
Dissolved oxygen ^b	mg/L	12	11.6	6.71	9.51 $\pm$ 1.38
Alkalinity	mg/L	12	17	3	10.5 $\pm$ 4.18
Conductivity ^b	μ mhos/cm	12	64	44	54.5 $\pm$ 5.36
Turbidity	NTU	12	6.1	1.23	3.11 $\pm$ 1.62
Suspended solids	mg/L	12	5	1	3.1 $\pm$ 1.19
Volatile solids	mg/L	12	3	1	1.4 $\pm$ 0.7

a Metals are analyzed quarterly from a monthly grab composite.

b Field measurements.

Table 8-20
SRS Stream Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Four Mile Creek at Road A Cont'd.^a					
Total dissolved solids	mg/L	12	54	35	47.1 $\pm$ 5.5
Total solids	mg/L	12	58	40	49.6 $\pm$ 5.4
Fixed residue	mg/L	12	4	1	2.11 $\pm$ 0.93
Chemical oxygen demand	mg/L	12	28	5	11.1 $\pm$ 6.35
Chloride	mg/L	12	4.91	2.58	3.38 $\pm$ 0.66
Nitrogen (NO ₂ /NO ₃)	mg/L	12	2.66	0.23	1.07 $\pm$ 0.65
Sulfate	mg/L	12	8	3.85	5.48 $\pm$ 1.64
Phosphorus (as PO ₄)	mg/L	12	0.11	0.02	0.041 $\pm$ 0.027
Aluminum	mg/L	4	0.16	0.094	—
Nitrogen (as NH ₃)	mg/L	12	0.19	0.03	0.09 $\pm$ 0.05
Calcium	mg/L	2	3.43	2.87	—
Copper	mg/L	4	0.051	0.02	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	0.65	0.57	—
Manganese	mg/L	2	0.02	<0.01	—
Mercury	µg/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	6.75	4.79	—
Iron	mg/L	4	0.5	0.051	—
Lead	mg/L	4	0.003	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	0.011	<0.01	—
Upper Three Runs -1A^a					
Water volume	L		9.40E+10 (total)		
Temperature ^b	°C	12	22.2	11.6	16.5 $\pm$ 3.72
pH ^b	pH	12	8.2	5.2	6.85 $\pm$ 0.84
Dissolved oxygen ^b	mg/L	12	9.8	7.7	8.77 $\pm$ 0.7
Alkalinity	mg/L	12	6	0	3 $\pm$ 2.1
Conductivity ^b	µmhos/cm	12	30	16	22 $\pm$ 5.57
Turbidity	NTU	12	3.9	0.99	1.82 $\pm$ 0.87
Suspended solids	mg/L	12	6	1	4.25 $\pm$ 1.65
Volatile solids	mg/L	12	4	1	2.08 $\pm$ 0.99
Total dissolved solids	mg/L	12	28	17	22.25 $\pm$ 3.49
Total solids	mg/L	12	34	20	26.4 $\pm$ 4.54
Fixed residue	mg/L	12	5	1	2.16 $\pm$ 1.11
Chemical oxygen demand	mg/L	12	11	1	6.58 $\pm$ 3.91
Chloride	mg/L	12	3.55	1.03	2.19 $\pm$ 0.79
Nitrogen (NO ₂ /NO ₃)	mg/L	12	0.4	0.15	0.22 $\pm$ 0.07
Sulfate	mg/L	12	5	1.9	3.02 $\pm$ 0.87
Phosphorus (as PO ₄)	mg/L	12	0.1	0.01	0.044 $\pm$ 0.029
Aluminum	mg/L	4	0.145	0.089	—

^a Metals are analyzed quarterly from a monthly grab composite.

^b Field measurements.

Table 8-20
SRS Stream Water Quality, Cont'd.

Parameter	Units	No. of Analyses	Maximum	Minimum	Arithmetic Mean $\pm\sigma$
Upper Three Runs -1A , cont'd.^a					
Nitrogen (as NH ₃)	mg/L	12	0.46	0.01	0.122 $\pm$ 0.131
Calcium	mg/L	2	0.486	0.47	—
Copper	mg/L	4	0.02	0.011	—
Cadmium	mg/L	4	<0.01	<0.01	—
Magnesium	mg/L	2	0.36	0.31	—
Manganese	mg/L	2	0.01	<0.01	—
Mercury	μg/L	4	<0.0001	<0.0001	—
Nickel	mg/L	4	<0.05	<0.05	—
Sodium	mg/L	4	1.42	1.02	—
Iron	mg/L	4	0.443	0.2	—
Lead	mg/L	4	0.01	<0.003	—
Chromium	mg/L	4	<0.02	<0.02	—
Zinc	mg/L	4	<0.01	<0.01	—

^a Metals are analyzed quarterly from a monthly grab composite.

Table 8-20
SRS Stream Water Quality, Cont'd.

Beaver Dam Creek Water Quality Data Summary^a

Quarter 1, January 1–March 31, 1991

Parameter	Units	Hourly Maximum	Hourly Minimum	Hourly Average
Temperature	°F	71	41	58
pH	pH	7.5	5.9	67
Dissolved oxygen	mg/L	10.1	8.2	9.4
Conductivity	µmhos/cm	195	67	96
Oxidation/reduction potential	mV	446	345	387

Quarter 2, April 1–May 31, 1991

Parameter	Units	Hourly Maximum	Hourly Minimum	Hourly Average
Temperature	°F	79	61	69
pH	pH	7.2	5.9	6.8
Dissolved oxygen	mg/L	9.6	4.6	8
Conductivity	µmhos/cm	100	44	69
Oxidation/reduction potential	mV	456	345	400

^a Data not available for Quarters 3 and 4 because of expiration of contract.

Table 8-20
SRS Stream Water Quality, Cont'd.

Steel Creek Water Quality Data Summary^a

Quarter 1, January 1–March 31, 1991

Parameter	Units	Hourly Maximum	Hourly Minimum	Hourly Average
Temperature	°F	64	48	55
Dissolved oxygen	mg/L	10.6	8	9.6

Quarter 2, April 1–May 31, 1991

Parameter	Units	Hourly Maximum	Hourly Minimum	Hourly Average
Temperature	°F	79	63	72
Dissolved oxygen	mg/L	8.6	5.8	7.1

---

^a Data not available for Quarters 3 and 4 because of expiration of contract.

Table 8-21
Herbicides in Stream and River Water

Constituents (ug/L) ^a	River 2 Above SRS ^b	River 10 Below SRS ^b	Upper Three Runs at Road F ^b
Aldrin	<0.05	<0.05	<0.05
Alpha-BHC	<0.05	<0.05	<0.05
Beta-BHC	<0.05	<0.05	<0.05
Delta-BHC	<0.05	<0.05	<0.05
Lindane	<0.05	<0.05	<0.05
Alpha-chlordane	<0.05	<0.05	<0.05
Gamma-chlordane	<0.05	<0.05	<0.05
Tech, chlordane	<0.25	<0.25	<0.25
4,4-DDD	<0.05	<0.05	<0.05
4,4-DDE	<0.05	<0.05	<0.05
4,4-DDT	<0.05	<0.05	<0.05
Dieldrin	<0.05	<0.05	<0.05
Endosulfan I	<0.05	<0.05	<0.05
Endosulfan II	<0.05	<0.05	<0.05
Endosulfan sulfate	<0.05	<0.05	<0.05
Endrin	<0.05	<0.05	<0.05
Endrin aldehyde	<0.05	<0.05	<0.05
Heptachlor	<0.05	<0.05	<0.05
Heptachlor epoxide	<0.05	<0.05	<0.05
Methoxychlor	<0.20	<0.20	<0.20
Toxaphene	<2.50	<2.50	<2.50
2,4-D	<0.20	<0.20	<0.20
2,4,5-TP (Silvex)	<0.05	<0.05	<0.05

^a Results reported by subcontracted offsite laboratory, Thermo Analytical, Inc.

^b Samples collected July 16, 1991.

Table 8-21
Herbicides in Stream and River Water, Cont'd.

Constituents (µg/L)^a	Steel Creek at Road A^b	Par Pond Pumphouse^a	Lower Three Runs at Road F^b
Aldrin	<0.05	<0.05	<0.05
Alpha-BHC	<0.05	<0.05	<0.05
Beta-BHC	<0.05	<0.05	<0.05
Delta-BHC	<0.05	<0.05	<0.05
Lindane	<0.05	<0.05	<0.05
Alpha-chlordane	<0.05	<0.05	<0.05
Gamma-chlordane	<0.05	<0.05	<0.05
Tech, chlordane	<0.25	<0.25	<0.25
4,4-DDD	<0.05	<0.05	<0.05
4,4-DDE	<0.05	<0.05	<0.05
4,4-DDT	<0.05	<0.05	<0.05
Dieldrin	<0.05	<0.05	<0.05
Endosulfan I	<0.05	<0.05	<0.05
Endosulfan II	<0.05	<0.05	<0.05
Endosulfan sulfate	<0.05	<0.05	<0.05
Endrin	<0.05	<0.05	<0.05
Endrin aldehyde	<0.05	<0.05	<0.05
Heptachlor	<0.05	<0.05	<0.05
Heptachlor epoxide	<0.05	<0.05	<0.05
Methoxychlor	<0.20	<0.20	<0.20
Toxaphene	<2.50	<2.50	<2.50
2,4-D	<0.20	<0.20	<0.20
2,4,5-TP (Silvex)	<0.05	<0.05	<0.05

^a Results reported by subcontracted offsite laboratory, Thermo Analytical, Inc.

^b Samples collected July 16, 1991.

Table 8-21
Herbicides in Stream and River Water, Cont'd.

Constituents (µg/L)^a	Upper Three Runs at Road A^b	Four Mile Creek at Road A^b	Pen Branch at Road A^b
Aldrin	<0.05	<0.05	<0.05
Alpha-BHC	<0.05	<0.05	<0.05
Beta-BHC	<0.05	<0.05	<0.05
Delta-BHC	<0.05	<0.05	<0.05
Lindane	<0.05	<0.05	<0.05
Alpha-chlordane	<0.05	<0.05	<0.05
Gamma-chlordane	<0.05	<0.05	<0.05
Tech, chlordane	<0.25	<0.25	<0.25
4,4-DDD	<0.05	<0.05	<0.05
4,4-DDE	<0.05	<0.05	<0.05
4,4-DDT	<0.05	<0.05	<0.05
Dieldrin	<0.05	<0.05	<0.05
Endosulfan I	<0.05	<0.05	<0.05
Endosulfan II	<0.05	<0.05	<0.05
Endosulfan sulfate	<0.05	<0.05	<0.05
Endrin	<0.05	<0.05	<0.05
Endrin aldehyde	<0.05	<0.05	<0.05
Heptachlor	<0.05	<0.05	<0.05
Heptachlor epoxide	<0.05	<0.05	<0.05
Methoxychlor	<0.20	<0.20	<0.20
Toxaphene	<2.50	<2.50	<2.50
2,4-D	<0.20	<0.20	<0.20
2,4,5-TP (Silvex)	<0.05	<0.05	<0.05

^a Results reported by subcontracted offsite laboratory, Thermo Analytical, Inc.

^b Samples collected July 16, 1991.

Table 8-22
Temperature Profile Surveys on Beaver Dam Creek and Steel Creek

Location	Ambient Temperature^a	Consent Order 84-4-W Allowable Temperature Above Ambient^b	Maximum Temperature Above Ambient
Beaver Dam Creek			
03-26-91	17.4°C	17.5°C	1.9°C
10-09-91	19.4°C	17.5°C	2.8°C
12-11-91	14.2°C	17.5°C	4.0°C
Steel Creek			
03-26-91	17.4°C	16.6°C	1.2°C
10-09-91	19.4°C	16.6°C	c
12-11-91	14.2°C	16.6°C	c

a Ambient temperature was determined from a temperature profile 100 yards upstream of Beaver Dam Creek.

b Consent Order between SCDHEC and DOE.

c The temperature in Steel Creek was below ambient.

Table 8-23
Radioactivity in River and Stream Sediment

Location	River Mile	Cs-137, pCi/g (dry weight)		
		1989	1990	1991
Savannah River				
Below Four Mile Creek	150.2	9.40 ± 01.1 E-01	5.00 ± 3.00 E-02	2.30 ± 0.34 E-01
Above Little Hell Landing	136.5	6.20 ± 0.90 E-01	6.70 ± 0.90 E-01	2.20 ± 0.21 E-01
Below Little Hell Landing	134.0	9.00 ± 1.20 E-01	1.00 ± 0.07 E+00	<1.75 E-01
Above Lower Three Runs	129.5	9.40 ± 1.20 E-01	1.10 ± 0.14 E+00	7.21 ± 0.56 E-01
Highway 301	118.7	7.20 ± 9.00 E-01	3.40 ± .500 E-01	4.32 ± 0.40 E-01
Demier's Landing (Control)	160.5	6.00 ± 3.00 E-02	1.70 ± 0.60 E-01	<1.42 E-01
SRS Stream				
Four Mile at Road A-7		8.50 ± 0.52 E+00	2.40 ± 0.140 E+01	6.19 ± 0.20 E+00
Four Mile A-7A (in a beaver pond)		4.10 ± 0.220 E+02	7.10 ± 0.40 E+00	5.14 ± 0.15 E+01
Four Mile Discharge at Swamp		8.60 ± 1.00 E-01	8.00 ± 1.00 E-01	5.27 ± 0.29 E-01
Pen Branch Discharge at Swamp		3.00 ± 0.28 E+00	3.60 ± 0.700 E-01	3.99 ± 0.18 E+00
Steel Creek at Road B		4.80 ± 0.270 E+01	8.80 ± 0.900 E-01	9.85 ± 0.42 E-01
Steel Creek Discharge at Swamp		2.60 ± 0.19 E+00	7.30 ± 0.700 E-01	3.66 ± 0.15 E+00
Steel Creek - Pen Branch Mouth		2.40 ± 0.18 E+00	1.40 ± 0.10 E+00	2.11 ± 0.11 E+00
Lower Three Runs Mouth		5.40 ± 0.38 E+00	4.80 ± 0.600 E-01	5.06 ± 0.47 E-01
Upper Three Runs Mouth (Control)		3.90 ± 0.900 E-01	2.60 ± 0.800 E-01	2.59 ± 0.34 E-01

Location	River Mile	K-40, pCi/g (dry weight)		
		1989	1990	1991
Savannah River				
Below Four Mile Creek	150.2	1.90 ± 0.100 E+01	1.20 ± 0.130 E+01	2.11 ± 0.12 E+01
Above Little Hell Landing	136.5	1.70 ± 0.180 E+01	1.70 ± 0.170 E+01	1.01 ± 0.06 E+01
Below Little Hell Landing	134.0	2.00 ± 0.220 E+01	1.80 ± 0.110 E+01	1.51 ± 0.11 E+01
Above Lower Three Runs	129.5	2.30 ± 0.230 E+01	1.50 ± 0.200 E+01	1.72 ± 0.11 E+01
Highway 301	118.7	1.70 ± 0.170 E+01	1.40 ± 0.140 E+01	1.23 ± 0.08 E+01
Demier's Landing (Control)	160.5	9.80 ± 1.20 E+00	1.50 ± 0.220 E+01	1.67 ± 0.11 E+01
SRS Streams				
Four Mile at Road A-7		<0.94	<1.5	<6.48 E-01
Four Mile A-7A (in a beaver pond)		4.70 ± 1.40 E+00	<1.0	<1.89 E+00
Four Mile Discharge at Swamp		1.10 ± 0.49 E+00	<1.0	<6.62 E-01
Pen Branch Discharge at Swamp		6.60 ± 1.40 E+00	1.30 ± 0.170 E+01	6.29 ± 0.72 E+00
Steel Creek at Road B		4.10 ± 1.30 E+00	<1.0	<5.36 E-01
Steel Creek Discharge at Swamp		1.30 ± 0.45 E+00	4.70 ± 3.50 E-01	3.53 ± 0.43 E+00
Steel Creek - Pen Branch Mouth		7.50 ± 3.70 E-01	6.50 ± 0.87 E+00	5.31 ± 0.56 E+00
Lower Three Runs Mouth		2.00 ± 0.200 E+01	1.30 ± 0.130 E+01	1.89 ± 0.11 E+01
Upper Three Runs Mouth (Control)		9.20 ± 1.40 E+00	1.60 ± 0.220 E+01	8.80 ± 0.71 E+00

– No quantifiable activity.

Table 8-23
Radioactivity in River and Stream Sediment, Cont'd.

		Co-60, pCi/g (dry weight)		
Location	River Mile	1989	1990	1991
Savannah River				
Below Four Mile Creek	150.2	—	—	<1.42 E-01
Above Little Hell Landing	136.5	—	—	<6.63 E-02
Below Little Hell Landing	134.0	—	—	<1.78 E-01
Above Lower Three Runs	129.5	—	—	<1.46 E-01
Highway 301	118.7	—	—	<1.29 E-01
Demier's Landi:g (Control)	160.5	—	—	<1.49 E-01
SRS Streams				
Four Mile at Road A-7		0.00 ± 0.01 E+00	3.70 ± 0.500 E-01	6.75 ± 0.86 E-02
Four Mile A-7A (in a beaver pond)		2.10 ± 0.19 E+00	9.00 ± 3.00 E-02	6.53 ± 0.46 E-01
Four Mile Discharge at Swamp		9.00 ± 3.00 E-02	—	6.49 ± 0.86 E-02
Pen Branch Discharge at Swamp		1.70 ± 0.16 E+00	—	7.78 ± 0.55 E-01
Steel Creek at Road B		1.40 ± 0.14 E+00	—	<4.41 E-02
Steel Creek Discharge at Swamp		0.00 ± 0.08 E+00	7.30 ± 0.700 E-01	<1.58 E-01
Steel Creek - Pen Branch Mouth		1.50 ± 0.500 E-01	—	1.15 ± 0.05 E+00
Lower Three Runs Mouth		—	—	<1.61 E-01
Upper Three Runs Mouth (Control)		—	—	<1.72 E-01
		Sr-90, pCi/g (dry weight)		
Location	River Mile	1989	1990	1991
Savannah River				
Below Four Mile Creek	150.2	7.00 ± 25.0 E-02	2.00 ± 6.00 E-02	1.62 ± 1.89 E-02
Above Little Hell Landing	136.5	3.00 ± 8.00 E-02	-2.00 ± 5.00 E-02	-0.17 ± 1.76 E-02
Below Little Hell Landing	134.0	7.00 ± 6.00 E-02	1.00 ± 5.00 E-02	-1.36 ± 2.24 E-02
Above Lower Three Runs	129.5	2.00 ± 6.00 E-02	2.00 ± 6.00 E-02	3.85 ± 2.06 E-02
Highway 301	118.7	1.00 ± 6.00 E-02	-1.00 ± 5.00 E-02	2.10 ± 1.72 E-02
Demier's Landing (Control)	160.5	2.00 ± 2.90 E-01	3.00 ± 4.00 E-02	-2.42 ± 2.41 E-02
SRS Streams				
Four Mile at Road A-7		2.00 ± 5.50 E-01	6.00 ± 8.00 E-02	4.12 ± 0.39 E-01
Four Mile A-7A (in a beaver pond)		2.5 ± 0.90 E+00	2.00 ± 6.00 E-02	9.11 ± 0.53 E-01
Four Mile Discharge at Swamp		4.50 ± 5.60 E-01	-1.00 ± 5.00 E-02	5.10 ± 2.11 E-02
Pen Branch Discharge at Swamp		1.20 ± 0.800 E-01	6.00 ± 7.00 E-02	1.24 ± 0.25 E-01
Steel Creek at Road B		1.60 ± 0.700 E-01	1.00 ± 5.00 E-02	5.10 ± 1.95 E-02
Steel Creek Discharge at Swamp		-3.00 ± 6.00 E-02	1.00 ± 5.00 E-02	4.25 ± 2.17 E-02
Steel Creek - Pen Branch Mouth		5.20 ± 3.70 E-01	0.00 ± 0.05 E+00	(no sample counted)
Lower Three Runs Mouth		2.00 ± 6.00 E-02	1.00 ± 5.00 E-02	1.29 ± 0.23 E-01
Upper Three Runs Mouth Control		1.30 ± 1.10 E-01	4.00 ± 6.00 E-02	5.59 ± 3.01 E-02

— No quantifiable activity.

Table 8-23
Radioactivity in River and Stream Sediment, Cont'd.

		Pu-238, pCi/g (dry weight)		
Location	River Mile	1989	1990	1991
Savannah River				
Below Four Mile Creek	150.2	8.90 ± 0.800 E-02	2.70 ± 1.00 E-02	2.89 ± 4.20 E-03
Above Little Hell Landing	136.5	2.20 ± 0.200 E-02	4.40 ± 1.00 E-02	1.52 ± 0.23 E-03
Below Little Hell Landing	134.0	—	6.40 ± 1.00 E-02	8.49 ± 0.33 E-04
Above Lower Three Runs	129.5	2.90 ± 0.300 E-02	7.10 ± 1.00 E-02	2.93 ± 1.20 E-04
Highway 301	118.7	1.00 ± 0.100 E-02	7.40 ± 1.00 E-02	1.42 ± 1.31 E-04
Demier's Landing (Control)	160.5	1.20 ± 0.200 E-02	1.20 ± 0.100 E-01	-0.80 ± 1.00 E-04
SRS Streams				
Four Mile at Road A-7		1.70 ± 0.900 E-02	7.80 ± 0.300 E-01	7.78 ± 0.26 E-02
Four Mile A-7A (in a beaver pond)		5.7 ± 0.031 E+00	2.30 ± 0.100 E-01	1.18 ± 0.01 E+00
Four Mile Discharge at Swamp		1.50 ± 0.200 E-02	7.00 ± 1.00 E-03	1.88 ± 0.27 E-03
Pen Branch Discharge at Swamp		7.00 ± 0.400 E-02	2.00 ± 0.200 E-02	1.00 ± 0.13 E-02
Steel Creek at Road B		2.10 ± 1.00 E-02	9.00 ± 1.00 E-02	1.46 ± 0.17 E-03
Steel Creek Discharge at Swamp		5.00 ± 1.00 E-03	2.00 ± 1.00 E-03	2.90 ± 0.56 E-03
Steel Creek - Pen Branch Mouth		4.90 ± 0.400 E-02	5.00 ± 1.00 E-02	1.25 ± 0.10 E-02
Lower Three Runs Mouth		—	4.00 ± 1.00 E-02	1.05 ± 0.22 E-03
Upper Three Runs Mouth (Control)		6.10 ± 0.400 E-02	6.00 ± 10.0 E-03	5.15 ± 1.88 E-03
		Pu-239, pCi/g (dry weight)		
Location	River Mile	1989	1990	1991
Savannah River				
Below Four Mile Creek	150.2	6.00 ± 2.00 E-03	1.00 ± 1.00 E-03	0.62 ± 1.38 E-03
Above Little Hell Landing	136.5	3.00 ± 1.00 E-03	2.00 ± 1.00 E-03	8.71 ± 1.51 E-04
Below Little Hell Landing	134.0	—	4.00 ± 1.00 E-03	1.91 ± 1.71 E-04
Above Lower Three Runs	129.5	4.00 ± 4.00 E-03	8.00 ± 2.00 E-03	2.32 ± 0.23 E-03
Highway 301	118.7	2.00 ± 1.00 E-03	5.00 ± 3.00 E-03	1.48 ± 0.19 E-03
Demier's Landing	160.5	2.00 ± 5.00 E-03	9.00 ± 3.00 E-03	6.42 ± 8.30 E-05
SRS Streams				
Four Mile at Road A-7		5.40 ± 0.500 E-02	2.30 ± 0.100 E-01	3.16 ± 0.16 E-02
Four Mile A-7A (in a beaver pond)		1.1 ± 0.014 E+00	6.90 ± 1.00 E-02	3.73 ± 0.06 E-01
Four Mile Discharge at Swamp		6.00 ± 1.00 E-03	3.00 ± 10.0 E-03	3.07 ± 0.33 E-03
Pen Branch Discharge at Swamp		1.90 ± 0.200 E-02	2.00 ± 1.00 E-03	2.78 ± 0.21 E-02
Steel Creek at Road B		9.30 ± 0.600 E-02	7.00 ± 3.00 E-03	4.31 ± 0.26 E-03
Steel Creek Discharge at Swamp		3.00 ± 1.00 E-03	2.00 ± 2.00 E-04	7.14 ± 0.83 E-03
Steel Creek - Pen Branch Mouth		1.40 ± 2.00 E-02	4.00 ± 1.00 E-03	2.56 ± 0.14 E-02
Lower Three Runs Mouth		—	1.00 ± 10.0 E-03	1.71 ± 0.23 E-03
Upper Three Runs Mouth (Control)		2.00 ± 0.200 E-02	7.00 ± 2.00 E-03	6.48 ± 1.66 E-03

– No quantifiable activity.

Table 8-24
Herbicides in Stream and River Sediment

Constituents (µg/kg)^a	River 2, Above SRS^b	River 10 Below SRS^b	Upper Three Runs at Road F^b
Aldrin	<97.4	<97.4	<97.4
Alpha-BHC	<97.4	<97.4	<97.4
Beta-BHC	<97.4	<97.4	<97.4
Delta-BHC	<97.4	<97.4	<97.4
Lindane	<97.4	<97.4	<97.4
Alpha-chlordane	<97.4	<97.4	<97.4
Gamma-chlordane	<97.4	<97.4	<97.4
Tech. chlordane	<487	<487	<487
4,4'-DDD	<97.4	<97.4	<97.4
4,4'-DDE	<97.4	<97.4	<97.4
4,4'-DDT	<97.4	<97.4	<97.4
Dieldrin	<97.4	<97.4	<97.4
Endosulfan I	<97.4	<97.4	<97.4
Endosulfan II	<97.4	<97.4	<97.4
Endosulfan sulfate	<97.4	<97.4	<97.4
Endrin	<97.4	<97.4	<97.4
Endrin aldehyde	<97.4	<97.4	<97.4
Heptachlor	<97.4	<97.4	<97.4
Heptachlor epoxide	<97.4	<97.4	<97.4
Methoxychlor	<390	<390	<390
Toxaphene	<4870	<4870	<4870
2,4-D	<195	<195	<195
2,4,5-TP (Silvex)	<48.7	<48.7	<48.7

a Results reported by subcontracted offsite laboratory, TMA/Eberline.

b Samples collected July 12, 1991

Table 8-24
Herbicides in Stream and River Sediment, Cont'd.

Constituents (µg/kg) ^a	Steel Creek at Road A ^b	Par Pond Pumphouse ^b	Lower Three Runs at Road A ^b
Aldrin	<97.4	<97.4	<97.4
Alpha-BHC	<97.4	<97.4	<97.4
Beta-BHC	<97.4	<97.4	<97.4
Delta-BHC	<97.4	<97.4	<97.4
Lindane	<97.4	<97.4	<97.4
Alpha-chlordane	<97.4	<97.4	<97.4
Gamma-chlordane	<97.4	<97.4	<97.4
Tech. chlordane	<487	<487	<487
4,4'-DDD	<97.4	<97.4	<97.4
4,4'-DDE	<97.4	<97.4	<97.4
4,4'-DDT	<97.4	<97.4	<97.4
Dieldrin	<97.4	<97.4	<97.4
Endosulfan I	<97.4	<97.4	<97.4
Endosulfan II	<97.4	<97.4	<97.4
Endosulfan sulfate	<97.4	<97.4	<97.4
Endrin	<97.4	<97.4	<97.4
Endrin aldehyde	<97.4	<97.4	<97.4
Heptachlor	<97.4	<97.4	<97.4
Heptachlor epoxide	<97.4	<97.4	<97.4
Methoxychlor	<390	<390	<390
Toxaphene	<4870	<4870	<4870
2,4-D	<195	<195	<195
2,4,5-TP (Silvex)	<48.7	<48.7	<48.7

^a Results reported by subcontracted offsite laboratory, TMA/Eberline.

^b Samples collected July 12, 1991

Table 8-24
Herbicides in Stream and River Sediment, Cont'd.

Constituents ($\mu\text{g/kg}$) ^a	Upper Three Runs at Road A ^b	Four Mile Creek at Road A ^b	Pen Branch at Road A ^b
Aldrin	<97.4	<97.4	<97.4
Alpha-BHC	<97.4	<97.4	<97.4
Beta-BHC	<97.4	<97.4	<97.4
Delta-BHC	<97.4	<97.4	<97.4
Lindane	<97.4	<97.4	<97.4
Alpha-chlordane	<97.4	<97.4	<97.4
Gamma-chlordane	<97.4	<97.4	<97.4
Tech. chlordane	<487	<487	<487
4,4'-DDD	<97.4	<97.4	<97.4
4,4'-DDE	<97.4	<97.4	<97.4
4,4'-DDT	<97.4	<97.4	<97.4
Dieldrin	<97.4	<97.4	<97.4
Endosulfan I	<97.4	<97.4	<97.4
Endosulfan II	<97.4	<97.4	<97.4
Endosulfan sulfate	<97.4	<97.4	<97.4
Endrin	<97.4	<97.4	<97.4
Endrin aldehyde	<97.4	<97.4	<97.4
Heptachlor	<97.4	<97.4	<97.4
Heptachlor epoxide	<97.4	<97.4	<97.4
Methoxychlor	<390	<390	<390
Toxaphene	<4870	<4870	<4870
2,4-D	<195	<195	<195
2,4,5-TP (Silvex)	<48.7	<48.7	<48.7

^a Results reported by subcontracted offsite laboratory, TMA/Eberline.

^b Samples collected July 12, 1991

Table 8-25
Radioactivity in Drinking Water

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha ($\mu\text{Ci/mL}$)				
ORA Site	2	$8.38 \pm 3.42 \text{ E-10}$	$-1.74 \pm 1.20 \text{ E-10}$	$3.32 \pm 7.16 \text{ E-10}$
241-24H	4	$5.78 \pm 0.81 \text{ E-09}$	$9.88 \pm 2.99 \text{ E-10}$	$3.07 \pm 1.99 \text{ E-09}$
A Area	4	$1.05 \pm 0.39 \text{ E-09}$	$-1.55 \pm 1.36 \text{ E-01}$	$4.74 \pm 5.07 \text{ E-10}$
Allendale Gate	4	$2.18 \pm 2.76 \text{ E-10}$	$-2.11 \pm 1.46 \text{ E-10}$	$-0.72 \pm 1.98 \text{ E-10}$
Barnwell Gate	4	$4.59 \pm 2.83 \text{ E-10}$	$-0.97 \pm 1.58 \text{ E-10}$	$1.43 \pm 2.48 \text{ E-10}$
Classification Yard	3	$1.08 \pm 0.43 \text{ E-09}$	$4.49 \pm 2.82 \text{ E-10}$	$6.99 \pm 3.36 \text{ E-10}$
Emer Oper Center	4	$9.61 \pm 3.87 \text{ E-10}$	$2.34 \pm 2.97 \text{ E-10}$	$5.94 \pm 3.03 \text{ E-10}$
Firing Range	4	$3.78 \pm 0.60 \text{ E-09}$	$1.64 \pm 0.41 \text{ E-09}$	$3.13 \pm 1.01 \text{ E-09}$
Forestry Bldg	3	$4.19 \pm 0.63 \text{ E-09}$	$2.70 \pm 0.53 \text{ E-09}$	$3.50 \pm 0.75 \text{ E-09}$
Jackson Gate	4	$4.11 \pm 0.64 \text{ E-09}$	$9.00 \pm 3.57 \text{ E-10}$	$2.14 \pm 1.47 \text{ E-09}$
Par Pond Lab	4	$1.68 \pm 0.51 \text{ E-09}$	$-1.96 \pm 1.37 \text{ E-10}$	$6.75 \pm 7.76 \text{ E-10}$
Talatha Gate	4	$1.55 \pm 0.12 \text{ E-08}$	$4.57 \pm 0.68 \text{ E-09}$	$1.18 \pm 0.49 \text{ E-08}$
Talatha Site	2	$8.34 \pm 3.62 \text{ E-10}$	$1.19 \pm 2.59 \text{ E-10}$	$4.77 \pm 5.06 \text{ E-10}$
TC-1	4	$2.50 \pm 0.53 \text{ E-09}$	$1.29 \pm 0.39 \text{ E-09}$	$1.78 \pm 0.52 \text{ E-09}$
TNX	4	$6.22 \pm 4.52 \text{ E-10}$	$2.38 \pm 2.55 \text{ E-10}$	$3.46 \pm 1.84 \text{ E-10}$
Williston Gate	4	$1.24 \pm 2.70 \text{ E-10}$	$-2.10 \pm 1.40 \text{ E-10}$	$-0.19 \pm 1.59 \text{ E-10}$
Z Area	4	$2.54 \pm 0.56 \text{ E-09}$	$4.97 \pm 3.01 \text{ E-10}$	$1.35 \pm 0.98 \text{ E-09}$
105-C Bldg	11	$2.86 \pm 0.56 \text{ E-09}$	$-0.98 \pm 1.71 \text{ E-10}$	$1.05 \pm 0.85 \text{ E-09}$
105-K Bldg	11	$1.64 \pm 0.45 \text{ E-09}$	$1.97 \pm 2.42 \text{ E-10}$	$6.80 \pm 4.60 \text{ E-10}$
105-L Bldg	11	$1.55 \pm 0.42 \text{ E-09}$	$2.22 \pm 1.80 \text{ E-10}$	$5.79 \pm 3.56 \text{ E-10}$
105-P Bldg	11	$1.23 \pm 0.41 \text{ E-09}$	$2.84 \pm 2.16 \text{ E-10}$	$7.79 \pm 3.81 \text{ E-10}$
221-F Bldg	11	$3.41 \pm 0.65 \text{ E-09}$	$7.03 \pm 3.73 \text{ E-10}$	$1.96 \pm 0.85 \text{ E-09}$
221-H Bldg	11	$3.41 \pm 0.59 \text{ E-09}$	$6.57 \pm 3.13 \text{ E-10}$	$1.95 \pm 0.87 \text{ E-09}$
617-G Wackenhut	3	$1.89 \pm 0.44 \text{ E-09}$	$5.08 \pm 2.69 \text{ E-10}$	$1.17 \pm 0.69 \text{ E-09}$
681-1G	4	$1.08 \pm 0.39 \text{ E-09}$	$4.78 \pm 3.07 \text{ E-10}$	$7.86 \pm 2.99 \text{ E-10}$
681-3G	4	$2.05 \pm 0.49 \text{ E-09}$	$9.64 \pm 3.69 \text{ E-10}$	$1.48 \pm 0.45 \text{ E-09}$
701-1F	3	$4.70 \pm 0.88 \text{ E-09}$	$8.11 \pm 3.20 \text{ E-10}$	$3.05 \pm 2.01 \text{ E-09}$
701-1H	3	$2.61 \pm 0.54 \text{ E-09}$	$1.45 \pm 0.40 \text{ E-09}$	$2.20 \pm 0.65 \text{ E-09}$
701-12G Barricade 7	4	$1.45 \pm 1.33 \text{ E-10}$	$2.97 \pm 2.62 \text{ E-10}$	$-0.13 \pm 2.08 \text{ E-10}$
701-13G Barricade 6	4	$2.05 \pm 0.48 \text{ E-09}$	$9.65 \pm 3.32 \text{ E-10}$	$1.60 \pm 0.47 \text{ E-09}$
701-8G Barricade 8	4	$1.90 \pm 0.42 \text{ E-09}$	$7.84 \pm 3.16 \text{ E-10}$	$1.27 \pm 0.48 \text{ E-09}$
704-F	4	$4.67 \pm 0.75 \text{ E-09}$	$1.27 \pm 0.48 \text{ E-09}$	$2.91 \pm 1.54 \text{ E-09}$
704-H	4	$6.41 \pm 0.81 \text{ E-09}$	$2.58 \pm 0.54 \text{ E-09}$	$4.12 \pm 1.65 \text{ E-09}$

Table 8-25
Radioactivity in Drinking Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
704-S DWPF	4	$3.81 \pm 0.62 \text{ E-09}$	$8.80 \pm 3.58 \text{ E-10}$	$1.96 \pm 1.37 \text{ E-09}$
772-F	4	$4.08 \pm 0.75 \text{ E-09}$	$6.42 \pm 2.52 \text{ E-10}$	$1.96 \pm 1.61 \text{ E-09}$
Aiken Post Office	2	$9.07 \pm 3.98 \text{ E-10}$	$3.51 \pm 2.96 \text{ E-10}$	$6.29 \pm 3.93 \text{ E-10}$
Allendale Post Office	2	$0.02 \pm 3.63 \text{ E-10}$	$-0.13 \pm 3.27 \text{ E-10}$	$-0.54 \pm 1.03 \text{ E-11}$
Augusta Post Office	2	$-0.08 \pm 2.24 \text{ E-10}$	$-2.27 \pm 1.53 \text{ E-10}$	$-1.18 \pm 1.55 \text{ E-10}$
Barnwell Post Office	2	$0.02 \pm 2.48 \text{ E-10}$	$-2.37 \pm 1.62 \text{ E-10}$	$-1.17 \pm 1.69 \text{ E-10}$
Bath Post Office	2	$1.54 \pm 0.51 \text{ E-09}$	$9.79 \pm 4.23 \text{ E-10}$	$1.26 \pm 0.40 \text{ E-09}$
Blackville Post Office	2	$1.90 \pm 0.67 \text{ E-09}$	$-0.92 \pm 1.55 \text{ E-09}$	$0.49 \pm 1.99 \text{ E-09}$
Clearwater Post Office	2	$4.86 \pm 1.01 \text{ E-09}$	$9.04 \pm 5.45 \text{ E-10}$	$2.88 \pm 2.80 \text{ E-09}$
Jackson Post Office	2	$4.39 \pm 0.75 \text{ E-09}$	$2.08 \pm 0.56 \text{ E-09}$	$3.24 \pm 1.63 \text{ E-09}$
Langley Post Office	2	$6.76 \pm 0.82 \text{ E-09}$	$2.64 \pm 0.56 \text{ E-09}$	$4.70 \pm 2.91 \text{ E-09}$
New Ellenton Post Office	2	$1.65 \pm 0.43 \text{ E-09}$	$1.25 \pm 0.42 \text{ E-09}$	$1.45 \pm 0.28 \text{ E-09}$
N Augusta Post Office	2	$-0.09 \pm 2.26 \text{ E-10}$	$-1.05 \pm 1.79 \text{ E-10}$	$-5.73 \pm 6.80 \text{ E-11}$
Sardis Post Office	2	$0.02 \pm 1.21 \text{ E-09}$	$-2.33 \pm 3.56 \text{ E-10}$	$-1.07 \pm 1.77 \text{ E-10}$
Waynesboro Post Office	2	$3.24 \pm 4.01 \text{ E-10}$	$1.20 \pm 2.91 \text{ E-10}$	$2.22 \pm 1.44 \text{ E-10}$
Williston Post Office	2	$3.03 \pm 0.68 \text{ E-09}$	$7.30 \pm 5.06 \text{ E-10}$	$1.88 \pm 1.62 \text{ E-09}$
Beaufort Finished	12	$4.84 \pm 3.41 \text{ E-10}$	$-2.24 \pm 1.53 \text{ E-10}$	$0.92 \pm 2.41 \text{ E-10}$
Beaufort Raw	12	$7.60 \pm 2.49 \text{ E-10}$	$-1.11 \pm 1.83 \text{ E-10}$	$2.07 \pm 2.81 \text{ E-10}$
N Augusta Finished	12	$6.08 \pm 2.86 \text{ E-10}$	$-2.08 \pm 1.45 \text{ E-10}$	$0.27 \pm 2.26 \text{ E-10}$
N Augusta Raw	12	$3.08 \pm 1.51 \text{ E-10}$	$-2.08 \pm 1.43 \text{ E-10}$	$0.23 \pm 1.42 \text{ E-10}$
Port Wentworth Finished	12	$1.12 \pm 2.84 \text{ E-10}$	$-2.67 \pm 1.75 \text{ E-10}$	$-0.86 \pm 1.20 \text{ E-10}$
Port Wentworth Raw	12	$3.45 \pm 3.10 \text{ E-10}$	$-2.35 \pm 1.57 \text{ E-10}$	$-0.07 \pm 1.74 \text{ E-10}$
400-D Finished	12	$1.43 \pm 2.68 \text{ E-10}$	$-3.32 \pm 2.15 \text{ E-10}$	$-1.05 \pm 1.46 \text{ E-10}$
400-D Raw	12	$4.55 \pm 3.30 \text{ E-10}$	$-1.08 \pm 1.66 \text{ E-10}$	$0.82 \pm 1.64 \text{ E-10}$
Nonvolatile Beta ($\mu\text{Ci/mL}$)				
ORA Site	2	$6.76 \pm 4.52 \text{ E-10}$	$1.72 \pm 3.94 \text{ E-10}$	$4.24 \pm 3.56 \text{ E-10}$
241-24H	4	$7.98 \pm 0.54 \text{ E-09}$	$3.41 \pm 0.56 \text{ E-09}$	$6.45 \pm 2.06 \text{ E-09}$
A Area	4	$3.05 \pm 0.61 \text{ E-09}$	$1.08 \pm 0.48 \text{ E-09}$	$1.75 \pm 0.88 \text{ E-09}$
Allendale Gate	4	$1.71 \pm 0.52 \text{ E-09}$	$7.91 \pm 4.67 \text{ E-10}$	$1.25 \pm 0.38 \text{ E-09}$
Barnwell Gate	4	$1.35 \pm 0.48 \text{ E-09}$	$6.24 \pm 4.45 \text{ E-10}$	$9.13 \pm 3.10 \text{ E-10}$
Classification Yard	3	$3.97 \pm 0.63 \text{ E-09}$	$2.46 \pm 0.56 \text{ E-09}$	$3.20 \pm 0.76 \text{ E-09}$
Emer Oper Center	4	$3.62 \pm 0.61 \text{ E-09}$	$7.57 \pm 4.52 \text{ E-10}$	$2.07 \pm 1.18 \text{ E-09}$
Firing Range	4	$3.92 \pm 0.59 \text{ E-09}$	$1.62 \pm 0.49 \text{ E-09}$	$3.00 \pm 1.07 \text{ E-09}$
Forestry Bldg	3	$4.70 \pm 0.63 \text{ E-09}$	$2.38 \pm 0.52 \text{ E-09}$	$3.28 \pm 1.25 \text{ E-09}$

Table 8-25
Radioactivity in Drinking Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Jackson Gate	4	4.16 $\pm$ 0.61 E-09	2.08 $\pm$ 0.54 E-09	3.16 $\pm$ 1.13 E-09
Par Pond Lab	4	3.27 $\pm$ 0.62 E-09	9.08 $\pm$ 5.18 E-10	2.18 $\pm$ 1.26 E-09
Talatha Gate	4	1.04 $\pm$ 0.06 E-08	4.78 $\pm$ 0.65 E-09	8.57 $\pm$ 2.57 E-09
Talatha Site	2	1.30 $\pm$ 0.53 E-09	5.68 $\pm$ 4.68 E-10	9.36 $\pm$ 5.21 E-10
TC-1	4	3.69 $\pm$ 0.61 E-09	1.81 $\pm$ 0.51 E-09	2.75 $\pm$ 0.93 E-09
TNX	4	4.86 $\pm$ 0.70 E-09	4.14 $\pm$ 0.66 E-09	4.55 $\pm$ 0.36 E-09
Williston Gate	4	1.14 $\pm$ 0.47 E-09	2.44 $\pm$ 4.51 E-10	7.20 $\pm$ 3.85 E-10
Z Area	4	3.62 $\pm$ 0.60 E-09	1.54 $\pm$ 0.49 E-09	2.45 $\pm$ 1.01 E-09
105-C Bldg	11	3.49 $\pm$ 0.59 E-09	6.13 $\pm$ 4.43 E-10	1.88 $\pm$ 0.92 E-09
105-K Bldg	11	4.67 $\pm$ 0.65 E-09	1.07 $\pm$ 0.49 E-09	2.81 $\pm$ 0.90 E-09
105-L Bldg	11	3.30 $\pm$ 0.57 E-09	1.33 $\pm$ 0.50 E-09	2.16 $\pm$ 0.59 E-09
105-P Bldg	11	4.08 $\pm$ 0.60 E-09	1.49 $\pm$ 0.49 E-09	2.64 $\pm$ 0.73 E-09
221-F Bldg	11	7.51 $\pm$ 0.76 E-09	2.70 $\pm$ 0.57 E-09	4.85 $\pm$ 1.96 E-09
221-H Bldg	11	6.71 $\pm$ 0.74 E-09	1.56 $\pm$ 0.49 E-09	4.69 $\pm$ 1.79 E-09
617-G Wackenhut	3	1.95 $\pm$ 0.52 E-09	1.38 $\pm$ 0.49 E-09	1.61 $\pm$ 0.30 E-09
681-1G	4	5.43 $\pm$ 0.67 E-09	3.72 $\pm$ 0.61 E-09	4.69 $\pm$ 0.71 E-09
681-3G	4	4.38 $\pm$ 0.63 E-09	3.38 $\pm$ 0.60 E-09	3.98 $\pm$ 0.48 E-09
701-1F	3	8.68 $\pm$ 0.85 E-09	9.19 $\pm$ 4.44 E-10	6.02 $\pm$ 4.42 E-09
701-1H	3	6.65 $\pm$ 0.72 E-09	5.92 $\pm$ 0.69 E-09	6.35 $\pm$ 0.38 E-09
701-12G Barricade 7	4	2.65 $\pm$ 0.56 E-09	1.08 $\pm$ 0.47 E-09	1.82 $\pm$ 0.76 E-09
701-13G Barricade 6	4	2.51 $\pm$ 0.54 E-09	4.27 $\pm$ 4.23 E-10	1.61 $\pm$ 0.94 E-09
701-8G Barricade 8	4	1.77 $\pm$ 0.49 E-09	1.08 $\pm$ 0.46 E-09	1.34 $\pm$ 0.30 E-09
704-F	4	6.22 $\pm$ 0.69 E-09	2.08 $\pm$ 0.57 E-09	4.63 $\pm$ 1.78 E-09
704-H	4	1.02 $\pm$ 0.08 E-08	5.55 $\pm$ 0.68 E-09	7.02 $\pm$ 2.17 E-09
704-S DWPF	4	8.27 $\pm$ 0.78 E-09	2.08 $\pm$ 0.55 E-09	4.17 $\pm$ 2.78 E-09
772-F	4	4.73 $\pm$ 0.66 E-09	2.27 $\pm$ 0.39 E-09	3.48 $\pm$ 1.06 E-09
Aiken Post Office	2	2.89 $\pm$ 0.63 E-09	1.05 $\pm$ 0.49 E-09	1.97 $\pm$ 1.30 E-09
Allendale Post Office	2	1.93 $\pm$ 0.63 E-09	9.19 $\pm$ 5.34 E-10	1.42 $\pm$ 0.72 E-09
Augusta Post Office	2	2.00 $\pm$ 0.54 E-09	1.67 $\pm$ 0.56 E-09	1.84 $\pm$ 0.23 E-09
Barnwell Post Office	2	7.57 $\pm$ 4.83 E-10	4.58 $\pm$ 4.99 E-10	6.07 $\pm$ 2.11 E-10
Bath Post Office	2	1.86 $\pm$ 0.55 E-09	8.72 $\pm$ 5.31 E-10	1.37 $\pm$ 0.70 E-09
Blackville Post Office	2	2.67 $\pm$ 0.68 E-09	1.73 $\pm$ 0.66 E-09	2.20 $\pm$ 0.66 E-09
Clearwater Post Office	2	5.14 $\pm$ 0.75 E-09	1.54 $\pm$ 0.62 E-09	3.34 $\pm$ 2.54 E-09
Jackson Post Office	2	5.15 $\pm$ 0.74 E-09	1.95 $\pm$ 0.55 E-09	3.55 $\pm$ 2.27 E-09

Table 8-25
Radioactivity in Drinking Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Langley Post Office	2	5.68 $\pm$ 0.69 E-09	4.80 $\pm$ 0.70 E-09	5.24 $\pm$ 0.62 E-09
New Ellenton Post Office	2	2.16 $\pm$ 0.53 E-09	8.18 $\pm$ 5.05 E-10	1.49 $\pm$ 0.95 E-09
N Augusta Post Office	2	1.80 $\pm$ 0.57 E-09	7.84 $\pm$ 4.68 E-10	1.29 $\pm$ 0.72 E-09
Sardis Post Office	2	2.70 $\pm$ 0.78 E-09	2.61 $\pm$ 0.69 E-09	2.66 $\pm$ 0.07 E-09
Waynesboro Post Office	2	2.00 $\pm$ 0.60 E-09	1.27 $\pm$ 0.54 E-09	1.64 $\pm$ 0.52 E-09
Williston Post Office	2	1.74 $\pm$ 0.59 E-09	6.76 $\pm$ 5.20 E-10	1.21 $\pm$ 0.76 E-09
Beaufort Finished	12	2.43 $\pm$ 0.59 E-09	1.46 $\pm$ 0.50 E-09	1.90 $\pm$ 0.32 E-09
Beaufort Raw	12	2.70 $\pm$ 0.53 E-09	1.16 $\pm$ 0.50 E-09	2.21 $\pm$ 0.43 E-09
N Augusta Finished	12	2.54 $\pm$ 0.59 E-09	1.16 $\pm$ 0.49 E-09	2.01 $\pm$ 0.39 E-09
N Augusta Raw	12	2.95 $\pm$ 0.63 E-09	1.28 $\pm$ 0.33 E-09	2.00 $\pm$ 0.54 E-09
Port Wentworth Finished	12	2.70 $\pm$ 0.57 E-09	1.35 $\pm$ 0.48 E-09	2.25 $\pm$ 0.43 E-09
Port Wentworth Raw	12	3.21 $\pm$ 0.61 E-09	1.49 $\pm$ 0.46 E-09	2.30 $\pm$ 0.58 E-09
400-D Finished	12	3.56 $\pm$ 0.67 E-09	1.29 $\pm$ 0.56 E-09	2.11 $\pm$ 0.60 E-09
400-D Raw	12	2.87 $\pm$ 0.62 E-09	1.20 $\pm$ 0.45 E-09	1.98 $\pm$ 0.52 E-09
Tritium (μCl/mL)				
ORA Site	2	6.03 $\pm$ 1.52 E-07	0.39 $\pm$ 1.14 E-07	3.21 $\pm$ 3.99 E-07
241-24H	4	3.39 $\pm$ 1.47 E-07	0.81 $\pm$ 1.34 E-07	1.91 $\pm$ 1.08 E-07
A Area	4	3.89 $\pm$ 1.48 E-07	9.46 $\pm$ 9.41 E-08	2.59 $\pm$ 1.35 E-07
Allendale Gate	4	3.84 $\pm$ 1.47 E-07	1.30 $\pm$ 1.09 E-07	2.92 $\pm$ 1.16 E-07
Barnwell Gate	4	3.62 $\pm$ 1.47 E-07	0.26 $\pm$ 1.02 E-07	2.04 $\pm$ 1.75 E-07
Classification Yard	4	5.36 $\pm$ 1.46 E-07	-1.82 $\pm$ 1.00 E-07	2.47 $\pm$ 3.22 E-07
Emer Oper Center	4	5.31 $\pm$ 1.49 E-07	-0.38 $\pm$ 1.01 E-07	1.31 $\pm$ 2.68 E-07
Firing Range	4	1.78 $\pm$ 0.16 E-06	1.97 $\pm$ 1.46 E-07	1.08 $\pm$ 0.65 E-06
Forestry Bldg	4	1.51 $\pm$ 0.16 E-06	9.01 $\pm$ 1.53 E-07	1.18 $\pm$ 0.26 E-06
Jackson Gate	4	4.63 $\pm$ 1.49 E-07	0.24 $\pm$ 1.46 E-07	2.56 $\pm$ 1.98 E-07
Par Pond Lab	4	5.41 $\pm$ 1.47 E-07	-6.80 $\pm$ 9.41 E-08	2.53 $\pm$ 3.30 E-07
Talatha Gate	2	1.31 $\pm$ 0.15 E-06	7.98 $\pm$ 1.08 E-07	1.04 $\pm$ 0.22 E-06
Talatha Site	2	9.37 $\pm$ 1.53 E-07	7.52 $\pm$ 1.65 E-08	5.06 $\pm$ 6.10 E-07
TC-1	4	4.12 $\pm$ 1.47 E-07	-0.43 $\pm$ 1.02 E-07	2.05 $\pm$ 2.26 E-07
TNX	4	3.71 $\pm$ 1.47 E-07	-1.47 $\pm$ 1.00 E-07	1.63 $\pm$ 2.29 E-07
Williston Gate	4	4.33 $\pm$ 1.45 E-07	-1.49 $\pm$ 1.47 E-07	1.73 $\pm$ 2.88 E-07
Z Area	4	4.27 $\pm$ 1.47 E-07	-0.86 $\pm$ 1.50 E-07	1.97 $\pm$ 2.47 E-07
105-C Bldg	11	1.83 $\pm$ 0.13 E-06	-0.56 $\pm$ 1.01 E-07	3.19 $\pm$ 5.32 E-07
105-K Bldg	12	6.78 $\pm$ 1.48 E-07	-0.46 $\pm$ 1.49 E-07	2.73 $\pm$ 1.95 E-07

Table 8-25
Radioactivity in Drinking Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
105-L Bldg	11	6.44 $\pm$ 1.48 E-07	0.57 $\pm$ 1.02 E-07	2.48 $\pm$ 1.85 E-07
105-P Bldg	12	1.30 $\pm$ 0.15 E-06	-3.95 $\pm$ 9.40 E-08	3.98 $\pm$ 4.35 E-07
221-F Bldg	11	4.37 $\pm$ 1.46 E-07	-0.71 $\pm$ 1.10 E-07	1.91 $\pm$ 1.79 E-07
221-H Bldg	11	7.43 $\pm$ 1.55 E-07	-1.15 $\pm$ 1.16 E-07	2.51 $\pm$ 2.69 E-07
617-G Wackenhut	4	1.77 $\pm$ 0.16 E-06	7.68 $\pm$ 1.56 E-07	1.27 $\pm$ 0.54 E-06
681-1G	4	1.64 $\pm$ 0.15 E-06	-0.80 $\pm$ 1.46 E-07	5.16 $\pm$ 7.83 E-07
681-3G	4	3.60 $\pm$ 1.48 E-07	0.00 $\pm$ 1.01 E-07	1.91 $\pm$ 1.91 E-07
701-1F	4	5.75 $\pm$ 1.46 E-07	-3.70 $\pm$ 9.41 E-08	2.50 $\pm$ 2.88 E-07
701-1H	4	4.91 $\pm$ 1.48 E-07	1.18 $\pm$ 1.53 E-07	3.41 $\pm$ 1.62 E-07
701-12G Barricade 7	4	1.05 $\pm$ 0.11 E-06	3.42 $\pm$ 1.52 E-07	7.43 $\pm$ 3.33 E-07
701-13G Barricade 6	4	3.05 $\pm$ 0.16 E-06	2.38 $\pm$ 0.17 E-06	2.75 $\pm$ 0.30 E-06
701-8G Barricade 8	4	3.17 $\pm$ 0.17 E-06	3.01 $\pm$ 0.17 E-06	3.12 $\pm$ 0.08 E-06
704-F	4	3.63 $\pm$ 1.53 E-07	-4.30 $\pm$ 9.39 E-08	1.61 $\pm$ 1.94 E-07
704-H	4	5.60 $\pm$ 1.49 E-07	1.31 $\pm$ 0.94 E-07	2.83 $\pm$ 1.98 E-07
704-S DWPF	4	5.50 $\pm$ 1.45 E-07	-6.03 $\pm$ 9.88 E-08	2.34 $\pm$ 3.08 E-07
772-F	4	3.13 $\pm$ 1.46 E-07	-0.57 $\pm$ 1.10 E-07	0.68 $\pm$ 2.12 E-07
Aiken Post Office	2	6.44 $\pm$ 1.51 E-07	4.51 $\pm$ 1.17 E-07	5.47 $\pm$ 1.37 E-07
Allendale Post Office	2	3.55 $\pm$ 1.47 E-07	0.34 $\pm$ 1.14 E-07	1.94 $\pm$ 2.27 E-07
Augusta Post Office	2	5.01 $\pm$ 1.49 E-07	1.04 $\pm$ 1.14 E-07	3.02 $\pm$ 2.81 E-07
Barnwell Post Office	2	3.27 $\pm$ 1.49 E-07	0.81 $\pm$ 1.14 E-07	2.04 $\pm$ 1.74 E-07
Bath Post Office	2	5.20 $\pm$ 1.49 E-07	2.20 $\pm$ 1.15 E-07	3.70 $\pm$ 2.12 E-07
Blackville Post Office	2	4.42 $\pm$ 1.50 E-07	0.96 $\pm$ 1.15 E-07	2.69 $\pm$ 2.44 E-07
Clearwater Post Office	2	6.53 $\pm$ 1.51 E-07	5.68 $\pm$ 1.67 E-08	3.55 $\pm$ 4.21 E-07
Jackson Post Office	2	9.88 $\pm$ 1.54 E-07	8.94 $\pm$ 1.69 E-08	5.39 $\pm$ 6.35 E-07
Langley Post Office	2	5.84 $\pm$ 1.51 E-07	1.70 $\pm$ 1.14 E-07	3.77 $\pm$ 2.92 E-07
New Ellenton Post Office	2	7.95 $\pm$ 1.51 E-07	4.69 $\pm$ 1.65 E-08	4.21 $\pm$ 5.29 E-07
N Augusta Post Office	2	5.29 $\pm$ 1.51 E-07	3.06 $\pm$ 1.16 E-07	4.17 $\pm$ 1.58 E-07
Sardis Post Office	2	8.32 $\pm$ 1.53 E-07	3.02 $\pm$ 1.16 E-07	5.67 $\pm$ 3.75 E-07
Waynesboro Post Office	2	7.12 $\pm$ 1.52 E-07	2.67 $\pm$ 1.17 E-07	4.89 $\pm$ 3.15 E-07
Williston Post Office	2	8.13 $\pm$ 1.52 E-07	3.05 $\pm$ 1.15 E-07	5.59 $\pm$ 3.59 E-07
Beaufort Finished	12	2.75 $\pm$ 0.17 E-06	7.64 $\pm$ 1.49 E-07	1.58 $\pm$ 0.64 E-06
Beaufort Raw	12	2.57 $\pm$ 0.17 E-06	6.15 $\pm$ 1.20 E-07	1.51 $\pm$ 0.69 E-06
N Augusta Finished	11	1.01 $\pm$ 0.15 E-06	-2.97 $\pm$ 9.85 E-08	4.08 $\pm$ 3.25 E-07
N Augusta Raw	11	8.37 $\pm$ 1.54 E-07	6.41 $\pm$ 9.99 E-08	3.81 $\pm$ 2.48 E-07

Table 8-25
Radioactivity in Drinking Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Port Wentworth Finished	12	$3.30 \pm 0.14 \text{ E-06}$	$9.95 \pm 1.56 \text{ E-07}$	$1.92 \pm 0.74 \text{ E-06}$
Port Wentworth Raw	12	$4.00 \pm 0.18 \text{ E-06}$	$7.65 \pm 1.54 \text{ E-07}$	$1.95 \pm 0.87 \text{ E-06}$
400-D Finished	11	$1.86 \pm 0.16 \text{ E-06}$	$2.23 \pm 1.00 \text{ E-07}$	$9.52 \pm 5.45 \text{ E-07}$
400-D Raw	11	$4.01 \pm 0.11 \text{ E-06}$	$2.95 \pm 1.23 \text{ E-07}$	$1.19 \pm 1.03 \text{ E-06}$
Sr-90 ($\mu\text{Ci/mL}$)				
ORA Site	1	$-7.51 \pm 8.07 \text{ E-10}$	$-7.51 \pm 8.07 \text{ E-10}$	$-7.51 \pm 8.07 \text{ E-10}$
A-Area	1	$0.45 \pm 8.47 \text{ E-10}$	$0.45 \pm 8.47 \text{ E-10}$	$0.45 \pm 8.47 \text{ E-10}$
Barnwell Gate	1	$9.69 \pm 0.03 \text{ E-10}$	$9.69 \pm 0.03 \text{ E-10}$	$9.69 \pm 0.03 \text{ E-10}$
Emer Oper Center	1	$-1.01 \pm 1.87 \text{ E-09}$	$-1.01 \pm 1.87 \text{ E-09}$	$-1.01 \pm 1.87 \text{ E-09}$
Firing Range	1	$-7.40 \pm 7.82 \text{ E-10}$	$-7.40 \pm 7.82 \text{ E-10}$	$-7.40 \pm 7.82 \text{ E-10}$
Forestry Bldg	1	$0.39 \pm 8.42 \text{ E-10}$	$0.39 \pm 8.42 \text{ E-10}$	$0.39 \pm 8.42 \text{ E-10}$
Jackson Gate	1	$-1.26 \pm 7.43 \text{ E-09}$	$-1.26 \pm 7.43 \text{ E-09}$	$-1.26 \pm 7.43 \text{ E-09}$
Par Pond Lab	1	$2.25 \pm 1.39 \text{ E-09}$	$2.25 \pm 1.39 \text{ E-09}$	$2.25 \pm 1.39 \text{ E-09}$
Talatha Site	1	$-1.17 \pm 0.83 \text{ E-09}$	$-1.17 \pm 0.83 \text{ E-09}$	$-1.17 \pm 0.83 \text{ E-09}$
TC-1	1	$1.15 \pm 1.27 \text{ E-09}$	$1.15 \pm 1.27 \text{ E-09}$	$1.15 \pm 1.27 \text{ E-09}$
Williston Gate	1	$-7.43 \pm 0.18 \text{ E-11}$	$-7.43 \pm 0.18 \text{ E-11}$	$-7.43 \pm 0.18 \text{ E-11}$
Z Area	1	$1.22 \pm 0.97 \text{ E-09}$	$1.22 \pm 0.97 \text{ E-09}$	$1.22 \pm 0.97 \text{ E-09}$
105-C Bldg	1	$-0.35 \pm 2.27 \text{ E-09}$	$-0.35 \pm 2.27 \text{ E-09}$	$-0.35 \pm 2.27 \text{ E-09}$
105-K Bldg	1	$-0.96 \pm 1.84 \text{ E-09}$	$-0.96 \pm 1.84 \text{ E-09}$	$-0.96 \pm 1.84 \text{ E-09}$
105-L Bldg	1	$3.71 \pm 8.75 \text{ E-10}$	$3.71 \pm 8.75 \text{ E-10}$	$3.71 \pm 8.75 \text{ E-10}$
105-P Bldg	1	$-3.04 \pm 8.48 \text{ E-10}$	$-3.04 \pm 8.48 \text{ E-10}$	$-3.04 \pm 8.48 \text{ E-10}$
221-F Bldg	1	$-0.71 \pm 8.91 \text{ E-10}$	$-0.71 \pm 8.91 \text{ E-10}$	$-0.71 \pm 8.91 \text{ E-10}$
221-H Bldg	1	$1.13 \pm 0.90 \text{ E-09}$	$1.13 \pm 0.90 \text{ E-09}$	$1.13 \pm 0.90 \text{ E-09}$
617-G Wackenhut	1	$-0.74 \pm 8.61 \text{ E-10}$	$-0.74 \pm 8.61 \text{ E-10}$	$-0.74 \pm 8.61 \text{ E-10}$
681-1G	1	$-9.77 \pm 7.68 \text{ E-10}$	$-9.77 \pm 7.68 \text{ E-10}$	$-9.77 \pm 7.68 \text{ E-10}$
681-3G	1	$4.98 \pm 9.08 \text{ E-10}$	$4.98 \pm 9.08 \text{ E-10}$	$4.98 \pm 9.08 \text{ E-10}$
701-1F	1	$2.79 \pm 8.98 \text{ E-10}$	$2.79 \pm 8.98 \text{ E-10}$	$2.79 \pm 8.98 \text{ E-10}$
701-12G Barricade 7	1	$2.68 \pm 9.01 \text{ E-10}$	$2.68 \pm 9.01 \text{ E-10}$	$2.68 \pm 9.01 \text{ E-10}$
701-13G Barricade 6	1	$1.22 \pm 1.34 \text{ E-09}$	$1.22 \pm 1.34 \text{ E-09}$	$1.22 \pm 1.34 \text{ E-09}$
701-8G Barricade 8	1	$1.35 \pm 3.59 \text{ E-09}$	$1.35 \pm 3.59 \text{ E-09}$	$1.35 \pm 3.59 \text{ E-09}$
704-S DWPF	1	$1.08 \pm 0.91 \text{ E-09}$	$1.08 \pm 0.91 \text{ E-09}$	$1.08 \pm 0.91 \text{ E-09}$
Aiken Post Office	1	$9.03 \pm 8.79 \text{ E-10}$	$9.03 \pm 8.79 \text{ E-10}$	$9.03 \pm 8.79 \text{ E-10}$
Allendale Post Office	1	$0.17 \pm 1.01 \text{ E-09}$	$0.17 \pm 1.01 \text{ E-09}$	$0.17 \pm 1.01 \text{ E-09}$
Augusta Post Office	1	$4.60 \pm 8.39 \text{ E-10}$	$4.60 \pm 8.39 \text{ E-10}$	$4.60 \pm 8.39 \text{ E-10}$

Table 8-25
Radioactivity in Drinking Water, Cont'd.

Location	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Barnwell Post Office	1	$1.65 \pm 1.12 \text{ E-09}$	$1.65 \pm 1.12 \text{ E-09}$	$1.65 \pm 1.12 \text{ E-09}$
Bath Post Office	1	$0.46 \pm 1.08 \text{ E-09}$	$0.46 \pm 1.08 \text{ E-09}$	$0.46 \pm 1.08 \text{ E-09}$
Blackville Post Office	1	$0.71 \pm 1.05 \text{ E-09}$	$0.71 \pm 1.05 \text{ E-09}$	$0.71 \pm 1.05 \text{ E-09}$
Clearwater Post Office	1	$-3.24 \pm 9.04 \text{ E-10}$	$-3.24 \pm 9.04 \text{ E-10}$	$-3.24 \pm 9.04 \text{ E-10}$
Jackson Post Office	1	$1.42 \pm 3.50 \text{ E-09}$	$1.42 \pm 3.50 \text{ E-09}$	$1.42 \pm 3.50 \text{ E-09}$
Langley Post Office	1	$-1.40 \pm 0.90 \text{ E-09}$	$-1.40 \pm 0.90 \text{ E-09}$	$-1.40 \pm 0.90 \text{ E-09}$
New Ellenton Post Office	1	$-1.42 \pm 1.15 \text{ E-09}$	$-1.42 \pm 1.15 \text{ E-09}$	$-1.42 \pm 1.15 \text{ E-09}$
N Augusta Post Office	1	$1.39 \pm 8.46 \text{ E-10}$	$1.39 \pm 8.46 \text{ E-10}$	$1.39 \pm 8.46 \text{ E-10}$
Sardis Post Office	1	$-6.00 \pm 9.45 \text{ E-10}$	$-6.00 \pm 9.45 \text{ E-10}$	$-6.00 \pm 9.45 \text{ E-10}$
Waynesboro Post Office	1	$-0.65 \pm 1.74 \text{ E-09}$	$-0.65 \pm 1.74 \text{ E-09}$	$-0.65 \pm 1.74 \text{ E-09}$
Williston Post Office	1	$-2.75 \pm 7.67 \text{ E-10}$	$-2.75 \pm 7.67 \text{ E-10}$	$-2.75 \pm 7.67 \text{ E-10}$

Table 8-26
Drinking Water Analysis Results for Residual Chlorine and Total Coliform

Area	Date	Building	Residual Chlorine (mg/L) ^a	Total Coliform ^a (Counts/100mL)
D	4/2/91	484-D	0.9	Present
A	4/9/91	703-A	0.7	Present
A	4/10/91	703-43A	0.7	Present
F	4/10/91	723-F	1.0	Present
F	4/11/91	717-F	0.9	Present
K	4/9/91	183-2K	1.2	Present
P	4/9/91	183-2P	0.8	Present
G	5/15/91	905-108G	0.7	Present
D	5/15/91	484-4D	1.5	Present
G	8/13/91	735-7G	0.5	Present
G	8/13/91	905-7G	0.6	Present

^a Results reported as received from the Bacteria Laboratory 772-D.

Table 8-27
Chlorocarbon Monitoring Results from A-Administration Area Wells

Location	Lab	(µg/L)											
		1,1,1-Trichloroethane				Trichloroethylene				Tetrachloroethylene			
		Results ^a	Max	Min	Avg ^b	Results ^a	Max	Min	Avg ^b	Results ^a	Max	Min	Avg ^b
Well 68A	c	0/12	<5			6/12	5.0	0.4	3.0	0/12	<5		
	d	0/12	<2			3/12	3.9	3.7		0/12	<2		
Well 82A	c	0/6	<5			0/6	<5			0/6	<5		
	d	0/6	<2			1/6	31			0/6	<2		
735-A	c	0/12	<5			0/12	<5			0/12	<5		
	d	0/12	<2			0/12	<2			0/12	<2		
784-A	c	0/4	<5			0/4	<5			0/4	<5		
	d	0/4	<2			1/4	9.0			0/4	<2		
Well 113-G	c	0/4	<5			0/4	<5			0/4	<5		
	d	0/4	<2			0/4	<2			0/4	<2		
Well 20A ^e	c	0/12	<10			12/12	172	5.6	104	4/12	6.3	2.2	4.9
	d	0/12	<2			12/12	175	3.5	83	5/12	9.8	2.3	4.4
Well 53A ^e	c	0/10	<10			10/10	200	91	120	9/10	13	5.5	8.3
	d	0/10	<2			9/10	132	78	95	8/10	13	5.0	8.9
Service water	c	0/12	<10			5/12	14	2.7	7.8	0/12	<5		
	d	0/12	<2			4/12	6.9	2.8	5.0	0/12	<2		
400-D	c	0/4	<10			0/4	<10			0/4	<10		
	d	0/4	<2			0/4	<2			0/4	<2		

a Detected concentrations/total measurements.

b Averages calculated only for four or more detected results.

c SRS laboratory results.

d Results reported by subcontracted offsite laboratory.

e Process well.

Table 8-28
SRS Drinking Water Chlorocarbon Monitoring Results

Sample Location	Maximum Concentration (µg/L)					
	1,1,1-Trichloroethane		Trichloroethylene		Tetrachloroethylene	
	1/16/91 ^a	7/18/91 ^b	1/16/91 ^a	7/18/91 ^b	1/16/91 ^a	7/18/91 ^b
C Area	<2	<2	<2	<2	<2	<2
K Area	<2	<2	<2	<2	<2	<2
P Area	<2	<2	<2	<2	<2	<2
L Area	<2	<2	<2	<2	<2	<2
F Area	<2	<2	<2	<2	<2	<2
H Area	<2	<2	<2	<2	<2	<2
D Area	<2	<2	<2	<2	<2	<2
Classification Yard	<2	<2	<2	<2	<2	<2
River Pump Station (1G)	<2	<2	<2	<2	<2	<2
River Pump Station (3G)	<2	<2	<2	<2	<2	<2
Central Shops	<2	<2	<2	<2	<2	<2
Par Pond Lab	<2	<2	<2	<2	<2	<2
Forestry	<2	<2	<2	<2	<2	<2
Jackson Barricade	<2	<2	<2	<2	<2	<2
Talatha Barricade	<2	<2	<2	<2	<2	<2
Williston Barricade	<2	<2	<2	<2	<2	<2
Barnwell Barricade	<2	<2	<2	<2	<2	<2
Allendale Barricade	<2	<2	<2	<2	<2	<2
Patrol Gate 6	<2	<2	<2	<2	<2	<2
Patrol Gate 7	<2	<2	<2	<2	<2	<2
Patrol Gate 8	<2	<2	<2	<2	<2	<2
A-Area Cafeteria	<2	<2	<2	<2	<2	<2
Emergency Operating Center	<2	<2	<2	<2	<2	<2
Firing Range	<2	<2	<2	<2	<2	<2
TNX	<2	<2	<2	<2	<2	<2
S Area (DWPF)	<2	<2	<2	<2	<2	<2
B Area	<2	<2	<2	<2	<2	<2
Z Area	<2	<2	<2	<2	<2	<2
Wackenhut (ATTA)	^c	<2	^c	<2	^c	<2

^a Analyses performed by Normandeau Associates, Inc.

^b Analyses performed by Thermo Analytical, Inc.

^c No result reported.

Table 8-29
Maximum Volatile Organic Compound and Unregulated Organic Compound
Levels in SRS Drinking Water

Constituent ^a	Results (µg/L)	Constituent ^a	Results (µg/L)
Benzene ^b	<0.5	1,1-Dichloropropene	<0.5
Bromobenzene	<0.5	1,3-Dichloropropene	<0.5
Bromochloromethane	<0.5	Ethylbenzene	<0.5
Bromodichloromethane	3.72 ^c	Hexachlorobutadiene	<0.5
Bromoform	<0.5	Isopropylbenzene	<0.5
Bromomethane	<0.5	P-Isopropyltoluene	<0.5
N-Butylbenzene	<0.5	Methylene chloride	<0.5
Sec-Butylbenzene	<0.5	Naphthalene	<0.5
Tert-Butylbenzene	<0.5	N-Propylbenzene	<0.5
Carbon tetrachloride ^b	<0.5	Styrene	<0.5
Chlorobenzene	<0.5	1,1,1,2-Tetrachloroethane	<0.5
Chloromethane	<0.5	1,1,2,2-Tetrachloroethane	<0.5
Chloroethane	<0.5	Tetrachloroethene	<0.5
Chloroform	29.6 ^c	Toluene	<0.5
2-Chlorotoluene	<0.5	1,2,3-Trichlorobenzene	<0.5
4-Chlorotoluene	<0.5	1,2,4-Trichlorobenzene	<0.5
Dibromochloromethane	<0.5	1,1,1-Trichloroethane ^b	<0.5
Dibromomethane	<0.5	1,1,2-Trichloroethane	<0.5
1,2-Dichlorobenzene	<0.5	Trichloroethylene ^b	<0.5
1,3-Dichlorobenzene	<0.5	Trichlorofluoromethane	<0.5
1,4-Dichlorobenzene ^b	<0.5	1,2,3-Trichloropropane	<0.5
Dichlorodifluoromethane	<0.5	1,2,4-Trimethylbenzene	<0.5
1,1-Dichloroethane	<0.5	1,3,5-Trimethylbenzene	<0.5
1,2-Dichloroethane ^b	<0.5	Vinyl chloride ^b	<0.5
Cis-1,2-Dichloroethene	<0.5	O-xylene	<0.5
Trans-1,2-Dichloroethene	<0.5	M-xylene	<0.5
1,1-Dichloroethylene ^b	<0.5	P-xylene	<0.5
1,2-Dichloropropane	<0.5	1,2-Dibromo-3-Chloropropane	<0.5
1,3-Dichloropropane	<0.5	1,2-Dibromoethane	<0.5
2,2-Dichloropropane	<0.5		

a Samples collected at SRS domestic water systems.

b SCDHEC-regulated volatile organic compound.

c Sample collected from 400-D domestic drinking water system.

Table 8-30
SCDHEC Chemical Analysis Results for SRS Drinking Water

Constituent (mg/L)	A Area	F Area	H Area	B Area	Central Shops
Arsenic	<0.005	<0.005	<0.005	<0.005	<0.005
Chloride	6.9	8.3	4.4	9.4	5
Calcium	0.36	0.91	0.85	8.1	11
Magnesium	0.2	0.23	0.33	0.42	0.47
Hardness	2	3	3	22	29
Sodium	28	17	5	5.5	5.7
Barium	<0.5	<0.05	<0.05	<0.05	<0.05
Cadmium	<0.01	<0.01	<0.01	<0.01	<0.01
Chromium	<0.01	<0.01	<0.01	<0.01	<0.01
Copper	0.01	0.02	0.02	0.01	0.03
Iron	<0.01	0.86	0.47	0.12	0.32
Manganese	<0.01	0.02	0.02	<0.01	<0.01
Silver	<0.03	<0.03	<0.03	<0.03	<0.03
Zinc	<0.01	0.02	0.02	<0.01	<0.01
Fluoride	<0.10	<0.10	<0.10	<0.10	<0.10
Mercury	<0.0002	<0.0002	<0.0002	<0.0002	<0.0002
Nitrate	0.03	<0.02	<0.02	<0.02	<0.02
Lead	<0.005	<0.005	<0.005	<0.005	<0.005
Selenium	<0.005	<0.005	<0.005	<0.005	<0.005

Table 8-30
SCDHEC Chemical Analysis Results for SRS Drinking Water, Cont'd.

Constituent (mg/L)	TNX	P Area	K Area	C Area	L Area
Arsenic	<0.005	<0.005	<0.005	<0.005	<0.005
Chloride	9.9	5.6	5.7	5.1	4.5
Calcium	5.4	6.4	4.9	4.9	6.1
Magnesium	1	0.48	0.64	0.38	0.58
Hardness	18	18	15	14	18
Sodium	18	3.5	3.3	2.7	2.4
Barium	0.08	<0.05	<0.05	<0.05	<0.05
Cadmium	<0.01	<0.01	<0.01	<0.01	<0.01
Chromium	<0.01	<0.01	<0.01	<0.01	<0.01
Copper	<0.01	0.01	0.02	<0.01	0.04
Iron	1.8	0.55	0.81	0.32	1.4
Manganese	0.04	0.02	0.03	<0.01	0.03
Silver	<0.03	<0.03	<0.03	<0.03	<0.03
Zinc	<0.01	0.02	0.01	0.01	<0.01
Fluoride	<0.10	<0.10	<0.10	<0.10	<0.10
Mercury	0.0011	<0.0002	<0.0002	<0.0002	<0.0002
Nitrate	<0.02	<0.02	<0.02	Lab Error	<0.02
Lead	<0.005	<0.005	<0.005	<0.005	0.016
Selenium	<0.005	<0.005	<0.005	<0.005	<0.005

Table 8-31
Surface Water Treatment Plant Self-Monitoring Results for 400-D Area

FECAL COLIFORM

Month	Number of Samples	Result
January	31	A ^a
February	28	A
March	31	A
April	30	A
May	31	A
June	30	A
July	31	A
August	31	A
September	30	A
October	31	A
November	30	A
December	31	A

TURBIDITY

Month	Number of Samples	NTU		
		Maximum	Minimum	Average
January	31	0.19	0.02	0.08
February	28	0.51	0.10	0.21
March	31	22	0.10	0.84
April	30	1.12	<0.10	0.24
May	31	0.62	0.10	0.21
June	30	0.68	<0.10	0.17
July	31	0.53	0.10	0.16
August	31	0.88	<0.10	0.39
September	28	5.3	<0.10	0.46
October	31	3.1	<0.10	0.36
November	30	1.0	<0.10	0.22
December	31	0.85	<0.10	0.21

a Total coliform is reported as present (P) or absent (A).

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems

PARAMETER	Units	LLD	A Area	B Area	Forestry	K Area
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Barium, Total	µg/L	50	<50	<50	<50	<50
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Chromium, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Lead, Total	µg/L	0.75	1.7	<0.75	<0.75	<0.75
Mercury, Total	µg/L	0.25	<0.25	<0.25	0.77	0.30
Nitrate, as N	mg/L	0.10	0.29	0.22	0.77	<0.10
Selenium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS						
Endrin	µg/L	0.10	<0.10	<0.10	<0.10	cancelled
gamma-BHC (Lindane)	µg/L	0.05	<0.05	<0.05	<0.05	cancelled
Methoxychlor	µg/L	0.50	<0.50	<0.50	<0.50	cancelled
Toxaphene	µg/L	1.0	<1.0	<1.0	<1.0	cancelled
2,4-D	µg/L	1.0	<1.0	<1.0	<1.0	<1.0
2,4,5-TP (Silvex)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
RADIONUCLIDES						
Alpha, Gross	pCi/L	-	<2	<1	9.2 ± 2.3	1.9 ± 1.3
Beta, Gross	pCi/L	-	4.5 ± 1.5	<2	4.4 ± 1.4	2.5 ± 1.3
Iodine -131	pCi/L	-	<3	<4	<4	<3
Radium-226	pCi/L	-	<1	1.0 ± 0.4	1.4 ± 0.6	<1
Radium-228	pCi/L	-	0.77 ± 0.5	1.5 ± 1.1	1.2 ± 0.5	<1
Strontium-90	pCi/L	-	<0.4	<0.5	<0.7	<0.7
Tritium	pCi/L	-	68 ± 29	63 ± 29	1200 ± 100	<40
SECONDARY MCLs						
Chloride	mg/L	5.0	6.7	5.2	7.7	<5.0
Color	CUU	5.0	10	10	5.0	5.0
Copper, Total	µg/L	6.3	18	11	7.8	10
Corrosivity	PH SAT	-15	-2.1	-2.1	-6.0	-3.0
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	<25	108	139	738 ^a
Manganese, Total	µg/L	3.8	<3.8	3.9	5.9	25

^a Value exceeds SCDHEC maximum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	A Area	B Area	Forestry	K Area
SECONDARY MCLs, cont'd.						
Odor	TON	-	N/A	N/A	N/A	N/A
pH	pHU	0.01	7.8	7.0	5.2 ^a	6.6
Sulfate	mg/L	5.0	<5.0	<5.0	<5.0	10.5
Total Dissolved Solids	mg/L	5.0	65	45	36	47
Zinc, Total	µg/L	5.0	8.3	14	15	11
SODIUM						
Sodium, Total	µg/L	1250	16400	3220	4720	3730
PARAMETER	Units	LLD	L Area	TNX	D Area	1G Pump H
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Barium, Total	µg/L	50	<50	53	<50	100
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Chromium, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Lead, Total	µg/L	0.75	0.80	<0.75	<0.75	<0.75
Mercury, Total	µg/L	0.25	<0.25	<0.25	<0.25	<0.25
Nitrate, as N	mg/L	0.10	<0.1	0.26	0.57	0.17
Selenium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS						
Endrin	µg/L	0.10	cancelled	<0.10	<0.10	<0.10
gamma-BHC (Lindane)	µg/L	0.05	cancelled	<0.05	<0.05	<0.05
Methoxychlor	µg/L	0.50	cancelled	<0.50	<0.50	<0.50
Toxaphene	µg/L	1.0	cancelled	<1.0	<1.0	<1.0
2,4-D	µg/L	1.0	<1.0	<1.0	<1.0	<1.0
2,4,5-TP (Silvex)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
RADIONUCLIDES						
Alpha, Gross	pCi/L	-	<1	<2	<2	<2
Beta, Gross	pCi/L	-	2.2 ± 1.3	4.2 ± 1.5	2.5 ± 1.4	5.5 ± 1.6
Iodine -131	pCi/L	-	<3	<2	<2	<2
Radium-226	pCi/L	-	<1	<1	<1	<1
Radium-228	pCi/L	-	<1	0.74 ± 0.48	<1	<1
Strontium-90	pCi/L	-	0.50	<0.6	<0.8	<0.8

^a Value exceeds SCDHEC maximum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	L Area	TNX	D Area	1G Pump H
RADIONUCLIDES, cont'd.						
Tritium	pCi/L	-	37 ± 21	93 ± 31	81 ± 40	<100
SECONDARY MCLs						
Chloride	mg/L	5.0	5.8	<5.0	13	13
Color	CUU	5.0	5.0	5.0	5.0	5.0
Copper, Total	µg/L	6.3	<6.3	9.1	25	104
Corrosivity	PH SAT	-15	-3.1	-2.8	-3.1	-4.5
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	1080 ^a	1000 ^a	<25	15300 ^a
Manganese, Total	µg/L	3.8	22	30	9.2	171 ^a
Odor	TON	-	N/A	N/A	N/A	N/A
pH	PHU	0.01	6.5	7.4	7.3	9.0 ^a
Sulfate	mg/L	5.0	9.0	11	20	8.8
Total Dissolved Solids	mg/L	5.0	53	94	84	57
Zinc, Total	µg/L	5.0	5.6	20	8.4	40
SODIUM						
Sodium, Total	µg/L	4080	24200 ^a	19600	4720	10100
PARAMETER	Units	LLD	3G Pump H	Patrol Gate 7	Jackson Bar	Alken Bar
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Barium, Total	µg/L	50	51.0	<50	<50	<50
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Chromium, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Lead, Total	µg/L	0.75	2.5	1.8	5.3	6.0
Mercury, Total	µg/L	0.25	<0.25	<0.25	<0.25	<0.25
Nitrate, as N	mg/L	0.10	0.14	0.41	0.63	1.7
Selenium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS						
Endrin	µg/L	0.10	<0.10	<0.10	<0.10	<0.1
gamma-BHC (Lindane)	µg/L	0.05	<0.05	<0.05	<0.05	<0.05
Methoxychlor	µg/L	0.50	<0.50	<0.50	<0.50	<0.50

^a Value exceeds SCDHEC minimum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	3G Pump H	Patrol Gate 7	Jackson Bar	Aiken Bar
ORGANIC CHEMICALS, cont'd.						
Toxaphene	µg/L	1.0	<1.0	<1.0	<1.0	<1.0
2,4-D	µg/L	1.0	<1.0	<1.0	<1.0	<1.0
2,4,5-TP (Silvex)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
RADIONUCLIDES						
Alpha, Gross	pCi/L	-	<1	<2	<2	4.6 ± 1.7
Beta, Gross	pCi/L	-	3.5 ± 1.4	<2	<2	<2
Iodine -131	pCi/L	-	<2	<2	<2	<2
Radium-226	pCi/L	-	<1	<1	<1	3.6 ± 0.6
Radium-228	pCi/L	-	<0.6	<0.05	1.5 ± 0.6	3.0 ± 1.5
Strontium-90	pCi/L	-	<0.6	<0.5	<0.4	<0.4
Tritium	pCi/L	-	<40	1800 ± 100	140 ± 30	960 ± 50
SECONDARY MCLs						
Chloride	mg/L	5.0	7.4	6.0	5.5	6.4
Color	CUU	5.0	5.0	5.0	5.0	5.0
Copper, Total	µg/L	6.3	108	367	1160 ^a	107
Corrosivity	PH SAT	-15	-4.7	-3.0	-3.9	-4.1
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	1300 ^a	1370 ^a	194	299
Manganese, Total	µg/L	3.8	33.2	23.4	15.7	10.3
Odor	TON	-	N/A	N/A	N/A	N/A
pH	pHU	0.01	5.6 ^a	5.8 ^a	5.2 ^a	5.6 ^a
Sulfate	mg/L	5.0	10.4	6.3	<5.0	<5.0
Total Dissolved Solids	mg/L	5.0	133	47.0	31.0	23.0
Zinc, Total	µg/L	5.0	8.7	14.7	115	224
SODIUM						
Sodium, Total	µg/L	1250	4290	3420	3000	4500
PARAMETER	Units	LLD	Patrol Gate 8	Patrol Gate 6	Allendale Bar	Williston Bar
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Barium, Total	µg/L	50	<50	<50	<50	<50
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3

^a Value exceeds SCDHEC minimum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	Patrol Gate 8	Patrol Gate 6	Allendale Bar	Williston Bar
INORGANIC CHEMICALS, cont'd.						
Chromium, Total	µg/L	2.5	<2.5	<2.5	3.3	<2.5
Fluoride	mg/L	0.10	<0.10	<0.10	0.14	<0.10
Lead, Total	µg/L	0.75	2.4	2.1	<0.75	4.2
Mercury, Total	µg/L	0.25	<0.25	<0.25	<0.25	<0.25
Nitrate, as N	mg/L	0.10	<0.10	0.62	0.30	1.8
Selenium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS						
Endrin	µg/L	0.10	<0.10	<0.10	<0.10	<0.10
gamma-BHC (Lindane)	µg/L	0.05	<0.05	<0.05	<0.05	<0.05
Methoxychlor	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Toxaphene	µg/L	1.0	<1.0	<1.0	<1.0	<1.0
2,4-D	µg/L	1.0	<1.0	<1.0	<1.0	4.6
2,4,5-TP (Silvex)	µg/L	0.50	<0.50	<0.50	<0.50	2.3
RADIONUCLIDES						
Alpha, Gross	pCi/L	-	<2	<2	8.0 ± 2.6	<1
Beta, Gross	pCi/L	-	<2	<2	8.7 ± 1.8	<2
Iodine -131	pCi/L	-	<2	<2	<2	<2
Radium-226	pCi/L	-	<1	<1	<1	<1
Radium-228	pCi/L	-	<0.7	<1	<1	<1
Strontium-90	pCi/L	-	<0.6	<0.4	<0.4	<0.5
Tritium	pCi/L	-	3300 ± 100	2500 ± 100	66 ± 30	87 ± 34
SECONDARY MCLs						
Chloride	mg/L	5.0	<5.0	6.3	5.3	10.2
Color	CPU	5.0	5.0	5.0	5.0	5.0
Copper, Total	µg/L	6.3	242	461	7.0	99.5
Corrosivity	PH SAT	-15	-4.3	-4.4	-0.75	-2.2
Fluoride	mg/L	0.10	<0.10	<0.10	0.14	0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	33.4	326 ^a	30.9	1560 ^a
Manganese, Total	µg/L	3.8	<3.8	84.3	<3.8	29.5
Odor	TON	-	N/A	N/A	N/A	N/A
pH	pHU	0.01	5.6 ^a	5.7 ^a	8.2	7.1

^a Value exceeds SCDHEC minimum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	Patrol Gate 8	Patrol Gate 6	Allendale Bar	Williston Bar
SECONDARY MCLs, cont'd.						
Sulfate	mg/L	5.0	<5.0	<5.0	<5.0	<5.0
Total Dissolved Solids	mg/L	5.0	11.0	21.0	84.0	55.0
Zinc, Total	µg/L	5.0	34.6	70.7	142	1710
SODIUM						
Sodium, Total	µg/L	1250	1750	4500	2830	7350
PARAMETER	Units	LLD	Cental Shops	F Area	H Area	P Area
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Barium, Total	µg/L	50	<50	<50	<50	<50
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Chromium, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Lead, Total	µg/L	0.75	1.7	1.2	0.80	1.5
Mercury, Total	µg/L	0.25	<0.25	<0.25	<0.25	0.25
Nitrate, as N	mg/L	0.10	<0.10	0.13	0.18	0.10
Selenium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS						
Endrin	µg/L	0.10	<0.10	<0.10	<0.10	<0.10
gamma-BHC (Lindane)	µg/L	0.05	<0.05	<0.05	<0.05	<0.05
Methoxychlor	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Toxaphene	µg/L	1.0	<1.0	<1.0	<1.0	<1.0
2,4-D	µg/L	1.0	<2.3	<2.3	<2.3	<2.9
2,4,5-TP (Silvex)	µg/L	0.50	<1.2	<1.2	<1.2	<1.4
RADIONUCLIDES						
Alpha, Gross	pCi/L	-	<1	<1	1.7 ± 1.2	<1
Beta, Gross	pCi/L	-	<2	4.8 ± 1.5	2.9 ± 1.5	2.1 ± 1.3
Iodine -131	pCi/L	-	<2	<2	<2	<2
Radium-226	pCi/L	-	<1	1.2 ± 0.5	1.3 ± 0.4	<1
Radium-228	pCi/L	-	<1	2.1 ± 0.7	<2	<1
Strontium-90	pCi/L	-	<1	<0.4	<0.6	<0.7
Tritium	pCi/L	-	40	40	100 ± 30	92 ± 28

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	Cental Shops	F Area	H Area	P Area
SECONDARY MCLs						
Chloride	mg/L	5.0	<5.0	5.4	<5.0	<5.0
Color	CPU	5.0	5.0	5.0	5.0	5.0
Copper, Total	µg/L	6.3	21.7	35	12.7	6.3
Corrosivity	PH SAT	-15	-2.0	-2.1	-3.6	-2.5
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	284	673 ^a	1050 ^a	786 ^a
Manganese, Total	µg/L	3.8	6.7	13.5	17.9	12.8
Odor	TON	-	N/A	N/A	N/A	N/A
pH	pHU	0.01	6.9	7.1	6.9	6.9
Sulfate	mg/L	5.0	10.3	11.4	10.7	8.1
Total Dissolved Solids	mg/L	5.0	75	69	41	51
Zinc, Total	µg/L	5.0	11	233	60	9.8
SODIUM						
Sodium, Total	µg/L	1250	8230	22000 ^a	6250	3080
PARAMETER	Units	LLD	C Area	Firing Range	Par Pond Lab	Class Yard
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Barium, Total	µg/L	50	<50	<50	71	<50
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Chromium, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
Fluoride	mg/L	0.10	<0.10	<0.10	0.10	0.10
Lead, Total	µg/L	0.75	2.1	6.3	1.8	4.0
Mercury, Total	µg/L	0.25	<0.25	<0.25	<0.25	<0.25
Nitrate, as N	mg/L	0.10	0.16	0.38	0.22	0.22
Selenium, Total	µg/L	1.3	<1.3	<1.3	<1.3	<1.3
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS						
Endrin	µg/L	0.10	<0.10	<0.10	<0.10	<0.10
gamma-BHC (Lindane)	µg/L	0.05	<0.05	<0.05	<0.05	<0.05
Methoxychlor	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Toxaphene	µg/L	1.0	<1.0	<1.0	<1.0	<1.0

^a Value exceeds SCDHEC minimum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	C Area	Firing Range	Par Pond Lab	Class Yard
ORGANIC CHEMICALS, cont'd.						
2,4-D	µg/L	1.0	<2.5	<2.5	<2.9	<2.2
2,4,5-TP (Silvex)	µg/L	0.50	<1.2	<1.2	<1.4	<1.1
RADIONUCLIDES						
Alpha, Gross	pCi/L	-	<1	<1	<2	<2
Beta, Gross	pCi/L	-	<2	2.5 ± 1.3	2.5 ± 1.4	2.4 ± 1.4
Iodine -131	pCi/L	-	<2	<2	<2	<2
Radium-226	pCi/L	-	<1	<1	<1	<1
Radium-228	pCi/L	-	<0.8	1.5 ± 0.06	<2	1.7 ± 1.2
Strontium-90	pCi/L	-	<0.5	<1	<0.5	<0.5
Tritium	pCi/L	-	49 ± 26	1100 ± 100	<40	42 ± 26
SECONDARY MCLs						
Chloride	mg/L	5.0	<5.0	<5.0	<5.0	5.3
Color	CPU	5.0	5.0	5.0	5.0	5.0
Copper, Total	µg/L	6.3	<6.3	116	475	47
Corrosivity	PH SAT	-15	-3.4	-5.3	-2.0	-1.5
Fluoride	mg/L	0.10	<0.10	<0.10	0.10	0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	432 ^a	618 ^a	874	844 ^a
Manganese, Total	µg/L	3.8	9.0	30	8.6	8.5
Odor	TON	-	N/A	N/A	N/A	N/A
pH	pHU	0.01	6.5	5.3 ^a	6.4 ^a	6.8
Sulfate	mg/L	5.0	8.5	<5.0	8.0	<5.0
Total Dissolved Solids	mg/L	5.0	49	23	103	102
Zinc, Total	µg/L	5.0	17.9	842	51	27
SODIUM						
Sodium, Total	µg/L	1250	2910	2570	3810	2680
PARAMETER	Units	LLD	S Area	Barnwell Bar	ATTA ^b	
INORGANIC CHEMICALS						
Arsenic, Total	µg/L	2.5	<2.5	<2.5	10	
Barium, Total	µg/L	50	<50	<50	<50	
Cadmium, Total	µg/L	1.3	<1.3	<1.3	<1.3	
Chromium, Total	µg/L	2.5	<2.5	<2.5	<2.5	

^a Value exceeds SCDHEC minimum concentration level.

^b Samples collected 12/5/90 – 12/13/90 from all sites except ATTA. ATTA samples were collected 6/25/91.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	S Area	Barnwell Bar	ATTA ^a
INORGANIC CHEMICALS, cont'd.					
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10
Lead, Total	µg/L	0.75	<0.75	1.7	3.9
Mercury, Total	µg/L	0.25	<0.25	<0.25	<0.25
Nitrate, as N	mg/L	0.10	<0.10	0.17	1.1
Selenium, Total	µg/L	1.3	<1.3	<1.3	5.0
Silver, Total	µg/L	2.5	<2.5	<2.5	<2.5
ORGANIC CHEMICALS					
Endrin	µg/L	0.10	<0.10	<0.10	<0.10
gamma-BHC (Lindane)	µg/L	0.05	<0.05	<0.05	<0.05
Methoxychlor	µg/L	0.50	<0.50	<0.50	<0.51
Toxaphene	µg/L	1.0	<1.0	<1.0	<1.0
2,4-D	µg/L	1.0	<1.0	<1.0	<1.0
2,4,5-TP (Silvex)	µg/L	0.50	<0.52	<0.52	<0.51
RADIONUCLIDES					
Alpha, Gross	pCi/L	-	<1	<1	1.7 ± 1.4
Beta, Gross	pCi/L	-	<2	<2	7.3 ± 2.1
Iodine -131	pCi/L	-	<1	<1	<1
Radium-226	pCi/L	-	1.2 ± 0.6	<1	6.1 ± 0.34
Radium-228	pCi/L	-	<1	<2	<1
Strontium-90	pCi/L	-	<0.4	<0.5	<1
Tritium	pCi/L	-	<40	<50	1500 ± 100
SECONDARY MCLs					
Chloride	mg/L	5.0	6.6	6.7	<5.0
Color	CUU	5.0	5.0	5.0	5.0
Copper, Total	µg/L	6.3	<6.3	<6.3	10.1
Corrosivity	PH SAT	-15	-2.6	-4.1	-4.0
Fluoride	mg/L	0.10	<0.10	<0.10	<0.10
Foaming Agents	mg/L	0.10	<0.10	<0.10	<0.10
Iron, Total	µg/L	25	674 ^b	1970 ^b	1040 ^b
Manganese, Total	µg/L	3.8	15.9	89	11.2
Odor	TON	-	N/A	N/A	8.0
pH	PHU	0.01	6.4 ^b	5.2 ^b	6.1 ^b
Sulfate	mg/L	5.0	11.2	<5.0	5.3

^a Samples collected 12/5/90 – 12/13/90 from all sites except ATTA. ATTA samples were collected 6/25/91.

^b Value exceeds SCDHEC minimum concentration level.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	S Area	Barnwell Bar	ATTA ^a		
SECONDARY MCLs, cont'd.							
Total Dissolved Solids	mg/L	5.0	75	42	30		
Zinc, Total	µg/L	5.0	8.8	298	66		
SODIUM							
Sodium, Total	µg/L	1250	16500	3570	<1250		
PARAMETER	Units	LLD	A Area	B Area	Forestry	K Area	
TOTAL TRIHALOMETHANES (THM)							
Total TMH	µg/L	2.5	7.6	2.6	2.8	8.6	
VOLATILE SYNTHETIC ORGANIC CHEMICALS							
Benzene	µg/L	0.50	<0.50	<0.50	<0.50	<0.50	
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	<0.50	
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50	
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50	
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0	
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0	
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	<0.50	
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	<0.50	
ANALYSES OF INTEREST TO SRS							
Alkalinity	mg/L	0.50	32	24	1.0	9.0	
Calcium, Total	µg/L	1250	<1250	9350	<1250	4800	
Conductivity	umhos/cm	1.0	N/A	N/A	N/A	N/A	
Hardness	mg/L	0.10	3.0	27.3	4.1	16.3	
Magnesium, Total	µg/L	1250	<1250	<1250	<1250	<1250	
Potassium, Total	µg/L	1250	4740	<1250	<1250	2000	
Silicon, Total	µg/L	25.0	2740	2980	1970	3390	
Total Suspended Solids	mg/L	5.0	<5.0	<5.0	<5.0	<5.0	
Turbidity	NTU	0.05	0.18	1.0	0.45	1.3	
Silica	mg/L	0.40	N/A	N/A	N/A	N/A	
PARAMETER	Units	LLD	L Area	TNX	D Area	1G Pump H	
TOTAL TRIHALOMETHANES (THM)							
Total TMH	µg/L	2.5	9.2	<2.5	52.9	4.9	

a Samples collected 12/5/90 – 12/13/90 from all sites except ATTA. ATTA samples were collected 6/25/91.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	L Area	TNX	D Area	1G Pump H
VOLATILE SYNTHETIC ORGANIC CHEMICALS						
Benzene	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
ANALYSES OF INTEREST TO SRS						
Alkalinity	mg/L	0.50	9.8	2.6	2.0	2.1
Calcium, Total	µg/L	1250	5680	4810	3900	2560
Conductivity	umhos/cm	1.0	N/A	N/A	N/A	N/A
Hardness	mg/L	0.10	18.1	18.9	15.8	9.0
Magnesium, Total	µg/L	1250	<1250	<1250	1270	<1250
Potassium, Total	µg/L	1250	<1250	3900	1870	4140
Silicon, Total	µg/L	25.0	3340	3180	2390	3920
Total Suspended Solids	mg/L	5.0	<5.0	<5.0	<5.0	<5.0
Turbidity	NTU	0.05	0.59	1.6	0.17	2.0
Silica	mg/L	0.40	N/A	N/A	N/A	N/A
PARAMETER	Units	LLD	3G Pump H	Patrol Gate 7	Jackson Bar	Alken Bar
TOTAL TRIHALOMETHANES (THM)						
Total TMH	µg/L	2.5	<2.5	4.5	3.8	7.0
VOLATILE SYNTHETIC ORGANIC CHEMICALS						
Benzene	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
ANALYSES OF INTEREST TO SRS						
Alkalinity	mg/L	0.50	2.3	60	60	24
Calcium, Total	µg/L	1250	4810	6010	<1250	<1250

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	3G Pump H	Patrol Gate 7	Jackson Bar	Alken Bar
ANALYSES OF INTEREST TO SRS, cont'd.						
Conductivity	umhos/cm	1.0	N/A	N/A	N/A	N/A
Hardness	mg/L	0.10	17.0	19.7	8.4	5.6
Magnesium, Total	µg/L	1250	<1250	<1250	<1250	<1250
Potassium, Total	µg/L	1250	2500	1470	<1250	<1250
Silicon, Total	µg/L	25.0	4050	8670	2950	1920
Total Suspended Solids	mg/L	5.0	<5.0	<5.0	<5.0	<5.0
Turbidity	NTU	0.05	0.68	3.1	0.53	0.62
Silica	mg/L	0.40	N/A	N/A	N/A	N/A
PARAMETER	Units	LLD	Patrol Gate 8	Patrol Gate 6	Allendale Bar	Williston Bar
TOTAL TRIHALOMETHANES (THM)						
Total TMH	µg/L	2.5	3.4	4.6	11.2	8.8
VOLATILE SYNTHETIC ORGANIC CHEMICALS						
Benzene	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
ANALYSES OF INTEREST TO SRS						
Alkalinity	mg/L	0.50	9.0	6.8	11.3	15.4
Calcium, Total	µg/L	1250	<1250	<1250	23800	6120
Conductivity	umhos/cm	1.0	N/A	N/A	N/A	N/A
Hardness	mg/L	0.10	10.4	7.7	64	22.4
Magnesium, Total	µg/L	1250	<1250	<1250	<1250	<1250
Potassium, Total	µg/L	1250	<1250	<1250	<1250	<1250
Silicon, Total	µg/L	25.0	1800	1730	4990	2840
Total Suspended Solids	mg/L	5.0	<5.0	<5.0	<5.0	5.0
Turbidity	NTU	0.05	0.54	1.9	0.49	2.8
Silica	mg/L	0.40	N/A	N/A	N/A	N/A

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	Cental Shops	F Area	H Area	P Area
TOTAL TRIHALOMETHANES (THM)						
Total TMH	µg/L	2.5	9.2	9.2	5.0	12.4
VOLATILE SYNTHETIC ORGANIC CHEMICALS						
Benzene	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
ANALYSES OF INTEREST TO SRS						
Alkalinity	mg/L	0.50	28	30	2.6	11.6
Calcium, Total	µg/L	1250	10900	<1250	<1250	5900
Conductivity	umhos/ cm	1.0	N/A	N/A	N/A	N/A
Hardness	mg/L	0.10	32.5	13.2	8.0	24
Magnesium, Total	µg/L	1250	<1250	<1250	<1250	<1250
Potassium, Total	µg/L	1250	<1250	<1250	1260	<1250
Silicon, Total	µg/L	25.0	3620	3190	3110	3840
Total Suspended Solids	mg/L	5.0	<5.0	<5.0	6.0	<5.0
Turbidity	NTU	0.05	1.2	0.65	0.65	0.88
Silica	mg/L	0.40	N/A	N/A	N/A	N/A
PARAMETER	Units	LLD	C Area	Firing Range	Par Pond Lab	Class Yard
TOTAL TRIHALOMETHANES (THM)						
Total TMH	µg/L	2.5	11.9	3.4	2.5	4.7
VOLATILE SYNTHETIC ORGANIC CHEMICALS						
Benzene	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	<0.50
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	1.0
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	<0.50

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	C Area	Firing Range	Par Pond Lab	Class Yard
VOLATILE SYNTHETIC ORGANIC CHEMICALS, cont'd.						
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	<0.50
ANALYSES OF INTEREST TO SRS						
Alkalinity	mg/L	0.50	6.4	3.3	56	62.5
Calcium, Total	µg/L	1250	4550	<1250	25200	24500
Conductivity	umhos/cm	1.0	N/A	N/A	N/A	N/A
Hardness	mg/L	0.10	14.2	4.4	63	63.9
Magnesium, Total	µg/L	1250	<1250	<1250	<1250	<1250
Potassium, Total	µg/L	1250	<1250	<1250	1870	<1250
Silicon, Total	µg/L	25.0	2850	1900	4910	4920
Total Suspended Solids	mg/L	5.0	<5.0	<5.0	<5.0	<5.0
Turbidity	NTU	0.05	0.56	1.2	1.8	0.71
Silica	mg/L	0.40	N/A	N/A	N/A	N/A
PARAMETER	Units	LLD	S Area	Barnwell Bar	ATTA ^a	
TOTAL TRIHALOMETHANES (THM)						
Total TMH	µg/L	2.5	7.6	2.6	2.8	
VOLATILE SYNTHETIC ORGANIC CHEMICALS						
Benzene	µg/L	0.50	<0.50	<0.50	5.1 ^b	
Carbon Tetrachloride	µg/L	0.50	<0.50	<0.50	<0.50	
Dichlorobenzene (1,4)	µg/L	0.50	<0.50	<0.50	<0.50	
Dichloroethane (1,2)	µg/L	0.50	<0.50	<0.50	<0.50	
Dichloroethane (1,1)	µg/L	1.0	<1.0	<1.0	<1.0	
Trichloroethane (1,1,1)	µg/L	1.0	<1.0	<1.0	<1.0	
Trichloroethane	µg/L	0.50	<0.50	<0.50	<0.05	
Vinyl Chloride	µg/L	0.50	<0.50	<0.50	<0.05	
ANALYSES OF INTEREST TO SRS						
Alkalinity	mg/L	0.50	54	18.5	3.4	
Calcium, Total	µg/L	1250	3780	5940	<1250	
Conductivity	umhos/cm	1.0	N/A	N/A	42.9	
Hardness	mg/L	0.10	11.9	17.2	14	
Magnesium, Total	µg/L	1250	<1250	<1250	<1250	
Potassium, Total	µg/L	1250	<1250	<1250	<1250	

a Samples collected 12/5/90 – 12/13/90 from all sites except ATTA. ATTA samples were collected 6/25/91.

Table 8-32
Comprehensive Analyses Results for SRS Drinking Water Systems, Cont'd.

PARAMETER	Units	LLD	S Area	Barnwell Bar	ATTA ^a
<i>ANALYSES OF INTEREST TO SRS, cont'd.</i>					
Silicon, Total	µg/L	25.0	3080	2560	N/A
Total Suspended Solids	mg/L	5.0	<5.0	5.0	7.0
Turbidity	NTU	0.05	0.24	4.4	38.4
Silica	mg/L	0.40	N/A	N/A	5.4

^a Samples collected 12/5/90 – 12/13/90 from all sites except ATTA. ATTA samples were collected 6/25/91.

Table 8-33**Maximum Constituents Results Exceeding Applicable Standards for Wells at the A-Area Burning Rubble Pits**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Lead	mg/L	0.015	0.015	4	1
Tetrachloroethylene	mg/L	0.0050	0.044	4	1
Trichloroethylene	mg/L	0.0050	0.56	4	2

Table 8-34**Maximum Constituents Results Exceeding Applicable Standards for Wells at the A-Area Coal Pile Runoff Containment Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	2.4E-08	4	1
Specific conductance	μS/cm	100	256	4	2
Total radium	μCi/mL	5.0E-09	3.8E-08	4	2

Table 8-35
Maximum Constituents Results Exceeding Applicable Standards for Wells at the A-Area Metals Burning Pit

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	958	6	1
Nonvolatile beta	μCi/mL	5.0E-08	6.0E-08	6	1
Specific conductance	μS/cm	100	2,770	6	1
Lead	mg/L	0.015	0.017	6	1
pH	pH	≥8.5	13	6	1
Antimony	mg/L	0.0050	0.012	6	1
Tetrachloroethylene	mg/L	0.0050	0.026	6	2
Total dissolved solids	mg/L	200	883	6	1
Total radium	μCi/mL	5.0E-09	7.3E-09	6	1
Trichloroethylene	mg/L	0.0050	0.040	6	4
Tritium	μCi/mL	2.0E-05	3.1E-05	6	1

Table 8-36
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
M-Area Hazardous Waste Management Facility

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Background Wells					
Total radium	μCi/mL	5.0E-09	9.2E-09	9	1
Point-of-Compliance Wells					
Alkalinity (as CaCO3)	mg/L	100	1,220	41	9
Nonvolatile beta	μCi/mL	5.0E-08	1.2E-07	41	7
Carbon tetrachloride	mg/L	0.0050	2.0	41	1
Chloroform	mg/L	0.10	7.0	41	1
Specific conductance	μS/cm	100	4,330	41	24
Nitrate as nitrogen	mg/L	10	188	41	20
Lead	mg/L	0.015	0.092	41	6
pH	pH	≥8.5	13	41	12
Tetrachloroethylene	mg/L	0.0050	570 ^a	41	36
Total dissolved solids	mg/L	200	863	41	11
Thallium	mg/L	0.0010	0.0032	41	2
Total radium	μCi/mL	5.0E-09	1.0E-08	41	14
Trichloroethylene	mg/L	0.0050	160 ^a	41	36
Uranium	mg/L	0.020	0.19	36	1
Uranium-234	μCi/mL	1.4E-08	3.6E-08	2	2
1,1-Dichloroethylene	mg/L	0.0070	0.040	41	9
1,1,1-Trichloroethane	mg/L	0.20	2.0	41	1
1,1,2-Trichloroethane	mg/L	0.0050	2.7	41	2

^a DNAPL samples from well MSB 3D that consisted primarily of tetrachloroethylene and trichloroethylene were collected during 1991

Table 8-37
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Metallurgical Laboratory Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	157	19	2
Gross alpha	μCi/mL	1.5E-08	3.7E-08	19	3
Specific conductance	μS/cm	100	642	19	8
Lead	mg/L	0.015	0.044	19	1
pH	pH	≥8.5	11	19	3
Antimony	mg/L	0.0050	0.014	19	1
Tetrachloroethylene	mg/L	0.0050	0.076	19	5
Total dissolved solids	mg/L	200	228	19	1
Total radium	μCi/mL	5.0E-09	8.9E-09	19	4
Trichloroethylene	mg/L	0.0050	0.51	19	9

Table 8-38
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Miscellaneous Chemical Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	1,460	7	2
Nonvolatile beta	μCi/mL	5.0E-08	1.6E-07	7	1
Carbon tetrachloride	mg/L	0.0050	0.014	7	2
Specific conductance	μS/cm	100	5,540	7	2
Lead	mg/L	0.015	0.031	7	1
pH	pH	≥8.5	13	7	2
Tetrachloroethylene	mg/L	0.0050	0.080	7	5
Total dissolved solids	mg/L	200	1,170	7	2
Total radium	μCi/mL	5.0E-09	3.1E-08	7	3
Trichloroethylene	mg/L	0.0050	0.70	7	6
Tritium	μCi/mL	2.0E-05	4.0E-05	7	1

Table 8-39**Maximum Constituents Results Exceeding Applicable Standards for Wells at the Motor Shop Oil Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Tetrachloroethylene	mg/L	0.0050	0.15	3	1
Total radium	μCi/mL	5.0E-09	5.6E-09	3	1
Trichloroethylene	mg/L	0.0050	0.15	3	1

Table 8-40
Maximum Constituents Results Exceeding Applicable Standards for Wells at the A- and M-Areas Plume Definition Wells

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	1,030	211	11
Gross alpha	μCi/mL	1.5E-08	6.3E-08	207	4
Americium-241	μCi/mL	6.3E-09	7.3E-09	8	1
Barium	mg/L	2.0	2.7	209	1
Nonvolatile beta	μCi/mL	5.0E-08	9.7E-08	207	6
Bromodichloromethane	mg/L	0.10	0.19	87	1
Carbon tetrachloride	mg/L	0.0050	0.024	111	6
Cadmium	mg/L	0.0050	0.011	209	2
Chloroform	mg/L	0.10	0.63	211	1
Specific conductance	μS/cm	100	6,650	211	44
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.14	87	1
Benzene	mg/L	0.0050	0.0090	87	1
Dibromochloromethane	mg/L	0.10	0.23	87	1
Mercury	mg/L	0.0020	0.0043	209	4
Nitrate as nitrogen	mg/L	10	615	209	15
Lead	mg/L	0.015	0.55	209	19
pH	pH	≥8.5	13	211	26
pH	pH	≤4.0	3.8	211	2
Radium-228	μCi/mL	7.8E-09	1.1E-08	8	2
Tetrachloroethylene	mg/L	0.0050	387	211	82
Total dissolved solids	mg/L	200	951	206	9
Total radium	μCi/mL	5.0E-09	8.7E-08	207	30
Trichloroethylene	mg/L	0.0050	777	211	117
Tritium	μCi/mL	2.0E-05	6.2E-05	206	5
trans-1,2-Dichloroethylene	mg/L	0.10	1.7	211	1
1,1-Dichloroethylene	mg/L	0.0070	0.087	211	13
1,1,1-Trichloroethane	mg/L	0.20	0.24	211	1
1,1,2-Trichloroethane	mg/L	0.0050	0.029	87	2

Table 8-41
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Savannah River Laboratory Seepage Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	186	13	2
Americium-241	μCi/mL	6.3E-09	2.1E-08	13	6
Specific conductance	μS/cm	100	795	13	6
Chromium	mg/L	0.10	0.14	13	1
Iodine-131	μCi/mL	3.0E-09	3.4E-09	10	1
pH	pH	≥8.5	12	13	3
Radium-226	μCi/mL	1.6E-08	3.0E-08	13	2
Radium-228	μCi/mL	7.8E-09	1.4E-08	13	5
Tetrachloroethylene	mg/L	0.0050	0.26	13	7
Total dissolved solids	mg/L	200	244	13	1
Total radium	μCi/mL	5.0E-09	1.2E-08	13	2
Trichloroethylene	mg/L	0.0050	3.7	13	9
Tritium	μCi/mL	2.0E-05	3.0E-05	13	3
Uranium-235	μCi/mL	1.4E-08	1.5E-08	13	1
Uranium-238	μCi/mL	1.5E-08	6.4E-07	13	5

Table 8-42
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Silverton Road Waste Site

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Carbon tetrachloride	mg/L	0.0050	0.013	28	5
Lead	mg/L	0.015	0.099	28	10
Tetrachloroethylene	mg/L	0.0050	0.033	29	2
Trichloroethylene	mg/L	0.0050	0.023	29	6
1,2-Dichloroethane	mg/L	0.0050	0.055	28	1

Table 8-43**Maximum Constituents Results Exceeding Applicable Standards for Wells at the C-Area Burning/Rubble Pit**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	258	4	1
Specific conductance	μS/cm	100	1,110	4	1
Chromium	mg/L	0.10	0.15	4	1
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.017	4	1
Lead	mg/L	0.015	0.017	4	1
pH	pH	≥8.5	12	4	1
Tetrachloroethylene	mg/L	0.0050	0.034	4	4
Total dissolved solids	mg/L	200	245	4	1
Trichloroethylene	mg/L	0.0050	21	4	4
Tritium	μCi/mL	2.0E-05	2.2E-04	4	2
1,1-Dichloroethylene	mg/L	0.0070	0.012	4	1

Table 8-44**Maximum Constituents Results Exceeding Applicable Standards for Wells at the C-Area Disassembly Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	117	2	1
Lead	mg/L	0.015	0.18	2	1
Tritium	μCi/mL	2.0E-05	5.7E-04	2	2

Table 8-45
Maximum Constituents Results Exceeding Applicable Standards for Wells at the C-Area Reactor Seepage Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	117	6	1
Specific conductance	μS/cm	100	470	6	2
Copper	mg/L	1.3	2.3	6	1
Lead	mg/L	0.015	0.081	6	2
pH	pH	≥8.5	12	6	2
Tetrachloroethylene	mg/L	0.0050	0.010	6	1
Trichloroethylene	mg/L	0.0050	0.035	6	3
Tritium	μCi/mL	2.0E-05	5.3E-02	6	5
1,2-Dichloroethane	mg/L	0.0050	0.034	6	1

Table 8-46
Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Acid/Caustic Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	1,030	7	6
Lead	mg/L	0.015	0.076	7	1
Sulfate	mg/L	400	544	7	2
Total dissolved solids	mg/L	200	511	7	3

Table 8-47**Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Ash Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	216	4	1
Specific conductance	μS/cm	100	627	4	3
Total dissolved solids	mg/L	200	347	4	1
Total radium	μCi/mL	5.0E-09	1.4E-08	4	2

Table 8-48**Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Burning/Rubble Pit**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Lead	mg/L	0.015	0.044	4	1
Tetrachloroethylene	mg/L	0.0050	0.11	4	2
Trichloroethylene	mg/L	0.0050	0.034	4	1

Table 8-49**Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Coal Pile Runoff Containment Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	106	4	1
Gross alpha	μCi/mL	1.5E-08	2.3E-08	4	1
Specific conductance	μS/cm	100	573	4	3
pH	pH	≤4.0	3.8	4	1
Total dissolved solids	mg/L	200	248	3	1
Total radium	μCi/mL	5.0E-09	2.0E-08	4	2
Tritium	μCi/mL	2.0E-05	2.6E-05	4	2

Table 8-50
Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Disassembly Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	148	3	1
Specific conductance	μS/cm	100	287	3	2
Lead	mg/L	0.015	0.038	3	2
Tetrachloroethylene	mg/L	0.0050	0.015	3	2
Total dissolved solids	mg/L	200	276	3	1
Total radium	μCi/mL	5.0E-09	6.3E-09	3	2
Trichloroethylene	mg/L	0.0050	0.016	3	2
Tritium	μCi/mL	2.0E-05	3.6E-03	3	3

Table 8-51
Maximum Constituents Results Exceeding Applicable Standards for Wells at the K-Area Reactor Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	202	5	1
Nonvolatile beta	μCi/mL	5.0E-08	8.2E-07	5	1
Specific conductance	μS/cm	100	155	5	1
Trichloroethylene	mg/L	0.0050	0.019	4	2
Tritium	μCi/mL	2.0E-05	9.8E-02	5	5

Table 8-52
Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Acid/Caustic Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	137	4	1
Specific conductance	μS/cm	100	284	4	2
Lead	mg/L	0.015	0.045	4	2
pH	pH	≥8.5	9.2	4	1
Tetrachloroethylene	mg/L	0.0050	0.013	4	1
Trichloroethylene	mg/L	0.0050	0.047	4	2

Table 8-53
Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Disassembly Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Lead	mg/L	0.015	0.38	2	2
Tetrachloroethylene	mg/L	0.0050	0.0050	2	1

Table 8-54
Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Oil and Chemical Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	161	4	1
Nonvolatile beta	μCi/mL	5.0E-08	5.5E-08	4	1
Specific conductance	μS/cm	100	769	4	2
Lead	mg/L	0.015	0.021	4	1
pH	pH	≥8.5	9.6	4	1
Sulfate	mg/L	400	452	4	1
Tetrachloroethylene	mg/L	0.0050	0.064	4	2
Total dissolved solids	mg/L	200	496	4	2
Total radium	μCi/mL	5.0E-09	8.8E-09	4	1
Trichloroethylene	mg/L	0.0050	0.018	4	2
Tritium	μCi/mL	2.0E-05	6.7E-04	4	2

Table 8-55
Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Reactor Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	9.5E-08	4	1
Nonvolatile beta	μCi/mL	5.0E-08	4.3E-07	4	1
Lead	mg/L	0.015	0.021	4	3
Tritium	μCi/mL	2.0E-05	1.0E-02	4	3

Table 8-56**Maximum Constituents Results Exceeding Applicable Standards for Wells at the L-Area Research Wells**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	141	3	2
Specific conductance	μS/cm	100	727	3	2
pH	pH	≥8.5	12	3	2

Table 8-57**Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Acid/Caustic Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	140	6	2
Specific conductance	μS/cm	100	501	6	4
Total dissolved solids	mg/L	200	47,000	6	4

Table 8-58**Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Burning/Rubble Pit**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Carbon tetrachloride	mg/L	0.0050	0.019	4	1
Lead	mg/L	0.015	0.078	4	2
Tetrachloroethylene	mg/L	0.0050	0.030	4	1
Trichloroethylene	mg/L	0.0050	0.048	4	2
Tritium	μCi/mL	2.0E-05	8.0E-05	4	1
1,1-Dichloroethylene	mg/L	0.0070	0.14	4	1
1,1,1-Trichloroethane	mg/L	0.20	0.24	4	1
1,2-Dichloroethane	mg/L	0.0050	0.23	4	1

Table 8-59**Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Coal Pile Runoff Containment Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	1.5E-08	4	1
Cadmium	mg/L	0.0050	0.0060	4	1
Specific conductance	μS/cm	100	1,020	4	3
Nickel	mg/L	0.10	0.13	4	1
Lead	mg/L	0.015	0.046	4	2
pH	pH	≤4.0	3.5	4	3
Sulfate	mg/L	400	23,400	4	3
Total dissolved solids	mg/L	200	435	4	3
Total radium	μCi/mL	5.0E-09	2.4E-08	4	1

Table 8-60**Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Disassembly Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	113	2	1
Potassium-40	μCi/mL	3.0E-07	4.7E-07	2	1
Lead	mg/L	0.015	0.085	2	2
Tritium	μCi/mL	2.0E-05	1.5E-03	2	2

Table 8-61
Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-Area Reactor Seepage Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	234	7	1
Nitrate as nitrogen	mg/L	10	19	7	1
Lead	mg/L	0.015	0.069	7	5
Strontium-89/90	μCi/mL	8.0E-09	9.7E-09	7	1
Tritium	μCi/mL	2.0E-05	1.9E-01	7	7

Table 8-62
Maximum Constituents Results Exceeding Applicable Standards for Wells at the R-Area Burning/Rubble Pits

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.093	4	1
Lead	mg/L	0.015	0.016	4	1

Table 8-63
Maximum Constituents Results Exceeding Applicable Standards for Wells at the R-Area Disassembly Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	146	3	2
Specific conductance	μS/cm	100	311	3	3
Tritium	μCi/mL	2.0E-05	3.9E-05	3	1

Table 8-64
Maximum Constituents Results Exceeding Applicable Standards for Wells at the R-Area Reactor Seepage Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	1.8E-07	52	10
Nonvolatile beta	μCi/mL	5.0E-08	3.0E-06	52	18
Cadmium	mg/L	0.0050	0.16	10	5
Specific conductance	μS/cm	100	203	52	9
pH	pH	≥8.5	10	52	1
Total radium	μCi/mL	5.0E-09	5.2E-09	9	1
Tritium	μCi/mL	2.0E-05	4.1E-04	52	2

Table 8-65
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Acid/Caustic Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	3.4E-08	6	1
Specific conductance	μS/cm	100	322	6	6
pH	pH	≥8.5	9.0	6	1
Tetrachloroethylene	mg/L	0.0050	0.026	6	2
Total dissolved solids	mg/L	200	205	6	1
Total radium	μCi/mL	5.0E-09	2.3E-08	6	2
Trichloroethylene	mg/L	0.0050	0.029	6	2

Table 8-66
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Burma Road Rubble Pit

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	193	5	3
Lead	mg/L	0.015	0.016	5	1
Total radium	μCi/mL	5.0E-09	7.0E-09	5	1
Tritium	μCi/mL	2.0E-05	2.6E-04	5	3

Table 8-67
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Burning/Rubble Pits

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Nonvolatile beta	μCi/mL	5.0E-08	5.5E-08	4	1
Carbon tetrachloride	mg/L	0.0050	0.012	4	1
Specific conductance	μS/cm	100	126	4	2
Tetrachloroethylene	mg/L	0.0050	0.070	4	1
Trichloroethylene	mg/L	0.0050	0.053	4	2

Table 8-68
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Canyon Building and A-Line Uranium Recovery Facility

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
F–Area A–Line Uranium Recovery Facility and Canyon Building					
Alkalinity (as CaCO ₃)	mg/L	100	186	9	2
Gross alpha	μCi/mL	1.5E–08	1.1E–07	9	4
Nonvolatile beta	μCi/mL	5.0E–08	8.0E–07	9	2
Specific conductance	μS/cm	100	374	9	7
Nitrate as nitrogen	mg/L	10	26	8	4
Lead	mg/L	0.015	0.15	7	1
pH	pH	≤4.0	3.8	9	2
Strontium-89/90	μCi/mL	8.0E–09	1.7E–07	8	1
Strontium-90	μCi/mL	8.0E–09	4.1E–08	8	1
Total dissolved solids	mg/L	200	260	5	1
Total radium	μCi/mL	5.0E–09	3.2E–08	9	7
Trichloroethylene	mg/L	0.0050	0.11	9	7
Tritium	μCi/mL	2.0E–05	3.4E–04	8	1
Uranium-235	μCi/mL	1.4E–08	1.7E–08	7	1
1,2-Dichloroethane	mg/L	0.0050	0.011	8	1
Wells Between F–Area Canyon Building and Naval Fuel Facility					
Nonvolatile beta	μCi/mL	5.0E–08	6.2E–08	5	1
Specific conductance	μS/cm	100	882	5	2
Potassium-40	μCi/mL	3.0E–07	4.5E–07	5	1
Nitrate as nitrogen	mg/L	10	89	5	2
Lead	mg/L	0.015	0.062	5	4
Tetrachloroethylene	mg/L	0.0050	0.0070	5	1
Total dissolved solids	mg/L	200	641	5	1
Total radium	μCi/mL	5.0E–09	2.1E–08	5	2
Trichloroethylene	mg/L	0.0050	0.092	5	3
Tritium	μCi/mL	2.0E–05	2.7E–03	5	3

Table 8-69
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Coal Pile Runoff Containment Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	3.4E-08	5	1
Nonvolatile beta	μCi/mL	5.0E-08	7.8E-08	5	1
Specific conductance	μS/cm	100	140	5	1
Lead	mg/L	0.015	0.020	5	1
Total radium	μCi/mL	5.0E-09	1.6E-08	5	5

Table 8-70
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Seepage Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Congaree-Fourmile					
Alkalinity (as CaCO ₃)	mg/L	100	412	18	5
Specific conductance	μS/cm	100	1,740	18	16
Nitrate as nitrogen	mg/L	10	21	18	1
pH	pH	≥8.5	12	18	5
Radium-226	μCi/mL	1.6E-08	1.9E-08	12	2
Antimony	mg/L	0.0050	0.0050	18	1
Strontium-90	μCi/mL	8.0E-09	1.2E-08	12	1
Total dissolved solids	mg/L	200	733	18	3
Total radium	μCi/mL	5.0E-09	6.3E-09	18	2
Tritium	μCi/mL	2.0E-05	5.7E-04	18	11
Uranium-234	μCi/mL	1.4E-08	1.4E-08	12	1
Uranium-238	μCi/mL	1.5E-08	4.6E-07	12	4
Production					
Benzene	mg/L	0.0050	0.0060	1	1
Water table					
Silver	mg/L	0.050	0.068	65	1
Alkalinity (as CaCO ₃)	mg/L	100	325	70	1

Table 8-70
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Seepage Basins, Cont'd.

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	1.7E-06	70	38
Americium-241	μCi/mL	6.3E-09	2.2E-07	36	11
Barium	mg/L	2.0	2.0	65	1
Nonvolatile beta	μCi/mL	5.0E-08	5.7E-06	70	39
Cadmium	mg/L	0.0050	0.034	65	20
Specific conductance	μS/cm	100	2,890	70	48
Copper	mg/L	1.3	1.8	65	1
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.0039	65	1
Fluoride	mg/L	4.0	4.6	65	1
Mercury	mg/L	0.0020	0.0074	65	6
Nickel	mg/L	0.10	0.29	65	7
Nitrate as nitrogen	mg/L	10	640	65	42
Lead	mg/L	0.015	0.30	65	16
pH	pH	≥8.5	12	70	2
pH	pH	≤4.0	2.8	70	28
Radium-226	μCi/mL	1.6E-08	1.8E-07	36	14
Radium-228	μCi/mL	7.8E-09	4.5E-07	36	16
Antimony	mg/L	0.0050	0.0098	65	4
Sulfate	mg/L	400	7,320	65	4
Strontium-89	μCi/mL	2.0E-08	1.6E-06	38	8
Strontium-90	μCi/mL	8.0E-09	1.4E-06	38	17
Tetrachloroethylene	mg/L	0.0050	0.037	65	6
Total dissolved solids	mg/L	200	1,970	65	39
Total radium	μCi/mL	5.0E-09	4.1E-07	65	35
Trichloroethylene	mg/L	0.0050	0.071	65	5
Tritium	μCi/mL	2.0E-05	3.6E-02	70	57
Uranium	mg/L	0.020	5.4	65	26
Uranium-233/234	μCi/mL	1.4E-08	1.9E-07	15	8
Uranium-234	μCi/mL	1.4E-08	2.6E-07	36	11
Uranium-235	μCi/mL	1.4E-08	4.9E-08	36	3
Uranium-238	μCi/mL	1.5E-08	8.5E-07	36	16
1,1-Dichloroethylene	mg/L	0.0070	0.027	65	1

Table 8-71
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Sludge Land Application Site

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	165	4	2
Lead	mg/L	0.015	0.12	4	1
Total radium	μCi/mL	5.0E-09	1.2E-08	4	2
Tritium	μCi/mL	2.0E-05	2.8E-04	4	3

Table 8-72
Maximum Constituents Results Exceeding Applicable Standards for Wells at the F-Area Tank Farm

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	1.2E-07	20	17
Nonvolatile beta	μCi/mL	5.0E-08	1.2E-06	20	9
Specific conductance	μS/cm	100	4,790	24	14
pH	pH	≥8.5	12	24	4
Total radium	μCi/mL	5.0E-09	9.4E-08	20	16
Tritium	μCi/mL	2.0E-05	6.4E-05	20	2

Table 8-73
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Acid/Caustic Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	537	4	3
Sulfate	mg/L	400	4,280	4	2
Total dissolved solids	mg/L	200	308	4	2
Total radium	μCi/mL	5.0E-09	7.2E-09	4	1
Tritium	μCi/mL	2.0E-05	6.2E-05	4	4

Table 8-74**Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Auxiliary Pump Pit**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	101	2	1
Specific conductance	μS/cm	100	302	2	1

Table 8-75**Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Canyon Building**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	207	4	3
Lead	mg/L	0.015	0.11	4	2
Tetrachloroethylene	mg/L	0.0050	0.060	4	1
Total radium	μCi/mL	5.0E-09	1.5E-08	4	2
Trichloroethylene	mg/L	0.0050	0.029	4	1
Tritium	μCi/mL	2.0E-05	9.9E-05	4	4
Uranium-238	μCi/mL	1.5E-08	4.4E-07	4	2

Table 8-76
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Coal Pile Runoff Containment Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	1.5E-08	4	1
Specific conductance	μS/cm	100	1,100	4	3
Lead	mg/L	0.015	0.044	4	3
pH	pH	≤4.0	3.2	4	2
Sulfate	mg/L	400	3,520	4	2
Total dissolved solids	mg/L	200	895	3	1
Total radium	μCi/mL	5.0E-09	7.4E-09	4	2
Tritium	μCi/mL	2.0E-05	3.1E-05	4	4

Table 8-77
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Retention Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Lead	mg/L	0.015	0.021	5	1
Total radium	μCi/mL	5.0E-09	5.7E-09	5	1
Tritium	μCi/mL	2.0E-05	4.8E-05	5	5

Table 8-78
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Seepage Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Congaree-Fourmile					
Alkalinity (as CaCO ₃)	mg/L	100	274	19	2
Gross alpha	μCi/mL	1.5E-08	2.0E-08	19	1
Nonvolatile beta	μCi/mL	5.0E-08	4.1E-07	19	1
Specific conductance	μS/cm	100	1,320	19	19
Nitrate as nitrogen	mg/L	10	425	19	1
pH	pH	≥8.5	12	19	3
Radium-228	μCi/mL	7.8E-09	6.7E-08	2	1
Strontium-90	μCi/mL	8.0E-09	2.1E-07	2	1
Tetrachloroethylene	mg/L	0.0050	0.010	19	1
Total dissolved solids	mg/L	200	255	19	1
Total radium	μCi/mL	5.0E-09	5.1E-08	19	2
Trichloroethylene	mg/L	0.0050	0.013	19	2
Tritium	μCi/mL	2.0E-05	3.8E-03	19	5
Production					
Benzene	mg/L	0.0050	0.015	1	1
Lead	mg/L	0.015	0.023	1	1
Water table					
Silver	mg/L	0.050	0.13	108	1
Alkalinity (as CaCO ₃)	mg/L	100	966	112	7
Gross alpha	μCi/mL	1.5E-08	6.1E-07	114	37
Americium-241	μCi/mL	6.3E-09	1.9E-08	17	4
Arsenic	mg/L	0.050	0.40	108	1
Nonvolatile beta	μCi/mL	5.0E-08	1.2E-05	114	47
Cadmium	mg/L	0.0050	0.018	108	2
Specific conductance	μS/cm	100	3,600	114	75
Cobalt-60	μCi/mL	1.0E-07	3.3E-07	17	6
Mercury	mg/L	0.0020	0.0094	108	11
Nickel	mg/L	0.10	0.16	108	1
Nitrate as nitrogen	mg/L	10	695	108	52
Lead	mg/L	0.015	0.12	108	8
pH	pH	≥8.5	13	114	10

Table 8-78
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Seepage Basins, Cont'd.

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
pH	pH	≤4.0	3.5	114	16
Radium-226	μCi/mL	1.6E-08	4.9E-08	17	6
Radium-228	μCi/mL	7.8E-09	1.1E-06	17	10
Antimony	mg/L	0.0050	0.0066	108	2
Sulfate	mg/L	400	529	108	1
Strontium-89	μCi/mL	2.0E-08	3.1E-07	18	6
Strontium-90	μCi/mL	8.0E-09	3.9E-06	18	14
Tetrachloroethylene	mg/L	0.0050	0.016	108	8
Total dissolved solids	mg/L	200	1,010	108	32
Total radium	μCi/mL	5.0E-09	3.3E-07	108	39
Trichloroethylene	mg/L	0.0050	0.0069	108	1
Tritium	μCi/mL	2.0E-05	2.2E-02	114	97
Uranium-234	μCi/mL	1.4E-08	2.4E-08	16	2
1,1,1-Trichloroethane	mg/L	0.20	0.27	108	1

Table 8-79
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Sludge Land Application Site

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Lead	mg/L	0.015	0.032	3	1
Total radium	μCi/mL	5.0E-09	6.8E-09	3	1

Table 8-80
Maximum Constituents Results Exceeding Applicable Standards for Wells at the H-Area Tank Farm

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	1.6E-07	28	6
Nonvolatile beta	μCi/mL	5.0E-08	2.6E-07	28	2
Cadmium	mg/L	0.0050	0.24	28	14
Specific conductance	μS/cm	100	1,040	28	10
Mercury	mg/L	0.0020	0.0037	28	2
Nitrate as nitrogen	mg/L	10	36	28	1
Lead	mg/L	0.015	0.43	28	14
Total radium	μCi/mL	5.0E-09	1.9E-08	27	12
Tritium	μCi/mL	2.0E-05	2.4E-04	28	17

Table 8-81
Maximum Constituents Results Exceeding Applicable Standards for Wells at the M-Area Waste Disposal Facility (Y Area)

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	239	5	2
Specific conductance	μS/cm	100	1,030	5	3
pH	pH	≥8.5	12	5	3
Total dissolved solids	mg/L	200	281	5	1
Total radium	μCi/mL	5.0E-09	5.9E-09	5	1
Tritium	μCi/mL	2.0E-05	2.0E-05	5	1

Table 8-82
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Old F-Area Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	5.4E-08	4	1
Nonvolatile beta	μCi/mL	5.0E-08	2.9E-07	4	2
Specific conductance	μS/cm	100	167	4	2
Nitrate as nitrogen	mg/L	10	12	4	1
pH	pH	≤4.0	3.6	4	1
Total radium	μCi/mL	5.0E-09	9.0E-09	4	2
Trichloroethylene	mg/L	0.0050	0.040	4	2
Tritium	μCi/mL	2.0E-05	1.6E-04	4	3
Uranium-233/234	μCi/mL	1.4E-08	1.5E-08	4	1
Uranium-238	μCi/mL	1.5E-08	2.7E-08	4	2

Table 8-83
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Radioactive Waste Burial Grounds

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Burial Ground 643-E					
Alkalinity (as CaCO ₃)	mg/L	100	538	27	2
Gross alpha	μCi/mL	1.5E-08	2.2E-07	42	5
Nonvolatile beta	μCi/mL	5.0E-08	1.3E-07	42	3
Carbon tetrachloride	mg/L	0.0050	0.012	27	1
Cadmium	mg/L	0.0050	0.029	27	1
Specific conductance	μS/cm	100	1,630	48	11
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.12	27	3
Mercury	mg/L	0.0020	0.013	34	3
Nitrate as nitrogen	mg/L	10	16	34	1
Lead	mg/L	0.015	0.041	27	4
pH	pH	≥8.5	12	48	2
Antimony	mg/L	0.0050	0.0056	23	1

Table 8-83**Maximum Constituents Results Exceeding Applicable Standards for Wells at the Radioactive Waste Burial Grounds, Cont'd.**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Tetrachloroethylene	mg/L	0.0050	0.029	27	5
Total dissolved solids	mg/L	200	921	27	2
Total radium	μCi/mL	5.0E-09	9.8E-08	33	12
Trichloroethylene	mg/L	0.0050	0.69	27	8
Tritium	μCi/mL	2.0E-05	2.6E-01	42	35
trans-1,2-Dichloroethylene	mg/L	0.10	0.62	27	4
Uranium-235	μCi/mL	1.4E-08	2.0E-08	22	2
1,1-Dichloroethylene	mg/L	0.0070	0.035	27	1
Congaree-Fourmile (Burial Grounds 643-E)					
Alkalinity (as CaCO ₃)	mg/L	100	1,110	6	3
Nonvolatile beta	μCi/mL	5.0E-08	5.5E-08	6	1
Specific conductance	μS/cm	100	4,380	6	6
Mercury	mg/L	0.0020	0.0020	6	1
Lead	mg/L	0.015	0.018	6	1
pH	pH	≥8.5	13	6	6
Total dissolved solids	mg/L	200	2,410	6	3
Total radium	μCi/mL	5.0E-09	5.6E-09	6	1
Trichloroethylene	mg/L	0.0050	0.0080	6	1
Tritium	μCi/mL	2.0E-05	9.0E-05	6	1
Burial Grounds 643-7E and Mixed Waste Management Facility 643-28E					
Alkalinity (as CaCO ₃)	mg/L	100	145	39	3
Americium-241	μCi/mL	6.3E-09	7.8E-09	12	1
Specific conductance	μS/cm	100	451	39	12
Benzene	mg/L	0.0050	0.045	39	1
Endrin	mg/L	0.00020	0.00058	37	1
Lindane	mg/L	0.00020	0.00025	37	1
Nickel	mg/L	0.10	0.12	39	1
Nitrate as nitrogen	mg/L	10	11	39	1
pH	pH	≥8.5	11	39	4
Tetrachloroethylene	mg/L	0.0050	0.054	39	7
Total radium	μCi/mL	5.0E-09	1.0E-08	38	2
Trichloroethylene	mg/L	0.0050	0.17	39	17

Table 8-83
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
Radioactive Waste Burial Grounds, Cont'd.

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Tritium	μCi/mL	2.0E-05	2.3E-01	39	29
Uranium-234	μCi/mL	1.4E-08	1.4E-08	6	1
Congaree-Fourmile (Burial Grounds 643-7E and Mixed Waste Management Facility 643-28E)					
Alkalinity (as CaCO ₃)	mg/L	100	385	15	10
Americium-241	μCi/mL	6.3E-09	3.9E-08	7	1
Specific conductance	μS/cm	100	1,840	15	15
Lead	mg/L	0.015	0.020	15	1
pH	pH	≥8.5	13	15	6
Tetrachloroethylene	mg/L	0.0050	0.0055	15	2
Total dissolved solids	mg/L	200	435	15	4
Trichloroethylene	mg/L	0.0050	0.023	15	5
Tritium	μCi/mL	2.0E-05	1.5E-04	15	3
E-Area Vaults					
Alkalinity (as CaCO ₃)	mg/L	100	109	15	1
Gross alpha	μCi/mL	1.5E-08	2.6E-08	15	1
Specific conductance	μS/cm	100	470	15	4
pH	pH	≥8.5	11	15	2
Tetrachloroethylene	mg/L	0.0050	0.0065	15	1
Total radium	μCi/mL	5.0E-09	1.7E-08	15	1
Trichloroethylene	mg/L	0.0050	0.0090	15	2
Tritium	μCi/mL	2.0E-05	9.8E-03	15	7
Congaree-Fourmile (E-Area Vaults)					
Alkalinity (as CaCO ₃)	mg/L	100	1,300	2	2
Gross alpha	μCi/mL	1.5E-08	1.5E-08	2	1
Nonvolatile beta	μCi/mL	5.0E-08	9.2E-08	2	1
Specific conductance	μS/cm	100	5,030	2	2
Lead	mg/L	0.015	0.052	2	1
pH	pH	≥8.5	13	2	1
Total dissolved solids	mg/L	200	1,490	2	1
Total radium	μCi/mL	5.0E-09	8.1E-09	2	1
Tritium	μCi/mL	2.0E-05	1.8E-04	2	1

Table 8-83
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
Radioactive Waste Burial Grounds, Cont'd.

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Hazardous Waste/Mixed Waste Disposal Facility					
Specific conductance	μS/cm	100	143	4	1
Tetrachloroethylene	mg/L	0.0050	0.0050	4	1
Total radium	μCi/mL	5.0E-09	5.0E-09	4	1
SRL Site Characterization					
Specific conductance	μS/cm	100	231	15	4
Nitrite as nitrogen	mg/L	1.0	1.7	15	1
Lead	mg/L	0.015	0.073	15	5
Tritium	μCi/mL	2.0E-05	5.7E-04	15	8
Uranium-235	μCi/mL	1.4E-08	1.8E-08	14	3
Uranium-238	μCi/mL	1.5E-08	4.5E-07	14	6

Table 8-84
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
S-Area Defense Waste Processing Facility

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Tetrachloroethylene	mg/L	0.0050	0.0090	6	1
Total dissolved solids	mg/L	200	440	6	1
Total radium	μCi/mL	5.0E-09	5.8E-09	6	1
Trichloroethylene	mg/L	0.0050	0.043	6	1
Tritium	μCi/mL	2.0E-05	3.9E-05	6	2

Table 8-85
Maximum Constituents Results Exceeding Applicable Standards for Wells at the S-Area Vitrification Building

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	182	8	1
Specific conductance	μS/cm	100	606	8	4
pH	pH	≥8.5	9.7	8	1
Total dissolved solids	mg/L	200	405	8	2
Total radium	μCi/mL	5.0E-09	1.5E-08	8	3
Tritium	μCi/mL	2.0E-05	3.1E-05	8	4

Table 8-86
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Z and ZW Wells

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	196	19	3
pH	pH	≥8.5	9.6	19	3
Tritium	μCi/mL	2.0E-05	1.4E-04	11	5

Table 8-87
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Z-Area Low Point Drain Tank

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	130	2	1
Tritium	μCi/mL	2.0E-05	2.6E-05	2	2

Table 8-88
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Central Shops Burning/Rubble Pit South of the Ford Building Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Mercury	mg/L	0.0020	0.0025	3	1
Tetrachloroethylene	mg/L	0.0050	0.0050	3	1
Total radium	μCi/mL	5.0E-09	2.9E-08	3	2
Trichloroethylene	mg/L	0.0050	0.0095	3	1
Tritium	μCi/mL	2.0E-05	2.1E-05	3	1

Table 8-89
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Central Shops Diesel Spill

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	153	9	2
Specific conductance	μS/cm	100	400	9	2
Nitrite as nitrogen	mg/L	1.0	3.4	9	1
pH	pH	≥8.5	11	9	1
Total radium	μCi/mL	5.0E-09	1.0E-08	8	1
Trichloroethylene	mg/L	0.0050	0.0050	1	1

Table 8-90
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Ford Building Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	131	5	1
Total radium	μCi/mL	5.0E-09	5.1E-09	5	1
Tritium	μCi/mL	2.0E-05	1.8E-04	5	2

Table 8-91
Maximum Constituents Results Exceeding Applicable Standards for Wells at the D-Area Burning/Rubble Pits

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	197	4	2
Total dissolved solids	mg/L	200	1,140	4	1

Table 8-92
Maximum Constituents Results Exceeding Applicable Standards for Wells at the D-Area Coal Pile Runoff Containment Basin and Ash Basins

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	261	15	2
Gross alpha	μCi/mL	1.5E-08	2.4E-07	15	4
Beryllium	mg/L	0.0010	0.044	14	4
Nonvolatile beta	μCi/mL	5.0E-08	1.0E-07	15	3
Cadmium	mg/L	0.0050	0.028	15	4
Specific conductance	μS/cm	100	5,110	15	12
Chromium	mg/L	0.10	1.6	15	3
Nickel	mg/L	0.10	1.6	14	6
Lead	mg/L	0.015	0.026	15	1
pH	pH	≥8.5	8.6	15	1
pH	pH	≤4.0	2.1	15	6
Sulfate	mg/L	400	69,900	15	9
Tetrachloroethylene	mg/L	0.0050	0.013	15	2
Total dissolved solids	mg/L	200	9,070	15	12
Total radium	μCi/mL	5.0E-09	3.8E-08	15	5
Trichloroethylene	mg/L	0.0050	0.066	15	5
Tritium	μCi/mL	2.0E-05	1.9E-04	15	2

Table 8-93**Maximum Constituents Results Exceeding Applicable Standards for Wells at the D-Area Oil Disposal Basin**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	196	4	1
Tetrachloroethylene	mg/L	0.0050	0.013	4	2
Trichloroethylene	mg/L	0.0050	0.059	4	1

Table 8-94**Maximum Constituents Results Exceeding Applicable Standards for Wells at the Chemicals, Metals, and Pesticide Pits**

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	105	19	2
Specific conductance	μS/cm	100	199	19	12
Lead	mg/L	0.015	0.034	19	4
pH	pH	≥8.5	11	19	3
Tetrachloroethylene	mg/L	0.0050	0.069	19	4
Trichloroethylene	mg/L	0.0050	0.048	19	2
1,2-Dichloroethane	mg/L	0.0050	0.098	19	2

Table 8-95
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
Interim Waste Technology Sites

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Site B					
Alkalinity (as CaCO ₃)	mg/L	100	397	14	3
Specific conductance	μS/cm	100	1,220	14	6
Lead	mg/L	0.015	0.077	14	1
pH	pH	≥8.5	12	14	6
Radium-226	μCi/mL	1.6E-08	2.7E-08	14	5
Antimony	mg/L	0.0050	0.0069	14	1
Total dissolved solids	mg/L	200	336	14	2
Uranium-235	μCi/mL	1.4E-08	1.9E-08	14	2
Uranium-238	μCi/mL	1.5E-08	4.5E-07	13	8
Site P					
Alkalinity (as CaCO ₃)	mg/L	100	128	11	2
Specific conductance	μS/cm	100	456	11	3
pH	pH	≥8.5	12	11	2
Uranium-235	μCi/mL	1.4E-08	1.7E-08	10	1
Uranium-238	μCi/mL	1.5E-08	4.7E-07	10	6
Site Q					
Alkalinity (as CaCO ₃)	mg/L	100	128	13	2
Specific conductance	μS/cm	100	490	13	4
Potassium-40	μCi/mL	3.0E-07	4.4E-07	13	1
pH	pH	≥8.5	12	13	3
Radium-226	μCi/mL	1.6E-08	1.0E-07	13	2
Uranium-235	μCi/mL	1.4E-08	2.3E-08	12	1
Uranium-238	μCi/mL	1.5E-08	4.5E-07	11	5

Table 8-96
Maximum Constituents Results Exceeding Applicable Standards for Wells at the P-28 Well Cluster in F Area

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	568	3	1
Specific conductance	μS/cm	100	1,750	3	1
pH	pH	≥8.5	12	3	1
Total dissolved solids	mg/L	200	436	3	1

Table 8-97
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Potential New Production Reactor Site Characterization Wells

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	163	14	1
Specific conductance	μS/cm	100	710	14	5
pH	pH	≥8.5	12	14	4
Total dissolved solids	mg/L	200	252	13	1

Table 8-98
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Road A Chemical Basin (Baxley Road)

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Lead	mg/L	0.015	0.048	4	1
Tetrachloroethylene	mg/L	0.0050	0.055	4	3
Total radium	μCi/mL	5.0E-09	6.1E-09	4	2
Trichloroethylene	mg/L	0.0050	0.0060	4	1

Table 8-99
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Sanitary Landfill

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Alkalinity (as CaCO ₃)	mg/L	100	216	57	9
Cadmium	mg/L	0.0050	0.021	57	4
Specific conductance	μS/cm	100	668	57	11
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.40	57	9
Benzene	mg/L	0.0050	0.0099	57	5
Fluoride	mg/L	4.0	6.2	57	1
Lead	mg/L	0.015	0.040	57	2
pH	pH	≤4.0	3.9	57	1
Antimony	mg/L	0.0050	0.016	31	2
Tetrachloroethylene	mg/L	0.0050	0.029	57	5
Total dissolved solids	mg/L	200	238	57	1
Total radium	μCi/mL	5.0E-09	1.4E-08	57	13
Trichloroethylene	mg/L	0.0050	0.049	57	11
Tritium	μCi/mL	2.0E-05	1.4E-04	57	4
trans-1,2-Dichloroethylene	mg/L	0.10	0.19	57	4
1,1-Dichloroethylene	mg/L	0.0070	0.034	57	4
1,1,1-Trichloroethane	mg/L	0.20	0.25	57	1
1,1,2-Trichloroethane	mg/L	0.0050	1.2	57	1
1,2-Dichloroethane	mg/L	0.0050	0.0050	57	4
1,4-Dichlorobenzene	mg/L	0.075	0.099	23	1

Table 8-100
Maximum Constituents Results Exceeding Applicable Standards for Wells at the Sewage Sludge Application Sites

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
40-Acre Hardwood					
Total radium	μCi/mL	5.0E-09	1.9E-08	3	1
Lower Kato Road					
Gross alpha	μCi/mL	1.5E-08	1.6E-08	3	1
Specific conductance	μS/cm	100	140	3	1
Lead	mg/L	0.015	0.031	3	1
Total radium	μCi/mL	5.0E-09	1.5E-08	3	2
Sandy (Lucy)					
Specific conductance	μS/cm	100	113	2	1
Kato Road					
Gross alpha	μCi/mL	1.5E-08	2.0E-08	3	1
Total radium	μCi/mL	5.0E-09	8.2E-09	3	1
Second Par Pond Borrow Pit					
Alkalinity (as CaCO ₃)	mg/L	100	116	3	1
Specific conductance	μS/cm	100	113	3	1
Total radium	μCi/mL	5.0E-09	2.1E-08	3	3

Table 8-101
Maximum Constituents Results Exceeding Applicable Standards for Wells at the New TNX Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Specific conductance	μS/cm	100	391	4	2
Total dissolved solids	mg/L	200	204	4	1
Total radium	μCi/mL	5.0E-09	1.2E-08	4	2

Table 8-102
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
Old TNX Seepage Basin

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Carbon tetrachloride	mg/L	0.0050	0.033	7	2
Specific conductance	μS/cm	100	789	7	4
Mercury	mg/L	0.0020	0.0022	7	1
Nitrate as nitrogen	mg/L	10	150	7	2
pH	pH	≥8.5	8.6	7	1
Radium-226	μCi/mL	1.6E-08	1.7E-08	7	2
Radium-228	μCi/mL	7.8E-09	9.3E-08	7	4
Strontium-90	μCi/mL	8.0E-09	8.8E-09	7	1
Tetrachloroethylene	mg/L	0.0050	0.031	7	1
Total dissolved solids	mg/L	200	687	7	2
Total radium	μCi/mL	5.0E-09	7.4E-09	7	1
Trichloroethylene	mg/L	0.0050	1.2	7	5
Tritium	μCi/mL	2.0E-05	2.4E-05	7	1

Table 8-103
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
TNX-Area Assessment Wells

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Gross alpha	μCi/mL	1.5E-08	7.3E-08	12	1
Americium-241	μCi/mL	6.3E-09	1.5E-08	12	1
Nonvolatile beta	μCi/mL	5.0E-08	2.1E-07	12	1
Carbon tetrachloride	mg/L	0.0050	0.26	12	3
Specific conductance	μS/cm	100	280	12	7
Chloroethene (Vinyl chloride)	mg/L	0.0020	0.0020	12	1
Endrin	mg/L	0.00020	0.00063	12	10
Potassium-40	μCi/mL	3.0E-07	4.5E-07	12	1
Lindane	mg/L	0.00020	0.00028	12	8
Nitrate as nitrogen	mg/L	10	31	12	3
Radium-226	μCi/mL	1.6E-08	2.9E-08	12	4
Radium-228	μCi/mL	7.8E-09	1.6E-08	12	3
Tetrachloroethylene	mg/L	0.0050	0.018	12	4
Total dissolved solids	mg/L	200	264	12	1
Total radium	μCi/mL	5.0E-09	7.0E-09	12	2
Trichloroethylene	mg/L	0.0050	0.82	12	5
Uranium-238	μCi/mL	1.5E-08	4.6E-07	12	6

Table 8-104
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
TNX-Area Background Wells

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Americium-241	μCi/mL	6.3E-09	1.6E-08	3	2
Radium-226	μCi/mL	1.6E-08	2.6E-08	3	1
Total radium	μCi/mL	5.0E-09	6.7E-09	3	1
Uranium-238	μCi/mL	1.5E-08	4.2E-07	3	1

Table 8-105
Maximum Constituents Results Exceeding Applicable Standards for Wells at the
TNX Burying Ground

Constituent	Unit	Standard	Maximum Result	Number of Wells	
				Analyzed	Exceeding Standards
Carbon tetrachloride	mg/L	0.0050	0.58	8	4
Specific conductance	μS/cm	100	379	8	5
Mercury	mg/L	0.0020	0.0037	8	1
Nitrate as nitrogen	mg/L	10	43	8	4
pH	pH	≤4.0	4.0	8	1
Radium-226	μCi/mL	1.6E-08	2.9E-08	5	2
Radium-228	μCi/mL	7.8E-09	1.3E-07	5	2
Tetrachloroethylene	mg/L	0.0050	0.031	8	2
Total radium	μCi/mL	5.0E-09	3.6E-08	8	4
Trichloroethylene	mg/L	0.0050	2.5	8	5

Table 8-106
EPA Primary Drinking Water Standards used for the Groundwater Monitoring Program

Analyte	Level	Unit	Status	Reference
Americium-241	6.34E-09	μCi/mL	proposed	EPA, 1991
Antimony	0.005 ^a	mg/L	proposed	EPA, 1990
Antimony-125	3E-07	μCi/mL	final	EPA, 1977
Arsenic	0.05	mg/L	final	CFR, 1991
Barium	2	mg/L	final	CFR, 1991
Benzene	0.005	mg/L	final	CFR, 1991
Beryllium	0.001	mg/L	proposed	EPA, 1990
2-sec-Butyl-4,6-dinitrophenol (Dinoseb)	0.007	mg/L	proposed	EPA, 1990
Cadmium	0.005	mg/L	final	CFR, 1991
Carbon tetrachloride	0.005	mg/L	final	CFR, 1991
Cerium-141	3E-07	μCi/mL	final	EPA, 1977
Cerium-144	2.61E-07	μCi/mL	proposed	EPA, 1991
Cesium-134	8.13E-08 ^b	μCi/mL	proposed	EPA, 1991
Cesium-137	2E-07	μCi/mL	final	EPA, 1977
Chlordane	0.002	mg/L	final	CFR, 1991
Chloroethene (Vinyl chloride)	0.002	mg/L	final	CFR, 1991
Chromium	0.1	mg/L	final	CFR, 1991
Chromium-51	6E-06	μCi/mL	final	EPA, 1977
Cobalt-57	1E-06	μCi/mL	final	EPA, 1977
Cobalt-58	9E-06	μCi/mL	final	EPA, 1977
Cobalt-60	1E-07	μCi/mL	final	EPA, 1977
Copper	1.3	mg/L	final	CFR, 1991
Cyanide	0.2	mg/L	proposed	EPA, 1990
Dibromochloropropane	0.0002	mg/L	final	CFR, 1991
1,2-Dichlorobenzene	0.6	mg/L	final	CFR, 1991
1,4-Dichlorobenzene	0.075	mg/L	final	CFR, 1991
1,2-Dichloroethane	0.005	mg/L	final	CFR, 1991
1,1-Dichloroethylene	0.007	mg/L	final	CFR, 1991
cis-1,2-Dichloroethylene	0.07	mg/L	final	CFR, 1991
trans-1,2-Dichloroethylene	0.1	mg/L	final	CFR, 1991
Dichloromethane (Methylene chloride)	0.005	mg/L	proposed	EPA, 1990
2,4-Dichlorophenoxyacetic acid	0.07	mg/L	final	CFR, 1991

^a This is the lower of two proposed levels.

^b EPD/EMS uses the proposed standard because it is a lower value; the final DWS in 1977 may have been in error.

Table 8-106
EPA Primary Drinking Water Standards used for the Groundwater Monitoring Program, Cont'd.

Analyte	Level	Unit	Status	Reference
1,2-Dichloropropane	0.005	mg/L	final	CFR, 1991
Endrin	0.0002	mg/L	final	CFR, 1991
Ethylbenzene	0.7	mg/L	final	CFR, 1991
Europium-154	2E-07	μCi/mL	final	EPA, 1977
Europium-155	6E-07	μCi/mL	final	EPA, 1977
Fluoride	4	mg/L	final	CFR, 1991
Gross alpha ^a	1.5E-08	μCi/mL	final	CFR, 1991
Heptachlor	0.0004	mg/L	final	CFR, 1991
Heptachlor epoxide	0.0002	mg/L	final	CFR, 1991
Hexachlorobenzene	0.001	mg/L	proposed	EPA, 1990
Hexachlorocyclopentadiene	0.05	mg/L	proposed	EPA, 1990
Iodine-131	3E-09	μCi/mL	final	EPA, 1977
Lead	0.015	mg/L	final	CFR, 1991
Lindane	0.0002	mg/L	final	CFR, 1991
Manganese-54	3E-07	μCi/mL	final	EPA, 1977
Mercury	0.002	mg/L	final	CFR, 1991
Methoxychlor	0.04	mg/L	final	CFR, 1991
Neptunium-237	7.06E-09	μCi/mL	proposed	EPA, 1991
Nickel	0.1	mg/L	proposed	EPA, 1990
Niobium-95	3E-07	μCi/mL	final	EPA, 1977
Nitrate (as nitrogen)	10	mg/L	final	CFR, 1991
Nitrite (as nitrogen)	1	mg/L	final	CFR, 1991
Nonvolatile beta	5E-08	μCi/mL	proposed	EPA, 1986
PAHs:				
Benzo[a]anthracene	0.0001	mg/L	proposed	EPA, 1990
Benzo[b]fluoranthene	0.0002	mg/L	proposed	EPA, 1990
Benzo[k]fluoranthene	0.0002	mg/L	proposed	EPA, 1990
Benzo[a]pyrene	0.0002	mg/L	proposed	EPA, 1990
Chrysene	0.0002	mg/L	proposed	EPA, 1990
Dibenz[a,h]anthracene	0.0003	mg/L	proposed	EPA, 1990
PCBs ^b	0.0005	mg/L	final	CFR, 1991
Pentachlorophenol	0.001	mg/L	final	CFR, 1991

a The standard given is for gross alpha including radium-226 but excluding radon and uranium.

b Analyses were conducted in 1991 for the following: PCB 1016, PCB 1221, PCB 1232, PCB 1242, PCB 1248, PCB 1254, PCB 1260, and PCB 1262.

Table 8-106

EPA Primary Drinking Water Standards used for the Groundwater Monitoring Program, Cont'd.

Analyte	Level	Unit	Status	Reference
Plutonium-238	7.02E-09	μCi/mL	proposed	EPA, 1991
Plutonium-239	6.21E-08	μCi/mL	proposed	EPA, 1991
Plutonium-239/240	6.21E-08 ^a	μCi/mL	proposed	EPA, 1991
Plutonium-241	6.26E-08	μCi/mL	proposed	EPA, 1991
Plutonium-242	6.54E-08	μCi/mL	proposed	EPA, 1991
Potassium-40	3E-07	μCi/mL	proposed	EPA, 1986
Radium-226	1.57E-08	μCi/mL	proposed	EPA, 1991
Radium-228	7.85E-09	μCi/mL	proposed	EPA, 1991
Ruthenium-103	2E-07	μCi/mL	final	EPA, 1977
Ruthenium-106	3E-08	μCi/mL	final	EPA, 1977
Selenium	0.05	mg/L	final	CFR, 1991
Silver	0.05	mg/L	final	CFR, 1991
Sodium-22	4.66E-07	μCi/mL	proposed	EPA, 1991
Strontium-89	2E-08 ^b	μCi/mL	final	EPA, 1977
Strontium-89/90	8E-09 ^a	μCi/mL	final	CFR, 1991
Strontium-90	8E-09	μCi/mL	final	CFR, 1991
Styrene	0.1	mg/L	final	CFR, 1991
Sulfate	400	mg/L	proposed	EPA, 1990
Technetium-99	9E-07	μCi/mL	final	EPA, 1977
Tetrachloroethylene	0.005	mg/L	final	CFR, 1991
Thallium	0.001 ^c	mg/L	proposed	EPA, 1990
Thorium-228	1.25E-07	μCi/mL	proposed	EPA, 1991
Thorium-230	7.92E-08	μCi/mL	proposed	EPA, 1991
Thorium-232	8.8E-08	μCi/mL	proposed	EPA, 1991
Toluene	1	mg/L	final	CFR, 1991
Total radium	5E-09	μCi/mL	final	CFR, 1991
Toxaphene	0.003	mg/L	final	CFR, 1991
2,4,5-TP (Silvex)	0.05	mg/L	final	CFR, 1991
1,2,4-Trichlorobenzene	0.009	mg/L	proposed	EPA, 1990
1,1,1-Trichloroethane	0.2	mg/L	final	CFR, 1991
1,1,2-Trichloroethane	0.005	mg/L	proposed	EPA, 1990

a For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

b This is the lower of two levels given for strontium-89.

c This is the lower of two proposed levels.

Table 8-106
EPA Primary Drinking Water Standards used for the Groundwater Monitoring Program, Cont'd.

Analyte	Level	Unit	Status	Reference
Trichloroethylene	0.005	mg/L	final	CFR, 1991
Total trihalomethanes ^a (includes bromodichloromethane, bromoform, chloroform, and dibromochloromethane)	0.1	mg/L	final	CFR, 1991
Tritium	2E-05	μCi/mL	final	CFR, 1991
Uranium	0.02	mg/L	proposed	EPA, 1991
Uranium alpha activity	3E-08	μCi/mL	proposed	EPA, 1991
Uranium-233/234	1.38E-08 ^b	μCi/mL	proposed	EPA, 1991
Uranium-234	1.39E-08	μCi/mL	proposed	EPA, 1991
Uranium-235	1.45E-08	μCi/mL	proposed	EPA, 1991
Uranium-238	1.46E-08	μCi/mL	proposed	EPA, 1991
Xylenes	10	mg/L	final	CFR, 1991
Zinc-65	3E-07	μCi/mL	final	EPA, 1977
Zirconium-95	2E-07	μCi/mL	final	EPA, 1977

Note:

Drinking water standards set by EPA (1977) correspond to the level at which each radionuclide contributes 4 mrem/yr of dose to an individual consuming 2 L of contaminated liquid a day. See EPA (1977) for details.

References (for Table 8-106 Only):

CFR (Code of Federal Regulations), 1991. "National Primary Drinking Water Regulations," *40 CFR, Part 141*, pp. 578-715, Washington, DC.

EPA (U.S. Environmental Protection Agency), 1977. *National Interim Primary Drinking Water Regulations*, EPA-570/9-76-003, Washington, DC.

EPA (U.S. Environmental Protection Agency), 1986. "Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides (Proposed)," *Federal Register*, September 30, 1986, pp. 34835-34862, Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. "National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals; Proposed Rule," *Federal Register*, July 25, 1990, pp. 30369-30448, Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. "National Primary Drinking Water Regulations; Radionuclides; Proposed Rule," *Federal Register*, July 18, 1991, pp. 33052-33127, Washington, DC.

^a EPD/EMS does not test for total trihalomethanes, but each of these analytes is tested separately.

^b For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

To Learn About:	Turn to page:
♦ Gross alpha, nonvolatile beta, and Cs-137 concentrations in Savannah River fish	444
♦ Cs-137 concentrations in fish from onsite streams and ponds	445
♦ Radiation doses from consumption of fish and deer	448
♦ Mercury concentrations in fish from the Savannah River, SRS streams/ponds, and offsite lakes	449

Compiled by Jason H. Chappell
Environmental Protection Department

Wildlife Monitoring

1991 HIGHLIGHTS

- ♦ Thirty-five fish were collected on the Savannah River and analyzed for Cs-137. The maximum concentration measured in fish downriver from SRS was 0.25 pCi/g.
- ♦ For SRS deer and hogs, the laboratory analysis of muscle samples collected from 124 animals indicated that the maximum concentration of Cs-137 in deer muscle was 13.7 pCi/g, compared to the field maximum in a different deer of 21 pCi/g.
- ♦ The consumption of fish comprised 71 percent of the total maximum committed effective dose equivalent from liquid releases, with the majority of this dose (70 percent) attributed to Cs-137 in fish.
- ♦ University of Tennessee scientists analyzed 53 deer thyroids from SRS deer for I-129 content in 1991. Ninety percent of the animals contained thyroid I-129 concentrations of less than 50 pCi/g. The I-129 concentration in half the animal thyroids was less than 1.5 pCi/g.
- ♦ Bone samples from eight deer and five hogs were analyzed for concentrations of total strontium. Concentrations ranged from 2.03 pCi/g in a hog to 12.4 pCi/g in a deer.
- ♦ SRS, in coordination with GDNr and SCDHEC, began development of a new fish monitoring program for the Savannah River.

INTRODUCTION

The protected boundary of the Savannah River Site (SRS) provides refuge for an abundance of wildlife. One objective of the site's environmental monitoring program is to assess the potential radiation dose to humans from consumption of radionuclides in game animals harvested onsite in controlled public hunts and offsite from animals that migrate from SRS and are killed by hunters. Fulfilling this objective requires collecting and analyzing representative samples of wildlife on and in the vicinity of the site.

RADIOLOGICAL MONITORING

Fish and Seafood

Description of Monitoring Program

Savannah River fish are collected upriver from, adjacent to, and downriver from SRS throughout the year. Downriver sampling includes shellfish taken from the river mouth (river miles 0-8). Samples also are collected in site streams and ponds (Chapter 8, "Water Pathways").

Fish caught in Thurmond Lake are used as control samples because the lake is located upriver from SRS.

Whole blended fish samples are analyzed for gross alpha-, nonvolatile beta-, and gamma-emitting radionuclides (Chapter 4, "Sample Collection, Analytical Procedures, and Data Interpretation").

Seafood (crabs and oysters) is collected annually from the mouth of the Savannah River near Savannah, Ga. In 1991, seafood was analyzed for gamma-emitting radionuclides. To analyze these samples, the site's Environmental Monitoring Section (EMS) composites the flesh of crabs collected during each sampling event into one sample; oyster meat is also composited for analysis. Fish sampling locations are shown in Figure 9-1.

Monitoring Results

Chart 9-1 presents the maximum gross alpha, nonvolatile beta, and Cs-137 activity measured in fish caught in the Savannah River, onsite streams and ponds, and Thurmond Lake, and in seafood caught near the Savannah River's mouth.

Monitoring data for fish caught in the Savannah River, SRS streams and ponds, and Thurmond Lake—the control location—are presented in Table 9-1. For comparison, concentrations of Cs-137 measured in fish during previous years are presented in Table 9-2.

In the following monitoring-results discussion, uncertainty values are provided because most measurements are at or near the lower limits of detection (Tables 4-2 and 4-6).

Savannah River

Seventeen fish from the Savannah River were analyzed for gross alpha and nonvolatile beta to screen for radioactivity.

Gross alpha activities ranged from -0.46 ± 0.32 pCi/g to 2.71 ± 0.84 pCi/g. The maximum gross alpha activity was detected in a catfish caught upriver from the site. Nonvolatile beta activities ranged from 1.35 ± 0.98 pCi/g to 19 ± 1.9 pCi/g. The maximum nonvolatile beta activity was detected in a bream caught upriver from the site. In fish from Thurmond Lake, the maximum gross alpha (-0.21 ± 0.21) and nonvolatile beta (1.01 ± 0.85) activities were detected in a bass.

In 1991, fish from the Savannah River and Thurmond Lake were analyzed for gamma-emitting radionuclides. (Figure 9-1 shows fish sample locations on the Savannah River.) Cs-137 was the only man-made, gamma-emitting radionuclide detected. Both the high and low concentrations for Cs-137 in river fish were found in bream taken near Shell Bluff (River 2 location). The concentrations ranged from 0.034 ± 0.014

Figure 9-1 SRS collects fish along the Savannah River above the site, adjacent to the site, and at the river mouth.

Chart 9-1
Radioactivity In Fish and Seafood

<u>Location</u>	<u>Maximum concentration (pCi/g)^a</u>		
	<u>Alpha</u>	<u>Nonvolatile Beta</u>	<u>Cs-137</u>
Savannah River	2.71 ± 0.84 (17)	19 ± 1.9 (17)	1.72 ± 0.10 (35) ^b
Savannah River mouth	na	na	nd
Onsite	3.08 ± 1.66 (106)	2.62 ± 12 (106)	155 ± 6 (235) ^c
Thurmond Lake	nd	1.01 ± 0.85 (1)	nd

a The numbers in parentheses indicate the number of samples analyzed. The ± expresses the analytical uncertainty of the measured concentration.

b Detected in a bream from the River 2 location.

c Detected in a bass from Pond B.

na Not analyzed.

nd Below detection limit.

pCi/g to 1.72 ± 0.10 pCi/g. Cs-137 levels in fish from Thurmond Lake were below detection limits.

Crabs and oysters caught at the mouth of the Savannah River were analyzed for gamma-emitting radionuclides. Cs-137 was below detection limits in both the crab and oyster composite samples. Because the samples were misplaced during preparation, alpha and beta analyses were not completed.

Onsite Surface Waters

Gross alpha and nonvolatile beta analyses were performed on fish caught in SRS streams and ponds. Gross alpha activities ranged from -0.45 ± 0.30 pCi/g to a maximum of 3.08 ± 1.66 pCi/g. The maximum gross alpha activity was detected in a sucker from Par Pond. Nonvolatile beta activities ranged from 0.05 ± 0.80 pCi/g to 262 ± 12 pCi/g, with the maximum detected in a bass from Pond B.

Cs-137 was the only man-made, gamma-emitting radionuclide detected in fish from onsite streams and ponds. The maximum Cs-137 concentration in a fish from an SRS stream was 8.63 ± 0.30 pCi/g, measured in a catfish from Four Mile Creek. This stream receives effluents from processes in F and H areas.

The highest Cs-137 concentration in fish caught in SRS ponds was 155 ± 6 pCi/g, detected in a bass from Pond B. The average Cs-137 concentration in fish from Pond B was 63.4 pCi/g. Fish from Pond B probably contain higher concentrations of Cs-137 than fish from other onsite locations because effluents released from R

Reactor were discharged through this body of water to Par Pond. R Reactor was operated from the late 1950s until permanent shutdown in 1964. During this period, R Area released approximately 170 Ci of Cs-137. The concentrations measured in 1991 were similar to those measured since 1979 (Table 9-2). The current source of Cs-137 probably is sediment in the pond.

Concentrations of Cs-137 in fish from site streams and ponds generally decreased between 1971 and 1979. Since 1979, concentrations of Cs-137 in fish from site streams and ponds have remained fairly constant (Table 9-2).

Ongoing Changes in the Fish Sampling Program

In October 1990, the Georgia Department of Natural Resources (GDNR) identified higher concentrations of radionuclides in Savannah River fish caught near the mouth of Four Mile Creek than previously reported by SRS. In July 1991, GDNR, the South Carolina Department of Health and Environmental Control (SCDHEC), the Environmental Protection Agency (EPA), the U.S. Department of Energy (DOE), and personnel from SRS began a series of meetings to determine the cause of the inconsistencies between SRS and GDNR data and to agree on appropriate follow-up activities. After several meetings in 1991, the consortium (SRS, GDNR, SCDHEC, DOE, and EPA) began formulating a new Sampling and Analysis Plan for the SRS fish monitoring program. This process is scheduled to continue into 1992.

The South Carolina Wildlife and Marine Resources Department repopulates areas in the state with turkeys caught at SRS.

Deer and Hogs

Description of Monitoring Program

Annual hunts are conducted at SRS to control the site's deer and hog populations and to reduce animal-vehicle accidents. Before any animal is released to a hunter, EMS performs field analysis for Cs-137 on the deer and hogs at the hunt site using a portable field detector. Samples of thyroid and muscle are removed from 10 percent of the animals and analyzed for I-129 and Cs-137. The 1991 hunts yielded 1,092 deer and 126 hogs, compared to 1,071 deer and 132 hogs in 1990.

During the 1991 hunts, bone samples were collected from eight deer and five hogs for total-strontium analyses. No samples were analyzed for tritium in 1991.

Measured concentrations of Cs-137 in deer from SRS are compared to those in deer from an 18,000-acre controlled hunting camp located on the South Carolina Coastal Plain (SCCP). The SCCP is approximately 65 miles southeast of SRS in Beaufort County.

Monitoring Results

Gamma-Emitting Radionuclides

In deer, the 1991 maximum Cs-137 field measurement in muscle tissue was 21 pCi/g, and the average measurement was 1.4 pCi/g. For hogs, the concentration ranged from 1.0 to 6.5 pCi/g.

Muscle samples were collected from 124 deer and hogs in 1991 for Cs-137 analysis. These samples were analyzed in the laboratory to verify field measurements and determine the presence of other gamma-emitting radionuclides. Gamma analysis of the laboratory samples detected only Cs-137 and normal levels of naturally occurring K-40.

Table 9-3 compares field and laboratory Cs-137 measurements in deer and hogs. Laboratory measurements of Cs-137 in the muscle samples ranged from 0.1 pCi/g to 13.7 pCi/g. The 1991 maximum concentration was lower than the 1990 maximum concentration of 24.1 pCi/g. The 1991 average concentration of Cs-137 in deer, as measured in the laboratory, was 3.3 pCi/g, compared to 8.1 pCi/g in 1990.

Historical comparisons of Cs-137 concentrations in SRS and SCCP deer since 1968 have shown year-to-year variations in both maximum and average

concentrations (Figure 9-2). A complete summary of the information appears in Table 9-4.

These comparisons indicate that the majority of deer collected from SRS contain Cs-137 concentrations that are typical of the surrounding areas. Higher concentrations in a few individual deer, however, do reflect uptake of Cs-137 from SRS areas, probably from streams or ponds that receive Cs-137 from liquid effluents.

The sandy soils of the lower coastal plain of the southeastern United States are low in clay content, organic matter, and available potassium. Nutrients are efficiently taken up from soil and retained in the vegetation. Consequently, concentrations of Cs-137 from worldwide fallout are relatively high in plants and animals from this area.

Deer from the lower coastal plain contain Cs-137 concentrations 10 to 100 times higher than other regions of the continental United States (Whicker, 1983). These relatively high concentrations make the process of separating SRS contributions from that of fallout more difficult.

Strontium

In 1991, bone samples from eight deer and five hogs were analyzed for total strontium. Higher concentrations of strontium occur in bone than in muscle, due to the chemical similarity between strontium and calcium. For bone samples analyzed in 1991, total stron-

tium ranged from 2.03 to 4.90 pCi/g in hogs and 5.47 to 12.4 pCi/g in deer. Complete results for the strontium analyses are presented in Table 9-5.

Analyses by University of Tennessee

Muscle and thyroid samples were collected from 53 deer from SRS and sent to the Department of Physiology and Biophysics, University of Tennessee, Memphis, for analysis. Muscle samples were analyzed for Cs-137; thyroids, for I-129 and Cs-137.

The University of Tennessee reported concentrations of Cs-137 in 28 of the 53 muscle samples. The results reported for Cs-137 in muscle ranged from 0.18 pCi/g to 9.6 pCi/g.

Concentrations of Cs-137 in the 53 thyroids analyzed ranged from 0.08 pCi/g to 6.6 pCi/g. Concentrations of I-129 ranged from less than 1 pCi/g to 925 pCi/g, with an average of 49 pCi/g. Ninety percent of the animals contained I-129 concentrations in the thyroid that were less than 50 pCi/g, and half the animal thyroids contained less than 1.5 pCi/g. The maximum I-129 concentration was measured in a female deer collected from a deer-vehicle accident on Road C near F Area. The Cs-137 concentrations in the thyroid and muscle of this deer were 2.7 pCi/g and 3 pCi/g, respectively.

Results reported by the University of Tennessee are presented in Table 9-6.

Figure 9-2 SRS has compared Cs-137 in deer from the SCCP hunting camp since 1968.

Turtles

Description of Monitoring Program

Although no turtles were trapped in 1991 as part of the normal monitoring program, The Savannah River Ecology Laboratory (SREL) trapped 818 turtles onsite and offsite as part of other research projects. Of these, 672 were pondsliders and eastern mud turtles from El-lenton Bay, Par Pond, and Rainbow Bay.

The turtles were monitored for gross beta-gamma with a portable Geiger-Mueller instrument. None of the turtles trapped during 1991 had radioactivity levels above background readings of 150 counts per minute.

Turkeys

Description of Monitoring Program

Wild turkeys are trapped live onsite by the South Carolina Wildlife and Marine Resources Department and used to repopulate South Carolina game areas. All turkeys are monitored with a portable NaI(Tl) detector before leaving SRS. EMS monitored 34 turkeys in 1991. The maximum concentration of Cs-137 was 4 pCi/g.

DOSES TO THE PUBLIC FROM WILDLIFE CONSUMPTION

DOE specifies radiation dose limits for individual members of the public in DOE Order 5400.5, "Radiation Protection of the Public and Environment." A limit of 100 mrem effective dose equivalent (EDE) per year, which applies to all members of the public, includes doses a person receives from DOE operations through all exposure pathways. Pathways that relate to wildlife monitoring include the consumption of fish and seafood, primarily from the Savannah River, and consumption of deer and hogs obtained on SRS property.

Fish Consumption

The maximum dose from liquid releases to a hypothetical individual living downstream from SRS, 0.34 mrem, was calculated in part by factoring in fish consumption. To calculate this factor, SRS used an average Cs-137 concentration measured in fish caught adjacent to the site. In previous years, concentrations at or below the instrument detection limit were set to zero in the average calculation. Recognizing this as faulty practice, the 1991 dose of 0.34 mrem was calculated using the more conservative detection limits in the average.

SRS Deer Hunts

Controlled Public Hunts Help Manage Deer/Hog Population

- ◆ For approximately six weeks each year, annual controlled deer hunts are conducted over the 300-square-mile Savannah River Site. These hunts help control the deer population and reduce animal-vehicle accidents. Fourteen hunts were conducted in 1991.
- ◆ The hunts normally are conducted on Wednesday and Saturday of each week, beginning in November and lasting until mid-December. Members of the public who wish to participate in the hunts submit applications to the Westinghouse Savannah River Company (WSRC) Security Department Deer Hunt Office. A random drawing determines the hunt participants. Each hunt may consist of 100 to 300 hunters, depending on the size of the hunting area.
- ◆ SRS is divided into 50 hunting areas called compartments. Different compartments are hunted each day. A typical hunt day begins at 4 a.m. and lasts until about 8 p.m. Before a hunter is allowed to leave the meeting point, he or she must receive an identification badge and a safety orientation. The hunters are transported to a hunting compartment and positioned at a specific location, where they hunt until noon.
- ◆ The hunters then are taken to a second compartment to hunt for the remainder of the day (around 5 p.m.). The deer are gathered after each hunt, analyzed for Cs-137 with a portable detector, then distributed to the hunters.

For comparison, had the practice of including zeros in the average continued in 1991, the dose estimate for the maximally exposed downstream individual would have been calculated at 0.22 mrem, an increase of 29 percent over 1990's 0.17 mrem. Because fish consumption is a smaller percentage of the population dose than it is of the maximally exposed downstream individual dose, the 1991 estimate of 3.23 person-rem would have been calculated at 2.81 person-rem, an increase of 20 percent over 1990's 2.35 person-rem.

In 1991, the maximum individual dose from the consumption of fish was 0.24 mrem. This comprised 71.3

percent of the total maximum committed EDE from liquid releases. The majority of this dose (90 percent) is attributed to Cs-137. The maximum EDE from liquid releases includes a source term for fish consumption. Average Cs-137 concentrations used for calculating maximum doses from fish consumption are measured in edible fish collected adjacent to SRS (River 8); other radionuclide concentrations are calculated. Average Cs-137 concentrations were used in the dose calculation, rather than the maximum measured Cs-137 concentration because the average is more typical of intake over an entire year. The weighted average Cs-137 concentration in fish from the River 8 location in 1991 is 0.24 pCi/g. The 50-year committed EDE to a maximally exposed individual is based on a maximum consumption rate of 19 kg (42 lbs) of fish per year [Hamby, 1991]. In 1991, this estimated EDE is 0.24 mrem. Some fraction of this estimated dose is due to Cs-137 present from worldwide fallout; however, that amount is difficult to determine and is not subtracted from the total.

Since a higher committed EDE would result from eating fish caught in SRS streams and ponds than would result from eating river fish, access to SRS streams and ponds is restricted. Therefore, the EDE does not include fish caught within the SRS boundary.

Deer and Hog Consumption

It is important to measure Cs-137 in animals because of the prevalence of cesium from worldwide fallout and SRS operations. The animal with the highest field Cs-137 concentration, 21 pCi/g, had approximately 14.6 kg of edible meat. There was no confirmatory lab measurement of Cs-137 in this deer; therefore, it is not included in Table 9-3. An adult consuming all this meat would receive a committed EDE of 15.3 mrem, or 15 percent of the DOE annual dose limit. The previous special-survey data and routine monitoring results (1990 SRS Annual Environmental Report) suggest that the majority of this concentration, and therefore the dose received, can be attributed to worldwide fallout.

The committed EDE to an individual who consumed one 8-oz steak of deer meat with 21 pCi/g of Cs-137 would be 0.24 mrem. The dose from consuming food with concentrations of radionuclides is directly proportional to the amount of food consumed. For instance, if the same person were to eat one 8-oz steak that contained a concentration of 21 pCi/g Cs-137 every day for one year, he/she would receive a committed EDE of 87.6 mrem. This dose is 87 percent of the DOE annual dose limit and 23 percent of the average Central Savannah River Area (CSRA) resident's average annual dose from naturally occurring radioactivity (380 mrem).

DOSES TO NATIVE AQUATIC ANIMAL ORGANISMS

DOE Order 5400.5 also establishes an interim dose limit for protection of native aquatic animal organisms. The absorbed dose limit to these organisms is one rad per day from exposure to radioactive material in liquid effluents released to natural waterways.

SRS calculated doses to aquatic biota in all onsite streams for 1991 with the LADTAP computer program (Chapter 6, "Calculating Radiation Doses," contains a discussion of dose calculation models). Doses to these organisms are presented in Table 9-7. As shown in the table, all doses were below the 1-rad-per-day interim limit. They ranged from 2E-6 to 2.6E-2 rads per day.

NONRADIOLOGICAL MONITORING

Fish

Description of Monitoring Program

EMS analyzes the flesh of fish caught from onsite streams and ponds, the Savannah River, and Thurmond Lake to determine concentrations of mercury in the fish. The fish analyzed represent the most common edible species of fish in the CSRA. Fish collected from Thurmond Lake are used as control samples.

Applicable Standards

Other than occupational exposure, the greatest source of mercury intake in people is consumption of food, particularly fish. The Food and Drug Administration (FDA) has established an action limit of 1.0 µg Hg/g [FDA, 1990]. Action limits are established to reflect maximum allowable concentrations allowed in fish destined for interstate commerce. SRS uses the FDA guideline, which has been adopted by SCDHEC, to gauge concentrations of mercury in fish from onsite streams.

Discussion

Mercury in the environment can come from natural sources, such as volcanoes and venting of the earth's crust, and man-made sources, including fungicides, the manufacture of chlorine and sodium hydroxide, the production of plastics and electrical apparatus, and fossil fuel combustion by-products.

An important source in the SRS region may be in releases upriver from the site. Much of the mercury detected in fish from SRS has been attributed to offsite sources, such as Savannah River water (Davis et al., 1989). In the past, contamination reached levels that were high enough to warrant restriction of the consumption of Savannah River fish.

Chart 9-2
Mercury in Fish

Location	In Flesh ($\mu\text{g Hg/g}$) ^a	
	Maximum	Average
Savannah River		
Upriver (R-2)	1.28	0.34
Adjacent (R-8)	1.61	0.48
Downriver (R-10)	2.06	0.23
SRS		
Par Pond	1.63	0.62
Pond B	1.99	0.72
Lower Three Runs Creek	1.69	0.98
Steel Creek	2.26	0.88
Pen Branch	0.76	0.35
Beaver Dam Creek	0.45	0.14
Upper Three Runs (Rd A)	0.48	0.38
Upper Three Runs (Hwy 278)	1.01	0.33
Four Mile Creek	1.13	0.65
Thurmond Lake	1.51	0.83

a The Food and Drug Administration (FDA) has established a guideline of $1.0 \mu\text{g Hg/g}$, which is the action limit for food fish destined for interstate commerce.

Savannah River water is used as cooling water in SRS facilities and subsequently pumped into site streams and lakes. Increased levels of mercury in onsite fish have been detected since 1989.

In late 1991, a new research study was initiated by SREL to determine whether mercury levels in fish from SRS waters are higher than offsite levels, and whether levels are increasing with time. In addition to the SREL research, EMS of the Environmental Protection Department (EPD), is implementing a more aggressive monitoring program for the detection

of mercury in fish. The number of fish samples will be increased from the 181 analyzed in 1991 to approximately 300 in 1992.

Monitoring Results

In 1991, a total of 181 fish from SRS streams and ponds, the Savannah River, and offsite lakes was collected and analyzed for mercury. Chart 9-2 summarizes maximum and average concentrations of mercury in fish from all locations sampled. A complete summary of the data is presented in Table 9-8.

Table 9-1
Radioactivity in Fish and Seafood

Location	Species	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Gross Alpha in whole fish (pCi/g)					
Savannah River					
River above Site (R-2, RM-160)	Bream	10	5.95 $\pm$ 5.21 E-01	-3.31 $\pm$ 2.64 E-01	-0.27 $\pm$ 2.73 E-01
	Catfish	4	2.71 $\pm$ 0.84 E+00	-4.62 $\pm$ 3.19 E-01	0.56 $\pm$ 1.45 E+00
	Crappie	3	2.93 $\pm$ 5.29 E-01	-2.02 $\pm$ 2.51 E-01	0.26 $\pm$ 2.50 E-01
Control					
Thurmond Lake	Bass	1	-2.14 $\pm$ 2.10 E-01	-2.14 $\pm$ 2.10 E-01	-2.14 $\pm$ 2.10 E-01
Ponds					
Par Pond	Bass	5	7.57 $\pm$ 7.58 E-01	-3.06 $\pm$ 2.59 E-01	1.11 $\pm$ 5.13 E-01
	Bream	9	5.66 $\pm$ 6.12 E-01	-0.12 $\pm$ 3.36 E-01	1.10 $\pm$ 2.00 E-01
	Crappie	7	8.42 $\pm$ 6.53 E-01	-0.52 $\pm$ 4.68 E-01	2.88 $\pm$ 3.51 E-01
	Sucker	4	3.08 $\pm$ 1.66 E+00	-0.08 $\pm$ 5.10 E-01	0.77 $\pm$ 1.54 E+00
Pond B	Bass	14	1.51 $\pm$ 0.86 E+00	-0.59 $\pm$ 4.49 E-01	4.51 $\pm$ 4.93 E-01
	Bream	6	2.09 $\pm$ 0.87 E+00	-3.61 $\pm$ 4.85 E-01	4.71 $\pm$ 9.05 E-01
	Catfish	1	-2.97 $\pm$ 3.74 E-01	-2.97 $\pm$ 3.74 E-01	-2.97 $\pm$ 3.74 E-01
Streams					
Steel Creek	Bass	9	2.74 $\pm$ 5.14 E-01	-4.23 $\pm$ 2.76 E-01	-1.38 $\pm$ 2.40 E-01
	Bream	7	3.20 $\pm$ 6.33 E-01	-4.45 $\pm$ 3.04 E-01	-1.28 $\pm$ 2.98 E-01
	Catfish	7	8.19 $\pm$ 6.06 E-01	-3.42 $\pm$ 2.95 E-01	-0.35 $\pm$ 3.96 E-01
	Crappie	4	0.24 $\pm$ 5.46 E-01	-2.87 $\pm$ 3.56 E-01	-0.74 $\pm$ 1.44 E-01
Upper Three Runs	Catfish	5	5.62 $\pm$ 4.91 E-01	-0.08 $\pm$ 5.60 E-01	1.11 $\pm$ 2.52 E-01
	Crappie	1	-0.04 $\pm$ 4.20 E-01	-0.04 $\pm$ 4.20 E-01	-0.04 $\pm$ 4.20 E-01
	Sucker	3	-0.01 $\pm$ 3.25 E-01	-3.02 $\pm$ 2.62 E-01	-1.02 $\pm$ 1.73 E-01
Four Mile Creek	Bass	3	1.32 $\pm$ 3.70 E-01	-3.44 $\pm$ 2.58 E-01	-0.87 $\pm$ 2.40 E-01
	Bream	1	-2.38 $\pm$ 2.07 E-01	-2.38 $\pm$ 2.07 E-01	-2.38 $\pm$ 2.07 E-01
	Catfish	2	7.53 $\pm$ 5.14 E-01	-0.65 $\pm$ 2.69 E-01	3.44 $\pm$ 5.78 E-01
Lower Three Runs	Bass	12	2.63 $\pm$ 4.67 E-01	-3.02 $\pm$ 2.54 E-01	-0.05 $\pm$ 1.92 E-01
	Bream	4	-0.05 $\pm$ 3.76 E-01	-2.39 $\pm$ 2.28 E-01	-0.65 $\pm$ 1.16 E-01
	Catfish	1	2.09 $\pm$ 3.62 E-01	2.09 $\pm$ 3.62 E-01	2.09 $\pm$ 3.62 E-01
	Crappie	1	-2.53 $\pm$ 2.17 E-01	-2.53 $\pm$ 2.17 E-01	-2.53 $\pm$ 2.17 E-01

Table 9-1
Radioactivity in Fish and Seafood, Cont'd.

Location	Species	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Nonvolatile Beta in whole fish (pCi/g)					
Savannah River					
River above Site (R-2, RM-160)	Bream	10	1.90 $\pm$ 0.19 E+01	1.35 $\pm$ 0.98 E+00	4.58 $\pm$ 5.20 E+00
	Catfish	4	7.33 $\pm$ 1.21 E+00	2.37 $\pm$ 0.94 E+00	3.64 $\pm$ 2.46 E+00
	Crappie	3	8.72 $\pm$ 1.54 E+00	2.59 $\pm$ 0.83 E+00	6.40 $\pm$ 3.32 E+00
Control					
Thurmond Lake	Bass	1	1.01 $\pm$ 0.85 E+00	1.01 $\pm$ 0.85 E+00	1.01 $\pm$ 0.85 E+00
Ponds					
Par Pond	Bass	5	1.30 $\pm$ 0.04 E+02	9.83 $\pm$ 0.91 E+00	3.57 $\pm$ 5.30 E+01
	Bream	9	1.80 $\pm$ 0.19 E+01	0.12 $\pm$ 1.08 E+00	5.94 $\pm$ 4.89 E+00
	Crappie	7	1.49 $\pm$ 0.18 E+01	6.49 $\pm$ 0.86 E+00	1.03 $\pm$ 0.34 E+01
	Sucker	4	2.87 $\pm$ 0.36 E+01	0.10 $\pm$ 1.01 E+00	1.05 $\pm$ 1.36 E+01
Pond B	Bass	14	2.62 $\pm$ 0.12 E+02	0.35 $\pm$ 1.22 E+01	1.18 $\pm$ 0.69 E+02
	Bream	6	1.01 $\pm$ 0.04 E+02	1.07 $\pm$ 0.14 E+01	6.15 $\pm$ 3.14 E+01
	Crappie	1	7.57 $\pm$ 0.29 E+01	7.57 $\pm$ 0.29 E+01	7.57 $\pm$ 0.29 E+01
Streams					
Steel Creek	Bass	9	1.14 $\pm$ 0.17 E+01	0.18 $\pm$ 1.29 E+00	7.66 $\pm$ 3.39 E+00
	Bream	7	1.56 $\pm$ 0.19 E+01	4.62 $\pm$ 1.11 E+00	8.01 $\pm$ 3.86 E+00
	Catfish	7	1.26 $\pm$ 0.24 E+01	0.01 $\pm$ 1.40 E+00	8.22 $\pm$ 4.38 E+00
	Crappie	4	4.96 $\pm$ 0.25 E+01	6.23 $\pm$ 1.39 E+00	2.14 $\pm$ 1.98 E+01
Upper Three Runs	Catfish	5	4.20 $\pm$ 1.09 E+00	0.50 $\pm$ 8.05 E-01	0.90 $\pm$ 1.85 E+00
	Crappie	1	0.84 $\pm$ 9.50 E-01	0.84 $\pm$ 9.50 E-01	0.84 $\pm$ 9.50 E-01
	Sucker	3	1.17 $\pm$ 0.17 E+01	0.81 $\pm$ 9.15 E-01	5.16 $\pm$ 5.93 E+00
Four Mile Creek	Bass	3	2.66 $\pm$ 0.19 E+01	1.67 $\pm$ 0.16 E+01	2.28 $\pm$ 0.53 E+01
	Bream	1	8.32 $\pm$ 1.23 E+00	8.32 $\pm$ 1.23 E+00	8.32 $\pm$ 1.23 E+00
	Catfish	2	3.00 $\pm$ 0.20 E+01	2.26 $\pm$ 0.17 E+01	2.63 $\pm$ 0.53 E+01
Lower Three Runs	Bass	12	1.22 $\pm$ 0.61 E+01	0.00 $\pm$ 1.37 E+00	5.07 $\pm$ 4.19 E+00
	Bream	4	5.55 $\pm$ 1.10 E+00	3.08 $\pm$ 9.80 E+00	4.33 $\pm$ 1.01 E+00
	Catfish	1	4.00 $\pm$ 1.02 E+00	4.00 $\pm$ 1.02 E+00	4.00 $\pm$ 1.02 E+00
	Crappie	1	9.56 $\pm$ 1.29 E+00	9.56 $\pm$ 1.29 E+00	9.56 $\pm$ 1.29 E+00

Table 9-1
Radioactivity in Fish and Seafood, Cont'd.

Location	Species	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Cs-137 In whole fish (pCi/g)					
Savannah River					
River above Site (R-2, RM-160)	Bream	13 / 7 ^a	1.72 $\pm$ 0.10 E+00	3.38 $\pm$ 1.37 E-02	4.62 $\pm$ 5.78 E-01
	Catfish	5 / 1	9.29 $\pm$ 1.91 E-02	9.29 $\pm$ 1.91 E-02	9.29 $\pm$ 1.91 E-02
	Crappie	4 / 2	1.07 $\pm$ 0.21 E-01	6.36 $\pm$ 1.52 E-02	8.51 $\pm$ 3.03 E-02
River adjacent to Site (R-8, RM-140)	Bass	1 / 1	3.37 $\pm$ 0.35 E-01	3.37 $\pm$ 0.35 E-01	3.37 $\pm$ 0.35 E-01
	Bream	21 / 10	1.05 $\pm$ 0.07 E+00	9.29 $\pm$ 1.90 E-02	4.09 $\pm$ 3.23 E-01
	Catfish	12 / 5	2.12 $\pm$ 0.34 E-01	4.33 $\pm$ 1.67 E-02	9.02 $\pm$ 6.92 E-02
	Crappie	6 / 6	1.10 $\pm$ 0.09 E+00	1.49 $\pm$ 0.28 E-01	4.89 $\pm$ 3.96 E-01
	Yellow Perch	1 / 1	2.07 $\pm$ 0.25 E-01	2.07 $\pm$ 0.25 E-01	2.07 $\pm$ 0.25 E-01
River below Site (R-10, RM-120)	Bream	8 / 2	2.49 $\pm$ 0.29 E-01	1.68 $\pm$ 0.33 E-01	2.09 $\pm$ 0.57 E-01
Ponds					
Par Pond	Bass	23 / 23	1.29 $\pm$ 0.05 E+01	1.33 $\pm$ 0.23 E-01	4.65 $\pm$ 2.61 E+00
	Bream	28 / 28	5.52 $\pm$ 0.21 E+00	6.11 $\pm$ 0.54 E-01	2.34 $\pm$ 0.95 E+00
	Chain Pickerel	10 / 10	9.22 $\pm$ 0.35 E+00	2.04 $\pm$ 0.07 E+00	5.70 $\pm$ 2.33 E+00
	Crappie	20 / 20	7.09 $\pm$ 0.25 E+00	2.86 $\pm$ 0.12 E+00	4.82 $\pm$ 1.27 E+00
	Sucker	3 / 3	8.15 $\pm$ 0.29 E+00	2.44 $\pm$ 0.13 E+00	4.62 $\pm$ 3.08 E+00
	Yellow Perch	1 / 1	4.13 $\pm$ 0.19 E+00	4.13 $\pm$ 0.19 E+00	4.13 $\pm$ 0.19 E+00
Pond B	Bass	17 / 17	1.55 $\pm$ 0.06 E+02	6.56 $\pm$ 0.21 E+01	1.04 $\pm$ 0.21 E+02
	Bream	20 / 20	5.17 $\pm$ 0.16 E+01	1.50 $\pm$ 0.05 E+01	3.08 $\pm$ 1.03 E+01
	Catfish	4 / 4	1.13 $\pm$ 0.04 E+02	4.45 $\pm$ 0.14 E+01	7.30 $\pm$ 2.89 E+01
	Crappie	1 / 1	3.26 $\pm$ 0.10 E+01	3.26 $\pm$ 0.10 E+01	3.26 $\pm$ 0.10 E+01
Jack's Lake	Bass	4 / 4	4.87 $\pm$ 0.38 E-01	3.44 $\pm$ 0.33 E-01	3.94 $\pm$ 0.65 E-01
	Bream	4 / 4	3.79 $\pm$ 0.34 E-01	3.09 $\pm$ 0.36 E-01	3.35 $\pm$ 0.39 E-01
	Jackfish	8 / 8	9.56 $\pm$ 0.55 E-01	2.46 $\pm$ 0.22 E-01	5.62 $\pm$ 2.41 E-01

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 9-1
Radioactivity in Fish and Seafood, Cont'd.

Location	Species	No. of Samples	Max $\pm \sigma$	Min $\pm \sigma$	Arithmetic Mean $\pm \sigma$
Cannuck	Bass	2 / 2 ^a	4.35 $\pm$ 0.31 E-01	3.32 $\pm$ 0.38 E-01	3.83 $\pm$ 0.73 E-01
	Bream	11 / 11	2.73 $\pm$ 0.45 E-01	6.51 $\pm$ 1.53 E-02	1.53 $\pm$ 0.74 E-01
	Crappie	2 / 2	1.60 $\pm$ 0.29 E-01	1.46 $\pm$ 0.31 E-01	1.53 $\pm$ 0.09 E-01
Streams					
Steel Creek	Bass	15 / 13	3.51 $\pm$ 0.16 E+00	4.08 $\pm$ 0.33 E-01	2.34 $\pm$ 0.85 E+00
	Bream	10 / 9	5.54 $\pm$ 0.49 E-01	1.30 $\pm$ 0.18 E-01	2.81 $\pm$ 1.47 E-01
	Catfish	10 / 10	3.23 $\pm$ 0.13 E+00	3.73 $\pm$ 0.37 E-01	1.28 $\pm$ 0.84 E+00
	Crappie	5 / 5	4.67 $\pm$ 0.18 E+00	1.81 $\pm$ 0.33 E-01	1.77 $\pm$ 1.71 E+00
	Sucker	1 / 1	7.28 $\pm$ 0.69 E-01	7.28 $\pm$ 0.69 E-01	7.28 $\pm$ 0.69 E-01
Upper Three Runs	Bream	3 / 1	2.40 $\pm$ 0.38 E-01	2.40 $\pm$ 0.38 E-01	2.40 $\pm$ 0.38 E-01
	Catfish	6 / 6	1.29 $\pm$ 0.13 E+00	2.41 $\pm$ 0.27 E-01	4.86 $\pm$ 4.01 E-01
	Crappie	1 / 1	7.92 $\pm$ 0.82 E-01	7.92 $\pm$ 0.82 E-01	7.92 $\pm$ 0.82 E-01
	Jackfish	1 / 1	3.06 $\pm$ 0.33 E-01	3.06 $\pm$ 0.33 E-01	3.06 $\pm$ 0.33 E-01
	Sucker	5 / 3	2.64 $\pm$ 0.37 E-01	3.26 $\pm$ 1.09 E-02	1.46 $\pm$ 1.16 E-01
Four Mile Creek	Bass	2 / 2	3.86 $\pm$ 0.15 E+00	1.97 $\pm$ 0.10 E+00	2.91 $\pm$ 1.34 E+00
	Bream	4 / 4	3.01 $\pm$ 0.17 E+00	3.10 $\pm$ 0.53 E-01	1.17 $\pm$ 1.25 E+00
	Catfish	3 / 3	8.63 $\pm$ 0.30 E+00	3.90 $\pm$ 0.19 E+00	6.18 $\pm$ 2.37 E+00
	Sucker	2 / 2	1.09 $\pm$ 0.20 E-01	1.02 $\pm$ 0.20 E-01	1.05 $\pm$ 0.05 E-01
Lower Three Runs	Bass	15 / 15	7.88 $\pm$ 0.28 E+00	5.57 $\pm$ 0.33 E-01	4.91 $\pm$ 1.98 E+00
	Bream	17 / 17	6.03 $\pm$ 0.23 E+00	9.00 $\pm$ 5.81 E-01	2.08 $\pm$ 1.30 E+00
	Catfish	1 / 1	2.95 $\pm$ 0.12 E+00	2.95 $\pm$ 0.12 E+00	2.95 $\pm$ 0.12 E+00
	Crappie	3 / 3	3.42 $\pm$ 0.17 E+00	1.56 $\pm$ 0.12 E+00	2.20 $\pm$ 1.06 E+00
Beaver Dam Creek	Bream	9 / 4	6.17 $\pm$ 0.49 E-01	9.89 $\pm$ 2.15 E-02	2.98 $\pm$ 2.23 E-01
	Catfish	2 / 1	1.00 $\pm$ 0.21 E-01	1.00 $\pm$ 0.21 E-01	1.00 $\pm$ 0.21 E-01
	Sucker	2 / 1	9.50 $\pm$ 1.86 E-02	9.50 $\pm$ 1.86 E-02	9.50 $\pm$ 1.86 E-02
Pen Branch	Bass	3 / 3	1.91 $\pm$ 0.27 E-01	1.59 $\pm$ 0.28 E-01	1.76 $\pm$ 0.16 E-01
	Bream	3 / 1	4.85 $\pm$ 0.56 E-01	4.85 $\pm$ 0.56 E-01	4.85 $\pm$ 0.56 E-01
	Crappie	2 / 1	2.28 $\pm$ 0.37 E-01	2.28 $\pm$ 0.37 E-01	2.28 $\pm$ 0.37 E-01

^a The gamma analysis package currently used by Environmental Monitoring does not force an activity determination if a threshold setting is not met. For these reported radionuclides, notably Cs-137, I-131, and K-40, "No. of Samples" is displayed as "number of samples counted / number with activities quantified"; only the number quantified are used in the max, min, and mean generation.

Table 9-2
Summary of Cesium-137 in Fish

Location	Cesium-137 in Whole Fish, Average pCi/g				
	1975 ^a	1979	1980	1981	1982
Steel Creek at Road A	28 (49)	5 (21)	12 (8)	17 (3)	6 (10)
Steel Creek near mouth	1.1 (63)	1.8 (10)	0.6 (22)	0.8 (26)	-
Four Mile Creek at Road 3	32 (31)	9 (7)	10 (5)	15 (8)	-
Four Mile Creek at SC 125	-	-	-	-	-
Four Mile Creek at Cassel's Pond	1.4 (74)	1.1 (12)	0.5 (18)	0.6 (2)	0.4 (49)
Par Pond	15 (74)	1.0 (28)	3 (39)	2.6 (14)	3 (22)
Pond B	180 (70)	83 (16)	69 (47)	80 (22)	73 (14)
Lower Three Runs Creek at Patterson Mill	14 (10)	4.7 (22)	2 (6)	-	-
Savannah River above SRS	0.1 (87)	0.6 (16)	<0.4 (42)	0.2 (65)	0.04 (8)
Savannah River adjacent to SRS	0.2 (55)	0.4 (9)	<0.2 (62)	0.2 (62)	0.6 (32)
Savannah River below SRS	0.2 (90)	0.2 (4)	<0.2 (32)	0.3 (68)	0.6 (57)

Location	Cesium-137 in Whole Fish, Average pCi/g			
	1983	1984	1985	1986
Steel Creek at Road A	9 (6)	7.6 (24)	5.5 (1)	5 (72)
Steel Creek near mouth	-	-	-	-
Four Mile Creek at Road 3	-	-	-	-
Four Mile Creek at SC 125	-	-	-	8.5 (13)
Four Mile Creek at Cassel's Pond	0.4 (25)	2.3 (16)	0.2 (9)	1.1 (16)
Par Pond	9 (46)	3.3 (48)	8.9 (6)	9.9 (36)
Pond B	-	71 (39)	52.5 (7)	37 (21)
Lower Three Runs Creek at Patterson Mill	-	1.2 (9)	0.7 (3)	6.3 (52)
Beaver Dam Creek	-	-	-	-
Pen Branch	-	-	-	-
Upper Three Runs at Road A	-	-	-	-
Savannah River above SRS	0.14 (45)	0.11 (119)	0.01 (29)	0.12 (68)
Savannah River adjacent to SRS	0.18 (65)	0.12 (187)	0.12 (57)	0.37 (32)
Savannah River below SRS	0.08 (63)	0.06 (63)	0.01 (40)	0.38 (50)

Location	Cesium-137 in Whole Fish, Average pCi/g				
	1987	1988	1989	1990	1991 ^b
Steel Creek at Road A	1.5 (54)	0.94 (80)	1.1 (74)	1.5 (55)	1.4 (38)
Four Mile Creek	6.1 (17)	4.4 (20)	6.2 (35)	3.0 (26)	2.66 (11)
Par Pond	2.8 (52)	2.1 (68)	3.9 (57)	3.6 (52)	4.0 (85)
Pond B	86 (24)	74 (35)	86 (52)	73 (48)	63.4 (42)
Lower Three Runs Creek	3.3 (9)	2.9 (68)	2.8 (45)	2.8 (48)	3.30 (36)
Beaver Dam Creek	0.53 (15)	0.29 (39)	0.42 (30)	0.15 (25)	0.23 (6)
Pen Branch	0.36 (14)	0.21 (57)	0.10 (43)	0.19 (26)	0.25 (5)
Upper Three Runs Creek	0.33 (35)	0.29 (56)	0.22 (51)	0.24 (50)	0.39 (12)
Savannah River above SRS	0.17 (44)	0.18 (28)	0.06 (43)	0.11 (36)	0.38 (10)
Savannah River adjacent to SRS	0.40 (59)	0.35 (52)	0.12 (39)	0.10 (16)	0.35 (23)
Savannah River below SRS	0.19 (32)	0.42 (47)	0.19 (46)	0.10 (40)	0.20 (2)
Savannah River below SRS at Savannah, Ga. (RM 0-8)	0.26 (8)	0.23 (67)	0.002 (85)	0.003 (28)	<LLD (2)

a Number in parentheses in columns for years 1975 through 1990 is the number of fish analyzed.

b Number in parentheses in 1991 column is the number of fish with quantifiable activity. For changes in method for calculating Cs-137 levels in fish, refer to the section on fish consumption in this chapter.

- No analyses.

Table 9-3
Comparison of Field and Laboratory Cesium-137 Measurements in Deer and Hogs

Collection Date	Tag Number	Compartment Number	Field Cs-137 (pCi/g)	Lab Cs-137(pCi/g)
10/30/91	11556	8	1	0.1±.01
10/30/91	8504	8	4	6.8±.47
10/30/91	8565	8	1	1.2±.13
10/30/91	8571	42	1	2.0±.18
10/30/91	11558	8	7	11.1±.73
10/30/91	205	9	1	6.4±.45
10/30/91	8584	10	1	5.2±.38
10/30/91	8594	10	1	0.4±.07
10/30/91	11558	8	7	11.7±.77
11/02/91	113	20	1	1.9±.21
11/02/91	213	24	1	2.7±.23
11/02/91	209	24	1	2.6±0.2
11/02/91	8683	20	1	3.2±.26
11/02/91	8686	20	2	3.3±.26
11/02/91	8695	20	1	8.6±.58
11/02/91	11077	44	1	3.1±.26
11/02/91	217	44	1	2.2±.19
11/02/91	8697	36	1	0.9±.13
11/02/91	8855	44	1	0.9±.09
11/02/91	8864	44	1	4.8±.35
11/02/91	8686	20	2	2.4±.21
11/02/91	227	44	1	5.7±.41
11/02/91	8864	44	1	5.0±.37
11/06/91	11575	3	1	2.2±.17
11/06/91	11086	15	1	2.9±.24
11/06/91	11088	15	1	1.2±.13
11/06/91	8866	15	2	4.4±.33
11/06/91	11528	3	1	2.5±.19
11/06/91	11251	7	1	2.7±0.2
11/06/91	11115	6	1	3.6±.32
11/06/91	11533	6	1	6.0±.47

Table 9-3
Comparison of Field and Laboratory Cesium-137 Measurements in Deer and Hogs, Cont'd.

Collection Date	Tag Number	Compartment Number	Field Cs-137 (pCi/g)	Lab Cs-137(pCi/g)
11/06/91	11255	7	1	3.0±.25
11/06/91	11255	7	1	2.9±.24
11/09/91	144	29	1	1.4±.14
11/09/91	143	29	1	1.4±.14
11/09/91	11007	29	1	0.5±.08
11/09/91	11011	43	1	0.3±.06
11/09/91	149	19	4	4.6±.34
11/09/91	11263	48	1	0.6±.07
11/09/91	11015	48	1	0.4±.06
11/09/91	11023	45	1	2.0±.16
11/09/91	144	29	1	1.4±.14
11/09/91	150	48	1	0.8±.09
11/09/91	231	29	1	0.7±0.1
11/09/91	11023	45	1	1.6±.16
11/09/91	150	48	1	2.6±0.2
11/13/91	162	46	1	2.1±.18
11/13/91	11270	49	1	4.4±0.3
11/13/91	11072	46	1	2.8±0.2
11/13/91	11296	46	1	2.5±.21
11/13/91	8880	42	1	3.9±.27
11/13/91	8882	42	1	1.3±.17
11/16/91	11164	13	1	3.1±.25
11/16/91	11033	16	1	3.2±.26
11/16/91	11170	16	1	2.9±.24
11/16/91	11599	13	1	2.9±.21
11/16/91	172	12	1	1.7±.13
11/20/91	546	4	1	3.2±.23
11/20/91	412	5	1	4.3±.29
11/20/91	420	4	1	1.8±0.2
11/20/91	11230	5	2	4.3±.36
11/20/91	423	5	1	2.7±.26

Table 9-3
Comparison of Field and Laboratory Cesium-137 Measurements in Deer and Hogs, Cont'd.

Collection Date	Tag Number	Compartment Number	Field Cs-137 (pCi/g)	Lab Cs-137(pCi/g)
11/20/91	553	27	1	1.2±.13
11/20/91	429	7	1	0.8±0.1
11/20/91	557	7	1	2.4±.18
11/20/91	423	5	1	2.4±.24
11/23/91	483	32	1	2.3±.18
11/23/91	11244	32	1	1.5±.18
11/23/91	440	30	1	2.2±.17
11/23/91	449	30	1	1.2±.13
11/23/91	258	32	1.3	0.9±.13
11/23/91	11502	30	1	1.6±.13
11/23/91	11240	32	1.3	3.1±.25
11/23/91	953	33	1.3	3.1±.25
11/23/91	11508	33	1	1.9±.17
11/23/91	258	32	1.3	1.0±.14
11/30/91	791	15	1	0.9±.09
11/30/91	793	15	1	2.1±.19
12/04/91	563	42	1	4.2±.31
12/04/91	564	42	1	1.3±.14
12/04/91	857	41	1	2.5±.19
12/04/91	989	42	1	1.4±.15
12/04/91	715	9	1	1.4±.14
12/04/91	992	9	1	1.9±.15
12/04/91	994	9	1	2.1±.22
12/04/91	993	9	1	2.3±.24
12/04/91	237	9	1	2.3±0.2
12/04/91	872	8	2	7.9±.59
12/04/91	569	9	1	1.4±.17
12/07/91	278	5	1	3.1±.29
12/07/91	998	18	1	4.5±.37
12/07/91	883	5	2	4.8±.39
12/07/91	896	18	3	7.2±.54

Table 9-3
Comparison of Field and Laboratory Cesium-137 Measurements in Deer and Hogs, Cont'd.

Collection Date	Tag Number	Compartment Number	Field Cs-137 (pCi/g)	Lab Cs-137(pCi/g)
12/07/91	899	5	1	4.6±.38
12/07/91	899	5	1	4.9±0.4
12/07/91	754	26	1	4.5±.37
12/07/91	575	25	6	9.6±.69
12/07/91	753	5	1	8.2±0.6
12/11/91	580	36	1	5.0±.37
12/11/91	584	36	1	5.1±.42
12/11/91	724	44	1	1.0±.11
12/11/91	291	44	1	1.0±0.1
12/11/91	609	36	1	2.2±.21
12/11/91	624	44	1	1.1±.15
12/11/91	586	36	1	4.4±.37
12/11/91	11173	44	1	2.2±.17
12/11/91	725	44	5	7.1±.54
12/11/91	725	44	5	7.6±.52
12/11/91	11171	44	8	8.6±.55
12/11/91	655	36	1	6.4±.46
12/11/91	302	46	1	1.6±.16
12/11/91	627	45	1	3.3±.23
12/11/91	660	48	1	0.6±.08
12/11/91	631	45	1	3.8±.29
12/11/91	672	47	1	2.0±.16
12/11/91	763	36	7	13.7±.89
12/14/91	308	40	1	1.7±.15
12/14/91	307	40	1	1.4±.14
12/14/91	640	37	7	9.3±.67
12/14/91	637	37	1	5.0±.33
12/14/91	636	37	4	6.0±.47
12/14/91	680	20	2	5.6±.44
12/14/91	733	29	1	1.9±0.2
12/14/91	700	29	5	7.1±.53

Table 9-4
Summary of Cesium-137 in Deer

Year	No. of Deer		Average, pCi/g		Maximum, pCi/g	
	SRS ^a	SCCP ^b	SRS ^a	SCCP ^b	SRS ^a	SCCP ^b
1965	198		10		10	
1966	541		6		24	
1967	1,032		9		104 ^c	
1968	669	34	11	23	74 ^d	80
1969	889 ^e	31	15	15	204 ^d	72
1970	864	33	18	20	77 ^d	57
1971	865	42	11	21	48	42
1972	808	72	8	11	38	32
1973	1,158	78	6	16	31	49
1974	1,551	89	5	9	52	23
1975	1,391	42	9	17	36	38
1976	1,357	35	11	16	41	36
1977	1,271	41	10	16	42	25
1978	1,287	36	5	11	65	21
1979	1,079	57	10	12	98	29
1980	961	51	10	9	98	32
1981	1,791	32	8	8	47	18
1982	2,063	28	14	15	73	33
1983	1,597	f	4	f	16	f
1984	1,038	59	6	14	23	16
1985	1,022	30	7 ± 11 ^h	6 ± 4	30	11
1986	944	23	7 ± 8	6 ± 1	29	15
1987	606	5	5 ± 5	9 ± 5	45	15
1988	855	5	10.2 ± 11.0	6.9 ± 6.2	60	11.8
1989	710	22	7.3 ± 8.5	6.8 ± 7.0	25	11.7
1990	1,071	f	5.5 ± 6.6		18	
1991	1,092	9	1.4 ± 2.6	3.8 ± 4.6	21	9.5

a SRS values are field measurements.

b SCCP (South Carolina Coastal Plain) values are laboratory measurements.

c Killed along Four Mile Creek.

d Killed near Steel Creek.

e Approximately 20% of deer monitored before 1969; each deer monitored since 1969.

f Program discontinued by The University of Georgia.

g Samples collected from SCCP deer and counted by SRS.

h The ± value represents the 2 standard deviation.

Table 9-5
Summary of Strontium in Deer and Hog

Date	Clinch Tag	Species	Total Strontium (pCi/g)
11/02/91	8686	Deer	7.35
11/02/91	8864	Deer	5.47
11/06/91	8874	Hog	4.45
11/09/91	11011	Hog	3.98
11/09/91	11023	Deer	7.16
11/20/91	423	Deer	8.40
11/23/91	258	Deer	8.54
10/30/91	11558	Deer	7.98
12/07/91	899	Deer	12.4
11/06/91	11255	Deer	9.62
11/09/91	150	Hog	2.03
11/09/91	231	Hog	3.56
11/09/91	152	Hog	4.90

Table 9-6
Iodine-129 and Cesium-137 in Deer Thyroids and Muscle

Collection Date	Wet Weight, pCi/g		
	I-129 Thyroid ^a	Cs-137 Thyroid ^a	Cs-137 Muscle ^a
1/1/91	0.811	2.838	N/A ^b
1/3/91	1.865	5.811	N/A
1/3/91	3.846	2.486	N/A
1/11/91	0.800	4.433	N/A
1/14/91	0.108	3.784	N/A
1/30/91	0.189	1.406	N/A
1/30/91	0.703	1.433	N/A
2/14/91	2.459	0.595	N/A
2/20/91	25.919	1.00	N/A
3/8/91	0.270	2.027	N/A
3/11/91	2.459	0.649	N/A
3/14/91	0.992	0.460	N/A
3/19/91	0.616	0.487	N/A
3/24/91	0.235	0.405	N/A
3/25/91	0.605	0.075	N/A
4/10/91	0.773	0.351	N/A
4/11/91	0.808	0.243	N/A
4/11/91	1.619	1.216	N/A
4/11/91	3.281	0.243	N/A
4/19/91	0.546	0.405	N/A
4/26/91	0.386	0.135	N/A
5/11/91	475.568	0.081	N/A
5/13/91	2.159	1.460	N/A
7/5/91	1.824	1.811	N/A
8/8/91	0.713	1.559	1.628
8/11/91	5.367	6.569	1.980
8/12/91	2.699	2.461	2.244
8/23/91	925.354	2.656	3.046
9/21/91	3.390	5.017	6.525
9/25/91	0.436	0.361	0.538
10/4/91	1.199	0.297	0.893
10/6/91	1.640	0.195	0.747

a Analyses performed by the Department of Physiology and Biophysics at the University of Tennessee, Memphis.

b "N/A" indicates data is not available.

Table 9-6
Iodine-129 and Cesium-137 in Deer Thyroids and Muscle, Cont'd.

Collection Date	Wet Weight, pCi/g		
	I-129 Thyroid ^a	Cs-137 Thyroid ^a	Cs-137 Muscle ^a
10/7/91	47.162	0.297	0.663
10/7/91	0.553	0.574	1.365
10/7/91	324.954	4.348	9.581
10/11/91	530.802	0.844	1.838
10/13/91	1.465	0.882	2.116
10/14/91	3.081	0.641	1.087
10/14/91	39.305	1.364	2.218
10/22/91	3.746	0.995	4.707
10/24/91	129.137	0.831	1.410
10/30/91	0.499	0.817	2.014
10/30/91	0.391	1.247	2.289
10/30/91	0.138	0.645	N/A ^b
10/30/91	0.237	0.906	2.757
11/2/91	1.863	0.826	1.427
11/2/91	0.362	0.310	0.184
11/2/91	2.171	1.473	2.426
11/2/91	12.211	2.596	2.740
11/8/91	2.972	2.474	8.618
11/8/91	1.285	6.236	8.974
11/8/91	0.053	2.410	2.208
11/8/91	1.489	2.617	3.949

a Analyses performed by the Department of Physiology and Biophysics at the University of Tennessee, Memphis.

b "N/A" indicates data is not available.

Table 9-7
Calculated Doses to Aquatic Biota from SRS Releases

Stream	Location	Flow, cfs	Dose to Biota, mrad/yr ^a		
			Fish	Invertebrate	Algae
Upper Three Runs	Tim's Branch 5 (Road C)	194	2.16E+00	2.34E+00	2.51E+00
Beaver Dam Creek	Below 400-D	80	9.57E-01	1.45E+00	3.21E+00
Four Mile Creek	FM2 (Road 4)	12	2.39E+02	3.40E+02	7.35E+02
Pen Branch	K-011	184	5.26E+00	5.44E+00	6.45E+00
Steel Creek	Steel Creek 2A above Road B	28	3.01E+00	3.42E+00	5.80E+00
Lower Three Runs	LTR1A above Road B	53	5.96E-01	1.12E+00	3.42E+00

Stream	Location	Flow, cfs	Dose to Biota, mrad/yr ^a	
			Raccoon	Duck
Upper Three Runs	Tim's Branch 5 (Road C)	194	7.32E-01	1.21E+01
Beaver Dam Creek	Below 400-D	80	1.36E+00	3.19E+01
Four Mile Creek	FM2 (Road 4)	12	1.64E+03	9.40E+03
Pen Branch	K-011	184	1.39E+00	2.39E+01
Steel Creek	Steel Creek 2A above Road B	28	1.94E+00	4.85E+01
Lower Three Runs	LTR1A above Road B	53	1.62E+00	4.32E+01

^a Calculated with CRITR methodology incorporated in the LADTAP computer program.

Table 9-8
Mercury in Fish

Location	No. of Samples	In Flesh (µg Hg/g)			
		Maximum	Minimum	Arithmetic Mean	± Std Dev
Onsite Locations					
Par Pond					
Bass	8	1.63	.40	.96	± .47
Bream	8	.66	.10	.37	± .22
Crappie	4	1.31	.13	-	-
Catfish	1	.23	-	-	-
Average ^a .62					
Pond B					
Bass	8	1.99	.81	1.20	± .40
Bream	8	.73	.08	.30	± .24
Crappie	2	.63	.23	-	-
Catfish	2	.78	.78	-	-
Average ^a .72					
Lower Three Runs Creek-2					
Bass	5	1.69	1.08	1.29	± .24
Bream	5	.88	.25	.67	± .29
Average ^a .98					
Steel Creek					
Bass	8	1.69	1.13	1.31	± .20
Bream	8	2.26	.13	.68	± .69
Catfish	6	1.48	.33	.58	± .45
Average ^a .88					
Pen Branch					
Bass	3	.55	.28	-	-
Bream	3	.35	.10	-	-
Crappie	1	.45	-	-	-
Catfish	2	.76	<.01	-	-
Average ^a .35					
Beaver Dam Creek					
Bass	2	.45	.43	-	-
Bream	6	.13	<.01	.056	± .048
Catfish	4	.43	<.01	-	-
Average ^a .0.14					

a Average is for all fish sampled at the location.

- Insufficient data; mean not calculated for <5 samples.

Table 9-8
Mercury in Fish, Cont'd.

Location	No. of Samples	In Flesh (µg Hg/g)			
		Maximum	Minimum	Arithmetic Mean	± Std Dev
Onsite Locations, cont'd.					
Upper Three Runs Creek-4					
Bass	2	1.01	.38	-	-
Bream	7	.81	<.01	.31	± .30
Cattfish	8	.66	.08	.37	± .19
Average ^a .38					
Four Mile Creek-6					
Bass	5	1.13	.78	.98	± .13
Bream	4	.53	.05	-	-
Cattfish	2	.73	.43	-	-
Average ^a .65					
Upper Three Runs at U.S. 278					
Bream	2	.48	.15	-	-
Crappie	3	.38	.30	-	-
Average ^a .33					
Offsite Locations					
Thurmond Lake					
Bass	2	1.51	.15	-	-
Average ^a .83					
Savannah River River Mile 160 (Upriver of SRS)					
Bass	1	1.23	-	-	-
Bream	6	.18	<.01	.08	± .058
Crappie	3	.53	.35	-	-
Cattfish	4	1.28	.05	-	-
Average ^a .34					

a Average is for all fish sampled at the location.

- Insufficient data; mean not calculated for <5 samples.

Table 9-8
Mercury in Fish, Cont'd.

Location	No. of Samples	In Flesh (µg Hg/g)				
		Maximum	Minimum	Arithmetic Mean	± Std Dev	
Offsite Locations, cont'd.						
River Mile 140 (Adjacent to SRS)						
Bass	5	1.61	.50	1.11	±	.43
Bream	8	.45	.13	.26	±	.13
Crappie	2	.76	.13	-		-
Catfish	6	.73	<.01	.25	±	.26
Average*.48						
River Mile 120 (Downriver from SRS)						
Bass	1	<.01	-	-		-
Bream	8	2.06	<.01	.34	±	.70
Crappie	3	.35	.18	-		-
Catfish	5	.20	<.01	.07	±	.08
Average*.23						

a Average is for all fish sampled at the location.

- Insufficient data; mean not calculated for <5 samples.

Chapter 10

To Learn About:	Turn to page:
♦ Ground contamination near F-Area laboratory buildings	470
♦ Water and sediment sampling after Twin Lakes dam failure	470
♦ Liquid release of Cs-137 and Sr-90 from an H-Area retention basin	471
♦ Tritiated water release from K Reactor	472

Compiled by George A. Taylor
Environmental Protection Department

Nonroutine Occurrences

1991 HIGHLIGHTS

- ♦ An unplanned release of about 150 gallons of tritiated water from one of the K-Reactor heat exchangers occurred Dec. 22-25. An estimate of 5,700 Ci of tritium released during the incident was obtained using tritium analyses of water and measured river flow rates. Contamination moved through Pen Branch and Steel Creek to the Savannah River, resulting in detectable concentrations all the way to Savannah, Ga. The maximum dose to an offsite individual was calculated to be 0.035 mrem.
- ♦ Heavy rainfall in August resulted in failure of the Twin Lakes Dam, which retains rainwater and groundwater outcroppings before release into Four Mile Creek. Because the groundwater outcroppings in this area can be influenced by seepage, primarily tritium, from the C-Area Seepage Basin, a special sampling of water and sediment was conducted. Radionuclide concentrations in sediment were typical of those in soils from worldwide fallout, and tritium results were consistent with historical measurements of this drainage.
- ♦ Offsite dose consequences of an unplanned liquid release of Cs-137 and Sr-90 from an H-Area retention basin to Four Mile Creek in September were estimated to be 0.005 mrem to a maximally exposed individual from drinking water and fish consumption.
- ♦ Ground contamination near laboratory buildings in F Area was detected during a routine health physics survey. It was determined that the contamination resulted from a release from the failure of a high-level transfer line. EMS conducted special expedited analyses of water from the runoff area and detected primarily Sr-90 with lesser amounts of Cs-137. No increase in radioactivity was evident at the next sampling location downstream. No estimate of the total activity released is available.

INTRODUCTION

The environmental monitoring program at the Savannah River Site (SRS) extends beyond monitoring routine releases of radioactivity to the environment. Nonroutine releases of radioactivity, as well as releases of nonradiological contaminants, also are monitored.

If a nonroutine release of radioactivity is suspected, a special sampling and analysis program is initiated to determine whether a release occurred and to evaluate the environmental impacts and dose consequences of the release.

Samples are collected from the suspected source of the release and from locations along the release's environmental pathway. The samples—which may include air, water (process, stream, or river), vegetation, and/or soil—then are analyzed as priority samples (Figure 10-1).

All radiological results (both atmospheric and liquid) from nonroutine releases are incorporated into final dose determinations (Chapters 7 and 8, "Air Pathways" and "Water Pathways," respectively). Therefore, doses are not calculated for every nonroutine release. If a dose was calculated for an occurrence, the value is included in the following summaries.

772-F CONTAMINATION—APRIL 1991

In late April 1991, an area of contamination was discovered near F-Area laboratory buildings 772-F and 772-1F. On April 25, SRS's Environmental Monitoring Section (EMS) was notified by Health Protection Operations that elevated readings had been observed in the area during a routine health physics survey. The contaminated areas included soil in the vicinity of a high-level transfer line and several storm drains with associated sewer lines. It was determined that the contamination was caused by a high-level transfer line failure.

Surface runoff and storm water from the affected area pass through Upper Three Runs-2 (U3R-2) monitoring location. Therefore, EMS conducted special weekly analyses of routine samples from this location; routine samples normally are analyzed every two weeks. Analytical results indicated that the released activity was primarily Sr-90, with smaller amounts of Cs-137. Analytical results are presented in Table 10-1.

Also determined were activity levels in samples from the U3R-3 monitoring location—downstream of the U3R-2 discharge. Again, special weekly analyses of routine samples were performed. No increase in activity from the incident was observed at U3R-3 (Table 10-2).

A special sediment sample was collected from the stream bed at U3R-2. The analytical results indicated

the presence of a variety of fission products, including Cs-137 and Sr-90, and decay products from the uranium and thorium decay chains. Historically, deposition of radioactivity from routine operations and storm water runoff has occurred at this stream bed location. However, this location is not part of the routine EMS sediment monitoring program, therefore, no previous samples are available for comparison. Concentrations present before the release are unknown, and the contribution of this incident cannot be quantified.

Because of the lack of flow measurements at U3R-2, no estimate of the total activity released was made. However, plans are in place for the installation of a flow-proportional sampling system, which also will provide a continuous measurement of flow.

TWIN LAKES DAM FAILURE—AUG. 1-2, 1991

The dam at Twin Lakes failed Aug. 1-2, 1991. Heavy rainfall Aug. 1 caused a failure of the upper dam, releasing water that subsequently breached the lower dam. The Twin Lakes system receives rainwater and groundwater outcroppings. Groundwater may be influenced by seepage, primarily tritium, from the C-Area seepage basin. The lakes drain into Four Mile Creek (FMC) above Road A-7.

EMS learned of the Twin Lakes dam failure Aug. 6. Special grab sampling of the water and sediment was conducted Aug. 7. Sediment samples were analyzed for Cs-137, and water samples were analyzed for

Figure 10-1 If a non-routine release is suspected, SRS follows a specific sampling and analysis regime to determine the kind and amount of material released and then calculates annual dose consequences and environmental impacts.

Figure 10-2 Map shows the locations where samples were taken following the September 1991 liquid release of cesium and strontium at the H-Area waste management facilities.

Cs-137 and tritium. Sample analysis results are presented in Table 10-3. Because of analytical urgency, sediment samples were not dried and pulverized prior to analysis.

The tritium results indicated concentrations consistent with those seen historically. Gamma spectrometry is not routinely performed on water samples, nor does EMS conduct routine sediment sampling of the Twin Lakes region. Therefore, there is no historical data with which to compare the sediment analyses results. However, the radioactivity detected in the sediment samples (Table 10-3) was typical of levels seen in soils contaminated only with worldwide fallout [NCRP, 1976].

H-AREA WASTE MANAGEMENT FACILITIES—SEPT. 23-30, 1991

From Sept. 23-30, 1991, 0.011 Ci of Cs-137 and 0.012 Ci of Sr-90 were released from the 281-8H retention basin to FMC. On Oct. 3, EMS was notified of a possible unplanned release to FMC resulting from operations at the H-Area waste management facilities. Initial indications were that the release was composed of contaminated water from certain zones of the H-Area Tank Farm. Operating conditions at the time were normal, and storm water was being released from the H-Area Tank Farm to FMC via discharge point HP-52 (Figure 10-2). The confusion surrounding the early part of the release was primarily attributable

to several factors. The existing process monitors were gamma sensitive and under-responded to betas; thus the release, which was unusually rich in Sr, was not detected. Also, errors were made in routine sample screening. Communication problems between Health Protection Operations, Waste Management Operations, and EMS compounded these problems.

Concurrent with the Waste Management notification, EMS identified elevated gross beta levels at monitoring point Four Mile 2 (FM-2) from routine weekly samples collected and composited from Sept. 16-30. After notification, EMS collected grab samples from both HP-52 and FM-2. These samples were analyzed for gross alpha, gross beta and gamma emitters. The weekly samples, which normally are composited on a monthly basis for strontium analyses, instead were analyzed each week following this incident. The results of all of these analyses and the historical values appear in Table 10-4.

Analytical results during the release indicated elevated gross beta levels at FM-2 attributed to Cs-137 and Sr-90. However, no increase in activity levels was indicated at HP-52. Subsequent routine samples collected from FM-2 indicated normal levels. This implies that the release of activity was from the 281-8H basin—not directly from the H-Area Tank Farm. The maximum offsite dose equivalent to an individual was 4.7E-03 mrem (drinking water plus

fish consumption), calculated using the activity levels and stream flow at FM-2 from Sept. 23-30.

K-REACTOR TRITIUM RELEASE—DEC. 22-25, 1991

From Dec. 22-25, 1991, approximately 150 gallons of tritiated water leaked from one of the K-Reactor heat exchangers. EMS began a comprehensive program Dec. 25 to collect and analyze surface water from SRS to the Savannah River estuary (Figure 10-3). Upon notification, the Environmental Technology Section (ETS) activated its emergency response team to provide predictions of river concentrations, transport times, and radiological effects to downstream water users.

EMS collected water samples from the K-Area discharge to determine if any radionuclides other than tritium had been released; no other nuclides were detected. EMS also conducted a survey of the swamp from Pen Branch to Steel Creek Dec. 31 to determine whether any significant tritium inventory was being held in the swamp. This survey showed variable concentrations that mimicked the results of surveys at the mouth of Steel Creek, demonstrating that the swamp was not retaining substantial tritium from the release [Hamby et al., 1992].

Elevated tritium concentrations in the Savannah River at Highway 301 initially were detected Dec. 26. Further downstream at Becks Ferry, adjacent to the intake canal for the Beaufort-Jasper (S.C.) Water Treatment Plant, elevated tritium concentrations first were detected during the morning of Dec. 28. Later that afternoon, tritium concentrations began to rise at Abercorn Creek, where the lift station for the Port Wentworth (Ga.) Water Treatment Plant is located [Hamby et al, 1992].

Tritium concentrations at each location reached their peak about 30 hours after arrival of the plume's leading edge. The maximum measured concentration at Highway 301 was 66.9 pCi/mL on Dec. 28. The maximum concentrations at the Beaufort-Jasper and Port Wentworth intakes occurred Dec. 30 and were 56.2 and 52.7 pCi/mL, respectively [Beals et al, 1992]. Daily average river flow rates and measured tritium concentrations were used to determine the daily amounts of tritium transported past the Highway 301 bridge and the Beaufort-Jasper intake canal. From these data, it was estimated that approximately 5,700 Ci of tritium were released from the leaking heat exchanger to the Savannah River [Hamby et al, 1992].

The K-Reactor release was the largest unplanned tritium release to surface water in the last six years (Table 10-5). The next largest was a 2,100-Ci release resulting from an incident at the D-Powerhouse heavy water rework unit [Zeigler et al, 1987].

The maximum dose to an individual consuming two liters of water per day at Highway 301 was calculated to be 0.035 mrem. This dose is 0.9 percent of the Environmental Protection Agency (EPA) drinking water standard of 4 mrem/yr. The maximum doses to individuals consuming drinking water from the Beaufort-Jasper and the Port Wentworth domestic water systems were 0.0096 mrem (0.2 percent of the EPA dose standard) and 0.030 mrem (0.8 percent of the EPA dose standard), respectively [Hamby et al, 1992]. The dose equivalent for all of 1991 to the maximally exposed offsite individual was 0.073 mrem from tritium in the Savannah River. This dose includes all aqueous tritium releases from SRS, including the K-Reactor incident.

Figure 10-3 Map shows path followed by tritium from K Area to the Savannah River estuary after December 1991 release.

Table 10-1
Radioactivity in Upper Three Runs Creek at U3R-2

Date	Nuclide	Activity (1E-09 $\mu\text{Ci/mL}$) ± 2 Std Dev
4/1 - 4/8	Gross Beta	550.4 $\pm$ 43.1
	Gross Alpha	8.5 $\pm$ 2.3
	^{137}Cs	55.4 $\pm$ 11.1
	^{90}Sr	228. $\pm$ 12.3
4/8 - 4/15	Gross Beta	80.0 $\pm$ 7.9
	Gross Alpha	3.0 $\pm$ 1.1
	^{137}Cs	29.4 $\pm$ 8.3
	^{90}Sr	35.4 $\pm$ 5.0
4/15 - 4/22	Gross Beta	48.0 $\pm$ 5.2
	Gross Alpha	2.8 $\pm$ 1.1
	^{137}Cs	<LLD; LLD = 20.7
	^{90}Sr	17.6 $\pm$ 3.5
4/22 - 4/29	Gross Beta	29.7 $\pm$ 3.4
	Gross Alpha	1.6 $\pm$ 0.9
	^{137}Cs	<LLD; LLD = 46.8
	^{90}Sr	Not Analyzed
4/29 - 5/6	Gross Beta	35.4 $\pm$ 3.6
	Gross Alpha	2.6 $\pm$ 1.4
	^{137}Cs	<LLD; LLD = 27.6
	^{90}Sr	Not Analyzed
Historical Levels		
1/1/91 – 4/1/91	Gross Beta	43.2
	Gross Alpha	3.2
	^{137}Cs	16.4
	^{90}Sr	7.7
1/1/90 – 12/31/90	Gross Beta	19. $\pm$ 49.
	Gross Alpha	2.3 $\pm$ 3.4
	^{137}Cs	Variable, most <LLD's, max: 36
	^{90}Sr	2.6 $\pm$ 5.4

Table 10-2
Radioactivity in Upper Three Runs Creek at U3R-3

Date	Nuclide	Activity (1E-09 μCl/ml) $\pm$ 2 Std Dev
4/1 - 4/8	Gross Beta	1.7 $\pm$ 0.8
	Gross Alpha	1.0 $\pm$ 0.7
4/8 - 4/15	Gross Beta	1.8 $\pm$ 0.8
	Gross Alpha	1.8 $\pm$ 0.9
4/15 - 4/22	Gross Beta	3.2 $\pm$ 1.0
	Gross Alpha	1.6 $\pm$ 0.9
3/25 - 4/29	^{137}Cs	<LLD; LLD = 22.6
	^{90}Sr	0.6 $\pm$ 0.7
Historical Levels		
1/1/91 - 4/1/91	Gross Beta	2.14
	Gross Alpha	2.26
	^{137}Cs	<LLDs
	^{90}Sr	0.14
1/1/90 - 12/31/90	Gross Beta	1.5
	Gross Alpha	1.4
	^{137}Cs	<LLDs
	^{90}Sr	0.4

Table 10-3
Twin Lakes Special Sampling Summary

	Cs-137(pCi/g)^a	H-3(μCi/ml)^a	Mercury(mg/kg)
Upper lake bank (sediment)	1.05 ± 0.14	N/A	N/A
Upper lake middle (sediment)	0.73 ± 0.11	N/A	< 0.0001
Lower lake (sediment)	1.14 ± 0.15	N/A	< 0.0001
Below lower lake (sediment)	0.27 ± 0.07	N/A	N/A
Below lower lake (flowing water)	<LLD; LLD=13.1	14.0 ± 1.4 E-06	N/A
Below lower lake (standing water)	<LLD; LLD=12.51	14.8 ± 1.3 E-06	N/A

Historical Tritium Results^a

1991 Average	1.96 ± 0.30 E-05
1990 Average	2.50 ± 1.20 E-05
1989 Average	2.88 ± 0.83 E-05

^a ± 2 standard deviation.

Table 10-4
Sample Analysis Summary for the H-Area Tank Farm Release

Location	Date	(1E-09 $\mu\text{Ci/mL}$) ± 2 Std Dev			
		Cs-137	Alpha	Beta	Sr
FM-2	9/3-9/16	<15.0	0.6 ± 0.7	14.6 ± 2.4	a
	9/16-9/30	32.6 ± 8.2	0.9 ± 0.7	88.1 ± 11.3	a
	9/23-9/30	58.8 ± 11.1	0.8 ± 3.0	163 ± 22.5	62.6 ± 4.1
	10/2 grab	17.3 ± 7.1	3.3 ± 1.3	27.7 ± 4.0	N/R ^b
	9/30-10/7	21.9 ± 7.8	0.6 ± 0.7	45.8 ± 6.0	15.2 ± 2.1
HP-52	9/3-9/16	<16.8	2.2 ± 1.2	14.9 ± 2.4	c
	9/16-9/30	<14.5	1.9 ± 0.9	8.6 ± 1.8	c
	9/23-9/30	<17.0	8.6 ± 3.4	24.4 ± 4.2	N/R
	10/2 grab	32.0 ± 9.3	11.9 ± 2.7	59.3 ± 7.6	N/R
	9/30-10/7	<15.7	0.4 ± 0.5	11.1 ± 2.1	3.4 ± 1.2
281-8H	10/3 grab	1565 ± 104	11.6 ± 3.5	$4.7\text{E}3 \pm 5.8\text{E}+02$	$4.7\text{E}3 \pm 5.8\text{E}+02$
241-28H ^d	10/2 grab	283.7 ± 28.4	57.8 ± 9.8	$2.6\text{E}4 \pm 3.2\text{E}+03$	N/R

Historical Results (FM-2) ± 2 Std Dev

	1987	1988	1989	1990	1991
Gross Beta (1E-09 $\mu\text{Ci/mL}$)					
Average	19 ± 37	35 ± 65	37 ± 44	27 ± 20	19
Maximum	96	170	94	51	32
Sr-90 (1E-09 $\mu\text{Ci/mL}$)					
Average	2.7 ± 4.1	5.9 ± 7.1	4.2 ± 3.4	3.8 ± 2.3	2.3
Maximum	7.6 ± 1.7	15 ± 3.2	7.5 ± 2.0	6.2 ± 1.5	3.6

a Indicates routine EMS analysis frequency (monthly). Monthly composite results: 28.13 ± 2.87 .

b Indicates analysis not requested.

c Indicates routine EMS analysis frequency (monthly). Monthly composite results: 1.67 ± 0.93 .

d 241-28H sample also labeled as 6H Storm Monitor.

Table 10-5
Perspectives on the December 1991 Tritium Release from K Reactor

Tritium Releases (Ci) to Surface Water for SRS ^a			
Year	Total Releases	Nonroutine Releases	Location of Nonroutine Release
1991	27,000	5,700	To Pen Branch from K Reactor
1990	16,000	3.7	To Beaver Dam Creek via D -Area process sewer
1989	17,000	70	To Pen Branch via K-Area process sewer
		530	To Pen Branch via K-Area process sewer
		8	To L Lake via L-Area process sewer
		240	To Beaver Dam Creek via D-Area sewer
		68	To Par Pond via P-Area Canal
1988	19,000	3.2	To Pen Branch via K-Area process sewer
		15	To Par Pond via P-Area process sewer
		110	To Pen Branch via K-Area process sewer
		0.09	To Pen Pond via P-Area process sewer
		70	To Pen Branch via K-Area process sewer
1987	23,000	160	To Four Mile Creek from H-Area
		430	To Beaver Dam Creek from D-Area sewer
1986	28,000	2,100	To Beaver Creek via D-Area sewer

^a Rounded to two significant figures. Data obtained from SRS annual environmental reports.

To Learn About:	Turn to page:
♦ Par Pond drawdown survey	479
♦ Surveys of radioactive contamination in Savannah River Swamp	482
♦ Four Mile Creek surveys	485
♦ Academy of Natural Sciences of Philadelphia surveys of the Savannah River	
Diatom communities survey	486
Cursory biological surveys	488
Plant Vogtle comprehensive survey	489

Compiled by George A. Taylor
Environmental Protection Department

Special Surveys

1991 HIGHLIGHTS

- ♦ A survey of Par Pond was performed during the water drawdown for a safety investigation of the Par Pond dam. Sediments of Pond C and Par Pond contained elevated concentrations of Cs-137, up to about 140 pCi/g. Air sampling during the investigation indicated no increase in airborne radioactivity from wind erosion of sediments.
- ♦ Results of the 1990 comprehensive survey and the 1991 cursory survey of the Savannah River Swamp indicate that the areal extent of Cs-137 contamination generally is similar to that seen in previous surveys. Concentrations of Cs-137 in soil ranged up to about 280 pCi/g. Core samples of the soils show the expected decrease in concentrations with increasing depth. Contamination extended to depths of at least 9-12 inches.
- ♦ Results of the Pu-238 and Pu-239,240 in soil analyses for the 1990 Four Mile Creek survey were completed, and the concentrations generally followed the same patterns as other radionuclides. The concentrations ranged up to 2.7 and 1.3 pCi/g for Pu-238 and Pu-239,240, respectively, with the highest levels occurring immediately downstream of F and H areas and near the beaver pond on Four Mile Creek.
- ♦ In September, the Academy of Natural Sciences of Philadelphia conducted the sixth comprehensive survey in the vicinity of Vogtle Electric Generating Plant on the Savannah River. The survey characterizes and compares the biological and chemical conditions of the Savannah River above and below the Plant Vogtle cooling water discharge.

INTRODUCTION

In addition to routine sampling and special sampling during nonroutine environmental releases, radiological and nonradiological surveys are conducted onsite and offsite by the Savannah River Site (SRS) Environmental Protection Department's Environmental Monitoring Section (EPD/EMS) and other groups, including the Savannah River Laboratory (SRL) and the Academy of Natural Sciences of Philadelphia (ANSP). Both short- and long-term radiological and nonradiological surveys are used to monitor the effects of SRS effluents on the environment at SRS and in its immediate vicinity.

RADIOLOGICAL MONITORING SURVEYS

Par Pond Survey

Description of Survey

Par Pond is a 2,640-acre reservoir constructed in 1958 on Lower Three Runs Creek. It serves as a recirculating cooling reservoir for R and P Reactors. From August 1958 to October 1961, Par Pond received thermal effluent from R Reactor via a precooler pond, Pond C. Both reactors utilized Par Pond from November 1961 to June 1964. After R-Reactor operations were suspended in July 1964, Par Pond received thermal effluent from P Reactor only. Since these reactors are not

Par Pond was drawn down after a March 1991 inspection revealed a depression on the downstream face of the pond's dam.

currently operating, thermal discharge to Par Pond has ceased.

In March 1991, an inspection of the Par Pond dam revealed a depression on the downstream face. Subsequent investigations revealed piping (erosion around the outside of buried conduits) and erosion of fill materials within the dam. Although the investigation revealed no imminent potential for dam failure, precautionary measures were taken. To minimize the potential for failure and decrease the magnitude of associated flooding, the reservoir was drawn down to the 181-foot elevation; normal reservoir elevation is 200 feet above mean sea level. Concurrently, a detailed investigation of the safety of the dam was performed.

During the summer and fall of 1991, EMS conducted a special sampling program in support of the Par Pond drawdown effort. The survey was conducted to determine the extent and levels of contaminants. This information was used to indicate the activity of sediment, identify source term isotopes, and assist in risk assessment. EMS sampled Par Pond at incremental water levels during the drawdown. Also, four air monitoring stations (Figure 11-1) were established

around the perimeter of Par Pond to measure airborne radioactivity that may have been created by contaminated, wind-suspended particles as the drawdown proceeded.

An initial survey conducted June 29 consisted of collecting and analyzing sediment samples and measuring penetrating radiation exposure rates at 12 locations when the water level was approximately 200 feet. Subsequent sampling was expanded to encompass 17 locations (Figure 11-1), including sediment core and vegetation samples. Also, additional one-time sediment and vegetation samples were collected near a dam in the North Arm of Par Pond, which was discovered as Par Pond was drawn down. This dam was in place prior to the construction of Par Pond but was breached during the construction. Pond C also was sampled as part of the drawdown effort, since it is a part of the Par Pond system. These additional Par Pond surveys were conducted July 28 (195 feet), Aug. 15 (190 feet), Sept. 4 (185 feet), and Oct. 3 (182 feet). Pond C was surveyed one time only—at the 195-foot level—because its water level was maintained by water control systems. Table 11-1 presents a summary of the sampling and measurements conducted during each survey.

Figure 11-1 Map shows air and land monitoring locations established for a special sampling program conducted during the 1991 drawdown of Par Pond. The reservoir was lowered to permit a detailed safety inspection of its dam.

The sediment samples collected from the June 29 survey were analyzed for gamma-emitting radionuclides and Pu-238 and Pu-239. Sediment samples from subsequent surveys were analyzed for Cs-137, and five locations from each survey were chosen for Sr-89,90 and plutonium analysis based on Cs-137 levels. (The samples with the highest Cs-137 levels were chosen for analysis.) Analyses on core and vegetation samples were not completed.

Several samples from other biological media were taken during the course of the Par Pond drawdown. On Aug. 8, clams were dredged from the sediment near survey point 1 (Figure 11-1). The clams were shucked and analyzed for gamma-emitting radionuclides.

In late September, Savannah River Ecology Laboratory (SREL) personnel discovered elevated Cs-137 levels in a hog feces sample near Par Pond. Using an SREL metabolic model, it was estimated that the

Cs-137 body burden could be as high as 85 pCi/g muscle. This level was of concern to EMS because of the feces' proximity to the annual SRS controlled deer/hog hunts.

In addition to radiological analyses, mercury analyses were performed on composited sediment samples collected from Par Pond and Pond C. Mercury levels are a concern because of the toxicity and potential for harmful effects to the health of individuals residing downstream in event of dam failure.

To assess the Cs-137 levels and potential dose impact from this pathway, EMS worked with Savannah River Ecology Laboratory (SREL) to obtain samples of two hogs taken in the vicinity of Par Pond. Samples also were taken from hogs killed near Par Pond during annual deer/hog hunts. These samples were analyzed for gamma-emitting radionuclides. Results appear in Table 11-8.

Monitoring Results

Air samples were collected weekly and analyzed for gross alpha/beta activity. Air sample results indicated that there was no increased level of gross alpha or gross beta activity. Gross alpha activity ranged from below detection limits to $5.4\text{E-}15$ $\mu\text{Ci/mL}$. Gross beta activity ranged from $2.6\text{E-}15$ to $4.1\text{E-}14$ $\mu\text{Ci/mL}$. Sample results are presented in Table 11-2.

Analytical results for Cs-137, Pu-238, and Pu-239 in sediment samples are presented in Tables 11-3 and 11-4. These results generally show low Cs-137 levels. However, concentrations in Pond C were slightly higher than those in Par Pond. Variations in levels and spatial distribution also were observed. The spatial variations were observed among all locations at a specific water level and at a specific location with decreasing water levels. The Cs-137 results generally agree with trends seen in previous aerial overflight surveys. Cs-137 concentrations ranged from 0.14 to 136 pCi/g in Par Pond and from 5.5 to 39 pCi/g in Pond C. Small quantities of Co-60 were detected in only 11 samples. The Co-60 is a result of past reactor operations. Pu-238 concentrations in Par Pond sediment ranged from 0 to 0.012 pCi/g, while Pu-239 levels ranged from 0.001 to 0.22 pCi/g. Three of the five Pond C samples were analyzed for plutonium concentrations; the concentrations ranged from 0.006 to 0.010 pCi/g and 0.035 to 0.14 pCi/g for Pu-238 and Pu-239, respectively.

Sr-89,90 sediment sample results for Par Pond and Pond C are presented in Table 11-5. Concentrations in Par Pond ranged from 0 to 0.20 pCi/g, while concentrations in Pond C ranged from 0.08 to 0.25 pCi/g.

Table 11-6 contains the results of the penetrating radiation measurements taken in proximity to the location of core sampling. Penetrating radiation levels generally were higher at Par Pond than at the Pond C sampling locations because P-Reactor effluent discharges directly to the pond and because of the sedimentation of entrained contaminants.

Mercury analyses results are given in Table 11-7. Concentrations ranged from <0.0001 to 0.18 mg of mercury per kg of sediment. The higher concentrations were observed in samples collected during the early stages of the drawdown. Sample results for clams and hogs are given in Table 11-8. Cs-137 was the only radionuclide detected. Negligible amounts of Cs-137 were present in the clam samples, and slight activity was detected in the hog samples. However, hog muscle sam-

Figure 11-2 Radioactivity released from SRS operations contaminated the Savannah River Swamp between Steel Creek and Little Hell Landing during the 1960s.

ple results were significantly less than the 85 pCi/g estimated by SREL.

Savannah River Swamp Survey

Description of Survey

In the 1960s, a portion of the Savannah River Swamp between Steel Creek Landing and Little Hell Landing was contaminated with approximately 25 Ci of Cs-137 and 1 Ci of Co-60. The contaminated swamp area extends beyond the SRS boundary to private property known as Creek Plantation (Figure 11-2). The offsite swamp area is uninhabited and not easily accessible except for occasional hunting or fishing.

The contamination resulted from failed fuel elements that leaked radioactivity into P-Area storage basin water used to shield and cool the irradiated fuel elements. Over time, some of the fuel storage basin water containing the Cs-137 and Co-60 was discharged to Steel Creek. During periods of high river flow, Steel Creek flowed along the lowlands comprising the swamp and entered the Savannah River at

Little Hell Landing. Consequently, radioactivity settled in the swamp. The failed fuel elements were removed from P-Area fuel storage basins in 1970.

Ten sampling trails were established in the swamp in 1974 so that specific locations could be routinely monitored to determine the amount and migration of radioactivity within the Creek Plantation Swamp.

Comprehensive surveys were conducted annually along the trails between 1974 and 1977 to characterize the contaminated area. These comprehensive surveys included measuring penetrating radiation with thermoluminescent dosimeters (TLDs) and analyzing vegetation, soil, and fish samples for radioactivity. The frequency of the comprehensive surveys was reduced to five-year intervals after 1977 because no significant changes in radiological conditions were measured.

However, cursory surveys, which consist of penetrating radiation measurements and sampling at selected locations, have been conducted annually to provide interim monitoring of the swamp.

To characterize the contaminated area, a comprehensive survey was conducted in 1990, but survey results were not included in last year's report because analyses were not completed before publication of the annual report. The remainder of this section describes the 1990 comprehensive survey and the 1991 cursory survey—with program changes noted—then presents results of the two surveys.

Program Changes

The following tasks were performed during the 1990 comprehensive survey:

- Penetrating radiation exposures were measured using portable survey instruments (microR meters) at 100-ft intervals on the monitoring trails as well as at each of the 54 sampling locations. This is the first time microR meters have been used in a comprehensive survey.
- TLDs were placed 1m above ground at each sampling/monitoring location to measure penetrating radiation exposures.
- Surface and vegetation samples were collected at each of the 54 sampling locations. All samples were analyzed for gamma-emitting radionuclides and Sr-89,90.
- Twelve-inch soil core samples were collected from 10 locations (representing the area of highest

historical exposure and Cs-137 concentration on each trail). The cores were split into 3-inch segments and analyzed for gamma-emitting radionuclides and Sr-89,90. Collection and analysis of core samples have not been conducted as part of the swamp survey since the mid-1970s.

The sampling/monitoring program for the cursory survey conducted in 1991 was similar to that of the 1990 comprehensive survey. However, sample collection was not as extensive. The 1991 cursory survey differed from the 1990 comprehensive survey in the following ways:

- No core samples were collected.
- Soil and vegetation samples were collected at only the 10 locations representing the area of highest historical penetrating exposure and Cs-137 concentration on each trail. All samples were analyzed for gamma-emitting radionuclides and Sr-89,90.

1990 Comprehensive Survey Results

Results of the survey show that recent migration of radioactivity may have occurred in the Savannah River Swamp. In surveys through 1989, results indicated that not all of sampling trails 3 and 5 were contaminated [Cummins et al., 1990]. Recent results indicate that more of these trails may be contaminated with low levels of Cs-137. Additional information regarding the extent of Cs-137 contamination will be determined by examining results of future Savannah River Swamp surveys.

Surface Soil

Soil samples were analyzed for gamma-emitting radionuclides and Sr-89,90. Slight variations in activity levels were observed but were comparable to levels seen in previous surveys. Concentrations of radionuclides vary in the soil from year to year and sample to sample because of slight differences in sampling locations and soil homogeneity.

Cs-137 and Co-60 were the only man-made gamma-emitting radionuclides detected in the soil samples. The concentrations of Cs-137 were within ranges observed in previous surveys and ranged from 0.19 to 75 pCi/g. The majority of samples indicated Co-60 levels below detection limits. Detectable concentrations of Co-60 ranged from 0.10 to 0.26 pCi/g. Ranges for Sr-89,90 are not provided because only four locations from Trail 5 were analyzed. Analytical results are presented in Table 11-9.

Vegetation

Vegetation samples were analyzed for gamma-emitting radionuclides and Sr-89,90. Cs-137 and Co-60 were the only man-made gamma-emitting radionuclides detected in vegetation samples. The concentrations of Cs-137 were within ranges observed in previous surveys and ranged from 0.12 to 15 pCi/g. Co-60 was detected in only one sample (0.15 pCi/g); the rest were either below detection limits or not available.

Sr-89,90 analyses were performed on vegetation samples for the first time since the mid-1970s. As such, there are no other data for comparison of 1990 activity levels. The concentrations of Sr-89,90 ranged from 0.03 to 10.9 pCi/g. Analytical results for vegetation samples are presented in Table 11-10.

Soil Cores

Core samples were taken at one location per trail. Each sample was divided into 3-inch segments and analyzed for gamma-emitting radionuclides and Sr-89,90. Cs-137 and Co-60 were the only gamma-emitting radionuclides detected in core samples. The concentrations of Cs-137 ranged from 0.04 to 92 pCi/g. Co-60 concentrations ranged from 0.08 to 0.52 pCi/g. Sr-89,90 concentrations ranged from 0 to 0.81 pCi/g. The activity distribution of results follows expected patterns, showing a decrease in activity with an increase in depth. Analytical results are presented in Table 11-9.

Penetrating Radiation

In 1990, penetrating radiation exposures were measured using portable survey instruments at 100-foot intervals along each trail, as well as at each monitoring/sampling location. These measurements were compared with penetrating radiation exposures measured with TLDs at locations with both microR and TLD measurements.

Measurements were taken with the microR meter at ground level and 1 meter above the ground. The measurements ranged from 0 to 140 μ R/hr at ground level, and from 0 to 110 μ R/hr at 1 meter above ground. The microR survey results are presented in Table 11-11.

TLDs were placed one meter above ground at each monitoring/sampling location. They were collected for processing after an exposure period of approximately 30 days. Exposure rates ranged from 0.10

mR/day to 0.59 mR/day. Penetrating radiation measured with TLDs are presented in Table 11-12.

Both TLD and microR meter exposure measurements were obtained at 25 locations where the TLD monitoring point coincided with the 100-foot survey meter location. As in previous years, the results indicate an apparent microR over-response relative to the TLDs. Most likely, this discrepancy results from converting short-term exposure rates measured with the microR meter (μ R/hr) into units of long-term exposure rates measured with TLDs (mR/day). Also, there are differences in the response characteristics of micro-R meters and TLDs. The values for both TLD and microR meter measurements are presented in Table 11-13.

1991 Cursory Survey Results

The annual cursory survey is, by nature, limited in scope and performed to monitor for drastic changes in the environment. With few exceptions, results from the 1991 survey were similar to those observed in previous surveys.

Surface Soil

Nine soil samples were analyzed for gamma-emitting radionuclides and Sr-89,90. Cs-137 and Co-60 were the only man-made gamma-emitting radionuclides detected in soil samples. With one exception (Cs-137 at Trail 7, which was higher than normal) the gamma analysis results generally agreed with those seen in previous surveys. The observed differences may be the result of sampling location. Concentrations of radionuclides may vary in the soil from year to year, and results should be used as a long-term indicator. Cs-137 concentrations ranged from 1 to 277 pCi/g. Co-60 levels ranged from 0.14 to 1 pCi/g, and Sr-89,90 concentrations ranged from 0.01 to 0.06 pCi/g. Analytical results for soil samples are presented in Table 11-14.

Vegetation

Vegetation samples were analyzed for gamma-emitting radionuclides and Sr-89,90. Cs-137 was the only man-made gamma-emitting radionuclide detected in vegetation samples. The concentrations of Cs-137 were within ranges observed in previous surveys and ranged from 0.40 to 18 pCi/g.

Sr-89,90 analyses were performed as part of the 1990 survey on vegetation samples for the first time since the mid-1970s. Sr-89,90 results in 1991 generally agree with those from the previous year, and ranged from 0.02 to 0.97 pCi/g. Analytical results for vegetation samples are presented in Table 11-15.

Penetrating Radiation

In 1991, penetrating radiation exposures were measured using TLDs. Portable survey instrument (microR meter) measurements were not obtained because of equipment malfunction.

TLDs were placed 1 meter above ground at each monitoring/sampling location. They were collected for processing after an exposure period of 30 days. Exposure results ranged from 0.11 mR/day to 0.61 mR/day. Exposure levels were in agreement with levels measured in previous surveys. This is true for locations of elevated observed exposures and magnitudes of observed levels. Penetrating radiation levels measured with TLDs are presented in Table 11-16.

Four Mile Creek Survey

Description of Survey

Four Mile Creek originates on SRS, flows across the central area of the site, and eventually discharges into

the Savannah River (Figure 11-3). During SRS operations, Four Mile Creek receives process effluents from F, H, and C areas. The stream also receives groundwater migration from the C-, F-, and H-Area seepage basins. Because of site operations, various radionuclides, including Cs-137, Sr-90, Pu-238, Pu-239, and tritium, have been deposited in the Four Mile Creek stream bed and valley.

During the spring of 1990, the first comprehensive survey of Four Mile Creek was conducted to characterize the radiological condition of the stream and stream valley. Chart 11-1 lists the sampling locations and the rationale for choosing each location.

During 1990, most of the required analyses on the Four Mile Creek survey samples were completed. A shortage of analytical resources prevented the analysis of soil samples for Pu-238 and Pu-239. These analyses have since been completed and are presented in Chart 11-2 and Table 11-17.

Figure 11-3 The Environmental Monitoring Section conducted a first-ever comprehensive survey of Four Mile Creek in 1990 to characterize the radiological condition of the stream and stream valley. Analyses were completed in 1991, and results indicate that site operations in F and H areas have caused increased levels of radioactivity in the area.

The plutonium results followed expected patterns and generally agreed with trends observed from the other survey analyses. Pu-238 concentrations in soil and sediment ranged from 0 to 2.7 pCi/g, and Pu-239 concentrations ranged from 0 to 1.3 pCi/g. Increased activity was observed at locations immediately downstream of F and H areas (Trail 2 and Trail 3) and near the beaver pond on Four Mile Creek (Trail 4), where sedimentation occurred. This activity was observed at increased levels in the soil and in the shallow core samples. However, comparison of results between the control (Trail 1) and creek mouth (Trail 7) locations indicated that plutonium levels dropped to near background levels. Although neither gross alpha nor U/Pu analyses were performed on the soil or sediments collected, the plutonium results were consistent with the distribution of other radionuclides previously observed in the survey.

Surveys of Dry Monitoring Wells in F- and H-Area Waste Management Facilities

Annual surveys of these wells were discontinued in 1991. Groundwater monitoring results from these areas will be used to provide a more accurate assessment of possible contamination.

NONRADIOLOGICAL SURVEYS

Introduction

The Division of Environmental Research of ANSP, under contract to Westinghouse Savannah River Company (WSRC), has conducted studies to deter-

mine the effect, if any, of SRS effluent discharges on general river health.

During 1991, ANSP conducted semi-monthly surveys of diatom communities, cursory biological studies, and a comprehensive survey in the vicinity of Georgia Power Company's Vogtle Electric Generating Plant. Each survey is summarized in the following sections. Detailed survey results will be published by ANSP in 1992.

Diatom Community Surveys

Description of Survey

ANSP performs semi-monthly surveys of diatom communities to obtain data on diatom species diversity and relative abundance of diatoms. These data are used to evaluate water quality among sampling stations at various time periods.

For 26 two-week exposure periods between Dec. 27, 1990, and Dec. 23, 1991, Catherwood Diatometers® were placed in the Savannah River at Stations 1, 5, and 6 (Figure 11-4). During each exposure period, a single sample from each site was analyzed to determine diatom community structure. Station 1 is considered a control station.

Survey Results

As in previous years, the number of observed species was lower at Station 6 than at Stations 1 and 5 (yearly averages of 99, 91, and 68 at Stations 1, 5, and 6, respectively). The differences between Stations 6 and 1 were consistent, with 20 percent fewer species present at Station 6 for 18 of 25 exposure periods. The

Chart 11-1
Sampling Location and Rationale for Four Mile Creek Survey

Trail	Location	Rationale
T-1	Near Road F	Control/Background
T-2	At Road 4	Below H-Area effluents
T-3	At Road C	Below F-Area effluents
T-4	At Road A-7	Below seepage basin outcroppings
T-4A ^a	Pond at Road A-7	Below seepage basin outcroppings
T-5	Below C Canal	Below C-Area effluents
T-6	At Highway SC 125	Potential public access
T-7	Near FMC-6	Near Four Mile Creek mouth

^a Not a full sampling trail; vegetation samples were taken on the edge of the pond. Sediment and core samples were taken approximately 15 ft from the shore in standing water.

Chart 11-2
Maximum Levels of Radioactivity Measured During Four Mile Creek Survey

Media	Analysis	(pCi/g) ^a		Location ^b
		Result	± Counting Error	
Soil	Cs-137	136.1	± 7.3	T-2 NW Bank
	Cs-134	0.3	± 0.1	T-3 SE Bank
	Co-60	2.59	± 0.18	T-3 SE Bank
	Sr-89	5.4	± 4.2	T-4 NW FP
	Sr-90	2.19	± 0.22	T-4 NW Bank
	Pu-238	2.68	± 0.07	T-3 SE Bank
	Pu-239	1.30	± 0.02	T-3 NW FP
Core (0-9")	Cs-137	81.1	± 4.4	T-2 SE Bank
	Co-60	0.70	± 0.06	T-7 SE Bank
	Sr-89	0.62	± 0.38	T-2 SE Bank
	Sr-90	0.69	± 0.13	T-4 SE Bank
	Pu-238	1.27	± 0.02	T-3 SE FP
	Pu-239	0.19	± 0.01	T-3 SE FP
Core (> 9")	Cs-137	10.40	± 0.54	T-2 SE Bank
	Co-60	1.0	± 0.1	T-5 SE FP
	Sr-89	2.8	± 1.8	T-6 SE Bank
	Sr-90	0.08	± 0.07	T-5 SE FP
	Pu-238	0.08	± 0.01	T-2 SE Bank
	Pu-239	0.034	± 0.003	T-5 SE Bank
Vegetation	Cs-137	527	± 29	T-2 NW Bank
	Cs-134	1.01	± 0.21	T-5 SE Bank
	Co-60	0.28	± 0.20	T-6 SE Bank
	Sr-89	2.3	± 2.3	T-6 NW Bank
	Sr-90	29.9	± 1.8	T-4 NW Bank
	Tritium	964	± 3 (pCi/mL)	T-2 NW FP
	U/Pu	0.87	± 0.26	T-4 SE Bank
	Gross Alpha	4.1	± 2.2	T-4 NW Bank
	Gross Beta	174	± 22	T-4 NW FP
Timber	Cs-137	13.35	± 0.71	T-3 SE FP
	Co-60	0.04	± 0.03	T-7 NW HG
	Tritium	1718	± 3 (pCi/mL)	T-4 SE FP

a Unless otherwise noted.

b SE= South or east side of Four Mile Creek; NW= North or west side of Four Mile Creek; FP= Floodplain; HG= High ground.

number of species observed at Station 1 was 90 or greater for 50 percent of the exposure periods, compared to only 16 percent of the exposure periods for Station 6. Only slight differences in species richness were observed between Stations 1 and 5.

In contrast, the percent dominance of observed species (highest number of a particular species present) was usually higher at Station 6 (greater than 90 percent during 18 of 25 exposure periods) than at

Station 1 (greater than 90 percent during six of 25 exposure periods). Similar to species richness, the percent dominance at Stations 1 and 5 was similar.

Lower species richness and higher percent dominance at Station 6 in comparison with Station 1 are indicative of a less balanced biota. Since 1988, diatom communities at Station 6 have indicated deteriorated water quality, probably due to water quality conditions on Lower Three Runs Creek. A special study of the creek was planned for the summer of 1991, but increased stream flow from the Par Pond drawdown prevented it. The study has been rescheduled for 1992.

Cursory Biological Surveys

Description of Survey

Cursory surveys of algal, insect, and fish communities of the Savannah River in the vicinity of SRS were conducted during 1991 as part of long-term biomonitoring studies. Chart 11-3 lists the three types of surveys conducted in 1991 and the dates of each

Chart 11-3
ANSP Cursory Surveys In 1991

Biota	Survey Dates
Algae/aquatic macrophytes	April 2-4 Dec. 10-12
Fish	Nov. 8-10
Insects	April 2-4 June 25-27 Sept. 17-19 Dec. 10-12

survey. Preliminary results from the cursory surveys are summarized below for each biological group.

Survey Results

Algae and Aquatic Macrophytes

During 1991, surveys of algae and aquatic macrophytes were conducted April 2-4 and Dec. 10-12. There were no detectable differences in water quality among the three stations. Both communities were fundamentally similar to the communities observed at Stations 1, 5, and 6 during other Savannah River surveys.

Diatoms were the dominant algal group at all three stations during both surveys. The dominant diatom species, *Melosira varians* and *Gomphonema parvulum*, were the ones which have been dominant during past surveys. No change in the overall water quality of recent years was indicated.

Beds of aquatic macrophytes have waxed and waned in response to water levels and enrichment during the period since 1951, but species composition has remained essentially unchanged.

The dominant algal flora of this section of the Savannah River continues to consist of the cosmopolitan forms characteristic of moderate to high nutrient levels and the flora remains typical of southeastern coastal plain rivers.

Insects

Aquatic insect surveys were conducted April 2-4, June 25-27, Sept. 17-19, and Dec. 10-12. Four insect traps were deployed at each station approximately one month before each survey; trap material was collected during each survey. Hand collections from the river's natural substrates were made during each sampling period.

Figure 11-4 The Academy of Natural Sciences of Philadelphia has established specific sampling locations for surveys of the Savannah River. Stations 1, 3, 5, and 6 are used in most of the surveys; stations V-1 and V-2 are part of the Plant Vogtle survey.

Researchers identified more than 74 different taxa from the hand collections. Detailed analyses of the 1991 insect collections are ongoing.

Fish

Fish collections were made at each station during the fall of 1991 using rotenone. Thirteen species of fish were caught at Station 1, 17 at Station 5, and 23 at Station 6. Overall, 29 different species of fish were caught during the survey.

In comparison to samples from past years, preliminary data indicate that the species richness in the 1991 samples was typical, except at Station 1 (below average). However, the species richness at all stations in 1991 was less than in 1990.

Plant Vogtle Comprehensive Survey

Description of Survey

In September 1991, ANSP conducted the sixth comprehensive survey in the vicinity of Plant Vogtle on the Savannah River.

The goals of these surveys are to characterize and compare the biological and chemical conditions of stations above and below the Plant Vogtle cooling water discharge and to relate these findings to data obtained from similar surveys of other Savannah River stations studied in the long-term monitoring program.

Initial surveys conducted prior to Plant Vogtle startup in 1985 and 1986 provided baseline data on river conditions in the area of the river to be affected by cooling water discharge from the plant. Commercial operation of Plant Vogtle began in early summer 1987, approximately three months before the first ANSP operational survey of the river. Most of the 1991 survey, conducted Sept. 3-14 at Stations V-1 (above the Plant Vogtle discharge) and V-2 (below the discharge), consisted of chemical analyses of river water and community analyses of algae, macrophytes, protozoa, non-insect macroinvertebrates, and fish. Extended sampling periods occurred Oct. 22-23 and Nov. 9-11 for insects and fish, respectively.

Survey Results

Chemistry and Bacteriology

Water samples collected from Stations V-1 and V-2 were analyzed for fecal coliform and chemical water quality parameters. The results indicated no appreciable differences between the two stations during 1991.

Catherwood Diatometers®

What are they?

Devices used to collect diatoms, which are groups of algae.

How do they work?

Vertically oriented glass slides on the device serve as artificial substrates for colonization by diatoms. The diatometers, which are secured by anchors, float so that the slides remain just below the water's surface.

Why are they useful?

This diatometer samples the diatom flora continuously in a non-selective manner to obtain a representative collection of diatom growth.

What happens after the diatoms are collected?

Following the exposure period, the diatometers are replaced by clean diatometers and immediately placed in the river to ensure the river is continuously sampled.

Fecal coliform counts increased to their second highest level since 1985. The analytical results for chemical parameters, which were compared with data from previous years, indicated minor differences due to natural variability, along with improvements in general water quality.

Algae and Aquatic Macrophytes

Similar results were observed at Stations V-1 and V-2, with the exception of diatom diversity. In 1991, algal growth was light and dominated by the diatoms at both stations. No beds of submerged aquatic macrophytes were present at either station. This pattern of similarity has been observed for the past six years.

Evidence of organic loading persists at both stations. Two of the dominant species at these stations indicate a zone where oxidation of organic pollutants is either ongoing or complete, with high concentrations of inorganic nutrients present. Several of the dominant diatom species in the individual collections are also pollution indicators.

The initial data suggest that the water quality remains improved at the two stations compared to the water quality for the years prior to 1990. The 1991 data show that the operation of Plant Vogtle had no adverse effect on the water quality of the Savannah River.

Protozoa

In 1990, species of protozoans were present only in small numbers, with the richest collections taken from patches of *Vaucheria*, the yellow-green algae that dominates at V-1 and V-2. In 1991, even these patches were absent. The result is that a poorer community was found compared to previous years. The lack of many species may be directly attributable to physical changes brought about by higher water levels during the survey period.

No other significant differences were apparent between the 1991 protozoan community and communities observed in previous years, but a much clearer comparison can be made only with stations under similar habitat and flow regimes.

Non-Insect Macroinvertebrates

Field observations of the non-insect macroinvertebrate fauna near Plant Vogtle indicate that diversity reflects the loss of submerged aquatic vascular vegetation beds. Concentrations of submerged vascular plants constitute one of the most important habitats in the Savannah River. Even though there was a lack of this substrate in 1991, comparisons between the two stations will be possible when the analyses are complete. These beds of aquatic plants were also lacking in 1990. However, water levels were different,

and comparisons among the years of Plant Vogtle surveys will be constrained by differences in water levels, habitats, and delineations of the survey zones.

Insects

Four aquatic insect traps, composed of artificial insect substrates, were deployed at Stations V-1 and V-2 approximately one month before the field effort. Hand collections of the river's natural insect substrates were made, and colonizing insects were removed from the traps during the field effort.

More than 32 different taxa were identified from the hand collections, including mayflies, caddisflies, the whirligig beetle, and the riffle beetle.

Sample analyses for the trap samples have not been completed.

Fish

Sampling techniques used were gill nets, traps, rotenone, and a mesh seine. Thirty fish species were collected at Station V-1 and 38 species at V-2. Forty-one different species were collected in 1991. A preliminary assessment of the data suggests that species richness, community structure, abundance, and size structure of the fish communities were typical of collections made in past years at both stations.

Table 11-1
Par Pond Sampling Summary

LOCATION	6/29/91	7/28/91	8/15/91	9/4/91	10/3/91
1	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
2	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
3	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
4	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
5	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
6	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
7	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
8	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
9	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
10	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
11	S, C, V, M	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M
12	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M	S, C, M
13	N/S	S, C, V, M	S, C, V, M	S, C, V, M	S, C, V, M
14	N/S	S, C, V, M	S, C, V, M	S, C, V, M	S, C, M
15	N/S	S, C, V, M	S, C, V, M	S, C, M	S, C, M
16	N/S	S, C, V, M	S, C, V, M	S, C, M	S, C, M
17	N/S	S, C, V, M	S, C, V, M	S, C, M	S, C, M
Dam-North	N/S	N/S	N/S	S, C, V, M	N/S
Dam-South	N/S	N/S	N/S	S, C, V, M	N/S

NOTE: S = sediment sampling
 C = core sampling
 V = vegetation sampling
 M = portable survey meter readings
 N/S = not sampled

Table 11-2
Air Monitoring Results for Par Pond

Location	No. of Samples	Maximum ± CT ERR	Minimum ± CT ERR	Average ± 2 Std Dev
Gross Alpha, (E-15 $\mu\text{Ci/mL}$)				
Par Pond Bubble Up	17	3.58 ± 0.66	0.61 ± 0.35	1.88 ± 0.82
Par Pond East	13	5.40 ± 1.4	-0.06 ± 1.88	1.49 ± 1.47
Par Pond Dam	18	3.32 ± 0.06	0.36 ± 0.31	2.13 ± 2.11
Par Pond Pump House	19	3.91 ± 0.68	-0.44 ± 0.69	1.46 ± 1.10
Nonvolatile Beta, (E-15 $\mu\text{Ci/mL}$)				
Par Pond Bubble Up	17	39.7 ± 1.7	9.88 ± 0.97	22.5 ± 7.59
Par Pond East	13	30.5 ± 6.1	9.70 ± 1.03	24.8 ± 14.1
Par Pond Dam	18	40.5 ± 1.7	2.59 ± 0.65	21.9 ± 14.4
Par Pond Pump House	19	41.2 ± 1.7	7.26 ± 2.30	21.6 ± 9.33

Table 11-3
Radioactivity in Par Pond Sediment

Samples Collected 6/29/91

Location	pCi/g		
	Cs-137	Pu-238	Pu-239
1	25.80 ± 0.85	0.004 ± 0.001	0.036 ± 0.002
2	17.60 ± 0.59	0.002 ± 0.0003	0.022 ± 0.001
3	6.64 ± 0.25	Not Analyzed	Not Analyzed
4	8.46 ± 0.31	Not Analyzed	Not Analyzed
5	5.77 ± 0.22	Not Analyzed	Not Analyzed
6	5.39 ± 0.21	0.001 ± 0.001	0.007 ± 0.001
7	8.15 ± 0.30	Not Analyzed	Not Analyzed
8	1.09 ± 0.07	Not Analyzed	Not Analyzed
9	7.49 ± 0.29	Not Analyzed	Not Analyzed
10	6.24 ± 0.23	Not Analyzed	Not Analyzed
11	Insufficient Sample	Not Analyzed	Not Analyzed
12	Insufficient Sample	Not Analyzed	Not Analyzed

Note: Only those samples showing the highest levels of Cs-137 were analyzed for Pu-238 and Pu-239.

Table 11-3
Radioactivity in Par Pond Sediment, Cont'd.

Samples Collected 7/28/91

Location	pCi/g		
	Cs-137	Pu-238	Pu-239
1	9.92 ± 0.69	0.011 ± 0.002	0.022 ± 0.003
2	14.14 ± 0.94	0.002 ± 0.001	0.008 ± 0.002
3	13.99 ± 0.93	0.002 ± 0.001	0.017 ± 0.002
4	7.44 ± 0.53	Not Analyzed	Not Analyzed
5	4.71 ± 0.35	Not Analyzed	Not Analyzed
6	2.21 ± 0.20	0 ± 0.0002	0.001 ± 0.0005
7	2.87 ± 0.24	Not Analyzed	Not Analyzed
8	4.66 ± 0.35	Not Analyzed	Not Analyzed
9	10.63 ± 0.72	Low Recovery	Low Recovery
10	2.87 ± 0.24	Not Analyzed	Not Analyzed
11	9.12 ± 0.64	Not Analyzed	Not Analyzed
12	5.82 ± 0.43	Not Analyzed	Not Analyzed
13	4.60 ± 0.36	Not Analyzed	Not Analyzed
14	1.31 ± 0.14	Not Analyzed	Not Analyzed
15	2.71 ± 0.24	Not Analyzed	Not Analyzed
16	7.42 ± 0.53	Not Analyzed	Not Analyzed
17	6.71 ± 0.49	0.001 ± 0.001	0.016 ± 0.004

Note: Only those samples showing the highest levels of Cs-137 were analyzed for Pu-238 and Pu-239.

Note: "Low Recovery" indicates insufficient sample recovered during radiochemical separation.

Table 11-3
Radioactivity in Par Pond Sediment, Cont'd.

Samples Collected 8/15/91

Location	pCi/g		
	Cs-137	Pu-238	Pu-239
1	34.44 ± 2.19	0.002 ± 0.002	0.054 ± 0.007
2	28.26 ± 1.80	0.002 ± 0.001	0.027 ± 0.005
3	21.15 ± 1.36	Not Analyzed	Not Analyzed
4	15.21 ± 1.01	Not Analyzed	Not Analyzed
5	16.19 ± 1.05	Not Analyzed	Not Analyzed
6	13.80 ± 0.98	Not Analyzed	Not Analyzed
7	26.52 ± 1.70	Not Analyzed	Not Analyzed
8	42.03 ± 2.55	0.002 ± 0.002	0.034 ± 0.008
9	22.48 ± 1.45	Not Analyzed	Not Analyzed
10	26.08 ± 1.67	Not Analyzed	Not Analyzed
11	55.89 ± 3.35	0.005 ± 0.001	0.095 ± 0.005
12	18.24 ± 1.19	Not Analyzed	Not Analyzed
13	58.93 ± 3.54	0.011 ± 0.002	0.183 ± 0.007
14	1.25 ± 0.13	Not Analyzed	Not Analyzed
15	25.62 ± 1.64	Not Analyzed	Not Analyzed
16	1.99 ± 0.18	Not Analyzed	Not Analyzed
17	7.03 ± 0.50	Not Analyzed	Not Analyzed

Note: Only those samples showing the highest levels of Cs-137 were analyzed for Pu-238 and Pu-239.

Note: Gamma analysis indicated Co-60 at the following locations only:

Location 4: Co-60: 0.20 ± 0.05

Location 7: Co-60: 0.09 ± 0.05

Location 11: Co-60: 0.37 ± 0.06

Location 13: Co-60: 0.57 ± 0.08

Location 15: Co-60: 0.31 ± 0.05

Table 11-3
Radioactivity in Par Pond Sediment, Cont'd.

Samples Collected 9/4/91

Location	pCi/g		
	Cs-137	Pu-238	Pu-239
1	30.57 ± 1.88	0.002 ± 0.001	0.04 ± 0.005
2	15.88 ± 1.04	0.00 ± 0.001	0.01 ± 0.003
3	3.99 ± 0.31	Not Analyzed	Not Analyzed
4	4.30 ± 0.34	Not Analyzed	Not Analyzed
5	2.96 ± 0.25	Not Analyzed	Not Analyzed
6	7.23 ± 0.52	Not Analyzed	Not Analyzed
7	15.08 ± 1.01	0.003 ± 0.001	0.026 ± 0.004
8	78.56 ± 4.70	0.006 ± 0.003	0.068 ± 0.009
9	9.42 ± 0.65	Not Analyzed	Not Analyzed
10	15.28 ± 1.01	0.00 ± 0.001	0.014 ± 0.005
11	1.38 ± 0.12	Not Analyzed	Not Analyzed
12	11.37 ± 0.73	Not Analyzed	Not Analyzed
13	1.61 ± 0.14	Not Analyzed	Not Analyzed
14	1.29 ± 0.14	Not Analyzed	Not Analyzed
15	2.31 ± 0.18	Not Analyzed	Not Analyzed
16	4.08 ± 0.29	Not Analyzed	Not Analyzed
17	10.53 ± 0.67	Not Analyzed	Not Analyzed
Dam— North	4.92 ± 0.36	0.001 ± 0.001	0.007 ± 0.003
Dam— South	12.24 ± 0.83	0.001 ± 0.002	0.028 ± 0.007

Note: Only those samples showing the highest levels of Cs-137 were analyzed for Pu-238 and Pu-239.

Note: Gamma analysis indicated Co-60 at the following locations only:

Location 8: Co-60: 0.33 ± 0.06

Dam — South: Co-60: 0.18 ± 0.04

Table 11-3
Radioactivity in Par Pond Sediment, Cont'd.

Samples Collected 10/3/91

Location	pCi/g		
	Cs-137	Pu-238	Pu-239
1	7.75 ± 0.52	Not Analyzed	Not Analyzed
2	33.1 ± 2.02	0.002 ± 0.002	0.033 ± 0.006
3	10.8 ± 0.70	Not Analyzed	Not Analyzed
4	13.1 ± 0.83	Not Analyzed	Not Analyzed
5	15.9 ± 0.99	0.001 ± 0.001	0.020 ± 0.004
6	15.27 ± 1.02	Not Analyzed	Not Analyzed
7	14.1 ± 0.89	Not Analyzed	Not Analyzed
8	27.17 ± 1.75	0.001 ± 0.001	0.020 ± 0.003
9	12.4 ± 0.78	Not Analyzed	Not Analyzed
10	13.6 ± 0.87	Not Analyzed	Not Analyzed
11	135.5 ± 8.2	0.009 ± 0.004	0.22 ± 0.017
12	1.96 ± 0.16	Not Analyzed	Not Analyzed
13	0.72 ± 0.08	Not Analyzed	Not Analyzed
14	0.14 ± 0.04	Not Analyzed	Not Analyzed
15	7.00 ± 0.50	Not Analyzed	Not Analyzed
16	7.91 ± 0.56	Not Analyzed	Not Analyzed
17	71.94 ± 4.34	0.012 ± 0.002	0.015 ± 0.007

Note: Only those samples showing the highest levels of Cs-137 were analyzed for Pu-238 and Pu-239.

Note: Gamma analysis indicated Co-60 at the following locations only:

Location 2 : Co-60: 0.12 ± 0.02

Location 5: Co-60: 0.08 ± 0.02

Location 11: Co-60: 0.39 ± 0.05

Location 17: Co-60: 0.81 ± 0.06

Table 11-4
Radioactivity in Pond C Sediment

Location	pCi/g		
	Cs-137	Pu-238	Pu-239
1	5.47 ± 0.41	Not Analyzed	Not Analyzed
2	14.72 ± 0.98	Not Analyzed	Not Analyzed
3	26.83 ± 1.68	0.010 ± 0.004	0.140 ± 0.014
4	38.34 ± 2.35	0.006 ± 0.001	0.035 ± 0.003
5	38.54 ± 2.30	Low Recovery	Low Recovery

Note: Only those samples showing the highest levels of Cs-137 were analyzed for Pu-238 and Pu-239.

Note: "Low Recovery" indicates insufficient sample recovered during radiochemical separation.

Note: Gamma analysis indicated Co-60 at the following locations only:

Location 2: Co-60: 0.44 ± 0.07
 Location 3: Co-60: 0.68 ± 0.09
 Location 4: Co-60: 0.27 ± 0.06
 Location 5: Co-60: 0.36 ± 0.04

Table 11-5
Strontium in Par Pond and Pond C

Sr-89,90(pCi/g)			
Date	Location	Duplicate #1 ^a	Duplicate #2
Par Pond			
8/15	1	0.079 ± 0.112	0.195 ± 0.040
	2	0.013 ± 0.037	0.053 ± 0.044
	8	0.027 ± 0.038	0.036 ± 0.047
	11	0.058 ± 0.047	0.027 ± 0.039
	13	0.011 ± 0.036	0.038 ± 0.039
9/4	1	0.027 ± 0.039	0.034 ± 0.039
	2	0.031 ± 0.039	0.005 ± 0.035
	7	0.023 ± 0.041	0 ± 0.030
	8	0.067 ± 0.043	0.007 ± 0.034
	0	0.010 ± 0.036	0 ± 0.032
	Dam N	0 ± 0.034	0.032 ± 0.041
	Dam S	0.007 ± 0.037	0.015 ± 0.036
10/3	2	0.033 ± 0.035	0.041 ± 0.035
	5	0 ± 0.027	0.016 ± 0.031
	8	0.046 ± 0.037	0.111 ± 0.045
	1	0.126 ± 0.047	0.088 ± 0.043
	7	0.106 ± 0.043	0.050 ± 0.036
Sr-89,90 (pCi/g)			
Pond C			
7/30	3	0.053±0.026	
	4	0.25±0.060	
	5	0.078±0.031	

a A field sample is split to obtain the "duplicate" samples.

Table 11-6
Par Pond Penetrating Radiation Measurements

Location	July 28 and 30		August 15	
	Ground Level ($\mu\text{R/hr}$)	1 Meter ($\mu\text{R/hr}$)	Ground Level ($\mu\text{R/hr}$)	1 Meter ($\mu\text{R/hr}$)
Par Pond 1	5	2	11	9
Par Pond 2	4	1-2	14	12
Par Pond 3	3	1-2	12	11
Par Pond 4	4	1-2	11	11
Par Pond 5	3	1-2	10	8
Par Pond 6	3	1-2	6	6
Par Pond 7	3	1-2	14	12
Par Pond 8	5	1-2	17	17
Par Pond 9	4	1-2	15	14
Par Pond 10	3	1-2	7	6
Par Pond 11	5	1-2	9	9
Par Pond 12	3	1-2	9	7
Par Pond 13	4	1-2	10	7
Par Pond 14	4	1-2	7	7
Par Pond 15	3	1-2	11	11
Par Pond 16	4	1-2	12	10
Par Pond 17	2	1-2	9	7
Pond C 1	4	4	Not Sampled	Not Sampled
Pond C 2	22	12	Not Sampled	Not Sampled
Pond C 3	25	15	Not Sampled	Not Sampled
Pond C 4	30	15	Not Sampled	Not Sampled
Pond C 5	15	12	Not Sampled	Not Sampled
Location	September 4		October 3	
	Ground Level ($\mu\text{R/hr}$)	1 Meter ($\mu\text{R/hr}$)	Ground Level ($\mu\text{R/hr}$)	1 Meter ($\mu\text{R/hr}$)
Par Pond 1	9	8	11	14
Par Pond 2	12	9	17	15
Par Pond 3	10	9	18	17
Par Pond 4	14	2	13	12
Par Pond 5	5	4	11	19
Par Pond 6	4	2	9	8
Par Pond 7	8	8	10	9
Par Pond 8	25	21	25	25
Par Pond 9	10	7	12	9
Par Pond 10	10	7	14	11
Par Pond 11	7	9	14	13
Par Pond 12	13	13	13	13
Par Pond 13	7	7	13	12
Par Pond 14	5	3	11	10
Par Pond 15	10	6	21	19
Par Pond 16	10	7	20	21
Par Pond 17	13	10	17	23

Table 11-7
Mercury in Par Pond and Pond C Sediment

Sampling Date	Composite	Locations	Hg (mg/kg)
7/30/91	Pond C	1,2,3,4,5	<0.0001
8/15/91 (190 ft)	1	1,9,10,11,12	0.176
	2	2,3,4,6,7,8	0.051
	3	5,13,14,15,16,17	0.055
9/4/91 (185 ft)	1	1,9,10,11,12	<0.0001
	2	2,3,4,6,7,8	0.032
	3	5,13,14,15,16,17	0.040
	4	Old Mill Pond Dam	0.026

Table 11-8
Radioactivity in Biological Media

Date	Media	Cs-137	Co-60	Cs-134
8/9/91	Clams	0.67 ± 0.06	< 0.04	< 0.04
10/1/91	Hog1	14.28 ± 0.88	< 0.06	< 0.07
	Hog2	16.30 ± 1.00	< 0.07	< 0.07

NOTES:

Hog muscle samples were from different animals.

Hog1 Sample was muscle from the leg.

Hog2 Sample was muscle from various parts of the body.

Table 11-9
Radioactivity in Savannah River Swamp Soil – 1990

Trail	Distance from River (ft)	pCi/g		
		Cs-137	Co-60	Sr-89,90
1	0	12.73 ± 0.65	<LLD ^a	N/S ^b
	585	15.28 ± 0.77	<LLD	N/S
	1175	17.12 ± 1.07	0.10 ± 0.03	N/S
	1805	75.39 ± 3.26	<LLD	N/S
	2150 ^c	N/S	N/S	0.21 ± 0.06
	2150 ^d	48.70 ± 2.49	0.27 ± 0.05	0 ± 0.39
	2150 ^e	22.25 ± 1.41	<LLD	0.07 ± 0.06
	2150 ^f	10.97 ± 0.71	0.09 ± 0.03	0.04 ± 0.05
	2640	1.07 ± 0.10	<LLD	N/S
2	0	0.33 ± 0.05	<LLD	N/S
	680	1.11 ± 0.13	<LLD	N/S
	1330	N/S	N/S	N/S
	1960	N/S	N/S	N/S
	2620	2.07 ± 0.14	<LLD	N/S
	3100 ^c	N/S	N/S	0.09 ± 0.04
	3100 ^d	N/S	N/S	0.23 ± 0.06
	3100 ^e	14.86 ± 0.95	<LLD	0.10 ± 0.05
	3100 ^f	N/S	N/S	0 ± 0.03
	3200	1.62 ± 0.18	<LLD	N/S
3	0	N/S	N/S	N/S
	920 ^c	0.80 ± 0.12	<LLD	0.40 ± 0.39
	920 ^d	0.54 ± 0.09	<LLD	0.07 ± 0.46
	920 ^e	0.08 ± 0.03	<LLD	0.03 ± 0.04
	920 ^f	0.04 ± 0.02	<LLD	0.06 ± 0.04
	2055	<LLD	<LLD	N/S

a Nominal LLDs for each analysis are presented in Table 4-6.

b "N/S" indicates no sample analysis available.

c 0"- to 3"-deep core segment.

d 3"- to 6"-deep core segment.

e 6"- to 9"-deep core segment.

f 9"- to 12"-deep core segment.

Table 11-9
Radioactivity in Savannah River Swamp Soil – 1990, Cont'd.

Trail	Distance from River (ft)	pCi/g		
		Cs-137	Co-60	Sr-89,90
4	0	0.19 ± 0.04	<LLD ^a	N/S ^b
	960	10.23 ± 0.68	<LLD	N/S
	1245	26.08 ± 1.38	<LLD	N/S
	1690	27.21 ± 1.67	0.19 ± 0.04	N/S
	1900 ^c	92.21 ± 5.56	0.52 ± 0.05	0.14 ± 0.05
	1900 ^d	18.53 ± 1.20	0.13 ± 0.04	0.33 ± 0.07
	1900 ^e	10.55 ± 0.69	<LLD	0.24 ± 0.06
	1900	6.72 ± 0.46	<LLD	0.09 ± 0.04
	2390	1.04 ± 0.12	<LLD	N/S
5	0	N/S	N/S	N/S
	1750	21.62 ± 1.18	<LLD	0.16 ± 0.34
	1880	45.70 ± 2.35	0.26 ± 0.05	0.18 ± 0.27
	2100 ^c	58.15 ± 3.51	0.38 ± 0.05	0.19 ± 0.05
	2100 ^d	37.12 ± 2.27	0.29 ± 0.04	0.26 ± 0.06
	2100 ^e	15.87 ± 1.05	<LLD	0.19 ± 0.05
	2100 ^f	10.10 ± 0.61	<LLD	0 ± 0.43
	2535	1.21 ± 0.13	<LLD	0 ± 0.42
6	0	0.74 ± 0.11	<LLD	N/S
	1800	10.51 ± 0.67	<LLD	N/S
	2300	56.40 ± 3.33	0.12 ± 0.02	N/S
	2530 ^c	41.36 ± 2.45	0.21 ± 0.03	0.10 ± 0.04
	2530 ^d	59.42 ± 3.04	0.25 ± 0.06	0.05 ± 0.43
	2530 ^e	13.34 ± 0.77	<LLD	0 ± 0.33
	2530 ^f	2.57 ± 0.19	<LLD	0.03 ± 0.04
	2680	1.35 ± 0.16	<LLD	N/S

a Nominal LLDs for each analysis are presented in Table 4-6.

b "N/S" indicates no sample analysis available.

c 0"- to 3"-deep core segment.

d 3"- to 6"-deep core segment.

e 6"- to 9"-deep core segment.

f 9"- to 12"-deep core segment.

Table 11-9
Radioactivity in Savannah River Swamp Soil – 1990, Cont'd.

Trail	Distance from River (ft)	pCi/g		
		Cs-137	Co-60	Sr-89,90
7	0	0.46 ± 0.07	<LLD ^a	N/S ^b
	1900	3.93 ± 0.28	<LLD	N/S
	2600	35.66 ± 1.59	0.13 ± 0.03	N/S
	2700 ^c	29.86 ± 1.35	<LLD	0.03 ± 0.04
	2700 ^d	11.09 ± 0.68	<LLD	0 ± 0.37
	2700 ^e	7.75 ± 0.50	<LLD	0.09 ± 0.39
	2700 ^f	4.44 ± 0.33	<LLD	0.11 ± 0.42
	3100	7.86 ± 0.38	<LLD	N/S
	3200	1.38 ± 0.12	<LLD	N/S
8	0	0.24 ± 0.05	<LLD	N/S
	550	1.84 ± 0.17	<LLD	N/S
	915	1.17 ± 0.13	<LLD	N/S
	1460	1.42 ± 0.14	<LLD	N/S
	2005	N/S	N/S	N/S
	2670	14.72 ± 0.71	<LLD	N/S
	2900 ^c	66.43 ± 2.88	<LLD	0.08 ± 0.04
	2900 ^d	23.45 ± 1.25	<LLD	0.01 ± 0.43
	2900 ^e	9.52 ± 0.56	<LLD	0.81 ± 0.51
	2900 ^f	3.95 ± 0.28	<LLD	0 ± 0.39
	3000	0.22 ± 0.05	<LLD	N/S
9	0	0.39 ± 0.05	<LLD	N/S
	1680	25.83 ± 1.19	<LLD	N/S
	2035	20.77 ± 1.00	<LLD	N/S
	2200 ^c	61.48 ± 3.13	0.22 ± 0.05	0.17 ± 0.43
	2200 ^d	43.12 ± 2.23	0.19 ± 0.05	0.35 ± 0.42
	2200 ^e	16.65 ± 0.92	<LLD	0 ± 0.37
	2200 ^f	8.50 ± 0.42	<LLD	0.04 ± 0.04
	2525	0.88 ± 0.07	<LLD	N/S

a Nominal LLDs for each analysis are presented in Table 4.-6

b "N/S" indicates no sample analysis available.

c 0"- to 3"-deep core segment.

d 3"- to 6"-deep core segment.

e 6"- to 9"-deep core segment.

f 9"- to 12"-deep core segment.

Table 11-9
Radioactivity in Savannah River Swamp Soil – 1990, Cont'd.

Trail	Distance from River (ft)	pCi/g		
		Cs-137	Co-60	Sr-89,90
10	0	19.34 ± 1.24	<LLD ^a	N/S ^b
	100 ^c	19.14 ± 0.86	0.08 ± 0.02	0.06 ± 0.04
	100 ^d	16.15 ± 1.04	<LLD	0.08 ± 0.05
	100 ^e	8.02 ± 0.49	<LLD	0 ± 0.39
	100 ^f	1.52 ± 0.15	<LLD	0.75 ± 0.41
	240	1.55 ± 0.13	<LLD	N/S

a Nominal LLDs for each analysis are presented in Table 4-6.

b "N/S" indicates no sample analysis available.

c 0"- 3" deep core segment

d 3"- 6" deep core segment

e 6"- 9" deep core segment

f 9"- 12" deep core segment

Table 11-10
Radioactivity in Savannah River Swamp Vegetation – 1990

Trail	Distance from River (ft)	pCi/g $\pm \sigma$ (dry weight)		
		Cs-137	Co-60	Sr-89,90
1	0	N/S ^a	N/S	N/S
	585	N/S	N/S	N/S
	1175	0.72 $\pm$ 0.15	<LLD ^b	4.62 $\pm$ 0.57
	1805	6.62 $\pm$ 0.53	<LLD	1.21 $\pm$ 0.29
	2150	15.07 $\pm$ 0.92	0.15 $\pm$ 0.05	0.16 $\pm$ 0.18
	2640	<LLD	<LLD	0.57 $\pm$ 0.23
2	0	N/S	N/S	0.17 $\pm$ 0.18
	680	<LLD	<LLD	0.41 $\pm$ 0.24
	1330	0.42 $\pm$ 0.13	<LLD	10.9 $\pm$ 0.68
	1960	<LLD	<LLD	0.27 $\pm$ 0.16
	2620	1.34 $\pm$ 0.21	<LLD	0.29 $\pm$ 0.20
	3100	N/S	N/S	0.65 $\pm$ 0.27
	3200	N/S	N/S	0.40 $\pm$ 0.17
3	0	0.16 $\pm$ 0.08	<LLD	0.18 $\pm$ 0.21
	920	<LLD	<LLD	0.25 $\pm$ 0.19
	2055	<LLD	<LLD	0.53 $\pm$ 0.23
4	0	0.18 $\pm$ 0.05	<LLD	0.38 $\pm$ 0.21
	960	0.80 $\pm$ 0.15	<LLD	10.3 $\pm$ 0.73
	1245	2.08 $\pm$ 0.32	<LLD	1.92 $\pm$ 0.36
	1690	2.85 $\pm$ 0.40	<LLD	0.03 $\pm$ 0.15
	1900	11.08 $\pm$ 0.92	<LLD	0.32 $\pm$ 0.24
	2390	<LLD	<LLD	0.27 $\pm$ 0.19
5	0	N/S	N/S	1.16 $\pm$ 0.32
	1750	0.71 $\pm$ 0.14	<LLD	0.44 $\pm$ 0.24
	1880	4.86 $\pm$ 0.53	<LLD	2.25 $\pm$ 0.38
	2100	1.39 $\pm$ 0.21	<LLD	0.46 $\pm$ 0.22
	2535	<LLD	<LLD	0.40 $\pm$ 0.21
6	0	0.12 $\pm$ 0.07	<LLD	0.28 $\pm$ 0.20
	1800	N/S	N/S	N/S
	2300	N/S	N/S	N/S

a *N/S" indicates no sample analysis is available.

b Nominal LLDs for each analysis are presented in Table 4-6.

Table 11-10
Radioactivity in Savannah River Swamp Vegetation – 1990, Cont'd.

Trail	Distance from River (ft)	pCi/g $\pm \sigma$ (dry weight)		
		Cs-137	Co-60	Sr-89,90
7	2530	4.46 $\pm$ 0.40	<LLD	0.70 $\pm$ 0.25
	2680	<LLD	<LLD	1.28 $\pm$ 0.30
	0	<LLD ^a	<LLD	0.33 $\pm$ 0.20
	1900	N/S ^b	N/S	N/S
	2600	N/S	N/S	N/S
	2700	N/S	N/S	N/S
	3100	1.91 $\pm$ 0.25	<LLD	0.48 $\pm$ 0.28
	3200	0.30 $\pm$ 0.07	<LLD	0.51 $\pm$ 0.23
8	0	<LLD	<LLD	N/S
	550	<LLD	<LLD	0.90 $\pm$ 0.30
	915	<LLD	<LLD	0.46 $\pm$ 0.22
	1460	0.33 $\pm$ 0.11	<LLD	0.31 $\pm$ 0.23
	2005	N/S	N/S	N/S
	2670	N/S	N/S	N/S
	2900	5.35 $\pm$ 0.44	<LLD	0.28 $\pm$ 0.17
	3000	0.32 $\pm$ 0.09	<LLD	0.65 $\pm$ 0.24
9	0	<LLD	<LLD	0.52 $\pm$ 0.23
	1680	N/S	N/S	N/S
	2035	N/S	N/S	N/S
	2200	13.35 $\pm$ 0.91	<LLD	0.52 $\pm$ 0.23
	2525	<LLD	<LLD	0.55 $\pm$ 0.26
10	0	0.55 $\pm$ 0.17	<LLD	1.19 $\pm$ 0.33
	100	0.54 $\pm$ 0.13	<LLD	0.26 $\pm$ 0.19
	240	0.15 $\pm$ 0.07	<LLD	0.26 $\pm$ 0.18

a Nominal LLDs for each analysis are presented in Table 4-6.

b "N/S" indicates no sample analysis is available

Table 11-11
Savannah River Swamp MicroR Measurements – 1990

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
1	0	W	W
	100	W	W
	200	W	W
	300	W	W
	400	W	W
	500	W	W
	585	W	W
	600	W	W
	700	W	W
	800	W	W
	830	13	10
	900	16	13
	1000	13	11
	1100	12	9
	1175	9	6
	1200	W	W
	1300	W	W
	1400	W	W
	1500	W	W
	1600	W	W
	1700	W	W
	1800	W	W
	1805	23	21
	1900	W	W
	2000	W	W
	2100	W	W
	2150	40	30
	2200	30	30
	2300	16	14
	2400	5	5
	2500	4	4
	2600	4	4
	2640	5	5
2	0	7	8
	100	8	6

"W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
2, cont'd.	200	5	5
	300	10	7
	400	6	8
	500	9	7
	600	8	8
	680	6	7
	700	8	7
	800	7	7
	900	8	7
	1000	8	7
	1100	8	8
	1200	8	8
	1300	6	8
	1330	8	7
	1400	7	7
	1500	8	6
	1600	8	6
	1700	6	9
	1800	6	7
	1900	7	8
	1960	7	7
	2000	8	8
	2100	9	8
	2200	10	10
	2300	10	7
	2400	10	9
	2500	8	8
	2600	10	8
	2620	8	8
	2700	12	9
	2800	W	W
	2900	W	W
	3000	W	W
	3100	21	14
	3200	5	5

"W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
3	0	9	7
	100	11	10
	200	10	10
	300	10	10
	400	11	10
	500	W	W
	600	W	W
	700	W	W
	800	11	11
	900	13	11
	920	12	10
	1000	11	10
	1100	W	W
	1200	W	W
	1300	11	10
	1400	12	9
	1500	11	9
	1600	11	10
	1700	10	10
	1800	10	10
	1900	10	10
	2000	10	8
	2055	10	10
4	0	8	7
	100	7	5
	200	6	7
	300	W	W
	400	W	W
	500	W	W
	600	W	W
	700	W	W
	800	W	W
	900	W	W
	960	W	W
	1000	W	W

"W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
4, cont'd.	1100	W	W
	1200	W	W
	1245	W	W
	1300	W	W
	1400	W	W
	1500	W	W
	1600	W	W
	1690	W	W
	1700	W	W
	1800	W	W
	1900	60	55
	2000	60	50
	2100	22	22
	2200	21	22
	2300	11	10
	2390	9	8
5	0	15	15
	100	14	14
	200	13	12
	300	14	13
	400	13	12
	500	15	14
	600	14	14
	700	20	18
	800	14	13
	900	17	14
	1000	15	15
	1100	17	17
	1200	18	18
	1300	17	16
	1400	18	18
	1500	15	13
	1600	15	15
	1700	20	20
	1750	19	19

"W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
5, cont'd.	1800	W	W
	1880	23	22
	1900	50	40
	2000	W	W
	2100	130	90
	2200	120	80
	2300	W	W
	2400	50	40
	2500	15	15
	2535	15	14
6	0	2	2
	100	140	110
	200	10	10
	300	9	9
	400	W	W
	500	2	2
	600	2	2
	700	2	2
	800	2	2
	900	1	1
	1000	W	W
	1100	W	W
	1200	W	W
	1300	W	W
	1400	W	W
	1500	W	W
	1600	W	W
	1700	W	W
	1800	W	W
	1900	W	W
	2000	W	W
	2100	W	W
	2200	W	W
	2300	W	W
	2400	W	W

"W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
6, cont'd.	2500	W	W
	2530	7	6
	2600	3	2
	2680	1	1
7	0	4	4
	100	5	5
	200	W	W
	300	6	6
	400	5	5
	500	5	5
	600	6	6
	700	4	4
	800	5	5
	900	W	W
	1000	W	W
	1100	W	W
	1200	W	W
	1300	6	6
	1400	3	3
	1500	W	W
	1600	W	W
	1700	W	W
	1800	W	W
	1900	W	W
	2000	W	W
	2100	W	W
	2200	W	W
	2300	W	W
	2400	W	W
	2500	W	W
	2600	W	W
	2800	W	W
	2900	W	W
	3000	W	W
	3100	2	2

"W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
7, cont'd.	3200	2	2
8	0	7	7
	100	4	4
	200	6	6
	300	5	5
	400	2	2
	500	5	5
	550	5	5
	600	5	5
	700	5	5
	800	4	4
	900	4	4
	915	W	W
	1000	W	W
	1100	5	5
	1200	3	3
	1300	5	5
	1400	5	5
	1460	5	5
	1500	5	5
	1600	W	W
	1700	W	W
	1800	W	W
	1900	W	W
	2005	W	W
	2100	W	W
	2200	W	W
	2300	W	W
	2400	W	W
	2500	W	W
	2600	W	W
	2670	W	W
	2700	W	W
	2800	W	W
	2900	0	0

*W" indicates the location was underwater during the survey.

Table 11-11
Savannah River Swamp MicroR Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (uR/hr)	
		Ground Level	1 m
8, cont'd.	3000	0	0
9	0	6	6
	100	5	5
	200	4	4
	300	W	W
	400	W	W
	500	W	W
	600	6	6
	700	5	5
	800	6	6
	900	5	5
	1000	W	W
	1100	W	W
	1200	W	W
	1300	W	W
	1400	W	W
	1500	W	W
	1600	W	W
	1680	W	W
	1700	W	W
	1800	W	W
	1900	W	W
	2000	W	W
	2035	W	W
	2100	W	W
	2200	W	W
	2300	14	14
	2400	W	W
	2500	3	3
	2525	4	4
10	0	W	W
	100	13	13
	200	4	4
	240	3	3

"W" indicates the location was underwater during the survey.

Table 11-12
Savannah River Swamp TLD Exposure Measurements – 1990

Trail	Distance from River (ft)	Exposure Rate (mR/day)
1	1175	0.31 ± 0.06
	1805	0.52 ± 0.09
	2150	0.59 ± 0.11
	2640	0.10 ± 0.02
2	0	0.16 ± 0.03
	680	0.18 ± 0.03
	1330	0.17 ± 0.03
	1960	0.18 ± 0.03
	2620	0.21 ± 0.04
	3100	0.33 ± 0.06
	3200	0.12 ± 0.02
3	0	0.18 ± 0.03
	920	0.16 ± 0.03
	2055	0.12 ± 0.02
4	0	0.16 ± 0.03
	960	0.18 ± 0.03
	1245	0.25 ± 0.05
	1690	0.22 ± 0.04
	1900	0.45 ± 0.08
	2390	0.17 ± 0.03
5	0	0.16 ± 0.03
	1750	0.19 ± 0.03
	1880	0.31 ± 0.06
	2100	0.55 ± 0.10
	2535	0.16 ± 0.03
6	0	0.22 ± 0.04
	2300	0.30 ± 0.05
	2530	0.45 ± 0.08
	2680	0.25 ± 0.04
7	0	0.21 ± 0.04
	3100	0.29 ± 0.05
	3200	0.24 ± 0.04
8	0	0.20 ± 0.04
	550	0.26 ± 0.05

Table 11-12
Savannah River Swamp TLD Exposure Measurements – 1990, Cont'd.

Trail	Distance from River (ft)	Exposure Rate (mR/day)
	915	0.21 ± 0.04
	1460	0.23 ± 0.04
	2900	0.46 ± 0.08
	3000	0.23 ± 0.04
9	0	0.22 ± 0.04
	2205	0.40 ± 0.07
	2525	0.20 ± 0.04
10	0	0.26 ± 0.05
	100	0.29 ± 0.05
	240	0.21 ± 0.04

Table 11-13
Comparison of TLD and MicroR Measurements
in the Savannah River Swamp – 1990

Trail	Distance from River (ft)	mR/day	
		TLD Measurement	MicroR Measurement
1	0	0.15	0.31
2	0	0.17	0.17
	3100	0.29	0.62
	3200	0.12	0.12
3	0	0.13	0.17
4	0	0.14	0.17
	1900	0.44	0.72
	2390	0.19	0.17
5	0	0.17	0.19
	2100	0.58	0.72
6	1800	0.23	0.17
	2300	0.27	0.36
	2530	0.39	0.60
7	0	0.21	0.19
	1900	0.17	0.12
	3100	0.29	0.29
	3200	0.23	0.17
8	0	0.18	0.14
	2900	0.40	0.41
	3000	0.21	0.17
9	0	0.20	0.17
	2200	0.30	0.48
10	0	0.21	0.17
	100	0.24	0.29
	240	0.20	0.14

Table 11-14
Radioactivity in Savannah River Swamp Soil – 1991

Trail	Distance from River (ft)	pCi/g		
		Cs-137	Co-60	Sr-89,90
1	2150	13.84 ± 0.92	<LLD ^a	0.02 ± 0.02
2	3100	1.05 ± 0.12	<LLD	0.02 ± 0.03
3	920	2.61 ± 0.22	<LLD	0.03 ± 0.03
4	1900	76.02 ± 4.65	0.31 ± 0.05	0.03 ± 0.02
6	2530	66.82 ± 4.04	0.14 ± 0.03	0.01 ± 0.03
7	2700	277.36 ± 22.66	1.01 ± 0.27	0.03 ± 0.03
8	2900	68.03 ± 4.09	0.14 ± 0.03	0.02 ± 0.03
9	2200	36.63 ± 2.32	0.15 ± 0.03	0.06 ± 0.04
10	100	22.44 ± 1.42	<LLD	0.02 ± 0.03

^a Nominal LLDs for each analysis are presented in Table 4-6.

Table 11-15
Radioactivity in Savannah River Swamp Vegetation – 1991

Trail	Distance From River (ft)	pCi/g		
		Cs-137	Co-60	Sr-89,90
1	2150	0.40 ± 0.19	<LLD ^a	0.52 ± 0.20
2	3100	<LLD	<LLD	0.02 ± 0.09
3	920	<LLD	<LLD	0.24 ± 0.13
4	1900	5.73 ± 0.48	<LLD	0.34 ± 0.13
6	2530	17.63 ± 1.28	<LLD	0.97 ± 0.25
7	2700	N/S ^b	N/S	0.25 ± 0.12
8	2900	2.29 ± 0.27	<LLD	0.18 ± 0.12
9	2200	7.21 ± 0.69	<LLD	0.24 ± 0.11
10	100	10.73 ± 0.80	<LLD	0.24 ± 0.12

a Nominal LLDs for each analysis are presented in Table 4-6.

b "N/S" indicates no sample analysis available.

Table 11-16
Savannah River Swamp TLD Exposure Measurements – 1991

Trail	Distance from River (ft)	Exposure Rate (mR/day)	Trail	Distance from River (ft)	Exposure Rate (mR/day)
1	0	0.18 ± 0.03	6	0	0.17 ± 0.03
	585	0.20 ± 0.04		1800	0.15 ± 0.03
	1175	0.34 ± 0.06		2300	0.22 ± 0.04
	1805	0.55 ± 0.10		2530	0.34 ± 0.06
	2150	0.61 ± 0.11		2680	0.17 ± 0.03
	2640	0.11 ± 0.02	7	0	0.15 ± 0.03
2	0	0.16 ± 0.03		1900	0.13 ± 0.02
	680	0.17 ± 0.03		2600	0.15 ± 0.03
	1330	0.18 ± 0.03		2700	0.18 ± 0.03
	1960	0.21 ± 0.04		3100	0.22 ± 0.04
	2620	0.21 ± 0.04		3200	0.15 ± 0.03
	3100	0.36 ± 0.06	8	0	0.15 ± 0.03
	3200	0.15 ± 0.03		550	0.21 ± 0.04
3	0	0.16 ± 0.03		915	0.17 ± 0.03
	920	0.19 ± 0.03		1460	0.15 ± 0.03
	2055	0.13 ± 0.02		2005	0.15 ± 0.03
4	0	0.18 ± 0.03		2670	0.12 ± 0.02
	960	0.20 ± 0.04		2900	0.43 ± 0.08
	1245	0.28 ± 0.05		3000	0.14 ± 0.02
	1690	0.23 ± 0.04	9	0	0.16 ± 0.03
	1900	0.49 ± 0.09		1680	0.19 ± 0.03
	2390	0.18 ± 0.03		2035	0.21 ± 0.04
5	0	0.17 ± 0.03		2205	0.33 ± 0.06
	1750	0.19 ± 0.03		2525	0.13 ± 0.02
	2535	0.16 ± 0.03	10	0	0.21 ± 0.04
				100	0.24 ± 0.04
				240	0.13 ± 0.02

Table 11-17
Plutonium Results from Four Mile Creek Survey

Date	Location	Sample Type	pCi/g			
			Pu-239	CT ERR	Pu-238	CT ERR
04/19/90	1 NW Highground ^a	Plug	b			
04/19/90	1 NW Floodplain	Plug	0.0580	±0.0050	0.0125	±0.0024
04/19/90	1 NW Bank	Plug				
04/19/90	1 SE Bank	Plug	0.0260	±0.0013	0.0040	±0.0006
04/19/90	1 SE Floodplain	Plug	0.0130	±0.0047	0.0020	±0.0032
04/19/90	1 SE Highground	Plug				
04/19/90	1 SE Highground	Core 0-9	0.0033	±0.0007	0.0011	±0.0004
04/19/90	1 SE Highground	Core 9+	0.0003	±0.0002	0.0002	±0.0002
04/19/90	1 SE Floodplain	Core 0-9	0.0000	±0.0021	0.0000	±0.0033
04/19/90	1 SE Floodplain	Core 9+	0.0000	±0.0000	0.0010	±0.0033
04/19/90	1 Stream Bed	Core 0-9	0.0020	±0.0009	0.0015	±0.0011
04/19/90	1 Stream Bed	Core 9+	0.0000	±0.0001	0.0001	±0.0002
04/26/90	2 NW Highground	Plug	0.1230	±0.0075	0.0460	±0.0046
04/26/90	2 NW Floodplain	Plug	0.0070	±0.0020	0.0190	±0.0039
04/26/90	2 NW Bank	Plug	0.0710	±0.0045	1.3650	±0.0197
04/26/90	2 SE Bank	Plug	0.0130	±0.0026	0.3870	±0.0139
04/26/90	2 SE Floodplain	Plug	0.0840	±0.0071	0.7520	±0.0211
04/26/90	2 SE Highground	Plug	0.0160	±0.0023	0.0070	±0.0015
04/26/90	2 SE Highground	Core 0-9	0.0540	±0.0087	0.0130	±0.0044
04/26/90	2 SE Highground	Core 9+	0.0000	±0.0010	0.0010	±0.0130
04/26/90	2 SE Floodplain	Core 0-9	0.0250	±0.0024	0.5270	±0.0108
04/26/90	2 SE Floodplain	Core 9+	0.0000	±0.0007	0.0020	±0.0012
04/26/90	2 SE Bank	Core 0-9	0.0380	±0.0042	1.0610	±0.0220
04/26/90	2 SE Bank	Core 9+	0.0330	±0.0046	0.0750	±0.0071
04/26/90	2 Stream Bed	Core 0-9	0.0090	±0.0080	0.0960	±0.0059
05/02/90	3 NW Highground	Plug	0.0110	±0.0015	0.0110	±0.0014
05/02/90	3 NW Floodplain	Plug	1.2980	±0.0190	1.7840	±0.0220
05/02/90	3 NW Bank	Plug	0.9310	±0.0244	1.0440	±0.0258
05/02/90	3 SE Bank	Plug	0.6760	±0.0352	2.6790	±0.0701
05/02/90	3 SE Floodplain	Plug	0.4650	±0.0012	2.0470	±0.0213
05/02/90	3 SE Highground	Plug	0.0500	±0.0031	0.0180	±0.0019
05/02/90	3 SE Highground	Core 0-9	0.0080	±0.0031	0.0040	±0.0023
05/02/90	3 SE Highground	Core 9+	0.0050	±0.0017	0.0140	±0.0025
05/02/90	3 SE Floodplain	Core 0-9	0.1940	±0.0081	1.2710	±0.0208

a Trail sampling locations along Four Mile Creek are numbered 1 through 7.

b Blank spaces indicate samples were not analyzed.

Table 11-17
Plutonium Results from Four Mile Creek Survey, Cont'd.

Date	Location	Sample Type	pCi/g			
			Pu-239	CT ERR	Pu-238	CT ERR
05/02/90	3 SE Floodplain ^a	Core 9+	0.0010	±0.0013	0.0050	±0.0027
05/02/90	3 SE Bank	Core 0-9	0.0100	±0.0021	0.0270	±0.0036
05/02/90	3 Stream Bed	Core 0-9	0.1520	±0.0096	0.8550	±0.0022
05/02/90	3 Stream Bed	Core 9+	0.0020	±0.0008	0.0070	±0.0015
05/11/90	4 NW Highground	Plug	0.0450	±0.0039	0.0140	±0.0023
05/11/90	4 NW Floodplain	Plug	0.0660	±0.0064	0.2030	±0.0113
05/11/90	4 NW Bank	Plug	0.2900	±0.0123	0.9500	±0.0224
05/11/90	4 SE Bank	Plug	0.8640	±0.0298	2.5260	±0.0510
05/11/90	4 SE Floodplain	Plug	b			
05/11/90	4 SE Highground	Plug				
05/11/90	4 SE Highground	Core 0-9	0.0060	±0.0011	0.0030	±0.0008
05/11/90	4 SE Highground	Core 9+	0.0000	±0.0003	0.0290	±0.0006
05/11/90	4 SE Floodplain	Core 0-9	0.0280	±0.0042	0.0640	±0.0063
05/11/90	4 SE Floodplain	Core 9+				
05/11/90	4 SE Bank	Core 0-9	0.1350	±0.0075	0.4520	±0.0138
05/11/90	4 SE Bank	Core 9+				
05/11/90	4 Stream Bed	Core 0-9	0.0370	±0.0043	0.0530	±0.0052
05/11/90	4 Stream Bed	Core 9+	0.0140	±0.0020	0.0150	±0.0021
05/16/90	5 NW Highground	Plug	0.0940	±0.0051	0.0330	±0.0030
05/16/90	5 NW Floodplain	Plug	0.0630	±0.0042	0.0440	±0.0035
05/16/90	5 NW Bank	Plug	0.0120	±0.0017	0.0260	±0.0026
05/16/90	5 SE Bank	Plug	0.0180	±0.0022	0.0080	±0.0015
05/16/90	5 SE Floodplain	Plug	0.0030	±0.0014	0.0070	±0.0020
05/16/90	5 SE Highground	Plug				
05/16/90	5 SE Highground	Core 0-9	0.0060	±0.0015	0.0060	±0.0015
05/16/90	5 SE Highground	Core 9+				
05/16/90	5 SE Floodplain	Core 0-9	0.0080	±0.0028	0.0030	±0.0021
05/16/90	5 SE Floodplain	Core 9+				
05/16/90	5 SE Bank	Core 0-9				
05/16/90	5 SE Bank	Core 9+	0.0340	±0.0034	0.0730	±0.0050
05/16/90	5 Stream Bed	Core 0-9				
05/16/90	5 Stream Bed	Core 9+				
05/17/90	6 NW Highground	Plug	0.0110	±0.0019	0.0040	±0.0012
05/17/90	6 NW Floodplain	Plug	0.0340	±0.0051	0.0550	±0.0064

a Trail sampling locations along Four Mile Creek are numbered 1 through 7.

b Blank spaces indicate samples were not analyzed.

Table 11-17
Plutonium Results from Four Mile Creek Survey, Cont'd.

Date	Location	Sample Type	pCi/g			
			Pu-239	CT ERR	Pu-238	CT ERR
05/17/90	6 NW Bank ^a	Plug	0.0580	±0.0046	0.1270	±0.0069
05/17/90	6 SE Bank	Plug	0.0650	±0.0037	0.1640	±0.0059
05/17/90	6 SE Floodplain	Plug	0.0155	±0.0002	0.0027	±0.0007
05/17/90	6 SE Highground	Plug	0.0050	±0.0012	0.0020	±0.0008
05/17/90	6 SE Highground	Core 0-9	0.0010	±0.0006	0.0010	±0.0007
05/17/90	6 SE Highground	Core 9+	b			
05/17/90	6 SE Floodplain	Core 0-9				
05/17/90	6 SE Floodplain	Core 9+				
05/17/90	6 SE Bank	Core 0-9				
05/17/90	6 SE Bank	Core 9+				
05/17/90	6 Stream Bed	Core 0-9				
05/17/90	6 Stream Bed	Core 9+	0.0010	±0.0003	0.0000	±0.0002
05/24/90	7 NW Highground	Plug	0.0310	±0.0025	0.0040	±0.0010
05/24/90	7 NW Floodplain	Plug	0.1040	±0.0056	0.0110	±0.0018
05/24/90	7 NW Bank	Plug	0.0300	±0.0021	0.0240	±0.0019
05/24/90	7 SE Bank	Plug	0.0540	±0.0055	0.0850	±0.0069
05/24/90	7 SE Floodplain	Plug	0.0070	±0.0014	0.0010	±0.0006
05/24/90	7 SE Highground	Plug	0.0230	±0.0037	0.0050	±0.0019
05/24/90	7 SE Highground	Core 0-9	0.0000	±0.0001	0.0000	±0.0001
05/24/90	7 SE Highground	Core 9+	0.0010	±0.0004	0.0000	±0.0002
05/24/90	7 SE Floodplain	Core 0-9	0.0210	±0.0020	0.0040	±0.0009
05/24/90	7 SE Floodplain	Core 9+	0.0000	±0.0003	0.0000	±0.0003
05/24/90	7 SE Bank	Core 0-9	0.0290	±0.0040	0.0270	±0.0039
05/24/90	7 SE Bank	Core 9+	0.0000	±0.0001	0.0000	±0.0002
05/24/90	7 Stream Bed	Core 0-9				
05/24/90	7 Stream Bed	Core 9+	0.0010	±0.0005	0.0000	±0.0003

a Trail sampling locations along Four Mile Creek are numbered 1 through 7.

b Blank spaces indicate samples were not analyzed.

Chapter 12

To Learn About:	Turn to page:
♦ Remote-sensing studies	528
♦ Wetlands assessment	529
♦ Using microbes to clean up organic chemicals in soil and groundwater	530
♦ Studies of the Pen Branch geologic fault	532
♦ Groundwater modeling research	532
♦ Impact of K-Reactor pump testing on surface water quality and fish	534

Compiled by Dr. John B. Gladden
Savannah River Laboratory

Savannah River Laboratory

1991 HIGHLIGHTS

- ♦ SRL and other investigators developed and patented a process which uses algae (single-cell plants) to cost-effectively reduce the environmental effects of thermal and nutrient loading from the discharge of SRS cooling waters.
- ♦ Sitewide Geographic Information System landcover/landuse and soils databases were completed for SRS, and wetland subsets from these databases were prepared.
- ♦ A low-altitude aerial gamma survey covering more than 500 square miles of the site and nearby areas was conducted from October through December. These data will be incorporated into a sitewide gamma GIS database.
- ♦ Monitoring for total suspended solids in stream water and fisheries community changes was conducted during the year in the Indian Grave/Pen Branch drainage, in conjunction with the pump testing for K-Reactor cooling water. Comprehensive testing over about an eight-month period showed that pump testing increased values. Total numbers of fish and fish species were not affected by the increased flows.

INTRODUCTION

The Savannah River Laboratory (SRL), a research and development facility located in A Area, provides support to many onsite operations. Research activities conducted by SRL personnel cover a range of environmental areas, including dosimetry of Savannah River Site (SRS) operations, airborne and aqueous radionuclide effluent studies, activities to meet environmental permits or other requirements, and enhancement of emergency response capabilities.

This chapter summarizes many of the activities SRL conducted during 1991 in the general areas of environmental research, seismic and geoscience research, and operations support.

ENVIRONMENTAL RESEARCH PROJECTS

Status of L-Lake/Steel Creek Monitoring Program

L Lake was constructed in 1985 to receive the heated effluents from L Reactor. A biomonitoring program has been documenting the development of Balanced (Indigenous) Biological Communities (BBCs) in L Lake since January 1986. The studies have been conducted in support of L Reactor's thermal variance, per Section 316(a) of the Clean Water Act. L Lake continues to experience patterns of biological changes similar to other newly constructed basins with regard to water quality, macronutrients, phytoplankton, aquatic macrophytes, zooplankton, benthic macroinvertebrates, fish populations, and limnetic community succession. Several trends of biological community development in L Lake can be interpreted using current

models of lake ecosystem succession. "Bottom up" trophic dynamic models support hypotheses regarding nitrogen and light limitation of the phytoplankton, while the "top down" predator-prey model provides mechanisms that explain zooplankton size distributions and relative abundance, planktivore predation effects, and species succession in fish populations. Community components in L Lake exhibit all of the characteristics that justify BBCs for environmental compliance.

Par Pond Drawdown Evaluation and Monitoring Program

Par Pond water levels were lowered during the summer of 1991 to minimize the consequences in the event of a dam failure. A weekly sampling of vertical profiles of temperature, pH, and dissolved oxygen was initiated during the summer and continued until thermal destratification in the fall. The vertical distributions of these water quality parameters during and following the water-level drawdown were similar to those observed during other years. Dissolved-oxygen concentrations remained in excess of 4 mg/L throughout this period, confirming the reservoir's ability to support fish populations in the lake's mixed-surface layer. Periodic sampling will continue in 1992 during the period of thermal stratification.

Remote-sensing data, including videotaping, vertical and oblique photography, airborne multispectral scanner data, and aerial helicopter gamma surveys, were collected during and after the drawdown period. They will be used to assess both the drawdown's influence on the re-establishment of Par Pond's biological communities, and the distribution of man-made radionuclides, primarily Cs-137, within the lake.

In addition to the water quality sampling, biological communities have been monitored in Par Pond since January 1990. This sampling program, which includes measurements of phytoplankton, zooplankton, benthic invertebrates, aquatic plants, and fish, will continue in 1992.

Remote-Sensing Developments for Environmental Studies

During 1991, SRL conducted routine airborne multispectral scanner (MSS) and vertical and oblique photographic surveys for environmental monitoring and the assessment of wetlands and waste site closure projects, as well as for support of public and

facilities-mapping information. Sitewide Geographic Information System (GIS) landcover/landuse and soils databases were completed for SRS, and wetland subsets from these databases were prepared.

Also, to support environmental restoration activities at SRS, a low-altitude aerial gamma survey covering more than 500 square miles of the site and nearby areas was conducted from October through December 1991. These data will be incorporated into a sitewide gamma GIS database. Preparation of sitewide, historical aerial gamma survey GIS databases incorporating 1979-1989 gamma surveys continued. Completion of a manual catalogue for approximately 25,000 frames of vertical photography for SRS from 1958 to 1990 has been completed, primarily to support environmental restoration activities. Analysis of SPOT (a French earth observation satellite) data and development of GIS models for monitoring aquatic plant development along Par Pond's shoreline was completed for the spring and fall of 1988 through 1990. This analysis indicates that Par Pond aquatic plant growth has declined since the shutdown of P Reactor in 1988. In addition, aquatic plant growth data derived from historical photography of Par Pond from 1958 to 1990 indicate that planting aquatic vegetation around L Lake may have accelerated growth of aquatic vegetation in the lake by about 10 years, relative to the rate that would have been achieved by natural succession.

Biological Restoration of Lost Lake

An inter-organization task team under the leadership of SRL has developed a biological restoration plan for Lost Lake, a large Carolina bay at SRS. The plan was formed after the closure of the M-Area Settling Basin in 1989 and the resulting cessation of periodic overflows from the basin into Lost Lake. Non-flooded areas were seeded with grass and planted with a variety of wetland and terrestrial trees and shrubs. The Carolina bay was divided into eight concentric, pie-shaped zones, which received various forms of treatment, such as ripping, liming, and fertilization. Locally available aquatic vegetation species were introduced along the shoreline during the early spring of 1991 in study plots in six of the zones. Follow-up surveys during September 1991 indicate that reasonable survival and establishment of all the introduced species were realized, except for one species that will be reintroduced during early 1992. Aerial photographs and multispectral scanner data collected in the spring and fall of 1991 will be evaluated as a method for monitoring Lost Lake's wetlands re-vegetation.

Wetland vegetation survival and growth in Lost Lake was favorable in 1991, with many species flowering and producing seed.

SRS Wetlands Assessment

Airborne multispectral data for 1987 through 1991 continue to be studied for the Pen Branch corridor and delta area of SRS as part of the evaluation of potential wetland effects and restoration needs with the planned K-Reactor restart. Estimates of the acreage involved and wetland changes during that time period will be developed. In addition, field surveys of the hydrological responses and community types for the SRS forest swamp environment were conducted in 1991. Evaluation of SPOT satellite data for 1987 to 1991 for the Pen Branch delta area continues as a low-cost alternative for monitoring long-term wetland changes in this swamp environment.

Transport and Cycling of Tritium in the Environment

Because tritium accounts for about 85 percent of the SRS offsite radiation dose, SRS has a continuing

research program focusing on the environmental transport and cycling of tritium. In 1991, the results of a comprehensive assessment of tritium transport and dose were presented to an international audience at the Fourth Topical Meeting on Tritium Technology in Fission, Fusion, and Isotopic Applications in Albuquerque, N.M. This study's results show that tritium concentrations in the environment around SRS have approached a steady state. The concentration at the plant boundary in rainwater is about half that in atmospheric moisture. The low levels measured in the atmospheric moisture and rainwater are consistent with the levels of tritium found in streams and wells at the site boundary. The measurements support the accepted view that tritium is not accumulated or biomagnified in food chains—one reason for the relatively low risk to humans from tritium exposure. Studies of fish from Four Mile Creek, a tributary of the Savannah River inside the site boundary, indicate that aquatic plants and fish in the creek have reached equilibrium with the

What is a bioreactor?

A bioreactor is a large, enclosed tank used to provide an optimum environment for a desired biological process.

How does it work?

- ◆ Through the control of nutrients, temperature, pH, oxygen, flow rates, substratum, and other parameters, growth rates of microorganisms can be greatly accelerated.

What does it do?

- ◆ Bioreactors permit control of biological processes in such a way that reaction rates can be increased by thousands of times their rates in natural environments. Bioreactors allow such rapid biodegradation of contaminants in groundwater that very high flow rates (1,000 gallons per minute) can be used, even when the natural biodegradation rate is barely perceptible.

Other uses

- ◆ Bioreactors also are used to produce chemicals and antibiotics and remove metals.

creek water. No evidence of biomagnification was found in this aquatic system.

Bioremediation Research and Development

SRL scientists have been evaluating the use of natural soil microbes for degrading waste organic chemicals in soil and groundwater. An SRL-designed, prepared-bed bioreactor has received preliminary approval from the South Carolina Department of Health and Environmental Control (SCDHEC) and is under construction. The facility, which will treat surface soils contaminated with petroleum products (diesel fuel and gasoline), addresses an important problem for SRS, since the material can only be stored. There are 20,000 cubic yards of contaminated soils in storage, and 4,000 to 5,000 cubic yards are generated each year. Naturally occurring soil bacteria will be encouraged to completely degrade the petroleum contaminants in the soil by aeration and the addition of small amounts of fertilizer. Initially, the facility will run several batches of soil a year under different nutrient regimes proven to be effective in the laboratory, in order to optimize operating parameters for remediation.

Studies continue on methods for cleaning up trichloroethylene- and tetrachloroethylene-contaminated soil and groundwater. Operation of a pilot-scale (1 gpm), trickle-filter bioreactor for treatment of groundwater began after permit approval was received from SCDHEC. The reactor vessel was received from the U.S. Air Force and fitted to SRS conditions. Naturally occurring soil bacteria capable of using methane (natural gas) as their principal food have been isolated from SRS soils and established in similar bioreactors. These bacteria completely degrade trichloroethylene with the help of other bacteria. The system is being optimized to show treatment efficiency and cost effectiveness. SRL is completing construction of a similar trickle-filter bioreactor of its own design that is trailer mounted and can be tested at a variety of field sites. Design of a new, fluidized, expanded-bed system was completed in cooperation with the Gas Research Institute. This system will be installed in 1992.

SRL and Oak Ridge National Laboratory researchers have demonstrated the feasibility of using vegetation (such as pine trees and grasses) to remediate surface soils contaminated with chlorinated solvents. It has been shown that plant roots excrete nutrients used by solvent-degrading bacteria and fungi living in the soil around roots. Pine trees are particularly good for accelerating biodegradation of chlorinated solvents and do not translocate—or absorb—the contaminant into tissue. Greenhouse studies are complete, and field plot studies are awaiting SCDHEC permit approval.

Integrated Demonstration Project for Cleanup of Groundwater and Soil

Studies related to the cleanup of soils and groundwater contaminated with organics continue for the U.S. Department of Energy (DOE) Office of Technology Development. The program emphasizes use of emerging remediation, characterization, and monitoring technologies to improve the performance and efficiency of DOE's environmental restoration activities. During 1991, many technologies were demonstrated and transferred to the Environmental Restoration and Waste Management Programs. For example, the use of horizontal wells to improve environmental remediation systems was demonstrated and licensed for application by private companies. Evaluation of new photocatalytic vapor-phase organic treatment systems yielded promising results in 1991.

Post-test site characterization of the SRS *in situ* air stripping process was performed in 1991. This process utilizes two horizontal wells—one for injection of air below the water table and the other for vacuum

extraction above the water table. The process simultaneously cleans contaminated groundwater and the overlying soils. Data from the site characterization indicate that the process effectively performed these tasks. Several of the characterization and monitoring tests also were successful, and some have been incorporated into DOE's environmental restoration efforts.

During 1991, site preparation and permits were completed for the next major remediation demonstration: *in situ* bioremediation. Air containing a small amount of natural gas will be injected into the groundwater via a horizontal well below the water table. As in the *in situ* air-stripping test, a horizontal vacuum well above the water table will be used. In this case, the vacuum's primary purpose is to encourage air/methane flow through the groundwater and soil. Laboratory studies have shown that naturally occurring soil bacteria at this site have the ability to completely degrade the organic contaminants when given methane as a nutrient source. Thus, the test has been designed to enhance the natural cleansing capacity of the environment.

Uptake of Transuranic Elements in Burial Ground Trenches by Vegetation

This research is part of a program to assess the potential risk to people who might live on SRS at some point in the future. In 1991, pine needle samples were collected from trees planted over unlined earthen trenches containing low-level transuranic waste. Analyses indicate that the potential radiation dose from exposure to this type of vegetation is small.

SEISMIC AND GEOSCIENCE RESEARCH PROJECTS

Seismic Studies

Seismic evaluations and geoscience research studies at SRS intensified and diversified during 1990 and 1991. Seismic analysis and upgrades of critical facilities and system components are under way to ensure that they can survive a design-basis earthquake. Extensive geophysical data have been collected and are being evaluated from gravity, reflection-seismic, transient electromagnetic, and *in situ* stress measurements at the site. Geologic studies are under way to establish the site's basic framework in terms of the stratigraphic sequences and structures.

In March 1988, SRL initiated a comprehensive program to characterize seismic potential and

earthquake hazard in the SRS vicinity. The program's objective is to establish confidence in the seismic safety of existing and proposed SRS facilities by providing the basic data required for design and analysis. Program elements include:

- Monitoring site and regional seismicity through the SRS seismic network to identify source parameters, such as location, magnitude, depth, and mechanisms.
- Monitoring free-field (ground) and structural response to earthquake motions through the establishment of a site strong-motion network.
- Reviewing existing data and combining it with new data on the geology and seismicity of the region to establish seismic source zone and earthquake source mechanisms.
- Describing the seismicity in terms of occurrence and magnitude in the seismic zones.
- Developing an earthquake recurrence model for the region for specific seismic zones.
- Deriving or selecting a transfer function (attenuation relationship) to mathematically carry information from the epicenter to the site in terms of structurally relevant parameters.
- Integrating the data to determine the potential seismic activity of all sources for all earthquake magnitudes to determine the probability that a certain acceleration will not be exceeded within a given time period.

In support of this effort, specific geologic, geotechnical, and seismological programs have been completed or are ongoing. These include:

- The geologic investigations of several faults identified by seismic-reflection surveys and drilling on the site.
- Borehole *in situ* stress measurements.
- At-depth analysis of the influence of the Coastal Plain sedimentary wedge on strong ground motions.
- Gravity surveys of the site and surrounding area in South Carolina.

Probabilistic seismic-hazard analyses of the site were performed using the eastern U.S. data and methodology developed for the Nuclear Regulatory Commission (NRC) and commercial nuclear power plants. Facility-specific geotechnical investigations are being performed to determine the possibility for liquefaction and settlement. Work is under way to develop a

site-specific response spectra and to determine the effect of the deep-soil column on earthquake ground motion.

Pen Branch Fault Program

The Pen Branch Fault (Figure 12-1) was identified in the subsurface at SRS in 1989, based on interpretation of earlier seismic-reflection surveys and other geologic investigations. A program was initiated at that time to determine the capability of the fault to release seismic energy as defined in NRC guidelines, 10 CFR 100. Separate actions under this program include:

- Shallow drilling of Coastal Plain sediments with paired drill holes to bracket the Pen Branch Fault.
- Formation of the Earth Science Advisory Committee (ESAC) to provide independent program oversight.
- Design and initiation of the high-resolution, shallow, seismic-reflection survey.

The resulting geological and geophysical interpretations did not produce unequivocal conclusions; therefore, a quaternary investigation was initiated late in the summer of 1991, with a confirmatory drilling project scheduled for the spring of 1992 and studies of other faults planned for the future.

The confirmatory drilling project will involve the drilling of 18 boreholes distributed in a cross pattern over the fault and along a previously run seismic-reflection survey line. The boreholes will be no more than 70 feet apart. Two holes will go to the basement rock at a depth of approximately 1,000 feet. The other 16 holes will be drilled to about 300 feet to penetrate the Congaree Formation to establish an undisputed stratigraphic datum in the borehole. These boreholes will be cored and given a detailed geologic description. The U.S. Geological Survey (USGS) will provide a full suite of high-quality, down-hole geophysical logs. Seismic-wave velocity measurements will be taken in the two deep boreholes in Coastal Plain sediments and in the basement rock. These measurements will be used for ground motion and site response estimates.

The Quaternary investigation is designed to locate and identify Quaternary deposits and surfaces that may be used as strain gauges to assess or demonstrate the presence or absence of fault deformation that has occurred in a time span pertinent to hazard assessment. Field investigation will provide relative and, perhaps, absolute age estimates of Quaternary deposits. Detailed watershed and other tectono-geomorphic

analyses are being carried out to evaluate regional slope indications of the presence or absence of neotectonic deformation, focusing on the Pen Branch and Atta faults (Figure 12-1). Information gathered during this study will be integrated with other Pen Branch fault studies and ultimately with a geotechnical database to be used for subsequent geologic and geotechnical interpretations at SRS.

SRL has expanded the studies to refine the understanding of other geologic faults in the SRS vicinity. Seismic-reflection surveys completed in 1990 indicated several subsurface faults in the basement and Coastal Plain section within plant boundaries. Subsequent reprocessing of these data has yielded a clearer understanding of relative age and geometry of these faults. The Atta and Ellenton faults have been identified as areas of initial investigation.

Sitewide Hydrogeologic Investigations

An understanding of the groundwater structure and flow in the region of SRS is vital to protecting groundwater resources and minimizing offsite impacts of SRS operations. Aquifers and aquifer systems have been delineated by detailed analysis of data from geophysical logs and from more than 16,000 feet of core collected at 18 widely spaced localities on the site. Published geologic cross sections show the principal aquifers and aquitards underlying the SRS region. A new aquifer nomenclature scheme has been proposed for the hydrogeologic units. Water quality and isotopic data are being evaluated to determine the sources and fate of chemical constituents in the regional groundwater flow system. Radiometric-dating techniques applied to samples collected during this study indicate that the oldest groundwater beneath the site is about 10,000 years old.

Groundwater Modeling Program

During 1991, the groundwater modeling program provided support to numerous projects across the site. Modeling techniques were utilized to estimate de-watering requirements for the construction of the Modular High Temperature Gas-Cooled Reactor at SRS. Modeling techniques were utilized to develop and optimize monitoring and groundwater recovery well systems for the TNX, A, and M areas at SRS. Technical support was provided to the Environmental Restoration Department for the evaluation of contaminants in groundwater. A stochastic groundwater flow and transport code is being developed by SRL in conjunction with the South Carolina University Consortium.

Figure 12-1 Map pinpoints location of Pen Branch fault and other Savannah River Site basement faults.

SRL recently acquired computer hardware and software that has been used to apply three-dimensional imaging techniques to environmental studies at the site. Three-dimensional imaging is used to synthesize large, diverse data sets that may include geologic, geophysical, chemical, hydrologic, microbial, and modeling results into integrated models. The models are powerful visualization tools used to make improved decisions for environmental restoration at contaminated sites. In addition, volumes of contaminated material can be calculated easily from the models to estimate the level of effort required for remediation. Three-dimensional images have been completed for studies in M Area, the General Separations Area, Metallurgical Lab Basin, TNX, D-Area coal pile, and the Integrated Demonstration Site.

OPERATIONS SUPPORT PROJECTS

K-Reactor Flow Test Assessment

Pre-restart testing of K Reactor required that increased volumes of ambient-temperature cooling water be released from the reactor into the Indian Grave/Pen Branch drainage. Monitoring for total suspended solids

(TSS) and fishery community changes was conducted in the stream in conjunction with the K-Reactor cooling water pump testing during 1991. TSS data were combined with flow data recorded simultaneously by the USGS and rainfall data obtained by Westinghouse Savannah River Company (WSRC) to differentiate between flow effects attributable to pump testing and flow effects caused by natural factors, such as rainfall and runoff. Comprehensive testing over approximately an eight-month period at two locations in the Pen Branch system showed that pump testing increased TSS values. However, the resultant TSS values were rarely in excess of typical maximum TSS values monitored at various SRS outfalls. Also, occasional high TSS values occurred when no pump testing was being conducted—and were attributable to heavy rainfall. TSS monitoring results indicated that the K-Reactor pre-operational pump testing caused little or no deleterious environmental impact on the Pen Branch Creek system. Fishery studies indicated that while some individual species showed changes in relative abundance, the total numbers of fish and numbers of fish species in the stream were not affected by the increased flows.

To Learn About:	Turn to:
♦ Mercury studies in Upper Three Runs Creek	537
♦ Habitat mitigation for lost wetlands	537
♦ New Production Reactor pre-operational studies	539
♦ Research studies in wetlands ecology	539
♦ Research in remote-sensing techniques	540

Compiled by Dr. Carl L. Stojan
Savannah River Ecology Laboratory

Savannah River Ecology Laboratory

1991 HIGHLIGHTS

- ♦ A new laboratory was developed for applications involving remote-sensing geographic information systems. Initial efforts have centered on developing vegetation and habitat maps of the SRS. A laboratory also was completed for research in the ecology of microorganisms.
- ♦ New research efforts examined the ecological and radiological implications of water draw-down from the Par Pond reservoir.
- ♦ Pre-operational studies were begun to characterize baseline environmental conditions at the proposed NPR site. Surveys were conducted for birds, mammals, amphibians and reptiles, aquatic invertebrates, and plant species.
- ♦ A new research study was initiated to determine whether mercury levels in fish are higher at SRS than offsite, and whether the levels are increasing with time.
- ♦ A system for archiving SREL research data was developed, and a plan was implemented to archive research data from previous and ongoing studies.

INTRODUCTION

The year 1991 marked the 40th anniversary for research conducted by the Savannah River Ecology Laboratory (SREL) at Savannah River Site (SRS). The year featured a number of scientific achievements and activities.

SREL is operated by the University of Georgia under contract with the U.S. Department of Energy (DOE). Since 1951, SREL has conducted independent environmental studies of SRS, surrounding streams and ponds, and the Savannah River. Because public access to SRS is limited, many long-term research programs are conducted without the disturbances that could occur in unrestricted areas.

Some of the first studies performed at SRS included biological inventories of plant and animal species, competition in animal and plant communities, and the use of radioactive tracers to understand food chains.

The research programs have evolved through the years and now are carried out in three major divisions: biogeochemical ecology, wildlife ecology and toxicology, and wetlands ecology. A fourth division focuses on environmental outreach and education activities as part of SREL's overall mission to acquire and communicate knowledge of ecological processes and principles.

Research activities focus on both freshwater and terrestrial systems in natural and disturbed habitats. Other research activities are coordinated by SREL in association with the National Environmental Research Parks program.

This chapter summarizes the major research activities conducted by SREL at SRS during 1991. Included for each program is a short description of the purpose or major findings of the research. More complete descriptions of the research can be found in the SREL Annual Technical Progress Report for 1991.

SREL—in its 40th Anniversary Year— Continues Quality Environmental Research Programs

- ◆ The year 1991, which marked the 40th anniversary for research conducted by SREL at SRS, featured a number of scientific achievements and activities.
- ◆ SREL's faculty, technicians, students, and visiting scientists published three books and about 100 research articles in the scientific literature.
- ◆ A cover article in the journal *Science* (Aug. 23, 1991) presented long-term census data for four amphibian species. Collected from 1979 to 1990 at SRS's Rainbow Bay, the data illustrate that long-term studies may be required to distinguish between natural population fluctuations and declines associated with human activities.
- ◆ Eight scientific conferences, meetings, or symposia were organized by SREL, including one on theoretical ecology that was attended by about 35 of the nation's top scientists in the field.

BIOGEOCHEMICAL ECOLOGY

For an understanding of biogeochemical principles in terrestrial and aquatic systems, major emphasis is placed on interactions among biological and chemical cycling processes and their effect on the transport, bioavailability, fate, and effects of potential contaminants.

Many of the biogeochemical research programs focus on the cycling of radionuclides and other contaminants, environmental chemistry and toxicology, and modeling the transport and fate of environmental contaminants. Summarized below are research projects conducted during 1991.

Trace Organic Compounds

The mobility of hydrophobic organic contaminants in terrestrial and aquatic systems is greatly affected by natural organic components in the environment. Lipids (fats and oils) are one of the major classes of naturally occurring organic molecules that will play an important role in the behavior of hydrophobic organic contaminants. The composition and distribution of lipids are

being determined in various soils and decomposing leaf litter to evaluate the dynamics of this important fraction of the soil organic matter.

Radioecology

This research emphasizes the understanding of radionuclide transport processes in reservoirs of the Savannah River Site, including Par Pond, Pond B, and Pond C. The research will lead to increased knowledge of the amounts and distributions of radionuclides in these systems, fundamental understanding of transport processes, and the ability to predict the long-term fate of contaminants. Such predictions can serve as the foundation for multiple-pathway dose/risk assessments for humans as well as other species, and for evaluating different management scenarios. A joint SREL/Westinghouse Savannah River Company (WSRC) program to inventory and map the gamma-emitting radionuclides in Par Pond sediments was begun in 1991.

Ecological studies of radionuclide cycling in Pond B, an SRS cooling pond that received radioactive discharges from R Reactor in the 1960s, focused on animals such as resident turtles, catfish, alligators, and waterfowl. These studies are part of an ongoing effort to examine the long-term distribution, cycling, and fate of radionuclides in Pond B.

Contaminants from Coal and Other Fossil Fuels

Research conducted in this area provides information on the extent of underlying soil and surrounding vadose sediments, transport, and environmental effects of contaminants from coal storage piles and fly ash basins at SRS. Other collaborative studies with WSRC are examining the subsurface transport of diesel fuel contaminants from leaking storage tanks in the Central Shops area at SRS.

Biobarrier Field Testing

The goal of this effort is to determine the suitability of a biobarrier for use as a plant root barrier in hazardous-waste containment systems. The biobarrier consists of capsules of an herbicide (trifluralin), which is fused to porous geotextile sheets and inhibits root growth. The sheets are placed in the soil between the plant root zone and the underlying waste. Tests conducted with Savannah River Laboratory (SRL) indicate that the biobarrier is effective at preventing penetration by roots of Bermuda grass, bamboo, pine, and oak. Shallow-growing rhizomes, found in grasses and bamboo, have been relatively unaffected by the trifluralin but have not penetrated the geotextile.

Environmental Geochemistry and Toxicology of Uranium

This research is examining the distribution, fate, and mobilization potential of uranium and other introduced metals in contaminated sediments in the Tims Branch-Steeds Pond regions of the Upper Three Runs Creek watershed. Analyses of soil cores suggest that uranium, chromium, nickel, and copper occur in chemical forms that may be easily mobilized and potentially bioavailable under a range of environmental conditions. To assess whether these contaminants may have had an impact on the genetics of fish populations, a genetic survey was conducted in mosquitofish populations from Tims Branch in 1991. There was no indication of contamination effects on the frequencies of the allozymes used in the survey.

Environmental Transport Processes

The chemical forms of inorganic and organic contaminants control the mobility of the contaminants in the environment, as well as their bioavailability and toxicity. Research in 1991 examined basic and applied aspects of the chemical forms of contaminants and their transport through soils and water. The research has included studies on the movement of contaminants through subsoil and groundwater, the potential role of naturally occurring humic substances in the transport of organic contaminants in the subsurface environment, and the development of analytical methods.

Mercury Toxicology and Water Chemistry

This research provides information for assessing some ecological effects of the Effluent Treatment Facility (ETF) discharges into Upper Three Runs Creek. During planning for the ETF, mercury was identified as a constituent of the ETF effluent, with potential ecological consequences to Upper Three Runs Creek. Population-level responses to mercury and bioaccumulation of mercury in a fish—the dusky shiner—are being examined. Comparisons of mercury concentrations in dusky shiner tissue from 1987 (pre-operational) and 1989 (post-operational) suggest no obvious increase associated with the ETF. Additional comparisons will be made with a sampling conducted in late 1991. A new research study was initiated in late 1991 to determine whether mercury levels in fish are higher at SRS than offsite, and whether the levels are increasing with time.

WILDLIFE ECOLOGY AND TOXICOLOGY

Studies in wildlife ecology and toxicology focus on natural populations of plants and animals and how they respond to the stresses caused by human activities.

Some of the programs conducted at SRS include research on the effects of SRS operations on terrestrial and aquatic organisms, the effectiveness of alternative habitats to populations whose primary habitat has been destroyed, and studies of endangered species.

The following sections summarize studies conducted during 1991.

Waterfowl Studies

An annual census of waterfowl use of SRS, begun in 1982, was continued during 1991. During the past decade, waterfowl studies conducted by SREL have demonstrated the significance of SRS as one of the Southeast's most important inland wintering sites for diving ducks.

Wood Stork Program

The wood stork, the only North American stork, has been steadily declining in numbers, primarily because of loss of habitat. Study of the breeding biology of the wood storks of the Birdsville, Ga., colony, and stork use of the Savannah River Swamp System and Kathwood Lake foraging ponds was conducted in 1991 for the eighth consecutive year. The Kathwood Lake ponds are managed by SREL on the National Audubon Society Silver Bluff Plantation as alternate foraging areas for wood storks, to replace the areas in the Steel Creek Delta. The ponds continue to provide an excellent foraging area for storks, particularly juvenile birds. During the year, the partial draining of Par Pond created suitable foraging conditions for wood storks, which normally do not frequent Par Pond.

Habitat Mitigation for Amphibian Populations

Construction of the Defense Waste Processing Facility (DWPF) in S and Z areas resulted in the loss of a Carolina bay. Carolina bays are regionally important wetlands that enhance biodiversity and provide breeding sites for many species of amphibians. Four small refuge ponds were built around the DWPF site in 1983 as part of an experiment in mitigating the loss of the Carolina bay habitat caused by the DWPF construction. As of 1991, nine species of frog and toad and two species of salamander had colonized the refuge ponds; however, other species that formerly bred at the Carolina bay have not established populations.

Endangered Species

A rare and potentially endangered species of freshwater mussel has been identified from Mill Creek

Thunder Bay is an 11-acre Carolina bay located near the eastern boundary of SRS.

at SRS. Mill Creek is located in the Upper Three Runs Creek watershed. Because mussels repeatedly have been recognized on state and federal endangered species lists, SREL began efforts to clarify the taxonomic status of the endangered freshwater mussel species at SRS. Other endangered species at SRS are

the bald eagle, red-cockaded woodpecker, and wood stork.

Fish Populations in Four Mile Creek

Studies of growth and reproduction in the dusky shiner have indicated that populations in Four Mile Creek, recovering from years of thermal discharge impacts, have more rapid growth and greater food resources than unimpacted control populations in Upper Three Runs Creek. The effects most likely are due to higher productivity in Four Mile Creek resulting from more sunlight reaching the stream, combined with broader resource availability due to fewer competing species.

Fish Studies in Upper Three Runs Creek

Dusky shiners from three sites above the ETF outfall were compared with those from two sites below in terms of growth, reproduction, and body fat. The results suggest that the ETF is not having an effect on this species. Where there is significant variation among sites, the variation appears to be related to stream size, with upstream populations showing lower growth, less reproductive output, and lower fat levels than downstream populations. New analytical techniques

What are Carolina Bays?

- ◆ Carolina bays are unique, naturally occurring wetlands found only on the southeastern Coastal Plain. Their origin is unknown.
- ◆ Approximately 200 Carolina bays exist at SRS, ranging in size from about .2 acre to 125 acres.
- ◆ They are elliptical in shape and oriented northwest to southeast along their long axes.
- ◆ Carolina bays are shallow and may dry up seasonally.
- ◆ They provide important habitat and refuge for many SRS plants and animals.

have been developed that will enable a more sensitive analysis to be completed.

Biodiversity in Reptiles and Amphibians

The long-term objective of this effort is to develop and implement field techniques to enhance or restore biological diversity in reptiles and amphibians within a managed landscape. During 1991, efforts focused on:

- Developing standardized censusing techniques to estimate relative abundance and various measures of biodiversity.
- Quantifying population variations caused by natural and management processes.
- Comparing biodiversity under different management regimes.

Fish Biodiversity

Studies were initiated in 1991 to learn more about biological diversity in fish on the SRS. One goal is to develop a better understanding of fish biodiversity in streams, relative to habitat diversity, human disturbance, and biological interactions. Future studies will address whether differences in body shape, reproduction, and growth characteristics within a species are caused by genetic differences among populations or the characteristics of their environments.

Genotoxicology

Preliminary results of flow cytometry analyses in fish from Par Pond identified abnormal DNA patterns in almost 7 percent of the individuals analyzed, while no control fish showed this pattern. Similar abnormalities were found in mallard ducks inhabiting Pond B. These results may indicate that genetic damage is occurring. Future studies will focus on an exhaustive characterization of potential DNA damage at several contaminated SRS sites and on expanded efforts to identify the causes.

New Production Reactor Pre-operational Studies

Pre-operational studies are characterizing baseline environmental conditions at the proposed New Production Reactor (NPR) site. During 1991, surveys were conducted for birds, mammals, amphibians and reptiles, aquatic invertebrates, and plant species. Forty-seven bird species were found at the NPR site, including 24 permanent residents, 22 summer residents, and one spring migrant. Eight species of mammals were captured, including raccoons, opossums, shrews, and rodents. The low numbers of species are typical of young pine plantations at SRS.

Twenty-one species of reptiles and amphibians were recorded in a wetland area of the site. Invertebrate populations are still being identified. No threatened or endangered plant species have been found.

WETLANDS ECOLOGY

Research in wetlands ecology emphasizes the study of biological communities in both natural and disturbed wetlands. The studies contribute to understanding the structure and function of wetland ecosystems and the role of biological diversity. Some studies provide information about the restoration and recovery of disturbed environments that may be encountered in cleanup of waste sites. Wetlands currently studied at SRS include Carolina bays, swamp and bottomland forests, cooling reservoirs, and creeks. This section summarizes research programs conducted by SREL in 1991.

Establishment and Productivity of Floodplain Forests

Studies in forested wetlands along stream and river floodplains have indicated the significance of fluctuating water levels on seedling establishment and survival. Flood events and alterations of water levels—resulting from SRS activities and from upstream control of discharge from impoundments on the Savannah River—may limit forest regeneration, reduce growth of tree species, and affect the long-term maintenance of forest structure.

Asiatic Clam Impacts on Native Bivalves

The Asiatic clam continues to move upstream on many SRS drainages. This nuisance species was introduced through pumping of Savannah River water and its subsequent release to onsite streams. SREL experiments continue to investigate competition between this organism and native bivalves. Preliminary results have revealed that the Asiatic clam could reduce the food base in the water column over long reaches of stream.

Zooplankton in Carolina Bays and Other Temporary Ponds

Although the majority of animals live in variable environments, most predictive theory about their development is based on analyses for stable environments, because models for stable environments are easier to construct. Current research on Carolina bays shows that the development of zooplankton populations in variable environments can differ quantitatively and qualitatively from development in stable environments. The conditions under which the predictions diverge indicate limits of applicability for theory based on stable conditions.

Mapping of Disturbed Wetland Forest Communities

Plant communities were mapped using Geographic Information Systems (GIS) programs for a 3,000-hectare area of the Savannah River floodplain, where early logging and recent releases of industrial discharges have resulted in a complex mosaic of vegetation types. Communities identified included thermally influenced freshwater marshes, successional scrub-shrub communities, second-growth bottomland hardwood stands, and cypress-tupelo swamps.

Boron Sensitivity of Bottomland Forest Species

While boron is an important micro-nutrient required by plants, it can be toxic at very low concentrations. Significant amounts of boron are contained in fly ash, a byproduct of coal combustion and a major source of waste generated at SRS. This research is examining how boron might affect a number of hardwood species that normally inhabit the bottomland forest found along streams of the SRS that might receive runoff from fly ash piles and basins.

Invertebrates, Microbes, and Organic Matter in Aquatic Systems

These studies are designed to determine the role that invertebrates and microbes play in the energetics and transformation of organic matter in aquatic systems. Macroinvertebrates, a fundamental component of all aquatic systems, are widely used as indicators of system health. Macroinvertebrate shredders—organisms capable of consuming leaves—have been shown to contribute very little to decomposition in SRS streams. Experimental studies are being conducted to determine why these organisms are not found in higher densities.

Application of Remote-Sensing Techniques to Biodiversity

An important component of biodiversity involves the distribution and arrangement of different habitat types into patches on the landscape. Alternative arrangements of habitats in patches of differing size and shape may promote or restrict biodiversity or the existence of threatened or endangered species. A remote-sensing-based geographic information system is being used to analyze satellite images to classify habitat types and arrangements on the SRS. A preliminary classification of habitats has been completed and compiled into a spatial database that is being used to generate maps, which then are tested for accuracy.

Effects of Land Management Practices on Forest Biodiversity

This research focuses on how land management practices at SRS affect species composition of the forest plant community. One aspect involves documenting changes in plant species composition, population-size structure of each species, and relative growth rates of each species in the longleaf pine-turkey oak community in response to fire. A second aspect involves studying forest regeneration dynamics of a bottomland hardwood forest blown down during a tornado.

ENVIRONMENTAL OUTREACH AND EDUCATION

During 1991, outreach activities included onsite tours and presentations to school groups, civic organizations, and garden clubs. The program also communicated results of SREL research to the general public through local and national media coverage. SREL's education program included onsite participation in research by about 60 high school, undergraduate, and graduate students, along with pre-college teachers from throughout the United States.

To Learn About:	Turn to page:
♦ Timber management at SRS	541
♦ Protection of endangered species habitat	542
♦ Erosion control and road maintenance	542
♦ Forest research activities	544

Chapter 14

Compiled by Stephanie A. Neal
Savannah River Forest Station

Savannah River Forest Station

1991 HIGHLIGHTS

- ♦ SRFS's expanded program, which more than doubled the size of the forest station's staff (to 62 full-time employees), was completed.
- ♦ SRFS upgraded its engineering section in preparation for assuming the responsibility for secondary-road management at SRS.
- ♦ Endangered species management emphasis at SRFS now is placed on the recovery or maintenance of 31 onsite plant and animal species listed as sensitive, threatened, or endangered. SRFS also continued its long-standing work with the endangered red-cockaded woodpecker.
- ♦ Total revenue to the federal government from timber harvested at SRS during the year was more than \$4.3 million—a record for site timber sales.
- ♦ As a result of improved planting methods, SRFS was able to plant about 1,650 acres of the native longleaf pine and began work on a cloned-seed orchard to replace a Francis Marion National Forest orchard destroyed by Hurricane Hugo in 1989.

INTRODUCTION

The Savannah River Forest Station (SRFS) was formed in 1952 when the Atomic Energy Commission (AEC), now the U.S. Department of Energy (DOE), and the U.S. Department of Agriculture's Forest Service (USFS) formed an interagency agreement to create a forest management organization at the Savannah River Site (SRS).

SRFS has expanded from the management of timber only to the management of all site natural resources. This activity includes wildlife, fish, and botany studies, as well as the protection of soil and watershed quality and of a healthy forest for environmental research. October 1990 through September 1991 was the first full year of operation for most of the expanded program. Thus, most of 1991 was spent meeting the natural resource management needs of SRS.

Also, SRFS spearheaded an initiative to coordinate all SRS natural resource issues under one program. That effort resulted in the SRS Natural Resource Management Plan, also available from SRFS, which

was finalized and signed by DOE management Feb. 15, 1991.

NATURAL RESOURCE MANAGEMENT PLANNING AND OPERATIONS

Timber Management

SRFS implements forest management at SRS by preparing 10-year plans that define specific activities for particular forest areas. These areas usually are bounded by easily recognized features such as streams or roads. The 10-year plans normally include a comprehensive collection of data required for forest resources management, road maintenance, and construction. Inventories of wildlife habitats are included in the process. These data are needed to coordinate with the more than 800 other onsite activities in the SRS Site-Use Approval System.

During 1991, more than 22 million board feet of timber were marked, more than 29 million sold, and more than 22 million cut. The price received for timber from SRS steadily increased during the year, and the last sale brought a record \$305 per thousand board feet. Total revenue to the government from SRS

The Red-Cockaded Woodpecker

Home to Endangered Species

- ◆ In the 1970s, SRFS began monitoring the red-cockaded woodpecker species—distinguished by its black-and-white ladder-back markings and the small red markings on its head.
- ◆ At the beginning of 1986, only four birds—a breeding pair and two bachelor males—comprised the total red-cockaded woodpecker population found at SRS.
- ◆ But with the translocation of three female woodpeckers to the site, the birds' total population had grown to 11 by the end of that year's nesting season.
- ◆ Since that time, SRFS has used research conducted by the Southeastern Forest Experiment Station on translocation and cavity inserts to improve the birds' required habitat, provide artificial nest cavities, and bring in birds from other forests to augment the SRS population.
- ◆ Thirty red-cockaded woodpeckers are now onsite, living in nine clusters of cavity trees.

Year	Population
1986	11
1987	14
1988	14
1989	18
1990	25
1991	30

timber sales exceeded \$4.3 million, a record for the site.

Longleaf pine planting acreage at SRS during fiscal year 1991 was the highest since 1960. SRFS plants about 2,200 acres of trees at SRS annually—about three-fourths of that in loblolly pine. Because of improved planting methods for longleaf pine, SRFS now plans to plant about three-fourths of its total acreage in longleaf.

Although more difficult to grow, the longleaf species is being used by SRFS because it is a native pine of

SRS sandhill habitats and is preferred by the endangered red-cockaded woodpecker for nesting and feeding. Superior seedlings are needed to improve the longleaf's chance of survival, and SRFS oversees special contracts with nurseries to grow these seedlings for planting at SRS.

Soil and Water Management

SRFS has been involved for many years in stabilizing soils eroded by construction activities. As part of an ongoing project to reclaim eroding land, 159 acres were stabilized in 1991, while 76 acres of previously stabilized land were repaired, seeded, and fertilized. SRFS assisted Westinghouse Savannah River Company (WSRC) with 20 other projects and has entered into a long-term agreement to maintain soil stability at waste sites closed by its Environmental Restoration Department. Also during 1991, SRFS and the U.S. Soil Conservation Service presented five workshops on a variety of soil and water conservation topics. The sessions were attended by 187 participants from onsite and offsite organizations.

Road Management

On Oct. 1, 1991, SRFS assumed total responsibility from WSRC for maintaining the site's secondary-road system. SRFS had coordinated the upgrade of timber roads annually to accommodate large trucks that haul tree-length sawtimber and pulpwood. During 1991, SRFS coordinated maintenance on 34 miles of secondary roads and reconstructed 1.6 miles of roads. About two miles of new secondary roads were constructed during the year.

To prepare for assuming the management of the secondary-road and perimeter boundary systems, SRFS upgraded its engineering section with state-of-the-art capabilities in survey and design. Coordination efforts, as well as the development of standards and inventories, began with site road system users.

Wildlife, Fisheries, and Botany Program

The overall objective of the Wildlife, Fisheries, and Botany Program is to provide the amount and mix of different habitats that will support viable populations of the native plants and animals of SRS. Management emphasis is placed on the recovery or maintenance of the 31 plant and animal species listed as threatened, endangered, or sensitive. Examples of these species are bog spice bush, Bachman's Sparrow, smooth purple coneflower, and red-cockaded woodpecker.

Program objectives are accomplished through direct habitat improvement, coordination with the timber

The American bald eagle is among the endangered species at SRS.

management program, and manipulation of wildlife populations. Partnerships involving the Southeastern Forest Experiment Station in Asheville, N.C., the University of Georgia's Savannah River Ecology Laboratory (SREL), the South Carolina Wildlife Marine and Resources Department, Quail Unlimited, and the WSRC Deer Hunt Group were instrumental in implementing the 1991 program. Work completed in fiscal year 1991 included:

- 736 acres of red-cockaded woodpecker nesting habitat improvement.
- Placement of 20 artificial red-cockaded woodpecker cavity inserts.
- Mowing of 140 acres of grassy openings.
- Establishment of four acres of new grassy openings.
- Establishment of a 500-acre Quail Habitat Improvement Cooperative Project on Crackneck Game Management Area.
- Population survey activities—primarily for red-cockaded woodpecker, American bald eagle, and deer—conducted on 4,500 acres.

- Harvest of 1,117 deer and about 250 hogs.
- Increase of the SRS red-cockaded woodpecker population to 30 individuals in nine active clusters (groups of cavity trees where the birds live).

This expanded program is working toward a comprehensive approach addressing traditional wildlife management issues as well as new issues in conservation biology.

Fire Management

Extremely wet weather in January 1991 contributed to a reduction in prescribed-burning activities for the rest of the year. Prescribed burning was employed on 807 acres to stimulate vegetation growth on the forest floor for wildlife food. Another 4,655 acres were prescribed-burned to reduce wildfire hazard by reducing fuels, such as leaves and pine needles, on the forest floor.

SRFS initiated a growing-season burn program in 1991, burning 96 acres. Growing-season burns are understory burns conducted during the summer or early fall instead of during the winter dormant season. South Carolina's smoke management guidelines are

followed in the prescribed-burning program at SRS. The South Carolina Department of Health and Environmental Control's (SCDHEC) Bureau of Air Quality Reg. 61-62.2D allows burning for forest land management practices.

Fiscal year 1991 saw a smaller-than-average incidence of wildfires at SRS; a relatively small number of acres was burned. SRFS crews made 58 responses to 10 wildfires, which burned only 1.2 acres. The fire crews also responded to several offsite fires under a cooperative agreement with the South Carolina Forestry Commission.

In addition to fire duties, the fire crews also manage the Smokey Bear fire prevention outreach program. As part of the numerous outreach activities in 1991, more than 3,000 children in South Carolina and Georgia benefited from visits from Smokey at schools and special events.

SOUTHEASTERN FOREST EXPERIMENT STATION STUDIES

USFS scientists from the Southeastern Forest Experiment Station in Asheville conduct numerous studies to improve overall forest management activities conducted at SRS. During 1991, a total of 36 forest-related studies, some of which are listed below, were ongoing at SRS.

- Modeling potential community diversity in relation to soil characteristics.
- Biological diversity of small mammals on SRS in relation to forest structure and age.
- Biology of heavy-seeded hardwoods.
- Improvement of hardwood and pine seedling establishment for reforestation through various nursery technology applications.
- Ecology, genetics, and foraging requirements of the red-cockaded woodpecker.
- Measurement of the effects of pine straw removal from the forest floor on the growth of trees and nutrient cycling processes.

NATIONAL ENVIRONMENTAL RESEARCH PARK ACTIVITIES

SRFS also conducted activities in association with the National Environmental Research Park program. To demonstrate alternatives for environmental management, SRFS is maintaining long-term forest manage-

Tree Improvement

Working Together

- ◆ After Hurricane Hugo destroyed the seed orchard of South Carolina's Francis Marion National Forest in South Carolina, SRFS began working with the forest to establish a new cloned-seed orchard at SRS.
- ◆ Planting is under way that will produce this clone bank.
- ◆ The SRFS long-range plan for this project is to have a longleaf seed orchard established at SRS.
- ◆ The location has been chosen, with planting scheduled for completion in early 1992.
- ◆ More than 100 candidate trees have been selected from SRS. SRFS is working closely with other national forests and the state of South Carolina to obtain grafts from their orchards.
- ◆ SRFS also is working on an agreement with the state of South Carolina in 1991 to collect longleaf seeds from SRS.
- ◆ Two longleaf seed production areas have been chosen, and all non-seed trees are being removed.
- ◆ During the year, SRFS collected enough seeds from SRS's general forest area to supply about half the seeds needed for the state's 1993 planting season.
- ◆ The seeds will be planted and cultivated as seedlings during 1992.

ment experiments. Listed here are National Environmental Research Park activities conducted at SRS that deal with forest management.

- Comparison of the productivity of southern pine species on various soil types
- Studies of hardwood plantings to determine the relationship of biomass production to species characteristics
- Comparison of the growth of pine families with varying sensitivities to ozone as part of a regional monitoring program.

A listing of research-related publications is available on request from SRFS.

References

- Aadland, 1990** Aadland, R.W. and Bledsoe, H.W., 1990. *Classification of Hydrostratigraphic Units at the Savannah River Site*, WSRC-RP-90-987, Savannah River Site, Aiken, S.C.
- Alter and Oswald, 1988** Alter, H.W. and Oswald, R.A., 1988, "Nationwide Distribution of Indoor Radon Measurements," *Radiation Protection Practice*, Proceedings of the Seventh International Congress of International Radiation Protection Association, Pergamon Press, Sydney.
- Anderson, 1983** Anderson, E.L., 1983, "Quantitative Approaches in Use to Assess Cancer Risk," *Report of Carcinogen Assessment Group of U.S. EPA*, Risk Analysis, Vol. 3, pp. 277-295.
- APHA, 1981** American Public Health Association, 1981, *Standard Methods for the Examination of Water and Wastewater*, 15th edition, Washington, D.C.
- Beaufait, 1952** Beaufait, L.J. and Lukens, H.R., 1952, "Handbook of Radiochemical Analysis," Vol. II, *Radiochemical Procedures*, US AEC Report NP-5057 Del.
- BEIR, 1988** Committee on the Biological Effects of Ionizing Radiations (BEIR IV), 1988, *Health Risks of Radon and Other Internally Deposited Alpha-Emitters*, National Research Council, National Academy of Sciences, National Academy Press, Washington, D.C.
- BEIR, 1990** Committee on the Biological Effects of Ionizing Radiations (BEIR V), 1990, *Health Effects of Exposure to Low Levels of Ionizing Radiation*, National Research Council, National Academy of Sciences, National Academy Press, Washington, D.C.
- Bevington, 1969** Bevington, P.R., 1969, *Data Reduction and Error Analysis for the Physical Sciences*, McGraw Hill Book Co., New York, N.Y.
- Blunt, 1992** Blunt, B.C. 1992, *Calculated release levels from Phase III installations*, WSRC-RP-92-542, Savannah River Site, Aiken, S.C.
- CAAC, 1986** Radiation Shielding Information Center, 1986, *Code System for Implementation of Atmospheric Dispersion Assessment Required by the Clean Air Act*, Report CCC-476, Oak Ridge National Laboratory, Tenn.
- CFR, 1986** "National Primary Drinking Water Regulations," 1986, *Title 40 Code of Federal Regulations, Part 141*, pp. 521-568, Washington, D.C.
- CFR, 1987** "National Primary Drinking Water," 1987, *Title 40 Code of Federal Regulations, Part 141*, pp. 526-575, Washington, D.C.
- CFR, 1991a** "Hazardous Materials Tables, Hazardous Materials Communication Requirements, and Emergency Response Information Requirements," 1991 *Title 49 Code of Federal Regulations, Part 172*, Washington, D.C.
- CFR, 1991b** "National Secondary Drinking Water Regulations," *Title 40 Code of Federal Regulations, Part 143*, Washington, D.C.
- Colquhoun, 1983** Colquhoun, D.J.; Woolen, I.D.; Van Nieuhuse, D.S.; Padgett, G.G.; Oldham, R.W.; Boylan, D.; Bishop, J.W.; and Howell, P.D., 1983. *Surface and Subsurface Stratigraphy, Structure and Aquifers of the South Carolina Coastal Plain*, South Carolina Department of Health and Environmental Control, Governor's Office, and University of South Carolina, Columbia, S.C.
- Colquhoun, 1991** Colquhoun, D.J. and Muthig, M.G., 1991, "Stratigraphy and Structure of the Paleocene and Lower Eocene Black Mingo Group," *Geology of the Carolinas*, Horton, J.W., Jr., and Zullo, V.A., eds., University of Tennessee Press, Knoxville, Tenn.
- Corley, 1981** Corley, J.P., et. al., 1981, *A Guide for Environmental Radiological Surveillance at U.S. Department of Energy Installations*, DOE/EP-0023.
- Corn, 1985** Corn, M. and Breyse, P.N., 1985, "Human Exposure Estimates for Hazardous Waste Site Risk Assessment," *Risk Quantification and Regulatory Policy*, eds. Hoel, D.G., Merrill, R.A., and Perera, F.P., Banbury Report 19, pp. 283-291, Cold Spring Harbor Laboratory.

- Cummins, 1990** Cummins, C.L.; Martin, D.K.; and Todd, J.L., 1990, *Savannah River Site Environmental Report for 1989*, WSRC-IM-90-60, Savannah River Site, Aiken, S.C.
- Cummins, 1991** Cummins, C.L.; Martin, D.K.; and Todd, J.L. 1991, *Savannah River Site Environmental Report for 1990*, WSRC-IM-91-28 Savannah River Site, Aiken, S.C.
- Davis, 1989** Davis, H.A.; Martin, D.K.; and Todd, J.L., 1989, *Savannah River Site Environmental Report for 1988*, WSRC-RP-89-59-1, Savannah River Site, Aiken, S.C.
- D'Itri, 1991** D'Itri, F.M., 1991. "Mercury contamination - What we have learned since Minimata," *Environmental Monitoring and Assessment* 19: 165-182.
- DOE, 1988a** U.S. Department of Energy, 1988, "General Environmental Protection Program," DOE Order 5400.1, U. S. Department of Energy, Washington, D.C.
- DOE, 1988b** U.S. Department of Energy, 1988, *External and Internal Dose Conversion Factors for Calculation of Dose to the Public*, DOE/EH-0070&71, U. S. Department of Energy, Washington, D.C.
- DOE, 1990a** U.S. Department of Energy, 1990, "Radiation Protection of the Public and the Environment," DOE Order 5400.5, U. S. Department of Energy, Washington, D.C.
- DOE, 1990b** U.S. Department of Energy, 1990, *Tiger Team Assessment of the Savannah River Site Environment, Safety, and Health*.
- DOE, 1991** U.S. Department of Energy, 1991, *Environmental Regulatory Guide for Radiological Effluent Monitoring and Environmental Surveillance*, DOE/EH-0173T, National Technical Information Service, Springfield, Va.
- Dukes, 1984** Dukes, E.K., 1984, *The Savannah River Plant Environment*, DP-1642, Savannah River Laboratory, Savannah River Site, Aiken, S.C.
- Eckerman, 1980** Eckerman, K.F., et al., 1980, *Users Guide to GASPAR Code*, NUREG-0597, U.S. Nuclear Regulatory Commission.
- Environmental Monitoring, 1991a** Environmental Monitoring (Environmental Protection Department) and Exploration Resources, 1991, *The Savannah River Site's Groundwater Monitoring Program, First Quarter 1991*, ESH-EMS-910087, Savannah River Site, Aiken, S.C.
- Environmental Monitoring, 1991b** Environmental Monitoring (Environmental Protection Department) and Exploration Resources, 1992, *The Savannah River Site's Groundwater Monitoring Program, Second Quarter 1991*, ESH-EMS-910088, Savannah River Site, Aiken, S.C.
- Environmental Monitoring, 1991c** Environmental Monitoring (Environmental Protection Department) and Exploration Resources, 1992, *The Savannah River Site's Groundwater Monitoring Program, Third Quarter 1991*, ESH-EMS-910089, Savannah River Site, Aiken, S.C.
- Environmental Monitoring, 1991d** Environmental Monitoring (Environmental Protection Department) and Exploration Resources, 1992, *The Savannah River Site's Groundwater Monitoring Program, Fourth Quarter 1991*, ESH-EMS-910090, Savannah River Site, Aiken, S.C.
- EPA, 1975** U.S. Environmental Protection Agency, 1975, "National Interim Primary Drinking Water Regulations," *Title 40 Code of Federal Regulations, Part 141*, Washington, D.C.
- EPA, 1977** U.S. Environmental Protection Agency, 1977, "National Interim Primary Drinking Water Regulations," EPA-570/9-76-003, Washington, D.C.
- EPA, 1979** U.S. Environmental Protection Agency, 1979, *Methods for Chemical Analysis of Water and Wastes*, EPA-600/4-79-020, Washington, D.C.
- EPA, 1980** U.S. Environmental Protection Agency, 1980, *Procedures for Measurement of Radioactivity in Drinking Water*, EPA-600/4-80-032, Washington, D.C.
- EPA, 1982** U.S. Environmental Protection Agency, 1982, *Methods for Organic Chemical Analysis of Municipal and Industrial Wastewater*, EPA-600/4-82-057, Washington, D.C.
- EPA, 1982, 1983** U.S. Environmental Protection Agency, 1982, 1983, *Environmental Radiation Data, Reports 31-33* (Sept., Dec., 1982 and Mar., 1983). USEPA 520/5-83, 015, and 016, Washington, D.C.
- EPA, 1986a** RCRA Groundwater Monitoring Technical Enforcement Guidance Document, OSWER-9950.1, Washington, D.C.

- EPA, 1986b** U.S. Environmental Protection Agency, 1986, "Water Pollution Control; National Primary Drinking Water Regulations, Radionuclides, (proposed)," *Federal Register*, pp. 34836-34862, Washington, D.C.
- EPA, 1987** U.S. Environmental Protection Agency, July 8, 1987, "National Primary Drinking Water Regulations," *Federal Register*, Washington, D.C.
- EPA, 1989a** U.S. Environmental Protection Agency, 1989, "National Emission Standards for Hazardous Air Pollutants; Radionuclides," *Title 40 Code of Federal Regulations, Part 61, Volume 54, No. 240*, Washington, D.C.
- EPA, 1989b** U.S. Environmental Protection Agency, 1989, "Environmental Impact Statement: NESHAP for Radionuclides, Background Information Document, Volume I," EPA 520/1-89-05, Washington, D.C.
- EPA, 1989c** U.S. Environmental Protection Agency, 1989, "National Primary and Secondary Drinking Water Regulations (proposed rule)," *Federal Register*, 1989, Washington, D.C.
- EPA, 1989, 1990, 1991** U.S. Environmental Protection Agency, 1989, 1990, 1991 *Environmental Radiation Data*, Reports 58-63 (Dec., 1989; March, June, Sept., Dec., 1990; and March 1991). USEPA 520/5-89-034; 520/5-90-003, 013, 018, 031; and 520/5-91-025, Washington, D.C.
- Evans, 1986** Evans, J.S.; Moeller, D.W.; and Cooper, D.W., 1986, *Health Effects Model for Nuclear Power Plant Accident Consequence Analysis*, NUREG/CR-4214, Washington, D.C.
- FDA, 1990** U.S. Food and Drug Administration, 1990. *Risk Assessment Methodology for Environmental Contaminants in Fish and Shellfish*, Center for Food Safety and Applied Nutrition, Washington, D.C.
- Goldman, 1987** Goldman, M.; Catlin, R.; and Anspaugh, L., 1987, "Health and Environmental Consequences of the Chernobyl Nuclear Power Plant Accident," *Report to the U.S. Department of Energy from the Interlaboratory Task Group on Health and Environmental Aspects of the Soviet Nuclear Accident*, DOE/ER-1332.
- Hamby et al., 1992** Hamby, D.; Addis, R.; Beals, D.; Cadieux, J.; Carlton, W.; Dunn, D.; Hall, G.; Hayes, D.; Lorenz, R.; Kantelo, M.; and Taylor, R., 1992, *Emergency Response Monitoring Activities and Environmental Impact of the K-Reactor Aqueous Tritium Release of December 1991 (U)*, WSRC-RP-92-186, Savannah River Site, Aiken S.C.
- Hamby, 1991** Hamby, D.M., 1991, *Land and Water Use Characteristics in the Vicinity of the Savannah River Site (U)*, WSRC-RP-91-17, Savannah River Site, Aiken, S.C.
- Hubbard, 1988** Hubbard, J. E.; Stephenson; Steel, J. L.; and Gordon, D.E., 1988, *Water Resource Management Planning Guide for the Savannah River Plant*, Savannah River Plant, Aiken, S.C.
- Huddleston, 1985** Huddleston, P. F. and Hetrick, J. H., 1985, "Upper Eocene Stratigraphy of Central and Eastern Georgia," *Georgia Geologic Survey Bulletin* 95, 78 p.
- Hunter, 1990** Hunter, C.H., 1990, *A Climatological Description of the Savannah River Site*, WSRC-RP-89-313, Savannah River Site, Aiken, S.C.
- ICRP, 1948** International Commission on Radiological Protection, 1948, "The Metabolism of Plutonium and Related Elements," *ICRP Publication 48, Annals of the ICRP Vol. 16, No. 2/3*.
- ICRP, 1959** International Commission on Radiological Protection, 1959, "Recommendations of the International Commission on Radiological Protection," *Report of Committee II on Permissible Dose for Internal Radiation*, *ICRP Publication 2*, Pergamon Press, Oxford.
- ICRP, 1965** International Commission on Radiological Protection, 1965, "Principles of Environmental Monitoring Related to the Handling of Radioactive Materials," *ICRP Publication 7*, Pergamon Press, New York, N.Y.
- ICRP, 1968** International Commission on Radiological Protection, 1968, *ICRP Publication 10*, Pergamon Press, Oxford.
- ICRP, 1977** International Commission on Radiological Protection, 1977, "Recommendations of the International Commission on Radiological Protection," *ICRP Publication 26, Annals of the ICRP 1(3)*.
- ICRP, 1979** International Commission on Radiological Protection, 1979, "Limits for Intake of Radionuclides by Workers," *ICRP Publication 30, Annals of the ICRP 3(4)*.

- ICRP, 1981** International Commission on Radiological Protection, 1981, "Limits of Inhalation of Radon Daughters by Workers," *ICRP Publication 32, Annals of the ICRP* 6(1).
- ICRP, 1985** International Commission on Radiological Protection, 1985, "Principles of Monitoring for the Radiation Protection of the Public," *ICRP Publication 43*.
- Kumazawa et al., 1984** Kumazawa, S.; Nelson, D.R.; and Richardson, A.C.B., 1984, *Occupational Exposure to Ionizing Radiation in the United States: A Comprehensive Review for the Year 1980 and a Summary of Trends for the Years 1960-1985*, EPA/520/1-84-005, U.S. Government Printing Office, Washington, D.C.
- Marter, 1984** Marter, W.L., 1984, *Environmental Dosimetry for Normal Operations at SRP*, DPST 83-270 Rev. 1, Aiken, S.C.
- Michel, 1980** Michel, J. and Moore, W.S., 1980, "Ra-228 and Ra-226 Content of Groundwater in Fall Line Aquifers," *Health Physics*, Vol. 38, pp. 663-671.
- Mikol et al., 1988** Mikol, S.C.; Burckhalter, L.T.; Todd, J.L.; and Martin, D.K., 1988, *Savannah River Plant Environmental Report for 1987*, DPSPU-88-30-1, Savannah River Plant, Aiken, S.C.
- Murphy et al., 1990** Murphy, C.E., et al., 1990, *Tritium in the Savannah River Site Environment (U)*, WSRC-RP-90-424-1, Savannah River Site, Aiken, S.C.
- NAS, 1960** National Academy of Sciences, 1960, *The Radiochemistry of Barium, Calcium, and Strontium*, AS-NS-3010.
- Natrella, 1966** Natrella, M.G., 1966, "Experimental Statistics," *National Institute of Standards and Technology, Handbook 91*, Wiley & Sons, New York, N.Y.
- NCRP, 1971a** National Council on Radiation Protection and Measurements, 1971, "Basic Radiation Protection Criteria," *NCRP Report No. 39*, Washington, D.C.
- NCRP, 1971b** National Council on Radiation Protection and Measurements, 1971, "A Handbook of Radioactivity Measurements Procedures," *NCRP Report No. 58*, Washington D.C.
- NCRP, 1976** National Council on Radiation Protection and Measurements, 1976, "Environmental Radiation Measurements," *NCRP Report No. 50*, Washington, D.C.
- NCRP, 1979** National Council on Radiation Protection and Measurements, 1979, "Tritium in the Environment," *NCRP Report No. 62*, Washington, D.C.
- NCRP, 1983** National Council on Radiation Protection and Measurements, "Iodine-129: Evaluation of Releases from Nuclear Power Generation," *NCRP Report No. 75*, Bethesda Md.
- NCRP, 1984** National Council on Radiation Protection and Measurements, "Radiological Assessment: Predicting the Transport, Bioaccumulation, and Uptake by Man of Radionuclides Released to the Environment," *NCRP Report No. 76*, Bethesda Md.
- NCRP, 1987a** National Council on Radiation Protection and Measurements, 1987, "Ionizing Radiation Exposure of the Population of the United States," *NCRP Report No. 93*, Washington, D.C.
- NCRP, 1987b** National Council on Radiation Protection and Measurements, 1987, "Recommendations on Limits for Ionizing Radiation Exposure," *NCRP Report No. 91*, Washington, D.C.
- NCRP, 1988** National Council on Radiation Protection and Measurements, 1988, "Environmental Radiation Measurements," *NCRP Report No. 50*, Washington, D.C.
- NCRP, 1989** National Council on Radiation Protection and Measurements, 1989, "Exposure of the U.S. Population from Diagnostic Medical Radiation," *NCRP Report No. 100*, Bethesda, Md.
- NCRP, 1989b** National Council on Radiation Protection and Measurements, 1989, "Comparative Carcinogenicity of Ionizing Radiation and Chemicals," *NCRP Report 96*, Bethesda, Md, NCRP.
- NRC, 1973** U.S. Nuclear Regulatory Commission, 1973, *Methods for Estimating Atmospheric Transport and Dispersion of Gaseous Effluents in Routine Releases from Light-Water-Cooled Reactors*, Regulatory Guide 1.111, Washington, D.C.
- NRC, 1977** U.S. Nuclear Regulator Commission, 1977, *Regulatory Guide 1.109, Calculation of Annual Doses to Man from Routine Releases of Reactor Effluents for the Purpose of Evaluating Compliance with 10CFR50, Appendix I, Revision 1*.

- NRC, 1979** U.S. Nuclear Regulatory Commission, 1979, NUREG 172, prepared by Battelle Pacific Northwest Laboratory.
- NUREG, 1984** National Bureau of Standards for the Division of Systems Integration, Office of Nuclear Reactor Regulations, 1984, *Lower Limit of Detection: Definition and Elaboration of a Proposed Position for Radiological Effluent and Environmental Measurements*, NCR FIN B8615, U.S. Nuclear Regulatory Commission.
- Nystrom, 1991** Nystrom, P.G.; Willoughby, R.H.; and Price, L.K., 1991, "Cretaceous and Tertiary Stratigraphy of the Upper Coastal Plain, South Carolina," *Geology of the Carolinas*, pp. 241-250, Horton, J.W., Jr., and Zullo, V.A., eds., University of Tennessee Press, Knoxville, Tenn.
- Oakley, 1972** Oakley, D.T., 1972, *Natural Radiation Exposure in the United States*, ORP/SID 72-1, U.S. Environmental Protection Agency, Washington, D.C.
- Osteen, 1991** Osteen, S.B. and Bibler, J.P., 1991, "Treatment of Radioactive Waste for Mercury Removal." *Water, Air and Soil Pollution* 56:63-74.
- Price, 1991** Price, V.; Fallaw, W.C.; and McKinney, J.B., 1991, *Geologic Setting of the New Production Reactor Reference Site Within the Savannah River Site*, WSRC-RO-91-96, ESH-EMS-90171, Savannah River Site, Aiken, S.C.
- Prowell, 1985** Prowell, D.C.; Christopher, R.A.; Edwards, L.E.; Bybell, L.M.; and Gill, H.E., 1985, "Geologic Section of the Updip Coastal Plain from Central Georgia to Western South Carolina," U.S. Geological Survey Miscellaneous Field Studies Map MF-1737, 11 sheets.
- Sagendorf and Goll, 1977** Sagendorf, J.F. and Goll, J.T., 1977, *XOQ/DOQ Program for Meteorological Evaluation of Routine Effluent Releases at Nuclear Power Stations*, NUREG-0324, U.S. Nuclear Regulatory Commission, Washington D.C.
- SCDHEC, 1981** South Carolina Department of Health and Environmental Control, 1981, *Water Classification Standards System for the State of South Carolina*, Columbia, S.C.
- SCDHEC, 1985** South Carolina Department of Health and Environmental Control, 1985, Savannah River Plant, Aiken, Allendale, and Barnwell Counties, NPDES Permit 0000175, Columbia, S.C.
- SCDHEC, 1990** South Carolina Department of Health and Environmental Control, 1990, "Water Classifications and Standards," Regulation 61-68, and "Classified Waters," Regulation 61-69, promulgated by the Department of Health and Environmental Control pursuant to the South Carolina Pollution Control Act, Columbia, S.C.
- Sharaf, 1986** Sharaf, M.A.; Ilman, D.L.; and Kowalski, B.R., 1986, *Chemometrics*, pp. 332, John Wiley & Sons, New York, N.Y.
- Simpson, 1980** Simpson, D.B. and McGill, B.L., 1980, *Users Manual for LADTAP II - A Computer Program for Calculating Radiation Exposure to Man from Routine Release of Nuclear Reactor Liquid Effluents*, NUREG/CR-1276, (ORNL/NUREG/TOMC-1), Oak Ridge National Laboratory, Oak Ridge, Tenn.
- Siple, 1967** Siple, G.E., 1967, *Geology and Groundwater of the Savannah River Plant and Vicinity*, U.S. Geological Survey Water Supply Paper 1841, 113 p., S.C.
- Sorenson, 1987** Sorenson, J.A. and Phelps, M.E., 1987, *Physics in Nuclear Medicine*, p. 521, Grune and Stratton, Inc., Fla.
- SREL, 1990** University of Georgia Savannah River Ecology Laboratory, 1991, *Communicating Science*, Vol. II, Aiken, S.C.
- Steel, 1980** Steel, R.G. and Torrie, J.H., 1980, *Principles and Procedures of Statistics*, 2nd ed., McGraw-Hill Book, Co., New York, N.Y.
- Stone, 1983** Stone, J.A., 1983, *Technical Summary of Groundwater Quality Protection Program at Savannah River Plant*, Report DPST-83-829, Vol. II, Savannah River Laboratory, Savannah River Site Aiken, S.C.
- SW, 1986** U.S. Environmental Protection Agency, 1986, *Test Methods for Evaluating Solid Waste*, Vol. 1A, Laboratory Manual, Physical/Chemical Methods, SW-846.
- Taylor, 1987** Taylor, J.K., 1987, *Quality Assurance of Chemical Measurements*, Lewis Publishers, Inc., Minn.
- Tice, 1984** Tice, R.R., 1984, *An Overview of Occupational Studies Directed at Assessing Genetic Damage, in Reproduction: The New Frontier in Occupational and Environmental Health Research*, p. 439, Lockey, J.E., Lemasters, G.K., and Koye, W.R., Jr. eds, Alan R. Liss, Inc., New York, N.Y.

References

- Tureotte, 1983** Turcotte, M.D.S., 1983, *Georgia Fishery Study: Implications for Dose Calculations*, DPST-83-319, Rev. 1, Savannah River Laboratory, Savannah River Site, Aiken, S.C.
- USPHS, 1989** U.S. Public Health Service, 1989, *Toxicologic Profile for Mercury*, ATSDR/TP-89/16, PB90-181256, National Technical Information Service, Va.
- Watson, 1980** Watson, J.E., 1980, *Upgrading Environmental Radiation Data*, Health Physics Society Committee Report HPSR-1 (1980).
- Whicker, 1983** Whicker, F.W., 1983, "Radionuclide Transport Processes in Terrestrial Ecosystems," *Radiation Research*, 94:135-150.
- WSRC, 1990** Westinghouse Savannah River Company, 1990, *Savannah River Site Action Plan in Response to the Department of Energy Environmental Health and Safety Compliance Assessment of the Savannah River Site*, Vols. I and II, Revision 10, U.S. Department of Energy, Savannah River Site, Aiken, S.C.
- Zeigler, 1985** Zeigler, C.C.; Lawrimore, I.B.; and Heath, E.M., 1985, *Savannah River Plant Environmental Report for 1985*, DPSPU-86-30-1, Savannah River Plant, Aiken, S.C.
- Zeigler, 1986** Zeigler, C.C.; Lawrimore, I.B.; Heath, E.M.; and Till, J.E., 1986, *Savannah River Plant Environmental Report for 1986*, DPSPU-87-30-1, Savannah River Plant, Aiken, S.C.

Glossary

A

absorbed dose - The amount of energy deposited by radiation in a given amount of mass. The unit of absorbed dose is the rad.

absorption - The process by which the number and energy of particles or photons entering a body of matter is reduced by interaction with the matter.

accuracy - The closeness of the result of a measurement to the true value of the quantity.

activity - (see radioactivity)

aliquot - The quantity of sample being used for analysis.

algaculture - The growth of microorganisms in a nutrient medium.

alkalinity - Alkalinity is a measure of the buffering capacity of water, and since pH has a direct effect on organisms as well as an indirect effect on the toxicity of certain other pollutants in the water, the buffering capacity is important to water quality.

allozyme - Variant form of an enzyme that results from the presence of different alleles. It is used to estimate genetic variability in populations.

alpha particle - A positively charged particle emitted from the nucleus of an atom having the same charge and mass as that of a helium nucleus (two protons and two neutrons).

ambient air - The surrounding atmosphere as it exists around people, plants, and structures.

analytical detection limit - The lowest reasonably accurate concentration of an analyte that can be detected; this value varies depending on the method, instrument, and dilution used.

analyte - A constituent or parameter that is being analyzed.

anion - A negatively charged ion.

anneal, annealing - Maintenance of glass or metal at a specified temperature for a specific length of time, then gradually cooling. This treatment removes internal strains and eliminates distortions and imperfections.

a priori - Decisions made before or without examination ("before the fact"); based on hypothesis or theory rather than on experiment or experience.

Appendix IX - List of constituents specified by Appendix IX in the *Code of Federal Regulations*, Title 40, Part 264. Analyses for Appendix IX constituents are required by the Resource Conservation and Recovery Act under specified conditions.

aquifer - A saturated, permeable geologic unit that can transmit significant quantities of water under ordinary hydraulic gradients.

aquitard - A geologic unit that inhibits the flow of water.

ash - Inorganic residue remaining after ignition of combustible substances.

assimilate - To take up or absorb into the body.

atom - Smallest particle of an element capable of entering into a chemical reaction.

atomic absorption spectrometry (AA) - Chemical analysis performed by vaporizing a sample and measuring the absorbance of light by the vapor.

Atomic Energy Commission (AEC) - A federal agency created in 1946 to manage the development, use, and control of nuclear energy for military and civilian application. It was abolished by the Energy Reorganization Act of 1974 and succeeded by the Energy Research and Development Administration (now part of the U.S. Department of Energy and the U.S. Nuclear Regulatory Commission).

B

bail - To remove water from a well by lowering a container called a bailer into the water, allowing it to fill with water, and then removing it from the well.

beta particle - A negatively charged particle emitted from the nucleus of an atom. It has a mass and charge equal to those of an electron.

biobarrier - A general term for a variety of materials or approaches that prevent organisms from moving into a defined area. A barrier in the soil that prevents root growth is one example of biobarrier technology.

biogeochemical ecology - The study of interactions among biological and chemical cycling processes and their effect on transport, bioavailability, fate, and effects of potential contaminants.

biomass - The weight of any specific or general kind of organic matter, usually expressed per area or volume.

bioreactor - A container filled with microbial organisms which degrade substances (such as oil) as the substance passes through the container.

biota - The animal and plant life of a particular region considered as a total ecological entity.

bivane - Meteorological instrument which simultaneously measures vertical and horizontal wind direction.

blank - A control sample that is identical, in principle, to the sample of interest, except that the substance being analyzed is absent. In such cases, the measured value or signal for the substance being analyzed is believed to be due to artifacts and should be subtracted from the measured value to give a net result reflecting the amount of the substance in the sample.

blind blank - A sample container of deionized water sent to a laboratory under an alias name as a quality control check.

blind replicate - In the EPD/EMS Groundwater Monitoring Program, a second sample taken from the same well at the same time as the primary sample, assigned an alias well name, and sent to a laboratory for analysis (as an unknown to the analyst).

blind sample - A control sample of known concentration in which the expected values of the constituent are unknown to the analyst.

BNA - Base/Neutral and Acid Extractables; a group of organic compounds analyzed as part of Appendix IX and Priority Pollutants.

Brailsford pump - A surface water sampling device which is stationed on a stand above a stream. The device, which continuously samples stream water, consists of an all-plastic valveless piston driven by a Brailsford small electric motor. The variable pump speed is set normally at 0.75 gallons/day.

C

calibration - Determination of variance from a standard or accuracy of a measuring instrument to ascertain necessary correction factors.

carcinogen - A cancer-causing substance.

Carolina bay - A type of shallow depression commonly found on the coastal Carolina plains. Carolina bays are typically circular or oval. Some are wet or marshy, while others are dry.

carrier - A quantity of non-radioactive or non-labeled material having the same chemical composition as its corresponding radioactive or labeled counterpart. When mixed with the corresponding radioactive labeled material, the carrier permits chemical (and some physical) manipulation of the mixture with less label or radioactivity loss than would be true for the undiluted label or radioactivity.

cation - Positively charged ion.

cavity/wake zones - Areas where air is recirculated or altered due to the proximity of obstacles such as buildings or trees.

Central Savannah River Area (CSRA) - A 12-county area in Georgia and South Carolina surrounding Augusta, Ga. SRS is included in the CSRA.

CERCLA-reportable release - A release to the environment that exceeds reportable quantities as defined by CERCLA (Comprehensive Environmental Response Compensation and Liability Act).

chain-of-custody - A form that documents sample collection, transport, analysis, and disposal.

chemical oxygen demand - The chemical oxygen demand (COD) indicates the quantity of oxidizable materials present in a water and varies with water composition, concentrations of reagent, temperature, period of contact, and other factors.

chemical speciation - The occurrence of chemical elements in different forms or species (e.g., elemental, ionic, complexed) depending upon environmental conditions.

chlorocarbons - Chlorocarbons are compounds of carbon and chlorine, or carbon, hydrogen, and chlorine, such as carbon tetrachloride, chloroform, tetrachloroethylene, etc. They are among the most significant and widespread environmental contaminants. Classified as hazardous wastes, chlorocarbons may have a tendency to cause detrimental effects, such as birth defects.

closure - Control of a hazardous-waste management facility under RCRA requirements.

collective dose equivalent/collective effective dose equivalent - The sums of the dose equivalents or effective dose equivalents of all individuals in an exposed population within an 80-mile (128-km) radius, and expressed in units of person-rem (or person-sievert). When the collective dose equivalent of interest is for a specific organ, the units would be organ-rem (or organ-sievert). The 80-mile distance is measured from a point located centrally with respect to major facilities or DOE program activities.

committed dose equivalent - The calculated total dose equivalent to a tissue or organ over a 50-year period after known intake of a radionuclide into the body. Contributions from external dose are not included. Committed dose equivalent is expressed in units of rem (or sievert).

committed effective dose equivalent - The sum of the committed dose equivalents to various tissues in the body, each multiplied by the appropriate weighting factor. Committed effective dose equivalent is expressed in units of rem (or sievert).

compliance - Fulfillment of applicable requirements of a plan or schedule ordered or approved by government authority.

comprehensive analyses - A group of analyses that forms the core of the EPD/EMS Groundwater Monitoring Program each quarter. See the **Sample Sched-**

uling section of this report for a complete list of constituents.

concentration - The amount of a substance contained in a unit volume or mass of a sample.

conductivity - A measure of water's capacity to convey an electric current. This property is related to the total concentration of the ionized substances in a water and the temperature at which the measurement is made.

confluence - The point at which two or more streams meet; the point where a tributary joins the main stream.

contamination - Deposition of unwanted radioactive material on the surfaces of structures, areas, objects, or personnel.

control chart - A statistical tool used to demonstrate whether or not a specific process is within acceptable standards or limits of performance.

control limits - A statistical tool used to define the bounds of virtually all values produced by a system in statistical control.

cosmic radiation - Ionizing radiation with very high energies, originating outside the earth's atmosphere. Cosmic radiation is one source contributing to natural background radiation.

count - The signal that announces an ionization event within a counter; a measure of the radiation from an object or device.

counter - A general designation applied to radiation detection instruments or survey meters that detect and measure radiation.

counting geometry - A well-defined sample size and shape for which a counting system has been calibrated.

curie (Ci) - A unit of radioactivity. One curie is defined as 3.7×10^{10} (37 billion) disintegrations per second. Several fractions and multiples of the curie are in common usage:

kilocurie (kCi) - 10^3 Ci, one thousand curies; 3.7×10^{13} disintegrations per second.

millicurie (mCi) - 10^{-3} Ci, one-thousandth of a curie; 3.7×10^7 disintegrations per second.

microcurie (μ Ci) - 10^{-6} Ci, one-millionth of a curie; 3.7×10^4 disintegrations per second.

picocurie (pCi) - 10^{-12} Ci, one-trillionth of a curie; 0.037 disintegrations per second.

D

2,4-D - 2,4-Dichlorophenoxyacetic acid.

daughter - A nuclide formed by the radioactive decay of a parent nuclide.

decay, radioactive - The spontaneous transformation of one radionuclide into a different radioactive or non-radioactive nuclide, or into a different energy state of the same radionuclide.

derived concentration guide (DCG) - The concentration of a radionuclide in air or water that, under conditions of continuous exposure for one year by one exposure mode (i.e., ingestion of water, submersion in air or inhalation), would result in either an effective dose equivalent of 0.1 rem (1 mSv) or a dose equivalent of 5 rem (50 mSv) to any tissue, including skin and lens of the eye. The guides for radionuclides in air and water are given in DOE Order 5400.5.

detector - Material or device (instrument) that is sensitive to radiation and can produce a signal suitable for measurement or analysis.

diatoms - Unicellular or colonial algae of the class Bacillariophyceae, having siliceous cell walls with two overlapping, symmetrical parts. Diatoms represent the predominant periphyton (attached algae) in most water bodies and have been shown to be reliable indicators of water quality.

diatometer - Diatom collection equipment consisting of a series of microscope slides in a holder that is used to determine the amount of algae in a water system.

dilution factor - The mathematical factor by which a sample is diluted in order to bring the concentration of an analyte in a sample within the analytical range of a detector (e.g., 1 mL sample + 9 mL solvent = 1:10 dilution, or a dilution factor of 10).

disintegration, nuclear - A spontaneous nuclear transformation (radioactivity) characterized by the emission of energy and/or mass from the nucleus of an atom.

dissolved oxygen - A desirable indicator of satisfactory water quality in terms of low residuals of biologically available organic materials. Dissolved oxygen prevents

the chemical reduction and subsequent leaching of iron and manganese from sediments.

DNAPL - Dense Non-Aqueous Phase Liquids; the liquid phase of chlorinated organic solvents. These liquids are denser than water and include commonly used industrial compounds such as tetrachloroethylene and trichloroethylene.

dose - The energy imparted to matter by ionizing radiation. The unit of absorbed dose is the rad, equal to 0.01 joules per kilogram in any medium.

dose equivalent - The product of the absorbed dose (rad) in tissue and a quality factor. Dose equivalent is expressed in units of rem (or sievert) (1 rem=0.01 sievert).

dosimeter - A portable detection device for measuring the total accumulated exposure to ionizing radiation.

dosimetry - The theory and application of principles and techniques involved in the measurement and recording of radiation doses. Its practical aspect is concerned with using various types of radiation instruments to make measurements.

downgradient - In the direction of decreasing hydrostatic head.

downgradient well - A well that is installed hydraulically downgradient of a site and may be capable of detecting migration of contaminants from a site.

drum chopping - A mechanical means to prepare a clear-cut site for planting a new stand of trees. A large, heavy cylinder (drum) with blades perpendicular to the drum is pulled behind a large crawler tractor. The blade chops limbs and small non-merchantable stems into pieces.

duplicate result - A result derived by taking a portion of a primary sample and performing the identical analysis on that portion as is performed on the primary sample.

dusky shiner - The common name for *Notropis cummingsae*, an abundant schooling minnow in SRS streams.

DWS - Drinking water standards (e.g., federal primary and secondary drinking water standards, both proposed and final, as set forth by EPA).

E

effective dose equivalent - It is the sum of the committed effective dose equivalents received by all organs or tissues of the body after each one has been multiplied by an appropriate weighting factor.

effluent - A liquid or gaseous waste discharge to the environment.

effluent monitoring - The collection and analysis of samples or measurements of liquid and gaseous effluents for purposes of characterizing and quantifying the release of contaminants, assessing radiation exposures of members of the public, and demonstrating compliance with applicable standards.

electrophoretic techniques - Laboratory techniques based on the differential migration of particles in an electrical field, that are used to determine genetic characteristics of organisms.

eluate - The liquid resulting from removing the trapped material from an ion-exchange resin.

elute - To remove absorbed ions from an ion exchange resin.

equipment blank - A sample container of deionized water that has been pumped through or has filled a sampling device (e.g., well pump bailer). Laboratory analysis of the blank can identify potential contaminants in water, sample container, or analytical equipment.

eutrophication - Accelerated growth of organisms in a body of water due to excess nutrients.

exposure (radiation) - The incidence of radiation on living or inanimate material by accident or intent. Background exposure is the exposure to natural background ionizing radiation. Occupational exposure is that exposure to ionizing radiation which takes place during a person's working hours. Population exposure is the exposure to the total number of persons who inhabit an area.

external radiation - Exposure to ionizing radiation when the radiation source is located outside the body.

F

fauna - The population of animals at a given area, environment, formation, or time span.

fecal coliform - The coliform group comprises all of the aerobic, nonspore-forming, rod-shaped bacteria. The test determines the presence or absence of coliform organisms.

field blank - A sample container of deionized water generated by filling the sample container at the sample location and treated as a groundwater sample.

fixed residue - Fixed residue is material left in the vessel after evaporating a water sample and its subsequent ashing in an oven at a high temperature. Water yielding considerable residue are generally inferior with respect to palatability, or they may induce an unfavorable physiological reaction in the transient consumer.

flagging criteria - Criteria established to aid in determining the relative concentration and testing frequency for analytes. See **Flagging Criteria** section of this report for further information.

flora - The population of plants at a given area, environment, formation, or time span.

formation - A mappable unit of consolidated or unconsolidated geologic material of a characteristic lithology or assemblage of lithologies.

friable asbestos - Asbestos that is brittle or readily crumbled.

G

gamma PHA - A group of analyses performed to determine activities of gamma-emitting radionuclides.

gamma ray - High-energy, short-wavelength electromagnetic radiation emitted from the nucleus of an excited atom. Gamma rays are identical to x-rays except for the source of the emission.

gamma spectrometry - A system consisting of a detector, associated electronics, and a multi-channel analyzer that is used to analyze samples for gamma-emitting radionuclides.

gas-flow proportional counter - A device or instrument that measures various alpha- and beta-emitting radionuclides.

Gaussian puff/plume model - A computer simulated atmospheric dispersion of a release using a Gaussian (normal) statistical distribution to determine concentrations in air.

GC VOA (Gas Chromatographic Volatile Organic Analyses) - An analytical technique detecting and quantifying volatile organic compounds in a sample by gas chromatography.

GCMS VOA (Gas chromatograph/Mass Spectrometer Volatile Organics Analyses) - An analytical technique for detecting and quantifying volatile organic compounds in a sample by gas chromatography/mass spectroscopy. The analytes in the GC VOA suite are included in the GCMS VOA suite.

Geiger-Mueller (GM) counter - A highly sensitive, gas-filled radiation detector, which operates at voltages sufficiently high to produce ionization. The counter is used primarily in the detection of gamma radiation and beta emission. It is named for Hans Geiger and W. Mueller who invented it in 1928.

genotoxicology - the study of the effects of chemicals or radioactive contaminants on the genetics of individual animals or plants.

Geographic Information System - Computer-based system for storing, manipulating, and analyzing geographical information.

grab sample - A sample collected instantaneously with a glass or plastic bottle placed below the water surface to collect surface water samples (also called dip samples).

groundwater, unconfined - Groundwater exposed to the unsaturated zone.

H

half-life, biological - The time required for a biological system, such as that of a human, to eliminate by natural processes half the amount of a substance (such as a radioactive material) that has entered it.

half-life, radiological - The time required for half of a given number of atoms of a specific radionuclide to decay. Each nuclide has a unique half-life.

halogenated compound - An organic compound bonded with one of the five halogen elements (e.g., astatine, bromine, chlorine, fluorine, and iodine).

halomethane - Any compound that includes a methane group (CH₃) bonded to a halogen element (e.g., astatine, bromine, chlorine, fluorine or iodine).

hardness - Water hardness is caused by the polyvalent metallic ions dissolved in water. In fresh waters these are mainly calcium and magnesium although other metals such as iron, strontium, and manganese contribute to the extent that appreciable concentrations are present. Concentrations in water have not proven health related; therefore, the final levels achieved are a function of economics.

head reversal - The hydrologic phenomenon in which a deeper formation has a higher water pressure than a more shallow formation in the same location. This condition results in a tendency for groundwater to flow upward from the deeper aquifer to the more shallow formation.

heavy water - Water in which the molecules contain oxygen and deuterium, an isotope of hydrogen that is heavier than ordinary hydrogen.

HEPA - The acronym for high-efficiency particulate air filter.

herbicides/pesticides - Suite of analyses consisting of 2,4-dichlorophenoxyacetic acid, endrin, lindane, methoxychlor, toxaphene, and 2,4,5-TP (silvex). See the **Sample Scheduling** section of this report for further information.

heterotrophic - Organisms that obtain energy from the breakdown of existing organic matter; the opposite of autotrophic organisms.

high-purity germanium (HPGe) detector - A device that detects photon radiation by employing diffused junctions generated by the application of a high voltage across a semiconductor material.

humic substances - A variety of complex organic molecules found in soils and water following the breakdown of leaves and other types of organic matter.

hydrology - The science dealing with the properties, distribution, and circulation of natural water systems.

hydrogeology - Hydrologic aspects of site geology.

hydrophobic - Not capable of uniting with or absorbing water.

I

in situ - In its original place; field measurements taken without removing the sample from its origin.

internal blank - deionized water sample generated by the laboratory; an internal blank is analyzed with each batch of samples as an in-house check of analytical procedures and equipment.

internal dose factor - A factor used to convert intakes of radionuclides to dose equivalents.

internal radiation - Internal radiation occurs when natural radionuclides enter the body by ingestion of foods, milk, and water, and by inhalation. Radon is the major contributor to the annual dose equivalent for internal radionuclides.

ion - An atom or compound that carries an electrical charge.

ion exchange - Process in which a solution, containing soluble ions is passed over a solid ion exchange column which removes the soluble ions by exchanging them with labile ions from the surface of the column. The process is reversible so that the trapped ions are removed (eluted) from the column and the column is regenerated.

irradiation - Exposure to radiation.

Isco sampler - A portable, microprocessor-controlled water sampler that utilizes a peristaltic pump for sample collection. The sampler may be used with a flowmeter to obtain a flow-proportional sample or without a flowmeter to obtain a time-proportional sample.

isopach map - A map showing the thickness of geologic units.

isotopes - Forms of an element having the same number of protons in their nuclei but differing in the number of neutrons.

long-lived isotope - A radionuclide that decays at such a slow rate that a quantity of it will exist for an extended period (half-life is greater than three years).

short-lived isotope - A radionuclide that decays so rapidly that a given quantity is transformed almost completely into decay products within a short period (half-life is two days or less).

K

K_d (equilibrium distribution coefficient) - The distribution coefficient that is the ratio of the contaminant concentration in sediments to the concentration of the contaminant in the water at equilibrium conditions. This method is used in modeling to determine the extent that a contaminant is adsorbed to sediments or desorbed to the surrounding water.

L

laboratory blank - See **internal blank**.

liquid scintillation cocktail - A solution combined with a radioactive sample which converts the energy of the particle emitted during radioactive decay into light, which is detected by a liquid scintillation counter.

liquid scintillation counter - The combination of phosphor, photomultiplier tube, and associated circuits for counting light emissions produced in the phosphors.

littoral zone - The shallow water along the shore line of a body of water.

lysimeters - A container that holds soil. A leachate collection system is located in the bottom of the container.

lower limit of detection (LLD) - The smallest concentration/amount of analyte that can be reliably detected in a sample at a 95 percent confidence level.

M

macroinvertebrates - A size-based classification used for a variety of insects and other small invertebrates; as defined by EPA, those organisms that are retained by a No. 30 (590 micron) U.S. Standard Sieve.

macrophyte - A plant that can be observed with the naked eye.

major ions - A group of analyses performed in the EPD/EMS Groundwater Monitoring Program. The ions include calcium, carbonate/bicarbonate, magnesium, potassium, and silica.

Marinelli beaker - A 1-L beaker molded to fit around a germanium or sodium iodide detector to optimize geometry.

maximally exposed individual - A hypothetical individual who remains in an uncontrolled area and would,

when all potential routes of exposure from a facility's operations are considered, receive the greatest possible dose equivalent.

mean relative difference (MRD) - a percentage error based on statistical analysis.

mercury - A silver-white, liquid metal solidifying at -38.9 °C to form a tin-white, ductile, malleable mass. It is widely distributed in the environment and biologically is a non-essential or non-beneficial element. Human poisoning due to this highly toxic element has been clinically recognized.

microbes - Microscopic organisms.

migration - The transfer or movement of a material through the air, soil, or groundwater.

milliroentgen (mR) - A measure of X-ray or gamma radiation. The unit is one-thousandth of a roentgen.

minimum detectable concentration - The smallest amount or concentration of a radionuclide that can be distinguished in a sample by a given measurement system at a preselected counting time and at a given confidence level (MDC).

monitoring - Process whereby the quantity and quality of factors that can affect the environment and/or human health are measured periodically in order to regulate and control potential impacts.

mrem - The dose equivalent which is one-thousandth of a rem.

N

natural radiation - Radiation arising from cosmic and other naturally occurring radionuclide (such as radon) sources present in the environment.

nonroutine radioactive release - Unplanned or non-scheduled release of radioactivity to the environment.

nonstochastic effects - Biological effects in which the severity in affected individuals varies with the magnitude of the dose above a threshold.

nuclide - An atom specified by its atomic weight, atomic number, and energy state. A radionuclide is a radioactive nuclide.

O

outfall - The point of conveyance (e.g., drain or pipe) of wastewater or other effluents into a ditch, pond, or river.

P

paddlewheel sampler - A water sampling device constructed of a Lexan® wheel, suspended on two pontoons and anchored in streams and rivers.

Pasquill stability classes - Ranking of atmospheric dispersion used in standard meteorology. Pasquill distinguished six stability classes from A (highly unstable stratification) to F (highly stable stratification). Criteria for Pasquill's original classification considered the relationship of wind speed, isolation (amount of incoming solar radiation), and cloudiness.

part per million (ppm) - A unit measure of concentration equivalent to the weight/volume ratio expressed as mg/L.

part per billion (ppb) - A unit measure of concentration equivalent to the weight/volume ratio expressed as mg/L or ng/mL.

perched groundwater - Unconfined groundwater separated from underlying groundwater by impermeable or non-transmissive material.

person-rem - Collective dose to a population group. For example, a dose of one rem to 10 individuals results in a collective dose of 10 person-rem.

pH - A measure of the hydrogen ion concentration in an aqueous solution. Acidic solutions have a pH from 0-6, basic solutions have a pH > 7, and neutral solutions have a pH = 7.

piezometer - An instrument used to measure the potentiometric surface of the groundwater. Also, a well designed for this purpose. See **Potentiometric surface**.

planchet - A small, round, lipped, metal dish used to mount samples for radiological analyses.

population dose commitment - (see collective dose equivalent)

precision - The closeness of approach of a value of similar or replicate results to a common value in a series of measurements.

priority pollutants - A group of approximately 130 chemicals (about 110 are organics) that appear on a U.S. Environmental Protection Agency list because they are toxic and relatively common in industrial discharges.

process water - Water used within a system process.

process sewer - Pipe or drain, generally located underground, used to carry off process water and/or waste matter.

pulse height analysis - A spectroscopy technique in which the voltage (height) of an electronic pulse from a detector is related to the energy of the detected radiation.

purge - To remove water prior to sampling, generally by pumping or bailing. Under the EPD/EMS Groundwater Monitoring Program, four well volumes are purged before sampling.

Q

quality assurance (QA) - Any action in environmental monitoring to assure the reliability of monitoring and measurement data.

quality control (QC) - The routine application of procedures within environmental monitoring to obtain the required standards of performance in monitoring and measurement processes.

quality factor - The factor by which the absorbed dose (rad) is multiplied to obtain a quantity that expresses, on a common scale for all ionizing radiation, the biological damage to exposed persons. It is used because some types of radiation, such as alpha particles, are more biologically damaging than others.

quench - (a) The reduction of the signal from a liquid scintillation cocktail due to chemical or color interferences; (b) a process by which a gas (usually a halogen) is added to a detector to inhibit avalanche ionizations.

R

rad - The unit of absorbed dose deposited in a volume of material.

radiation detection instruments - Devices that detect and record the characteristics of ionizing radiation.

radioactivity - The spontaneous emission of radiation, generally alpha or beta particles, or gamma rays, from the nucleus of an unstable isotope.

radioisotopes - Radioactive isotopes.

radionuclide - An unstable nuclide capable of spontaneous transformation into other nuclides by changing its nuclear configuration or energy level. This transformation is accompanied by the emission of photons or particles.

RCRA site - Solid waste management unit under RCRA regulation. See **Resource Conservation and Recovery Act**.

reagent - Any substance used in a chemical reaction to detect or measure another substance or to convert one substance into another by means of the reaction that it causes.

reagent blank - A control sample which is used to determine the background of each reagent or solvent used in a given method of analysis. They are composed of all constituents that will contact the sample except the sample itself.

reclamation - Recovery of wasteland, desert, etc., by ditching, filling, draining, or planting.

reference detection limit - The detection limit chosen to allow comparison of several analyses with different detection limits. For the purposes of this report, the individual detection limits of at least 90% of the analyses are less than the reference detection limit. See the **Quality Control Samples** section of this report for further information.

reference material - A material or substance with one or more properties that is sufficiently well established and used to calibrate an apparatus, to assess a measurement method, or assignment of values to materials.

reforestation - The process of planting new trees on land once forested.

refractory - Not easily decomposed or broken down.

regression analysis - A collection of statistical techniques that serve as a basis for drawing inferences about relationships among quantities in a scientific system.

release - Any discharge to the environment. Environment is broadly defined as any water, land, or ambient air.

rem - The unit of dose equivalent (absorbed dose in rads $\times$ the radiation quality factor). Dose equivalent is frequently reported in units of millirem (mrem) which is one-thousandth of a rem.

replicate - In the EPD/EMS Groundwater Monitoring Program, a second sample from the same well taken at the same time as the primary sample and sent to the same laboratory for analysis.

replicate result - The analytical result of a blind replicate sample. See **blind replicate**.

resin - An organic polymer used as an ion-exchange material.

Resource Conservation and recovery act (RCRA) - Federal legislation that regulates the transport, treatment, and disposal of solid and hazardous wastes.

RFI Program - RCRA Facility Investigation Program; EPA-regulated investigation of a solid waste management unit with regard to its potential impact on the environment.

RFI/RI Program - RCRA Facility Investigation/Remedial Investigation Program; at SRS, the expansion of the RFI Program to include CERCLA and hazardous substance regulations.

rhizotron - A facility designed to hold soil for plant and root growth. Such facilities are used often in research and study projects.

riparian - On or along a river or stream bank.

roentgen - A unit of exposure from X- or gamma rays. One roentgen equals 2.58×10^{-4} coulombs per kilogram of air.

routine radioactive release - A planned or scheduled release of radioactivity to the environment.

S

screen zone - In well construction, the section of a formation that contains the screen, or perforated pipe that allows water to enter the well.

seepage basin - An excavation that receives wastewater. Insoluble materials settle out on the floor of the basin and soluble materials seep with the water through the soil column where they are removed partially by ion

exchange with the soil. Construction may include dikes to prevent overflow or surface runoff.

self-absorption - Absorption of radiation by the sample itself, preventing detection by the counting instrument.

sensitivity - The capability of methodology or instruments to discriminate between samples with differing concentrations or containing varying amounts of analyte.

settling basin - A temporary holding basin (excavation) that receives wastewater which is subsequently discharged.

sidegradient well - A well that intercepts groundwater flowing next to a site; a sidegradient well is located neither upgradient nor downgradient to the monitored site.

sievert (Sv) - The SI (International System of Units) unit of dose equivalent, 1 Sv=100 rem.

Site-Use Approval System - A system managed by DOE-SR to control the various uses of SRS. An organization or department must request approval from DOE to use any land on SRS. Examples of the system include requests by the Savannah River Forest Station to conduct timber sales, prescribed burning, research, and building construction.

site custodian - wsrc employee responsible for the site being monitored.

slurry - A suspension of solid particles (sludge) in water.

Solid Waste Disposal Facility (SWDF) - A place for burying unwanted radioactive material to prevent escape of radioactivity. The surrounding water acts as a shield. Such material is placed in watertight, noncorrodible containers so that it cannot leach out and invade underground water.

source - A point or object from which radiation or contamination emanates.

source check - A radioactive source with a known amount of radioactivity used to check the performance of the radiation detector instrument.

source term - Quantity of radioactivity released in a set period of time that is traceable to the starting point of an effluent stream or migration pathway.

specific conductance - The ability of water to conduct electricity; this ability varies in proportion to the amount of ionized minerals in the water.

spike - The addition of a known amount of reference material containing the analyte of interest to a blank sample.

split sample - In the EPD/EMS Groundwater Monitoring Program, two samples from the same well, taken at the same time, and sent to two different laboratories for analysis.

SRS stream - Any natural stream on the SRS site. Surface drainage of the site is via these streams to the Savannah River.

stable - Not radioactive or not easily decomposed or otherwise modified chemically.

stack - A vertical pipe or flue designed to exhaust airborne gases and suspended particulate matter.

standard deviation - An indication of the dispersion of a set of results around their average.

standard reference material (SRM) - A reference material distributed and certified by the National Institute of Standards and Technology.

stochastic effects - Biological effects, whose probability, rather than the severity, is a function of the magnitude of the radiation dose without threshold (i.e., stochastic effects are random in nature).

strata - beds, layers, or zones of rocks.

substrate - The substance, base, surface, or medium in which an organism lives and grows.

sulfate - Sulfate is widely distributed in nature and may be present in natural waters in concentrations ranging from a few to several thousand mg/l. Mine drainage wastes may contribute high sulfate by virtue of pyrite oxidation. The recommended sulfate level in portable supplies is limited to 250 mg/L.

supernatant - The portion of a liquid above settled materials in a tank or other vessel.

surface water - All water on the surface of the earth, as distinguished from groundwater.

T

temperature - the thermal state of a body considered with its ability to communicate heat to other bodies.

tank farm - An installation of interconnected underground tanks for storage of high-level radioactive liquid wastes.

taxa richness - The abundance of any rank such as a particular species, family, or class.

terrestrial radiation - Ionizing radiation emitted from radioactive materials, primarily ^{40}K , thorium, and uranium, in the earth's soils. Terrestrial radiation contributes to natural background radiation.

thermoluminescent dosimeters (TLDs) - A device used to measure external gamma radiation.

timber compartment - A tract of SRS land divided into 2,000-acre sections for inventory purposes (i.e., wildlife, research opportunities, timber management, and soil stabilization and secondary road maintenance needs).

timber compartment prescriptions - A plan used to manage resources within a timber compartment.

TOC (top of casing) - The elevation of the top of the well casing used as a reference for water depth measurements.

total activity - The total quantity of radioactive decay particles that are emitted from a sample.

total dissolved solids - Dissolved solids and total dissolved solids are terms generally associated with freshwater systems and consist of inorganic salts, small amounts of organic matter and dissolved materials.

total phosphorus - When concentrations exceed 25 mg/L at the time of the spring turnover on a volume-weighted basis in lakes or reservoirs, it may occasionally stimulate excessive or nuisance growths of algae and other aquatic plants.

total organic halogens - A measure of the total concentration of organic compounds that have one or more halogen atoms.

total solids - The sum total of total dissolved solids and suspended solids.

total suspended particulates - Refers to the concentration of particulates in suspension in the air irrespective of the nature, source, or size of the particulates.

transect - A line across an area being studied. The line is composed of points where specific measurements or samples are taken.

transmissive zone - A zone of sediments that is sufficiently porous and permeable to allow the flow of groundwater through the zone.

transuranic (TRU) waste - Solid radioactive waste containing primarily alpha-emitting elements heavier than uranium.

transuranium elements - Elements with higher atomic weights than uranium; all 13 known transuranic elements are radioactive and are produced artificially.

trifluralin - An organic chemical [C₁₃H₁₆F₃N₃O₄] used commercially as an herbicide on a variety of crops. This chemical is currently being tested at SRS in bio-barrier research.

trip blank - A sample container of deionized water that is transported to the well sample location, treated as a well sample, and sent to the laboratory for analysis; trip blanks are used to check for contamination resulting from transport, shipping, and site conditions.

tritium (³H) - The hydrogen isotope with one proton and two neutrons in the nucleus. It emits a low-energy beta particle (0.0186 MeV max) and has a half-life of 12.5 years.

t-test - Statistical method used to determine if the means of groups of observations are equal.

turbidity - A measure of the concentration of sediment or suspended particles in solution.

U

uncontrolled area - Any area to which access is not controlled for the purpose of protecting individuals from exposure to radiation and radioactive materials.

The area beyond the boundary of SRS is an uncontrolled area.

upgradient - In the direction of increasing hydrostatic head.

V

vadose zone - Soil zone located above the water table.

variation - The divergence in the structural or functional characteristics of an organism from those considered typical of the group to which it belongs.

volatile organic compounds - 1, 1, 1-TCE, Perclene, Triclene are common names for trichloroethane, tetrachloroethylene, and trichloroethylene, respectively. Used in many processes, the levels of these carcinogenic compounds must be kept to a minimum. They are measured by volatile organic analyses content.

W

watershed - The region draining into a river, river system, or body of water.

weighting factor - A value used to calculate dose equivalents. It is tissue-specific and represents the fraction of the total health risk resulting from uniform, whole-body irradiation that could be contributed to that particular tissue. The weighting factors used in this report are recommended by the ICRP (Publication 26).

wetlands - A lowland area, such as a marsh or swamp, inundated or saturated by surface or groundwater sufficiently to support hydrophytic vegetation typically adapted for life in saturated soils.

worldwide fallout - Radioactive debris from atmospheric weapons tests that has been deposited on the earth's surface after being airborne and cycling around the earth.

Z

zooplankton - microscopic animals that live in aquatic environments (e.g., copepods).

Appendix A

SRS Environmental Permits

Listed below are the construction and operating permits held by SRS. The permits are divided by type of permit; for each type, the permit number, permit title, and permitted source are provided.

AIR PERMITS

Permit Number	Permit Title
0080-0042-01	71.1 MMBTU/HR COAL BOILER #1; CYCLONES 784-A
0080-0042-02	71.1 MMBTU/HR COAL BOILER #2; CYCLONES, 784-A
0080-0042-03	600 KW EMERGENCY POWER DIESEL GENERATOR, 794-A
0080-0042-04	400 KW EMERGENCY POWER DIESEL GENERATOR, 773-A
0080-0042-07	200 KW EMERGENCY POWER DIESEL GENERATOR, 777-10A
0080-0042-05	150 KW EMERGENCY POWER DIESEL GENERATOR, 751-A
0080-0042-06	400 KW EMERGENCY POWER DIESEL GENERATOR, South of 774-A
0080-0042-CB	250 KW STANDBY DIESEL DRIVEN ELECTRIC GENERATOR, 754-4A (EMERGENCY POWER DIESEL)
0080-0042-CC	455 KW EMERGENCY POWER DIESEL GENERATOR, 720-2A
0080-0042-CD	1250 KW DIESEL GENERATOR #1, 754-5A (EMERGENCY POWER TO 703-44A)
0080-0042-CE	1250 KW DIESEL GENERATOR #2, 754-5A (EMERGENCY POWER TO 703-44A)
0080-0042-CF	70 GPM AIR STRIPPER, SRL
0080-0042-CG	2500 GPM (370 BHP) DIESEL FIRE PUMP, CENTRAL SHOPS (MATERIALS MGT REC'G & STORAGE)
0080-0042-CH	2500 GPM (370 BHP) DIESEL FIRE PUMP, B-AREA
0080-0042-CI	2500 GPM (330 BHP) DIESEL FIRE PUMP #1, 241-125H
0080-0042-CI	2500 GPM (330 BHP) DIESEL FIRE PUMP #2, 241-125H
0080-0042-CJ	WASTE PAINT SOLVENTS DISTILLATION AND CONDENSATION UNIT #1, CENTRAL SHOPS

0080-0042-CJ	WASTE PAINT SOLVENTS DISTILLATION AND CONDENSATION UNIT #2,CENTRAL SHOPS
0080-0043-01	225 KW EMERGENCY POWER DIESEL GENERATOR, 152-7C
0080-0043-CA	365 KW EMERGENCY POWER DIESEL GENERATOR, 183-2C
0080-0044-01	396 MMBTU/HR COAL BOILER #1, CYCLONES, ESP, 484-D
0080-0044-02	396 MMBTU/HR COAL BOILER #2, CYCLONES, ESP, 484-D
0080-0044-03	396 MMBTU/HR COAL BOILER #3, CYCLONES, ESP, 484-D
0080-0044-04	396 MMBTU/HR COAL BOILER #4, CYCLONES, ESP, 484-D
0080-0044-05	150 KW EMERGENCY POWER DIESEL GENERATOR, 501-D
0080-0044-06	1.1 TON/HR REJECT SYSTEM; BAGHOUSE, 484-D
0080-0044-07	300 TON/HR COAL CRUSHER, 484-D
0080-0045-06	200 KW CONTINUOUS RUNNING DIESEL GENERATOR, 254-5F #1
0080-0045-05	URANIUM DISSOLUTION, 221-F (PENDING ENFORCEMENT ACTION RESOLUTION)
0080-0045-13	250 KW EMERGENCY POWER DIESEL GENERATOR, 254-1F
0080-0045-14	200 KW EMERGENCY POWER DIESEL GENERATOR, 241-74F
0080-0045-24	FUEL MATERIALS FACILITY (FMF) MAIN STACK - (SCRUBBERS & HEPA FILTERS), 247-F
0080-0045-25	FMF WASTEWATER TREATMENT FACILITY - (DEMISTER), 247-F
0080-0045-07	200 KW CONTINUOUS RUNNING DIESEL GENERATOR, 254-5F #2
0080-0045-11	350 KW EMERGENCY POWER DIESEL GENERATOR, 235-F
0080-0045-12	350 KW EMERGENCY POWER DIESEL GENERATOR, 254-4F
0080-0045-19	300 KW EMERGENCY POWER DIESEL GENERATOR, 292-2F
0080-0045-22	600 KW EMERGENCY POWER DIESEL GENERATOR, 254-10F
0080-0045-15	600 KW EMERGENCY POWER DIESEL GENERATOR, 292-F
0080-0045-16	600 KW EMERGENCY POWER DIESEL GENERATOR, 247-1F (FMF)
0080-0045-26	NINE FINISHING PROCESSES FOR FMF, 247-F
0080-0045-08	175 KW EMERGENCY POWER DIESEL GENERATOR, 772-F #1
0080-0045-18	415 KW EMERGENCY POWER DIESEL GENERATOR, 772-1F

0080-0045-09	175 KW EMERGENCY POWER DIESEL GENERATOR, 772-F #2
0080-0045-17	315 KW EMERGENCY POWER DIESEL GENERATOR, 221-FB
0080-0045-21	1000 KW EMERGENCY POWER DIESEL GENERATOR, 221-F
0080-0045-20	300 KW EMERGENCY POWER DIESEL GENERATOR, 254-9F
0080-0045-10	350 KW EMERGENCY POWER DIESEL GENERATOR, 241-19F
0080-0045-23	350 KW EMERGENCY POWER DIESEL GENERATOR, 254-8F
0080-0045-CJ	455 KW EMERGENCY POWER DIESEL GENERATOR, 720-F
0080-0045-CK	NEW SPECIAL RECOVERY FACILITY, 221-F
0080-0046-01	71.7 MMBTU/HR COAL BOILER #1; 2 CYCLONES, 784-H
0080-0046-02	71.7 MMBTU/HR COAL BOILER #2; 2 CYCLONES, 784-H
0080-0046-03	71.7 MMBTU/HR COAL BOILER #3; 2 CYCLONES, 784-H
0080-0046-04	400 LBS/HR TYPE "O" WASTE INCINERATOR, BAGHOUSE & HEPA FILTERS (BETA-GAMMA INCINERATOR)
0080-0046-05	SEPARATION PROCESS, 221-H
0080-0046-06	200 KW EMERGENCY POWER DIESEL GENERATOR, 234-4H
0080-0046-07	200 KW EMERGENCY POWER DIESEL GENERATOR, 299-1H
0080-0046-08	200 KW EMERGENCY POWER DIESEL GENERATOR, 241-74H
0080-0046-09	250 KW EMERGENCY POWER DIESEL GENERATOR, 254-1H
0080-0046-10	275 KW EMERGENCY POWER DIESEL GENERATOR, 254-3H
0080-0046-12	300 KW NORMAL/EMERGENCY POWER DIESEL GENERATOR, 254-5H, #1
0080-0046-13	300 KW NORMAL/EMERGENCY POWER DIESEL GENERATOR, 254-5H, #2
0080-0046-14	300 KW EMERGENCY POWER DIESEL GENERATOR, 232-H
0080-0046-15	300 KW EMERGENCY POWER DIESEL GENERATOR, 234-H
0080-0046-17	500 KW EMERGENCY POWER DIESEL GENERATOR, 254-H
0080-0046-18	600 KW EMERGENCY POWER DIESEL GENERATOR, 292-H
0080-0046-11	300 KW EMERGENCY POWER DIESEL GENERATOR, 221-HB
0080-0046-16	500 KW EMERGENCY POWER DIESEL GENERATOR, 232-H #2
0080-0046-19	1000 KW EMERGENCY POWER DIESEL GENERATOR, 221-H

0080-0046-CD	ALTER TANKS 48H AND 49H TO USE FOR IN-TANK PRECIPITATION PROCESS
0080-0046-CE	150 KW EMERGENCY POWER DIESEL GENERATOR, 241-96H
0080-0046-CG	765 KW EMERGENCY POWER DIESEL GENERATOR, 233-H (RTF)
0080-0046-20	500 KW EMERGENCY POWER DIESEL GENERATOR, 254-8H
0080-0046-21	400 KW EMERGENCY POWER DIESEL GENERATOR, 254-9H
0080-0046-CJ	455 KW EMERGENCY POWER DIESEL GENERATOR, 720-H
0080-0047-03	1250 KW EMERGENCY POWER DIESEL GENERATOR, 108-1K
0080-0047-04	1250 KW EMERGENCY POWER DIESEL GENERATOR, 108-2K
0080-0047-05	150 KW EMERGENCY POWER DIESEL GENERATOR, 108-4K, #1
0080-0047-06	150 KW EMERGENCY POWER DIESEL GENERATOR, 108-4K, #2
0080-0047-09	520 BHP EMERGENCY DIESEL BOOSTER PUMP, 191-K (SERVING 105-K)
0080-0047-01	194.5 MMBTU/HR COAL BOILER, CYCLONES; UNIT #1
0080-0047-07	200 KW EMERGENCY POWER DIESEL GENERATOR, 152-7K
0080-0047-08	365 KW EMERGENCY POWER DIESEL GENERATOR, 183-2K
0080-0047-CB	800 KW EMERGENCY POWER DIESEL GENERATOR-A, 107-K
0080-0047-CB	800 KW EMERGENCY POWER DIESEL GENERATOR-B, 107-K
0080-0047-CC	76.8 MMBTU/HR OIL FIRED BOILER, K-AREA
0080-0048-02	194.5 MMBTU/HR COAL BOILER, CYCLONES, 184-P #2
0080-0048-03	1250 KW EMERGENCY POWER DIESEL GENERATOR, 108-1P
0080-0048-04	1250 KW EMERGENCY POWER DIESEL GENERATOR, 108-2P
0080-0048-05	150 KW EMERGENCY POWER DIESEL GENERATOR, 108-4P, #1
0080-0048-06	150 KW EMERGENCY POWER DIESEL GENERATOR, 108-4P, #2
0080-0048-09	520 BHP EMERGENCY DIESEL BOOSTER PUMP, 191-P (SERVING 105-P)
0080-0048-07	225 KW EMERGENCY POWER DIESEL GENERATOR, 152-7P
0080-0048-08	365 KW EMERGENCY POWER DIESEL GENERATOR, 183-2P
0080-0048-CB	800 KW EMERGENCY POWER DIESEL GENERATOR-A, 107-3P
0080-0048-CC	800 KW EMERGENCY POWER DIESEL GENERATOR-B, 107-2P

0080-0048-CD	38 MMBTU/HR PACKAGE STEAM GENERATOR, K-AREA
0080-0049-01	1250 KW EMERGENCY POWER DIESEL GENERATOR, 108-1L
0080-0049-02	1250 KW EMERGENCY POWER DIESEL GENERATOR, 108-2L
0080-0049-03	520 BHP EMERGENCY DIESEL BOOSTER PUMP, 191-L
0080-0049-04	150 KW EMERGENCY POWER DIESEL GENERATOR, 108-4L, #1
0080-0049-05	150 KW EMERGENCY POWER DIESEL GENERATOR, 108-4L, #2
0080-0049-06	225 KW EMERGENCY POWER DIESEL GENERATOR, 152-7L
0080-0049-07	365 KW EMERGENCY POWER DIESEL GENERATOR, 183-2L
0080-0049-CB	800 KW EMERGENCY POWER DIESEL GENERATOR-A, 107-L
0080-0049-CC	800 KW EMERGENCY POWER DIESEL GENERATOR-B, 107-L
0080-0055-01	URANIUM METAL CLEANING WITH NITRIC ACID, 313-M
0080-0055-02	ALUMINUM TUBE CLEANING WITH NITRIC ACID, 321-M
0080-0055-04	610 GPM AIR STRIPPER, M-AREA
0080-0055-03	200 KW EMERGENCY POWER DIESEL GENERATOR, 320-M (REPLACED 150)
0080-0060-02	300 KW EMERGENCY POWER DIESEL GENERATOR, 673-T
0080-0060-04	20 LBS/HR SHIRCO INCINERATOR, HEPA FILTERS, 677-T
0080-0060-03	300 KW EMERGENCY POWER DIESEL GENERATOR, 672-T
0080-0060-05	PROCESS TO DECOMPOSE TETRAPHENYLBORATE INTO AQUEOUS AND ORGANIC PORTIONS, 682-T
0080-0060-CE	300 KW EMERGENCY POWER DIESEL GENERATOR, 654-T (SERVING 678-T)
0080-0060-06	1000 KW EMERGENCY POWER DIESEL GENERATOR, 654-1T
0080-0066-05	2000 KW EMERGENCY POWER DIESEL GENERATOR #1, 292-S
0080-0066-CA	DWPF VITRIFICATION PROCESS, 221-S
0080-0066-06	2000 KW EMERGENCY POWER DIESEL GENERATOR #2, 292-S
0080-0066-CC	187 KW EMERGENCY POWER DIESEL GENERATOR, 980-S
0080-0080-02	SILO TO STORE CEMENT, WITH BAGHOUSE
0080-0080-01	425 KW EMERGENCY POWER DIESEL GENERATOR
0080-0080-03	THREE FLY ASH SILOS WITH BAGHOUSE

0080-0080-04	WEIGH HOPPER WITH BAGHOUSE
0080-0080-05	TWO PREMIX AIR BLENDERS WITH BAGHOUSE
0080-0080-06	PREMIX FEED BIN WITH BAGHOUSE
0080-0080-07	GROUT MIXER WITH BAGHOUSE, SCRUBBER, AND 2 HEPA FILTERS (1 IN SERVICE, 1 STANDBY)
0080-0080-02	MODIFICATION TO 0080-0080-02; SILO TO STORE CEMENT OR SLAG, WITH BAGHOUSE
0080-0080-CI	MODIFICATION TO 0080-0080-07 TO INCLUDE VOC EMISSIONS FROM STACK (Z-AREA)
0080-0080-08	LOW-POINT DRAIN TANK VENT WITH HEPA FILTER (Z-AREA)
VERBAL APPROVAL TO CONSTRUCT 15,000 LB/HR PORTABLE PACKAGE STEAM GENERATOR #1, GENERAL SITE	
VERBAL APPROVAL TO CONSTRUCT 15,000 LB/HR PORTABLE PACKAGE STEAM GENERATOR #2, GENERAL SITE	

DOMESTIC WATER

Permit Number	Permit Title
111626	UPGRADE GASEOUS CHLORINATION FACILITY; 683-D
200092	DEEP WELLS, 905-104L, 904-105L
200279	INSTALL DOMESTIC DEEPWELL 905-120P; P-AREA
201715	DOMESTIC DEEPWELL, RAILROAD CLASSIFICATION YARD, 905-107G
202822	D-AREA DOMESTIC WATER SYSTEM (TEST WELL)
202915	WATER SUPPLY AND WELL SYSTEM, DWPF CONSTRUCTION SUPPORT AREA
203427	SODIUM HYPOCHLORITE SYSTEM, 280-F
203467	SODIUM HYPOCHLORITE SYSTEM, 280-H
203590	100-AREA FIRE STATION WELL, 709-1G (INTERSECTION OF ROAD C & ROAD 7)
203628	REPLACE PISTOL RANGE WELL
203638	REPLACE ALLENDALE BARRICADE WELL
203786	DRINKING WATER WELL 905-114G, TO SERVE 681-3G
204138	INSTALL DOMESTIC DEEPWELL 905-106K (REPLACE WELL 905-94K)

204198	REPLACE DOMESTIC DEEPWELL, 905-66H
205217	UPGRADE INSTRUMENTATION 280-1H; (F AREA ALSO COVERED UNDER THIS PERMIT)
205217	UPGRADE INSTRUMENTATION 280-1F; (H AREA ALSO COVERED UNDER- THIS PERMIT)
205877	AUGUSTA BARRICADE WATER WELL, 905-116G
206501	B-AREA DOMESTIC DEEPWELL, 905-125B (TEST WELL)
206575	DOMESTIC WATER DEEPWELLS AND DISTRIBUTION LINE, A-AREA
207005	ACTIVATED CARBON TREATMENT SYSTEM, 3/700 AREA
208201	DOMESTIC TEST WELL AT K-COOLING TOWER SITE
208425 & 208425AI	ATTA DOMESTIC WATER SYSTEM
208434	DOMESTIC WATER SYSTEM, BARRICADES 701-8G, 701-12G, 701-13G
208866	DOMESTIC WATER WELL FOR AIKEN BARRICADE GATE HOUSE (701-5G)
209191	PAR POND DOMESTIC TEST WELL
209454	TNX DOMESTIC WATER SYSTEM AND WELL
210657	INSTALL DOMESTIC DEEPWELL 905-103F (REPLACE WELL 905-39F) AND DISTRIBUTION SYSTEM
212745	DWPF DOMESTIC WATER WELLS 1 AND 2
400347	DOMESTIC WATER HEADERS, TNX AREA
400737	WATER LINE, DWPF, Z AREA
401118	DOMESTIC WATER FOR NWTF
401446	PRODUCTION CONTROL FACILITY FOR 200 AREA PROCESS 772-1F
402186	DWPF DOMESTIC WATER DISTR. SYSTEM
402874	SEGREGATED DOMESTIC WATER SUPPLY, 300/700 AREA, PHASE I
402925-RI	DWPF TEMPORARY DOMESTIC WATER
403434	SEGREGATED DOMESTIC WATER SUPPLY, 300/700 AREA, PHASE II
404608	717-K DOMESTIC WATER
404618	7C5-C DOMESTIC WATER
405184	WATER LINE, 773-41A, 773-42A

405556	DOMESTIC WATER SYSTEM, 200-H
405566	UPGRADE DOMESTIC WATER SYSTEM, 200-F
406137	INTERIM STORAGE AND REDRUMMING FAC., DOMESTIC WATER, 709-1G, 709-2G
406871	DOMESTIC WATER TO SERVE ENGINEERING CENTER, B-AREA
407830	MATERIAL MANAGEMENT RECEIVING & STORAGE FACILITY, CENTRAL SHOPS
408221	K-AREA DOMESTIC WATER TREATMENT AND DISTRIBUTION SYSTEM UPGRADE
408285	DOMESTIC WATER SERVICE FOR SANITARY WASTE TREATMENT FACILITY, TNX
408595	DOMESTIC WATER LINE, CONSTRUCTION OFFICE BUILDING, 300-M
409484	WATER LINE, REACTOR SIMULATOR FACILITY, 707-C
409955	DOMESTIC WATER & FIRE PROTECTION FOR HELICOPTER FACILITY; 703-5G & 703-6G
410406	DRINKING WATER SYSTEM, 777-A
411337	INSTALL SODIUM HYPOCHLORITE SYSTEM, 780-A
411357	ETF-H LIFT STATION DOMESTIC WATER
411995	WATER DISTRIBUTION SYSTEM, 340-M, 341-M
41225	3/700 A-AREA WATER LINE FROM NEW DOMESTIC WELLS
412917	DRINKING WATER SYSTEM, ETF, 241-84H, 241-81H
48061	TEMPORARY WATER SYSTEM, 905-104L, 904-105L
LS-1-W	WATER LINE, TRITIUM FACILITIES SUPPORT BLDG, 235-H
LS-106-W	DWPF AUXILIARY PUMP PIT WATER LINES, S-511
LS-11-W	WATER LINE, NAVAL FUELS MATERIAL FACILITY (FMF), 247-F
LS-115-W	WATER LINE, CRAFTS & ENGINEERS, CAB/CENTRAL SHOP
LS-118-W	WATER LINE, 719-4A
LS-119-W	WATER LINE, 730-M
LS-139-W	REPLACE TRITIUM FACILITY DOMESTIC WATER, 233-H, 249-H
LS-168-W	WATERLINE TO SERVE BLDG. 716-2A

LS-178-W	COMPUTER REPAIR BUILDING DOMESTIC WATER, 722-5A
LS-185-W	DOMESTIC WATER MAIN, 901-A
LS-187-W	ETF-F LIFT STATION DOMESTIC WATER
LS-232-W	TEMPORARY DOMESTIC WATER FOR FPF & RTF FACILITIES
LS-233-W	TEMPORARY DOMESTIC WATER FOR F/H ETF CONSTRUCTION OFFICE
LS-238-W	ECF/CAS SECURITY UPGRADE FACILITIES, H-AREA (720-H & 701-3H)
LS-25-W	CHEMICAL FEED FACILITY WATER SYSTEM, 100-C
LS-264-W	CENTRAL SHOPS CONSTRUCTION DIV. QUALITY OFFICE BLDG.
LS-265-W	DOM WATER SUPPLY FOR EQUIPMENT STORAGE & HEALTH PROTECTION (HP) FAC. , 221-25F
LS-4-W	WATER LINE, OFFICE BLDG., 703-41A
LS-43-W	"AS BUILT" TECHNICAL AREA WATER MAIN BYPASS, 773-14A
LS-55-W	DOMESTIC WATER SUPPLY FOR CHEMICAL FEED FACILITIES IN G&H AREAS (G-AREA)
LS-56-W	DOMESTIC WATER SUPPLY FOR CHEMICAL FEED FACILITIES IN G&H AREAS (H-AREA)
LS-57-W	DOMESTIC WATER LINE RELOCATION & SERVICE LINE INSTALL BLDG. 735-11A
LS-59-W	WATER SYSTEM, DWPF ICE HOUSE
LS-60-W	DOMESTIC WATER LINE FOR 704-S ADMINISTRATION BLDG. DWPF
LS-61-W	DOMESTIC WATER LINE TO FEED DWPF SANITARY TREATMENT PLANT
LS-7-W	WATER LINE, NAVAL FUELS MATERIAL FACILITY (FMF), 221-17F, 221-18F
LS-8-W	WATER LINE, 703-4A, 703-6A, 703-34A
LS-81-W	DOMESTIC WATER FOR CONSTRUCTION OFFICE BLDG., C-AREA
LS-82-W	DOMESTIC WATER FOR SANITARY TREATMENT FACILITY, B-AREA
LS-91009	TEMPORARY MODULAR OFFICE TRAILER, 245-F THROUGH 245-12F
LS89002	TEMPORARY MODULAR OFFICES, 100-C
LS89008	EXPANSION OF DOM. WATER & FIRE PROTECTION FOR MODULAR OFFICES, B-AREA
LS89016	RELOCATION OF DOMESTIC WATER LINE AT L-AREA EQ BASIN

LS89017	TEMPORARY MODULAR OFFICE TRAILERS, 707-7K THRU 707-19K
LS89020	INSTALL BLOCK VALVE ON 200-F AREA WELL WATER HEADER
LS89028	WATER DISTRIBUTION SYSTEM TO SERVE TRAILER 777-18A
LS89029	MATERIAL MANAGEMENT, RECEIVING & STORAGE FACILITIES FIRE TANK MAKEUP
LS91001	TEMPORARY MODULAR OFFICE TRAILERS 773-62A THROUGH 773-70A
LS91005	DOMESTIC WATER LINE TO FILL ITP FIRE TANK, 241-20H
LS91006	DOMESTIC WATER LINE TO FILL ITP FIRE TANK, 241-21H
LS91007	REROUTE DOM. WATER LINE-REPLACEMENT HIGH LEVEL EVAPORATOR, H-AREA
LS91010	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, B-AREA
LS91011	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, 3/700-AREA
LS91012	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, C-AREA
LS91013	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, CS-AREA
LS91014	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, D-AREA
LS91015	UPGRADE DOM WATER SYSTEMS INSTRUMENTS, FORESTRY AREA
LS91016	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, L-AREA
LS91017	UPGRADE DOMESTIC WATER SYSTEMS INSTRUMENTS, P-AREA
LS91018	UPGRADE DOM WATER SYSTEMS INSTRUMENTS, RAILROAD YARD
M0012	DOMESTIC WATER FILL LINE FOR FIRE WATER TANK, B-AREA (ISSUED BY EPD UNDER MODIFIED PERMITTING PROGRAM (MPP))
M0022	PORTABLE BOILER INSTALLATION, 183-2P (ISSUED BY EPD UNDER MODIFIED PERMITTING PROGRAM (MPP))
M0032	PORTABLE BOILER INSTALLATION, 183-2K (ISSUED BY EPD UNDER MODIFIED PERMITTING PROGRAM (MPP))
M0042	773-72A LUNCHROOM TRAILER (ISSUED BY EPD UNDER MODIFIED PERMITTING PROGRAM (MPP))

INDUSTRIAL SOLID WASTE

Permit Number	Permit Title
CWP-030	BURMA ROAD INERT LANDFILL

DWP-087A	INDUSTRIAL WASTE DISPOSAL FACILITY (SANITARY LANDFILL)
IWP-210	D-F STEAMLINE EROSION CONTROL SITE
IWP-211	200-H EROSION CONTROL SITE
IWP-217	Z-AREA SALTSTONE DISPOSAL FACILITY (SOLID WASTE) - MODIFICATION
IWP-219	200-F EROSION CONTROL SITE

INDUSTRIAL WASTEWATER

Permit Number	Permit Title
10253	M-AREA 610 GPM AIR STRIPPER
10287	LIQUID EFFLUENT TREATMENT FACILITIES, 300-M (LETf)
10349	672-T TNX PROCESS SEWER TO OUTFALL X-008
10358	S-AREA OIL SEPARATOR
10389	M-AREA DRAIN LINE
10469	735-11A LAB BLDG. PROCESS SEWER SYSTEM NEUTRALIZATION FAC. 607-17A
10475	NON-CONTACT COOLING WATER DIVERSION, 300-M AREA
10696	INTERIM SLUDGE STORAGE TANK, M-AREA
10765	WASTEWATER NEUTRALIZATION FACILITY, 704-B
10778	WASTEWATER TREATMENT FACILITY, NAVAL FUEL (FMF)
10920	SREL WASTEWATER DISINFECTION FACILITY
10949	TRADE WASTE FLOW EQUALIZATION TANK, 607-18A FOR 703-43A SILVER REC.
10955	DWPF CONCRETE BATCH PLANT WASTEWATER TREATMENT POND, S- AREA
11406	FIRE BRIGADE TRAINING FACILITIES OIL SEPARATOR, 411-D
11411	DWPF TREATED EFFLUENT LINE
11413	DWPF CHEMICAL TREATMENT FACILITY, S-AREA
11497	PRODUCTION CONTROL FACILITY SANITARY/PROCESS SEWER, 772 - 1F
11498	FLOW MONITORING STATION FOR NPDES OUTFALL L-007
11588	POWERHOUSE EFFLUENT DIVERSION TO ASH BASINS; 200-D (H-AREA ALSO COVERED UNDER THIS PERMIT)

11588	POWERHOUSE EFFLUENT DIVERSION TO ASH BASINS; 200-H (D-AREA ALSO COVERED UNDER THIS PERMIT)
11589	POWERHOUSE EFFLUENT DIVERSION TO ASH BASIN, 184-P (184-K ALSO COVERED UNDER THIS PERMIT)
12622	ORGANICS REMOVAL FACILITY, TNX
12633	EFFLUENT TREATMENT PLANT, TNX (ETP)
12683	Z-AREA SALTSTONE MFG. FAC.
12782	RTF PROCESS SEWER
12870	EFFLUENT TREATMENT FACILITY - F/H ETF
12888	METALLURGICAL LABORATORY NEUTRALIZATION FACILITY, 723-A
12894	FILTRATE HOLD TANK COVERS, M AREA
12922	MODIFICATIONS TO NAVAL FUEL (FMF) WASTEWATER TREATMENT FACILITY; PIPING MOD.
12973	P-AREA NEUTRALIZATION FACILITY, 183-2P
13105	ETF PROCESS SEWER LINES, F/H-AREA
13154	FLOW MEASUREMENT DEVICE, L AREA
13354	D-AREA NEUTRALIZATION FACILITY, 483-1D
13355	F-AREA NEUTRALIZATION FACILITY, 280-1F
13356	H-AREA NEUTRALIZATION FACILITY, 280-H
13357	K-AREA NEUTRALIZATION FACILITY, 183-2K
13431	FLUME AT M-004 OUTFALL
13456	L-TANK "AS BUILT"; SRL
13734	INDUSTRIAL WASTEWATER pH CONTROL SYSTEM, 211-H
13,735	INDUSTRIAL WASTEWATER pH CONTROL SYSTEM, 211-F
13978	TNX ION EXCHANGE FACILITY
14020	MERCURY AND ORGANIC REMOVAL FACILITY FOR F/H ETF
14068	M-BASIN CLOSURE WASTEWATER TREATMENT FACILITY (M-AREA BASIN)
14100	REPAIR ASH BASIN DIKE 488-1D
14214	MODIFICATIONS TO NAVAL FUEL (FMF) WW TREATMENT FACILITY; BATCH MIXER SYSTEM

14218	NPDES OUTFALL STRUCTURES F-012 & F-013 (FLOW MONITORING WEIR-BOX STRUCTURES)
14219	NPDES OUTFALL STRUCTURES H-017 & H-018 (MONITORING WEIR BOX STRUCTURES)
14338	"AS-BUILT" H-Z INTER-AREA SALT SOLUTION TRANSFER LINE
14338	"AS-BUILT" H-Z INTER-AREA SALT SOLUTION TRANSFER LINE
14379	UPPER THREE RUNS CREEK DIFFUSER (FOR F&H ETF - OUTFALL H-016)
14520	F&H ETF TANK 50 AS-BUILT
14624	EXISTING F/H ETF AREA PROCESS SEWER LINES
14832	SUPERNATANT TRANSFER & POLYMER ADDITION SYSTEMS IN M-AREA LETF (MOD. TO #10,287)
15256	EVAPORATOR RECYCLE LINE FOR F/H ETF
15467	UPGRADE PROCESS SEWERS, 211- F/H ETF (211-F&H)
15892	F/H ETF INTERIM pH ADJUSTMENT SYSTEM (CAUSTIC & ACID SUPPLY)
16119	F/H ETF PERMANENT pH ADJUSTMENT SYSTEM
16449	K-REACTOR EMERGENCY RETENTION BASIN PERCOLATION DRAIN-FIELD
16478	FOUNDATIONS & SUPP. STRUCTURE SURROUNDING CWST; K RETENTION BASIN
16614	K-REACTOR EMERGENCY RETENTION BASIN LINER AND COVER
16783	"AS BUILT" DWPF INDUSTRIAL WASTEWATER TREATMENT FACILITY
16785	K-AREA NATURAL DRAFT COOLING TOWER THERMAL MITIGATION
16797	(70 GPM AIR STRIPPER) PROTOTYPE AIR STRIPPER COLUMN RELOCATION & RECOVERY WELL INSTALL.
16938	K-REACTOR RETENTION BASIN UMBRELLA TOP STRUCTURE
17022	UPGRADE D-AREA NEUTRALIZATION FACILITY, 483-1D
7289	"AS BUILT" WASTEWATER TREATMENT FACILITIES, A-AREA (M-AREA ALSO COVERED UNDER THIS PERMIT)
7289	"AS BUILT" WASTEWATER TREATMENT FACILITIES, M-AREA (A-AREA ALSO COVERED UNDER THIS PERMIT)
7290	"AS BUILT" WASTEWATER TREATMENT FACILITIES, F-AREA
7291	"AS BUILT" WASTEWATER TREATMENT FACILITIES, H-AREA

7292	"AS BUILT" WASTEWATER TREATMENT FACILITIES, P-AREA
7293	"AS BUILT" WASTEWATER TREATMENT FACILITIES, K-AREA
7294	"AS BUILT" WASTEWATER TREATMENT FACILITIES, C-AREA
7295	"AS BUILT" WASTEWATER TREATMENT FACILITIES, D-AREA
7296	"AS BUILT" WASTEWATER TREATMENT FACILITIES, CS AREA
9886	50 GPM AIR STRIPPER; M-AREA (RELOCATED TO SRL-NOW 70 GPM)
9974	CONCRETE BATCH PLANT, S-AREA
LS-112-S	FIRE TRAINING FACILITY PROCESS SEWER, 904-D
LS-42-S	INERT L FACILITY LOADING DOCK SEWER RELOCATION, 234-H
SC 88-D-005	F/H ETF DIFFUSER (PERMIT APPL. TO S.C. WATER RESOURCES COMM. SCWRC)

MAINTENANCE DREDGING

Permit Number	Permit Title
84-2Z-209	MAINTENANCE DREDGING IN RAW WATER INTAKE CANALS (681-1G, 681-3G, & 681-5G) ON SAVANNAH RIVER

SANITARY WASTEWATER

Permit Number	Permit Title
02-91040041	SEPTIC TANK AND DRAINFIELD; OFFICE BLDG. 5002-H
10131-P	SEPTIC TANK AND DRAIN FIELD FOR RTF CONSTRUCTION ENGINEERS OFFICE
10132-P	SEPTIC TANK AND DRAIN FIELD FOR FPF CONSTRUCTION ENGINEERS OFFICE
10236	LIFT STATION, CHANGE STATION FACILITY, 241-58H
10314	DWPF CONSTRUCTION SITE SANITARY SEWER SYSTEM
10499	DWPF SANITARY SEWER SYSTEM, 200-S
10521	CHEMICAL FEED FACILITY, A-AREA
10522	CHEMICAL FEED FACILITY, F-AREA
10523	CHEMICAL FEED FACILITY, H-AREA
10524	CHEMICAL FEED FACILITY, P-AREA

10525	CHEMICAL FEED FACILITY, G-AREA
10526	CHEMICAL FEED FACILITY, D-AREA
10530	TNX SANITARY WASTEWATER TREATMENT PLANT, 607-40G
10533	SEPTIC TANK AND DRAINFIELD FOR DEER HUNT BLDG. (760-12G)
10825	SANITARY SEWER LIFT STATION, 607-19-A
11407	SANITARY WASTE TRANSFER STATION 321-M CHANGE ROOM RENOVATION
11442	LIFT STATION - FORCE MAIN, 241-82H
11615	SANITARY TREATMENT PLANT, B-AREA
11755	100-AREA FIRE STATION SEPTIC TANK (INTERSECTION OF ROAD C & ROAD 7)
11847	EFFLUENT WEIR FOR SANITARY TREATMENT SYSTEM, TNX
12076	SANITARY SLUDGE LAND APPLICATION, F&H AREA BORROW PITS
12386	SANITARY SEWER, 730-M
12498	F-AREA STP-PHASE II
12695	RTF SANITARY SEWER
12725	F-AREA STP-PHASE III, 607-F
12910	SANITARY TREATMENT FACILITY, H-AREA
13155	NAVAL FUELS (FMF) FLOW MEASUREMENT DEVICE; OUTFALL F-003 (A)
13156	716-2A SANITARY SEWER
13157	COMPUTER REPAIR BUILDING SANITARY SEWER, 722-5A
13173	SANITARY SLUDGE LAND APPLICATION, K-AREA (761-4G) AND PAR POND (761-5G) BORROW PITS
13175	FLOW EQUALIZATION BASIN, BUILDING 607-22A
13291	H-AREA SEPTIC TANK & TILE FIELD (COMMERCIAL TOILET TRAILER)
13430	SANITARY SEWAGE TREATMENT FACILITY, 607-21F
13538	SEPTIC TANK & DRAINFIELD FOR K-COOLING TOWER CONSTRUCTION TRAILER
13539	SEPTIC TANK & DRAINFIELD FOR K-COOLING TOWER ECR/ICR BLDG.

13717	Z-AREA SEPTIC TANK AND TILE FIELD SYSTEM
14311	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-7C
14312	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-17K
14313	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-17L
14314	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-7P & 607-23P
14315	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-7F & 607-21F
14316	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-7H & 607-21H
14317	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 831-1S & 832-2S
14318	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-15D
14319	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-1B
14320	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-9A
14321	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR SREL WATER-FOWL LAB
14322	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-18G & 607-42G
14323	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-17F (NF)
14324	INTERIM SODIUM HYPOCHLORITE DISINFECTION FOR 607-40T
14407	INCREASED SANITARY WASTEWATER TREATMENT CAPACITY, 607-15D
14443	SEPTIC TANK AND TILE FIELD, H-AREA
15005	SANITARY TREATMENT PLANT, 700-A AREA
15049	EQUALIZATION BASIN FOR SANITARY TREATMENT FACILITIES, CENTRAL SHOPS
15416	SANITARY FLOW EQUALIZATION BASIN FOR 100-K AREA
15417	SANITARY FLOW EQUALIZATION BASIN FOR 100-P AREA
15418	SANITARY FLOW EQUALIZATION BASIN FOR 100-L AREA
15419	SANITARY LIFT STATION, RTF, 200-H AREA
15444	SANITARY LIFT STATION TO SERVE BUILDING 341-M
15506	SANITARY FLOW EQUALIZATION BASIN FOR NAVAL FUELS (FMF)
15530	100-C AREA SANITARY FLOW EQUALIZATION BASIN
15740	SANITARY SEWER SYSTEM EXPANSION, C-AREA (LIFT STATION)

16477	MATERIAL MANAGEMENT RECEIVING & STORAGE FACILITIES, CENTRAL SHOPS
16784	TNX AREA SAN WTP EFFLUENT REROUTE FROM OUTFALL X-013 TO X-008A
16961	SAN. GRAVITY SEWER LINE-MMRSF TO CS STP-CENTRAL SHOPS
17057	SANITARY TREATMENT PLANT UPGRADE, B-AREA
17059	B-AREA ENGINEERING CENTER SANITARY WASTEWATER COLLECTION-SYSTEM
17156	FLOW CONTROL BOXES FOR SANITARY TREATMENT FACILITY
17157	FLOW CONTROL BOXES FOR SANITARY TREATMENT FACILITIES
8611-P	SEPTIC TANK AND TILE FIELD; CS-AREA, 709-1G
8670	SANITARY TREATMENT PLANT, 100-K AREA
8881	FLOW EQUALIZATION BASIN, 700-A
8928	FMF SANITARY WASTE TREATMENT PLANT
9256P	SEPTIC TANK AND TILE FIELD, LANDFILL MONITORING BLDG. 642-E
9326	SANITARY WASTEWATER TREATMENT PLANT; H-AREA (F, P & G AREAS ALSO INCLUDED UNDER THIS PERMIT)
9326	SANITARY WASTEWATER TREATMENT PLANT; P-AREA (F, H & G AREAS ALSO INCLUDED UNDER THIS PERMIT)
9326	SANITARY WASTEWATER TREATMENT PLANT; G-AREA (F, H & P AREAS ALSO INCLUDED UNDER THIS PERMIT)
9326	SANITARY WASTEWATER TREATMENT PLANT; F-AREA (H, P & G AREAS ALSO INCLUDED UNDER THIS PERMIT)
9694	SANITARY SEWER SYSTEM, 773-41A, 773-42A
9888	DWPF SANITARY WASTE TREATMENT PLANT
9940	SANITARY SEWER SYSTEM, REACTOR SIMULATOR FACILITY, 707-C
9983	SANITARY TREATMENT PLANT, 100-C AREA
9998	SEPTIC TANK AND DRAIN FIELD FOR F&H ETF
LS-10-S	SANITARY SEWER SYSTEM, NAVAL FUELS MATERIAL FACILITY (FMF) 247-F & 248-F
LS-129-S	SANITARY SEWER, 719-4A

LS-134-S	DWPF SANITARY SEWER LINE MODIFICATION
LS-149-S	SANITARY SEWER, TNX-ETP
LS-158-S	SANITARY SEWER, 3/700 CONSTRUCTION FACILITY
LS-2-S	SANITARY SEWER LINE, TRITIUM FACILITIES SUPPORT BLDG., 235-H
LS-206-S	SEWER PIPE AND MANHOLE, 704-1T
LS-227-S	705-C SANITARY SEWER
LS-228-S	717-K SANITARY SEWER
LS-239-S	ECF/CAS SECURITY UPGRADE FACILITIES, F-AREA
LS-240-S	3/700 AREA SECURITY UPGRADE, BUILDING 720-2A
LS-244-S	ECF/CAS SECURITY UPGRADE FACILITIES, 701-3H & 720-H
LS-256-S	GRINDER PUMP FOR F-AREA EQ. BASIN (MACERATOR), 607-18F
LS-275-S	SANITARY SEWER FOR EQUIPMENT STORAGE & HEALTH PROTECTION (HP) FACILITY, 221-25F
LS-3-S	SANITARY SEWER SYSTEM, OFFICE BLDG., 703-41A
LS-32-S	SANITARY SEWER LINE, WACKENHUT BLDG.; B-AREA
LS-335-S	TEMPORARY MODULAR OFFICE TRAILERS, 704-7K THRU 704-19K
LS-336-S	"AS-BUILT" OIL/WATER SEPARATOR, 716-A
LS-337-S	"AS-BUILT" OIL/WATER SEPARATOR, 722-4A
LS-35-S	SANITARY SEWER RELOCATION, BLDG. 735-11A
LS-351-S	TEMPORARY MODULAR OFFICE TRAILER, 245-F THROUGH 245-12F
LS-352-S	NEW EMPLOYEE PROCESSING CENTER IN CENTRAL SHOPS AREA
LS-354-S	SAN. SEWER COLLECTION SYSTEM TO SERVE GENERAL PHYSICS OFFICE; 777-18A
LS-52-S	SANITARY SEWER, 707-H
LS-53-S	SANITARY SEWER LINE, CONSTRUCTION OFFICE BUILDING, M-AREA
LS-62-S	SANITARY SEWER LINE RELOCATION, 717-F
LS-78-S	SANITARY SEWER LINE FOR CONSTRUCTION OFFICE BLDG., C-AREA
LS-79-S	SANITARY SEWER LINE-ELECTRICAL OFFICE BLDG., CONST. CENTRAL-SHOPS

LS-80-S   SAN. SEWER LINE-RECEIVING & STORES WAREHOUSE CONST. CENTRAL SHOPS.

UNDERGROUND STORAGE TANKS

Permit Number	Permit Title
C-02-GF-12476	5000-GALLON UNDERGROUND DIESEL FUEL STORAGE TANK, 754-6A
GW-02-894	GASOLINE TANK REPLACEMENT, H-AREA (A, C, K, L, P, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, L-AREA (A, C, K, H, P, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, C-AREA (A, H, K, L, P, & CSAREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, K-AREA (A, H, C, L, P, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, P-AREA (A, H, C, L, K, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, A-AREA TANK #1 (H, C, K, L, P, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, A-AREA TANK #2 (H, C, K, L, P, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, A-AREA TANK #3 (H, C, K, L, P, & CS AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, CS-AREA TANK #1 (H, C, K, L, P, & A-AREAS ALSO INCLUDED)
GW-02-894	GASOLINE TANK REPLACEMENT, CS-AREA TANK #2 (H, C, K, L, P, & A-AREAS ALSO INCLUDED)

FISH MONITORING PERMIT

Permit Number	Permit Title
F-91-22	SOUTH CAROLINA WILDLIFE AND MARINE RESOURCES DEPARTMENT PERMIT FOR COLLECTION OF FISH SPECIMENS.

Appendix B

Radionuclide and Chemical Nomenclature

Nomenclature and Half-life for Radionuclides

Radionuclide	Symbol	Half-life ^a	Radionuclide	Symbol	Half-life ^a
Americium-241	²⁴¹ Am	458 y	Osmium-185	¹⁸⁵ Os	94 d
Americium-243	²⁴³ Am	7.95E3 y	Phosphorus-32	³² P	14.3 d
Antimony-125	¹²⁵ Sb	2.7 y	Polonium-210	²¹⁰ Po	138.4 d
Argon-41	⁴¹ Ar	1.83 h	Plutonium-238	²³⁸ Pu	87.4 y
Beryllium-7	⁷ Be	53 d	Plutonium-239	²³⁹ Pu	2.4E4 y
Carbon-14	¹⁴ C	5,730 y	Potassium-40	⁴⁰ K	1.26E9 y
Cerium-141	¹⁴¹ Ce	33 d	Promethium-147	¹⁴⁷ Pm	2.62 y
Cerium-144	¹⁴⁴ Ce	284 d	Ruthenium-103	¹⁰³ Ru	39.6 d
Cesium-134	¹³⁴ Cs	2.05 y	Ruthenium-106	¹⁰⁶ Ru	367 d
Cesium-137	¹³⁷ Cs	30 y	Selenium-75	⁷⁵ Se	120.4 d
Cobalt-58	⁵⁸ Co	71.3 d	Strontium-89	⁸⁹ Sr	52 d
Cobalt-60	⁶⁰ Co	5.26 y	Strontium-90	⁹⁰ Sr	28.1 y
Curium-242	²⁴² Cm	163 d	Tritium	³ H	12.3 y
Curium-244	²⁴⁴ Cm	17.6 d	Uranium-235	²³⁵ U	7.1E8 y
Iodine-129	¹²⁹ I	1.7E7 y	Uranium-238	²³⁸ U	4.5E9 y
Iodine-131	¹³¹ I	8.05 d	Xenon-133	¹³³ Xe	5.27 d
Krypton-85	⁸⁵ Kr	10.76 y	Xenon-135	¹³⁵ Xe	9.16 h
Krypton-88	⁸⁸ Kr	2.8 h	Yttrium-90	⁹⁰ Y	64 h
Manganese-54	⁵⁴ Mn	303 d	Zirconium-95	⁹⁵ Zr	65 d
Niobium-95	⁹⁵ Nb	35 d			

h = hour; d = day; y = year

^a Reference: U.S. Department of Health, Education, and Welfare, 1970, *Radiological Health Handbook*, Food and Drug Administration, Bureau of Radiological Health, Rockville, MD.

Nomenclature for Elements and Chemical Constituents

Constituent	Symbol	Constituent	Symbol
Aluminum	Al	Mercury	Hg
Ammonia	NH ₃	Nickel	Ni
Antimony	Sb	Nitrogen	N
Arsenic	As	Nitrate	NO ₃
Barium	Ba	Nitrite	NO ₂
Beryllium	Be	Oxygen	O
Cadmium	Cd	Ozone	O ₃
Calcium	Ca	Phosphorus	P
Calcium Carbonate	CaCO ₃	Phosphate	PO ₄
Carbon	C	Potassium	K
Chlorine	Cl	Radium	Ra
Chromium	Cr	Rhenium	Re
Cobalt	Co	Selenium	Se
Copper	Cu	Silver	Ag
Fluorine	F	Sodium	Na
Iron	Fe	Sulfate	SO ₄
Lead	Pb	Sulfur Dioxide	SO ₂
Lithium	Li	Thallium	Tl
Magnesium	Mg	Vanadium	V
Manganese	Mn	Zinc	Zn

Nomenclature for Common Chemical Analyses

Analysis	Symbol	Analysis	Symbol
Biological Oxygen Demand	BOD	Total Organic Carbon	TOC
Chemical Oxygen Demand	COD	Total Organic Halogens	TOH
Dissolved Oxygen	DO	Total Phosphates	TPO ₄
Particulate Matter <10 microns	PM ₁₀	Total Solids	TS
Polychlorinated Biphenyl	PCB	Total Suspended Solids	TSS
Total Dissolved Solids	TDS	Volatile Organic Compound	VOC

Appendix C

Drinking Water Standards

Analyte	Level ^a	Units	Status	Reference
Americium-241	6.34E+00	pCi/L	proposed	EPA, 1991
Americium-243	6.37E+00	pCi/L	proposed	EPA, 1991
Antimony	0.005 ^a	mg/L	proposed	EPA, 1990
Antimony-125	1.94E+03	pCi/L	proposed	EPA, 1991
Arsenic	0.05	mg/L	final	CFR, 1991
Barium	1	mg/L	final	CFR, 1991
Barium-140	5.82E+02	pCi/L	proposed	EPA, 1991
Benzene	0.005	mg/L	final	CFR, 1991
Beryllium	0.001	mg/L	proposed	EPA, 1990
Beryllium-7	4.35E+04	pCi/L	proposed	EPA, 1991
2-sec-Butyl-4, 6-dinitrophenol (Dinoseb)	0.007	mg/L	proposed	EPA, 1990
Cadmium	0.010	mg/L	final	CFR, 1991
Carbon-14	3.20E+03	pCi/L	proposed	EPA, 1991
Carbon tetrachloride	0.005	mg/L	final	CFR, 1991
Cerium-141	1.89E+03	pCi/L	proposed	EPA, 1991
Cerium-144	2.61E+02	pCi/L	proposed	EPA, 1991
Cesium-134	8.13E+01	pCi/L	proposed	EPA, 1991
Cesium-137	1.19E+02	pCi/L	proposed	EPA, 1991
Chlordane	0.002	mg/L	final	CFR, 1991
Chloroethene (Vinyl chloride)	0.002	mg/L	final	CFR, 1991
Chloroform ^b	0.1	mg/L	final	CFR, 1991
Chromium	0.1	mg/L	final	CFR, 1991
Chromium-51	3.80E+04	pCi/L	proposed	EPA, 1991
Cobalt-58	1.59E+03	pCi/L	proposed	EPA, 1991
Cobalt-60	2.18E+02	pCi/L	proposed	EPA, 1991
Copper	1.3	mg/L	final	CFR, 1991
Curium-242	1.33E-02	pCi/L	proposed	EPA, 1991
Curium-243	8.3E+00	pCi/L	proposed	EPA, 1991
Curium-244	9.84E+00	pCi/L	proposed	EPA, 1991

*Standards for beta- and gamma-emitting radionuclides are based on the 4 mrem/yr whole-body dose [EPA91].

^a This is the lower of two proposed levels

^b The level for total trihalomethanes is set at 0.1 mg/L. Because bromated methanes are rarely detected in SRS groundwater, EPD presumes that most of the trihalomethanes present in site groundwater are chloroform.

Appendix C

Analyte	Level*	Units	Status	Reference
Curium-246	6.27E+00	pCi/L	proposed	EPA, 1991
Cyanide	0.2	mg/L	proposed	EPA, 1990
Dibromochloropropane	0.0002	mg/L	final	CFR, 1991
1,2-Dichlorobenzene	0.6	mg/l	final	CFR, 1991
1,4-Dichlorobenzene (p-Dichlorobenzene)	0.075	mg/L	final	CFR, 1991
1,2-Dichloroethane	0.005	mg/L	final	CFR, 1991
cis-1,2-Dichloroethylene	0.07	mg/L	final	CFR, 1991
trans-1,2-Dichloroethylene	0.1	mg/L	final	CFR, 1991
1,1-Dichloroethylene	0.007	mg/L	final	CFR, 1991
Dichloromethane (Methylene chloride)	0.005	mg/L	proposed	EPA, 1990
2,4-Dichlorophenoxyacetic acid	0.1	mg/L	final	CFR, 1991
1,2-Dichloropropane	0.005	mg/L	final	CFR, 1991
Endrin	0.0002	mg/L	final	CFR, 1991
Ethylbenzene	0.7	mg/L	final	CFR, 1991
Europium-154	5.73E+02	pCi/L	final	EPA, 1991
Europium-155	3.59E+03	pCi/L	final	EPA, 1991
Fluoride	4	mg/L	final	CFR, 1991
Gross alpha	15	pCi/L	final	CFR, 1991
Heptachlor	0.0004	mg/L	final	CFR, 1991
Heptachlor epoxide	0.0002	mg/L	final	CFR, 1991
Hexachlorobenzene	0.001	mg/L	proposed	EPA, 1990
Hexachlorocyclopentadiene	0.05	mg/L	proposed	EPA, 1990
Iodine-129	2.10E+01	pCi/L	proposed	EPA, 1991
Iodine-131	1.08E+02	pCi/L	proposed	EPA, 1991
Iron-55	9.25E+03	pCi/L	proposed	EPA, 1991
Iron-59	8.44E+02	pCi/L	proposed	EPA, 1991
Lanthanum-140	6.25E+02	pCi/L	proposed	EPA, 1991
Lead	0.05	mg/L	final	CFR, 1991
Lindane	0.004	mg/L	final	CFR, 1991
Manganese-54	2.01E+03	pCi/L	proposed	EPA, 1991
Mercury	0.002	mg/L	final	CFR, 1991
Methoxychlor	0.1	mg/L	final	CFR, 1991
Neptunium-237	7.06E+00	pCi/L	proposed	EPA, 1991
Nickel	0.1	mg/L	proposed	EPA, 1990
Nickel-59	2.70E+04	pCi/L	proposed	EPA, 1991
Nickel-63	9.91E+03	pCi/L	proposed	EPA, 1991
Niobium-95	2.15E+03	pCi/L	proposed	EPA, 1991
Nitrate (as N)	10	mg/L	final	CFR, 1991
Nitrite (as N)	1	mg/L	final	CFR, 1991
Nonvolatile beta	50	pCi/L	final	CFR, 1991

*Standards for beta- and gamma-emitting radionuclides are based on the 4 mrem/yr whole-body dose [EPA91].

Analyte	Level*	Units	Status	Reference
PAHs				
Benz[a]anthracene	0.0001	mg/L	proposed	EPA, 1990
Benzo[b]fluoranthene	0.0002	mg/L	proposed	EPA, 1990
Benzo[k]fluoranthene	0.0002	mg/L	proposed	EPA, 1990
Benzo[a]pyrene	0.0002	mg/L	proposed	EPA, 1990
Chrysene	0.0002	mg/L	proposed	EPA, 1990
Dibenz[a,h]anthracene	0.0003	mg/L	proposed	EPA, 1990
PCBs	0.0005	mg/L	final	CFR, 1991
Pentachlorophenol	0.001	mg/L	final	CFR, 1991
Plutonium-238	7.02E+00	pCi/L	proposed	EPA, 1991
Plutonium-239	6.21E+01	pCi/L	proposed	EPA, 1991
Plutonium-239/240	6.21E+01 ^a	pCi/L	proposed	EPA, 1991
Plutonium-240	6.22E+01	pCi/L	proposed	EPA, 1991
Plutonium-241	6.26E+01	pCi/L	proposed	EPA, 1991
Plutonium-242	6.54E+01	pCi/L	proposed	EPA, 1991
Potassium-40	300	pCi/L	proposed	EPA, 1986
Radium-226	20	pCi/L	proposed	EPA, 1991
Radium-228	20	pCi/L	proposed	EPA, 1991
Radon-222	300	pCi/L	proposed	EPA, 1991
Ruthenium-103	1.81E+03	pCi/L	proposed	EPA, 1991
Ruthenium-106	2.03E+02	pCi/L	proposed	EPA, 1991
Selenium	0.01	mg/L	final	CFR, 1991
Silver	0.05	mg/L	final	CFR, 1991
Sodium-22	4.66E+02	pCi/L	proposed	EPA, 1991
Strontium-89	5.99E+02	pCi/L	proposed	EPA, 1991
Strontium-89/90	4.20E+01 ^b	pCi/L	final	CFR, 1991
Strontium-90	4.20E+01	pCi/L	proposed	EPA, 1991
Styrene	0.1	mg/L	final	CFR, 1991
Sulfate	400 ^c	mg/L	proposed	EPA, 1990
Technetium-99	3.79E+03	pCi/L	proposed	EPA, 1991
Tetrachloroethylene	0.005	mg/L	final	CFR, 1991
Thallium	0.001 ^d	mg/L	proposed	EPA, 1990
Thorium-228	1.25E+02	pCi/L	proposed	EPA, 1991
Thorium-230	7.92E+01	pCi/L	proposed	EPA, 1991
Thorium-232	8.8E+01	pCi/L	proposed	EPA, 1991
Thorium-234	4.01E+02	pCi/L	proposed	EPA, 1991
Tin-113	1.74E+03	pCi/L	proposed	EPA, 1991

*Standards for beta- and gamma-emitting radionuclides are based on the 4 mrem/yr whole-body dose [EPA91].

- a For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.
- b For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.
- c This is the lower of two proposed levels.
- d This is the lower of two proposed levels.

Analyte	Level*	Units	Status	Reference
Toluene	1.0	mg/L	final	CFR, 1991
Total radium	5	pCi/L	final	CFR, 1991
Toxaphene	0.005	mg/L	final	CFR, 1991
2,4,5-TP (Silvex)	0.01	mg/L	final	CFR, 1991
1,2,4-Trichlorobenzene	0.009	mg/L	proposed	EPA, 1990
1,1,1-Trichloroethane	0.2	mg/L	final	CFR, 1991
1,1,2-Trichloroethane	0.005	mg/L	proposed	EPA, 1990
Trichloroethylene	0.005	mg/L	final	CFR, 1991
Total trihalomethanes ^a	0.1	mg/L	final	CFR, 1991
(includes bromodichloromethane, bromoform, chloroform, and dibromochloromethane)				
Tritium	6.09E+04	pCi/L	proposed	EPA, 1991
Uranium	0.02	mg/L	proposed	EPA, 1991
Uranium alpha activity	30	pCi/L	proposed	EPA, 1991
Uranium-234	1.39E+01	pCi/L	proposed	EPA, 1991
Uranium-235	1.45E+01	pCi/L	proposed	EPA, 1991
Uranium-238	1.46E+01	pCi/L	proposed	EPA, 1991
Xylenes	10	mg/L	final	CFR, 1991
Zinc-65	3.96E+02	pCi/L	proposed	EPA, 1991
Zirconium-95	1.46E+03	pCi/L	proposed	EPA, 1991
Zirconium/Niobium-95 ^b	1.46E+03	pCi/L	proposed	EPA, 1991

*Standards for beta- and gamma-emitting radionuclides are based on the 4 mrem/yr whole-body dose [EPA91].

References:

CFR (Code of Federal Regulations), 1991. "National Primary Drinking Water Regulations," *40 CFR, Part 141*, pp. 578-715, Washington, DC.

EPA (U.S. Environmental Protection Agency), 1990. "National Primary and Secondary Drinking Water Regulations; Synthetic Organic Chemicals and Inorganic Chemicals; Proposed Rule" *Federal Register*, July 25, 1990, pp. 30369-30448, Washington, DC.

EPA (U.S. Environmental Protection Agency), 1991. "National Primary Drinking Water Regulations; Radionuclides; Proposed Rule," *Federal Register*, July 18, 1991, pp. 33052-33127, Washington, DC.

a EPD/EMS does not test for total trihalomethanes, but each of these analytes are tested separately.

b For double radionuclide analyses where each separate radionuclide has its own standard, the more stringent standard is used.

Appendix D

Environmental Monitoring Reports

Reports of the routine environmental monitoring program at SRS have been prepared periodically since before SRS construction in 1951. The monitoring report numbering system and titles have been changed several times over the years to reflect the evolving progress in the concepts of environmental monitoring. The amount of detailed information contained in the reports also varies from time to time, and probably reflects the relative importance and emphasis given to topics by different authors.

Except for July–December 1953, reports were issued semi-annually from 1951 to 1962, and annually beginning in 1963. Attempts to find a report for July–December 1953 have been unsuccessful. The onsite report was discontinued in 1985 when the onsite and offsite reports were merged into a single publication.

Some of the monitoring reports originally contained secret information, primarily radioactive release values that could be related to production rates. The secret information in these reports was deleted in the mid-1970s, and a deleted version (DEL) of the report was issued.

ONSITE REPORTS

Natural Radioactivity Content of the Savannah River Plant

DP27 Jun 1951–Jan 1953

Works Technical Department Data Record, Health Physics Site Survey Data

DPSPU 54–11–12 Jan–Jul 1953
No report Jul–Dec 1953

Radioactivity in the Environment of the Savannah River Plant

DP92 Jan–Jul 1954

Semi-Annual Progress Report–Regional

DPSP 55–25–34 Jul–Dec 1954

Semi-Annual Progress Report–Regional

DPSP 56–25–13 Jan–Jun 1955

Health Physics Regional Monitoring

DPSP 56–25–54 (DEL) Jul–Dec 1955
DPSP 56–25–4 (DEL) Jan–Jun 1956
DPSP 57–25–15 (DEL) Jul–Dec 1956
DPSP 57–25–43 (DEL) Jan–Jun 1957
DPSP 58–25–17 (DEL) Jul–Dec 1957
DPSP 58–25–38 (DEL) Jan–Jun 1958
DPSPU 59–11–23 Jul–Dec 1958
DPSPU 59–11–30 Jan–Jun 1959

DPSPU 60–11–9 Jul–Dec 1959
DPSP 60–25–26 (DEL) Jan–Jun 1960
DPSP 61–25–4 (DEL) Jul–Dec 1960
DPSP 62–25–2 (DEL) Jan–Jun 1961
DPSP 62–25–9 (DEL) Jul–Dec 1961
DPSP 63–25–3 (DEL) Jan–Jun 1962
DPSP 63–25–10 (DEL) Jul–Dec 1962

Environmental Monitoring at the Savannah River Plant

DPSPU 64–11–12 Jan–Dec 1963

Environmental Monitoring at the Savannah River Plant

DPST 65–302 Jan–Dec 1964
DPST 66–302 Jan–Dec 1965
DPST 67–302 Jan–Dec 1966
DPST 68–302 Jan–Dec 1967
DPST 69–302 Jan–Dec 1968
DPST 70–302 Jan–Dec 1969
DPST 71–302 Jan–Dec 1970
DPSPU 72–302 Jan–Dec 1971
DPSPU 73–302 Jan–Dec 1972
DPSPU 74–302 Jan–Dec 1973
DPSPU 75–302 Jan–Dec 1974
DPSPU 76–302 Jan–Dec 1975
DPSPU 77–302 Jan–Dec 1976

ONSITE REPORTS, CONT'D.

DPSPU 78-302	Jan-Dec 1977	DPSPU 82-302	Jan-Dec 1981
DPSPU 79-302	Jan-Dec 1978	DPSPU 83-302	Jan-Dec 1982
DPSPU 80-302	Jan-Dec 1979	DPSPU 84-302	Jan-Dec 1983
DPSPU 81-302	Jan-Dec 1980	DPSPU 85-302	Jan-Dec 1984

OFFSITE REPORTS

Results of the environmental monitoring program that affected the offsite environment have been reported to the public since 1959. These reports contained data from the site boundary and beyond. The offsite report was discontinued in 1985 when the onsite and offsite reports were merged into a single publication. A listing of the offsite reports follows:

The Effect of the Savannah River Plant on Environmental Radioactivity

No document number	Jan-Mar 1960
No document number	Apr-Jun 1960
No document number	Jul-Sep 1960
No document number	Oct-Dec 1960
No document number	Jan-Mar 1961
No document number	Apr-Jun 1961
No document number	Jul-Sep 1961
DPSPU 62-30-11	Oct-Dec 1961
DPSPU 62-30-24	Jan-Jun 1962
DPSPU 63-30-12	Jul-Dec 1962
DPSPU 63-30-1	Jan-Jun 1963
DPSPU 64-30-1	Jul-Dec 1963
DPSPU 64-30-2	Jan-Jun 1964
DPSPU 65-30-1	Jul-Dec 1964
DPST 65-30-2	Jan-Jun 1965
DPST 66-30-1	Jul-Dec 1965

The Effects of the Savannah River Plant on Environmental Radioactivity

DPST 66-30-2	Jan-Jun 1966
DPST 67-30-1	Jul-Dec 1966
DPST 67-30-2	Jan-Jun 1967
DPST 68-30-1	Jul-Dec 1967
DPST 68-30-2	Jan-Jun 1968

DPST 69-30-1	Jul-Dec 1968
DPST 69-30-2	Jan-Jun 1969
DPST 70-30-1	Jul-Dec 1969
DPST 70-30-2	Jan-Jun 1970
DPST 71-30-1	Jul-Dec 1970
DPST 71-30-16	Jan-Jun 1971

Environmental Monitoring in the Vicinity of the Savannah River Plant

DPSPU 72-30-1	Jan-Dec 1971
DPSPU 73-30-1	Jan-Dec 1972
DPSPU 74-30-1	Jan-Dec 1973
DPSPU 75-30-1	Jan-Dec 1974
DPSPU 76-30-1	Jan-Dec 1975
DPSPU 77-30-1	Jan-Dec 1976
DPSPU 78-30-1	Jan-Dec 1977
DPSPU 79-30-1	Jan-Dec 1978
DPSPU 80-30-1	Jan-Dec 1979
DPSPU 81-30-1	Jan-Dec 1980
DPSPU 82-30-1	Jan-Dec 1981
DPSPU 83-30-1	Jan-Dec 1982
DPSPU 84-30-1	Jan-Dec 1983

Savannah River Plant Environmental Report

DPSPU 85-30-1	Jan-Dec 1984

ENVIRONMENTAL REPORTS (COMBINED ONSITE AND OFFSITE)

In 1985, the onsite and offsite environmental monitoring reports were merged into a single publication. A listing of these reports follows:

Savannah River Plant Environmental Report

DPSPU 86-30-1	Jan-Dec 1985
DPSPU 87-30-1	Jan-Dec 1986
DPSPU 88-30-1	Jan-Dec 1987

Savannah River Site Environmental Report

WSRC-RP-89-59-1a	Jan-Dec 1988
WSRC-IM-90-60	Jan-Dec 1989
WSRC-IM-91-28	Jan-Dec 1990

Appendix E

SRS Environmental Highlights

This appendix provides a historical look at major highlights in the history of the Savannah River Site from 1950 through 1991. Although there may have been many highlights for a particular year, only some of the most important ones relating to environmental concerns are given.

1950 - Original Du Pont contract awarded in August	1972 - Provided first radioactive dose calculations for offsite public from SRS releases in annual environmental monitoring report
1951 - Began onsite environmental monitoring	1972 - Prepared a report on SRS thermal distributions in SRS waters and in the Savannah River
1951 - Started forest management	1972 - Technical standards took "As Low As Reasonably Achievable" approach for environmental releases and this was applied to release guides on an annual basis
1951 - Began biological monitoring of the Savannah River by the Academy of Natural Sciences of Philadelphia	1972 - Technical standards set for offsite dose to the maximum individual were 10 mrem/year to whole body, gonads, and bone marrow, 30 mrem to the GI tract, bone, thyroid, and all other organs
1952 - Began the University of Georgia ecology studies at SRS	1972 - Developed an applied research plan for SRL/SRS
1953 - Began using environmental technical standards based on recommendations of standards-setting organizations such as the NCRP, ICRP, FRC, and the AEC	1972 - Became the first National Environmental Research Park within DOE
1959 - Began distribution of annual environmental monitoring report to the public	1973 - Formed an Environmental Research Organization within SRL
1960 - Established radionuclide release guides for specific SRS streams	1973 - Formed a Central Environmental Committee
1961 - Established Savannah River Ecology Laboratory operated by the University of Georgia	1974 - Performed first epidemiological studies of populations surrounding the site
1964 - Related release guides to potential dose and technical standards containing release guides for all SRS streams were established to stay under the dose limit	1974 - Began improving meteorological input to site emergency capabilities
1964 - Established release guides for ^{131}I from all SRS stacks	1975 - Published a report outlining the needs for environmental monitoring of nonradioactive materials
1965 - Began controlled deer hunts	1975 - Began studies on tritiated gas cycling in forest ecosystems
1971 - Formed Environmental Analysis and Planning Division which reported directly to Du Pont management	1976 - Conducted studies on uptake of plutonium by agricultural crops
1971 - Developed a radioactivity emission inventory	

1977	- Conducted dye studies on site creeks to obtain transport and dispersion parameters	1986	- Published the DOE strategic environmental plan
1978	- Added automated forecast meteorology to site emergency response capability through collaboration with the National Weather Service	1988	- Published a draft DOE Environmental Implementation Plan
1979	- Developed an understanding of the ecology of the Legionnaires disease bacterium	1989	- The Westinghouse Savannah River Company assumed responsibility as the primary contractor for the Savannah River Site
1980	- Developed a computer model of heavy gas dispersion	1989	- SRS was officially included on the National Priority List and became regulated under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)
1983	- Formed a Du Pont environmental advisory committee for the site	1990	- Began cold-run testing of the Defense Waste Processing Facility, the nation's first high-level radioactive waste vitrification plant, and began radioactive operation of the Z-Area Saltstone Facility
1985	- Completed the TRAC mobile laboratory	1990	- Began construction of a cooling tower for K Reactor
1985	- Merged the on-and offsite environmental monitoring reports and included highlights of sitewide environmental studies in the annual environmental report	1991	- Formally announced closure of the M-Area Settling Basin, the F- and H-Area seepage basins, and the Mixed-Waste Management Facility
1985	- Completed the Ultra-Low-level Underground Counting Laboratory		
1986	- Standardized and verified methods of calculating dose to public through environmental pathways		

Appendix F

ERRATA

The following information was reported incorrectly in the *Savannah River Site Environmental Report for 1990*, WSRC-IM-91-28:

Table 5-6 (Appendix A, page A-9): The table units should be E-3 pCi/g rather than pCi/g.

Table 8-4 (Chapter 8, page 98): Pu-238 and Pu-239, should be reversed.

Table 14-7 (Appendix A, page A-219): Trail 1, Distance 10, Direction SE, 1-meter (μ R/hr) should be 3.0 rather than 30.

Table 5-6 (Appendix A, page A-9): The table units should be femtoCi/g (fCi/g) rather than pCi/g.

Table 8-6 (Appendix A, page A-74): Tritium and Tritium in Atmospheric Moisture should be reversed.

Throughout the text and most notably in Table 9-3 (Appendix A, page A-92) U3R-2F should be U3R-2.

Appendix G

Distribution List for the SRS Environmental Report

INTRODUCTION

The *Savannah River Site Environmental Report for 1991* is distributed to Department of Energy (DOE) and Westinghouse Savannah River Company (WSRC) personnel, federal and state health officials, federal, state, and local legislators, print and broadcast media, environmental groups, universities, and libraries.

DOE-Savannah River provided the names of DOE recipients; WSRC provided the remainder of the list. Federal and state, environmental, media, university, and library recipients include persons primarily from the two states bounded by SRS—Georgia and South Carolina.

To prepare the final 1991 distribution list, WSRC mailed out business reply cards to all persons on the 1990 distribution list (with the exception of most DOE-affiliated addresses). The recipients made a choice or choices to receive a volume, a summary brochure, or none. All of the names, organizations, and companies that appear in this list will receive the choice/choices they made on the reply cards. If no reply was received, the name and address was removed from the 1991 distribution list.

To obtain a copy of the 1991 report, please contact the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831, (615) 576-8401.

WESTINGHOUSE SAVANNAH RIVER COMPANY

A. L. SCHWALLIE, PRESIDENT

J. J. BUGGY, EXECUTIVE
VICE PRESIDENT

J. G. WISE, GENERAL COUNSEL

J. JACKSON, ENVIRONMENTAL COUNSEL

J. N. HERRMANN, PUBLIC RELATIONS

R. R. CAMPBELL, VP & GM, ESH&QA

R. T. BEGLEY, VP & DIRECTOR, SRL

W. C. REINIG, ESH&QA DEPARTMENT

D. A. STEVENSON, HEALTH PROTECTION
DEPARTMENT

J. S. ROBERTS, ENVIRONMENTAL
PROTECTION DEPARTMENT

J. M. POPE, ENVIRONMENTAL
RESTORATION DEPARTMENT

G. A. KRIST, PLANNING

W. A. QUINN, HUMAN RESOURCES

A. D. CLARK, VP & GM, NUCLEAR MATERIALS
PROCESSING DIVISION

C. L. PECKINPAUGH, DEPUTY GM,
REACTOR OPERATIONS

R. MAHER, DEPUTY GM, NUCLEAR
MATERIALS PROCESSING DIVISION

P. D. RICE, VP & GM,
REACTOR RESTART

W. H. BRITTON, GM, E&PD

T. A. MANGELSDORF, DEPUTY GM, E&PD

C. W. THIESSEN, VP & GM NPR PROGRAM

P.D. GREFENSTETTE VP & MANAGER,
BUSINESS SERVICES & FINANCE

D. W. CALL, SAFETY DEPARTMENT

J. R. BUSH, QA DEPARTMENT

WESTINGHOUSE CORPORATE MANAGEMENT

S. PITTS, EXECUTIVE VICE PRESIDENT
ENVIRONMENTAL AFFAIRS
PITTSBURG, PA

S. GREEN, PROJECT ENGINEER OF
ENVIRONMENTAL AFFAIRS
PITTSBURGH, PA

DOE SAVANNAH RIVER FIELD OFFICE

P. HEKMAN, MANAGER

M. N. SILVERMAN, DEPUTY MANAGER

T. F. HENNAN, ASSISTANT MANAGER FOR
ENVIRONMENT, SAFETY, HEALTH, AND
QUALITY PROGRAMS

W. J. BRUMLEY, DEPUTY ASSISTANT
MANAGER FOR ENVIRONMENT, SAFETY,
HEALTH, AND QUALITY PROGRAMS

L. C. SJOSTROM, ASSISTANT MANAGER FOR
ENVIRONMENTAL RESTORATION AND
WASTE MANAGEMENT

C. C. MASON, ASSISTANT MANAGER FOR
NUCLEAR MATERIALS PROCESSING

E. S. CHAPUT, SPECIAL ASSISTANT
TO THE MANAGER

J. S. COTE, ACTING ASSISTANT
MANAGER FOR ADMINISTRATION

W. E. BERGHOLZ, CHIEF COUNSEL,
OFFICE OF CHIEF COUNSEL (2 CYS)

J. M. GAVER, DIRECTOR,
OFFICE OF EXTERNAL AFFAIRS (40 CYS)

S. R. WRIGHT, DIRECTOR, ENVIRONMENTAL
PROGRAMS AND LABORATORIES DIVISION

A. B. GOULD, DIRECTOR, ENVIRONMENTAL
COMPLIANCE DIVISION

D. N. BRIDGES, DIRECTOR,
MANUFACTURING DIVISION

J. E. ANDERSON, DIRECTOR,
SAFETY DIVISION

A. L. WATKINS, DEPUTY ASSISTANT
MANAGER FOR ENVIRONMENTAL
RESTORATION & MANAGEMENT

M. G. O'REAR, DIRECTOR,
SOLID WASTE DIV.

W. L. NOLL, DEPUTY ASSISTANT MANAGER
FOR ENGINEERING & PROJECTS

L. R. OGLETREE, DIRECTOR,
INFRASTRUCTURE MGMT. DIV.

L. C. GOIDELL, DIRECTOR,
ENVIRONMENTAL RESTORATION DIV.

L. E. SNYDER, DIRECTOR,
PROJECT SUPPORT DIVISION

F. R. McCOY, DIRECTOR, SR RESTART
SPECIAL PROJECTS OFFICE

D. J. WALTZMAN, ACTING CHIEF
FINANCIAL OFFICER

R. D. ROLLINS, DIRECTOR, QUALITY
PROGRAMS DIVISION

D. R. SPENCE, ASSISTANT MANAGER
FOR ENGINEERING & PROJECTS

R. L. LYNCH, DIRECTOR, CONTRACTS
DIVISION

D. R. CARPENTER, DEPUTY ASSISTANT
MANAGER FOR NUCLEAR MATERIALS
PROCESSING

STEVE D. RICHARDSON, ASSISTANT
MANAGER FOR SITE, SAFEGUARDS, AND SE-
CURITY

K. H. BESECKER, ACTING DEPUTY
ASSISTANT MANAGER FOR SITE,
SAFEGUARDS, AND SECURITY

E. L. BOWSER, DIRECTOR, PROGRAM
SUPPORT DIVISION

S. M. KING, DIRECTOR,
SEPARATIONS DIVISION

**HALLIBURTON NUS CORPORATION (SAVAN-
NAH RIVER CENTER)**

R. L. SHOUP, VICE PRESIDENT AND GENERAL
MANAGER, HALLIBURTON NUS
ENVIRONMENTAL CORP., SAVANNAH RIVER
CENTER (10 CYS)

STONE & WEBSTER SOUTH OPERATIONS

G.E. KRAUTER, REGIONAL ENVIRONMENTAL
MANAGER,
OAK RIDGE, TENN

**SAVANNAH RIVER ECOLOGY
LABORATORY (U. OF GEORGIA)**

M. H. SMITH, DIRECTOR

R. I. NESTOR, ASSISTANT DIRECTOR

D. C. ADRIANO, MANAGER, DIVISION OF BIO-GEOCHEMICAL ECOLOGY

M. H. SMITH, MANAGER, DIVISION OF WILD-LIFE AND STRESS ECOLOGY

R. R. SHARITZ, MANAGER, DIVISION OF WETLANDS ECOLOGY

W. SAFTER, RADIATION SAFETY OFFICER

U. S. FOREST SERVICE

J. G. IRWIN, FOREST MANAGER, SRFS, SRS

DOE HEADQUARTERS

DEPUTY ASSISTANT SECRETARY FOR SAFETY & QUALITY ASSURANCE, EH-30 GERMANTOWN, MD

CHIEF, NORTHWESTERN ONSITE REMEDIATION BRANCH, EM-442 GERMANTOWN, MD

ASSISTANT SECRETARY FOR ENVIRONMENT, SAFETY & HEALTH, EH-1 WASHINGTON, DC (10 CYS)

DIRECTOR, OFFICE OF ENVIRONMENTAL GUIDANCE, EH-23 WASHINGTON, DC

DIRECTOR, OFFICE OF EPIDEMIOLOGY & HEALTH SURVEILLANCE, EH-42 GERMANTOWN, MD (4 CYS)

DEPUTY ASSISTANT SECRETARY FOR ENVIRONMENT, EH-20 WASHINGTON, DC

DIRECTOR, REFERENCE AND INFORMATION MANAGEMENT DIVISION, AD-62 WASHINGTON, DC

DIRECTOR, OFFICE OF NEPA OVERSIGHT, EH-25 WASHINGTON, DC (2 CYS)

DIRECTOR, OFFICE OF ENVIRONMENTAL AUDIT, EH-24 WASHINGTON, DC (2 CYS)

DEPUTY ASSISTANT SECRETARY FOR HEALTH, EH-40 GERMANTOWN, MD

DIRECTOR, OFFICE OF HEALTH PHYSICS/INDUSTRIAL HYGIENE PROGRAMS, EH-41 WASHINGTON, DC

ASSOCIATE DIRECTOR, OFFICE OF ENVIRONMENTAL RESTORATION, EM-40 WASHINGTON, DC

ASSISTANT SECRETARY FOR DEFENSE PROGRAMS, DP-1 WASHINGTON, DC

DIRECTOR, AIR, WATER, AND RADIATION DIVISION, EH-232 WASHINGTON, DC

DIRECTOR, OFFICE OF ENVIRONMENTAL RESTORATION & WASTE MANAGEMENT, EM-1 WASHINGTON, DC

DIRECTOR, OFFICE OF ENERGY RESEARCH ER-1 WASHINGTON, DC

DEPUTY DIRECTOR, OFFICE OF ENVIRONMENTAL RESTORATION AND WASTE MANAGEMENT, EM-2 WASHINGTON, DC

ASSOCIATE DIRECTOR, OFFICE OF HEALTH & ENVIRONMENT RESEARCH, ER-70 GERMANTOWN, MD

DEPUTY ASSISTANT SECRETARY FOR FACILITIES, DP-60 WASHINGTON, DC

ASSOCIATE DIRECTOR, OFFICE OF WASTE OPERATIONS, EM-30 WASHINGTON, DC

DEPUTY ASSISTANT SECRETARY FOR MILITARY APPLICATIONS, DP-20 GERMANTOWN, MD

DIRECTOR, OFFICE OF WEAPONS AND MATERIALS PLANNING, DP-27 GERMANTOWN, MD

DIRECTOR, OFFICE OF PROCESSING AND
REACTOR FACILITIES, DP-63
GERMANTOWN, MD

PRINCIPAL DEPUTY ASSISTANT
SECRETARY FOR FACILITIES, DP-6
WASHINGTON, DC

DIRECTOR, OFFICE OF NUCLEAR
SELF-ASSESSMENT & EMERGENCY
MANAGEMENT, DP-9
WASHINGTON, DC

DIRECTOR, OFFICE OF
ENGINEERING & OPERATIONS
SUPPORT, DP-62
GERMANTOWN, MD

DOE FIELD OPERATIONS

C. R. ROBERTSON ACTING DIRECTOR,
OFFICE OF EXTERNAL AFFAIRS
IDAHO FIELD OFFICE
IDAHO FALLS, IDAHO

THOMAS F. GESELL, DIRECTOR,
RADIOLOGICAL & ENVIRONMENTAL
SCIENCES LABORATORY
IDAHO FIELD OFFICE
IDAHO FALLS, IDAHO

EDDIE W. CHEW, CHIEF, ENVIRONMENTAL
SCIENCE BRANCH RADIOLOGICAL AND
ENVIRONMENTAL SCIENCES LAB.
IDAHO FIELD OFFICE
IDAHO FALLS, IDAHO

RICHARD A. HOLTEN, DIRECTOR,
SAFETY & ENVIRONMENT DIVISION
RICHLAND FIELD OFFICE
RICHLAND, WASHINGTON

OFFICE OF COMMUNICATIONS
RICHLAND FIELD OFFICE
RICHLAND, WASHINGTON

MICHAEL W. TIERNAN, CHIEF,
ENVIRONMENTAL COMPLIANCE BR.
SAFETY AND ENVIRONMENTAL DIV.
RICHLAND FIELD OFFICE
RICHLAND, WASHINGTON

JAMES T. ALEXANDER, ASSISTANT TO
MANAGER FOR PUBLIC INFORMATION

OAK RIDGE FIELD OFFICE
OAK RIDGE, TENNESSEE

P. J. GROSS, DIRECTOR,
ENVIRONMENTAL PROTECTION DIV.
OAK RIDGE FIELD OFFICE
OAK RIDGE, TENNESSEE

BARRETT R. FRITZ, ENVIRONMENTAL
PROTECTION BRANCH
CHICAGO FIELD OFFICE
ARGONNE, ILLINOIS

GARY L. PITCHFORD, DIRECTOR,
OFFICE OF COMMUNICATIONS
CHICAGO FIELD OFFICE
ARGONNE, ILLINOIS

CHRIS L. WEST, DIRECTOR,
OFFICE OF EXTERNAL AFFAIRS
NEVADA FIELD OFFICE
LAS VEGAS, NEVADA

BRUCE W. CHURCH, ASSISTANT MGR.
ENVIRONMENTAL SAFETY & HEALTH
NEVADA FIELD OFFICE
LAS VEGAS, NEVADA

JAMES T. DAVIS, ASSISTANT MANAGER,
ENVIRONMENTAL MANAGEMENT
AND SUPPORT
SAN FRANCISCO FIELD OFFICE
OAKLAND, CALIFORNIA

DICK NOLAN, DIRECTOR, OFFICE OF
COMMUNICATION AND PLANNING
SAN FRANCISCO FIELD OFFICE,
OAKLAND, CALIFORNIA

J. G. THEMELIS, DIRECTOR,
ENVIRONMENTAL PROTECTION DIVISION
ALBUQUERQUE FIELD OFFICE
ALBUQUERQUE, NEW MEXICO

E. E. PATENAUDE, DEPUTY AREA MGR.
PINELLAS AREA OFFICE
LARGO, FLORIDA

U.S. DOE PUBLIC READING ROOMS

U.S. DEPARTMENT OF ENERGY, FREEDOM OF
INFORMATION READING ROOM, ROOM 1E-190
WASHINGTON, DC

LIBRARY
DEPARTMENT OF ENERGY
WASHINGTON, DC

PUBLIC READING ROOM
ENERGY RESOURCES CENTER
SAN FRANCISCO FIELD OFFICE
OAKLAND, CA

PUBLIC READING ROOM
IDAHO FIELD OFFICE
IDAHO FALLS, ID

GREGG-GRANITEVILLE LIBRARY
AIKEN, SC

FREEDOM OF INFORMATION
PUBLIC DOCUMENT ROOM
UNIVERSITY OF SC AT AIKEN
AIKEN, SC

PUBLIC READING ROOM
CHICAGO FIELD OFFICE
ARGONNE, IL

PUBLIC READING ROOM
OAK RIDGE OFFICE
FEDERAL BUILDING
OAK RIDGE, TN

PUBLIC READING ROOM
NEVADA FIELD OFFICE
LAS VEGAS, NV

PUBLIC READING ROOM
ALBUQUERQUE FIELD OFFICE
NATIONAL ATOMIC MUSEUM
ALBUQUERQUE, NM

PUBLIC READING ROOM
RICHLAND FIELD OFFICE
FEDERAL BUILDING
RICHLAND, WA

**US DOE NATIONAL LABORATORIES AND
OPERATING CONTRACTORS**

SAFETY AND ENVIRONMENTAL
PROTECTION DIVISION
BROOKHAVEN NATIONAL LABORATORY
UPTON, NEW YORK

ATOMIC ENERGY OF CANADA
LIMITED RESEARCH COMPANY
CHALK RIVER NUCLEAR LAB.
ONTARIO, CANADA

OFFICE OF HANFORD ENVIRONMENT
PACIFIC NORTHWEST LABORATORY
RICHLAND, WASHINGTON

WASTE MANAGEMENT AND ENVIRON-
MENTAL COMPLIANCE
PACIFIC NORTHWEST LABORATORY
RICHLAND, WASHINGTON

BIOLOGICAL, ENVIRONMENTAL AND
MEDICAL RESEARCH DIVISION
ARGONNE NATIONAL LABORATORY
ARGONNE, ILLINOIS

ENVIRONMENTAL PROTECTION SEC.
ENVIRONMENTAL, WASTE MANAGEMENT
ARGONNE NATIONAL LABORATORY,
ARGONNE, ILLINOIS

ENVIRONMENTAL, SAFETY AND HEALTH
DEPARTMENT, ARGONNE NATIONAL LAB.,
ARGONNE, ILLINOIS

DOSIMETRY AND ENVIRONMENTAL STUDIES
HEALTH INSTRUMENTATION DIVISION, SAN-
DIA NATIONAL LABORATORIES, ALBUQUER-
QUE, NEW MEXICO

RADIATION, HEALTH & ENVIRONMENTAL
PROTECTION KNOLLS ATOMIC POWER
LABORATORY, SCHENECTADY, NEW YORK

ENVIRONMENTAL MANAGEMENT BR.
HEALTH, SAFETY & ENV. DIVISION
ROCKWELL INTERNATIONAL
ROCKY FLATS PLANT
GOLDEN, CO

ENVIRONMENTAL AND HEALTH
PROTECTION DIVISION
OAK RIDGE NATIONAL LABORATORY
OAK RIDGE, TENNESSEE

ENVIRONMENTAL MONITORING AND
COMPLIANCE SECTION
OAK RIDGE NATIONAL LABORATORY
OAK RIDGE, TENNESSEE

TRAINING PROGRAM, OFFICE OF HUMAN
RESOURCES DIVISION, OAK RIDGE
NATIONAL LABORATORY OAK RIDGE,
TENNESSEE

HEALTH, SAFETY & ENVIRONMENT
DIVISION UNIVERSITY OF CALIFORNIA
LOS ALAMOS NATIONAL LABORATORY
LOS ALAMOS, NEW MEXICO

RADIATION MONITORING SECTION
ENVIRONMENTAL & HEALTH
PROTECTION
OAK RIDGE NATIONAL LABORATORY
OAK RIDGE, TENNESSEE

COMMUN. & PUBLIC RELATIONS
PERSONNEL DEPARTMENT
MONSANTO RESEARCH CORPORATION
MOUND LABORATORY
MIAMISBURG, OH

HEALTH, SAFETY, AND ENVIRONMENT
ROCKWELL INTERNATIONAL
ROCKY FLATS PLANT GOLDEN, CO

ENVIRONMENTAL RESEARCH LAB.
ENVIRONMENTAL PROTECTION AGENCY
ATHENS, GA

ENVIRONMENTAL SERVICES DIVISIONS
ENVIRONMENTAL PROTECTION AGENCY
REGION IV
ATHENS, GA

ENVIRONMENTAL PROTECTION DIV.
UNIVERSITY OF CALIFORNIA
LAWRENCE LIVERMORE NATIONAL LAB.
LIVERMORE, CALIFORNIA

ENVIRONMENTAL MONITORING
SAFETY & ENVIRONMENTAL
PROTECTION DIVISION
BROOKHAVEN NATIONAL LABORATORY
UPTON, NEW YORK

SAFETY SECTION
FERMI NATIONAL ACCELERATOR LAB.
BATAVIA, IL

FEDERAL AGENCIES

REGIONAL ADMINISTRATOR
REGION II
U. S. NUCLEAR REGULATORY COMM.
ATLANTA, GA

PUBLIC AFFAIRS OFFICER
U. S. NUCLEAR REGULATORY COMM.
ATLANTA, GA

VOGTLE LICENSING PROJECT MANAGER
NUCLEAR REACTOR REGULATION
U. S. NUCLEAR REGULATORY COMM.
WASHINGTON, DC

NUCLEAR REACTOR REGULATION
ATTN: ELINOR G. ADENSAM
U. S. NUCLEAR REGULATORY COMM.
REGIONAL ADMINISTRATOR, REGION IV
ENVIRONMENTAL PROTECTION AGENCY
ATLANTA, GA

ENVIRONMENTAL ASSESSMENT BRANCH
OFFICE OF POLICY AND MANAGEMENT
ENVIRONMENTAL PROTECTION AGENCY
REGION IV
ATLANTA, GA

NEPA REVIEW STAFF
ENVIRONMENTAL ASSESSMENT BRANCH
OFFICE OF POLICY AND MANAGEMENT
ENVIRONMENTAL PROTECTION AGENCY
REGION IV
ATLANTA, GA

AIR, PESTICIDES, AND TOXICS DIVISION
ENVIRONMENTAL PROTECTION AGENCY
REGION IV
ATLANTA, GA

THERMAL ANALYSIS UNIT
ENVIRONMENTAL PROTECTION AGENCY
REGION IV, ATTN: MR. KAPLAN
ATLANTA, GA

OFFICE OF CONGRESSIONAL
AND EXTERNAL AFFAIRS
ENVIRONMENTAL PROTECTION AGENCY
REGION IV
ATLANTA, GA

ENVIRONMENTAL PROTECTION AGENCY
EASTERN ENVIRONMENTAL RADIATION
FACILITY
MONTGOMERY, AL

CRITERIA AND STANDARDS DIVISION
OFFICE OF RADIATION PROGRAMS
ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC

ORP LAS VEGAS FACILITY
ENVIRONMENTAL PROTECTION AGENCY
LAS VEGAS, NEVADA

OFFICE OF RADIATION PROGRAMS NE108
ENVIRONMENTAL PROTECTION AGENCY
WATERSIDE MALL
WASHINGTON, DC

NATIONAL ENVIRONMENTAL RESEARCH
CENTER
ENVIRONMENTAL PROTECTION AGENCY
LAS VEGAS, NV

CENTER FOR DEVICES AND
RADIOLOGICAL HEALTH
PUBLIC HEALTH SERVICE
U. S. DEPARTMENT OF HEALTH AND
HUMAN SERVICES
ROCKVILLE, MD

OPERATIONS DIVISION
U. S. ARMY OF CORPS OF ENGINEERS
SAVANNAH DISTRICT
SAVANNAH, GA

U. S. ARMY CORPS OF ENGINEERS
SAVANNAH DISTRICT
SAVANNAH, GA

U. S. ARMY CORPS OF ENGINEERS
THURMOND LAKE
CLARKS HILL, SC

CHARLESTON DISTRICT, SAC CO-P
U. S. ARMY CORPS OF ENGINEERS
CHARLESTON, SC

U. S. DEPT OF HEALTH AND HUMAN
SERVICES, PUBLIC HEALTH SERVICE
FOOD AND DRUG ADMINISTRATION,
REGION IV
ATLANTA, GA

FEDERAL EMERGENCY
MANAGEMENT AGENCY, REGION IV
ATLANTA, GA

U. S. SENATORS

HONORABLE STROM THURMOND
UNITED STATES SENATE
WASHINGTON, DC

HONORABLE ERNEST F. HOLLINGS
UNITED STATES SENATE
WASHINGTON, DC

HONORABLE SAM NUNN
UNITED STATES SENATE
WASHINGTON, DC

HONORABLE WYCHE FOWLER, JR.
UNITED STATES SENATE
WASHINGTON, DC

U. S. REPRESENTATIVES

HONORABLE BUTLER DERRICK
HOUSE OF REPRESENTATIVES
WASHINGTON, DC

HONORABLE ARTHUR RAVENEL, JR.
HOUSE OF REPRESENTATIVES
WASHINGTON, DC

HONORABLE FLOYD SPENCE
HOUSE OF REPRESENTATIVES
WASHINGTON, DC

HONORABLE JOHN SPRATT
HOUSE OF REPRESENTATIVES
WASHINGTON, DC

HONORABLE D. DOUGLAS BARNARD
HOUSE OF REPRESENTATIVES
WASHINGTON, DC

HONORABLE LINDSAY THOMAS
HOUSE OF REPRESENTATIVES
WASHINGTON, DC

STATE LEGISLATORS - SOUTH CAROLINA

HONORABLE ADDISON JOE WILSON
SOUTH CAROLINA SENATE
WEST COLUMBIA, SC

HONORABLE NIKKI G. SETZLER
SOUTH CAROLINA SENATE
COLUMBIA, SC

HONORABLE IRENE K. RUDNICK
SOUTH CAROLINA HOUSE OF
REPRESENTATIVES
AIKEN, SC

HONORABLE JOSEPH B. WILDER
SOUTH CAROLINA HOUSE OF
REPRESENTATIVES
BARNWELL, SC

HONORABLE J. ROLAND SMITH
SOUTH CAROLINA HOUSE OF
REPRESENTATIVES
LANGLEY, SC

HONORABLE LARRY E. GENTRY
SOUTH CAROLINA HOUSE OF
REPRESENTATIVES
SALUDA, SC

HONORABLE CANDY Y. WAITES
SOUTH CAROLINA HOUSE OF
REPRESENTATIVES
COLUMBIA, SC

HONORABLE THOMAS L. MOORE,
CHAIRMAN
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
CLEARWATER, SC

HONORABLE HARRIET H. KEYSERLING
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
BEAUFORT, SC

HONORABLE WILLIAM H. ODELL,
MEMBER
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
WARE SHOALS, SC 29692

RESEARCH DIRECTOR
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
COLUMBIA, SC

HONORABLE ROBERT A. BARBER
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
CHARLESTON, SC

HONORABLE TIMOTHY F. ROGERS
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
COLUMBIA, SC

HONORABLE LUCILLE S. WHIPPER
SOUTH CAROLINA JOINT LEGISLATIVE
COMMITTEE ON ENERGY
MT. PLEASANT, SC

STATE LEGISLATORS - GEORGIA

HONORABLE HENRY HOWARD
GEORGIA HOUSE OF REPRESENTATIVES
AUGUSTA, GA 30913

HONORABLE JACK CONNELL
GEORGIA HOUSE OF REPRESENTATIVES
AUGUSTA, GA

HONORABLE ROBIN L. WILLIAMS
GEORGIA HOUSE OF REPRESENTATIVES
AUGUSTA, GA

HONORABLE JOSEPH BRUSH, JR.
GEORGIA HOUSE OF REPRESENTATIVES
APPLING, GA

HONORABLE BOBBY HARRIS
GEORGIA HOUSE OF REPRESENTATIVES
THOMSON, GA

HONORABLE GEORGE M BROWN
GEORGIA HOUSE OF REPRESENTATIVES
P.O. BOX 1114
AUGUSTA, GA

**STATE GOVERNMENT OFFICIALS -
SOUTH CAROLINA**

HONORABLE CARROLL A CAMPBELL
GOVERNOR OF SOUTH CAROLINA
COLUMBIA, SC

HONORABLE NICK A THEODORE
LIEUTENANT GOVERNOR OF
SOUTH CAROLINA
COLUMBIA, SC

DR. HARRY MILEY
SENIOR EXECUTIVE ASSISTANT
ECONOMIC DEVELOPMENT
OFFICE OF THE GOVERNOR
STATE OF SOUTH CAROLINA
COLUMBIA, SC

MR. TUCKER ESKEW
PRESS SECRETARY TO THE GOVERNOR
STATE OF SOUTH CAROLINA
COLUMBIA, SC

MR. WARREN TOMPKINS, CHIEF OF STAFF
OFFICE OF THE GOVERNOR
STATE OF SOUTH CAROLINA
COLUMBIA, SC

**STATE GOVERNMENT OFFICIALS -
GEORGIA**

HONORABLE ZELL MILLER
GOVERNOR OF GEORGIA
ATLANTA, GA

MS. BARBARA MORGAN,
PRESS SECRETARY
OFFICE OF THE GOVERNOR
STATE OF GEORGIA
ATLANTA, GA

STATE AGENCIES - SOUTH CAROLINA

SOUTH CAROLINA DEPARTMENT OF HEALTH
AND ENVIRONMENTAL CONTROL
AIKEN, SC

BUREAU OF RADIOLOGICAL HEALTH
SOUTH CAROLINA DEPARTMENT OF HEALTH
AND ENVIRONMENTAL CONTROL
COLUMBIA, SC

BUREAU OF AIR QUALITY CONTROL
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
COLUMBIA, SC

BUREAU OF SOLID AND HAZARDOUS
WASTES MANAGEMENT
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
COLUMBIA, SC

BUREAU OF WATER POLLUTION CONTROL
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
COLUMBIA, SC

BUREAU OF DRINKING WATER
PROTECTION
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
COLUMBIA, SC

WATER QUALITY ASSESSMENT AND
ENFORCEMENT DIVISION
BUREAU OF WATER POLLUTION CONTROL
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
COLUMBIA, SC

BUREAU OF SOLID AND HAZARDOUS WASTE
ATT. HARRY MATHES
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
COLUMBIA, SC (5 copies)

BUREAU OF ENVIRONMENTAL QUALITY
CONTROL LABS
DIVISION OF RADIATION MONITORING
SOUTH CAROLINA DEPARTMENT OF
HEALTH & ENVIRONMENTAL CONTROL
COLUMBIA, SC

DISTRICT DIRECTOR
LOWER SAVANNAH DISTRICT OFFICE
SOUTH CAROLINA DEPARTMENT OF HEALTH
& ENVIRONMENTAL CONTROL
AIKEN, SC

ENVIRONMENTAL BIOLOGIST

SOUTH CAROLINA WATER
RESOURCES COMMISSION
COLUMBIA, SC

OFFICE OF ENERGY RESOURCES
STATE OF SOUTH CAROLINA
COLUMBIA, SC

GEOLOGY-HYDROLOGY DIVISION
SOUTH CAROLINA WATER RESOURCES
COMMISSION
CAPITOL CENTER
COLUMBIA, SC

DIVISION OF ADMINISTRATION
STATE CLEARINGHOUSE
STATE OF SOUTH CAROLINA
COLUMBIA, SC

SOUTH CAROLINA STATE
DEVELOPMENT BOARD
COLUMBIA, SC

STATE AGENCIES - GEORGIA

COMMISSIONER
GEORGIA DEPARTMENT OF NATURAL
RESOURCES
FLOYD BUILDING
ATLANTA, GA

PROGRAM MANAGER
SURFACE WATER SUPPLY
GEORGIA DEPARTMENT OF NATURAL
RESOURCES
ATLANTA, GA

DIRECTOR
ENVIRONMENTAL PROTECTION DIV.
GEORGIA DEPARTMENT OF NATURAL
RESOURCES
ATLANTA, GA

MANAGER, ENVIRONMENTAL
RADIATION PROGRAMS
GEORGIA DEPARTMENT OF NATURAL
RESOURCES
ATLANTA, GA

DIVISION OF PHYSICAL HEALTH
STATE HEALTH BUILDING - ROOM 522
ATLANTA, GA

GAME AND FISH COMMISSION
GEORGIA DEPARTMENT OF NATURAL
RESOURCES
ATLANTA, GA

DIRECTOR
OFFICE OF ENERGY RESOURCES
ATLANTA, GA

STATE AGENCIES - FLORIDA

DISTRICT ADMINISTRATOR
FLORIDA DEPARTMENT OF HEALTH AND
REHABILITATIVE SERVICES
ORLANDO, FL

STATE AGENCIES - NORTH CAROLINA

STATE OF NORTH CAROLINA
LOW-LEVEL RADIOACTIVE
WASTE MANAGEMENT AUTHORITY
RALEIGH, NORTH CAROLINA

MAYORS - SOUTH CAROLINA

HONORABLE F. CAVANAUGH
MAYOR OF AIKEN
AIKEN, SC

HONORABLE WILLIAM HOLMES
MAYOR OF ALLENDALE
ALLENDALE, SC

HONORABLE FRANKLIN DICKSON
MAYOR OF BAMBERG
BAMBERG, SC

HONORABLE H. CREECH SANDERS
MAYOR OF BARNWELL
BARNWELL CITY HALL
BARNWELL, SC

HONORABLE DAVID M. TAUB
MAYOR OF BEAUFORT
BEAUFORT, SC

HONORABLE JOSEPH P. RILEY, JR.
MAYOR OF CHARLESTON
CHARLESTON, SC

HONORABLE P. K. GREENE
MAYOR OF JACKSON
JACKSON, SC

HONORABLE RANDY W. SHAW
MAYOR OF NEW ELLENTON
NEW ELLENTON, SC

HONORABLE THOMAS GREENE
MAYOR OF NORTH AUGUSTA
NORTH AUGUSTA, SC

HONORABLE THOMAS B. BRADY
MAYOR OF WILLISTON
WILLISTON, SC

HONORABLE OLIVIA COHEN
MAYOR OF FAIRFAX
FAIRFAX, SC

MAYORS - GEORGIA

HONORABLE SUSAN WEINER
MAYOR OF SAVANNAH
SAVANNAH, GA

HONORABLE CHARLES A. DEVANEY
MAYOR OF AUGUSTA
AUGUSTA, GA

HONORABLE GEORGE L. DELOACH
MAYOR OF WAYNESBORO
WAYNESBORO, GA

MAYOR OF GIRARD
CITY OF GIRARD
GIRARD, GA

MAYOR OF MILHAVEN
216 MINS RD
SYLVANIA, GA

MAYOR OF NEWINGTON
P.O. BOX 297
NEWINGTON, GA

MAYOR OF SARDIS
SARDIS CITY HALL
P.O. BOX 398
SARDIS, GA

MAYOR OF SHELL BLUFF
P.O. BOX 495
WAYNESBORO, GA

MAYOR OF SPRINGFIELD
P.O. BOX 1
SPRINGFIELD, GA

MAYOR OF STATESBORO
STATESBORO CITY HALL
STATESBORO, GA

MAYOR OF SYLVANIA
SYLVANIA CITY HALL
SYLVANIA, GA

MAYOR OF TYBEE
P.O. BOX 128
TYBEE, GA

CITY OFFICIALS - SOUTH CAROLINA

MR. STEVE THOMPSON, CITY MANAGER
AIKEN, SC

ADMINISTRATOR
CITY OF NORTH AUGUSTA
NORTH AUGUSTA, SC

CITY OFFICIALS - GEORGIA

MR. HARRY JUE
WATER OPERATIONS DIRECTOR
INDUSTRIAL AND DOMESTIC
WATER SUPPLY COMMISSION
SAVANNAH, GA

TOWN REPRESENTATIVE OF BLOOMINGDALE
P.O. BOX 216
BLOOMINGDALE, GA

TOWN REPRESENTATIVE OF GARDEN CITY
P.O. BOX 7548
GARDEN CITY, GA

CHAIRMAN, RICHMOND COUNTY BOARD OF
COMMISSIONERS
MUNICIPAL BLDG., RM 605
AUGUSTA, GA

TOWN REPRESENTATIVE OF POOLER
100 SOUTH WEST HIGHWAY 80
POOLER, GA

CITY ADMINISTRATOR
305 SOUTH COASTAL HIGHWAY
PORT WENTWORTH, GA

TOWN REPRESENTATIVE OF THUNDERBOLT
2702 MECHANIC AVENUE
THUNDERBOLT, GA

UNIVERSITIES - SOUTH CAROLINA

BOTANY DEPARTMENT
CLEMSON UNIVERSITY
CLEMSON, SC

DEPARTMENT OF ENVIRONMENTAL
SYSTEMS ENGINEERING
COLLEGE OF ENGINEERING
CLEMSON UNIVERSITY
CLEMSON, SC

Mr. JOHN C. MORSE
CLEMSON UNIVERSITY
CLEMSON, SC

DEPARTMENT OF ENTOMOLOGY AND
ECONOMIC ZOOLOGY
CLEMSON UNIVERSITY
CLEMSON, SC

BIOLOGY DEPARTMENT
WOFFORD COLLEGE
SPARTANBURG, SC 29301

MARINE RESOURCES CENTER
CHARLESTON, SC

UNIVERSITIES - GEORGIA

SAFETY SERVICES - BARROW H
UNIVERSITY OF GEORGIA
ATHENS, GA

WILDLIFE MANAGEMENT
SCHOOL OF EST RESOURCES
UNIVERSITY OF GEORGIA
ATHENS, GA

PROFESSOR OF PHYSICS
EMORY UNIVERSITY
ATLANTA, GA

DEPARTMENT OF BIOLOGY
EMORY UNIVERSITY
ATLANTA, GA

DEPARTMENT OF BIOLOGY
EMORY UNIVERSITY
ATLANTA, GA

ENVIRONMENTAL RESOURCES CENTER
GEORGIA INSTITUTE OF TECHNOLOGY
ATLANTA, GA

UNIVERSITIES - FLORIDA

DEPARTMENT OF PHYSICS
FLORIDA STATE UNIVERSITY
TALLAHASSEE, FL

JACKSONVILLE UNIVERSITY LIBRARY
JACKSONVILLE, FL

DIRECTOR OF RESEARCH
UNIVERSITY OF SOUTH FLORIDA
TAMPA, FL 33620

ENVIRONMENTAL ENGINEER
UNIVERSITY OF FLORIDA
GAINESVILLE, FL 32611

UNIVERSITIES - OTHER

DEPARTMENT OF PHYSIOLOGY AND
BIOPHYSICS
UNIVERSITY OF TENNESSEE
MEMPHIS, TN

VANDERBILT UNIVERSITY
NASHVILLE, TN

THE TECHNICAL INSTITUTE
DEPARTMENT OF CIVIL ENGINEERING
NORTHWESTERN UNIVERSITY
EVANSTON, IL

DEPARTMENT OF HYDROLOGY AND
WATER RESOURCES
UNIVERSITY OF ARIZONA
TUCSON, AZ

CENTER ENVIRONMENTAL STUDY
VIRGINIA POLYTECHNIC INSTITUTE
AND STATE UNIVERSITY
BLACKSBURG, VA

NEW YORK UNIVERSITY
INSTITUTE ENVIRONMENTAL MEDICINE
TUXEDO, NY

**INDUSTRIES/UTILITIES -
SOUTH CAROLINA**

SITE ADMINISTRATOR
ALLIED GENERAL NUCLEAR SERVICES
BARNWELL, SC

KIMBERLY-CLARK CORPORATION
BEECH ISLAND, SC

REGULATORY AFFAIRS
CHEM-NUCLEAR SYSTEMS
COLUMBIA, SC

PRODUCTION ENGINEERING
SOUTH CAROLINA ELECTRIC
AND GAS COMPANY
COLUMBIA, SC

INDUSTRIES/UTILITIES - GEORGIA

FEDERAL PAPER BOARD COMPANY
AUGUSTA, GA

ENVIRONMENTAL ENGINEER
GEORGIA POWER COMPANY
ATLANTA, GA

ENVIRONMENTAL AFFAIRS
GEORGIA POWER COMPANY
ATLANTA, GA

NUCLEAR GENERATION DEPARTMENT
GEORGIA POWER COMPANY
ATLANTA, GA

SPECIAL SERVICES
PUBLIC INFORMATION/ADVERTISING
GEORGIA POWER COMPANY
ATLANTA, GA

SITE ENVIRONMENTAL ENGINEER
A. W VOGTLE NUCLEAR POWER PLANT
GEORGIA POWER COMPANY
WAYNESBORO, GA

A. W. VOGTLE NUCLEAR POWER PLANT
GEORGIA POWER COMPANY
WAYNESBORO, GA

PLANT E. I. HATCH
GEORGIA POWER COMPANY
BAXLEY, GA

GEORGIA POWER COMPANY
CENTRAL LABORATORY
SMYRNA, GA

INDUSTRIES/UTILITIES - OTHER STATES

HEALTH PHYSICS SERVICES
TENNESSEE VALLEY AUTHORITY
MUSCLE SHOALS, AL

RADIOLOGICAL HYGIENE BRANCH
TENNESSEE VALLEY AUTHORITY
MUSCLE SHOALS, AL

RADIOLOGICAL SUPPORT SERVICES
FLORIDA POWER CORPORATION
CRYSTAL RIVER, FL 32629 (NA2H)

SMITH AND GILLESPIE ENGINEERS, INC.
JACKSONVILLE, FL

REYNOLDS, SMITH AND HILLS
JACKSONVILLE, FL

PUBLIC RELATIONS
CAROLINA POWER AND LIGHT COMPANY
RALEIGH, NC

DUKE POWER COMPANY
DAVID NABOW LIBRARY
CHARLOTTE, NC

ENVIRONMENTAL SCIENCES DEPT.
REYNOLDS ELECTRICAL &
ENGINEERING CO., INC.
NEVADA TEST SITE
MERCURY, NV

MR. A. J. HOGAN
ENVIRONMENTAL ENGINEERING SEC.
PHILADELPHIA ELECTRIC COMPANY
PHILADELPHIA, PA

ENVIRONMENTAL HEALTH DEPT.
MASON & HANGER
SILAS MASON, CO., INC.
PANTEX PLANT
AMARILLO, TX

VIRGINIA ELECTRIC AND
POWER COMPANY
RICHMOND, VA

**ENVIRONMENTAL GROUPS -
SOUTH CAROLINA**

LEAGUE OF WOMEN
VOTERS OF NORTHERN
BEAUFORT COUNTY
BEAUFORT, SC

SIERRA CLUB
AIKEN, SC

PHYSICIANS & PROFESSIONALS
FOR SOCIAL RESPONSIBILITY
COLUMBIA, SC

LOW COUNTRY COUNCIL
YEMASSEE, SC

PEOPLE FOR A CLEAN ENVIRONMENT
CLEMSON, SC

LEAGUE OF WOMEN VOTERS
OF SOUTH CAROLINA
COLUMBIA, SC

ENVIRONMENTALISTS, INC.
COLUMBIA, SC

GROW
COLUMBIA, SC

THE SOUTH CAROLINA
WILDLIFE FEDERATION
COLUMBIA, SC

ENERGY RESEARCH FOUNDATION
COLUMBIA, SC

ENVIRONMENTAL GROUPS - GEORGIA

THE GEORGIA CONSERVANCY
SAVANNAH, GA

GREENPEACE ACTION
ATLANTA, GA

GEORGIANS AGAINST NUCLEAR ENERGY
ATLANTA, GA

NUCLEAR COORDINATOR
SOUTH CAROLINA CHAPTER

CITIZENS FOR ENVIRONMENTAL JUSTICE
720 MAUPAS AVE
SAVANNAH, GA

LEAGUE OF WOMEN VOTERS OF GEORGIA
ATLANTA, GA

LEAGUE OF WOMEN VOTERS OF
GEORGIA
AUGUSTA, GA

SIERRA CLUB
500 NORWICH RD. Apt. 40
AUGUSTA, GA

ENVIRONMENTAL GROUPS - OTHER

DIVISION OF LIMNOLOGY AND ECOLOGY
ACADEMY OF NATURAL SCIENCES OF
PHILADELPHIA
PHILADELPHIA, PA

DIV. OF ENVIRONMENTAL RESEARCH
ACADEMY OF NATURAL SCIENCES OF
PHILADELPHIA
PHILADELPHIA, PA

NATURAL RESOURCES DEFENSE
COUNCIL, INC.
WASHINGTON, DC

LIBRARIES - SOUTH CAROLINA

AIKEN COUNTY PUBLIC LIBRARY
AIKEN, SC

AHJ REGIONAL LIBRARY
ALLENDALE, SC

BEAUFORT COUNTY LIBRARY
BEAUFORT, SC

SOUTH CAROLINA STATE LIBRARY
COLUMBIA, SC

NANCY CARSON PUBLIC LIBRARY
NORTH AUGUSTA, SC

AIKEN-BAMBERG-BARNWELL-
EDGEFIELD REGIONAL LIBRARY
NORTH AUGUSTA, SC

LIBRARIES - GEORGIA

AUGUSTA-RICHMOND COUNTY PUBLIC
LIBRARY
AUGUSTA, GA

REESE LIBRARY
AUGUSTA COLLEGE
AUGUSTA, GA

PRINT MEDIA - SOUTH CAROLINA

AIKEN STANDARD
AIKEN, SC

BUREAU CHIEF
AUGUSTA CHRONICLE-HERALD
SOUTH CAROLINA BUREAU
AIKEN, SC

ALLENDALE COUNTY CITIZEN LEADER
ALLENDALE, SC

THE BARNWELL BANNER
BARNWELL, SC

THE BARNWELL PEOPLE-SENTINEL
BARNWELL, SC

THE BEAUFORT GAZETTE
BEAUFORT, SC

THE CHARLESTON NEWS & COURIER
CHARLESTON, SC

THE STATE
COLUMBIA, SC

THE CHARLOTTE OBSERVER
COLUMBIA BUREAU
COLUMBIA, SC

SOUTH CAROLINA BROADCASTERS
ASSOCIATION
USC COLLEGE OF JOURNALISM
COLUMBIA, SC

THE ASSOCIATED PRESS
COLUMBIA BUREAU
COLUMBIA, SC

THE HAMPTON GUARDIAN
HAMPTON, SC

THE ISLAND PACKET
HILTON HEAD ISLAND, SC

PRESS AND STANDARD
WALTERBORO, SC

PRINT MEDIA - GEORGIA

THE ATLANTA CONSTITUTION
ATLANTA, GA

THE AUGUSTA CHRONICLE
AUGUSTA, GA

THE MACON TELEGRAPH-NEWS
MACON, GA

THE SAVANNAH MORNING NEWS
SAVANNAH, GA

THE STATESBORO HERALD
STATESBORO, GA

PRINT MEDIA - OTHER

THE CHARLOTTE OBSERVER
CHARLOTTE, NC

TELEVISION STATIONS - GEORGIA

CABLE NEWS NETWORK
ATLANTA, GA

WAGT-TV
AUGUSTA, GA

WJBF-TV
AUGUSTA, GA

TELEVISION STATIONS—OTHER

WLOS-TV
ASHVILLE, NC

RADIO STATIONS—SOUTH CAROLINA

WLTR RADIO
COLUMBIA, SC

RADIO STATIONS—GEORGIA

WRFC RADIO
ATHENS, GA

GEORGIA RADIO NEWS SERVICE
ATLANTA, GA

WGAC RADIO
AUGUSTA, GA

Index

A

A Area, description of operations, 8
Absorbed dose, 102
Academy of Natural Sciences of Philadelphia
  overview, 486
  water quality surveys
    cursory biological
      description of, 488
      survey results, 488
    diatom community
      description of, 486
      survey results, 486
    Plant Vogtle survey
      description of, 489
      survey results, 489
Acid/caustic basins, closures, 15
Administration Area, description of operations, 8
Air
  nonradiological monitoring, 132
    analytical procedures, 59
    nonradioactive effluent releases, 132
    sample collection, 59
  radiological monitoring, 126
    analytical procedures, 48
    effluent releases, 126
    sample collection, 48
Algae, in Savannah River
  cursory biological survey results, 488
  Plant Vogtle survey results, 489
Analytical procedures. *See* specific medium
ANSP. *See* Academy of Natural Sciences of Philadelphia
Applicable standards
  for QA/QC programs, 73
  for wildlife, 448
  nonradiological monitoring, for fish, 449

  radiation dose, 105

Appraisals
  compliance inspections, 22
  Comprehensive Environmental Protection Evaluation Program, 22
  environmental program, 21
  Tiger Team assessment, 22
Aquatic macrophytes, in Savannah River
  cursory biological survey results, 488
  Plant Vogtle survey results, 489
asbestos, NESHAP requirements, 20
Atmospheric releases, modeling, 109

B

Biochemical ecology, 536
Bioremediation, 530
Brailsford motor pumps, 49

C

C Area, description of operations, 4
CAP88, 107
Catherwood, diatometer, 486, 489
CEPEP. *See* Comprehensive Environmental Protection Evaluation Program
CERCLA. *See* Comprehensive Environmental Response, Control, and Liability Act
Cesium-137
  in hogs, special survey results, 481
  releases, liquid, 471
Chemical exposure, perspectives on, 41
Chemistry and bacteriology, in Savannah River,
  Plant Vogtle survey results, 489
Clean Air Act
  air quality permits, 19

- compliance inspection, 22
- compliance with NESHAP, 127
- NESHAP requirements, 19
- Clean Water Act, NPDES program, 18
- coal, burned at SRS, 132
- Collective effective dose equivalent, 103
- Compliance, summary for 1992, 25
- Comprehensive Environmental Protection Evaluation Program (CEPEP), 22
- Comprehensive Environmental Response, Control, and Liability Act (CERCLA), 17
  - integration with RCRA, 17
  - Public Involvement Plan, 17
  - reportable releases, 17
- Contamination, 772-F, 470
- Counting geometries, 46
- Creek Plantation. *See* Savannah River Swamp

D

- D Area, description of operations, 6
- Data
  - illegitimate errors, 57
  - interpretation of, 55
  - measurement difficulties, 56
  - nomenclature used, 55
  - radionuclides reported, 56
  - random errors, 57
  - reported uncertainties, 57
  - significant figures, 55
  - systematic errors, 57
  - tracking, 74
  - units, 56
  - validation, 74
- Deer
  - controlled hunts, 448
  - dose from consumption of, 449
  - radiological monitoring
    - description of, 446
    - monitoring results, 446
  - sample collection and analysis, 53
- Defense Waste Processing Facility, description of operations, 6
- Diatometer, Catherwood, 486, 489
- Diatoms, in Savannah River, 486

- Dose
  - absorbed dose, 102
  - applicable standards, 105
  - collective effective dose equivalent, 103
  - defined, 101
  - dose equivalent, 102
  - effective dose equivalent, 102
  - environmental dose commitment, 104
  - from atmospheric releases, 127
    - collective effective dose equivalent, 127
  - from consumption
    - of deer, 449
    - of fish, 448
    - of hogs, 449
  - to aquatic organisms, 449
- Dose calculations
  - collective dose, 103
  - models, 107
  - nonroutine releases, 469
  - offsite, 106

Dose factors, 103

- Drinking water
  - dose standards, 105
  - nonradiological monitoring, 219
    - analytical procedures, 61
    - sample collection, 61
  - radiological monitoring, 53, 216

Dry monitoring wells, special surveys, 486

E

- E Area, description of operations, 4
- Effective dose equivalent, 102
  - defined, 102
  - from atmospheric releases, 127
  - weighting factors used, 59
- Emergency Planning and Community Right-to-Know Act (EPCRA), SARA Title III reporting requirements, 19
- EMCAP. *See* Environmental Monitoring Computer Automation Project
- Environmental Advisory Committee, 8
- Environmental Assessment
  - Consolidated Incinerator Facility, 18
  - Plantwide Fire Protection Project, 18
- Environmental awareness, 10
- Environmental data exchange, 8
- Environmental dose commitment, 104

Environmental Impact Statement, New Production Reactor, 18

Environmental monitoring

- 1991 program changes, 38
- description of programs, 8
- design criteria for, 31
- implications of pathways analysis for, 37
- objectives of, 29
- program basis, 29
- program changes in 1991, 44
  - expansion of groundwater data format, 45
  - sample identification and tracking, 44
  - termination of nonradiological ambient air monitoring, 45
- rationale for, 31

Environmental Monitoring Computer Automation Project, 44

Environmental outreach, 540

Environmental penetrating radiation, radiological monitoring

- reporting results, 47
- sample collection, 47

Environmental research, 8

Environmental sampling, blind sample program, 75

EPA Water Pollution Study, results

- J.H. Carr and Associates, 79
- TMA/Eberline, Inc., 79

EPCRA. *See* Emergency Planning and Community Right-to-Know Act

F

F Area, description of operations, 4

Federal Facilities Agreement, 17

Federal Facilities Compliance Agreement, 15

Fish

- dose from consumption, 448
- in Savannah River
  - cursory biological survey results, 489
  - Plant Vogtle survey results, 490
- nonradiological monitoring, 60
  - analytical procedures, 60
  - applicable standards, 449
  - description of, 449
  - monitoring results, 450
  - sample collection, 60

radiological monitoring

- description of, 443
- monitoring results, 444
- sample collection and analysis, 53
- special sampling, 24

Food, radiological monitoring, 52

- analytical procedures, 52
- sample collection, 52

Food products, 140

- doses from consumption, 143
  - food, 144
  - milk, 144
- foodstuffs, 142
  - description of monitoring program, 142
  - monitoring results, 143
- milk
  - description of monitoring program, 140
  - monitoring results, 140

Four Mile Creek, special survey, description of, 485

G

G Area, description of operations, 4

Gamma-emitting radionuclides

- analytical procedures, 49, 50, 51, 52, 54, 55
- deposition, 134
- in air, 131
- in clams, 481
- in food, 143
- in milk, 140
- in seepage and retention basin vegetation, 140
- in soil, 136
- lower limits of detection, 56
- radionuclides reported, 56

Geology, of Savannah River Site, 2

Gross alpha

- analytical procedures, 48, 50, 51, 54, 55
- deposition, 134
- in air, 130
- usefulness of analysis, 56

Groundwater

- cleanup, 530
- data preparation, 58
- evaluation of data, 58
- modeling program, 532
- monitoring
  - General Engineering Laboratories, 79
  - IT Analytical Services, 79
- nonradiological monitoring
  - analytical procedures, 60

- sample collection, 60
- QA/QC program, 79
- radiological monitoring, 51
  - sample collection and analysis, 51
- statistical treatment, 58
- Groundwater Monitoring Program, 221

H

- H Area
  - description of operations, 4
  - retention basin, liquid releases from, 471
    - analytical results, 471
- Heavy Water Reprocessing Area, description of operations, 6
- Hogs
  - dose from consumption of, 449
  - radiological monitoring
    - description of, 446
    - monitoring results, 446
  - sample collection and analysis, 53
- Hydrology, of Savannah River Site, 2

I

- Insects, in Savannah River
  - cursory biological survey results, 488
  - Plant Vogtle survey results, 490
- Interlaboratory comparison programs
  - EPA Water Pollution Study, 79
  - for groundwater, 80
  - for NPDES, 78
  - for radiological chemistry, 77
- Intralaboratory comparison programs
  - for groundwater, 80
  - for NPDES, 78

J

- J.H. Carr and Associates
  - EPA Water Pollution Study, 79
  - QA/QC requirements
    - NPDES program, 78
    - water quality program, 79

K

- K Area, description of operations, 4
- K Reactor
  - flow test assessment, 534
  - lawsuit, 24
  - tritium release, 472

L

- L Area, description of operations, 4
- L Lake, monitoring program, 527
- LADTAP, 107
- Land disposal restrictions, 15
- Land resources, at Savannah River Site, 2
- Liquid Effluent Treatment Facility, description of operations, 4
- Liquid effluents (NPDES), nonradiological monitoring, 59
  - analytical procedures, 59
  - sample collection, 59
- Liquid releases, modeling, 112
- Lost Lake, biological restoration, 528
- Lower limits of detection (LLD), 57

M

- M Area, description of operations, 4
- MAXIGASP, 107
- Meteorology, of Savannah River Site, 2
- MicroR meters, measuring environmental penetrating radiation, 482, 483, 484
- Milk, radiological monitoring, 51
  - analytical procedures, 52
  - sample collection, 51
- mixed waste management facility closures, 15

N

- National Emissions Standards for Hazardous Air Pollutants, 19
  - dose standards, 105
- National Environmental Policy Act, 17

- National Environmental Research Park, 544
program overview, 8
- National Pollutant Discharge Elimination System
compliance for 1991, 19
compliance inspection, 22
nonradiological monitoring
analytical procedures, 59
sample collection, 59
QA/QC program, 78
- Natural resource management, 541
fire, 543
soil, 542
timber, 541
water, 542
wildlife, fisheries, botany, 542
- NEPA. *See* National Environmental Policy Act
- NESHAP. *See* National Emissions Standards for Hazardous Air Pollutants
- Non-insect macroinvertebrates, in Savannah River, Plant Vogtle survey results, 490
- Nonradiological. *See* specific medium
- Nonradiological air monitoring, 132
1991 nonradioactive effluent releases to the atmosphere, 132
ambient air quality, 133
applicable standards, 132
description of monitoring program, 132
monitoring results, 133
- Nonradiological monitoring
analytical procedures, 59
of wildlife, 449
overview, 59
program overview, 31
sample collection, 59
special surveys, 486
cursory biological, 488
diatom community, 486
results of, 486
Plant Vogtle, 489
- Nonroutine occurrences
772-F contamination, 470
772-F contamination, monitoring results, 470
H-Area Retention Basin, analytical results, 471
K-Reactor tritium release, monitoring results, 472
liquid releases
H-Area Retention Basin, 471
K-Reactor tritium release, 472
Twin Lakes Dam failure, 470
monitoring results, 471
- Nonvolatile beta
analytical procedures, 48, 50, 51, 54, 55
deposition, 134
in air, 130
- NPDES. *See* National Pollutant Discharge Elimination System
- ## P
- P Area, description of operations, 4
- Paddlewheel samplers, 49
- Par Pond
drawdown, 22, 480
drawdown evaluation, 528
monitoring program, 528
radiological survey, 479
special survey
description of, 479
monitoring results, 482
- Pathways analysis, implications for environmental monitoring, 37
- Pen Branch fault, 532
- Penetrating radiation, 136
description of monitoring program, 136
expansion of monitoring network, 137
monitoring results, 136
- Permits, 21
- PIP. *See* Public Involvement Plan
- Plant Vogtle, ANSP special survey
description of, 489
survey results, 489
- Plutonium
analytical procedures, 49, 51, 52, 54, 55
deposition, 135
in air, 131
in food, 143
in soil, 136
- Polychlorinated biphenyls, TSCA, 20
- Pond C, radiological survey, 480
- POPGASP, 107
- Power plants, boiler capacities, 132
- Protozoa, in Savannah River, Plant Vogtle survey results, 490
- Public Involvement Plan, 17
public outreach, 10

Q

QA/QC Programs

- applicable standards, 73
- for NPDES program, 78
- for subcontracted laboratories, 77
- for water quality, 79
- groundwater monitoring, 79
- guidelines, 73
- indicators, 75

Quality Assessment Program, program results, 77

Quality Assurance Division, program results, 77

R

R Area, description of operations, 4

Radiation

- man-made sources of, 40
  - consumer products, 40
  - medical diagnosis and therapy, 40
- sources of
  - cosmic, 39
  - internal, 39
  - natural background, 39
  - other, 40
  - radiation work, 40
  - radioactive fallout, 40
  - terrestrial, 39

Radiation dose

- See also* dose
- comparison of levels of, 40, 42
- definitions, 101

Radiation exposures, perspectives on, 39

Radioactivity, measurement techniques, 45

Radiological Chemistry, blind sample program, 76

Radiological monitoring, 126

- See also* specific medium
- 1991 effluent releases to the atmosphere, 126
  - applicable regulations, 126
  - description of effluent monitoring program, 126
  - effluent monitoring results, 126
- air, 48
- analytical procedures, 47
- calculated offsite radiation doses from atmospheric releases, 127
  - applicable regulations, 127
  - average individual effective dose equivalent, 127
  - collective effective dose equivalents, 127
  - maximum individual effective dose equivalent, 127

NESHAP compliance, 127

calculated radionuclide concentrations in air, 126

applicable regulations, 126

calculated concentrations, 126

deer, 446

drinking water, 53

EMCAP, 45

food, 52

groundwater, 51

hogs, 446

measured radionuclide concentrations in air, 129

applicable standards, 129

description of monitoring program, 129

monitoring results, 129

milk, 51

penetrating radiation, 47

program overview, 32

radioactivity measuring techniques, 45

counting geometries, 46

general measurement processes, 46

instrumentation, 46

rainwater, 54

sample collection, 47

Savannah River, 51

sediment, 54

seepage basins, 51

soil, 54

special surveys

dry monitoring wells, 486

Four Mile Creek, 485

Par Pond, 479

Savannah River Swamp, 482

streams, 49

vegetation, 55

wildlife, 53, 443

Radionuclides

important pathways for releases from SRS, 36

released to air, 32

released to surface water, 34

summary of important, 35

Rainwater, 133

description of monitoring program, 133

monitoring results, 134

radiological monitoring, 54

analytical procedures, 54

sample collection, 54

RCRA. *See* Resource Conservation and Recovery Act

Reactor areas, description of operations, 4

Reactor Materials Area, description of operations, 4

Research projects, seismic, 531

Receiving Basin for Offsite Fuel, description of operations, 6

regulations, followed at SRS, 14

Releases, measurement capabilities, 38

Replacement Tritium Facility, description of operations, 4

Research projects
     environmental, 527
     geoscience, 531

Resource Conservation and Recovery Act (RCRA), 13
     defined, 13
     Facility Investigation Program, 16
     integration with CERCLA, 17
     land disposal restrictions, 15
     RFI Program, 16
     waste unit closures, 15

S

S Area, description of operations, 4

Safe Drinking Water Act, 18

Saltstone Facility, description of operations, 6

Sample collection. *See* specific medium

Savannah River
     nonradiological monitoring, 212
         analytical procedures, 60
         sample collection, 59
         temperature surveys, 214
     radiological monitoring, 51
         analytical procedures, 51
         sample collection, 51
     water quality surveys, 486

Savannah River Site
     description of, 1
     description of operations, 3
     geology, 2
     hydrology, 2
     land resources, 2
     location, 1
     meteorology, 2

Savannah River Swamp
     1990 comprehensive survey results, 483
     1991 cursory survey results, 484
     special survey, description of, 482

Sediment
     nonradiological monitoring, sample collection, 61
     nonradiological monitoring program, analytical procedures, 61
     radiological monitoring, 54
         analytical procedures, 54
         description of, 214, 216
         sample collection, 54

Seepage basin, closures, 15

Seepage basins
     radiological monitoring
         analytical procedures, 51
         vegetation monitoring results, 139
     radiological monitoring program, 51
     sample collection, 51

Seismic studies, 531

Separations Areas, description of operations, 4

Settling basin closures, 15

Shellfish, sample collection and analysis, 53

Soil, 135
     cleanup, 530–534
     description of monitoring program, 135
     monitoring results, 136
     radiological monitoring, 54
         analytical procedures, 54
         sample collection, 54

Solid Waste Disposal Facility
     description of operations, 6
     radiological monitoring, vegetation monitoring results, 140

Special surveys
     nonradiological monitoring, 486
         cursory biological, 488
         diatom community, 486
         Plant Vogtle comprehensive, 489
     radiological monitoring, 479
         dry monitoring wells, 486
         Four Mile Creek, 485
         Par Pond, 479
         Savannah River Swamp, 482

Steel Creek, monitoring program, 527

Streams
     nonradiological monitoring, 59, 213
         analytical procedures, 60
         sample collection, 59
         temperature surveys, 214
     radiological monitoring, 49
         analytical procedures, 50

sample collection, 49

Strontium
analytical procedures, 49, 50, 51, 52, 54, 55
deposition, 135
in food, 143
in milk, 140
in soil, 136

Strontium-90, releases, liquid, 471

Superfund Amendments and Reauthorization Act,
reporting requirements, 19

Surface water, radiological monitoring, 200
monitoring results, 207
offsite radiation doses, 203
radionuclide concentrations, 203

Surveillances, environmental programs, 21

SWDF. *See* Solid Waste Disposal Facility

T

Thermoluminescent dosimeters, measuring environmental penetrating radiation, 47

Tiger Team Assessment, 22

TMA/Eberline, Inc.
EPA Water Pollution Study, 79
QA/QC requirements
NPDES program, 78
water quality program, 79

Toxic Substances Control Act, 20
PCB storage, 20

Training
environmental awareness, 10
QA, 74

Tritium
analytical procedures, 49, 50, 51, 52, 53, 54, 55
in air, 131
in food, 143
in Georgia wells, 24
in milk, 142
in rainwater, 135
K-Reactor release, 25
releases, liquid, 472

Turkeys
radiological monitoring, 448
sample collection and analysis, 54

Turtles
radiological monitoring, 448
sample collection and analysis, 54

Twin Lakes Dam failure, 470
monitoring results, 471

U

Underground storage tanks, regulated under RCRA, 16

Uranium/plutonium
analytical procedures, 50, 52
in food, 143

V

Vegetation, 138
description of monitoring program, 138
monitoring results, 138
radiological monitoring
analytical procedures, 55
sample collection, 55
seepage and retention basin, 139
Solid Waste Disposal Facility, monitoring results, 140

W

Waste
management under RCRA, 13
minimization program, 9

Waste Management Areas, description of operations, 4

Water, nonradiological monitoring, 211
for herbicides, 214
NPDES, 211

Water quality
QA/QC program, 79
standards, 213

Wetlands
assessment, 529
ecology, 539

Wildlife
ecology, 537
radiological monitoring
See also specific wildlife
sample collection and analysis, 53
toxicology, 537

Y

Y Area, description of operations, 4

Z

Z Area, description of operations, 4

PRINCIPAL RADIATION TYPES EMITTED BY RADIONUCLIDES

Alpha

- A particle consisting of 2 protons and 2 neutrons emitted from the nucleus.
- Low penetration: a 5-MeV alpha particle would travel about 3.5 cm in air but would be stopped by a sheet of paper.
- For environmental dosimetry, particularly important for internal exposure, especially in the respiratory passages, on bone surfaces, and in red marrow. Alpha energy is concentrated along short paths and can deliver high localized doses to sensitive surface regions.

Beta

- An electron emitted from the nucleus.
- Moderate penetration: the range of a 1-MeV beta particle is about 3 m in air but only about 4 mm in tissue.
- For environmental dosimetry, of primary concern for internal exposure. Because of their relatively short range in tissue, beta particles principally irradiate the organs in which they originate.

Gamma and X-rays

- Electromagnetic radiation, emitted as energy packets called photons, like light and radio waves, but from a higher energy region of the electromagnetic spectrum.
- High penetration: to absorb 95% of the gamma energy from a Co-60 source, 6 cm of lead, 10 cm of iron, or 33 cm of concrete would be needed.
- For environmental dosimetry, important both for internal and external exposure. Gamma emitters deposited in one organ of the body can significantly irradiate other organs.

END

**DATE
FILMED**

3 / 9 / 93