DOE/PC/91284-T1

**NITRATION OF POLYNUCLEAR AROMATIC HYDROCARBONS
IN COAL COMBUSTORS AND EXHAUST STREAMS**

Quarterly Report for the
Period September 1, 1991 to December 31, 1991
Grant DE-FG22-91PC91284

Prepared for
THE UNITED STATES DEPARTMENT OF ENERGY

Venkat K. Venkataraman
Project Officer
Morgantown Energy Technology Center
P. O. Box 880; MS C04
Morgantown, WV 26507

Submitted by

Ms. Liya Yu, Mr. John Dadamio, Asst. Prof. Lynn Hildemann and Asst. Prof. Stephen Niksa

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, mark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

August 1992

TABLE OF CONTENTS

<u>Section</u>	<u>Page</u>
1. SUMMARY	1
2. INTRODUCTION TO THE PROGRAM	2
3. FINDINGS	3
3.1 Introduction	3
3.2 Sample Preparation	3
3.2.1 Background	3
3.2.2 The Radiant Coal Flow Experiment	4
3.2.3 Representative Results	8
3.2.4 Current Activity	10
3.3 Sample Analysis	10
3.3.1 Background	10
3.3.2 Candidate Analytical Strategies	12
3.3.3 Current Activity	14
4. SHORT RANGE OBJECTIVES	16
5. REFERENCES	17

1. SUMMARY

Pending approval of our environmental impact statement and release of funds for this project, we have moved forward with contingency financial backing from the Mechanical and Civil Engineering Departments at Stanford. During the period September 1, 1991 to December 31, 1991, two graduate students were inducted into this project.

Mr. John Dadamio of the ME Department will be responsible for preparing the polynuclear aromatic hydrocarbons (PAH) under closely monitored pulverized fuel (p. f.) firing conditions. He will be using the radiant coal flow experiment developed by Dr. John Chen from 1986 through 1991 under EPRI sponsorship, and since duplicated twice in our laboratory for studies with different objectives. He has been digesting the layout, performance characteristics, and results from previous studies which are summarized in this report.

Ms. Liya Yu, a doctoral student in the CE Department, will be responsible for analyzing the PAH samples generated from the radiant coal flow experiments. She will be using a wide range of analytical equipment to fractionate and characterize the PAH, including a gravity-flow column chromatograph and a high pressure liquid chromatograph (HPLC), both of which are already fully operational. She has been familiarizing herself with the operation characteristics of the HPLC, and reviewing the literature to select an appropriate fractionation scheme for the coal tar samples.

2. INTRODUCTION TO THE PROGRAM

Nitro-polynuclear aromatic hydrocarbons (nitro-PAH) are the predominant mutagens on respirable particles from coal-fired boilers. Since nitro-PAH are not primary products of coal devolatilization, their formation must involve secondary chemistry at elevated temperatures. However, it is not known where in the combustion or exhaust processes they form, which reaction species are involved, or how concentrations are influenced by operating conditions. Results from this study will help to relate the environmental impact of mutagenic emissions to boiler firing strategies.

The objectives of this three-year project are to (1) identify the conditions which promote the nitration of PAH during primary combustion, reburning, hot gas cleanup, and particulate removal; and (2) investigate the potential relationship between NO_x abatement and PAH nitration. A novel coal flow reactor burning actual coal products operates over the domains of heating rates, temperatures, fuel-equivalence ratios, and residence times in utility boilers. A fluidized bed will be built for studies of simulated hot gas cleanup at lower temperatures. Gas chromatography with chemiluminescence detection will measure the aggregate amount of nitro groups present, to determine when nitro-PAH first appear, and how nitration is affected by the operating conditions. Tars from primary and secondary pyrolysis and oxidative pyrolysis will be fractionated into chain hydrocarbons, polynuclear aromatics, oxygenated species, and a basic fraction, so that their ring number distribution can be monitored with high performance liquid chromatography.

3. FINDINGS

3.1 Introduction

Meeting the objectives of this program involves two broad tasks: (1) Preparing the polynuclear aromatic hydrocarbons (PAH) under closely monitored pulverized fuel (p. f.) firing conditions; and, (2) analyzing the PAH samples to monitor extents of nitration, ring number distribution, etc. While both activities are essential to this project, they involve scientific principles which are almost completely unrelated. So in this and all future reports, our findings will be segregated according to their relation to either sample preparation or sample analysis. In actuality, Profs. Niksa and Hildemann each have a student working on these respective parts of this project.

The current status of the instrumentation and procedures for these two activities are grossly different. The sample preparation scheme is already fully-operational. This laboratory enterprise was largely sponsored by the Electric Power Research Institute and developed by Prof. Niksa and coworkers during the past 7 years. A small fluidized bed is the only equipment item to be built to prepare samples during this project. Most of the instrumentation for the sample analysis scheme is available, but virtually all of the procedures will be developed during this project. However, the recent literature describes several candidate methods for acquiring the information we need from samples with many of the same chemical properties.

Being that this is our first quarterly report, it is devoted to introductions of the research staff and the operating principles behind our approaches in the laboratory. The reactor that generates PAH samples under simulated utility boiler conditions is described first, using past applications to show its performance characteristics. Then the literature on PAH analysis is surveyed with an eye toward schemes to characterize their ring number distributions.

3.2 Sample Preparation

3.2.1. Background

During pulverized fuel firing in utility boilers, PAH are converted in three stages. Initially during primary devolatilization, PAH are expelled as heavy, aromatic compounds collectively called tar. Next, the volatiles in hot fuel-rich gases undergo secondary pyrolysis and oxidative pyrolysis. Tar has a strong propensity to soot, so PAH levels fall and they become smaller during secondary pyrolysis. Eventually, in the third stage, oxygen contacts the PAH and soot and converts them into ultimate exhaust gases. Our radiant coal flow

experiment maintains the conditions needed to clearly resolve these stages while it imparts heat fluxes, heating rates, temperatures, and reaction times which are similar to those in pulverized coal flames. In this project, The PAH prepared under simulated p. f. firing conditions will be generated in this system. It was developed by Dr. John Chen from 1986 through 1991 under EPRI sponsorship, and since duplicated twice in our laboratory for studies with different objectives. Mr. John Dadamio will be operating the system to prepare PAH for this project. Although he is working toward a M.S. Degree, his program accommodates 9 credit hours of research per quarter, which is the same level as most beginning Ph.D. students at Stanford.

The furnace has a unique heating scheme that presents several new possibilities for high-temperature reactivity studies. Most importantly, the thermal histories of the coal suspension and its entrainment stream can be independently regulated over wide ranges. In its operating mode for primary devolatilization studies, the particles are hundreds of degrees hotter than the gases at the furnace outlet, so PAH are quenched as soon as they are expelled and recovered with their most illuminating structural features intact. In its operating mode for secondary pyrolysis studies, the suspension and entrainment streams are heated at similar rates to promote secondary chemistry among the volatiles.

In our experiments, the flowfields and mixing characteristics are deliberately idealized to yield unambiguous reaction times, temperatures, and equivalence ratios - the prerequisites for legitimate reaction analysis. Nevertheless, since we run separate studies for primary devolatilization and secondary pyrolysis (and oxidative pyrolysis and combustion in the future), our database covers the range of mixing conditions and equivalence ratios in actual coal flames. Depending on the way it is operated, the coal reactor produces PAH samples having a prescribed extent of primary or secondary pyrolysis.

The following sections briefly illustrate the operating principles and performance with previous results. Publications are available on the instrumentation (Chen and Niksa, 1992a), the characterizations of primary devolatilization (Chen and Niksa, 1992b) and secondary pyrolysis (Chen, Castagnoli, and Niksa, 1992), and selected aspect of fuel nitrogen evolution (Chen and Niksa, 1993).

3.2.2 The Radiant Coal Flow Experiment

A schematic of the radiant coal flow reactor appears in Fig. 1. At the top a feeder dumps pulverized particles into an entrainment stream, forming an optically-thin suspension which flows downward into a radiant furnace section. The radiant section consists of a quartz tube on the axis of a graphite cylinder which is inductively-heated to

Fig. 1. The radiant coal flow reactor.

temperatures up to 1850 K. Near-black-body thermal emission from the graphite rapidly heats the particles as they traverse the furnace. Since the entrainment gas is transparent to the radiation its only means of heating is by convection from the tube wall and particles. Dilute suspensions, which are used in the primary pyrolysis studies, have little interfacial surface area for interphase heat transfer, so the entrainment gas remains relatively cool and quenches chemistry among primary products as they are expelled. To promote secondary reactions of the volatiles, the suspension loading is increased to enhance interphase heat transfer and raise the gas temperature. In addition, residence times are extended for secondary chemistry studies by using a similar furnace whose hot zone is two-and-one-half times longer than that for the primary pyrolysis studies.

Adding oxygen to the process stream achieves higher particle temperatures for the same nominal operating condition because of the combustion exotherm. Residence times are extended with the longer furnace by extending the flow tube by 30 cm beyond the exit of the radiant section. Oxygen is blended in the entrainment streams to the desired level upstream of the furnace section.

Nominal particle residence times are set by the inlet gas flow rate and the distance between the inlet plane and an argon quench nozzle, which is fixed; reported values are measured under actual conditions. For primary pyrolysis studies, residence times are varied at fixed furnace temperature (1840 K). As seen in Fig. 2a, thermal histories in a series of runs have nearly the same heating rate, but the suspension achieves different temperatures at the outlet in each case. These are calculated temperature profiles for all of the operating conditions for primary pyrolysis studies. As in the actual experimental runs, gas velocities and coal feed rates are simultaneously adjusted to vary residence time but fix the suspension loading at 300 particles/cm³ at the inlet. Particles begin heating 1 cm upstream of the inlet plane, due to the radiation escaping through the flow tube. Even though their heating rate exceeds 104 K/s, particles are always much cooler than the wall temperature at the outlet. Yet with the furnace at 1840 K, the radiant flux onto the centerline is 60 W/cm², similar to the 50 to 100 W/cm² estimated for coal-fired burners in utility boilers. Most importantly, the gas heats at only 2300 K/s, and reaches only 550 K at the outlet. At this temperature, secondary reactions are too slow to affect coal-derived products. As explained by Chen and Niksa (1992b), various product characteristics strongly corroborate the minimal extents of secondary chemistry achieved in this furnace.

For secondary pyrolysis studies, the severity of the thermal processing is regulated simply by increasing the furnace temperature in successive runs with the same inlet gas velocity and suspension loading. The thermal histories for all cases in secondary pyrolysis studies appear in Fig. 2b. They have similar heating rates but different reaction times at different ultimate temperatures. The suspension initially heats faster than the gas, but

Fig. 2a. Calculated thermal histories of the suspensions (solid curves) for measured values of residence time in the primary devolatilization studies of 56, 61, 66, 72, 77, 83, 87, and 90ms, and calculated gas temperature for 90ms (dotted curve).

Fig. 2b. Calculated thermal histories of particles (solid curves) and gas (dotted curves) for secondary pyrolysis with 1200 particles/cm³ entrained at 18cm/s at the inlet. The letters denote furnace temperatures and measured residence times as follows: a = 1480K, 174ms; b = 1570K, 170ms; c = 1660K, 167ms; and d = 1740K, 156ms.

the high convective heat transfer rate quickly brings the particle and gas heating rates into balance at nominal values of 104 K/s. As a result, the temperature difference is less than 150 K at the outlet of the 1740 K furnace, and gas temperatures reach 1100 K in the longer furnace at 1740 K. The most severe condition for primary pyrolysis of 90 ms in an 1840 K furnace imparts an outlet temperature of 950 K, which is the same as for the least severe secondary pyrolysis condition of 175 ms through the furnace at 1480 K, in Fig. 2b. At the most severe condition the maximum particle temperature is 1350 K.

Product recovery and analysis begins at the furnace outlet, where a quench nozzle blasts argon into the process stream, rapidly quenching all chemistry and nucleating tar into an aerosol. About 2-4 wt.% of aerosol deposits in the nozzle, regardless of the aerosol yield, so 2 wt.% is added to all aerosol yields greater than 4 wt.%. Products are segregated into bulk solid particles, tar/soot aerosol, and noncondensable gases with virtual impaction in an aerodynamic classifier. All tar and char is collected so that yields are determined gravimetrically. Tars are recovered on a four-stage assembly of glass-fiber filters and a polypropylene liner. Pure tar samples for subsequent chemical analyses are prepared by extraction with tetrahydrofuran (THF) in an ultrasonic bath, followed by filtration through a 0.2 micron Teflon membrane. The membrane residue is weighed and denoted as the soot yield.

Noncondensable gases are quantified by non-dispersive infrared (NDIR) and chemiluminescence analyzers, and gas chromatography. Carbon, hydrogen, and nitrogen contents of condensed products are determined in-house. Mass and elemental balances are closed to within 5% in individual runs, so that subsequent interpretations are not subject to inordinate scatter in the data.

3.2.3 Representative Results

In this section, results from past studies are presented to illustrate trends in the PAH yields through primary devolatilization and secondary pyrolysis. Transient weight loss and tar yields during primary devolatilization for Dietz subbituminous and Pit. #8 hvA bituminous coals appear in Fig. 3. They indicate clearly that the relative contribution of tar to the initial weight loss is rank dependent. The Dietz expels significant amounts of gases from the onset of devolatilization, whereas initially the gas yields from the Pit. #8 are too low to resolve on this scale. Tar evolution from all coals ceases well before weight loss reaches asymptotic values. For the Dietz, rate of weight loss actually increases while tar yields remain at the ultimate value. CO and H₂O evolution account for most of the additional weight loss during the final stages, so the increase in rate of weight loss in the later stage for the Dietz is consistent with its higher oxygen content.

Fig. 3. Transient weight loss (○) and tar yields (●) versus measured residence times from the furnace at 1840K for (a) Dietz and (b) Pit. #8.

To characterize the impact of secondary pyrolysis, total weight loss, the combined yields of tar, oils, and soot, and the soot percentage among these three products appear in Fig. 4 for the Dietz and Pit. #8 coals. Weight loss reaches its ultimate values of 57 wt.% and 61 wt.% daf for the Dietz and the Pit. #8, respectively, for temperatures above 1550 K. These values are comparable to respective values of 53% and 58% obtained at the longest residence time for primary devolatilization (Fig. 3).

The yields of tar/oils plus soot remain the same throughout secondary pyrolysis, within an experimental uncertainty of 2wt.%. Regressions of the data indicate that the aggregate yields decrease by 3wt.% with the Dietz, and increase by 1 wt.% with the Pit. #8. For both coals, the invariant values are identical to the yields of tar/oils at the longest residence time for primary devolatilization, which are 22% for the Dietz and 32% for the Pit. #8. As seems intuitively obvious, these yields would be invariant if tars are the precursors to soot. However, by virtue of their radically different elemental compositions, tar and soot cannot possibly be exchanging quantitatively at all stages of secondary pyrolysis, as demonstrated by Chen et al. (1992). While aggregate yields remain the same, the soot percentage among oils and aerosol covers a wide range as furnace temperatures are increased from 1480 to 1740K, growing from 18 to 70% for the Dietz, and from 30 to 86% for the Pit. #8. Note also that the soot percentage is near-linearly proportional to furnace temperature, so furnace temperature becomes a convenient scale for the severity of secondary reactions in any of our results.

3.2.4 Current Activity

Activity this quarter on sample preparation focused on Mr. Dadamio's training program on the radiant coal flow reactor. He studied Dr. Chen's Ph.D. thesis and all previous publications on this system. In the laboratory he prepared diagrams of all flow paths, and began preliminary studies to learn to regulate flow rates.

3.3 Sample Analysis

3.3.1 Background

The tar samples collected from the radiant coal flow experiments will each contain hundreds of organic compounds, ranging from low to high molecular weights, and from neutral to extremely polar. The chemical characteristics of each sample will be influenced both by the actual coal combustion conditions, and by the type of coal burned. In particular, tar from high rank coals will contain predominantly neutral organics, while lower rank coals will generated a high fraction of polar organics.

Fig. 4 Weight loss (○), aggregate yields of tar plus oils plus soot (●), and soot percentage in the aggregate (× and dashed curve) versus furnace temperature for (a) Dietz and (b) Pit. #8.

Our analytical procedures will chemically characterize each sample, both with respect to compounds polarities and ring number distributions. The characteristics and trends observed for PAH as a compound class will be compared with those of the nitro-PAH compound class as well as with individual nitro-PAH species.

While development of analytical procedures for coal tar will be an integral part of this project, the scientific literature provides substantial guidance for identifying promising analytical approaches. In the next section, a brief review of the literature on PAH analytical methods will be presented.

3.3.2 Candidate Analytical Strategies

Each radiant coal flow experiment will generate an organic sample of incredible complexity. The analytical challenge is to quantitatively characterize the organic material in a way that allows comparisons to be made both over a range of combustion conditions and between different coals. To achieve this goal, the focus must be on characterizing the tar as fully as possible. Hence, as an integral part of this nitro-PAH study, the trends for total PAH as a compound class (as well as nitro-PAH as a more specific compound class) must be examined.

The first step in the analytical procedure is to extract the organics from the tar sample, which may also contain soot. Previous research has found that tetrahydrofuran (THF) allows quantitative recovery of the PAH fraction from the tar (Chen et al., 1989). A procedure has also been published for concentrating the PAH sample and then evaporating the THF to obtain a "pure" PAH sample (Lafleur et al., 1986); using the radiant coal flow reactor, approximately 100 mg of purified organic material can be obtained (Chen et al., 1989).

Researchers have utilized the HPLC to determine the ring number distribution of neutral PAH present in tar from a high-rank coal (Wornat et al., 1988) under a limited range of secondary pyrolysis conditions. However, it is known that polar compounds interfere with this characterization (Wornat, 1991). Hence, a fractionation scheme will be necessary to separate the neutral organics from the more polar material before analysis via HPLC.

The most promising fractionation scheme involves gravity-flow column chromatography. One research group has utilized this method with the sequential use of four solvents (ranging from nonpolar to highly polar) to separate the neutral PAH from the more polar species in a coal tar (Lafleur et al., 1988). The fractionation they obtained with this approach is shown in Fig. 5; the middle two solvent fractions contain the 3- to 10-ring PAH species, separated from the highly polar PAH eluting in the methanol fraction.

Fig. 5. Fractionation of organic species via gravity-flow column chromatography using hexane, toluene, dichloromethane (DCM) and methanol (information from Lafleur et al., 1988). [PAC = polycyclic aromatic compounds; CXPAH = carboxy-PAH; H₂PAH = dihydroxy-PAH]

To quantitatively determine the total amount of nitro-PAH species present, a sensitive and specific detection method is needed. The literature contains many approaches to this problem, including derivatization (Campbell and Lee, 1984), multiple fractionation schemes (Later et al., 1981; Draper, 1986), and specialized detectors (Nishioka et al., 1982). Gas chromatography with chemiluminescence detection appears most promising as a method of nitro-PAH detection; the work of Yu (1983) has shown (see Fig. 6) that it specifically detects NO₂-substituted PAH with no interference either from parent PAH or from other nitrogen-containing (e.g., cyano- and ammonia-substituted) PAH.

3.3.3 Current Activity

Activity this quarter on development of analytical methods focused on Ms. Yu's training to familiarize herself in the laboratory with the operation, calibration, and maintenance of the HPLC. She also reviewed in detail the literature covering organic fractionation schemes, with the goal of beginning tests on the gravity-flow column chromatography scheme.

Fig. 6. Analysis of a standard mixture of PAHs using gas chromatography with chemiluminescence detection (from Yu, 1983). 2-Nitronaphthalene (1) and 1-nitropyrene (2) were selectively detected out of a standard mixture that also contained naphthalene, phenanthrene, chrysene, fluorenone, carbazole, dibenzofuran, isoquinoline, 1-cyanonaphthalene, 2-aminofluorene, dibenzothiophene, and benzi[g,h,i]perylene.

4. SHORT RANGE OBJECTIVES

During the coming quarter, Mr. Dadamio will begin to operate the radiant flow reactor. As he becomes more comfortable he will begin compiling his own database to compare against yields from previous studies.

During the next three months, Ms. Yu will begin the assembly and testing of the gravity-flow column chromatography apparatus. She will review the literature to select an appropriate packing material, and to identify strategies for optimizing the operation of this system.

5. REFERENCES

- Campbell, R. M. and Lee, M. L. "Capillary Column Gas Chromatographic Determination of Nitro Polycyclic Aromatic Compounds in Particulate Extracts," *Analytical Chemistry* 56:1026 (1984).
- Chen, J. C. and Niksa, S. "A Radiant Flow Reactor For High Temperature Reactivity Studies of Pulverized Solids," *Rev. Sci. Instr.* 63(3):2073 (1992a).
- Chen, J. C. and Niksa, S. "Coal Devolatilization During Rapid Transient Heating. Part 1. Primary Devolatilization," *Energy and Fuels* 6:254 (1992b).
- Chen, J. C., Castagnoli, C. and Niksa, S. "Coal Devolatilization During Rapid Transient Heating. Part 2. Secondary Pyrolysis," *Energy and Fuels* 6:264 (1992).
- Chen, J. C., Chang, Y.-J. C. and Niksa, S. "Rapid Coal Devolatilization in a Radiant Coal Flow Reactor," *ACS Division Fuel Chemistry Pre.* 34(4):1347 (1989).
- Chen, J. C. and Niksa, S. "Suppressed Nitrogen Evolution For Coal-Derived Soot and Low Volatility Coal Chars," *Twenty-Fourth Int. Symp. on Combust.*, in press, 1993.
- Draper, W. M. "Quantitation of Nitro- and Dinitropolycyclic Aromatic Hydrocarbons in Diesel Exhaust Particulate Matter," *Chemosphere* 15:437 (1986).
- Later, D. W., Lee, M. L., Bartle, K. D., Kong, R. C. and Vassilaros, D. L. "Chemical Class Separation and Characterization of Organic Compounds in Synthetic Fuels," *Analytical Chemistry* 53:1612 (1981).
- Lafleur, A. L., Monchamp, P. A., Plummer, E. F. and Kruzel, E. L. "Evaluation of Gravimetric Methods of Dissoluble Matter in Extracts of Environmental Samples," *Analytical Letters* 19(21&22):2103 (1986).
- Lafleur, A. L., Monchamp, P. A., Chang, N. T., Plummer, E. F. and Wornat, M. J. "Evaluation of Cyano-Bonded Phase for the Fractionation of Bioactive Complex Mixtures," *J. Chrom. Sci.* 26:337 (1988).
- Nishioka, M. G., Petersen, B. A. and Lewtas, J. "Comparison of Nitro-Aromatic Content and Direct-Acting Mutagenicity of Diesel Emissions," in *Polynuclear Aromatic Hydrocarbons: Physical and Biological Chemistry* (M. Cook, A.J. Dennis and G.L. Fisher, eds.), Battelle Press, Columbus, OH, p. 603 (1982).
- Wornat, M. J., Sarofim, A. F., Longwell, J. P. and Lafleur, A. L. "Effect of Pyrolysis Conditions on the Composition of Nitrogen-Containing Polycyclic Aromatic Compounds from a Bituminous Coal," *Energy and Fuel* 2:775 (1988).
- Wornat, M. J., personal communication, 1991.
- Yu, W. C. "Trace Level Determination of Nitro-PAHs by Capillary Gas Chromatography with a Chemiluminescent Detector," in *Polynuclear Aromatic Hydrocarbons: Formation, Metabolism and Measurement* (M. Cook and A.J. Dennis, eds.), Battelle Press, Columbus, OH, p. 1267 (1983).

END

**DATE
FILMED**

12 / 8 / 92