WSRC-RP--92-878

DE93 001894

SOIL GAS INVESTIGATIONS AT THE SANITARY LANDFILL (U)

by

D. E. Wyatt, R. J. Pirkle, and D. J. Masdea

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

This report was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U.S. Department of Energy. By acceptance of this report, the publisher and/or recipient acknowledges the U.S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this report, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted report.

MASTER

ds
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Soil Gas Investigations at the Sanitary Landfill (U)

D. E. Wyatt
R. J. Pirkle
D. J. Masdea

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

DISCLAIMER

This report was prepared by Westinghouse Savannah River Company (WSRC) for the United States Department of Energy under Contract No. DE-AC09-89SR18035 and is an account of work performed under that contract. Neither the United States Department of Energy, nor WSRC, nor any of their employees makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness, of any information, apparatus, or product or process disclosed herein or represents that its use will not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trademark, name, manufacturer or otherwise does not necessarily constitute or imply endorsement, recommendation, or favoring of same by WSRC or by the United States Government or any agency thereof. The views and opinions of the authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Printed in the United States of America

Available from
National Technical Information Service
U. S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161

Soil Gas Investigations at the Sanitary Landfill (U)

D. E. Wyatt
R. J. Pirkle
D. J. Masdea

Westinghouse Savannah River Company
Savannah River Site
Aiken, SC 29808

TABLE OF CONTENTS

List of Figures	2
List of Tables	6
Executive Summary	7
I. Introduction	8
II. Background	8
III. Quality Assurance	9
A. Sampling Methods	9
B. Analytical Methods	9
C. Accuracy	10
D. Reliability of Selected Data	10
E. Precision	11
F. Minimum Detection Levels	12
G. Blanks	13
H. Data on Magnetic Disk	13
IV. Results	14
V. Conclusions	17
VI. Appendix I	
Sampling Method SM1	
Sampling Method SM4	
Analytical Method AM1	
Analytical Method AM4	
Analytical Method AM8	
Standard Preparation Method SP3	
VII. Appendix II	
Soil Gas Collection Logs	
Mercury Collection Logs	
Waste Management Unit Worksheet	

LIST OF FIGURES

- Figure 1a. The 740-G Sanitary Landfill Site Index Map
(all locations @ 1" = 400 ft)
- Figure 1b. The 740-G Sanitary Landfill North Area Sample Location Map
(sample locations @ 1" = 250 ft)
- Figure 1c. The 740-G Sanitary Landfill South Area Sample Location Map
(sample locations @ 1" = 250 ft)
- Figure 1c. The 740-G Sanitary Landfill Background Area Sample Location
Map (sample locations @ 1" = 200 ft)
- Figure 2a. Gas Chromatogram of Soil Gases at Site 111 from the Flame
Ionization Detector(FID)
- Figure 2b. Gas Chromatogram of Soil Gases at Site 111 from the Electron
Capture Detector(ECD)
- Figure 3. Gas Chromatogram of System Blank # 7
- Figure 4. Gas Chromatogram of C₁-C₄ Standards "M" and "224"
- Figure 5. Gas Chromatogram (FID) of VOC Standard "I", Level 3
- Figure 6. Gas Chromatogram (ECD) of VOC Standard "I", Level 4
- Figure 7. Benzene Retention Time vs Room Temperature
- Figure 8. Gas Chromatogram of C₁-C₄ Hydrocarbon Standard M @ 200:1
Dilution in N₂
- Figure 9. Methane Symbol Map
- Figure 10. Methane (percent) Map, North Area
- Figure 11. Methane (percent) Map, South Area
- Figure 12. Propane Symbol Map
- Figure 13. Propane (ppmv) Map, North Area
- Figure 14. Propane (ppmv) Map, South Area
- Figure 15. n-Butane Symbol Map

LIST OF FIGURES (cont.)

- Figure 16. n-Butane (ppmv) Map, North Area
- Figure 17. n-Butane (ppmv) Map, South Area
- Figure 18. i-Butane Symbol Map
- Figure 19. i-Butane (ppmv) Map, North Area
- Figure 20. i-Butane (ppmv) Map, South Area
- Figure 21. Pentane Symbol Map
- Figure 22. Pentane (ppmv) Map, North Area
- Figure 23. Pentane (ppmv) Map, South Area
- Figure 24. Hexane Symbol Map
- Figure 25. Hexane (ppmv) Map, North Area
- Figure 26. Hexane (ppmv) Map, South Area
- Figure 27. Heptane Symbol Map
- Figure 28. Heptane (ppmv) Map, North Area
- Figure 29. Heptane (ppmv) Map, South Area
- Figure 30. Octane Symbol Map
- Figure 31. Octane (ppmv) Map, North Area
- Figure 32. Octane (ppmv) Map, South Area
- Figure 33. Nonane Symbol Map
- Figure 34. Nonane (ppmv) Map, North Area
- Figure 35. Nonane (ppmv) Map, South Area
- Figure 36. Decane Symbol Map
- Figure 37. Decane (ppmv) Map, North Area
- Figure 38. Decane (ppmv) Map, South Area

LIST OF FIGURES (cont.)

- Figure 39. Ethylene Symbol Map
- Figure 40. Ethylene (ppmv) Map, North Area
- Figure 41. Ethylene (ppmv) Map, South Area
- Figure 42. Propylene Symbol Map
- Figure 43. Propylene (ppmv) Map, North Area
- Figure 44. Propylene (ppmv) Map, South Area
- Figure 45. Benzene Symbol Map
- Figure 46. Benzene (ppmv) Map, North Area
- Figure 47. Benzene (ppmv) Map, South Area
- Figure 48. Toluene Symbol Map
- Figure 49. Toluene (ppmv) Map, North Area
- Figure 50. Toluene (ppmv) Map, South Area
- Figure 51. Ethylbenzene Symbol Map
- Figure 52. Ethylbenzene (ppmv) Map, North Area
- Figure 53. Ethylbenzene (ppmv) Map, South Area
- Figure 54. m- & p-Xylene Symbol Map
- Figure 55. m- & p-Xylene (ppmv) Map, North Area
- Figure 56. m- & p-Xylene (ppmv) Map, South Area
- Figure 57. o-Xylene Symbol Map
- Figure 58. o-Xylene (ppmv) Map, North Area
- Figure 59. o-Xylene (ppmv) Map, South Area
- Figure 60. Methylene Chloride Symbol Map
- Figure 61. Methylene Chloride (ppmv) Map, North Area

LIST OF FIGURES (cont.)

- Figure 62. Methylene Chloride (ppmv) Map, South Area
- Figure 63. Chloroform Symbol Map
- Figure 64. Chloroform (ppmv) Map, North Area
- Figure 65. Chloroform (ppmv) Map, South Area
- Figure 66. trans 1,2-Dichloroethylene Symbol Map
- Figure 67. trans 1,2-Dichloroethylene (ppmv) Map, North Area
- Figure 68. trans 1,2-Dichloroethylene (ppmv) Map, South Area
- Figure 69. 1,1,1-Trichloroethane Symbol Map
- Figure 70. 1,1,1-Trichloroethane (ppmv) Map, North Area
- Figure 71. 1,1,1-Trichloroethane (ppmv) Map, South Area
- Figure 72. Trichloroethylene Symbol Map
- Figure 73. Trichloroethylene (ppmv) Map, North Area
- Figure 74. Trichloroethylene (ppmv) Map, South Area
- Figure 75. Tetrachloroethylene Symbol Map
- Figure 76. Tetrachloroethylene (ppmv) Map, North Area
- Figure 77. Tetrachloroethylene (ppmv) Map, South Area
- Figure 78. Mercury Symbol Map
- Figure 79. Mercury (ng/g) Map

LIST OF TABLES

Table 1.	Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill
Table 2.	Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill
Table 3.	Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill
Table 4.	VOC Prepared Standard Concentrations
Table 5.	Analyses of "I" Standards: a) Hydrocarbons; b) Chlorinated Hydrocarbons
Table 6.	Analyses of "I2" Standards: a) Hydrocarbons; b) Chlorinated Hydrocarbons
Table 7.	Analyses of "J2" Standards: a) Hydrocarbons; b) Chlorinated Hydrocarbons
Table 8.	Light Hydrocarbon Analyses of All Standards "M" and "224"
Table 9.	Minimum Detection Levels
Table 10.	System Blanks for All Sanitary Landfill Data Directories: a) Hydrocarbons; b) Chlorinated Hydrocarbons

EXECUTIVE SUMMARY

A soil gas survey was performed at the 740-G Sanitary Landfill during December, 1990. The survey monitored the presence and distribution of the C₁-C₄ hydrocarbons; the C₅-C₁₀ normal paraffins; the aromatic hydrocarbons, BTXE; selected chlorinated hydrocarbons; and mercury. Significant levels of several of these contaminants were found associated with the burial site. In the northern area of the Landfill, methane concentrations ranged up to 63% of the soil gas and were consistently high on the western side of the access road. To the east of the access road in the northern and southern area high concentrations of methane were encountered but were not consistently high. Methane, the species found in highest concentration in the landfill, was generated in the landfill as the result of biological oxidation of cellulose and other organics to carbon dioxide followed by reduction of the carbon dioxide to methane. Distributions of other species are the result of burials in the landfill of solvents or other materials.

I. INTRODUCTION

A soil gas survey was designed and executed at the 740-G, Sanitary Landfill at the Savannah River Site in December, 1990. The survey was extended in May, 1991. The objective of the survey was to determine the presence and extent, or absence of, contamination **in near surface soil gases**. A sample grid on 100 foot centers **consisting of 288 sample locations** was established, as shown on Figures 1a-d, and sampled for soil gases in order to accomplish these objectives. The outermost row of samples along the eastern, western and southern boundaries of the grid over both the north and south areas of the landfill, as shown on Figures 1b and 1c, is approximately 100 feet outside the area of burial and was designed to provide evidence of migration of monitored species from the landfill. Along the southern boundary of the landfill a second row of boundary sites was established 10 feet to the south of the first boundary rows shown on Figure 1c. This second row was sampled at a depth of 6 feet (as compared to 3 feet at all other sites). Species monitored were the light hydrocarbons, (C₁-C₄); gasoline range normal paraffins (C₅-C₁₀); gasoline range aromatic hydrocarbons, (BTXE); and selected chlorinated organics. Soil samples were also taken at sites 1-261 and analyzed for labile mercury. Analyses of soil and soil gas samples were carried out in an on-site laboratory. The results of all analyses are shown on Tables 1, 2 and 3, and selected data are mapped as shown on Figures 9 - 79.

II. BACKGROUND

The 740-G Sanitary Landfill was established in 1974 and remains active at the present. The dimensions are 3,275 x 1300 ft or about 70 acres. Burial has been in excavated earthen trenches and the known disposal at this site as documented on page A-12 of Volume I: Waste Management Unit Worksheets, October, 1990; WSRC-RP90-1046 (which is attached in Appendix II), includes paper, plastic, construction and metallic debris, solvent rags, empty cans, and carcasses. At the time this soil gas survey was begun, low levels of volatile organic compounds, including trichloroethylene, tetrachloroethylene, and 1,1,1-trichloroethane had been reported in groundwater monitoring wells at the site.

III. QUALITY ASSURANCE

The quality assurance/quality control procedures of the sampling subcontractor were followed for all field and laboratory analytical work. Documentation of applicable sampling and analytical methods and associated quality assurance procedures are included in this report in Appendix I.

A. Sampling Methods

Methods and quality assurance procedures used to obtain soil gas samples are documented in Sampling Method SM1 in Appendix I. Samples were generally obtained from depths of 36" to 48". Actual sample depths for this survey are recorded in the Soil Gas Sample Collection Log in Appendix II. Samples for the light hydrocarbon analyses were taken in previously evacuated 125 ml bottles. Samples for volatile organic compound (VOC) analyses were taken in previously evacuated 22 ml bottles. A duplicate sample and a blank was collected for every ten samples. Each duplicate sample was taken from a separate location which was approximately 1 ft. from the original site. Logs which document the details of sample collection are included in Appendix II. Soil samples for mercury analyses were taken from a depth of 12 to 18 inches using the methods documented in Sample Method SM4 in Appendix I. A duplicate sample, from a separate location approximately 1 ft. away, was taken for every ten samples. Details of the collection of soil samples for mercury are contained in the Mercury Sample Collection Logs in Appendix II.

B. Analytical Methods

Methods and quality assurance procedures for the analysis of light hydrocarbon soil gas samples are documented in Analytical Method AM1 and for VOC soil gas samples in Analytical Method AM4 in Appendix I. Methods AM1 and AM4 are modifications of EPA Headspace Method 5020. Representative chromatograms of a sample and a blank from this data set are shown on Figures 2a and 2b, and Figure 3. Methods and quality assurance procedures for

the analysis of mercury in soils are documented in Analytical Method AM8 in Appendix I.

C. Accuracy

Calibration of the C₁-C₄ hydrocarbon gas chromatograph was accomplished using a certified commercial standard (Matheson Gas Products Inc.) which is of the order 10 ppm for methane and 1 ppm for the other light hydrocarbons and is called Standard "M". A second commercial standard (Scotty Specialty Gases, Can Mix 224, ICN #35) was used which contains only the C₁-C₄ straight chain hydrocarbons and is of the order 1000 ppmv for each hydrocarbon. Chromatograms of Standards "M" and "224" are shown on Figure 4.

Calibration of the gas chromatograph used to analyze volatile organics was accomplished using standards prepared as a blend of pure compounds according to the methods documented in Standard Preparation Method SP3 which is included in Appendix I. These standards were prepared in methanol (Aldrich, HPLC grade, ICN #30), at six concentration levels as shown on Table 4. Initially three standards from each of levels 1 through 6 were run to set up the calibration table. Thereafter, one standard was run for every 10 samples. A chromatogram of Standard "I", Level 3 for the FID is shown on Figure 5 and Level 4 for the ECD on Figure 6. Calibration of the gas chromatograph for vinyl chloride was achieved using a commercial standard gas (Scotty Specialty Gases, Can Mix 74, ICN # 9) @ 1000 ppmv.

D. Reliability of Selected Data

The reliability of results presented in this report for vinyl chloride and methylene chloride is seriously affected by factors beyond experimental control; namely, in the case of vinyl chloride, the presence of two frequently occurring compounds which elute 0.07 minutes before and 0.15 minutes after the vinyl chloride elution time. The earlier peak is probably n-butane and the later peak is not identified, however it may be a "freon" thought to have been in the air in the on-site laboratory. For methylene chloride, an impurity thought to be derived from the

septum, elutes 0.07 minutes before the methylene chloride elution time. Under normal laboratory conditions, we can distinguish these impurities from vinyl chloride and methylene chloride. However, during the period of these analyses, we occupied a laboratory in which temperature varied by as much as 11 degrees Fahrenheit during some 24 hour periods, causing the chromatographic retention times to vary as much as 0.7 minutes in a 24 hour period as shown for benzene in Figure 7. Under these circumstances it was not possible to reliably distinguish the desired signals from those of interfering compounds which elute very closely in time, even though retention times are adjusted to compensate for the drift due to temperature change. Thus the peak areas measured are not unequivocally attributable to vinyl chloride or methylene chloride since, if no signal due to these compounds is present, the signal due to the nearby interfering compounds may be within the retention time window and thus be selected. As a result, we have noted on Table 2 where the measured concentration at the retention time of vinyl chloride is less than 1 ppm. In cases where no value is given, the measured concentration was larger than 1 ppm, however we have not listed these values since we believe that they may result from the above mentioned interferences, not vinyl chloride. It is at these locations that future investigations would be most likely to encounter vinyl chloride if it exists in the landfill and if confirmation of its presence is necessary.

For methylene chloride, the interference is derived largely from the septum and we have estimated the magnitude of the interference from the system blanks to be approximately 1 ppm ($X_{avg} + 2\sigma = 0.7$ ppm). We have reported values for methylene chloride in Table 2 which are above 1 ppm.

E. Precision

The analytical precision was calculated using the repetitive analysis of standards as shown in Tables 5, 6, 7 and 8. In order to derive a meaningful estimate of precision for the VOC's, the calculation was made over all standards in a data directory rather than a single survey. A data directory includes data from the analyses of all samples, standards and blanks for a period of 3 to 6 weeks. The 740-G Sanitary Landfill data reside in data directories W2, W3, and

W9. Standards, which were run with the VOC samples and blanks from the Sanitary Landfill survey are designated on Tables 5, 6, and 7 as area "740-G".

For the VOC standards in general, percent standard deviations are less than 10%. At the 10 and 100 ppbv level, percent standard deviations for some chlorinated hydrocarbon standard analyses increase as background concentrations become a significant part of the overall signal, reaching about 20% for chloroform and 1,1,1-trichloroethane. Higher percent standard deviations for methylene chloride at the 1 ppmv level are due to an interfering compound from the septum as discussed above in section D.

For the light hydrocarbons, the precision is better than 5.5% for all saturate hydrocarbons for analyses of standards "M" and "224". For the unsaturates, ethylene and propylene, the precision is better than 20%.

F. Minimum Detection Levels

Minimum detection levels reported in this survey for the light hydrocarbons, C₁-C₄, are 5 ppb. In practice a 5 ppb standard (Microseeps Standard M diluted 200:1) is reliably determined with a signal to noise ratio greater than 2 (S/N>2). A chromatogram of the diluted standard is shown on Figure 8.

For the VOC standard, where peaks are well separated and the baseline is stable, signals on the order of 8 uv may be detected with a S/N >4. In a complex mixture of VOC's with many compounds, and overlapping peaks, we have determined that signals of the order 20 uv are the smallest that can be reliably and routinely determined. This corresponds to a concentration of about 70 ppbv for the gasoline range compounds; 5 ppbv for the tri- and tetrahalocarbons; and 20 ppb for trans 1,2-dichloroethylene. We have visually checked the integration of each peak for these compounds down to these concentration levels. We have not reported concentration levels for smaller signals, though in some individual cases they may be valid.

Under ideal conditions where an 8 μv signal can be reliably integrated, minimum detection levels may be lower. Experience has shown that with our system, an 8 μv signal corresponds to approximately 40 area counts. We have used our calibration factors to calculate the amount of each compound corresponding to 40 area counts as shown on Table 9. In practice, we have set the "area reject" of our system to 40 area counts, which rejects lesser areas and minimizes the integration of noise related events.

G. Blanks

System blanks are collected after normal purging of the probe sampler at each 10th sample location. Ambient air is drawn through the probe then displaced into evacuated vials. The vials are then given the same consideration as samples and analyzed as such. The purpose of the system blanks are to determine if and when sample to sample contamination occurs, and also to help establish background levels throughout the sampling/analysis process.

Results of the analyses of all Landfill blank samples are shown on Table 10. The symbol "ND" means "not detected" and suggests an area of less than 40 area counts as discussed above. For the calculation of means and standard deviations, the amounts indicated on Table 9 for 40 area counts were used when "ND" is indicated. Results of the analyses of blank samples for the 740-G, Sanitary Landfill data set are also included on Tables 1 - 3, and a representative chromatogram is shown on Figure 3. Amounts measured in the blanks have not been subtracted from the reported sample concentrations in this report.

H. Data On Magnetic Disk

All analytical data, including samples, duplicates, standards, and blanks are provided (one copy) on magnetic disk. All data are in units of ppmv or ppbv as reported on Tables 1 - 3.

All data are in Lotus 123 (Release 2, 1985) spreadsheet format using DOS (Version 5.0). VOC analytical data are accumulated and processed via Microseeps gas chromatographic data system.

IV. RESULTS

The results of the soil gas survey at the Sanitary Landfill are recorded in Tables 1 - 3, and selected data are mapped on Figures 9 - 79. In general, levels of all volatile organics monitored in this survey are above background in specific areas of the landfill. With the exception of methane, which was largely generated in the Landfill, levels and distribution of species detected reflect burial of materials which contained these species.

A. Methane

Levels of methane encountered in soil gases at the Sanitary Landfill are recorded in Table 3 as both percent methane and parts per million by volume. The distribution of methane is shown on Figures 9 - 11 in terms of percent methane. The overall distribution is best understood from the symbol map shown on Figure 9, in which the symbol size is proportional to the square root of the percentage methane.

Methane is the product of biological oxidation of cellulose and other organic substrates followed by biological reduction of the produced carbon dioxide. It is clear that methane concentrations are much more developed in the northern area of the landfill than the southern area. In the northern area, levels are consistently high to the west of the access road than they are to the east. It is not known whether this distribution is reflective of a difference in relative amounts of biologically degradable material in these different parts of the Landfill, or simply to differences in the age of burial. It has been stated that the north area was closed in 1978, however no indication was given of the order of use between the western and eastern portions of this area. Burial in the southern area is more recent. Trenches on the northern edge of the southern area were being

filled while sampling was being carried out for this survey. Levels of methane in the south area are much lower, although two sites were found to have levels of 14% and 26%. The first of these sites was associated with burial of carcasses,.

No evidence of methane migration from the Landfill was found in the boundary sites outside the area of active burial. Methane levels in the "background area" to the north were considered background. This area is currently being developed as an extension of the landfill for active burial.

B. The Saturate Hydrocarbons, C₅ - C₁₀

Concentrations of the saturate hydrocarbons, propane through decane, are shown in Tables 1 and 3 and the distribution of these species are shown on Figures 12 - 38. All of these species may be components of gasoline, although propane would certainly be a minor constituent of this fluid. Propane and the butanes have been used as propellants for certain aerosols, while pentane and the higher hydrocarbons may be a part of many petroleum mixtures or indeed used as pure solvents. Differences in distribution pattern between the light saturates and the heavy saturates may reflect burial of materials having different compositional characteristics. Any observed distribution, however, may have been altered since the time of burial since all of these species readily undergo biological oxidation in the presence of bacteria and sufficient oxygen. In general, rates of oxidation decrease with decreasing number of carbons and straight chain saturates are oxidized in preference to branched or cyclic saturates. In extreme cases, gasoline range saturates may be entirely oxidized to carbon dioxide and water. Some or all of the carbon dioxide produced may subsequently be reduced to methane.

C. The Unsaturated Hydrocarbons Ethylene and Propylene

Concentrations of ethylene and propylene are listed on Table 3, and their distributions are shown on Figures 39 - 44.

Both species may have been buried in the Landfill as a part of the materials discarded by facilities at SRS, however both gases are found naturally as a part of uncontaminated soil gases. It is generally thought that there may be some biological mechanism for their formation, however details of their generation in this manner are not well documented.

D. The Aromatic Hydrocarbons

Concentrations of the aromatic hydrocarbons monitored; benzene, toluene, ethylbenzene, and the xylenes, are shown on Table 1 and their distributions are shown on Figures 45 - 59. These compounds are components of many petroleum based oils, solvents, and fuels. The presence of these compounds in the soil gases at the landfill is evidence that such petroleum based materials have been a part of the materials buried.

The large benzene anomaly at site 69 in the north area is accompanied by the other aromatics and the entire suite of gasoline range saturates. This is suggestive, but not conclusive, evidence of gasoline. In general, the heavier aromatics (xylenes, ethylbenzene and toluene) are much more prevalent in the northern area than benzene. This may be attributable to the greater solubility of benzene in water than the heavier aromatics, but could also be explained by the presence of materials such as paints or oils with component distributions in which the heavier of these aromatics are more prominent.

In general, levels of the aromatics in the south area are lower than in the northern area although selected sites were found to have high concentrations, particularly of the heavier aromatics.

E. The Chlorinated Hydrocarbons

Concentrations of the chlorinated hydrocarbons monitored are shown on Table 2, and their distribution is shown on Figures 50-77. In general, methylene chloride, chloroform and trans 1,2 dichloroethylene are minor constituents of the soil air at the Landfill relative to 1,1,1-trichloroethane, trichloroethylene, and

tetrachloroethylene. No carbon tetrachloride was observed above its minimum detection level of 5 ppbv. Tetrachloroethylene was found at 140 ppm at site 34 in the northern area and was present at lower levels at many sites in both the northern and southern areas. A larger amount of 1,1,1-trichloroethane was found in the southern area than the northern area. Trichloroethylene was found in many sites in both the northern and southern areas.

F. Mercury

Mercury levels measured in soils at a depth of 1 foot are in general very low. The highest levels recorded were 33 and 31 ng/g. While these levels are above the general background observed at the Landfill, they may represent extrema in the normal distribution rather than evidence of buried mercury. Note that one site in the "background area" was observed to have 13 ng/g.

V. CONCLUSIONS

The data presented in this report confirm that a variety of common petroleum based fluids and chlorinated solvents have been a part of the materials buried at the 740-G Sanitary Landfill. Levels of the species monitored greatly exceed background concentrations.

In an independent study of the effects of barometric pumping on soil gases at this site (WSRC-MS-92-877), it was shown that during periods of falling barometric pressure, all species found in the soil gas survey discussed in this report migrate through the soil cover into the atmosphere.

Methane levels, although high, are to be expected for a landfill where large amounts of cellulose and organics have been buried. It is known that even large organic species have a significant solubility in methane under high pressure. It may be that methane in high concentrations, even at atmospheric pressure, is a factor in the migration of the larger organic species.

This page intentionally left blank.

Figures and Tables

This page intentionally left blank.

Figure 1a. The 740-G Sanitary Landfill Site Index Map
(all locations @ 1" = 400 ft)

740-G LANDFILL (NORTH AREA) SAMPLE LOCATION MAP

SCALE 1 inch = 250 Feet

Figure 1b. The 740-G Sanitary Landfill North Area Sample Location Map (sample locations @ 1" = 250 ft)

740-G LANDFILL (SOUTH AREA) SAMPLE LOCATION MAP

SCALE 1 inch = 250 Feet

Figure 1c. The 740-G Sanitary Landfill South Area Sample Location Map (sample locations @ 1" = 250 ft)

Figure 1d. The 740-G Sanitary Landfill Background Area Sample Location Map (sample locations @ 1" = 200 ft)

File=C:\CP\DATA4\W2A1.65R Date printed = 11-22-1991 Time = 16:43:30
 3.00 to 30.00 min. Low Y = -12.52761 mv High Y = 3300.10083 mv Span = 3312.62842 mv

File=C:\CP\DATA4\W2A1.65R Date printed = 11-22-1991 Time = 16:45:06
 4.00 to 30.00 min. Low Y = -0.32111 mv High Y = 14.08442 mv Span = 14.40552 mv

Figure 2a. Gas Chromatogram of Soil Gases at Site 111 from the Flame Ionization Detector(FID)

File=C:\CP\DATA4\W2B1.65R Date printed = 11-22-1991 Time = 16:48:46

2.00 to 30.00 min. Low Y = -1.50212 mv High Y = 490.56058 mv Span = 492.06271 mv

File=C:\CP\DATA4\W2B1.65R Date printed = 11-22-1991 Time = 16:51:39

5.08 to 11.24 min. Low Y = -0.97455 mv High Y = 6.26096 mv Span = 7.23551 mv

Figure 2b. Gas Chromatogram of Soil Gases at Site 111 from the Electron Capture Detector(ECD)

File=C:\CP\DATA4\W2A.85R Date printed = 11-22-1991 Time = 16:57:41

3.00 to 30.00 min. Low Y = -0.27952 mv High Y = 0.42976 mv Span = 0.70927 mv

File=C:\CP\DATA4\W2B.85R Date printed = 11-22-1991 Time = 16:59:04

2.00 to 30.00 min. Low Y = 0.33500 mv High Y = 11.73912 mv Span = 11.40412 mv

Figure 3. Gas Chromatogram of System Blank # 7

RUN # 444 NOV/13/90 08:59:17
 WORKFILE ID: B
 WORKFILE NAME:

ESTD	RT	AREA	TYPE	CAL #	AMOUNT
	0.19	2497300	SHB	1	10.389
	0.40	494130	TPV	2	1.034
	0.55	604670	TVV	3	1.038
	1.09	647220	TVV	4R	1.040
	1.99	496450	TVV	5	1.040
	3.22	677280	PV	6	1.023
	3.75	527890	VV	7	0.997

RUN # 443 NOV/13/90 08:47:18
 WORKFILE ID: B
 WORKFILE NAME:

ESTD	RT	AREA	TYPE	CAL #	AMOUNT
	0.19	2961700	SPH	1	1040.600
	0.40	5319700	SHB	2	1050.300
	0.55	9198	TBB	3	1.579
	1.09	7429900	BB	4	1020.700
	3.18	752	PB	6	0.114
	3.71	7540500	PB	7	1030.900

Figure 4. Gas Chromatogram of C₁-C₄ Standards "M" and "224"

File=C:\CP\DATA4\W2A3.10R Date printed = 11-22-1991 Time = 16:26:49

4.09 to 29.92 min. Low Y = -0.25062 mv High Y = 6.39529 mv Span = 6.64590 mv

Figure 5. Gas Chromatogram (FID) of VOC Standard "I", Level 3

File=C:\CP\DATA4\W2B2.98R Date printed = 11-22-1991 Time = 16:35:05

2.00 to 30.00 min. Low Y = -0.05700 mv High Y = 84.30374 mv Span = 84.36074 mv

Figure 6. Gas Chromatogram (ECD) of VOC Standard "I", Level 4

Figure 7. Benzene Retention Time vs Room Temperature

File=A:\11C\17R from 0.01 to 4.00 min. Low scale = 0.1120 mv. High scale = 0.1473 mv.

File=A:\11C\17R from 0.02 to 1.05 min. Low scale = 0.1137 mv. High scale = 0.1273 mv.

Figure 8. Gas Chromatogram of C_1 - C_4 Hydrocarbon Standard M @ 200:1 Dilution in N_2

740-G LAND FILL PERCENT METHANE

Figure 9. Methane Symbol Map

740-G LANDFILL (NORTH AREA) PERCENT METHANE

Figure 10. Methane (percent) Map, North Area

740-G LANDFILL (SOUTH AREA) PERCENT METHANE

Figure 11. Methane (percent) Map, South Area

740-G LAND FILL PROPANE CONCENTRATION

Figure 12. Propane Symbol Map

740-G LANDFILL (NORTH AREA) PROPANE CONCENTRATION - (ppmv)

Figure 13. Propane (ppmv) Map, North Area

Figure 14. Propane (ppmv) Map, South Area

Figure 15. n-Butane Symbol Map

740-G LANDFILL (NORTH AREA)

N-BUTANE CONCENTRATION - (ppmv)

Figure 16. n-Butane (ppmv) Map, North Area

Figure 17. n-Butane (ppmv) Map, South Area

740-G LAND FILL
I-BUTANE CONCENTRATION

Figure 18. i-Butane Symbol Map

740-G LANDFILL (NORTH AREA)

I-BUTANE CONCENTRATION - (ppmv)

SCALE 1 inch = 250 Feet

Figure 19. i-Butane (ppmv) Map, North Area

740-G LANDFILL (SOUTH AREA) I-BUTANE CONCENTRATION - (ppmv)

Figure 20. i-Butane (ppmv) Map, South Area

740-G LAND FILL PENTANE CONCENTRATION

SCALE 1 inch = 400 Feet

Figure 21. Pentane Symbol Map

740-G LANDFILL (NORTH AREA) PENTANE CONCENTRATION - (ppmv)

Figure 22. Pentane (ppmv) Map, North Area

Figure 23. Pentane (ppmv) Map, South Area

740-G LAND FILL HEXANE CONCENTRATION

Figure 24. Hexane Symbol Map

740-G LANDFILL (NORTH AREA) HEXANE CONCENTRATION - (ppmv)

Figure 25. Hexane (ppmv) Map, North Area

740-G LAND FILL HEPTANE CONCENTRATION

Figure 27. Heptane Symbol Map

Figure 28. Heptane (ppmv) Map, North Area

Figure 29. Heptane (ppmv) Map, South Area

740-G LAND FILL OCTANE CONCENTRATION

Figure 30. Octane Symbol Map

Figure 31. Octane (ppmv) Map, North Area

Figure 32. Octane (ppmv) Map, South Area

740-G LAND FILL NONANE CONCENTRATION

Figure 33. Nonane Symbol Map

Figure 34. Nonane (ppmv) Map, North Area

Figure 35. Nonane (ppmv) Map, South Area

740-G LAND FILL DECANE CONCENTRATION

Figure 36. Decane Symbol Map

740-G LANDFILL (NORTH AREA) DECANE CONCENTRATION - (ppmv)

Figure 37. Decane (ppmv) Map, North Area

Figure 38. Decane (ppmv) Map, South Area

740-G LAND FILL ETHYLENE CONCENTRATION

SCALE 1 inch = 400 Feet

Figure 39. Ethylene Symbol Map

740-G LANDFILL (NORTH AREA) ETHYLENE CONCENTRATION - (ppmv)

Figure 40. Ethylene (ppmv) Map, North Area

Figure 41. Ethylene (ppmv) Map, South Area

740-G LAND FILL PROPYLENE CONCENTRATION

Figure 42. Propylene Symbol Map

740-G LANDFILL (NORTH AREA)

PROPYLENE CONCENTRATION - (ppmv)

Figure 43. Propylene (ppmv) Map, North Area

Figure 44. Propylene (ppmv) Map, South Area

740-G LAND FILL BENZENE CONCENTRATION

SCALE 1 inch = 400 Feet

Figure 45. Benzene Symbol Map

Figure 46. Benzene (ppmv) Map, North Area

Figure 47. Benzene (ppmv) Map, South Area

740-G LAND FILL TOLUENE CONCENTRATION

SCALE 1 inch = 400 Feet

Figure 48. Toluene Symbol Map

Figure 49. Toluene (ppmv) Map, North Area

Figure 50. Toluene (ppmv) Map, South Area

740-G LAND FILL EYHYL BENZENE CONCENTRATION

Figure 51. Ethylbenzene Symbol Map

Figure 52. Ethylbenzene (ppmv) Map, North Area

Figure 53. Ethylbenzene (ppmv) Map, South Area

740-G LANDFILL (NORTH AREA) M & P - XYLENE CONCENTRATION - (ppmv)

Figure 55. m- & p-Xylene (ppmv) Map, North Area

Figure 56. m- & p-Xylene (ppmv) Map, South Area

Figure 57. o-Xylene Symbol Map

Figure 58. o-Xylene (ppmv) Map, North Area

Figure 59. o-Xylene (ppmv) Map, South Area

740-G LAND FILL METHYLENE CHLORIDE CONCENTRATION

Figure 60. Methylene Chloride Symbol Map

Figure 61. Methylene Chloride (ppmv) Map, North Area

Figure 62. Methylene Chloride (ppmv) Map, South Area

740-G LAND FILL CHLOROFORM CONCENTRATION

Figure 63. Chloroform Symbol Map

Figure 64. Chloroform (ppmv) Map, North Area

Figure 65. Chloroform (ppmv) Map, South Area

Figure 67. trans 1,2-Dichloroethylene (ppmv) Map, North Area

Figure 68. trans 1,2-Dichloroethylene (ppmv) Map, South Area

Figure 69. 1,1,1-Trichloroethane Symbol Map

Figure 70. 1,1,1-Trichloroethane (ppmv) Map, North Area

Figure 71. 1,1,1-Trichloroethane (ppmv) Map, South Area

740-G LAND FILL TRICHLOROETHYLENE CONCENTRATION

Figure 72. Trichloroethylene Symbol Map

Figure 73. Trichloroethylene (ppmv) Map, North Area

Figure 74. Trichloroethylene (ppmv) Map, South Area

740-G LAND FILL TETRACHLOROETHYLENE CONCENTRATION

Figure 75. Tetrachloroethylene Symbol Map

Figure 76. Tetrachloroethylene (ppmv) Map, North Area

Figure 77. Tetrachloroethylene (ppmv) Map, South Area

740-G LAND FILL MERCURY CONCENTRATION

Figure 78. Mercury Symbol Map

740-G LAND FILL MERCURY CONCENTRATION (ng/g)

Figure 79. Mercury (ng/g) Map

This page intentionally left blank.

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
740-G 1	5.29	0.16	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 2	0.55	0.47	0.36	<.07	0.84	0.52	1.13	0.34	0.96	0.40	0.48
740-G 3	0.37	0.30	0.22	0.82	0.29	0.31	1.05	0.17	0.90	0.48	0.64
740-G 4	<.07	0.31	0.13	<.07	0.52	0.26	1.07	0.67	1.07	0.33	0.82
740-G 5	0.20	0.73	0.31	<.07	0.13	0.12	0.57	0.19	0.51	0.16	0.13
740-G 6	0.18	0.22	0.13	<.07	<.07	0.10	<.07	<.07	<.07	<.07	<.07
740-G 7	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 8	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 9	1.17	1.85	1.52	0.14	1.65	0.67	2.61	0.20	1.14	0.52	0.47
740-G 10	0.47	1.26	1.53	0.30	4.42	1.72	9.72	0.67	3.10	1.51	2.93
740-G 10A	0.40	1.06	1.42	0.28	4.19	1.72	10.69	1.01	3.34	2.00	3.46
740-G 11	1.77	4.59	4.34	0.47	6.43	0.48	9.10	0.34	2.89	2.88	3.50
740-G 12	1.64	4.18	4.10	0.29	2.83	0.89	3.39	0.27	3.34	0.66	1.39
740-G 13	1.81	3.42	3.75	0.38	5.48	2.21	2.49	0.18	1.17	0.52	0.41
740-G 14	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 15	2.96	3.90	4.13	0.34	6.56	1.97	5.04	0.67	3.42	0.73	1.67
740-G 16	0.69	2.32	3.61	0.38	4.29	22.45	4.89	4.89	12.54	4.00	2.21
740-G 17	0.29	1.15	1.73	0.17	1.59	3.52	3.74	4.24	9.04	2.94	1.93
740-G 18	0.99	1.88	1.83	0.36	1.35	4.05	2.09	1.86	3.60	1.09	0.70
740-G 19	<.07	0.37	0.72	0.29	1.45	7.38	5.24	2.15	4.28	1.34	3.97
740-G 20	<.07	<.07	<.07	<.07	<.07	0.08	0.11	0.08	0.15	<.07	0.08
740-G 20A	<.07	0.09	<.07	<.07	<.07	0.16	0.09	0.22	0.28	<.07	<.07
740-G 21	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 22	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.15	<.07
740-G 23	2.94	6.36	5.00	0.74	6.78	16.54	6.68	11.12	26.61	6.12	2.28
740-G 24	0.38	2.17	1.46	0.24	2.77	2.23	4.43	1.90	5.12	1.75	5.97
740-G 25	0.97	1.97	1.37	0.56	1.31	15.69	0.64	1.40	1.37	0.40	0.52
740-G 26	0.16	<.07	<.07	<.07	<.07	0.10	0.11	<.07	0.25	0.08	0.16
740-G 27	0.74	0.98	0.71	0.11	0.78	0.46	0.90	0.13	0.53	0.28	0.26
740-G 28	2.25	2.83	4.95	0.22	3.89	0.69	2.11	0.12	0.98	0.29	0.51
740-G 29	0.81	0.87	1.11	0.40	1.01	8.57	0.97	1.73	3.51	1.28	0.61
740-G 30	10.02	11.17	2.68	0.21	1.54	0.63	1.04	0.16	0.80	0.21	0.26
740-G 30A	21.76	25.18	6.10	0.54	3.68	4.97	2.71	1.08	2.58	0.65	0.47
740-G 31	0.68	0.18	0.09	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 32	2.07	2.18	1.33	0.23	1.30	0.58	1.87	0.19	1.43	0.55	0.42
740-G 33	0.36	0.07	<.07	<.07	<.07	0.07	<.07	<.07	<.07	<.07	<.07
740-G 34	4.18	0.21	0.29	0.16	0.85	11.32	2.55	1.94	4.45	1.58	1.09
740-G 35	0.08	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
740-G 36	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 37	0.44	0.38	0.18	<.07	0.23	<.07	1.29	0.47	2.62	0.68	0.33
740-G 38	0.08	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 39	1.19	2.50	0.48	<.07	0.52	1.68	0.20	0.83	1.48	0.50	<.07
740-G 40	<.07	0.48	<.07	<.07	0.09	<.07	<.07	<.07	0.08	<.07	<.07
740-G 40A	<.07	0.69	<.07	<.07	0.08	<.07	<.07	<.07	0.14	<.07	<.07
740-G 41	18.21	15.47	3.47	0.16	2.24	1.07	1.04	0.79	1.24	0.29	0.14
740-G 42	2.03	1.79	0.95	<.07	0.68	0.44	0.93	0.45	1.14	0.23	0.26
740-G 43	5.60	3.18	1.59	0.44	1.52	1.90	1.83	0.93	3.87	1.85	0.55
740-G 44	0.37	0.33	0.33	<.07	0.12	0.11	0.22	0.14	0.53	<.07	0.25
740-G 45	0.89	31.08	1.34	0.26	<.07	0.43	<.07	0.67	1.43	0.38	0.11
740-G 46	0.37	0.92	0.13	0.12	0.17	3.02	0.90	0.99	0.62	0.31	0.31
740-G 47	2.61	6.07	14.45	0.66	12.75	6.59	5.28	11.53	3.50	0.89	0.23
740-G 48	1.58	0.78	0.51	0.21	0.14	0.56	0.37	1.20	0.32	0.13	0.12

Table 1. Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
 ----- 740-G LANDFILL AREA -----
 ----- SOIL GAS CONCENTRATIONS (PPMV) -----

	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
	<.07	<.07	<.07	<.07	0.08	<.07	<.07	<.07	<.07	<.07	<.07
	5.23	8.07	0.62	0.47	1.28	2.86	4.27	5.77	16.76	6.80	1.48
	14.63	6.02	1.90	0.14	0.69	2.48	0.78	1.50	3.70	0.45	0.30
	17.06	7.38	3.15	0.16	0.45	1.80	0.20	1.51	1.98	0.47	0.20
	51.66	9.55	1.87	1.16	1.08	5.18	0.65	1.36	0.99	0.32	0.10
	17.10	5.24	0.64	0.27	0.34	1.26	0.32	0.47	0.49	0.08	0.10
	0.91	0.15	<.07	<.07	0.21	0.23	<.07	<.07	0.08	<.07	<.07
	107.43	16.38	3.57	0.34	2.33	1.11	2.64	0.44	1.42	0.53	0.39
	0.58	0.13	<.07	0.08	<.07	<.07	0.08	<.07	0.10	<.07	0.09
	0.19	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
	121.33	11.31	4.66	0.96	0.63	3.63	0.24	1.14	0.38	0.10	<.07
	105.56	9.87	4.06	0.85	0.63	3.87	0.29	1.05	0.42	0.16	<.07
	59.98	9.98	3.51	1.75	2.21	22.77	0.53	4.77	20.23	0.22	0.33
	95.86	14.10	7.02	1.38	7.55	8.67	4.13	1.68	3.44	0.94	0.26
	<.07	<.07	<.07	<.07	0.11	<.07	<.07	<.07	0.12	<.07	<.07
	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
	206.32	24.54	4.12	0.62	8.18	196.87	10.78	5.62	13.26	4.57	0.71
	46.44	28.16	3.34	2.30	4.06	120.88	13.63	7.30	20.57	5.69	2.39
	202.07	19.44	4.99	0.77	6.50	26.06	11.31	13.41	30.24	7.54	5.00
	355.61	96.98	63.50	8.63	23.40	77.46	15.53	7.18	16.64	6.17	3.57
	774.58	993.19	366.51	154.94	112.69	400.04	23.87	33.90	93.12	26.04	0.98
	69.94	15.38	9.96	1.66	20.65	9.80	12.30	2.89	6.97	2.44	2.05
	56.72	6.76	3.55	0.53	9.26	3.66	5.69	0.90	2.49	0.91	0.55
	0.37	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.12	<.07	<.07
	4.64	4.15	1.71	0.53	0.48	0.25	0.29	0.21	0.44	0.10	<.07
	18.98	7.40	0.79	0.15	0.44	0.37	0.34	0.08	0.35	0.13	<.07
	31.91	6.30	1.55	0.17	2.31	0.96	1.10	0.16	0.53	0.23	0.17
	32.43	20.88	0.89	0.10	0.91	0.97	0.24	3.95	0.24	0.08	0.36
	40.14	122.86	1.27	0.11	0.47	0.32	0.30	0.08	0.16	0.16	0.15
	0.09	0.09	<.07	<.07	<.07	<.07	<.07	<.07	0.12	<.07	<.07
	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
	131.58	20.74	1.10	0.42	0.31	9.71	0.15	2.89	6.90	1.39	<.07
	25.88	12.37	1.11	0.19	0.99	2.64	2.58	0.84	1.86	0.90	0.44
	19.47	6.78	0.84	0.17	0.47	0.66	2.73	0.48	1.26	0.77	0.33
	141.11	42.02	2.27	0.73	0.95	3.31	0.63	0.81	1.64	0.38	0.15
	38.41	6.32	1.47	0.14	1.32	1.00	1.95	0.40	1.49	0.69	0.48
	24.78	5.94	1.64	26.75	3.31	1.28	1.93	0.30	1.12	0.36	0.35
	0.39	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
	1.24	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
	50.39	10.21	3.07	0.22	2.05	3.04	0.73	5.99	18.67	5.35	<.07
	0.92	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
	9.92	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
	4.40	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.10	<.07	<.07
	119.15	100.44	1.84	27.14	4.80	69.23	1.81	6.14	17.56	3.71	0.12
	154.98	124.70	2.51	21.02	7.31	68.42	3.01	8.01	23.42	5.37	0.19
	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07	0.15	<.07	<.07
	<.07	<.07	<.07	<.07	0.10	<.07	<.07	<.07	<.07	<.07	<.07
	14.18	13.98	0.90	0.08	0.32	0.22	0.44	0.17	0.51	0.15	<.07
	2.70	<.07	<.07	<.07	<.07	0.08	<.07	<.07	0.07	<.07	<.07
	1.82	0.08	<.07	<.07	<.07	0.39	<.07	0.10	0.25	<.07	<.07

1. Hydrocarbon Soil Gas Concentrations and System Blanks
 at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
740-G 96	0.79	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
740-G 97	123.45	3.70	1.51	3.08	0.44	8.56	1.10	3.77	3.04	1.00	0.70
740-G 98	3.54	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
740-G 99	1.80	0.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 100	10.81	1.21	0.38	0.10	0.14	1.35	<.07	0.15	0.36	0.09	<.07
740-G 100A	26.13	3.42	0.92	0.24	0.64	2.53	0.12	0.41	1.05	0.36	<.07
740-G 101	0.09	<.07	<.07	<.07	<.07	0.21	<.07	<.07	<.07	<.07	<.07
740-G 102	0.09	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G 103	0.28	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
740-G 104	1.70	2.84	0.30	<.07	0.12	0.08	<.07	<.07	<.07	<.07	<.07
740-G 105	<.07	<.07	<.07	<.07	0.09	<.07	<.07	<.07	<.07	<.07	<.07
740-G 106	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 107	12.81	2.49	0.21	<.07	0.23	0.17	0.22	<.07	0.16	0.08	<.07
740-G 108	0.27	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G 109	4.21	1.03	0.57	<.07	0.26	0.22	0.12	<.07	0.10	<.07	<.07
740-G 110	1.25	0.31	0.13	0.12	0.52	2.25	0.11	1.03	0.28	0.07	<.07
740-G 110A	0.72	0.13	0.11	0.11	0.22	7.06	0.22	0.19	0.22	0.11	<.07
740-G 111	46.00	38.74	3.94	1.04	2.58	67.99	5.04	15.69	47.17	14.91	0.67
740-G 112	1.04	<.07	<.07	<.07	<.07	0.27	<.07	0.13	0.48	0.16	0.07
740-G 113	23.63	5.54	0.87	0.08	1.13	0.79	0.95	0.34	1.42	0.42	0.23
740-G 114	0.31	<.07	<.07	<.07	<.07	0.35	<.07	<.07	0.08	<.07	<.07
740-G 115	188.06	37.25	2.54	0.61	0.95	6.08	0.27	0.75	1.58	0.34	<.07
740-G 116	0.56	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
740-G 117	115.26	16.64	4.59	2.14	1.94	6.88	1.22	5.20	9.30	1.13	0.12
740-G 118	22.79	4.21	1.34	0.08	1.84	1.43	1.65	0.20	0.85	0.58	0.37
740-G 119	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 120	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 121	2.20	0.65	0.49	0.13	0.39	0.67	0.57	0.20	0.40	0.20	0.10
740-G 122	1.87	3.09	0.39	0.14	0.27	1.90	0.14	0.41	0.46	0.14	<.07
740-G 123	6.87	0.30	0.09	<.07	<.07	0.08	<.07	<.07	<.07	<.07	<.07
740-G 124	164.65	22.58	3.69	0.13	1.54	0.48	2.59	0.27	0.70	0.43	0.16
740-G 125	175.14	42.56	5.78	0.27	6.74	2.07	2.64	0.68	1.25	0.73	0.33
740-G 126	32.04	14.29	2.47	0.28	2.64	0.85	2.17	0.22	0.91	0.52	0.25
740-G 127	12.92	4.97	1.18	0.22	1.71	6.91	0.95	0.82	1.50	0.52	<.07
740-G 128	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 129	49.61	38.71	2.82	0.08	8.43	2.58	1.44	0.13	0.30	0.19	<.07
740-G 129A	60.17	59.28	3.30	0.10	11.22	4.43	2.15	0.50	0.62	0.31	<.07
740-G 130	12.77	11.86	5.00	1.15	6.53	48.99	6.40	6.02	12.60	2.99	1.34
740-G 131	56.90	17.06	5.08	1.25	4.51	19.47	8.85	4.90	10.07	3.58	1.22
740-G 131A	25.69	7.53	2.42	0.86	2.16	12.15	3.99	2.71	5.25	2.01	0.85
740-G 132	0.27	<.07	<.07	0.14	<.07	<.07	<.07	<.07	0.12	<.07	0.08
740-G 133	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.14	<.07	<.07
740-G 134	<.07	<.07	<.07	0.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
740-G 135	6.63	0.10	<.07	0.08	0.08	0.18	0.19	<.07	0.12	0.12	0.09
740-G 136	58.87	14.76	7.36	0.60	4.06	1.43	1.39	3.07	1.55	1.25	0.09
740-G 137	6.66	0.10	<.07	0.10	0.08	<.07	<.07	0.08	0.12	<.07	<.07
740-G 138	4.82	0.18	0.10	0.20	0.11	0.14	<.07	0.14	0.18	0.23	<.07
740-G 139	8.16	1.41	0.48	0.19	0.38	0.18	0.25	<.07	0.15	0.08	<.07
740-G 140	72.99	32.44	5.46	0.61	3.01	1.54	1.25	0.37	0.76	0.30	0.10
740-G 140A	64.21	28.52	4.77	0.54	2.61	2.01	1.15	0.52	0.97	0.34	0.12
740-G 141	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
740-G 142	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07

Table 1. Hydrocarbon Soil Gas Concentrations and System Blanks
at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
740-G 143	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 144	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 145	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 146	<.07	<.07	<.07	<.07	0.09	<.07	<.07	<.07	0.07	<.07	<.07
740-G 147	<.07	<.07	<.07	<.07	0.09	<.07	<.07	<.07	0.07	<.07	<.07
740-G 148	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
740-G 149	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 150	<.07	<.07	<.07	<.07	0.13	<.07	<.07	<.07	<.07	<.07	<.07
740-G 151	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 152	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 153	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 154	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 155	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 155A	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 156	0.21	<.07	<.07	<.07	0.11	<.07	<.07	<.07	0.12	<.07	<.07
740-G 157	1.97	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G 158	2.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 159	0.87	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 160	1.08	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 160A	1.80	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 161	1.17	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 162	2.15	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 163	6.00	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 164	2.14	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 165	1.32	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 166	1.06	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 167	0.19	<.07	<.07	<.07	0.08	<.07	<.07	<.07	<.07	<.07	<.07
740-G 168	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 169	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 170	0.25	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 170A	0.24	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 171	172.22	84.29	4.16	0.23	1.57	2.08	0.70	0.27	1.76	0.44	0.09
740-G 172	107.88	57.17	5.32	0.26	2.11	1.85	0.79	0.70	2.30	0.56	<.07
740-G 173	6.94	0.16	<.07	<.07	<.07	<.07	<.07	<.07	0.13	<.07	<.07
740-G 174	4.01	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
740-G 175	16.52	1.25	0.80	0.25	0.43	0.88	0.39	0.13	0.30	0.09	<.07
740-G 176	3.84	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	0.12
740-G 177	9.98	1.09	0.13	0.10	<.07	0.12	<.07	0.07	0.58	0.13	<.07
740-G 178	0.76	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07	<.07	<.07
740-G 179	9.68	2.12	0.07	<.07	<.07	0.21	<.07	<.07	0.10	<.07	0.09
740-G 180	7.09	0.35	0.10	0.16	<.07	0.10	<.07	<.07	<.07	<.07	0.11
740-G 180A	1.17	0.07	<.07	<.07	<.07	0.14	<.07	<.07	<.07	<.07	<.07
740-G 181	8.64	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 182	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 183	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 184	20.11	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 185	154.92	9.45	2.43	0.47	0.64	2.13	0.25	5.08	17.27	4.04	<.07
740-G 186	201.48	26.02	<.07	<.07	1.21	0.34	0.45	0.77	0.75	0.29	<.07
740-G 187	60.95	9.77	1.20	0.16	0.79	0.98	1.21	0.43	1.67	0.50	0.10
740-G 188	2.32	<.07	<.07	0.07	<.07	<.07	<.07	<.07	0.09	<.07	0.07
740-G 189	3.51	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G 190	2.31	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07

Table 1. Hydrocarbon Soil Gas Concentrations and System Blanks
at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
740-G 190A	2.26	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 191	89.40	4.93	<.07	0.18	0.60	1.15	0.99	2.74	7.83	2.63	0.11
740-G 192	2.43	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.24	0.07	<.07
740-G 193	0.14	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	0.12
740-G 194	0.52	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 195	1.53	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	0.10
740-G 196	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.10
740-G 197	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.10	<.07	<.07
740-G 198	0.17	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.11
740-G 199	153.82	11.83	3.45	<.07	0.55	0.37	0.25	<.07	<.07	<.07	<.07
740-G 200	84.88	16.28	1.21	<.07	0.54	0.28	0.49	0.14	0.35	<.07	0.15
740-G 200A	68.18	15.63	1.09	0.07	0.74	0.48	0.63	0.27	0.62	0.14	0.11
740-G 201	149.48	13.39	3.79	0.11	1.49	1.04	1.25	1.05	2.31	0.48	<.07
740-G 202	14.85	3.35	0.47	0.29	0.13	0.12	0.24	0.12	0.13	<.07	<.07
740-G 203	0.55	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 204	3.25	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 205	77.68	8.09	1.49	<.07	1.60	1.38	0.71	0.77	2.49	0.51	<.07
740-G 206	112.80	13.26	11.14	0.14	5.76	2.01	1.27	0.14	0.54	0.18	<.07
740-G 207	1.37	0.11	0.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.10
740-G 208	471.50	2.25	2.07	0.23	0.66	43.15	0.67	60.66	169.08	34.86	<.07
740-G 209	9.60	0.15	0.20	<.07	0.30	0.15	<.07	0.30	1.10	0.31	0.08
740-G 210	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07
740-G 210A	<.07	<.07	<.07	<.07	0.21	<.07	<.07	<.07	<.07	<.07	<.07
740-G 211	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 212	1.70	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 213	4.05	0.14	<.07	<.07	<.07	0.07	<.07	<.07	<.07	<.07	<.07
740-G 214	134.67	1.24	0.65	0.25	0.33	1.08	0.18	0.75	2.95	0.52	0.07
740-G 215	5.82	0.22	<.07	<.07	<.07	<.07	0.08	<.07	0.11	<.07	0.10
740-G 216	1.01	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 217	0.27	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 218	0.15	<.07	<.07	<.07	<.07	0.15	<.07	<.07	<.07	<.07	<.07
740-G 219	0.87	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 220	44.59	0.83	0.76	0.38	0.50	99.15	0.45	6.41	13.26	2.66	0.08
740-G 220A	26.34	0.66	0.43	0.12	0.28	5.05	0.18	6.38	14.06	2.61	<.07
740-G 221	97.53	0.11	<.07	<.07	0.07	0.15	<.07	0.17	0.48	0.11	<.07
740-G 222	0.87	0.07	<.07	<.07	<.07	<.07	<.07	<.07	0.19	<.07	<.07
740-G 223	<.07	<.07	<.07	<.07	0.09	<.07	<.07	<.07	0.07	<.07	0.08
740-G 224	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G 225	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.07
740-G 226	0.09	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
740-G 227	2.38	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	0.11
740-G 228	0.76	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	0.10
740-G 229	0.50	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.11	<.07	0.08
740-G 230	0.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07	<.07	<.07	0.09
740-G 230A	0.09	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08
740-G 231	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	0.07
740-G 232	0.66	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09
740-G 233	1.15	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 234	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 235	0.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 236	0.42	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 237	1.00	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	0.09

Table 1. Hydrocarbon Soil Gas Concentrations and System Blanks
at the 740-G Sanitary Landfill

(

(

;

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
740-G 285	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 286	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 287	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G 288	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 1	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 2	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 3	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 4	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 5	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 6	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 7	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G BLK 8	<.07	0.08	<.07	<.07	0.09	0.08	<.07	<.07	0.12	<.07	0.08
740-G BLK 9	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.09	<.07	<.07
740-G BLK 10	0.10	<.07	<.07	<.07	<.07	0.07	<.07	<.07	0.13	<.07	<.07
740-G BLK 11	0.10	0.19	<.07	<.07	<.07	0.31	<.07	0.09	0.30	<.07	<.07
740-G BLK 12	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G BLK 13	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G BLK 14	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07	0.13	<.07	<.07
740-G BLK 15	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.08	<.07	<.07
740-G BLK 16	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 17	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 18	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 19	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 20	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 21	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 22	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 23	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 24	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 25	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	0.17	0.10	0.08
740-G BLK 26	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 27	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 28	<.07	<.07	<.07	<.07	<.07	0.10	<.07	<.07	<.07	<.07	<.07
740-G BLK 29	<.07	<.07	<.07	<.07	0.23	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 30	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 31	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 32	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 33	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07
740-G BLK 34	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07	<.07

Table 1. Hydrocarbon Soil Gas Concentrations and System Blanks
at the 740-G Sanitary Landfill

This page intentionally left blank.

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #		VINYL	METHYLENE	TRANS 1,2	CHLORO	111 TRI	CARBON	TETRA	TETRA
		CHLORIDE	CHLORIDE	DICHLORO	FORM	ETHANE	TETRA	TRICLORO	CHLORO
				ETHYLENE			CHLORIDE	ETHYLENE	ETHYLENE
740-G	1	<1.0	<1.0	<.02	<.005	0.017	<.005	0.007	0.089
740-G	2	<1.0	<1.0	<.02	<.005	<.005	<.005	0.012	0.009
740-G	3	<1.0	<1.0	<.02	<.005	<.005	<.005	0.020	0.032
740-G	4	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G	5	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.005
740-G	6	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	0.018
740-G	7	<1.0	<1.0	<.02	<.005	0.011	<.005	<.005	0.000
740-G	8	<1.0	<1.0	<.02	<.005	0.008	<.005	<.005	0.014
740-G	9	<1.0	<1.0	0.10	<.005	<.005	<.005	0.181	0.227
740-G	10	<1.0	<1.0	0.13	<.005	0.005	<.005	0.057	0.070
740-G	10A	<1.0	<1.0	0.12	<.005	0.006	<.005	0.053	0.071
740-G	11	<1.0	<1.0	0.26	<.005	<.005	<.005	0.101	0.184
740-G	12	<1.0	<1.0	0.17	<.005	0.005	<.005	0.061	0.067
740-G	13	<1.0	<1.0	0.17	<.005	0.005	<.005	0.096	0.150
740-G	14	<1.0	<1.0	<.02	<.005	0.022	<.005	<.005	0.157
740-G	15	<1.0	<1.0	0.14	<.005	0.017	<.005	0.163	0.153
740-G	16	<1.0	2.1	0.11	<.005	0.006	<.005	0.107	0.175
740-G	17	<1.0	<1.0	0.03	<.005	0.007	<.005	0.023	0.022
740-G	18	<1.0	<1.0	0.15	<.005	0.005	<.005	0.035	0.032
740-G	19	<1.0	<1.0	0.07	<.005	0.006	<.005	0.296	5.894
740-G	20	<1.0	<1.0	<.02	<.005	0.007	<.005	0.011	0.016
740-G	20A	<1.0	<1.0	<.02	<.005	0.008	<.005	0.013	0.010
740-G	21	<1.0	<1.0	<.02	<.005	0.007	<.005	<.005	0.049
740-G	22	<1.0	<1.0	<.02	<.005	0.006	<.005	<.005	0.041
740-G	23	<1.0	2.6	0.18	<.005	0.048	<.005	1.334	3.225
740-G	24	<1.0	1.4	0.10	<.005	0.013	<.005	0.122	0.090
740-G	25	<1.0	4.7	0.12	<.005	0.009	<.005	5.985	3.924
740-G	26	<1.0	<1.0	<.02	<.005	<.005	<.005	0.027	0.070
740-G	27	<1.0	<1.0	0.04	<.005	<.005	<.005	0.022	0.015
740-G	28	<1.0	<1.0	0.08	<.005	0.005	<.005	0.107	0.155
740-G	29	<1.0	<1.0	<.02	<.005	0.005	<.005	0.058	0.009
740-G	30	<1.0	<1.0	<.02	<.005	0.008	<.005	1.484	4.018
740-G	30A	<1.0	1.4	0.06	<.005	0.039	<.005	3.656	10.203
740-G	31	<1.0	<1.0	<.02	<.005	0.006	<.005	0.007	0.021
740-G	32	<1.0	<1.0	0.03	<.005	0.005	<.005	0.107	0.028
740-G	33	<1.0	<1.0	<.02	<.005	0.006	<.005	0.024	0.000
740-G	34	<1.0	2.7	<.02	0.295	0.023	<.005	0.878	139.987
740-G	35	<1.0	1.0	<.02	<.005	0.010	<.005	<.005	0.359
740-G	36	<1.0	1.4	<.02	<.005	0.012	<.005	<.005	0.079
740-G	37	<1.0	<1.0	<.02	<.005	0.009	<.005	0.010	0.055
740-G	38	<1.0	<1.0	<.02	<.005	0.009	<.005	<.005	0.071
740-G	39	<1.0	1.1	<.02	<.005	0.043	<.005	0.436	0.043
740-G	40	<1.0	1.6	<.02	<.005	0.020	<.005	<.005	0.031
740-G	40A	<1.0	1.3	<.02	<.005	0.015	<.005	<.005	0.014
740-G	41	<1.0	1.9	<.02	<.005	0.149	<.005	0.446	0.363
740-G	42	<1.0	1.7	<.02	<.005	0.032	<.005	0.138	0.095
740-G	43	<1.0	2.6	<.02	<.005	1.168	<.005	0.911	0.040
740-G	44	<1.0	<1.0	<.02	<.005	0.005	<.005	0.035	0.030
740-G	45	<1.0	<1.0	<.02	<.005	0.007	<.005	0.007	0.006
740-G	46	<1.0	<1.0	<.02	<.005	0.009	<.005	0.059	0.010
740-G	47	<1.0	<1.0	0.02	<.005	0.066	<.005	0.757	0.022
740-G	48	<1.0	<1.0	<.02	<.005	0.008	<.005	0.047	0.005

* SEE SECTION III. D.

Table 2. Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
 ----- 740-G LANDFILL AREA -----
 ----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICHLORO ETHYLENE	TETRA CHLORO ETHYLENE
740-G 49	<1.0	<1.0	<.02	<.005	0.027	<.005	<.005	0.006
740-G 50	<1.0	<1.0	<.02	<.005	0.018	<.005	<.005	0.000
740-G 50A	<1.0	<1.0	<.02	<.005	0.021	<.005	<.005	0.000
740-G 51	<1.0	1.0	<.02	<.005	0.019	<.005	0.805	0.011
740-G 52	<1.0	2.7	<.02	<.005	0.252	<.005	1.616	0.550
740-G 53	<1.0	1.8	<.02	<.005	1.615	<.005	1.399	0.053
740-G 54	*	15.5	<.02	0.012	0.353	<.005	11.836	0.020
740-G 55	<1.0	<1.0	<.02	<.005	0.085	<.005	0.162	0.025
740-G 56	<1.0	<1.0	<.02	<.005	0.588	<.005	0.206	0.051
740-G 57	*	1.5	<.02	0.061	1.474	<.005	2.657	0.129
740-G 58	*	<1.0	<.02	<.005	0.009	<.005	0.025	0.013
740-G 59	<1.0	<1.0	<.02	<.005	0.007	<.005	0.016	0.000
740-G 60	<1.0	5.4	<.02	<.005	0.108	<.005	5.366	0.234
740-G 60A	<1.0	4.8	<.02	<.005	0.198	<.005	5.385	0.130
740-G 61	<1.0	1.5	<.02	0.005	<.005	<.005	5.475	0.055
740-G 62	<1.0	<1.0	0.04	<.005	0.105	<.005	1.424	0.097
740-G 63	<1.0	<1.0	<.02	<.005	<.005	<.005	0.008	0.000
740-G 64	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 65	<1.0	17.5	<.02	<.005	0.042	<.005	4.366	0.090
740-G 66	<1.0	2.1	<.02	0.023	<.005	<.005	0.155	0.075
740-G 67	<1.0	20.7	0.11	<.005	0.230	<.005	4.366	0.078
740-G 68	<1.0	85.1	<.02	<.005	0.014	<.005	2.573	0.082
740-G 69	<1.0	93.4	<.02	0.013	1.140	<.005	14.169	0.452
740-G 70	<1.0	<1.0	0.15	<.005	0.005	<.005	0.148	0.006
740-G 70A	<1.0	<1.0	0.07	<.005	<.005	<.005	0.081	0.000
740-G 71	<1.0	<1.0	<.02	<.005	0.256	<.005	0.035	0.333
740-G 72	<1.0	1.2	<.02	<.005	0.073	<.005	0.113	0.138
740-G 73	*	1.2	<.02	0.006	0.805	<.005	0.149	0.469
740-G 74	*	1.2	0.58	<.005	0.249	<.005	1.017	2.109
740-G 75	<1.0	1.3	<.02	<.005	0.016	<.005	0.021	0.032
740-G 76	*	<1.0	0.04	<.005	0.083	<.005	0.032	0.046
740-G 77	<1.0	<1.0	<.02	<.005	<.005	<.005	0.029	0.000
740-G 78	<1.0	<1.0	<.02	<.005	<.005	<.005	0.007	0.000
740-G 79	*	6.2	<.02	<.005	0.654	<.005	8.359	0.022
740-G 80	*	4.9	<.02	0.187	8.275	<.005	1.717	0.231
740-G 80A	*	3.3	<.02	0.129	3.363	<.005	1.540	0.147
740-G 81	*	35.1	0.09	0.048	2.188	<.005	9.696	0.371
740-G 82	*	3.2	<.02	<.005	5.873	<.005	1.845	0.238
740-G 83	*	<1.0	<.02	<.005	1.328	<.005	0.396	0.132
740-G 84	<1.0	<1.0	<.02	<.005	1.171	<.005	0.144	0.249
740-G 85	*	<1.0	<.02	<.005	3.182	<.005	0.409	0.202
740-G 86	*	27.7	<.02	0.041	4.466	<.005	3.295	0.016
740-G 87	*	<1.0	<.02	<.005	0.272	<.005	0.036	0.006
740-G 88	*	<1.0	<.02	0.022	12.572	<.005	0.263	0.087
740-G 89	*	<1.0	<.02	<.005	2.246	<.005	1.853	0.019
740-G 90	*	26.6	<.02	0.068	21.960	<.005	17.360	15.798
740-G 90A	*	28.8	<.02	0.051	9.497	<.005	13.673	16.803
740-G 91	<1.0	<1.0	<.02	<.005	0.018	<.005	0.013	0.005
740-G 92	<1.0	<1.0	<.02	<.005	<.005	<.005	0.009	0.000
740-G 93	*	2.1	<.02	0.005	0.460	<.005	1.115	3.724
740-G 94	*	4.9	<.02	0.036	1.555	<.005	2.714	0.280
740-G 95	*	1.6	<.02	<.005	0.025	<.005	0.018	0.010

* SEE SECTION III. D.

Table 2. Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
740-G 96	*	<1.0	<.02	<.005	0.008	<.005	0.007	0.011
740-G 97	*	1.5	<.02	<.005	0.005	<.005	0.016	0.005
740-G 98	*	<1.0	<.02	0.036	5.389	<.005	1.270	0.235
740-G 99	*	<1.0	<.02	0.013	3.413	<.005	0.514	0.118
740-G 100	*	2.7	<.02	<.005	0.010	<.005	0.066	0.138
740-G 100A	*	5.4	<.02	<.005	0.007	<.005	0.094	0.127
740-G 101	<1.0	<1.0	<.02	<.005	0.007	<.005	<.005	0.000
740-G 102	<1.0	<1.0	<.02	<.005	0.008	<.005	0.062	0.000
740-G 103	*	<1.0	<.02	<.005	0.005	<.005	0.011	0.006
740-G 104	*	<1.0	<.02	<.005	0.006	<.005	0.013	0.000
740-G 105	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 106	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	0.000
740-G 107	*	1.0	<.02	<.005	0.018	<.005	0.012	0.011
740-G 108	*	1.1	<.02	<.005	0.036	<.005	0.102	0.060
740-G 109	*	<1.0	<.02	<.005	0.095	<.005	0.008	0.015
740-G 110	<1.0	2.9	<.02	<.005	0.018	<.005	0.017	0.000
740-G 110A	<1.0	1.1	<.02	<.005	0.028	<.005	0.011	0.000
740-G 111	*	21.4	0.85	0.008	2.071	<.005	4.459	12.469
740-G 112	*	<1.0	<.02	<.005	1.019	<.005	0.137	0.348
740-G 113	*	<1.0	<.02	0.020	1.395	<.005	1.378	0.398
740-G 114	<1.0	<1.0	<.02	<.005	0.252	<.005	0.075	0.017
740-G 115	*	10.1	<.02	0.005	0.015	<.005	0.302	0.036
740-G 116	<1.0	<1.0	<.02	<.005	0.092	<.005	0.091	0.031
740-G 117	*	2.0	<.02	0.042	0.097	<.005	1.704	0.874
740-G 118	*	<1.0	<.02	<.005	0.065	<.005	0.165	0.115
740-G 119	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 120	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 121	<1.0	<1.0	<.02	<.005	0.148	<.005	1.321	4.846
740-G 122	<1.0	1.9	<.02	<.005	0.938	<.005	0.760	0.086
740-G 123	*	<1.0	<.02	0.011	1.481	<.005	0.464	0.072
740-G 124	*	2.1	0.44	0.024	0.519	<.005	2.495	0.345
740-G 125	<1.0	3.2	0.05	<.005	0.013	<.005	0.473	0.032
740-G 126	<1.0	1.9	<.02	0.012	0.300	<.005	1.762	0.311
740-G 127	<1.0	17.8	<.02	<.005	2.466	<.005	0.634	0.301
740-G 128	<1.0	<1.0	<.02	<.005	0.019	<.005	0.076	0.284
740-G 129	*	<1.0	<.02	<.005	0.208	<.005	0.430	0.193
740-G 129A	*	<1.0	<.02	<.005	0.310	<.005	0.643	0.238
740-G 130	*	11.8	<.02	<.005	0.060	<.005	1.996	0.632
740-G 131	*	7.1	4.62	0.008	1.045	<.005	6.977	9.415
740-G 131A	*	6.0	3.10	0.006	0.901	<.005	4.960	11.445
740-G 132	<1.0	<1.0	<.02	<.005	0.026	<.005	0.020	0.070
740-G 133	<1.0	<1.0	<.02	<.005	0.023	<.005	<.005	0.007
740-G 134	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	0.000
740-G 135	<1.0	<1.0	<.02	<.005	0.085	<.005	0.030	0.043
740-G 136	<1.0	4.3	<.02	<.005	0.035	<.005	1.030	0.045
740-G 137	<1.0	1.0	<.02	<.005	0.037	<.005	0.025	0.000
740-G 138	<1.0	<1.0	<.02	<.005	<.005	<.005	0.017	0.000
740-G 139	<1.0	<1.0	<.02	<.005	0.005	<.005	0.103	0.000
740-G 140	<1.0	1.1	0.05	0.005	0.035	<.005	0.826	0.348
740-G 140A	<1.0	1.4	0.03	0.005	0.042	<.005	0.794	0.340
740-G 141	<1.0	<1.0	<.02	<.005	0.006	<.005	<.005	0.000
740-G 142	<1.0	<1.0	<.02	<.005	0.007	<.005	<.005	0.000

* SEE SECTION III. D.

Table 2. Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

[illegible]

Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2		111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
			DICHLORO ETHYLENE	CHLORO FORM				
740-G 190A	*	<1.0	<.02	0.008	6.810	<.005	0.759	0.888
740-G 191	*	2.3	<.02	0.013	6.018	<.005	0.459	0.148
740-G 192	*	<1.0	<.02	0.009	3.707	<.005	0.162	0.074
740-G 193	*	2.1	<.02	<.005	0.025	<.005	<.005	0.000
740-G 194	<1.0	<1.0	<.02	<.005	0.031	<.005	<.005	0.000
740-G 195	*	<1.0	<.02	<.005	1.381	<.005	0.069	0.052
740-G 196	*	1.1	<.02	<.005	0.006	<.005	<.005	0.000
740-G 197	<1.0	1.4	<.02	<.005	<.005	<.005	<.005	0.000
740-G 198	<1.0	<1.0	<.02	<.005	0.301	<.005	<.005	0.000
740-G 199	*	14.8	<.02	0.206	27.223	<.005	1.064	1.014
740-G 200	*	1.0	<.02	<.005	2.746	<.005	0.149	0.014
740-G 200A	*	<1.0	<.02	<.005	2.504	<.005	0.243	0.036
740-G 201	*	2.2	<.02	0.177	35.930	<.005	1.364	0.111
740-G 202	*	<1.0	<.02	0.080	13.172	<.005	0.964	0.190
740-G 203	<1.0	<1.0	<.02	<.005	2.319	<.005	0.023	0.034
740-G 204	*	<1.0	<.02	<.005	2.784	<.005	0.008	0.016
740-G 205	*	2.0	<.02	0.085	16.496	<.005	1.110	0.601
740-G 206	*	<1.0	<.02	0.007	21.770	<.005	1.359	0.670
740-G 207	<1.0	<1.0	<.02	<.005	0.031	<.005	0.010	0.009
740-G 208	*	39.2	<.02	0.100	0.711	<.005	0.876	0.094
740-G 209	*	<1.0	<.02	0.071	10.508	<.005	4.925	0.134
740-G 210	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 210A	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 211	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 212	<1.0	<1.0	<.02	0.011	16.930	<.005	0.694	0.751
740-G 213	<1.0	<1.0	<.02	0.011	10.281	<.005	<.005	0.016
740-G 214	*	4.9	<.02	0.022	25.101	<.005	0.298	0.264
740-G 215	*	1.5	<.02	0.006	2.731	<.005	<.005	0.023
740-G 216	*	<1.0	<.02	<.005	57.413	<.005	0.044	0.010
740-G 217	<1.0	<1.0	<.02	<.005	2.913	<.005	<.005	0.000
740-G 218	<1.0	<1.0	<.02	<.005	6.615	<.005	<.005	0.000
740-G 219	*	<1.0	<.02	<.005	9.182	<.005	<.005	0.009
740-G 220	*	<1.0	<.02	<.005	0.023	<.005	0.065	0.000
740-G 220A	*	<1.0	<.02	<.005	0.024	<.005	0.006	0.000
740-G 221	*	1.3	<.02	0.008	0.339	<.005	<.005	0.032
740-G 222	*	<1.0	<.02	0.005	0.104	<.005	<.005	0.000
740-G 223	<1.0	<1.0	<.02	<.005	0.045	<.005	<.005	0.000
740-G 224	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 225	<1.0	<1.0	<.02	0.010	<.005	<.005	<.005	0.000
740-G 226	<1.0	1.3	<.02	<.005	0.010	<.005	<.005	0.000
740-G 227	<1.0	1.3	<.02	<.005	3.129	<.005	0.020	0.000
740-G 228	*	1.3	<.02	<.005	0.909	<.005	<.005	0.000
740-G 229	<1.0	2.0	<.02	<.005	0.366	<.005	<.005	0.000
740-G 230	<1.0	1.1	<.02	<.005	0.377	0.006	<.005	0.000
740-G 230A	<1.0	1.4	<.02	<.005	0.540	0.007	<.005	0.000
740-G 231	<1.0	1.0	<.02	<.005	0.010	<.005	<.005	0.000
740-G 232	*	2.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 233	<1.0	<1.0	<.02	<.005	0.143	<.005	<.005	0.000
740-G 234	<1.0	<1.0	<.02	<.005	0.026	<.005	<.005	0.000
740-G 235	<1.0	<1.0	<.02	<.005	0.008	<.005	<.005	0.000
740-G 236	<1.0	<1.0	<.02	<.005	1.443	<.005	<.005	0.000
740-G 237	*	<1.0	<.02	<.005	6.686	<.005	0.041	0.054

* SEE SECTION III. D.

Table 2. Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
----- 740-G LANDFILL AREA -----
----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICHLORO ETHYLENE	TETRA CHLORO ETHYLENE
740-G 238	<1.0	<1.0	<.02	<.005	0.009	<.005	<.005	0.000
740-G 239	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 240	<1.0	<1.0	<.02	<.005	0.006	<.005	<.005	0.000
740-G 240A	<1.0	<1.0	<.02	<.005	0.006	<.005	<.005	0.000
740-G 241	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	0.000
740-G 242	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 243	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 244	*	<1.0	<.02	<.005	0.005	<.005	<.005	0.000
740-G 245	<1.0	1.5	<.02	<.005	0.005	<.005	<.005	0.000
740-G 246	<1.0	1.4	<.02	<.005	<.005	<.005	<.005	0.000
740-G 247	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 248	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 249	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 250	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 250A	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 251	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 252	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 253	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	0.000
740-G 254	*	1.8	<.02	<.005	<.005	<.005	<.005	0.000
740-G 255	*	1.7	<.02	<.005	<.005	<.005	<.005	0.000
740-G 256	*	1.8	<.02	<.005	<.005	<.005	<.005	0.000
740-G 257	*	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 258	*	1.3	<.02	<.005	<.005	<.005	<.005	0.000
740-G 259	*	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 260	*	2.1	<.02	<.005	<.005	<.005	<.005	0.000
740-G 260A	*	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 261	*	<1.0	<.02	<.005	<.005	<.005	<.005	0.000
740-G 262	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 263	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 264	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 265	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 266	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 267	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 268	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 269	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 269A	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 270	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 271	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 272	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 273	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 274	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 275	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 276	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 277	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 278	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 279	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 279A	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 280	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 281	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 282	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 283	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 284	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005

* SEE SECTION III. D.

Table 2. Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

----- SAVANNAH RIVER SITE -----
 ----- 740-G LANDFILL AREA -----
 ----- SOIL GAS CONCENTRATIONS (PPMV) -----

SAMPLE #	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
740-G 285	<1.0	<1.0	<.02	<.005	.007	<.005	<.005	<.005
740-G 286	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 287	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G 288	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 1	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 2	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 3	<1.0	<1.0	<.02	<.005	0.007	<.005	<.005	<.005
740-G BLK 4	<1.0	<1.0	<.02	<.005	<.005	<.005	0.010	0.013
740-G BLK 5	<1.0	<1.0	<.02	<.005	0.009	<.005	<.005	<.005
740-G BLK 6	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 7	<1.0	<1.0	<.02	<.005	0.005	<.005	0.019	<.005
740-G BLK 8	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 9	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	<.005
740-G BLK 10	<1.0	<1.0	<.02	<.005	<.005	<.005	0.039	<.005
740-G BLK 11	<1.0	<1.0	<.02	<.005	0.011	<.005	0.044	0.016
740-G BLK 12	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 13	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 14	<1.0	<1.0	<.02	<.005	0.006	<.005	0.022	0.053
740-G BLK 15	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	0.053
740-G BLK 16	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 17	<1.0	<1.0	<.02	<.005	0.006	<.005	<.005	<.005
740-G BLK 18	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 19	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 20	<1.0	<1.0	<.02	<.005	0.023	<.005	<.005	<.005
740-G BLK 21	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 22	<1.0	<1.0	<.02	<.005	0.010	<.005	<.005	0.006
740-G BLK 23	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	<.005
740-G BLK 24	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 25	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 26	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 27	<1.0	<1.0	<.02	<.005	0.005	<.005	<.005	<.005
740-G BLK 28	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 29	*	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 30	*	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 31	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005
740-G BLK 32	<1.0	<1.0	0.03	<.005	<.005	<.005	<.005	<.005
740-G BLK 33	<1.0	<1.0	0.03	<.005	<.005	<.005	<.005	<.005
740-G BLK 34	<1.0	<1.0	<.02	<.005	<.005	<.005	<.005	<.005

* SEE SECTION III. D.

Table 2. Chlorinated Hydrocarbon Soil Gas Concentrations and System Blanks at the 740-G Sanitary Landfill

This page intentionally left blank.

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	I-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G 1	16.4	163880000	<5	8696	10532	1992	1083	1687	1	740-G 1
740-G 2	24.0	240120000	<5	8634	13757	<5	376	246	<1	740-G 2
740-G 3	25.6	256050000	<5	2860	5170	<5	1500	917	2	740-G 3
740-G 4	48.8	487760000	<5	797	295	<5	<5	317	<1	740-G 4
740-G 5	40.0	399640000	<5	56	<5	<5	<5	<5	2	740-G 5
740-G 6	9.2	92353000	<5	1029	603	118	541	299	<1	740-G 6
740-G 7	0.0	4069	47	15	<5	<5	25	60	<1	740-G 7
740-G 8	0.0	2902	25	9	<5	<5	15	112	2	740-G 8
740-G 9	46.2	461820000	<5	8518	12590	<5	<5	938	33	740-G 9
740-G 10	52.9	528570000	<5	2682	2528	216	3139	1814	6	740-G 10
740-G 10A	53.2	532080000	<5	2173	919	<5	3091	808	5	740-G 10A
740-G 11	61.0	610080000	<5	12461	19042	260	2088	2927	6	740-G 11
740-G 12	58.1	581080000	<5	17860	22009	<5	1864	3220	5	740-G 12
740-G 13	50.3	503050000	<5	20996	26054	<5	1526	9241	9	740-G 13
740-G 14	0.0	394117	88	218	535	<5	42	758	3	740-G 14
740-G 15	40.6	405560000	<5	9852	10889	352	2406	4159	5	740-G 15
740-G 16	57.4	573780000	1858	2924	<5	<5	7250	7852	9	740-G 16
740-G 17	58.1	581080000	<5	12808	12891	<5	<5	1479	2	740-G 17
740-G 18	58.1	580820000	<5	9269	14401	<5	2061	2494	5	740-G 18
740-G 19	55.7	557210000	<5	959	151	<5	936	1801	12	740-G 19
740-G 20	44.7	446560000	<5	875	<5	<5	<5	398	3	740-G 20
740-G 20A	54.6	546460000	<5	3035	459	187	<5	163	5	740-G 20A
740-G 21	0.0	5586	38	50	13	<5	24	195	3	740-G 21
740-G 22	0.0	11893	95	66	464	6	53	231	2	740-G 22
740-G 23	62.7	627470000	<5	30152	28918	<5	3360	5918	5	740-G 23
740-G 24	60.9	608600000	<5	7272	4919	<5	1446	2070	7	740-G 24
740-G 25	49.4	493720000	<5	6547	5037	<5	4082	3367	11	740-G 25
740-G 26	8.8	87769800	<5	671	<5	<5	739	378	10	740-G 26
740-G 27	46.3	462890000	<5	3881	4452	<5	<5	1191	1	740-G 27
740-G 28	32.5	325210000	<5	6297	6486	<5	2004	3649	6	740-G 28
740-G 29	52.1	520610000	<5	2390	2320	<5	2135	918	5	740-G 29
740-G 30	50.8	508010000	<5	33031	52445	1331	7102	27073	<1	740-G 30
740-G 30A	53.1	530910000	<5	39640	61157	1417	7923	34926	2	740-G 30A
740-G 31	1.6	15827338	<5	1528	230	<5	917	<5	2	740-G 31
740-G 32	49.4	493690000	<5	4964	7435	<5	895	1620	2	740-G 32
740-G 33	11.6	115827000	<5	1091	434	<5	485	274	3	740-G 33
740-G 34	41.4	414010000	<5	253	334	267	3176	33961	3	740-G 34
740-G 35	0.0	6736	24	10	<5	<5	18	1376	3	740-G 35
740-G 36	0.0	3054	23	10	<5	<5	14	51	1	740-G 36
740-G 37	25.6	256140000	<5	2515	445	<5	<5	671	2	740-G 37
740-G 38	4.2	41726600	<5	<5	<5	<5	<5	<5	<1	740-G 38
740-G 39	7.4	74244600	<5	5870	6767	299	<5	<5	3	740-G 39
740-G 40	19.1	191130000	<5	1644	3915	<5	<5	<5	2	740-G 40
740-G 40A	16.1	160630000	<5	2074	3882	<5	493	604	3	740-G 40A
740-G 41	52.3	523400000	<5	65786	85546	2070	4445	11025	3	740-G 41
740-G 42	35.7	357060000	<5	26959	33780	<5	1464	785	7	740-G 42
740-G 43	33.0	329940000	7348	71537	45651	33045	7144	3617	2	740-G 43
740-G 44	23.4	233660000	<5	293	<5	<5	<5	<5	<1	740-G 44
740-G 45	32.5	324770000	<5	161	<5	75	774	485	2	740-G 45
740-G 46	49.7	497180000	<5	780	621	<5	1249	1119	7	740-G 46
740-G 47	46.0	459540000	<5	6319	18454	4678	2057	1057	3	740-G 47
740-G 48	49.5	495120000	<5	517	1181	<5	<5	994	4	740-G 48
740-G 49	0.0	11499	14	179	558	<5	8	28	2	740-G 49

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	I-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G 50	0.0	7248	12	<5	<5	<5	6	8	2	740-G 51
740-G 50A	0.0	4717	11	<5	<5	<5	6	12	3	740-G 52
740-G 51	50.5	505000000	<5	744	49	<5	1128	1667	4	740-G 53
740-G 52	38.3	382810000	<5	25926	34516	7929	2403	3401	3	740-G 54
740-G 53	27.7	277180000	<5	19614	27170	3390	2191	5635	4	740-G 55
740-G 54	19.5	195270000	7072	88749	180900	81352	5021	35163	4	740-G 56
740-G 55	15.5	154900000	5496	38646	68307	32640	1975	2496	4	740-G 57
740-G 56	0.0	4474	140	2056	7593	977	82	1422	4	740-G 58
740-G 57	4.0	40287800	15719	75882	111690	49576	4195	13673	6	740-G 59
740-G 58	0.5	5366764	324	321	317	112	204	268	4	740-G 60
740-G 59	0.0	7135	292	91	9	14	122	1677	7	740-G 60A
740-G 60	45.1	451280000	9864	108420	118110	45512	7000	11019	2	740-G 61
740-G 60A	41.6	415990000	8725	92550	104680	39860	6258	9794	3	740-G 62
740-G 61	62.4	624150000	16095	58669	67522	32344	10206	9756	2	740-G 63
740-G 62	38.4	383680000	9530	154460	154810	66065	5802	11716	7	740-G 64
740-G 63	0.0	29418	7	15	10	<5	6	<5	3	740-G 65
740-G 64	0.0	4070	10	6	<5	<5	6	8	2	740-G 66
740-G 65	43.6	435590000	24923	90543	113240	58836	14580	15274	4	740-G 67
740-G 66	62.4	624010000	<5	8398	10338	8959	5422	5864	4	740-G 68
740-G 67	39.6	395930000	33989	84643	82375	43661	11458	12577	7	740-G 69
740-G 68	37.9	378580000	42049	98591	122150	60781	20559	20856	12	740-G 70
740-G 69	37.0	369620000	67735	86727	115140	84590	23396	21849	10	740-G 70A
740-G 70	34.6	346480000	13189	21580	20711	12412	7978	5524	10	740-G 71
740-G 70A	36.4	364070000	9817	14437	12836	7523	7038	4589	7	740-G 72
740-G 71	0.0	24547	62	49	74	9	38	1392	7	740-G 72A
740-G 72A	13.8	138129490	20363	44207	18201	17242	3400	6402	7	740-G 73
740-G 73	13.9	138705000	52888	71803	37527	31777	7530	12569	6	740-G 74
740-G 74	16.3	163453200	77508	80894	65684	45918	19387	11110	3	740-G 75
740-G 75	31.2	312260000	45465	110730	89467	65164	7622	9551	6	740-G 76
740-G 76	15.3	153230000	27359	97662	68734	55139	4026	5871	4	740-G 77
740-G 77	0.0	13426	22	21	17	<5	11	14	6	740-G 78
740-G 78	0.0	5655	15	12	7	<5	9	17	2	740-G 79
740-G 79	24.4	244210000	101190	201140	273240	166320	19586	21107	1	740-G 80
740-G 80	2.4	24172600	52391	148190	121090	45121	5218	11967	6	740-G 80A
740-G 80A	2.9	28777000	47873	131990	118840	38642	4963	9314	4	740-G 81
740-G 81	5.3	53237410	194550	207990	220350	104300	21770	29992	5	740-G 82
740-G 82	3.3	33380000	<5	98459	83013	42011	4629	14935	18	740-G 83
740-G 83	6.0	59712200	40504	58535	54697	22147	3572	9053	5	740-G 84
740-G 84	0.0	29877	689	200	801	<5	14	1906	5	740-G 85
740-G 85	0.0	190360	13280	2639	14599	<5	1754	7473	3	740-G 86
740-G 86	1.1	10962000	115700	98743	84212	61176	15267	23341	7	740-G 87
740-G 87	0.0	33395	2481	108	1784	<5	56	1333	18	740-G 88
740-G 88	0.0	497520	41540	35930	45052	<5	2778	16587	31	740-G 89
740-G 89	0.0	116730	7870	1879	4070	21	60	10302	4	740-G 90
740-G 90	2.8	27625800	60874	93870	74844	83491	10085	22857	7	740-G 90A
740-G 90A	4.9	48920800	100950	155480	124870	126840	16814	40324	3	740-G 91
740-G 91	0.0	3605	51	25	<5	<5	28	110	4	740-G 92
740-G 92	0.0	325	20	8	<5	<5	16	9	<1	740-G 93
740-G 93	3.8	37714200	50471	116240	127150	58198	9884	24520	1	740-G 94
740-G 94	1.4	14140000	161320	72070	100440	3529	12012	29341	1	740-G 95
740-G 95	0.2	2306500	70855	39601	26836	18665	10465	10412	2	740-G 96
740-G 96	0.2	2472300	578	496	180	166	279	577	1	740-G 97
740-G 97	56.4	563750000	176420	297700	141170	202710	46632	73434	1	

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	1-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G 98	0.0	353571	37545	17402	26639	<5	463	10303	5	740-G 98
740-G 99	0.0	225714	20972	2495	2576	62	400	11913	10	740-G 99
740-G 100	25.1	251430000	156140	809680	682380	346990	77328	58729	2	740-G 100
740-G 100A	18.7	187470000	183770	970070	966750	549270	86642	74174	3	740-G 100A
740-G 101	0.0	13865	84	36	16	10	36	196	1	740-G 101
740-G 102	0.0	44289	135	42	<5	<5	47	284	2	740-G 102
740-G 103A	0.0	288571	687	497	624	206	329	1095	3	740-G 103A
740-G 104	2.0	19710144	36490	39605	40463	14538	4513	14175	5	740-G 104
740-G 105	0.0	767	6	<5	<5	<5	<5	5	7	740-G 105
740-G 106	0.0	763	11	<5	<5	<5	9	<5	<1	740-G 106
740-G 107	8.6	85507200	26331	74221	59946	29525	4371	11260	3	740-G 107
740-G 108	0.1	746376	7334	2169	2291	<5	156	1546	2	740-G 108
740-G 109	3.0	30434800	11512	27332	33645	4164	2062	9081	2	740-G 109
740-G 110	58.7	586860000	<5	10571	3478	3966	2569	3617	3	740-G 110
740-G 110A	55.0	550320000	<5	1591	366	775	<5	1653	2	740-G 110A
740-G 111	7.7	76812000	135500	181410	166540	123830	30271	45345	2	740-G 111
740-G 112	0.0	61055	1035	1215	3770	<5	37	4787	2	740-G 112
740-G 113	0.7	6734200	4139	42667	51030	23935	1141	12373	5	740-G 113
740-G 114	0.0	1355	94	77	233	<5	30	1682	4	740-G 114
740-G 115	17.3	172840000	93174	239320	202280	132150	24594	61746	5	740-G 115
740-G 116	0.0	1424	157	45	10	<5	83	3609	8	740-G 116
740-G 117	9.5	95362318	32520	103790	80771	44763	10232	84962	5	740-G 117
740-G 118	9.7	97101400	20407	59624	50552	25750	5985	32976	5	740-G 118
740-G 119	0.0	727	10	6	<5	<5	7	11	2	740-G 119
740-G 120	0.0	335	10	<5	<5	<5	9	20	<1	740-G 120
740-G 121	2.6	26086956	1808	6557	21827	2434	1716	6762	2	740-G 121
740-G 122	4.6	46376800	2180	10906	6433	2601	1530	3081	2	740-G 122
740-G 123	0.6	5860000	4912	22739	20486	9394	1887	6678	5	740-G 123
740-G 124	6.8	67647000	27850	96698	97239	57317	11910	22537	3	740-G 124
740-G 125	48.6	485760000	25171	47308	49691	37218	17102	12987	3	740-G 125
740-G 126	16.7	167058000	6816	45158	37824	21815	4239	15565	3	740-G 126
740-G 127	23.3	232500000	4549	14514	14483	4418	1883	2753	17	740-G 127
740-G 128	0.0	32600	106	34	10	<5	64	2070	3	740-G 128
740-G 129	6.6	66470600	6469	33187	37605	24009	2604	5684	3	740-G 129
740-G 129A	14.5	145000000	12602	66672	74813	49644	4679	11224	3	740-G 129A
740-G 130	13.5	135000000	6984	93306	55802	31442	4945	16373	3	740-G 130
740-G 131	14.9	149490000	32132	81264	66297	41674	34087	20281	3	740-G 131
740-G 131A	16.0	159705000	26534	65334	52308	32802	27847	18089	4	740-G 131A
740-G 132	0.0	2959	103	38	22	<5	131	2069	3	740-G 132
740-G 133	0.0	2086	20	28	238	<5	15	279	<1	740-G 133
740-G 134	0.0	5005	9	5	<5	<5	10	28	<1	740-G 134
740-G 135	0.9	8764400	269	611	409	386	155	412	2	740-G 135
740-G 136	36.9	369130000	<5	58803	36829	14631	3991	3694	1	740-G 136
740-G 137	0.5	5231100	1978	4467	71519	3128	876	805	2	740-G 137
740-G 138	34.3	343010000	<5	3381	3149	434	<5	680	2	740-G 138
740-G 139	0.6	6354400	240	482	588	470	162	218	1	740-G 139
740-G 140	27.8	277580000	10407	42803	49767	34329	5995	10232	2	740-G 140
740-G 140A	24.3	243250000	9410	38056	44129	30515	5327	9164	1	740-G 140A
740-G 141	0.0	332	21	7	<5	<5	10	11	3	740-G 141
740-G 142	0.0	300	18	6	<5	<5	15	14	2	740-G 142
740-G 143	0.0	202	11	<5	<5	<5	10	22	3	740-G 143
740-G 144	0.0	203	16	6	<5	<5	12	<5	2	740-G 144
740-G 145	0.0	407	10	<5	<5	<5	5	<5	2	740-G 145

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	1-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G 146	0.0	335	19	10	<5	<5	13	18	4	740-G 146
740-G 147	0.0	251	8	<5	<5	<5	6	<5	4	740-G 147
740-G 148	0.0	278	13	6	<5	<5	11	14	3	740-G 148
740-G 149	0.0	297	16	6	<5	<5	11	19	1	740-G 149
740-G 150	0.0	264	14	5	<5	<5	9	9	2	740-G 150
740-G 151	0.0	337	35	16	<5	<5	24	27	2	740-G 151
740-G 152	0.0	313	22	8	<5	<5	12	16	3	740-G 152
740-G 153	0.0	304	12	6	<5	<5	9	10	4	740-G 153
740-G 154	0.0	344	<5	6	<5	<5	9	10	2	740-G 154
740-G 155	0.0	336	19	8	<5	<5	11	13	3	740-G 155
740-G 155A	0.0	292	18	8	<5	<5	10	11	3	740-G 155A
740-G 156	0.0	14651	265	32	47	<5	9	129	2	740-G 156
740-G 157	0.0	46345	5648	4067	5120	615	149	1766	3	740-G 157
740-G 158	0.0	9387	609	32	207	<5	17	1016	3	740-G 158
740-G 159	0.0	78584	5364	7605	13067	1184	111	5322	3	740-G 159
740-G 160	0.0	10058	185	21	119	<5	19	1155	3	740-G 160
740-G 160A	0.0	16213	437	58	338	<5	27	1953	2	740-G 160A
740-G 161	0.0	25910	57	19	<5	<5	34	2155	2	740-G 161
740-G 162	0.0	164029	3027	279	1521	<5	34	5025	2	740-G 162
740-G 163	0.0	213500	24958	10099	14137	204	587	10743	3	740-G 163
740-G 164	0.0	29088	6295	569	3245	<5	26	4504	3	740-G 164
740-G 165	0.0	13206	1047	265	615	<5	106	2045	2	740-G 165
740-G 166	0.0	7331	124	23	16	<5	28	1203	3	740-G 166
740-G 167	0.0	4108	116	16	6	<5	16	281	4	740-G 167
740-G 168	0.0	316	14	11	<5	<5	9	17	4	740-G 168
740-G 169	0.0	319	11	5	<5	<5	9	46	1	740-G 169
740-G 170	0.0	13122	305	20	541	<5	10	876	2	740-G 170
740-G 170A	0.0	14519	360	21	618	<5	9	911	1	740-G 170A
740-G 171	1.0	9688300	141950	188330	159690	121690	17058	58191	3	740-G 171
740-G 172	0.7	7227100	142920	138740	131730	69616	13517	96986	3	740-G 172
740-G 173	0.0	241727	29820	4361	10934	276	461	26609	4	740-G 173
740-G 174	0.0	179856	10014	1239	2643	<5	83	19995	3	740-G 174
740-G 175	0.2	1536800	35845	14939	24386	1569	1715	22520	4	740-G 175
740-G 176	0.0	397122	12066	1235	3654	<5	51	18919	5	740-G 176
740-G 177	0.1	1207400	27034	12784	15820	1549	1827	21315	3	740-G 177
740-G 178	0.0	17484	1033	228	229	40	154	2960	3	740-G 178
740-G 179	0.0	399020	8699	8085	7659	1524	1462	2680	5	740-G 179
740-G 180	0.0	463380	1375	1303	<5	<5	707	<5	6	740-G 180
740-G 180A	0.1	877885	727	562	536	374	308	321	4	740-G 180A
740-G 181	0.1	847730	29219	22644	63521	3020	652	9445	2	740-G 181
740-G 182	0.0	287	20	9	<5	<5	12	11	3	740-G 182
740-G 183	0.0	302	10	<5	<5	<5	6	9	3	740-G 183
740-G 184	0.1	1352700	41175	16291	27696	<5	1364	58131	10	740-G 184
740-G 185	1.4	14339000	133550	142890	145550	100200	14354	169890	5	740-G 185
740-G 186	1.3	13022000	205160	289640	197460	158010	18206	127060	6	740-G 186
740-G 187	1.1	11419000	99278	112080	66299	34045	8247	67415	6	740-G 187
740-G 188	0.2	2259500	39423	4754	13897	<5	1562	43841	6	740-G 188
740-G 189	0.1	961950	34233	5566	14696	<5	404	34307	9	740-G 189
740-G 190	0.1	578417	10210	5340	18776	382	76	19389	7	740-G 190
740-G 190A	0.0	414388	10683	5687	19564	390	104	19993	5	740-G 190A
740-G 191	1.7	16978000	79562	91284	59168	42902	6101	40546	6	740-G 191
740-G 192	0.6	5565500	39246	8675	7598	1387	4427	43459	6	740-G 192
740-G 193	0.0	323741	447	191	158	29	151	459	6	740-G 193

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	I-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G 194	0.4	3712200	1202	1308	249	192	1195	295	6	740-G 194
740-G 195	0.0	79137	3388	557	2421	15	23	5278	4	740-G 195
740-G 196	0.0	597	19	8	<5	<5	13	75	1	740-G 196
740-G 197	0.0	520	14	6	<5	<5	10	9	1	740-G 197
740-G 198	0.0	3341	113	43	234	<5	10	1189	3	740-G 198
740-G 199	1.9	19393939	216040	208440	188770	147110	16762	50934	5	740-G 199
740-G 200	5.5	55142800	71036	206030	106920	135120	10134	18245	<1	740-G 200
740-G 200A	5.2	52000000	70891	208910	114790	144900	9699	19661	3	740-G 200A
740-G 201	3.7	36571400	100780	178480	134080	177910	8250	105210	1	740-G 201
740-G 202	0.7	6666666	44861	49565	19973	19011	3523	19447	5	740-G 202
740-G 203	0.0	378571	432	69	145	<5	29	5139	6	740-G 203
740-G 204	0.0	421290	2267	798	162	<5	633	5849	4	740-G 204
740-G 205	1.6	16000000	44681	76233	54322	43472	4648	14101	3	740-G 205
740-G 206	6.0	59714200	63209	178960	103170	101750	8575	20556	<1	740-G 206
740-G 207	1.4	14251000	2688	4641	277	423	1735	1374	7	740-G 207
740-G 208	13.6	136285600	85386	157250	91151	102740	17019	25266	2	740-G 208
740-G 209	0.4	3883500	41311	20427	28126	3300	1510	27169	4	740-G 209
740-G 210	0.0	238	14	<5	<5	<5	11	6	4	740-G 210
740-G 210A	0.0	264	7	<5	<5	<5	6	<5	6	740-G 210A
740-G 211	0.0	397	15	7	<5	<5	10	11	4	740-G 211
740-G 212	0.0	37584	4257	4510	8620	524	224	13017	2	740-G 212
740-G 213	0.0	38225	1285	1234	947	1038	468	708	4	740-G 213
740-G 214	0.6	6273100	169040	133510	158430	143590	12881	142760	3	740-G 214
740-G 215	0.2	2242600	25713	7814	8421	7493	2341	18177	3	740-G 215
740-G 216	0.0	75382	13325	14188	18803	<5	<5	16991	4	740-G 216
740-G 217	0.0	18782	377	313	114	<5	397	415	2	740-G 217
740-G 218	0.0	82857	117	35	559	<5	36	2440	3	740-G 218
740-G 219	0.0	33063	449	93	324	<5	46	3004	9	740-G 219
740-G 220	26.1	260900000	220490	683020	130170	169070	9002	6595	4	740-G 220
740-G 220A	20.8	207670000	125040	284660	52648	64044	7037	4935	4	740-G 220A
740-G 221	5.1	50571400	53345	104820	45813	46493	7261	27387	6	740-G 221
740-G 222	1.2	11589000	10787	9186	1644	1564	7942	12090	5	740-G 222
740-G 223	0.0	774	24	12	<5	<5	18	137	<1	740-G 223
740-G 224	0.0	357	19	11	<5	<5	15	22	<1	740-G 224
740-G 225	0.0	367	13	6	<5	<5	13	16	2	740-G 225
740-G 226	0.0	1170	22	10	<5	<5	20	285	2	740-G 226
740-G 227	0.0	93563	2272	967	1800	132	185	5535	4	740-G 227
740-G 228	0.0	13792	867	127	286	76	69	1490	4	740-G 228
740-G 229	0.0	36569	1012	1792	944	2038	526	600	3	740-G 229
740-G 230	0.0	7705	1833	134	55	60	43	825	5	740-G 230
740-G 230A	0.0	8067	2015	148	61	31	28	1365	5	740-G 230A
740-G 231	0.0	6579	31	13	<5	27	21	24	4	740-G 231
740-G 232	0.0	322222	4664	5614	3347	2200	128	367	2	740-G 232
740-G 233	0.0	45043	792	218	222	67	75	467	4	740-G 233
740-G 234	0.0	6756	127	48	6	74	68	76	9	740-G 234
740-G 235	0.0	1194	60	20	<5	26	45	62	4	740-G 235
740-G 236	0.3	3189000	955	2348	388	541	405	475	4	740-G 236
740-G 237	0.0	41635	2227	1503	2586	240	12	1134	3	740-G 237
740-G 238	0.0	362	13	5	<5	<5	12	8	1	740-G 238
740-G 239	0.0	413	23	9	<5	15	18	19	4	740-G 239
740-G 240	0.0	560	35	11	<5	16	23	18	4	740-G 240
740-G 240A	0.0	608	32	12	<5	13	21	19	2	740-G 240A
740-G 241	0.0	406	24	9	<5	13	16	26	2	740-G 241

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	1-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G 242	0.0	381	24	11	<5	15	27	21	2	740-G 242
740-G 243	0.0	413	20	6	<5	<5	17	7	<1	740-G 243
740-G 244	0.0	642	37	14	<5	19	27	28	1	740-G 244
740-G 245	0.0	583	39	10	<5	20	19	22	1	740-G 245
740-G 246	0.0	295	22	9	<5	12	19	19	2	740-G 246
740-G 247	0.0	484	36	13	<5	8	23	25	1	740-G 247
740-G 248	0.0	438	26	10	<5	11	20	20	1	740-G 248
740-G 249	0.0	516	30	13	<5	15	23	26	1	740-G 249
740-G 250	0.0	547	49	24	<5	9	30	30	1	740-G 250
740-G 250A	0.0	523	39	16	<5	8	23	27	<1	740-G 250A
740-G 251	0.0	497	36	13	<5	8	22	21	4	740-G 251
740-G 252	0.0	944	55	20	<5	22	31	36	2	740-G 252
740-G 253	0.0	3709	238	74	<5	47	121	125	13	740-G 253
740-G 254	0.0	538	52	17	<5	19	34	34	1	740-G 254
740-G 255	0.0	1445	87	29	<5	58	76	63	<1	740-G 255
740-G 256	0.0	512	28	11	<5	14	21	19	3	740-G 256
740-G 257	0.0	197	5	<5	<5	<5	8	<5	2	740-G 257
740-G 258	0.0	483	12	5	<5	<5	16	9	2	740-G 258
740-G 259	0.0	1611	69	53	<5	36	71	77	2	740-G 259
740-G 260	0.0	191	10	<5	<5	<5	9	<5	<1	740-G 260
740-G 260A	0.0	147	9	<5	<5	<5	14	<5	<1	740-G 260A
740-G 261	0.0	723	43	15	<5	25	25	23	<1	740-G 261
740-G 262	0.0	3395	123	42	64	9	78	181	NA	740-G 262
740-G 263	0.0	674	62	25	41	<5	45	157	NA	740-G 263
740-G 264	0.0	537	57	22	30	<5	40	119	NA	740-G 264
740-G 265	0.0	1013	103	52	58	7	79	208	NA	740-G 265
740-G 266	0.0	454	41	17	15	<5	32	115	NA	740-G 266
740-G 267	0.0	453	37	15	21	<5	26	127	NA	740-G 267
740-G 268	0.0	1134	96	37	56	11	63	154	NA	740-G 268
740-G 269	0.0	695	51	19	14	<5	30	126	NA	740-G 269
740-G 269A	0.0	1035	75	30	9	<5	49	167	NA	740-G 269A
740-G 270	0.0	462	51	22	29	<5	35	163	NA	740-G 270
740-G 271	0.0	318	12	7	6	<5	11	98	NA	740-G 271
740-G 272	0.0	802	71	28	46	<5	48	150	NA	740-G 272
740-G 273	0.0	409	36	14	28	<5	26	111	NA	740-G 273
740-G 274	0.0	436	37	15	16	<5	27	166	NA	740-G 274
740-G 275	0.0	622	35	16	22	<5	26	116	NA	740-G 275
740-G 276	0.0	166	9	<5	9	<5	8	123	NA	740-G 276
740-G 277	0.0	6146	418	163	164	32	334	475	NA	740-G 277
740-G 278	0.0	1423	91	33	29	5	62	180	NA	740-G 278
740-G 279	0.0	3507	168	65	88	19	120	279	NA	740-G 279
740-G 279A	0.0	257	31	12	11	<5	27	129	NA	740-G 279A
740-G 280	0.0	4927	228	90	117	<5	175	319	NA	740-G 280
740-G 281	0.0	8634	391	162	128	57	264	453	NA	740-G 281
740-G 282	0.0	4912	346	134	47	59	226	278	NA	740-G 282
740-G 283	0.0	1308	84	35	41	41	64	142	NA	740-G 283
740-G 284	0.0	359	34	14	15	<5	27	138	NA	740-G 284
740-G 285	0.0	390	24	9	11	<5	19	117	NA	740-G 285
740-G 286	0.0	444	35	16	14	<5	23	48	NA	740-G 286
740-G 287	0.0	1727	155	69	104	7	118	327	NA	740-G 287
740-G 288	0.0	517	60	25	48	<5	45	176	NA	740-G 288

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

-----WESTINGHOUSE SAVANNAH RIVER SITE-----
 ---- 740-G LANDFILL ----
 ----- SOIL GAS AND MERCURY CONCENTRATIONS @ 3 FT-----

SAMPLE #	METHANE %	METHANE PPB	ETHANE PPB	PROPANE PPB	I-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB	MERCURY ng/g	SAMPLE #
740-G SB1	0.0	2584	7	<5	<5	<5	<5	<5	NA	740-G SB1
740-G SB2	0.0	8935	<5	<5	<5	<5	<5	<5	NA	740-G SB2
740-G SB3	0.0	14145	<5	<5	<5	<5	<5	<5	NA	740-G SB3
740-G SB4	0.0	6397	5	<5	<5	<5	<5	<5	NA	740-G SB4
740-G SB5	0.0	6198	<5	<5	<5	<5	<5	<5	NA	740-G SB5
740-G SB6	0.0	3292	<5	<5	<5	<5	<5	<5	NA	740-G SB6
740-G SB7	0.0	5589	8	<5	<5	<5	<5	<5	NA	740-G SB7
740-G SB8	0.0	4687	6	<5	<5	<5	<5	<5	NA	740-G SB8
740-G SB9	0.0	2552	7	<5	<5	<5	<5	<5	NA	740-G SB9
740-G SB10	0.0	9820	8	13	8	5	<5	<5	NA	740-G SB10
740-G SB11	0.0	2871	7	6	<5	<5	<5	<5	NA	740-G SB11
740-G SB12	0.0	3486	8	13	<5	<5	5	<5	NA	740-G SB12
740-G SB13	0.0	5528	6	<5	<5	<5	<5	<5	NA	740-G SB13
740-G SB14	0.0	2848	<5	<5	<5	<5	<5	<5	NA	740-G SB14
740-G SB15	0.0	2527	6	5	<5	<5	<5	<5	NA	740-G SB15
740-G SB16	0.0	4921	5	7	<5	<5	7	<5	NA	740-G SB16
740-G SB17	0.0	2562	6	<5	<5	<5	7	<5	NA	740-G SB17
740-G SB18	0.0	2586	6	<5	<5	<5	<5	<5	NA	740-G SB18
740-G SB19	0.0	2611	5	<5	<5	<5	<5	<5	NA	740-G SB19
740-G SB20	0.0	2546	5	<5	<5	<5	7	<5	NA	740-G SB20
740-G SB21	0.0	2619	5	<5	<5	<5	<5	<5	NA	740-G SB21
740-G SB22	0.0	2541	<5	<5	<5	<5	<5	<5	NA	740-G SB22
740-G SB23	0.0	3010	<5	5	<5	<5	<5	<5	NA	740-G SB23
740-G SB24	0.0	2489	9	<5	<5	<5	<5	<5	NA	740-G SB24
740-G SB25	0.0	3789	<5	6	<5	<5	<5	<5	NA	740-G SB25
740-G SB26	0.0	1542	5	<5	<5	<5	10	8	NA	740-G SB26
740-G SB27	0.0	1554	<5	<5	<5	<5	6	<5	NA	740-G SB27
740-G SB28	0.0	1549	<5	<5	<5	<5	6	<5	NA	740-G SB28
740-G SB29	0.0	1545	<5	<5	<5	<5	8	<5	NA	740-G SB29
740-G SB30	0.0	1578	<5	<5	<5	<5	7	<5	NA	740-G SB30
740-G SB31	0.0	1572	<5	<5	<5	<5	9	<5	NA	740-G SB31
740-G SB32	0.0	1661	<5	89	<5	<5	<5	<5	NA	740-G SB32
740-G SB33	0.0	1680	<5	<5	<5	<5	<5	105	NA	740-G SB33
740-G SB34	0.0	1735	5	<5	<5	<5	<5	101	NA	740-G SB34

Table 3. Light Hydrocarbon Soil Gas, Soil Mercury Concentrations and System Blanks at the 740-G Sanitary Landfill

This page intentionally left blank.

COMPOUND	RANGE 1	RANGE 2	RANGE 3	RANGE 4	RANGE 5	RANGE 6
PENTANE	942.19	91.52	9.13	0.91	0.091	0.0091
11 DICHLOROETHYLENE	1358.80	131.99	13.16	1.32	0.132	0.0132
METHYLENE CHLORIDE	1694.16	164.57	16.41	1.64	0.164	0.0164
TRANS 1,2 DICHLORO	1408.09	136.78	13.64	1.36	0.136	0.0136
11 DICHLOROETHANE	1291.56	125.46	12.51	1.25	0.125	0.0125
CHLOROFORM	1356.81	131.80	13.14	1.31	0.131	0.0131
111 TRICHLOROETHANE	1089.10	105.79	10.55	1.05	0.105	0.0105
CARBON TETRACHLORIDE	1125.32	109.31	10.90	1.09	0.109	0.0109
HEPTANE	741.22	72.00	7.18	0.72	0.072	0.0072
BENZENE	1214.92	118.02	11.77	1.18	0.118	0.0118
TRICHLOROETHYLENE	1208.33	117.38	11.70	1.17	0.117	0.0117
OCTANE	668.30	64.92	6.47	0.65	0.065	0.0065
TOLUENE	1021.92	99.27	9.90	0.99	0.099	0.0099
TETRACHLOROETHYLENE	1062.81	103.24	10.29	1.03	0.103	0.0103
NONANE	607.90	59.05	5.89	0.59	0.059	0.0059
ETHYL BENZENE	886.78	86.14	8.59	0.86	0.086	0.0086
M-XYLENE	883.71	85.84	8.56	0.86	0.086	0.0086
P-XYLENE	880.64	85.54	8.53	0.85	0.085	0.0085
O-XYLENE	888.83	86.34	8.61	0.86	0.086	0.0086
DECANE	557.12	54.12	5.40	0.54	0.054	0.0054

Table 4. VOC Prepared Standard Concentrations

This page intentionally left blank.

----- NOVEMBER, 1990 (W2) STANDARDS -----
----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P-XYLENE	O-XYLENE	DECANE
STD I L6	740-G	W2 4	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD I L6	740-G	W2 5	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD I L5	740-G	W2 6	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD I L5	740-G	W2 7	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD I L5	740-G	W2 263	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
MEAN													
STD DEV													
% STD DEV													
STD I L4	740-G	W2 8	NA	NA	0.73	1.19	0.67	1.04	0.62	0.89	1.78	0.87	0.55
STD I L4	740-G	W2 9	NA	NA	0.72	1.18	0.64	1.00	0.61	0.88	1.75	0.86	0.55
STD I L4	740-G	W2 25	NA	NA	0.72	1.18	0.67	0.93	0.60	0.87	1.68	0.82	0.55
STD I L4	740-G	W2 37	NA	NA	0.71	1.15	0.63	0.95	0.58	0.84	1.66	0.84	0.53
STD I L4	740-G	W2 49	NA	NA	0.74	1.23	0.66	0.91	0.62	0.90	1.77	0.97	0.58
STD I L4	740-G	W2 61	NA	NA	0.72	1.18	0.68	0.84	0.61	0.87	1.71	0.87	0.55
STD I L4	740-G	W2 73	NA	NA	0.73	1.19	0.64	1.04	0.58	0.86	1.70	0.87	0.54
STD I L4	740-G	W2 86	NA	NA	0.69	1.13	0.64	0.99	0.55	0.82	1.60	0.86	0.53
STD I L4	740-G	W2 97	NA	NA	0.68	1.16	0.65	0.93	0.58	0.85	1.70	0.85	0.53
STD I L4	740-G	W2 110	NA	NA	0.68	1.13	0.61	0.93	0.55	0.81	1.60	0.81	0.52
STD I L4	740-G	W2 121	NA	NA	0.73	1.20	0.65	0.94	0.60	0.89	1.80	0.88	0.55
STD I L4	740-G	W2 133	NA	NA	0.71	1.17	0.65	0.98	0.58	0.87	1.73	0.86	0.53
STD I L4	740-G	W2 146	NA	NA	0.71	1.18	0.67	1.02	0.60	0.88	1.74	0.88	0.52
STD I L4	740-G	W2 158	NA	NA	0.71	1.16	0.64	0.93	0.57	0.86	1.72	0.89	0.52
STD I L4	740-G	W2 171	NA	NA	0.72	1.19	0.66	1.01	0.59	0.88	1.74	0.89	0.54
STD I L4	740-G	W2 189	NA	NA	0.73	1.19	0.68	0.97	0.57	0.87	1.74	0.89	0.54
STD I L4	740-G	W2 201	NA	NA	0.73	1.20	0.69	1.07	0.63	0.88	1.74	0.89	0.79
STD I L4	740-G	W2 213	NA	NA	0.67	1.06	0.64	0.97	0.56	0.86	1.74	0.82	0.50
STD I L4	740-G	W2 237	NA	NA	0.72	1.19	0.65	0.99	0.58	0.87	1.74	0.86	0.52
STD I L4	740-G	W2 286	NA	NA	0.71	1.17	0.65	0.97	0.57	0.86	1.72	0.88	0.53
STD I L4	740-G	W2 298	NA	NA	0.70	1.15	0.63	0.94	0.56	0.83	1.65	0.88	0.52
MEAN					0.71	1.17	0.65	0.97	0.58	0.86	1.71	0.87	0.55
STD DEV					0.02	0.03	0.02	0.05	0.02	0.02	0.05	0.03	0.06
% STD DEV					2.45	2.89	2.96	5.37	3.89	2.61	3.09	3.65	10.45
STD I L3	740-G	W2 10	8.06	NA	6.89	11.34	6.25	9.51	5.69	8.30	16.55	8.38	5.25
STD I L3	740-G	W2 11	8.16	NA	6.90	11.33	6.25	9.50	5.71	8.30	16.51	8.29	5.23
STD I L3	740-G	W2 177	8.15	NA	6.91	11.37	6.30	9.54	5.71	8.35	16.56	8.39	5.19
STD I L3	740-G	W2 225	8.11	NA	6.90	11.36	6.31	9.66	5.72	8.38	16.69	8.44	5.21
STD I L3	740-G	W2 249	7.95	NA	6.82	11.22	6.22	9.51	5.65	8.27	16.47	8.35	5.18
STD I L3	740-G	W2 310	7.77	NA	6.71	11.05	6.09	9.33	5.54	8.06	16.06	8.12	5.01
MEAN			8.03		6.86	11.28	6.24	9.51	5.67	8.28	16.47	8.33	5.18
STD DEV			0.14		0.07	0.11	0.07	0.10	0.06	0.10	0.20	0.10	0.08
% STD DEV			1.74		1.06	1.01	1.15	1.02	1.13	1.24	1.19	1.24	1.55
STD I L2	740-G	W2 12	107.70	NA	74.95	122.90	68.03	103.92	62.09	90.48	180.30	90.84	57.08
STD I L2	740-G	W2 13	108.72	NA	75.82	124.42	68.65	104.95	62.52	91.24	181.52	91.53	57.30
STD 224	740-G	W2 15	1003.62	1035.00	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 224	740-G	W2 74	1023.28	1061.15	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 224	740-G	W2 176	1022.20	1058.75	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	740-G	W2 16	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	740-G	W2 175	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

Table 5. Analyses of "I" Standards: a) Hydrocarbons

----- NOVEMBER, 1990 (W2) STANDARDS -----

----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICHLORO ETHYLENE	TETRA CHLORO ETHYLENE
STD I L6	740-G	W2 4	NA	NA	NA	0.013	0.010	0.011	0.012	0.010
STD I L6	740-G	W2 5	NA	NA	NA	0.013	0.011	0.011	0.012	0.010
STD I L5	740-G	W2 6	NA	NA	0.15	0.131	0.104	0.109	0.119	0.104
STD I L5	740-G	W2 7	NA	NA	0.15	0.130	0.104	0.108	0.117	0.103
STD I L5	740-G	W2 263	NA	NA	0.16	0.188	0.148	0.112	0.162	0.103
MEAN					0.15	0.150	0.119	0.110	0.133	0.103
STD DEV					0.00	0.023	0.018	0.001	0.018	0.000
% STD DEV					1.78	15.686	15.137	1.342	13.550	0.395
STD I L4	740-G	W2 8	NA	1.65	1.28	1.352	1.059	1.117	1.203	1.175
STD I L4	740-G	W2 9	NA	1.64	1.27	1.340	1.054	1.066	1.193	1.094
STD I L4	740-G	W2 25	NA	1.71	1.31	1.392	1.060	1.068	1.212	1.056
STD I L4	740-G	W2 37	NA	1.62	1.25	1.291	1.033	1.045	1.125	0.993
STD I L4	740-G	W2 49	NA	1.70	1.35	1.555	1.160	1.074	1.328	1.180
STD I L4	740-G	W2 61	NA	1.67	1.27	1.344	1.065	1.112	1.159	1.001
STD I L4	740-G	W2 73	NA	1.66	1.34	1.496	1.147	1.216	1.281	1.123
STD I L4	740-G	W2 86	NA	1.82	1.27	1.355	1.104	1.075	1.173	1.027
STD I L4	740-G	W2 97	NA	1.64	1.37	1.554	1.180	1.194	1.326	1.156
STD I L4	740-G	W2 110	NA	1.50	1.31	1.440	1.120	1.086	1.215	1.044
STD I L4	740-G	W2 121	NA	1.54	1.40	1.191	1.275	1.140	1.410	1.202
STD I L4	740-G	W2 133	NA	1.60	1.32	1.599	1.185	1.139	1.246	1.076
STD I L4	740-G	W2 146	NA	1.60	1.33	1.637	1.202	1.209	1.263	1.141
STD I L4	740-G	W2 158	NA	1.66	1.32	1.582	1.186	1.146	1.245	1.065
STD I L4	740-G	W2 171	NA	1.59	1.35	1.271	1.231	1.203	1.291	1.106
STD I L4	740-G	W2 189	NA	1.60	1.32	1.690	1.224	1.169	1.255	1.083
STD I L4	740-G	W2 201	NA	1.80	1.32	1.271	1.220	1.122	1.287	1.114
STD I L4	740-G	W2 213	NA	2.57	1.22	1.361	1.080	1.111	1.096	0.921
STD I L4	740-G	W2 237	NA	1.62	1.35	1.356	1.076	1.131	1.183	1.106
STD I L4	740-G	W2 286	NA	1.61	1.36	1.372	1.082	1.144	1.191	1.110
STD I L4	740-G	W2 298	NA	1.78	1.30	1.351	1.074	1.039	1.154	1.034
MEAN				1.69	1.31	1.419	1.134	1.124	1.230	1.087
STD DEV				0.21	0.04	0.133	0.070	0.052	0.073	0.044
% STD DEV				12.47	3.19	9.36	6.20	4.63	5.95	6.01
STD I L3	740-G	W2 10	NA	15.70	11.20	12.621	10.131	10.891	11.178	9.404
STD I L3	740-G	W2 11	NA	15.75	11.08	12.645	10.139	10.907	11.206	9.991
STD I L3	740-G	W2 177	NA	15.57	11.99	12.377	10.164	11.431	11.354	9.557
STD I L3	740-G	W2 225	NA	15.41	11.88	12.301	10.126	11.604	11.199	9.050
STD I L3	740-G	W2 249	NA	15.26	11.67	12.761	10.288	11.458	11.430	9.065
STD I L3	740-G	W2 310	NA	14.91	11.69	12.687	10.166	10.687	11.260	9.123
MEAN				15.43	11.58	12.565	10.169	11.163	11.271	9.365
STD DEV				0.28	0.34	0.167	0.055	0.346	0.092	0.336
% STD DEV				1.85	2.92	1.33	0.54	3.10	0.81	3.55
STD I L2	740-G	W2 12	NA	172.47	NA	137.286	110.334	109.159	121.876	107.012
STD I L2	740-G	W2 13	NA	173.86	NA	138.376	111.426	109.431	122.949	107.656
STD 224	740-G	W2 15	NA	NA	NA	NA	NA	NA	NA	NA
STD 224	740-G	W2 74	NA	NA	NA	NA	NA	NA	NA	NA
STD 224	740-G	W2 176	NA	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	740-G	W2 16	1000	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	740-G	W2 175	959	NA	NA	NA	NA	NA	NA	NA

Table 5. Analyses of "I" Standards: b) Chlorinated Hydrocarbons

----- WESTINGHOUSE SAVANNAH RIVER SITE -----
 ----- DECEMBER, 1990 (W3) STANDARDS -----
 ----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P-XYLENE	O-XYLENE	DECANE
STD 12 R6	ALL	3	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R6	ALL	4	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R6	S,1G	229	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R6	CMP	416	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R6	CMP	436	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
MEAN													
STD DEV													
% STD DEV													
STD 12 R5	ALL	5	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	ALL	6	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	S	200	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	S,1G	228	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	1GL	270	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	CMP	301	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	CMP	415	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	CMP	435	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 12 R5	CMP	449	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
MEAN													
STD DEV													
% STD DEV													
STD 12 R4	ALL	7	NA	NA	0.75	1.17	0.67	0.90	0.66	0.90	1.76	1.03	0.58
STD 12 R4	ALL	8	NA	NA	0.71	1.17	0.64	0.92	0.58	0.85	1.70	0.85	0.54
STD 12 R4	ALL	16	NA	NA	0.67	1.11	0.65	0.99	0.60	0.87	1.73	0.85	0.59
STD 12 R4	740G	29	NA	NA	0.74	1.20	0.67	1.02	0.61	0.87	1.74	0.89	0.54
STD 12 R4	740G,H	54	NA	NA	0.76	1.20	0.70	1.05	0.61	0.89	1.77	0.88	0.55
STD 12 R4	H	66	NA	NA	0.75	1.20	0.65	1.01	0.62	0.88	1.73	0.89	0.56
STD 12 R4	H	78	NA	NA	0.74	1.21	0.68	0.89	0.61	0.87	1.72	0.85	0.58
STD 12 R4	H	90	NA	NA	0.75	1.20	0.66	0.83	0.61	0.89	1.80	0.88	0.52
STD 12 R4	G	103	NA	NA	0.74	1.18	0.67	0.98	0.58	0.87	1.73	0.88	0.50
STD 12 R4	S	115	NA	NA	0.75	1.19	0.67	0.92	0.59	0.87	1.73	0.82	0.51
STD 12 R4	S	127	NA	NA	0.73	1.20	0.65	0.83	0.59	0.87	1.73	0.83	0.51
STD 12 R4	S	139	NA	NA	0.74	1.13	0.64	0.88	0.58	0.85	1.69	0.80	0.50
STD 12 R4	S	151	NA	NA	0.74	1.19	0.66	0.86	0.59	0.86	1.72	0.83	0.50
STD 12 R4	S	163	NA	NA	0.74	1.18	0.65	0.88	0.57	0.85	1.69	0.87	0.49
STD 12 R4	S	175	NA	NA	0.73	1.19	0.67	1.03	0.59	0.86	1.72	0.85	0.51
STD 12 R4	S	187	NA	NA	0.74	1.21	0.65	0.83	0.59	0.87	1.74	0.89	0.51
STD 12 R4	S	212	NA	NA	0.73	1.21	0.67	1.04	0.59	0.87	1.72	0.82	0.49
STD 12 R4	S	224	NA	NA	0.72	1.18	0.63	0.98	0.57	0.85	1.69	0.82	0.49
STD 12 R4	1G	238	NA	NA	0.73	1.20	0.67	1.01	0.59	0.87	1.75	0.89	0.51
STD 12 R4	1G	253	NA	NA	0.76	1.24	0.66	1.04	0.61	0.90	1.81	0.91	0.53
STD 12 R4	1GL	271	NA	NA	0.75	1.19	0.64	0.80	0.60	0.87	1.71	0.88	0.53
STD 12 R4	1GL	277	NA	NA	0.75	1.20	0.70	1.09	0.60	0.88	1.76	0.81	0.53
STD 12 R4	CMP	289	NA	NA	0.73	1.19	0.64	1.09	0.64	0.89	1.76	0.94	0.52
STD 12 R4	CMP	317	NA	NA	0.74	1.20	0.64	1.00	0.61	0.88	1.73	0.88	0.54
STD 12 R4	CMP	328	NA	NA	0.74	1.21	0.64	1.00	0.60	0.87	1.71	0.87	0.53
STD 12 R4	CMP	340	NA	NA	0.74	1.20	0.64	1.00	0.63	0.89	1.76	0.89	0.54
STD 12 R4	CMP	352	NA	NA	0.74	1.18	0.64	0.99	0.61	0.86	1.70	0.85	0.57
STD 12 R4	CMP	376	NA	NA	0.73	1.18	0.63	0.99	0.61	0.86	1.71	0.89	0.54
STD 12 R4	CMP	388	NA	NA	0.73	1.20	0.64	0.99	0.59	0.87	1.73	0.89	0.51
STD 12 R4	CMP	400	NA	NA	0.74	1.20	0.64	1.00	0.59	0.86	1.73	0.85	0.50

Table 6. Analyses of "I2" Standards: a) Hydrocarbons

STANDARD NAME	AREA	GC CYCLE	PENTANE	HEXANE	HEPTANE	OCTANE	NONANE	DECANE	UNDECANE	DODECANE	TRIDECA	MYRIST	XYLENE	DECANE
STD 12 R4	CMP	414	1.1	1	0.71	1.14	0.64	0.54	0.4	0.3	1.77	0.84	0.52	
STD 12 R4	CMP	422	1.1	1	0.74	1.12	0.64	0.54	0.4	0.3	1.72	0.84	0.50	
MEAN					0.74	1.12	0.65	0.54	0.4	0.3	1.73	0.87	0.53	
STD DEV					0.01	0.01	0.02	0.01	0.01	0.01	0.03	0.04	0.03	
% STD DEV					1.34	1.84	2.75	1.84	2.42	3.04	1.67	4.93	5.15	
STD 12 R3	ALL	9	8.12	1	0.54	1.14	0.36	0.17	0.14	1	0.13	0.38	5.27	
STD 12 R3	ALL	10	8.17	1	0.54	1.14	0.43	0.14	0.14	1	0.13	0.39	5.35	
STD 12 R3	740G	47	8.17	1	0.57	1.14	0.43	0.14	0.14	1	0.13	0.42	5.29	
STD 12 R3	S	141	8.12	1	0.54	1.14	0.57	0.14	0.14	1	0.13	0.79	5.51	
STD 12 R3	CMP	201	8.17	1	0.57	1.14	0.57	0.14	0.14	1	0.13	0.84	5.54	
MEAN					0.54	1.14	0.47	0.14	0.14	1	0.13	0.50	5.39	
STD DEV					0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.19	0.11	
% STD DEV					1.87	1.17	1.25	1.14	1.14	1.14	1.14	2.17	2.08	
STD 12 R2	ALL	11	52.1		1.14	1.14	1.14	1.14	1.14	1.14	1.14	11.73	55.10	
STD 224	ALL	11	10.12	1	1	1	1	1	1	1	1	1	NA	
STD 224	CMP	201	10.12	1	1	1	1	1	1	1	1	1	NA	
STD 224	CMP	411	10.12	1	1	1	1	1	1	1	1	1	NA	
STD VC 1000	ALL	15	1	1	1	1	1	1	1	1	1	1	NA	
STD VC 1000	CMP	201	1	1	1	1	1	1	1	1	1	1	NA	
STD VC 1000	CMP	412	1	1	1	1	1	1	1	1	1	1	NA	

Table 6. Inertness of HPLC column for various compounds

----- WESTINGHOUSE SAVANNAH RIVER SITE -----
 ----- DECEMBER, 1990 (W3) STANDARDS -----
 ----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
STD 12 R6	ALL	3	NA	NA	NA	0.010	0.008	0.011	0.009	0.010
STD 12 R6	ALL	4	NA	NA	NA	0.011	0.009	0.011	0.010	0.010
STD 12 R6	S,1G	229	NA	NA	NA	0.015	0.012	0.012	0.011	0.011
STD 12 R6	CMP	416	NA	NA	NA	0.015	0.013	0.013	0.011	0.011
STD 12 R6	CMP	436	NA	NA	NA	0.017	0.014	0.013	0.011	0.011
MEAN						0.014	0.011	0.012	0.010	0.011
STD DEV						0.003	0.002	0.001	0.001	0.000
% STD DEV						19.510	20.671	7.454	7.692	4.622
STD 12 R5	ALL	5	NA	NA	0.16	0.185	0.144	0.109	0.165	0.103
STD 12 R5	ALL	6	NA	NA	0.17	0.187	0.146	0.109	0.165	0.103
STD 12 R5	S	200	NA	NA	0.17	0.182	0.142	0.130	0.156	0.108
STD 12 R5	S,1G	228	NA	NA	0.17	0.185	0.138	0.132	0.157	0.109
STD 12 R5	1GL	270	NA	NA	0.17	0.188	0.146	0.135	0.159	0.111
STD 12 R5	CMP	301	NA	NA	0.17	0.188	0.151	0.135	0.159	0.108
STD 12 R5	CMP	415	NA	NA	0.18	0.190	0.153	0.137	0.158	0.109
STD 12 R5	CMP	435	NA	NA	0.19	0.197	0.157	0.141	0.163	0.112
STD 12 R5	CMP	449	NA	NA	0.19	0.201	0.162	0.145	0.169	0.114
MEAN					0.17	0.189	0.149	0.130	0.161	0.109
STD DEV					0.01	0.006	0.007	0.012	0.004	0.003
% STD DEV					4.51	3.028	4.834	9.327	2.595	3.224
STD 12 R4	ALL	7	NA	1.63	1.36	1.278	1.026	1.094	1.142	1.037
STD 12 R4	ALL	8	NA	1.61	1.35	1.273	1.022	1.086	1.135	1.025
STD 12 R4	ALL	16	NA	2.61	1.40	1.383	1.099	1.211	1.170	1.069
STD 12 R4	740G	29	NA	1.56	1.49	1.408	1.121	1.315	1.211	1.243
STD 12 R4	740G,H	54	NA	1.60	1.53	1.467	1.187	0.992	1.238	1.000
STD 12 R4	H	66	NA	2.21	1.48	1.436	1.175	1.497	1.206	1.217
STD 12 R4	H	78	NA	3.29	1.46	1.429	1.179	1.501	1.176	1.119
STD 12 R4	H	90	NA	2.13	1.60	1.552	1.273	1.348	1.294	1.148
STD 12 R4	G	103	NA	5.49	1.57	1.551	1.289	1.087	1.277	1.033
STD 12 R4	S	115	NA	2.01	1.61	1.563	1.287	1.358	1.289	1.140
STD 12 R4	S	127	NA	4.71	1.58	1.553	1.292	1.092	1.270	1.027
STD 12 R4	S	139	NA	9.47	1.55	1.549	1.299	1.089	1.251	0.987
STD 12 R4	S	151	NA	4.49	1.61	1.595	1.331	1.123	1.302	1.060
STD 12 R4	S	163	NA	5.96	1.59	1.588	1.333	1.119	1.287	1.033
STD 12 R4	S	175	NA	3.96	1.63	1.599	1.342	1.131	1.300	1.065
STD 12 R4	S	187	NA	4.54	1.63	1.612	1.360	1.148	1.301	1.068
STD 12 R4	S	212	NA	4.78	1.36	1.307	1.062	1.114	1.143	1.023
STD 12 R4	S	224	NA	4.22	1.36	1.289	1.041	1.093	1.133	1.008
STD 12 R4	1G	238	NA	5.36	1.36	1.308	1.054	1.115	1.143	1.025
STD 12 R4	1G	253	NA	4.13	1.42	1.355	1.094	1.160	1.191	1.104
STD 12 R4	1GL	271	NA	2.07	1.36	1.295	1.057	1.095	1.123	1.019
STD 12 R4	1GL	277	NA	2.08	1.38	1.328	1.088	1.143	1.165	1.068
STD 12 R4	CMP	289	NA	2.40	1.39	1.323	1.086	1.136	1.156	1.049
STD 12 R4	CMP	317	NA	2.59	1.40	1.345	1.109	1.157	1.165	1.061
STD 12 R4	CMP	328	NA	2.20	1.42	1.357	1.119	1.166	1.171	1.070
STD 12 R4	CMP	340	NA	2.57	1.41	1.351	1.118	1.161	1.165	1.060
STD 12 R4	CMP	352	NA	3.91	1.37	1.342	1.116	1.154	1.148	1.028
STD 12 R4	CMP	376	NA	2.91	1.39	1.345	1.119	1.160	1.155	1.046
STD 12 R4	CMP	388	NA	3.17	1.42	1.363	1.133	1.174	1.169	1.070
STD 12 R4	CMP	400	NA	4.97	1.41	1.369	1.145	1.181	1.172	1.067

Table 6. Analyses of "I2" Standards: b) Chlorinated Hydrocarbons

----- WESTINGHOUSE SAVANNAH RIVER SITE -----
 ----- DECEMBER, 1990 (W3) STANDARDS -----
 ----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
STD 12 R4	CMP	414	NA	3.68	1.40	1.358	1.134	1.172	1.161	1.052
STD 12 R4	CMP	429	NA	5.44	1.40	1.373	1.151	1.186	1.167	1.049
MEAN				3.55	1.46	1.414	1.164	1.174	1.199	1.065
STD DEV				1.69	0.09	0.109	0.102	0.111	0.059	0.056
% STD DEV				47.58	6.50	7.706	8.722	9.494	4.923	5.230
STD 12 R3	ALL	9	NA	16.12	13.42	12.780	10.280	10.910	11.370	9.850
STD 12 R3	ALL	10	NA	16.71	13.79	13.040	10.470	10.710	11.630	10.590
STD 12 R3	740G	42	NA	18.54	15.14	13.350	10.680	10.730	11.660	10.580
STD 12 R3	S	191	NA	14.57	13.56	13.420	10.630	11.380	11.880	10.810
STD 12 R3	CMP	303	NA	14.28	13.79	13.330	10.660	11.090	11.870	10.890
MEAN				16.04	13.94	13.184	10.544	10.964	11.682	10.544
STD DEV				1.55	0.62	0.240	0.151	0.249	0.187	0.368
% STD DEV				9.64	4.42	1.822	1.435	2.275	1.602	3.486
STD 12 R2	ALL	11	NA	167.34	NA	134.130	107.670	109.280	119.552	104.081
STD 224	ALL	14	NA	NA	NA	NA	NA	NA	NA	NA
STD 224	CMP	304	NA	NA	NA	NA	NA	NA	NA	NA
STD 224	CMP	411	NA	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	ALL	15	1000	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	CMP	305	1018	NA	NA	NA	NA	NA	NA	NA
STD VC 1000	CMP	412	1012	NA	NA	NA	NA	NA	NA	NA

Table 6. Analyses of "I2" Standards: b) Chlorinated Hydrocarbons

----- JUNE, 1991 (W9) STANDARDS -----
 ----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P-XYLENE	O-XYLENE	DECANE
STD J2 R6	ALL	W9 8	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD J2 R6	ALL	W9 17	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD J2 R6	080-30G	W9 61	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD J2 R6	080-01R	W9 133	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD J2 R6	904-83G	W9 182	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
MEAN													
STD DEV													
% STD DEV													
STD J2 R5	ALL	W9 9	NA	NA	0.07	0.12	0.07	0.10	0.06	0.09	0.13	0.08	0.05
STD J2 R5	ALL	W9 18	NA	NA	0.06	0.11	0.06	0.09	0.07	0.09	0.17	0.08	0.06
STD J2 R5	131-4L	W9 37	NA	NA	0.07	0.11	0.06	0.09	0.06	0.08	0.17	0.09	0.05
STD J2 R5	080-29G	W9 86	NA	NA	0.07	0.11	0.06	0.09	0.06	0.08	0.16	0.08	0.05
STD J2 R5	ALL	W9 113	NA	NA	0.07	0.11	0.07	0.09	0.06	0.07	0.13	0.09	0.05
STD J2 R5	904-83G	W9 214	NA	NA	0.07	0.11	0.06	0.09	0.06	0.08	0.13	0.07	0.05
STD J2 R5	904-83G	W9 286	NA	NA	0.08	0.11	0.06	0.09	0.06	0.08	0.13	0.08	0.06
STD J2 R5	904-83G	W9 360	NA	NA	0.07	0.11	0.06	0.09	0.06	0.08	0.18	0.10	0.05
STD J2 R5	904-83G	W9 384	NA	NA	0.07	0.10	0.06	0.09	0.05	0.08	0.14	0.09	0.06
STD J2 R5	108-4R	W9 432	NA	NA	0.06	0.10	0.06	0.09	0.05	0.08	0.15	0.07	0.04
MEAN					0.07	0.11	0.06	0.09	0.06	0.08	0.15	0.08	0.05
STD DEV					0.01	0.01	0.00	0.00	0.00	0.00	0.02	0.01	0.00
% STD DEV					8.20	4.85	2.89	3.66	7.62	6.00	12.28	11.77	9.27
STD J2 R4	ALL	W9 10	NA	NA	0.72	1.19	0.66	1.00	0.61	0.88	1.72	0.87	0.55
STD J2 R4	ALL	W9 19	NA	NA	0.72	1.19	0.63	0.97	0.57	0.83	1.64	0.83	0.50
STD J2 R4	131-4L	W9 25	NA	NA	0.72	1.17	0.64	0.98	0.57	0.85	1.70	0.85	0.53
STD J2 R4	080-30G	W9 49	NA	NA	0.71	1.17	0.63	0.94	0.54	0.81	1.65	0.84	0.47
STD J2 R4	080-29G	W9 74	NA	NA	0.73	1.20	0.65	0.98	0.58	0.86	1.74	0.87	0.55
STD J2 R4	080-29G	W9 98	NA	NA	0.72	1.17	0.62	0.95	0.56	0.82	1.61	0.79	0.52
STD J2 R4	ALL	W9 111	NA	NA	0.70	1.14	0.62	0.95	0.54	0.80	1.57	0.82	0.46
STD J2 R4	080-01R	W9 121	NA	NA	0.72	1.17	0.62	0.96	0.54	0.81	1.61	0.77	0.45
STD J2 R4	740-G	W9 145	NA	NA	0.72	1.18	0.63	0.94	0.55	0.81	1.58	0.78	0.46
STD J2 R4	740-G	W9 170	NA	NA	0.73	1.20	0.65	0.98	0.59	0.85	1.66	0.84	0.55
STD J2 R4	904-83G	W9 194	NA	NA	0.70	1.16	0.62	0.94	0.56	0.81	1.60	0.79	0.48
STD J2 R4	904-83G	W9 226	NA	NA	0.73	1.19	0.64	0.97	0.56	0.84	1.64	0.86	0.51
STD J2 R4	904-83G	W9 250	NA	NA	0.72	1.18	0.63	0.97	0.58	0.84	1.68	0.79	0.51
STD J2 R4	904-83G	W9 274	NA	NA	0.71	1.16	0.64	0.96	0.56	0.82	1.62	0.82	0.52
STD J2 R4	904-83G	W9 300	NA	NA	0.71	1.17	0.63	0.96	0.55	0.82	1.63	0.82	0.49
STD J2 R4	904-83G	W9 324	NA	NA	0.73	1.17	0.64	0.97	0.57	0.84	1.71	0.86	0.54
STD J2 R4	904-83G	W9 348	NA	NA	0.71	1.16	0.63	0.95	0.56	0.82	1.61	0.87	0.51
STD J2 R4	904-83G	W9 372	NA	NA	0.73	1.20	0.64	1.10	0.55	0.83	1.61	0.86	0.50
STD J2 R4	904-83G	W9 393	NA	NA	0.65	1.05	0.56	1.14	0.47	0.70	1.38	0.63	0.42
STD J2 R4	904-49G	W9 420	NA	NA	0.69	1.13	0.61	0.92	0.53	0.78	1.53	0.76	0.44
MEAN					0.71	1.17	0.63	0.98	0.56	0.82	1.62	0.82	0.50
STD DEV					0.02	0.03	0.02	0.05	0.03	0.04	0.08	0.06	0.04
% STD DEV					2.53	2.80	3.24	5.32	4.76	4.34	4.68	6.76	7.58
STD J2 R3	ALL	W9 11	9.13	NA	7.18	11.77	6.47	9.90	5.89	8.59	17.09	8.61	5.40
STD J2 R3	ALL	W9 110	8.98	NA	6.95	11.46	6.16	9.44	5.40	8.02	15.73	8.02	4.63
STD J2 R3	740-G	W9 158	8.93	NA	6.99	11.50	6.27	9.58	5.66	8.28	16.41	8.29	5.10
STD J2 R3	904-49G	W9 238	8.85	NA	6.95	11.45	6.21	9.50	5.57	8.19	16.19	8.23	4.96
STD J2 R3	904-49G	W9 312	8.91	NA	6.92	11.40	6.09	9.32	5.34	7.93	15.51	7.90	4.55
STD J2 R3	904-49G	W9 408	8.57	NA	6.72	11.07	5.92	9.05	5.17	7.68	15.02	7.60	4.44

Table 7. Analyses of "J2" Standards: a) Hydrocarbons

----- JUNE, 1991 (W9) STANDARDS -----

----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
STD J2 R3	108-4R	W9 443	8.64	NA	6.82	11.25	6.13	9.37	5.57	8.14	16.20	8.18	5.10
MEAN					6.93	11.41	6.18	9.45	5.51	8.12	16.02	8.12	4.88
STD DEV					0.13	0.20	0.16	0.24	0.22	0.26	0.62	0.30	0.32
% STD DEV					1.92	1.78	2.53	2.55	3.94	3.26	3.88	3.64	6.65
STD J2 R2	ALL	W9 12	91.52	NA	72.00	118.02	64.92	99.27	59.05	86.14	171.38	86.34	52.98
STD J2 R2	ALL	W9 21	89.37	NA	69.86	114.72	62.42	95.48	55.66	81.94	161.38	82.03	48.22
STD 220	ALL	W9 7	98.85	100.18	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	ALL	W9 16	98.76	99.81	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	ALL	W9 109	97.52	97.85	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	904-83G	W9 208	96.85	97.38	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	108-4R	W9 444	96.43	96.97	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	ALL	W9 5	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	ALL	W9 14	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	ALL	W9 107	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	904-83G	W9 207	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	904-49G	W9 396	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-1027	ALL	W9 6	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-1027	ALL	W9 15	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-1027	ALL	W9 108	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA	NA

Table 7. Analyses of "J2" Standards: a) Hydrocarbons

----- JUNE, 1991 (W9) STANDARDS -----
 ----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
STD J2 R6	ALL	W9 8	NA	NA	NA	0.013	0.011	0.011	0.012	0.010
STD J2 R6	ALL	W9 17	NA	NA	NA	0.013	0.009	0.011	0.012	0.010
STD J2 R6	080-30G	W9 61	NA	NA	NA	0.013	0.009	0.011	0.012	0.010
STD J2 R6	080-01R	W9 133	NA	NA	NA	0.012	0.009	0.011	0.011	0.009
STD J2 R6	904-83G	W9 182	NA	NA	NA	0.012	0.009	0.011	0.011	0.010
MEAN						0.013	0.009	0.011	0.012	0.010
STD DEV						0.000	0.001	0.000	0.000	0.000
% STD DEV						3.888	8.511	0.000	4.223	4.082
STD J2 R5	ALL	W9 9	NA	NA	0.14	0.131	0.105	0.109	0.117	0.103
STD J2 R5	ALL	W9 18	NA	NA	0.14	0.131	0.104	0.110	0.118	0.101
STD J2 R5	131-4L	W9 37	NA	NA	0.15	0.134	0.108	0.112	0.119	0.101
STD J2 R5	080-29G	W9 86	NA	NA	0.14	0.131	0.105	0.112	0.118	0.100
STD J2 R5	ALL	W9 113	NA	NA	0.14	0.124	0.101	0.107	0.112	0.094
STD J2 R5	904-83G	W9 214	NA	NA	0.15	0.125	0.116	0.109	0.114	0.096
STD J2 R5	904-83G	W9 286	NA	NA	0.15	0.126	0.109	0.111	0.116	0.098
STD J2 R5	904-83G	W9 360	NA	NA	0.15	0.125	0.109	0.110	0.115	0.097
STD J2 R5	904-83G	W9 384	NA	NA	0.15	0.124	0.103	0.109	0.116	0.099
STD J2 R5	108-4R	W9 432	NA	NA	0.14	0.116	0.098	0.102	0.109	0.092
MEAN					0.14	0.127	0.106	0.109	0.115	0.098
STD DEV					0.00	0.005	0.005	0.003	0.003	0.003
% STD DEV					2.65	3.718	4.280	2.423	2.400	3.148
STD J2 R4	ALL	W9 10	NA	1.62	1.34	1.308	1.046	1.086	1.174	1.041
STD J2 R4	ALL	W9 19	NA	1.60	1.36	1.294	1.040	1.078	1.152	1.007
STD J2 R4	131-4L	W9 25	NA	1.65	1.39	1.313	1.055	1.094	1.167	1.019
STD J2 R4	080-30G	W9 49	NA	1.67	1.37	1.297	1.061	1.096	1.139	0.981
STD J2 R4	080-29G	W9 74	NA	1.57	1.40	1.306	1.071	1.107	1.169	1.025
STD J2 R4	080-29G	W9 98	NA	1.64	1.38	1.276	1.050	1.087	1.138	0.991
STD J2 R4	ALL	W9 111	NA	1.60	1.34	1.233	1.022	1.059	1.122	0.963
STD J2 R4	080-01R	W9 121	NA	1.64	1.37	1.257	1.045	1.085	1.133	0.969
STD J2 R4	740-G	W9 145	NA	1.67	1.45	1.296	1.098	1.120	1.166	0.995
STD J2 R4	740-G	W9 170	NA	1.67	1.48	1.297	1.093	1.123	1.192	1.036
STD J2 R4	904-83G	W9 194	NA	1.67	1.41	1.255	1.051	1.092	1.146	0.990
STD J2 R4	904-83G	W9 226	NA	1.67	1.48	1.286	1.092	1.123	1.183	1.019
STD J2 R4	904-83G	W9 250	NA	1.65	1.49	1.277	1.082	1.115	1.189	1.026
STD J2 R4	904-83G	W9 274	NA	1.69	1.45	1.259	1.067	1.104	1.165	1.007
STD J2 R4	904-83G	W9 300	NA	1.63	1.45	1.258	1.066	1.103	1.165	1.005
STD J2 R4	904-83G	W9 324	NA	1.70	1.47	1.261	1.069	1.105	1.186	1.031
STD J2 R4	904-83G	W9 348	NA	1.63	1.45	1.250	1.058	1.100	1.165	1.003
STD J2 R4	904-83G	W9 372	NA	1.71	1.46	1.255	1.070	1.110	1.168	0.999
STD J2 R4	904-83G	W9 393	NA	1.58	1.29	1.141	1.000	1.018	1.027	0.865
STD J2 R4	904-49G	W9 420	NA	1.63	1.39	1.190	1.014	1.059	1.131	0.961
MEAN				1.64	1.41	1.265	1.058	1.093	1.154	0.997
STD DEV				0.04	0.05	0.041	0.025	0.025	0.035	0.038
% STD DEV				2.24	3.85	3.21	2.36	2.26	3.05	3.79
STD J2 R3	ALL	W9 11	NA	16.41	13.64	13.100	10.500	10.901	11.700	10.291
STD J2 R3	ALL	W9 110	NA	16.19	13.66	12.464	10.312	10.741	11.316	9.599
STD J2 R3	740-G	W9 158	NA	16.11	13.91	12.611	10.439	10.680	11.607	10.019
STD J2 R3	904-49G	W9 238	NA	16.19	13.91	12.451	10.372	10.491	11.587	9.998
STD J2 R3	904-49G	W9 312	NA	16.14	13.89	12.421	10.399	10.489	11.426	9.442
STD J2 R3	904-49G	W9 408	NA	15.85	13.62	11.663	9.815	9.912	11.194	9.440

Table 7. Analyses of "J2" Standards: b) Chlorinated Hydrocarbons

----- JUNE, 1991 (W9) STANDARDS -----
 ----- GAS CONCENTRATIONS (PPMV) -----

STANDARD NAME	AREA	GC CYCLE	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRICLORO ETHYLENE	TETRA CHLORO ETHYLENE
STD J2 R3	108-4R	W9 443	NA	15.96	13.94	11.882	9.960	10.064	11.543	9.571
MEAN				16.12	13.80	12.370	10.257	10.468	11.482	9.766
STD DEV				0.17	0.14	0.439	0.243	0.334	0.165	0.310
% STD DEV				1.03	0.99	3.55	2.37	3.19	1.44	3.17
STD J2 R2	ALL	W9 12	NA	164.57	99.31	131.799	105.789	109.312	117.380	103.240
STD J2 R2	ALL	W9 21	NA	161.31	97.51	129.530	103.775	104.813	113.081	98.709
STD 220	ALL	W9 7	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	ALL	W9 16	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	ALL	W9 109	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	904-83G	W9 208	NA	NA	NA	NA	NA	NA	NA	NA
STD 220	108-4R	W9 444	NA	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	ALL	W9 5	10.1	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	ALL	W9 14	10.5	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	ALL	W9 107	10.0	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	904-83G	W9 207	9.9	NA	NA	NA	NA	NA	NA	NA
STD VC-10.3	904-49G	W9 396	10.1	NA	NA	NA	NA	NA	NA	NA

Table 7. Analyses of "J2" Standards: b) Chlorinated Hydrocarbons

----- SAVANNAH RIVER SITE -----
 ----- LIGHT HYDROCARBON STANDARD ANALYSIS FOR 740-G LANDFILL -----

STANDARD TYPE	DATE ANALYZED	METHANE PPB	ETHANE PPB	PROPANE PPB	1-BUTANE PPB	N-BUTANE PPB	ETHYLENE PPB	PROPYLENE PPB
STD M	11-11-90	10060	1006	1003	988	937	1011	1012
STD M	11-11-90	10088	1013	1007	1000	966	1017	1018
STD M	11-11-90	10229	1010	1016	977	922	1016	1016
STD M	11-11-90	10049	1009	1004	987	954	1010	1008
STD M	11-12-90	10056	1007	1003	1001	979	1008	1004
STD M	11-12-90	10014	1005	1002	996	973	1006	1010
STD M	11-13-90	10311	1027	1032	1018	998	1031	1032
STD M	11-13-90	10342	1041	1043	1047	1040	1049	1035
STD M	11-13-90	10323	1035	1034	1029	995	1041	1042
STD M	11-13-90	10421	1049	1046	1053	1030	1055	1049
STD M	11-13-90	10446	1047	1050	1041	1019	1055	1046
STD M	11-15-90	10000	1000	1000	1000	1000	1000	1000
STD M	11-15-90	9916	1005	993	994	976	1006	1003
STD M	11-15-90	9898	1000	994	993	977	995	1001
STD M	11-16-90	9926	994	990	989	977	993	992
STD M	11-16-90	9859	994	988	992	980	986	992
STD M	11-16-90	9809	991	985	1005	1025	986	995
STD M	11-16-90	9937	998	993	994	996	997	993
STD M	11-17-90	9927	994	991	986	975	992	992
STD M	11-17-90	9837	991	985	1012	1037	987	990
STD M	11-17-90	9884	989	983	985	972	988	987
STD M	11-17-90	9858	987	984	976	952	983	990
STD M	11-17-90	9943	994	995	986	991	1003	999
STD M	11-18-90	9982	993	992	976	954	991	998
STD M	11-18-90	9826	989	983	983	977	982	984
STD M	11-18-90	10685	1095	1174	1058	983	1111	1186
STD M	12-10-90	9562	958	958	908	841	995	1008
STD M	12-10-90	9563	958	958	912	844	996	1011
STD M	12-10-90	10000	1000	1000	1000	1000	1000	1000
STD M	12-10-90	10147	1018	1016	1031	1061	1019	1014
STD M	12-10-90	10110	1018	1017	1003	988	1016	1015
STD M	12-10-90	10112	1016	1017	1052	1095	1014	1022
STD M	12-10-90	10078	1010	1011	1010	1000	1012	1010
AVERAGE		10036	1007	1007	999	982	980	983
STD DEV		234	25	36	32	49	175	177
% STD DEV		2.33	2.52	3.61	3.24	5.02	17.88	18.03
STD 224	11-11-90	1045500	1058200	1027900	NA	1004800	NA	NA
STD 224	11-12-90	1036100	1045900	1015400	NA	1021800	NA	NA
STD 224	11-12-90	1028500	1037100	1007100	NA	1066700	NA	NA
STD 224	11-13-90	1040600	1050300	1020700	NA	1030900	NA	NA
STD 224	11-13-90	1064600	1074400	1043500	NA	1054500	NA	NA
STD 224	11-13-90	998520	1003100	971300	NA	1004500	NA	NA
STD 224	11-17-90	981370	982290	949890	NA	987410	NA	NA
STD 224	11-18-90	1018300	1027900	997360	NA	974470	NA	NA
AVERAGE		1026686	1034899	1004144		1018135		
STD DEV		24985	28049	28703		29732		
% STD DEV		2.43	2.71	2.86		2.92		

Table 8. Light Hydrocarbon Analyses of All Standards "M" and "224"

This page intentionally left blank.

----- WESTINGHOUSE SAVANNAH RIVER SITE -----
 ----- MINIMUM DETECTION LEVELS (W2,W3,W9 DATA SETS) ---
 ----- AREA REJECT = 40, CONCENTRATIONS IN PPMV -----

COMPOUND NAME	IDEAL M.D.L.	ACTUAL M.D.L.
VINYL CHLORIDE	0.10	1.0
PENTANE	0.040	0.070
HEXANE	0.033	0.070
METHYLENE CHLORIDE	0.03	1.0
TRANS 1,2 DICHLORO CHLOROFORM	0.011	0.020
111 TRICHLOROETHANE	0.00019	0.005
CARBON TETRACHLORIDE	0.00007	0.005
HEPTANE	0.00004	0.005
BENZENE	0.026	0.070
TRICHLOROETHYLENE	0.032	0.070
OCTANE	0.00015	0.005
TOLUENE	0.023	0.070
TETRACHLOROETHYLENE	0.028	0.070
NONANE	0.00005	0.005
ETHYL BENZENE	0.021	0.070
M&P-XYLENE	0.024	0.070
O-XYLENE	0.025	0.070
DECANE	0.024	0.070
	0.020	0.070

Table 9. Minimum Detection Levels

This page intentionally left blank.

----- SAVANNAH RIVER SITE -----
 ----- SOIL GAS SYSTEM BLANKS -- LANDFILL DATA DIRECTORIES -----
 ----- GAS CONCENTRATIONS (PPMV) -----

SAMPLE NAME		PENTANE	HEXANE	HEPTANE	BENZENE	OCTANE	TOLUENE	NONANE	ETHYL BENZENE	M&P- XYLENE	O- XYLENE	DECANE
740-G SYS BLK 1	1	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
740-G SYS BLK 2	2	ND	ND	ND	ND	ND	ND	0.035	ND	ND	ND	0.023
740-G SYS BLK 3	3	ND	ND	ND	ND	ND	0.053	ND	ND	ND	ND	ND
740-G SYS BLK 4	4	ND	ND	ND	ND	ND	0.027	0.034	ND	0.027	ND	0.024
740-G SYS BLK 5	5	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
740-G SYS BLK 6	6	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
740-G SYS BLK 7	7	0.054	ND	ND	ND	ND	0.046	ND	0.029	0.075	ND	0.027
740-G SYS BLK 8	8	0.055	0.083	0.059	ND	0.085	0.084	0.063	0.030	0.118	0.026	0.080
740-G SYS BLK 9	9	ND	ND	ND	ND	ND	0.032	ND	0.028	0.088	ND	0.019
740-G SYS BLK 10	10	0.100	0.059	ND	ND	ND	0.074	ND	0.047	0.130	0.031	0.041
740-G SYS BLK 11	11	0.098	0.194	ND	0.051	0.049	0.308	0.024	0.086	0.300	0.067	ND
740-G SYS BLK 12	12	ND	ND	ND	ND	ND	ND	ND	0.028	0.076	ND	ND
740-G SYS BLK 13	13	ND	ND	ND	ND	ND	0.047	ND	0.032	0.079	ND	ND
740-G SYS BLK 14	14	ND	0.043	ND	ND	ND	0.084	0.066	0.064	0.134	ND	0.058
740-G SYS BLK 15	15	ND	ND	ND	ND	ND	0.041	ND	0.028	0.082	0.033	0.025
740-G SYS BLK 16	16	0.056	0.038	ND	ND	ND	0.024	ND	ND	0.058	ND	ND
740-G SYS BLK 17	17	ND	ND	ND	ND	ND	ND	ND	ND	0.056	ND	ND
740-G SYS BLK 18	18	ND	ND	ND	ND	ND	ND	ND	ND	0.037	ND	ND
740-G SYS BLK 19	19	ND	ND	ND	ND	ND	ND	ND	ND	0.059	ND	ND
740-G SYS BLK 20	20	ND	ND	ND	ND	ND	ND	ND	ND	0.042	ND	ND
740-G SYS BLK 21	21	ND	ND	ND	ND	ND	ND	ND	ND	0.052	ND	ND
740-G SYS BLK 22	22	ND	ND	ND	ND	ND	ND	ND	ND	0.042	ND	ND
740-G SYS BLK 23	23	ND	ND	ND	ND	ND	ND	0.029	ND	0.026	ND	0.054
740-G SYS BLK 24	24	ND	ND	ND	ND	ND	ND	ND	ND	0.029	ND	0.051
740-G SYS BLK 25	25	ND	ND	ND	ND	ND	ND	ND	ND	0.169	0.100	0.079
740-G SYS BLK 26	26	ND	ND	ND	ND	ND	ND	ND	ND	0.034	ND	0.031
740-G SYS BLK 27	27	ND	ND	ND	ND	ND	ND	ND	ND	0.032	ND	ND
740-G SYS BLK 28	28	ND	ND	ND	ND	ND	0.100	ND	ND	ND	ND	0.043
740-G SYS BLK 29	29	ND	ND	ND	ND	0.226	ND	ND	ND	0.036	ND	0.034
740-G SYS BLK 30	30	ND	ND	ND	ND	ND	ND	ND	ND	0.025	ND	ND
740-G SYS BLK 31	31	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
740-G SYS BLK 32	32	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
740-G SYS BLK 33	33	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
740-G SYS BLK 34	34	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
AVERAGE		0.045	0.040	0.027	0.033	0.032	0.045	0.025	0.029	0.060	0.028	0.029
STD DEV		0.014	0.028	0.006	0.003	0.036	0.050	0.011	0.013	0.056	0.015	0.016
AVG+2STD DEV		0.073	0.097	0.038	0.039	0.103	0.144	0.046	0.054	0.172	0.057	0.062

Table 10. System Blanks for All Sanitary Landfill Data Directories: a) Hydrocarbons

----- SAVANNAH RIVER SITE -----
 ----- SOIL GAS SYSTEM BLANKS -- LANDFILL DATA DIRECTORIES -----
 ----- GAS CONCENTRATIONS (PPMV) -----

SAMPLE NAME	VINYL CHLORIDE	METHYLENE CHLORIDE	TRANS 1,2 DICHLORO ETHYLENE	CHLORO FORM	111 TRI CHLORO ETHANE	CARBON TETRA CHLORIDE	TRI CHLORO ETHYLENE	TETRA CHLORO ETHYLENE	FILE CYCLE
740-G SYS BLK 1	ND	ND	ND	ND	0.00200	ND	ND	ND	W2 17
740-G SYS BLK 2	ND	ND	ND	ND	0.00200	ND	ND	0.00100	W2 26
740-G SYS BLK 3	ND	0.378	ND	ND	0.00700	ND	ND	0.00200	W2 38
740-G SYS BLK 4	ND	ND	ND	ND	0.00300	ND	0.01000	0.01300	W2 50
740-G SYS BLK 5	ND	0.495	ND	ND	0.00900	ND	ND	0.00400	W2 62
740-G SYS BLK 6	0.121	ND	ND	ND	0.00400	ND	ND	0.00200	W2 75
740-G SYS BLK 7	0.102	0.354	ND	ND	0.00500	ND	0.01900	0.00200	W2 85
740-G SYS BLK 8	0.191	ND	ND	ND	0.00100	ND	0.00300	ND	W2 98
740-G SYS BLK 9	0.248	0.489	ND	ND	0.00500	ND	0.00100	0.00100	W2 109
740-G SYS BLK 10	0.451	ND	ND	ND	0.00300	ND	0.03900	0.00200	W2 122
740-G SYS BLK 11	0.169	0.798	ND	ND	0.01100	ND	0.04400	0.01600	W2 134
740-G SYS BLK 12	0.185	0.350	ND	ND	0.00400	ND	0.00100	0.00100	W2 157
740-G SYS BLK 13	ND	0.332	ND	ND	0.00400	ND	0.00100	0.00100	W2 170
740-G SYS BLK 14	0.120	0.567	ND	ND	0.00600	ND	0.02200	0.05300	W2 188
740-G SYS BLK 15	0.156	0.620	ND	0.00100	0.00500	ND	0.00200	0.05300	W2 200
740-G SYS BLK 16	0.147	0.370	ND	ND	0.00300	ND	0.00300	0.00300	W2 212
740-G SYS BLK 17	0.147	0.309	ND	ND	0.00600	ND	0.00100	ND	W2 224
740-G SYS BLK 18	ND	ND	ND	ND	0.00400	ND	0.00100	0.00100	W2 236
740-G SYS BLK 19	ND	0.264	ND	ND	0.00300	ND	ND	ND	W2 248
740-G SYS BLK 20	ND	ND	ND	ND	0.02300	ND	0.00200	0.00300	W2 262
740-G SYS BLK 21	0.123	0.307	ND	ND	0.00400	ND	ND	0.00100	W2 274
740-G SYS BLK 22	ND	0.011	ND	ND	0.01000	ND	0.00300	0.00600	W2 285
740-G SYS BLK 23	0.414	0.462	ND	ND	0.00500	ND	0.00100	0.00100	W2 297
740-G SYS BLK 24	0.250	ND	ND	ND	0.00200	ND	ND	ND	W2 309
740-G SYS BLK 25	0.727	0.567	ND	ND	0.00400	ND	ND	ND	W2 320
740-G SYS BLK 26	0.309	ND	ND	ND	0.00200	ND	ND	0.00100	W3 17
740-G SYS BLK 27	ND	ND	ND	ND	0.00500	ND	ND	ND	W3 28
740-G SYS BLK 28	0.246	0.239	ND	ND	0.00200	ND	ND	0.00100	W3 41
740-G SYS BLK 29	2.172	0.250	ND	ND	0.00300	ND	ND	ND	W3 53
740-G SYS BLK 30	2.591	0.655	ND	ND	0.00300	ND	0.00100	ND	W3 93
740-G SYS BLK 31	ND	0.279	ND	ND	0.00400	ND	ND	0.00200	W3 102
740-G SYS BLK 32	0.614	0.231	0.031	ND	0.00100	ND	ND	ND	W9 144
740-G SYS BLK 33	0.890	0.269	0.033	ND	0.00100	ND	ND	ND	W9 156
740-G SYS BLK 34	0.854	0.330	0.019	ND	0.00200	ND	ND	ND	W9 169
AVERAGE	0.366	0.272	0.012	0.00021	0.00465	0.00004	0.00460	0.00502	
STD DEV	0.551	0.218	0.005	0.00014	0.00397	0.00000	0.01047	0.01247	
AVG+2STD DEV	1.467	0.707	0.023	0.00049	0.01259	0.00004	0.02553	0.02996	

Table 10. System Blanks for All Sanitary Landfill Data Directories: b) Chlorinated Hydrocarbons

Appendix I

Sampling Method SM1

Sampling Method SM4

Analytical Method AM1

Analytical Method AM4

Analytical Method AM8

Standard Preparation Method SP3

This page intentionally left blank.

SAMPLING METHOD SM1

SOIL GAS PROBE SAMPLING

1.0 Scope and Application

1.1 Soil gas probe samples are collected with Microseeps unique, portable soil gas sampling probe which permits access to any area. In addition, the probe allows unlimited purging between sample sites and incorporates the capability to discard the volume of air in the sample probe before the soil gas sample at each site is taken.

2.0 Apparatus

2.1 Soil Gas Probe: The soil gas probe consists of a 1/2 inch diameter steel tube equipped with a rubber packer and a 1/8" o.d. ss sample tube inserted concentrically to the bottom of the 1/2" diameter tube to minimize dead space in the sample volume. The 1/8" o.d. sample tube is connected through a three way valve to a 250 cc gas tight syringe mounted as an integral part of the sample probe. The third port of the three-way valve is terminated with a syringe needle and serves two functions: first a small amount of gas equal to or larger than the dead space volume of the 1/8" o.d. sample tube is discarded through this port before each soil gas sample is taken; second, the syringe needle serves to facilitate transfer of the soil gas sample through a rubber septum into a previously evacuated sample vial, minimizing the possibility of contamination of any sample.

2.2 Slide Hammer Plunger Bar: The slide hammer plunger bar contains a 5.5 ft. x .5 in rod with a 9/16 inch ball. Fitted over one end of the rod is a weighted slide hammer. (Heath Consultants cat# 478).

2.3 Sample vials: The sample vials used are determined by the analytical method that is required for analysis. All vials should be free of interferences and meet the specifications described in the analytical method to be used.

3.0 Procedure

3.1 Prior to any sampling, the soil gas sampling probe should be purged clean of interferences, the syringe needle should be removed, and the three way valve should be in the stop flow position.

3.2 A 9/16 inch diameter hole is created to the desired depth using the slide hammer plunger bar.

3.3 The plunger bar is removed and the sample probe is inserted into the hole. A seal should be obtained to prevent ambient air from entering the hole when the soil gas sample is removed.

3.4 The three way valve is turned to the probe/syringe position.

3.5 A 10 cc volume of gas is drawn into the syringe.

3.6 The three way valve is turned to the syringe/needle position (needle removed as described in section 3.1) and the 10 cc sample is discarded.

3.7 The three way valve is turned to the probe/syringe position and the appropriate amount of soil gas is drawn into the syringe.

3.8 The three way valve is turned to the stop flow position

3.9 The needle is attached to the probe needle fitting.

3.10 An evacuated sample vial is attached by inserting the sample vial septum onto the needle.

3.11 The three way valve is turned to the syringe/needle position. The volume of the evacuated vial will be drawn into the sample vial. Additional volume (positive pressure) can then be added by depressing the plunger and displacing the remaining volume in the syringe.

3.12 The sample vial should be quickly removed once desired volume is displaced.

3.13 A volume of approximately 50 cc of ambient air should be drawn back through the needle.

3.14 Remove the needle.

3.15 Remove the sample probe from the hole.

3.16 Purge the sample probe clean of interferences by filling and exhausting the syringe five times before taking the next sample.

4.0 Sample Documentation

4.1 All samples should be labeled immediately after collection with the following information:

1. Site number
2. Daily sequence number
3. Date and time
4. Samplers initials
5. Project

4.2 All samples taken in the field by Microseeps, Ltd. should be entered onto a Field Log Sheet. For each sample, the following entries will be made:

1. Site number
2. Daily sequence number
3. Date and time
4. Samplers initials
5. Project
6. Location
7. Sample description
8. Miscellaneous comments

4.3 When appropriate, samples will be security sealed and chain of custody records will be maintained.

5.0 Safety Precautions

5.1 Do not use a mechanical device to depress the sampling syringe plunger.

5.2 Do not attempt to collect soil gas probe samples without prior knowledge of the location of underground utilities and other possible environmental hazards.

5.3 Always cap or remove the soil gas probe syringe needle when transporting or handling the soil gas probe.

6.0 Preventive Maintenance

6.0 The soil gas sample probe should be cleaned when necessary or at the end of each day with soap and organic free water. It is especially important to keep the gas sampling syringe clean from fine soil particles as the particles will quickly deteriorate the teflon/glass plunger seal.

6.1 The glass wool filter plug (located in the probe tip) should be changed often and the probe tip should be kept clear of soil.

This page intentionally left blank.

SAMPLING METHOD SM4

SOIL PLUG SAMPLING FOR MERCURY

Soil plugs of 6 inches in length are collected between the depths of 12 and 18 inches. A 1.25 inch stainless steel pipe is driven 12 inches, removed from the hole and the 12 inch core discarded. The pipe is re-inserted into the hole and the 6 inch soil plug is obtained between 12 and 18 inches.

A portion of this six inch soil plug is then placed directly into a plastic sample bag and labeled. A duplicate sample is collected for every 10 sites.

A field collection log is maintained which lists the sample name, date and time of collection, collection sequence number, sample depth, sample type, and comments.

This page intentionally left blank.

ANALYTICAL METHOD AM1

ANALYSIS OF C₁-C₄ HYDROCARBONS, HYDROGEN, HELIUM, IN SOIL GAS

1.0 Scope and Application

1.1 Method AM1 is used to determine the concentration of C₁-C₄ hydrocarbons, helium and hydrogen in soil gas samples. Specifically, Method AM1 may be used to detect the following substances:

- methane
- ethane
- ethylene
- propane
- propylene
- i-butane
- n-butane
- helium
- hydrogen

1.2 This method is recommended for use by, or under the supervision of, analysts experienced in the operation of gas chromatographs and in the interpretation of chromatograms.

2.0 Summary of Method

2.1 Analysis of the above constituents of free soil gas is accomplished with a custom chromatograph, built by Microseeps. The custom, dual detector gas chromatograph provides a sequential output from two detectors. First, the C₁-C₄ hydrocarbons are detected with a flame ionization detector (FID), next helium and hydrogen are detected with a thermal conductivity detector (TCD). The sample (and standard calibration gas) is flowed through the gas chromatograph and introduced into the columns by the mechanical injection of two sample loops.

3.0 Interferences

3.1 Contamination by carryover can occur whenever high-level and low-level samples are sequentially analyzed. A non-restricted flow of pure nitrogen from a 10 psig source should be purged for 30 seconds through the sample loops prior to all analyses.

3.2 The analyst should demonstrate the absence of contamination by carryover by analysis of the contents of the sample loops when purged with nitrogen. This demonstration should be performed prior to the

analysis of a sample set and when carryover contamination is suspected (after high samples). In the event that 'ghost peaks' (peaks similar to previous sample) appear when a pure nitrogen sample is analyzed, measures should be taken to eliminate the carryover contamination.

3.3 Extra peaks in a chromatogram can be actual peaks from a previous run. Contamination from late eluting peaks can occur when injection to injection time is too short. The dual gas chromatograph is set up in the backflush pre-column valve arrangement to minimize this interference.

3.4 The analyst should be certain that all peaks have eluted from the previous analysis prior to analyzing any sample or standard. If samples or standard chromatograms contain suspected 'extra peaks' the sample should again be analyzed after a clean baseline is established.

4.0 Apparatus and Materials

4.1 Sample vials: 125 ml glass vials (Wheaton #223748 or equivalent). Vials should be free of hydrocarbons, helium, and hydrogen prior to use. This can be accomplished by heating to 100 degrees C followed by purging with pure nitrogen.

4.2 Septums: Butyl rubber septums (Wheaton #224154 or equivalent) may be used provided vials are capped within two weeks prior to use. Other septums may be used, provided they are gas tight and do not produce interferences.

4.3 Gas Chromatograph: The chromatograph is equipped with two sets of the following: column oven, pre-column, analytical column, detector, injection port, sample valve and sample loop. The column and detector for determination of C₁-C₄ hydrocarbons are a granular 3 ft. x 3/16 in. alumina analytical column and a flame ionization detector. The alumina column is protected against contamination by heavy organics by a 3 in. x 3/16 in. pre-column which is back-flushed after butanes have entered the analytical column. This arrangement allows rapid turn-around for consecutive analyses and a clean baseline for accurate, reproducible results. The flame ionization detector is of a special design which allows considerably more sensitivity than commercially available models. In a laboratory setting, noise levels are commonly at the 500 ppt level. Although, these sensitivities are rarely realized in the field, 1 to 2 ppb is achievable and 5 ppb is routine. Hydrogen and helium, are simultaneously determined using a 3 ft. x 3/16 in. molecular sieve 5A (80/100 mesh) pre-column and 10 ft. x 3/16 in. analytical column connected to a thermal conductivity detector. Injection times and the signal output are sequenced so that the output of the two detectors is displayed in a single continuous chromatogram.

4.4 Data Collection: The output of the chromatograph is directed to a chart recorder and a Hewlett Packard (HP-3392A) Networking Integrator

5.0 Sample Preparation and Analysis

5.1 Sample vial preparation: All sample vials should meet specifications as noted in sections 4.1 and 4.2 above. Vials should be tightly capped and evacuated to a pressure of less than 100 millitorr. The vial septum should be punctured with needles of 22 gauge or smaller.

5.2 The evacuated sample vials should be filled with sample gas to a pressure of 9 psig. A positive pressure capable of delivering at least 25 cc of sample must be available per each injection.

5.3 The pressurized sample vial is connected to the sample loops through a needle fitting and flow control valve. The flow is monitored by a flow meter connected to the out port on the gas chromatograph.

5.4 After the appropriate volume of sample (minimum 25 cc) has been flushed through the sample loops of the gas chromatograph, the injection valves may be activated. This is accomplished by switching on the cycle timer.

6.0 Calibration

6.1 The standard calibration gas should be introduced in the same manner as described in section 5.4 above. Measured peak areas are converted to concentrations in parts per million by volume using certified commercial gas standards traceable to NBS standards. (Matheson Gas Products Inc., or Scott Specialty Gases). The sample concentrations are calculated from calibration points near the concentration level of the sample.

6.2 At the beginning of a project or sample set, standards of appropriate calibration ranges will be run at least three times or until the results agree with a percent standard deviation no greater than 10%.

6.3 The instrument response (for any one subsequent standard in section 6.5 above) must not vary by more than 20%; or any two consecutive standards must not vary by more than 15% from the mean of the three previous standards.

7.0 Quality Control

7.1 If the parameters set forth in section 6.3 are not met, the analytical program will be terminated until the cause is determined and a solution is effected. The cause and the solution will be recorded in the Laboratory Notebook and signed by the operator, before the analytical program is resumed.

7.2 Before and during sample analysis, instrument blanks (sample loops filled with flush nitrogen) should be analyzed to assure the absence of interferences as described in section 3.0 above.

7.3 Standards analyzed during the course of analyzing samples are averaged into the calibration table as well as being used for peak identification. All chromatograms should be examined by an experienced analyst.

7.4 Throughout analysis the soil gas samples are injected mechanically to achieve a uniform sample size from a flow directly from the soil gas sample vial which has been pressured at the time of sampling. This pressuring preserves sample integrity since any leakage is out of the vial and does not result in contamination or sample dilution.

7.5 Calibration records are generated and stored. All such records will be maintained in the laboratory during the course of the project.

8.0 Instrument Conditions

8.1 Gas Chromatograph:

- Injection Temp. ambient
- Flame Ionization Detector Temp. ambient
- Thermal Conductivity Detector Temp. 45 deg. C.
- C1-C4 Oven Temp. 100 deg. C. isothermal
- Helium/Hydrogen Oven Temp. 45 deg. C. isothermal
- Initial T.C.D. Signal Range 10
- Initial F.I.D. Signal Range 10E9
- Carrier Gas Regulator Pressures:
 - T.C.D. 40 psig.
 - F.I.D. 17 psig.
- Hydrogen Pressure 22 psig.
- Flame Air Pressure 30 psig. (1.0 scfh)

ANALYTICAL METHOD AM4

ANALYSIS OF VOLATILE ORGANIC COMPOUNDS IN SOIL GAS

1.0 Scope and Application

1.1 Method AM4 is used to determine the concentration of volatile organic compounds in soil gas samples. Specifically, Method AM4 may be used to detect the following compounds:

pentane	benzene
hexane	toluene
heptane	m & p-xylene
octane	o-xylene
nonane	ethyl benzene
methane	
vinyl chloride	
1,1-dichloroethylene	
methylene chloride	
1,1-dichloroethane	
1,2-dichloroethane	
trans 1,2-dichloroethylene	
chloroform	
1,1,1-trichloroethane	
carbon tetrachloride	
trichloroethylene	
tetrachloroethylene	

1.2 This method is recommended for use by, or under the supervision of, analysts experienced in the operation of a gas chromatograph and in the interpretation of a chromatogram.

2.0 Summary of Method

The volatile organic compounds are analyzed using a Hewlett Packard Model 5890A Gas Chromatograph in conjunction with a Hewlett Packard Model 19395A Automated Headspace Sampler and an H.P. 3396A Networking Integrator. A Supelco, 60M x 0.75mm i.d. Vocol, wide bore capillary column is used in conjunction with an output splitter connected to an electron capture detector and a flame ionization detector. The integrator is interfaced to an IBM microcomputer for data storage and processing. Data transfer and analyses are facilitated using a chromatography data system (Chrom Perfect, Justice Innovations).

3.0 Interferences

3.1 Contamination by carryover can occur whenever high-level and low-level samples are sequentially analyzed. While in the standby mode, the HP 19395A provides continuous flushing of the sample loop and sample valve between sample analyses. This flush flow should be maintained and the sample valve and loop should be kept heated.

3.2 The analyst should demonstrate the absence of carryover contamination by analysis of the contents of the sample loop when purged with pure nitrogen. This demonstration should be performed prior to the analysis of a sample set and when carryover contamination is suspected (after high samples). In the event that 'ghost peaks' (peaks similar to previous sample) appear when a pure nitrogen sample is analyzed measures should be taken to eliminate the carryover contamination.

3.3 Extra peaks in a chromatogram can be actual peaks from a previous run. Contamination from compounds eluting late in the chromatogram can occur when injection to injection time is too short. The HP 5890A is equipped with a temperature programmable oven which can be utilized to minimize this interference.

3.4 The analyst should be certain that all peaks have eluted from the previous analysis prior to analyzing any sample or standard. This can be accomplished by elevating the oven temperature after an analysis until such time that a clean stable baseline is obtained. If samples or standard chromatograms contain suspected 'extra peaks' the sample should be reanalyzed after a clean baseline is established.

4.0 Materials and Equipment

4.1 Sample vials: 22 ml glass vials (Hewlett Packard #9301-0716 or equivalent). Vials should be free of chlorinated hydrocarbons prior to use. This can be accomplished by washing and rinsing with hydrocarbon free water then heating to 100 degrees C for 1 hour followed by purging with pure nitrogen.

4.2 Septums: Teflon lined septums (Wheaton #224168 or equivalent) may be used provided vials are capped within two weeks prior to use. Other septums may be used provided they are gas tight and do not produce interferences.

4.3 Gas Chromatograph: The Hewlett Packard 5890A Gas Chromatograph is equipped with a Supelco, 60M x 0.75mm i.d. Vocol, wide bore capillary column connected to an electron capture detector and flame ionization detector.

4.4 Headspace Sampler: A Hewlett Packard Model 19395A Automated Headspace Sampler is used which contains a heated bath with 24 slots for headspace vials, a heated sample valve, a heated sample loop and a heated transfer line to facilitate transfer of the sample onto the column in the gas chromatograph.

4.5 Data Collection: The output of the chromatograph is directed to a chart recorder and a Hewlett Packard (HP-3396A) Networking Integrator which passes the processed data to a microcomputer for data storage and/or further processing.

5.0 Sample Preparation and Analysis

5.1 Sample vial preparation: All sample vials should meet specifications as noted in sections 4.1 and 4.2 above. Vials should be tightly capped and evacuated to a pressure of less than 100 millitorr. The vial septum should be punctured only with needles of 22 gauge or smaller.

5.2 The evacuated sample vials should be filled with sample or standard gas to a positive gauge pressure. Sample vials should be used (filled with sample) within two weeks of preparation.

5.3 The 22 cc sample vials are placed directly into the heated headspace sampling unit for a minimum of 90 minutes prior to injection.

5.4 The headspace sampling unit is programmed to mechanically puncture the septum, transfer the sample to the heated sample loop, and mechanically inject the sample into the column flow stream via the heated transfer line.

6.0 Standards and Calibrations

6.1 Gas standards or liquid standards may be used to achieve calibrations. In some situations it may be necessary to use both types of standards. Certified commercial gas standards are most desirable, but may not always be available for all the compounds or for the concentration levels of the compounds of interest.

6.2 Commercial gas standards are introduced by filling a 22ml headspace vial with standard gas. The gas standards are placed in the vials and analyzed in the same manner as samples (as described in section 5.0). The concentrations are those certified by the manufacturer.

6.3 Liquid standard solutions are injected directly into a capped vial and allowed to vaporize. These standards are produced from high purity compounds as described in Standard Preparation Method SP1. The liquid standard solutions are placed in vials that meet specifications described in sections 4.1 and 4.2. The vials

used must be capped and be at atmospheric pressure when the liquid standard is injected. The vial is then analyzed in the same manner as a sample as described in section 5.3.

6.4 At the beginning of a project or sample set, standards of appropriate calibration ranges will be run at least three times or until the results agree with a percent standard deviation no greater than 10%.

6.5 Thereafter, at least one standard will be run for every 10 samples.

6.6 The instrument response (for any one subsequent standard in section 6.5 above) must not vary by more than 20%; or any two consecutive standards must not vary by more than 15% from the mean of the three previous standards.

7.0 Quality Control

7.1 If the parameters set forth in section 6.6 are not met the analytical program will be terminated until the cause is determined and a solution is effected. The cause and the solution will be recorded in the Laboratory Notebook and signed by the operator, before the analytical program is resumed.

7.2 Before and during sample analysis, instrument blanks (sample loops filled with flush nitrogen) should be analyzed to assure the absence of interferences as described in section 3.0 above.

7.3 Prior to the analysis of a sample set, multiple standards, at different concentration levels, should be analyzed to establish an initial calibration table. During sample analysis, standards should be run at a rate of 1 for each 10 samples.

7.4 Standards analyzed during the course of analyzing samples are compared to the calibration table as well as being used for peak identification. All chromatograms should be examined by an experienced analyst.

7.5 The soil gas sample vial is pressurized at the time of sampling. This pressure preserves sample integrity since any leakage is out of the vial and does not result in contamination or sample dilution.

7.6 The headspace sampling unit contains a heated bath as well as a heated sampling loop and transfer line. The latter two zones are continually flushed with nitrogen between sample analyses to minimize the chance of instrumental carry over. This nitrogen in the sample loop is injected periodically to check for instrument contamination.

ANALYTICAL METHOD AM8

ANALYSIS OF MOBILE MERCURY IN SOILS

1.0 Scope and Application

1.1 Method AM8 is used to determine the concentration of mobile (low temperature, adsorbed) mercury in soil samples.

1.2 This method is recommended for use by, or under the supervision of, analysts experienced in the operation of mercury analyzers and in the interpretation of mercury concentration data.

2.0 Summary of Method

2.1 Mobile (low temperature, adsorbed) mercury is analyzed using a Jerome Model 411 Gold Film Mercury Analyzer. A weighed soil sample (dried and sieved < 35 mesh) is placed in a silica test tube (6 mm id x 65mm) which has the bottom inside surface coated with a thin gold film. The soil in the tube is heated at 175 degrees centigrade for 1 hour. The soil is then discarded and each tube is heated individually to 600 degrees centigrade in a resistance heater. At 600 degrees C, vapors in the tube are caused to flow into the mercury analyzer where mercury is adsorbed onto the calibrated gold film. This gold film changes resistance proportional to the amount of mercury adsorbed. The resistance change is converted to weight of mercury adsorbed.

3.0 Interferences

3.1 The analyst should demonstrate that the gold coated test tubes are mercury free before soil is added. This may be accomplished by heating each tube to 600 degrees centigrade and flowing the heated vapors in the tube into the mercury analyzer. Temperature of the tube should be kept at 600 degrees centigrade until no mercury is detected on successive analyses.

3.2 In order to prevent interferences from sulfur gases, other compounds generated when soil is heated, and dust, the analyst should ensure that Malcosorb and dust filters are connected in series with the analyzer as shown in the instrument operation manual.

3.3 The analyst should demonstrate that the system is mercury free at the beginning of the analysis of a sample set. This may be accomplished by heating an uncoated test tube to 600 degrees

centigrade and flowing the heated vapors into the analyzer for measurement. The temperature should be maintained and the flow should be repeated until no mercury is detected on successive runs.

3.4 The analyst should regularly check the status of the gold film detector and burn of the accumulated mercury when appropriate.

4.0 Materials and Equipment

4.1 Sample test tubes: fused silica (6 mm id x 65 mm) with bottom half of inner surface coated with a thin gold film.

4.2 Heating block: aluminum block (12 x 12 x 2.5 inches) with sixty four 5/16 x 2 inch holes for holding gold coated silica tubes.

4.3 Hot plate: Thermodyne Sybron, Model 2200

4.4 Resistance heater: Nichrome wire coil to hold one silica test tube and heat to 600 degrees centigrade.

4.5 Mercury Analyzer: Jerome Model 411 Gold Film Mercury Analyzer including Malcosorb and dust filters.

4.6 Balance: Fisher Model 50 with +/- 0.005 gram accuracy.

5.0 Sample Preparation and Analysis

5.1 Sample test tube preparation: All sample test tubes should meet specifications as noted in sections 3.1 and 4.1 above.

5.2 The sample should be air dried overnight(8-10 hours), then sieved using a 35 mesh sieve. The < 35 mesh fraction should be collected, placed in a clean sample envelope and labeled.

5.3 A weighed, 0.25 - 0.50 gram, portion of the dried, sieved soil sample is placed into a gold coated silica test tube and the test tube number is recorded with the sample number.

5.4 The gold coated silica test tubes containing the weighed, sieved soil samples are placed in the heating block (4.2) and heated to 175 degrees centigrade for 1 hour.

5.5 After removal from the heating block, the soil is discarded from the gold coated silica test tubes. Excess dust may be removed from the vial with compressed air at room temperature.

5.6 Each empty gold coated silica tube is heated to 600

degrees centigrade in the resistance heater and the mercury vapor is caused to flow into the analyzer where it is absorbed on the gold film.

5.7 The change in film resistance is recorded as the number of counts which may be related to the amount of mercury absorbed.

6.0 Standards and Calibrations

6.1 Calibration of the mercury analyzer is achieved by injecting a known amount of mercury vapor directly into a stream of air flowing into the analyzer.

6.2 Mercury metal is maintained at known temperature inside each of six 125 ml sample bottles which are capped with septa.

6.3 A chart of mercury vapor pressure in air vs temperature is maintained.

6.4 A 1 ml volume of air saturated with mercury vapor at a known temperature from one or more of the 125 ml bottles (6.2) is injected into the input air flow to the analyzer and a reading is taken.

6.5 After three or more such procedures, the analyzer calibration is derived as average counts/ng mercury. Typical range is 5 - 8 counts per ng. mercury.

6.6 The analyst should ensure that each bottle of mercury is left at atmospheric pressure after calibration so that temperature and vapor pressure equilibration can occur before the next use. This is achieved by puncturing the septum with a syringe needle after several calibration volumes are removed from a bottle.

7.0 Quality Control

7.1 The analyzer should be calibrated before and after each set of 50 samples is analyzed.

7.2 The instrument response should not vary by more than 20% between any two successive calibrations.

7.3 One blank gold coated vial should be analyzed with every ten samples. The blank vial should be representative of background contamination that could be obtained in the sample vials.

7.4 The instrument detector status should be monitored and recorded during sample analysis.

This page intentionally left blank.

STANDARD PREPARATION METHOD SP3

GAS STANDARD PREPARATION FOR VOC'S

1.0 Scope and Application

1.1 Gas standards may be prepared from pure liquid compounds when commercial gas standards are not available. Known weights of pure compounds are placed in a 22ml vial under known conditions. The ideal gas law is used to calculate gas volumes for each compound. Concentrations may be calculated in parts per million volume (ppmv) or micrograms per liter air (ug/l air).

2.0 Summary

2.1 Equal volumes of pure liquid compounds are combined. A uL amount of the pure blend is injected into a 22ml headspace vial (at atmos. pressure) to produce a known concentration gas (level 1 standard). The pure compound blend is diluted in solvent so that when uL amounts of the diluted blend are injected into a 22ml Headspace vial (at atmos. pressure) a known concentration of gas (level 2) is produced. The pure blend is again diluted in solvent to produce other gas standards (level 3 and 4). Level 5 and level 6 gas standard may be produced by further diluting level 2 and level 3 blends 1000:1. For each level number increase, the weight amount of compound (ug/uL blend) decreases by a factor of 10.

3.0 Apparatus and Materials

3.1 Solvent: The solvent normally used is high purity (99+%) chromatographic grade methyl alcohol. It must be determined if the solvent will interfere with or mask compounds of interest.

3.2 Pure compounds of interest: All compounds used must meet required specifications and be approved on the Supplies and Materials List.

3.3 Storage of Prepared Standards: Vials (Alltech #72716 or equivalent), Caps (Alltech #95246, mininert valves), septa (Alltech #9548).

3.4 1 ml disposable pipettes: Corning #7078-1CN or equivalent.

3.5 22 ml Headspace Vial: Hewlett Packard #9301-0716.

3.6 10 uL liquid syringe: Hamilton #701 or equivalent.

3.7 Pipette Dispenser, Micro-Pipex: Fisher Scientific.

4.0 Procedure

4.1 Add 1ml of each compound to a pre-cleaned 22ml vial using a new disposable 1ml pipette for each compound. The total volume of the pure blend should be greater than 9 ml. If less than 9 compounds are used then 2ml of each compound should be combined.

4.2 Using a disposable 1.0 ml glass pipette, fill at least two 4.5 ml vials with the pure blend. Immediately cap the vials with mininert valve caps. Label the vials "Pure Blend Standard [I.D.] Level 1" along with the date and the preparer's initials.

4.3 Using a disposable 1.0 ml glass pipete, fill each of three new pre-labeled 4.5ml vials with the following ml amounts of solvent; 3.960 (level 2), 4.355 (level 3), and 4.395 (level 4). The labels should reflect the appropriate standard I.D. and level. Cap all vials with mininert valve caps.

4.4 Using a clean 10ul syringe add 4.4 ul of pure blend to the vial containing 4.395 ml of solvent and labeled level 4.

4.5 Using the same 10 ul syringe as in step 4.4 add 4.4 ul of pure blend to the vial containing 4.355 and labeled level 3.

4.6 Using a clean 1 ml pipette add .44 ml of pure blend to the vial containing 3.960 ml of solvent and labeled level 2.

4.7 To produce level 5 and level 6 dilute blends add 4.395 ml of solvent to two clean prelabeled 4.5 ml vials. For level 5 add 4.4 ul of level 2 blend and for level 6 add 4.4 ul of level 3 blend.

4.8 Gas standards are produced by injecting ul amounts of blend (levels 1-6) into 22ml headspace vials containing clean air and capped with TFE lined septums. Refer to the appropriate Standard Calculations Table for actual amounts to inject into the headspace vials and resulting concentrations of each compound.

4.9 The standard calculations table is produced in spreadsheet format and contains at least the following information; solvent used, compound density and molecular weight, ul compound/1ul blend, compound weight/volume of blend, gas volume of compound, weight of compound per liter of air, and the parts per million of compound by volume for each concentration level of standard.

5.0 Calculations

5.1 The following formulas are used to calculate the gas concentration (vol/vol) originating from liquid (weight).

$$\text{CONCENTRATION in PPMV} = (\text{COMPOUND VOL/TOTAL VOL}) * 1000000$$

$$P = 1 \text{ ATM}$$

$$V = 1 \text{ MOLE (IDEAL GAS) } 22.4 \text{ LITER}$$

$$T = \text{TEMP. } 273\text{K}$$

$$R = \text{IDEAL GAS CONSTANT } (.082) \quad R = PV/NT \quad R = (1 * 22.4) / (1 * 273)$$

$$N = \text{COMPOUND WEIGHT/MOL. WEIGHT}$$

$$W = \text{WEIGHT OF COMPOUND USED (IN ug)}$$

$$M = \text{MOL. WEIGHT OF THE COMPOUND}$$

$$D = \text{DENSITY (GRAMS/mL)}$$

$$L = \text{LIQUID VOL. USED (IN uL)}$$

$$t = \text{TEMP. } 25\text{C} + 273\text{K} = 298\text{K}$$

$$v = \text{UNKNOWN VOLUME}$$

$$Pv = NRT$$

$$D = W/L * 1000$$

$$v = N (Rt/P)$$

$$W = DL * 1000$$

$$v = W/M (Rt/P)$$

$$v = W/M ((.082 * 298)/1)$$

$$v = (W/M) * 24.4$$

5.2 To calculate the standard gas concentrations in ug/l air the above ideal gas law formula must be used to calculate the volume of gas of the compound when added to the headspace vial. This volume is then added to the volume of the headspace vial to determine the total volume. The following formula can then be used:

$$\text{CONCENTRATION (ug/l air)} = \frac{(1 \text{ Liter air/total vol}) (\text{compound weight/total volume})}{1}$$

6.0 Safety Precautions

6.1 General laboratory safety precautions should be followed when preparing standards. The safety precautions should include, but not be limited to, the following safeguards; Eye and face protection, proper clothing (gloves, shoes, etc.), proper ventilation, spill protection, and an emergency response plan.

6.2 All safety precautions as stated on the material data sheets should be followed when handling hazardous materials.

This page intentionally left blank.

Appendix II

**Soil Gas Collection Logs
Mercury Collection Logs
Waste Management Unit Worksheet**

This page intentionally left blank.

MICROSEEPS LTD.

CLIENT: WSRCLOCATION: 740-G LandfillPROJECT(S): TASK 1PAGE: 1 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. Pirkle/A. Cayton

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	M		
740-G-SHK 1	11/4	1420	1	0	✓			22	
-345 HK 1		1421	2	0	✓			125	
-0001		1435	3	3.0	✓			22	↑
-0001		1436	4	3.0	✓			125	
-0002		1444	5		✓			22	
-0002		1445	6		✓			125	break through
-0003		1456	7		✓			22	0.2'
-0003		1457	8		✓			125	
-0004		1504	9		✓			22	
-0004		1505	10		✓			125	
-0005		1508	11		✓			22	
-0005		1509	12		✓			125	
-0006		1514	13		✓			22	
-0006		1515	14		✓			125	↓
-0007		1520	15		✓			22	
-0007		1521	16		✓			125	
-0008		1528	17		✓			22	
-0008		1529	18		✓			125	
-0009		1533	19		✓			22	↑
-0009		1534	20		✓			125	
-0010		1539	21		✓			22	MANAGER A
-0010		1540	22		✓			125	pick up
-0010A		1544	23		✓			22	↑ 125' all to 100'
-0010A		1545	24		✓			125	
-345 HK 2		1547	25		✓			22	
-345 HK 2		1548	26		✓			125	
-0011		1552	27		✓			22	
-0011		1553	28		✓			125	
-0012		1559	29		✓			22	
-0012		1600	30		✓			125	
-0013		1603	31		✓			22	
-0013		1604	32		✓			125	
-0014		1609	33		✓			22	
-0014		1610	34		✓			125	↓
-0015	11/5	0729	35		✓			22	
-0015	11/5	0740	36		✓			125	
-0016		0743	37		✓			22	
-0016		0744	38		✓			125	
-0017		0749	39		✓			22	
-0017		0750	40		✓			125	
-0018		0754	41		✓			22	
-0019		0755	42		✓			125	
-0019		0759	43		✓				

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. L. K. & A. Carson

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	M		
740-G-0019	11/5	0800	44	3.0	✓			125	
-0020		0804	45					22	
-0020		0808	46					125	
-0020A		0809	47					22	
-0020A		0810	48					125	
-sys blk 3			49	0				22	
-sys blk 3			50	0				125	
-0021		0814	51	3.0				22	
-0021		0815	52					125	
-0022		0821	53					22	
-0022		0822	54					125	
-0023		0822	55					22	
-0023		0823	56					125	
-0024		0823	57					22	
-0024		0824	58					125	
-0025		0829	59					22	
-0025		0840	60					125	
-0026		0845	61					22	CV, tight
-0026		0846	62					125	
-0027		0853	63					22	
-0027		0854	64					125	
-0028		0859	65					22	
-0028		0900	66					125	
-0029		0906	67					22	
-0029		0907	68					125	
-0030		0913	69					22	
-0030		0914	70					125	
-0030A		0918	71					22	
-0030A		0919	72					125	
-sys blk 4		0921	73	0				22	
-sys blk 4		0922	74	0				125	
-0031		0926	75	3.0				22	
-0031		0927	76					125	
-0032		0933	77					22	1.4 tight
-0032		0934	78					125	
-0033	11/7	1406	79					22	tight
-0033		1407	80					125	
-0034		1411	81					22	
-0034		1412	82					125	
-0035		1416	83					22	
-0035		1417	84					125	
-0036		1420	85					22	
-0036		1421	86					125	

MICROSEEPS LTD.

CLIENT: WSRC
 LOCATION: 740-E
 PROJECT(#): TASK 1
 PAGE: 3 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): _____

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	M		
740-E-0037	11/7	1424	87	3.0	✓			22	
-0037		1425	88					125	
-0038		1426	89					22	
-0039		1429	90					125	
-0039		1434	91					22	
-0039		1435	92					125	
-0040		1441	93					22	
-0040		1442	94					125	
-0040A		1446	95					22	
-0040A		1447	96					125	
-0040K5		1448	97	0				22	
-0040K5		1449	98	0				125	
-0041		1452	99	3.0				22	
-0041		1453	100					125	
-0042		1456	101					22	
-0042		1457	102					125	
-0043		1501	103					22	
-0043		1502	104					125	
-0044		1507	105					22	
-0044		1508	106					125	
-0045		1511	107					22	
-0045		1512	108					125	
-0046		1516	109					22	WOOD @ 60 ft
-0046		1517	110					125	CAME UP ON PROBE -
-0047		1525	111					22	SOIL OBJECT IN 1st hole @ 24 ft.
-0047		1526	112					125	2nd hole penetrator - print object
-0048		1532	113					22	
-0048		1533	114					125	
-0049		1535	115					22	
-0049		1536	116					125	
-0050		1540	117					22	
-0050		1541	118					125	
-0050A		1543	119					22	
-0050A		1544	120					125	
-0050K6		1546	121	0	0			22	
-0050K6		1547	122	0				125	
-0051		1549	123	3.0				22	
-0051		1550	124					125	
-0052		1553	125					22	
-0052		1554	126					125	
-0053		1559	127					22	
-0053		1600	128					125	
-0054	11/8	1126	129					22	

CLIENT: NSRC
 LOCATION: 740-G
 PROJECT(S): TASK 1
 PAGE: 4 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R.R.W. / Adams

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
740-G-0054	11/8	1127	130	3.0	✓			125	
-0055		1132	131					22	
-0055		1133	132					125	
-0056		1138	133					22	
-0056		1139	134					125	
-0057		1144	135					22	
-0057		1146	136					125	
-0058		1157	137					22	light
-0058		1152	138					125	2 2 bottom
-0059		1200	139					22	
-0059		1201	140					125	
-0060		1204	141					22	
-0060		1205	142					125	
-0060A		1207	143					22	
-0060A		1208	144					125	
-545 HK7		1210	145	0				22	
-545 HK7		1211	146	0				125	
-0061		1214	147	3.0				22	
-0061		1215	148					125	
-0062		1229	149					22	
-0062		1230	150					125	
-0063		1233	151					22	
-0063		1234	152					125	
-0064		1239	153					22	
-0064		1240	154					125	
-0065		1243	155					22	maybe encountered some
-0065		1244	156					125	Asphalt - Black with on probe
-0066		1253	157					22	light clay wet
-0066		1255	158					125	
-0067		1301	159					22	light
-0067		1302	160					125	
-0068		1307	161					22	
-0068		1308	162					125	
-0069		1311	163					22	
-0069		1312	164					125	
-0070		1313	165					22	
-0070		1314	166					125	
-0070A		1322	167					22	
-0070A		1323	168					125	
-515 HK8		1325	169					22	
-515 HK8		1326	170					125	

MICROSEEPS LTD.

CLIENT: WSPC
 LOCATION: G LANDFILL
 PROJECT(S): TASK 1A
 PAGE: 1 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): RIP DTM AGC

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
Sys Blk 9	11-9		1	3.0'	✓			22	
Sys Blk 9			2					125	
G-71			3					22	
G-71			4					125	
G-72			5					22	
G-72			6					125	NO PRESS. N 2nd
G-73			7					22	
G-73			8					125	NO PRESS. N 2nd
G-72A		11:30	9					125	Resampled site
G-72A		11:35	10					125	Resampled site
G-74		11:37	11					22	
G-74		11:38	12					125	
G-75		11:41	13					22	
G-75		11:42	14					125	
G-76		11:47	15					22	
G-76		11:48	16					125	
G-79		11:50	17					22	
G-79		11:51	18					125	
Sys Blk 10		11:55	19					22	
Sys Blk 10		11:56	20					125	
G-77		12:01	21					22	
G-77		12:02	22					125	
G-78		12:04	23					22	
G-78		12:05	24					125	
G-80		12:08	25					22	
G-80		12:09	26					125	
G-80A		12:11	27					22	
G-80A		12:12	28					125	
G-81		12:17	29					22	
G-81		12:18	30					125	
G-82		12:25	31					22	
G-82		12:26	32					125	
G-83		12:30	33					22	
G-83		12:31	34					125	
G-84		12:34	35					22	
G-84		12:35	36					125	
G-85		12:37	37					22	
G-85		12:38	38					125	
G-86		12:40	39					22	
G-86		12:41	40					125	
G-87		14:35	41					22	
G-87		14:36	42					125	
G-88			43					22	

MICROSEEPS LTD.

CLIENT: WSRC
LOCATION: 740-E
PROJECT(S): TRAIL
PAGE: 2 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): Pike / Carron

[illegible]

USE A NEW SHEET WHEN RESTARTING SEQUENCE :

MICROSEEPS LTD.

 CLIENT: WSRL
 LOCATION: 740-G
 PROJECT(S): TASK 1
 PAGE: 1 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. Pirkle/D. Mosler

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
G-99	11/11	1121	1	3.0	✓			22	
G-99		1122	2					125	
G-100		1127	3					22	
G-100		1128	4					125	
G-100A		1130	5					22	
G-100A		1131	6					125	
G-575 BK 12		1133	7	0				22	
G-575 BK 12		1134	8	0				125	
G-101		1138	9	3.0				22	
G-101		1139	10					125	
G-102		1143	11					22	
G-102		1144	12					125	
G-103		1149	13					22	Sv. tight
G-103A		1150	14					22	
G-104		1156	15					22	
G-104		1157	16					125	
G-105		1204	17					22	
G-105		1205	18					125	
G-106		1210	19					22	
G-106		1211	20					125	
G-107		1215	21					22	
G-107		1216	22					125	
G-108		1220	23					22	
G-108		1221	24					125	
G-109		1223	25					22	
G-109		1223	26					125	
G-110		1233	27					22	
G-110		1234	28					125	
G-110A		1236	29					22	
G-110A		1237	30					125	
G-575 BK 13		1238	31	0				22	
G-575 BK 13		1239	32	0				125	
G-111		1244	33	3/0				22	
G-111		1245	34					125	
G-112		1247	35					22	
G-112		1248	36					125	
G-116		1441	37					22	Sample then dumped soil
G-116		1442	38					125	
G-117		1446	39					22	
G-117		1447	40					125	
G-118		1453	41					22	
G-118		1454	42					125	
G-121		1503	43					22	↓

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

MICROSEEPS LTD.

CLIENT: WSPC
LOCATION: 740-B
PROJECT(S): TASK1
PAGE: 2 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): RRivkle / D. Masda

[illegible]

USE A NEW SHEET WHEN RESTARTING SEQUENCE :

MICROSEEPS LTD.

CLIENT: WSPC
 LOCATION: 740-15
 PROJECT(S): TASK1
 PAGE: 1 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. Pirker / D. Mayden

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
G-543 blk 15	11/12	1345	1	0	✓			22	
G-543 blk 15	7	1346	2	0	7			125	
G-119		1353	3	3.0	7			22	
G-119		1354	4	7				125	
G-120		1359	5					22	10' toward end
G-120		1400	6					125	
G-123		1403	7					22	15' toward end (in)
G-123		1404	8					125	
G-124		1407	9					22	15' toward end (in)
G-124		1408	10					125	
G-135		1411	11					22	height
G-135		1412	12					125	
G-136		1414	13					22	
G-136		1415	14					125	
G-137		1420	15					22	
G-137		1421	16					125	
G-138		1425	17					22	
G-138		1426	18					125	
G-139		1429	19					22	
G-139		1430	20					125	
G-140		1436	21					22	
G-140		1437	22					125	
G-140 A		1439	23					22	
G-140 A		1440	24					125	
G-543 blk 16		1443	25					22	
G-543 blk 16		1444	26					125	
G-127		1447	27					22	
G-127		1448	28					125	
G-128		1453	29					22	
G-128		1454	30					125	
G-129		1455	31					22	
G-129		1456	32					125	
G-129A		1459	33					22	
G-129A		1500	34					125	
G-124		1503	35					22	
G-124		1504	36					125	
G-125		1507	37					22	
G-125		1508	38					125	
G-126		1512	39					22	
G-126		1513	40					125	

CLIENT: WSRC
 LOCATION: 740-G
 PROJECT(S): TRK-1
 PAGE: 1 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S):

RJP/DJM

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
G-156	11/13	1622	1	3.0	✓			22	
G-156		1623	2					125	
G-157		1624	3					22	
G-157		1625	4					125	
G-158		1626	5					22	
G-158		1627	6					125	
G-159		1630	7					22	
G-159		1631	8					125	
G-160		1635	9					22	
G-160		1636	10					125	
G-160A		1637	11					22	
G-160A		1638	12					125	
G-161 blk 17		1638	13	0				22	
G-161 blk 17		1639	14	0				125	
G-161		1641	15	3.0				22	
G-161		1642	16					125	
G-168	11/14	1335	17					22	
G-168		1336	18					125	
G-141		1346	19					22	
G-141		1347	20					125	
G-167		1351	21					22	
G-167		1352	22					125	
G-142		1354	23					22	
G-142		1355	24					125	
G-166		1356	25					22	
G-166		1357	26					125	
G-143		1400	27					22	
G-143		1401	28					125	
G-165		1403	29					22	
G-165		1404	30					125	
G-144		1406	31					22	
G-144		1407	32					125	
G-164		1410	33					22	
G-164		1411	34					125	
G-145 blk 18		1413	35	0				22	
G-145 blk 18		1414	36	0				125	
G-145		1418	37	3.0				22	
G-145		1419	38					125	
G-163		1424	39					22	
G-163		1425	40					125	
G-146		1428	41					22	
G-146		1429	42					125	
G-162		1434	43					22	

MICROSEEPS LTD.

CLIENT: WSRC
 LOCATION: 740-G
 PROJECT(S): TASK1
 PAGE: 2 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): RSP/DJM

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	M		
G-162	11/14	1435	44	3.0	✓			125	
G-147		1440	45	1				22	
G-147		1441	46	1				125	
G-148		1446	47	1				22	
G-148		1446	48	1				125	
G-149	11/15	1139	49	1				22	
G-149		1140	50	1				125	
G-150		1148	51	1				22	
G-150		1149	52	1				125	
G-151		1153	53	1				22	
G-151		1154	54	1				125	
G-152		1159	55	1				22	
G-152		1200	56	1				125	
G-153		1205	57	1				22	
G-153		1206	58	1				125	
G-154		1211	59	1				22	
G-154		1212	60	1				125	
G-155		1217	61	1				22	
G-155		1218	62	1				125	
G-343 blk 19		1220	63	0				22	
G-248 blk 19		1221	64	0				125	
G-155A		1358	65	3.0				22	
G-155A		1359	66	1				125	
G-169		1420	67	1				22	
G-169		1421	68	1				125	
G-170		1424	69	1				22	
G-170		1425	70	1				125	
G-170A		1427	71	1				22	
G-170A		1428	72	1				125	
G-171		1429	73	1				22	
G-171		1430	74	1				125	
G-172		1435	75	1				22	
G-172		1436	76	1				125	
G-173		1439	77	1				22	
G-173		1440	78	1				125	
G-174		1444	79	1				22	
G-174		1445	80	1				125	
G-175		1450	81	1				22	
G-175		1451	82	1				125	
G-176		1457	83	1				22	
G-176		1458	84	1				125	
G-343 blk 20		1459	85	1				22	
G-343 blk 20		1500	86	1				125	

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

CLIENT: WSRC
 LOCATION: 740-G
 PROJECT(S): TABL
 PAGE: 3 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. P. K. - 1 D. Maslow

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
G-177	11/15	1505	87	3.0	✓			22	
G-177		1506	88					125	
G-178		1510	89					22	
G-178		1511	90					25	
G-179		1515	91					22	
G-179		1516	92					125	
G-180		1520	93					22	
G-180		1521	94					125	
G-180A		1525	95					22	
G-180A		1526	96					125	
G-181		1529	97					22	
G-181		1530	98					125	
G-343 blk 21	11/16	1349	99	0				22	
G-343 blk 21		1350	100	0				125	
G-182		1355	101	3.0				22	
G-182		1356	102					125	
G-183		1359	103					22	
G-183		1400	104					125	
G-184		1405	105					22	
G-184		1406	106					125	
G-185		1410	107					22	
G-185		1411	108					125	
G-186		1414	109					22	
G-186		1415	110					125	
G-187		1419	111					22	
G-187		1420	112					125	
G-188		1424	113					22	
G-188		1425	114					125	
G-189		1429	115					22	
G-189		1430	116					125	
G-190		1433	117					22	
G-190		1434	118					125	
G-190A		1437	119					22	
G-190A		1438	120					125	
G-343 blk 22		1440	121	0				22	
G-343 blk 22		1441	122	0				125	
G-191		1444	123	3.0				22	
G-191		1445	124					125	
G-192		1449	125					22	
G-192		1450	126					125	
G-193		1454	127					22	
G-193		1455	128					125	
G-194		1458	129					22	

CLIENT: WSRL
 LOCATION: 740-G
 PROJECT(S): TASK 1
 PAGE: 4 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. Pirkle / D. Hansen

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
G-194	11/16	1459	130	3.0	✓			125	
G-195		1504	131					22	
G-195		1505	132					125	
G-196		1511	133					22	
G-196		1512	134					125	
G-197		1513	135					22	
G-197		1514	136					125	
G-198		1519	137					22	
G-198		1520	138					125	
G-199		1523	139					22	
G-199		1524	140					125	
G-200		1527	141					22	
G-200		1528	142					125	
G-200A		1530	143					22	
G-200A		1531	144					125	
G-201 blk 23		1533	145	0				22	
G-201 blk 23		1534	146	0				125	
G-201		1536	147	3.0				22	
G-201		1537	148					125	
G-202		1543	149					22	
G-202		1544	150					125	
G-203		1547	151					22	
G-203		1548	152					125	
G-204		1552	153					22	
G-204		1553	154					125	
G-205		1557	155					22	
G-205		1558	156					125	
G-206		1600	157					22	
G-206		1601	158					125	
G-207		1606	159					22	
G-207		1607	160					125	
G-208		1611	161					22	
G-208		1612	162					125	
G-209		1615	163					22	
G-209		1616	164					125	
G-210	11/17	1429	165					22	
G-210		1430	166					125	
G-210A		1433	167					22	
G-210A		1434	168					125	
G-211 blk 24		1436	169	0.0				22	
G-211 blk 24		1437	170	0.0				125	
G-211		1440	171	3.0				22	
G-211		1451	172					125	

MICROSEEPS LTD.

CLIENT: WSRC
LOCATION: 740-G
PROJECT(S): TASK 1
PAGE: 5 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. Pirkle / D. Masoka

[illegible]

USE A NEW SHEET WHEN RESTARTING SEQUENCE 1

MICROSEEPS LTD.

CLIENT: WSRC
 LOCATION: 240 G
 PROJECT(S): TASK 1
 PAGE: 1 OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): R. Pyke / ACarr

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
SYS BLK 26	12/2	1030	1	0.0	✓			22	
SYS BLK 26		1031	2	0.0	✓			125	
G-225		1040	3	3.0				22	
G-225		1041	4	3.0				125	
G-226		1045	5					22	
G-226		1046	6					125	
G-227		1052	7					22	
G-227		1053	8					125	
G-228		1058	9					22	
G-229		1059	10					125	
G-229		1103	11					22	
G-229		1104	12					125	
G-230		1107	13					22	
G-230		1108	14					125	
G-230A		1111	15					22	
G-230A		1112	16					125	
G-231		1116	17					22	in + re-run
G-231		1117	18					125	
G-232		1124	19					22	
G-232		1125	20					125	
G-233		1132	21					22	
G-233		1133	22					125	
G-SYS BLK 27		1134	23	0				22	
G-SYS BLK 27		1135	24	0				125	
G-234		1137	25	3.0				22	
G-234		1140	26					125	
G-235		1144	27					22	
G-235		1145	28					125	
G-236		1150	29					22	
G-236		1151	30					125	
G-237		1156	31					22	8' N of LF-W 42
G-237		1157	32					125	
G-238		1159	33					22	
G-238		1200	34					125	
G-239		1429	35	6.0				22	
G-239		1430	36					125	
G-240		1434	37					22	
G-240		1435	38					125	
G-240A		1437	39					22	
G-240A		1438	40					125	
G-241		1440	41					22	
G-241		1441	42					125	
G-242		1443	43					22	

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

CLIENT: WSRK
LOCATION: 746-B
PROJECT(S): TASK 1
PAGE: 2 OF:

SAMPLER NAME(S): R. Pickle / A. Canyon

USE A NEW SHEET WHEN RESTARTING SEQUENCE :

CLIENT: WSRS/Doug Wyatt
 LOCATION: Landfill Extension
 PROJECT(S): 740-G
 PAGE: OF:

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): Kab/AaC

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
740-G-SB32	5-29-91	1440	1	-0-	✓			22	
740-G-SB-32		1442	2	-0-				125	
740-G-262		1444	3	3'				22	
G-262		1445	4					125	
G-263		1447	5						
G-263		1448	6						
G-264		1452	7						
G-264		1454	8						
G-265		1456	9						
G-265		1457	10						
G-266		1458	11						
G-266		1500	12						
G-267		1503	13						
G-267		1504	14						
G-268		1506	15						
G-268		1507	16						
G-269		1510	17						
G-269		1511	18						
G-269A		1513	19						
G-269A		1514	20	✓					
G-SB-33		1515	21	-0-					
G-SB-33		1516	22	-0-					
G-270		1517	23	3'					
G-270	✓	1518	24						
G-271	5-30-91	843	25						
G-271		844	26						
G-272		845	27						
G-272		847	28						
G-273		848	29						
G-273		849	30						
G-274		850	31						
G-274		851	32						
G-275		854	33						
G-275		855	34						
G-276		901	35						
G-276		902	36						
G-277		918	37						
G-277		920	38						
G-278		1204	39						
G-278		1205	40						
G-279		1210	41						
G-279		1212	42						
✓ G-279A	✓	1214	43	✓	✓			✓	

CLIENT: WSRS / Dave Wyatt
LOCATION: Landfill Extension
PROJECT #: 740-G
PAGE: _____ OF: _____

SAMPLER NAME(S): _____

USE A NEW SHEET WHEN RESTARTING SEQUENCE 1

MICROSEEPS LTD.

CLIENT: WSRLLOCATION: 740-G - LavofillPROJECT(S): Task #1PAGE: 1 OF: 2

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC + JPS

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	M		
740-G-1	1-8-91		1	1 ft		✓			
-2			2						
-3			3						
-4			4						
-5			5						
-6			6						
-7			7						
-8			8						
-9			9						
-10			10						
-10H			11						
-11			12						
-12			13						
-13			14						
-14			15						
740-G-15	1-9-91		16						
-16			17						
-17			18						
-18			19						
-19			20						
-20			21						
-20A			22						
-21			23						
-22			24						
-23			25						
-24			26						
-25			27						
-26			28						
-27			29						
-28			30						
-29			31						
-30			32						
-30A			33						
-31			34						
-32			35						
-33			36						
-34			37						
-35			38						
-36			39						
-37			40						
-38			41						
-39			42						
-40			43						

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

MICROSEEPS LTD.

CLIENT: WSRCLOCATION: 740-G- LANDFILLPROJECT(S): TASK#1PAGE: 2 OF: 2

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC+JP+JS

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	M		
740-G-40A	1-9-91		44	1ft		✓			
-41			45			✓			
-42			46			✓			
-43			47						
-44			48						
-45			49						
-46			50						
-47			51			✓			
-48			52			✓			
-49			53						
-50			54						
-50A			55						
-51			56						
-52			57						
-53			58			✓			
-54			59			✓			
-55			60						
-56			61						
-57			62			✓			
-58			63			✓			
-59			64						
-60			65						
-60A			66			✓			
-61			67						
-62			68						
-63			69						
-64			70						
-65			71						
-66			72						
-67			73						
-68			74						
-69			75						
-70			76						
-70A			77						
-71			78						
-72			79						
-73			80						
-74			81						
-75			82			✓			
-76			83			✓			
-77			84						
-78			85						
-79			86						

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

MICROSEEPS LTD.

CLIENT: WSRCLOCATION: 740G- LandfillPROJECT(S): Task #1PAGE: 3 OF: 7

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC+JP+JS

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
740-G-80	1-9-91		87	14		✓			
-80A			88			✓			
-81			89	✓		✓			
-82			90	✓		✓			
-83			91			✓			
-84			92			✓			
-85			93			✓			
-86			94			✓			
-87			95			✓			
-88			96			✓			
-89			97			✓			
-90			98			✓			
-90A			99			✓			
-91			100			✓			
-92			101			✓			
-93			102			✓			
-94			103			✓			
-95			104			✓			
-96			105			✓			
-97			106			✓			
-98			107			✓			
-99	1-10-91		108			✓			
-100			109			✓			
-100A			110			✓			
-101			111			✓			
-102			112			✓			
-103			113			✓			
-104			114			✓			
-105			115			✓			
-106			116			✓			
-107			117			✓			
-108			118			✓			
-109			119			✓			
-110			120			✓			
-110A			121			✓			
-111			122			✓			
-112			123			✓			
-113			124			✓			
-114			125			✓			
-115			126			✓			
-116			127			✓			
-117			128			✓			
-118			129			✓			

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC+JP+JS

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
740-G-119	10-10		130	1A		V			
-120			131						
-121			132						
-122			133						
-123			134						
-124			135						
-125			136						
-126			137						
-127			138						
-128			139						
-129			140						
-129-A			141						
-130			142						
-131			143						
-131-A			144						
-132			145						
-133			146						
-134			147						
-135			148						
-136			149						
-137			150						
-138			151						
-139			152						
-140			153						
-140A			154						
-141	1-1291		155						
-142			156						
-143			157						
-144			158						
-145			159						
-146			160						
-147			161						
-148			162						
-149			163						
-150			164						
-151			165						
-152			166						
-153			167						
-154			168						
-155			169						
-155A			170						
-156			171						
-157			172						

MICROSEEPS LTD.

CLIENT: WSRCLOCATION: 740-G LandfillPROJECT(S): TASK#1PAGE: 5 OF: 7

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC+IP+JS

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
740-6-158	1-12		173	1 ft		✓			
-159			174			✓			
-160			175			✓			
-160A			176			✓			
-161			177			✓			
-162			178			✓			
-163			179			✓			
-164			180			✓			
-165			181			✓			
-166			182			✓			
-167			183			✓			
-168			184			✓			
-169			185			✓			
-170			186			✓			
-170A			187			✓			
-171			188			✓			
-172			189			✓			
-173			190			✓			
-174			191			✓			
-175			192			✓			
-176			193			✓			
-177			194			✓			
-178			195			✓			
-179			196			✓			
-180			197			✓			
-180A			198			✓			
-181			199			✓			
-182			200			✓			
-183			201			✓			
-184			202			✓			
-185			203			✓			
-186			204			✓			
-187			205			✓			
-188			206			✓			
-189			207			✓			
-190			208			✓			
-190A			209			✓			
-191			210			✓			
-192			211			✓			
-193			212			✓			
-194			213			✓			
-195			214			✓			
-196			215			✓			

USE A NEW SHEET WHEN RESTARTING SEQUENCE #

CLIENT: WSRC
 LOCATION: 740-G Lowhill
 PROJECT(S): TASK #1
 PAGE: 6 OF: 7

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC+JP+JS

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	N		
740-6-197	1-12		216	1ft		✓			
-198			217						
-199			218						
-200			219						
-200A			220						
-201			221						
-202			222						
-203			223						
-204			224						
-205			225						
-206			226						
-207			227						
-208			228						
-209			229						
-210			230						
-210A			231						
-211			232						
-212			233						
-213			234						
-214			235						
-215			236						
-216			237						
-217			238						
-218			239						
-219			240						
-220			241						
-220A			242						
221			243						
222			244						
223			245						
224			246						
225	1-14		247						
226			248						
227			249						
228			250						
229			251						
230			252						
230A			253						
231			254						
232			255						
233			256						
234			257						
235			258						

MICROSEEPS LTD.

CLIENT: WSRC

LOCATION: 740-G Lane 111

PROJECT(S): TASK #1

PAGE: 2 OF: 2

***** SAMPLE COLLECTION LOG *****

SAMPLER NAME(S): AGC + J P + J S

SAMPLE ID#	DATE	TIME	SEQ.#	SAMPLE DEPTH	SAMPLE TYPE			SAMPLE SIZE	COMMENTS
					G	S	W		
740-G-236	4/4		259	1 ft		✓			
-237			260						
-238			261						
-239	1-12		262						
-240			263						
-240A			264						
-241			265						
-242			266						
-243			267						
-244			268						
-245			269						
-246			270						
-247			271						
-248			272						
-249			273						
-250			274						
-250A			275						
-251			276						
-252			277						
-253			278						
-254			279						
-255			280						
-256			281						
-257			282						
-258			283						
-259			284						
-260			285						
-260A			286						
-261			287						

USE A NEW SHEET WHEN RESTARTING SEQUENCE :

This page intentionally left blank.

UNIT NAME: SANITARY LANDFILL

BLDG. NO.: 740-G

COORDINATES: N84559 E45231

STATUS: ACTIVE

CAPACITY: APPROX. 70 ACRES

DIMENSIONS: APPROX. 3,275 FT X 1,300 FT

MATERIALS OF CONSTRUCTION: EXCAVATED EARTHEN TRENCHES

OTHER: DATES OF WASTE RECEIPT: 1974 - PRESENT.
THIS SITE IS ACTIVE.

WASTE DESCRIPTION: PAPER, PLASTIC, CONSTRUCTION DEBRIS, EMPTY CANS, CARCASSES.

WASTE COMPONENTS: SOLVENT RAGS

WASTE QUANTITY: UNKNOWN

GROUNDWATER MONITORING: ONGOING: QUARTERLY MONITORING OF 32 WELLS.

PLANNED: CONTINUE ONGOING MONITORING. PLANNED GROUNDWATER ASSESSMENT INVOLVES 11 GEOLOGIC BORINGS AND 32 NEW WELLS. THIS SITE IS IN THE RFI/RI PROGRAM.

WELL DATA CODE: LFW (DPSPU-88-30-1, VOL II)

SUMMARY OF DATA: THIS SITE IS PERMITTED AS A SANITARY LANDFILL BY SCDHEC. HAZARDOUS WASTE DISPOSAL IS PROHIBITED BY PROCEDURE AND AS A PERMIT CONDITION. WASTE SEPARATION IS MADE AT THE SITE OF GENERATION. LOW LEVELS OF VOLATILE ORGANIC COMPOUNDS, INCLUDING TRICHLOROETHYLENE, TETRACHLOROETHYLENE, AND 1,1,1-TRICHLOROETHANE, HAVE BEEN DETECTED IN THE GROUNDWATER.

CORRECTIVE ACTIONS: ONGOING: GROUNDWATER ASSESSMENT.

PLANNED: THIS SITE IS IN THE RFI/RI PROGRAM.

INSPECTIONS AND FREQUENCY:

This page intentionally **left blank.**

END

**DATE
FILMED**

3 / 5 / 93