1 of 1

DECLASSIFIED

HM-78100

This document consists of
39 pages. No. 278 of
100 copies. Series

670691
OOT 1

HANFORD REACTOR AND SEPARATIONS
FACILITY ADVANTAGES

By the Staffs of the
Irradiation Processing Department
and
Chemical Processing Department

Approved by:

A. B. Greninger, General Manager
IRRADIATION PROCESSING DEPARTMENT

P. H. Reiniker, General Manager
CHEMICAL PROCESSING DEPARTMENT

June 27, 1963

HANFORD ATOMIC PRODUCTS OPERATION
Richland, Washington

DECLASSIFIED

MASTER

CIRCULATING COPY
RECEIVED 100 D AREA
JUN 29 1963
RETURN 10
TECHNICAL INFORMATION FILES

Classification Cancelled and Changed To
DECLASSIFIED
By Authority of LSA/Sunder
CG, PR-2, July 26, 1953
By JS/Seely 8-4-53
Verified By PN/Clark 8-5-93

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DECLASSIFIED

TABLE OF CONTENTS

	Page
INTRODUCTION - - - - -	3
SUMMARY - - - - -	3
1. Production Flexibility - - - - -	3
2. Nuclear Safety - - - - -	7
3. Economy - - - - -	8
4. Reliability - - - - -	8
DISCUSSION - - - - -	9
A. Reactor Characteristics and Flexibility - - -	9
1. Flux - - - - -	9
2. Neutron Spectrum - - - - -	11
3. Fuel Element Design Flexibility - - - - -	13
4. Neutron Efficiency - - - - -	18
5. Loading Pattern Flexibility - - - - -	21
6. Product Changeover Time - - - - -	22
7. Multiproduct Flexibility - - - - -	23
8. Pilot and Full-Production Timing - - - - -	24
B. Separations-Plant Characteristics and Flexibility	26
1. Purex - - - - -	26
2. Redox - - - - -	27
3. UO ₃ -Plant - - - - -	27
4. Plutonium Processing - - - - -	28
5. Strontium Semiworks - - - - -	28
6. B-Plant - - - - -	28
7. T-Plant - - - - -	29
8. U-Plant - - - - -	29
9. 2101 M Building - - - - -	29
10. Miscellaneous Facilities for Recovering By-Products - - - - -	29
C. Alternate-Product Possibilities - - - - -	31
1. Weapons-Grade Plutonium - - - - -	31
2. Tritium - - - - -	31
3. Unclassified (and High-240) Plutonium - - -	31
4. Uranium-233 - - - - -	33
5. Neptunium-237 - - - - -	34
6. Plutonium-238 - - - - -	34
7. Polonium-210 - - - - -	35
8. Transplutonium Isotopes - - - - -	35
9. Cobalt-60 - - - - -	36
10. Thulium - - - - -	37
REFERENCES - - - - -	38

HANFORD REACTOR AND SEPARATIONS
FACILITY ADVANTAGES

DECLASSIFIED

INTRODUCTION

This document describes the advantages and limitations of Hanford production facilities as requested in reference 1. In addition to summarizing the technical parameters of the reactors and separations plants and their mechanical features, we have related the unique aspects of these facilities to the production of special materials in which the Commission may be interested.

As the primary difference between the B-C-D-DR-F-H reactors and the K reactors is in the number and length of process channels, this report is addressed primarily to the 2000-tube reactors; K reactor characteristics are within the range of lattice and flexibility parameters described. A companion document discusses N-Reactor characteristics and capabilities.^{/2/}

SUMMARY

In the Hanford production complex the Commission possesses reactors and supporting facilities with outstanding features of production flexibility, of nuclear safety, of production economy and of operating reliability.

1. Production Flexibility

a. "Open-ended" Channels

The B-C-D-DR-F-H reactors contain over 12,000 process channels and 50 test holes with individual flexibility. The one-pass coolant system and access to charge and experimental faces during operation provide the potential for using any number of these 12,000 channels or of the available test holes for experimental loops, either very short-term or very long-term irradiation columns, or potential poison columns (spline tubes).

With extension of the present Poison Column Charging Facility concept, the possibility exists of charging any target element in any spot in the reactor at any time.

Power-takeoff potential is also enhanced by the individual-tube access. A recirculating power-takeoff core surrounded by a one-pass production blanket is one possibility. Or some as-yet-undeveloped method for direct electrical conversion which would require leads to every process channel could be considered.

b. Productive Capacity

Except in irradiation programs involving very short half-lives and/or limited quantities of target material, total megawatt output is the most direct factor indicative of production capacity. The megawatt capacity of these six reactors is on the order of 13,000 MW,^{/3/} the exact value varying slightly with the seasonal variation in inlet coolant temperature; the values listed apply to current operating conditions and do not

DECLASSIFIED

reflect expected improvements in hydraulic configurations.

A 10 to 15 percent increase in productive capacity per megawatt of heat production may be obtained at reasonable cost with the overboring of the graphite channels. This attractive potential is summarized more fully in the paragraphs on Economy.

Volume available for irradiation is also favorable. The six 2000-tube reactors contain over 50 miles of active channel capacity of greater than 1.5 sq. in. element cross section.

c. Alternate Products

The feature listed previously of individual channel availability permits wide flexibility in the timing of irradiations, both into and out of the reactor. A less obvious but potentially significant advantage of individual tube access is that of permitting loops for the concurrent operation of the irradiation and chemical processes in liquid systems. Loop irradiation and bleedoff of neptunium-237 or thorium-232 solutions, for example, would reduce both the burnup of product atoms and the formation of product contaminants. Such facilities designed with high ratio of in-reactor to out-of-reactor inventory would also compete in production rate with reactors having higher flux levels but lacking loop flexibility. Loops for chemo-nuclear, organic, or liquid-metal use could also be installed if desired.

The high moderator temperatures in the water-cooled graphite reactors provide a relatively higher flux in the resonance regions of many of the isotopes of interest in the transuranium series. For a given amount of plutonium in a Hanford reactor, the percentage of Pu^{240} buildup is increased; thus the use of Hanford reactors is especially attractive for the first stage of a curium-244 campaign.

The H reactor loadings at Hanford have demonstrated the efficiency with which tritium can be produced in a Hanford reactor. With a relatively "black" target element supported by an increase in enrichment level, the number of target atoms converted has been approximately twice the displaced plutonium atom production; in other words, direct irradiation cost per alternate-product atom is about half that of a plutonium atom otherwise produced. Similar reasoning would apply to the irradiation of other relatively black materials such as cobalt or thulium, or to the consideration of higher levels of enrichment to obtain an even "blacker" lattice with atom-production rates of target material approaching 50 per cent of the total product.

The tremendous volume capacity could be used for the irradiation of low-cross-section materials, such as bismuth for the production of polonium-210. If such materials can be substituted for space presently left void or filled by coolant or moderator, irradiation costs would be almost negligible. Displacement of fuel for the irradiation of low-cross-section materials, however, would be in the direction of lowering both attainable power level and conversion ratio.

DECLASSIFIED

HW-78100

Page 5

d. Chemical Processing Facilities

The isolation of the separations areas, combined with the favorable climate and ground conditions, make Hanford an ideal site in which to process radioactive materials.

The installed chemical-processing complex includes several varied facilities in which chemical processing is being, or has been, conducted. The salient features of these plants are discussed below.

1) Purex Plant

The Purex plant is ideally suited for the large-scale processing of irradiated uranium or thorium for the recovery of fissile and fertile materials. By combining high efficiency with large throughput, this plant can operate at a lower unit cost than can any other separations plant in the AEC complex. Because of its large size, changing from one product to another is relatively expensive, and scheduling of alternate products should ideally be in relatively large batches with infrequent changeover.

At present, the plant is limited to the processing of irradiated aluminum-clad natural uranium at rates up to 7800 tons per year. Irradiated thorium could be processed at similar rates, or irradiated thorium at rates two- to four-fold lower. With equipment changes costing about three million dollars, this plant could be modified by 1966 to process aluminum-jacketed uranium enriched up to 0.94 per cent U²³⁵ at rates up to 8650 tons per year. Uranium having a higher enrichment could then be processed at reduced rates; a processing capability for 1.5 per cent U²³⁵ fuels is projected to be 5800 tons per year. Zirconium-jacketed fuels could also be processed at rates about 20 per cent lower than those for aluminum-jacketed fuels.

2) Redox Plant

The Redox plant is ideally suited to the processing of specialty fuels. Relatively small quantities can be processed with good yields and little cross-contamination of consecutive products. For example, a six-kilogram batch of plutonium contained in zirconium-clad aluminum-alloy fuel was recently processed with 99.5 per cent recovery, excellent decontamination from fission product, and about five per cent contamination with the normal plutonium.

The plant is now equipped to process irradiated zirconium or aluminum-jacketed uranium, containing up to 0.94 per cent U²³⁵, at rates up to 2400 tons per year. The plant can also recover U²³³ from irradiated thorium at similar rates, or from irradiated thorium at rates two- to four-fold lower; the thorium could be recovered with low efficiency. While the technology is not firm, it is also probable that polonium could be extracted from irradiated bismuth in this facility.

DECLASSIFIED

HW-78100

Page 6

With the expenditure of a few million dollars, the flexibility of the Redox plant could be increased considerably. For example, irradiated thorium could be processed with high efficiency; uranium power fuels of all enrichments, clad in aluminum, zirconium, or stainless steel, and containing alloying agents such as molybdenum could also be processed.

3) UO₃ Plant

The 224UA facility is ideally suited to the calcination of uranium nitrate to the oxide at rates up to 12,000 tons per year. Two different enrichments can be processed in parallel. Enrichments up to 1.25 per cent can now be processed; studies in progress indicate that enrichments up to 1.5 per cent can be processed with minor modifications of equipment and control systems. Processing costs are very low in this facility.

4) 234-5 Facility

In the 234-5 facility plutonium can be processed from the nitrate salt to the metal at rates up to 6000 kilograms per year, although additional shielding would be required if the plutonium contained more than about 8% Pu²⁴⁰. Space is available for the installation of a parallel line in which plutonium of a different type or U²³³ could be processed. Facilities are being constructed in which plutonium can be recovered from a wide variety of scrap materials. Laboratory and pilot plant equipment are available to process developmental quantities of other moderately radioactive materials, such as americium, curium, etc., to metallic form.

5) Strontium Semiworks

The strontium semiworks is ideally suited for the processing of highly radioactive materials on a semiproduction scale. The unit is contact-maintained and does not have the operating reliability of the remotely-maintained plants. This unit has successfully processed fully irradiated uranium by both the Redox and Purex processes, and is currently being used to purify strontium-90 for the SNAP program. The complex is equipped for dissolution, distillation, precipitation, solvent extraction, and ion exchange operations.

6) By-Product Recovery

By-product recovery can be effected in many facilities. Purified strontium-90 and crude cesium-137 are currently being produced on a limited production basis. Developmental quantities of cerium-144 and promethium-147, have been recovered. Facilities are being scoped, for installation in B-Plant, to segregate large quantities of these materials as a part of the waste-management program. Americium and curium could be segregated with the rare-earth fission products in a small-volume precipitate in the head end of the Purex plant.

DECLASSIFIED

HW-78100
Page 7

Transportation of this material to a purification facility could be accomplished in shielded filter casks.

7) Other Large Facilities

Three heavily shielded processing buildings, originally intended to recover plutonium from irradiated fuel, are available for other assignment. One of these buildings (T-Plant) is now being used to decontaminate and repair process equipment. A second, (B-Plant) is scheduled to play a key role in the waste-management program. A third (U-Plant) was modified and operated to recover uranium by solvent extraction from stored process wastes. This building has no current or future commitment. A large steel-and-transite structure (2101M) is now vacant and could be readily adapted for the processing or storage of slightly radioactive materials.

2. Nuclear Safety

The large volume, relatively low excess reactivity status, nominal coefficient effects, and long moderator thermal relaxation time combine to make the Hanford production reactors relatively sluggish in kinetics characteristics. Individual control and safety rod worths are small, thus minimizing excursion potential.

The one significant adverse reactivity characteristic, a positive void coefficient in case of coolant loss, is given particularly rigorous attention. The coolant system is pressurized to the extent that column power rather than local specific flux is of primary importance. Each of the 12,000 tubes in these reactors is monitored by a pressure-sensitive gage set to activate the safety system in time to prevent deleterious results should coolant flow be threatened either by mechanical effects or by excessive heat-generation rates. Two levels of backup protection are provided to the primary coolant supply system. In view of the high degree of protection provided against coolant flow interruption, the possibility of sudden complete loss of coolant to the operating reactor is not considered to be a "credible accident." A comprehensive description of the safety protection measures provided and their administration is contained in reference ⁴.

Overboring of the graphite channels to provide increased conversion efficiency would simultaneously change the void coefficient in the desired direction; at the degree of overbore desired for efficiency reasons the void coefficient would be negative, or "fail safe," at operating temperatures.

The processing of enriched uranium in the Purex plant would require the installation of some new equipment and administrative controls to assure that nuclear safety is maintained. All of the indicated changes appear reasonable and nonrestrictive.

DECLASSIFIED

3. Economy

The one-pass low-temperature coolant supply gives the Hanford production reactors a distinct advantage in the coolant cost per megawatt. The Hanford plant has thus been consistently able to provide weapons-grade plutonium at lowest cost.^{/5/}

Unit production costs can be decreased even further and near-maximum conversion efficiencies achieved with the overboring of the graphite stacks to provide them with larger tube channels. A gain of 14-16 per cent in conversion efficiency, equivalent to 300 MW in productive capacity, could be achieved for an estimated cost of \$13,000,000 per reactor for the 500-mil-overbore, zirconium-tube case.^{/6/} A worthwhile fraction of the nuclear safety and conversion efficiency benefits of this program could be achieved at little more than the aluminum-tube-replacement costs with a 200-mil increase at the B-D-DR-F reactors.

A similar but not entirely additive measure for increasing neutron economy, and thus reducing unit product atom cost, is the "blackening" of the lattice with the addition of relatively black target elements to be supported by an increased enrichment level in the fuel elements. As was pointed out in item 1c, the average irradiation cost of tritium atoms was only about half that of the displaced plutonium atoms in the E-N loading.^{/7/}

Within the limits of the processing capability of the modified Purex plant, separations unit costs would be substantially reduced, about one-third, by processing all irradiated uranium through Purex-only as compared with the current Redox-plus-Purex processing pattern.

4. Reliability

The six 2000-tube reactors have accumulated approximately 90 reactor years of consistently efficient and safe operation. In addition many years of successful experience have been attained at Hanford in the operation of in-reactor loops. As pointed out in reference 8, we do not expect reactor-life-associated problems to unduly restrict production capacity and continuity during the ten-year period assigned to that particular study.

During the past six to ten years, the Purex and Redox plants have consistently demonstrated their capability to meet changing production assignments as scheduled. This pattern of reliability can be expected to continue under the revised operating patterns discussed above. To the extent that Redox would not be available as back-up, the reliability of Purex-only cases would be slightly less than at present.

DECLASSIFIEDDISCUSSION

The eight items characterizing reactor operation listed in reference 1 are discussed in the same sequence in Section A. Analogous considerations with respect to the Hanford separations plant are discussed in Section B. Comments on each of the alternate-product possibilities mentioned are given in Section C.

A. Reactor Characteristics and Flexibility1. Flux

Thermal flux in the Hanford reactors may be considered generally to be available in the range of 1×10^{13} to 1×10^{14} . The term "flux" must be subjected to considerable qualification, however, in order to be consistently applied.

a. Variation Within Lattice Cell

Figure 1 illustrates the variation in thermal neutron flux from the center of the fuel element in one lattice cell to the equivalent position in the adjacent lattice cell. There is almost a factor of two difference between the unperturbed flux peak in the moderator and the average across a natural uranium fuel element; this ratio would be increased or decreased with respective increase or decrease of the column blackness in a given lattice geometry.

b. Variation Within Active Zone

The Hanford production reactors are flattened to a considerable extent in the radial direction but only slightly so axially. The output of the 12,000 channels in the B-C-D-DR-F-H reactors is equivalent to somewhat over 9,000 effective maximum-power columns, or 9,000 ECT (Effective Central Tubes). The heat-generation rate of the average column is therefore approximately three-fourths that of the maximum.

The axial flux along the column may be described by a chopped cosine whose peak is approximately 1.4 times the value to which the average fuel element is subjected.

The average fuel segment within the active zone of the reactor is thus subjected to slightly over half of the maximum flux value to which any fuel element is irradiated and approximately 30 per cent of the unperturbed flux at the maximum point in the moderator.

Localized "flux traps" may be designed by varying the concentrations of fuel blackness and enrichment level in a number of surrounding columns. Increases of the order of 2 to 2.5 in local flux could be obtained by this method which has been used in partial degree in the past to create "hot spot" zones for accelerated fuel-irradiation tests.

Typical Flux Profile in Hanford Lattice
(2000-Tube Reactors)

Figure 1

DECLASSIFIED

c. Effective Value

In order to avoid the confusion of neutron energy groups and their effective cutoff energies, it is customary to state fluxes in terms of effective activation ability at room temperature (2200-meter-per-second neutron speed) of a $1/v$ absorber. In other words the activation counted on a foil would be interpreted in terms of the 2200 m/sec cross section listed in a table for that material.

Values of the "unperturbed" thermal flux of 7 to 9×10^{13} determined from detectors located in Hanford test facilities would correspond in general to values within the graphite moderator. Thus the effective thermal flux to which a segment of natural uranium, or a material of equivalent blackness, is subjected would have a maximum value on the order of $4-5 \times 10^{13}$ and an average value of about $2.5-3 \times 10^{13}$.

d. Flux Times Macroscopic Cross Section

The flux figure gives the local density of neutrons, but the isotope-production capacity must also include the volume to which that flux density applies. The volume of material which may be subjected to the given flux level in the six 2000-tube reactors may be easily estimated from the fact that the active column length of each of the 12,000 channels is 24 feet, and the fuel element's cross section is in excess of 1.5 in sq. In other words, over 50 miles of fuel elements may be under irradiation in these six reactors.

Another way of accounting for the product of macroscopic cross section and flux is to consider the proportionate megawatt output of the reactor. Except in the case of limitations on quantities of material available for irradiation, or limiting half-life and/or minimum specific-activity conditions, the total heat-generation output is generally a good index for approximating total isotope-production capacity. The total heat-generation capacity of the six 2000-tube reactors is on the order of 13,000 MW under current operating conditions.^{13/}

2. Neutron Spectrum

Although the lattice design of the Hanford reactors is regarded as "over-moderated," the fact that the graphite moderator, which largely establishes the effective thermal neutron speed, runs at elevated temperatures results in an upward shift of the thermal spectrum. As shown in Figure 2, which was based on a machine calculation applied consistently to the three reactor types indicated, the Hanford production reactors have a proportionately high component of flux in the logarithmic interval above 0.1 electron volt. It may be seen from the resonances also indicated in Figure 2 that the production of higher isotopes is favored in this situation. Thus a feature tending to limit the goal exposure of weapons-grade plutonium produced at Hanford becomes an asset in the production of higher-isotope plutonium, especially Pu^{240} .

Figure 2

DECLASSIFIED

Flux Spectrum Within Fuel
(Moderator-Temperature and Hardening Effects)

Relative Flux Per Unit Logarithmic Energy Interval
(Normalized to Peak Value)

Reference 9 describes the advantages of a program for producing plutonium of 18 per cent Pu^{240} content in Hanford reactors as the first stage in a curium-244 production campaign. Such a program is shown to have considerable advantage in the ultimate output of curium-244 relative to the irradiation of weapons-grade feed material.

Overboring of the process channels for increasing neutron efficiency would result in a somewhat "harder" neutron spectrum. Hardening of the spectrum, combined with the expected higher graphite temperatures in the overbored reactor, would increase the rightward shift indicated in Figure 2, adding to the effective production rate in target materials having resonant absorption peaks as shown.

3. Fuel Element Design Flexibility

Of the two major considerations in fuel-element design flexibility - irradiation performance capabilities and nuclear conversion characteristics - this section is directed to the former, and Section 4, Neutron Efficiency, covers the second aspect.

a. Channel Size and Fuel Shape

The Hanford reactors have operated for many years with ribbed aluminum tubes. The tube and rib design is intended to approximately center the fuel elements which rest on the ribs. The early solid-cylinder fuel design was replaced in 1958 with an I and E (Internal and External) design which provides a cooling channel through the core of the fuel element as well as along the outer annulus. The I and E design overcame the problem of "split" ruptures which were associated with the approach of the natural uranium core to α, β transition temperatures. Corrosion effects on the alsi-aluminum clad elements have been attacked in part by ensuring alignment (such as the partial use of bumper slugs to prevent "hot spot" failures), by reducing local cladding temperatures (with use of water-mixer elements, and radial, and to some extent axial, flattening), and use of chemical additives such as ph adjustments.

The graphite-moderated reactors have a high degree of flexibility open in fuel element design, but full advantage may be realized only at a price. The availability of large, smooth channels as would be provided by overboring would remove geometry restrictions presently imposed by the ribs (the fuel elements would have self-supporting feet) and would allow room for increased heat transfer surface and consideration of other fuel and target configurations and enrichment levels. Table I summarizes the available tube and channel sizes, including the convincing number of channels at the C reactor in which the overbore technique has been demonstrated.

DECLASSIFIED

Table I

Channel and Tube Configurations

Reactor Type	Approx. Number of Channels Per Reactor	Graphite Channel Diameter	Channel Length Including Reflector	Tube Dia. Inner Outer	Tube Rib Height	Tube Material and Type
B,D,DR,F,H	2000	1.769"	28'	1.604" 1.729"	0.080"	Ribbed Al
C	2000	1.804"	28'	1.640" 1.764"	0.089"	Ribbed Al
1) C Overbore	60-70	2.269"	28'	2.147" 2.248"	None	Smooth Bore Zr-2
2) K Self-Support	2500	1.906"	33.438'	1.724" 1.807"	None	Smooth Bore Zr-2
K-Ribbed	700	1.906"	33.438'	1.680" 1.806"	0.120"	Ribbed Al

- 1) Representative channels, both singly and in block array have been overbored at C Reactor to demonstrate the feasibility of increasing the channel size in the operating reactors.
- 2) Conversion from all ribbed aluminum tubes to thinner-walled zirconium tubes as shown above for the K's is currently underway, and is expected to be completed by the end of CY 1964.

With the space available in the overbore case, tube-in-tube and rod-in-tube geometries can be visualized which would be compatible with dimensional limitations of both fuel cladding and hydraulic requirements. Use of oxide elements could also be considered with the added channel space.

The large physical volume of the graphite reactors allows the possibility not only of increasing the fuel channel size, but of doing it on a selective basis. Thus a core of 500 to 1500 tubes could be overbored for increasing resonant flux, fuel design flexibility, or possibly power takeoff, and the remaining smaller-diameter channels could be used as a blanket to contain materials appropriate to a highly moderated thermal flux.

An additional favorable feature of the fuel flexibility afforded by the Hanford reactors is the potential access of instrumentation and electrical leads to each channel. This advantage may be used for monitoring pilot fuel tests and continuing irradiations, and it opens the intriguing possibility of ultimately tapping each reactor channel for electricity produced by direct conversion.

DECLASSIFIED

b. Fuel Performance Capabilities

High level fuel performance has been achieved at Hanford in the irradiation of metallic uranium clad in aluminum with AlSi bonding. Figure 3 shows the power-exposure relationship used in production scheduling¹⁰ of both natural and E metal used in the nonrepresentative plutonium program currently under irradiation in the D reactor.

In spite of the large increase in fuel volume in the overbore case, mechanical and thermal hydraulic demands on this element are somewhat less severe than on the present 0.94 enriched element as shown in Table II.

In addition to potential improvements in metal treatment, aluminum-cladding techniques, water treatment, flattening, and increased coolant flow, there is the possibility discussed previously of altering the fuel-target geometry in the overbore lattice to accommodate thermal hydraulic requirements (such as the tube-in-tube and rod-in-tube concepts mentioned earlier).

The ultimate exposure capability of metallic uranium fuel under Hanford reactor conditions is best exemplified by N-Reactor fuel-development experience. With maximum and average uranium temperatures greater than 380C, exposures in excess of 3000 MWD have been attained. Zirconium-clad E metal has been partially used to meet enrichment requirements in the present reactors, simultaneously providing pilot experience for N-Reactor under operating conditions.

A tube-in-tube or rod-in-tube design would permit consideration of driver-target combinations. If the outer-tube-contained target material were of relatively low cross section and very stable to irradiation (as in the case of an oxide or magnesium-heavy-metal dispersion clad with zirconium), an inner driver element of enriched uranium clad in less expensive aluminum might be charged on a shorter exposure cycle.

c. Available Fuel Fabrication Techniques

Large-scale facilities for fuel fabrication by the AlSi process are of course available. This process is limited to cylindrical elements, either of the solid or I&E type.

The large hydraulic press used to coextrude zirconium-clad fuel for N-Reactor is also available and has been used to produce demonstration quantities of E metal elements for the operating reactors.

Facilities are available for pilot-scale production of diffusion-bonded aluminum-clad I&E elements by the Hot Die Size process; however, none of the elements produced by this process have been irradiated as yet. The Hot Die Size process is less restricted to cylindrical symmetry than the AlSi process.

DECLASSIFIED

Figure 3

Exposure-Power Optimization
Used for D Reactor Scheduling

Table II

Fuel Dimensions and Thermal Hydraulic Characteristics

Reactor Model	Fuel Radius		Eff.	Heat Flux		Flow, gpm	Tube Power	Can Skin		Max. U	Avg. U	Max* Core Stress psi	Factor Weight Lbs U Per Fuel Element	Number of Elements Per Tube
	Outer	Inner		Inner	Outer			Temp °F	Temp °C					
Standard Nat.														
U Element for	0.310"	0.423		890,852	11.5			288						
B,D,DR,F,H	1.444"	1.356	8.865	472,666	37.7	1300	73.9	237	330	261	71,744	7.43		32-34
Standard Enriched														
Elements for	0.310"	0.423		965,850	12.3			280						
B,D,DR,C,F,H	1.444"	1.356	6.650	552,359	40.0	1300	84.7	244	377	293	87,182	5.36		32-34
C Overbore														
Nat. Uranium	0.334"	0.452		780,984	15.4			229						
Element	1.986	1.883	8.865	388,488	45.0	1400	80.1	226	363	280	85,438	14.87		32-34

*Unrelieved stresses corresponding to maximum instantaneous temperature changes.

DECLASSIFIED

Facilities for fabrication of ceramic and magnesium-dispersion elements are available in Hanford Laboratories for providing small quantities of these fuel elements. The plutonium-fabrication facilities used in the Plutonium Recycle Program provide technology for potential use in transplutonium irradiation campaigns.

4. Neutron Efficiency

The primary advantage of graphite-moderated reactors has been the low cost of heat removal; in the past this lower cost per MWD^{5/} has more than offset the greater inherent neutron economy of the heavy-water lattice. However, even this difference can be alleviated. The modest increase in fuel-to-moderator ratio accomplished in the K lattice design by going from an 8 3/8" to a 7 1/2" lattice resulted in a gain of approximately six per cent in conversion ratio. Extension of this principal in a program of overboring the 2000-tube reactors would result in a gain in conversion ratio in the range of 10-15 per cent as indicated in Figure 4. As the lattice effective blackness to neutrons is increased, the relative competition for neutrons by the graphite atoms is significantly reduced. Combined with their "hotter" neutron spectrum in the graphite reactor, the overbored Hanford reactors would be competitive in neutron economy also with the smaller heavy-water reactors. Graphite and shield-component boring techniques have been demonstrated in the C reactor on some 60-70 channels which have been provided with smooth-bore zirconium tubes and the larger self-supported aluminum-clad I&E elements. At a cost of \$13,000,000 for project action, the channels of a 2000-tube reactor could be overbored 500 mils and supplied with zirconium smooth-bore tubes to provide additional production capability equivalent to 300 MW heat-generation capability.^{6/} Lesser amounts of overbore would also provide a favorable return, though the largest rate of return on investment would be obtained in the 500-mil case. Thermal shield perforation dimensions in the B, D, DR and F reactors are such that a 200-mil overbore could be accomplished at much smaller cost; a worthwhile fraction of the available gains in Void-coefficient reduction and conversion-ratio increase could be considered for those four reactors with little expense beyond the normal replacement cost of aluminum tubes.

Another procedure for increasing the neutron economy is simply to increase the blackness of the loading by increasing the enrichment level and trapping the excess neutrons in added target atoms. This procedure may be employed either in the existing lattice or with overbore, although in the latter case the indicated gains would not be entirely additive. Figure 5 shows the potential relation in the present lattice for increasing production in relatively black target material as the uranium enrichment is increased. Although the available degree of enrichment has in the past been limited to 0.94 per cent U²³⁵, thus limiting alternate product capacity to about 20 per cent, dissolver limitations on enrichment level can no doubt be relieved by proper modifications and the use of E metal of up to 1.5 per cent U²³⁵ content considered; the potential alternate product capacity in that case might approach 50 per cent of the total, with a potential increase in neutron economy of 20 per cent as indicated in Figure 5.

DECLASSIFIED

Figure 4

Conversion Efficiency With Overbore

DECLASSIFIED

Figure 5

Conversion-Efficiency and Alternate-Product Potential
vs. Enrichment Level

DECLASSIFIED

5. Loading Pattern Flexibility

The ability to have individual access to 12,000 tubes in the B-C-D-DR-F-H reactors, most of which contain 32 individual fuel elements, makes the potential variation in loading patterns almost unlimited when supported by the dual aids of enriched fuel and supplementary control.

Enrichment may be used both to provide excess reactivity for irradiating target absorbers and to compensate additional leakage losses as the reactor flattening is extended. It is customarily loaded in one of four patterns: (1) In "spike" columns adjacent to columns containing either natural uranium or target elements, (2) In "E-ring" columns in a band around the edge of the flattened zone, (3) In "Blanket E" columns in the second and third lattice units from the reflector to support the blanket isotope-producing ("fringe poison") columns, and (4) In "striped" columns containing a staggered pattern of both E and target elements whose net reactivity effect approximates that of natural uranium.

Supplementary control is provided primarily by poison splines, solid boron-aluminum tapes inserted through a charging-face cap seal between the ribs beneath the fuel elements. These splines may be inserted or withdrawn during operation (the system is mechanized for remote withdrawal) into or from any tube in the reactor which has been provided with an inexpensive teflon cap seal.

These two degrees of freedom - E metal and splines - would permit the irradiation of any kind of material in any tube, or any partial column, within the reactor. Assurance of adequate excess reactivity by the charging of enrichment during outages is backed by the assurance provided by poison splines of adequate total-control capacity, adequate short-term and long-term reactivity-transient-compensating ability, and adequate geometric-control flexibility during the ensuing operating period.

An additional element of flexibility is available in the PCCF (Poison Column Charging Facility) which permits the insertion and removal of poison and dummy elements during operation. This facility was the sole method for providing supplementary poison insertion and withdrawal during operation prior to adoption of the spline system. Target elements with short half-lives or those to be discharged on a moment's notice may be discharged from such columns at any time desired during reactor operation (as well as during outages). Considerable development experience has also been obtained at Hanford in the use of an Operational Fueling Facility which would provide the ability to charge or discharge fuel during operation by means of water flushing; the latter system has not been taken to the project stage, however, and would require a thorough review of incentives for its adoption.

It is safe to consider the location of a given fuel and/or target assembly in any of the 12,000 channels. Each channel is individually monitored for flow and temperature; the pressure-sensitive flow monitor indication from each column is capable of activating the reactor safety control system.

DECLASSIFIED

HW-78100

Page 22

Volume II of the recently published hazards summary report^{/4/} describes the technology of the Hanford reactor process both qualitatively and quantitatively; pressures, specific heat generation rates, reactivity characteristics, operational procedure administration, safety instrumentation and control system automatic protection, and backup systems are included in the items discussed. The substantial degree of pressurization of the Hanford reactors, combined with the highly redundant pressure-monitor safety-trip system, has provided excellent assurance of flow integrity and high-level protection for many operating years.

One element of flexibility of the graphite-moderated reactors that has not been fully explored but which may have a large potential is the use of the process tube itself as a carrier for target material. With present co-extrusion techniques it would appear feasible to extrude the present tube with an inner aluminum surface and an outer target surface, such as an aluminum-cobalt alloy. Such a target would increase the conversion efficiency of the reactor; those neutrons absorbed in the target material would not be as subject to parasitic capture in water and aluminum as in present target-fuel configurations, and the fact that fuel would not be displaced by the poison would result in greater fuel utilization of the channel volume. Effectively, this is a "wrap-around" fuel concept with the existing fuel geometry. The target material incorporated in such an irradiation would have to possess a relatively low cross section, and the isotope produced should not have a short half-life. It would be envisioned that by the time the inner aluminum surface of the process tube had worn away by corrosion, the desired amount of outer material would have been converted by neutron combination. The discharged process tube could then be processed for the contained product. Cobalt-60 seems ideally suited for this concept. Americium-243 might also be of interest as a target material.

6. Product Changeover Time

As indicated in Section 5, small quantities of target material may be charged or discharged at any time during operation from a PCCF column, within the bounds of available supplementary control flexibility.

Variations in irradiation time desired may be accommodated over a large range. From maximum to minimum point, the flux level varies by a factor of three to four in an individual column and by a similar factor between central and corner fringe tubes. Under present operating conditions the central 80 per cent of the columns are discharged at approximately three-month intervals, and the remaining outer columns at longer intervals of up to twelve months. Although a central "block discharge" of the entire central zone is made at the H reactor (which is irradiating a series of E-N cores), a staggered discharge pattern is more characteristic of the other reactors at which several charging outages will take place during a three-month span.

In general, then, a major changeover of the core could be made over a three-month interval without significant effect on operating efficiency

DECLASSIFIED

HW-78100

Page 23

presuming, of course, advance notice of the Feed Materials and Fuel Preparation functions and previous representative test experience with the loading. The flexibility features of enrichment and splines discussed in Section 5 are counted on to accommodate a major loading transition such as in the case of current E-N loads and an earlier E-D load. There is no problem involved in leaving any number of columns in the central zone longer than the normal cycle, within the bounds of fuel and/or target-material integrity.

Fringe material would be changed out more slowly, requiring as much as a year in some cases to reach goal exposure. Discharges at less than goal exposure during the changeover do not, however, imply a linear loss, and discharge losses may become negligible during the final quarter of irradiation.

When buildup of fissionable atoms is involved, as in the production of higher plutonium isotopes or uranium-233, the time required for a changeover would be somewhat greater. Column and graphite heat-generation rates and reactivity parameters must be explored for both operational safety and efficiency implications. Again the availability of splines and the possibility of installing a spline-seal cap on each tube within and around an experimental loading pattern provides a wide margin of empirical flexibility.

7. Multiproduct Flexibility

The Hanford reactors have produced alternate products for the Commission for many years. As long as 15 years ago approximately one per cent of the neutrons were absorbed in the irradiation of such materials as thorium to make U²³³, beryllium nitride to produce C¹⁴, and lithium fluoride to produce tritium. Essentially all of the Co⁶⁰ supplied by the AEC in the early years was produced at Hanford. "Special Pickups" are routinely listed on every shutdown schedule.

The use of enrichment for augmenting reactivity, increasing flattening, and supporting blanket loadings has likewise been under conditions characteristic of dual-product operation. Approximately one-sixth of the columns in the reactors now contain E metal for which special handling and accounting measures are carried out. Complete operation with special handling techniques (for the purpose of keeping enriched fuel groupings from approaching minimum critical-mass configurations) has been demonstrated at the H reactor with its full-reactor E-N load; equipment and techniques were devised which resulted in only minor increases in discharge time.

Nuclear capacity for the irradiation of target materials is limited to around 20 per cent with the present 0.94 per cent E metal assuming reasonably black target elements. As was indicated in Figure 5 an increase in the U²³⁵ concentration in E metal to 1.5 per cent would permit the target-atom production rate to approach 50 per cent of the total reactor production. With overbore geometry consideration could be given to the designing of wrap-around elements employing U²³⁵-Al alloy fuel to assume fail-safe configurations on meltdown; if target-yield atoms were of higher value than

DECLASSIFIED

HW-78100
Page 24

plutonium, the lower conversion resulting in the loading void of U²³⁸ (due to loss of resonance and fast-fission effects) might be tolerated in order to make 100 per cent product from a given target material.

Within the percentage of neutrons provided by the indicated enrichment levels, the division of alternate-product irradiations could be quite flexible. Thus quantities of tritium, high 240-content plutonium, uranium-233, or other target products could be made over a range of desired ratios.

8. Pilot and Full-Production Timing

The question of time to produce requested quantities of materials, either in pilot lots or at large-scale equilibrium rates involves most of the aspects previously discussed, some of which are specific in nature but several of which are broad. Flux level and neutron spectrum and efficiency are certainly important in establishing the specific irradiation rate, but the effective exposure is also a function of the volume of material under irradiation, the decay constants of mother and daughter isotopes, and the cooling times required prior to chemical separation. Fuel-fabrication facilities are available for a number of element types, and the local Special Irradiations service has routinely handled hundreds of requests for special assemblies with and without special heat-generation and/or reactivity problems.

As pointed out in Sections 4 and 5, the range of enrichment and supplementary-control flexibility permits testing to be initiated on a pilot scale on a nearly empirical basis and at almost any time relative to reactor schedules. Thus pilot tests involving materials and configurations similar to those already encountered might be initiated within a few weeks, including preparation and signature of the necessary authorization documents.

Large-scale loadings would require, in addition to pilot test information, assurance that fuel integrity, hydraulic characteristics, reactivity coefficients, and other safety aspects were compatible with safe and efficient reactor performance. If such aspects are well known or represent a modest extrapolation from previous experience, as in the case of the later E-N loadings, a Process Improvement Transition Authorization may be prepared under which the irradiation may proceed with special plant-assistance attention but without major technical reservations; such a transition to operating practice could take place over a single irradiation cycle. If, on the other hand, the technical aspects are still subject to uncertainty, special production tests must first be carried out for evaluating incremental reactivity effects with critical experiments, or for evaluating thermal-hydraulic effects with special instrument probes and charge configurations. A year or more would be required to make a drastic large-scale change in loading or fuel type as, for example, in the case of the change from solid to I&E fuel elements.

The time to initiate a loop irradiation could vary all the way from the immediate insertion of a low-heat-generation target element into a one-pass or existing recirculating loop to the development, design, project installation, and testing of loops for the irradiation of thorium or neptunium

DECLASSIFIED

HW-78100

Page 25

solutions undergoing continuous chemical processing. The former might be accomplished in two days, the latter in two years.

In general, high flux levels are desirable for irradiating rare and limited amounts of material, though even in that case the cooling times required in the separations stages may alter the apparent cycle significantly. For large-scale loadings of high-cross-section materials, the Hanford reactors are ideally suited by virtue of their high megawatt capacity, low heat-removal cost, and large degree of loading flexibility.

DECLASSIFIED

B. Separations-Plant Characteristics and Flexibility

The Hanford area is an ideal location in which to process radioactive materials. The isolation of the chemical processing area makes it highly unlikely that small emissions of radioactive materials into the atmosphere could become of biological concern. So little rain falls in the area (about seven inches per year) that rain water evaporates rather than percolating through the soil to the ground water some 200 feet below the surface. This soil is sufficiently dry that water can be added up to about ten per cent by volume without drainage to the ground water. In addition, the soil has ion-exchange properties, so that radioactive materials tend to move through much more slowly than does water. Some materials, such as plutonium, are very tightly held and are effectively stored in the soil.

The complex of separations facilities includes eight plants in which the chemical processing of radioactive materials has been, or is being, conducted, plus a large steel-and-transite structure which could be readily adapted to the processing or storage of slightly radioactive materials. These facilities, together with a supporting complex of shops, laboratories, etc., are capable of conducting a wide variety of unit operations at rates varying from small-scale demonstration runs to large-scale committed production. The salient characteristics and advantages of each plant are discussed below.

1. Purex

The Purex plant, 202A, is a large-scale, heavily shielded solvent-extraction plant. It is currently capable of processing up to 7800 tons of aluminum-jacketed natural uranium per year for the recovery of decontaminated uranium, plutonium, and neptunium nitrates. With the change of a few pieces of operating equipment, irradiated thorium could also be processed at similar rates for the recovery of decontaminated uranium-233 and thorium. Irradiated thoria could be processed at rates of one-fourth to one-half those for metallic thorium.

Since the operating cost of this efficient plant is relatively insensitive to processing rate, the unit processing costs for the three current products are quite low at high processing rates. Because the equipment is large and the recycle of process streams is utilized to minimize product losses, a relatively large inventory of process materials is in the system at all times. This fact makes it relatively time-consuming to change from one set of products to another; alternate processing assignments are thus best handled in minimum numbers of large batches of materials.

With the expenditure of about three million dollars for three new dissolvers, some process vessels and pulse columns, and control equipment, the processing capability of the plant could be safely extended to include slightly enriched uranium in zirconium jackets. The revised plant would be capable of processing aluminum-jacketed uranium containing up to 0.94 per cent U²³⁵ at rates up to 8650 tons uranium per year. Higher-enrichment fuels could be processed at somewhat lower rates; for example, uranium containing 1.5 per cent U²³⁵ could be processed at a rate of about 5800 tons per year.

DECLASSIFIED

HW-78100

Page 27

Zirconium-jacketed fuels could be processed at rates about 20 per cent lower than those for aluminum-jacketed fuels of comparable enrichment.

This plant is ideally suited to the continuous processing of large quantities of radioactive materials. Within the limits of its processing capability, the unit processing costs are lower than those of any other comparable facility.

The processing costs of the revised Purex facility would be about one-third less than would be incurred by Redox-plus-Purex when processing a comparable load.

2. Redox

The Redox plant, 202S, is a heavily shielded solvent-extraction facility. It is currently capable of processing irradiated, aluminum- or zirconium-clad uranium containing up to 0.94 per cent U^{235} at rates up to 2400 tons per year. Decontaminated uranium, plutonium, and neptunium nitrates are recovered as aqueous solutions. In lieu of its normal assignment, this plant is capable of dissolving and processing relatively small quantities of specialty fuels for experimental purposes. For example, a six-kilogram batch of aluminum-plutonium alloy (PRTR fuel) was processed with a 99.5 per cent recovery of plutonium, excellent decontamination from fission products, and only about five per cent cross-contamination with normal Redox product. One-ton batches of irradiated uranium or thorium can be dissolved and analyzed to assist in determining reactor-physics constants. Small batches of irradiated thorium could be readily processed for the recovery of uranium-233; the thorium could also be recovered but with limited efficiency. Although the technology is not firm, it is probable that polonium-210 could be recovered from irradiated bismuth in this facility.

With the expenditure of a few million dollars for storage facilities, mechanical processing equipment, and changes of solvent extraction columns and controls, the processing capability of this plant could be greatly extended. For example, uranium power fuels of all enrichments, clad in aluminum, zirconium, or stainless steel, and containing alloying agents such as molybdenum, could be safely processed in the revised facility. Irradiated thorium* could also be recovered efficiently.

The Redox plant is best suited for the processing of specialty fuels. Although the unit processing cost incurred is somewhat higher than in Purex because of limited throughput, this plant can be operated on a campaign basis with minimum cross-contamination of consecutive products.

3. UO₃ Plant

The 224UA building houses six electrically-heated trough calciners and auxiliary facilities for the continuous conversion of uranium nitrate to uranium trioxide at rates up to 12,000 tons of uranium per year. Operating costs are low. Uranium containing up to 1.25 per cent U^{235} can be processed, with two different enrichments being run in parallel; studies in

*Thoria could also be processed at reduced rates.

progress indicate that enrichments up to 1.5 per cent U^{235} can be handled with minor changes in the process equipment and control systems. By current technology, this facility is not capable of calcining thorium nitrate to the oxide.

The uranium oxide produced in the continuous calciners is of uniformly good quality and reactivity - sometimes good enough to produce metal-grade UF_4 ; experimental work is in progress (in conjunction with Union Carbide personnel) to determine how this quality product can be produced consistently.

4. Plutonium Processing

In the 234-5 building, small-scale equipment is installed in lightly shielded hoods to convert plutonium nitrate to plutonium metal at rates up to 6000 kilograms per year. These facilities are operable with plutonium containing up to about 8% Pu^{240} ; the processing of plutonium having a higher fraction of the higher isotopes would require the addition of more shielding, currently estimated to cost about \$500,000.

Space is available for the installation of parallel processing equipment for the simultaneous processing of different-specification products. For example, U^{233} might be reduced to the metal in one line, while plutonium (either weapons-grade or unclassified) might be processed in the other.

Laboratory and pilot-plant equipment are available in which development quantities of plutonium or other slightly radioactive materials can be converted from a chemical salt to the metal or to the metal alloyed with other materials. These facilities are being used part time in support of the PRTR program, and could be used for other developmental purposes as well.

Facilities are currently being installed in which plutonium can be recovered from a wide variety of scrap materials. This facility will be quite flexible and, when not processing plutonium scrap, could be made available for the recovery of other moderately radioactive materials.

5. Strontium Semiworks

The 202C building and auxiliaries were originally used to pilot the Redox and Purex processes at full levels of radioactivity. In 1961, the facilities were modified for the purification of strontium-90 for the SNAP program. The facility contains equipment in which dissolution, distillation, precipitation, solvent extraction, and ion exchange operations can be performed. Whereas the facility is heavily shielded and can therefore process very radioactive materials, it is contact-maintained and does not have the operating reliability associated with the other processing plants.

This plant is ideally suited for the processing of relatively small quantities of highly radioactive materials.

6. B-Plant

The 221B plant was originally used to recover plutonium from irradiated uranium, using the obsolete bismuth-phosphate-precipitation process. According to current plans, not yet approved in their entirety, this facility is to be modified to segregate the long-lived heat-producing fission products from radioactive wastes as a part of the Hanford Waste Management Program.

DECLASSIFIED

7. T-Plant

The T plant was originally identical with the B plant, except that it included two heavily shielded cells equipped as a remotely-operated and-maintained pilot plant. The pilot-plant portion is not now in use, but the rest of the facility is being used to decontaminate and repair plant vehicles and operating equipment.

8. U-Plant

The U plant was also originally identical with B-Plant. It was later modified to recover uranium from T- and B-Plant wastes, using a solvent-extraction process. This large-scale processing complex is available for reassignment.

This facility is best suited to the processing of relatively large quantities of highly radioactive materials. The flexibility of the unit is somewhat limited, however, in that the cell covers do not have enough shielding capability to provide sufficient attenuation of gamma radiation from very radioactive materials, and the sampling of process solutions must be accomplished from the affected area. Processes using either precipitation or solvent extraction would likely be compatible with this facility.

9. 2101M Building

This building was originally constructed for the machining, inspection, and storage of graphite-moderator bars for the later Hanford reactors. The equipment used for this work has since been removed, and the building is nearly vacant. The building, serviced by railroad and truck unloading docks, contains over 110,000 square feet of concrete floor space. Constructed of steel frame and transite siding, the building is ideal for the processing or storage of slightly radioactive materials.

10. Miscellaneous Facilities for Recovering By-Products

In several areas, facilities have been modified or installed to permit the recovery of selected fission products on a limited basis. In the head end of the Purex Plant (202S) two solid-bowl centrifuges and auxiliaries were bypassed by the normal production flows and made available for other use. These facilities are being used to recover a strontium concentrate from the Purex wastes. This concentrate is accumulated in an underground tank and subsequently purified in the Strontium Semiworks. The purified strontium can be precipitated as the carbonate and transported to other sites in specially designed shielded filter casks. Other fission products can occasionally be isolated by precipitation processes, and shipped in the shielded filter-casks to the Hanford Laboratories for purification and experimentation.

Experimental quantities of purified cerium-144, promethium-147, cesium-137, strontium-90, and technetium-99 were prepared in this way. This processing pattern could also be used to develop processes for the recovery of americium and curium from irradiated materials.

DECLASSIFIED

HW-78100
Page 30

A loading facility is located near an underground tank (in C Farm) in which cesium-137 can be adsorbed on a zeolite material in special shielded tanks mounted on a railroad car. The loaded tanks can then be transported to Oak Ridge and the cesium eluted.

With the installation of the waste-management facilities in B-Plant, the recovery capability for long-lived heat-producing fission-products will be greatly increased. Plans are being developed by the Division of Isotope Development to install a purification and encapsulation facility adjacent to the B plant, so that the fission products can be prepared in end-use form. During a five-year period starting about 1967, recovery capabilities will be increased as indicated below, then will decrease sharply to a value dependent on the normal rate of irradiated-fuels processing at that time.

<u>Fission Product</u>	<u>Annual Recovery Rate, millions of curies</u>	
	<u>1963</u>	<u>1967-71</u>
Strontium-90, crude	-	25
, purified	4	-
Cesium-137, crude	5	25
Cerium-144, crude	5	350
Promethium-147, crude	-	50
	<u>kilograms</u>	
Technetium-99, crude	-	200

Other fission products and transuranic elements could also be recovered, although the current plan does not include these activities.

DECLASSIFIED

C. Alternate-Product Possibilities

The parameters of Hanford production reactor and separations plant characteristics are discussed in the following paragraphs in relation to the production of the various isotopes indicated in reference 1.

1. Weapons-Grade Plutonium

The Hanford production reactors have advantages and disadvantages in the production of weapons-grade plutonium. However, the low cost of heat removal in the one-pass system having a low-temperature water supply outweighs the disadvantages of more limited goal exposure due to contaminant buildup, (which limit is not far removed, however, from optimum limits based on fuel performance and product burnout) and to reduction in conversion ratio in the overmoderated graphite lattice. The latter disadvantage can be largely alleviated by overboring of the reactors, substantially increasing the 2000-tube-reactor unit-cost advantage.

The Purex separations plant could, within the limits of its processing capability, recover and decontaminate the uranium, plutonium, and neptunium at very low unit cost. With the indicated revisions, all types could be processed in this facility, leaving the Redox plant free for other assignments.

2. Tritium

As indicated earlier, the graphite reactors benefit greatly from an increase in the productive cross section inventory in the reactor. The large cross section of lithium-6 allows a greater conversion gain for this product than with any other useful target material. The most economical process for making limited amounts of tritium (up to 12-14 kgs/year at all eight Hanford production reactors) thus appears to be that of combining slightly enriched uranium loadings with lithium-aluminum targets (E-N loadings). The irradiation cost to produce tritium on an atom basis would be roughly half of that of the displaced plutonium atoms, assuming the value per atom of the plutonium which was still produced remained the same as without the E-N load.

Hanford currently has no capability for recovering tritium from irradiated lithium.

3. Unclassified (and High-240) Plutonium

The lower cost of heat removal in the Hanford reactors becomes even more advantageous as the restrictions on Pu²⁴⁰ content are removed.

DECLASSIFIED

Figure 6

Pu^{240} Buildup in 2000-Tube Reactors

For applications in which the goal is to convert as much Pu^{239} to higher isotopes as possible, the previous disadvantage of the higher-temperature neutron spectrum in forming Pu^{240} becomes an asset. For a given amount of plutonium fuel, or a given amount of heat withdrawal from plutonium fissions, 10-15 per cent more higher isotope is formed than in a heavy-water lattice. The greater efficiency of the graphite reactors for producing higher-isotope plutonium does not extend past the non-fissioning isotope Pu^{242} . At that point, premium is indicated for higher flux levels.

Figure 6 shows the rate of Pu^{240} buildup in plutonium in the 2000-tube reactors as a function of exposure and fuel-enrichment level.

The recovery of unclassified and high-240-content plutonium from irradiated uranium can be effected on a campaign basis in the Purex plant for the same low unit cost as indicated for weapons-grade plutonium. The conversion of the recovered plutonium to the metal would require additional shielding or equipment modifications to protect 234-5 Building operating personnel.

4. Uranium-233

The Hanford reactors have a unique opportunity for producing "clean" U^{233} , relatively free from the bothersome isotope U^{232} . The following schematic shows the high-energy n,2 reaction on thorium-232, which is a major contributor to this contaminant. By placing the thorium in segregated columns, which are protected by the surrounding graphite moderator from high-energy neutrons, and by discharging it before the U^{233} being formed from its 27-day mother has had a chance to undergo excessive fissions (and thereby generation of fast neutrons), the buildup of U^{232} in the product will be limited.

* $T_{1/2}$

The possibility of producing clean U^{233} will be tested in the near future, as well as the effect of lattice parameters.

The possibility of loop irradiations discussed for Np^{237} could also be considered as a method for enhancing "clean" U^{233} production.

The feasibility of producing "clean" U^{233} can be readily established by dissolving test quantities of irradiated thorium in the Redox plant and recovering the U^{233} in existing facilities. Some plant modifications

should be made if thorium is to be recovered routinely in large quantities in this facility. To the extent that the total processing capability is not exceeded in Purex, irradiated thorium could be processed in that facility without major change.

5. Neptunium-237

The following diagram shows the manner in which Np^{237} is formed from irradiation of accumulated U^{236} and from $n,2n$ reactions in U^{238} .

* $n,2n$ reaction in U^{238} proceeds at about three per cent of the fast-fission rate.

The production of neptunium-237 from uranium-236 is favored by a uranium-236 resonance just below the uranium-238 resonance peak. This reaction is presently being exploited by the recycling of all slightly enriched fuel at Hanford to build up the uranium-236 levels in this material as a target for producing neptunium-237.

Facilities are in place to recover most of the neptunium from all of the irradiated uranium processed at Hanford.

6. Plutonium-238

The following diagram shows the way in which Pu^{238} is obtained from Np^{237} .

A greater over-all yield of Pu^{238} from Np^{237} can be obtained in a low-flux field due to the large fission cross section of Np^{238} and its particular half life. Np^{238} fission products also contribute substantially to the amount of decay time required prior to Pu^{238} separation.

DECLASSIFIED

The accessibility of the Hanford reactor experimental facilities and process tubes allows the consideration of the continuous irradiation of Np^{237} in solution form with product bleed-off to remove the Pu^{238} formed. Because the Pu^{238} cross section is greater than that of the Np^{237} , small-percentage conversions per irradiation interval are necessary if the product is not to become excessively contaminated with higher plutonium isotopes. Even with irradiations targeted at 20 to 25 per cent conversion, product purity of less than 80 per cent is obtained, indicative of even greater losses in the conversion from the Np^{237} .

The aims of a loop facility for Np^{237} irradiation would be (1) to reduce substantially the ratio of out-of-pile to in-pile inventory presently restricted by decay and separation times, and (2) to increase substantially the attainable purity of final product, say to 90 per cent rather than 80 per cent, simultaneously minimizing Np^{237} losses.

7. Polonium-210

Bismuth-209 has an extremely low cross section for the formation of polonium-210 by neutron capture. Reduction of fuel inventory to provide space for bismuth would thereby lower the effective blackness of the reactor and thus reduce its conversion efficiency. Space not otherwise productively used in the reactor, as in centering materials for short fuel charges or in unused test holes or possibly purposely created voids, could be profitably filled with bismuth provided nominal cooling were supplied. Or continuous processing of liquid bismuth from a circulating loop might be visualized if demand were sufficiently great and process-channel and test-hole space were made available. The bismuth-polonium chain is shown below:

The technology for recovering polonium from irradiated bismuth in the Hanford facilities is not well known. If solid bismuth target elements were to be irradiated, it is probable that the polonium could be recovered in the Redox facility. Development work would be required to define the recovery process for Redox or for the reactor loop concept.

8. Transplutonium Isotopes

Curium-242, an isotope having a half life similar to that of polonium, can be produced by the irradiation of americium-241 which has a large cross section allowing high conversion in a single irradiation. Americium could be occasionally "milked" from plutonium inventories by the Hanford separations plants, then alloyed with aluminum for irradiation as target elements. The 163-day curium-242 decays by alpha emission to the 89-year plutonium-238; in fact this chain could be used to produce a significant fraction of the total Pu^{238} production.

DECLASSIFIED

HW-78100

Page 36

Cross sections of Pu^{242} and Am^{243} , of importance in the Cm^{244} -production chain are fairly low. It would be beneficial to carry out the first irradiation stage starting with depleted uranium in the graphite reactors; the quantities involved at this stage are large, and the higher-energy neutrons in the graphite lattice are conducive to higher Pu^{240} production. Due to lower cross sections and limited quantities, the higher stages can probably be most effectively carried out under maximum flux conditions. Methods have been considered for their complete production in the Hanford reactors, ¹¹/utilizing PuAl-alloy elements in the intermediate stage. The PuAl alloy could be fabricated in the 234-5 Building without interference with weapons production with the addition of some new equipment.

The following sketch shows the chains involved in curium-242 and curium-244 production.

* $T_{1/2}$

NOTE: Branching ratio, or capture to fission ratio, from Pu^{239} increases with neutron temperature.

9. Cobalt-60

It has been previously mentioned that a possibility exists for incorporating cobalt into the process tube. The cost of neutrons absorbed in the cobalt so placed would be less than the cost of neutrons now used in plutonium production in that the process efficiency for dual product operation--cobalt-60 and plutonium--would be less per atom of product than now exists for plutonium only. The productive cross section added to the reactor would then be in a position now occupied by parasitic cross section. The increased enrichment required to support neutrons absorbed by the cobalt would be made up by increasing the amount of slightly enriched uranium. If sufficient cobalt could be added to the tubes (subject in part to a study of the reactivity and safety parameters involved), such a configuration could be as efficient as an E-N loading. Thus the over-all cost to the process, as far as atoms of cobalt-60 are concerned, would be about half that of atoms of plutonium formed. The cobalt-60 might have a cost as low as ten cents a curie. It has been roughly estimated that an irradiation time of two to three years, which is about the life of tube service in the

DECLASSIFIED

HW-78100
Page 37

central tubes, would provide near optimum exposure for production of cobalt-60. Thus the useful tube life would essentially be terminated at the point of optimum cobalt-60 buildup. If this point happened to coincide with determination of the useful life of the reactor, the uranium could be discharged from the reactor at that time. The cobalt built up in the process tubes could then be used in the reactor for a chemo-nuclear process. Such a process would have to accommodate itself to tube geometry and reactor piping as much as possible. Immediately suggested would be a gaseous reaction that utilized the present stack-atmosphere system, or a simple liquid reaction that utilized the process-tube channels. If reactions were found that could be adapted to this facility, no expense would be necessary for a building for special packaging of the cobalt, nor for special containers for taking care of the gamma irradiation when the source was not desired. Alternatively, of course, the cobalt built into the process tubes could be discharged from the reactor into the cooling basin much as is done now during tube replacement. Further processing and packaging then would have to be done prior to its utilization in a commercial facility.

If desirable for handling reasons, cobalt could, of course, be irradiated for any length of time desired in segregated columns, supported by surrounding E columns which could be changed out at normal goal-exposure frequency.

10. Thulium

Thulium has been recently proposed as an interim isotope heat source which might fill in for the transplutonium isotopes during the space mission development stage.^{12/}

The most desirable feature of this 170-day-half-life material is that it could be encapsulated in pure form prior to irradiation and simply left in a reactor until needed for a space mission. Irradiation of such a material, which has a reasonably high neutron absorption cross section, in Hanford PCCF columns would provide ideal flexibility for its buildup, continuing activation, and immediate availability.

DECLASSIFIED

REFERENCES

1. HAN-85360, Reactor Advantages, J. E. Travis to W. E. Johnson, 6-14-63.
2. HW-78101, Hanford N-Reactor Advantages, R. L. Dickeman, 6-27-63.
3. HW-74094 Vol 2, P. 234.
4. HW-74094 Vol 2, Hazards Summary Report, Process and Technical Data, B-C-D-DR-F-H Reactors, Research and Engineering Operation - IPD, 5-15-63.
5. HW-74551, Product Costs - Grams Generated Fourth Quarter FY-1962, W. G. Smith, 8-3-62.
6. HW-66823, Major Overboring of C Reactor, E. C. Wood, et al, 10-6-60.
7. HW-75921, Test Results and Economic Analysis for H Reactor E-N Core Loadings, L. W. Lang, 12-18-62.
8. HW-77946, Study of Hanford Production Capability Through FY-1973, A. B. Greninger, 6-19-63.
9. HW-77675, Depleted Uranium Irradiations, L. W. Lang, 5-21-63.
10. HW-77285, Status of Special Loadings, R. W. Bown, 4-1-63.
11. HW-77202, Proposal to Produce Transuranium Isotopes in Hanford Production Reactors, L. E. Kusler and R. O. Gumprecht, 4-12-63.
12. Vol. 6, No. 1, ANS Transactions, June 1963, Evaluation of Isotope Thermionic Generators, R. J. Harvey, et al.

DECLASSIFIED

DISTRIBUTION

- 1-10. RLOO-AEC
Attention: J. E. Travis
- 11. W. E. Johnson
- 12. R. L. Dickeman
- 13. L. L. German
- 14. A. B. Greninger
- 15. H. M. Parker
- 16. P. H. Reinker
- 17. S. H. Small
- 18. D. L. Sorenson
- 19-98. Extras
- 99. Records Center
- 100. 300 Files

**DATE
FILMED**

10/27/93

END