BNL-73457-2005-CP

***Upgrade of RHIC Vacuum Systems For High
Luminosity Operation***

H.C. Hseuh, M. Mapes, L.A. Smart, R. Todd, D. Weiss

***Presented at the Particle Accelerator Conference(PAC'05)
Knoxville, Tennessee
May 16-20, 2005***

Collider-Accelerator Department

**Brookhaven National Laboratory
P.O. Box 5000
Wpton, NY 11973-5000
www.bnl.gov**

***Managed by*
Brookhaven Science Associates, LLC
for the United States Department of Energy under
Contract No. DE-AC02-98CH10886**

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FOR UNCLASSIFIED, UNLIMITED STI PRODUCTS

Available electronically at:

OSTI:

<http://www.osti.gov/bridge>

Available for a processing fee to US. Department of Energy and its contractors, in paper from:

US. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831
Phone: (865) 576-8401
Facsimile: (865) 576-5728
E-mail: reports@adonis.osti.gov

National Technical Information Service (NTIS):

Available for sale to the public from:

US. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22131
Phone: (800) 553-6847
Facsimile: (703) 605-6900
Online ordering: <http://www.ntis.gov/ordering.htm>

Printed on recycled paper

H.C. Hseuh[†], M. Mapes, **L.A. Smart**, R. Todd and D. Weiss, **BNL, Upton, NY 11973, USA**

*Work performed under Contract No. DE-AC02-98CH1-886 with the auspices of the US Department of Energy
thseuh@bnl.gov

Cu ions were divided by 2.7 ($= Z_{Au} / Z_{Cu}$) and that of proton and deuteron by 79 to give the Au charge equivalent in unit of 10^9 Au ions. For the initiation of pressure rise at injection, I_{th} was about a factor of two higher after bake (e.g. 2001 and 2002 vs. 2003). I_{th} has increased further with the addition of NEG coated beam pipes at these sections. The equivalent I_{th} for p, d and Cu are higher than that of Au, even after factoring in the total charges.

Table 1. I_{th} expressed at 10^9 Au charge equivalent for different species and running modes at IR12 (IP) and BO11 (Single). NEG coated beam pipes were installed and activated in these regions for 2004 run (IP only) and 2005 run.

2002 – not baked			
p - 110	p - 110	p - 110	2002 – not baked
p - 110	114	44	2003 - baked
p - 110	126	76	2005 - NEG
d - 55	>150	>89	2003 - baked
d - 110		89	2003 - baked
Cu - 55	> 92	> 92	2005 - NEG
Cu - 110	> 55	~ 55	2005 - NEG
Au - 55	~ 70	20	2001 – not baked
Au - 110	~ 60	10	2001 – not baked
Au - 55	>120	45	2003 - baked
Au - 110		35	2003 - baked
Au - 55	>100	>50	2004 - NEG

Figure 2. The Cu beam ion induced desorption yields from vacuum chamber wall vs. incident angles for stainless beam pipes (open markers) and NEG coated surface (filled markers) at single beam insertion regions. The effective desorption yields of NEG coated pipes are several times lower than the ones without coating.

NEG Coating of Warm Beam Pipes

To increase the effective pumping speed, linearly distributed pumps in the form of NEG coated beam pipes [5] have been installed in RHIC warm sections. The NEG coating will provide effective pumping speed of $> 10^2$ l/s.m and will reduce the SEY, and the electron and ion desorption rates. The NEG coating of the standard 12cm diameter insertion beam pipes was contracted to SAES Getters, Inc. with license from CERN. Up to this date, approximately 250m of NEG coated pipes have been installed and activated. The pressure rise threshold of the NEG coated sections, as shown in Table 1, is found to be higher than un-coated sections (for example, p-110 in

2005 vs p-110 in 2003 for the single beam section). The magnitude of pressure rise at warm sections with NEG coated beam pipes is also lower than that of un-coated sections [4]. However, the magnitude of the pressure reduction is not as dramatic as one would expect based on pumping speed alone. The beam ion induced desorptions of the NEG coated and un-coated sections have been studied using Cu beam at 10 GeV/ μ and the result is shown in Fig. 2. The un-coated section has effective desorption coefficients about one decade higher than the coated sections [6]. Additional 250m NEG coated beam pipes will be installed in the upcoming shutdown.

Cold Bore Pressure Rise

Pressure rise of a few decades, as shown in Fig. 3, has been observed in some cold sections during machine studies with 108ns bunch spacing. This was measured by cold cathode gauges at room temperature connected to the cold bore through a small conduit with conductance of ~ 1 l/s for hydrogen. Assuming balanced gas flow to and from the cold bore and considering thermal transpiration, the real gas density in the cold bore is about one decade higher than the gauges indicated. This cold bore pressure rise was caused by electron cloud and ESD. To reduce ESD for high luminosity operation, the amount of cryo-condensed gas has to be reduced to less than one monolayer. Without active pumping, the cold sections would usually drift to 10^{-1} Torr level during the annual summer warm up, equivalent to ~ 10 monolayers of condensed gas after cool down. Some of the 40 cold bore sections had been pumped out to below 10^{-3} Torr before cool down, to evaluate its effect on the cold bore pressure rise. Roughing pumps and small ion pumps will be installed to pump and maintain the cold bore at high vacuum levels after warm up. Additional hydrogen pumping will also be implemented in the future at warm-cold transition to reduce hydrogen migration from some warm sections to near by cold sections.

Fig. 3. Pressure rises (top) in the arc cold bore during 110-bunchproton (bottom) injections. The pressures were monitored with cold cathode gauges at room temperature connected to cold bore through a small conduit, resulted in readings a decade lower than the actual gas density in the cold bore.

Vacuum Monitoring

The monitoring and control of RHIC vacuum devices is through the use of RS485 serial communication. Up to 32 like devices are connected to a common PLC co-processor port. Due to the integral processing time of the co-processors, the digital vacuum readings are updated ~ every 8 seconds for vacuum gauges, and up to 30 seconds for multi-parameter devices like residual gas analyzers and turbopump stations. To monitor and correlate the pressure rise with the beam intensity and other machine parameters, faster **data** logging was implemented. The analog output signals of selected CCGs from both warm and cold sections were fed into MADC modules, digitized and logged at rates up to 10 Hz. The enhanced **data** logging capability allows accurate comparison and correlation of the pressure rise with the signals from beam current monitors, electron detectors, beam loss monitors and other diagnostics.

FUTURE IMPROVEMENT

To meet the luminosity goals in RHIC for year 2006 and beyond, the total beam intensity has to be increased by a factor of two or more, through increased bunch intensity, number of bunches or both. The expected pressure rise during injection and transition will be excessive based on observation from the past runs. The following remedies are being planned to further reduce the pressure rise.

In-Situ Bake of Diagnostic Devices

The major goal in the last few years was to lower the pressure rise at the incoming insertion sections and at the common beam lines around the detectors, thus reduce the beam-gas background to the major experiment detectors. However, during a few high intensity stores, excessive pressure rise was observed at the outgoing lines where most diagnostic equipments were located. This high pressure has caused large amount of beam scattering and beam loss in the long arcs. Therefore individual devices, such as polarimeters and IPM, in the outgoing sections will be evaluated and in-situ baked to the maximum allowable temperature to reduce the static and dynamic pressure. Non-conventional bakeout methods will be developed for some of these devices.

Vacuum Upgrades of Interaction Regions

The beam intensity limits at RHIC are mainly at a few interaction regions, where the pressure rise has been the highest, due to the doubling of the number of bunches. Upgrade of the IR vacuum, however, is most difficult since the beam pipes are integral part of the experimental detectors which prevent the addition of conventional pumps or thorough in-situ baking. Furthermore, the IR beam pipes are made of beryllium and aluminium for their transparency to energetic particles. Both beryllium and aluminum have high SEY as compared with stainless surface. The upgrade path for each IR will be different depending on the exact nature of the detectors and the beam pipes. In general, the plan is to coat the 7cm

diameter IR beam pipes with NEG and activate it if possible. If fully activated, the coating should have low SEY, low ESD and high linear pumping speed. Partially activated NEG surface should also provide the advantage of lower SEY. The vendor for the NEG coating of RHIC 12cm insertion stainless beam pipes is not interested to coat RHIC beryllium beam pipes, which are up to 8m in length, brittle, toxic and very expensive to replace; and may have residual radiation. Development of NEG coatings using an innovative horizontal magnetron cathode [7] has been carried out in the last year. Test pipes of similar dimensions to the IR pipes have been successfully coated using this DC magnetron sputtering technique developed for titanium nitride coating of SNS accumulator ring vacuum chambers [8]. Coating of actual IR beam pipes will start this coming shutdown when the actual beam pipes are removed from the detectors.

SUMMARY

Improvement of the RHIC vacuum system before 2005 physics runs has produced some positive effect on the beam intensity thresholds for the pressure rise as compared with previous runs. The magnitude of the pressure rise is also lower than that of the previous years. Both thorough in-situ bakeouts and NEG coated beam pipes have offered the most benefits in reducing the pressure rise during high intensity ramps. Further improvement, especially at interaction regions and at cold bore sections, is needed to allow further luminosity development. To that end, the NEG coated beam pipes will be installed at IR, and the surface condensates in the cold bore will be reduced to below a monolayer through active pumping after warm up.

ACKNOWLEDGEMENTS

The authors would like to thank W. Fischer, H. Huang, U. Iso-Ariz and S.Y. Zhang for fruitful discussion and members of Collider-Accelerator Vacuum Group for their relentless effort in improving the RHIC beam vacuum systems.

REFERENCES

- [1] M.J. Rhoades-Brown and M. A. Harrison, RHIC Technical Note #106, BNL-47070, Dec, 1993.
- [2] H.C. Hseuh, et al, Proc. PAC'99, 557 (1999).
- [3] W. Fischer, et al, Proc. ECLLOUD'04, 'Electron Clouds and Vacuum Pressure Rise in RHIC', Napa, CA (2004).
- [4] S.Y. Zhang, et al, 'Beam Induced Pressure Rise in RHIC', these proceedings.
- [5] C. Benvenuti, Proc. PAC'01, 602 (2001).
- [6] H. Huang, et al, 'Beam Pipe Desorption Rate in RHIC', these proceedings.
- [7] D. Weiss, et al, 'Development of NEG Coating for RHIC Experimental Beam Tubes', these proceedings.
- [8] R. Todd, et al, 'Summary of TiN Coating for SNS Ring Vacuum Chambers', these proceedings.