BNL-73492-2005-CP

***Measurement and Optimization of Local Coupling
from RHIC BPM Data***

R. Calaga, S. Abeytunge, M. Bai, W. Fischer, et al

***Presented at the Particle Accelerator Conference(PAC'05)
Knoxville, Tennessee
May 16-20,2005***

Collider-Accelerator Department

Brookhaven National Laboratory

P.O. Box 5000

Upton, NY ■1973-5000

www.bnl.gov

Managed by

Brookhaven Science Associates, LLC

for the United States Department of Energy under

Contract No. DE-AC02-98CH10886

This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or **imply** its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FOR UNCLASSIFIED, UNLIMITED STI PRODUCTS

Available electronically at:

OSTI:

<http://www.osti.gov/bridge>

Available for a processing fee to US. Department of Energy and its contractors, in paper from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831
Phone: (865) 576-8401
Facsimile: (865) 576-5728
E-mail: reports@adonis.osti.gov

National Technical Information Service (NTIS):

Available for sale to the public from:

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22131
Phone: (800) 553-6847
Facsimile: (703) 605-6900
Online ordering: **<http://www.ntis.gov/ordering.htm>**

Printed on recycled paper

Measurement and optimization of local coupling from RHIC BPM data *

R. Calaga, S. Abeytunge, M. Bai, W. Fisches, *BNL, NY 11973, USA*

R. Tomás *CELLS, Barcelona, Spain*

A. Franchi *GSI, Darmstadt, Germany*

Abstract

Global coupling in RHIC is routinely corrected by using three skew quadrupole families to minimize the tune split (ΔQ_{min}). In this paper we propose to re-optimize transverse coupling by minimizing the resonance driving terms (RDT's) and the coupling matrix ($|\bar{C}|/\gamma^2$) in two steps: 1. Identify locations with coupling sources by inspection of the driving terms and the C-matrix around the ring and minimize the discontinuities and 2. Find the best configuration of the three skew quadrupole families to minimize both ΔQ_{min} and RDTs (f_{1001}). The measurements of f_{1001} and $|\bar{C}|/\gamma^2$ at injection and top energy to identify local coupling sources are presented.

INTRODUCTION AND MOTIVATION

RHIC has the following relevant sources of transverse coupling:

- Skew quadrupolar errors in the interaction region (IR) magnets
- Tilts in the triplet quadrupoles
- Sextupolar feed-down to skew quadrupolar field at the chromaticity sextupoles and at all the dipoles

RHIC is equipped with three families of skew quadrupoles in the arcs to compensate global coupling. The coupling vectors of these families are represented in Fig. 1. In addition, RHIC is also equipped with two local skew correctors in each interaction region (IR). Global coupling is routinely corrected at RHIC by minimizing ΔQ_{min} using skew families either by a tune scan, a skew quadrupole modulation technique [1], or at injection using N-turn maps [2]. Two families with a 90° phase advance are enough to construct a unique coupling vector and minimize the closest tune approach. The RHIC coupling correction system consists of three families with a phase advance of 120° between them. Therefore, there exists an infinite number of settings for three families that minimize the closest tune approach.

Assuming that the setting given by the vector (f_1, f_2, f_3) minimizes the tune split, then any other setting of the form $(f_1 + \Delta, f_2 - \Delta, f_3 + \Delta)$ with arbitrary Δ is also a local minimum of the tune split. This feature can lead to situations in which the tune split is minimum (globally decoupled) but the machine is highly coupled locally. Fig. 2 shows an illustration by plotting the RDT, $|f_{1001}|$ around RHIC

Figure 1: Coupling vectors of the three skew quadrupolar families of RHIC.

lattice (yellow ring) for different configuration of the three families, all yielding a ΔQ_{min} of about 0.001.

Figure 2: f_{1001} from model for a set of different skew families configurations. All of them have a tune split close to 0.001. The numbers in brackets represent the strength of the families in units of $10^{-5} m^{-1}$.

Although, different configurations all yield a minimum tune split, $|f_{1001}|$ varies significantly for each setting. The best setting should have the lowest values without large spikes. A good recipe is to minimize the average and the standard deviation at the same time. Situations as the top curve of the plot have an impact even in the machine optics and must be avoided. The measurement of the coupling RDTs and C matrix around the ring is the only way to ensure an optimum correction of coupling.

* This work was performed under the auspices of the US Department of Energy

MEASUREMENT OF COUPLING RDT'S AND $|\bar{C}|/\gamma^2$

A variety of techniques to measure RDT's and the C matrix exist. Equivalence relations between the RDT's and C matrix were derived together with extensions to the existing techniques of measurement using BPM turn-by-turn data [3]. RHIC is uniquely equipped with an ac dipole to excite coherent betatron oscillations which are routinely used to measure RHIC optics [4, 5]. An analytical formalism to measure RDT's in the presence of an ac dipole was proposed in [6] and the measurements of local and global sextupolar RDT's using BPM data generated from ac dipole excitation have been demonstrated at RHIC [7].

Measurements at Injection Energy

Beam experiments were performed during the 2005 polarized proton run to measure f_{1001} and $|\bar{C}|/\gamma^2$. Global coupling was initially corrected using the skew quadrupole families to minimize the tune split [1]. Coherent betatron oscillations in both transverse planes were driven using two ac dipoles and BPM data were simultaneously recorded. The natural betatron tunes along with the ac dipole drive tunes and amplitudes are shown in Table 1.

Figure 3: $4|f_{1001}|$ (top) and $|\bar{C}|/\gamma^2$ (bottom) plotted as a function of longitudinal position along the yellow ring. A representation of the lattice (dipoles in black and quadrupoles in red) is shown in the bottom graph.

The data is initially processed to remove faulty BPMs according to criteria discussed in [8]. Approximately 10-15% of the BPMs were found to be consistently faulty which

Table 1: Injection energy settings

Parameter	Yellow		Blue	
	H	V	H	V
Tunes	0.731	0.723	0.735	0.721
Drive Tune	0.74	0.719	0.745	0.712
Drive Amp [mm]	0.05	0.05	0.05	0.05

were not used in this analysis. Fig. 3 shows four measurements of f_{1001} and $|\bar{C}|/\gamma^2$ as a function of longitudinal position in the yellow ring.

Figure 4: $4|f_{1001}|$ (top) and $|\bar{C}|/\gamma^2$ (bottom) plotted as a function of longitudinal position along the blue ring.

Although globally decoupled, the f_{1001} and $|\bar{C}|/\gamma^2$ in the yellow ring (Fig. 3) shows significant variations in the ring indicating uncorrected local coupling sources. f_{1001} and $|\bar{C}|/\gamma^2$ in the blue ring (Fig. 4) looks relatively flat and also globally well decoupled. The goal of future experiments would be to precisely identify and measure these local sources and use local IR correctors to compensate them. The procedure will involve scanning local skew correctors in each IR and minimize the local jumps in f_{1001} . The residual coupling will be further compensated with global skew families that yields the minimum f_{1001} for the minimum achievable ΔQ_{min} .

A systematic scan of a local corrector in IR8 (yo9-sq3) was performed as an initial experiment and f_{1001} and $|\bar{C}|/\gamma^2$ were measured. Both positive and negative deviations from its nominal value increases the global coupling which is evident from the increase in f_{1001} . Therefore, an effective local correction would also entail a simultaneous

global family correction for each local scan value.

Measurements at Top Energy

RHIC operates close to the difference coupling resonance which requires effective decoupling at top energy. A similar experiment as at injection was performed at top energy for the blue ring to measure f_{1001} and $|\overline{C}|/\gamma^2$. Global coupling was initially compensated like at injection and the skew families were set at nominal operation values. The settings for the tunes and amplitudes for top energy in the blue ring are shown in Table 2.

Parameter	Blue		Yellow	
	H	V	H	V
Tune	0.684	0.694	0.697	0.685
Drive Tune	0.675	0.703	0.705	0.675
Drive Amp [mm]	0.2	0.2	0.3	0.3

The data was processed to remove faulty BPMs similar to the injection data. However, the BPMs between IR4 - IR6 (3.5 - 3.85 km) in blue ring yield a zero f_{1001} which is being investigated. Fig. 5 shows a measurement of f_{1001} at top energy for the blue ring. A large discontinuity in f_{1001} is observed at IR12 (2 km) and smaller ones at IR8 (0.5 km) and IR4 (3 km) which indicate local skew sources.

Figure 5: $4|f_{1001}|$ (top) and $|\overline{C}|/\gamma^2$ (bottom) plotted as a function of longitudinal position along the blue ring.

The yellow ring exhibits large discontinuities at IR8 (0.5 km) and IR2 (2.5 km) as shown Fig. 6. A similar correction scheme proposed for injection using IR corrector scan will

be used at top energy to minimize the discontinuities in f_{1001} .

Figure 6: $4|f_{1001}|$ (top) and $|\overline{C}|/\gamma^2$ (bottom) plotted as a function of longitudinal position along the yellow ring at top energy.

ACKNOWLEDGEMENTS

We would like to thank the operations group for their help during data acquisition.

REFERENCES

- [1] Y. Luo et al., "Measurement of global betatron coupling with skew quadrupole modulation", Phys. Rev. ST Accel. Beams 8,014001 (2005).
- [2] W. Fischer, "Robust Linear Coupling Correction with N-turn Maps", Phys. Rev. ST. Accel. Beams 6,062801, BNL-71379-2003-JA, BNL C-A/AP/99 (2003).
- [3] R. Calaga, R. Tomás, and A. Franchi, "Betatron coupling: Merging Hamiltonian and matrix approaches", Phys. Rev. ST Accel. Beams 8,034001 (2005)
- [4] M. Bai et al., "Measuring Beta Function and Phase Advance in RHIC with an ac dipole", The proceedings of the 2003 Particle Accelerator Conference, Portland (May 2003).
- [5] R. Calaga et al., "RHIC Optics Measurement with Different Working Points", The proceedings of the 2004 Particle Accelerator Conference, Lucerne (May 2004).
- [6] R. Tomás, "Normal form of particle motion under the influence of an ac dipole", Phys. Rev. ST Accel. Beams 5, 054001 (2002).