BNL--48145

DE93 005588

APPLICATION OF MULTITRACER TECHNOLOGY TO
PETROLEUM RESERVOIR STUDIES

QUARTERLY PROGRESS REPORT
REPORTING PERIOD: APRIL 1 - JUNE 30, 1992

G. I. SENUM

SEPTEMBER 1992

Received by OSTI
JAN 08 1993

DEPARTMENT OF APPLIED SCIENCE

BROOKHAVEN NATIONAL LABORATORY
UPTON, LONG ISLAND, NEW YORK 11973

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

APPLICATION OF MULTITRACER TECHNOLOGY TO
PETROLEUM RESERVOIR STUDIES

QUARTERLY PROGRESS REPORT

REPORTING PERIOD: APRIL 1 - JUNE 30, 1992

Gunnar I. Senum, Principal Investigator
Tracer Technology Center
Environmental Chemistry Division
Brookhaven National Laboratory
Upton, NY 11973

September 1992

Prepared for
Chandra M. Nautiyal, Project Manager
Bartlesville Project Office
U.S. Department of Energy
Bartlesville, OK 74005

MASTER

UNDER CONTRACT NO. DE-AC02-76CH00016 WITH THE
UNITED STATES DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

OBJECTIVES

The objectives of this research program are to:

1. Improve the assessment of the character of petroleum reservoirs using tracer technology for the monitoring and improvement of EOR techniques, specifically, (a) to apply the presently available multitracer perfluorocarbon tracer (PFT) technology to the study of petroleum reservoirs in characterizing reservoir bulk subsurface flow transport and dispersion rates; and, (b) to demonstrate that PFTs with differing physical properties will interact with differing rates of adsorption and dispersion within such reservoirs, from which may be inferred difference in the character and/or extent of petroleum in those reservoirs.
2. Develop additional tracers, and tracer injection, sampling and analyses methodologies for use in petroleum reservoir characterization experiments.
3. Develop a data base of petroleum transport and dispersion properties from tracer experiments for use by modellers for developing, validating and extending petroleum reservoirs models used for characterizing petroleum reservoirs.

SUMMARY OF TECHNICAL PROGRESS

Technical progress will be discussed according to the three ongoing field experiments at the Naval Petroleum Reserve in California (NPRC).

I. The Shallow Oil Zone (SOZ) Experiment

The SOZ is a multilayered reservoir which originally contained more than 1,250 million barrels of oil. It is estimated that the primary recovery efficiency in the SOZ will be less than 50%. Cumulative production to date is 439 MMBO. The SS-1 interval in the SOZ has the lowest reservoir pressure, less than 50 psig, of any of the intervals in the SOZ. The low reservoir pressure provides the opportunity to increase the economic value of its remaining primary reserves by implementing processes which increase reservoir pressure and productivity, thereby accelerating recovery.

Gas injection is a potentially viable means to increase the economic value of the remaining oil-in-place by supplementing the natural gravity drainage mechanism. A pilot gas injection project was initiated in April 1991 to gather production and injection data to assess the technical feasibility and economic viability of injecting gas to increase reservoir pressure and productivity.

The PFTs were specifically utilized to qualitatively determine the direction of migration of the injected gas and possible gas migration across the faults. PMCP and PMCH were simultaneously injected into 34-10G on June 18, 1991 over a 28 hour period when the well was injecting 250 MCFPD of gas. The PFTs were introduced into the reservoir in the gas phase by injecting a small flow of PFTs from a high pressure cylinder flowing through a regulator into the injection well. The regulator was used to ensure a constant injection rate over the 28 hour injection period. The high pressure cylinder contained approximately 0.05% of gaseous PMCP and 0.06% of gaseous PMCH in nitrogen. Approximately 12 grams of each PFT was used in this experiment. Ten monitoring wells (including both inactive gas cap wells and active producers) were sampled daily starting on June 19, 1991. The gas cap wells were produced at low rates, about 1 MCFPD, to ensure turnover of the gas in the well bore. Samples were collected directly at the well head into pre-evacuated one liter pressure bombs by the field operator.

Fifty mL aliquots of gas were withdrawn from the pressure bombs and injected onto CATS (Capillary Adsorbent Tracer Samplers) and sent to BNL for analysis for PFTs by gas chromatography and electron capture detection.

In this quarter, sampling continued at up to fifteen wells surrounding the injectors, and generally indicated a westerly flow across some apparent non-sealing faults. These results will be used to revise the faulting of the SOZ.

The two PFTs injected at 34-10G have significantly appeared at Well 81-10G, located 3600 feet to the northeast of 34-10G. The measured tracer concentration are shown in Figure 1 with the open squares showing the measured PMCP values and the filled squares showing the PMCH values. Note that PMCH "broke" through approximately 40 days later than PMCP. This observed retardation is proportional to a path average residual oil saturation along the path of transport from 34-10G to 81-10G. Further analyses of these results, including the physical properties of the oil, will yield this important estimate of residual oil saturation.

An additional demonstration of this tracer retardation is given in Figure 2 for Well 25-10G. As before, PMCH broke through after the PMCP. Gary Pope at the University of Texas, at Austin, has taken this data, along with a PVT characterization of SOZ oil, and calculated average residual oil saturation of 30% along the path of transport between 34-10G and 25-10G. Part of this path is on the oil production zone. Note also the appearance of OC-PDCH and ot-PDCH, the tracers injected at 44-10G at this well at 150 days after injection.

This experiment will be completed by the end of FY 1992, since all of the experimental goals have been met.

II. The 24Z Experiment

The 24Z reservoir at NPRC is currently undergoing gas and water injection for pressure maintenance. The gas injection is into the gas cap and the water injectors are at the edges of the 24Z field. A six PFT experiment was started in mid-October/mid-November 1991. Two PFTs (PMCP and PMCH) were injected in the gas cap over a two week period. The PFT (about 30 gm) were dissolved in 500 gallons of methanol and injected at a proportional rate over two weeks. Four other PFTs (PDCB, o-PDCH, m-PDCH, and PTCH) were similarly injected into 4 water injectors, also over a two week duration.

Biweekly sampling started at the production wells in mid-November 1991 and, to date, there has been only one possible breakthrough of tracer, namely, the PFTs injected in the gas cap to a nearby producer. It is expected that this experiment will be of a longer duration than the SOZ, since it is estimated that the water injectors will breakthrough at the producers in a year. Sampling is continuing in this field.

III. The 26R Experiment

The 26R reservoir is currently undergoing gas injection for pressure maintenance. Six stages of tracer experiments are scheduled for this reservoir in order to discern the flow of injected gas in order to optimize the injected gas usage.

Stage 1 of the experiment was started in mid-November 1991, with two PFTs (PMCP and o-PDCH) injected at a gas injector, along with SF₆, a field-proven tracer. The inclusion of SF₆ is

to provide a comparison of the PFTs with SF₆. The specific goal of this stage 1 experiment is to uncover if the injected gas is crossing a certain fault. To date, no PFT has been detected at the twenty sampling wells.

In support of this 26R experiment, Gary Pope at UT/Austin has provided some modeling of this reservoir which indicated that tracer breakthrough should start to occur in April. However, no breakthrough has occurred. Sampling will continue.

Stage III of this experiment was started in mid-March 1992, with the injection of PMCH. Sampling will start in April at surrounding production wells, some of which are in the Stage I sampling protocol. Breakthrough is not expected for several months for this stage.

Other Activities

Results of the SO₂ experiment were presented at the SPE/DOE Eighth Symposium on Enhanced Oil Recovery, Tulsa, Oklahoma, in April, 1992. Several oil companies and oil service companies have approached the Tracer Technology Center for technology transfer of the perfluorocarbon tracer technology for use in petroleum reservoir characterization experiments.

Also, a presentation of the SO₂ results was given at the First Workshop on Reservoir Tracer Testing Technology, at UT/Austin. As a result of this meeting, an additional effort has been added to this program, i.e., the development of a subsurface PFT sampler for use in reservoir characterization.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Figure 1

25-10G Tracer Concentrations

Figure 2

END

**DATE
FILMED**

2 / 23 / 93