WSRC-RP-92-756

**ANALYSIS OF K-AREA CORE SAMPLES FOR K-AREA
FORMATION STABILIZATION WORK (U)**

by C. A. Langton

Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

WSRC-RP--92-756

DE93 003381

This paper was prepared in connection with work done under Contract No. DE-AC09-89SR18035 with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

WESTINGHOUSE SAVANNAH RIVER COMPANY
SAVANNAH RIVER TECHNOLOGY CENTER

WSRC-RP-92-756

Keywords: K-Area Core
Foundation
Stabilization

May 27, 1992

cc: PAUL BROWN, Bechtel SF
BILL GODWIN, Bechtel SF
FRANK SIMS, Bechtel SF
W.L. TAMOSAITS, 773-A
SRL Records (4)

TO: W. E. STEVENS, 773-43A

FROM: C. A. LANGTON, 773-43A *cal*

ANALYSIS OF K-AREA CORE SAMPLES FOR K-AREA FORMATION
STABILIZATION WORK (U)

SUMMARY

Foundation stabilization work in K-Area has been recently completed by Bechtel Inc. This effort involved pumping cement and cement-sand grout into unconsolidated sediments under K-Area. Subsequent to stabilization, core samples were collected to document the extent of grout flow in the area. Samples of this core were examined by SRTC personnel in support of the grouting program at the request of Bechtel personnel. This report summarizes the results of the SRTC study.

OBJECTIVE

The objectives of this study were to differentiate between grout emplaced by the Army Corps of Engineers as part of an earlier attempt to stabilize the area in the 1950's and grout emplaced by KASS within the last year. In addition samples were examined for evidence of multiple grout injections in an attempt to determine how the stabilizing material filled the

May 27, 1992

void spaces in the unconsolidated sediments. Interfacial regions between grout and the formation were examined. Samples were also evaluated for specific gravity, adsorption, and compressive strength. Porosity was not measured because the range in pore size distribution gave misleading results. Porosity was estimated to range between 20-30% based on specific gravity measurements.

RESULTS AND DISCUSSION

Field and laboratory sample labeling and field descriptions are listed in Table I. Specific gravity, water absorption and compressive strength results are presented in Tables 2-4, respectively. The spg of all samples was 2.0 ± 0.1 except for the apatitic sandstone (spg 2.3) in Core P-2-VSH-2.0 taken from 158-160.2 ft. Water absorption ranged from 5 to 15%. Right cylinders 4 1/2 inches long were cut and tested for compressive strength in an Instron. Values ranged from 704 to 2855 psi.

X-Ray diffraction was used to differentiate between 40 year old grout and one year old material. Ettringite, a calcium aluminum sulfate hydrate, and hydrogarnet were indicative of the 40 year old Army Corps of Engineers (COE) grout. Portlandite (i.e. calcium hydroxide and calcium silicate hydrate gel) were characteristic of the one year old grout. Calcite was detected in all of the grout samples except P-7-VSH-19.0 (CL-14). Consequently even one year appears to provide sufficient time for some of the $\text{Ca}(\text{OH})_2$ to carbonate to calcite. Results are summarized in Table V. X-Ray patterns are included in Appendix V.

X-Ray diffraction data indicate that the sediment contains montmorillonite clay and quartz sand. Samples from P-2-VSH-2.0 at 158-160.2 ft were identified as apatitic sandstone. Magnification of the samples up to 30x indicates that some of the quartz grains contain oxidized iron sulfide which results in orange (rust) staining. See Appendix II. A few ilmenite, black sand, grains were also detected.

Layering of the core samples was documented on a scale of centimeters to 0.1 mm. This is illustrated in 1) Appendix I which contains the macroscopic photographs of each core 2) binocular microscope photos in Appendix II, and 3) scanning electron microscope images in Appendix III. For example, core P-2-VSH-3.0 at 122-127 ft, (CL-7) was identified as COE sanded grout containing small pieces of apatitic sandstone. Sample CL-8 taken from Core P-2-VSH-3.0 at 125-126.3 ft, showed discrete interfaces between clayey sandstone and cement grout (with some sand). Sample CL-11 taken from core P-2-VSH-3.0 at 125 to 132 ft. shows a thin cement grout layer

injected into a sandy zone in the formation. Sample CL-14 taken from core P-7-VSH-19.0 at 129.5-130 ft contains well consolidated cement grout (with some sand) in contact with what could be a cement stabilized sand formation or sanded grout. CL-15 shows orientation of quartz grains in a layer in sanded grout or stabilized formation.

SEM microscopy also shows interfacial zoning as illustrated in Appendix III. Sample CL-12 taken from core P-2-VSH-4.0 at 122 to 123 ft shows neat cement grout with a few sand grains forming a sharp interface with sanded-cement grout. This suggests that separate injections make up this section of core.

CONCLUSION

Portlandite and calcium silicate hydrate gel were conclusive in identifying KASS grout. Ettringite and hydergarnet were well crystallized in Army Corps of Engineers grout which is about 40 years old. The absence of portlandite was also indicative of the 40 year old grout.

The sediment examined ranged from unconsolidated sand to sandy clay (montmorillonite). Core P-2-VSH-2.0 at 158-160.2 ft contained zones of apatitic sandstone.

The core samples displayed extensive layering on a macroscopic and microscopic scale. The interfaces between the regions were either sharp contacts or were characterized by alignment of quartz grains.

Samples which were obviously injected grout were CL-1, 2, 3, 11, 12, 17, and 18. Several samples including, CL-6, 7, 8, 9, 11, 14, and 15 have ambiguous features and could be described as cement + water injected into the formation sand. This interpretation is based on the clear, glassy surfaces of the sand (also found in the sediments) as opposed to the frosted sand surfaces found in the obvious grout samples, such as CL-17 and CL-18. It is also based on the texture and mineralogy of the samples. However, portions of CL-6, 7, 8, 9, 11, 14, and 15 also resemble injected sand-cement grout.

SRS-K955
 Prepared by WJG
 3/21/92 557-3770
 - APJC SIVAS
 SEEP 3184

TABLE I
 Field Description and Laboratory Numbering

Summary of Select Graft Samples

Date	Boring Sample	Depth	Source	Graft Type	Sample Shape	porosity	TE specific gravity	STING compression	retrograde	COMMENTS
CL-1	P-2-VH-10 C-12	120.7	COE	SAND	long cylinder		X	X	X	oversize
CL-2	" C-13	129.4	COE	SAND	short cylinder		X		X	jar
CL-3	P-2-VH-20 C-1	124.8-125.5	COE	SAND	short cylinder					jar
CL-4	" C-4	158-159.4	Formation	sandstone	short cylinder	X	X	X	X	jar
CL-5	" " 159.4-160.2		"	"	short cylinder		X			jar
CL-6	P-2-VH-30 R-13	122-127	COE	SAND	short cylinder		X			jar #1
CL-7	" " "	"	"	"	"					jar #2
CL-8	" " 125-126.3		"	sand and SAND	"					Interbedded sand and gravel
CL-9	" R-14	127-127.5	"	"	angled cylinder	X	X	X	X	"
CL-10	" " 127.5-127.7		"	NOT KNOWN	large fragment					may contain some leached cement
CL-11	" " 127-132		COE	NEAT and soil	thin seam					thin laminar graft seam
CL-12	P-2-VH-40	122-123.1	COE	SAND	long cylinder			X		oversize
CL-13	P-2-VH-17 C-8	129-135	KASS	soil/grout	long cylinder	X	X	X	X	oversize
CL-14	P-2-VH-15 C-8	129.5-130.0	KASS	SAND and NEAT	large fragment				(X)	jar
CL-15	" " ~131.5		"	SAND	large fragment				(X)	jar
CL-16	P-2-VH-10 R-1	90-95.5	KASS	NEAT and soil	thin seam					thin laminar graft seam
CL-17	P-2-VH-10 C-8	130.8	KASS	SAND and NEAT	small fragment				(X)	jar
CL-18	P-2-VH-10 C-9	134.5-140	KASS	SAND	short cylinder	X	X	X	✓	jar
CL-19										
CL-20										
CL-21										
CL-22										
CL-23										
CL-24										
CL-25										
CL-26										
CL-27										
CL-28										
CL-29										
CL-30										
CL-31										
CL-32										
CL-33										
CL-34										
CL-35										
CL-36										
CL-37										
CL-38										
CL-39										
CL-40										
CL-41										
CL-42										
CL-43										
CL-44										
CL-45										
CL-46										
CL-47										
CL-48										
CL-49										
CL-50										
CL-51										
CL-52										
CL-53										
CL-54										
CL-55										
CL-56										
CL-57										
CL-58										
CL-59										
CL-60										
CL-61										
CL-62										
CL-63										
CL-64										
CL-65										
CL-66										
CL-67										
CL-68										
CL-69										
CL-70										
CL-71										
CL-72										
CL-73										
CL-74										
CL-75										
CL-76										
CL-77										
CL-78										
CL-79										
CL-80										
CL-81										
CL-82										
CL-83										
CL-84										
CL-85										
CL-86										
CL-87										
CL-88										
CL-89										
CL-90										
CL-91										
CL-92										
CL-93										
CL-94										
CL-95										
CL-96										
CL-97										
CL-98										
CL-99										
CL-100										

TABLE II

SPECIFIC GRAVITY OF K-AREA CORE SAMPLES

	P-2-VSH-1.0		P-2-VSH-2.0		P-2-VSH-3.0		P-2-VSH-4.0	P-7-VSH-17	P-7-VSH-49.0
	CL-1	CL-2	CL-4	CL-5	CL-6	CL-9	CL-12	CL-13	CL-18
wt (g)	513	176	363	472	520	370	492	158	336
volume (ml)	280	90	170	205	260	185	255	80	160
spg $\pm$ 0.1	1.9	2.0	2.1	2.3	2.0	2.0	2.0	2.0	2.1

TABLE III

**ADSORPTION
K-AREA CORE SAMPLES**

Sample ID	Initial wt (g)	Final Saturated wt (g)	% Water Adsorption
CL-1	513	591	15
CL-4	354	376	6
CL-9	356	375	5
CL-12	488	547	12
CL-18	328	353	7

TABLE IV

COMPRESSIVE STRENGTH OF K-AREA CORE SAMPLES (psi)

	P-2-VSH-1.0	P-2-VSH-2.0	P-2-VSH-3.0	PS-2-VSH-4.0	P-7-VSH-49.0
Test	CL-1	CL-4	CL-9	CL-12	CL-18
1	2092	730	704	1802	2855
2	1859	-	-	-	-
AVE	1976	730	704	1802	2855

TABLE V
RESULTS OF X-RAY DIFFRACTION ANALYSIS OFK-AREA CORE SAMPLES

SAMPLE ID		FIELD		SRQC		AGGREGATE		CLAY		HYDRATED CEMENT				SUMMARY	
BECHTEL	SRQC	DESCRIPTION	SRQC DESCRIPTION	QUARTZ	APATITE	MONTMORILLONITE	ETTRINGITE	HYDROGARNET	CSH GEL	PORTLANDITE	CALCITE				
P-2-VSH-1.0 (120.7)	CL-1	COE SAND-CEMENT GROUT	COE (AGED) SAND-CEMENT GROUT	X	-	-	X	X	-	-	X				COE grout
P-2-VSH-1.0 (129.4-129.8)	CL-2	COE SAND-CEMENT GROUT	COE (AGED) SAND-CEMENT GROUT	X	-	-	X	X	-	-	X				COE grout + COE stabilized clayey sandstone (App. IV)
P-2-VSH-2.0 (124.8-125.4)	CL-3	COE SAND-CEMENT GROUT	COE (AGED) SAND-CEMENT GROUT	X	-	-	X	TRACE?	-	-	X				COE grout
P-2-VSH-2.0 (158-159.4) (158.0-158.6)	CL-4 BOTTOM	SANDSTONE	ROCK FORMATION = QUARTZ + APATITE	X	X	-	-	-	-	-	-				Apatic Sandstone
P-2-VSH-2.0 (159.7-160.2)	CL-5	SANDSTONE	ROCK FORMATION = QUARTZ + APATITE + CLAY	X	X	X	-	-	-	-	-				Apatic clayey sandstone
P-2-VSH-3.0 (122-127)	CL-6 MIDDLE	COE SAND-CEMENT GROUT	COE (AGED) SAND-CEMENT GROUT	X	-	-	-	X	-	-	X				COE grout or grout stabilized formation
P-2-VSH-3.0 (122-127)	CL-7 TOP	COE SAND-CEMENT GROUT	COE (AGED) SAND-CEMENT GROUT	X	-	-	-	X	-	-	X				COE grout and/or grout, stabilized clay-sand formation
P-2-VSH-3.0 (125-126.3)	CL-8	COE SAND-CEMENT GROUT + SOIL		X	-	X	-	X	-	-	X				KASS sanded grout
P-2-VSH-3.0 (127-132) (127.5)	CL-9 BOTTOM	COE SAND-CEMENT GROUT & SOIL	COE (AGED) SAND-CEMENT GROUT & QUARTZ SAND FORMATION	X	-	TR	-	X	-	-	X				COE grout in clay-sand formation
P-2-VSH-3.0 (127.5-127.7)	CL-10	NOT GROUT		X	-	X	-	-	-	-	-				Clayey Sandstone
P-2-VSH-3.0 (127-132)	CL-11 TOP	COE NEAT CEMENT GROUT & SOIL	KASS (FRESH) CEMENT GROUT + CLAY-SAND FORMATION	X	-	TR	X	-	X	X	X				KASS grout ± COE grout
P-2-VSH-4.0 (122-123.1)	CL-12	COE SAND-CEMENT GROUT	COE AGED GROUT	X	-	-	-	X	-	-	X				COE sanded and neat grout ± COE stabilized sand formation
P-7-VSH-17 (129-135)	CL-13	KASS GROUT + SOIL	COE AGED GROUT + SOIL	X	-	X	-	X	-	-	X				COE grout and clayey sandstone
P-7-VSH-19.0 (129.5-130.0)	CL-14	KASS SAND-CEMENT AND NEAT CEMENT GROUT	KASS (FRESH) SAND-CEMENT GROUT + CLAY-SAND FN.	X	-	TR	X	-	X	X	-				KASS cement grout and cement sand grout + clayey sandstone
P-7-VSH-19.0 (131.5)	CL-15 MIDDLE	KASS SAND-CEMENT GROUT	SMALL AMOUNT OF KASS CEMENT GROUT + SAND FROM FW OR KASS CEMENT-SAND GROUT	X	-	-	-	-	-	X	X				KASS grout or KASS stabilized sand formation
P-7-VSH-21.0 (90-95.5)	CL-16 TOP & BOTTOM	KASS NEAT CEMENT GROUT + SOIL	CLAY - QUARTZ FORMATION	X	-	X	-	-	-	-	-				Sandy clay-clayey sandstone formation
P-7-VSH-24.0 (130.8)	CL-17	KASS SAND-CEMENT GROUT + NEAT CEMENT GROUT		X	-	-	X	-	X	X	X				KASS neat grout
P-7-VSH-19.0 (134.5-140)	CL-18	KASS SAND-CEMENT GROUT		X	-	-	X	-	TR	X	X				KASS sanded grout

APPENDIX I

Photographs of K-Area Core Samples with Sample Labels

APPENDIX II

Binocular Microscope Photographs of K-Area Samples

CL-3 30x
cement - sand grout

CL-4 30x
apatitic sandstone with clay

CL-6 30X

*cement-sand grout - formation interface
(quartz grains are clear and smaller than CL-17, 18)*

CL-7 . 5X

cement-sand grout containing apatitic sandstone

CL-88 30x

cement rich grout - sandy clay formation interface

CL-11 15x

cement rich grout - clay sand interfaces

CL-14 5x

next cement - sand cement grout interface
 or
 next cement - sand formation which was stabilized
 note sand grains appear aligned.

CL-14 20x

CL-12 30x

cement-sand grout

CL-15 20x

cement-sand grout

CL 16 - 20x

unconsolidated sand formation

CL 16 - 20x

iron staining from oxidized iron sulfide grains in quartz sand.

CL - 17

30X

Cement-sand grout (Note: Frosted surfaces
on quartz grains)

CL 18

30X

Cement-sand grout.

APPENDIX III

Interfacial Regions in Scanning Electron Microscope Photographs of K-Area Core Samples

clayey sandstone tested positive for CaCO_3

K-area Core

Sandy
} not much sand
Both
tr. t.
positive
for CaCO_3

K-area Core

Sanded
Grout

← Next Grout

K-area Core

DATA FILE: 1108.112

FILE: 02-JUN-88 12:01

NAME: 2048

0.000

VPS = 2048 10.240

1108.112 CL #12

35

SEM SRTG/ADS 773-A C-108-112

TIME 13-00-400 1-4121

10-600V C-000-4V = 0

0.000

VFS = 1024

10.240

X-CORE CL #17 (SANDY GROUT)

MATRIX

35

CL-17 GROUT

P. IV 4

SRTC/ADS 773-R 10-108-112

FILE 00-001-93 1-1-8

Channel: 0 000keV = 0

0.000

VFS = 1024 10.240

R-CORE CL #17 MATRIX - NEAT

35

25KV 248X 40.3P 0335 SRTC/ADS

06-17 NEAT

Tubular /
Needle
Material
is $\text{Ca}(\text{OH})_2$

P. III 5

APPENDIX IV

**Scanning Electron Microscope Secondary Images of K-Area Core
with Energy Dispersive X-Ray Spectra of Selected Regions**

5

10

100

101

102

103

104

105

106

107

108

109

110

111

112

113

114

115

116

117

118

119

100

101

102

103

104

105

106

107

108

APPENDIX V

X-Ray Diffraction Powder Pattern Charts of K-Area Samples

30-010
 * SIEMENS *
 DIFFRAC-5000
 LAMINAR ALUMINUM SULFATE HYDRATE / ANATASE

30-010
 * SIEMENS *
 DIFFRAC-5000

4-DIFFRAC-5000 7597.HAN
* 5000 *
0000

P. V - 3

SALMON ALUMINUM HYDROXIDE FILLS / MORTAR

12-100
* SIEMENS *
DIFFRAC-5000

* STEVENS *
 5-000
 DIFFRAC-5000 75985.HAW
 CL-7A
 CALCIUM CARBONATE / CALCITE SYN
 (11.21 g)

TWO - THETA (DEGREES)

CL-8A

* STEMS *
5-586
DIFFRAC-5000 75987.RAW

CALCIUM CARBONATE / CALCITE, SYN
CALCIUM CARBONATE / CALCITE, SYN

SERIAL: 001 000 0000

TWO - THETA (DEGREES)

CEMENT GEL CALCIUM SILICATE HYDRATE NON CRYSTALLINE SOLID

4-750
* 01175100 *
DIFFRACT 500075393.RAW
CL-11A

CALCIUM HYDROXIDE / PORTLAND CEMENT
CL-11A

TWO - THETA (DEGREES)

Sample: 100% Polyethylene / 100%
 Date: 10/10/77
 Time: 10:00 AM
 Operator: J. H. ...

* SIEMENS *
 DIFFRAC-5000

TWO - THETA (DEGREES)

5-580
 * SIEMENS *
 DIFFRAC-5000 76001.RAW
 CL-15A

CALCIUM CARBONATE / CALCITE, SYN
 CALCIUM HYDROXIDE / PORTLANDITE, SYN
 CALCIUM OXIDE / CAUSTIC, SYN

SERIES: 01.PLOT: 01.00

DOC - THETA (DE-1000)

END

**DATE
FILMED**

2 / 8 / 93