RECEIVED

DOE-PC-91308-5

DOE/PC/91308--5

DE93 009680

**PARTICULATE BEHAVIOR IN A CONTROLLED-PROFILE PULVERIZED COAL-FIRED
REACTOR: A STUDY OF COUPLED TURBULENT PARTICLE DISPERSION AND
THERMAL RADIATION TRANSPORT**

Quarterly Technical Progress Report

For Period September 15, 1992 to December 14, 1992

Mardson Queiroz and Brent W. Webb

Brigham Young University

Provo, UT 84602

**Prepared for the United States Department of Energy
Pittsburgh Energy Technology Center (PETC)**

Under Contract No. DE-FG22-91PC91308

"US/DOE Patent Clearance is not required prior to
the publication of this document"

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees nor any of their contractors, subcontractors, or their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would infringe privately owned rights.

FORWARD

This report summarizes technical progress during the fifth quarter (September 15, 1992 to December 14, 1992) of a three-year study conducted for the Department of Energy (DOE) under contract number DE-FG22-91PC91308. The principal investigators for this work are Dr. Mardson Queiroz and Dr. Brent W. Webb; Dr. Clifford Smith is the technical representative for DOE.

TABLE OF CONTENTS

	PAGE
DISCLAIMER	I
FORWARD	II
ABSTRACT	IV
1. OBJECTIVES AND SCOPE	1
1.1 BACKGROUND	1
1.2 OBJECTIVES	1
1.3 TECHNICAL APPROACH	1
2. SUMMARY OF TECHNICAL PROGRESS	2
2.1 REACTOR REFURBISHMENT	2
2.2 TRANSMISSOMETER DEVELOPMENT	2
2.3 RADIATION AND PARTICLE DISPERSION MODELLING	3
3. REFERENCES	3
4. APPENDIX	4

ABSTRACT

During the fifth quarter progress has been made in the following areas: preparation for reactor refurbishment, instrumentation development, coal acquisition for experimental tests, and radiation and particle dispersion modelling. Refurbishment of the Controlled Profile Reactor was initiated this summer and is almost finished. Construction work for the local transmissometer probe is now completed. This laser-based instrument, combined with the data from the PCSV probe will enable estimate of the local concentration of particulates below $0.5\text{ }\mu\text{m}$ in size. Additionally, it will permit measurement of the temporal statistics of the local particulate number density.

1. OBJECTIVES AND SCOPE

1.1 BACKGROUND

Improved understanding of the fundamental processes involved in pulverized-coal combustion is needed to make the energy extraction more efficient and the combustion byproducts environmentally safe. While the characterization of the local particulate behavior (concentration, size, and velocity) is important to the understanding of virtually all processes in a pulverized coal-fired furnace, it influences in a more direct way the turbulent particle dispersion and thermal radiation heat transfer. Yet the local particulate dynamics have gone relatively unaddressed, primarily because of lack of adequate instrumentation to carry out such a study. With recent advances in optical techniques such an effort is now possible. This proposal seeks to characterize the local particulate concentration, velocity, and size distribution in a well-controlled, parametrically-varied laboratory-scale reactor using a new laser diagnostic technique. This newly-developed technique is the only one currently available for the investigation of aspherical particles. The particulate data will be collected simultaneously with local gas temperature and wall radiant heat flux distributions.

1.2 OBJECTIVES

This report describes recent progress in a fundamental, three-year investigation of the coupled problem of turbulent particle dispersion and thermal radiation transport. The project's objective is to make measurements of particle size, velocity, number density, temperature and wall radiant heat flux in a parametrically-controlled reactor presently existent at Brigham Young University (BYU). Although the study proposed here is primarily designed to provide experimental data not currently available for the evaluation of turbulent particle dispersion and radiation models, comparisons of analytical predictions and the experimental data obtained will be performed, using appropriate submodels integral to comprehensive pulverized-coal combustion codes existent at BYU.

1.3 TECHNICAL APPROACH

To accomplish the above objectives, the project is divided in the following tasks:

- Design and fabrication of a modified section for the BYU controlled-profile reactor, which will allow access of several probes to be used in the proposed study.
- Design and fabrication of a two-color pyrometer and cooled probe for local particulate temperature measurement.
- Characterization of the non-reacting turbulent flow field in the reactor using the PCSV-P probe, which will serve as an input during the turbulent particle dispersion submodel validation.
- Literature review dealing with particle dispersion and radiation transport in support of the model validation effort.

- Perform the parametrically-controlled measurements in the controlled-profile reactor.
- Experimental data analysis.
- A comprehensive comparison of experimental data and model predictions.
- Final report.

2. SUMMARY OF TECHNICAL PROGRESS

2.1 REACTOR REFURBISHMENT

Renovation on the controlled profile reactor (CPR) was completed during the fall of 1992. Improvement of flame symmetry, was achieved by disrupting the flow pattern of secondary air before it entered the swirl generator. New temperature data acquisition boards have been installed that allow sampling and multiplexing of 115 type K thermocouples which are potted at varying depths and positions on the reactor. Fifty defective thermocouples have been replaced and re-potted. The ignition system has been overhauled to increase reliability and ease of use. A system that will allow dustless loading of the coal feeders is being implemented.

Reactor wall temperatures, air flow rates, and coal feed rates will be acquired by a single Macintosh II computer running National Instruments' LabVIEW software package and utilizing 16-bit A/D boards for all signal sampling. Twin Acrison auger feeders, rotating 180° out of phase to minimize pulsing, deliver the pulverized coal, and dual load cells are multiply sampled and averaged every 40 seconds for feed rate calculations. Closed-loop control of coal feed rates will be achieved using an Acrison analog feedback controller.

2.2 TRANSMISSOMETER DEVELOPMENT

Figure 1 shows the design of a transmissometer probe to be used in combination with the Insitac Particle Concentration, Size, and Velocity (PCSV) instrument in resolving particle number densities below the 0.5 μm lower bound of the PCSV. The probe measures transmission of a 1 mm diameter HeNe laser beam along the beam path. It has been recently redesigned and will be rebuilt and tested in the weeks to come. The new design has been simplified since the original prototype model. A reference detector was used in the original design to sense any drift in the laser beam power, but recent testing has shown the beam power to be very stable, eliminating the need for an additional detector. Data acquisition is accomplished by sample-and-hold of the detector signal through a 12-bit National Instruments A/D board at a user-defined sampling frequency. Pre-acquisition frequency filters have been used with good success in eliminating background signal noise. Beer's law for participating medium radiation attenuation will be used in combination with number density data gathered with the PCSV instrument to infer a sub-micron number density distribution. Emission and absorption properties of the measured particles for use in Beer's Law are derived using Mie particle light scattering theory.

During November, the transmissometer was used in ABB Combustion Engineering's FPTF facility to resolve local soot volume fractions in a fuel-rich methane flame. A new probe is now being constructed based on design improvements conceptualized during the testing period.

Figure 1. Schematic of transmissometer probe.

2.3 RADIATION AND PARTICLE DISPERSION MODELLING

The particle trajectory model used in PCGC-2 computes the trajectory representing an ensemble of particles of a particular size, originating from one of several specified starting locations. Therefore, if the coal size distribution is represented by 'n' discrete particle sizes and if there are 'm' specified starting locations, the trajectory model calculates 'n x m' different trajectories at each iteration. In the present code, the maximum number of starting locations possible for the CPR geometry is 10. The question of interest here is that keeping the number of starting locations fixed at 10, what is the influence of increasing the number of discrete particles sizes used to represent the input coal size distribution? The motivation for this is to determine a minimum number of required discrete particle sizes representing the input coal size distribution such that, by increasing the number of discrete sizes used beyond this value, the dispersion predictions do not change significantly.

In order to establish the above objective, a numerical experiment was designed using the input coal size distribution with mass mean diameter of 55 μm . Simulations were planned for three different numbers of particle sizes, 5, 10 and 15. In order to determine the required particle sizes as per the input coal distribution, a histogram fitting program developed by Sowa (1992) was used. The listing of this program can be found in Shirolkar (1992).

The results of the simulation for the above three cases are analyzed by comparing the particle axial velocity profiles at several ports. Figure 2 illustrates the results of this comparison at Port 2b. The figure shows that at Port 2b ($x = 0.7 \text{ m}$), remarkably similar spread of data points is observed for the ten- and fifteen-size case. Also it is quite evident that the five-size case predicts relatively lower velocities compared to the other two cases. There is no significant variation between the profiles for all three cases

at Port 1b ($x = 0.3$ m) (Figure not shown). At Port 4b ($x = 1.5$ m), although the five-size case does predict the magnitude of velocities similar to the other cases, it does not exhibit the kind of spread observed in the ten- and fifteen-size cases (Figure not shown).

Figure 3 presents the axial gas velocity comparison between the three cases at two different axial locations. It is clearly evident from this figure that the gas velocity predictions do not change significantly between the ten- and fifteen-size cases. However, there is a noticeable difference between the five-size and the other two cases at both the axial locations. These results indicate that the five-size case does not represent a solution that is independent of the number of particle sizes selected.

It is evident from the above results that for a fixed number of starting locations the code predictions does not change appreciably by increasing the number of discrete particle classes used from ten to fifteen, indicating that ten size classes are sufficient to obtain a number of particle-size independent solution. Although ten size classes may not be the minimum number required to obtain such a solution, it does guarantee this solution and hence all future simulations will be performed with ten discrete particle sizes.

4. REFERENCES

Shirolkar, J. S. (1992). An Analytical Study Of Particle Dispersion In Dilute, Particle-Laden, Reacting And Non-Reacting Turbulent Flows. M.S. Thesis, Brigham Young University, Provo, Utah.

Sowa, William A. (1992). Private Communication.

Figure 2. Predicted particle Lagrangian axial velocity comparison between different initial particle sizes used at Port 2b ($x = 0.699$ m).

Figure 3. Predicted gas Eulerian axial velocity comparison between different initial particle sizes used at the axial locations of $x = 0.03\text{ m}$ and $x = 0.46\text{ m}$.

END

**DATE
FILMED**

4/13/93