Coal Liquefaction Process Streams Characterization and Evaluation

**Quarterly Technical Progress Report
April 1 Through June 30, 1992**

By: S. D. Brandes, M. S. Lancet, G. A. Robbins,
R. A. Winschel, and F. P. Burke

November 1992

CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for the:

United States Department of Energy
Contract No. DE-AC22-89PC89883

MASTER

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on September 22, 1992.

48

NOTICE

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States nor any agency thereof, nor any of their employees, makes any warranty, expressed or implied, or assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, or represents that its use by such third party would not infringe privately owned rights.

Coal Liquefaction Process Streams Characterization and Evaluation

**Quarterly Technical Progress Report
April 1 Through June 30, 1992**

By: S. D. Brandes, M. S. Lancet, G. A. Robbins,
R. A. Winschel, and F. P. Burke

November 1992

CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Prepared for the:

United States Department of Energy
Contract No. DE-AC22-89PC89883

U.S. DOE Patent Clearance was provided by
Chicago Operations Office on September 22, 1992.

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION	1
Overview	1
Contract Objectives	2
Contract Activities - This Period	3
RESULTS AND DISCUSSION	6
Preheater Simulation Studies	6
Summary and Conclusions	6
Experimental	7
Results and Discussion	8
Recommendations	10
UOP Bench Coprocessing Run 37	11
Summary	11
Results and Discussion	11
Calibration and Analysis of Standard Coal	16
Resid Conversion Kinetics	18
Introduction	18
Corrections to Wilsonville Run 260 Resid Conversions and Kinetic Constants	18
Error Limits for Deactivation Rate Constants in Wilsonville Runs 258 and 261	18
850°F ⁺ Resid Conversion and Kinetics	20
Background	20
Parametric Approach to 850 x 1050°F Conversions	23
Exact Solution Approach to 850 x 1050°F Conversions	25
Participants Program Status	27
Summary	27
Phase I	27
Phase II	27
Discussion	28
Phase I	28
Phase II	28
CONSOL Evaluation and Executive Summary of Final Report From Battelle, Pacific Northwest Laboratory	30
Project Assessment	30
Introduction	30
Summary	30
Program Description	31
Methodology	32
Major Findings	33
CONSOL Evaluation	34
Further Development	35
Statement of Work	36
Battelle, PNL, Executive Summary	37
EXPERIMENTAL	41
REFERENCES	42

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Preheater Tests	45
2	Baseline Preheater Tests	46
3	Operating Conditions and Process Performance	47
4	Feedstock Analysis - UOP Bench-Scale Coprocessing Run 37	48
5	Analysis of Feeds and Products - UOP Bench-Scale Coprocessing Run 37, Period 49	49
6	Carbon Sources, Selectivities and Conversions - UOP Bench Coprocessing Run 37, Period 49	50
7	Analysis of 1988 Batch of Old Ben No. 1 Mine, Indiana V Coal	51
8	Microautoclave Test Matrix and Conversions - Old Ben No. 1 Mine, Indiana V Coal	52
9	Parametric Calculation of Conversion of 850 x 1050°F Relative to 1050°F	53
10	Modeling of 1050°F ⁺ , 850 x 1050°F ⁺ , and 850°F ⁺ Conversion in Wilsonville Runs 260 and 262	54
11	Calculation of 850 x 1050°F ⁺ Conversions in Wilsonville Run 262	55

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Heating Profiles for Coal Preheater Simulation Studies	56
2	UOP Coprocessing Bench-Scale Unit.	57
3	Coal Carbon to Total Carbon Ratio Plotted vs Product Fraction, UOP Coprocessing Run 37, Period 49	58
4	Conversion of Coal Carbon Plotted vs Product Fraction, UOP Coprocessing Run 37, Period 49	59
5	Corrected Conversions of Coal and Petroleum Carbon Plotted vs Product Fraction, UOP Coprocessing Run 37, Period 49	60
6	Comparison of Coal Carbon Conversions in UOP Coprocessing Run 37 with Those in UOP Run 26	61

APPENDICES

<u>Appendix</u>		<u>Page</u>
1	Corrections to Resid Conversions and Kinetic Constants for Run 260	62
2	The Application of FT-IR Methods to the Characterization of Coal Liquefaction process Streams	81
3	Application of ²⁵² Cf-Plasma Desorption Mass Spectrometry to Analysis of Direct Coal Liquefaction Heavy Products	93
4	Conversion of Resid Components in CC-ITSL Processing at Wilsonville	99
5	The Chemical Nature of Coal Liquid Resids and the Implications for Process Development	107
6	Strategic Considerations of Coal Liquid Refining	115

ABSTRACT

COAL LIQUEFACTION PROCESS STREAMS CHARACTERIZATION AND EVALUATION, QUARTERLY TECHNICAL PROGRESS REPORT, APRIL 1 THROUGH JUNE 30, 1992

This is the the eleventh Quarterly Technical Progress Report under DOE Contract DE-AC22-89PC89883. Major topics reported are:

- The results of a study designed to determine the effects of the conditions employed at the Wilsonville slurry preheater vessel on coal conversion is described.
- Stable carbon isotope ratios were determined and used to source the carbon of three product samples from Period 49 of UOP bench-scale coprocessing Run 37. The results from this coprocessing run agree with the general trends observed in other coprocessing runs that we have studied.
- Microautoclave tests and chemical analyses were performed to "calibrate" the reactivity of the standard coal used for determining donor solvent quality of process oils in this contract.
- Several aspects of Wilsonville Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) resid conversion kinetics were investigated; results are presented. Error limits associated with calculations of deactivation rate constants previously reported for Runs 258 and 261 are revised and discussed. A new procedure is described that relates the conversions of 850°F⁺, 1050°F⁺, and 850 x 1050°F material. Resid conversions and kinetic constants previously reported for Run 260 were incorrect; corrected data and discussion are found in Appendix 1 of this report.
- A brief summary of the status of the Participants Program is given.
- A summary of the final report produced by Battelle, Pacific Northwest Laboratory, under the Participants Program is presented.
- Five papers which will be presented at the 204th National Meeting of the American Chemical Society are appended. One paper is authored by researchers at Advanced Fuel Research and describes work done under Phase I of the Participants Program. The second paper is authored by researchers at Lehigh University and describes work done under Phase II of the Participants Program. The third and fourth papers were authored by CONSOL. The third paper deals with the conversion of resid components in the CC-ITSL process at Wilsonville. The fourth paper describes results accumulated from Phase I of the Participants Program. The fifth paper was co-authored by CONSOL and Burns & Roe and discusses the outlook for producing specification fuels by direct liquefaction.

Section 1

INTRODUCTION

This is the Technical Progress Report for the eleventh quarter of activities under DOE Contract No. DE-AC22-89PC89883. It covers the period April 1 through June 30, 1992.

OVERVIEW

Direct coal liquefaction is a complicated chemical process. Recent advances in the technology, which significantly reduced the product costs, have come about through an improved fundamental understanding of liquefaction chemistry. Further improvements are possible, and will depend on continued advances in our knowledge of process chemistry. Supplying this knowledge requires the use of a variety of the tools of analytical chemistry applied to the appropriate samples, and interpretation of the analytical data in context to process development.

The Research and Development Department of CONSOL Inc. (CONSOL) is conducting a three-year project to characterize process and product streams from direct coal liquefaction process development programs sponsored by the Department of Energy. In this project, CONSOL obtains samples from current process development activities in coal liquefaction and coal-oil coprocessing, and characterizes them using established analytical techniques. In addition, selected samples are characterized by other analytical techniques to evaluate their potential for aiding process development. These analyses and interpretation of the results in relation to process operations are provided by a subcontracted project team.

In addition to samples from current process development programs, CONSOL maintains a bank of coal liquids samples from the SRC-I, H-Coal, ITSL (Lummus and Wilsonville) and HRI-CTSL coal liquefaction programs, and the Lummus, HRI and UOP coprocessing development programs. These samples, which represent important stages in the recent development of coal liquefaction technology, are also used in the analytical program.

CONTRACT OBJECTIVES

CONSOL is conducting a three-year program to characterize process and product streams from direct coal liquefaction process development projects. The program objectives are two-fold: 1) to obtain and provide appropriate samples of coal liquids for the evaluation of analytical methodology, and 2) to support ongoing DOE-sponsored coal liquefaction process development efforts. The two broad objectives have considerable overlap and together serve to provide a bridge between process development and analytical chemistry.

More specifically, the first objective is to identify, collect, and disburse appropriate samples of coal liquids for analysis by techniques that hold promise, but are not fully demonstrated, for use in liquefaction process development efforts. Samples are chosen from ongoing DOE-funded liquefaction and coprocessing projects and from CONSOL's collection of coal liquids produced during the past ten years. Samples are chosen based on their relevance to process development programs, and are well-documented in terms of feedstocks, sampling location, time and operating conditions. The samples chosen are sufficient to judge the applicability of the analytical methods being evaluated. These process oils are analyzed by CONSOL in a base characterization program using techniques established in previous CONSOL research. Selected samples also are provided to project team participants (as subcontractors), other researchers active in the analysis of coal liquids, who characterize them using a range of methods beyond those used in the base program. Subcontracts to approximately 16 organizations that have specialized analytical capabilities are a major aspect of this work. Individual analytical specialists from the subcontractors take a major role in interpreting their own results in context to the liquefaction process, and not merely provide data. This portion of the program includes an evaluation of the utility of promising analytical techniques for providing useful information for coal liquefaction process development; those results will be applied to ongoing development efforts. This evaluation will be based on the usefulness of an analytical method in process monitoring, to obtain specific chemical information, and as judged by precision and accuracy.

The second objective is to support the process developers. This includes support in the form of providing results and interpretation of data obtained with the analytical techniques being assessed. However, more directly, appropriate

process oils are being characterized in the base program by a variety of standard techniques that have proven relevance to development efforts. The results from these more routine analyses aid plant operations and planning. Also, these results provide the data needed to select appropriate samples for the non-routine techniques and provide a set of data for correlations with the results of the more exploratory techniques.

CONTRACT ACTIVITIES - THIS PERIOD

Contract activities for this quarter are listed below. Each activity is summarized and discussed under a separate heading in Section 2 of this report. Consequently, there is no overall Summary section provided in this report.

- Preheater simulation studies were conducted using coal/recycle solvent slurries. The recycle solvents from Wilsonville were paired with the feed coals used to produce them. Different heating profiles and residence times were tested. In most cases the bulk of the coal conversion attributed to the first stage at Wilsonville occurred in the simulated preheater.
- Carbon isotope analyses of several coprocessing samples from period 49 of UOP Run 37 were determined by Conoco's Stable Isotope Laboratory. Carbon sourcing calculations were performed.
- Twelve microautoclave tests were made to "calibrate" the reactivity of the standard coal (Indiana V, Old Ben Mine No.1) which is used to determine donor solvent quality of the process oils tested in this contract. The coal was analyzed by chemical analyses to monitor oxidation.
- A simple equation was derived which relates the conversion of 850°F⁺, 1050°F⁺, and 850 x 1050°F material to each other so that CONSOL and Wilsonville conversion results can be better compared. Development of the methodology and application to Wilsonville Runs 260 and 262 are presented in this report.
- First-stage and total conversions of resid, resid components, and associated kinetics for Wilsonville Run 260 were recalculated because of

failure to account in the original calculations for 2 wt % iron oxide fed to the first stage during Run 260.

- Substantial progress was made in the Participants Program this quarter. A brief summary of the Participants Program is presented. The evaluation and executive summary of the final report from Battelle, Pacific Northwest Laboratory, is included. It is the first Phase II project completed. Under the Participants Program, researchers at Advanced Fuel Research and Lehigh University submitted papers to the 204th National Meeting of the American Chemical Society. Both papers are appended. The Lehigh paper is entitled, "Application of ^{232}Cf -Plasma Desorption Mass Spectrometry to Analysis of Direct Liquefaction Heavy Products", and is authored by A. R. Lapucha and J. W. Larsen. The Advanced Fuel Research paper is entitled, "The application of FT-IR Methods to the Characterization of Coal Liquefaction Process Streams". The authors are H. Teng, M. A. Serio, R. Bassilakis, K. S. Knight, S. C. Bates, and P. R. Solomon.
- Eleven samples (ten process oils from Wilsonville Run 263 Periods G and J and coal from Run 262) were sent to Dr. F. P. Miknis, Western Research Institute, for analysis by ^{13}C - and ^1H -NMR. Mass balance information for these two periods was compiled and ultimate analyses were obtained on the samples. This information was sent to Dr. Miknis.
- Three CONSOL papers were submitted for the 204th National Meeting of the American Chemical Society. One paper, entitled "The Chemical Nature of Coal Liquid Resids and the Implications for Process Development" authored by S. D. Brandes, R. A. Winschel, and F. P. Burke, describes data obtained from the Participants Program of this contract. The second paper concerns resid conversion chemistry in Wilsonville liquefaction. It is titled "Conversion of Resid Components in CC-ITSL Processing at Wilsonville" and is authored by G. A. Robbins, R. A. Winschel, and F. P. Burke. The third paper is entitled "Strategic Considerations in Coal Liquid Refining" and is authored by P.-Z. Zhou, J. J. Marano and R. A. Winschel. The three papers are appended to this report.

- Work in progress, but not yet completed this quarter, includes:
 1. Analysis of oils from Wilsonville Run 263
 2. Literature search concerning analytical methods for coal liquids

Section 2

RESULTS AND DISCUSSION

PREHEATER SIMULATION STUDIES

SUMMARY AND CONCLUSIONS

The Wilsonville Advanced Coal Liquefaction R&D Facility in Wilsonville, Alabama, operated with a preheater situated ahead of the first-stage reactor. However, the plant, as configured, did not provide for sampling of the coal slurry between the preheater vessels and the first reactor stage. It is considered important to evaluate the effect of the preheater on coal conversion in order to fully understand the initial reactions of the coal and the recycle solvent in the two-stage direct liquefaction process.¹ In lieu of installing a sampling port in the pilot plant at the desired location, an experiment was designed to simulate the conditions in the preheater vessels at the Wilsonville facility, and to measure the conversion of the coal after it had been subjected to those conditions.

Tests were conducted with three different coals: Illinois No. 6 seam, Burning Star No. 2 Mine; Wyodak and Anderson seam, Black Thunder Mine; and Pittsburgh seam, Ireland Mine. The coals were slurried with recycle oil (V131B) from the Wilsonville facility. Recycle oils in these experiments were paired with the feed coals that had been used to produce them at the Wilsonville plant (Table 1). Several different heating profiles were used which approximated heating profiles used at Wilsonville. They can be categorized into two groups: Profiles 1 and 3, rapid heating from ~320°F to ~800°F; and Profile 2, a long pre-soak time at ~370°F followed by rapid heating to ~800°F. Coal conversion for each test was calculated from the tetrahydrofuran (THF)-insoluble material obtained from reacting the coal/recycle solvent slurry mixture, corrected for the amount of THF-insoluble material obtained from the recycle solvent alone. It generally was found that for each coal tested, the conversion of the coal in the simulated preheater was equal to or greater with recycle solvent than with tetralin. Long pre-soak times at temperatures close to 370°F were not detrimental to coal conversion, and in the case of Wyodak (and possibly Illinois No. 6) coal, were beneficial. Coal conversions under simulated preheater conditions were as high as 99%, and no lower than 58%, of the first-stage conversions reported by Wilsonville for the corresponding pilot plant run. It can be concluded from these results that most of the conversion occurring across the preheater and

first stage is completed in the preheater. Of the coals tested, the higher the rank (Pittsburgh > Illinois 6 > Wyodak), the greater was the completeness of coal conversion in the simulated preheater.

EXPERIMENTAL

Coal/recycle oil slurries were made with 30 wt % coal and 70 wt % V131B recycle oil. Fifteen grams of slurry was weighed into a 45 mL stainless steel tubing-bomb reactor equipped with a thermocouple well. The reactor was sealed and pressurized to 1500 psi (cold charge) with hydrogen. A series of heating profiles were used in the experiments. They are as follows:

	<u>Temperatures</u>	<u>Time</u>
Heating Profile 1:	-320°F 320→790°F	2-3 min Hold 10 min Ramp
Heating Profile 2:	-370°F 370→320°F 320→675°F 675→790°F	4 hr Hold 10 min Ramp 5 min Ramp 5 min Ramp
Heating Profile 3:	-320→790°F	5 min Ramp

Actual test data for heating profiles 1, 2, and 3 are shown in Figure 1. It can be seen in Figure 1 that profile 1 was executed in three ways. Profile 1a entails rapid heating and a soak period at the higher temperature; profile 1b involves a hold period at the lower temperature and then rapid heating; profile 1c entails a more or less linear increase to the higher temperature. The different heating profiles used in these tests were achieved by suspending the tubing bomb in a heated fluidized sand bath at different depths. To speed or retard the heating, the reactor was raised or lowered in the bed. To achieve constant temperature control at low temperature followed by rapid heating (heating profile 2), the reactor was heat-traced and the temperature was controlled with a variable transformer. The heat-tracing was removed before the reactor was brought in contact with the fluid bath. The reactor was continuously shaken during the tests to achieve uniform heating of the contents. All tests were concluded by rapidly cooling the reactor in a water bath. Conversions (Table 1) were determined by pressure filtration of the reactor contents with tetrahydrofuran (THF). The insoluble material was weighed and the weight was

corrected for the ash contents of the recycle oil and coal, and the insoluble material obtained from the recycle oil, which had been determined in control tests performed with no coal (Table 2). Because of the nature of these tests, reproducibility was poorer than in our standard microautoclave tests (1.2%). As Table 1 shows, many repeat tests gave good conversion repeatability (<2% difference between repeats); however, in several cases, conversions repeated poorly (6 to 11% difference between repeats). All data are considered in the following discussion. Baseline tests were performed with coal and tetralin (a good hydrogen donor) and with 1-methylnaphthalene (a non-donor solvent) (Table 2).

RESULTS AND DISCUSSION

The intent of this study was to estimate the amount of coal conversion that occurs in the preheater vessels at the Wilsonville two-stage coal liquefaction facility by simulating the conditions in the preheaters in bench-scale tests. At the Wilsonville plant, the coal is slurried with recycle solvent in the slurry tanks and held at approximately 350°F for 4 to 8 hr before it is passed into the preheaters.² In transit to the preheaters, there is a small dip in the temperature to approximately 320°F and then upon entering reactor one of the two-stage system, the slurry is rapidly heated to the chosen reactor temperature, about 800°F.^{4,6,8} First approximations to this rather complicated heating regime were to simply rapidly heat the coal slurry to 350°F and then to 800°F by following three different heating profiles (1a, 1b, and 1c). There was no discernable difference in the coal conversion using these heating regimes with Pittsburgh seam coal (Table 1). The coal conversions with the Pittsburgh seam coal and V131B recycle solvent from Run 259 G were over 90 wt %. This left little room to show improvements, if there were to be any, with the use of other heating profiles. Consequently, experiments with the Pittsburgh seam coal were discontinued. Experiments with Wyodak coal show that on average there is about the same coal conversion with any of the three heating profiles. Based on the finding with the Wyodak coal, experiments with the Illinois No. 6 coal were performed with the 1c profile.

A comparison of conversions obtained using the 1c heating profile and tetralin (a good hydrogen donor) as solvent to those obtained with the recycle oils, shows that the recycle oils were more effective solvents for the higher rank coals.

For the Wyodak coal, the recycle oil did not perform as a better solvent under any of the conversion conditions.

The non-donor solvent (1-methylnaphthalene) produced a lower coal conversion than tetralin and the recycle oils for the Pittsburgh and Wyodak coals and about the same conversion for the Illinois No. 6 coal.

It was expected that adding the long soak time to the front end of the heating experiment to simulate the extended time the slurry spends in the slurry tanks at the Wilsonville site would be detrimental to the coal conversion. This turned out not to be the case. There was a small but significant improvement in coal conversion with the Wyodak coal when heating profile 2 was used, and there may have been a small but perhaps insignificant improvement in coal conversion in the case of the Illinois No. 6 coal when heating profile 2 was used. It is notable that in the experiments as performed here, the long pre-soak periods were conducted under hydrogen pressure; whereas, in the Wilsonville slurry tanks, the coal slurry is held under a nitrogen purge until it is injected into the preheater. The extended hold time under hydrogen could be a contributing factor in the elevation of the Illinois coal conversions. In tests with Illinois No. 6 coal, very rapid heating (heating profile 3) actually was detrimental to coal conversion.

Coal conversion reported by Wilsonville^{3,4} for period G of Run 259, was 93.1 wt % in the first stage and 95.1 wt % overall for the two-stage liquefaction (TSL) system. Conversions are reported by Wilsonville as percent cresol-solubles; for a first approximation, THF-solubles can be considered comparable. The conversion of the Pittsburgh seam coal to THF-soluble material is essentially complete in a recycle oil slurry under the conditions simulating the preheater conditions at the Wilsonville plant. Ninety-seven to 99% of the eventual conversion takes place in the simulated preheater. In the case of the Illinois coal, 87.0 wt % cresol-solubles are reported by Wilsonville for Run 261B first-stage conversion (91.7 wt % overall).^{5,6} The coal conversions to THF-solubles obtained in these preheater simulation tests were 79% to 91% of the values reported by Wilsonville for first-stage conversion and 79% to 88% for overall TSL conversion.

Comparison of coal conversion for the Wyodak coal case is not as straightforward. In Run 260, as with most low-rank coal tests that were performed at Wilsonville, there was an addition of iron oxide to the coal slurry which was sulfided in the first-stage reactor to produce an iron sulfide catalyst. In the preheater tests, as performed here, no iron oxide was added to the reactor. Nonetheless, it is apparent that the long pre-soak time (profile 2) was not detrimental to coal conversion. Approximately 74% of the conversion in the first stage, and 72% of the overall TSL conversion obtained at Wilsonville in Run 260 B was achieved in these preheater simulation tests.^{7,8}

RECOMMENDATIONS

The work described here points to the efficacy of conversion (to THF solubles) of all three ranks of coal under the relatively mild conditions that the coal/recycle oil slurries experience in the preheaters. A number of avenues for further work are indicated by these findings: 1) It is of importance to test the quality of the material that is produced under these mild treatments. It would be interesting to make a comparison of the quality of these materials to the quality of the first-stage products produced in the corresponding Wilsonville runs. 2) The effect of long pre-soak times under nitrogen should be investigated. Hydrogen was employed here. 3) The effect of the addition of iron oxides to the low rank coal/recycle oil slurries prior to the long pre-soak times also should be investigated.

UOP BENCH COPROCESSING RUN 37

SUMMARY

Stable carbon isotope ratios were measured for three product fractions (product gas, $C_5 \times 510^\circ C$ liquid, and toluene soluble $510^\circ C^+$ vacuum still bottoms) from UOP bench-scale coprocessing Run 37 to determine the source of the carbon in each fraction. Both carbon and isotope balances were good, but the results suggest significant over-accounting for the coal carbon and a corresponding under-accounting for the petroleum carbon. The results from this UOP coprocessing run agree with the general trends observed in other coprocessing runs we have studied. The coal carbon is selectively converted to the highest boiling fraction while the petroleum carbon is preferentially converted to lower boiling liquids.

RESULTS AND DISCUSSION

Samples of three product fractions and a recycle gas fraction from Period 49 of UOP bench-scale coprocessing Run 37 were received from Mr. John Gatsis of UOP. Lloydminster $950^\circ F^+$ vacuum resid and Illinois No. 6 coal (Burning Star No. 2 Mine) (2:1 MAF ratio) were the feedstocks to Run 37. Twenty to thirty grams of each condensed product were received. Gas samples were contained in 125 mL goeckel tubes. A summary of the operating conditions, yields and process performance indicators for period 49 of UOP Run 37 is shown in Table 3. A flow diagram of the UOP bench unit is shown in Figure 2. UOP Run 37 used a 2:1 blend of petroleum to MAF coal with 0.09 wt % (total MAF feed basis) of a proprietary dispersed molybdenum catalyst. The reactor temperature used during this period was $468^\circ C$. A high pressure separator (HPS) liquid to fresh feed recycle ratio of 5:1 (minimum) was used and the relative space velocity was 1.

Analyses of the feed coal and feed petroleum to UOP coprocessing Run 37, as reported by UOP,⁹ are given in Table 4.

The samples obtained by CONSOL from this run included three net product streams and one recycle gas stream. They were:

- A combined sample of the debutanizer underflow and vacuum still overhead product. This sample represents $C_5 \times 510^\circ C$ liquid product, except for the minor C_5^+ component of the gas stream.

- Toluene-soluble 510°C⁺ vacuum still bottoms product.
- Product gas from the debutanizer.
- Recycle gas from the high pressure separator. There was not enough carbonaceous gas in the recycle gas sample tube for carbon isotope analysis. However, since this stream is not a net product, there is no net yield of it and it would, therefore, not have been included in the mass, carbon or isotope balances anyway.

One net product stream, the toluene insoluble 510°C⁺ vacuum still bottoms was not provided for analysis because it contains UOP's proprietary catalyst. Since this stream also contains the insoluble carbonaceous product, the samples analyzed by CONSOL do not represent the entire carbon in the products. The yield of the ash-free portion of this unanalyzed sample was only 2.9 wt % of the MAF feed; as such, it is a minor product.

The carbon and carbon isotope analyses of the feeds and products from UOP Run 37 are shown in Table 5. Carbon contents of the product liquids were determined by CONSOL. The carbon content of the product gas sample was calculated from the gas composition, as supplied by UOP.¹⁰ The carbon isotope ratios reported in Table 5 were determined, at least in duplicate, by Conoco's Stable Isotope Laboratory.

The Lloydminster resid and Illinois No.6 coal feedstocks to Run 37 were identical to those used in UOP Run 26. The isotope ratios of the feedstocks used here are those determined for Run 26.¹¹ The large difference in the isotope ratios of the two feedstocks, 5.4 per mil, makes this feedstock pair an excellent one for carbon sourcing by carbon isotope analysis. Such a large difference is conducive to good precision and good accuracy.

The recovery of feed carbon in the products analyzed (i.e., in the C₁ x C₄, C₅ x 510°C and 510°C⁺ toluene-soluble products) is 97.3 wt %. The isotopic composition of the total feed (i.e., a 2:1 ratio of petroleum/MAF coal) was -28.11 per mil. The calculated isotope ratio of the recovered and analyzed products from period 49 is -27.76 per mil. This value shows that the carbon recovered in the products analyzed is similar in isotopic composition, but more "coal-like", than the total carbon fed. The small difference results from

exclusion of the minor toluene-insolubles stream and all analytical and sampling errors.

The results of using the raw isotope data, uncorrected for selective isotopic fractionation, to source the carbon in each of the product fractions, are shown in Table 6. Comparing the isotope ratio of the product gas (-29.87 per mil) with that of the total feed (-28.11 per mil), it appears that selective isotopic fractionation was less pronounced in this UOP coprocessing run than in most other continuous coprocessing runs we have studied.

We obtained the isotopic analyses of the product gas for UOP Run 37; therefore, our selective isotopic fractionation correction method can be directly applied to the results without the need to define a "hypothetical" gas product. Using our standard assumptions concerning the origin and composition of the gas and isotopic homogeneity of the non-gas fraction of the feeds,¹² we can calculate isotopic compositions of the non-gaseous coal products and non-gaseous petroleum products. Because of the relatively low yield of carbonaceous gas (12.25% MAF $C_1 \times C_4$ yield) and the relatively small difference between the isotopic composition of the product gases and that of the total feed, -1.76 per mil, the calculated isotopic compositions of the non-gaseous portion of the coal products and petroleum products are nearly the same as the isotopic composition of the respective feedstock. The measured isotopic compositions of the two feeds were: $\delta^{13}C_{\text{coal}} = -24.45$ per mil, $\delta^{13}C_{\text{petroleum}} = -29.83$ per mil.¹¹ The calculated values for the non-gaseous products of each feed, based on the isotopic compositions of the product gas, were -24.22 for the coal and -29.60 per mil for the petroleum. This difference represents only relatively minor selective isotopic fractionation. This is consistent with the implied low degree of selective isotopic fractionation previously observed in other UOP bench coprocessing Runs.¹³

The 510°C* (950°F*) resid conversion obtained in period 49 of UOP Run 37 was 84%. This is only slightly lower than the 975°F* (524°C*) resid conversions obtained during most of the HRI coprocessing run periods from which we have analyzed samples. In those HRI runs, 975°F* resid conversion was typically 85% or greater; however, in those HRI runs, selective isotopic fractionation was much more pronounced.

The corrected carbon sources, conversions and selectivities for coal carbon conversion are also shown in Table 6. As expected, the corrected values shown in this table are only slightly different from the uncorrected values because of the relatively small amount of selective isotopic fractionation. The uncorrected and corrected coal carbon as a percent of the total carbon is plotted versus product fraction in Figure 3. The corrected and uncorrected coal carbon conversions are compared in Figure 4 and the corrected coal carbon and petroleum carbon conversions are shown Figure 5. The remainder of the conclusions concerning UOP Run 37 are based on the corrected carbon source information in Table 6 and Figures 3 through 5.

The calculated total coal carbon conversion, 118 wt %, is high and the petroleum carbon conversion, 88 wt %, is low. Both should be 100%. A potential source of error is the use of the feed isotope ratios from Run 26 to calculate the Run 37 data. Directionally, a more negative (isotopically lighter) feed coal isotope ratio and/or a less negative (isotopically heavier) feed petroleum isotope ratio are required to lower the calculated coal carbon conversion and increase the calculated petroleum carbon conversion. This over-accounting for coal carbon and under-accounting for petroleum carbon make quantitative comparisons of the Run 37 results with those from Run 26 impossible. However, a graphical comparison of the results from the two runs, Figure 6, illustrates some qualitative features of these runs.

The corrected carbon source data show the selectivity for conversion of coal carbon to toluene soluble 510°C^+ material (1.5) to be the same as that in Period 24 of Run 26. In that run, we observed an increase in the selectivity for conversion of coal carbon to toluene soluble 510°C^+ with increased temperature. For example, the coal-derived component of this product increased from 31% to 48% from period 8 to period 24 of Run 26 as the temperature was increased from 427°C to 449°C . At the higher temperature of Run 37, 468°C , the coal derived component of this fraction remained at about 48%. As seen in Figure 6, the actual conversion of coal carbon to this fraction decreased from 42.2 wt % at 427°C , (Period 8) to 26.2 wt % at 449°C (Period 24) in Run 26. However, at the higher temperature (468°C) of Run 37, significantly more coal carbon (43%) was converted to 510°C^+ material. Some of this increase probably reflects the over-accounted coal carbon conversion in this run.

The corrected coal carbon conversion to 510°C liquids in Run 37 was significantly lower than that calculated for this fraction in the highest temperature period of Run 26, 64 wt % vs. 71 wt %. If the total coal carbon conversion was closer to 100%, it is likely this conversion of coal carbon to 510°C material would be even lower.

CALIBRATION AND ANALYSIS OF STANDARD COAL

Routine microautoclave solvent quality assays are made with a single standard coal: Old Ben No. 1 Mine, Indiana V seam. The currently used batch of coal was received in November 1988. In April 1990, this coal batch was found to be rapidly deteriorating and it was repacked for long-term storage in air-tight, N₂-purged plastic bags in batches of 500g.¹⁵ At the time of sealing, the coal was retested. Reported here are the chemical analyses and microautoclave test results from a recently opened plastic bag (March 1992). Comparison is made to the analyses of the as-received coal (November 1988), the analyses made upon resealing the coal in April 1990, and the analyses made one year later in March 1991.

The degree of deterioration of the coal sample via weathering is indicated by alteration in the oxygen functional-group distribution and an increase in total and organic oxygen content.¹⁶ Pyritic sulfur is known to slowly convert to sulfate; this and a loss of calorific value often are the only perceptible changes in the chemical analysis of the coal sample. The analyses given in Table 7 show that the coal, since testing in March 1991, has not oxidized at all. There is no increase in sulfate sulfur and no significant change in calorific value. This is in sharp contrast to the large degree of oxidation which occurred between receipt of the sample in November 1988 and retesting in April 1990.¹⁵

Generally, it has been found that oxidation results in a decrease in liquefaction yields.^{17,18} In order to determine the relative decline in performance of this coal, batch microautoclave tests have been periodically made using this coal and solvents containing varying ratios of tetralin and 1-methylnaphthalene. Three commonly used sets of test conditions were employed.¹⁹ The results of the most recent tests, and tests made twelve and twenty-five months earlier, are given in Table 8. The coal conversions obtained with these tests can be used as reference points for liquefaction solvents tested with this coal. Similar data for earlier (1979 and 1981) batches of the same coal were previously reported.¹⁹⁻²²

The repeatability of the microautoclave assay was shown to have a standard deviation of 1.2% absolute.¹⁹ All data are within this 1.2% deviation of the average with the exception of one value as indicated on Table 8. Therefore,

comparison with the sample analyzed in February 1990 and march 1991 show no significant change in coal conversion in the analyses performed in March 1992.

Although the oxidation of the standard coal may not have completely halted, its rapidity has significantly abated. Any limited oxidation which has occurred in the last twelve months has not affected the coal conversion results from microautoclave tests.

RESID CONVERSION KINETICS

INTRODUCTION

Several aspects of Wilsonville Close-Coupled-Integrated Two-Stage Liquefaction (CC-ITSL) resid conversion kinetics were investigated, and results are presented in this section. The first topic is a correction of the resid conversions and kinetic constants previously reported for Wilsonville Run 260.⁷ The second topic is a brief discussion and new values for the error limits associated with calculation of deactivation rate constants previously reported for Run 258²³ and for Run 261.⁵ The third topic is a discussion showing how conversions of 850°F* (CONSOL-measured), 1050°F* (Wilsonville-measured), and 850 x 1050°F (calculated by a new procedure) material can be related to each other. Additional new results are included in a written paper provided as Appendix 4 of this report.

CORRECTIONS TO WILSONVILLE RUN 260 RESID CONVERSIONS AND KINETIC CONSTANTS

When CONSOL's Run 260 report⁷ was issued, it contained first-stage and total system resid conversions and kinetic constants which were in error. The error resulted from failure to account for the contribution of 2 wt % Fe₂O₃ (MF coal basis) slurry catalyst to the ash balances involving the first stage (affecting the first-stage and total system conversions). The corrected data tables, graphs, and discussion appear in Appendix 1 of this report, numbered as they originally appeared.⁷ Briefly, the consequence of this correction is that the first-stage and total conversions of resid + IOM and resid components reported here are lower by 1 to 11% absolute, compared with those first reported. The second-stage conversions and kinetic constants were unaffected.

ERROR LIMITS FOR DEACTIVATION RATE CONSTANTS IN WILSONVILLE RUNS 258 AND 261

The deactivation rate constants were evaluated for Wilsonville Runs 258²³ and 261⁵ by considering the conversion activity, A, to have an exponential dependence on catalyst age, t, as $A = A'e^{\alpha t}$, where A' is the initial conversion activity. As written, catalyst deactivation results in negative values of α , the deactivation rate constant. The value of α was determined by regression of $\ln A$ on t, as $\ln A = \ln A' + \alpha t$, using the regression command in Lotus 1-2-3™ (version 2.01). A standard error, σ , is associated with each term determined by the regression. Rewriting the regression expression to include the standard errors, we have $\ln A = \ln A' \pm \sigma(A') + [\alpha \pm \sigma(\alpha)]t$; in the exponential form, $A = A'e^{\pm \sigma(A')}e^{[\alpha \pm \sigma(\alpha)]t}$. Although error limits for α can be reported as $\pm \sigma(\alpha)$, the

situation for the A' error limits is more complicated. The lower error limit for A' is $A'e^{-\sigma(A')}$ and the upper error limit for A' is $A'e^{+\sigma(A')}$. Thus, the standard error in A' is used in a term $\exp[\pm\sigma(A')]$, which is multiplied by A' instead of added to or subtracted from A', as a standard error is usually treated. To report error limits for A', it would be appropriate to give a lower confidence limit (LCL) and an upper confidence limit (UCL) corresponding to one standard deviation. The implications of this were not fully appreciated when the deactivation constants were first reported; therefore, the standard errors for A' were not appropriately reported. To remedy this situation, the errors in A' are properly reported here for Runs 258 and 261. The complete results are given below.

Run 258

Shell 324 Catalyst, periods K through M and average of periods B, C, D, E, F, H, and I:

First Stage:

$$\begin{aligned}\alpha &= 0.30 \times 10^{-4}, \sigma(\alpha) = 1.17 \times 10^{-4}, \\ A' &= 1.56 \times 10^7, \sigma(A') = 1.18, \\ LCL(A') &= 0.48 \times 10^7, UCL(A') = 5.11 \times 10^7, \\ R^2 &= 0.03\end{aligned}$$

Second Stage:

$$\begin{aligned}\alpha &= -6.2 \times 10^{-4}, \sigma(\alpha) = 0.06 \times 10^{-4}, \\ A' &= 4.96 \times 10^7, \sigma(A') = 1.09, \\ LCL(A') &= 1.67 \times 10^7, UCL(A') = 14.75 \times 10^7, \\ R^2 &= 0.98\end{aligned}$$

Run 261

First Stage, EXP-A0-60 Catalyst (periods A through D):

$$\begin{aligned}\alpha &= 0.2 \times 10^{-4}, \sigma(\alpha) = 3.0 \times 10^{-4}, \\ A' &= 4.1 \times 10^7, \sigma(A') = 1.5, \\ LCL(A') &= 0.9 \times 10^7, UCL(A') = 18.4 \times 10^7, \\ R^2 &= 0.00\end{aligned}$$

Second Stage, EXP-A0-60 Catalyst (periods A through D):

$$\begin{aligned}\alpha &= -2.6 \times 10^{-4}, \sigma(\alpha) = 3.4 \times 10^{-4}, \\ A' &= 3.1 \times 10^7, \sigma(A') = 1.4, \\ LCL(A') &= 0.8 \times 10^7, UCL(A') = 12.9 \times 10^7, \\ R^2 &= 0.24\end{aligned}$$

First Stage, Criterion 324 (periods E through G):

$$\begin{aligned}\alpha &= -3.5 \times 10^{-4}, \sigma(\alpha) = 2.6 \times 10^{-4}, \\ A' &= 2.5 \times 10^7, \sigma(A') = 1.1, \\ LCL(A') &= 0.8 \times 10^7, UCL(A') = 7.9 \times 10^7, \\ R^2 &= 0.65\end{aligned}$$

Second Stage, Criterion 324 (periods E through G):

$$\begin{aligned}\alpha &= -13.3 \times 10^{-4}, \sigma(\alpha) = 14.4 \times 10^{-4}, \\ A' &= 7.1 \times 10^7, \sigma(A') = 1.5, \\ LCL(A') &= 1.6 \times 10^7, UCL(A') = 31.9 \times 10^7, \\ R^2 &= 0.46\end{aligned}$$

Having the uncertainties properly defined allows the initial catalyst activities, A' (A at $t = 0$) to be compared within a run or between runs. The error in A' seems to be high in the results from both runs. The results indicate that all six of the initial activities are statistically equivalent.

850°F⁺ RESID CONVERSION AND KINETICS

Background

Due to a difference in distillation conditions, CONSOL measures 850°F⁺ resid concentration and calculates conversion of 850°F⁺ material, whereas Wilsonville measures 1050°F⁺ resid concentration and calculates conversion of 1050°F⁺ material.^{22,24} A simple equation was derived which relates the conversions of 850°F⁺, 1050°F⁺, and 850 x 1050°F material to each other. This will permit a more rigorous comparison of CONSOL and Wilsonville resid + UC conversion results, and a better understanding of their meaning. In this section, we will describe this relation and discuss how it may be applied to results from Wilsonville.

The following definitions are used:

C_1 = Conversion of 850 x 1050°F material

C_2 = Conversion of 1050°F⁺ material

C_3 = Conversion of 850°F⁺ material

I_1 = Input Flow of 850 x 1050°F material

I_2 = Input Flow of 1050°F⁺ material

I_3 = Input Flow of 850°F⁺ material

O_1 = Output Flow of 850 x 1050°F material

O_2 = Output Flow of 1050°F⁺ material

O_3 = Output Flow of 850°F⁺ material

Conversions and flows refer to organic material only (MAF basis) in each reactor or the total system. The input and output flows are on an ash balance basis. That is, flows are adjusted so that ash in=ash out. The conversion formulas for the three boiling fractions are:

$$C_1 = (I_1 - O_1)/I_1$$

$$C_2 = (I_2 - O_2)/I_2$$

$$C_3 = (I_3 - O_3)/I_3$$

The conversions C_1 , C_2 , and C_3 are on a weight fraction basis and could be put on a weight percent basis by multiplication by 100%. Rearranging each of these formulas, we get:

$$C_1 \cdot I_1 = I_1 - O_1$$

$$C_2 \cdot I_2 = I_2 - O_2$$

$$C_3 \cdot I_3 = I_3 - O_3$$

Since

$$I_3 = I_1 + I_2$$

and

$$O_3 = O_1 + O_2,$$

$$C_3 \cdot I_3 = I_3 - O_3 \text{ becomes}$$

$$\begin{aligned} C_3 \cdot I_3 &= (I_1 + I_2) - (O_1 + O_2) \\ &= (I_1 - O_1) + (I_2 - O_2) \end{aligned}$$

$$= C_1 \cdot I_1 + C_2 \cdot I_2$$

$$C_3 \cdot I_3 = C_1 \cdot I_1 + C_2 \cdot I_2$$

can be rearranged to

$$C_3 = C_1 \cdot I_1/I_3 + C_2 \cdot I_2/I_3, \quad (1)$$

and subsequently to

$$C_3 = (1 - F) \cdot C_1 + F \cdot C_2 \quad (2)$$

where $(1 - F) = I_1/I_3$ is the weight fraction of 850 x 1050°F material in the 850°F+ material and $F = I_2/I_3$ is the weight fraction of 1050°F+ material in the 850°F+ material.

In comparing Wilsonville and CONSOL resid + U¹³C conversions in reports describing recent Wilsonville runs, we have reported and discussed the ratios of CONSOL conversion to Wilsonville conversions. Eventually, we interpreted this ratio as a measure of 850 x 1050°F conversion relative to 1050°F+ conversion^{5,7,25} (see Appendix 4), but the relationship was not quantified. The conversion ratio used in past reports ($R(C/W)$ in Appendix 4) is represented by C_3/C_2 in the symbolism used here. Using Equation (2), we obtain:

$$C_3/C_2 = (1 - F) \cdot C_1/C_2 + F \quad (3)$$

Note that the ratio C_3/C_2 is related to C_1/C_2 , the 850 x 1050°F conversion relative to 1050°F+ conversion, as interpreted in the past, but the relation also contains $(1 - F)$ as a multiplicative term and F as an additive term. If the value of F is known, the 850 x 1050°F conversion can be calculated. At this point, we are faced with two possibilities. If F is unknown, the relationship between C_3/C_2 and C_1/C_2 can be explored parametrically at several values for F . This provides a better understanding of the 850 x 1050°F conversion trends in present and past results. The other possibility is to obtain a calculation using a determined or estimated value for F . As it so happens, a value for F is routinely available by combining CONSOL and Wilsonville analyses, if certain assumptions are made. The two problems with the second approach are: 1) CONSOL and Wilsonville do not always report analyses from the same sample, and 2)

Wilsonville reports cresol insolubles (CI) concentration, but not IOM and ash. Since nearly all of CONSOL's samples come from material balance periods, the first problem appears to be minimized, and should not prevent obtaining a fairly accurate value for F. The simplest calculational approach to the second problem is to assume that the CONSOL V-131B ash value is accurate. Thus, Wilsonville's IOM contribution from the recycle solvent is obtained by subtracting the CONSOL ash value from the Wilsonville CI concentration.

Another difficulty is that Wilsonville's resid and CI concentrations are only available for the solvent recycled to the first stage. However, using C_3 obtained from CONSOL, C_2 obtained from Wilsonville, and F obtained from both laboratories, it should be possible to calculate an F for reactor stage two, by assuming that I_2/I_3 for reactor stage two equals O_2/O_3 for stage one. Thus, it should be possible to obtain 850 x 1050°F conversions for each reactor stage by this method.

In sections to follow, both the parametric (F unknown) and exact (F known) approaches are used to illustrate how these methods can be used to elucidate 850 x 1050°F conversion and kinetics.

Parametric Approach to 850 x 1050°F Conversions

In evaluating conversions in past Wilsonville runs, the ratio of CONSOL-to-Wilsonville conversions, C_3/C_2 , also expressed as $R(C/W)$ in one treatment of the subject (Appendix 4), has been used as an indirect measure of relative 850 x 1050°F conversion. Ratios from Runs 250-259 averaged 0.98 in the first stage, 0.85 in the second stage, and 0.94 in the total system. Ratios from individual periods have ranged from lower than 0.6 to about 1.3. To calculate C_1/C_2 from C_3/C_2 , Equation 3 was rewritten to the following form:

$$C_1/C_2 = ((C_3/C_2) - F)/(1 - F) \quad (4)$$

To examine a broad range of possible values for F, Equation 4 was used to generate the data in Table 9. The values of F in Table 9 range from 0.70 to 0.95, representing reasonable estimates for 850°F+ composition. (Appendix 4 gives values of 0.70-0.75 for several runs, but recycle IOM and fresh coal are not included in those values.) Even with the few results listed, it is readily

apparent that C_3/C_2 is a very sensitive indicator of C_1/C_2 , and that the correspondence of C_3/C_2 with C_1/C_2 is closer as F decreases (see Equation 3). Thus, our previous interpretation of C_3/C_2 as indicating relative conversion of 850 x 1050°F (low when $C_3/C_2 < 1$, and high when $C_3/C_2 > 1$), was essentially correct. However, the ratio C_3/C_2 is a much more sensitive indicator of the 850 x 1050°F conversion than we expected.

The 850 x 1050°F conversion was explored in a simple model using results from Runs 262 and 260. The model results are shown in Table 10. Shown are flows of 1050°F⁺, 850 x 1050°F, and 850°F⁺ in and out of the Wilsonville liquefaction system (both stages together). A total of 100 lb/hr was input and the outputs of 1050°F⁺ and 850 x 1050°F were calculated such that the conversions of 1050°F⁺ (Wilsonville) and 850°F⁺ (CONSOL) material matched the actual run average values for each of the two runs. Run average resid+UC conversions were 35.2 ±3.0 (CONSOL) and 37.3 ±5.1 (Wilsonville) for Run 260 (Appendix 1), and 20.9 ±3.0 (CONSOL) and 36.3 ±2.7 (Wilsonville) for Run 262.²⁵ The F values used were the run averages of 0.86 ±0.02 for Run 262 (see discussion below for the Run 262 calculations) and 0.85 ±0.02 for Run 260. Representative values of 0.80 and 0.90 also were included. The ratios of CONSOL/Wilsonville conversions obtained from the model were very close to the run average values of 0.95 ±0.09 for Run 260 (Appendix 1) and 0.58 ±0.07 for Run 262.²⁵ The results indicate that during Run 262, the 850 x 1050°F conversion had to be about -70% (a net increase, instead of disappearance) to account for the observed results. The results indicate that about 30% of the converted 1050°F⁺ ended up as the 850 x 1050°F increase. Thus, not only was the conversion of 850 x 1050°F low, relative to the conversion of 1050°F⁺, but there was a net make of 850 x 1050°F. In steady-state operation, this material must exit the process either as distillate product or as ash concentrate. We postulate that this may have been caused by a concentration or buildup of paraffinic components in the 850 x 1050°F fraction, as previously stated.²⁵ In contrast, we obtain a positive value for the 850 x 1050°F conversion in Run 260. As expected, it is lower than the 1050°F⁺ conversion. Run 260 results probably typify most past CC-ITSL runs, based on the CONSOL and Wilsonville conversions of resid + UC. However, the results in Table 10 suggest a deficit of 850 x 1050°F material in Run 260, in contrast to a surplus of 850 x 1050°F material in Run 262. The calculations in the table provide estimates of the quantity of 850 x 1050°F⁺ material needed or produced per 100 lb/hr (MAF)

850°F reactor feed. We can use the percent MAF coal in the 850°F reactor feed (run average of 38.7 wt % in Run 260 and 40.3 wt % in Run 262) and the MAF coal feed rate (run average 289.8 lb/hr in Run 260 and 277.5 lb/hr in Run 262) to estimate the amount of 850 x 1050°F material involved on an MAF coal or lb/hr basis. The results indicate a deficit of 850 x 1050°F material in Run 260 which is 9.0 wt % of the MAF coal, or about 26 lb/hr. The Run 262 results indicate a surplus of 850 x 1050°F material which is 25.6 wt % of the MAF coal, or about 71 lb/hr.

Several possible explanations are offered for these results.

1. The values are distorted or incorrect because of calculation or analytical errors. These calculations are based on sample analyses, and not on any Wilsonville flow rates (except the MF coal feed rate).
2. The results represent imbalanced operation (not at steady-state), which would have resulted in shifts in the recycle oil inventory and in product and recycle oil properties.
3. The surplus 850 x 1050°F material in Run 262 must exit the system as distillate or ash concentrate, the only non-gas net products.
4. The deficit in Run 260 is made up from an unaccounted source of 850 x 1050°F material. Perhaps flows of pump seal oil and various flush oil streams at the Wilsonville plant were large enough to account for the 26 lb/hr of material. Accurate flow rates of these streams have not been widely available. This suggests that such streams may have a more significant impact than has been heretofore assessed.
5. The ROSE-SR system, which is downstream of the reactor system, somehow interconverts 850 x 1050°F material with other material fractions.

At present, information is insufficient to know which explanation is appropriate for the 850 x 1050°F material deficit indicated in Run 260. Surplus 850 x 1050°F material which exits as ash concentrate in Run 262 does not appear to be inconsistent with other Run 262 results.

Exact Solution Approach to 850 x 1050°F Conversions

In this section, we develop and apply the exact solution approach for 850 x 1050°F conversions, based on a determined or estimated value for F. First, Equation 2 can be rearranged to:

$$C_1 = (C_3 - F \cdot C_2)/(1 - F) \quad (5)$$

Equation 5 then provides the basis for calculation of C_1 , the 850 x 1050°F conversion. The value of F is obtained by the following formula:

$$[(100-D)(A+B-C) + D(100-E)]/[(100-D)(G+H) + D(100-E)], \quad (6)$$

where

A = Wilsonville Resid Concentration in Pasting Solvent (V-131B) in wt %

B = Wilsonville CI Concentration in Pasting Solvent (V-131B) in wt %

C = CONSOL Ash Concentration in V-131B in wt %

D = Wilsonville MF Coal Concentration in Feed in wt %

E = Wilsonville MF Ash Concentration in Coal in wt %

G = CONSOL THF-soluble Resid Concentration in V-131B in wt %

H = CONSOL IOM Concentration in V-131B in wt %

This assumes that the CONSOL ash measurement is valid for each corresponding Wilsonville sample, as described earlier. Results of these calculations for Wilsonville Run 262 are presented in Table 11. Note that values for F are given for the inputs to the first and second stage and the output from the second stage (F_1 , F_2 , and F_3 , respectively). Since 1050°F material was converted through the process, there was a decrease in these F values through the process (averages went from 0.86 ± 0.02 to 0.78 ± 0.05 to 0.69 ± 0.04). The conversion of 850 x 1050°F material showed considerable period-to-period variation between stages, but the total conversion was fairly consistent. For each stage, the standard deviation was greater in magnitude than the corresponding average. In agreement with the simple model results presented in the previous section, the conversion of 850 x 1050°F material is shown to be negative (indicating a net yield) in most periods in each stage and the total system. The results for period B look particularly suspicious, being quite high in the first stage and quite low in the second stage.

These results show that the method can be used to provide new information about 850 x 1050°F conversion at Wilsonville. Application of these various approaches (parametric and exact solution) to additional data should allow a better understanding of the fate of 850 x 1050°F material in liquefaction processing at Wilsonville.

PARTICIPANTS PROGRAM STATUS

SUMMARY

The following items were accomplished in the eleventh quarter of this contract.

Phase I

The final reports from Advanced Fuel Research and the National Institute for Petroleum and Energy Research were printed and issued. All Phase I subcontracts now are complete.

A paper was prepared which presents some of the subcontractor data accumulated in Phase I of the Participants Program. It will be presented at the 204th National Meeting of the American Chemical Society. A copy of the preprint appears as Appendix 4 of this report.

Advanced Fuel Research will present work performed under Phase I of the Participants Program at the 204th National Meeting of the American Chemical Society. A copy of the preprint appears as Appendix 1 of this report.

Phase II

All remaining sample sets and information packages were issued to Phase II subcontractors.

Battelle, Pacific Northwest Laboratory (PNL) issued a draft final report; it was reviewed by CONSOL and revised by PNL. A CONSOL evaluation was written. The evaluation and the PNL executive summary are found later in this report.

Draft final reports were received from Vander Sande Assoc. and the University of Utah.

The third and fourth status reports were received from Lehigh University. Lehigh will present work performed under Phase II of the Participants Program at the 204th National Meeting of the American Chemical Society. A copy of the preprint appears as Appendix 2 of this report.

Second and third status reports and a draft final report were received from Iowa State University. An extension of two weeks was granted to the University of Pittsburgh researchers because of unanticipated instrument down-time in the last month.

Work is concluding for all Phase II subcontracts. Draft final reports are due from all subcontractors (with the exception of the University of Pittsburgh) by July 1, 1992.

DISCUSSION

Phase I

All Phase I subcontracts are now closed. All subcontract final reports were printed and issued as topical reports under this contract.²⁶⁻³² The CONSOL evaluations for all projects were included in the topical reports and were reproduced in quarterly technical progress reports.^{5,7,25}

A paper was prepared for presentation at the 204th National American Chemical Society Meeting in Washington DC, August 1992. The full paper appears as Appendix 4 of this report.

AFR will present their work at the 204th National American Chemical Society Meeting in Washington DC, August 1992. A copy of the preprint appears as Appendix 1 of this report.

Phase II

All remaining sample sets and information packages were issued to Phase II subcontractors in this quarter. The final set of samples, which was obtained from Wilsonville Run 263, was issued to Vander Sande Associates.

Battelle, Pacific Northwest Laboratory (PNL) issued a draft final report; it was reviewed by CONSOL and revised by PNL. A CONSOL evaluation was written. The evaluation and the PNL executive summary are found later in this report. The revised final report is in printing.

The second and third status reports and the draft final report were received from Iowa State University. Draft final reports were received from Vander Sande Assoc., West Virginia University, and the University of Utah. All final reports will be reviewed, and the CONSOL evaluations will be included in subsequent technical reports under this contract.

The third and fourth status reports were received from Lehigh University. Lehigh will present work performed under the Participants Program at the 204th National ACS Meeting in Washington, DC. A copy of the preprint appears as Appendix 2 of this report. Lehigh University and the University of Chicago, report that they have completed data acquisition and are beginning to interpret the data in the context of the processing information. An extension of two weeks was granted to the University of Pittsburgh because of unanticipated instrument down-time in the last month. The University of Kentucky requested a three-week extension so that they might return to Brookhaven National Laboratory and re-examine some of the samples using Brookhaven's synchrotron.

CONSOL EVALUATION AND EXECUTIVE SUMMARY OF FINAL REPORT FROM BATTELLE, PACIFIC NORTHWEST LABORATORY

PROJECT ASSESSMENT

Introduction

Under contract from the DOE (Contract No. DE-AC06-RL01830), and in association with CONSOL Inc. (DOE Contract No. DE-AC22-89PC89883), Battelle, Pacific Northwest Laboratory (PNL) evaluated four principal and several complementary techniques for the analysis of non-distillable direct coal liquefaction materials in support of process development. Field desorption mass spectrometry (FDMS) and nuclear magnetic resonance (NMR) spectroscopic methods were examined for potential usefulness as techniques to elucidate the chemical structure of residual (non-distillable) direct coal liquefaction derived materials. Supercritical fluid extraction (SFE) and supercritical fluid chromatography/mass spectrometry (SFC/MS) were evaluated for effectiveness in compound-class separation and identification of residual materials. Liquid chromatography (including microcolumn) separation techniques, gas chromatography/mass spectrometry (GC/MS), mass spectrometry/mass spectrometry (MS/MS), and GC/Fourier transform infrared (FTIR) spectroscopy methods were applied to supercritical fluid extracts. The full report authored by the PNL researchers is presented here. The following assessment briefly highlights the major findings of the project, and evaluates the potential of the methods for application to coal liquefaction materials. These results will be incorporated by CONSOL into a general overview of the application of novel analytical techniques to coal-derived materials at the conclusion of CONSOL's contract.

Summary

This study demonstrated the feasibility of using FDMS, NMR, SFE, and SFC/MS for the examination of the tetrahydrofuran-soluble portion of the 850°F⁺ distillation resid materials derived from direct coal liquefaction. In addition, liquid chromatographic (LC) separations were employed to pre-separate the resids prior to analysis by NMR and FDMS methods. Other techniques, including microcolumn LC separations, GC/MS, GC/FTIR, and MS/MS, were tested with the supercritical fluid extracts of the THF-soluble distillation resids.

A heteronuclear correlation (HETCOR) spectroscopy two-dimensional (2-D) NMR technique was applied without success to the THF-soluble distillation resids.

Spectral-editing NMR techniques yielded some information on the aromatic cluster size and degree of aliphatic substitution in the THF-soluble resid samples.

FDMS analysis of the THF-soluble portion of the distillation resids showed differences in the molecular weight ranges and intensities of the prominent ions, and ratios of those ions, in samples obtained from different feed coals and in samples from different stages in the direct liquefaction process.

Supercritical fluid extraction reproducibly separated the THF-soluble resids with high extraction efficiency (>80%). The SFE fractions were successfully analyzed by FDMS and GC/FTIR, although no useful structural information was obtained. SFC of the unfractionated THF-soluble resids was not successful; there was very little or no peak resolution in the chromatograms. However, SFC did resolve some components of the SFE fractions. SFC/MS was not successful; this was primarily attributed to equipment limitations, such as a poorly performing SFC-MS interface, and not the technique. The MS/MS method, employing desorption chemical ionization, was demonstrated with one of the SFE extracts. The MS/MS experiment was performed on the m/z 277 ion, chosen because it was presumed to be m/z (276 H^+); m/z 276 was found to be a prominent peak in the FDMS study. Although the results obtained were not those for the predicted structure of the m/z 277 ion, the method appears to be promising.

Program Description

This report describes the work performed at PNL under a contract from the U.S. DOE (Contract No. DE-AC06-76RL01830) in association with CONSOL Inc., Research and Development. CONSOL's contract to the U.S. Department of Energy (Contract No. DE-AC22-89PC89883, "Coal Liquefaction Process Streams Characterization and Evaluation") established a program for the analysis of direct coal liquefaction derived materials. The program involves a number of participating organizations whose analytical expertise is being applied to these materials. This Participants Program has two main objectives. The broad objective is to improve our understanding of fundamental coal liquefaction chemistry to facilitate process improvement and new process development. The specific approach to achieving this objective is to provide a bridge between direct coal liquefaction process development and analytical chemistry by demonstrating the application of various advanced analytical methods to coal liquefaction materials. The

methodologies (or techniques) of interest are those which are novel in their application for the support of coal liquefaction and those which have not been fully demonstrated in this application. CONSOL is providing well-documented samples from different direct coal liquefaction process development facilities to the program participants. The participants are required to interpret their analytical data in context to the processing conditions under which the samples were generated. The methodology employed is then evaluated for its usefulness in analyzing direct coal liquefaction derived materials.

Methodology

PNL used field desorption mass spectrometry (FDMS) and various NMR techniques to analyze the THF-soluble portion or 850°F⁺ distillation resid. 2-D NMR and NMR spectral editing techniques, which rely on the unique polarization parameters between the proton and carbon nuclei, were applied to the THF-soluble resid. These techniques included the attached proton test (APT) and distortionless enhancement by polarization transfer (DEPT). The resid materials, which are solids at room temperature, were analyzed as THF solutions. The samples analyzed by FDMS and NMR were produced at the Wilsonville pilot plant. Two major processing parameters were varied among the Wilsonville runs: feed coal and reactor configuration (thermal/catalytic or catalytic/catalytic). Samples from Wilsonville were taken from three locations: between the reactors, after the second-stage reactor, and at the recycle oil tank. These samples are expected to represent different extents of coal liquefaction. All of the Wilsonville samples were composites of samples taken over long periods of single runs.

Separation techniques, including SFE, SFC, SFC/MS, high pressure liquid chromatography (HPLC), microcolumn liquid chromatography, open column liquid chromatography, gas chromatography/Fourier transform infrared (GC/FTIR) spectroscopy, MS/MS and GC/MS were applied to THF-soluble materials obtained from two facilities. Four of the samples analyzed by these methods were identical to those analyzed by FDMS and NMR. Two additional samples, which represent single run periods, were obtained from the HRI process development unit. The HRI samples were chosen to represent two methods of pretreating the coal before it is fed to the liquefaction system.

Major Findings

The following principal observations were reported by PNL for the application to coal liquefaction materials of Field desorption mass spectrometry (FDMS), nuclear magnetic resonance (NMR) spectroscopy, and the assorted separation techniques inclusive of supercritical fluid extraction (SFE), supercritical fluid chromatography (SFC), and high pressure liquid chromatography (HPLC), microcolumn liquid chromatography, and open column liquid chromatography.

The FDMS technique shows that all the resid samples examined have roughly the same molecular weight distribution; the bulk of the material is within the range of 200 to 600 Da. However, many of the samples exhibited peaks as high as 3500 Da. PNL reports that the molecular weights of resid samples obtained at different locations in the liquefaction process increases slightly in the order: second-stage product sample < recycle oil sample < interstage oil sample for each set of samples produced during different runs at the Wilsonville Advanced Two-Stage Liquefaction Facility. Tentative structures were assigned to several prominent ions in the 200 to 400 Da range (e.g., m/z 242, 276, 308, and 316). The prominent peaks and their assignments agreed with previous published field-ionization mass spectroscopy work on the same samples.²⁹ It was noted by PNL that the ratios of these ions differ among the various samples.

Application of the heteronuclear correlation (HETCOR) spectroscopy technique, also referred to as 2-D NMR, was not successful with the whole resid samples. This is due to the lack of peak resolution obtained in both the component ^{13}C - and ^1H -NMR spectra. In an exploratory test, PNL found that it is possible to improve the resolution by preliminary separation of the resid samples by supercritical-fluid techniques and open column liquid chromatography. DEPT and APT techniques are used to determine the distribution of carbon types. The experiments can distinguish between protonated and non-protonated aromatic carbon, and the amount of methyl, methylene, and methene carbon. The DEPT and APT spectra of the samples examined by PNL (Nos. 2, 3, and 4), show very little aliphatic methene (mono-protonated) carbon to be present.

Supercritical fluid extraction gave high extraction efficiencies for four samples (>80% in all cases) with the THF-soluble resid samples. However, HPLC of the whole THF-soluble resids and supercritical fluid chromatography of the SFE

fractions were not successful; only broad, unresolved peaks were observed. The SFE fractions were further separated by open column liquid chromatography followed by HPLC. Although peak resolution was greatly improved, the separated components were not characterized. GC/FTIR of the SFE fractions was performed; however, no compound identifications could be made. GC/MS of a nonpolar (hexane-eluted) HPLC fraction of an isopropyl alcohol/CO₂ SFE fraction of one HRI filter liquid was reported. Some of the identified structures are consistent with the prominent ions identified by FDMS of the parent THF-soluble resid.

The SFE fractions also were analyzed by electrospray mass spectrometry and desorption chemical ionization (DCI) MS/MS of selected ions from the electrospray MS analyses. As most of the compounds in the SFE fractions were not ionizable by electrospray ionization, this technique appears to have little potential for use with these samples. The DCI MS/MS technique, while not fully explored in this study, showed potential for further analysis of single ions in the complex MS spectra. The SFE fractions also were examined by FDMS. The different SFE fractions consist of materials with distinctly different molecular weight ranges.

CONSOL Evaluation

The FDMS technique appears to have potential for the analysis of the coal-derived resids. A number of unresolved issues remain to be addressed before the method can be unconditionally recommended. One issue concerns the limitation placed upon the analysis by the introduction into the mass spectrometer of only the soluble portion of the samples. Alternate mass spectral techniques also have limitations: field ionization (FI) MS is limited by sample volatility, plasma desorption (PD) MS is limited by the ability of the experimenter in creating a thin film of sample material. Which of these constraints is more restrictive is not obvious. A second issue is the potential for different FDMS responses to various compound types in complicated mixtures that have a wide range of molecular weights (such as in a resid); this also must be determined before the FDMS method could be routinely used for process development application.

The use of 2-D NMR techniques and the various NMR spectral editing techniques for coal derived resids appears feasible and potentially useful for structure determination if the samples are first separated into sufficiently specific compound class fractions. Such separations, as demonstrated in this work, were

performed fairly well by a series of techniques: supercritical extraction with various organic fluids, followed by liquid chromatographic methods. The resultant information from such extensive and labor-intensive work was not fully evaluated by PNL, although such an evaluation would be required before the use of such a complicated scheme could be recommended as a process development tool.

The different techniques employed in this work require large capital investment for the equipment. Some costs reported by PNL to CONSOL follow. The high-resolution mass spectrometer with FD capabilities costs approximately \$800,000. A supercritical fluid extraction system costs about \$60,000. A supercritical fluid chromatograph/mass spectrometer costs on the order of \$300,000. A high-resolution NMR costs approximately \$300,000. The expendable supplies used in this contract for the supercritical fluid systems (e.g., columns, solvents and gases), cost about \$5,000. The open column chromatography experiments, as performed in this work, used about \$5,000 worth of supplies (columns, packing, and solvents). Each of the experimental procedures requires 1 - 2 hours to prepare and run a sample.

Further Development

Each of the analytical techniques demonstrated in this study can be further developed for use in the analysis of direct coal liquefaction derived resid materials. Suggestions made by the PNL research group include: 1) further examination of the specific hydrocarbons, some of which were tentatively identified by FDMS, that have prominent ion intensities, 2) identification of specific compounds that have molecular weights greater than 300 Da., 3) the analysis of all process streams in the direct liquefaction process by various NMR techniques, including HETCOR, DEPT, APT, and quantitative proton and carbon NMR, 4) application of PNL's ultra-high pressure NMR cell for the in situ analysis of supercritical fluid extracts from coal liquefaction resids, and 5) expanded use of separation techniques, especially supercritical fluid techniques, as hyphenated methods (i.e. SFC-MS, SFC-FTIR, and SFE-desorption chemical ionization (DCI) MS) for the analyses of the resid materials. Other research directions based on this work that are worthy of note include: 1) a detailed comparison of the results and usefulness of FDMS, FIMS and ²⁵²Cf-PDMS for process development, and 2) development of a systematic separation and analysis scheme for non-distillable coal-derived resids utilizing the methods demonstrated in this study.

Statement of Work

In order to better elucidate the composition of the non-distillable residuum portion of coal liquefaction streams as it relates to conversion activity, a number of novel techniques will be applied to coal liquefaction process derived materials. These techniques include field desorption mass spectrometry (FDMS), two dimensional nuclear magnetic resonance spectroscopy (2D-NMR), and supercritical fluid extraction (SFE) coupled with supercritical fluid chromatography (SFC). FDMS is noted for its ability to directly analyze high molecular weight materials. 2D-NMR is a powerful method for obtaining organic structural information. SFE is useful for compound class separations, especially of high molecular weight materials. SFE, followed by SFC with mass spectral detection, is useful for the analysis of compounds with high molecular weight and limited volatility. It is, therefore, a promising technique for analysis of coal derived materials.

Field desorption mass spectrometry (FDMS) will be used for resid characterization. A potential advantage of FDMS over other mass spectrometric methods is that high molecular weight samples can be ionized directly from the condensed phase without the need for vaporization by heating. The application of FDMS to a reasonably large sample set (12 samples) will allow a demonstration of the value of this technique. These samples have been selected (see attached list) so that the utility of FDMS for addressing the issue of resid reactivity can be evaluated. The twelve samples will be supplied to PNL with the following information (as available): elemental analyses, ash content, ash elemental analysis, phenolic -OH concentration, calorific value, hydrogen classes by ¹H-NMR, resid reactivity data (calculated), and the full history of the sample (plant, process conditions, age, and storage conditions). All samples are non-distillable residual materials which may contain insoluble organic matter (IOM) and ash. Sample size will be at least 0.5g. Most samples will be brittle pitch-like materials that will be supplied as approximately -8 mesh (2.4 mm) pieces.

Supercritical fluid extraction-supercritical fluid chromatography (SFE-SFC) is a combined technique which may prove useful for the separation of the high molecular weight, polar materials found in coal liquefaction process streams. These materials are primary candidates for retrogressive reactions leading to poor conversion in coal liquefaction. The extraction will provide a rough

compound class separation. With the use of mass spectrometric detection, supercritical fluid chromatography can be used to detect compounds with molecular weights in excess of 600 daltons. The method is not amenable to solids-containing samples and, therefore, a sample set has been selected which contains only the tetrahydrofuran (THF) soluble portion of distillation resids and filtered liquids from different process streams. Six samples will be supplied to PNL for supercritical fluid chromatography. Each will be supplied with the following information (as available): elemental analyses, phenolic -OH concentration, calorific value, hydrogen classes by ^1H -NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). Sample size will be nominally 1 g.

Two dimensional NMR (2D-NMR) will be used to obtain structural information of the heavy materials found in coal liquids. The technique is only amenable to liquid or soluble material. CONSOL will supply to PNL THF-soluble portions of four distillation resids for 2D-NMR. These materials will be supplied with the following information (as available): elemental analyses, phenolic -OH concentration, calorific value, hydrogen classes by ^1H -NMR, and the full history of the sample (plant, process conditions, age, and storage conditions). Sample size will be nominally 0.5 g.

Battelle, PNL, Executive Summary

Pacific Northwest Laboratory (PNL) has analyzed a series of coal-derived residual oils by field desorption mass spectrometry (FDMS) and two-dimensional nuclear magnetic resonance (2D-NMR) to better elucidate the composition of the non-distillable residuum portion of coal liquefaction streams as it relates to conversion activity. Supercritical fluid extraction and supercritical fluid chromatography/mass spectrometry (SFC/MS) have also been evaluated for compound class separation and identification. The results of the analyses are briefly summarized in Table 1.

Twelve coal-derived samples taken from the Wilsonville facility at three different locations during the same run to represent different degrees of coal processing have been analyzed by FDMS. The molecular weight distributions obtained by FDMS are similar for all of the samples analyzed. The molecular

weight ranges are between 200 and 800 Da. There are, however, subtle differences that exist between samples. Qualitatively, there appears to be a slight increase in the molecular weight in going from the product oil, to the recycle oil, to the interstage oil for each set of samples. For some samples, there is also a difference between the ratio of extracted ions for a specific mass range, e.g. 400 to 500 Da, and the total ion intensity. In addition, the ratio of the intensities for several of the predominant ions varies for many of the samples. Tentative structures for several of the predominant ions m/z 242, 276, 308, and 316 have been assigned. Mass spectra for the above listed ions have been obtained by supercritical fluid fractionation of one of the samples, followed by open column chromatographic separations, with subsequent analysis by gas chromatography/mass spectrometry. The tentative structures are consistent with the observed mass spectra. Other methylated homologues have also been tentatively assigned.

For several of the Pittsburgh seam and Wyodak samples, field desorption (FD) spectra were difficult to obtain, possibly due to suppression of the signal from higher molecular weight material or degree of solubility in THF. However, for the most part, there was good agreement between the results obtained by FD and field ionization (FI) studies conducted by SRI. The results also provide clear evidence for the value of FDMS analysis of coal-derived resids.

Field desorption mass spectrometry has also shown a clear molecular weight distribution difference between supercritical fluid fractionated high molecular resids. Desorption chemical ionization (DCI), a technique similar to both FD and FIMS except chemical ionization is utilized rather than electron impact ionization, has also provided information on both the coal-derived resids and also the supercritical fluid fractionated resids.

Quantitative proton and ^{13}C solution spectra were collected at 300 MHz and 75 MHz on four THF-soluble portions of the distillation resid. The coal liquefaction residues were found to contain aromaticities, f_a , from 52-74%. Distortionless enhancement by polarization transfer (DEPT), Heteronuclear Correlation Spectroscopy (HETCOR) and the Attached Proton Test (APT) were used to determine the distribution of the functional groups throughout these coal products. The failure of the HETCOR experiments on the coal liquefaction residues is, in part,

caused by the lack of peak definition in both the ^{13}C and ^1H NMR spectra of these samples. A comparison of the spectra obtained in this study with those of solvent refined coal (SRC) distillate products show a large difference in NMR signal type. In order to effectively apply two-dimensional NMR techniques to coal products, fractionation of the products is necessary. As an example, the samples may be fractionated with the utilization of supercritical fluids prior to NMR analysis. Preliminary results obtained in a study employing fractionation by supercritical fluids, followed by separation with open column chromatography, and subsequent NMR analysis show significant improvement in resolution compared to NMR analysis of the original material.

Four of the six samples (17-20) provided by CONSOL were extracted with supercritical propane, pentane, pentane/methanol, pentane/THF, and pentane/acetic acid in a sequential manner. The summation of the weights of all of the extracts and the residue added up to 99+% of the material placed in the extraction cell for each sample. The total amount extracted by the non-polar solvents, propane and pentane, was fairly constant at 43.6 to 44.8 wt %. The last two samples, HRI and filter liquid samples, were extracted with supercritical fluid carbon dioxide with a modifier of 10% isopropanol. Approximate extraction efficiencies were 20-30% for both of the last two samples. Supercritical fluid chromatography (SFC) was attempted on the extracts, but met with little success. Only a broad, unresolved hump was present; there was no indication of any separation or resolution of components for any of the samples. Both packed and capillary column SFC were attempted using supercritical propane, pentane, and modified pentane but little difference in resolution was observed.

Supercritical fluid chromatography/mass spectrometry has been used to analyze complex hydrocarbon mixtures. Mass spectral data were obtained and the preliminary results are very promising; however, more work needs to be directed toward development of the appropriate restrictor. We do feel that SFC/MS warrants further attention for the analysis of the high molecular weight resid samples.

Supercritical fluid extraction with subsequent analysis by electrospray mass spectrometry appears to be of little use for these types of samples. However, supercritical fluid extraction and fractionation followed by desorption chemical

ionization (DCI) mass spectrometry or FD holds promise for providing additional structural information. Preliminary results of the pentane and pentane/methanol fractions by FD showed different molecular weight distributions. Fractionation by supercritical fluid extraction with subsequent analysis by NMR may also provide structural information on the coal liquefaction products. In addition, preliminary results from microcolumn separations and open column separations with subsequent mass spectrometry analysis indicate that further insight into structure elucidation or compound class identification in the resids may be possible.

Section 3

EXPERIMENTAL

Experimental details are described, where appropriate, in the Discussion section of this report. Details of the other analytical techniques used in this work were reported previously.^{19,21}

Section 4

REFERENCES

1. Brandes, S. D.; Robbins, G. A.; Winschel, R. A. ; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Analytical Needs Assessment Topical Report", DOE/PC 89883-18, March 1991.
2. Personal communication with O. Davies, SEI.
3. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, April 1 through June 30, 1990", DOE/PC 89883-22, July 1991.
4. Southern Clean Fuels, Wilsonville Advanced Coal Liquefaction R&D Facility, Handouts from Technical Meeting No. 103 (March 14, 1990), No. 104 (May 16, 1990, and No. 105 (July 11, 1990).
5. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, October 1 through December 31, 1991", DOE/PC 89883-43, March 1992.
6. Southern Clean Fuels, Wilsonville Advanced Coal Liquefaction R&D Facility, Handout from Technical Meeting No. 109 (March 20-21, 1991).
7. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Quarterly Technical Progress Report, April 1 through June 30, 1991", DOE/PC 89883-29, November 1991.
8. Southern Clean Fuels, Wilsonville Advanced Coal Liquefaction R&D Facility, Handout from Technical Meeting No. 106 (Sept. 19-20, 1990).
9. Gatsis, J. G.; Lea, C. L.; Miller, M. A. "Single-Stage Slurry-Catalyzed Co-Processing Developments", *Fuel* 1990, 35(4), 975-987.
10. Gatsis, J. G., personal communication to M. S. Lancet, May 23, 1992.
11. Lancet, M. S.; Winschel, R. A.; Burke F. P. "Stable Carbon Isotope Analysis of Coprocessing Materials - Quarterly Technical Progress Report, April 1 - June 30, 1990", DOE/PC 88800-37, February 1991.
12. Winschel, R. A.; Lancet, M. S.; Burke, F. P. "Stable Carbon Isotope Analysis of Coprocessing Materials - Final Technical Progress Report", DOE/PC 88800-43, April 1991.
13. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation - Second Annual Report, January 1 - December 31, 1986", DOE/PC 70018-37, June 1987. See also revisions that appear as Appendix 2 of companion report No. DOE/PC 70018-46, February 1988.

14. Piasecki, C. A., personal communication to M. S. Lancet, December 3, 1990.
15. Robbins, G. A.; Brandes, S. D.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Technical Progress Report, January 1 through March 31, 1990", DOE/PC 89883-16, February 1991.
16. Liotta, R.; Brons, G.; Isaacs, J. "Oxidative Weathering of Illinois No. 6 Coal", *Fuel* 1983, 62, 781.
17. Chang, C. Y., Guin, J. A., Tarrer, A. R., *J. Chinese Chemical Society* 1981, 28, 155.
18. Cronauer, D. C. "The Influence of Coal Aging and Oxidation on Liquefaction" presented at the Japan/U.S. NSF Chemistry of Coal Liquefaction Meeting, 1982.
19. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Recycle Slurry Oil Characterization Final Report, October 1980 through March 1985", DOE/PC 30027-61, March 1985.
20. Kleinpeter, J. A.; Burke, F. P.; Dudd, P. J.; Jones, D. C. "Process Development for Improved SRC Options: Interim Short Residence Time Studies", Interim Report, EPRI Project 1134-1, EPRI AF-1158, August 1979.
21. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1 through September 30, 1985", DOE/PC 70018-13, December 1985.
22. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, January 1 through March 31, 1988", DOE/PC 70018-62, March 1989.
23. Robbins, G. A.; Winschel, R. A.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Technical Progress Report, October 1 through December 31, 1989", DOE/PC 89883-10, October 1990.
24. Burke, F. P.; Winschel, R. A.; Robbins, G. A. "Coal Liquefaction Process Solvent Characterization and Evaluation - Final Report", DOE/PC 70018-70, September 1989.
25. Robbins, G. A.; Winschel, R. A.; Brandes, S. D.; Burke, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation, Technical Progress Report, January 1 through March 31, 1992", DOE/PC 89883-50, July 1992.
26. Taylor, L. T.; Hellgaeth, J. W.; Sequeira, A. "Coal Liquefaction Process Streams Characterization and Evaluation; Analysis of Coal Liquefaction Process Streams by Chromatographic and Spectroscopic Techniques, Topical Report", DOE/PC 89883-41, January 1992.
27. Mitchell, G.; Davis, A. "Coal Liquefaction Process Streams Characterization and Evaluation; Gold Tube Carbonization and Reflectance Microscopy, Topical Report," DOE/PC 89883-37, December 1991.

28. Rathbone, R. F.; Hower, J. C.; Derbyshire, F. J. "Coal Liquefaction Process Streams Characterization and Evaluation; Novel Analytical Techniques for Coal Liquefaction: Fluorescence Microscopy, Topical Report." DOE/PC 89883-30, October 1991.
29. Malhotra, R.; McMillen, D. F. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Liquids by Field Ionization Mass Spectrometry and Iodotrimethylsilane Derivatization, Topical Report", DOE/PC 89883-39, January, 1992.
30. Miknis, F.P. "Coal Liquefaction Process Streams Characterization and Evaluation; Solid-State NMR Characterization of Coal Liquefaction Products, Topical Report", DOE/PC 89883-36, November 1991.
31. Serio, M.A.; Hsisheng, T.; Bassilakis, R.; Solomon, P.R. "Coal Liquefaction Process Streams Characterization and Evaluation; FT-IR Methods for Characterization of Coal Liquefaction Products, Topical Report", DOE/PC 89883-45, April 1992.
32. Green, J.B.; Pearson, C.D.; Young, L.L.; Green, J.A. "Coal Liquefaction Process Streams Characterization and Evaluation; Application of Liquid Chromatographic Separation Methods to THF-Soluble Portions of Integrated 2-Stage Coal Liquefaction Resids, Topical Report", DOE/PC 89883-47, May 1992.
33. Nafis, D. A.; Gatsis, J. G.; Lea, C. L.; Miller, M. A. "Slurry-Catalyzed Co-Processing", presented at CANMET/DOE Joint Technical Workshop on Coprocessing; Ottawa, Ontario, Canada, June 6, 1990.

/1s

TABLE 1
PREHEATER TESTS

Test Date	Coal Sample (Seam)	Recycle Solvent (V131B)	Heating Profile	Coal Conversion wt %
10/11/90	Pittsburgh	Run 259 G	1a	92.7
10/12/90	Pittsburgh	Run 259 G	1b	91.5
10/10/90	Pittsburgh	Run 259G	1c	91.1
11/30/90	Wyodak & Anderson	Run 260 C	1a	53.6
11/9/90	Wyodak & Anderson	Run 260 C	1b	65.3
1/14/91	Wyodak & Anderson	Run 260 C	1b	53.8
11/1/90	Wyodak & Anderson	Run 260 C	1c	58.1
11/29/90	Wyodak & Anderson	Run 260 C	1c	50.3
5/12/92	Wyodak & Anderson	Run 260 B	2	68.8
5/14/92	Wyodak & Anderson	Run 260 B	2	68.8
3/25/91	Illinois No.6	Run 261 B	1c	77.3
3/27/91	Illinois No.6	Run 261 B	1c	77.8
4/1/91	Illinois No.6	Run 261 B	2	79.5
4/3/91	Illinois No.6	Run 261 B	2	74.5
4/9/91	Illinois No.6	Run 261 B	2	79.7
4/15/91	Illinois No.6	Run 261 B	2	80.8
4/16/91	Illinois No.6	Run 261 B	3	69.3
4/18/91	Illinois No.6	Run 261 B	3	72.6

TABLE 2
BASELINE PREHEATER TESTS^a

Test Date	Coal Sample	Solvent	Conversion, wt % ^b
11/16/90	Pittsburgh	1-Methylnaphthalene	81.7
10/15/90	Pittsburgh	Tetralin	88.0
10/17/90	NONE	Run 259 G V131B	93.6 ^c
11/6/90	Wyodak & Anderson	1-Methylnaphthalene	40.4
11/5/90	Wyodak & Anderson	Tetralin	65.9
10/30/90	NONE	Run 260 C V131B	93.5 ^c
5/26/92	NONE	Run 260 B V131B	93.9 ^c
3/22/91	Illinois No.6	1-Methylnaphthalene	77.3
3/20/91	Illinois No.6	Tetralin	75.6
3/26/91	NONE	Run 261 B V131B	95.6 ^c

- a) All tests run with heating profile 1c
- b) Conversion defined as weight percent THF solubles
- c) Corrected for the ash and IOM content of the recycle solvent

TABLE 3
OPERATING CONDITIONS AND PROCESS PERFORMANCE
UOP Bench-Scale Coprocessing Run 37, Period 49

Feed Coal	Illinois 6
Feed Petroleum	Lloydminster 950°F ⁺ Vacuum Resid
Feedstock Ratio (Petroleum/MAF Coal)	2
Temperature, °C (°F)	468 (874)
Pressure, psig	3000
Relative Space Velocity (WHSV)	1.0
Mo Catalyst Metal Conc., wt % MAF Feed	0.09
HPS Recycle/Feed Ratio	~5.0
Process Performance	
MAF Coal Conversion, %	91.9
Heptane Insolubles Conversion, %	86.3
510°C ⁺ Resid Conversion, %	84.2
Yields, wt % MAF Feed	
C ₁ x C ₄	12.15
C ₅ x 510°C	55.84
510°C ⁺ Tol. Solubles	26.11
Unconverted Coal	2.93
Total	97.03

Source: Reference 11

/ls

TABLE 4
FEEDSTOCK ANALYSIS
UOP Bench-Scale Coprocessing Run 37

Coal: Illinois No. 6, Burning Star Mine

Proximate, wt % As Received	
Volatile Matter	38.84
Fixed Carbon (by diff.)	45.80
Ash	11.28
Moisture	4.08
Ultimate, wt % MF	
Carbon	69.59(a)
Hydrogen	4.85
Nitrogen	1.40
Sulfur	3.03
Oxygen (by diff.)	9.37
Ash	11.76

Petroleum: Lloydminster 950°F+ Vacuum Resid

API Gravity	6.6
Specific Gravity	1.0246
Distillation	
IBP, °C	379
5 vol. %	455
10 vol. %	473
20 vol. %	509
EP, °C	512
Vol. % over at EP	22.0
Analysis, wt %	
Carbon	83.6(b)
Hydrogen	10.3
Nitrogen	0.59
Oxygen	0.54
Sulfur	4.77
Heptane Insolubles	13.56
Toluene Insolubles	0.01
Carbon Residue (MCRT)	17.39
Petroleum Ash	0.04
Ni, ppm	82
V, ppm	163
Fe, ppm	34

Source: Reference 9

(a) This value used for all carbon sourcing calculations.

(b) This value supplied by UOP. CONSOL's analysis (Table 5) was used for all carbon sourcing calculations.

/1s

TABLE 4
FEEDSTOCK ANALYSIS
UOP Bench-Scale Coprocessing Run 37

Coal: Illinois No. 6, Burning Star Mine

Proximate, wt % As Received	
Volatile Matter	38.84
Fixed Carbon (by diff.)	45.80
Ash	11.28
Moisture	4.08
Ultimate, wt % MF	
Carbon	69.59(a)
Hydrogen	4.85
Nitrogen	1.40
Sulfur	3.03
Oxygen (by diff.)	9.37
Ash	11.76

Petroleum: Lloydminster 950°F⁺ Vacuum Resid

API Gravity	6.6
Specific Gravity	1.0246
Distillation	
IBP, °C	379
5 vol. %	455
10 vol. %	473
20 vol. %	509
EP, °C	512
Vol. % over at EP	22.0
Analysis, wt %	
Carbon	83.6(b)
Hydrogen	10.3
Nitrogen	0.59
Oxygen	0.54
Sulfur	4.77
Heptane Insolubles	13.56
Toluene Insolubles	0.01
Carbon Residence (MCRT)	17.39
Petroleum Ash	0.04
Ni, ppm	82
V, ppm	163
Fe, ppm	34

Source: Reference 9

(a) This value used for all carbon sourcing calculations.

(b) This value supplied by UOP. CONSOL's analysis (Table 5) was used for all carbon sourcing calculations.

/ls

TABLE 5
ANALYSIS OF FEEDS AND PRODUCTS
UOP Bench-Scale Coprocessing Run 37, Period 49

Feeds	UOP No.	Yield, wt % MAF Feed	Carbon, wt % as determined (a)	$\delta^{13}\text{C}$, per mil
Lloydminster Resid	01-03547	-	84.16	-29.83 $\pm$ 0.01
Illinois No. 6 Coal	01-03543	-	78.86	-24.45 $\pm$ 0.02
Products				
C ₅ x 510°C (b)	6702-165A	55.84	85.22	-27.71 $\pm$ 0.01
510°C*, Toluene Sol.	6702-165B	26.11	87.69	-26.46 $\pm$ 0.05
Product Gas	6702-165D	12.15	79.75 (c)	-29.87 $\pm$ 0.16
Recycle Gas	6702-165C	-	-	NES (d)
Unconverted Coal + Missing (e)	-	5.90	-	-

- (a) Feed Coal analysis from UOP, all others from CONSOL.
(b) Combined debutanizer bottoms material and vacuum still overhead, Ref. 14.
(c) Calculated from UOP gas yield data, Ref. 10.
(d) Not enough sample for analysis.
(e) Missing fraction contains H₂O, H₂S, NH₃ and toluene insolubles.

TABLE 6
CARBON SOURCES, SELECTIVITIES AND CONVERSIONS
UOP Bench Coprocessing Run 37, Period 49

Fraction	Coal Carbon as % of Carbon	Conversion of Coal Carbon to Fraction	Conversion of Petroleum Carbon to Fraction	Selectivity for Coal Carbon Conversion
<u>Uncorrected</u>				
Product Gas	-0.7 $\pm$ 0.9	-0.3 $\pm$ 0.4	17.4 $\pm$ 1.5	-0.0 $\pm$ 0.0
C ₈ x 510°C	39.4 $\pm$ 0.3	71.3 $\pm$ 2.6	51.4 $\pm$ 1.2	1.2 $\pm$ 0.0
510°C (Tot. Soluble)	53.3 $\pm$ 1.0	46.5 $\pm$ 2.4	19.0 $\pm$ 0.8	1.7 $\pm$ 0.0
Total		117.5	87.8	
<u>Corrected</u>				
Product Gas	31.9 $\pm$ 0.9	11.8 $\pm$ 1.1	11.8 $\pm$ 1.0	1.0 $\pm$ 0.0
C ₈ x 510°C	35.1 $\pm$ 0.3	63.5 $\pm$ 2.3	55.1 $\pm$ 1.3	1.1 $\pm$ 0.0
510°C (Tot. Soluble)	49.0 $\pm$ 1.0	42.7 $\pm$ 2.2	20.8 $\pm$ 0.9	1.5 $\pm$ 0.0
Total		118.0	87.7	

/1s

TABLE 7

ANALYSIS OF 1988 BATCH OF OLD BEN NO. 1 MINE, INDIANA V COAL

	Sample Date			
	11/88 (a)	4/90 (b)	3/91 (c)	3/92 (c)
<u>Moisture, wt % as determined</u>	8.67	8.24	7.69	7.09
<u>Proximate, wt % dry basis</u>				
Volatile Matter	41.24	41.17	41.29	41.62
Fixed Carbon	49.53	49.69	49.65	49.43
Oxidized Ash	9.23	9.14	9.06	8.95
<u>Ultimate, wt % dry basis</u>				
Carbon	71.35	71.91	71.11	71.22
Hydrogen	5.04	4.98	4.99	5.00
Nitrogen	1.43	1.49	1.38	1.44
Oxygen (diff.)	9.03	8.70	9.57	9.61
Sulfur, Total	3.87	3.78	3.85	3.73
Pyritic	1.59	1.04	1.15	1.08
Sulfate	0.10	0.57	0.66	0.63
Organic (diff.)	2.18	2.17	2.04	2.02
Chlorine	0.05	N/A	0.04	0.05
Oxidized Ash	9.23	9.14	9.06	8.95
<u>Elemental, wt % oxidized ash</u>				
Na ₂ O	0.44		0.55	
K ₂ O	2.12		2.21	
CaO	4.78		4.86	
MgO	0.81		0.83	
Fe ₂ O ₃	26.94		27.32	
TiO ₂	0.89		0.92	
P ₂ O ₅	0.18		0.18	
SiO ₂	39.57		39.44	
Al ₂ O ₃	18.82		19.17	
SO ₃	3.12		3.30	
Unaccounted	2.33		1.22	
<u>Calorific Value, dry (HHV), Btu/lb</u>	13,154	12,799	12,788	12,745

(a) As-received sample

(b) Sample stored in plastic bucket

(c) Sample stored (from 4/90) in heat-sealed, nitrogen-purged, plastic bag.

/ls

TABLE 8
MICROAUTOCLAVE TEST MATRIX AND CONVERSIONS
Old Ben No. 1 Mine, Indiana V Coal

Test	Solvent		% MAF Conversion			
	Tetralin, wt %	1-Methyl- Naphthalene wt %	2/1/90	3/5/91	3/24/92	Avg.
KIN	0	100	55.0	57.2	-	56.1
KIN	5	95	63.9	65.3	64.3	64.5
KIN	10	90	68.1	69.6	-	68.9
KIN	25	75	75.8	74.9	73.6	74.8
KIN	50	50	76.1	77.1	78.3	77.2
KIN	100	0	71.7	72.4	71.8	72.0
EQ	0	100	48.9	49.6	-	49.3
EQ	5	95	60.7	60.3	60.0	60.3
EQ	10	90	68.4	68.3	-	68.4
EQ	25	75	63.9*	74.2	74.1	74.2
EQ	50	50	81.1	82.3	81.6	81.7
EQ	100	0	85.9	85.7	87.1	86.2
MOD-EQ	0	100	48.7	48.7	-	48.7
MOD-EQ	5	95	57.4	55.3	57.9	56.9
MOD-EQ	10	90	63.5	63.2	-	63.4
MOD-EQ	25	75	71.7	71.2	71.9	71.6
MOD-EQ	50	50	82.8	80.6	80.5	81.3
MOD-EQ	100	0	87.3	88.3	87.2	87.6

KIN = Kinetic Test: 12g solvent, 1.5g coal, 10 min, 750°F

EQ = Equilibrium Test: 10g solvent, 5g coal, 30 min, 740°F

MOD-EQ = Modified Equilibrium Test, 9g solvent, 6g coal, 30 min, 750°F

* This value excluded from average

TABLE 9
PARAMETRIC CALCULATION OF CONVERSION OF
850 x 1050°F RELATIVE TO 1050°F⁺

C_3/C_2 (Conversion, CONSOL/ Wilsonville)	C_1/C_2 (Conversion, 850 x 1050°F/ 1050°F ⁺)	C_3/C_2 (Conversion, CONSOL/ Wilsonville)	C_1/C_2 (Conversion, 850 x 1050°F/ 1050°F ⁺)
F=0.70		F=0.85	
0.50	-0.67	0.50	-2.33
0.60	-0.33	0.60	-1.67
0.70	0.00	0.70	-1.00
0.80	0.33	0.80	-0.33
0.90	0.67	0.90	0.33
1.00	1.00	1.00	1.00
1.10	1.33	1.10	1.67
1.20	1.67	1.20	2.33
F=0.75		F=0.90	
0.50	-1.00	0.50	-4.00
0.60	-0.60	0.60	-3.00
0.70	-0.20	0.70	-2.00
0.80	0.20	0.80	-1.00
0.90	0.60	0.90	0.00
1.00	1.00	1.00	1.00
1.10	1.40	1.10	2.00
1.20	1.80	1.20	3.00
F=0.80		F=0.95	
0.50	-1.50	0.50	-9.00
0.60	-1.00	0.60	-7.00
0.70	-0.50	0.70	-5.00
0.80	0.00	0.80	-3.00
0.90	0.50	0.90	-1.00
1.00	1.00	1.00	1.00
1.10	1.50	1.10	3.00
1.20	2.00	1.20	5.00

Note 1: F = Resid in Recycle Solvent, Wilsonville/CONSOL

Note 2: See text for definitions of values listed

TABLE 10

MODELING OF 1050°F⁺, 850 X 1050°F⁺, AND 850°F⁺ CONVERSION
IN WILSONVILLE RUNS 260 AND 262

Fraction	Flow In	Flow Out	Gain, (Out-In)	Conversion, %	Ratio, Conversion 850°F ⁺ / 1050°F ⁺	Ratio Conversion 850 x 1050°F/ 1050°F ⁺
Run 262 Example -- Actual F=0.86						
1050°F ⁺	86	54.78	-31.22	36.30		
850x1050°F	14	24.32	10.32	-73.70		-2.030
850°F ⁺	100	79.10	-20.90	20.90	0.576	
Run 260 Example -- Actual F=0.85						
1050°F ⁺	85	53.30	-31.70	37.30		
850x1050°F	15	11.50	-3.50	23.30		0.625
850°F ⁺	100	64.80	-35.20	35.20	0.944	
Run 262 Example -- F=0.80						
1050°F ⁺	80	50.96	-29.04	36.30		
850x1050°F	20	28.14	8.14	-40.70		-1.121
850°F ⁺	100	79.10	-20.90	20.90	0.576	
Run 260 Example -- F=0.80						
1050°F ⁺	80	50.16	-29.84	37.30		
850x1050°F	20	14.64	-5.36	26.80		0.718
850°F ⁺	100	64.80	-35.20	35.20	0.944	
Run 262 Example -- F=0.90						
1050°F ⁺	90	57.33	-32.67	36.30		
850x1050°F	10	21.77	11.77	-117.70		-3.242
850°F ⁺	100	79.10	-20.90	20.90	0.576	
Run 260 Example -- F=0.90						
1050°F ⁺	90	56.43	-33.57	37.30		
850x1050°F	10	8.37	-1.63	16.30		0.437
850°F ⁺	100	64.80	-35.20	35.20	0.944	

TABLE 11

CALCULATION OF 850 X 1050°F⁺ CONVERSIONS IN WILSONVILLE RUN 262

Period	A	B	C1	C2	D	E	F	Avg.	St. Dev.
Previous Results (Ref. 25) Used in Calculations									
THF-Sol. Resid in V-131B, wt%	42.4	51.3	50.2	47.6	50.3	54.2	52.2	49.7	3.8
IOM in V-131B, wt%	10.4	10.1	10.4	11.2	10.0	10.0	9.6	10.2	0.5
Ash in V-131B, wt%	10.7	9.0	11.9	11.9	10.3	10.5	10.6	10.7	1.0
Resid in PS, wt%	32.1	37.7	39.1	35.8	36.2	38.3	41.3	37.2	2.9
Cl in PS, wt%	19.3	18.7	18.6	19.2	19.6	20.0	20.1	19.4	0.6
Coal Conc. in Feed, wt% MF	29.6	29.7	29.9	29.5	29.7	29.8	30.0	29.7	0.2
Coal Ash Content, wt% MF	6.4	6.3	6.5	6.5	6.4	6.3	6.5	6.4	0.1
CONSOL Stage 1 Conversion, %	18.7	30.1	13.2	11.6	20.10	13.2	12.7	17.1	6.6
Wilsonville Stage 1 Conversion, %	29.7	28.9	23.8	20.9	24.7	21.4	22.9	24.6	3.5
CONSOL/Wils. Stage 1 Conversion Ratio	0.630	1.042	0.555	0.555	0.814	0.617	0.555	0.68	0.18
CONSOL Stage 2 Conversion, %	7.1	-14.3	14.7	7.4	-1.00	6.8	7.8	4.1	9.3
Wilsonville Stage 2 Conversion, %	11.8	11.8	19.7	19.6	16.5	18.8	9.8	15.4	4.2
CONSOL/Wils. Stage 2 Conversion Ratio	0.602	-1.212	0.746	0.378	-0.061	0.362	0.796	0.23	0.70
CONSOL Total System Conversion, %	24.5	20.1	26.0	18.1	19.3	19.1	19.5	20.9	3.0
Wilsonville Total System Conversion, %	38.0	37.3	38.8	36.4	37.1	36.2	30.5	36.3	2.7
CONSOL/Wils. Total System Conversion Ratio	0.644	0.539	0.669	0.498	0.520	0.528	0.641	0.58	0.07
Newly Obtained Results (This Report)									
F ₁ (Wt Fraction 1050°F ⁺ , Stage 1 Input)	0.87	0.86	0.85	0.84	0.85	0.84	0.89	0.86	0.02
Stage 1 Conv. of 850x1050°F, %	-54.1	37.6	-48.2	-37.1	-6.3	-30.6	-71.6	-30.0	36.1
F ₂ (Wt Fraction 1050°F ⁺ , Stage 2 Input)	0.75	0.88	0.75	0.75	0.80	0.76	0.79	0.78	0.05
Stage 2 Conv. of 850x1050°F, %	-7.1	-198.9	-0.2	-29.5	-72.2	-31.8	0.4	-48.5	71.0
F ₃ (Wt Fraction 1050°F ⁺ , Stage 2 Output)	0.71	0.68	0.70	0.65	0.66	0.66	0.77	0.69	0.04
Total System Conv. of 850x1050°F, %	-65.0	-86.7	-48.4	-77.5	-83.1	-72.1	-70.9	-72.0	12.7

Figure 1. Heating Profiles for Coal Preheater Simulation Studies.

Figure 2. UOP Coprocessing Bench-Scale Unit.
Source: Reference 33.

Figure 3. Coal Carbon to Total Carbon Ratio Plotted vs Product Fraction, UOP Coprocessing Run 37, Period 49.

Figure 4. Conversion of Coal Carbon Plotted vs Product Fraction, UOP Coprocessing Run 37, Period 49.

Figure 5. Corrected Conversions of Coal and Petroleum Carbon Plotted vs Product Fraction, UOP Coprocessing Run 37, Period 49.

Figure 6. Comparison of Coal Carbon Conversions in UOP Coprocessing Run 37 With Those in UOP Run 26.

APPENDIX 1

CORRECTIONS TO RESID CONVERSIONS AND KINETIC CONSTANTS FOR RUN 260

(This Appendix replaces page numbers 17-25, 54-56, and 72-77
in DOE/PC 89883-29, November 1991)

Resid conversions and kinetic constants previously reported (Report No. DOE/PC 8983-29) for Run 260 were incorrect and are corrected here. The original report cannot be revised because it was released some time ago. In order to disseminate the corrections, all pages that contain revisions are included here. Only those pages with corrections are included. Table, figure and reference numbers refer to the original document in which the data appeared; however, pages are numbered to be in sequence with this report.

850°F⁺ RESID CONVERSION AND KINETICS

CONSOL analyses of the process oils were used to calculate conversions (forced ash balance method) of the 850°F⁺ material and its various components in each reactor stage (Table 21). The 850°F⁺ conversions then were used to calculate conversion rate constants and conversion activities (Table 22). The conversion and kinetic calculations were made as described elsewhere.⁵ Briefly, the following equations are used in the calculations:

$$C = \text{Conversion} = \left\{ \frac{850^{\circ}\text{F}^{+} \text{ In/Ash In} - 850^{\circ}\text{F}^{+} \text{ Out/Ash Out}}{850^{\circ}\text{F}^{+} \text{ In/Ash In}} \right\} \times 100\%$$

$$K = \text{Rate Constant} = \text{WHSV} \left(\frac{C}{100 - C} \right)$$

$$A = \text{Conversion Activity} = K e^{E_{\text{act}}/RT},$$

where E_{act} is assumed to be 23,500 cal/mol, as has been used in the past at CONSOL. In the first equation and in the figures and discussion to follow, 850°F⁺ refers to the organic portion of the distillation bottoms, consisting of IOM and THF-soluble resid. The thermal stage WHSV used is the same as the catalytic stage when reactor volumes are equal. The catalytic stage WHSV is used for the thermal stage because the absolute thermal space velocities are proprietary and the only values provided are on a relative basis. In Run 260, however, a correction was applied to account for differing volumes in the catalytic and thermal reactors. The following correction was applied to the thermal space velocities.

$$\text{WHSV (thermal stage)} = \text{WHSV (catalytic stage)} \times \left(\frac{75\% \text{ volume}}{100\% \text{ volume}} \right)$$

Conversions of 850°F⁺ resid and its components calculated for each reactor stage and the total system are given in Table 21. Figure 14 shows the first stage and total 850°F⁺ and coal + IOM conversions for Run 260. Several interesting observations can be made. First, the first-stage conversion of UC (Coal + IOM) was much lower in catalytic/thermal operation than in thermal/catalytic operation. The catalytic second-stage (periods A through C) contributed almost

nothing to UC conversion, whereas the thermal second-stage (periods D through F) contributed a substantial amount. However the total UC conversion was slightly lower in periods D-F than in periods A-C. The plant personnel were unable to raise the thermal reactor temperature high enough during periods D-F to achieve higher coal conversion. These results indicate that the thermal effect on coal conversion was significant. Overall 850°F⁺ THF-soluble resid conversions were near zero throughout the run (Figure 15), the average being not (statistically) significantly different from zero. This merely indicates that there is little net make or net loss of THF-soluble resid in the process. It appears that the first-stage conversion of soluble 850°F⁺ resid was improved in periods D-F over periods A-C. The negative conversions in most periods represent net yields of 850°F⁺ soluble resid. When the catalytic stage was the second stage (periods A-C), second-stage 850°F⁺ THF-soluble resid conversion was consistently positive, ranging from 8 to 20%. Except for period F, the second-stage conversion of 850°F⁺ resid was higher than that of the first stage. The conversion of the oil fraction (hexane solubles) was small and invariant for periods B through D (Figure 16). In periods E and F, total conversion of oils was higher. First-stage oil conversions calculated by CONSOL for period F were quite high; those for second-stage oil conversion were low. Perhaps some problem existed with the analyses or the samples. The conversions of asphaltenes (Figure 17) and preasphaltenes (Figure 18) showed trends which were similar to each other. Catalytic stage conversions of these components were consistently higher in thermal/catalytic periods (A through C) relative to catalytic/thermal periods (D through F). Thermal stage conversions of these components were consistently higher in catalytic/thermal periods (D through F) than in thermal/catalytic periods (A through C). Viewed another way, the conversions of these components in the second stage were consistently greater than or equivalent to their conversions in the first stage. In Table 22, the 850°F⁺ resid + UC conversions obtained by CONSOL are compared with those obtained by Wilsonville. The associated kinetic rate constants and conversion activities obtained by CONSOL also are given. The conversions obtained by CONSOL are different from those obtained by Wilsonville because of a difference in laboratory distillation conditions. CONSOL uses an 850°F atmospheric equivalent distillation endpoint, whereas Wilsonville uses a 1050°F atmospheric equivalent endpoint. Therefore, CONSOL calculates conversion of 850°F⁺ material, but Wilsonville calculates

conversion of 1050°F⁺ material. The effect of this difference on measured conversions has been discussed elsewhere.⁵

The average ratios of CONSOL conversions to Wilsonville conversions are compared below.

RATIO CONSOL/WILSONVILLE CONVERSIONS OF RESID + UC

Period	First Stage	Second Stage	Total
260C	0.90 (thermal)	0.68 (catalytic)	0.85
260D-F	0.76 $\pm$ 0.17 (catalytic)	1.79 $\pm$ 0.72 (thermal)	1.00 $\pm$ 0.09
258 Average (A, G, J omitted)	0.89 $\pm$ 0.12	0.78 $\pm$ 0.33	0.87 $\pm$ 0.11
Average Runs 250-259	0.98 $\pm$ 0.10	0.85 $\pm$ 0.16	0.94 $\pm$ 0.06

Relative to the global averages (Runs 250-259), all the 260C ratios were slightly low. Relative to the Run 258 averages, the 260C second-stage ratio was slightly low; the 260C and Run 258 first-stage and total ratios were identical. In contrast, the ratios for 260D-F were low for the first stage, quite high for the second stage and slightly high for the total. A ratio higher than one indicates that the percentage conversion of 850 x 1050°F material is greater than the percentage conversion of 1050°F⁺ material. A ratio lower than one indicates that the percentage conversion of 850 x 1050°F material is less than that of the 1050°F⁺ material. The ratio for the thermal reactor in 260D-F is quite high, indicating high 850 x 1050°F conversion or, alternatively, low conversion of 1050°F⁺ (including unconverted coal). Note that a thermal second stage is atypical at Wilsonville. Also note that the thermal stage temperature was quite low during periods D through F. The ratio of 1.00 $\pm$ 0.09 for the total conversion for 260 D-F is slightly higher than the averages from the prior runs (Runs 250 to 259). Perhaps this results from thermal severity so low in 260 D-F that the 1050°F⁺ conversion (including coal conversion) was relatively low. Evidently, the catalytic-stage conversion of 850 x 1050°F⁺ material was relatively low during periods D-F.

The kinetic rate constants and conversion activities for each reactor stage are given in Table 22. Activities (i.e., pre-exponential factors) for resid + UC conversion in the first and second stages are shown in Figure 19. The first stage had activities consistently greater than or equivalent to the second stage. Whereas, the resid + UC conversion activity of the thermal reactor was not greatly affected by reactor order (first-stage in periods A-C vs second stage in

periods D-F), operation of the catalytic reactor as the first reactor significantly increased its resid + UC conversion activity (second-stage in periods A-C vs first-stage in periods D-F). The first reactor provides most of the resid + UC conversion, whether it be thermal or catalytic. The conversion activity of the catalytic reactor is higher in catalytic/ thermal operation because, in addition to converting resid (its usual function), it is also converting coal, a function which is not greatly demanded of it in thermal/catalytic operation. Overall, the conversion activity of the catalytic stage in periods A-C was poor (about 1×10^{-7}). Its conversion activity during periods D-F was much higher (2×10^{-7} to 4×10^{-7}) and was more typical of past catalytic stage performance in past runs at Wilsonville.⁵

EFFECT OF CATALYTIC/THERMAL VS THERMAL/CATALYTIC REACTOR CONFIGURATIONS

In periods D through F, the sequence of reactors was reversed relative to that used in periods A through C. The configuration for D through F was catalytic/thermal, and nominally low/high temperature. However, in periods D through F, the plant could not be operated to achieve the higher thermal-stage temperatures desired. In fact, in period D the thermal (second) stage was about 15°F lower than the catalytic stage. A comparison of oil properties from period C (thermal/catalytic) with those from period D (catalytic/thermal) shows the effects of reactor configuration, although the comparison is partly confounded by the difference in temperatures (825/790°F in period C, 790/774°F in period D).

Wilsonville personnel found that product yields in period D were not bad, in spite of a coal conversion of only 88.5 wt % MAF, down from 94.2 wt % MAF in period C. Distillate (C_4+) and resid yields were 54.1 and 7.5 wt % in period C, respectively, and were 59.8 and 0.3 wt % in period D. The yield of C_4+ naphtha was 11.6 wt % in period D, but only 4.4 wt % in period C. The yield of C_1-C_3 gas was 11.2 wt % in period C, but only 5.6 wt % in period D. So, in addition to a slightly higher distillate yield in period D, the yield structure favored increased production of naphtha and lowered gas production. Thermal reactor temperature was increased by increasing the coal feed rate (to increase the heat input from the exothermic hydrogenation reaction); however, the distillate yield decreased in response. The period D results sparked an interest in the catalytic/thermal configuration, with the hope that in a future run the thermal

reactor can be run at higher temperature for increased coal conversion and distillate yield.

Before proceeding further with a discussion of oil properties, it deserves mention here that the oil samples from period 260D were found to be contaminated with Dowtherm A heat transfer fluid. The amount of contamination was found to be up to about 1.7 wt %, with contaminant concentration decreasing in the order V-131B > interstage > V-1067. More detail on the Dowtherm A contamination can be found in a separate section of this report.

Relative to period C, the whole samples from period D contained more IOM and less ash (Tables 4 through 6 and Figures 3 through 5). This reflects the lower coal conversion obtained in period D and later. Figure 6 shows the large increase in IOM in the interstage sample from period C to D, resulting from much lower first-stage coal conversion with the catalytic first stage in 260D. The V-131B and interstage whole samples in period D also showed somewhat higher concentrations of 850°F distillate and lower concentrations of the resid than in period C. This resulted in part from the use of a lower resid concentration in Wilsonville's recycle solvent blend in period D (Table 2), and contamination by Dowtherm A, which would be included in the distillate.

THF-soluble resids (Tables 7 through 9, Figures 6 through 8) from period D contained relatively more oils (hexane solubles) and less preasphaltenes, than did those from period C (especially the V-131B and V-1067 samples). With one exception, the proton aromaticity (Figures 9 through 11) of distillates (Tables 13 through 15) and THF-soluble resids (Tables 16 through 18) dropped significantly from period C to period D. The exception was the V-131B distillate, which contained the most Dowtherm A (period D) and showed no aromaticity change from period C to D. Relatively high uncondensed aromatic hydrogen and total aromatic hydrogen contents for the V-131B distillate from period D (Table 13 and Figure 9), in the absence of other identifiable factors, indicate that the Dowtherm A contamination is responsible for this exceptional sample. Dowtherm A fluid is a mixture of diphenyl ether and biphenyl and all of its hydrogen is classified as uncondensed aromatic. In the distillate samples, an increase in paraffinic hydrogen content accompanied the aromaticity decrease from period C to period D (Figures 9-11). Also evident is a corresponding

increase in hydroaromatic protons in the interstage and V-1067 distillates (Figures 10 and 11). This is most prominent in the interstage distillate and results from changing from a thermal first stage to a catalytic first stage. The catalytic first stage will produce hydroaromatics, whereas the thermal first stage will deplete them. Thus, a rather large increase is seen here.

The interstage distillate also shows a very large (-0.9 meq/g sample) decrease in phenolic -OH concentrations from period C to period D, as would be (qualitatively) expected (Figure 12, Table 19). A small decrease in the phenolic -OH concentration of the interstage resid also occurred. Curiously, the V-131B and V-1067 resids show a small increase in phenolic -OH concentration from period C to period D. This is consistent with the increased preasphaltene and decreased oil concentrations in the resids. However, the resid aromaticity in these samples decreased from period C to period D. It should be noted that the phenolic -OH, preasphaltene and oil concentrations are on a wt % sample basis, whereas the aromaticity units are % of protons. The hydrogen content of the samples must be accounted for in quantitation on a weight basis. Wilsonville data for several samples indicate that they had a higher hydrogen content in period D than in period C, consistent with CONSOL's usual interpretation that lower aromaticity indicates more hydrogenation. If we assume that the preasphaltene and phenolic -OH concentration in the resid samples represent functional groups in some general sense, then it is reasonable to conclude that the resids were more hydrogenated, but less defunctionalized in period D than in period C.

Distillate donor solvent quality, as determined by microautoclave assay, decreased by several percent in each sample type from period C to period D (Table 20 and Figure 13). Whole-sample donor solvent qualities of V-131B and V-1067 oils also decreased considerably from periods C and D. The interstage whole sample increased in solvent quality from period C to period D. It is interesting that the corresponding distillate decreased in solvent quality from C to D, instead of increasing.

COMPARISON OF RUN 260 WITH RUN 258

Differences in numerous run conditions preclude a good comparison of performance during Run 260 with that of prior Wilsonville runs. In spite of the differences, it is instructive to perform such an exercise, for two important reasons. First, it is likely that something useful can be learned from such a comparison. Second, it links the past with the future by referencing historical data. In some instances, it provides a yardstick by which progress can be measured.

Two periods from Run 258 were selected for comparison with period C of Run 260 (Table 23). Run 258 (periods H through M) was the only prior run in which Black Thunder coal was the feedstock. Period 258H had the same coal feed rate as in 260C and it had the lowest first-stage temperature of any from periods 258H to 258M. Period 258M had the same equilibrium catalyst age as in 260C, but higher first-stage temperature and coal feed rate than in 260C. Other major differences in reactor volumes, interstage separation and distillation operation existed between Runs 260 and 258. However, the same supported catalyst, Shell 324, was used in both runs.

Selected yield and performance data reported by Wilsonville for periods 260C, 258H and 258M are shown in Table 24. Yields of water and C_1 - C_3 gas were higher in 260C, but the other heterogases were lower in 260C, relative to 258H and M. Distillate yield in 260C was similar to that in the other two periods, but the distillate produced in 258H and 258M was much lighter, containing more naphtha and mid-distillate than that from 260C. Resid yield was higher, but ROSE-SR bottoms yield was lower in 260C relative to the other periods. Coal conversion and resid conversions were higher in 260C than in the comparison periods.

Table 25 gives process oil characteristics, 850°F⁺ conversions, and kinetic constants for the comparison periods. Properties for V-131B and V-1067 samples are grouped together as feed and product samples, because they are very similar. Calculated solvent quality indices (SQIs) from 260C distillate oils were similar to those from the Run 258 periods. The feed and product distillate SQI values of the Run 260C samples were, however, at the low end of the range of the Run 258 periods. This may result, in part, from the relatively high paraffinicity of the 260C distillates (all samples). The feed and product distillates from 260C were

intermediate in hydrogen aromaticity relative to the comparison Run 258 distillates, but the interstage distillate and all the resids from 260C were lower in aromaticity than the comparison samples. The low aromaticity and high paraffinicity of those samples indicates that they are better hydrogenated than their Run 258 counterparts. The distillate samples from 260C were similar to Run 258 samples in phenolic -OH concentration: the feed and product distillate values from 260C were intermediate between the Run 258 values; and the interstage distillate values from 260C were slightly higher than the Run 258 values. Feed, product, and interstage resid samples from 260C were all significantly lower in phenolic -OH than corresponding Run 258 samples. The resids produced in period 260C were lower in preasphaltenes and higher in oils than the 258H and 258M resids. Asphaltenes in the period 260C resids ranged from low (feed and product samples) to intermediate (interstage sample), relative to the Run 258 periods. Overall, the resids produced in period 260C were evidently more upgraded than those from the comparison periods. The period 260C resids were more extensively hydrogenated and defunctionalized relative to resids from periods 258H and 258M. In a product quality sense, the 260C resids were higher in quality than those from the periods in Run 258. A simple explanation is the significantly lower space velocity and higher hydrogen consumption in 260C relative to the Run 258 periods. The impact of other run conditions on resid properties is not known, however. The distillate samples from 260C were generally similar or had properties intermediate to those from 258H and 258M. Therefore, the distillates and resids behave differently in the comparison of Run 260C with Runs 258H and 258M. It is possible that other run conditions in addition to space velocity had more effect in determining the distillate properties.

CONSOL's calculated first-stage and total 850°F⁺ resid + UC conversions were higher in 260C were higher than in 258M, but comparable to those in 258H. These results are in fair agreement with those of Wilsonville, where 1050°F⁺ conversion is measured. CONSOL obtained a second-stage 850°F⁺ conversion for 260C which was slightly lower than in 258H and 258M, whereas Wilsonville reported it to be slightly higher for 260C relative to the other two periods. The thermal reactor space velocity was particularly low in 260C relative to 258H and 258M, because of the reactor volume in use. The relative thermal/catalytic space velocities also were different in Run 260, because different reactor volumes were used in the thermal and catalytic stages. The kinetic rate constants for first- and

second-stage 850°F⁺ conversion were lower in 260C than in the comparison periods. The first-stage activity for 850°F⁺ conversion in 260C was equal to that for 258M and somewhat lower than the 258H value, but the second-stage 850°F⁺ conversion activity was relatively low in 260C. It is not clear which run conditions might account for these observations. However, kinetic rate constants are directly dependent on space velocity, which was much lower in 260C than in 258H and 258M. It is probable that the kinetic model used here and at Wilsonville is not accurate. Thus, the calculated conversion activities and rate constants may be low because the activation energy is inappropriate, the assumption of first-order kinetics is incorrect, or result from other mathematical artifacts or inadequacies.

TABLE 21
CONVERSION OF RESID COMPONENTS
Wilsonville Run 260

Period	Conversion, %					
	850°F ⁺ (a)	Oils	Asphal- tenes	Preasphal- tenes	Coal + IOM	THF-Soluble Resid
First Stage						
A*	29.6	-15.6	-25.8	-93.2	87.4	-28.8
B*	28.8	-7.1	-15.6	-75.9	79.6	-16.1
C	29.9	0.1	-24.8	-83.8	80.1	-12.5
D	21.6	-8.6	-6.3	-27.3	54.2	-10.8
E	16.1	-3.2	-16.3	-33.2	45.1	-11.5
F	23.2	21.4	-3.4	-41.4	44.7	4.7
All Periods: Avg ±S.D.	24.8 ±5.5	-2.2 ±12.7	-15.4 ±9.2	-59.1 ±28.5	65.2 ±19.3	-12.5 ±10.7
Periods A-C: Avg ±S.D.	29.4 ±0.6	-7.5 ±7.9	-22.1 ±5.6	-84.3 ±8.7	82.4 ±4.4	-19.1 ±8.6
Periods D-F: Avg ±S.D.	20.3 ±3.7	3.2 ±16.0	-8.7 ±6.8	-33.9 ±7.1	48.0 ±5.4	-5.9 ±9.1
Second Stage						
A*	12.8	13.8	21.6	33.3	-57.7	19.7
B*	9.2	3.3	12.2	22.8	14.1	8.4
C	11.3	0.8	24.3	32.2	13.8	11.0
D	14.4	5.6	0.5	-0.6	41.2	3.3
E	23.6	11.5	10.0	11.6	50.3	11.1
F	9.8	-21.8	-1.6	12.7	44.7	-7.5
All Periods: Avg ±S.D.	13.5 ±5.3	2.2 ±12.7	11.2 ±10.6	18.6 ±13.2	17.7 ±40.1	7.7 ±9.1
Periods A-C: Avg ±S.D.	11.1 ±1.8	6.0 ±6.9	19.4 ±6.4	29.4 ±5.8	-9.9 ±41.4	13.0 ±5.9
Periods D-F: Avg ±S.D.	15.9 ±7.0	-1.6 ±17.7	3.0 ±6.2	7.9 ±7.4	45.4 ±4.6	2.3 ±9.4
Total						
A*	38.6	0.3	1.3	-28.9	80.2	-3.4
B*	35.3	-3.6	-1.5	-35.8	82.5	-6.4
C	37.8	0.9	5.6	-24.6	82.8	-0.1
D	32.9	-2.5	-5.8	-28.1	73.1	-7.1
E	35.9	8.6	-4.7	-17.8	72.7	0.9
F	30.7	4.3	-5.1	-23.5	69.4	-2.5
All Periods: Avg ±S.D.	35.2 ±3.0	1.3 ±4.5	-1.7 ±4.5	-26.4 ±6.1	76.8 ±5.8	-3.1 ±3.2
Periods A-C: Avg ±S.D.	37.2 ±1.7	-0.8 ±2.5	1.8 ±3.6	-29.8 ±5.7	81.8 ±1.4	-3.3 ±3.1
Periods D-F: Avg ±S.D.	33.2 ±2.6	3.5 ±5.6	-5.2 ±0.6	-23.1 ±5.1	71.7 ±2.0	-2.9 ±4.0

*Unstable

(a) Includes THF-soluble resid and IOM.

/ls

TABLE 22

850°F⁺ CONVERSION AND KINETICS
Wilsonville Run 260

Period	First Stage							A, 10 ⁷ (a)
	Temp., °F	WHSV (a)	Cat. Age (b)	Conversion (c)			K (a)	
				Consol (d)	W'ville (e)	Ratio C/W (f)		
A*	825	2.9	-	29.6	29.1	1.017	1.23	1.93
B*	840	2.5	-	28.8	33.2	0.867	1.00	1.30
C	825	2.3	-	29.9	33.3	0.898	0.99	1.56
D	790	2.8	1415	21.6	29.1	0.742	0.77	1.93
E	789	4.0	1461	16.1	27.0	0.596	0.77	1.95
F	774	4.0	1497	23.2	24.8	0.935	1.21	3.77
Averages for Stage 1:								
Average Periods A-C				29.4	31.9	0.93	1.07	1.60
± Std. Dev.				0.6	2.4	0.08	0.13	0.32
Average Periods D-F				20.3	27.0	0.76	0.92	2.55
± Std. Dev.				3.7	2.2	0.17	0.25	1.06
Average All Periods				24.9	29.4	0.84	0.99	2.07
± Std. Dev.				5.5	3.4	0.15	0.20	0.87
Average All Periods (A, B Omitted)				22.7	28.6	0.79	0.93	2.30
± Std. Dev.				5.7	3.6	0.16	0.21	1.00

Period	Second Stage								Total Conversion		
	Temp., °F	WHSV (a)	Cat. Age (b)	Conversion (c)			K (a)	A, 10 ⁷ (a)	Consol (d)	W'ville (e)	Ratio C/W (f)
				Consol (d)	W'ville (e)	Ratio C/W (f)					
A*	790	3.9	1330	12.8	12.4	1.032	1.43	1.43	38.6	37.9	1.019
B*	790	3.3	1362	9.2	11.9	0.773	0.84	0.84	35.4	41.1	0.859
C	790	3.1	1368	11.3	16.7	0.677	0.99	0.99	37.8	44.4	0.851
D	774	2.1	-	14.4	10.5	1.371	1.10	1.10	32.9	36.5	0.900
E	797	3.0	-	23.6	9.0	2.622	2.11	2.11	35.9	33.6	1.069
F	804	3.0	-	9.8	7.1	1.380	0.68	0.68	30.7	30.1	1.019
Averages for Stage 2 and Total:											
Average Periods A-C				11.1	13.7	0.83	0.43	1.09	37.3	41.2	0.91
± Std. Dev.				1.8	2.6	0.18	0.12	0.31	1.7	3.3	0.09
Average Periods D-F				15.9	8.9	1.79	0.54	1.30	33.2	33.4	1.00
± Std. Dev.				7.0	1.7	0.72	0.34	0.74	2.6	3.2	0.09
Average All Periods				13.5	11.3	1.31	0.48	1.19	35.2	37.3	0.95
± Std. Dev.				5.3	3.3	0.71	0.24	0.52	3.0	5.1	0.09
Average All Periods (A, B Omitted)				14.8	10.8	1.51	0.50	1.22	34.3	36.2	0.96
± Std. Dev.				6.2	4.2	0.81	0.29	0.62	3.1	6.1	0.10

*Unstable

- (a) Basis was lb total feed/hr/lb catalyst. K and A were calculated from Consol conversion data. See text for discussion of thermal stage WHSV.
- (b) lb coal + resid + UC/lb catalyst
- (c) First stage and total conversion: wt % resid + MAF coal + UC fed to first stage
 Second stage conversion: wt % resid + UC fed to second stage
- (d) 850°F distillation end point, atm equivalent
- (e) 1050°F distillation end point, atm equivalent
- (f) Ratio of Consol conversion to Wilsonville conversion

/ls

TABLE 25
COMPARISON OF WILSONVILLE RUNS 260 AND 258
PROCESS OIL CHARACTERISTICS, CONVERSIONS AND KINETIC CONSTANTS

Period	260C	258H	258M
Source (Reference)	This Report	6	6
<u>SQI (a)</u>			
Feed & Product Distillate	74.8-77.1	76.0-79.6	80.8-81.3
Interstage Distillate	74.9	70.8	74.4
<u>Hydrogen Aromaticity, % of Protons (b)</u>			
Feed & Product Distillate	19.4-19.6	17.4-19.9	19.9-21.0
Interstage Distillate	20.9	23.0	26.1
Feed & Product Resid	35.9-36.1	37.1-40.8	40.1
Interstage Resid	38.4	40.3	44.9
<u>Paraffinic Hydrogen, % of Protons (c)</u>			
Feed & Product Distillate	40.5-43.2	38.2-42.6	36.2-37.2
Interstage Distillate	40.3	40.7	35.3
<u>Phenolic -OH Concentration, meq OH/g Sample</u>			
Feed & Product Distillate	0.42-0.45	0.57	0.35-0.39
Interstage Distillate	1.20	1.13	1.00
Feed & Product Resid	0.65-0.67	0.93-0.98	0.78-0.80
Interstage Resid	0.94	1.18	1.11
<u>Feed & Product Resid Components, wt %</u>			
Oils	68.3-69.0	59.5-60.2	56.3-58.0
Asphaltenes	21.5-22.8	22.6-23.9	26.1-26.7
Preasphaltenes	8.2-10.2	15.9-17.9	15.9-17.0
<u>Interstage Resid Components, wt %</u>			
Oils	61.3	55.6	55.8
Asphaltenes	25.3	22.8	26.9
Preasphaltenes	13.4	21.5	17.3
<u>850°F⁺ Conversion, %</u>			
First Stage	29.9	27.9	20.6
Second Stage	11.3	15.3	13.5
Total	37.8	38.9	31.3
<u>Kinetic Rate Constants for 850°F⁺</u>			
<u>Conversion (d)</u>			
First Stage	0.99	1.74	1.40
Second Stage	0.39	0.81	0.84
<u>Activities for 850°F⁺ Conversion, 10⁷ (d)</u>			
First Stage	1.56	2.23	1.57
Second Stage	0.99	2.03	2.16

- (a) SQI = Solvent Quality Index, predicted microautoclave donor solvent quality based on proton distribution of each distillate sample.
(b) Sum of condensed and uncondensed aromatic protons.
(c) Sum of alkyl beta and gamma (aliphatic) protons.
(d) lb total feed/hr/lb catalyst.

/ls

Figure 14. First-Stage and Total Conversions of THF-Soluble 850°F⁺ Resid and Coal + IOM for Wilsonville Run 260.

Figure 15. THF-Soluble 850°F+ Conversions for Wilsonville Run 260.

Figure 16. Conversion of Oils (Hexane Solubles) in Wilsonville Run 260.

Figure 17. Conversion of Asphaltenes in Wilsonville Run 260.

Figure 18. Conversion of Preasphaltenes in Wilsonville Run 260.

Figure 19. Resid and UC Conversion Activity in Wilsonville Run 260.

APPENDIX 2

THE APPLICATION OF FT-IR METHODS TO THE CHARACTERIZATION OF COAL LIQUEFACTION PROCESS STREAMS

Hsisheng Teng, Michael A. Serio, Rosemary Bassilakis,
Kim S. Knight, Stephen C. Bates and Peter R. Solomon

Advanced Fuel Research, Inc.
87 Church Street
East Hartford, CT06108

Keywords: Coal Liquefaction, FT-IR, Fiber Optics

INTRODUCTION

Fourier transform infrared spectroscopy (FT-IR) is one of the most versatile analytical techniques available for the study of fossil fuel structure and reaction chemistry [1-5]. Among its advantages are: 1) its ability to study feedstocks and reaction products as solids, liquids and gases, since almost all have characteristic absorptions in the infrared; 2) its high sensitivity, allowing the study of strongly absorbing materials such as coal and char, and the use of techniques such as attenuated total reflectance (ATR) or photoacoustic spectroscopy; 3) its speed, allowing the possibility of following chemical reactions on-line. Because of these advantages, FT-IR spectroscopy has achieved increasing use in fuel science.

The objective of this work was to evaluate the use of two FT-IR methods for characterization of distillation resids from coal liquefaction process streams. The first method is quantitative FT-IR analysis of samples pressed into KBr pellets to determine functional group concentrations. The second method is Thermogravimetric Analysis with FT-IR analysis of evolved products (TG-FTIR). In addition, the application of on-line FT-IR Fiber Optic (F-O) ATR analysis to coal liquefaction processes is addressed.

EXPERIMENTAL

Characterization of Coal Liquefaction Products

The samples used in this study were supplied by Consolidation Coal Company (CONSOL), PA, along with chemical and structural information obtained with various techniques. These samples included: 1) Three feed coals (Wyodak, Illinois, and Pittsburgh); 2) Nine whole resid samples produced by distillation of process oils generated from the three different feed coals and obtained from three different sampling points (interstage, recycle, second stage) during liquefaction runs at the Wilsonville (AL) facility; 3) Nine THF soluble portions of the above whole resids; 4) Four additional solids free resids obtained during a catalyst aging study at the HRI (NJ) facility; 5) A single whole process oil for Pittsburgh coal obtained from the Wilsonville facility. These samples were analyzed by both FT-IR and TG-FTIR.

FT-IR Analysis - The samples are analyzed as KBr pellets in a Nicolet 7199 FT-IR. For quantitative analysis of such spectra, a curve analysis program is employed to synthesize the IR spectra [1-3]. The program uses a basic set of adsorption peaks identified with various functional groups. The synthesis routine can produce a spectrum which matches the actual spectrum well. The correction of a whole resid spectrum for scattering and minerals is demonstrated in Figure 1.

TG-FTIR Analysis - The apparatus consists of a sample suspended from a balance in a gas stream within a furnace. As the sample is heated in helium, the evolving volatile products are carried out of the furnace directly into a gas cell for analysis by FT-IR [5]. The results of a typical resid pyrolysis experiment are shown in Figure 2. The system continuously monitors the time-dependent evolution of the gases and tars, and weight of the non-volatile material. At the end of the pyrolysis experiment, oxygen is introduced to burn the residue to obtain the ash content of the sample.

In-Situ FT-IR/F-O/ATR Measurements

A coal liquefaction test cell which incorporates a FT-IR/F-O system is shown in Figure 3. The reactor is made of 3/8" stainless tubing and Swagelok tube fittings. This reactor can withstand a pressure as high as 3800 psig at 400 °C. A sapphire fiber, which is 15" (38 cm) in length and 0.25 mm in diameter, is used as an ATR sensor in the reactor. A zirconium fluoride fiber cable is used as a transmitting fiber to link between the sensor fiber and the FT-IR spectrometer and detector.

Liquefaction of demineralized Zap lignite was performed in the test cell, with 1 g of coal sample mixed with 6 ml of tetralin. The experiment was performed by heating the reactor from room temperature to 400 °C at 20 °C/min, and sustaining the final temperature for 40 minutes. The F-O/ATR spectra of the tetralin/coal liquid mixtures in the reactor were taken at regular intervals. Tetralin spectra at the relevant temperatures were taken and compared with those from coal liquefaction experiments.

RESULTS AND DISCUSSION

Characterization of Coal Liquefaction Products

Characterization of the samples using the FT-IR and TG-FTIR methods provides a good understanding of the average chemical structure of products from the various stages of a coal liquefaction process. In order to demonstrate the reliability of these two FT-IR techniques, correlation and comparison of the results in this study with those supplied by CONSOL using different methods are described below.

FT-IR Analysis

Aromatic and Aliphatic Hydrogen (Proton) Distribution - The comparison of the aromatic to total hydrogen ratio (H_{ar}/H_{total}) using FT-IR analysis with the aromatic proton fraction from the 1H -NMR method for the THF soluble samples is shown in Figure 4a. Figure 4b shows the comparison of the aliphatic hydrogens for the same set of samples. The results show that the FT-IR H_{ar}/H_{total} agrees reasonably well with the fraction of aromatic protons derived from the 1H -NMR method. The same is true of the aliphatic hydrogen. These figures contain two lines. The solid line is the mean value of the ratios between the two sets of measurements. The dashed line is a parity line. Figures 4a and 4b provide a relation between the results obtained by these two methods:

$$\begin{aligned} H_{ar}/H_{total} (\%, \text{ THF sol.}), \text{ FT-IR} &= 0.77 [\text{Aromatic Proton Fraction } (\% \text{ THF sol.}), ^1H\text{-NMR}] \\ H_{al}/H_{total} (\%, \text{ THF sol.}), \text{ FT-IR} &= 1.1 [\text{Aliphatic Proton Fraction } (\% \text{ THF sol.}), ^1H\text{-NMR}] \end{aligned}$$

Hydroxyl Groups - Both this study and CONSOL used an FT-IR method to determine the

concentration of hydroxyl groups in the samples. CONSOL used the -OH stretch band found between 3200 and 3400 cm^{-1} to determine the phenolic -OH concentration from measurements on THF-soluble portions of the samples. In this study, the concentration of hydroxyl groups was determined using the 3200 cm^{-1} O-H stretch to avoid the interference from the KBr- H_2O band which peaks at 3400 cm^{-1} [1]. The hydroxyl results obtained in this study and by CONSOL are in good agreement, considering the differences in sample preparation and the quantitative analysis routines. The relation between them is:

$$\text{-OH (wt\%, THF sol.)}, \text{FT-IR} = 0.90 [\text{Phenolic-OH (wt\%, THF sol.)}, \text{FT-IR} | \text{CONSOL}]$$

Oxygen Analysis - In general, most of the oxygen atoms in coal and coal products are contained in hydroxyl, ether, and carbonyl functional groups. In this study, oxygen contents of the samples were determined through quantitative analysis of hydroxyl and ether by the FT-IR method, assuming that the amount of oxygen in carbonyl functions is negligible. The oxygen contents of the samples provided by CONSOL were determined by difference in elemental analyses. The oxygen data in this study and from CONSOL for the whole resids and whole process oil show reasonable agreement, although the data are somewhat scattered. The relation between these two different methods is:

$$\text{O-Content (wt\%, MAF)}, \text{FT-IR} = 1.1 [\text{O-Content (wt\%, MAF)}, \text{Elemental Difference}]$$

Hydrogen Analysis - The total hydrogen content for each of the samples was determined by summing up the aliphatic, aromatic, and hydroxyl hydrogen determined by FT-IR. The hydrogen analysis provided by CONSOL was determined with a Leco CHN-600 elemental analysis instrument. The results of these two methods are in good agreement. The relation between them is:

$$\text{H-Content (wt\%, MAF)}, \text{FT-IR} = 1.1 [\text{H-Content (wt\%, MAF)}, \text{Elemental Analysis}]$$

Carbon Analysis - The carbon content of each sample was determined by mass balance difference with oxygen and hydrogen contents obtained with the FT-IR method, assuming that the fraction of others, such as nitrogen and sulfur, is negligible. The values supplied by CONSOL were obtained from carbon analysis with the Leco CHN-600 instrument. A comparison shows that these two sets of data from different methods are in good agreement, and the relation between them is:

$$\text{C-Content (wt\%, MAF)}, \text{FT-IR} = 1.0 [\text{C-Content (wt\%, MAF)}, \text{Elemental Analysis}]$$

Ash - FT-IR analysis can determine the contents of major minerals, i.e. mixed clays, Kaolinite, Quartz, and Calcite. The total ash content determined by FT-IR is the sum of these four minerals. Since the FT-IR measurement of minerals includes the associated water and is done at ambient temperature, it is expected to be higher than the high temperature ash determinations supplied by CONSOL. However, it is also true that the FT-IR method does not determine pyrite, so it may underestimate the ash content for coals which contain large amounts of this mineral. The comparison of the ash contents determined with FT-IR and by CONSOL is shown in Figure 4c. The results show that the trends in the FT-IR values of the total ash content agreed well with the values supplied by CONSOL, although the latter numbers were lower as expected. The relation between the two measurements is:

$$\text{Ash (wt\%, dry)}, \text{FT-IR} = 1.3 [\text{Ash (wt\%, dry)}, \text{Combustion}]$$

TG-FTIR Analysis

Proximate Analysis of Feed Coals - Pyrolysis up to 900 °C followed by combustion of the residue, when carried out in the TG-FTIR apparatus, gives a good proximate analysis for feed coals. The proximate analysis with TG-FTIR reveals the contents of ash, volatile matter, fixed carbon, and moisture in coal.

Pyrolysis of coal at temperatures as high as 900 °C will produce a char with a high carbon content (>95%, MAF). Therefore, the char yield (MAF) in pyrolysis represents the fixed carbon content in the coal. The comparison of the fixed carbon content obtained by TG-FTIR and that supplied by CONSOL is shown in Figure 4d. It shows that the two sets of values are in good agreement and the relation between them is:

$$\text{Fixed Carbon (wt\%, dry), TG-FTIR} = 1.0 [\text{Fixed Carbon (wt\%, dry), Proximate Analysis}]$$

The ash content is determined by burning the char in the presence of oxygen. A comparison of ash analyses is shown in Figure 4e, and the results show a good agreement. The relation between the two sets of data is:

$$\text{Ash (wt\%, dry), TG-FTIR} = 1.1 [\text{Ash (wt\%, dry), Proximate Analysis}]$$

The volatile matter of coal includes all the species evolved during pyrolysis. These species are gases and tars, which are measured by TG-FTIR during the process of pyrolysis. The comparison of the volatile matter contents determined by TG-FTIR with those provided by CONSOL from proximate analysis is shown in Figure 4f. The results show that they are in good agreement with each other and the relation is:

$$\text{Volatile (wt\%, dry), TG-FTIR} = 1.0 [\text{Volatile (wt\%, dry), Proximate Analysis}]$$

The moisture content of coal is determined by TG-FTIR prior to pyrolysis. The results obtained by TG-FTIR are not in good agreement with those supplied by CONSOL, although the trend is correct. The relation between them is:

$$\text{Moisture (wt\%, as rec.), TG-FTIR} = 0.45 [\text{Moisture (wt\%, as det.), Proximate Analysis}]$$

This difference is not surprising since the moisture content depends on how the sample is stored and handled.

Ash Analysis for Resids - The ash content of the distillation resids was determined using TG-FTIR by burning the char residue from the resids in the presence of oxygen. The comparison of the resid ash content obtained with TG-FTIR and that supplied by CONSOL is shown in Figure 5a. The results show that the ash contents determined by TG-FTIR are in very good agreement with those provided by CONSOL. The relation between the two sets of data is:

$$\text{Ash (wt\% dry), TG-FTIR} = 1.0 [\text{Ash (wt\%, dry), Combustion}]$$

Char Analysis for Resids - Coal chars produced at temperatures above 900 °C consist mainly of large condensed aromatic rings. It is expected that the char yield from resid pyrolysis would have a proportional relation with the content of condensed aromatics. The comparison of the char yield for pyrolysis performed in the TG-FTIR and the condensed aromatic proton fraction from NMR is shown in Figure 5b for the THF soluble fractions. The results show that the char

yield in resid pyrolysis increases with increasing condensed aromatic proton fraction. The relation between the two sets of values is:

$$\text{Char (wt\%, THF sol.)}, \text{ TG-FTIR} = 0.65 [\text{Cond. Aromatic Proton (\%, THF sol.) } ^1\text{H-NMR}]$$

Data Interpretation in the Context of the Liquefaction Process

The samples from the Wilsonville facility were taken from three locations to represent different degrees of coal processing. The Interstage Product samples were distillation resids obtained from a high pressure flash separation system located between the first stage and second stage reactors. The 2nd Stage Product samples were resids collected from the bottom product hold tank of a separation system following the second stage reactor. The Recycle samples were resids obtained from the solvent surge tank. The Recycle samples are the partially deashed products of the 2nd Stage Product. The structural differences of the samples, revealed in the analytical data, are due to differences in the feed coals and to different degrees of coal processing in liquefaction, as discussed below.

A comparison of -OH contents from THF soluble fractions of the resid samples from different degrees of processing is shown in Figure 6. The results show that the Interstage Product has a higher -OH content than the 2nd Stage Product due to upgrading by the second reactor. The TG-FTIR results show a corresponding reduction of CO evolution in pyrolysis for the 2nd Stage Product, as discussed below. Figure 6 shows a slight -OH reduction due to the deash process. In general, the -OH content of the resids decreases in the order Interstage > 2nd Stage > Recycle. The trends for char yield from TG-FTIR analysis follow the same general order, which is consistent with the role of oxygen functions in retrogressive reactions under pyrolysis [6] and liquefaction conditions [7].

Since the oxygen content of the feedstock would be reduced in the liquefaction process, the amount of CO evolution in pyrolysis is expected to decrease in the order coal > Interstage > 2nd Stage > Recycle, and the results shown in Figure 7 for the whole resids indicate that this is the case. If the results in Figures 6 and 7 are compared, it can be seen that the -OH content and the CO evolution from pyrolysis are related.

Similar to the result of CO evolution in pyrolysis, more CH₄ is evolved in coal pyrolysis than in resid pyrolysis. Because most of the CH₄ forming components in coal are consumed in the liquefaction process in which gaseous product CH₄ is separated from the process stream to become fuel gas, it is reasonable to see less CH₄ evolution in resid pyrolysis. A comparison of CH₄ yields from pyrolysis of the feed coals and various whole resid samples is shown in Figure 8. Since CH₄ forming components would be further reduced by the Second stage reactor, it is also not surprising to see less CH₄ evolution in the pyrolysis of the 2nd Stage Product than the Interstage Product. The amounts of CH₄ evolution from the 2nd Stage Product and from the Recycle are similar, which reveals that the deash process has little effect on the CH₄ forming structures in resids. In general, the amount of CH₄ evolution in the pyrolysis of liquefaction products follows the order coal > Interstage > 2nd Stage ~ Recycle.

The hydrogen content analyses indicate a slight increase in hydrogen concentration in the whole resids from the second stage reactor by comparing the 2nd Stage Product with the Interstage Product (except for Pittsburgh resid). These results are shown in Figure 9. This figure also shows the expected increase in hydrogen concentration for the resid products when compared to the feed coal. Also, as the material is upgraded, the absolute amount of aromatic hydrogen decreases, as shown in Figure 10.

The HRI samples represent production of material from a Continuous Two-Stage Liquefaction facility for different periods of time in a single run. Interpretation of the data reveals a consistent variation of the properties of the samples with the length of run period. The interpretation of these variations is discussed below and is based on information supplied by CONSOL on variations in run conditions as function of time.

The variation of the hydrogen content of the sample with the length of the run period is shown in Figure 11. The results show that the total hydrogen and aliphatic hydrogen content decrease with increasing run time, whereas the aromatic hydrogen shows an opposite trend. The decrease of the hydrogen content of the liquefaction product with run time may be attributable to catalyst aging as well as to a reduction in the solvent/coal ratio and an increase in solvent cut point. It is reasonable to observe a reduction in the aliphatic hydrogen content since the hydrogenation rate slows down with time due to catalyst aging. The increase in H_a with run time may also result from the increasing reaction temperature which would tend to increase the amount of aromatic hydrogen.

The variation of the hydroxyl and ether contents of the samples with the length of the run period is shown in Figure 12. The results show an increase of the hydroxyl content with run time. The change in -OH concentration is due to catalyst aging as well as to the reduction in the solvent/coal ratio and to the increase in solvent cut point. The FT-IR results also show an increase in the ether content with time. The increase of the ether content in the liquefaction products can be attributed mostly to the catalyst aging which would result in a lower rate of bond cleavage on ether linkages. A second possibility is an increase in the amount of ethers formed from retrogressive reactions involving hydroxy and dihydroxy functionalities structures.

In-Situ FT-IR/F-O/ATR Measurements

In order to accommodate the temperature ($\sim 400^\circ\text{C}$) and pressure (~ 3000 psig) requirements of a coal liquefaction process, a sapphire fiber optic element was used in the ATR mode for in-situ measurements. This cuts out the information below about 2500 cm^{-1} , but still allows significant amounts of chemical structural information to be obtained.

Since tetralin is the solvent used in coal liquefaction experiments, it is of interest to know how tetralin behaved under temperature conditions similar to those of coal liquefaction. Non-isothermal experiments which simulate the conditions of coal liquefaction are carried out in the test cell, and the infrared spectra from the F-O/ATR spectroscopy at different temperatures were obtained. Figure 13 shows the tetralin absorbance spectra in the C-H stretching region at different temperatures. Since tetralin does not contain oxygen functional groups, the focus of the analysis was on the C-H stretching region.

It can be seen from the spectra that the infrared absorbance decreases with temperature. This result is expected, since the depth of penetration of the infrared evanescent wave into the sample decreases with temperature. The temperature effect on F-O/ATR spectroscopy requires further study in order to obtain quantitative results.

Since it was known [8] that tetralin would undergo hydrogen transfer reactions to form a mixture of aliphatic and alkyl aromatic compounds by heat treatment, the aliphatic to aromatic ratio in the system would therefore vary with temperature. Based on Figure 13, one should be able to determine the aliphatic to aromatic hydrogen ratios at different temperatures from the absorbance ratios of 2930 cm^{-1} to 3020 cm^{-1} , if the extinction coefficients for each species were

known. This issue, for pure tetralin as well as coal liquefaction measurements, will be discussed in a future publication.

It has been reported [9] that the alkyl CH_3 gives rise to a symmetric stretching mode at 2870 cm^{-1} , and the $-\text{CH}_2-$ at 2850 cm^{-1} . Since tetralin does not contain methyl structures, the 2860 and 2840 cm^{-1} peaks shown in Figure 13 are actually from the splitting of the methylene symmetric stretching at 2850 cm^{-1} . By thermal treatment, tetralin will undergo decomposition to form its derivatives, which contain methyl groups. The methyl symmetric stretching at 2870 cm^{-1} would interfere with the 2860 cm^{-1} peak from the methylene, and, therefore, the former peak would not be distinct if its concentration is low. Because of this interference, we cannot see a 2870 cm^{-1} peak emerging at higher temperatures in Figure 13. However, if a series of absorbance spectra from coal liquefaction experiments are examined, as shown in Figure 14 for demineralized Zap, the emergence of the methyl 2870 cm^{-1} absorbance underneath the methylene 2860 cm^{-1} absorbance can be clearly seen. A curve resolving technique has recently been developed in our group to resolve overlapped absorption bands. This technique will be applied to the F-O/ATR spectra to improve quantitative analysis.

The O-H stretching region for the liquefaction run is shown in Figure 15. The absorbance spectrum of O-H stretching is usually a broad band, ranging between 3100 and 3600 cm^{-1} and centered near 3400 cm^{-1} [10]. Figure 15 shows that the absorbance by hydroxyls increases with the degree of liquefaction, indicating increasing amount of OH-containing coal fragments dissolved in the liquid phase.

CONCLUSIONS

Both FT-IR and TG-FTIR have been clearly shown to provide a wide variety of useful information for process stream characterization. Both techniques can be applied to whole process oils, resids, or distillates, including ash components, and require relatively small samples ($<50\text{ mg}$). Significant differences are observed between process stages, coal types, and with catalyst aging. A summary of the composition parameters that can be obtained by FT-IR and TG-FTIR is shown in Table 1. In many respects, FT-IR is probably the single most useful technique for this purpose, since it can provide measurements on both organic and mineral components. It has also demonstrated that on-line FT-IR measurements could be made in-situ using a sapphire fiber optic element in the Attenuated Total Reflectance mode.

ACKNOWLEDGEMENTS

This work was supported by a subcontract from the Consolidation Coal Company under DOE Contract No. DE-AC22-89PC89883, and by the DOE SBIR program under Grant No. DE-FG05-91ER81151. The authors also wish to acknowledge Dr. Susan Brandes and Mr. Richard Winschel of CONSOL Research and Development for many helpful discussions, and Mr. William Stevenson, Dr. Mark Druy, and Mr. Paul Glatkowski of Foster-Miller, Inc. of Waltham, Mass. for assisting with the FT-IR/F-O/ATR measurements. Marie DiTaranto of Advanced Fuel Research did the FT-IR analyses. Robert Carangelo and Erik Kroo consulted on the interpretation of the FT-IR, TG-FTIR and FT-IR/F-O/ATR results.

REFERENCES

1. Solomon, P.R., and Carangelo, R.M., *Fuel*, **61**, 663 (1982).
2. Solomon, P.R., and Carangelo, R.M., *Fuel*, **67**, 949 (1988).
3. Solomon, P.R., Hamblen, D.G., and Carangelo, R.M., *Am. Chem. Soc. Symp. Ser.*, **205**, 77 (1982).
4. Painter, P.C., Snyder, R.W., Starsinic, M., Coleman, M.M., Kuehn, D.W., and Davis, A., *Am. Chem. Soc. Symp. Ser.*, **205**, 47 (1982).
5. Carangelo, R.M., Solomon, P.R., and Gerson, D.J., *Fuel*, **66**, 960(1987).
6. Solomon, P.R., Serio, M.A., Desphande, G.V., and Kroo, E., *Energy & Fuels*, **4**, (1), 42 (1990).
7. Serio, M.A., Solomon, P.R., Kroo, E., Bassilakis, R., Malhotra, R., McMillen, D., *Prepr. Pap. - Am. Chem. Soc., Div. Fuel Chem.*, **35**, (1), 61 (1990).
8. Vlieger, J.J., Kieboom, A.P.G., and Bekkum, H., *Fuel*, **63**, 334, (1984).
9. Willard, H.H., Merritt, L.L., Jr., Dean, J.A., and Settle, F.A., Jr., Instrumental Methods of Analysis, 6th Edition, D. van Nostrand Co., New York (1981), Chapter 7.
10. Painter, P.C., Sobkowiak, M., and Youtcheff, J., *Fuel*, **66**, 973 (1987).

TABLE 1. SUMMARY OF FT-IR AND TG-FTIR MEASUREMENTS

FT-IR MEASUREMENT	ALTERNATIVE TECHNIQUE
Hydroxyl Hydrogen	Chemical Titration
Aliphatic Hydrogen	¹ H-NMR
Aliphatic Carbon*	¹³ C-NMR
Aromatic Hydrogen	¹ H-NMR
Hydrogen Content	Elemental Analysis
Carbon Content*	Elemental Analysis
Hydroxyl Oxygen	Chemical Titration
Ether Oxygen	- - -
Carbonyl Oxygen**	- - -
Total Ash	TGA
Mineral Components	ICP
TG-FTIR MEASUREMENT	ALTERNATIVE TECHNIQUE
Direct	
Volatile Content	Proximate Analysis
Fixed Carbon	Proximate Analysis
Total Ash	Proximate Analysis
Moisture	Proximate Analysis
C,H,N,S	Elemental Analysis
Indirect	
Char Yield → Condensed Aromatics	¹ H-NMR
CO Yield → Phenolic Content	FT-IR
CH ₄ Yield → Methyl Group Content	¹³ C-NMR
Tar Evolution Profile → Boiling Range	Distillation

Figure 1. Quantitative FT-IR Analysis of the Coal Liquefaction Product. Correction of Resid Spectrum for Scattering and Minerals. a) Correction of Resid Spectrum; b) Determination of Mineral Spectrum by Addition of Reference Spectra. Data for Whole Resid Sample (interstage) from Illinois No. 6 Coal.

Figure 2. TG-FTIR Results for Interstage Oil Resid from Illinois No. 6 Coal.

Figure 3. Schematic of FT-IR Fiber-Optic ATR System for Coal Liquefaction.

Figure 4. Correlation and Comparison of the Results from FT-IR Techniques and Other Methods. a) Resid Aromatic Hydrogen Distribution; b) Resid Aliphatic Hydrogen Distribution Resid; c) Resid Ash Content; d) Coal Fixed Carbon; e) Coal Ash Content; f) Coal Volatile.
* Present Study; + Data Supplied by CONSOL.

Figure 5. Correlation and Comparison of the Results from FT-IR Techniques and Other Methods. a) Resid Ash Content; b) Char Yield with Condensed Aromatic Proton Fraction. * Present Study; + Data Supplied by CONSOL.

Figure 6. -OH Content at Different Stages for Wilsonville Resids.

Figure 7. CO Evolution from Pyrolysis of Wilsonville Resids.

Figure 8. CH₄ Evolution from Pyrolysis of Wilsonville Resids.

Figure 9. Hydrogen Content at Different Stages for Wilsonville Resids.

Figure 10. Aromatic Hydrogen Content at Different Stages for Wilsonville Resids.

Figure 11. Hydrogen Analysis for HRI Liquids.

Figure 12. Oxygen Functional Group Analysis for HRI Liquids.

Figure 13. The Absorbance Spectra of Tetralin from F-O/ATR Spectroscopy in a Non-Isothermal Experiment.

Figure 14. The C-H Stretching Region of the Absorbance Spectra from F-O/ATR Measurements under Coal Liquefaction Conditions for Demineralized Zap.

Figure 15. The O-H Stretching Region of the Absorbance Spectra from F-O/ATR Measurements under Coal Liquefaction Conditions for Demineralized Zap.

APPENDIX 3

APPLICATION OF ^{252}Cf -PLASMA DESORPTION MASS SPECTROMETRY TO ANALYSIS OF DIRECT COAL LIQUEFACTION HEAVY PRODUCTS.

Andrzej R. Lapucha and John W. Larsen

Lehigh University, Department of Chemistry,
Bethlehem, PA 18015

Keywords: Plasma Desorption Mass Spectrometry, Coal Liquefaction.

ABSTRACT

Californium Plasma Desorption Mass Spectrometry (PDMS) has been used to analyze heavy distillation residues obtained from direct coal liquefaction processes. The characteristics of the ^{252}Cf -PDMS technique for the analysis of these non-polar materials were determined, especially the ionization efficiency of molecules of different chemical type. The molecular weight distributions of several THF soluble $850^\circ\text{F}+$ materials ("resids") from the Wilsonville pilot plant were determined. These data were compared to the results obtained by Field Ionization Mass Spectrometry (FIMS) and Gel Permeation Chromatography (GPC). In general, number average molecular weights for all three techniques agreed well. Both GPC and PDMS give higher weight average molecular weights than FIMS and agree with each other for weight averages below 1500 amu.

INTRODUCTION

Field ionization and field desorption mass spectrometry have been applied to the analysis of coal liquefaction products.¹⁻³ ^{252}Cf -PDMS, a different kind of mass spectrometry,⁴⁻⁶ has been incompletely explored for the analysis of coal products.^{7,8}

The ^{252}Cf plasma desorption technique utilizes energetic fission fragments from the decay of ^{252}Cf to volatilize and ionize a solid sample. The ionization source is typically a 10- μCi californium sandwiched between two thin sheets of nickel foil. A sample is dissolved in an appropriate solvent and the solution is electrosprayed over a 1 cm^2 area on an aluminized poly(ethylene terephthalate) foil (Mylar disk). ^{252}Cf -PDMS is capable of producing mass spectra consisting primarily of molecular ions for a wide variety of compounds, including amino acids,⁴ peptides,⁹ nucleotides,¹⁰ geoporphyrins,¹¹ polynuclear aromatic hydrocarbons,¹² polyethers¹³ and other synthetic polymers.¹⁴⁻¹⁶

Gel Permeation Chromatography (GPC), also known as Size Exclusion Chromatography (SEC), has been used to determine the molecular weight distribution of coal extracts.¹⁷⁻¹⁹ The limits of the method and lack of calibration standards for coal derived materials are well known.²⁰ Relative molecular weights values obtained using the same standards (often polystyrenes) and conditions can be satisfactorily compared.

EXPERIMENTAL

Mass spectra were obtained using a BIO-ION 20 commercial time-of-flight mass spectrometer (Bio-Ion Nordic, Upsala, Sweden) equipped

with PDP-11 microcomputer data acquisition system (DAS). The instrument is equipped with 10 μCi ^{252}Cf source and a short 15 cm flight tube. We used a positive 10kV acceleration voltage and the time resolution was set to 1ns/channel. Data collection was terminated at a preset count and 10^6 primary ion events were acquired. This took about 12 minutes. The samples of analyzed distillation resids were dissolved in THF (10 mg/mL) and 40 μl of each solution was electrosprayed onto nitrocellulose coated Mylar disks using the BIO-ION electrospray apparatus. Thin homogenous coverages were obtained. We also developed a software package (CFINT) that can be used on any IBM compatible PC to calculate the number average and weight average molecular weights using data imported from the Bio Ion 20 PDP-11 computer. In addition, this software package allows us to subtract the background spectrum which comes from the mylar film. The software supplied with the spectrometer also adds counts from surrounding channel to enhance the signal-to-noise ratio. This is undesirable for the determination of molecular weight distribution and has been removed from our data analysis.

The molecular weight distributions of five selected resids (#7, #13, #16, #19 and #22) provided by Consolidation Coal Company dissolved in pyridine were measured by a computer interfaced GPC with a mass sensitive detector. The components of the instrument were all commercially available. It consists of a Waters Liquid Chromatograph (Model ALL 201) equipped with high pressure pump, injector, and four μ -styragel columns ($10^4 + 10^3 + 500 + 100 \text{ \AA}$). The mass detector, built by Applied Chromatography Systems Ltd. (Model 750/14), works by nebulizing the liquid stream emerging from the column and then passing this uniform distribution of droplets down a heated tube in a flow of dry nitrogen, evaporating the solvent. The resulting solid passes a light scattering detector whose output is directly proportional to the mass of solid material passing in front of it. Between the mass detector and the columns is a digital thermal pulse flow meter. The outputs from the mass sensitive detector and the flow meter are directed to a Zenith Model 158 microcomputer, the former through a 12 bit resolution A to D converter (Data Translation Model DT 2805). The programs for data collection and manipulation were written in a high level language using the Asyst package (McMillan Software Co.). The instrument was carefully calibrated with polystyrene standards. HPLC grade pyridine was used as the eluting solvent with flow rate of ca. 1 mL/min. 50 μl of each sample with concentration of 10 mg/mL was loaded through the injector valve. For each run data were collected for the period of one hour.

RESULTS AND DISCUSSION

Five THF soluble samples of solid 850°F+ materials ("resids") obtained in the Wilsonville pilot plant during direct liquefaction of different coals were analyzed by ^{252}Cf - Plasma Desorption Mass Spectrometry. Molecular Weight Distribution curves were obtained and number average molecular weights (M_n) and weight average molecular weights (M_w) were calculated. These data are compared to the results obtained by Field Ionization Mass Spectrometry and Gel Permeation Chromatography.

Figure 1 shows the PDMS spectra of Mylar film (a), the software converted spectrum of resid #7 which includes the Mylar background (b), and of resid #7 with the Mylar background subtracted (c). As can be seen only traces of Mylar background remain in the range between 0-100 m/z.

Despite different coal feeds and processing conditions, all the samples show similarities. Table 1 summarize origin and physico/ chemical parameters of the analyzed recycle products. In Table 2. and Fig. 2 (a-c) PDMS results are compared with those obtained from FIMS and GPC. The PDMS M_n values are essentially identical to those from FIMS and GPC. PDMS M_w values are about twice the field ionization results. The FIMS spectra do not show any peaks with molecular weights higher than 1200 - 1300 m/z. Both PDMS and GPC detect molecules having molecular weight greater than 1300 amu. In fact, the PDMS intensity does not return to zero before 2000-2500 m/z. Based on these observations, much higher M_w values can be expected from PDMS and GPC. Probably the field ionization technique is not able to efficiently volatilize high boiling, high molecular weight species. GPC M_w values are higher than the corresponding PDMS results with an exception of resid #19. There are three possible explanations for this phenomenon. 1) The integral of GPC molecular weight distribution curve is very sensitive to small amounts of high molecular weight analytes which are not detected by PDMS. This leads to enormously high M_w values. 2) The recycle oils are fragmenting in PDMS. 3) PDMS is capable of producing mass spectra from a wide variety of natural products but less polar polymeric materials very often give low responses or no peaks at all. PDMS may not be detecting all of the sample.

As can be seen in Table 2, the molecular weights of Resid #19 are much lower then of the other samples. This sample has the highest percentage of condensed aromatics and is low in sulphur and beta and gamma protons (Table1). For this sample PDMS and GPC M_n and M_w values are in overall good agreement. Resids #7, #13 and #22 contain relatively low amounts of condensed aromatics, high numbers of cyclic and alkyl beta and gamma protons, and the highest percentage of oxygen. These resids show higher weight average molecular weights in GPC than in PDMS. The relatively low polarity and highly polymeric nature of these fractions are both unfavorable factors for PDMS. The instrument may not be providing a reliable analysis.

CONCLUSIONS

²⁵²Cf-PDMS is easy to operate, fast and less expensive than most other mass spectrometric techniques and is suitable for quantitative measurements of the molecular weight distributions of some coal conversion products.

Comparison of PDMS molecular weight distributions to the GPC and FIMS shows that, in general, number average molecular weights agree well. Both GPC and PDMS give higher weight average molecular weights than does FIMS.

ACKNOWLEDGMENTS

We thank Dr. Susan D. Brandes at the Consolidation Coal Company for providing samples for this study. This research was financed by the subcontract from Consolidation Coal Co. under DOE contract DE-AC22-89PC89883. We are most grateful to Dr. Patrick Wernett for writing the software used and to William Anderson for his instrumental advice and expertise.

REFERENCES

1. Aczel, T.; Laramee, J.; Hansen, G.J. in *Proceedings of the 30th Annual Conference on Mass Spectrometry and Allied Topics*, p.808 (1982)
2. Aczel, T.; Dennis, L.W.; Reynolds, S.D. in *Proceedings of the 35th Annual Conference on Mass Spectrometry and Allied Topics*, p.1066 (1987)
3. Larsen, B.S.; Fenselau, C.C.; Whitehurst, D.D.; Angelini, M.M. *Anal. Chem.* (1986), **58**, 1088
4. MacFarlane, R.D.; Torgeson, D.F. *Science* (1976), **191**, 920
5. MacFarlane, R.D. *Anal. Chem.* (1983), **55**, 1247 A
6. Cotter, R.J. *Anal. Chem.* (1988), **60**, 781 A
7. Lytle, J.M.; Tingey, G.L.; Macfarlane, R.D. *Anal. Chem.* (1982), **54**, 1881
8. Zingaro, R.A.; Macfarlane, R.D.; Garcia, J.M.; Vindiola, A.G.; Zoeller, J.H. in *Chemistry of Coal Liquefaction*, ACS Symposium Ser., Vol. 29, No 5, p. 22 (1984)
9. Alai, M.; Demirev, P.; Fenselau, C.; Cotter R.J. *Anal. Chem.* (1986), **58**, 1303
10. Scanlan, G.; Benson, L.; Tsarbopoulos, A.; Jardine, I. in *Proceedings of the 36th Annual Conference on Mass Spectrometry and Allied Topics*, Denver, CO. (1987), 80
11. Wood, K.V.; Bonham, C.C.; Chou, M.M. *Energy Fuels* (1990), **4**, 747
12. Zoeller, J.H.; Zingaro, R.A.; Macfarlane, R.D. *Int. J. Mass Spectrom. Ion Processes* (1987), **77**, 21
13. Chait, B.T.; Shpungin, J.; Field, F.H. *Int. J. Mass Spectrom. Ion Processes* (1984), **58**, 121
14. MacFarlane, R.D.; McNeal, C.J; Martin, C.R. *Anal. Chem.* (1986), **58**, 1091
15. Gehrig, C.C.; Wood, K.V. *The 38th ASMS Conference on Mass Spectrometry and Allied Topics* (1990), 255
16. Keough, T.; Lacey, M.P. *Anal. Chem.* (1991), **63**, 1482
17. Larsen, J.W.; Choudry, P. *J. Org. Chem.* (1979), **44**, 2856
18. Larsen, J.W.; Mohammadi, M.; Yiginsu, J.; Kovac, J. *Geochim. Cosmochim. Acta* (1984), **48**, 135
19. Larsen, J.W.; Wei, Y.C. *Energy Fuels* (1988), **2**, 344
20. Buchanan, D.H.; Warfel, L.C.; Biley, S.; Lucas, D. *Energy Fuels* (1988), **2**, 32

Table 1. Analysis of the Soluble Portion of the Distillation Resids

	Res.#7	Res.#13	Res.#16	Res.#19	Res.#22
Weight %	Ill.#6	Tex.Lign.Pitt.#8	Wyodak	Wyodak	
C	88.75	89.39	90.54	90.90	89.46
H	8.15	7.12	6.74	6.32	6.69
N	0.66	1.23	0.91	1.11	1.13
S	0.14	0.09	0.39	0.03	0.05
O	2.30	2.17	1.42	1.64	2.67

Proton Dist. (%)

Cond. Aromatics	16.7	22.4	26.1	32.2	22.5
Uncond. Aromatics	4.4	4.3	5.4	5.1	5.1
Cyclic Alpha	17.9	19.2	18.9	18.1	16.8
Alkyl Alpha	9.4	9.5	9.4	9.2	9.3
Cyclic Beta	18.6	15.9	14.8	13.6	14.4
Alkyl Beta	20.4	18.5	14.6	13.9	21.2
Gamma	12.5	10.3	10.8	7.8	10.8
Phenolic -OH Conc.	0.50	0.71	0.69	0.67	0.89

Table 2. Number Average and Weight Average Molecular Weights Obtained from Field Ionization Mass Spectrometry, Plasma Desorption Mass Spectrometry and Gel Permeation Chromatography.

	FIMS	PDMS	GPC	FIMS	PDMS	GPC
Resid #	M _n			M _w		
7	620	600	600	730	1370	1930
13	570	570	570	680	1340	2050
16	590	590	610	690	1340	1840
19	-	580	500	-	1300	1430
22	-	600	700	-	1460	2160

Figure 1. PDMS Spectra of Mylar Background (a), Software Converted Spectrum of Resid #7 which Include Mylar Background (b) and Resid #7 with Mylar Background Subtracted (c).

Figure 2. FIMS (a), PDMS (b) and GPC (c) Molecular Weight Distribution of Resid #7

APPENDIX 4

CONVERSION OF RESID COMPONENTS IN CC-ITSL PROCESSING AT WILSONVILLE

G. A. Robbins, R. A. Winschel, F. P. Burke
CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Key words: Liquefaction, Resid, Kinetics

INTRODUCTION

Integrated Two-Stage Liquefaction technology has evolved to its current configuration, in which high recycle rates of solids and non-distillable materials contribute to high conversions and distillate yields. At the Wilsonville, Alabama, 6 ton/day pilot plant, the feed stream contains 29-33 wt % coal, 27-34 wt % resid (850°F⁺), and 8-16 wt % cresol insolubles (CI). Only 25-28% of the feed is distillable. In a recent assessment of analytical needs,¹ it was concluded that the chemistry of residual materials is an important area for study, including improved analytical methods for resid characterization and more extensive kinetic modeling. CONSOL has characterized process oils from each of the last nineteen Wilsonville runs; Close-Coupled Integrated Two-Stage Liquefaction (CC-ITSL) operation of the plant spanned fifteen runs since 1985. This paper represents an initial attempt to review and refine some areas of our investigations of resid conversion chemistry in Wilsonville runs.

EXPERIMENTAL

The experimental methods used in the analysis of whole process oils were reported elsewhere in detail.²⁻⁴ A brief description is provided here. Each whole process oil is distilled to 850°F to produce a distillate and a resid. Tetrahydrofuran (THF) solubles are obtained by repeated washing of distillation bottoms with distilled THF and recovery by rotary evaporation. Phenolic -OH concentration in the THF-soluble resid is determined by Fourier Transform infrared spectroscopy in THF solution. The THF-soluble resid is fractionated successively into oils (hexane-solubles), asphaltenes (benzene-solubles), and preasphaltenes (pyridine-solubles) with analytical quantitation by flame ionization detection (using different response factors for each feed coal represented). Each insoluble resid fraction is ashed at 800°C to constant weight and insoluble organic matter (IOM, also referred to as unconverted coal, or UC) is determined by difference between weights of ash and THF-insolubles.

The process oils analyses are used to calculate conversions (forced ash balance method) of the 850°F⁺ material and its various components in each reactor stage. The 850°F⁺ conversions are used to calculate conversion rate constants, conversion activities, and a catalyst deactivation rate constant.⁵ Equations used are:

$$C = \text{Conversion} = \left(\frac{850^\circ\text{F}^+ \text{ In/Ash In} - 850^\circ\text{F}^+ \text{ Out/Ash Out}}{850^\circ\text{F}^+ \text{ In/Ash In}} \right) \times 100\%$$

$$K = \text{Rate Constant} = \text{WHSV} \left(\frac{C}{100 - C} \right)$$

$$A = \text{Conversion Activity} = K e^{E_{act}/RT},$$

where E_{act} is assumed to be 23,500 cal/mol. In addition to conversion of the total 850°F⁺ resid, it is possible to calculate conversion of any component, including IOM, THF-solubles, oils, asphaltenes, preasphaltenes, and phenolic -OH.

RESULTS AND DISCUSSION

Background. Table 1 summarizes the major operating conditions for CC-ITSL Runs 257 through 262. Generally several significant differences exist among runs. Detailed discussions of each run have been reported by Wilsonville⁶ and CONSOL⁷. A block diagram of the Wilsonville plant appears in Figure 1.

Comparison of CONSOL and Wilsonville Distillation Procedures and Resid Conversions CONSOL uses an 850°F atmospheric equivalent distillation endpoint; the Wilsonville laboratory uses a 1050°F endpoint.⁶ Therefore, the 850 x 1050°F boiling fraction is considered resid in CONSOL's analyses, but distillate in Wilsonville's analyses. Table 2 illustrates this. On average, CONSOL typically measured about 14 wt % more resid than did Wilsonville. The amount of the difference may be related to reactor volume either directly or indirectly (see Table 2). Because of the difference, conversions calculated from CONSOL data are of 850°F⁺ material; Wilsonville's conversions are of 1050°F⁺ material. Some implications of this difference have been discussed elsewhere.⁵

One way to compare the (850°F⁺) conversions obtained by CONSOL with those obtained by Wilsonville (for 1050°F⁺) is to calculate the CONSOL/Wilsonville conversion ratio (R(C/W)) (Figure 2). Several observations were made from these data. First, R(C/W) averaged 0.8-1.0 in most runs, indicating CONSOL conversions were generally somewhat lower than Wilsonville conversions. Second, the R(C/W) ratio did not correlate with CONSOL and Wilsonville values for V-131B resid content (Table 2). Third, Run 262 was unprecedented in the low R(C/W), in each stage (not shown) and total system. It is not obvious why the 850 x 1050°F conversion was so low relative to the conversion of 1050°F⁺ material, but perhaps paraffinic components present in the 850 x 1050°F fraction were not readily converted to distillate in Run 262. Several points can be made regarding this: 1) Wilsonville found significant quantities of waxes in the Run 262 distillate products, and experienced unprecedented handling problems with them. 2) CONSOL found the heavy distillate paraffinity to be very high in Run 262. 3) The Run 262 resid alkyl beta protons were high, but not unprecedented; they were consistently this high only in one other CC-ITSL run (Run 257). How these results may be related to the use of Molyvan L (dispersed catalyst precursor first used in Run 262) is unknown. Perhaps dispersed Mo is not a good paraffin cracking catalyst, or the high coal space velocity during Run 262 was a contributor to poor cracking.

Corresponding first- and second-stage results are not shown, but are summarized here. R(C/W) for the first stage (typically slightly lower than one) in any given period is usually greater than that of the second stage (typically 0.8). These observations seem consistent with the first stage conversion which is dominated by IOM, and is not highly subject to variation in distillation conditions. The conversion of material in the second stage is more sensitive to distillation conditions and shows a greater difference in CONSOL and Wilsonville results. There was more scatter in the second-stage ratios.

Catalyst Deactivation in Run 258. Kinetic rate constants and activities (pre-exponential factors) for 850°F⁺ conversion were calculated for Run 258 material balance periods to evaluate catalyst activity and deactivation. In many recent runs, a look at catalyst deactivation was impossible because most operating periods were obtained at similar (equilibrium) catalyst ages. However, tests at several catalyst ages (some were from batch aging) in Run 258 allowed a catalyst activity evaluation. In order that the calculation would not be skewed by many data points near the equilibrated age of ca. 2500 lb (resid + Cl)/lb cat, all of those data (periods B through F, H, and I) were averaged to a single value (transitional periods were omitted). The deactivation rate constant is evaluated by considering the conversion activity, A, to have an exponential dependence on catalyst age, t, as $A = A'e^{-\alpha t}$, where A' is the initial conversion activity. As written, catalyst deactivation will result in negative values of α , the deactivation rate constant. The value of α was determined by regression of $\ln A$ on t. The results (Table 3 and Figure 3) indicate no significant effect of second-stage catalyst age on first-stage activity, as is expected for the thermal first stage (in the absence of any solvent donor effect). However, a deactivation rate constant is obtained for the second-stage catalyst with a high correlation, although for only four data points. The α and A' values for the second-stage catalyst are similar to those CONSOL found for Wilsonville Runs 250 through 257.⁵ However, the correlation of catalyst activity with age in Run 258 was much stronger than in those prior runs.

Conversion of Resid Components. Conversions of components of the 850°F⁺ resid (850°F⁺ resid, THF-solubles, oils, asphaltenes, preasphaltenes, and phenolic -OH) were calculated for Runs 257 through 262 (Figure 5). In Run 262 (Black Thunder coal, see Figure 5a), the resid + IOM conversion was positive in the first stage and low in the second stage, resulting in equivalent first-stage and total conversions. The conversion of THF-soluble resid and its components showed negative first-stage and total conversions, with higher second-stage conversions. The negative conversions represent gains in those components, from conversion of coal to solubles. Second-stage conversions of THF solubles, oils, and asphaltenes were approximately zero, making the corresponding first-stage and total conversions equivalent. Conversions of

preasphaltenes and phenolic -OH differ from those of the other components: they are greater in magnitude, showing greater first-stage and total gains (negative conversions); and the second-stage conversions are large and positive, resulting in increases in the total system conversions. The large negative conversion (net gain) of preasphaltenes in the first stage implies that preasphaltenes are primary coal solubilization products and that they are an intermediate form in the transition from coal to distillate. In the second stage, little additional coal is converted, and the conversion of preasphaltenes to other products is positive. The phenolic -OH conversion shows a similar trend with reactor stage, presumably because preasphaltenes are high in phenolic -OH (but the other fractions contain phenolics, as well). These results suggest that preasphaltenes and/or phenolic -OH could be important to include as a group in lumped kinetic modeling. This could be important in overall evaluations of performance, since heteroatom removal is a significant role of the catalyst, and since refining of the liquids to final products has a major impact on process economics.

Figure 5b shows the average results from Run 261, a catalytic/catalytic, low/high temperature run, with Illinois 6 feed coal. The preasphaltene and phenolic -OH conversions show the same trends as in Run 262. Trends in conversions of resid + IOM and other components somewhat resemble those in Run 262, but a number of differences are evident. In Run 261, the second-stage conversion of resid + IOM was relatively high and contributed a great deal to the total conversion. Conversions of THF-solubles and asphaltenes were positive in the second stage in Run 261, contributing to the respective total conversions. Total conversions of THF-solubles, oils and asphaltenes, and conversion of oils in each stage, were all close to zero. The results for Run 257 (another catalytic/catalytic Illinois 6 coal run) were very similar to those for Run 261, in spite of the fact that Run 257 used a high/low temperature configuration.

Resid component conversion results from two segments of Run 260 (Black Thunder coal) are shown in Figures 5c and 5d. One is thermal/catalytic, high/low operation (periods A-C), and the other is catalytic/thermal, low/high operation (periods D-F). The trends in resid component conversion during thermal/catalytic operation are quite similar to those seen in Run 261 (Figure 5b). Run 260 resembles the other subbituminous thermal/catalytic runs (262 and 258), however, in the relatively low second-stage resid + IOM conversion. That situation changed during catalytic/thermal operation in Run 260 (Figure 5d), when the two reactors more equally shared the contribution to conversion of resid + IOM. Also during catalytic/thermal operation, the first-stage, second-stage, and total conversions of most resid components were approximately zero. The preasphaltene conversions were still the most sensitive, but their magnitude was greatly reduced relative to the other runs discussed. The phenolic -OH conversions were quite small in magnitude, and were close to zero. Overall, it appears as if catalytic/thermal operation in Run 260 nearly balanced the work performed by each reactor and put the reactors into a near-equilibrium situation with respect to resid conversion. Thus, for most components, there was little net conversion or gain. A net conversion of coal to preasphaltenes occurred in the first stage and total system. In the second stage, coal conversion to resid was balanced by resid conversion to distillate.

CONCLUSIONS

In the latest Wilsonville CC-ITSL runs, the first stage primarily converts coal to solubles; conversion of soluble components takes place principally in the second stage. Preasphaltenes (which are high in phenolics) seem to be the primary coal solubilization product, and their conversion is effected primarily in the second stage. Including preasphaltenes and/or phenolic -OH components in lumped kinetic models may be useful, because defunctionalization and upgrading are important roles of catalytic reactor systems. Second-stage conversions of the oil and asphaltene components were typically low (relative to preasphaltenes conversions), and in many cases were close to zero. These results are consistent with the conventional wisdom regarding thermal/catalytic processing, in which solubilization and upgrading take place primarily in different stages, but appear to apply as well to catalytic/catalytic operation. Trends in resid component conversions in two catalytic/catalytic runs with the same feed coal (Runs 257 and 261) were very similar, in spite of a difference in temperature configuration (high/low vs. low/high). Catalytic/thermal operation in the last part of Run 260 seemed to balance the load in each reactor and result in a near-equilibrium situation with respect to resid conversion (little net conversion or gain of most resid components in either reactor). This situation was not typical of the other runs investigated (Runs 257-262).

Second-stage resid + IOM conversion activities in Run 258 material balance periods decreased significantly with catalyst age, indicating catalyst deactivation. The thermal first stage conversion activity showed no dependence on second-stage catalyst age.

The concentration of 850 x 1050°F material in the recycle oil seems to be influenced primarily by reactor volume in use, perhaps by changing the reactor dynamics (such as the relative thermal and catalytic reaction volumes). During Run 262, the 850°F conversion relative to 1050°F conversion was quite low in each stage, possibly due to the presence of paraffinic components not easily converted to final products.

RECOMMENDED FUTURE WORK

The resid conversion chemistry of Wilsonville runs prior to Run 257 should be explored in more detail and more-detailed analysis of runs after 257 may also be warranted. Calculation of kinetic rate constants and conversion activities for individual components (instead of only the resid + IOM) might also be of interest. Addition of one more analysis would make it possible to obtain conversions of various hydrogen (proton) types, perhaps providing additional information on the nature of the converted resid.

What more is needed in the future? Innovative kinetic modeling is needed, even for empirical yield and conversion data. For example, experience indicates that bituminous coal converts readily to soluble resid, but less readily to distillate. Conversion of subbituminous coal to solubles is more difficult, but the solubles are readily converted to distillate. An adequate model of liquefaction phenomena would have to account for differences in the coal and resid conversion kinetics in various coals. A comprehensive kinetic model (of proper reaction order) should include the following (preferably mathematically separable) terms: coal (separate terms for IOM and resid reactivity), catalyst (activity and deactivation susceptibility by various routes), and processing conditions (temperature, space velocity, resid concentration, coal and ash recycle concentration, etc.). Current models do not adequately separate processing condition effects from those of the coal and catalyst.

ACKNOWLEDGEMENT

This work was supported by the U. S. Dept. of Energy under contract DE-AC22-89PC89883.

REFERENCES

1. Brandes, S. D.; Robbins, G. A.; Winschel, R. A.; Burke, F. P. 'Coal Liquefaction Process Streams Characterization and Evaluation, Analytical Needs Assessment Topical Report', DOE/PC 89883-18, March 1991.
2. Burke, F. P.; Winschel, R. A.; Robbins, G. A. 'Recycle Slurry Oil Characterization Final Report - October 1980 through March 1985', DOE/PC 30027-61, March 1985.
3. Winschel, R. A.; Robbins, G. A.; Burke, F. P. 'Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report, July 1 through September 30, 1985', DOE/PC 70018-13, December 1985.
4. Winschel, R. A.; Robbins, G. A.; Burke, F. P. *Fuel* 1986, 65, 526-532.
5. Burke, F. P.; Winschel, R. A.; Robbins, G. A. 'Coal Liquefaction Process Solvent Characterization and Evaluation - Final Report', DOE/PC 70018-70, September 1989.
6. Detailed Wilsonville Technical Review Meeting handouts and run reports under U. S. DOE Contract DE-AC22-90PC90033 and others preceding it; also see, for example, papers from recent DOE Liquefaction Contractors' Review Meetings and from recent EPRI Clean Fuels Conferences.
7. Various reports under U. S. DOE Contracts DE-AC22-80PC30027, DE-AC22-84PC70018, and DE-AC22-89PC89883.

Table 1. Conditions Used in Recent Wilsonville Runs

Condition	Wilsonville Run					
	257	258	259	260	261	262
Coal [*] (MF Ash Content, wt %)	BS 2 (11.3)	SC (5.6), BT (7.3)	Ire. (4.5), Ire. (14.9)	BT (6.2)	BS 2 (11.8)	BT (6.4)
Coal Feed Rate, MF lb/hr	166-531	193-293	230-356	251-352	357-548	242-346
Coal Concentration, MF wt %	30-34	30	30-33	30	29-33	30
Resid In Recycle Solvent, wt %	40-50	40-41	40-51	39-40	33-49	32-41
Solids In Recycle Solvent, wt %	12	20-25	6-13	20-21	11-12	10-20
Reactor Vol., % Stg 1/Stg 2	100/100, 50/50	50/50	50/50	100/75, 75/100	100/100	50/50
Catalyst Configuration	Cat/Cat	Th/Cat	Cat/Cat	Th/Cat, Cat/Th	Cat/Cat	Th/Cat, Th/Th
Temperature Configuration	High/Low	High/Low	High/Low	High/Low, Low/High	Low/High	High/Low
Interstage Separation	No	Yes	Yes	Varied	Yes	Yes
Temp. In Stage 1, °F	760-810	825-865	810-825	775-840	790-810	825
Temp. In Stage 2, °F	760-805	740-790	760-790	775-805	800-825	760-810
Stage 1 Catalyst ^{**}	Am 1C	None	Am 1C, Sh 324	None, Sh 324	EXP, Cr 324	None
Replace. Rate, lb/T MF Coal	0-3	-	0-4	3	0-3	-
Stage 2 Catalyst ^{**}	Am 1C	Sh 324	Am 1C, Sh 324	Sh 324, None	EXP, Cr 324	Cr 324, -
Replace. Rate, lb/T MF Coal	0-3	0-3	0-4	3, -	0-3	3, -
Thermal Stage Space Vel., lb MF Coal/hr/ft ³ , (C=Constant)	-	51C-78C	-	31C-43C	-	64C-92C
Catalytic Space Vel., Stg 1/Stg 2, lb feed/hr/lb cat.	3.7-6.7/ 3.7-7.0	-/3.6-5.7	1.8-6.8/ 1.7-6.5	-/3.1-3.9, 2.8-4.0/-	2.9-6.4/ 2.6-6.0	-/4.7-6.6, -/-
Stage 1 Catalyst Age, lb (Resid + Solids)/lb cat.	926-2308	-	895-1918	1415-1497	1324-2812	-
Stage 2 Catalyst Age, lb (Resid + Solids)/lb cat.	727-2314	415-3452	718-2710	1330-1368	1090-2238	1315-1545
Slurry Catalyst and Feed Rate: Fe ₂ O ₃ , wt % MF Coal	0	2	0	2	0	2
Molyvan L, Mo ppm of MF Coal	0	0	0	0	0	100-1000
Coals are: Black Thunder and Spring Creek (subbituminous), and Burning Star 2 and Ireland (bituminous). **Catalysts are: Amocat 1C, Shell 324, Criterion 324, and EXP-AO-60.						

Table 2. Comparison of CONSOL and Wilsonville Resid Concentrations in Wilsonville Pasting Solvent (V-131B)

Wilsonville Run	Reactor Volume Used, % (1st/2nd Stage)	Resid in V-131B Pasting Solvent, wt %		Fraction of 1050°F ⁺ in 850°F ⁺ (Wilsonville wt %/CONSOL wt %)
		Wilsonville	Difference (CONSOL-Wilsonville)	
Run 262	50/50	37.2 $\pm$ 2.9	12.5 $\pm$ 2.0	0.75 $\pm$ 0.03
Run 261	100/100	43.3 $\pm$ 6.7	18.5 $\pm$ 3.5	0.70 $\pm$ 0.07
Run 260	100/75 (A-C), 75/100 (D-F)	39.4 $\pm$ 0.8	15.2 $\pm$ 3.4	0.72 $\pm$ 0.05
Run 259	50/50	47.4 $\pm$ 4.1	13.4 $\pm$ 1.7	0.78 $\pm$ 0.02
Run 258	50/50	40.8 $\pm$ 0.4	7.1 $\pm$ 1.5	0.85 $\pm$ 0.03
Run 257	100/100, 50/50	46.0 $\pm$ 4.8	19.1 $\pm$ 4.9	0.71 $\pm$ 0.07
257A-257H	100/100	45.7 $\pm$ 4.9	21.9 $\pm$ 1.2	0.67 $\pm$ 0.03
257I-257K	50/50	46.8 $\pm$ 5.4	11.7 $\pm$ 0.4	0.80 $\pm$ 0.02

Table 3. Catalyst Deactivation Rate Calculation For Wilsonville Run 258

Period	Cat. Age, lb (Resid+Cl)/lb Cat.	First Stage A, 10 ⁷	Second Stage A, 10 ⁷
K	559	1.84	3.75
L	1130	1.36	2.22
M	1314	1.57	2.16
Equilibrated (Avg. B, C, D, E, F, H, I)	2523 $\pm$ 84	1.81 $\pm$ 0.43	1.05 $\pm$ 0.61
First Stage: $\alpha = 0.30 \times 10^{-4}$, $\sigma(\alpha) = 1.17 \times 10^{-4}$, $A' = 1.56 \times 10^7$, $\sigma(A') = 1.18$, $R^2 = 0.03$ Second Stage: $\alpha = -6.2 \times 10^{-4}$, $\sigma(\alpha) = 0.06 \times 10^{-4}$, $A' = 4.96 \times 10^7$, $\sigma(A') = 1.09$, $R^2 = 0.98$ Note: Units of A' are lb total feed/hr/lb cat, units of α are lb Cat./lb (Resid + Cl).

Figure 1. Block Diagram of Wilsonville Liquefaction Plant

Figure 2. Ratios of Total CONSOL and Wilsonville Resid + UC Conversions for CC-ITSL Runs

Figure 3. Catalyst Activity Plot For Wilsonville Run 258

Figure 5. Conversion of Resid Components in Selected Wilsonville CC-ITSL Runs.

APPENDIX 5

THE CHEMICAL NATURE OF COAL LIQUID RESIDS AND THE IMPLICATIONS FOR PROCESS DEVELOPMENT

S. D. Brandes, R. A. Winschel, F. P. Burke
CONSOL Inc.
Research & Development
4000 Brownsville Road
Library, PA 15129

Key words: coal liquids, resid

INTRODUCTION

The informational needs for the advancement of direct coal liquefaction process development include the knowledge to choose the appropriate analytical tools. CONSOL Inc. is working with a number of research groups to evaluate various methods for analyzing direct coal liquefaction process-derived samples.¹ Each individual method was applied to process-derived samples and the advantages (and some drawbacks) for each have come to light.²⁻⁸ The large database accumulated in the study may be useful in choosing analytical methods for process development and design of facilities. This paper will explore the usefulness of these data for that purpose by examining a few specific examples.

Close-coupled integrated two-stage direct coal liquefaction, on a pilot plant scale, is a continuous, multi-step operation. The process steps include mixing feed coal with recycled coal liquid to form a slurry; thermal and/or catalytic liquefaction of the coal in the slurry; stripping of the light, high-value products; and recycling of the heavy residues to near extinction. The coal concentration in the feed slurry is typically 30 wt %. The slurry oil consists mostly of relatively high molecular weight material (resids) and some light distillable materials. Each process stream, with the exception of the distillation column overheads, also is comprised of 50% or more of non-distillable (850°F⁺) resid. Because of the preponderance of the resid in the system, and its influence on the overall properties of the process streams, the program described above was directed to the study of these materials.

RESULTS AND DISCUSSION

The results of the analyses of six 850°F⁺ distillation resid samples, obtained from two process runs (Run 257⁹ and Run 259¹⁰) conducted at the Wilsonville Advanced Two-Stage Direct Coal Liquefaction facility, will be used to demonstrate the potential usefulness of these data for process development. Each of the samples are composites of many daily samples obtained over the length of the liquefaction test. These tests lasted for a number of months and included numerous changes in operating conditions. The feed to Wilsonville Run 257 was Illinois No. 6 coal from Burning Star No. 2 Mine and the feed to Run 259 was Pittsburgh seam coal from Ireland Mine. The resid from Run 259 was notably more difficult to convert to distillate products, based on Wilsonville operating results. Both runs were carried out with catalyst in both reactors. Both runs operated, for the most part, with the first of the two reactors at a higher temperature than the second reactor. Samples were obtained from three locations in the plant (Figure 1): between the two reactors (Interstage), after the second reactor but before the deasher (2nd Stage Product), and at the vessel used to accumulate different process flows, to form the slurry solvent that is recycled back through the system (Recycle). Samples obtained from these different locations during a single run are expected to represent different degrees of coal conversion in the direct liquefaction process. The samples analyzed were the 850°F⁺ distillation resids of these three process streams, and, in some cases, the tetrahydrofuran-soluble portion of the resids.

The analyses performed by CONSOL on the samples include elemental analyses, proton NMR (and classification of the proton signal into defined groups), and determination of phenolic -OH by Fourier transform infrared spectroscopy (FTIR). Pyrolysis and subsequent detection and analysis of the pyrolysate by thermogravimetric (TG)-FTIR, fluorescence microscopy, reflectance microscopy, field ionization mass spectrometry (FIMS), and various separation techniques, including liquid chromatography were performed by Advanced Fuel Research,⁷ University of Kentucky,⁴ The Pennsylvania State University,³ SRI International,⁵ and Virginia Polytechnic and State University,² respectively.

Table 1 presents the elemental analyses of the six composite resid samples and the parent coals. It is readily apparent that the hydrogen content is increased and the heteroatom content is decreased in the resid as the coal slurry proceeds through the liquefaction process. Also given in Table 1 are the phenolic -OH contents of the tetrahydrofuran (THF)-soluble portion of each resid. Figure 2 shows that the phenolic -OH contents, determined by FTIR, correlate relatively well with the yield of the most polar liquid chromatography fraction of the THF-soluble portion of resids.² The data presented in Figure 2 were obtained from a number of resids obtained from different liquefaction runs made at different facilities, including Runs 257 and 259 made at Wilsonville.

The TG-FTIR results, presented in Table 2, show a reduction in gas make in the pyrolysis of the resids with a corresponding increase in tar yield as the coal is converted in the liquefaction system. The remaining ~2 to ~10% of the resid, not accounted for in these analyses, is converted to additional gases (NH₃, COS) and light hydrocarbons, such as C₂H₄ and benzene. It is notable that the resids produced in the Illinois No. 6 coal run generate a much larger proportion of these volatile materials and more tar than the resids produced from the Pittsburgh seam coal resid. The char yields from the distillation resids correlate with the phenolic -OH content of the THF-soluble portion of the resid, which, as discussed above, correlates to the very polar material found in the resid.

The proton NMR data for the THF-soluble portions of the resids (Table 3) are divided into five spectral regions corresponding to five proton types. These types are condensed aromatics, uncondensed aromatics, alpha protons, beta protons, and gamma protons. The condensed aromatic component of the Run 257 resids decreases from interstage to second-stage product samples and is relatively unchanged in the recycle stream by partial deashing. The increase in aromaticity from recycle to interstage samples comes about from the addition of fresh feed coal to the slurry which is then liquefied in the first reactor. The conversion of the 850°F resid in each stage of the liquefaction process is not the same; it was approximately two times greater in the first stage than in the second stage for Run 257, and about 1.5 times greater in the first stage than the second stage in Run 259. Nonetheless, it is concluded that for Run 257, the aromatic coal structure is broken down in the first stage of the liquefaction system with little additional change of aromaticity in the second reactor. The liquefaction process conditions in Run 259 were more severe than in Run 257 (higher temperature, lower space velocity) and the rejection of resid in the deasher was lower. This accounts for the total aromaticity being higher in the Run 259 samples. However, within Run 259, an interesting trend is seen. The percent of condensed aromatic protons decreases and that of the uncondensed aromatic materials increases sequentially from the interstage to second stage product to recycle resid. This indicates that the process stream (which is mostly resid) is being converted to less-condensed aromatic moieties, but the unconverted resid is not being saturated. This is supported by a number of other analyses. For example, total volatile material of the resids (100% char) determined from the TG-FTIR experiment is essentially the same as the percentage of uncondensed aromatic protons for each sample from Run 257. However, for the Run 259 samples, there is

a large increase observed for total volatiles and uncondensed aromatic protons in the recycle sample.

Microscopy proved to be a useful technique in the examination of the resids, which are solid at room temperature. It was possible to distinguish different petrographic components in the samples that are related to the extent that the coal slurry had reacted. Point counts and mean random reflectance measurement were made of three components: the high-reflecting vitroplast, the partially reacted vitrinite, and the low-reflecting vitroplast. Values for the interstage and recycle materials in this example data set are given in Table 4. The concentration of low-reflecting vitroplast is higher for the interstage samples than the recycle samples in both Runs 257 and 259. However, for the recycle samples, its concentration is considerably lower in Run 259 than in Run 257. This indicates that across the second stage reactor and deasher, the Pittsburgh coal resid is less upgraded than the Illinois coal-derived materials, and may, in fact, be undergoing retrogressive reactions. This supports the NMR results described above.

Fluorescence microscopy^{4,11} provides a great deal of qualitative information and some quantifiable values including the wavelength of maximum fluorescence (L_{max}) and the fluorescence intensity at L_{max} . It is possible to relate the intensity and the wavelength at L_{max} to the relative degree of aromaticity, and thus to the relative reactivity of the material; the lower the intensity and the longer the wavelength, the higher the aromatic concentration and therefore the lower the reactivity. Resids from Run 257 were found to contain two distinct populations; values of L_{max} and intensity are given in Table 5 for both. Comparison of samples from Run 257 (either population) and Run 259 (Table 5) shows the intensity of the Run 259 interstage sample is relatively low and the L_{max} is high (approaching 700nm). This suggests that the interstage resid from Run 259 is comprised of a more-condensed aromatic structure than the Illinois No. 6 interstage resid and it is thus inferred to be less reactive. The recycle resid samples follow the same trend; the Run 259 sample is also more aromatic and is inferred to be less reactive. Another quantifiable value is the quotient of the fluorescence intensities measured at 700nm (red) and 525nm (green). These red:green quotients (Q) can be used to assess the variability of the fluorescence properties within a heterogeneous sample. A shift to longer wavelengths (red) indicates a more extended pi-bond conjugation or a larger proportion of condensed aromatics. The red:green quotients usually are reported as histograms. Figure 3 shows the histograms for the Runs 257 and 259 interstage and recycle resid samples. The Run 259 samples exhibit much higher proportion of the material at higher Q values than the Run 257 samples. This is consistent with the ¹H-NMR data where ~20% of all protons are aromatic in the Run 257 recycle sample and ~32% are aromatic in the Run 259 recycle sample. Across the second-stage reactor (and including the part of the process stream that has been deashed), there is a considerable shift of the fluorescence of the material to the green (or shorter wavelength, lower aromaticity) in Run 257, but not in Run 259. This may help explain the greater propensity of the Run 259 resids to form char in the TG-FTIR experiments.

FIMS data and their interpretation for these samples have been presented elsewhere.¹² Because of a distinct bimodality, the FIMS profiles of the distillation resids were deconvoluted into two overlapping components, A and B. Component A represents a molecular weight (m/e) range centered at approximately 350 Da, component B is centered around 600 Da. The relative weight fractions of A and B were used to compare the resid samples. Table 6 presents the weight percent of component A for each of the six samples obtained from both the even- and odd-mass FIMS profiles. In agreement with the data discussed above, the concentration of component A in the Run 257 resid almost doubles as the coal slurry passes through the first-stage reactor indicating that the molecular weight of the resid was

reduced in the first-stage reactor. As discussed above, conversion of the resid in the first-stage reactor was approximately twice that of the second-stage reactor for Run 257, and correspondingly the concentration of component A in the second-stage product sample increases from the interstage sample, but is only about 1.5 times that of the interstage sample. In comparison, Run 259 interstage and second-stage samples are less enriched with lower molecular weight material. The concentration of low molecular weight material decreases across both the first-stage and second-stage reactors. It increases in the recycle sample only after part of the second-stage product stream passes through the deasher where high molecular weight materials are rejected along with the ash.

SUMMARY AND CONCLUSION

To briefly summarize the information presented above; relative to the Illinois No. 6 resids, the Pittsburgh seam resids are less hydrogenated, higher molecular weight, less fluorescent and they produce fewer volatiles upon pyrolysis. In addition, the Pittsburgh seam resids are more phenolic, more aromatic and contain more nitrogen. These characteristics are consistent with the lower observed reactivity of the Pittsburgh seam resids, which must have arisen from a combination of the coal and operating conditions. The NMR, FIMS and TG-FTIR data indicate that in Run 257, the upgrading of Illinois No. 6 coal to lower molecular weight, more volatile, less aromatic materials was primarily achieved in the first stage of the two-stage system. Additionally, reflectance microscopy data show that the resid derived from the Illinois No. 6 coal in the first-stage reactor is more upgraded in passing through the second-stage reactor and deasher than the Pittsburgh seam coal first-stage resid. Phenolic -OH determinations made on the THF-soluble portion of the distillation resids correlate with the amount of very polar fraction isolated from the resids by liquid chromatography and also with the char yield from the TG experiments. Fluorescence microscopic examination of the resids leads to inferences of resid reactivity. These inferences are supported by the other data. It is apparent that no single method fully describes process derived materials; however, the trends observed by any one method are generally mimicked in the response of the other methods. The implication for process development is that the choice of methodology for analytical use, among these methods tested, can be determined by the requirements of the process developer based on such factors as cost, time, or frequency of measurement.

ACKNOWLEDGEMENT

This work was funded by the U.S. Department of Energy under contract No. DE-AC22-89PC89883.

REFERENCES

1. Brandes, S. D.; Winschel, R. A.; Burke, F. P. "The Application of Advanced Analytical Techniques to Direct Coal Liquefaction," Am. Chem. Soc., Div. Fuel Chem. Preprints, 1991, 36(3), 1172.
2. Taylor, L. T.; Hellgeth, J. W.; Sequeira, A. "Coal Liquefaction Process Streams Characterization and Evaluation; Analysis of Coal Liquefaction Process Streams by Chromatographic and Spectroscopic Techniques, Topical Report," DOE/PC 89883-41, January 1992.
3. Mitchell, G.; Davis, A. "Coal Liquefaction Process Streams Characterization and Evaluation; Gold Tube Carbonization and Reflectance Microscopy, Topical Report," DOE/PC 89883-37, December 1991.
4. Rathbone, R. F.; Hower, J. C.; Derbyshire, F. J. "Coal Liquefaction Process Streams Characterization and Evaluation; Novel Analytical Techniques for Coal Liquefaction: Fluorescence Microscopy, Topical Report," DOE/PC 89883-30, October 1991.

TABLE 2
TG-FTIR ANALYSES OF 850°F⁺ DISTILLATION RESIDS⁷

TG Yield (wt% daf)	Run 257			Run 259		
	Interstage	2nd Stage	Recycle	Interstage	2nd Stage	Recycle
Tar	70.48	69.90	73.49	65.00	65.56	67.07
Gas ^(a)	4.85	4.32	3.71	5.59	3.89	3.61
Char	17.50	15.88	14.15	27.80	28.39	22.88
Unaccounted	7.17	9.90	8.65	1.61	2.16	6.44

(a) Gas = CH₄+CO+CO₂+SO₂

TABLE 3
PROTON NMR ANALYSES OF THF-SOLUBLE PORTION OF 850°F⁺ RESIDS^{9,10}

Proton Type (wt%)	Run 257			Run 259		
	Interstage	2nd Stage	Recycle	Interstage	2nd Stage	Recycle
Condensed Aromatic	18.1	16.9	16.8	30.7	27.8	26.1
Uncondensed Aromatic	3.7	3.4	3.1	2.6	3.8	5.4
Alpha	28.8	28.6	28.0	31.1	30.8	28.3
Beta	39.1	40.5	41.4	27.2	28.9	30.4
Gamma	10.4	10.7	10.6	8.4	8.7	10.8

TABLE 4
NORMALIZED CONCENTRATION OF PETROGRAPHIC COMPONENTS^(a)
OF 850°F⁺ DISTILLATION RESIDS³

Component, %	Run 257		Run 259	
	Interstage	Recycle	Interstage	Recycle
Low-Reflecting Vitroplast	78.0	73.5	79.0	63.5
Partially Reacted Vitrinite ^(b)	0.5	0.0	0.5	0.5
High-Reflecting Vitroplast	21.5	26.5	20.0	36.0

(a) 200 reflectance measurements made on each sample

(b) unreacted coal

TABLE 5
WAVELENGTH AND INTENSITY OF MAXIMUM FLUORESCENCE
OF 850°F⁺ DISTILLATION RESIDS⁴

	Run 257		Run 259	
	Interstage	Recycle	Interstage	Recycle
Fluorescence Spectrum Maximum, $L_{\max}$, nm	646 ^(a) /604 ^(b)	633 ^(a) /585 ^(b)	696	696
Intensity at $L_{\max}$, counts	6714/12666	9284/32108	6658	8497

(a) Population 1

(b) Population 2

TABLE 6
wt % COMPONENT A OF 850°F⁺ RESIDS
FROM EVEN- AND ODD-MASS FIMS PROFILES⁵

Weight %	Run 257			Run 259		
	Interstage	2nd Stage	Recycle	Interstage	2nd Stage	Recycle
A Even	22.4	32.0	13.1	13.7	9.2	18.5
A Odd	7.9	12.9	4.3	4.0	2.2	6.3

Figure 1. Simplified Flow Scheme Generic Integrated Two-Stage
Direct Coal Liquefaction Unit.

Figure 2. Phenolic -OH Concentration vs Yield of Liquid Chromatography Polar Fraction (F4).²

Figure 3. Red: Green Quotient Histograms for Run 257 and Run 259.⁴

APPENDIX 6

STRATEGIC CONSIDERATIONS OF COAL LIQUID REFINING

P.-Z. Zhou, J.J. Marano (Burns and Roe Services Corp.)
R.A. Winschel (CONSOL, Inc.)

The development of the two-stage coal liquefaction process over the past decade has resulted in remarkable improvements in process efficiency, including increased liquid yield, better product quality, improved hydrogen efficiency, and dramatic reduction in production costs. At this stage in liquefaction development, serious consideration should be given to the refining of coal liquids into marketable transportation fuels.

PROPERTIES OF COAL-DERIVED LIQUIDS

Properties of coal liquids representative of various single-stage and two-stage liquefaction (TSL) processes were compiled in a comprehensive review [Zhou and Rao, 1992]. The major differences between current two-stage liquefaction coal liquids and those from earlier processes are the higher hydrogen and lower heteroatom contents of the former. TSL liquids are usually richer in middle distillates than are single-stage liquids, probably due to the lower hydrogenation severity of the two-stage processes which leads to the lower hydrogen consumption and higher liquid yields.

Coal liquids produced from coals of the same rank under similar conditions are quite similar in properties. For coal liquids obtained from bituminous coals, the hydrogen content is high, in the range of 11.3-12.2 wt%; and heteroatom contents are low: 0.1- 0.3 wt% nitrogen, less than 0.1 wt% sulfur, and 1-2% oxygen [Lee et al. 1991]. Liquid products from lower-rank coals are characterized by more oxygen and higher paraffinicity than bituminous coal liquids. The subbituminous Black Thunder coal liquids have a greater concentration of normal paraffins, olefins, and phenols than Pittsburgh seam coal liquids [Robbins et al. 1992].

As complex mixtures of hydrocarbons and hetero-compounds, coal liquids and petroleum exhibit many fundamental similarities; therefore, coal liquids can be refined into liquid transportation fuels by current petroleum refining technologies. Extensive research on coal-liquid refining done by Chevron, UOP, and Exxon demonstrated that environmentally clean, quality liquid fuels, can be produced from coal liquids. Modern TSL liquids, however, have a lower boiling range than petroleum, with an end point around 427°C, and are free of residual materials and metals. The H/C ratio of TSL liquids falls within the H/C range of crude oils, although at the lower end, reflecting the cyclic nature of coal liquids. Coal liquids have very low sulfur contents, moderate nitrogen contents, and relatively high oxygen contents. These unique features of coal liquids require somewhat different refining strategies than those conventionally used for the refining of petroleum.

Oxygen compounds in coal liquids are concentrated in the 175-315°C boiling range, with a peak at 230°C [Pauls et al. 1990]. For Black Thunder coal liquid, 3.6 wt% of the naphtha (IBP - 193°C) and 10 wt% of the 193-266°F fraction are phenolic compounds and can be extracted easily by caustic washing [Burke et al. 1991]. This naphtha phenolic extract contains phenol, cresols, xylenols, ethyl phenol, methylethyl-phenol and propyl-phenol [Robbins et al. 1992].

Some coal liquids produced recently at Wilsonville are characterized in Table 1. Tables 2 through 4 compare the properties of respective fractions of these coal liquids with corresponding specifications for gasoline, jet fuel, and diesel fuel.

HYDROPROCESSING -- THE MAJOR TOOL FOR COAL-LIQUID REFINING

Based on the characteristics of coal liquids, hydroprocessing is obviously the most important refining technology for coal-liquid upgrading. Coal liquefaction is a hydrogenation process, and coal-liquid refining can be envisioned as an extension of the coal-to-liquid fuel conversion process. The hydrogenation conditions in the liquefaction step determine the yield and properties of the coal liquids produced, which in turn dictate the extent of upgrading required for coal-liquid fuel production.

Current liquefaction practice is to recycle resids to extinction to produce a total distillate product with an end point in the range of 370-427°C. With improved liquefaction operation, it is possible to lower the end point further to around 350°C, as suggested by some authors [Zhou and Rao, 1992]. This is particularly advantageous to the downstream refining facility which may have limited cracking (either catalytic or hydrocracking) capacity, and provides the added benefit of confining the toxicologically active polycyclic aromatic hydrocarbons within the boundary of the liquefaction plant. In fact, Exxon's new liquefaction process is generating 350°C- coal liquids, which make a naphtha plus distillate product slate [Stuntz 1991].

Hydroprocessing, e.g. hydrotreating and hydrocracking, of coal liquids is highly versatile in that the extent of hydrogenation can be adjusted to produce different product slates (maximum gasoline or maximum distillate) as well as product quality (primarily aromatics content).

UTILIZATION OF EXISTING PETROLEUM REFINERY INFRASTRUCTURE

It appears to be more realistic to consider the co-refining of coal liquids with petroleum in an existing petroleum refinery rather than in a grass-roots, dedicated coal-liquid refinery.

Coal liquids can be introduced into a refinery either as a single feed or as previously fractionated individual cuts. The unique properties of coal liquids warrant a different refining strategy than that for petroleum. Mixing the total coal liquid with petroleum would eliminate many possible refining schemes suitable for each of these two feedstocks. More flexibility in processing can be achieved if coal liquids are distilled in the liquefaction plant and individual fractions are introduced into the refinery at points where their properties are most compatible with petroleum counterparts.

Much work has been done on the hydrotreatment of total coal liquids; however, evidence shows that hydrotreating the individual naphtha, kerosene, and diesel fractions is advantageous from a product-quality standpoint. For example, jet fuels with higher smoke points may be obtained by hydrotreating the respective fractions rather than the total coal liquid [Sullivan 1987b, Zhou and Rao 1992]. Depending on the coal liquid properties, the product slate, and the refinery infrastructure, coal liquid fractions may be hydroprocessed together with or separately from their petroleum counterparts.

REFINERY LINEAR PROGRAMMING

Linear programming (LP) techniques are used routinely within the refining industry to evaluate the economics of petroleum processing. Linear programming can also be applied to coal liquids to determine their value as refinery feedstocks. LP is potentially a very powerful tool since the products from most liquefaction processes are intermediates which must be further upgraded or blended with petroleum-derived intermediates to meet product specifications. Thus, LP allows the effects of variations in yields and quality between different liquefaction operations to be quantified, and can provide a benchmark for comparing and ranking different coal liquid products.

The effect of feeding coal-liquid fractions to a refinery is being studied with the linear programming technique and preliminary results are reported here. The LP model used in this study was developed by Bechtel, Inc. as part of the DOE-funded Direct Liquefaction Baseline Design project [Bechtel, work in progress]. It is a model of the typical midwestern U.S. refinery, producing the average U.S. midwest product slate. Incremental quantities of different coal-liquid cuts are introduced into the refinery model, which calculates the effect of each cut on refinery net profit. In general, liquids produced by direct liquefaction are found to be more valuable than crude petroleum. The results reported here are expressed as a coal liquid premium defined as the percentage difference between the value of the coal liquid and the price of crude oil.

GASOLINE PRODUCTION FROM COAL NAPHTHA

Coal-liquid naphthas are similar to the naphtha fraction from a naphthenic crude oil. Data in Table 2 show that the oxidation stability, caused by heteroatoms (mainly oxygen), and lack of light ends are the two major problems in the manufacture of gasoline from coal liquids. Coal naphtha, however, has a high octane number and low aromatics content and is an ideal source for gasoline production. The clear motor octane of coal naphthas is in the range of 76-83 [Lhou and Rao, 1992]. The aromatics content of coal naphthas from recent TSL runs, contrary to conventional views, are fairly low (7-13 vol%), and the naphthene content is very high (60-70 vol%), as shown in Table 2. It is an excellent reformer feedstock to make gasoline components with a research octane number above 105 [Sullivan 1987b], which is attractive at the present time. However, conversion of naphthenes to aromatics by catalytic reforming may no longer be advisable due to provisions in the U. S. Clean Air Act Amendments. A cost-effective means of gasoline production from coal naphthas is to maintain the current level of naphthenes, which have fairly high octane numbers, and improve the oxidation stability of the coal naphtha via mild hydrotreating to remove the heteroatoms. Isomerization of light coal naphtha is also a promising option. Volatility requirements can be easily remedied by blending.

LP studies show that for a refinery not deficient in high-octane gasoline blendstocks, this scheme results in a premium for coal naphtha of 12% over the price of crude oil. Under the assumptions used in the calculation, straight blending of the hydrotreated coal naphtha is preferable to catalytic reforming which has a premium of 6.5%. This difference is due primarily to the loss of volume which occurs during reforming. In this study, the refinery product slate was assumed to be unchanged. Further studies are planned to explore various scenarios in which the refinery infrastructure and product slate are modified to take best advantage of coal liquid potentials. Higher premiums are anticipated.

PHENOLICS EXTRACTION

Since oxygen is the major heteroatom found in coal liquids, hydrogen used for oxygen removal during hydrotreating accounts for the major part of hydrogen consumption. The oxygen compounds in the 232°C- fraction are mostly single-ring phenolics, which can be easily extracted by caustic washing.

A promising approach is, therefore, to extract these phenolics before hydrotreating as chemicals by-product. Preliminary work indicated that this has good potential for raising the coal-liquid premium for the naphtha fraction.

JET FUEL PRODUCTION

As illustrated in Table 4, the coal-derived kerosene fractions have lower hydrogen contents than do naphthas from the same source. This follows the general trend that hydrogen content decreases with increasing boiling point. The hydrogen level of the coal-derived kerosene fraction is low compared with that of petroleum-derived jet fuels (H 13.5-14.0 wt%), and is a reflection of its high aromatics content, typically around 50%. As a result, the API gravity and smoke point, two major properties for jet fuels, are much lower than specifications.

The jet fuel fraction obtained from an EDS distillate by hydrotreating do not meet gravity and smoke point specifications [Erwin and Sefer 1989]. It was reported, however, that through appropriate hydrotreatment smoke points of at least 20 mm can be obtained for jet fuels from Illinois No. 6 coal liquids (aromatics content 10 vol% or lower) and for jet fuels from Wyodak coal liquids (aromatics content about 15 vol%) [Sullivan 1987a]. Hydrocracking appears to be a more efficient way of making specification jet fuels from coal liquids [Sullivan and O'Rear 1981]. In essence, this is a matter of the depth of hydrogenation. Jet fuels with no aromatics and no sulfur can be produced and meet all of the current ASTM specifications for jet fuel [Stuntz 1991].

Due to the compositional uniqueness, traditional density specification is more difficult to meet than smoke point for coal-derived jet fuel fractions, which comprise largely two-ring cycloparaffins. However, the high naphthene content of coal liquids makes them a remarkable feedstock for manufacturing high-density, high-energy jet fuels, a range-extender for high-mach aircrafts. More work is required in this area.

DIESEL FUEL PRODUCTION

With an even lower hydrogen content than the kerosene fraction, the coal-derived middle distillates have low cetane numbers, usually in the twenties. Upgrading of the middle distillates is necessary to increase the hydrogen content and remove hetero-compounds. However, saturation of a large part of the aromatics in the diesel fuel fractions may not be justified economically, and the use of multi-purpose additives may be advisable [Sefer and Erwin 1989]. The coal-derived diesel fuel does show good susceptibility to ignition improvers [Sullivan et al. 1981].

With all the aromatic hydrocarbons in coal diesel fractions saturated, a zero-aromatics, zero-sulfur diesel fuel is made by Exxon, which has a cetane value in the 42-53 range and considerably reduced particulate emissions relative to a typical petroleum diesel fuel [Stuntz 1991].

Initial LP work indicates that low-severity hydrotreating results in a diesel blendstock with a premium of about 4% over crude oil. A better premium may be possible by adjusting the cut points of this fraction.

CRACKING

Coal-derived middle and heavy distillates can be cracked, either by catalytic cracking or hydrocracking, to boost yields of gasoline or light distillate fuels. In order to be a good cat-cracker feedstock comparable to petroleum feedstocks, coal distillates must be hydrogenated to a 11.5-12.0 wt% hydrogen content [Riedl and deRosset 1980].

A decision on whether the hydrotreated middle distillate should be used as a diesel fuel blending stock or subjected to catalytic cracking should be based largely on economic considerations. Product slate constraints, however, will probably dictate that a certain part of the middle distillate should be blended to diesel fuel and the rest cracked to generate gasoline blending components. Heavy distillate or vacuum gas oil, if produced by the liquefaction plant, should be cracked. Hydrocracking of coal-derived heavy distillates can produce quality gasoline, jet, and diesel fuels. The choice between catalytic cracking and hydrocracking depends on the refinery infrastructure. The mode of operation for the hydrocracker, all-gasoline mode or maximum-jet-fuel mode, depends on refinery economics. Further LP work is under way to study this and other related options.

CONCLUSION

Coal liquids can be refined by modern refining technologies, primarily hydroprocessing, into specification transportation fuels. Mild hydrotreatment of coal naphtha to produce a gasoline blendstock is preferred over catalytic reforming in the long run. The middle distillate can be hydro-upgraded into high-density jet fuel or diesel fuel with the use of an appropriate additive package. Heavy distillates may be cracked to boost gasoline yield. By adjusting the depth of hydrogenation, zero-aromatics liquid fuels can be obtained with high quality. A high degree of product slate flexibility is possible with coal-liquid refining. Suitable refining strategies will result in a considerable premium for coal liquids over the price of crude oils. More research is recommended on coal-liquid characterization, including detailed analysis and development of correlations for property prediction; and on coal-liquid processing, including experimental and LP studies.

ACKNOWLEDGEMENT

This work was sponsored by the U.S. Department of energy (DOE), Pittsburgh Energy Technology Center (PETC), in part under Contract No. DE-AC22-89PC89883 (CONSOL) and in part under Contract No. DE-AC22-89PC88400 (BRSC). Special thanks go to Mr. S.R. Lee (DOE/PETC) for his support and comments on this paper.

REFERENCES

- Bechtel, Inc. work in progress. "Direct Coal Liquefaction Baseline Design and System Analysis," DOE Contract DE-AC22-90PC89857.
- Burke, F.P.; Winschel, R.A.; Robbins, G.A.; and Brandes, S.D. 1991. CONSOL Project Status Report under DOE Contract DE-AC22-89PC-89883, November 6, 1991.
- Erwin, J., and Sefer, N.R. 1989. "Synthetic Fuels from Coal-Derived Distillate as Jet Fuels for High Mach Aircraft," presented at ACS Meeting, Div. Petrol. Chem. September 10-15, 1989. Miami Beach, FL.
- Kramer, R.L. 1991. Conoco Research Report No. 6210-0003-T000-1-91, August 1991.
- Lee, J.M.; Cantrell, C.E.; Gollakota, S.V.; Davies, O.L.; Corser, M.M.; and Vimalchand, P. 1991. Prep. ACS National Meeting, Div. Fuel Chemistry, August 25-30, 1991. New York, N.Y. 36 (4), 1985.
- Pauls, R.E.; Bambacht, M.E.; Bradley, C.; Scheppele, S.E.; and Cronauer, D.C. 1990. Energy & Fuels, 4, 236.
- Riedl, F.J., and DeRosset, A.J. 1980. "Hydrotreating and Fluid Catalytic Cracking of SRC-II Process Derived Gas Oils," UOP Interim Report, DOE Contract No. EF-77-C-01-2566, July 1980.
- Robbins, G.A.; Brandes, S.D.; Winschel, R.A.; and Burke, F.P. 1992. CONSOL, Quarterly Technical Progress Report, Oct. 1 - Dec. 31, 1991. DOE Contract No. DE-AC22-89PC89883.
- Southern Electric International, Inc. 1991. "Advanced Coal Liquefaction Research Facility, Wilsonville, Alabama. Technical Progress Report, Run 258 with Subbituminous Coal," DOE Contract No. DE-AC22-82PC50041. May 1991.
- Stuntz, G.F. 1991. "Premium Products from Direct Coal Liquefaction," presented at Alternate Energy '91, April 16-19, 1991. Scottsdale, AR.
- Sullivan, R.F. 1987a. "High-Density Jet Fuels from Coal Syncrudes," presented at the Symposium on Structure of Future Jet Fuels, Div. Petroleum chemistry, ACS Meeting, April 5-10, 1987. Denver, CO.
- Sullivan, R.F. 1987b. "Refining and Upgrading of Synfuels from Coal and Oil Shales by Advanced Catalytic Processes," Final Report, prepared for USDOE, Contract No. DE-AC22-76ET10532, May 1987.
- Sullivan, R.F.; O'Rear, D.J.; and Frumkin, H.A. 1981. "Converting Syncrudes to Transportation Fuels," presented at 1981 Fuels and Lubricants Meeting, NPRA, November 5-6, 1981. Houston, TX.
- Vimalchand, P.; Lee, J.M.; Gollakota, S.V.; Davies, O.L.; Cantrell, C.E.; and Corser, M.M. 1991. "Recent Developments in Coal Liquefaction at Wilsonville Facility," presented at 16th Annual EPRI Conference, June 18 - 20, 1991. Palo Alto, CA.
- Winschel, R.A., and Zhou, P. 1991. "Inspection of Integrated Two-Stage Liquefaction Products by Petroleum Assay," presented at 16th Annual EPRI Conference on Fuel Science, June 16-21, 1991. Palo Alto, CA.
- Zhou, P.-Z., and Rao, S.N. 1992. "Assessment of Coal Liquids as Refinery Feedstocks," prepared for U.S. DOE/Pittsburgh Energy Technology Center, DOE Contract No. DE-AC22-89PC88400.

TABLE 1
PROPERTIES OF WILSONVILLE TWO-STAGE LIQUIDS

Coal	Spring Creek	Pittsburgh Seam	Black Thunder	Illinois No. 6
Gravity, °API @15°C	16.2-18.3	27.7	23.9	24.5
Elemental				
Carbon, wt%	86.2-86.9	86.9	87.4	87.2
Hydrogen, wt%	10.9-11.3	11.55	11.2	11.8
Sulfur, wt%	0.05-0.10	0.05	0.05	0.02
Nitrogen, wt%	0.40-0.52	0.1	0.3	0.22
Oxygen, wt% (diff)	1.36-2.21	1.4	1.10	0.76
H/C Atom Ratio	1.51-1.58	1.59	1.54	1.62
V, Ni, Fe, Cu, ppm	-	<4.5	<25.0	-
Characterization Factor	-	10.9	10.9	-
Ash, wt%	-	0.002	0.01	-
Conradson Carbon, wt%	-	0	0	-
Pour Point, °C	-	-59	-26	-
Bromine Number, g/100g	-	8	14	-
Aniline Point, °C	-	23.8	-	-
Kin. Viscosity, cSt, @38°C	-	2.1	3.1	-
Phenolic-OH Conc., meq/g	-	0.18	-	-
Acidity, meq/g	-	-	0.38	-
GC Simulated Dist., °C				
IBP	36-57	-	-	-
10%	118-180	85	80.5	-
50%	277-331	253	270	-
95%	363-417	362	379	-

Data Source for Tables 1 through 4:

Burke et al. 1991.

Kramer 1991.

Vimalchand et al. 1991.

Winschel, Burke, and Zhou 1991.

Kowalski and Basu 1984.

SEI 1991.

Winschel and Zhou 1991.

Zhou and Rao 1992.

TABLE 2
PROPERTIES OF WILSONVILLE COAL-DERIVED NAPHTHAS

Coal	Illinois No. 6 ¹	Pittsburgh Seam	Black Thunder	gasoline Specs
Cut, °C	IBP-182	IBP-193	IBP-193	
Gravity, °API @15°C	43.1	48.9	50.9	
D86 Distillation, °C				
10%	74 ²	91	80 ²	70 max
50%	121	126	116	77-121
90%	173	172	171	190 max
EP	197	187	204	225 max
RVP, kPa	-	19.3	21.4	62 max ³
Elemental, wt%				
C	85.2	85.3	84.3	
H	12.9	13.3	13.6	
N	0.008	<0.1	0.1	
S	0.36	0.05	0.08	0.10 max
O (diff)	1.56	1.25	1.92	
Group Analysis, vol%				
Paraffins	15.9	19.3	} 88.0	
Naphthenes	60.7	67.5		
Aromatics	23.4	13.2	7.0	
Olefins	5.5	-	5.0	
Acidity, mg KOH/g	-	-	0.38	
Phenolic-OH, meq/g	-	0.18	0.40	
Motor Octane	73.4	86.5 ³	87.1 ⁴	
Existent Gum, mg/g	-	7.6	40.2	5 max
Copper Corrosion	-	1A	1A	1 max
Oxidation Stability, min	-	Pass	Fail	240 min
Yield, wt%				
on Total Coal Liquid	18.4	26.7	23.7	
on maf Coal	-	19.7	-	

¹ Wilsonville Run 244.

³ Class A.

² GC Simulated.

⁴ by GC method.

END

**DATE
FILMED**

3 / 15 / 93

5. Malhotra, R.; McMillen, D. F. "Coal Liquefaction Process Streams Characterization and Evaluation; Characterization of Coal Liquids by Field Ionization Mass Spectrometry and Iodotrimethylsilane Derivatization, Topical Report," DOE/PC 89883-39, January 1992.
6. Miknis, F. P. "Coal Liquefaction Process Streams Characterization and Evaluation; Solid-State NMR Characterization of Coal Liquefaction Products, Topical Report," DOE/PC 89883-36, November 1991.
7. Serio, M. A.; Hsisheng, T.; Bassilakis, R.; Solomon, P. R. "Coal Liquefaction Process Streams Characterization and Evaluation; FT-IR Methods for Characterization of Coal Liquefaction Products, Topical Report," DOE/PC 89883-45, April 1992.
8. Green, J. B.; Pearson, C. D.; Young, L. L.; Green, J. A. "Coal Liquefaction Process Streams Characterization and Evaluation; Application of Liquid Chromatographic Separation Methods to THF-Soluble Portions of Integrated Two-Stage Coal Liquefaction Resids, Topical Report," DOE/PC89883-47, May 1992.
9. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report July 1 through Sept. 30, 1988," DOE/PC 70018-68, July 1989.
10. Winschel, R. A.; Robbins, G. A.; Burke, F. P. "Coal Liquefaction Process Solvent Characterization and Evaluation, Technical Progress Report April 1 through June 30, 1990," DOE/PC 89883-22, July 1991.
11. Rathbone, R. F.; Hower, J. C.; Derbyshire, F. J. "Application of Fluorescence Microscopy to Coal-Derived Resid Characterization," Am. Chem. Soc., Div. Fuel Chem. Preprints, 1991, 36(3), 1164.
12. Malhotra, R.; McMillen, D. F., Huestis, D. L. "Characterization of Coal Liquefaction Resids by Field Ionization Mass Spectrometry: Correlation Spectral Features with Processing Parameters," Am. Chem. Soc., Div. Fuel Chem. Preprints, 1992, 37 (2), 908.

TABLE 1
ELEMENTAL ANALYSES AND PHENOLIC -OH CONTENTS OF 850°F⁺
DISTILLATION RESIDS AND PARENT COALS^{9,10}

	Run 257				Run 259			
	Feed Coal	Inter-stage Resid	2nd Stage Resid	Recycle Resid	Feed Coal	Inter-stage Resid	2nd Stage Resid	Recycle Resid
wt % of 850°F ⁺ Resid in Process Stream	-	81.9	77.5	79.8	-	72.3	67.9	73.1
Ash wt % as det.	11.76	12.52	13.49	9.28	4.68	8.74	10.21	8.51
C wt % MAF	79.52	88.05	87.99	88.64	81.24	90.12	90.24	91.01
H wt % MAF	5.51	7.70	7.87	8.08	5.97	6.19	6.39	6.50
N wt % MAF	1.53	0.86	0.77	0.78	1.37	1.15	1.05	1.04
S wt % MAF	3.68	1.34	1.20	0.79	3.28	1.50	1.49	1.25
O wt % (by diff) MAF	9.58	2.05	2.16	1.71	8.07	1.04	0.83	0.20
Phenolic -OH, meq/g ^(a)	-	0.68	0.57	0.50	-	0.92	0.70	0.69

(a) determined on the THF-soluble portion of the resid