**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

EGG-BEG-8811

**INDEPENDENT VERIFICATION AND BENCHMARK
TESTING OF THE UNSAT-H COMPUTER CODE,
VERSION 2.0**

**Robert G. Baca
Swen O. Magnuson
Geosciences Unit**

February 1990

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, Idaho 83415**

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

Received by 3/7/91

AUG 2 1992

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

EGG-BEG--8811

DE92 019769

INDEPENDENT VERIFICATION AND BENCHMARK TESTING OF THE UNSAT-H COMPUTER CODE, VERSION 2.0

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Robert G. Baca
Sven O. Magnuson
Geosciences Unit

February 1990

Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, Idaho 83415

Prepared for
Westinghouse Hanford Company
Richland, Washington
and
U. S. Department of Energy
Under DOE Contract No. DE-AC07-76ID01570

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

Independent testing of the UNSAT-H computer code, Version 2.0, was conducted to establish confidence that the code is ready for general use in performance assessment applications. Verification (i.e., comparisons with known solutions) and benchmark (i.e., code-to-code comparisons) test problems were used to check the correctness of the FORTRAN coding, computational efficiency and accuracy of the numerical algorithm, and code capability to simulate diverse hydrologic conditions.

This testing was performed using a structured and quantitative evaluation protocol. The protocol consisted of: (1) blind testing, (2) independent applications, (3) maintaining test equivalence and (4) use of graduated test cases. Graphical comparisons and calculation of the relative root mean square (RRMS) values were used as indicators of accuracy and consistency levels. Four specific ranges of RRMS values were chosen for use in judging the quality of the comparison. All code testing was performed on the Idaho National Engineering Laboratory (INEL) Cray X-MP model 2/16 supercomputer.

Four verification test problems were used to check the computational accuracy of UNSAT-H in solving the uncoupled fluid flow and heat transport equations. Five benchmark test problems, ranging in complexity, were used to check the code's simulation capability. Some of the benchmark test cases include comparisons with laboratory and field data. The primary findings of this independent testing is that the UNSAT-H is fully operational. In general, the test results showed that computer code produced unsaturated flow simulations with excellent stability, reasonable accuracy, and acceptable speed.

This report describes the technical basis, approach, and results of the independent testing. A number of future refinements to the UNSAT-H code are recommended that would improve: (1) computational speed and accuracy, (2) code usability and (3) code portability. Aspects of the code that warrant further testing are outlined.

Table of Contents

	Page
List of Figures	ii
List of Tables	iii
1.0 INTRODUCTION	1
1.1 Background	1
1.2 Verification and Benchmark Testing	2
1.3 Description of Test Problems	3
2.0 TEST APPROACH AND REQUIREMENTS	6
2.1 Test Objectives	6
2.2 Test Protocol	6
2.3 Performance Indicator	7
3.0 VERIFICATION TEST CASES	10
3.1 Heat Conduction with Sinusoidal Boundary Condition	10
3.2 Heat Conduction with Constant Heat Flux	13
3.3 Philip's Solution for a Horizontal Column	15
3.4 Philip's Solution for a Vertical Column	19
4.0 BENCHMARK TEST CASES	23
4.1 Vertical Flow in a Laboratory Soil Column	23
4.2 Infiltration in a Stratified Vadose Zone	27
4.3 Partially Saturated Flow in Basalt	32
4.4 Thermal History of a Vadose Zone	38
4.5 Coupled Heat and Flow in a Field Test Plot	42
5.0 FINDINGS AND RECOMMENDATIONS	48
5.1 General Findings	48
5.2 Code Refinements	49
5.3 Further Code Testing	52
ACKNOWLEDGMENTS	54
REFERENCES	55

Table of Contents (Continued)

	Page
APPENDIX A - DESCRIPTIONS OF INDEPENDENT CODES	58
APPENDIX B - SUMMARY OF RRMS RESULTS	65
DISTRIBUTION LIST	67

List of Figures

1	Comparison of Temperature Profiles for Test Case VT-1	12
2	Comparison of Temperature Profiles for Test Case VT-2	14
3	Comparison of Pressure Heads for Test Case VT-3	18
4	Comparison of Moisture Contents for Test Case VT-3	18
5	Comparison of Pressure Heads for Test Case VT-4	21
6	Comparison of Moisture Contents for Test Case VT-4	21
7	Geometry for Laboratory Soil Column	23
8	Comparison of Moisture Contents Results for Test Case BT-1	26
9	Comparison of Wetting Front Positions for Test Case BT-1	26
10	Cross Section for Stratified Vadose Zone	28
11	Comparison of Pressure Head Results for Test Case BT-2	31
12	Comparison of Moisture Content Results for Test Case BT-2	31
13	Cross Section for Layered Basalt Setting	32
14	Comparison of Pressure Head Results for Test Case BT-3	36
15	Comparison of Moisture Content Results for Test Case BT-3	36
16	Simplified Cross Section for RWMC Vadose Zone	38

Table of Contents (Continued)

List of Figures

		Page
17	Comparison of Temperatures for Test Case BT-4	41
18	Calculated and Measured Temperatures for Test Case BT-4	41
19	Physical Setting for Soil System	43
20	Comparison of Pressure Heads for Test Case BT-5	46
21	Comparison of Moisture Contents for Test Case BT-5	46
22	Comparison of Temperature Histories for Test Case BT-5	47

List of Tables

1	UNSAT-H RRMS Results for Test Case VT-3	19
2	UNSAT-H RRMS Results for Test Case VT-4	22
3	UNSAT-H RRMS Results for Test Case BT-1	27
4	UNSAT-H RRMS Results for Test Case BT-2	30
5	Material Properties and van Genuchten Parameters	34
6	UNSAT-H RRMS Results for Test Case BT-3	37
7	Thermal Properties for Sediments and Basalt	39
8	UNSAT-H RRMS Results for Test Case BT-4	40
9	UNSAT-H RRMS Results for Test Case BT-5	45

1.0 INTRODUCTION

Independent testing of the UNSAT-H computer code, Version 2.0, was conducted to evaluate the correctness and operability of the code. Testing was aimed at determining code readiness for use in performance and risk assessment studies. This report describes the basis, approach and results of the code testing. All testing was performed on the INEL Cray X-MP 2/16 supercomputer.

1.1 BACKGROUND

The UNSAT-H computer code (Fayer, et al., 1986) is one of the primary analysis tools that will be used by Westinghouse Hanford Company to evaluate clean-up and disposal options at the Hanford Site, Washington. In particular, the UNSAT-H computer code will be used to: (1) interpret and analyze hydrologic data from field lysimeters, (2) predict recharge rates at various sites and (3) aid the design of barriers for waste sites. The UNSAT-H computer code is designed to perform detailed water balance calculations for the vadose zone of arid sites. The computer code is based on numerical solutions of one-dimensional forms of Richard's equation and the heat transport equation. The model formulation accounts for such factors and processes as:

- o evaporation and transpiration
- o thermal energy transfer in soil
- o diurnal meteorologic variations
- o liquid and vapor flow.

The governing equations describing these processes are solved by an iterative finite-difference technique. Major assumptions are: (1) the fluid is incompressible, (2) fluid flow is independent of the air phase, (3) hydraulic properties are non-hysteretic and (4) the porous medium is rigid.

To assure that the UNSAT-H computer code is a reliable analytical tool for performance assessment applications, EG&G Idaho performed an independent code verification and benchmark testing. The basic aim of the computational testing was to evaluate and demonstrate the general capabilities of UNSAT-H, Version 2.0. The computer code was evaluated in terms of:

- o computational accuracy, speed and stability
- o capability to simulate realistic soil conditions
- o versatility and ease of use.

The results of the computational testing reported here form the basis of recommendations for additional code development and/or refinement. The results of the testing also provide the technical documentation that certifies the operational status of the UNSAT-H computer code, Version 2.0. The scope of the computational testing performed is limited to verification and benchmark testing. No attempt was made to validate (i.e., evaluate the code's predictive capability) the code; however, some test cases include comparisons with actual field or laboratory data.

1.2 VERIFICATION AND BENCHMARK TESTING

One of the fundamental objectives of the testing was to examine the capabilities and limitations of the UNSAT-H computer code. The primary focus of the testing was to determine the code's operational status. The experience from the testing provided the basis for recommendations for code modifications that would enhance its usability in performance assessment applications. The testing process follows the general approach used in evaluating and/or certifying commercial high-level waste repository performance models (Ross, 1982). Computational testing was conducted in two categories: (1) verification and (2) benchmark testing.

Code verification was performed by making direct comparisons between known analytic solutions of appropriate problems and equivalent simulations by computer. The primary objectives of code verification are two-fold: (1) to check the accuracy and stability of the numerical techniques (e.g., finite difference) used to solve the governing equations, (2) to demonstrate that the computer code is fully operational; i.e., that the code performs as designed. As used here, a computer code is defined to be fully *verified* when computational test results clearly demonstrate that the computer code accurately represents the mathematical model.

Code benchmark testing involves code-to-code comparisons using test problems that are realistic in nature and of practical interest. The benchmark tests used here varied in complexity and were designed to test individual and coupled fluid flow processes. In addition, the tests were designed to evaluate the major features and options of the computer code. In the context of the objectives of this report, a computer code is defined to be *benchmark tested* when the computational tests show reasonable agreement with simulations obtained from other computer codes of similar capability.

1.3 DESCRIPTION OF TEST PROBLEMS

Nine (9) computational test problems were selected for evaluating UNSAT-H; they are categorized into two groups, verification and benchmark test problems. These test problems were obtained from various technical publications and from recent simulation studies at the Idaho National Engineering Laboratory (INEL). The verification tests consist of simple boundary-value problems with known solutions. These simple tests provided a means of verifying the accuracy of the numerical solution techniques employed by the UNSAT-H computer code. The benchmark test problems are relatively complex simulations of unsaturated flow and heat transport. These tests were designed to thoroughly evaluate the major features and capabilities of the UNSAT-H code.

The four verification test problems have quasi-analytic and/or closed form analytic solutions. These known solutions were used to make direct comparisons with the numerical solutions produced by the UNSAT-H code. The differences between the known solutions and numerical solutions were analyzed to quantify the computational accuracy of the UNSAT-H code.

The five benchmark tests consisted of practical problems of increasing complexity. Each problem was solved using the UNSAT-H code and two other, independently developed computer codes. The computer codes used in the benchmark testing were: FEMWATER (Yeh and Ward, 1979), TRACR3D (Travis, 1984), FLASH, TOUGH (Pruess, 1983) and SUTRA (Voss, 1984). These independent codes were selected because they were readily available and/or have been in common use by the technical community for a considerable period of time. These codes were also selected because they utilize distinct numerical solution techniques. Descriptions of the computer codes are given in Appendix A.

The following are brief descriptions of each verification and benchmark test problem.

VT-1 Heat Conduction with a Sinusoidal Boundary Condition. This test is a simple boundary-value problem for conductive heat transfer in a homogeneous soil column. The solution of this problem is representative of temperature distributions actually observed in soil. The closed form analytic solution for this problem is used to verify that UNSAT-H can accurately solve the heat conduction equation with time-varying boundary conditions.

VT-2 Heat Conduction with a Constant Heat Flux. This test considers conductive heat transfer in a homogeneous soil with a constant heat-flux boundary condition. This type of boundary condition is often encountered in practical simulations; therefore, it adds an additional element of realism. Comparisons between the analytic solution and the UNSAT-H numerical solution check the computational accuracy of the numerical technique.

VT-3 Philip's Solution for a Horizontal Column. In this test, unsaturated flow in a horizontal column of soil is simulated. Fluid flow through the soil column occurs only by capillary action, i.e., there are no gravity effects. A quasi-analytic solution for this problem has been published in the technical literature (Philip, 1957) and was evaluated by the INFIL computer code (El-Kadi, 1987). This test provides a basis for determining how accurately UNSAT-H can solve the nonlinear equation for a relatively simple unsaturated flow problem.

VT-4 Philip's Solution for a Vertical Column. This test is similar to VT-3 but includes the added effect of gravity. The test is more complex and realistic than VT-3 and requires simulating the rapid movement of the wetting front. A quasi-analytic solution also exists for this problem (Philip, 1957) and was obtained using the INFIL computer code. This test is used to check the computational accuracy of the UNSAT-H code in solving Richard's equation.

BT-1 Vertical Flow in a Laboratory Soil Column. Unsaturated flow in a relatively dry soil column is simulated in this test. This test is used to evaluate the capability of UNSAT-H to solve problems with strong nonlinearities and steep pressure gradients. The results of this test also provide insight to how well UNSAT-H tracks the position of the wetting front and estimates the rate of infiltration. For purposes of benchmark testing, the simulations are compared with those generated by the FLASH and TOUGH (Pruess, 1983) computer codes. In addition, the simulations are compared with data from a laboratory soil-column experiment.

BT-2 Infiltration in a Stratified Vadose Zone. This test, previously used by INEL in code testing, was published by Huyakorn, et al., (1984). The test problem is challenging in that it requires simulating large-scale infiltration and redistribution of water in a stratified vadose zone. In addition, the soil hydraulic properties are highly nonlinear and exhibit sharp contrasts between strata. Consequently, this test provides a good

basis for evaluating the strengths and weakness of the code's numerical solution technique. The computer simulations are compared with those of the FLASH and TRACR3D (Travis, 1984) computer codes.

BT-3 Partially Saturated Flow in Basalt. This test requires simulation of site-specific flow conditions at the INEL. The test problem involves time-dependent flooding of an excavated pit and unsaturated flow in the vadose zone. The geologic setting consists of surficial sediments underlain by flows of vesicular and massive basalt. The simulations of moisture movement are compared with those of FLASH and FEMWATER (Yeh and Ward, 1979).

BT-4 Thermal History of a Vadose Zone. The specifications for this test problem are derived from field studies conducted at the INEL. The objective of the test problem is to simulate the soil temperature history. The geologic setting consists of surficial sediments and basalt. The simulations are compared with those of FLASH and SUTRA (Voss, 1984). In addition, the UNSAT-H code is compared against actual field data for soil temperatures.

BT-5 Coupled Heat and Flow in a Field Test Plot. The specifications of this test problem were derived from a published field study (Sophocleous, 1978 and 1979) of coupled heat transfer and unsaturated flow. Both liquid and vapor-phase flow are simulated in this problem. The setting consists of a uniform layer of alluvium. Variations of soil temperature and moisture are simulated for a 20-day period. Simulations are compared with those of the FLASH computer code.

2.0 TEST APPROACH AND REQUIREMENTS

2.1 TEST OBJECTIVES

A primary objective of the work reported here was to establish the operational status of the UNSAT-H computer code. This was accomplished by an approach that thoroughly tested the options, features and computational algorithm of the code. Three basic conclusions resulting from this testing were possible: the computer code: (1) performs well and is fully operational, (2) is fully operational but improvements are recommended and (3) is not fully operational and requires additional development. The work was performed using a formalized test protocol, quantitative performance indicator(s) and evaluation criteria.

2.2 TEST PROTOCOL

The testing process was structured as an independent and unbiased evaluation of the UNSAT-H computer code, Version 2.0. To perform the testing in a systematic and consistent way, a test protocol was developed and employed. The protocol consisted of the following four requirements:

- (1) blind testing
- (2) independent applications
- (3) test equivalence
- (4) graduated test cases.

The first requirement was that each computer code(s) be applied to the test cases without prior knowledge of the analytic solution or benchmark simulation. This, in effect, forced the analyst to rely on their understanding of the physics of the problem and computational characteristics of the code. This blind testing prevented situations in which the analyst had an unfair advantage in selecting computational parameters such as the maximum time step size, integration factors, number of iterations, etc.

The second requirement was that the code developer not participate in the code testing process. The analyst performing the code testing was permitted to consult with the code developer(s) only: (1) if unexplained difficulties arose, (2) code modifications were necessary to accommodate the special characteristics of a specific test problem, or (3) to obtain clarification on input instructions.

The third requirement was that each code, to the degree practicable, use the same or similar spatial discretization for each test problem. The purpose of this requirement was to foster equivalence of computational effort. However, no constraints were placed on the time discretization (i.e., time step size) because several of the benchmark codes utilize automatic time step control.

The fourth and final requirement was adopted because of the need to test the major options and features of the UNSAT-H computer code for a wide range of problems. Consequently, the test cases selected range from simple boundary-value problems to relatively complex simulations.

2.3 PERFORMANCE INDICATOR

To evaluate the UNSAT-H code on a consistent basis, a quantitative indicator was needed to judge the code's computational performance for each test case. A broad choice of quantitative indicators currently exist. Among these are the: (1) maximum difference, (2) maximum relative difference, (3) root mean square error and (4) relative root mean square error. Each indicator is limited with respect to being able to reflect "significant differences" between the UNSAT-H simulation results (i.e., pressure heads and temperatures) and the known solution or reference simulation.

Relative root mean square error was adopted as the performance indicator for the code verification and benchmark tests reported here. This indicator is defined by the following formula:

$$RRMS = \sqrt{\frac{\sum_{i=1}^k ((a_i - n_i) / a_i)^2}{k}} \quad (1)$$

where

a_i = analytic solution (pressure head or temperature) at point i ,

n_i = numerical solution (pressure head or temperature) at point i and

k = number of comparison points.

In using this performance indicator, the boundary nodes (where the solution is specified) were excluded from the RRMS calculation. Also excluded from the

calculation were points where the analytic solution values, α_i , are very small; for purposes of this report, threshold pressure head and temperature values of 0.01 cm and 0.001 °C, respectively, were specified.

To judge the *accuracy level* of the verification test results, four performance categories were selected. The evaluation of code performance was keyed to a specific range of values for the RRMS. The ranges selected are somewhat arbitrary but nevertheless represent a consistent basis for evaluating the quality of the comparison.

The specific ranges and categories used in evaluating the code verification test results are listed below:

- o Excellent - $RRMS \leq 0.01$
- o Good - $RRMS \leq 0.05$
- o Acceptable - $RRMS \leq 0.10$
- o Unacceptable - $RRMS > 0.10$.

The task of judging the quality of the benchmark test results is somewhat problematic because the results are only *relative* comparisons. Numerical differences between simulation results generally reflect algorithm and/or distinct approximation approaches. A good example of this is the approach that finite difference codes use to compute the interfacial hydraulic conductivities, i.e., saturated hydraulic conductivities at interfaces between grid nodes. The specific method used for these calculations generally has a significant effect on numerical solutions of the unsaturated flow equation (Schnabel and Richie, 1984).

The UNSAT-H code (Fayer, et al., 1986), for example, uses the arithmetic, geometric, or harmonic means, depending on the user's specification. In contrast, the TOUGH code (Pruess, 1983) uses an upstream weighted approach whereas the TRACR3D code (Travis, 1984) uses a harmonic mean approach. It is very evident that there is no consensus among finite difference experts on the appropriate method for calculating interfacial conductivities. Patankar (1980, p. 44), for example, derives an equation for interfacial conductivity that indicates that only the harmonic mean will yield a "mass-conservative" approximation; Crichlow (1977, p. 112), however, claims that the harmonic mean leads to erroneous fluxes when there are sharp pressure head gradients and recommends the upwind approach. Finite element and spectral element codes, in contrast, do not use the concept of interfacial conductivity. Interfacial

conductivity is a *computational artifact* because hydraulic conductivity is actually discontinuous at the interface between grid nodes. Instead, the hydraulic conductivity is approximated as a function of space over the area or volume of the finite element.

Consequently, the use of the RRMS as a performance indicator for benchmark tests must reflect tolerance ranges that are large than those used in evaluating the verification test results. The specific ranges and categories selected for the purpose of this report are listed below:

- o Excellent - $RRMS \leq 0.05$
- o Good - $RRMS \leq 0.10$
- o Fair - $RRMS \leq 0.15$
- o Poor - $RRMS > 0.15$.

In this case, the RRMS values do not reflect computational accuracy; rather, they indicate the *degree of consistency* among independent simulation results. The RRMS values for the benchmark tests are computed using equation given previously, namely:

$$RRMS = \sqrt{\frac{\sum_{i=1}^k ((\alpha_i - n_i) / x_i)^2}{k}} \quad (1)$$

with the parameters defined as:

- α_i = numerical solution computed with the independent code(s) (pressure head or temperature) at grid node i ,
- n_i = numerical solution computed with the UNSAT-H code (pressure head or temperature) at grid node i and
- k = number of comparison points.

3.0 VERIFICATION TEST CASES

3.1 HEAT CONDUCTION WITH SINUSOIDAL BOUNDARY CONDITION

3.1.1 Problem Statement for VT-1

The physical system considered in this test case is a homogeneous soil column. A sinusoidal temperature boundary condition is applied at the top of the column while the bottom end is held at a fixed value. Pressure heads across the domain are fixed and uniform, so that the transfer of heat is independent of fluid flow.

The form of the governing equation for the conduction of heat in one dimension is given as:

$$\frac{\partial T}{\partial t} = D \frac{\partial^2 T}{\partial z^2}, \quad (2)$$

where T is temperature ($^{\circ}\text{K}$), t is time (hr), z is the distance coordinate (cm) and D is the thermal diffusivity (cm^2/hr) given by:

$$D = \frac{K_T}{\rho c}, \quad (3)$$

where K_T is the thermal conductivity (Joules/cm/hour/ $^{\circ}\text{K}$), ρc is the volumetric heat capacity (Joules/ $\text{cm}^3/^{\circ}\text{K}$).

3.1.2 Test Objectives

The objective of this test case was to evaluate the ability of the UNSAT-H computer code to solve the heat conduction equation for the following conditions:

- o sinusoidal temperature boundary condition
- o constant thermal properties
- o no fluid flow.

3.1.3 Analytic Solution

The analytic solution of this boundary-value problem, with the specified set of boundary conditions, is given by Kirkham and Powers (1978, p. 471) as:

$$T(z, t) = T_a + a \exp\left\{-\left(\frac{\omega}{2D}\right)^{1/2} z\right\} \sin\left[\omega t - \left(\frac{\omega}{2D}\right)^{1/2} z - \frac{7\pi}{12}\right], \quad (4)$$

where T_a is the mean temperature, α is the temperature amplitude and $\omega = 2\pi / P$, where P , the time period, is twenty-four hours. The last term in the analytic solution is necessary to make the maximum surface temperature occur at 1300 hours.

3.1.4 Input Specifications

The total length of the soil column for this problem is 18 cm. The one-dimensional domain is uniformly discretized into 0.5 cm grid spacings. The parameters required for a solution are:

$$T_a = 288^\circ\text{K}$$

$$\alpha = 3^\circ\text{K}$$

$$K_T = 9.4826 \times 10^{-2} \text{ J/cm/hr/}^\circ\text{K}$$

$$\rho c = 1.1705 \text{ J/cm}^3/^\circ\text{K}$$

$$D = 8.1013 \times 10^{-2} \text{ cm}^2/\text{hr}$$

The initial temperature profile is obtained by using the mean temperature as a uniform initial profile and then repetitively simulating the annual thermal cycle until the temperature profile at $t = 0$ hours converges.

3.1.5 Output Requirements

The transient temperature profiles are computed as functions of time. Results are compared to the analytic solution at $t = 4, 8, 12$ and 16 hours. The evaluations are made for these times in terms of both graphical comparisons and calculated RRMS values.

3.1.6 Verification Results

A special approach was required to solve this test case because UNSAT-H currently has no option to solve a "heat transport only" problem (i.e., no fluid flow). Thus, the simulation problem had to be configured to *nullify* the flow calculation in order to eliminate any possible coupling between heat transfer and fluid flow. This was accomplished by orienting the domain in a horizontal direction. The hydraulic conditions and properties were set to assure a hydrostatic flow condition. The thermal properties were specified at the arbitrary initial moisture content of 0.10, corresponding to an initial pressure head of 100 cm.

Using a uniform initial temperature of 288 °K, the code was first run to simulate a time period of 19 days to ensure that the entire temperature profile was in phase with the sinusoidal surface boundary condition. Proceeding from this simulation, UNSAT-H was run to produce output at the specified times. The simulation results for the upper 8 cm are compared to the analytic results in Figure 1.

The computed RRMS values for the four time planes range from 3.3×10^{-5} to 4.2×10^{-5} . All the RRMS values indicate that the accuracy level is in the "excellent" category (see section 2.3). Thus, it is concluded that the UNSAT-H can correctly and accurately solve heat transport problems with time-varying boundary conditions.

Figure 1. Comparison of Temperature Profiles for Test Case VT-1.

3.2 HEAT CONDUCTION WITH CONSTANT HEAT FLUX

3.2.1 Problem Statement for VT-2

In this second verification test, the physical system is again a homogeneous soil column. The surface boundary condition assumes that the atmosphere acts as the source of thermal energy. Transient heat flow occurs in response to a specified heat flux at the surface of the column. As in the VT-1 test case, the pressure heads across the domain are fixed and uniform to assure hydrostatic conditions. The governing equation is the same as for the VT-1 test.

3.2.2 Test Objectives

The objective of this computational problem was to evaluate the capability of UNSAT-H to solve the heat conduction equation for the following conditions:

- o constant heat flux boundary condition
- o constant thermal properties
- o no fluid flow.

3.2.3 Analytic Solution

The analytic solution to this boundary-value problem with the specified set of boundary conditions is given by Arpaci (1966, p. 277-279) as:

$$\frac{T(z, t) - T_i}{qL/K_T} = \frac{Dt}{L^2} + \frac{1}{2} \left(\frac{z}{L} \right)^2 - \frac{1}{6} - 2 \sum_{n=1}^{\infty} \frac{(-1)^n}{(\lambda_n L)^2} \exp \{-D \lambda_n^2 t\} \cos \{\lambda_n z\}, \quad (5)$$

where T_i is the initial temperature ($^{\circ}\text{K}$), q is the specified heat flux (W/m^2), L is the half-length (cm) of the domain, $\lambda_n = n\pi/L$ and n is the index for the terms of series.

3.2.4 Input Specifications

The total length of the soil column for this problem is 100 cm. A one-dimensional computational grid is superimposed onto this domain. The grid is uniform, with a constant grid spacing of 1.0 cm. The parameters required for the numerical solution are:

$$K_T = 30.24 \text{ J/cm/hr/}^{\circ}\text{K}$$

$$\rho c = 4.184 \text{ J/cm}^3/^{\circ}\text{K}$$

$$D = 7.228 \text{ cm}^2/\text{hr}$$

$$T_i = 288 \text{ }^{\circ}\text{K}$$

$$q = 1000.0 \text{ W/m}^2.$$

3.2.5 Output Requirements

The transient temperature profiles are computed as a function of time. Results are evaluated with respect to the analytic solution at $t = 24$ and 48 hours in terms of both graphical comparisons and the computed RRMS values.

3.2.6 Verification Results

The VT-2 test case was solved with UNSAT-H using the same approach as used in the VT-1 test case, to eliminate the flow coupling. The numerical solution was compared to the analytic solution for two times. As shown in Figure 2, the two solutions are nearly perfectly coincident with analytic solutions. The computed RRMS values were 2.5×10^{-5} for 24 hours and 2.7×10^{-5} for 48 hours. These RRMS values are well within the "excellent" category for code verification. These results are evidence that UNSAT-H correctly and accurately solves the heat transport equation with flux boundary conditions.

Figure 2. Comparison of Temperature Profiles for Test Case VT-2.

3.3 PHILIP'S SOLUTION FOR A HORIZONTAL COLUMN

3.3.1 Problem Statement for VT-3

For this test problem, the physical setting is a horizontal, homogeneous soil column. The initial condition is a uniform pressure head. Transient flow occurs solely due to capillary forces and in response to the boundary conditions. At the left boundary, the pressure head is set to a value corresponding to a fully saturated condition. This boundary condition causes imbibition to occur.

Horizontal movement of moisture in an unsaturated porous medium is governed by a nonlinear parabolic equation. The equation is a simplified form of Richard's equation and is given by:

$$C(\psi) \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial x} \left[K(\psi) \frac{\partial \psi}{\partial x} \right], \quad (6)$$

where ψ is the pressure head, $K(\psi)$ is the unsaturated hydraulic conductivity and x is the horizontal coordinate (cm). The specific moisture capacity $C(\psi)$ is given by

$$C(\psi) = \frac{\partial \theta}{\partial \psi}, \quad (7)$$

where θ is the volumetric moisture content. The pressure head, ψ , is a negative quantity in unsaturated soils and positive in fully saturated soils. Because the flow test cases presented in this report are limited to "unsaturated" situations, it is convenient to *drop* the *negative sign* in the numerical and graphical results.

3.3.2 Test Objectives

One objective of this test case was to determine the accuracy achieved by UNSAT-H in solving the simplified Richard's equation. A second objective was to evaluate the ability of UNSAT-H to calculate the position of the wetting front. This test is subject to the following conditions:

- o uniform initial moisture content
- o left boundary held approximately at saturation
- o temperature is fixed and uniform.

3.3.3 Analytic Solution

The quasi-analytic solution for this problem is evaluated by the INFIL (El-Kadi, 1987) computer code. The quasi-analytic solution is based on the derivations by Philip (1957).

3.3.4 Input Specifications

The total length of the horizontal column is 15 cm. A uniform finite-difference grid was superimposed on the domain using a grid spacing of 0.075 cm. The soil type in this verification problem is the same as that in the problem solved by Haverkamp, et al. (1977). The soil is a clay referred to as Yolo light clay. Functional relationships for the characteristic curve, i.e., pressure head versus moisture content and hydraulic conductivity curve are given by the Haverkamp, et al. (1977) formulae:

$$\theta(\psi) = \frac{\alpha(\theta_s - \theta_r)}{\alpha + (\ln |\psi|)^\beta} + \theta_r, \quad (8)$$

and

$$K(\psi) = K_s \frac{A}{(A + |\psi|^B)}, \quad (9)$$

where θ_s is the saturated volumetric moisture content, θ_r is the residual moisture content, K_s is the saturated hydraulic conductivity (cm/hr), and α, β, A and B are curve fitting parameters. For the Yolo light clay, the parameter values are:

$$\alpha = 739$$

$$\beta = 4.0$$

$$A = 124.6$$

$$B = 1.77$$

$$K_s = 0.04428 \text{ cm/hr}$$

$$\theta_s = 0.495$$

$$\theta_r = 0.124.$$

The initial condition is a uniform pressure head of 601.8 cm. This pressure head corresponds to a moisture content of 0.238.

3.3.5 Output Requirements

The outputs from this verification test are the pressure head and the moisture content profiles at $t = 2$ and 4 hours. Simulation results are graphically compared to the analytic solution and evaluated in terms of the RRMS values.

3.3.6 Verification Results

The VT-3 test case involved simulating the movement of a moisture front in a horizontal soil column. The problem formulation tests the code's ability to solve the simplified Richard's equation in conjunction with mildly nonlinear soil hydraulic properties. A series of computer runs were made using the UNSAT-H code. In each run the code option for interfacial hydraulic conductivity calculations was varied. The solution obtained using the arithmetic mean option predicted a more rapid advance of the front. In contrast, the solution with the harmonic mean option predicted a less rapid advance of the front.

The solution using the geometric mean option produced the best agreement to the analytic solution. These results were obtained using the mass balance-convergence criteria option and a convergence value of 1×10^{-4} cm. The numerical solutions obtained are compared with the quasi-analytic solution (generated with the INFIL code) in Figures 3 and 4. As can be noted from these graphical comparisons, UNSAT-H tends to predict an advance of the wetting front that is slightly more rapid than that of the analytic solution.

This slight difference may derive from two possible sources. The first is the space and time truncation errors introduced by the finite-difference algorithm. The second source may be the approximations in the quasi-analytic solution, as implemented in the INFIL code (El-Kadi, 1987); however, these are probably negligible. Better agreement was expected because on results published by other authors (Haverkamp, et al., 1977, Milly, 1982). Nevertheless, the magnitudes of the numerical error do not appear to be significant.

To calculate RRMS values, additional simulations were made using UNSAT-H, with a non-uniform grid as required for consistency with solution produced by the INFIL code. In addition, these results were cross checked by the results generated with the uniform grid. The computed RRMS values for the VT-3 test case are presented in Table 1.

Figure 3. Comparison of Pressure Heads for Test Case VT-3.

Figure 4. Comparison of Moisture Contents for Test Case VT-3.

The pressure head calculations are within the "acceptable" accuracy level while the moisture content values are in the "excellent" category. The RRMS values for pressure head are *more significant* than those for moisture content. Moisture content values are obtained directly from the characteristic curve data (i.e., ψ versus θ) and generally are relatively insensitive to errors in pressure head. Overall, the graphical comparisons and RRMS computations show that the UNSAT-H code does a good job of simulating horizontal movement of moisture.

TABLE 1. UNSAT-H RRMS Results for Test VT-3.

Solution Variable	t = 2 hours	t = 4 hours
Pressure head	7.4×10^{-2}	7.0×10^{-2}
Moisture content	9.6×10^{-3}	8.8×10^{-3}

3.4 PHILIP'S SOLUTION FOR A VERTICAL COLUMN

3.4.1 Problem Statement for VT-4

This problem is similar to the VT-3 test case except that the physical setting is a vertical, homogeneous soil column. The initial condition is a uniform pressure head. Transient infiltration in the vertical direction results from capillary forces and gravity. The upper boundary is held at a pressure head corresponding to full saturation. This problem was solved by Philip (1957) and by Haverkamp, et al. (1977).

The governing equation describing the vertical movement of moisture is Richard's equation, given by:

$$C(\psi) \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial z} \left[K(\psi) \left(\frac{\partial \psi}{\partial z} - 1 \right) \right], \quad (10)$$

3.4.2 Test Objectives

One objective of this test problem was to evaluate whether the UNSAT-H computer code correctly computes the position of the wetting front during vertical infiltration of moisture subject to the following conditions:

- o uniform initial moisture content

- o surface boundary held approximately at saturation
- o temperature is fixed and uniform.

3.4.3 Analytic Solution

This nonlinear boundary-value problem has a quasi-analytic solution derived by Philip (1957). The solution was evaluated using the INFIL code (El-Kadi, 1987).

3.4.4 Input Specifications

The input parameters for this problem are identical to those used in the VT-3 test case. The length of the vertical column is 15 cm. This domain was represented by a mesh consisting of 200 grid-blocks with a spacing of 0.075 cm. The soil type is again the Yolo light clay, with the same curve fitting parameter values as given previously (see section 3.3.4).

3.4.5 Output Requirements

The outputs from this problem are the pressure head and moisture content profiles at $t = 2$ and 4 hours. This output is shown graphically and by RRMS values.

3.4.6 Verification Results

Test case VT-4 is similar to VT-3 but includes the added effect of fluid flow by gravity. The objective of the test case was to test the code's ability to simulate the movement of moisture for conditions typical of field conditions. Based on knowledge gained from the VT-3 test case, the UNSAT-H simulation was performed using the geometric mean option and the same convergence requirement as for VT-2. The numerical and analytic solutions are shown in Figures 5 and 6.

To calculate the RRMS values, additional UNSAT-H simulations were made using the non-uniform discretization generated by INFIL code. The results of these simulations were checked against the results for the uniform grid simulation to ensure that no difference in wetting front position occurred due to a different discretization. The computed RRMS values for test case VT-4 are presented in Table 2. The accuracy level varies from the "acceptable" to "excellent" category. More consistently accurate results were expected because of results published by Haverkamp, et al. (1977) and Milly (1982). However, the magnitudes of the numerical errors do not appear to be significant.

Figure 5. Comparison of Pressure Heads for Test Case VT-4.

Figure 6. Comparison of Moisture Contents for Test Case VT-4.

TABLE 2. UNSAT-H RRMS Results for Test Problem VT-4.

Solution Variable	t = 2 hours	t = 4 hours
Pressure head	7.7×10^{-2}	6.8×10^{-2}
Moisture content	1.1×10^{-2}	8.1×10^{-3}

Based on the overall results, it is concluded that the UNSAT-H does a good job of modeling vertical moisture movement in a homogeneous soil.

4.0 BENCHMARK TEST CASES

4.1 VERTICAL FLOW IN A LABORATORY SOIL COLUMN

4.1.1 Problem Statement for BT-1

This benchmark test problem considers the movement of moisture into a relatively dry, laboratory soil-column (Figure 7). This test case was originally solved by Davis and Neuman (1983) using the UNSAT2 code. These authors compared their simulation results with the laboratory data collected by Skaggs, et al. (1970). Vertical flow through the soil column is induced by water ponded at the top boundary; the bottom boundary is open to allow the soil column to drain. This test problem is similar to VT-4, except that this case is more strongly nonlinear and the wetting front is very sharply defined; these are two features of this test case that are intended to challenge the capabilities of the codes.

9-8677

Figure 7. Geometry for Laboratory Soil Column.

4.1.2 Test Objectives

The objective of this test was to evaluate how well UNSAT-H simulates fluid flow when the governing equation exhibits highly nonlinear behavior. The simulation results are compared with those of other numerical codes and with laboratory data. The test problem also provided insight into the code's capability to track the position of a wetting front.

4.1.3 Computer Codes Used

Two computer codes were chosen for comparison with UNSAT-H. These were the FLASH and TOUGH (Pruess, 1983) codes.

4.1.4 Input Specifications

The homogeneous soil column is 50 cm long and discretized into a finite-difference grid composed of 100 grid blocks of uniform size (i.e., grid spacing of 0.5 cm). The simulation was performed using the geometric mean option, a minimum time step size of 10^{-7} hrs and a mass balance convergence level of 10^{-4} cm. The total simulation time was specified as 90 minutes.

The soil-hydraulic properties for this test problem were derived from data published by Davis and Neuman (1983); a spline-fit to their eight data points was used to create a continuous curve. In turn, this data was used to compute a segmented, polynomial fit for use in UNSAT-H; obtaining a satisfactory fit was not easy and required several repetitive fitting attempts. A polynomial fit for the relative hydraulic conductivity curve was produced in a similar fashion.

The saturated hydraulic conductivity was 7.22×10^{-4} cm/sec; the column initially had a uniformly low moisture content of 0.045 and a pressure head of 147.4 cm. The boundary condition at the top surface was fixed at the pressure head corresponding to saturation; the bottom boundary condition was fixed at the initial pressure head. As indicated earlier, the pressure head, ψ , is a negative quantity in unsaturated soils; however, because the test cases presented in this report are strictly for unsaturated conditions, the negative sign was dropped for convenience in the reporting results.

4.1.5 Output Requirements

Pressure head and moisture content profiles computed with UNSAT-H and the benchmark codes were compared at $t = 15, 30$ and 90 minutes after infiltration begins. The moisture content results are compared graphically whereas the pressure head

results were compared in terms of RRMS values. In addition, the calculated wetting front positions are graphically compared with values measured from a laboratory soil-column experiment.

4.1.6 Benchmark Results

The characteristics of test case BT-1 provide an opportunity to test how well the code can model the movement of a sharply defined wetting front in a relatively dry soil. These characteristics are typical of the proposed practical applications of the code.

The moisture content profiles produced by the three computer codes are shown in Figure 8. As can be noted from the figure, the moisture profiles computed by UNSAT-H and FLASH agree almost perfectly. The results from the TOUGH code suggest a slightly more rapid advance of the wetting front; this result is believed to derive from the upstream weighting approach for computing the interfacial hydraulic conductivities. The slight difference in initial moisture conditions below the wetting front (see Figure 8) is due to differences in the polynomial fit of the hydraulic properties for UNSAT-H versus the spline fit used by FLASH and TOUGH. This small difference is insignificant as can be seen from the match of the wetting front between UNSAT-H and FLASH.

The computer execution times for UNSAT-H, FLASH and TOUGH were 5.6, 5.6 and 149.4 central processing unit (cpu) seconds, respectively. (All cpu times reported in this document are for the CRAY XMP using UNICOS 4.0) The larger cpu time for TOUGH may, in part, be due to the additional overhead required this three-dimensional code.

The RRMS values were computed for pressure head and are shown in Table 3. The RRMS values computed relative to the FLASH results are well in the "good" to "excellent" category while the values based on the TOUGH results are in the "poor" category. As previously mentioned this disparity is likely to be due the upstream weighting method used in TOUGH.

Figure 8. Comparison of Moisture Contents for Test Case BT-1.

Figure 9. Comparison of Wetting Front Positions for Test Case BT-1.

TABLE 3. UNSAT-H RRMS Results for Test Case BT-1.

Solution Variable	FLASH	TOUGH
Pressure head 15 min	2.4×10^{-2}	3.1×10^{-1}
Pressure head 30 min	4.8×10^{-2}	3.2×10^{-1}
Pressure head 90 min	6.2×10^{-2}	4.0×10^{-1}

A comparison of the measured and calculated wetting front positions are shown in Figure 9. The measured data shown in this figure was obtained by digitizing the graphical results presented in Davis and Neumann (1983, p. 7-13). The method used to calculate wetting front position is the same as that used by these authors; the wetting front position was determined as the mid-point between two adjacent nodes where the moisture content at the upper node was greater than 0.05 and the moisture content at the lower node was less than 0.05.

As can be noted from Figure 9, the UNSAT-H and FLASH results show good agreement with the measured wetting front positions over the major part of the simulation period. The TOUGH results show a more rapid advance of the wetting front during the major part of the time period but then approaches the measured data at the end of the time period.

The overall results for this test case indicate that the UNSAT-H did an efficient and effective job of simulating the movement of a wetting front in a relatively dry soil.

4.2 INFILTRATION IN A STRATIFIED VADOSE ZONE

4.2.1 Problem Statement for BT-2

The physical setting for this problem is illustrated in Figure 10. This system is composed of a thick, multi-layer vadose zone with a constant recharge rate. The problem tests the codes ability to calculate the transient response of the vadose zone to a large change in recharge rate at the surface. The boundary condition at the bottom of the system is held at a fixed pressure head corresponding to saturation. This test problem is highly nonlinear and has the added complexity of contrasting soil properties. This test problem was originally solved by Huyakorn, et al. (1984).

4.2.2 Test Objectives

The objective of this test problem was to evaluate how well UNSAT-H could simulate variably saturated fluid flow in a stratified soil system with contrasting hydraulic properties. The test problem is computationally difficult because of the large contrasts and nonlinearities of the soil properties.

4.2.3 Computer Codes Used

In this test problem, the UNSAT-H simulation results were compared with those of FLASH and TRACR3D (Travis, 1984).

4.2.4 Input Specifications

The depth of the vadose zone is specified as 700 m. This one-dimensional spatial domain was approximated using a variably spaced, finite-difference grid consisting of 91 grid blocks. The grid spacing near the boundaries varied from 0.25 to 0.5 m. The grid spacing in center of the domain was 1 m. The time step was automatically controlled by each code; however, the minimum time step was set at 10^{-7} hrs. The mass convergence parameter was set at 10^{-4} cm.

Figure 10. Cross Section for a Stratified Vadose Zone.

The soil-hydraulic properties for this test problem were taken from graphs in Huyakorn, et al. (1984). These graphs were digitized and then fit with polynomial equations. The vadose zone consists of four distinct strata. The initial moisture profile varies with depth and is at steady-state for a recharge rate of 0.16 m/yr. The boundary condition at the top surface is set at a constant recharge rate of 0.006 m/yr; the bottom boundary condition is fixed at the pressure head corresponding to saturation.

4.2.5 Output Requirements

The pressure head and moisture content profiles calculated by UNSAT-H, FLASH and TRACR3D are presented graphically and by RRMS values. Comparisons of simulation results are made at two times, $t = 8$ years and 40 years.

4.2.6 Benchmark Results

Test case BT-2 was designed to provide the most difficult test of the various features and capabilities of the UNSAT-H code. The combination of sharp contrasts in hydraulic properties, steep pressure-head gradients and drying conditions pose a challenging computational problem. The characteristics of this test case are intended to reveal any deficiencies in the area of computational stability and accuracy.

The simulation results obtained with UNSAT-H, FLASH and TOUGH are shown in Figures 11 and 12. One region is enlarged in each figure to detail the agreement between UNSAT-H and FLASH. The UNSAT-H and TRACR3D results do not agree to the same extent but, overall, acceptable agreement. One possible cause of the disparity may be the transformation of the soil-hydraulic properties to the input units (i.e., hydraulic properties are input as functions of saturation, rather than pressure head) as required by TRACR3D.

The cpu times for UNSAT-H, FLASH and TRACR3D were 98.4, 0.3 and 30.0 seconds, respectively. The relatively long cpu time required by UNSAT-H is partially due to the fact the code internally constrains the time step to a maximum of 24 hours. Both FLASH and TRACR3D use algorithms that automatic increase the time step if the changes in pressure head are small; these algorithms significantly reduce the cpu times for this test case. The structure of the UNSAT-H code is designed primarily to track diurnal patterns rather than multi-year trends.

The computed RRMS values for UNSAT-H relative to FLASH and TRACR3D results are presented in Table 4. The RRMS values reflect "excellent" agreement between the UNSAT-H and FLASH results. The RRMS for UNSAT-H relative to TRACR3D, however, vary from "fair" to "excellent." Overall, these comparisons indicate that the UNSAT-H code has a capability to simulate moisture movement in a stratified vadose zone with conditions characteristic of an arid site. The results clearly demonstrate the stability of the computational algorithm.

TABLE 4. UNSAT-H RRMS Results for Test Case BT-2.

Solution Variable	FLASH		TRACR3D	
	8 years	40 years	8 years	40 years
Pressure head	3.7×10^{-2}	4.2×10^{-2}	1.0×10^{-1}	1.1×10^{-1}
Moisture content	1.7×10^{-2}	1.7×10^{-2}	4.2×10^{-2}	3.8×10^{-2}

Figure 11. Comparison of Pressure Heads for Test Case BT-2.

Figure 12. Comparison of Moisture Contents for Test Case BT-2.

4.3 PARTIALLY SATURATED FLOW IN BASALT

4.3.1 Problem Statement for BT-3

This problem tests a codes ability to simulate transient moisture infiltration into an unsaturated, field-scale, geologic setting. The geometry of the system is a simplified representation of the geology beneath the Radioactive Waste Management Complex (RWMC) at the Idaho National Engineering Laboratory (INEL). The soil and rock property data are from laboratory measurements on test cores from the INEL site. The stratigraphy represented in the conceptual model consists of eight units composed of four different materials. The geometry of the problem is shown in Figure 13.

Figure 13. Cross Section for Layered Basalt Setting.

A low infiltration rate at the surface is used to obtain the initial steady-state moisture profile. A higher rate is then used to simulate the effects of flooding in the excavated pit containing the waste. After a specified time, the infiltration rate returns to the lower rate to simulate the end of flooding. The remainder of the simulation describes the redistribution of the moisture added during flooding.

4.3.2 Test Objectives

The objective of this test was to examine the capability of the UNSAT-H code to model moisture movement at a specific site using actual field and laboratory data. Moreover, the test case assumes a high infiltration rate at the surface to enhance the computational difficulty. The hydraulic properties of the two types of basalt contrast sharply; this exacerbates the computational difficulty, especially in the areas near the sediment-basalt interfaces.

4.3.3 Computer Codes Used

The computer codes used for comparison with UNSAT-H for this benchmark test were FLASH and FEMWATER (Yeh and Ward, 1979).

4.3.4 Input Specifications

The physical setting for this problem is illustrated in the geologic cross section shown in Figure 13. The physical system was represented using a variably spaced finite-difference grid. The grid consisted of 83 grid blocks which varied in size from 1 to 150 cm. The 1-cm grid spacing was used at stratigraphic interfaces and 3.5 cm in the interiors of the stratigraphic units; the larger grid blocks were also used near the bottom of the domain. The time step was automatically controlled by the code; however, the minimum time step was set at 10^{-7} hrs. The mass convergence parameter was set at 10^{-4} cm.

The hydraulic properties of the four materials are listed in Table 5. The van Genuchten option in UNSAT-H was used to describe the water release and hydraulic conductivity relationships of each stratum. The hydraulic properties of the waste-disposal zone were arbitrarily chosen and are analogous to those of a well-drained soil. The hydraulic properties of the sediments are based on averages of measurements on soil samples collected near the surface of the RWMC. Hydraulic properties of the massive and vesicular basalt are based on mercury-injection

measurements for cores of basalt from the RWMC. For the purpose of this test problem, the hydraulic properties of the interbed are assumed to be the same as those of the surficial sediments.

Two infiltration rates are used in this problem: (1) a steady-state rate of 1.585×10^{-7} cm/s (5 cm/year) and (2) a flooding rate of 1×10^{-4} cm/s. The steady-state infiltration is used to generate the initial pressure head (and moisture content). These calculations are then used for simulation of the transient flooding; the enhanced flux is applied for 5 days and then reduced to the initial steady-state value. Redistribution of moisture occurs during the next 100 days, making the total time simulated 105 days. Free drainage is allowed at the bottom boundary for the duration of the problem.

TABLE 5. Material Properties and van Genuchten Parameters.

Material	θ_s	θ_r	α	n	K_s (cm/hr)
Waste	.35	0.0	.0551	2.43	360.
Sediments	.28	.10	.000918	1.788	1.08
V. Basalt	.244	.0427	.402559	1.3459	15.6492
M. Basalt	.12	.0123	.073993	1.6957	196.668

4.3.5 Output Requirements

Outputs from the simulations are the pressure head and moisture content profiles at two times: $t = 5$ days (end of flooding) and $t = 105$ days. This output is presented graphically and in terms of RRMS values.

4.3.6 Benchmark Results

Test case BT-3 is the most difficult of the set of the unsaturated flow test cases. The characteristics of the test problem exemplify all the complexities that can arise in modeling unsaturated flow for actual conditions. Consequently, a successful simulation of this problem is significant evidence of a computer code's capability. The numerical

results obtained with UNSAT-H, FLASH and FEMWATER are shown in Figures 14 and 15. Two areas are enlarged in each figure to provide additional detail in the vicinity of the wetting front.

The cpu times for UNSAT-H and FLASH were 1860 and 227 seconds, respectively. The FEMWATER cpu time for simulation of a 5 day period was 433 seconds. The FEMWATER code was run only to 5 days because the code failed to provide an adequate solution with reasonable time steps. Numerical experiments, however, indicated that the FEMWATER code gave better solutions with much smaller time steps; for example, using time steps of 1000, 500 and 100 seconds FEMWATER showed progressively better comparisons to the UNSAT-H and FLASH results. However, the execution times (and therefore computer costs) for the FEMWATER code quickly became prohibitive.

The computed RRMS values for UNSAT-H, relative to FLASH, are presented in Table 6. The UNSAT-H RRMS values relative to FEMWATER were only compiled for $t = 5$ days because of the numerical problems encountered. The RRMS results indicate "excellent" agreement between UNSAT-H and FLASH for both pressure heads and moisture contents at both of the simulated times. The RRMS values based on the FEMWATER code indicate "fair" agreement; however, the position of the wetting front calculated by FEMWATER was significantly different from that calculated by UNSAT-H and FLASH.

Thus, it is concluded that the UNSAT-H did an excellent job in solving a difficult and realistic test problem. The results showed remarkable agreement with the results of the FLASH code. The large cpu times required by the UNSAT-H code may be due to the nonlinear iteration algorithm and the method used for calculating the soil hydraulic properties. These topics are discussed further in Section 5.

Figure 14. Comparison of Pressure Heads for Test Case BT-3.

Figure 15. Comparison of Moisture Contents for Test Case BT-3.

TABLE 6. UNSAT-H RRMS Results for Test Case BT-3.

Solution Variable	FLASH		FEMWATER	
	5 days	105 days	5 days	105 days
Pressure head	3.8×10^{-2}	1.2×10^{-2}	1.4×10^{-1}	not computed
Moisture content	2.0×10^{-2}	5.3×10^{-3}	1.1×10^{-1}	not computed

4.4 THERMAL HISTORY OF A VADOSE ZONE

4.4.1 Problem Statement for BT-4

This problem tests a code's ability to simulate conductive heat transfer in the vadose zone (i.e., unsaturated zone) of the RWMC at the INEL site. The geometry of the domain is much simpler than that used in test case BT-3; in particular, there are only two strata, a surficial sediment and a basalt flow top (Figure 16). Surface and down-hole temperatures at this site were monitored with thermistors from 1985-1986 (Pittman, 1989).

For purposes of simulation, a harmonic function was fit to the data measured at the near surface; the resultant function was then used to specify the surface temperature. The thermal properties of the strata were treated as constants and were estimated from available field and laboratory measurements.

4.4.2 Test Objectives

The objective of this test problem was to simulate the temperature history of the surficial soil at the RWMC. Results from the UNSAT-H code were compared to results produced by the other codes. In addition, the simulation results were graphically compared with the measured data. The formulation of this test problem assumes:

- o no fluid flow
- o heat transfer by conduction only
- o thermal properties of each layer are homogeneous and constant.

4.4.3 Computer Codes Used

The codes used for comparison to UNSAT-H were FLASH and SUTRA (Voss, 1984).

9-8678

Figure 16. Simplified Cross Section for RWMC Vadose Zone.

4.4.4 Input Specifications

In this test problem, the thermal cycle is simulated for a three-year period. The physical system was simulated using a variably spaced finite-difference grid. The grid consisted of 172 nodes with grid spacings that varied from 2.5 to 25 cm. A finer grid spacing was used at the top boundary and in the vicinity of the material interface.

The thermal properties for the two material types were obtained from the information published by Marshall and Holmes (1979) and DOE (1986). The specific values used are listed in the table below:

The fitted harmonic function was used to specify the surface-temperature boundary condition and is given by:

TABLE 7. Thermal Properties for Sediments and Basalt.

Material	K_T (cal/cm/s/°C)	ρc (cal/cm ³ /°C)
Sediments	2.58×10^{-3}	0.6035
Basalt	3.82×10^{-3}	0.5086

$$\begin{aligned}
T_s = & 8.40 - 1.75 \sin(.005734(t_d + 1039.4)) + 3.21 \sin(.011470(t_d + 6.9)) \\
& + 17.2 \sin(.017200(t_d - 100.9)) - 2.81 \sin(.022940(t_d - 61.2)) \\
& + 3.62 \sin(.028670(t_d - 33.5)) + 1.27 \sin(.034400(t_d + 62.8)), \quad (11)
\end{aligned}$$

where $t_d = t - 417$ days. The initial temperature profile was a uniform 8.4 °C. The bottom boundary condition was fixed at the initial value of $T = 8.4$ °C.

4.4.5 Output Requirements

Output from this problem consists of temperature histories (i.e., temperature versus time) computed at 10, 210 and 400 cm below the land surface. This output is presented graphically. The UNSAT-H results for depths of 210 and 400 cm are superimposed on the measured soil temperatures for the period of record.

4.4.6 Benchmark Results

This test case is representative of a practical simulation problem and uses realistic data. A special approach was required to solve this test case because UNSAT-H does not currently have an option to simulate heat transport only (i.e., no fluid flow). Thus, the simulation problem was configured to *nullify* the flow calculation, to eliminate any possible coupling between heat transport and fluid flow. This was accomplished by orienting the domain in a horizontal direction. The hydraulic conditions and properties were set to assure a hydrostatic flow condition. The FLASH and SUTRA codes were run in the heat transport only mode (i.e., no fluid flow).

Simulation results generated by UNSAT-H, FLASH and SUTRA are shown in Figure 17. The results are in good agreement and show the effect of damping of the surface sinusoidal boundary condition with depth. The UNSAT-H and SUTRA results agree exceptionally well because both codes compute the thermal properties as a function of moisture content; the results are indistinguishable in Figure 17. The FLASH code, in contrast, used constant thermal properties which were assumed to be independent of soil moisture conditions.

The RRMS values computed using the SUTRA and FLASH simulation results are listed in Table 8. The RRMS values are tabulated for temperature calculations at three selected depths. The results clearly demonstrate "excellent" level of consistency. In addition to the code-to-code comparison, the UNSAT-H results were compared to available field data (Pittman, 1989). The UNSAT-H simulation results and field data are shown in Figure 18; this comparison is for the period of record of the field data. The comparison clearly shows very good agreement.

The cpu times for UNSAT-H, FLASH and SUTRA were 21.7, 10.7 and 73.8 seconds. The SUTRA code does not have a linear element option and solves the problem using a two-dimensional quadrilateral element; the additional computational nodes (twice as many as UNSAT-H and FLASH) accounts for the longer run time.

TABLE 8. UNSAT-H RRMS Results for Test Case BT-4.

Solution Variable	SUTRA	FLASH
Temperature at 50 cm	2.2×10^{-4}	4.9×10^{-3}
Temperature at 210 cm	1.8×10^{-4}	1.3×10^{-4}
Temperature at 400 cm	9.8×10^{-5}	9.4×10^{-5}

Figure 17. Comparison of Temperatures for Test Case BT-4

Figure 18. Calculated and Measured Temperatures for Test Case BT-4

4.5 COUPLED HEAT AND FLOW IN A FIELD TEST PLOT

4.5.1 Problem Statement for BT-5

This problem tests a code's ability to simulate coupled heat transfer and fluid flow. The problem setting and specifications are similar to that published by Sophocleous (1978, 1979). The physical system is a shallow vadose zone composed of sandy loam to sand. The problem geometry is illustrated in Figure 19. In this system, soil temperature is controlled by diurnal variations of the surface temperature; soil moisture distributions are controlled by evapotranspiration at the surface and effects of the water table at the bottom boundary.

The coupled heat and flow equations differ from those previously presented. The equation for moisture movement is the same, except that the unsaturated hydraulic conductivity depends on temperature. Darcy's law includes density and viscosity as follows:

$$K = k \frac{\rho g}{\mu}, \quad (12)$$

where K is hydraulic conductivity (cm/s), k is permeability (cm²), ρ is density (gm/cm³), g is the gravitational constant and μ is the viscosity (g/cm/s). To account for the temperature dependence of K , the following formula is used:

$$K(T) = K \frac{\mu_o \rho(T)}{\rho_o \mu(T)}, \quad (13)$$

where the subscript "o" refers to a reference temperature of 15.6 °C (Fetter, 1988, p. 79).

The coupled heat equation for transient soil temperature is given as:

$$\rho c \left(\frac{\partial T}{\partial t} + q \frac{\partial T}{\partial z} \right) = \frac{\partial}{\partial z} \left[K_T \frac{\partial T}{\partial z} \right], \quad (14)$$

where q is the Darcy velocity (cm/hr). All other variables are as previously defined.

Figure 19. Physical Setting for Soil System.

4.5.2 Test Objectives

The objective of this test was to evaluate the capabilities of the UNSAT-H code to simulate the coupled processes of heat conduction and unsaturated flow in a realistic setting. The problem tests code's ability to simulate the flow of both liquid and vapor phase.

4.5.3 Computer Codes Used

Of available benchmark codes, only FLASH has the capability to simulate coupled heat and flow processes with an equilibrium approach to vapor phase transport. Consequently, only the UNSAT-H and FLASH codes were run and compared.

4.5.4 Input Specifications

The physical system is a soil column with a total depth of 300 cm. To simulate the coupled heat and flow processes, the domain was discretized into a variably spaced finite-difference grid. The grid was composed of a total of 85 grid blocks. Grid block spacings varied from 0.8 to 6.0 cm; a finer grid was used near the surface boundary condition. The time step was automatically controlled by the code; however, the minimum time step was set at 10^{-7} hrs. The mass convergence parameter was set at 10^{-4} cm.

The hydraulic properties of the homogeneous soil column were represented using the van Genuchten option in UNSAT-H; the following parameter values were specified:

$$\theta_s = .41$$

$$\theta_r = .05$$

$$\alpha = .01188$$

$$n = 1.887$$

$$K_s = 4.0 \text{ cm/hr.}$$

The thermal conductivity function for the soils are represented by the following equation (Cass, et al., 1981):

$$K = A + B \frac{\theta}{\theta_s} - (A - D) \exp \left[- \left(C \frac{\theta}{\theta_s} \right)^E \right]. \quad (15)$$

The following coefficients are used for the soil:

$$A = 0.002$$

$$B = 1.5$$

$$C = 3.0$$

$$D = 0.1$$

$$E = 0.1.$$

These coefficients approximate the thermal conductivity function used by Sophocleous (1979). The bulk soil-water heat capacity, ρc , is $4.184 \text{ J/cm}^3/\text{°K}$. The initial temperature conditions are a uniform 283 °K . The initial pressure-head profile is obtained by solving for the steady-state profile with a flux rate of 1.0 cm/hr .

The thermal and flow boundary conditions for the problem are specified as follows: (1) a sinusoidal temperature at the surface and a constant temperature of 283 °K at the bottom of the domain and (2) a variable infiltration rate at the surface and saturation at the bottom. The sinusoidal variation of surface temperature was assigned a mean value of 283 °K and an amplitude of 5 °K. The fluid flux at the surface consists of a stepped decrease with a 0.75 cm/hr flux for the first day and a 0.25 cm/hr flux during the second day. The surface boundary condition for the remainder of the simulation period is zero flux.

4.5.5 Output Requirements

The output for this problem consists of pressure head and water-content profiles as a function of depth at times $t = 5$ and 20 days. Each result is shown in terms of a graphical comparison and a corresponding RRMS value. Additionally, the temperature history (i.e., temperature as a function of time) at depths of 0.8, 13 and 30 cm is shown.

4.5.6 Benchmark Results

This final test case was designed to test the code's capability to model physical systems in which coupling effects between heat transport and fluid flow are potentially important. The simulation results for test case BT-5 are summarized in Figures 20, 21 and 22. The agreement for the pressure head and moisture content plots is "excellent." This conclusion is confirmed by the RRMS values which are given in Table 9.

The slight differences in amplitude in the temperature-history plot are due to the fact that the FLASH code used a constant value for the bulk soil-water heat capacity but UNSAT-H calculates this quantity as a function of moisture content. The cpu times for UNSAT-H and FLASH were 11.5 and 5.0 seconds, respectively.

TABLE 9. UNSAT-H RRMS Values for Test Case BT-5.

Solution Variable	$t = 5$ days	$t = 20$ days
Pressure head	7.0×10^{-3}	6.2×10^{-3}
Moisture content	2.5×10^{-3}	2.9×10^{-3}

Figure 20. Comparison of Pressure Heads for Test Case BT-5.

Figure 21. Comparison of Moisture Contents for Test Case BT-5.

Figure 22. Comparison of Diurnal Temperatures for Test Case BT-5.

The results of the simulations by the two codes show exceptional agreement even though the codes solve slightly different formulations of the heat equation. In particular, the UNSAT-H code solves the heat transport equation formulated for advection and diffusion of heat; in contrast, the mathematical formulation implemented in the FLASH code neglects the advection term.

This finding demonstrates the generally insignificant of transport of heat by advection in the vadose zone. Advective heat flux is very small compared to diffusive heat flux in natural soil systems because of the typically low Darcian velocities. In general, the simulation results are more sensitive to the variation of thermal properties as a function of moisture content and the dependence of hydraulic conductivity on temperature.

The overall results of this test case strongly support the conclusion that the UNSAT-H code is an effective and reliable tool for simulating the coupled processes of heat transport and fluid flow in soil.

5.0 FINDINGS AND RECOMMENDATIONS

Independent testing of the UNSAT-H computer code, Version 2.0, was conducted to establish confidence that the code is ready for general use. Four verification tests (i.e., comparisons with known solutions) and five benchmark tests (i.e., code-to-code comparisons) were used to check the correctness of the FORTRAN coding, computational efficiency and accuracy of the numerical algorithm and code capability to simulate diverse hydrologic conditions. This testing was performed using a structured and quantitative testing protocol. The primary findings and recommendations derived from this detailed code testing are summarized here.

5.1 GENERAL FINDINGS

Overall, the results of the code verification and benchmark tests indicate that the UNSAT-H computer code is a reliable tool for simulating the processes of coupled heat and fluid flow in the unsaturated zone. The correctness of the FORTRAN code was established by the test results and confirmed by comprehensive software interrogations performed with INEL's CRAFT software. The CRAFT software analysis of the initial source code found only a few minor coding problems (eg., variables defined but not used, transfers into if then else logic). These errors were corrected and do not exist in version 2.0.

From the results of the four verification test cases, it is concluded that the UNSAT-H code does an "excellent" job of accurately solving the transient heat equation and computing the soil-temperature profiles. In contrast, the performance of the UNSAT-H code in solving the unsaturated flow equation and computing pressure head and moisture content profiles varied from "acceptable" to "excellent," according to the evaluation criteria (see section 2.3). This variability may be related to the accuracy limitations of the finite-difference method implemented and/or the algorithms used to estimate "interfacial" hydraulic conductivities. Discrete approximations derived using a Galerkin or Spectral finite element method would yield more consistently accurate results (see section 5.2.1).

The results of the five benchmark test cases generally showed "good" to "excellent" agreement between the UNSAT-H simulations and those of the five independent computer codes: FEMWATER, TRACR3D, FLASH, TOUGH and SUTRA (see Appendix A for code descriptions). By and large, the results of the benchmark tests

demonstrate that the UNSAT-H code has a strong capability to simulate realistic conditions. A few benchmark tests indicated only "poor" to "fair" agreement; however, these results were not significant because they were due to specific limitations of selected independent codes. Identification of these limitations is itself considered to be an important finding (see Appendix A).

Based on the results of this independent testing, it is concluded that the UNSAT-H code is a versatile and reliable analysis tool that can be used to:

- o interpret and analyze hydrologic data from field lysimeters,
- o predict recharge rates as a function of such factors as precipitation, evapotranspiration, soil hydraulic properties and
- o analyze moisture barrier designs for waste sites.

The UNSAT-H computer code is judged to be *fully operational*; however, the overall capability and utility of the code could be further improved. Specific recommendations are outlined in the following sections.

5.2 CODE REFINEMENTS

The UNSAT-H computer code is the product of more than three years of focused research and is now approaching a high level of development. The independent code testing reported here has aided in the identification of specific areas where the code benefit from further refinement. From the perspective of a general user, the current version of the code should be refined to improve:

- o computational efficiency and accuracy,
- o usability of the computer code and
- o source code portability.

Specific recommendations for improvements in these areas are discussed below.

5.2.1 Computational Efficiency and Accuracy

The overall results from the code testing indicate that the numerical methods used in UNSAT-H produce unsaturated flow simulations with *excellent* computational stability, *reasonable* accuracy and *acceptable* computational speed. However, the code did not, in general, exhibit the accuracy expected in the verification test cases, nor the computational speed of other independent codes used in the benchmark testing.

Moreover, comparisons of results from benchmark test BT-3 between UNSAT-H versions 1.0 and 2.0 indicate that the latest version of the code requires more than *twice the computational time* as the earlier version to produce comparable results.

A primary factor currently limiting the computational efficiency is the iteration technique used in the UNSAT-H code. The code uses a Picard iteration technique (i.e., successive substitutions) to solve the governing equations; this technique is only linearly convergent. Computational efficiency and, therefore, computational speed could be *significantly improved* by replacing the Picard iteration technique with a more efficient iteration method. The Newton-Raphson iteration method (Carnahan, et al., 1969, Johnstone, 1982), for example, would require fewer iterations and less computer time because it converges quadratically. In most cases, the use of the Newton-Raphson technique would also contribute to computational efficiency because fewer evaluations of the nonlinear coefficients (i.e., $C(\psi)$ and $K(\psi)$) would be needed. Timing studies (performed with the Cray profiling routines) indicate that more than 80% of the UNSAT-H code execution time is attributable to evaluations of the nonlinear coefficients. Replacement of the iteration method alone would likely *reduce the computer execution times* for unsaturated flow simulations by 50% or more.

Another modification that would improve the code's computational efficiency and accuracy is related to the mathematical formulation of the heat equation. The present formulation of UNSAT-H includes both conduction and advection of thermal energy. It is very rare, however, that the advective heat flux contributes significantly to the overall heat balance in natural soil systems. This is particularly true in arid settings such as those at Hanford and the INEL site. This fact was demonstrated in test cases BT-4 (see comparison with field data) and BT-5. Thus, the advective term could be easily dropped from the code formulation without loss of predictive reliability and with a slight gain in computational speed.

More accurate numerical solutions to the unsaturated flow equation could be obtained by replacing the current finite difference technique (which assumes linear variation of pressure head and hydraulic conductivity) with a technique that permits higher-order approximations. The Galerkin finite element method (Baca, 1978, Baker, 1983) or the Spectral element method (Patera, 1988) could be used to derive the grid block (or element) algorithms using quadratic or cubic approximations for the pressure head and hydraulic conductivity. These approaches, in addition to being more accurate,

avoid the *artifact* of interfacial hydraulic conductivities. This particular refinement would be relatively easy to implement because of the modular structure of the computer code.

5.2.2 Improvement of Code Usability

Recommendations regarding improvement of code usability are relatively subjective and reflect individual preferences. Although several recommendations are made here, the UNSAT-H code is relatively more versatile and easier to use than some of the codes used in the benchmark testing. Based on the kinds of applications documented in this report, modifications are recommended in four general areas:

1. control options for selection of process (or processes) simulated,
2. input option for use of tabular data for soil hydraulic and thermal properties,
3. output option to allow tabular output of Darcy or pore velocities and
4. streamlining of the input subroutine to allow consolidation of input data.

The above recommendations are listed in order of priority.

The first recommendation is motivated by the fact that the code currently allows only two control options: (1) solution of the unsaturated flow equation only or (2) solution of both the fluid flow and heat transfer equations. In many practical applications, there is a need to solve the heat equation alone because of the weak dependence of thermal conductivity on soil moisture content and the negligible contribution of advective heat flux. By incorporating a *heat equation only option*, the user could compute the temperature profiles separately and later use these results as input to unsaturated flow simulations, as appropriate. The addition of this feature would result in enhancement of user convenience and reduction of computer execution time.

Modification of the code to allow *input of tabular data* for the soil hydraulic and thermal properties is recommended because the current options for fitting equations are not sufficiently general. Problems were encountered, for example, in obtaining satisfactory polynomial fits to hydraulic data for a several benchmark test cases. Moreover, the polynomial fitting can be unreliable because this type of curve-fitting can introduce significant errors in computing the derivative of the polynomial (which is used in calculation of the specific moisture capacity term, $C(\psi)$). Specifically, it is recommended that the polynomial option be replaced with a spline interpolation

option that utilizes tabular data. This modification would result in enhanced user convenience and reduced data set up time. This modification would also result in a significant improvement of computational efficiency.

The Darcy and pore-water velocities can provide valuable insight into the reasonableness of simulation results, as well as allow a code user to estimate recharge rates and water travel times. The UNSAT-H code currently does not currently have an option to allow tabular output of these quantities. Appropriate output options should be added to the code to allow the user to select output of the Darcy and/or pore-water velocities.

In preparing input data for the various test cases, it was noted that the sequence of data input does not occur in a *logical order* or in *natural groupings*. For example, input flags for the top and bottom boundary conditions appear on separate cards of the data deck. Similarly, the various input parameters that control the time-step algorithm are distributed among several different cards. This dispersed input structure makes it difficult for the inexperienced user to setup and easily check the input data file. With relatively little effort, the input subroutine could be modified to eliminate this inconvenience.

5.2.3 Improvement of Code Portability

The UNSAT-H code is modular and internally documented which make the code structure relatively easy to follow and understand. Because of these aspects and capabilities, the code is likely to find wide usage. General use of the code would be greatly promoted by improving its portability, i.e., transferability to other computer facilities.

Version 2.0 of the code currently makes liberal use of VAX VMS-specific input/output statements. These system dependencies should be replaced with ANSI FORTRAN code to allow the code to be easily installed and used on a wide variety of computer resources. Also, portability is also limited by some non-standard FORTRAN 77 coding such as:

- (1) variable names longer than six characters,
- (2) variable names with " " character,
- (3) INCLUDE statements, and
- (4) special format specifiers

Portability problems with this type of coding will be lessened in the future as newer FORTRAN compilers incorporate the above options; these options are expected to be included in the next release of the standard FORTRAN.

5.3 FURTHER CODE TESTING

The major options, features and computational algorithms of the UNSAT-H code have been extensively tested in this study. However, there are selected features of the code that would benefit from further testing. In particular, additional testing should be performed on:

- o code logic for simulating wetting and drying cycles,
- o calculation of the vapor phase component and
- o calculation of the Darcy velocities.

Limited testing of the first two aspects was performed but more *thorough testing is warranted* and strongly recommended. The last aspect was not tested in this study because the code does not currently output Darcy velocities.

ACKNOWLEDGMENTS

The authors wish to thank a number of individuals that contributed to this project. First and foremost, the authors thank Dr. J. D. Davis, Westinghouse Hanford Company, for his thorough editorial review of the draft report. The readability of the report was greatly improved by his many editorial contributions. The authors also wish to thank Dr. M. J. Fayer, Pacific Northwest Laboratory, for his assistance with the UNSAT-H computer code and Dr. K. Pruess, Lawrence Berkeley Laboratory, for providing the TOUGH code and for his assistance. The authors wish to acknowledge the contributions of Mssrs. M. A. Lehto, R. M. Martineau, S. D. Cook and N. H. Marshall, of EG&G Idaho, Inc., for their assistance with installing, setting up and running the computer codes and with preparation of the numerous graphical comparisons.

REFERENCES

1. Arpaci, V. S., *Conduction Heat Transfer*, Addison-Wesley, Reading, MA (1966).
2. Baca, R. G., I. P. King, W. R. Norton, "Finite Element Models for Simultaneous Heat and Moisture Transport in Unsaturated Soils," in the *Proceedings of the Second International Conference on Finite Elements in Water Resources*, Imperial College, Pentech Press, London (1978).
3. Baker, A. J., *Finite Element Computational Fluid Mechanics*, Hemisphere Publishing Corporation, New York, NY (1983).
4. Bear, J. *Dynamics of Fluids in Porous Media*, Dover Publications, Inc., New York, NY (1972).
5. Cass, A., G. S. Campbell, and T. L. Jones, "Enhancement of Thermal Water Vapor Diffusion in Soil", *Soil Sci. Soc. Am. J.*, 48, 25-32 (1984).
6. Carnahan, B., H. A. Luther, and J. O. Wilkes, *Applied Numerical Methods*, John Wiley & Sons, New York, NY (1969).
7. Davis, L. A. and S. P. Neuman, Documentation and User's Guide: UNSAT2 - Variably Saturated Flow Model, WWL/TM-1791-1, Water, Waste & Land, Inc., Ft. Collins, CO (1983).
8. DOE, Environmental Assessment: Reference Repository Location, Hanford Site Washington, DOE/RW-0017, U. S. Department of Energy, Washington, D.C. (1986).
9. El-Kadi, A. I., INFIL, International Groundwater Modeling Center, Holcomb Research Institute, IN (1987).
10. Fayer, M. J., G. W. Gee, and T. L. Jones, UNSAT-H Version 1.0: Unsaturated Flow Code Documentation and Applications for the Hanford Site, PNL-5899, Pacific Northwest Laboratory, Richland, WA (1986).
11. Haverkamp, R., M. Vanclim, J. Touma, P. J. Wierenga, G. Vachaud, "A Comparison of Numerical Simulation Models for One-Dimensional Infiltration", *Soil Sci. Soc. Am. J.*, 41, 285-294 (1977).
12. Huyakorn, P. S., S. D. Thomas, and B. M. Thompson, *Water Resources Research*, 20(8), 1099-1115 (1984).
13. Johnston, R. L., *Numerical Methods, A Software Approach*, John Wiley & Sons, New York, NY (1982).

14. Kirkham, D. and W. L. Powers, *Advanced Soil Physics*, Wiley-Interscience, New York, NY (1972).
15. Marshall, T. J. and J. W. Holmes, *Soil Physics*, Cambridge University Press, Cambridge, London (1979).
16. Milly, P. C. D., "Moisture and Heat Transport in Hysteretic, Inhomogeneous Porous Media: A Matric Head-Based Formulation and Numerical Model," *Water Resources Research*, **18**(3), 489-498 (1982).
17. Patankar, S. V., Numerical Heat Transfer and Fluid Flow, Hemisphere Publishing Corporation, New York, NY (1980).
18. Patera, A. T. "Spectral Element Method for Fluid Dynamics: Laminar Flow in a Channel Expansion," *Journal of Computational Physics*, **54**, 468-488 (1984)
19. Perkins, B., B. J. Travis, and G Depoorter, Validation of the TRACR3D Code for Soil Water Flow Under Saturated-Unsaturated Conditions in Three Experiments, LA-10263, Los Alamos National Laboratory, Los Alamos, NM (1985).
20. Philip, J. R., "Numerical Solution of Equations of the Diffusion Type with Diffusivity Concentration-Dependent II", *Australian Journal of Physics*, **10**(2), 29-42 (1957).
21. Pittman, J. R., "Hydrological and Meteorological Data for an Unsaturated Zone Study Near the Radioactive Waste Management Complex, Idaho National Engineering Laboratory, Idaho, 1985-86," USGS open-file report 89-74 (DOE/ID-22079), U. S. Geological Survey, Idaho Falls, ID (1989).
22. Pruess, K., SHAFT, MULKOM, TOUGH: A Set of Numerical Simulators for Multiphase Fluid and Heat Flow, LBL-24430, Lawrence Berkeley Laboratory, Berkeley, CA (1983).
23. Pruess, K., TOUGH User's Guide, LBL-20700, NUREG/CR-4645, prepared for the U. S. Nuclear Regulatory Commission by Lawrence Berkeley Laboratory, Berkeley, CA (1987).
24. Ross, B., J. W. Mercer, S. D. Thomas, B. H. Lester, Benchmark Problems for Repository Siting Models, NUREG/CR-3097, prepared by GeoTrans, Inc. for the U. S. Nuclear Regulatory Commission, Washington, D.C. (1982).
25. Schnabel, R. R. and E. B. Richie, "Calculation of Internodal Conductances for Unsaturated Flow Simulations: A Comparison," *Soil Sci. Soc. Am. J.*, **48**, 1006-1010 (1984).

26. Skaggs, R. W., E. J. Monke, and L. F. Huggins, An Approximate Method for Determining the Hydraulic Conductivity Function of an Unsaturated Flow, Technical Report No. 11, Water Resources Research Center, Purdue University, Lafayette, IN (1970).
27. Sophocleous, M. A., "Analysis of Water and Heat Flow in Unsaturated-Saturated Porous Media", Ph.D. Thesis, University of Alberta, Edmonton, Alberta (1978).
28. Sophocleous, M. A., Analysis of Water and Heat Flow in Unsaturated-Saturated Porous Media, *Water Resources Research*, 15(5), 1195-1206 (1979).
29. Travis, B. J., TRACR3D: A Model of Flow and Transport in Porous-Fractured Media, LA-9667-MS, Los Alamos National Laboratory, Los Alamos, NM (1984).
30. Updegraff, C. D., Comparison of Strongly Heat-Driven Flow Codes for Unsaturated Media, NUREG/CR-5367, SAND88-7145, prepared by GRAM, Inc., for the U. S. Nuclear Regulatory Commission, Washington, DC (1989).
31. Voss, C. I., A Finite-Element Simulation Model for Saturated-Unsaturated, Fluid-Density-Dependent Ground-Water Flow with Energy Transport or Chemically-Reactive Single-Species Solute Transport, U. S. Geological Survey, Reston, VA (1984).
32. Yeh, G. T. and D. S. Ward, FEMWATER: A Finite-Element Model of Water Flow Through Saturated-Unsaturated Porous Media, ORNL-5567, Oak Ridge National Laboratory, Oak Ridge, TN (1979).

APPENDIX A - DESCRIPTIONS OF INDEPENDENT CODES

Five independent computer codes were selected for use in benchmark testing the single precision version of the UNSAT-H code. These codes are: FEMWATER, TRACR3D, FLASH, TOUGH, and SUTRA. These codes were selected because they were readily available, applicable to a wide ranges of test cases, and/or have been in common use by the technical community. This appendix contains brief descriptions of these computer codes and their major computational features.

FEMWATER Computer Code

Description:

The FEMWATER computer code is designed to simulate saturated-unsaturated flow in porous media. The code solves the two-dimensional flow equation in Cartesian coordinates. The mathematical model implemented in FEMWATER is relatively general and accounts for:

- o Darcian fluid flow by pressure gradients, gravity, boundary fluxes, recharge and withdrawals,
- o heterogeneous and anisotropic media,
- o transitions from unsaturated to saturated flow.

In addition, the FEMWATER code can accommodate problems with complex geometries.

The FEMWATER code is an extension of the code originally developed by Reeves and Duguid (1976). The code uses a Galerkin finite element technique and a Picard iteration algorithm to solve the nonlinear governing equation. The code has various options for solving the governing equations through time such as backward and mid-differencing, Crank-Nicolson, consistent mass and mass lumping. The finite element technique uses a mesh of 4-node quadrilateral elements.

The code accommodates two general types of boundary conditions: (1) Dirichlet or fixed head boundary conditions and (2) Neumann or flux boundary conditions. The computer code generates output for the nodal values of pressure head, volumetric moisture content, and Darcy velocities at each time step. Yeh and Ward (1979) have benchmark tested the FEMWATER code with results published in the literature for other computer codes.

Computer Requirements:

The FEMWATER computer code is written in standard FORTRAN and is easy to install on most mainframes and workstations.

Principal Contact:

Dr. G. T. Yeh
Oak Ridge National Laboratory
P. O. Box X
Oak Ridge, TN 37830

References:

1. G. T. Yeh and D. S. Ward, FEMWATER: a Finite Element Model of Water Flow through Saturated-Unsaturated Porous Media, ORNL-5567, Oak Ridge National Laboratory, Oak Ridge, TN (1979).
2. M. Reeves and J. O. Duguid, Water Movement Through Saturated-Unsaturated Porous Media: A Finite Element Galerkin Model, ORNL-4927, Oak Ridge National Laboratory, Oak Ridge, TN (1976).

TRACR3D Computer Code

Description:

The TRACR3D computer code, version 1.0, is designed to simulate one or two-phase fluid flow and multicomponent contaminant transport in a three-dimensional heterogeneous, porous medium. The mathematical basis for this code uses the equivalent porous continuum analogy and is applicable to water and/or air flow and transport of dissolved radionuclides with decay chain processes. The mathematical models implemented in the code account for the following major processes:

- o liquid and air flow,
- o fluid flow by pressure gradients, gravity and boundary fluxes,
- o mass transport attenuated by advection, dispersion, diffusion, sorption, and decay.

The model theory assumes isothermal conditions and a linear isotherm for the sorption process.

The numerical technique implemented in the TRACR3D code is specifically designed to handle strongly nonlinear problems such those of unsaturated flow in arid sites. An integrated finite-difference technique and a Newton-Raphson iteration algorithm are used to solve the nonlinear flow equations. The mass transport equation is also solved by an integrated finite-difference technique. Donor cell and tensorial anti-dispersion algorithms are options available to the user to minimize numerical dispersion effects.

The code accommodates three types of flow and mass transport boundary conditions. In addition, the codes allows three options for input of soil hydraulic properties: (1) Brooks-Corey equations, (2) van Genuchten equations or (3) tabular input. The code is interfaced with post-processor routines that allow the user to calculate and plot: (1) velocity vectors and (2) pressure and/or concentration contours.

The computer code has been extensively verified with analytical solutions (Travis, 1984) and compared with field data (Perkins, 1985). Version 1.0 of the computer code is maintained under configuration management and software control procedures.

Computer Requirements:

The computer code is written in standard FORTRAN and is operational on a Cray X-MP 2/16 supercomputer.

Principal Contact:

B. J. Travis
Los Alamos National Laboratory
Earth and Space Sciences Division
P. O. Box 1663
Los Alamos, NM 87545

References:

1. Travis, B. J., TRACR3D: A Model of Flow and Transport in Porous Media, LA-9667-MS, Los Alamos National Laboratory, Los Alamos, NM (1984).
2. Perkins, B., B. J. Travis and G. DePorter, Validation of the TRACR3D Code for Soil Water Flow Under Saturated-Unsaturated Conditions in Three Experiments, LA-10263, Los Alamos National Laboratory, Los Alamos, NM (1985).

FLASH Computer Code

Description:

The FLASH computer code is designed to simulate coupled heat and fluid flow in unsaturated fractured-porous media. The code solves the time-dependent, two-dimensional forms of the governing equations in Cartesian or radial coordinate system. The major processes modeled are:

- o liquid and vapor water flow
- o fluid flow by capillary, gravity and thermal forces
- o heat transport by conduction

The model theory uses a "dual permeability" approach for describing fluid flow in discrete fractures and porous continua. The numerical technique implemented in the code is specifically designed to handle strongly nonlinear problems such those of unsaturated flow in arid sites.

A Petrov-Galerkin finite element technique, in conjunction with a Newton-Raphson iteration algorithm, is used to solve the nonlinear governing equations. The code uses a time stepping algorithm that automatically adjusts the time step as necessary maintain a fixed truncation error. The code accommodates any combination of 3-node line elements, 6-node triangular elements, and 8-node quadrilateral elements.

The code accommodates three types of boundary conditions: (1) fixed pressure head and/or temperature, (2) fluid and/or heat flux and (3) free drainage flow boundary. The code is interfaced with a number of post-processor routines that allow the user to calculate and plot: (1) velocity vectors, (2) streamlines or pathlines, (3) pressure and/or temperature contours.

The FLASH computer code has been extensively verified with analytical solutions and benchmark tested with numerous other computer codes such as TRACR3D, FEMWATER, SUTRA, and TOUGH. The computer code is maintained under configuration management and software control procedures.

Computer Requirements:

The computer code is written in FORTRAN 8X and is operational on a Cray X-MP 2/16, SUN workstation and IBM PS/2 with extended memory.

Principal Contact:

R. G. Baca
EG&G Idaho, Inc.
Geosciences Unit
P. O. Box 1625/MS 2107
Idaho Falls, ID 83415

References:

1. R. G. Baca and S. O. Magnuson, "Finite Element Techniques for Nonlinear Porous Flow Equations," to be submitted to Journal of Computational Physics.

TOUGH Computer Code

Description:

The TOUGH computer code is designed to simulate coupled heat and multiphase fluid flow in fractured-porous media. The code solves the time-dependent, three-dimensional forms of the governing equations for coupled water, vapor, air and heat transport. The major processes modeled are:

- o fluid flow by pressure, viscous, and gravity forces,
- o heat transport by conduction, convection, and binary diffusion,
- o changes in thermophysical and hydraulic properties as a function of pressure and temperature

The model theory uses a "multiple continuum" approach for describing fluid flow and heat transport processes. The mathematical model is formulated for a three-dimensional, heterogeneous, anisotropic medium.

The numerical technique implemented in the code is specifically designed to handle strongly nonlinear equations such as those of multiphase flow. An integrated finite-difference technique is used to solve the governing equations; a Newton-Raphson iteration algorithm is employed to handle the nonlinearities of the governing equations. The numerical method uses an arbitrary computational grid composed of node centered grid blocks. The code accommodates the major types of boundary conditions for fluid flow and heat transport.

The computer code has been extensively verified with analytical solutions and benchmark tested using published results for other computer codes.

Computer Requirements:

The TOUGH computer code is written in ANSI FORTRAN 77 and is operational on a Cray X-MP, 2/16.

Principal Contact:

K. Pruess
Lawrence Berkeley Laboratory
Earth Sciences Division
University of California
Berkeley, CA 94720

References:

1. Pruess, K., TOUGH User's Guide, LBL-20700, NUREG/CR-4645, prepared for the U. S. Nuclear Regulatory Commission by Lawrence Berkeley Laboratory, Berkeley, CA (1987).
2. Pruess, K., SHAFT, MULKOM, TOUGH: A Set of Numerical Simulators for Multiphase Fluid and Heat Flow, LBL-24430, Lawrence Berkeley Laboratory, Berkeley, CA (1983).

SUTRA Computer Code

Description:

The SUTRA computer code is designed to simulate saturated-unsaturated fluid flow, and heat or solute transport in a homogeneous, anisotropic porous medium. The code solves the time-dependent, two-dimensional forms of the governing equations in Cartesian or radial coordinate systems. The major processes modeled are:

- o fluid density-dependent saturated-unsaturated groundwater flow,
- o heat transport by advection and dispersion or
- o solute transport attenuated by advection, dispersion, diffusion, sorption and decay.

The model formulation is based on the classical porous media theory (Bear, 1972). The modeling approaches takes advantage of the similarity between the governing equations of heat and solute transport to extend its simulation capability.

The numerical techniques implemented in the SUTRA code are primarily designed to handle saturated flow conditions but nevertheless can solve certain classes of unsaturated flow problems. A Galerkin finite element technique is used to formulate the numerical algorithm. A Picard iteration, i.e., successive substitution, method is used to solve the nonlinear unsaturated flow equation. The code has a control option that allows the user to vary the time step size. The code uses a finite element grid composed of 4-node quadrilateral elements.

The code accommodates a variety of fluid flow, heat transport and solute transport boundary conditions. Primary output of the code are the nodal values for pressure head, temperature or solute concentration. In addition, the code has options for producing line printer plots for the output variables.

The computer code has been verified with analytical solutions and benchmark tested using published results for other computer codes.

Computer Requirements:

The SUTRA computer code is written in standard FORTRAN-77 and is easy to install on most computer systems. The code has been installed on a Cray X-MP, 2/16, SUN workstation and IBM PS/2 model 70.

Principal Contacts:

Clifford I. Voss	HydroSoft, Inc.
U. S. Geological Survey	63 Sarasota Center Blvd., Suite 107
431 National Center	Sarasota, FL 34240
Reston, VI 22092	

References:

1. Voss, C. I., A Finite-Element Simulation Model for Saturated-Unsaturated, Fluid-Density-Dependent Ground-Water Flow with Energy Transport or Chemically-Reactive Single-Species Solute Transport, U. S. Geological Survey, Reston, VA (1984).

APPENDIX B - SUMMARY OF RRMS RESULTS

The relative root mean square (RRMS) was computed in the verification and benchmark test cases and used to judge the quality of the UNSAT-H simulation results. This appendix contains a summary of the UNSAT-H RRMS values obtained in each test case. The table below shows the RRMS values, its corresponding criterion classification (see section 2.3), and a short description of the comparison made.

Problem	RRMS	Classification	Description
VT-1	3.3×10^{-5}	Excellent	Temperature at 4 hours
	4.2×10^{-5}	Excellent	Temperature at 8 hours
	3.3×10^{-5}	Excellent	Temperature at 12 hours
	3.3×10^{-5}	Excellent	Temperature at 16 hours
VT-2	2.5×10^{-5}	Excellent	Temperature at 24 hours
	2.7×10^{-5}	Excellent	Temperature at 48 hours
VT-3	7.4×10^{-2}	Acceptable	Pressure head at 2 hours
	9.6×10^{-3}	Excellent	Moisture content at 2 hours
	7.0×10^{-2}	Acceptable	Pressure head at 4 hours
	8.8×10^{-3}	Excellent	Moisture content at 4 hours
VT-4	7.7×10^{-2}	Acceptable	Pressure head at 2 hours
	1.1×10^{-2}	Good	Moisture content at 2 hours
	6.8×10^{-2}	Acceptable	Pressure head at 4 hours
	8.1×10^{-3}	Excellent	Moisture content at 4 hours
BT-1	2.4×10^{-2}	Excellent	FLASH pressure head at 15 min
	4.8×10^{-2}	Excellent	FLASH pressure head at 30 min
	6.2×10^{-2}	Good	FLASH pressure head at 90 min
	3.1×10^{-1}	Poor	TOUGH pressure head at 15 min
	3.2×10^{-1}	Poor	TOUGH pressure head at 30 min
	4.0×10^{-1}	Poor	TOUGH pressure head at 90 min

Problem	RRMS	Classification	Description
BT-2	3.7×10^{-2}	Excellent	FLASH pressure head at 8 yrs
	1.7×10^{-2}	Excellent	FLASH moisture content at 8 yrs
	4.2×10^{-2}	Excellent	FLASH pressure head at 40 yrs
	1.7×10^{-2}	Excellent	FLASH moisture content at 40 yrs
	1.0×10^{-1}	Good	TOUGH pressure head at 8 yrs
	4.2×10^{-2}	Excellent	TOUGH moisture content at 8 yrs
	1.1×10^{-1}	Fair	TOUGH pressure head at 40 yrs
	3.8×10^{-2}	Excellent	TOUGH moisture content at 40 yrs
BT-3	3.8×10^{-2}	Excellent	FLASH pressure head at 5 days
	2.0×10^{-2}	Excellent	FLASH moisture content at 5 days
	1.2×10^{-2}	Excellent	FLASH pressure head at 105 days
	5.3×10^{-3}	Excellent	FLASH moisture content at 105 days
	1.4×10^{-1}	Fair	FEMWATER pressure head at 5 days
	1.1×10^{-1}	Fair	FEMWATER moisture content at 5 days
	<i>No value</i>	<i>Not Determined</i>	<i>FEMWATER solution not computed after 5 days</i>
BT-4	2.2×10^{-4}	Excellent	SUTRA temperature at 50 cm
	1.8×10^{-4}	Excellent	SUTRA temperature at 210 cm
	9.8×10^{-5}	Excellent	SUTRA temperature at 400 cm
	4.9×10^{-3}	Excellent	FLASH Temperature at 50 cm
	1.3×10^{-4}	Excellent	FLASH Temperature at 210 cm
	9.4×10^{-5}	Excellent	FLASH Temperature at 400 cm
BT-5	7.0×10^{-3}	Excellent	FLASH pressure head at 5 days
	2.5×10^{-3}	Excellent	FLASH moisture content at 5 days
	6.2×10^{-3}	Excellent	FLASH pressure head at 20 days
	2.9×10^{-3}	Excellent	FLASH moisture content at 20 days

DISTRIBUTION LIST

OFFSITE

D. J. Alexander
U. S. Department of Energy
Office of Civilian Radioactive
Waste Management
Forrestal Bldg., MS RW-23-2
Washington, DC 20585

A. K. Bhattacharyya
Department of Environmental Resources
Bureau of Radiation Protection
P. O. Box 2063
Harrisburg, PA 17120

T. C. Chee
U. S. Department of Energy
Research and Management Division
DP-123, A237
Germantown, MD 20545

D. L. Chery, Jr.
U. S. Nuclear Regulatory Commission
MS-4H3
Washington, DC 20555

J. S. Cho
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

R. B. Codell
U. S. Nuclear Regulatory Commission
MS-4H3
Washington, DC 20555

J. C. Corey
Westinghouse Savannah River Site
P. O. Box A
Aiken, SC 29808

P. A. Davis
Sandia National Laboratories
Division 6416
P. O. Box 5800
Albuquerque, NM 87185

P. Dickman
U. S. Department of Energy
Waste Management Project Office
P. O. Box 14100
Las Vegas, NV 89114

M. R. Dolenc
Reynolds Electrical and Engineering Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

R. R. Eaton
Sandia National Laboratories
Fluid Mechanics and Heat Transfer Div.
Albuquerque, NM 87185

L. Ebeling
Reynolds Electrical and Engineering Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

A. I. El-Kadi
Holcomb Research Institute
Butler University
4600 Sunset Avenue
Indianapolis, IN 46208

C. G. Enfield
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

M. J. Fayer
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

R. A. Freeze
Department of Geological Sciences
University of British Columbia
Vancouver, BC V6T 2B4, Canada

G. W. Gee
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

T. C. Gunderson
Los Alamos National Laboratory
P. O. Box 1663, MS K491
Los Alamos, NM 87545

D. Hillel
University of Massachusetts
Dept. of Plant and Soil Science
12A Stockbridge Hall
Amherst, MA 01003

C. Y. Hung
U. S. Environmental Protection Agency
Office of Radiation Programs, ANR-460
401 M Street, S. W.
Washington, DC 20460

W. A. Jury
University of California
at Riverside
Department of Soils
Riverside, CA 90024

C. T. Kincaid
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

E. C. Lemmon
University of Idaho
Dept. of Mechanical Engineering
Moscow, ID 83843

M. J. Martinez
Sandia National Laboratories
Fluid Mechanics and Heat Transfer Div.
Albuquerque, NM 87185

T. J. McCartin
U. S. Nuclear Regulatory Commission
Division of Engineering Safety
Office of Research
NL-005
Washington, DC 20555

J. T. McCord
Washington State University
Dept of Civil Engineering
Pullman, WA 99164-3001

D. B. McLaughlin
Massachusetts Institute of Technology
Department of Civil Engineering
Room 48-329
Cambridge, MA 02139

S. A. Mizell
Desert Research Institute
P. O. Box 60220
Reno, NV 89506

R. Murray
North Carolina Low-Level Radioactive
Waste Management Authority
8701 Murrayhill Dr.
Raleigh, NC 27615

S. P. Neuman
University of Arizona
Dept. of Hydrology and Water Resources
Tucson, AZ 85721

W. Newberry
U. S. Department of Energy
Nuclear Energy LLW Management
Program, NE-24
Washington, DC 20545

T. J. Nicholson
U. S. Nuclear Regulatory Commission
Division of Engineering Safety
MS NL-005
Washington, DC 20555

J. W. Nyhan
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

A. M. Parsons
Sandia National Laboratories
Division 3202
Albuquerque, NM 87545-5800

F. L. Parker
4400 Iroquois
Nashville, TN 37205

R. W. Prindle
Sandia National Laboratories
Division 6312
P. O. Box 5800
Albuquerque, NM 87185

K. Pruess
Lawrence Berkeley Laboratory
Earth Sciences Division
1 Cyclotron Road
Berkeley, CA 94720

T. C. Rasmussen
University of Arizona
Dept. of Hydrology and Water Resources
Tucson, AZ 85721

M. Reeves
INTERA, Inc.
6850 Austin Center Blvd., Suite 300
Austin, TX 78731

D. Reible
Louisiana State University
Dept. of Chemical Engineering
Baton Rouge, LA 70803

J. B. Robertson
Hydrogeologic, Inc.
503 Carlise Dr., Suite 250
Herndon, VA 22070

M. L. Rockhold
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

V. C. Rogers
Rogers & Associates Engineering Corp.
P. O. Box 330
Salt Lake City, UT 84110

B. Sagar
Center for Nuclear Waste Repository
Analyses
Southwest Research Institute
6220 Culebra Rd.
P. O. Drawer 28510
San Antonio, TX 78284

S. G. Schmelling
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

J. L. Smoot
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

C. J. Suen
Brookhaven National Laboratory
Nuclear Waste and Materials
Technology Division
Upton, Long Island, NY 11973

R. J. Starmer
U. S. Nuclear Regulatory Commission
Division of Waste Management, MS-5E4
Washington, DC 20555

Technical Library
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

Technical Library
Oak Ridge National Laboratory
P. O. Box X
Oak Ridge, TN 37830

Technical Library
Savannah River Laboratory
P. O. Box 1663
Los Alamos, NM 87545

B. J. Travis
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

S. Tyler
Water Resources Center
Desert Research Institute
P. O. Box 60220
Reno, NV 89506

M. T. Van Genuchten
USDA-ARS, U.S. Salinity Laboratory
4500 Glenwood Drive
Riverside, CA 92501

A. W. Warrick
University of Arizona
Dept. of Soil and Water Science
Tucson, AZ 85721

E. P. Weeks
U. S. Geological Survey
Federal Center, MS 413
Denver, CO 80225

M. Weinstein
U. S. Nuclear Regulatory Commission
MS NL/S-260
Washington, DC 20555

P. J. Wierenga
University of Arizona
Dept. of Soil and Water Science
Tucson, AZ 85721

J. L. Wilson
New Mexico Institute of Mining
and Technology
Dept. of Geosciences
Socorro, NM 87801

J. L. Yow
Lawrence Livermore National Laboratory
Earth Sciences Department
P. O. Box 808
Livermore, CA 94550
Westinghouse Hanford Company
P. O. Box 1970
Richland, WA 99352

L. C. Brown, MS H4-51
J. W. Camman, MS H4-54
J. D. Davis, MS H4-54
R. Khaleel, MS H4-54
J. C. Sonnichsen, MS H4-54
K. M. Suyama, MS I7-03
L. Vance, MS H4-54

ONSITE

EG&G Idaho, Inc.

R. C. Arnett
R. G. Baca
J. D. Bradford
M. J. Case
S. D. Cook
R. J. MacKinnon
S. O. Magnuson
S. J. Maheras
N. H. Marshall
R. T. Martineau
G. D. Newton
R. L. Nitschke

R. R. Seitz
J. B. Sisson
J. C. Walton

INEL Technical Library
Westinghouse Idaho Nuclear Co., Inc.

T. R. Thomas

U.S. Geological Survey

J. R. Pittman
L. J. Mann

END

**DATE
FILMED**

10/2/92

code solves the time-depe
Cartesian or radial coordi
o fluid density-depe
o heat transport by
o solute transport a
decay.

The model formulation is
modeling approaches tak
of heat and solute transpo