BNL-73482-2005-CP

Helium Flow Induced Orbit Jitter at RHIC

**C. Montag, P. He, L. Jia, A. Nicoletti, T. Satogata, J. Schmalzle,
T. Talerico**

***Presented at the Particle Accelerator Conference (PAC'05)
Knoxville, Tennessee
May 16-20, 2005***

Collider-Accelerator Department

Brookhaven National Laboratory

P.O. Box 5000

Upton, NY 11973-5000

www.bnl.gov

Managed by

Brookhaven Science Associates, LLC

for the United States Department of Energy under

Contract No. DE-AC02-98CH10886

This is a preprint of a paper intended for publication in a journal or proceedings. Since changes may be made before publication, this preprint is made available with the understanding that it will not be cited or reproduced without the permission of the author.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or any third party's use or the results of such use of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

FOR UNCLASSIFIED, UNLIMITED STI PRODUCTS

Available electronically at:

OSTI:

<http://www.osti.gov/bridge>

Available for a processing fee to U.S. Department of Energy and its contractors, in paper from:

U.S. Department of Energy
Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37831
Phone: (865) 576-8401
Facsimile: (865) 576-5728
E-mail: reports@adonis.osti.gov

National Technical Information Service (NTIS):

Available for sale to the public from:

U.S. Department of Commerce
National Technical Information Service
5285 Port Royal Road
Springfield, VA 22131
Phone: (800) 553-6847
Facsimile: (703) 605-6900
Online ordering: <http://www.ntis.gov/ordering.htm>

Printed on recycled paper

HELIUM FLOW INDUCED ORBIT JITTER AT RHIC *

C. Montag, P. He, L. Jia, A. Nicoletti, T. Satogata, J. Schmalzle, T. Talerico,
Brookhaven National Laboratory, Upton, NY 11973, USA

Figure 1: Schematic overview of the **RHIC** collider with its six interaction regions.

Abstract

Horizontal beam orbit jitter at frequencies around 10 Hz has been observed in **RHIC** for several years. The distinct frequencies of this jitter have been found at superconducting low-beta quadrupole triplets around the ring, where they coincide with mechanical modes of the cold masses. Recently, we have identified liquid helium flow as the driving force of these oscillations.

INTRODUCTION

The Relativistic Heavy Ion Collider (**RHIC**) at Brookhaven National Laboratory consists of two superconducting storage rings which intersect at six interaction points around the 3.8 km circumference of the machine, as schematically shown in Figure 1. Horizontal orbit jitter at frequencies around 10 Hz can be detected in both rings during regular machine operations [1]. The amplitude of this oscillation scales with the square root of the horizontal β -function at any location around the ring, indicating multiple sources. Given a normalized 6σ emittance of $\epsilon = 10\pi$ mm mrad of the 250 GeV proton beam, the orbit jitter amplitude corresponds to roughly 5 ... 10 percent of the rms beam size. Mechanical vibrations of the superconducting low- β quadrupole triplets at the six interaction

Figure 2: Flow diagram of the **RHIC** triplet cryostat and the associated valve box at the 6 o'clock location.

regions was identified as the source of the observed beam orbit jitter [1].

A kite-element analysis of the triplet assembly revealed that the observed beam jitter frequencies around 10 Hz are very close to the lowest mechanical eigenmodes of the triplet [2]. Given the fact that the effect of cooling the cold masses down to liquid helium temperature was not taken into account in this analysis, the small discrepancy between calculated and measured frequencies is no surprise, and it is very likely that the observed beam jitter frequencies are indeed eigenfrequencies of the triplet assembly. Therefore, an excitation force at practically any frequency around 10 Hz would cause mechanical vibrations of the triplets at their eigenfrequencies, and in turn lead to beam jitter at the observed frequencies.

To investigate the excitation force causing the triplets to vibrate at their eigenfrequencies, experiments were performed involving the cryo system. These experiments indicate that helium pressure oscillations may be the root cause of the observed beam jitter.

HELIUM PRESSURE MEASUREMENTS

To investigate the possible origin of the observed triplet magnet vibrations, helium pressures in the **RHIC** cryogenic system were monitored. Figure 2 shows a schematic flow diagram of one **RHIC** triplet cryostat and its associated valve box. Each triplet cryostat contains five helium transfer lines, supply (S), return (R), utility (U), thermal shield (H), and magnet (M) lines. At an operating temperature of

*Work performed under the auspices of the U.S. Department of Energy

Figure 3: Measured helium pressure P in the magnet line “M” vs. time. The frequency of the observed pressure oscillation is 10.7 Hz.

4.5 K the helium pressure in the magnet line is about 5 bar. The pressure drop in the magnet cooling loop is about 0.25...0.5 bar, and the mass flow rate is 100150 g/sec. To maintain the closed loop flow, a mechanical circulating compressor is used in each ring, located at the 6 o'clock valve boxes. A mechanical cold expander is installed in the refrigerator for pressure reduction in the recooler. Three power lead ports for each ring are extended out locally at each triplet cryostat. To monitor helium pressures, pressure transducers were installed in the five helium transfer lines (S, R, U, H, M) at the 6 o'clock valve box and at the six power lead ports of the 6 o'clock triplet. Pressure measurements performed during the FY04 RHIC run showed a 10.7 Hz oscillation in the “M”-line and a slow oscillation with a period of about 10 seconds in the “U” line, while the other three lines were very stable [3]. Figure 3 shows the measured pressure during 1 second in the “M”-line. This oscillation is caused by the mechanical circulating compressor, and vanishes when this circulator is turned off

OBSERVATIONS WITH BEAM

To study the effect of the helium circulator on the beam jitter, a dedicated experiment was performed in April 2004 during which both circulators were turned off while beam jitter in the “BLUE” RHIC ring was observed with the million-turn beam position monitor. This experiment was conducted under “store” conditions when the observed beam orbit vibration amplitudes are largest due to the β squeeze at the interaction points which results in large β -functions at the vibrating low- β quadrupole triplets. 256k turns were recorded every 30 seconds for about 30 minutes, during which the circulators were turned off and subsequently turned back on after a few minutes. The horizontal rms beam jitter amplitude $\sigma_x(8.5 \text{ Hz} \dots 14.5 \text{ Hz})$ in the frequency range from 8.5 Hz to 14.5 Hz was determined by integrating over the power density spectrum $P(\omega)$ of the

Figure 4: Measured horizontal rms beam jitter in the frequency range from 8.5 Hz to 14.5 Hz when the helium circulators in both rings were turned off.

Figure 5: Example of measured horizontal rms beam jitter in the frequency range from 8.5 Hz to 14.5 Hz during regular beam operations in FY05.

turn-by-turn BPM data,

$$\sigma_x(8.5 \text{ Hz} \dots 14.5 \text{ Hz}) = \sqrt{\int_{2\pi \cdot 8.5 \text{ Hz}}^{2\pi \cdot 14.5 \text{ Hz}} P(\omega) d\omega}. \quad (1)$$

As depicted in Figure 4, the rms beam jitter amplitude in this frequency band dropped by a factor of five when the helium circulators in both were turned off, and increased again when the circulators were turned on.

To ensure that the observed beam jitter amplitude variation is indeed correlated with circulator operations and not just a natural fluctuation, million-turn BPM data were again taken during regular operations in FY05. Data were processed in the same way as during the dedicated experiment described above. Figure 5 shows a typical example of horizontal rms beam jitter amplitudes during about 30 minutes.

During regular beam operations, the rms jitter amplitude is rather stable and shows peak-to-peak variations of

only about 20 percent around the average value, which is far less than the reduction observed when the circulators were turned off during the dedicated experiment (Figure 4). The mean rms jitter amplitude during regular operations is about a factor two smaller than at the beginning and the end of the dedicated experiment. This may be explained by the fact that the average helium pressure in the “M”-line was reduced from 4.7 atm in FY04 to 4.0 atm in FY05.

DISCUSSION

The ~~data~~ presented in this paper strongly point at the cryogenic system as the root cause of the observed beam jitter. However, more experiments are required to confirm this. It is currently planned to increase the helium pressure in the “M”-line from the present 4.0 atm to the FY04 value of 4.7 atm to check whether this influences the beam jitter amplitude. Furthermore, we are planning to repeat the measurement of beam jitter amplitude vs. circulator on/off to gain more confidence that the effect shown in Figure 4 is more ~~than~~ just a coincidence. Monitoring ~~and~~ frequent logging of cryo parameters such as helium pressure, circulator rpms and helium mass flow rate during this dedicated experiment is expected to contribute to an enhanced understanding of the observed effects.

REFERENCES

- [1] C. Montag, M. Brennan, J. Butler, R. Bonati, P. Koello, ‘Measurements of Mechanical Triplet Vibrations in RHIC’, Proc. EPAC 2002, Paris
- [2] J. Schmalzle, unpublished
- [3] L. X. Jia, C. Montag, T. Tallerico, W. Hirzel, and A. Nicoletti, ‘Pressure oscillations in RHIC cryogenic system’, AIP Conf. Proc. 710 154159, 2004