Development of a New Plasma Diagnostic of the Critical Surface and Studies of the Ion Acoustic Decay Instability Using Collective Thomson Scattering

Final Report for Contract DOE-FG03-91SF18861

by

K. Mizuno and J. S. DeGroot, University of California, Davis
W. Seka, Laboratory of Laser Energetics, and
R. P. Drake, Lawrence Livermore National Laboratory

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

Table of Content

I.	Summaries	3
II.	Developments of the collective Thomson scattering diagnostics for the ion acoustic decay instabilities	4
III.	Experimental Arrangements and the CTS experiments	10
IV.	Studies of the Ionic Charge State of High Z plasma	12
V.	The Ion Acoustic Decay Instability in High Power Laser Regime	13
VI.	Studies of laser absorption for moderate to high power irradiations	14
VII.	References	20
VIII.	Figure Captions	21

I. Summaries

We have developed 5-channel collective Thomson scattering system to measure the ion acoustic wave excited by the ion acoustic wave decay instabilities. The multi-channel collective Thomson scattering technique was established with 4ω probe laser beam using GDL laser system at LLE, Univ. of Rochester.

We have obtained the ionic charge state Z by measuring the second harmonic emission from the ion acoustic decay instability. The LASNEX computer simulation calculations have been carried out. The experimental results agree very well with the LASNEX computer simulation results with the flux number $f=0.1$.

In high power laser regime, the spectrum become broad, and the $\Delta\lambda$ decreases indicating that the turbulent like spectrum is observed.

In order to understand the experimental results, we have developed a theory to study absorption of laser and heat transport. This new theory includes the temporal evolution of the heat conduction region. The results agree with flux-limited hydrodynamic simulations.

II. Developments of the collective Thomson scattering diagnostics for the ion acoustic decay instabilities.

1. Measurement of Electron Temperature using Thomson Scattering -- Theoretical Considerations

Collective Thomson scattering is a three wave process satisfying the phase-matching conditions $\vec{k}_s = \vec{k}_o \pm \vec{k}_p$ (see Fig. 2) and the energy conservation $\omega_s = \omega_o \pm \Omega_i$. The k 's and ω 's are the wave vectors and frequencies of the three waves; the subscripts o and s refer to the incident and scattered electromagnetic waves for a probe beam, and the subscript p refers to a longitudinal plasma wave which, in our case, is an ion-acoustic wave generated by the IADI instability. Since $\Omega_i \ll \omega_s$ or ω_o , we have $|k_s| \approx |k_o|$ and

$$k_p \approx 2 k_o \sin (\theta/2), \quad (1)$$

where θ is the scattering angle $\alpha = \pi - \theta$, and $\beta = \alpha/2$. The frequency of the ion-acoustic wave is determined by the dispersion relation

$$\begin{aligned} \Omega_i &= k_p c_s = k_p \sqrt{(T_e/M) (Z + 3T_i/T_e)}, \text{ for } k_p \lambda_{De} \ll 1 \\ &\approx k_p \sqrt{Z T_e/M}, \text{ for high } Z \text{ targets,} \end{aligned} \quad (2)$$

where Z is the average ionic charge, T_e and T_i are the thermal electron and ion temperatures, and M is the average ion mass. For low Z targets such as CH, Ω_i depends only very weakly on the electron-ion temperature ratio, while for high Z targets this effect is negligible.

A good measure of the thermal electron temperature can thus be obtained from a simultaneous measurement of Ω_i and θ , i.e. from a simultaneous measurement of the spectrum and the scattering angle. This forms the basis for our proposed electron temperature measurements.

To aid the design of the experiments, we can estimate the appropriate scattering angles for the electron temperatures expected in our experiments by using Eq. (1) in conjunction with our past observations that the most prevalent values for k_i are found near the Landau damping cut-off, $k_i \lambda_D \approx 0.25$. This yields the simple relationship

$$\sin(\theta/2) = \sqrt{T_{\min}/T_e}, \quad (3)$$

where $T_{\min} \approx 500$ eV and 890 eV for a probe beam of frequency $\omega_0 = 4 \omega_L$ and $3 \omega_L$, with ω_L being the frequency of the plasma-producing laser. This relationship (Eq. (3)) is also plotted in Fig. 1 which clearly shows that good electron temperature measurements can be expected for large angle scattering of the probe beam.

Note that Eq. (3) is used solely for the purpose of estimating the appropriate range of scattering angles for the proposed experiments, while the actual determination of the electron temperature is made by simultaneously measuring ω_i and θ and using Eq. (2) as outlined above.

a. Scattered Power

The required energy of the probe beam is estimated using Thomson scattering theory. For the averaged scattered power in the frequency range $\omega_s \rightarrow \omega_s + d\omega_s$ and within the solid angle $d\Omega$ centered on $\vec{R}$, we have

$$\delta P_s(\vec{R}, \omega_s) d\Omega d\omega_s = \frac{P_0 r_0^2}{2\pi} d\Omega d\omega_s \left| \vec{s} \times \vec{s} \times \frac{\vec{E}_{i0}}{|\vec{E}_{i0}|} \right|^2 \cdot n_{e0} L \cdot S(\vec{k}, \omega) \quad (4)$$

and the spectral density function is defined as

$$S(\vec{k}, \omega) \equiv \lim_{T \rightarrow \infty} \frac{1}{TV} \frac{|\vec{n}_e(\vec{k}, \omega)|^2}{n_{e0}} \quad (5)$$

where P_0 is the incident power of the probe beam, $r_0^2 = e^4/m_0^2 c^4$ is the Thomson scattering cross section, $\vec{s}$ is the unit vector in the direction of the scattering, and L is the length of the interaction region. The time and space averaged ion acoustic wave amplitude may be written using the spectral density function,

$$\frac{|\vec{n}_e(\vec{r}, t)|^2}{n_{eo}} = \left(\frac{1}{2\pi}\right)^4 \frac{1}{n_{eo}} \int_{-\infty}^{\infty} d\omega \int_{-\infty}^{\infty} d\vec{k} S(\vec{k}, \omega) \quad (6)$$

Assuming that $S(\vec{k})$ is constant within a frequency range around Ω_i and the wavelength spread is $\Delta k_x, \Delta k_y, \Delta k_z$, and zero outside, we obtain the scattered power in the solid angle $\Delta\Omega$ from Eqs. (4) and (6)

$$P_s = (2\pi)^3 P_o r_o^2 \Delta\Omega n_{eo}^2 \left| \vec{s} \times \left(\vec{s} \times \frac{\vec{E}}{|\vec{E}_{io}|} \right) \right|^2 \cdot L \cdot \frac{1}{\Delta k_x \Delta k_y \Delta k_z} \cdot \left| \frac{n_e}{n_{eo}} \right|^2 \quad (7)$$

In order to obtain an order of magnitude estimate, we assume approximate values $\Delta k_{x,y,z} \sim 2\pi/\lambda_o$ (λ_o is the wavelength of the probe beam). The wave number of the ion acoustic wave k_p is of order k_o , because of the large scattering angle in our experiments. We obtain the following approximate value of the normalized scattered power

$$P_s/P_o \approx f r_o^2 n_{eo}^2 \Delta\Omega \cdot L \cdot \lambda_o^3 \left| \frac{n_e}{n_{eo}} \right|^2 \quad (8)$$

where f is the fraction of the incident power interacting with the ion acoustic waves. We obtain a scattered power of $P_s \approx 1 \times 10^5$ watt for our experimental parameters, $\left| \frac{n_e}{n_{eo}} \right|^2 = 10^{-4}$, $L = 100 \mu\text{m}$, $f = 0.1$, $\lambda_o = 1/4 \mu\text{m}$, $n_{eo} = 10^{21} \text{cm}^{-3}$, $\Delta\Omega/4\pi = 10^{-3}$, and $P = 10^9 \text{ W}$ (which corresponds to a 100 mJ and 100 psec probe beam). The estimated number of scattered photon is about 10^{11} for the 100 psec probe beam. The Bremsstrahlung emission is given by

$$P_B (\text{W}) = 1.9 \times 10^{-28} \frac{n_e n_i Z^2}{\lambda^2 (\text{\AA}) T_e^{1/2} (\text{eV})} \exp\left(\frac{-hc}{\lambda T_e}\right) \cdot V_p \cdot \frac{\Delta\Omega}{4\pi} \cdot \Delta\lambda (\text{\AA}) \quad (9)$$

We obtain $P_B (\text{W}) \approx 2$ watt for $T_e = 1 \text{ keV}$, a plasma volume $V_p = 6 \times 10^{-5} \text{ cm}^3$ (the width 300 μm and diameter 500 μm), $\Delta\lambda = 10 \text{ \AA}$, solid angle $\Delta\Omega/4\pi = 10^{-3}$, and plasma density $n_e = 10^{21} \text{ cm}^{-3}$. The scattered power is much larger than Bremsstrahlung

emission ($P_s/P_B \sim 10^3$). We have also estimated the scattering power, $P_{s,th}$, from the thermal electrons, which is given by

$$P_{s,th}(W) = \sigma_{Tot} \cdot I_0 \cdot n_e \cdot V_L \cdot \frac{\Delta\Omega}{4\pi} \cdot S(0) \cdot \Delta\lambda \quad (10)$$

and

$$S(0) = \frac{45}{T^{1/2}_e \lambda_0 \sin \frac{\theta}{2}} \quad (11)$$

We obtain $P_{s,th} \approx 0.3$ W for $\sigma_{Tot} = 6.65 \times 10^{-25} \text{ cm}^2$, $I_0 = 10^{12} \text{ W/cm}^2$, $n_e = 10^{21} \text{ cm}^{-3}$, $V = 6 \times 10^{-5} \text{ cm}^3$, $d\Omega/4\pi = 10^{-3}$, $\Delta\lambda = 10^{-6} \text{ \AA}$, $T_e = 1 \text{ keV}$. $P_{s,th}$ is slightly smaller than Bremsstrahlung emission.

The photon number in the scattered probe beam ($\sim 10^{11}$) is much larger than the minimum number required for detection ($10^5 \sim 10^6$), and the scattered power is also much larger than Bremsstrahlung emission ($P_s/P_B \sim 10^3$). Therefore, collective Thomson scattering from the ion acoustic waves can be measured in our experiments.

b. Experimental Accuracy

An estimate of the accuracy of the electron temperature measurement is obtained from Eq. (1):

$$\frac{\Delta T_e}{T_e} = \frac{\cos\left(\pi - \frac{\alpha}{2}\right)}{\sin\left(\pi - \frac{\alpha}{2}\right)} \times \Delta\alpha \quad (12)$$

The estimated uncertainty $|\Delta T_e/T_e|$ for our typical parameters is about 8% with a solid angle $\Delta\Omega/4\pi = 10^{-3}$ and $\alpha = 75^\circ$. We have designed our experiments to have a large scattering angle so that uncertainty in the measure electron temperature is minimized.

Ion acoustic waves are excited by the IADI. It is expected that the ion acoustic waves have a significant width in wave number and propagation angel. However, those widths will not induce any uncertainty in the electron temperature measurement, because we

measure the scattered angle and the frequency of the scattered signal simultaneously (each scattering angle corresponds to one frequency).

The advantage of our technique is that we do not have to know the absolute value of the scattered power to obtain the electron temperature. The measurements do not depend on the intensity of the probe beam. Most important of all, the temperature measurements are independent of the ion acoustic wave amplitude, so that accurate measurements are possible without dealing with the complicated nature of the instability.

c. Probe Beam Refraction

It is important to estimate the refraction of the probe beam at the critical surface of the interaction laser (IR laser). The probe beam is incident onto the plasma with angle u_0 , where the plasma density increases in the x direction (the inset in Fig. 4). Using Snell's Law, the angle of incidence $u(x)$ of the probe beam at the IR critical surface is given by the following relation:

$$\left(1 - \frac{\omega_p^2}{\omega^2}\right) \sin^2 u(x_c) = \sin^2 u_0 \quad (14)$$

where ω_p is the plasma frequency at the critical surface of the IR laser. The refraction of the probe beam $(u(x_c) - u_0)/u_0$ is shown as a function of the incident angle in Fig. 2. For example, with a typical electron temperature of $T_e = 0.8$ keV and a 4ω probe beam, $u_0 = 52^\circ$. Therefore, the refraction $(u(x_c) - u)/u$ is about 4.7%, which produces an error $\Delta T_e/T_e \approx 6\%$ in the electron temperature measurement. The effect of probe beam refraction is thus small for typical plasma parameters.

d. Ion Acoustic Waves Excited by SBS

It is expected that strong ion acoustic waves are excited by stimulated Brillouin scattering (SBS). The wave number of the ion acoustic wave excited by SBS is small, $k_B \approx 2\omega/c$. We obtain the ratio $k_p/k_B \approx 0.125 \times c/v_e \approx 3.2$ for $T_e = 0.8$ keV. This is equivalent to $k_B \lambda_{De}$ (λ_{De} at the critical surface) = 0.08. The dotted curve in Fig. 3(B) corresponds to this case, which is clearly separated from the solid curve. The SBS ion wave may therefore disturb our measurement only when the third harmonic of the ion acoustic wave is strongly excited in a direction perpendicular to the IR laser propagation direction,

which is improbable. Therefore, the ion acoustic waves excited by SBS will not disturb our measurements.

e. Plasma Drift Velocity

The ion acoustic dispersion relation is modified in a drifting plasma:

$$\Omega_i \simeq k_p C_s + \vec{k}_p \cdot \vec{U}$$

where $\vec{U}$ is the plasma drift velocity. The plasma is drifting mainly normal to the target surface. The ion waves are mainly driven along the electric field of the interaction laser, which is perpendicular to the drift direction. Thus, the drifting plasma should not strongly perturb our measurements. We will test the effect of the drift velocity by systematically varying the detection angle.

III. Experimental arrangements and the CTS experiments

1. Developments of the Multi-channel collective Thomson scattering system.

We have constructed a five-channel detector system for the collective Thomson scattering. The system is especially designed to measure the large angle scattering from the ion acoustic decay instabilities. Figure 3 shows the schematics of the collective Thomson scattering system. The scattered signals are collected by the array of five-mirrors. We use optical fibers to guide the signal to a monochromator. The diameters of the mirror and the optical fiber are 1/2 inch and 100 μm . This detector measures the scattered signal from 200 μm diameter. An interference filter is installed in each channel to protect the detector system from strong IR signal. The photographs of the improved version of the 5-channel detector system are shown in Fig. 4. Figure 4 (A), and 4 (B) show the top and side views. The improved version has capability of measuring the signal intensity using a diode array. The diode array is also be used for the calibration of the relative sensitivity of the each channel. The two-dimensional, angle and wavelength distribution is obtained with the film placed on the output of the monochromator.

Experiments

Figure 5 shows a schematic of the experiment. The interaction IR laser is normally incident onto a planar target. The ion acoustic wave will be strongly excited by the IADI in the direction of the electric field of the IR laser. A probe beam is incident on the IADI region and is scattered by the ion acoustic wave. An array of small lenses (see Fig. 5) will be used to measure the angular distribution of the scattered signal.

We set the incident angle $u_0 = 52^\circ$ of the probe beam as is shown in Fig. 5. The growth rate of the IADI will be proportional to $(\cos \theta)^2$, where θ is the angle between the wave vector of the ion acoustic wave and the electric field of the interaction laser. The ion wave vector will have an angular spread with a peak near $\theta = 0^\circ$. The scattering angle is, about 115° for T_e is 0.6 keV, large angle scattering. We see from Eq. (3) that T_e is a well behaved function of the scattering angle for our typical experimental parameters. The signals are collected by an array of lenses with a solid angle $\Delta\Omega/4\pi = 10^{-3}$ (one inch diameter lens placed at 20 cm from the target) and are fed to a monochromator.

Simultaneous measurements for the scattering angle and the wave length of the scattered signal are obtained on film with two dimensional plots.

The alignment of the detector system, and the 4ω laser probe beam was made using 254 nm UV light from Hg lamp. We used a shadow method to accurately measure the alignment position. The UV signal of 254 nm was applied through the optical fiber. A tiny PM tube (Hamamatsu-R-1657) was placed just behind the 200 μ m diameter spherical target. The target position was slowly moved by a stepping motor. The signal amplitude was recorded on a synchronized chart recorder. Each mirror position was adjusted so that the dip of the signal was obtained when the target was at the center of the GDL chamber. The laser probe beam positioning was also made using this shadow method. The 5-channel collective Thomson scattering system was installed and calibrated in the GDL system.

IV. Studies of the Ionic Charge State of High Z Plasma

It is possible to estimate the ionic charge state Z near the critical surface by measuring the second harmonic emission. The ionic charge state Z is obtained by measuring the ion wave frequency Ω_i of the most unstable ion acoustic wave excited by the IADI, and using the following equation:

$$Z = \left(4.4 \times \frac{\Omega_i^2}{\omega_{pe}} \right)^2 \times \frac{M}{m} - 3 \frac{T_i}{T_e}$$

The plasma density which corresponds to the Z measurements is obtained from the equation

$$\frac{N_e}{N_c} = 1 - 3 (M/m) (\Delta\lambda/\lambda_{2\omega_0})^2 / (Z + 3 T_i/T_e)$$

by measuring $\Delta\lambda$, and Z from the second harmonic emission due to IADI.

The measured plasma density which corresponds to the most unstable wave of the ion acoustic decay instability is about $n/n_c=0.86$.

A relatively weak intensity laser is incident on a planar target slightly above the threshold of the IADI. The second harmonic emissions are measured for CH, Mo, and gold targets with the irradiation of laser energy of $3 \times 10^{13} \text{ W/cm}^2$. The wavelength shift $\Delta\lambda$ (the difference between the $2\omega_0$ peak and the Stokes peak) clearly decreases as the atomic number of the target increases, as shown in Fig. 6. The estimated value of the ionic charge state Z is shown in Fig.7 for CH, Mo, and Gold targets.

We have also made LASNEX computer simulation calculations. The computer simulation results (with the flux number $f=0.1$) agree very well with the experimental results.

V. The Ion Acoustic Decay Instability in High Power Laser Regime

The ion acoustic decay instability with high power laser irradiation is quite different from the results with moderate intensity laser. The spectrum width of the Stokes peak increases with the laser intensity. Figure 8 shows a typical spectrum of the second harmonic emission. The sharp peak at the left-hand side is the $2\omega_0$ signal which is attributed to the emission from the electron plasma wave produced by the resonance absorption. The right-hand side peaks are the Stokes modes by the IADI. We define I_p and I_m as the peak value of the Stokes mode, and the minimum value of the valley. Then the parameter I_p/I_m shows the degree of the spectrum broadening of the Stokes mode. If $I_p/I_m = 1$, the spectrum is flat, and if it is small, the spectrum is sharp. The $\Delta\lambda$, distance between the $2\omega_0$ and the Stokes peaks give the frequency of the ion acoustic wave.

Figure 9 (A) show the I_p/I_m vs laser intensity. At laser power slightly above the threshold, the Stokes peak is sharp, so that the I_p/I_m is small. The I_p/I_m increases strongly with laser intensity. The I_p/I_m is nearly 1 when the laser intensity is larger than 1×10^{14} W/cm². The plasma spectrum become very broad, indicating that turbulent like spectrum is observed. The figure 9 (B) shows $\Delta\lambda$ vs laser intensity. The $\Delta\lambda$ decreases with the laser intensity as is expected in turbulent like spectrum.

VI. Studies of Laser Absorption for Moderate to High Power Irradiations

1. Hydrodynamic Equations

Consider a planar plasma driven by a laser energy flux ($I(t)$) that is suddenly switched-on and then remains constant in time, i. e., $I(t) = 0$, for $t < 0$, and $I(t) = I_0$ for $t \geq 0$. We will develop self-similar solutions of the planar, one fluid hydrodynamic equations for each region. The equations for conservation of mass, momentum, and energy are

$$\frac{\partial \rho}{\partial t} + \frac{\partial(\rho v)}{\partial x} = 0 \quad (15)$$

$$\frac{\partial v}{\partial t} + v \frac{\partial v}{\partial x} = - \frac{1}{\rho} \frac{\partial(\rho c^2)}{\partial x} \quad (16)$$

$$\frac{3}{2} \rho \frac{\partial c^2}{\partial t} + \frac{3}{2} \rho v \frac{\partial c^2}{\partial x} + \rho c^2 \frac{\partial v}{\partial x} = - \frac{\partial q}{\partial x} + \frac{\partial I}{\partial x} \quad (17)$$

where ρ is the mass density, v is the fluid velocity, c is the isothermal sound speed,

$c \equiv (P/\rho)^{1/2}$, P is the pressure, q is the heat flux, $I(x)$ is the spatially dependent laser energy flux, $I(x) = I_0 \exp(-\tau(x))$, I_0 is the incident laser energy flux, and $\tau(x)$ is the inverse Bremsstrahlung optical depth of the plasma from $x' = x$ to $x' = \infty$, i. e.,

$$\tau(x) = \int_x^\infty \kappa_{ib}(x') dx'. \quad (18)$$

The inverse Bremsstrahlung absorption coefficient is given by

$$\kappa_{ib}(x) = 3.4 \frac{(\rho/\rho_c)^2 Z \ln \Lambda_a}{\sqrt{1 - n_e/n_c} \lambda_{\mu m}^2 T_{keV}^{3/2}} \text{ cm}^{-1} \quad (19)$$

where ρ_c and n_c are the critical mass and number densities, n_e is the electron number density, $\ln \Lambda_a$ is the Coulomb logarithm for inverse Bremsstrahlung absorption, $\lambda_{\mu m}$ is the laser light wavelength (μm), and T_{keV} is the electron temperature (keV). The ponderomotive force is neglected since the radiation pressure due to the laser light is small compared to the plasma pressure for cases of interest. Radiation from the plasma and the inertial force due to ablative acceleration of the target have also been neglected. These terms are generally small for parameters of interest to laser pellet fusion, especially for shorter wavelength lasers. The electron and ion temperatures are assumed to be equal, so that $c^2 = (Z+1)T/(A M_p)$, Z is the ionic charge state, A is the atomic weight, and

M_p is the proton mass. The heat flux is given by the smaller of the classical heat flux and a phenomenological model for limited heat flux, i.e.,

$$q = \text{Min} \left[K_0 T_e^{5/2} \left| \frac{\partial T_e}{\partial x} \right|, f n_e T_e (T_e/m)^{1/2} \right] \left| \frac{\partial T_e}{\partial x} \right| \quad (20)$$

where the heat flux coefficient is $K_0 = 1.8 \times 10^{29} / Z \ln \Lambda, \text{ cm}^{-1} \text{ sec}^{-1} \text{ keV}^{-5/2}$, $\ln \Lambda$ is the Coulomb logarithm, m is the electron mass, and f is the flux limiter.

2. Conduction Region Model

We will show *a-posteriori* that the laser energy is deposited predominantly in the corona for moderate to high laser powers and typical pulse widths. We will therefore ignore laser deposition and develop a self-similar solution for the conduction region. We take the similarity variable to be, $s = (x - x_a) / \Delta_s(t)$, where, $\Delta_s(t)$ is the width of the conduction region, $\Delta_s = x_s - x_a$, to be determined. Guided by the LASNEX simulations, we assume that the dependent variables can be written: $\rho(x,t) = \rho_s(t)R(s)$, $v(x,t) = c_s(t)V(s)$, and $c^2(x,t) = c_s^2 E(s)$. The boundary conditions are: $E(0) = V(0) = 1/R(0) = 0$, and $E(1) = V(1) = R(1) = 1$. The hydrodynamic equations become

$$rR - s(n+1) \frac{dR}{ds} = - \frac{c_s t}{\Delta_s} \frac{d(RV)}{ds} \quad (21)$$

$$(r+n)RV - s(n+1) \frac{d(RV)}{ds} = - \frac{c_s t}{\Delta_s} \frac{d(RV^2 + RE)}{ds} \quad (22)$$

$$\frac{3}{2} \left[2nE - s(n+1) \frac{dE}{ds} \right] + \frac{3}{2} \frac{c_s t}{\Delta_s} V \frac{dE}{ds} + \frac{c_s t}{\Delta_s} E \frac{dV}{dx} = \frac{c_s t}{\Delta_s} \frac{K_0 T_s^{7/2}}{\rho_s c_s^3 \Delta_s} \frac{1}{R} \frac{d \left[E^{5/2} \frac{dE}{ds} \right]}{ds} \quad (23)$$

where

$$\frac{\partial \rho_s}{\partial t} = \frac{r \rho_s}{t}, \quad (24)$$

and

$$\frac{\partial c_s}{\partial t} = \frac{n c_s}{t}. \quad (25)$$

Eqs. (21) - (23) are self-similar (i.e., not explicitly a function of time and space) if: The factor, $(c_s t)/\Delta_s$ and the factor, $K_0 T_s^{7/2}/(\rho_s c_s^3 \Delta_s)$ are not a function of time. Using

Eqs. (24) and (25) the second condition results in, $r = 3n - 1$. Another condition results from requiring that the absorbed laser energy is the plasma energy source, i.e.,

$$I_0 = \beta \rho_s c_s^3 \quad (26)$$

where β is a constant that depends on the plasma spatial profile. This results in, $r = -3n$, or we find, $r = -1/2$ and $n = 1/6$.

The solution of Eqs. (21) - (23) require the solution of a set of four first order, nonlinear differential equations that are very difficult to solve. However, guided by the LASNEX simulations we find the following approximate solutions: $E \approx s^{2/5}$, $V \approx s^{3/5}$, and $R \approx 1/V$. The approximate solutions for the conduction region are therefore

$$T \approx T_s [(x - x_a)/\Delta_s]^{2/5} \quad (27)$$

$$v \approx c_s [(x - x_a)/\Delta_s]^{3/5} \quad (28)$$

$$\rho \approx 1/v \quad (29)$$

Since the local sound speed (c) is proportional to $T^{1/2}$, we see that one important prediction is that the Mach number ($M = v/c$) is equal to the normalized temperature. The predicted normalized temperature (from Eq. (27)) is in agreement with temperature (circles) and Mach number (diamonds) from LASNEX simulations. (The width of the conduction region was set equal to the LASNEX result (0.026 cm) for this figure.) The agreement is good for the three laser wavelengths shown ($\lambda = 0.35, 0.53$, and $1.059 \mu\text{m}$). We also see that the width of the conduction region is independent of wavelength. This agrees with results from the self-similar theory as will be shown below. In the LASNEX simulations, a thick aluminum slab was irradiated with a peak incident laser energy flux, $I_0 = 1 \times 10^{15} \text{ W/cm}^2$. The results are shown at the peak of the Gaussian pulse (pulse width, $t_L = 2 \text{ ns}$ (Full Width Half Maximum, FWHM)). The flux limit was, $f = 0.1$, for these calculations, and the heat flux for the conduction region was low enough so that the heat flux was below the flux limit.

3. Corona region Model

The well known similarity solution for the expansion of an isothermal plasma into vacuum is used for the corona region, i.e.

$$\rho(x, t) = \rho_s \exp(-(x - x_s)/c_s t) \quad (30)$$

$$v(x, t) = c_s + (x - x_s)/t$$

The range of validity of this assumption is determined *a-posteriori*. The isothermal rarefaction is maintained by a mass flux ($\rho_s c_s$) from the subsonic region and an energy flux ($\rho_s c_s^3$) due to laser absorption.

A. Heat Flux in the Corona

The heat flux in the corona can be found by integrating Eq. (17) $(\int_x^\infty dx')$ to obtain

$$q(x) = -\alpha(x)I_0 + \rho(x)c(x)^3 \quad (31)$$

where $\alpha(x)$ is the laser absorption in the plasma from x to ∞ , i.e.,

$\alpha(x) = 1 - \exp(-\tau(x))$. The terms with the derivative of the temperature (first and second terms in Eq. (17)) were neglected compared to the third term. It will be shown *a-posteriori* that these terms are small in the corona. We showed that in the steady state conduction region model the temperature must be a maximum at the sonic surface. Thus, the heat flux is zero at the sonic surface and in the isothermal corona. In our present time dependent model the heat flux is not zero in the corona and the heat flux at the sonic surface is (Eq. (31) evaluated at $x = x_s$)

$$q_s = -\alpha_s I_0 + \rho_s c_s^3. \quad (32)$$

Eq. (32) can be reduced to the steady state model by setting $q_s = 0$, so that $\alpha_s = \rho_s c_s^3 / I_0$, which along with $I_0 = 4\rho_s c_s^3$, from the steady state model gives $\alpha_s = 1/4$ in agreement with the steady state model.

4. Width of the Conduction region

The key features of our self-similar model are that the conduction region is subsonic and evolves in time. One estimate for the width of the subsonic region of a laser heated plasma, Δ_s , is the width of the subsonic region in the expansion of an isothermal plasma, $\Delta_{is} = c_s t$. The subsonic region in a laser heated plasma must be smaller than this because the subsonic region in a laser heated plasma is certainly not isothermal. In our model, the sonic surface is the boundary between the conduction and corona regions. The width of the conduction region is found by requiring that the heat flux in the corona (Eq. (32)) and the heat flux in the conduction region are equal at the sonic surface. Eq. (27) for the temperature in the conduction region is used to find the heat flux at the sonic surface, $q_s = -(2/5) K_0 T_s^{7/2} / \Delta_s$. Substituting this equation into Eq. (32) and solving for Δ_s results in

$$\Delta_s = \frac{2}{5} \frac{K_0 T_s^{7/2}}{\alpha_s I_0 - \rho_s c_s^3}. \quad (33)$$

Another equation for the width is found by matching the spatial derivative of the velocity at the sonic surface. From the approximate solution for the subsonic region (Eq. (28)), the derivative of the velocity is

$$\frac{\partial v}{\partial x}(x \leq x_s) \approx 0.6 \frac{c_s}{\Delta_s},$$

and, $\frac{\partial v}{\partial x} (x \geq x_s) \approx \frac{1}{t}$ from the supersonic region (Eq. (30)). Another equation for the width of the subsonic region is therefore

$$\Delta_s \approx 0.6 c_s t. \quad (34)$$

The sonic surface moves outward relative to the ablation surface at a velocity of $\approx 0.6 c_s$.

5. Plasma Properties

One condition on the plasma properties at the sonic surface is obtained by equating the absorbed laser flux, $I_0 t$, to the total plasma energy/area. The total plasma energy/area for the conduction region is obtained by using Eqs. (27) - (29) to form the energy density and then integrating over the conduction region. This energy/area is added to the energy/area for the corona ($4\rho_s c_s^3$), resulting in

$$I_0 \approx 5.5 \rho_s c_s^3. \quad (35)$$

Another equation is obtained by equating Eq. (33) to Eq. (34), resulting in

$$c_s t \approx 0.8 \frac{K_0 T_s^{7/2}}{I_0}. \quad (36)$$

In the spirit of our model, we assumed that the laser energy was deposited in the corona ($\alpha_s \approx 1$). The resulting density, temperature and mass ablation rate at the sonic surface are

$$\rho_s = 1.7 \times 10^{-9} \left[\frac{I_0}{Z t \ln \Lambda} \right]^{1/2} \left[\frac{A}{Z+1} \right]^{7/4} \text{ gm/cm}^3, \quad (37)$$

$$T_s = 1.1 \times 10^{-5} [Z I_0 t \ln \Lambda]^{1/3} \left[\frac{Z+1}{A} \right]^{1/6} \text{ keV}, \quad (38)$$

$$\rho_s c_s = 1.7 \times 10^{-4} \frac{I_0^{2/3}}{[Z t \ln \Lambda]^{1/3}} \left[\frac{A}{Z+1} \right]^{7/6} \frac{\text{gm}}{\text{cm}^2 \text{ sec}}, \quad (39)$$

Here, the units are: I_0 (W/cm^2), λ (μm), and t (ns). The ablation pressure is

$$P_a = 2 \rho_s c_s^2 = 3.4 \times 10^{-11} \frac{I_0^{5/6}}{(Z \ln \Lambda t)^{1/6}} \frac{A^{7/12}}{(Z+1)^{7/12}} \text{ Mbar}. \quad (40)$$

The key feature of these solutions is that the plasma properties at the sonic surface and the ablation pressure are not a function of laser wavelength. The mass density (Eq. (37)), temperature (Eq. (37)) at the sonic surface, and the ablation pressure (Eq. (40)) are compared to LASNEX simulations (circles, $\lambda = 1.059 \mu\text{m}$, crosses, $\lambda = 0.53 \mu\text{m}$,

triangles, $\lambda = 0.35 \mu\text{m}$) at the peak of the laser pulse. The target is a thick aluminum slab (in the model, the aluminum was taken as fully ionized in agreement with the LASNEX results). The width of the Gaussian laser pulse is, $t_L = 2 \text{ ns}$ (FWHM). The laser pulse width was reduced by a factor of 0.53 to compare our constant laser energy flux model to the Gaussian laser pulse used in the LASNEX simulations. (The factor is chosen so that the absorbed laser energy used in the model calculations is the same as in the LASNEX simulations.) Calculations were made for peak laser energy fluxes of, $I_0 = 1 \times 10^{14}$ and $1 \times 10^{15} \text{ W/cm}^2$ and laser wavelengths , $\lambda = 0.35, 0.53$, and $1.059 \mu\text{m}$. The LASNEX results are in good agreement with the self-similar theory. The steady state theory gives results that disagree by a factor of 2 to 3.

The time dependence from the self-similar theory agrees with the LASNEX simulations . The laser pulse in the LASNEX simulations was Gaussian (FWHM = 2ns) until the peak, then constant in time.

In agreement with the theory, LASNEX calculations of the spatially dependent pressure are to be closely independent of wavelength ($\lambda = 0.35 \mu\text{m}$ and $0.53 \mu\text{m}$ are shown) over the whole plasma. The pressure agreed in the conduction region and was about 20% lower in the corona. This reduced pressure is a direct result of limiting the heat flux as can be seen by solving Eq. (31) for the pressure, $P = (q + \alpha I_0)/c$.

VI. References

1. K. Mizuno, W. Seka, R. Bahr, R.P. Drake, P.E. Young, J.S. De Groot, and K. Estabrook, "Ion Acoustic Parametric Decay Instabilities in Laser Plasma Interactions," Laser Interaction and Related Plasma Phenomena, vol. 9, edited by Hora and G.H. Hiley.
2. K. Mizuno, P.E. Young, W. Seka, R. Bahr, J.S. De Groot, R.P. Drake, and K.G. Estabrook, Phys. Rev. Lett. 65, 428 (1990).
3. C. Yamanaka et al, Phys. Rev. Lett 30, 594 (1973).
4. J.L. Bobin, et al., Phys. Rev. Lett., 594 (1973)
5. K. Eidman and R. Sigel, Phys. Rev. Lett. 34, 799 (1975)
6. N.G. Basov, et al., Sov. Phys. JETP 49, 1059 (1979)
7. X. Zhihan, et al., J. Appl. Phys. 54, 4902 (1983)
8. Y. Takada, et al., Phys. Fluids 31, 692 (1988)
9. P.D. Carter, S.M. Sim, and T.P. Hughes, Opt. Commun, 27, 423 (1987)
10. K. Tanaka, et al., Phys. fluids 27, 2187 (1984)
11. K. Mizuno, J.S. De Groot, and K.G. Estabrook, Phys. Rev. Lett. 52, 271 (1984); Phys. Fluids 29, 568 (1968)
12. K. Mizuno, J.S. De Groot, W. Woo, P.W. Rambo, and K.G. Estabrook, Phys. Rev. 38, 4333 (1988).
13. K. Mizuno, F. Kehl, and J.S. De Groot, Phys. Rev. Lett. 56, 2184 (1986)
14. K. Mizuno and J.S. De Groot, The Proceedings of the 1987 International Conference on Plasma Physics, Kiev, USSR, 654, (1987) (edited by A.G. Stencko)
15. K. Mizuno and J.S. De Groot, "Anomalous Thermal Electron Heating and Heat Transport Inhibition Due to Parametric Instability," Phys. Fluids (in press)
16. J.S. De Groot, et al., The Proceedings of the Seventh International Workshop on Laser Interactions and Related Plasma Phenomena, Plenum Press (1987)
17. P.W. Rambo, W. Woo, J.S. De Groot, and K. Mizuno, Phys. Fluids 27, 2234 (1984)
18. K. Estabrook and W.L. Kruer, Phys. Fluids 26, 1888 (1983)
19. J.E. Bernard and J. Meyer, Phys. Fluids 29, 2313 (1986)
20. H.A. Baldis, D.M. Villeneuve, and C.J. Walsh, Can. J. Phys. 64, 961 (1986)

VII. Figure Captions

Fig. 1 Theoretical results of T_e vs the scattering angle.

Fig. 2 The refraction of the probe laser beam.

Fig. 3 The schematics of the collective Thomson scattering device.

Fig. 4 The pictures of the 5-channel detector . (A) top view, and (B) side view.

Fig. 5 The schematics of the collective Thomson scattering experiments.

Fig. 6 The spectrum of the 2ω emission for CH, Mo, and Au targets. The inset shows the normalized ion acoustic wave frequency vs atomic number.

Fig. 7 The estimated values of the ionic charge state vs atomic number.

Fig. 8 A typical second harmonic spectrum, which is shown define the parameters of I_p and I_m .

Fig. 9 (A) The measurement of the spectrum broadening. The I_m/I_p vs laser intensity. CH target.
(B) The measurements of the frequency shift. The $\Delta\lambda$ vs laser intensity.

Fig. 1

REFRACTION

Angle of probe beam at the critical surface
of IR laser

Fig. 2

Five-Channel Detector System for the Collective Thomson Scattering

Fig. 3

(A)

(B)

Fig. 4

The Schematics of the Collective Thomson Scattering

Fig. 5

Fig. 6

Z ESTIMATED FROM IADI

Fig. 7

Spectrum Broadening

Fig. 8

Fig. 9

END

**DATE
FILMED
9/17/92**