170
1-6-77

Calculating Fission Product Inventories in Peach Bottom FTE-4 Fuel Rods Using the ORIGEN Code

W. Davis, Jr.
C. W. Kee
V.C.A. Vaughen
M. L. Tobias

MASTER

OAK RIDGE NATIONAL LABORATORY

OPERATED BY UNION CARBIDE CORPORATION FOR THE ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
Price: Printed Copy \$3.50; Microfiche \$3.00

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration/United States Nuclear Regulatory Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

ORNL/TM-5691
Dist. Category UC-77

Contract No. W-7405-eng-26

CHEMICAL TECHNOLOGY DIVISION

CALCULATING FISSION PRODUCT INVENTORIES IN PEACH BOTTOM FTE-4
FUEL RODS USING THE ORIGEN CODE

W. Davis, Jr.
C. W. Kee
V. C. A. Vaughen
M. L. Tobias

Manuscript Completed: June 1976
Date Published: January 1977

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

NOTICE This document contains information of a preliminary nature. It is subject to revision or correction and therefore does not represent a final report.

Prepared by the
OAK RIDGE NATIONAL LABORATORY
OAK RIDGE, TENNESSEE 37830
operated by
UNION CARBIDE CORPORATION
for the
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

CALCULATING FISSION PRODUCT INVENTORIES IN PEACH BOTTOM FTE-4 FUEL RODS USING THE ORIGIN CODE

W. Davis, Jr., C. W. Kee, V. C. A. Vaughen, and M. L. Tobias

ABSTRACT

Nondestructive gamma-ray analyses (NDA) for fission products and mass-spectrometric analyses for five uranium isotopes in two samples of fuel removed from the Peach Bottom reactor have been compared with corresponding quantities calculated from reactor operating data using the ORIGIN code to form the basis for material balance calculations in head-end reprocessing steps. Satisfactory agreement between ORIGIN results and measured uranium isotopic distributions was found with the standard ORIGIN inputs.

Many fission products of interest, including ^{89}Sr , ^{91}Y , ^{95}Zr , ^{95}Nb , ^{103}Ru , ^{106}Ru , $^{127}\text{Te}^*$, $^{129}\text{Te}^*$, ^{131}I , ^{134}Cs , and ^{144}Ce , have half-lives that are less than about 2 years. Comparisons of ORIGIN calculations and NDA values for ^{95}Zr , ^{106}Ru , ^{125}Sb , ^{134}Cs , ^{144}Ce , and ^{154}Eu demonstrated the need to include realistic reactor operating data, including shutdown times, in the ORIGIN input parameters.

1. INTRODUCTION

Quantities of activation products (such as ^{14}C), actinides, and fission products formed in samples and fuel rods irradiated in the Peach Bottom reactor¹ may be calculated by use of the ORIGIN^{2,3} code and various parameters. Nuclear data libraries used in these calculations are frequently updated^{3,4} to improve the accuracies of calculated values; these may be used to provide cross checks for mass balances calculated from analytical data obtained from head-end reprocessing studies and from nondestructive gamma-ray scanning.⁵ Tobias⁶ has reported on some calculations for driver fuel and on the sensitivity of calculated values to the variation of several of the input parameters.

The usual calculations performed with ORIGIN are based on broad averages such as effective full-power days (EFPD). This approximation to reality is adequate for calculating reactor core inventories for nuclides with relatively long half-lives. However, for specific small fuel samples and for many nuclides of interest⁵ [(e.g., ^{89}Sr , ^{91}Y , ^{95}Zr , ^{95}Nb , ^{103}Ru , ^{106}Ru , $^{127}\text{Te}^*(109\text{d})$, $^{129}\text{Te}^*(33.4\text{d})$, ^{131}I , ^{134}Cs , and ^{144}Ce], inventories calculated on the basis of EFPD will be biased with respect to true inventories because radioactive decay in the time corresponding to the difference between true calendar days and EFPD is neglected. This bias can be eliminated by use of irradiation data, including actual irradiation times and power levels during operating intervals and shutdown-time intervals. Additional improvement may be obtained from more detailed knowledge of fluxes at the specific rod locations in the reactor core during the successive irradiation intervals.

obtained from more detailed knowledge of fluxes at the specific rod locations in the reactor core during the successive irradiation intervals.

The ORIGEN code requires input data obtained from flux and temperature distributions in the Peach Bottom reactor, as well as the various nuclear libraries that pertain to a high-temperature gas-cooled reactor. The terms THERM, RES, FAST, RITH, RING, RIF, etc., as defined by Bell,² are calculated from available information and are described in the next section.

2. PREPARATION OF ORIGEN INPUT DATA

Tobias⁶ has made calculations of ORIGEN input parameters for fuel element E06-01 in the Peach Bottom reactor; these are summarized in Table 1 and in the following equations in terms of the four-group fluxes listed by Wallroth.¹

From the definitions:

$$X \equiv \varphi_4 * Q/W,$$

$$Y \equiv \varphi_1 * P/R,$$

and

$$Z \equiv (\varphi_1 - Y) + \varphi_2 + \varphi_3 + (\varphi_4 - X),$$

we may obtain the input values of THERM, RES, and FAST for ORIGEN as follows:

$$\text{THERM} = \sqrt{\pi/4 * 293.16/T},$$

where

$$T = \text{sample (in reactor) temperature, } ^\circ\text{K};$$

$$\text{RES} = Z/(X * U);$$

$$\text{FAST} = 1.45 * Y/X.$$

The lethargy interval, U , conforms to Bell's definition of RITH. The definitions of ORIGEN terms SIGF, SIGNG, RING, and RIF are also used in the Tobias calculations; terms σ_{fi} and σ_{ci} are average cross sections for fission and capture, respectively, of the fissile nuclide (^{232}U , ^{233}U , or ^{235}U) in the flux band i ($i = 1, 2, 3, 4$). However, cross sections of each of the nuclides ^{232}U , ^{233}U , and ^{235}U were calculated for this study as follows:

$$\text{SIGF} = \sigma_{f4} * \text{THERM},$$

$$\text{SIGNG} = \sigma_{c4} * \text{THERM}.$$

Finally,

$$\text{RING} = U * [\sigma_{c1}(\varphi_1 - Y) + \sigma_{c2}\varphi_2 + \sigma_{c3}\varphi_3 + \sigma_{c4}(\varphi_4 - X)]/Z,$$

$$\text{RIF} = U * [\sigma_{f1}(\varphi_1 - Y) + \sigma_{f2}\varphi_2 + \sigma_{f3}\varphi_3 + \sigma_{f4}(\varphi_4 - X)]/Z.$$

The four-group cross sections used were from Table 2 of ref. 6.

The current study uses a modified definition of SIGF, SIGNG, RING, and RIF, which results in the same final reaction rate for use in the ORIGEN calculations; however, different

Table 1. Fluxes, lethargy intervals, and other parameters
pertaining to Peach Bottom fuel

Flux	Upper energy, E_u (eV)	Lower energy, E_l (eV)	Lethargy interval [$\Delta u = \ln (E_u/E_l)$]
φ_1	14.96E+6	8.65E+4	5.1530 $\equiv$ R
φ_2	8.65E+4	1.76E+1	8.5000 $\equiv$ S
φ_3	1.76E+1	2.38	2.0008 $\equiv$ V
φ_4	2.38	0.001 ^a	7.7749 $\equiv$ W
$P \equiv \ln (14.96E+6/1.0E+6) = 2.7054$			
$Q \equiv \ln (0.5/0.001) = 6.2146$			
$U \equiv \ln (1.0E+6/0.5) = 14.5087$			

^aWe use a lower limit of 0.001 eV, instead of 0. as listed by Wallroth,¹
for the lower energy of neutrons in the fourth flux group.

intermediate numbers apply. The modified definitions used in this study are given in Sect. 2.2.

At present, values for flux φ_4 are available for the individual rods at only a few times, as shown in Table 2. These have been used to provide fluxes for use in the ORIGIN code. For example, at the three real times of 356, 845, and 1142 days after July 15, 1970, the values of φ_4 for sample FTE-4-3-5-7 were 3.374×10^{13} , 4.294×10^{13} , and 4.530×10^{13} , respectively.¹ Multiplying each of these by the ratio $\ln(0.5/0.001)/\ln(2.38/0.001)$, which equals 0.79932, gives the three different values for flux used in these ORIGIN calculations.

2.1 Calculation of ORIGIN Input Values from Peach Bottom Parameters

Information provided by Wallroth has been used in desk-calculator calculations of input parameters required by ORIGIN; for convenience, it has also been used as the basis of a computer program (Appendix A) that generates both cards and magnetic tape information required for ORIGIN. The code to utilize the Peach Bottom reactor information uses fluxes, as in hand calculations, to determine THERM, RES, and FAST, and to determine the fluxes as a function of time. For determining the fluxes as a function of time, it is necessary to know the absolute value of φ_4 during each time period of the irradiation, including shutdown times when $\varphi_4 = 0$. The time-averaged ratios of φ_1/φ_4 , φ_2/φ_4 , and φ_3/φ_4 are also needed for each time period. In addition to the flux and temperature information, the program requires the composition of the sample, appropriate titles, and a list of decay times for which calculations are to be made. The irradiation, shutdown, and decay times may be presented as days (or hundredths of a day) following some reference time, or simply as calendar dates. In either case, the ORIGIN printout includes a table listing the corresponding days used in the ORIGIN calculations.

2.2 Reactor Dependence of the Code

The code assumes the input flux spectrum and cross sections given in Tables 1 and 2 of ref. 6. The ORIGIN code defines the cross sections of the main components (Table 2 of ref. 6) using only one of the factors (THERM) and a zero for resonant and fast cross sections. The thermal cross section is defined as:

$$\Sigma\sigma_i\varphi_i/(\text{THERM} * \text{Flux})$$

ORIGIN immediately collapses the three-group cross sections using THERM, RES, and FAST as weighting factors. Thus, after collapsing the cross sections and multiplying by the flux, the ORIGIN code will obtain a reaction rate of $\Sigma\sigma\varphi$. The end result is the same as that obtained by Tobias.

Table 2. Irradiation, power, and flux data for samples FTE-4-3-1-8 and FTE-4-3-5-7

Trevor time point ^a	Real time ^b (days)	Average reactor power ^a [MW(t)]	Real exposure time (days)	Effective full-power days ^a (EFPD)	Fluxes for samples FTE-4- [neutrons cm ⁻² sec ⁻¹ (1.0E-13)]			
					FTE-4- ϕ_4^c		ORIGEN calculations ^e	
					3-1-8	3-5-7	3-1-8	3-5-7
7	356.1	94.2	56.4	46	3.164 (3.164) ^d	3.374 (3.374) ^d	2.53	2.70
8	412.5	93.4	55.6	45	(3.164) ^d	(3.374) ^d	2.53	2.70
9	468.1	0.	22.0	0	0	0	0	0
10	490.1	103.2	47.0	42	(3.164) ^d	(3.374) ^d	2.53	2.70
11	537.1	0.	162.0	0	0	0	0	0
12	699.1	91.0	145.9	115	(3.164) ^d	(3.374) ^d	2.53	2.70
13	845.0	0.	46.0	0	4.038	4.294	0	0
14	891.0	91.7	80.6	64	(4.038) ^d	(4.294) ^d	3.23	3.43
15	971.6	103.2	51.5	46	(4.038) ^d	(4.294) ^d	3.23	3.43
16	1023.1	0.	20.0	0	0	0	0	0
17	1043.1	106.4	98.8	91	(4.260)	(4.530)	3.41	3.62
18	1141.9				4.260	4.530		

^aData from ref. 7.

^bSince July 15, 1970.

^cData from ref. 1.

^dAssumed to be unchanged until a different value is given.

^eSee text.

3. PRELIMINARY RESULTS AND COMPARISONS

Preliminary results of ORIGIN calculations are shown for uranium isotopic compositions in Table 3 with the pertinent analytical data. Calculated and mass spectrometric values of uranium isotopic compositions appear to be in good agreement for samples FTE-4-3-1-8 and FTE-4-3-5-7. The word "good" is more qualitative than quantitative at present.

In like manner, fission-product activities are presented in Table 4. These fall into three groups: (1) sample FTE-4-3-5-7, for which there is good agreement between ORIGIN calculations and the results of the nondestructive (NDA) gamma-ray scanning for seven gamma-emitting isotopes; (2) sample FTE-4-3-1-8, for which there is a consistently low ratio NDA/ORIGIN; and (3) the two nuclides ^{152}Eu and ^{155}Eu , for which there is no agreement between ORIGIN calculations and the gamma-ray scanning for either fuel sample.

The ratios of the values of NDA/ORIGIN approximate unity for ^{95}Zr , ^{106}Ru , ^{125}Sb , ^{134}Cs , ^{137}Cs , ^{144}Ce , and ^{154}Eu . This is considered to be a satisfactorily close agreement. The actual average of these seven values for sample FTE-4-3-5-7 is 1.09; the standard deviation is 0.19. The significantly lower values of the seven ratios, NDA/ORIGIN, for sample FTE-4-3-1-8 (average = 0.36, standard deviation = 0.15) are still under investigation by wet chemical techniques (the subject of a later report). The ^{152}Eu and ^{155}Eu discrepancies are explained by the low counting rates of these isotopes after a 2-year decay period.

Preliminary calculations were made to estimate the "residual nitrogen"^a content of the fuel rods from ^{14}C analyses. The amount of N_2 present during irradiation ("residual nitrogen") may be estimated by comparison of the ORIGIN results with the ^{14}C contents of the burner off-gases during the reprocessing studies (Table 5). The production of ^{14}C from ^{14}N predominates over that from ^{13}C . Based on the ratio of ^{14}C found experimentally to that produced from 1.0 g of N_2 (per ORIGIN) we estimate that the "residual N_2 " was 435 ppm in rod 4-3-1-8, and 1640 ppm in rod 4-3-5-7, based on total heavy-metal content. The ^{14}C values are valid only for fuel rods (i.e., matrix graphite and pyrolytic carbon). Block graphite was not analyzed in this study.

4. DISCUSSION

While some of the calculated results shown in Tables 3 and 4 suggest that the input data for two fuel samples from the Peach Bottom reactor yield relatively accurate ORIGIN results, at least two types of input data need further investigation, namely flux and the value of RES.

The fluxes used in ORIGIN (shown in Table 2) are based on only three sets of values for ϕ_1 , ϕ_2 , ϕ_3 , and ϕ_4 , although the power is seen to be different for each of the seven different nonzero power levels. A more detailed flux-time history obtained from reactor operating data appears likely to provide further improvement in ORIGIN calculations.

The second variable requiring additional investigation is RES. A series of calculations with the ORIGIN program, in which only RES was varied, showed that the quantities of ^{95}Zr , ^{106}Ru , ^{125}Sb , ^{137}Cs , and ^{144}Ce (direct fission products) were not sensitive to the magnitude of

^a It is likely that the fluidizing gas for the final LTI coating was N_2 , although it is not clear if definitive data for these very early fuels can be retrieved at this time.⁷

Table 3. Uranium isotopic compositions and burnup

Nuclide	Input	Composition (wt %)			
		FTE-4-3-1-8		FTE-4-3-5-7	
		ORIGEN	Mass spectrometer	ORIGEN	Mass spectrometer
²³² U	0.00	7.6E-04	-	4.3E-04	-
²³³ U	0.00	14.6	12.73	7.70	8.38
²³⁴ U	1.50	1.96	1.49	1.81	1.08
²³⁵ U	93.14	71.1	72.49	76.3	74.9
²³⁶ U	0.51	7.26	7.39	8.29	8.23
²³⁷ U	0.00	6.2E-10	-	7.4E-10	-
²³⁸ U	4.85	5.15	5.89	5.65	7.41
²⁴⁰ U	0.00	5.1E-29	-	9.4E-29	-
Burnup, MWd(t)/MT					
Fissile stream		536,000		558,000	
Fertile stream		10,200		11,300	
Power density, MW/MT					
Fissile stream		716		746	
Fertile stream		13.3		14.7	

Table 4. Comparisons of fission-product activities, measured (NDA) and calculated (ORIGEN)^a

Fission product	FTE-4-3-1-8			FTE-4-3-5-7		
	ORIGEN	Gamma scan (NDA)	NDA/ORIGEN	ORIGEN	Gamma scan (NDA)	NDA/ORIGEN
⁸⁶ Kr	1.26E+11			1.19E+11		
⁹⁰ Sr	1.01E+12			1.00E+12		
⁹⁶ Zr	8.08E+10	3.11E+10	0.39	7.67E+10	1.02E+11	1.33
⁹⁶ Nb	1.73E+11			1.65E+11		
¹⁰⁶ Ru	3.89E+11	1.13E+11	0.29	3.97E+11	5.00E+11	1.27
¹¹⁰ Ag	6.59E+09			6.96E+09		
¹²⁵ Sb	3.67E+10	1.78E+10	0.49	3.33E+10	2.89E+10	0.87
¹³⁴ Cs	5.43E+11	1.04E+11	0.19	5.81E+11	5.11E+11	0.88
¹³⁷ Cs	1.00E+12	3.15E+11	0.32	9.95E+11	1.19E+12	1.20
¹⁴⁴ Ce	4.47E+12	1.14E+12	0.26	4.39E+12	5.00E+12	1.14
¹⁵² Eu	1.03E+08	4.44E+09	43.	9.83E+07	1.11E+10	113.
¹⁵⁴ Eu	2.85E+10	1.78E+10	0.63	3.10E+10	2.89E+10	0.93
¹⁵⁶ Eu	6.64E+09	1.11E+11	17.	6.88E+09	2.06E+11	29.9

∞

^aActivities are in disintegrations per minute for the whole sample.

Table 5. Carbon-14 activities and calculated nitrogen contents
for samples FTE-4-3-1-8 and FTE-4-3-5-7

	FTE-4 sample	
	3-1-8	3-5-7
Weight in sample, U+Th, g	5.74	2.93
C, g	4.44	4.29
¹⁴ C yield calculated from reaction		
¹³ C(n,γ), dpm/g C	1.083E+5	1.146E+5
¹⁴ N(n,p), dpm/g N	1.245E+10	1.316E+10
Measured ¹⁴ C activity, dpm/g C	7.11E+6	1.49E+7
Estimated nitrogen content, g N/MTHM ^a	435	1640
g N/MTC ^b	562	1120

^aMTHM is metric tons of U+Th in the sample charged to the reactor.

^bMTC is metric tons of carbon in the sample.

RES. However, the quantities of ^{134}Cs and ^{154}Eu (activation products) are very sensitive to the value of RES. Further improvements in methods to calculate RES should yield improved estimates for the activation products.

5. REFERENCES

1. C. F. Wallroth, "FTE-4 and FTE-15 Fuel Rod Transfer to ORNL," letter to V. C. A. Vaughen, General Atomic Company File FTEA/202/CFW/75 (May 9, 1975).
2. M. J. Bell, *ORIGEN - The ORNL Isotope Generation and Depletion Code*, ORNL-4628 (May 1973).
3. *ORIGEN - Isotope Generation and Depletion Code - Matrix Exponential Method*, RSIC Computer Code Collection, CCC-217 (April 26, 1975).
4. C. W. Kee, *A Revised Light Element Library for the ORIGEN Code*, ORNL/TM-4896 (May 1975).
5. V. C. A. Vaughen, F. F. Dyer, and K. H. Valentine, *Determination of Fission Product Inventories in FTE-4 Fuel Rods by Gamma Scanning*, GCR: 75-37 (December 1975).
6. M. Tobias, *Estimates of Fission-Product Inventories in Fuel Element E06-01 of the Peach Bottom Core 2: Results, Comparisons, and Sensitivity Study*, ORNL/TM-4705 (October 1974).
7. C. F. Wallroth, J. R. Holzgrath, D. D. Jensen, and L.R. Zumwalt, *Post-irradiation Examination and Evaluation of Peach Bottom Fuel Test Elements FTE-4*, General Atomics Co., GA-A13452 (to be published).

APPENDIX A. COMPUTER CALCULATION OF ORIGIN INPUT DATA FROM PEACH BOTTOM PARAMETERS

The code to convert Peach Bottom reactor parameters to ORIGIN input data has been written in two versions. One version is for time-sharing use (PDP-10 version); it prompts the user for information. The time-sharing version allows free format input with consecutive input numbers separated by commas. The other version is for batch processing with card input (IBM 360 version); it assumes a standard order for the information. The batch version uses the formats listed below. The order in which the information is requested (or read) is the same for either version.

A. Reads: IO Format: I5

IO is the unit number to be used for output of the ORIGIN deck. For the IBM 360, this should correspond to a DD card referencing the card punch or a disc file. For the PDP-10 at ORNL, a value of 1 to 4 or 10 to 29 results in output to a file FORnn.DAT where nn is the two digit representation of IO.

B. Reads: TEMP Format: F10.0

TEMP - Temperature in °C

C. Reads: PHI1, PHI2, PHI3, PHI4 Format: 4F10.0

These are the time averaged values of φ_1 , φ_2 , φ_3 , and φ_4 , respectively. Since only the ratios are important, common factors (such as 10^{13}) may be omitted.

D. Reads: ISTRT, ITYPE Format: I10, I5

ISTRT is the time at which irradiation starts.

ITYPE describes the format of ISTRT and all other times.

If ITYPE = 1, all times are input as calendar dates. The first two digits from a six-digit time or the first four digits from an eight-digit time are interpreted as being the year. The next two digits are the month and the last two digits are the day of the month. The algorithm for determining the number of days between two dates considers leap years. As an added refinement, the algorithm considers century years as being leap years only when divisible by 400 if four-digit years are used. It is important that all dates have the same number of digits for the year (i.e., either 2 or 4) for any given case.

If ITYPE = 2, all times are assumed to be given in hundredths of a day. If ITYPE = 3, all times are assumed to be in days.

E. Reads: IIRR(I), FLX(I) Format: I10, F10.0

IIRR(I) is the end of the time period in which the flux ϕ_4 has the value FLX(I). Successive times are input until a nonpositive time occurs. If desired, any common factor of the flux values (e.g., 10^{13}) can be listed as the flux corresponding to the time, which is nonpositive, since all previous values of the flux are multiplied by this number (if it is greater than one). All the times must be of the form referred to by ITYPE.

F. Reads: IDEC(J)

Format: 110

IDEC(J) is the time (J) to be listed in the ORIGEN output as a decay time after reactor discharge. Times are read until a nonpositive value occurs. All must be defined as referenced by ITYPE.

G. Reads: CASE

Format: 10A4

CASE is a 40-character case name used in constructing titles for ORIGEN output. The titles are constructed by adding "IRRADIATION TIMES" or "DECAY TIMES" as appropriate.

H. Reads: BASIS

Format: 10A4

BASIS is a 40-character subtitle which appears in the ORIGEN output after the word "BASIS." BASIS and CASE are usually identified with a set of concentrations rather than with an irradiation history.

I. Reads: NO, MASS, GATOM

Format: I2, I3, F10.3

Cards (or lines) of this type are read until a card (or line) with NO = 0 is encountered. These values are the input composition. NO is the atomic number; MASS is the atomic mass; and GATOM is the charge in gram-atoms. The code distinguishes between materials of construction and actinides by examining the atomic number. If the material is a material of construction (i.e., NO < 85), a naturally occurring element can be indicated by making MASS = 0.

J. Reads: MORE

Format: 15

(MORE corresponds to NGO in the ORIGEN manual). There are two possible valid choices for MORE. If MORE is zero the code assumes that everything about the next case may be different and the next input is of type A. If MORE is negative the next case will have different titles and charge composition only. The next input is of type G and inputs of type A through F are assumed to be the same. Positive values for MORE are not allowed. If a positive value is input by mistake, the code will behave as if MORE is negative, but the next case (if there is one) will not be run successfully by ORIGEN.

There are two normal ways for the program to stop. When IO is read (type A) the program checks for an end-of-file indication. When input of type C is read the program stops

if PH11 = 0.

Running the ORIGIN Deck

The output deck is a complete set of ORIGIN input. It can be run at ORNL with the following control cards:

```

Job card
Class card (L = 20, suggested)
/*ROUTE PRINT LOCAL (for PDP-10 submission)
// EXEC ORIGIN
//GO.FT05F001 DD *
Deck of ORIGIN input
/*
//

```

If no materials of construction are needed, that part of the data library can be omitted by including the card

```
//GO.FT25F001 DD DUMMY
```

just before the DD card for unit 5. If, during any execution of this program, the last value of MORE is zero, the deck may be followed by any other complete ORIGIN deck. As many decks as desired may be stacked in this way.

INTERNAL DISTRIBUTION

1. J. W. Allen	55. R. E. Leuze
2. J. L. Anderson	56. K. H. Lin
3. B. J. Baxter	57. T. B. Lindemer
4. R. E. Blanco	58-59. E. L. Long
5. J. O. Blomeke	60-61. A. L. Lotts
6. W. D. Bond	62. A. P. Malinauskas
7. J. Botts	63. L. E. McNeese
8. R. E. Brooksbank	64. R. P. Morisette
9. K. B. Brown	65. E. Newman
10. R. A. Bradley	66. K. J. Notz
11. W. D. Burch	67. W. H. Pechin
12. C. Carney	68. R. H. Rainey
13. J. Carter	69. A. P. Roeh
14. W. L. Carter	70. A. D. Ryon
15. C. F. Coleman	71. C. D. Scott
16. J. H. Coobs	72. J. W. Snider
17. J. H. Cooper	73. R. G. Stacy
18. L. T. Corbin	74. T. N. Tiegs
19-27. W. Davis, Jr.	75-76. M. L. Tobias
28. F. E. Dearing	77. D. B. Trauger
29. F. F. Dyer	78. W. E. Unger
30. D. E. Ferguson	79-88. V. C. A. Vaughen
31. C. L. Fitzgerald	89. K. H. Valentine
32. R. W. Glass	90. B. L. Vondra
33. J. H. Goode	91-92. C. F. Wallroth
34. F. E. Harrington	93-94. R. P. Wichner
35. C. C. Haws	95. R. G. Wymer
36. J. R. Hightower	96. R. D. Zimmerman
37. N. Holder	97. W. K. Davis (Consultant)
38. J. Holzgrath	98. C. H. Ice (Consultant)
39. F. J. Homan	99. E. J. Gaden, Jr. (Consultant)
40-47. P. R. Kasten	100. R. B. Richards (Consultant)
48-49. C. W. Kee	101-102. Central Research Library
50. R. K. Kibbe	103. Document Reference Section
51. E. M. King	104-105. Laboratory Records
52. W. J. Lackey	106. Laboratory Records-RC
53. W. Laing	107. ORNL Patent Office
54. C. E. Lamb	

EXTERNAL DISTRIBUTION

- 108. Research and Technical Support Division, ERDA, ORO
- 109. Director, Reactor Division, ERDA, ORO
- 110-111. Director, Reactor Development and Demonstration, ERDA,
Washington, DC 20545
- 112-113. Director, Division of Nuclear Fuel Cycle and Production,
ERDA, Washington, DC 20545
- 114-289. Given distribution as shown in TID-4500 under Gas-Cooled
Reactor Technology category, UC-77 (25 copies - NTIS)