(200)

R210

ms. 76-288

USGS-OFR-76-288

UNITED STATES DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY

[Reports - Open file
series]

Magnetotelluric soundings in the
Darrrough Hot Springs Area, Nevada

TM

cm

Iwanaka

By

J.E. O'Donnell

U.S. Geological Survey

Open-file Report No. 76-288
1976

This report is preliminary and has not been
edited or reviewed for conformity with U.S.
Geological Survey standards and nomenclature.

MASTER

269793

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Magnetotelluric Soundings in the Darrough
Hot Springs Area, Nevada

By J.E. O'Donnell

Two magnetotelluric soundings (MTS) were made in the Darrough Hot Springs area, one at the hot springs ($38^{\circ} 49' 29''$ latitude, $117^{\circ} 10' 55''$ longitude) and the other four miles east ($38^{\circ} 49' 20''$ latitude, $117^{\circ} 06' 30''$ longitude) of the hot springs. The Cagniard resistivities are tabulated in table one along with the audio-magnetotelluric data for the hot springs and the one-dimensional model apparent resistivities derived from the data. The MTS data (.01-.3 Hz) is strongly anisotropic with the north-south (ρ_x) resistivities being approximately a factor of ten greater than the east-west (ρ_y) resistivities for the lower frequencies. Further more the data was found to be too three-dimensional for two-dimensional tensor analysis. An average apparent resistivity was made (table 1) for the Darrough Hot Springs site and then used for inversion data to produce the model given in table 2.

SITE: DARROUGH HOT SPRINGS

COMPUTED
MODEL DATA
FROM $\bar{\rho}$

FOUR MILES EAST OF
DARROUGH HOT SPRINGS

f	ρ_x	ρ_y	$\bar{\rho}$	ρ_A	ρ_x	ρ_y
0.01	12	3.0	4.0	5.0	20.0	0.6
0.04	80	10.0	10.0	6.4	70.0	4.0
0.08	4	0.6	1.5	4.6	7.0	0.7
0.12	3	0.4	1.1	3.5	2.0	0.7
0.16	3	0.8	1.5	2.8	1.2	0.9
0.20	3	1.0	1.7	2.4	1.5	0.9
0.24	6	1.0	2.4	2.2	1.5	0.8
0.28	10	3.0	5.5	2.0	1.0	2.0
7.5	5.7	5.0	5.3	2.9		
10.0	6.3	2.6	4.0	3.2		
14.0	5.3	3.0	4.0	3.7		
27.0	5.9	3.9	4.8	4.9		
76.0	6.6	6.3	6.4	8.5		
285.0	9.2	10.6	9.9	21.5		
6700.0	786.0	108.0	290.0	330.0		
10200.0	826.0	309.0	500.0	475.0		

TABLE 1 CAGNIARD RESISTIVITIES AND FREQUENCIES FOR TWO SITES AND MODEL RESISTIVITIES
COMPUTED FOR DARROUGH HOT SPRINGS.

LAYER	RESISTIVITY (OHM-METRES)	THICKNESS (METRES)
1	800.0	80
2	1.6	340
3	4.0	230
4	0.6	160
5	60.0	6400
6	0.5	--

TABLE 2 THEORETICAL MODEL USED TO DERIVE APPARENT RESISTIVITIES
GIVEN IN TABLE 1.