DOE/CE/50280--71

DOE/CE/50280--T1

DE93 006099

PHASE ONE REPORT
ALCOHOL TRANSPORTATION FUELS
DEMONSTRATION PROGRAM

FOR THE
U. S. DEPARTMENT OF ENERGY

Grant No. DE-FG01-88CE50280

BY THE
HAWAII NATURAL ENERGY INSTITUTE

2540 Dole Street, Honolulu, Hawaii 96822

Edited by
Charles M. Kinoshita

MASTER

0811

ED

TABLE OF CONTENTS

SUMMARY	i
I. INTRODUCTION	1
II. PROPOSED SCOPE OF WORK	1
III. PHASE ONE ACCOMPLISHMENTS	2
Task 1. Survey of Energy Situation and Ground Transportation Status in Hawaii	3
Task 2. Survey of Natural Energy Resources and Bio-methanol Potential in Hawaii	4
Task 3. Installation of Methanol Refueling Facility	4
Task 4. Demonstration of Methanol-Fueled Vehicles and Hybrid Generators	5
Task 5. Evaluation of Strategies for Methanol Fueled Diesel Engines	7
Task 6. Dissemination of Information on Methanol Fuel and Methanol-Fueled Vehicles	8
Task 7. Plan for Transition to Use Methanol Fuel in the State of Hawaii	8
IV. CONCLUSIONS	9
DOCUMENTS AND PUBLICATIONS RELATING TO THIS PROGRAM	10

SUMMARY

The State of Hawaii is unique in the nation in that it is almost entirely dependent on imported petroleum for transportation and for electricity; thus, the state is highly sensitive to fluctuations in global fuel oil prices and energy supplies. Presently, Hawaii pays the highest prices in the nation for transportation fuels and electricity. Fortunately, Hawaii has abundant natural energy resources, especially biomass, that could be used to produce alternative fuels for ground transportation and electricity. Concerns over vehicle exhaust emissions and global warming, and over pollution from oil spills, also favor conversion to biofuels.

This report summarizes activities performed during 1988 to June 1991 in the first phase of the Alcohol Transportation Fuels Demonstration Program. The Alcohol Transportation Fuels Demonstration Program was funded initially by the Energy Division of the State of Hawaii's Department of Business, Economic Development and Tourism, and then by the U.S. Department of Energy.

This program was intended to support the transition to an alternative transportation fuel, methanol, by demonstrating the use of methanol fuel and methanol-fueled vehicles, and solving the problems associated with that fuel. Specific objectives include surveying renewable energy resources and ground transportation in Hawaii; installing a model methanol fueling station; demonstrating a methanol-fueled fleet of (spark-ignition engine) vehicles; evaluating modification strategies for methanol-fueled diesel engines and fuel additives; and investigating the transition to methanol fueling. All major objectives of Phase 1 were met (survey of local renewable resources and ground transportation, installation of methanol refueling station, fleet demonstration, diesel engine modification and additive evaluation, and dissemination of information on alternative fueling), and some specific problems (e.g., relating to methanol fuel contamination during handling and refueling) were identified and solved. Several key issues emerging from Phase 1 (e.g., methanol corrosion, flame luminosity, and methanol-transition technoeconomics) were recommended as topics for follow-on research in subsequent phases of this program.

ALCOHOL TRANSPORTATION FUELS DEMONSTRATION PROGRAM

I. INTRODUCTION

With no indigenous fossil energy resources, Hawaii's economy is almost totally dependent on imported petroleum fuels. Hawaii pays the highest prices in the nation for petroleum fuels to meet its ground transportation, aviation, and power generation needs. The energy demand in Hawaii, like that for the rest of the world, keeps growing, but petroleum resources are finite. In addition, changes in energy pricing or supply, or political disturbances quickly and dramatically affect Hawaii's economy. Therefore, energy security and energy diversification have been and continue to be major economic issues and goals for Hawaii. During the past decade, pollution from automobile emissions and global warming have gained international concern, prompting the introduction and adoption of various new regulations. Restrictions on carbon monoxide, reactive unburned hydrocarbons, particulates, and nitrogen and sulfur oxides often favor the use of alternative fuels. Among the various alternative ground transportation fuels being considered, methanol appears to be the most promising. Hawaii's tropical climate and rich biomass resources make the concept of producing methanol fuel from indigenous renewable resources especially attractive from both the energy self-sufficiency and environmental protection standpoints.

During the 1980's, the Hawaii Natural Energy Institute of the University of Hawaii (HNEI) conducted various surveys, and research and demonstration on alternative transportation fuels, funded by the Department of Business, and Economic Development and Tourism (DBED), including operating and testing a small methanol fleet. In 1988, the U.S. Department of Energy (USDOE) decided to examine the transition of a small community to methanol fueling for ground transportation. HNEI submitted a proposal to perform such a study, and received an award for a five-year methanol demonstration program in 1989. This report summarizes work performed in the first phase of that program.

II. PROPOSED SCOPE OF WORK

The proposal called for a survey of Hawaii's biomass resource base and ground transportation, investigating the following areas:

Biomass resource base

- Types of biomass — grasses, fast growing trees, aquatic plants, residues, ...;
- Annual yield — current yield, potential output;
- Plantation — location, climatic conditions, agronomic and transportation conditions, ...;
- Technology — commercial, adaptation of existing technologies, emerging technologies;
- Economics — plantation costs, conversion costs;
- Environmental concerns — waste treatment, ...

Energy consumption

- Breakdown by end-use — power generation, ground transportation, aviation, industrial;
- Breakdown by energy resource — petroleum, coal, natural gas, renewable energy;
- Prediction of future demand.

Ground transportation

- Passenger vehicles — number, usage, power rating, fuel consumption;
- Diesel engines — application, manufacturer, age, power rating, fuel consumption;
- Techniques for using alternative fuels — type of engine, cost.

HNEI proposed to install a model methanol fueling station during the survey period. The major reasons for installing the facility were to:

1. Serve federal and state demonstration fleets, followed by private vehicles;
2. Gain experience in shipping and handling methanol fuel;
3. Provide a model fueling station and explore strategies for retrofitting existing stations;
4. Evaluate issues relating to fuel contamination, long-term storage, tank system ventilation, spark arresting, vapor recovery, tank leak detection, and tank-wall corrosion;
5. Evaluate economic factors, including costs of methanol tank and equipment, installation, data logging, and operations.

HNEI's existing fleet of seven methanol vehicles (one General Motors S-10 Chevy pickup truck, one Ford Crown Victoria, and five Ford Escorts) was proposed for the demonstration program. They were to be assigned to DBED, HNEI, and the Pacific International Center for High Technology Research (PICHTR) for use in daily work functions. The following activities were planned:

1. Evaluate methanol fuel and methanol vehicles — convenience, starting, drivability, reliability, and durability;
2. Evaluate refueling facility — convenience, safety, durability;
3. Identify and solve potential problems — gain experience for follow-on large-scale demonstration fleet;
4. Increase the acceptability of methanol fuel and methanol-fueled vehicles — make alternative fuels more acceptable to the public;
5. Train service team — fuel station operation, fuel testing, vehicle maintenance.

Since the demand for diesel fuel is greater than the demand for gasoline on some Hawaiian islands, studies on methanol as a possible replacement for diesel fuel were proposed. Regulations concerning soot emissions from city buses and trucks also made these evaluations important.

1. Evaluate engine combustion system modification strategies — applicable techniques, cost for replacement or retrofitting;
2. Evaluate additives for lubrication and cetane enhancement — concentrations required and associated cost;
3. Evaluate post-combustion treatment technologies — secondary burning, catalytic conversion.

Also, a preliminary plan for a more extensive demonstration of methanol applications was proposed as outlined below:

1. Design methanol distribution system — identify service sites for methanol distribution and locations for bulk storage;
2. Investigate the feasibility of producing methanol fuel from indigenous resources;
3. Prepare technical studies for widespread methanol applications — examine methanol's corrosive nature, enhancement of flame luminosity;
4. Evaluate biomass-methanol production.

III. PHASE ONE ACCOMPLISHMENTS

Monthly and annual reports describing work performed in Phase 1 were prepared for and forwarded to USDOE. The following provides a brief summary of accomplishments.

Task 1. Survey of Energy Situation and Ground Transportation Status in Hawaii

Table 1 lists petroleum fuels consumed in the State of Hawaii (data for all individual major islands were also compiled but are not reproduced here).

Table 1. Breakdown of petroleum fuels used in Hawaii

Fuel	10 ⁶ gallons	%
Gasoline	375	29
Diesel fuel — off-highway	150	12
Diesel fuel — on-highway	24	2
LPG — off-highway	4	—
LPG — on-highway	<1	—
Small boats — gasoline	<1	—
Small boats — diesel fuel	<1	—
Aviation fuel	750	57
Total	1303	100

Table 2 presents a breakdown of the energy used for electricity generation (data for all individual major islands were also compiled but are not reproduced here).

Table 2. Breakdown of sources of electricity generated in Hawaii

Source	10 ⁶ kWh	%
Petroleum	8589	89.8
Biomass	843	8.8
Hydro	105	1.1
Wind	28	0.3
Coal	<1	—
PV	<1	—
Total	9565	100

Surveys relating to diesel engines were conducted for the island of Oahu which comprises about 80% of the state's population. Unfortunately, only one-half of the questionnaires were completed and returned (therefore, the accuracy of the following information is uncertain).

Manufacturer:	%
Detroit	15.0
Nissan	11.6
Ford	9.6
Cummins	9.5
Mazda	8.9
GM	8.8
Caterpillar	7.6
Saab	7.4
Isuzu	7.3
International	5.9
Others	8.4

Age of vehicle:	%
<5 years	52.4
5 to 10 years	27.1
>10 years	6.0
Unknown	14.5

Power rating:	%
<300 hp	29.0
300 to 400 hp	21.9
>400 hp	0.5
No response	48.6

Monthly diesel fuel consumption:	%
<100 gallons	55.9
100-600 gallons	12.1
600-900 gallons	0
900-1500 gallons	31.9
1500-3000 gallons	0
>3000 gallons	0.1

In addition to the above, there are 800 tour buses and 500 city buses with power trains ranging from 275 to 375 horsepower.

Task 2. Survey of Natural Energy Resources and Bio-methanol Potential in Hawaii

Due to diverse geographical features, the Hawaiian islands have a wide array of renewable energy resources, including biomass, ocean wave and thermal, wind, solar, and geothermal energy. With respect to the production of liquid fuels for ground transportation, biomass seems to be the most promising candidate due to the quantity of resource available or potentially producible and the advanced state of conversion technologies. Although agriculture wastes are being generated by the sugar industry in substantial quantities on several Hawaiian islands, the most likely biomass feedstock for the production of biofuels probably would be energy grasses or fast growing tree crops. The annual yield of energy grasses (dry matter) probably would be $\geq 50\%$ greater than for fast growing trees; however, grasses requires more water and, because of their shorter harvest cycles, are more vulnerable to short-term fluctuations in production. Under ideal conditions, 4% of the land area in the state could provide enough biomass to produce the >500 million gallons of methanol fuel required to replace gasoline for ground transportation. However, considering the many factors involved (acreage requirement, irrigation, soil conditions, climatic condition, transportation, distance to the likely fuel plant, and labor costs), the amount of fuel that could feasibly be produced from biomass is difficult to predict.

Several private companies have grown energy crops during the past decade; however, commercial-scale ventures have yet to be developed. Research activities are currently underway by the University of Hawaii, the Hawaiian Sugar Planters' Association, the Mason Research Foundation, and BioEnergy Development Corporation. Cooperation between crop growers and researchers could help to develop a strong base for biomass-to-methanol production.

Task 3. Installation of Methanol Refueling Facility

A fueling station, located at the University of Hawaii's J.K.K. Look Laboratory, was installed by HNEI to support the methanol demonstration fleet and has been operating since its installation in July, 1989. In California (the state with the largest methanol demonstration

program), only M85 (85% methanol and 15% unleaded gasoline) and lower methanol-concentration blends are used due to safety and other concerns. Gasoline is added to methanol to increase flame visibility (gasoline contains aromatics which increase flame luminosity) and to reduce cold-starting problems. To this end, 15% unleaded gasoline is added to the methanol delivered to the Look Laboratory facility to form M85.

Due to the corrosive properties of methanol, storage tanks for methanol differ from tanks normally used for petroleum products. The Environmental Protection Agency has regulated the use of unprotected steel tanks for underground storage; therefore, only two different types of fuel tanks are available on the market: fiberglass-reinforced plastic and corrosion-protected steel. HNEI purchased an 8,000 gallon capacity, UL approved, double-wall fiberglass coated tank from Modern Welding. The tank is made of steel and coated with a 100 mil layer of fiberglass, which protects the tank from galvanic corrosion. The tank is subjected to a 35,000 volt test to ensure that no pinholes or hairline cracks exist in the coating. The tank meets US 58 tests and storage of hazardous materials codes (NFPA 30 and 31).

An Emco Wheaton liquid leak sensor detection system was installed with the storage tank. One of the sensor probes is located in the interstitial zone and the other is located in the sump area, setting-off an alarm if a leak is detected. The fuel pump dispenser is manufactured by Tokheim (model 785-PR-ME). This dispenser is accompanied by a pulsar kit to facilitate communication between the fuel pump and the fuel management system. An in-line flame arrester (Protecto Seal Model F 4952-F) was also installed.

A fuel management system, designed to automatically track the amount of fuel dispensed to each account (an account can be an individual, a vehicle, a department, a fleet, or any other unit), was installed. Only personnel with special keys can access the pump-starting system and dispense the fuel. This fuel management system allows the fueling station to provide round-the-clock refueling without the need for station attendants.

Methanol is highly hygroscopic and miscible with water; however, the gasoline portion of M85 separates from water-saturated methanol if the moisture content exceeds 5%. A Pressure Vacuum Vent (Emco Wheaton Model A85) was installed for dehumidification. Unfortunately, the desiccant for the dryer was not installed (additional details are provided under task).

Quantities of ~5,000 gallons of methanol fuel have been imported from California through a collaborative agreement with the California Energy Commission at prices of \$0.45-0.50 per gallon (plus \$0.75 per gallon shipping and handling).

Task 4. Demonstration of Methanol-Fueled Vehicles and Hybrid Generators

Seven first-generation methanol vehicles were used for demonstration and training in Honolulu. Routine maintenance and safety checks (identical to gasoline cars) are performed by the University of Hawaii's Transportation Service. Usage of the methanol vehicles has been only about one third the average (7000 miles per year) in Honolulu.

Vehicle drivability was assessed based on drivers' comments recorded on log sheets, and fuel economy was determined from odometer readings and data compiled by the fuel station management system. Exhaust emissions were evaluated under steady-state conditions using a probe-pump system. Information regarding engine durability was collected through oil analysis, cylinder compression tests, and maintenance records.

During the period 1988 to 1989, all seven vehicles performed normally. However, in early 1990, many unexpected repairs were required as summarized below.

Chevy S-10 — Replaced fuel injector; repaired fuel gauge.

Crown Victoria — Checked fuel injection system due to engine hesitation; replaced fuel pump.

Escorts — Replaced three ignition modules; replaced two carburetors (autochoke problem); replaced one power steering system; replaced one electric fuel pump.

During the summer of 1990, almost every vehicle (except the Crown Victoria which was driven the least) experienced start-up and stalling problems. Fuel samples collected from the fueling station and the vehicle tanks were analyzed and were found to be normal. When analyzing the sample taken from fueling station pump and vehicle fuel line, dust was found in the on-board filters. It was concluded that clogging of the filter was attributable to the method of fueling employed before the refueling facility was installed. Problems ceased after the fuel filters were replaced on all of the vehicles.

In response to the aforementioned engine problem, the fueling station and one Escort fuel system (from tank to carburetor) were thoroughly checked. Based on this inspection, it was discovered that desiccant had not been added to the fueling station venting system. Fortunately, the methanol was found to be of sound quality. When the Escort engine fuel line assembly (disassembly tank, filter, fuel line, hose, and carburetor) was checked, no evidence of methanol-induced corrosion was found.

Three small compression-ignition engines were tested as bench-scale models for large diesel engines and as potential supplementary power units for electric vehicles (EV), and to simulate methanol fuel cell battery systems under a separate HNEI project. The units tested were:

Lister diesel engine (5 kW);

Lombardini diesel engine (3 kW);

Dyna multifuel (gasoline, natural gas, propane) engine (4.5 kW).

Although minor modifications were required, both diesel engines operated at low power outputs when fueled with neat methanol and Avocet; noise levels were excessive. The Dyna generator (see Table 3), fueled with M85, produced the full-rated output after minor adjustments were made, and the fuel consumption rate and noise level were lower than the other engines. It is important to note that the Dyna engine was designed for low BTU fuels and the methanol fuel improved engine volumetric efficiency. Therefore, the Dyna 4.5 kW engine was selected to extend the working range of the EV power system. Normal EVs with eighteen lead-acid batteries have a travel range of 60 to 90 miles. If equipped with a small power generator, the range could be extended and the EV could continue operating in traffic. Also, this power system played the role of simulating a fuel cell for a separate hydrogen application project which planned to use methanol carrying hydrogen.

Table 3. Comparison of data in Dyna engine test

M85 Methanol			Gasoline		
Speed rpm	Power kW	Fuel g/kWh	Speed rpm	Power kW	Fuel g/kWh
3497	4.02	717	3360	3.66	483
3565	3.84	897	3453	3.70	483
3620	3.56	914	3580	3.43	520
3705	2.59	1083	3679	2.54	795
3757	1.39	1561	3735	1.37	1272

Task 5. Evaluation of Strategies for Methanol Fueled Diesel Engines

Major technologies capable of converting diesel engines to use methanol fuel were reviewed.

Compression ignition:

Pure methanol with cetane enhancer — requires least modification; cost of additive is high.

Pure methanol with glow-plug assistance — lowest operating cost; limited selection of models; glow plug lifetime is short.

Dual-fuel injection — limited selection of models; two fuel injection systems are needed; high modification costs; combustion process needs to be reorganized properly.

Spark ignition:

Carburation — combustion chamber needs to be redesigned; compression ratio must be modified.

Fuel injection — both electronic ignition system and fuel injection system are needed; combustion chamber and compression ratio need to be changed; limited selection of models.

Methanol dissociation — complicated system; engine subject to cold-starting problems.

Recently, methanol enhanced with additives and methanol used in engines with glow plugs have been the most popular approaches.

Since mixing methanol with small amounts of additive requires the least modification to the engine, most existing diesel engines considered for methanol fueling probably would follow this approach. Therefore, methanol additives for compression-ignition engines should be evaluated. The most popular commercial methanol additive, Avocet, was tested to determine the minimum dosage and operating cost. The engine tests under this task were performed mostly on a Lister Petter twin-cylinder diesel engine. Fig. 1 presents the results of the test.

Fig. 1. Load versus energy consumption for various methanol/additive combinations

Although the additive manufacturer claimed that the addition of 2% Avocet would yield satisfactory engine performance, tests conducted in this study suggested that higher dosages (~5%) were necessary to meet designed performance. It should be noted that no exhaust soot was observed when Avocet was added. The price of Avocet at the time of the tests was relatively high (~\$8.00 per gallon), which translates to an additional cost of ~\$0.80 per equivalent gallon of diesel fuel. The high cost for this fuel additive prompted the investigation of two other options: alternative additives and diesel/methanol emulsification.

One local resource, coconut oil, which contains a substantial amount of long-chain molecules, was tested as a methanol additive. Since the engine fuel injection system was not modified, the fuel spray was of poor quality when coconut oil was added. This resulted in rough operation and the emission of blue smoke. A diesel/methanol emulsion was prepared to replace part of the diesel fuel; however, since good emulsification could not be maintained at partial loads, the engine did not perform well and excessive knocking occurred.

Task 6. Dissemination of Information on Methanol Fuel and Methanol-Fueled Vehicles

To increase public awareness of ongoing work, all vehicles in the methanol fleet have markings to indicate that they run on an alternative fuel. In the first phase, HNEI held regular meetings every two months with DBED, the city bus company, petroleum companies, and others, to exchange information and to discuss solutions to ongoing problems. In addition, HNEI and its methanol fleet took part in a series of energy-related activities such as local exhibitions and parades, methanol work shops, and conferences. Along with these activities, several papers were published to disseminate information on methanol fueling. HNEI sponsored and participated in numerous workshops and conferences on alternative transportation during the first phase of this program; most notably, in 1991, HNEI sponsored a Renewable Transportation Alternatives Workshop in Honolulu [5], to identify issues and concerns relating to methanol fueling.

Task 7. Plan for Transition to Use Methanol Fuel in the State of Hawaii

Hawaii residents pay the highest prices in the nation for fuel and spend more than \$1 billion annually for imported energy. Hence, it would benefit the state to find alternative fuels that utilize locally available resources. As discussed earlier, Hawaii's unique conditions favor the growing of biomass to produce methanol. This enhances the concept of replacing gasoline and diesel fuel with methanol and the possibility for Hawaii to become the first test-case for a dedicated methanol-fueled community.

Most of the Hawaiian islands have sufficient amounts of land to grow biomass (fast-growing trees, grasses, or other energy crops) dedicated to the production of liquid fuels. The main concerns surrounding conversion to methanol fueling are public acceptance of the fuel, commercialization of the technology of biomass-to-methanol conversion, and price competitiveness. The public has not accepted methanol fuel as a replacement because of its high price in Hawaii and the absence of commercially-manufactured vehicles. Additionally, the vehicles modified to run on methanol have not been as dependable as gasoline cars and the selection of models has been limited. Presently, methanol cannot compete with gasoline, which is priced relatively low at this time. It is inevitable that prices for fossil fuels, including natural gas, will increase at some point in the future. When this occurs, renewable bio-methanol could become economically feasible. At present, no bio-methanol fuel plants exist, and a number of technical issues must be addressed at the pilot scale before a commercial scale plant can be established.

With proper incentives, the public might be willing to switch to methanol for transportation fueling. Regulations to restrict pollution from vehicles could help to accelerate the transition to methanol. Also, the development of a local methanol production plant could boost the public's

interest and confidence in alternative fuels. Details on the transition to methanol are presented in references [6-8].

Once manufacturers are able to provide methanol-fueled diesel engines, diesel trucks and buses should be considered for conversion to methanol since they are major consumers of fuels on many of the Hawaiian islands. This should be done only after the reliability of methanol engines has been fully demonstrated. Also, due to Oahu's highly concentrated population and short travel distances, vehicles powered by electricity are highly desirable. To complement this promising concept, renewable resources might also be used to generate additional amounts of electricity in the state.

IV. CONCLUSIONS

The objectives proposed for the first phase of this demonstration program have been achieved. The major accomplishments by HNEI (with partial support from the State of Hawaii), include:

1. Confirmation of the availability of lands to produce sufficient biomass feedstocks for conversion into methanol for transportation fueling.
2. Installation of the first commercial-type methanol fueling station in Hawaii; gaining of useful experience in methanol fuel handling; and solving of certain obstacles to methanol fueling.
3. Evaluation of current technologies for utilizing methanol in spark-ignition and compression-ignition engines; investigation of selected fuel additives.
4. Initiation of a preliminary plan for transitioning to methanol fueling in Hawaii.

Achievements described in this report will be useful in helping Hawaii overcome various problems relating to alternative transportation fueling and become a renewable energy model for the rest of the U.S. and the world.

DOCUMENTS AND PUBLICATIONS RELATING TO THIS PROGRAM*

1. "Alternative Transportation Conservation Program," Proposal Application Form, HNEI, 1987.
2. "Alcohol Transportation Fuels Demonstration Program First Year Report," HNEI, 1989.
3. "Alcohol Transportation Fuels Demonstration Program Monthly Report," HNEI, August, 1988–October, 1990.
4. "Outline of Program Proposal for USDOE Methanol Program," HNEI, 1988.
5. "HNEI Renewable Transportation Alternatives Workshop Proceedings," HNEI, 1991.
6. "University of Hawaii/Hawaii Natural Energy Institute Methanol Fuel Program Final Report," HNEI, 1989.
7. Browne, S.H., D.R. Neill, C. DeAlmeida, S. Xu, and P.K. Takahashi, "Biomass Methanol — A Renewable Fuel for Hawaii/U.S.," Solar Today, 1989.
8. Neill, D.R., P. Takahashi, V. Phillips, C. DeAlmeida, and S. Xu, "Hawaii's Program for Transition to Methanol Fuel," VIII International Symposium on Alcohol Fuels, Tokyo, Japan, 1988.

* Copies of these documents are available on request.

**DATE
FILMED**
2 / 8 / 93