(200)

K240

ms. 76-700-F

✓ UNITED STATES (DEPARTMENT OF THE INTERIOR)

GEOLOGICAL SURVEY.

[Reports - Open file series]

Audio-magnetotelluric station location map
Breitenbush Known Geothermal Resource Area,
Oregon

TM

am
Jurnal

By

Michael

Robert M. Senterfit and Carl L. Long

Open-File Report 76-700F
1976

This report is preliminary and has not been
edited or reviewed for conformity with U.S.
Geological Survey standards and nomenclature.

MASTER

272249

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

per

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

+ 44°50'

BREITENBUSH KGRA
OREGON

AMT STATION LOCATION MAP

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.	FREQUENCY												
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
1 _{NS}	pa	7.2	9.7	10.8	17.2	25.0	59.8	-	-	-	-	-	-
	N	9	8	8	10	10	8						
	Er	0.9	1.8	0.6	0.5	1.7	8.6						
1 _{EW}	pa	6.9	4.0	2.6	4.8	8.0	-	-	-	-	-	-	-
	N	8	7	9	8	6							
	Er	1.1	0.4	0.4	0.4	0.9							
2 _{NS}	pa	24.9	34.1	28.6	46.6	33.8	-	-	-	-	-	-	-
	N	8	8	10	10	11							
	Er	4.7	3.9	0.9	5.2	1.2							
2 _{EW}	pa	7.5	8.8	3.2	5.4	7.6	16.9	-	-	-	-	-	-
	N	9	10	10	10	9	7						
	Er	1.8	1.7	0.4	0.3	0.8	1.7						
3 _{NS}	pa	45.2	39.5	44.3	50.9	49.4	24.8	-	-	-	-	-	-
	N	11	6	10	9	9	8						
	Er	5.3	4.5	3.8	4.4	7.3	2.6						
3 _{EW}	pa	15.0	15.7	10.3	9.8	10.8	-	-	-	-	-	-	-
	N	10	10	11	8	10							
	Er	1.8	1.5	0.8	1.7	0.6							
4 _{NS}	pa	19.5	12.5	13.6	13.5	17.3	12.3	-	-	-	-	-	-
	N	9	7	7	9	7	2						
	Er	1.8	1.6	0.9	1.9	0.7	1.9						
4 _{EW}	pa	42.2	29.9	9.9	10.7	15.0	-	-	-	-	-	-	-
	N	11	10	7	8	3							
	Er	5.0	3.6	1.0	0.6	1.2							

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

		FREQUENCY											
Sta. No.		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
5 _{NS}	pa	30.8	25.8	30.5	52.5	66.4	62.2	-	-	-	-	-	-
	N	10	8	10	10	8	3						
	Er	4.2	3.4	3.8	4.9	3.1	14.0						
5 _{EW}	pa	46.3	26.4	14.2	29.7	32.4	-	-	-	-	-	-	-
	N	10	8	9	10	11							
	Er	7.1	3.5	1.2	1.9	2.2							
6 _{NS}	pa	19.8	28.7	15.4	17.5	34.3	-	-	-	-	-	-	-
	N	10	10	8	7	5							
	Er	2.1	1.8	2.1	1.9	1.5							
6 _{EW}	pa	43.3	32.5	16.9	22.8	52.6	-	-	-	-	-	-	-
	N	10	7	8	9	5							
	Er	7.4	3.4	2.5	2.6	5.9							
7 _{NS}	pa	35.7	17.3	29.7	33.9	29.9	19.8	-	-	-	-	-	-
	N	10	10	10	11	10	10						
	Er	3.4	2.9	3.1	3.4	2.4	0.7						
7 _{EW}	pa	11.9	12.9	8.1	11.8	15.3	-	-	-	-	-	-	-
	N	10	10	12	11	8							
	Er	1.8	2.0	0.4	0.9	1.2							
8 _{NS}	pa	79.0	79.1	93.5	79.9	119.5	41.8	-	-	-	-	-	-
	N	9	7	3	8	8	4						
	Er	7.5	10.6	19.8	15.9	3.9	1.3						
8 _{EW}	pa	20.1	20.4	25.8	25.9	33.2	-	-	-	-	-	-	-
	N	8	9	6	8	8							
	Er	1.7	1.7	3.7	2.3	2.5							

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
9NS	pa	20.6	16.8	12.5	20.3	21.5	15.8	-	-	-	-	-	-
	N	9	8	10	11	11	9						
	Er	2.9	1.7	1.0	2.4	0.9	2.0						
9EW	pa	20.2	16.9	14.7	14.3	19.1	-	-	-	-	-	-	-
	N	11	10	10	10	11							
	Er	2.2	2.0	1.2	0.9	0.9							
10NS	pa	23.1	18.6	21.3	34.9	39.3	54.7	-	-	-	-	-	-
	N	5	9	10	12	6	9						
	Er	2.7	1.4	2.2	2.3	4.2	5.1						
10EW	pa	13.6	11.8	13.6	17.9	27.9	-	-	-	-	-	-	-
	N	8	10	11	11	4							
	Er	1.6	1.6	1.1	0.8	2.5							
11NS	pa	20.3	22.5	23.4	27.4	32.3	21.8	-	-	-	-	-	-
	N	9	9	10	10	10	4						
	Er	1.2	3.5	1.5	1.4	3.4	3.4						
11EW	pa	19.2	14.8	16.8	22.8	28.9	-	-	-	-	-	-	-
	N	8	7	10	8	10							
	Er	1.9	1.7	1.2	1.9	2.6							
12NS	pa	36.4	38.4	24.7	42.8	62.3	-	-	-	-	-	-	-
	N	14	10	11	10	3							
	Er	5.0	6.4	1.3	2.4	13.1							
12EW	pa	25.5	31.4	15.6	11.6	-	-	-	-	-	-	-	-
	N	10	10	10	10								
	Er	2.8	2.5	2.4	1.0								

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
13NS	pa	22.3	20.8	28.0	37.2	40.5	32.3	-	-	-	-	-	-
	N	11	11	11	9	10	9						
	Er	2.7	2.8	2.3	2.7	2.2	1.4						
13EW	pa	8.7	7.8	5.1	7.8	9.7	-	-	-	-	-	-	-
	N	9	6	10	11	11							
	Er	1.4	1.1	0.3	0.6	0.3							
	pa												
	N												
	Er												
	pa												
	N												
	Er												
	pa												
	N												
	Er												
	pa												
	N												
	Er												
	pa												
	N												
	Er												
	pa												
	N												
	Er												