306
5-24-78

Lh. 103

ORNL/TM-6364

MASTER

AREAS: A Computer Code for Estimating Air Pollutant Concentrations from Dispersed Sources

R. E. Moore

OAK RIDGE NATIONAL LABORATORY
OPERATED BY UNION CARBIDE CORPORATION · FOR THE DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
Price: Printed Copy \$4.50; Microfiche \$3.00

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, contractors, subcontractors, or their employees, makes any warranty, express or implied, nor assumes any legal liability or responsibility for any third party's use or the results of such use of any information, apparatus, product or process disclosed in this report, nor represents that its use by such third party would not infringe privately owned rights.

ORNL/TM- 6364

Dist. Category UC-11, UC-41

Contract No. W-7405-eng-26

Health and Safety Research Division

AREAS: A COMPUTER CODE FOR ESTIMATING AIR POLLUTANT
CONCENTRATIONS FROM DISPERSED SOURCES

R. E. Moore

Date Published - May, 1978

Oak Ridge National Laboratory
Oak Ridge, Tennessee 37830

operated by

Union Carbide Corporation

for the

Department of Energy

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

leg

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

CONTENTS

Abstract	1
Introduction	1
Model Description	3
Data Input for the AREAS Code	5
Description of the Code	6
References	11
Appendix A. Listing of the AREAS Computer Code	19
Appendix B. Output of an Example Case Run with the AREAS Computer Code	27

ABSTRACT

The AREAS area-source computer code, written in FORTRAN IV, is described and listed. This code, which runs in less than 7 seconds on the IBM 360/91 computer, estimates annual-average concentrations of an air pollutant at ground level in each of 400 grid squares in a 20 by 20 area reference grid. AREAS can be used for multiple, dispersed sources located in each of the 400 grid squares by treating them as area sources. Required input includes 20 by 20 arrays of annual-average point-source x/Q values generated by use of a point-source model or computer code for specific grid sizes relative to the size of the area reference grid. AREAS can be applied to any size area for which a uniform meteorology can be assumed. It has been applied to dispersed emissions of fossil fuel combustion products and automobile emissions in Roane County, Tennessee, and to the atmospheric dispersion of radionuclides emitted from the tailings piles of uranium mills.

INTRODUCTION

Low-elevation, dispersed sources of air pollutants include emissions resulting from the combustion of coal, fuel oil, and natural gas by homes, schools, and commercial establishments, as well as emissions from vehicles. Air pollutants from these sources may significantly augment the contributions of air pollutants deriving from the tall stacks of industrial plants. A comprehensive study of the relative importance of various sources of air pollution in an area requires a quantitative treatment of the multiple dispersed sources as well as the major elevated point sources.

The AREAS computer code estimates concentrations in air at ground level from dispersed sources by treating them as area sources. That is, pollutants such as sulfur dioxide (SO_2), particulates, hydrocarbons, or carbon monoxide (CO) emitted from multiple, low-elevation dispersed sources are treated as though they were being emitted uniformly from square areas near ground level.

The code calculates average ground-level concentrations of an air pollutant for each of 400 grid squares of a 20 by 20 grid resulting from area emissions of the pollutant from all 400 grid squares. This 20 by 20 grid is referred to in this report as the area reference grid. It represents the geographic area under study, and it is assumed to be aligned west to east (x direction) and south to north (y direction). The grid squares are numbered from 1 to 20 from west to east and from south to north.

Input data include the total emission rate from the 20 by 20 grid (micrograms/second), the fraction of this total emitted from each of the 400 grid squares, and the grid size (meters). AREAS itself does not employ meteorological data as input, but instead uses arrays of 400 x/Q^a values to describe pollutant behavior derived from a point-source model which does employ annual-average meteorological data. A uniform meteorology across the area reference grid must be assumed.

^a x/Q = ground-level concentration of the pollutant in air (x) divided by its release rate from the source (Q).

MODEL DESCRIPTION

The basis of the AREAS model is the assumption that a square area source can be simulated by four point sources located at its corners. This was shown by computer runs to be a good approximation for squares located three or more squares away from a source square. Figure 1 illustrates the principle. The shaded square in (a) represents a square area source over which the pollutant is released at a uniform rate. The area release of the shaded square of (a) is simulated by four point sources at the corners of the square in (b). The release rate of each of these four point sources is equal to 1/4th of the release rate from the square area source. In order to estimate concentrations within three squares of a source, it may be necessary to change the size of the grid. This is done by subdividing the original grid into a smaller grid where it is possible to calculate concentrations at distances three grid squares away from the source. Figure 2 shows the relative sizes of each of the smaller grid sizes which may be used in this model. The first square shown in Fig. 2 (a) is taken from the area reference grid. If a receptor point is selected within the source square of this grid, it is necessary to go to a smaller grid such as that shown in (b). This alternative is a grid one-half as large. In the example shown in Fig. 2, the one-half scale size grid is not sufficiently small to permit utilization of the three square consideration. The next scale grid shown in (c) is sufficiently small to permit calculation of concentrations three squares away from the source square and so would be appropriate in this instance. Four arrays of point-source x/Q values for grids of various specific sizes

relative to that of the area reference grid are used in AREAS to generate reliable area-source χ/Q values.

Any point-source atmospheric dispersion computer code or model selected by the user may be used to produce the point-source χ/Q values for AREAS input. These χ/Q values should represent 22.5° sector averages. AIRDOS-II (ref. 1), a computer code based on the Gaussian plume model of Pasquill² and Gifford³, is being used to provide the arrays of point-source χ/Q values for AREAS input in a study of air pollutant sources in Roane County, Tennessee.⁴ It has also been used to provide AREAS input for predicting atmospheric dispersion of radionuclides emitted from the tailings piles of uranium mills. AIRDOS-II contains an option for estimating concentrations in a square grid configuration and can produce punched-card output for direct input to AREAS.

Annual-average meteorological data are used to produce the point-source χ/Q values which AREAS uses to generate annual-average area-source χ/Q values representing an area release from a single square in a 40 by 40 grid in which each of the 1600 squares is the same size as each of the 400 squares of the area reference grid. The source square is located at (20,20). The area-source χ/Q value for each of the 400 squares of the area reference grid is calculated by translocation from the (40,40) grid for each of the 400 area sources of the area reference grid. Figure 3 shows an example in which the source is (5,5) in the area reference grid. The χ/Q value at (15,15) is equal to the χ/Q value at (30,30) on the 40 by 40 grid. These χ/Q values are multiplied by the release rates of the 400 area sources to obtain the ground-level

concentration in air in each of the 400 grid squares from each of the 400 sources. Adding the 400 values contributed from the 400 sources for each grid square then results in values representing the total concentrations of the pollutant from all area sources within the area reference grid.

The validity of the AREAS model and its limits of applicability depend directly upon three major factors. First, the pollutant concentrations calculated by AREAS from area emissions are subject to the same uncertainties and limitations that apply to the model used to generate the arrays of point-source χ/Q values used as input. Second, there is an implicit assumption in the use of AREAS to the effect that the annual-average meteorology is uniform across the geographic area under study. Accordingly, the results from using AREAS can be valid only to the extent that this assumption is valid. The third factor is concerned with the application of AREAS to dispersed sources. In order for multiple dispersed sources to be simulated by uniform area sources, they must be very numerous, fairly uniformly distributed, reasonably uniform in magnitude, and located at nearly the same elevation. If these criteria are not met, it is necessary to treat the sources as individual point sources rather than as area sources.

DATA INPUT FOR THE AREAS CODE

Table 1 lists the input parameters for AREAS with the data card formats. The first data input is IPUN, which is an option for punched-card output as defined in the table. The next data entry is SQSD, defined as the length in meters of the side of each of the 400 grid

squares of the area reference grid. The total release rate of the pollutant from the area reference grid is then entered as ARSORC in units of micrograms/second. Next, 400 values for FRACT are entered. These FRACT values represent the fraction of ARSORC emitted from each of the 400 grid squares. The sum of the FRACT values is 1. The final input data consist of point-source x/Q values for the center points of each of the 400 squares of a 20 by 20 square grid with the point source located at the center of the grid. The specific size requirements are as follows:

DCN array	Values for a grid size equal to that of the area reference grid.
BCN array	Values for a grid size double that of the area reference grid.
ACN array	Values for a grid size half that of the area reference grid.
CCN array	Values for a grid size 1/10th that of the area reference grid.

A total of 1600 point-source x/Q values are entered for these four arrays.

DESCRIPTION OF THE CODE

AREAS, which is written in the FORTRAN IV computer language, will run on the IBM 360/91 machine in less than 7 sec. The various steps in the code are identified by Roman numerals in the discussion below and in the code listing in Appendix A. A sample run is given in Appendix B.

Step I is carried out after the input data listed in Table 1 are entered. A 40 by 40 array designated as BIR is defined as a grid with the sides of each of its 1600 squares equal in length to those of the 20 by 20 area reference grid. The external dimensions of the BIR grid are equal to those specified for the 20 by 20 BCN grid. Step I is the filling of the 40 by 40 BIR array with BCN values. This is accomplished by superposing the BIR grid on the BCN grid. Each BIR element of a contiguous block of four elements is given the same value as the BCN value which the block superposes. Thus, for example, BIR (1,1), BIR (1,2), BIR (2,1), and BIR (2,2) would each receive the χ/Q value of BCN (1,1). The superposition of the BIR grid on the BCN grid is shown in Fig. 4.

The next step (II) is to replace the inner 400 BIR values with χ/Q values for the 20 by 20 DCN grid.

The BIR grid containing point-source χ/Q values for a point source located at its center is then converted to a 39 by 39 area-source χ/Q array in which the square BIR (20,20) is the area source. This step (III) is accomplished by the DO loops

```

      DO 120 NO = 1,39
      DO 110 NR = 1,39
110   BIR (NO,NR) = (BIR (NO,NR) +
      > BIR (NO + 1, NR) +
      > BIR (NO,NR + 1) +
      > BIR (NO + 1, NR + 1))/4.
120   CONTINUE
```

The assumption used here is that a square area source can be simulated by four point sources located at the corner of the square.

At this stage, a 39 by 39 area-source x/Q array has been established which could be used to define area-source x/Q values for all of the 400 area sources within the smaller 20 by 20 area reference grid. Precision for squares near the area source squares is poor, however, for the BIR grid at this point, so additional refinement is carried out.

The refinement process consists first of defining a new array of 1600 squares designated as AIR as a grid having the same external dimensions as the 20 by 20 area reference grid. Step IV is the filling of AIR with point-source DCN values in the same manner as BIR was filled with BCN values. Next, the inner 400 squares of AIR are given ACN point-source values (Step V).

Step VI is a refinement of the inner 16 grid squares of AIR using CCN values.

Step VII is the conversion of the point-source AIR array to an area-source array in the same manner as is done in Step III for the BIR array.

Step VIII consists of refining the inner 9 squares of AIR, which are the squares from 19 through 21 in both x and y directions. Refinement is especially necessary for these squares because they include the source square itself and its eight adjacent squares. The refinement process uses the CCN 20 by 20 point-source array, which is 1/10 the size of the area reference grid and which covers an area consisting of squares 19 through 22 in both x and y directions of AIR. Figure 5 shows the AIR grid with the inner 9 squares which are refined by use of the CCN array.

In Step IX the inner 100 BIR values are replaced with values derived from the AIR array. At this point, BIR is a 39 by 39 refined area-source array.

Step X calculates the average concentrations in air at ground level for each of the 400 squares of the 20 by 20 area reference grid resulting from area emissions from each square. These air concentrations are defined as values for the array RSEP. The area emission rate for each square (Q) is

$$Q = \text{FRACT}(\text{NO}, \text{NR}) \times \text{ARSORC},$$

where NO and NR are the indices for the x and y axes of the area reference grid. The Q value for each of the 400 grids is multiplied by the appropriate x/Q value for each receptor grid, which is stored in the 39 by 39 BIR array. For example (see Fig. 6), for the source square located at (1,1) on the area reference grid, the value of BIR (39,20) is the appropriate x/Q for the receptor located at (20,1). The concentrations for each receptor square resulting from emissions from each of the 400 source squares are added together to produce the final RSEP values. Four nested DO loops are used to perform all of the operations in Step X:

```

DO 460 NO = 1,20
DO 450 NR = 1,20
DO 440 NA = 1,20
DO 430 NB = 1,20
IA = 20 + NA - NO
IB = 20 + NB - NR

```



```
430 RSEP(NA,NB) = BIR(IA,IB)* FRACT(NO,NR)* ARSORC + RSEP(NA,NB)
440 CONTINUE
450 CONTINUE
460 CONTINUE
```

Step XI performs the printing and card punching of the AREAS output. All of the input data are printed first. The total area release rate (micrograms/second) and the side of the grid squares of the area reference grid (meters) are printed. Then, a table is printed listing the fraction of the total area release rate for each of the 400 grid squares of the area reference grid. Next, a table is printed of point-source x/Q input values for each of the 400 grid squares for grids of sizes equal to, double, half, and 1/10 that of the area reference grid. The final output is a table of the ground-level concentrations of the pollutant in air (micrograms/cubic centimeter) calculated by AREAS for each of the 400 grid squares of the area reference grid.

REFERENCES

1. R. E. Moore, The AIRDOS-II Computer Code for Estimating Radiation Dose to Man from Airborne Radionuclides in Areas Surrounding Nuclear Facilities, ORNL-5245 (April 1977).
2. F. Pasquill, Meteorol. Mag. 90, 1063 (1961).
3. F. A. Gifford, Jr., Nucl. Saf. 2(4), 47 (1961).
4. C. W. Miller and R. E. Moore, "Verification of a Methodology for Computing Ground-Level Air Concentrations of SO₂ and Suspended Particulates for Both Point and Dispersed Sources," in Proceedings of the Joint Conference on Applications of Air Pollution Meteorology, Nov. 29 — Dec. 2, 1977, Salt Lake City, Utah, American Meteorological Society, Boston, Mass.

Table 1. Input parameters for AREAS code

Parameter	Definition	Number of Values	Number of Cards	Data Type	Format
IPUN	Option for punched card output: IPUN = 0 — no cards punched; IPUN = 1 — ground level concentrations for the area reference grid are punched; IPUN = 2 — χ/Q values for a 40 by 40 grid with a single area source at grid (20,20) are punched; IPUN = 3 — both decks are punched.	1	1	integer	I10
SQSD	Length of side of each square of the 20 by 20 area reference grid (m)	1	1	fixed point	F10.1
ARSORC	Total area release rate of pollutant ($\mu\text{g}/\text{sec}$)	1	1	floating point	E10.3
FRACT	Fraction of ARSORC for each of the 400 squares of the area reference grid	400	50	floating point	8E10.3
DCN	Point source χ/Q values for a 20 by 20 grid equal to the size of the area reference grid (sec/cm^3)	400	50	floating point	8E10.3
BCN	As above except double size	400	50	floating point	8E10.3
ACN	As above except half size	400	50	floating point	8E10.3
CCN	As above except 1/10th size	400	50	floating point	8E10.3

ORNL-DWG 78-2875

Fig. 1 Illustrations of alternate ways to simulate area sources. Both procedures yield approximately equivalent concentrations of an air pollutant at distances three or more units away from the source square.

ORNL-DWG 78-2876

Fig. 2 Relative sizes of grid squares available to generate reliable area source χ/Q values.

ORNL-DWG 78-1182

Fig. 3 Example case showing translocation of x/Q values for the 40 by 40 grid with a source square at (20,20) to the area reference grid with a source square at (5,5).

ORNL-DWG 78-1183

Fig. 4 Superposition of BIR grid on BCN grid.

ORNL-DWG 78-1184

Fig. 5 The 40 by 40 AIR grid with the same external dimensions as the area reference grid.

ORNL-DWG 78-1185

Fig. 6 The 20 by 20 area reference grid superposed on the BIR grid showing translocation of x/Q values for single area source squares.

APPENDIX A. LISTING OF THE AREAS COMPUTER CODE

C		0
C	THE AREAS COMPUTER CODE	5
C		10
C	R. E. MOORE, HEALTH AND SAFETY RESEARCH DIV. ORNL, 12-1-77	15
C		20
C		25
C	DIMENSION AIR(40,40),ACN(20,20),BCN(20,20),CCN(20,20),BIR(40,40),	30
C	> DCN(20,20),RSEP(20,20),FRACT(20,20),SHRP(15,15),AKACN(20,20)	35
C		40
C	PUNCH OPTION	45
C		50
C	IF IPUN=0,NO CARDS ARE PUNCHED	55
C	IF IPUN=1,GROUND-LEVEL CONCENTRATIONS ARE PUNCHED	60
C	IF IPUN=2,CHI/Q VALUES IN SEC/CUBIC CM FOR A (40,40) GRID WITH	65
C	A SINGLE AREA SOURCE AT (20,20) ARE PUNCHED	70
C	IF IPUN=3,BOTH THE ABOVE DECKS ARE PUNCHED	75
C		80
C	READ 9000,IPUN	85
C		90
C	SQSD=SIDE OF GRID SQUARE(METERS)	95
C		100
C	READ(50,9001)SQSD	105
C		110
C	ARSORC=TOTAL AREA-SOURCE RELEASE RATE(MICROGRAMS/SEC)	115
C		120
C	READ(50,9002)ARSORC	125
C		130
C	FRACT=FRACTION OF TOTAL RELEASE FOR EACH GRID SQUARE	135
C		140
C	READ(50,9002)((FRACT(NO,NR),NR=1,20),NO=1,20)	145
C		150
C	DCN=POINT SOURCE CHI/Q VALUES IN SEC/CUBIC CM FOR GRID	155
C	BCN=POINT SOURCE CHI/Q VALUES IN SEC/CUBIC CM FOR DOUBLE GRID	160
C	ACN=POINT SOURCE CHI/Q VALUES IN SEC/CUBIC CM FOR HALF GRID	165
C	CCN=POINT SOURCE CHI/Q VALUES IN SEC/CUBIC CM FOR 1/10TH GRID	170
C		175
C	READ(50,9002)((DCN(NO,NR),NR=1,20),NO=1,20)	180
C	READ(50,9002)((BCN(NO,NR),NR=1,20),NO=1,20)	185
C	READ(50,9002)((ACN(NO,NR),NR=1,20),NO=1,20)	190
C	READ(50,9002)((CCN(NO,NR),NR=1,20),NO=1,20)	195
C	DO 20 NO=1,20	200
C	DO 10 NR=1,20	205
10	RSEP(NO,NR)=0	210
20	CONTINUE	215
C	DO 40 NO=1,15	220
C	DO 30 NR=1,15	225
30	SHRP(NC,NR)=0	230
40	CONTINUE	235
C		240
C	STEP I	245
C		250
C	BIR GRID IS FILLED WITH BCN VALUES	255
C		260
C	BIR(1,1)=BCN(1,1)	265
C	BIR(1,2)=BCN(1,1)	270
C	BIR(2,1)=BCN(1,1)	275

BIR (2,2)=BCN (1,1)	280
NO=1	285
DO 50 NR=2,20	290
BIR (1,NR*2)=BCN (NO,NR)	295
BIR (1,NR*2-1)=BCN (NO,NR)	300
BIR (2,NR*2)=BCN (NO,NR)	305
50 BIR (2,NR*2-1)=BCN (NO,NR)	310
NR=1	315
DO 60 NO=2,20	320
BIR (NO*2,1)=BCN (NO,NR)	325
BIR (NO*2-1,1)=BCN (NO,NR)	330
BIR (NO*2,2)=BCN (NO,NR)	335
60 BIR (NO*2-1,2)=BCN (NO,NR)	340
DO 80 NO=2,20	345
DO 70 NR=2,20	350
BIR (NO*2,NR*2)=BCN (NO,NR)	355
BIR (NO*2-1,NR*2)=BCN (NO,NR)	360
BIR (NO*2,NR*2-1)=BCN (NO,NR)	365
70 BIR (NO*2-1,NR*2-1)=BCN (NO,NR)	370
80 CONTINUE	375
C STEP II	380
C	385
C INNER BIR GRID IS FILLED WITH DCN VALUES	390
C	395
C	400
DO 100 NO=1,20	405
DO 90 NR=1,20	410
90 BIR (NO+10,NR+10)=DCN (NO,NR)	415
100 CONTINUE	420
C STEP III	425
C	430
C BIR GRID IS CONVERTED TO AREA-SOURCE VALUES	435
C	440
C	445
DO 120 NO=1,39	450
DO 110 NR=1,39	455
110 BIR (NO,NR) = (BIR (NO,NR) + BIR (NO+1,NR) + BIR (NO,NR+1) + BIR (NO+1,	460
> NR+1)) / 4.	465
120 CONTINUE	470
C STEP IV	475
C	480
C AIR GRID IS FILLED WITH DCN VALUES	485
C	490
C	495
AIR (1,1)=DCN (1,1)	500
AIR (1,2)=DCN (1,1)	505
AIR (2,1)=DCN (1,1)	510
AIR (2,2)=DCN (1,1)	515
NO=1	520
DO 130 NR=2,20	525
AIR (1,NR*2)=DCN (NO,NR)	530
AIR (1,NR*2-1)=DCN (NO,NR)	535
AIR (2,NR*2)=DCN (NO,NR)	540
130 AIR (2,NR*2-1)=DCN (NO,NR)	545
NR=1	550
DO 140 NO=2,20	555
AIR (NO*2,1)=DCN (NO,NR)	560
AIR (NO*2-1,1)=DCN (NO,NR)	565

```

      AIR(NO*2,2)=DCN(NO, NR)
140  AIR(NO*2-1,2)=DCN(NO, NR)
      DO 160 NO=2, 20
      DO 150 NR=2, 20
          AIR(NO*2, NR*2)=DCN(NO, NR)
          AIR(NO*2-1, NR*2)=DCN(NO, NR)
          AIR(NO*2, NR*2-1)=DCN(NO, NR)
          AIR(NO*2-1, NR*2-1)=DCN(NO, NR)
150  CONTINUE
160  CONTINUE
C
C      STEP V
C
C      INNER AIR GRID IS FILLED WITH ACN VALUES
C
      DO 180 NO=1, 20
      DO 170 NR=1, 20
          AIR(NO+10, NR+10)=ACN(NO, NR)
170  CONTINUE
180  CONTINUE
C
C      STEP VI
C
C      INNER 16 AIR SQUARES ARE REFINED USING CCN
C
      DO 200 NA=19, 22
      DO 190 NB=19, 22
          AIR(NA, NB)=0
190  CONTINUE
200  CONTINUE
      DO 220 NO=1, 20
      DO 210 NR=1, 20
          NA=19+(NO-.1)/5
          NB=19+(NR-.1)/5
          AIR(NA, NB)=CCN(NO, NR)+AIR(NA, NB)
210  CONTINUE
220  CONTINUE
      DO 240 NA=19, 22
      DO 230 NB=19, 22
          AIR(NA, NB)=AIR(NA, NB)/25.
230  CONTINUE
240  CONTINUE
C
C      STEP VII
C
C      AIR GRID IS CONVERTED TO AREA-SOURCE VALUES
C
      DO 260 NO=1, 39
      DO 250 NR=1, 39
          AIR(NO, NR)=(AIR(NO, NR)+AIR(NO+1, NR)+AIR(NO, NR+1)+AIR(NO+1,
          NR+1))/4.
250  CONTINUE
260  CONTINUE
C
C      STEP VIII
C
C      INNER 9 AIR VALUES ARE REFINED USING CCN
C
      DO 280 NO=1, 19
      DO 270 NR=1, 19
          AKACN(NO, NR)=(CCN(NO, NR)+CCN(NO+1, NR)+CCN(NO, NR+1)+CCN(NO+
          1, NR+1))/4.
270  CONTINUE
280  CONTINUE
      DO 320 NO=6, 10

```

570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855

DO 310 NR=6,10	860
DO 300 NA=1,15	865
DO 290 NB=1,15	870
290 SMRP (NA,NB) = AKACN (10+NA-NO,10+NB-NR) /25. + SMRP (NA,NB)	875
300 CONTINUE	880
310 CONTINUE	885
320 CONTINUE	890
DO 340 NO=19,21	895
DO 330 NR=19,21	900
330 AIR (NO,NR) =0	905
340 CONTINUE	910
DO 360 NA=1,15	915
DO 350 NB=1,15	920
350 AIR (19+ ((NA-.1)/5), 19+ ((NB-.1)/5)) = SMRP (NA,NB) + AIR (19+ ((NA-	925
> .1)/5), 19+ ((NB-.1)/5))	930
360 CONTINUE	935
DO 380 NO=19,21	940
DO 370 NR=19,21	945
370 AIR (NC,NR) = AIR (NO,NR) /25.	950
380 CONTINUE	955
C	960
DO 400 NO=1,20	965
DO 390 NR=1,20	970
390 AIR (NC,NR) = AIR (NO+10,NR+10)	975
400 CONTINUE	980
C	985
C	990
C	995
C	1000
C	1005
DO 420 NA=6,14	1010
DO 410 NB=6,14	1015
NO=NA+10	1020
NR=NB+10	1025
410 BIR (NO,NR) = (4.*AIR (2*NA-10,2*NB-10) + 2.*AIR (2*NA-9,2*NB-10) +	1030
> 2.*AIR (2*NA-10,2*NB-9) + 2.*AIR (2*NA-11,2*NB-10) + 2.*AIR (2*	1035
> NA-10,2*NB-11) + AIR (2*NA-9,2*NB-9) + AIR (2*NA-11,2*NB-9) +	1040
> AIR (2*NA-9,2*NB-11) + AIR (2*NA-11,2*NB-11)) /16.	1045
420 CONTINUE	1050
C	1055
C	1060
C	1065
C	1070
C	1075
DO 460 NO=1,20	1080
DO 450 NR=1,20	1085
DO 440 NA=1,20	1090
DO 430 NB=1,20	1095
IA=20+NA-NO	1100
IB=20+NB-NR	1105
430 RSEP (NA,NB) = BIR (IA,IB) *FRACT (NO,NR) *ARSORC + RSEP (NA,NB)	1110
440 CONTINUE	1115
450 CONTINUE	1120
460 CONTINUE	1125
C	1130
C	1135
C	1140
C	1145
THE AREAS OUTPUT IS PRINTED AND PUNCHED ON CARDS	

C		1150
	WRITE (51,9003)	1155
	WRITE (51,9004)	1160
	WRITE (51,9005) ARSORD	1165
	WRITE (51,9006) SQSD	1170
	WRITE (51,9007)	1175
	WRITE (51,9008)	1180
	WRITE (51,9007)	1185
	WRITE (51,9009)	1190
	WRITE (51,9010)	1195
	WRITE (51,9004)	1200
	DO 480 NO=1,5	1205
	DO 470 NR=1,20	1210
	NK=NO+5	1215
	NL=NO+10	1220
	NH=NO+15	1225
470	WRITE (51,9011) NO, NR, FRACT (NO, NR), NK, NR, FRACT (NK, NR), NL, NR,	1230
>	FRACT (NL, NR), NH, NR, FRACT (NH, NR)	1235
480	CONTINUE	1240
	WRITE (51,9007)	1245
	WRITE (51,9012)	1250
	A=SQSD	1255
	B=SQSD*2.	1260
	C=SQSD*.5	1265
	D=SQSD*.1	1270
	WRITE (51,9013)	1275
	WRITE (51,9014)	1280
	WRITE (51,9015) A, B, C, D	1285
	WRITE (51,9016)	1290
	WRITE (51,9004)	1295
	WRITE (51,9017) (((NO, NR, DCN (NO, NR), BCN (NO, NR), ACN (NO, NR), CCN (NO, NR)	1300
>	), NR=1,20), NO=1,20)	1305
	WRITE (51,9012)	1310
	WRITE (51,9018)	1315
	WRITE (51,9004)	1320
	WRITE (51,9019)	1325
	WRITE (51,9010)	1330
	WRITE (51,9004)	1335
	DO 500 NO=1,5	1340
	DO 490 NR=1,20	1345
	NK=NO+5	1350
	NL=NO+10	1355
	NH=NO+15	1360
490	WRITE (51,9020) NO, NR, RSEP (NO, NR), NK, NR, RSEP (NK, NR), NL, NR,	1365
>	RSEP (NL, NR), NH, NR, RSEP (NH, NR)	1370
500	CONTINUE	1375
	WRITE (51,9007)	1380
	WRITE (51,9012)	1385
	IF (IPUN.EQ.0) GO TO 520	1390
	IF (IPUN.EQ.2) GO TO 510	1395
	PUNCH 9021, ((RSEP (NO, NR), NR=1,20), NO=1,20)	1400
	IF (IPUN.EQ.1) GO TO 520	1405
510	CONTINUE	1410
	PUNCH 9022, ((BIR (NO, NR), NR=1,40), NO=1,40)	1415
520	CONTINUE	1420
	STOP	1425
9000	FORMAT (I10)	1430
9001	FORMAT (F10.1)	1435

9002 FORMAT(8E10.3)	1440
9003 FORMAT('1',T56,'OUTPUT OF AREAS CODE')	1445
9004 FORMAT('0')	1450
9005 FORMAT('0',T20,'TOTAL AREA RELEASE RATE(MICROGRAMS/SEC)',T100,	1455
> E10.3)	1460
9006 FORMAT('0',T20,'SIDE OF GRID SQUARE(METERS)',T100,F10.1)	1465
9007 FORMAT(' ')	1470
9008 FORMAT('0',T38,'FRACTION OF TOTAL AREA RELEASE RATE FOR EACH GRID	1475
> SQUARE')	1480
9009 FORMAT('0',T8,'GRID',4X,'FRACTION',T41,'GRID',4X,'FRACTION', T75,	1485
> 'GRID',4X,'FRACTION',T109,'GRID',4X,'FRACTION')	1490
9010 FORMAT('0',T7,'X',T12,'Y',T40,'X',T45,'Y',T74,'X',T79,'Y',T108,	1495
> 'X',T113,'Y')	1500
9011 FORMAT(' ',T6,I2,T11,I2,T15,E10.3,T39,I2,T44,I2,T48,E10.3,T73,I2,	1505
> T78,I2,T82,E10.3,T107,I2,T112,I2,T116,E10.3)	1510
9012 FORMAT('0',T10,'NOTE--THE X AND Y VALUES FOR THE GRID ARE INDICES	1515
> NUMBERED FROM WEST TO EAST AND FROM SOUTH TO NORTH,RESPECTIVELY.')	1520
9013 FORMAT('1',T29,'POINT-SOURCE CHI/Q INPUT VALUES FOR FOUR SPECIFIED	1525
> GRID SIZES (SEC/CUBIC CM)')	1530
9014 FORMAT('0',T8,'GRID',T29,'GRID SIDE=',T57,'GRID SIDE=',T85,	1535
> 'GRID SIDE=',T113,'GRID SIDE=')	1540
9015 FORMAT(' ',T24,F10.1,' METERS',T52,F10.1,' METERS',T80,F10.1,	1545
> ' METERS',T108,F10.1,' METERS')	1550
9016 FORMAT('0',T7,'X',T12,'Y')	1555
9017 FORMAT(' ',T6,I2,T11,I2,T29,E10.3,T57,E10.3,T85,E10.3,T113,E10.3)	1560
9018 FORMAT('1',T43,'GROUND-LEVEL CONCENTRATION IN AIR (MICROGRAMS/CUBI	1565
> C CM)')	1570
9019 FORMAT('0',T8,'GRID',4X,'CONCENTRATION',T41,'GRID',4X,	1575
> 'CONCENTRATION',T75,'GRID',4X,'CONCENTRATION',T109,'GRID',4X,	1580
> 'CONCENTRATION')	1585
9020 FORMAT(' ',T6,I2,T11,I2,T17,E10.3,T39,I2,T44,I2,T50,E10.3,T73,I2,	1590
> T78,I2,T84,E10.3,T107,I2,T112,I2,T118,E10.3)	1595
9021 FORMAT(8E10.3)	1600
9022 FORMAT(10E8.2)	1605
END	1610

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

APPENDIX B. OUTPUT OF AN EXAMPLE CASE RUN WITH THE
AREAS COMPUTER CODE

The example case is for a hypothetical square area-source releasing 1200 $\mu\text{g}/\text{sec}$ of an air pollutant from near ground level. The square source is 2000 m on a side and assumed to cover the inner 100 grid squares of a 20 by 20 area reference grid. A uniform annual-average meteorology is used.

OUTPUT OF AREAS CODE

TOTAL AREA RELEASE RATE(MICROGRAMS/SEC)

0.120E 04

SIDE OF GRID SQUARE(METERS)

200.0

FRACTION OF TOTAL AREA RELEASE RATE FOR EACH GRID SQUARE

GRID FRACTION			GRID FRACTION			GRID FRACTION			GRID FRACTION		
X	Y		X	Y		X	Y		X	Y	
1	1	0.0	6	1	0.0	11	1	0.0	16	1	0.0
1	2	0.0	6	2	0.0	11	2	0.0	16	2	0.0
1	3	0.0	6	3	0.0	11	3	0.0	16	3	0.0
1	4	0.0	6	4	0.0	11	4	0.0	16	4	0.0
1	5	0.0	6	5	0.0	11	5	0.0	16	5	0.0
1	6	0.0	6	6	0.100E-01	11	6	0.100E-01	16	6	0.0
1	7	0.0	6	7	0.100E-01	11	7	0.100E-01	16	7	0.0
1	8	0.0	6	8	0.100E-01	11	8	0.100E-01	16	8	0.0
1	9	0.0	6	9	0.100E-01	11	9	0.100E-01	16	9	0.0
1	10	0.0	6	10	0.100E-01	11	10	0.100E-01	16	10	0.0
1	11	0.0	6	11	0.100E-01	11	11	0.100E-01	16	11	0.0
1	12	0.0	6	12	0.100E-01	11	12	0.100E-01	16	12	0.0
1	13	0.0	6	13	0.100E-01	11	13	0.100E-01	16	13	0.0
1	14	0.0	6	14	0.100E-01	11	14	0.100E-01	16	14	0.0
1	15	0.0	6	15	0.100E-01	11	15	0.100E-01	16	15	0.0
1	16	0.0	6	16	0.0	11	16	0.0	16	16	0.0
1	17	0.0	6	17	0.0	11	17	0.0	16	17	0.0
1	18	0.0	6	18	0.0	11	18	0.0	16	18	0.0
1	19	0.0	6	19	0.0	11	19	0.0	16	19	0.0
1	20	0.0	6	20	0.0	11	20	0.0	16	20	0.0
2	1	0.0	7	1	0.0	12	1	0.0	17	1	0.0
2	2	0.0	7	2	0.0	12	2	0.0	17	2	0.0
2	3	0.0	7	3	0.0	12	3	0.0	17	3	0.0
2	4	0.0	7	4	0.0	12	4	0.0	17	4	0.0
2	5	0.0	7	5	0.0	12	5	0.0	17	5	0.0
2	6	0.0	7	6	0.100E-01	12	6	0.100E-01	17	6	0.0
2	7	0.0	7	7	0.100E-01	12	7	0.100E-01	17	7	0.0
2	8	0.0	7	8	0.100E-01	12	8	0.100E-01	17	8	0.0
2	9	0.0	7	9	0.100E-01	12	9	0.100E-01	17	9	0.0
2	10	0.0	7	10	0.100E-01	12	10	0.100E-01	17	10	0.0
2	11	0.0	7	11	0.100E-01	12	11	0.100E-01	17	11	0.0
2	12	0.0	7	12	0.100E-01	12	12	0.100E-01	17	12	0.0
2	13	0.0	7	13	0.100E-01	12	13	0.100E-01	17	13	0.0
2	14	0.0	7	14	0.100E-01	12	14	0.100E-01	17	14	0.0
2	15	0.0	7	15	0.100E-01	12	15	0.100E-01	17	15	0.0
2	16	0.0	7	16	0.0	12	16	0.0	17	16	0.0
2	17	0.0	7	17	0.0	12	17	0.0	17	17	0.0
2	18	0.0	7	18	0.0	12	18	0.0	17	18	0.0
2	19	0.0	7	19	0.0	12	19	0.0	17	19	0.0
2	20	0.0	7	20	0.0	12	20	0.0	17	20	0.0
3	1	0.0	8	1	0.0	13	1	0.0	18	1	0.0
3	2	0.0	8	2	0.0	13	2	0.0	18	2	0.0
3	3	0.0	8	3	0.0	13	3	0.0	18	3	0.0
3	4	0.0	8	4	0.0	13	4	0.0	18	4	0.0
3	5	0.0	8	5	0.0	13	5	0.0	18	5	0.0
3	6	0.0	8	6	0.100E-01	13	6	0.100E-01	18	6	0.0

3	7	0.0	8	7	0.100E-01	13	7	0.100E-01	18	7	0.0
3	8	0.0	8	8	0.100E-01	13	8	0.100E-01	18	8	0.0
3	9	0.0	8	9	0.100E-01	13	9	0.100E-01	18	9	0.0
3	10	0.0	8	10	0.100E-01	13	10	0.100E-01	18	10	0.0
3	11	0.0	8	11	0.100E-01	13	11	0.100E-01	18	11	0.0
3	12	0.0	8	12	0.100E-01	13	12	0.100E-01	18	12	0.0
3	13	0.0	8	13	0.100E-01	13	13	0.100E-01	18	13	0.0
3	14	0.0	8	14	0.100E-01	13	14	0.100E-01	18	14	0.0
3	15	0.0	8	15	0.100E-01	13	15	0.100E-01	18	15	0.0
3	16	0.0	8	16	0.0	13	16	0.0	18	16	0.0
3	17	0.0	8	17	0.0	13	17	0.0	18	17	0.0
3	18	0.0	8	18	0.0	13	18	0.0	18	18	0.0
3	19	0.0	8	19	0.0	13	19	0.0	18	19	0.0
3	20	0.0	8	20	0.0	13	20	0.0	18	20	0.0
4	1	0.0	9	1	0.0	14	1	0.0	19	1	0.0
4	2	0.0	9	2	0.0	14	2	0.0	19	2	0.0
4	3	0.0	9	3	0.0	14	3	0.0	19	3	0.0
4	4	0.0	9	4	0.0	14	4	0.0	19	4	0.0
4	5	0.0	9	5	0.0	14	5	0.0	19	5	0.0
4	6	0.0	9	6	0.100E-01	14	6	0.100E-01	19	6	0.0
4	7	0.0	9	7	0.100E-01	14	7	0.100E-01	19	7	0.0
4	8	0.0	9	8	0.100E-01	14	8	0.100E-01	19	8	0.0
4	9	0.0	9	9	0.100E-01	14	9	0.100E-01	19	9	0.0
4	10	0.0	9	10	0.100E-01	14	10	0.100E-01	19	10	0.0
4	11	0.0	9	11	0.100E-01	14	11	0.100E-01	19	11	0.0
4	12	0.0	9	12	0.100E-01	14	12	0.100E-01	19	12	0.0
4	13	0.0	9	13	0.100E-01	14	13	0.100E-01	19	13	0.0
4	14	0.0	9	14	0.100E-01	14	14	0.100E-01	19	14	0.0
4	15	0.0	9	15	0.100E-01	14	15	0.100E-01	19	15	0.0
4	16	0.0	9	16	0.0	14	16	0.0	19	16	0.0
4	17	0.0	9	17	0.0	14	17	0.0	19	17	0.0
4	18	0.0	9	18	0.0	14	18	0.0	19	18	0.0
4	19	0.0	9	19	0.0	14	19	0.0	19	19	0.0
4	20	0.0	9	20	0.0	14	20	0.0	19	20	0.0
5	1	0.0	10	1	0.0	15	1	0.0	20	1	0.0
5	2	0.0	10	2	0.0	15	2	0.0	20	2	0.0
5	3	0.0	10	3	0.0	15	3	0.0	20	3	0.0
5	4	0.0	10	4	0.0	15	4	0.0	20	4	0.0
5	5	0.0	10	5	0.0	15	5	0.0	20	5	0.0
5	6	0.0	10	6	0.100E-01	15	6	0.100E-01	20	6	0.0
5	7	0.0	10	7	0.100E-01	15	7	0.100E-01	20	7	0.0
5	8	0.0	10	8	0.100E-01	15	8	0.100E-01	20	8	0.0
5	9	0.0	10	9	0.100E-01	15	9	0.100E-01	20	9	0.0
5	10	0.0	10	10	0.100E-01	15	10	0.100E-01	20	10	0.0
5	11	0.0	10	11	0.100E-01	15	11	0.100E-01	20	11	0.0
5	12	0.0	10	12	0.100E-01	15	12	0.100E-01	20	12	0.0
5	13	0.0	10	13	0.100E-01	15	13	0.100E-01	20	13	0.0
5	14	0.0	10	14	0.100E-01	15	14	0.100E-01	20	14	0.0
5	15	0.0	10	15	0.100E-01	15	15	0.100E-01	20	15	0.0
5	16	0.0	10	16	0.0	15	16	0.0	20	16	0.0
5	17	0.0	10	17	0.0	15	17	0.0	20	17	0.0
5	18	0.0	10	18	0.0	15	18	0.0	20	18	0.0
5	19	0.0	10	19	0.0	15	19	0.0	20	19	0.0
5	20	0.0	10	20	0.0	15	20	0.0	20	20	0.0

NOTE--THE X AND Y VALUES FOR THE GRID ARE INDICES NUMBERED FROM WEST TO EAST AND FROM SOUTH TO NORTH, RESPECTIVELY.

POINT-SOURCE CHI/Q INPUT VALUES FOR FOUR SPECIFIED GRID SIZES (SEC/CUBIC CM)

GRID		GRID SIDE= 200.0 METERS	GRID SIDE= 400.0 METERS	GRID SIDE= 100.0 METERS	GRID SIDE= 20.0 METERS
X	Y				
1	1	0.133E-12	0.304E-13	0.585E-12	0.181E-10
1	2	0.149E-12	0.340E-13	0.654E-12	0.203E-10
1	3	0.167E-12	0.380E-13	0.731E-12	0.226E-10
1	4	0.185E-12	0.423E-13	0.813E-12	0.252E-10
1	5	0.205E-12	0.468E-13	0.900E-12	0.279E-10
1	6	0.225E-12	0.513E-13	0.987E-12	0.306E-10
1	7	0.244E-12	0.556E-13	0.107E-11	0.331E-10
1	8	0.260E-12	0.593E-13	0.114E-11	0.353E-10
1	9	0.272E-12	0.620E-13	0.119E-11	0.370E-10
1	10	0.278E-12	0.635E-13	0.122E-11	0.378E-10
1	11	0.278E-12	0.635E-13	0.122E-11	0.378E-10
1	12	0.272E-12	0.620E-13	0.119E-11	0.370E-10
1	13	0.260E-12	0.593E-13	0.114E-11	0.353E-10
1	14	0.244E-12	0.556E-13	0.107E-11	0.331E-10
1	15	0.225E-12	0.513E-13	0.987E-12	0.306E-10
1	16	0.205E-12	0.468E-13	0.900E-12	0.279E-10
1	17	0.185E-12	0.423E-13	0.813E-12	0.252E-10
1	18	0.167E-12	0.380E-13	0.731E-12	0.226E-10
1	19	0.149E-12	0.340E-13	0.654E-12	0.203E-10
1	20	0.133E-12	0.304E-13	0.585E-12	0.181E-10
2	1	0.149E-12	0.340E-13	0.654E-12	0.203E-10
2	2	0.169E-12	0.385E-13	0.741E-12	0.230E-10
2	3	0.192E-12	0.437E-13	0.840E-12	0.260E-10
2	4	0.217E-12	0.494E-13	0.950E-12	0.294E-10
2	5	0.244E-12	0.556E-13	0.107E-11	0.331E-10
2	6	0.272E-12	0.620E-13	0.119E-11	0.370E-10
2	7	0.300E-12	0.683E-13	0.131E-11	0.407E-10
2	8	0.324E-12	0.739E-13	0.142E-11	0.436E-10
2	9	0.343E-12	0.781E-13	0.150E-11	0.466E-10
2	10	0.353E-12	0.804E-13	0.155E-11	0.479E-10
2	11	0.353E-12	0.804E-13	0.155E-11	0.479E-10
2	12	0.343E-12	0.781E-13	0.150E-11	0.466E-10
2	13	0.324E-12	0.739E-13	0.142E-11	0.436E-10
2	14	0.300E-12	0.683E-13	0.131E-11	0.407E-10
2	15	0.272E-12	0.620E-13	0.119E-11	0.370E-10
2	16	0.244E-12	0.556E-13	0.107E-11	0.331E-10
2	17	0.217E-12	0.494E-13	0.950E-12	0.294E-10
2	18	0.192E-12	0.437E-13	0.840E-12	0.260E-10
2	19	0.169E-12	0.385E-13	0.741E-12	0.230E-10
2	20	0.149E-12	0.340E-13	0.654E-12	0.203E-10
3	1	0.167E-12	0.380E-13	0.731E-12	0.226E-10
3	2	0.192E-12	0.437E-13	0.840E-12	0.260E-10
3	3	0.221E-12	0.503E-13	0.968E-12	0.300E-10
3	4	0.254E-12	0.580E-13	0.112E-11	0.346E-10
3	5	0.292E-12	0.666E-13	0.128E-11	0.397E-10
3	6	0.333E-12	0.759E-13	0.146E-11	0.453E-10
3	7	0.375E-12	0.854E-13	0.164E-11	0.509E-10
3	8	0.413E-12	0.942E-13	0.181E-11	0.561E-10
3	9	0.443E-12	0.101E-12	0.194E-11	0.603E-10
3	10	0.460E-12	0.105E-12	0.202E-11	0.625E-10
3	11	0.460E-12	0.105E-12	0.202E-11	0.625E-10
3	12	0.443E-12	0.101E-12	0.194E-11	0.603E-10
3	13	0.413E-12	0.942E-13	0.181E-11	0.561E-10
3	14	0.375E-12	0.854E-13	0.164E-11	0.509E-10
3	15	0.333E-12	0.759E-13	0.146E-11	0.453E-10

3	16	0.292E-12	0.666E-13	0.128E-11	0.397E-10
3	17	0.254E-12	0.580E-13	0.112E-11	0.346E-10
3	18	0.221E-12	0.503E-13	0.968E-12	0.300E-10
3	19	0.192E-12	0.437E-13	0.840E-12	0.260E-10
3	20	0.167E-12	0.380E-13	0.731E-12	0.226E-10
4	1	0.185E-12	0.423E-13	0.813E-12	0.252E-10
4	2	0.217E-12	0.494E-13	0.950E-12	0.294E-10
4	3	0.254E-12	0.580E-13	0.112E-11	0.346E-10
4	4	0.300E-12	0.683E-13	0.131E-11	0.407E-10
4	5	0.353E-12	0.804E-13	0.155E-11	0.479E-10
4	6	0.413E-12	0.942E-13	0.181E-11	0.561E-10
4	7	0.478E-12	0.109E-12	0.210E-11	0.650E-10
4	8	0.542E-12	0.123E-12	0.238E-11	0.736E-10
4	9	0.594E-12	0.135E-12	0.260E-11	0.807E-10
4	10	0.623E-12	0.142E-12	0.274E-11	0.847E-10
4	11	0.623E-12	0.142E-12	0.274E-11	0.847E-10
4	12	0.594E-12	0.135E-12	0.260E-11	0.807E-10
4	13	0.542E-12	0.123E-12	0.238E-11	0.736E-10
4	14	0.478E-12	0.109E-12	0.210E-11	0.650E-10
4	15	0.413E-12	0.942E-13	0.181E-11	0.561E-10
4	16	0.353E-12	0.804E-13	0.155E-11	0.479E-10
4	17	0.300E-12	0.683E-13	0.131E-11	0.407E-10
4	18	0.254E-12	0.580E-13	0.112E-11	0.346E-10
4	19	0.217E-12	0.494E-13	0.950E-12	0.294E-10
4	20	0.185E-12	0.423E-13	0.813E-12	0.252E-10
5	1	0.205E-12	0.468E-13	0.900E-12	0.279E-10
5	2	0.244E-12	0.556E-13	0.107E-11	0.331E-10
5	3	0.292E-12	0.666E-13	0.128E-11	0.397E-10
5	4	0.353E-12	0.804E-13	0.155E-11	0.479E-10
5	5	0.428E-12	0.975E-13	0.188E-11	0.581E-10
5	6	0.513E-12	0.117E-12	0.225E-11	0.705E-10
5	7	0.623E-12	0.142E-12	0.274E-11	0.847E-10
5	8	0.733E-12	0.167E-12	0.322E-11	0.997E-10
5	9	0.830E-12	0.189E-12	0.364E-11	0.113E-09
5	10	0.888E-12	0.202E-12	0.390E-11	0.121E-09
5	11	0.888E-12	0.202E-12	0.390E-11	0.121E-09
5	12	0.830E-12	0.189E-12	0.364E-11	0.113E-09
5	13	0.733E-12	0.167E-12	0.322E-11	0.997E-10
5	14	0.623E-12	0.142E-12	0.274E-11	0.847E-10
5	15	0.513E-12	0.117E-12	0.225E-11	0.705E-10
5	16	0.428E-12	0.975E-13	0.188E-11	0.581E-10
5	17	0.353E-12	0.804E-13	0.155E-11	0.479E-10
5	18	0.292E-12	0.666E-13	0.128E-11	0.397E-10
5	19	0.244E-12	0.556E-13	0.107E-11	0.331E-10
5	20	0.205E-12	0.468E-13	0.900E-12	0.279E-10
6	1	0.225E-12	0.513E-13	0.987E-12	0.306E-10
6	2	0.272E-12	0.620E-13	0.119E-11	0.370E-10
6	3	0.333E-12	0.759E-13	0.146E-11	0.453E-10
6	4	0.413E-12	0.942E-13	0.181E-11	0.561E-10
6	5	0.513E-12	0.117E-12	0.225E-11	0.705E-10
6	6	0.656E-12	0.150E-12	0.288E-11	0.892E-10
6	7	0.830E-12	0.189E-12	0.364E-11	0.113E-09
6	8	0.103E-11	0.235E-12	0.453E-11	0.140E-09
6	9	0.123E-11	0.280E-12	0.539E-11	0.167E-09
6	10	0.136E-11	0.309E-12	0.595E-11	0.184E-09
6	11	0.136E-11	0.309E-12	0.595E-11	0.184E-09
6	12	0.123E-11	0.280E-12	0.539E-11	0.167E-09
6	13	0.103E-11	0.235E-12	0.453E-11	0.140E-09
6	14	0.830E-12	0.189E-12	0.364E-11	0.113E-09
6	15	0.656E-12	0.150E-12	0.288E-11	0.892E-10
6	16	0.513E-12	0.117E-12	0.225E-11	0.705E-10

6	17	0.413E-12	0.942E-13	0.181E-11	0.561E-10
6	18	0.333E-12	0.759E-13	0.146E-11	0.453E-10
6	19	0.272E-12	0.620E-13	0.119E-11	0.370E-10
6	20	0.225E-12	0.513E-13	0.987E-12	0.306E-10
7	1	0.244E-12	0.556E-13	0.107E-11	0.331E-10
7	2	0.300E-12	0.683E-13	0.131E-11	0.407E-10
7	3	0.375E-12	0.854E-13	0.164E-11	0.509E-10
7	4	0.478E-12	0.109E-12	0.210E-11	0.650E-10
7	5	0.623E-12	0.142E-12	0.274E-11	0.847E-10
7	6	0.830E-12	0.189E-12	0.364E-11	0.113E-09
7	7	0.112E-11	0.256E-12	0.492E-11	0.153E-09
7	8	0.151E-11	0.345E-12	0.664E-11	0.204E-09
7	9	0.196E-11	0.447E-12	0.861E-11	0.266E-09
7	10	0.230E-11	0.524E-12	0.101E-10	0.312E-09
7	11	0.230E-11	0.524E-12	0.101E-10	0.312E-09
7	12	0.196E-11	0.447E-12	0.861E-11	0.266E-09
7	13	0.151E-11	0.345E-12	0.664E-11	0.204E-09
7	14	0.112E-11	0.256E-12	0.492E-11	0.153E-09
7	15	0.830E-12	0.189E-12	0.364E-11	0.113E-09
7	16	0.623E-12	0.142E-12	0.274E-11	0.847E-10
7	17	0.478E-12	0.109E-12	0.210E-11	0.650E-10
7	18	0.375E-12	0.854E-13	0.164E-11	0.509E-10
7	19	0.300E-12	0.683E-13	0.131E-11	0.407E-10
7	20	0.244E-12	0.556E-13	0.107E-11	0.331E-10
8	1	0.260E-12	0.593E-13	0.114E-11	0.353E-10
8	2	0.324E-12	0.739E-13	0.142E-11	0.436E-10
8	3	0.413E-12	0.942E-13	0.181E-11	0.561E-10
8	4	0.542E-12	0.123E-12	0.238E-11	0.736E-10
8	5	0.733E-12	0.167E-12	0.322E-11	0.997E-10
8	6	0.103E-11	0.235E-12	0.453E-11	0.140E-09
8	7	0.151E-11	0.345E-12	0.664E-11	0.204E-09
8	8	0.230E-11	0.524E-12	0.101E-10	0.312E-09
8	9	0.347E-11	0.791E-12	0.152E-10	0.470E-09
8	10	0.462E-11	0.105E-11	0.203E-10	0.625E-09
8	11	0.462E-11	0.105E-11	0.203E-10	0.625E-09
8	12	0.347E-11	0.791E-12	0.152E-10	0.470E-09
8	13	0.230E-11	0.524E-12	0.101E-10	0.312E-09
8	14	0.151E-11	0.345E-12	0.664E-11	0.204E-09
8	15	0.103E-11	0.235E-12	0.453E-11	0.140E-09
8	16	0.733E-12	0.167E-12	0.322E-11	0.997E-10
8	17	0.542E-12	0.123E-12	0.238E-11	0.736E-10
8	18	0.413E-12	0.942E-13	0.181E-11	0.561E-10
8	19	0.324E-12	0.739E-13	0.142E-11	0.436E-10
8	20	0.260E-12	0.593E-13	0.114E-11	0.353E-10
9	1	0.272E-12	0.620E-13	0.119E-11	0.370E-10
9	2	0.343E-12	0.781E-13	0.150E-11	0.466E-10
9	3	0.443E-12	0.101E-12	0.194E-11	0.603E-10
9	4	0.594E-12	0.135E-12	0.260E-11	0.807E-10
9	5	0.830E-12	0.189E-12	0.364E-11	0.113E-09
9	6	0.123E-11	0.280E-12	0.539E-11	0.167E-09
9	7	0.196E-11	0.447E-12	0.861E-11	0.266E-09
9	8	0.347E-11	0.791E-12	0.152E-10	0.470E-09
9	9	0.714E-11	0.163E-11	0.313E-10	0.959E-09
9	10	0.138E-10	0.314E-11	0.605E-10	0.182E-08
9	11	0.138E-10	0.314E-11	0.605E-10	0.182E-08
9	12	0.714E-11	0.163E-11	0.313E-10	0.959E-09
9	13	0.347E-11	0.791E-12	0.152E-10	0.470E-09
9	14	0.196E-11	0.447E-12	0.861E-11	0.266E-09
9	15	0.123E-11	0.280E-12	0.539E-11	0.167E-09
9	16	0.830E-12	0.189E-12	0.364E-11	0.113E-09
9	17	0.594E-12	0.135E-12	0.260E-11	0.807E-10

9	18	0.443E-12	0.101E-12	0.194E-11	0.603E-10
9	19	0.343E-12	0.781E-13	0.150E-11	0.466E-10
9	20	0.272E-12	0.620E-13	0.119E-11	0.370E-10
10	1	0.278E-12	0.635E-13	0.122E-11	0.378E-10
10	2	0.353E-12	0.804E-13	0.155E-11	0.479E-10
10	3	0.460E-12	0.105E-12	0.202E-11	0.625E-10
10	4	0.623E-12	0.142E-12	0.274E-11	0.847E-10
10	5	0.888E-12	0.202E-12	0.390E-11	0.121E-09
10	6	0.136E-11	0.309E-12	0.595E-11	0.184E-09
10	7	0.230E-11	0.524E-12	0.101E-10	0.312E-09
10	8	0.462E-11	0.105E-11	0.203E-10	0.625E-09
10	9	0.138E-10	0.314E-11	0.605E-10	0.182E-08
10	10	0.176E-09	0.407E-10	0.726E-09	0.853E-08
10	11	0.176E-09	0.407E-10	0.726E-09	0.853E-08
10	12	0.138E-10	0.314E-11	0.605E-10	0.182E-08
10	13	0.462E-11	0.105E-11	0.203E-10	0.625E-09
10	14	0.230E-11	0.524E-12	0.101E-10	0.312E-09
10	15	0.136E-11	0.309E-12	0.595E-11	0.184E-09
10	16	0.888E-12	0.202E-12	0.390E-11	0.121E-09
10	17	0.623E-12	0.142E-12	0.274E-11	0.847E-10
10	18	0.460E-12	0.105E-12	0.202E-11	0.625E-10
10	19	0.353E-12	0.804E-13	0.155E-11	0.479E-10
10	20	0.278E-12	0.635E-13	0.122E-11	0.378E-10
11	1	0.278E-12	0.635E-13	0.122E-11	0.378E-10
11	2	0.353E-12	0.804E-13	0.155E-11	0.479E-10
11	3	0.460E-12	0.105E-12	0.202E-11	0.625E-10
11	4	0.623E-12	0.142E-12	0.274E-11	0.847E-10
11	5	0.888E-12	0.202E-12	0.390E-11	0.121E-09
11	6	0.136E-11	0.309E-12	0.595E-11	0.184E-09
11	7	0.230E-11	0.524E-12	0.101E-10	0.312E-09
11	8	0.462E-11	0.105E-11	0.203E-10	0.625E-09
11	9	0.138E-10	0.314E-11	0.605E-10	0.182E-08
11	10	0.176E-09	0.407E-10	0.726E-09	0.853E-08
11	11	0.176E-09	0.407E-10	0.726E-09	0.853E-08
11	12	0.138E-10	0.314E-11	0.605E-10	0.182E-08
11	13	0.462E-11	0.105E-11	0.203E-10	0.625E-09
11	14	0.230E-11	0.524E-12	0.101E-10	0.312E-09
11	15	0.136E-11	0.309E-12	0.595E-11	0.184E-09
11	16	0.888E-12	0.202E-12	0.390E-11	0.121E-09
11	17	0.623E-12	0.142E-12	0.274E-11	0.847E-10
11	18	0.460E-12	0.105E-12	0.202E-11	0.625E-10
11	19	0.353E-12	0.804E-13	0.155E-11	0.479E-10
11	20	0.278E-12	0.635E-13	0.122E-11	0.378E-10
12	1	0.272E-12	0.620E-13	0.119E-11	0.370E-10
12	2	0.343E-12	0.781E-13	0.150E-11	0.466E-10
12	3	0.443E-12	0.101E-12	0.194E-11	0.603E-10
12	4	0.594E-12	0.135E-12	0.260E-11	0.807E-10
12	5	0.830E-12	0.189E-12	0.364E-11	0.113E-09
12	6	0.123E-11	0.280E-12	0.539E-11	0.167E-09
12	7	0.196E-11	0.447E-12	0.861E-11	0.266E-09
12	8	0.347E-11	0.791E-12	0.152E-10	0.470E-09
12	9	0.714E-11	0.163E-11	0.313E-10	0.959E-09
12	10	0.138E-10	0.314E-11	0.605E-10	0.182E-08
12	11	0.138E-10	0.314E-11	0.605E-10	0.182E-08
12	12	0.714E-11	0.163E-11	0.313E-10	0.959E-09
12	13	0.347E-11	0.791E-12	0.152E-10	0.470E-09
12	14	0.196E-11	0.447E-12	0.861E-11	0.266E-09
12	15	0.123E-11	0.280E-12	0.539E-11	0.167E-09
12	16	0.830E-12	0.189E-12	0.364E-11	0.113E-09
12	17	0.594E-12	0.135E-12	0.260E-11	0.807E-10
12	18	0.443E-12	0.101E-12	0.194E-11	0.603E-10

12	19	0.343E-12	0.781E-13	0.150E-11	0.466E-10
12	20	0.272E-12	0.620E-13	0.119E-11	0.370E-10
13	1	0.260E-12	0.593E-13	0.114E-11	0.353E-10
13	2	0.324E-12	0.739E-13	0.142E-11	0.436E-10
13	3	0.413E-12	0.942E-13	0.181E-11	0.561E-10
13	4	0.542E-12	0.123E-12	0.238E-11	0.736E-10
13	5	0.733E-12	0.167E-12	0.322E-11	0.997E-10
13	6	0.103E-11	0.235E-12	0.453E-11	0.140E-09
13	7	0.151E-11	0.345E-12	0.664E-11	0.204E-09
13	8	0.230E-11	0.524E-12	0.101E-10	0.312E-09
13	9	0.347E-11	0.791E-12	0.152E-10	0.470E-09
13	10	0.462E-11	0.105E-11	0.203E-10	0.625E-09
13	11	0.462E-11	0.105E-11	0.203E-10	0.625E-09
13	12	0.347E-11	0.791E-12	0.152E-10	0.470E-09
13	13	0.230E-11	0.524E-12	0.101E-10	0.312E-09
13	14	0.151E-11	0.345E-12	0.664E-11	0.204E-09
13	15	0.103E-11	0.235E-12	0.453E-11	0.140E-09
13	16	0.733E-12	0.167E-12	0.322E-11	0.997E-10
13	17	0.542E-12	0.123E-12	0.238E-11	0.736E-10
13	18	0.413E-12	0.942E-13	0.181E-11	0.561E-10
13	19	0.324E-12	0.739E-13	0.142E-11	0.436E-10
13	20	0.260E-12	0.593E-13	0.114E-11	0.353E-10
14	1	0.244E-12	0.556E-13	0.107E-11	0.331E-10
14	2	0.300E-12	0.683E-13	0.131E-11	0.407E-10
14	3	0.375E-12	0.854E-13	0.164E-11	0.509E-10
14	4	0.478E-12	0.109E-12	0.210E-11	0.650E-10
14	5	0.623E-12	0.142E-12	0.274E-11	0.847E-10
14	6	0.830E-12	0.189E-12	0.364E-11	0.113E-09
14	7	0.112E-11	0.256E-12	0.492E-11	0.153E-09
14	8	0.151E-11	0.345E-12	0.664E-11	0.204E-09
14	9	0.196E-11	0.447E-12	0.861E-11	0.266E-09
14	10	0.230E-11	0.524E-12	0.101E-10	0.312E-09
14	11	0.230E-11	0.524E-12	0.101E-10	0.312E-09
14	12	0.196E-11	0.447E-12	0.861E-11	0.266E-09
14	13	0.151E-11	0.345E-12	0.664E-11	0.204E-09
14	14	0.112E-11	0.256E-12	0.492E-11	0.153E-09
14	15	0.830E-12	0.189E-12	0.364E-11	0.113E-09
14	16	0.623E-12	0.142E-12	0.274E-11	0.847E-10
14	17	0.478E-12	0.109E-12	0.210E-11	0.650E-10
14	18	0.375E-12	0.854E-13	0.164E-11	0.509E-10
14	19	0.300E-12	0.683E-13	0.131E-11	0.407E-10
14	20	0.244E-12	0.556E-13	0.107E-11	0.331E-10
15	1	0.225E-12	0.513E-13	0.987E-12	0.306E-10
15	2	0.272E-12	0.620E-13	0.119E-11	0.370E-10
15	3	0.333E-12	0.759E-13	0.146E-11	0.453E-10
15	4	0.413E-12	0.942E-13	0.181E-11	0.561E-10
15	5	0.513E-12	0.117E-12	0.225E-11	0.705E-10
15	6	0.656E-12	0.150E-12	0.288E-11	0.892E-10
15	7	0.830E-12	0.189E-12	0.364E-11	0.113E-09
15	8	0.103E-11	0.235E-12	0.453E-11	0.140E-09
15	9	0.123E-11	0.280E-12	0.539E-11	0.167E-09
15	10	0.136E-11	0.309E-12	0.595E-11	0.184E-09
15	11	0.136E-11	0.309E-12	0.595E-11	0.184E-09
15	12	0.123E-11	0.280E-12	0.539E-11	0.167E-09
15	13	0.103E-11	0.235E-12	0.453E-11	0.140E-09
15	14	0.830E-12	0.189E-12	0.364E-11	0.113E-09
15	15	0.656E-12	0.150E-12	0.288E-11	0.892E-10
15	16	0.513E-12	0.117E-12	0.225E-11	0.705E-10
15	17	0.413E-12	0.942E-13	0.181E-11	0.561E-10
15	18	0.333E-12	0.759E-13	0.146E-11	0.453E-10
15	19	0.272E-12	0.620E-13	0.119E-11	0.370E-10

15	20	0.225E-12	0.513E-13	0.987E-12	0.306E-10
16	1	0.205E-12	0.468E-13	0.900E-12	0.279E-10
16	2	0.244E-12	0.556E-13	0.107E-11	0.331E-10
16	3	0.292E-12	0.666E-13	0.128E-11	0.397E-10
16	4	0.353E-12	0.804E-13	0.155E-11	0.479E-10
16	5	0.428E-12	0.975E-13	0.188E-11	0.581E-10
16	6	0.513E-12	0.117E-12	0.225E-11	0.705E-10
16	7	0.623E-12	0.142E-12	0.274E-11	0.847E-10
16	8	0.733E-12	0.167E-12	0.322E-11	0.997E-10
16	9	0.830E-12	0.189E-12	0.364E-11	0.113E-09
16	10	0.888E-12	0.202E-12	0.390E-11	0.121E-09
16	11	0.888E-12	0.202E-12	0.390E-11	0.121E-09
16	12	0.830E-12	0.189E-12	0.364E-11	0.113E-09
16	13	0.733E-12	0.167E-12	0.322E-11	0.997E-10
16	14	0.623E-12	0.142E-12	0.274E-11	0.847E-10
16	15	0.513E-12	0.117E-12	0.225E-11	0.705E-10
16	16	0.428E-12	0.975E-13	0.188E-11	0.581E-10
16	17	0.353E-12	0.804E-13	0.155E-11	0.479E-10
16	18	0.292E-12	0.666E-13	0.128E-11	0.397E-10
16	19	0.244E-12	0.556E-13	0.107E-11	0.331E-10
16	20	0.205E-12	0.468E-13	0.900E-12	0.279E-10
17	1	0.185E-12	0.423E-13	0.813E-12	0.252E-10
17	2	0.217E-12	0.494E-13	0.950E-12	0.294E-10
17	3	0.254E-12	0.580E-13	0.112E-11	0.346E-10
17	4	0.300E-12	0.683E-13	0.131E-11	0.407E-10
17	5	0.353E-12	0.804E-13	0.155E-11	0.479E-10
17	6	0.413E-12	0.942E-13	0.181E-11	0.561E-10
17	7	0.478E-12	0.109E-12	0.210E-11	0.650E-10
17	8	0.542E-12	0.123E-12	0.238E-11	0.736E-10
17	9	0.594E-12	0.135E-12	0.260E-11	0.807E-10
17	10	0.623E-12	0.142E-12	0.274E-11	0.847E-10
17	11	0.623E-12	0.142E-12	0.274E-11	0.847E-10
17	12	0.594E-12	0.135E-12	0.260E-11	0.807E-10
17	13	0.542E-12	0.123E-12	0.238E-11	0.736E-10
17	14	0.478E-12	0.109E-12	0.210E-11	0.650E-10
17	15	0.413E-12	0.942E-13	0.181E-11	0.561E-10
17	16	0.353E-12	0.804E-13	0.155E-11	0.479E-10
17	17	0.300E-12	0.683E-13	0.131E-11	0.407E-10
17	18	0.254E-12	0.580E-13	0.112E-11	0.346E-10
17	19	0.217E-12	0.494E-13	0.950E-12	0.294E-10
17	20	0.185E-12	0.423E-13	0.813E-12	0.252E-10
18	1	0.167E-12	0.380E-13	0.731E-12	0.226E-10
18	2	0.192E-12	0.437E-13	0.840E-12	0.260E-10
18	3	0.221E-12	0.503E-13	0.968E-12	0.300E-10
18	4	0.254E-12	0.580E-13	0.112E-11	0.346E-10
18	5	0.292E-12	0.666E-13	0.128E-11	0.397E-10
18	6	0.333E-12	0.759E-13	0.146E-11	0.453E-10
18	7	0.375E-12	0.854E-13	0.164E-11	0.509E-10
18	8	0.413E-12	0.942E-13	0.181E-11	0.561E-10
18	9	0.443E-12	0.101E-12	0.194E-11	0.603E-10
18	10	0.460E-12	0.105E-12	0.202E-11	0.625E-10
18	11	0.460E-12	0.105E-12	0.202E-11	0.625E-10
18	12	0.443E-12	0.101E-12	0.194E-11	0.603E-10
18	13	0.413E-12	0.942E-13	0.181E-11	0.561E-10
18	14	0.375E-12	0.854E-13	0.164E-11	0.509E-10
18	15	0.333E-12	0.759E-13	0.146E-11	0.453E-10
18	16	0.292E-12	0.666E-13	0.128E-11	0.397E-10
18	17	0.254E-12	0.580E-13	0.112E-11	0.346E-10
18	18	0.221E-12	0.503E-13	0.968E-12	0.300E-10
18	19	0.192E-12	0.437E-13	0.840E-12	0.260E-10
18	20	0.167E-12	0.380E-13	0.731E-12	0.226E-10

19	1	0.149E-12	0.340E-13	0.654E-12	0.203E-10
19	2	0.169E-12	0.385E-13	0.741E-12	0.230E-10
19	3	0.192E-12	0.437E-13	0.840E-12	0.260E-10
19	4	0.217E-12	0.494E-13	0.950E-12	0.294E-10
19	5	0.244E-12	0.556E-13	0.107E-11	0.331E-10
19	6	0.272E-12	0.620E-13	0.119E-11	0.370E-10
19	7	0.300E-12	0.683E-13	0.131E-11	0.407E-10
19	8	0.324E-12	0.739E-13	0.142E-11	0.436E-10
19	9	0.343E-12	0.781E-13	0.150E-11	0.466E-10
19	10	0.353E-12	0.804E-13	0.155E-11	0.479E-10
19	11	0.353E-12	0.804E-13	0.155E-11	0.479E-10
19	12	0.343E-12	0.781E-13	0.150E-11	0.466E-10
19	13	0.324E-12	0.739E-13	0.142E-11	0.436E-10
19	14	0.300E-12	0.683E-13	0.131E-11	0.407E-10
19	15	0.272E-12	0.620E-13	0.119E-11	0.370E-10
19	16	0.244E-12	0.556E-13	0.107E-11	0.331E-10
19	17	0.217E-12	0.494E-13	0.950E-12	0.294E-10
19	18	0.192E-12	0.437E-13	0.840E-12	0.260E-10
19	19	0.169E-12	0.385E-13	0.741E-12	0.230E-10
19	20	0.149E-12	0.340E-13	0.654E-12	0.203E-10
20	1	0.133E-12	0.304E-13	0.585E-12	0.181E-10
20	2	0.149E-12	0.340E-13	0.654E-12	0.203E-10
20	3	0.167E-12	0.380E-13	0.731E-12	0.226E-10
20	4	0.185E-12	0.423E-13	0.813E-12	0.252E-10
20	5	0.205E-12	0.468E-13	0.900E-12	0.279E-10
20	6	0.225E-12	0.513E-13	0.987E-12	0.306E-10
20	7	0.244E-12	0.556E-13	0.107E-11	0.331E-10
20	8	0.260E-12	0.593E-13	0.114E-11	0.353E-10
20	9	0.272E-12	0.620E-13	0.119E-11	0.370E-10
20	10	0.278E-12	0.635E-13	0.122E-11	0.378E-10
20	11	0.278E-12	0.635E-13	0.122E-11	0.378E-10
20	12	0.272E-12	0.620E-13	0.119E-11	0.370E-10
20	13	0.260E-12	0.593E-13	0.114E-11	0.353E-10
20	14	0.244E-12	0.556E-13	0.107E-11	0.331E-10
20	15	0.225E-12	0.513E-13	0.987E-12	0.306E-10
20	16	0.205E-12	0.468E-13	0.900E-12	0.279E-10
20	17	0.185E-12	0.423E-13	0.813E-12	0.252E-10
20	18	0.167E-12	0.380E-13	0.731E-12	0.226E-10
20	19	0.149E-12	0.340E-13	0.654E-12	0.203E-10
20	20	0.133E-12	0.304E-13	0.585E-12	0.181E-10

NOTE--THE X AND Y VALUES FOR THE GRID ARE INDICES NUMBERED FROM WEST TO EAST AND FROM SOUTH TO NORTH, RESPECTIVELY.

GROUND-LEVEL CONCENTRATION IN AIR (MICROGRAMS/CUBIC CM)

GRID CONCENTRATION			GRID CONCENTRATION			GRID CONCENTRATION			GRID CONCENTRATION		
X	Y		X	Y		X	Y		X	Y	
1	1	0.182E-09	6	1	0.333E-09	11	1	0.411E-09	16	1	0.301E-09
1	2	0.207E-09	6	2	0.429E-09	11	2	0.549E-09	16	2	0.377E-09
1	3	0.236E-09	6	3	0.582E-09	11	3	0.776E-09	16	3	0.492E-09
1	4	0.267E-09	6	4	0.874E-09	11	4	0.122E-08	16	4	0.684E-09
1	5	0.301E-09	6	5	0.215E-08	11	5	0.288E-08	16	5	0.112E-08
1	6	0.333E-09	6	6	0.105E-07	11	6	0.122E-07	16	6	0.215E-08
1	7	0.363E-09	6	7	0.118E-07	11	7	0.139E-07	16	7	0.258E-08
1	8	0.386E-09	6	8	0.120E-07	11	8	0.143E-07	16	8	0.275E-08
1	9	0.403E-09	6	9	0.122E-07	11	9	0.145E-07	16	9	0.284E-08
1	10	0.411E-09	6	10	0.122E-07	11	10	0.145E-07	16	10	0.288E-08
1	11	0.411E-09	6	11	0.122E-07	11	11	0.145E-07	16	11	0.288E-08
1	12	0.403E-09	6	12	0.122E-07	11	12	0.145E-07	16	12	0.284E-08
1	13	0.386E-09	6	13	0.120E-07	11	13	0.143E-07	16	13	0.275E-08
1	14	0.363E-09	6	14	0.118E-07	11	14	0.139E-07	16	14	0.258E-08
1	15	0.333E-09	6	15	0.105E-07	11	15	0.122E-07	16	15	0.215E-08
1	16	0.301E-09	6	16	0.215E-08	11	16	0.288E-08	16	16	0.112E-08
1	17	0.267E-09	6	17	0.874E-09	11	17	0.122E-08	16	17	0.684E-09
1	18	0.236E-09	6	18	0.582E-09	11	18	0.776E-09	16	18	0.492E-09
1	19	0.207E-09	6	19	0.429E-09	11	19	0.549E-09	16	19	0.377E-09
1	20	0.182E-09	6	20	0.333E-09	11	20	0.411E-09	16	20	0.301E-09
2	1	0.207E-09	7	1	0.363E-09	12	1	0.403E-09	17	1	0.267E-09
2	2	0.240E-09	7	2	0.475E-09	12	2	0.536E-09	17	2	0.326E-09
2	3	0.280E-09	7	3	0.660E-09	12	3	0.758E-09	17	3	0.408E-09
2	4	0.326E-09	7	4	0.103E-08	12	4	0.119E-08	17	4	0.523E-09
2	5	0.377E-09	7	5	0.258E-08	12	5	0.284E-08	17	5	0.684E-09
2	6	0.429E-09	7	6	0.118E-07	12	6	0.122E-07	17	6	0.874E-09
2	7	0.475E-09	7	7	0.133E-07	12	7	0.138E-07	17	7	0.103E-08
2	8	0.512E-09	7	8	0.137E-07	12	8	0.142E-07	17	8	0.113E-08
2	9	0.536E-09	7	9	0.138E-07	12	9	0.144E-07	17	9	0.119E-08
2	10	0.549E-09	7	10	0.139E-07	12	10	0.145E-07	17	10	0.122E-08
2	11	0.549E-09	7	11	0.139E-07	12	11	0.145E-07	17	11	0.122E-08
2	12	0.536E-09	7	12	0.138E-07	12	12	0.144E-07	17	12	0.119E-08
2	13	0.512E-09	7	13	0.137E-07	12	13	0.142E-07	17	13	0.113E-08
2	14	0.475E-09	7	14	0.133E-07	12	14	0.138E-07	17	14	0.103E-08
2	15	0.429E-09	7	15	0.118E-07	12	15	0.122E-07	17	15	0.874E-09
2	16	0.377E-09	7	16	0.258E-08	12	16	0.284E-08	17	16	0.684E-09
2	17	0.326E-09	7	17	0.103E-08	12	17	0.119E-08	17	17	0.523E-09
2	18	0.280E-09	7	18	0.660E-09	12	18	0.758E-09	17	18	0.408E-09
2	19	0.240E-09	7	19	0.475E-09	12	19	0.536E-09	17	19	0.326E-09
2	20	0.207E-09	7	20	0.363E-09	12	20	0.403E-09	17	20	0.267E-09
3	1	0.236E-09	8	1	0.386E-09	13	1	0.386E-09	18	1	0.236E-09
3	2	0.280E-09	8	2	0.512E-09	13	2	0.512E-09	18	2	0.280E-09
3	3	0.337E-09	8	3	0.720E-09	13	3	0.720E-09	18	3	0.337E-09
3	4	0.408E-09	8	4	0.113E-08	13	4	0.113E-08	18	4	0.408E-09
3	5	0.492E-09	8	5	0.275E-08	13	5	0.275E-08	18	5	0.492E-09
3	6	0.582E-09	8	6	0.120E-07	13	6	0.120E-07	18	6	0.582E-09
3	7	0.660E-09	8	7	0.137E-07	13	7	0.137E-07	18	7	0.661E-09
3	8	0.720E-09	8	8	0.140E-07	13	8	0.140E-07	18	8	0.720E-09
3	9	0.758E-09	8	9	0.142E-07	13	9	0.142E-07	18	9	0.758E-09
3	10	0.776E-09	8	10	0.143E-07	13	10	0.143E-07	18	10	0.776E-09
3	11	0.776E-09	8	11	0.143E-07	13	11	0.143E-07	18	11	0.776E-09
3	12	0.758E-09	8	12	0.142E-07	13	12	0.142E-07	18	12	0.758E-09
3	13	0.720E-09	8	13	0.140E-07	13	13	0.140E-07	18	13	0.720E-09
3	14	0.660E-09	8	14	0.137E-07	13	14	0.137E-07	18	14	0.661E-09

3	15	0.582E-09	8	15	0.120E-07	13	15	0.120E-07	18	15	0.582E-09
3	16	0.492E-09	8	16	0.275E-08	13	16	0.275E-08	18	16	0.492E-09
3	17	0.408E-09	8	17	0.113E-08	13	17	0.113E-08	18	17	0.408E-09
3	18	0.337E-09	8	18	0.720E-09	13	18	0.720E-09	18	18	0.337E-09
3	19	0.280E-09	8	19	0.512E-09	13	19	0.512E-09	18	19	0.280E-09
3	20	0.236E-09	8	20	0.386E-09	13	20	0.386E-09	18	20	0.236E-09
4	1	0.267E-09	9	1	0.403E-09	14	1	0.363E-09	19	1	0.207E-09
4	2	0.326E-09	9	2	0.536E-09	14	2	0.475E-09	19	2	0.240E-09
4	3	0.408E-09	9	3	0.758E-09	14	3	0.660E-09	19	3	0.280E-09
4	4	0.523E-09	9	4	0.119E-08	14	4	0.103E-08	19	4	0.326E-09
4	5	0.684E-09	9	5	0.284E-08	14	5	0.258E-08	19	5	0.377E-09
4	6	0.874E-09	9	6	0.122E-07	14	6	0.118E-07	19	6	0.429E-09
4	7	0.103E-08	9	7	0.138E-07	14	7	0.133E-07	19	7	0.475E-09
4	8	0.113E-08	9	8	0.142E-07	14	8	0.137E-07	19	8	0.512E-09
4	9	0.119E-08	9	9	0.144E-07	14	9	0.138E-07	19	9	0.536E-09
4	10	0.122E-08	9	10	0.145E-07	14	10	0.139E-07	19	10	0.549E-09
4	11	0.122E-08	9	11	0.145E-07	14	11	0.139E-07	19	11	0.549E-09
4	12	0.119E-08	9	12	0.144E-07	14	12	0.138E-07	19	12	0.536E-09
4	13	0.113E-08	9	13	0.142E-07	14	13	0.137E-07	19	13	0.512E-09
4	14	0.103E-08	9	14	0.138E-07	14	14	0.133E-07	19	14	0.475E-09
4	15	0.874E-09	9	15	0.122E-07	14	15	0.118E-07	19	15	0.429E-09
4	16	0.684E-09	9	16	0.284E-08	14	16	0.258E-08	19	16	0.377E-09
4	17	0.523E-09	9	17	0.119E-08	14	17	0.103E-08	19	17	0.326E-09
4	18	0.408E-09	9	18	0.758E-09	14	18	0.660E-09	19	18	0.280E-09
4	19	0.326E-09	9	19	0.536E-09	14	19	0.475E-09	19	19	0.240E-09
4	20	0.267E-09	9	20	0.403E-09	14	20	0.363E-09	19	20	0.207E-09
5	1	0.301E-09	10	1	0.411E-09	15	1	0.333E-09	20	1	0.182E-09
5	2	0.377E-09	10	2	0.549E-09	15	2	0.429E-09	20	2	0.207E-09
5	3	0.492E-09	10	3	0.776E-09	15	3	0.582E-09	20	3	0.236E-09
5	4	0.684E-09	10	4	0.122E-08	15	4	0.874E-09	20	4	0.267E-09
5	5	0.112E-08	10	5	0.288E-08	15	5	0.215E-08	20	5	0.301E-09
5	6	0.215E-08	10	6	0.122E-07	15	6	0.105E-07	20	6	0.333E-09
5	7	0.258E-08	10	7	0.139E-07	15	7	0.118E-07	20	7	0.363E-09
5	8	0.275E-08	10	8	0.143E-07	15	8	0.120E-07	20	8	0.386E-09
5	9	0.284E-08	10	9	0.145E-07	15	9	0.122E-07	20	9	0.403E-09
5	10	0.288E-08	10	10	0.145E-07	15	10	0.122E-07	20	10	0.411E-09
5	11	0.288E-08	10	11	0.145E-07	15	11	0.122E-07	20	11	0.411E-09
5	12	0.284E-08	10	12	0.145E-07	15	12	0.122E-07	20	12	0.403E-09
5	13	0.275E-08	10	13	0.143E-07	15	13	0.120E-07	20	13	0.386E-09
5	14	0.258E-08	10	14	0.139E-07	15	14	0.118E-07	20	14	0.363E-09
5	15	0.215E-08	10	15	0.122E-07	15	15	0.105E-07	20	15	0.333E-09
5	16	0.112E-08	10	16	0.288E-08	15	16	0.215E-08	20	16	0.301E-09
5	17	0.684E-09	10	17	0.122E-08	15	17	0.874E-09	20	17	0.267E-09
5	18	0.492E-09	10	18	0.776E-09	15	18	0.582E-09	20	18	0.236E-09
5	19	0.377E-09	10	19	0.549E-09	15	19	0.429E-09	20	19	0.207E-09
5	20	0.301E-09	10	20	0.411E-09	15	20	0.333E-09	20	20	0.182E-09

NOTE--THE X AND Y VALUES FOR THE GRID ARE INDICES NUMBERED FROM WEST TO EAST AND FROM SOUTH TO NORTH, RESPECTIVELY.

ORNL/TM-6364

Distribution Category
UC-11, UC-41

INTERNAL DISTRIBUTION

1. S. I. Auerbach	36. T. H. Orton
2. R. O. Chester	37-41. D. C. Parzyck
3. S. J. Cotter	42. C. H. Patrick
4. K. E. Cowser	43. J. K. Poggenburg
5. H. W. Dickson	44. H. Postma
6. D. E. Dunning, Jr.	45. M. L. Randolph
7. W. R. Emanuel	46. C. R. Richmond
8. E. L. Etnier	47-51. P. S. Rohwer
9. W. Fulkerson	52. E. M. Rupp
10. W. R. Garrett	53. D. L. Shaeffer
11. F. F. Haywood	54. R. W. Shor
12. R. F. Hibbs	55. E. G. Struxness
13. G. S. Hill	56. C. C. Travis
14. F. O. Hoffman	57. G. U. Ulrickson
15. S. V. Kaye	58. P. J. Walsh
16. G. G. Killough	59. A. P. Watson
17. D. C. Kocher	60. H. A. Wright
18. C. A. Little	61-65. J. P. Witherspoon
19. L. M. McDowell	66. M. G. Yalcintas
20. H. R. Meyer	67-68. Central Research Library
21. C. W. Miller	69. ORNL Y-12 Technical Library
22-33. R. E. Moore	70-72. Laboratory Records Department
34. B. D. Murphy	73. Laboratory Records, ORNL-RC
35. F. R. O'Donnell	74. ORNL Patent Office

EXTERNAL DISTRIBUTION

75. C. J. Barton, 237 Outer Drive, Oak Ridge, Tennessee 37830
76. J. P. Blackwell, Acting Chief, Air Quality Branch, Tennessee Valley Authority, Muscle Shoals, Alabama 35660
77. W. W. Burr, Jr., Division of Biology and Medicine, Department of Energy, Washington, DC 20545
78. T. V. Crawford, Savannah River Laboratory, E.I. duPont de Nemours and Company, Aiken, South Carolina 29801
79. R. C. Cooper, Division of Biomedical and Environmental Research, Department of Energy, Washington, DC 20545
80. F. L. Culler, Electric Power Research Institute, P.O. Box 10412, Palo Alto, California 94303
81. L. J. Deal, Division of Biomedical and Environmental Research, Department of Energy, Washington, DC 20545
82. J. W. Frey, Air Quality Branch, Tennessee Valley Authority, River Oaks Building, Muscle Shoals, Alabama 35660

83. H. Falkenberry, Power Branch, Tennessee Valley Authority, Chattanooga, Tennessee 37401
84. P. H. Gerhardt, Division of Technology Overview, Department of Energy, Washington, DC 20545
85. F. A. Gifford, Jr., Air Resources Atmospheric Turbulence and Diffusion Laboratory, National Oceanic and Atmospheric Administration, Oak Ridge, Tennessee 37830
86. S. R. Hanna, Air Resources Atmospheric Turbulence and Diffusion Laboratory, National Oceanic and Atmospheric Administration, Oak Ridge, Tennessee 37830
87. L. Markel, Librarian, Institute for Energy Analysis, Oak Ridge Associated Universities, Oak Ridge, Tennessee 37830
88. W. A. Mills, U.S. Environmental Protection Agency, Criteria and Standards Division, 401 M Street, S.W., Washington, DC 20460
89. T. L. Montgomery, Division of Environmental Planning, 401 Building, Tennessee Valley Authority, Chattanooga, Tennessee 37401
90. R. R. Newton, Division of Biological and Environmental Research, Department of Energy, Washington, DC 20545
91. Director, Research and Technical Support Division, DOE-ORO, Oak Ridge, Tennessee 37830
92. C. Osterberg, Division of Biomedical and Environmental Research, Department of Energy, Washington, DC 20545
93. R. M. Perhac, Environmental Assessment Department, Electric Power Research Institute, P.O. Box 10412, Palo Alto, California 94303
94. G. W. Reynolds, Air Quality Branch, Tennessee Valley Authority, Muscle Shoals, Alabama 35660
95. G. L. Sherwood, Division of Development and Demonstration, Department of Energy, Washington, DC 20545
96. J. D. Spengler, Assistant Professor of Environmental Health, School of Public Health, Harvard University, 665 Huntington Avenue, Boston, Massachusetts 02115
97. J. Swinebroad, Division of Biomedical and Environmental Research, Department of Energy, Washington, DC 20545
98. J. E. Till, Route 2, Box 79H, Neeses, South Carolina 29107
99. R. Watters, Division of Biomedical and Environmental Research, Department of Energy, Washington, DC 20545
100. R. W. Wood, Division of Biology and Medicine, Department of Energy, Washington, DC 20545
- 101-418. Given distribution as shown in TID-4500 under category UC-11, Environmental Control Technology and Earth Sciences, and category UC-41, Health and Safety.