Argonne National Laboratory
9700 South Cass Avenue
Argonne, Illinois 60439

**A Fast Reactor Transient Analysis Methodology
for PCs:
Volume 3. LTC Program Manual of the
QuickBASIC Code**

by

K. O. Ott and L. Chung
School of Nuclear Engineering
Purdue University
West Lafayette, Indiana 47907

Prepared for
Reactor Engineering Division
Argonne National Laboratory

June 1992

MASTER

Table of Contents

Abstract	1
I. The QuickBASIC Version of LTC	2
I.1 Overview of the Modification of the GW-BASIC Version	2
I.2 Setup	3
I.3 Input/Output Instruction, TOP Sample Problem	4
I.4 Change of the In-Core Iteration of the GW-BASIC Version	4
II. Comparison of Computation Times	15
III. Loss-of-Heat-Sink Sample Problem	16
IV. Listing of the QuickBASIC Version of LTC	34
References	57

List of Figures

Figure 1a/b. Input file, TOP.INP, TOP sample problem	5 - 6
Figure 2a/d. Output, TOP.OUT of TOP sample problem	7 - 10
Figure 3a/b. Output file POWRO.TOP	11 - 12
Figure 4a/b. Output file DTEMP.TOP	13 - 14
Figure 5a/b. Input file LOH.INP LOHS sample problem	17 - 18
Figure 6a/g. Output file LOH.OUT	19 - 25
Figure 7a/d. Output file POWRO.LOH	26 - 29
Figure 8a/d. Output file DTEMP.LOH	30 - 33

**A Fast Reactor Transient Analysis Methodology
for PCs:
Volume 3. LTC Program Manual of the QuickBASIC Code**

by

K. O. Ott and L. Chung

Abstract

This manual augments the detailed manual of the GW-BASIC version of the LTC code (see Refs. 1 and 2) for an application in QuickBASIC. As most of the GW-BASIC coding of this program for "LMR Transient Calculations" is compatible with QuickBASIC, this manual pertains primarily to the *required* changes, such as the handling of input and output, as described in Sec. I. The considerable reduction in computation time achieved by this conversion is demonstrated in Sections I to III for two sample problems, using a variety of hardware and execution options. It is summarized in Sec. II. The revised code is listed in Sec. IV.

Although the severe storage limitations of GW-BASIC no longer apply, the LOF transient path has not been completed in this QuickBASIC code. Its advantages are thus primarily in the much faster running time for TOP and LOHS transients. For the fastest PC hardware (486) and execution option (see Sec. II) the computation time is reduced by a factor of 124 compared to GW-BASIC on a 386/20.

I. The QuickBASIC Version of LTC

I.1 Overview of the Modifications of the GW-BASIC Version

The major changes of the GW-BASIC version of LTC are in the following four areas:

1. *Removal of the Incompatibilities:* The only incompatible statements were the LIST statements used in the GW-BASIC version for the on-screen handling of the four Input screens. They were naturally eliminated with reworking the Input screens into an Input file.
2. *Elimination of the Line Numbers:* The line numbers of GW-BASIC are not used in QuickBASIC. They have been removed. However, the line numbers in the GOTO statements have been left in place, playing now the role of identifiers of the target locations.
3. *Input:* The direct Input and the Input DATA of the four GW-BASIC Input screens have been combined into a single Input file. Before the execution of the program, the user is prompted to provide an Input file name, or press ENTER to use the default name LTC.INP.

As long as transients are run for a given reactor, *most* of the Input stays the same from run to run (e.g., delayed neutron and decay heat data, various dimensions, masses and heat capacities or coefficients). Thus, the normal Input preparation consists just of an "editing" of the Input file by standard means.

4. *Output:*

All on-line LPRINT-output statements have been eliminated. The output is now entirely in the form of "output files," except for an on-screen display of some of the results. Before execution, the user is prompted to specify the three Output-file names, or press ENTER for each individual one to use the default names:

- LTC.OUT
- POWRO.OUT
- DTEMP.OUT

Renaming the output files in a sequence of runs is required to avoid an overwriting of the previous results.

I.2 Setup

The compilation of the QuickBASIC version results in an executable file, called LTC.EXE. It can be run on any IBM compatible PC, such as XT(8088), AT(286), 385 or 486 under MS-DOS, PC-DOS or DR-DOS operating systems. The version available from the author can be run directly from the floppy disk. However, loading it on a hard disk (e.g., subdirectory LTC) is generally preferable. Table I lists the size of the required storage for the LTC program set. The size of the output files depends on the amount of output specified. The output-files of Tab. I hold for the TOP sample problem, presented below.

TABLE I
LTC Program Set
Input and Output Files for TOP Sample Problem

LTC.BAS (QuickBASIC)	50,384 bytes
LTC.EXE	79,650 bytes
TOP.INP (Sample Problem)	4,188 bytes
TOP.OUT (Sample Problem)	13,593 bytes
POWRO.TOP (Sample Problem)	5,195 bytes
DTEMP.TOP (Sample Problem)	5,721 bytes
LOH.INP (Sample Problem)	4,189 bytes
LOH.OUT (Sample Problem)	38,262 bytes
POWRO.LOH (Sample Problem)	16,612 bytes
DTEMP.LOH (Sample Problem)	18,226 bytes

I.3 Input/Output

The input file of the sample problem is displayed in Figs. 1a and 1b. Both, input and output files, are in ASCII format. As noted above, the user can specify the Input file name, with any extension. Before editing the Input file, it is good practice to back-up the previous version, or use a different name. The modifications of the file can be done with any of the standard editing programs. The following, however, needs to be observed: *Do not delete any of the "remark" statements, as they are explicitly deleted in calling the input. If you make a change, have at least one space between the number and the remark statement.*

At the end of the run, the user is prompted to decide on a hard copy of the results of the three Output-files by "y" or "n". The printing of these files can be stopped any time by pressing ESC. As in the GW-BASIC version, the Input file can be completely echoed as shown in Figs. 2a and 2b, preceding the listing of the "main" output on Figs. 2b through 2d. The "main" output shown on these two tables is also appearing on the screen during the calculation. The printing of the other two Output files, POWRO.OUT and DTEMP.OUT follows after a "new page" command (see Figs. 3 and 4).

Inspection of the power trajectory shows that the power is lower than the initial and the asymptotic values between about 150 min to about 448 minutes, i.e., for about 5 hours. As both, the initial and asymptotic relative precursor populations are equal to βp_0 (see Ref. 3), a period of "underproduction" of precursors is needed to compensate the "overproduction" during the early flux rise.

I.4 Change of the In-Core Iteration of the GW-BASIC Version

The following changes in the GW-BASIC Code (Vol. 2) correct an error in the coding of the in-core iteration. It does not affect the results for sufficiently small time steps. But it allows now a considerable relaxation of the time step increases. The time steps had to be limited to 16s or 32s before; they can now be increased to 256s. The revised lines are:

1726 PP = 0 : ITMAX = 2

2198 ITER = 0

2506 DTLPEFF = IV(14)

2518 DTS = IV(16)

Delete lines 2540 to 2554

4578 GOTO 4700

```

===== INPUT DATA PART I =====
I.   TRANSIENT TYPE :
1    : TT          '1=TOP, 2=LOHS, 3=LOF(NOT WORKING)
II.  TIME STRUCTURE :
2    : DT(1)       'TIME STEP SIZE (SEC) OF FIRST BLOCK
20   : NM          '# OF TIME STEPS PER BLOCK
16   : BE          '# OF BLOCKS
.01  : LDB         'RELATIVE-POWER-CHANGE LIMIT FOR DT(BL)-DOUBLING
.02  : LHA         'RELATIVE-POWER-CHANGE LIMIT FOR DT(BL)-HALVING
256  : MAXDT       'MAXIMUM STEP SIZE (SEC)
III. REACTIVITY INSERTION :
1    : RG          '1=RAMP, 2=WORTH-CURVE
.01  : A           'RAMP INSERTION RATE
.2   : RM          'END-POINT REACTIVITY OF RAMP
1    : DR          'DURATION OF PARABOLIC RAMP SMOOTHING
      :            'END-POINT OF RAMP +/- DR*DT
90   : H           'CORE HEIGHT (CM)
IV.  OTHER QUANTITIES :
1    : PO          'INITIAL POWER RELATIVE TO NOMINAL POWER
24   : TL          'FLOW-TIME CORE-OUTLET TO IHX-OUTLET (SEC)
===== INPUT DATA PART II =====
V.   OTHER QUANTITIES : (FP=FULL POWER; FPS=FP SECONDS)
.0036 : DHR        'DECAY HEAT REMOVAL FROM HOT POOL (FP)
.0587 : BH         'INITIAL DECAY HEAT FRACTION (FP)
1.11E-11 : SSP     'SPONTANEOUS FISSION SOURCE (FP)
110   : ARVHP      'HOT POOL VESSEL AREA (M**2)
190   : ARVCP      'COLD POOL VESSEL AREA (M**2)
.4613 : CLHP       'HOT POOL SODIUM HEAT CAPACITY (FPS)
.5089 : CLCP       'COLD POOL SODIUM HEAT CAPACITY (FPS)
.2188 : CSHP       'HOT POOL STEEL HEAT CAPACITY (FPS)
.5422 : CSCP       'COLD POOL STEEL HEAT CAPACITY (FPS)
.0083 : CVHP       'HOT POOL VESSEL HEAT CAPACITY (FPS)
.0205 : CVCP       'COLD POOL VESSEL HEAT CAPACITY (FPS)
.00762 : CCOR      'CORE HEAT CAPACITY (FPS)
.00271 : CFUL      'FUEL HEAT CAPACITY (FPS)
152.76 : DTCCOOL   'NOMINAL COOLANT TEMPERATURE RISE (K)
89.56 : DTFCO      'NOMINAL FUEL/CLAD TEMPERATURE RISE (K)
630.56 : TVCP0     'INITIAL COLD POOL SODIUM TEMPERATURE (K)
783.33 : TVHP0     'INITIAL HOT POOL SODIUM TEMPERATURE (K)
===== INPUT DATA PART III =====
REM: BETA , BT(1) TO BT(6), DELAYED NEUTRONS
.00826,.07248,.06336,.12134,.05513,.01773
REM: BETA , BT(7) TO BT(12), DECAY HEAT
1.6232,2.094,1.163,.5523,.0852,.3521
REM: BETA , BT(13) TO BT(21), FEEDBACK (INDEX NOT CORRESPONDIG TO LAMBDA)
-.0981,-0.1432,.1715,-.1184,-.1184,-.1110,.062,.062,78.9
REM: LAMDA, L(1) TO L(6), DELAYED NEUTRONS
.01298,.03137,.1354,.3457,1.369,3.7376
REM: LAMDA, L(7) TO L(12), DECAY HEAT
.1985,.01437,.009360,.0000762,.00000973,.000000888
REM: LAMDA, L(13) TO L(20), FEEDBACK (INDEX NOT CORRESPONDING TO BETA)
4.108,2.00,.0092,3.975,4.108,0.041,4.108,4.108
REM: LAMDA, L(21) TO L(32), FLOW LOOP
.01282,.01282,.001025,.01282,.00085,0.01282,0.01415,.01415,.01016,0.01415,
.00085,0.01415

```

Fig. 1a Input file TOP.INP for TOP sample problem

```

REM: SPECIAL LAMBDA VALUES
18.09,4.725,6.613,13.66,44.51
===== INPUT DATA PART IV =====
REM: TEMPERATURES FOR RACS HEAT-FLUX CORRELATION
433.,495.7,577.8,681.6,753.6,810.2,857.5,898.4,951.5,1025.,1086.,1139.
REM: RACS HEAT FLUXES
5.0E-7,1.0E-6,2.0E-6,4.0E-6,6.0E-6,8.0E-6,1.0E-5,1.2E-5,1.5E-5,2.0E-5,2.5E-
5,3.0E-5
REM: TIMES FOR STEAM GENERATOR HEAT-FLUX CORRELATION
0,2,4,6,8,10,12,14,16,18,20,25,30,35,40,45,50,55
REM: STEAM GENERATOR HEAT FLUXES
1,.368,.195,.122,.084,.062,.047,.038,.031,.026,.022,.015,.011,.009,.007,.00
6,.005,0
.....
1      : PR      ' NOMINAL HEAY REJECTION      (FP)
6      : TLOF    'CHARACTERISTIC TIME FOR FLOW LOSS IN LOF (SEC)
82     : TLOHS   'TIME FOR SG LOOSING HEAT FLUX IN LOHS  (SEC)
5      : NPNT    'PRINT EVERY NPNT STEP
1      : INED    '1=ENABLE INPUT EDIT; 0=NO EDIT; 0.1=ONLY HEADING
0      : STUCK   'STUCK=0 IF FUEL FREE TO EXPAND

```

Fig. 1b Continuation of TOP.INP

*****-- VERSION LTC-5 --*****
 06-16-1992 TOP 20:52:31
 -----EDIT OF INPUT DATA-----

TT=TRANSIENT TYPE, 1:TOP ; 2:LOHS ; 3:LOF..... 1
 DT(1)=TIME STEP SIZE OF FIRST BLOCK (SECONDS)..... 2
 MAXDT=MAXIMUM STEP SIZE (SECONDS)..... 256
 NM=NUMBER OF TIME STEPS PER BLOCK..... 20
 BE=NUMBER OF BLOCKS..... 16
 LDB=REL.POWER-CHANGE LIMIT FOR DT(BL)-DOUBLING..... .01
 LHA=REL.POWER-CHANGE LIMIT FOR DT(BL)-HALVING..... .02
 RG=OPTION OF EXTERNAL REACTIVITY, 1:RAMP ; 2:WORTH CURVE..... 1
 A=INPUT RAMP RATE (\$/S)..... .01
 RM=MAXIMUM RAMP REACTIVITY (\$)..... .2
 DR=DURATION OF PARABOLIC RAMP SMOOTHING (+/- DR*DT(1))..... 1
 H=CORE HEIGHT (CM)..... 90
 TL=FLOW DELAY BETWEEN OUTLET AND INLET (SECONDS)..... 24
 BH=INITIAL DECAY HEAT FRACTION OF TOTAL POWER..... .0587
 PR=HEAT REJECTION RATE (FULL POWER)..... 1
 ARVHP=HOT POOL VESSEL AREA (M**2)..... 110
 ARVCP=COLD POOL VESSEL AREA (M**2)..... 190
 DHR=DECAY HEAD REMOVAL (FULL POWER)..... .0036
 DTCOOL 'NOMINAL COOLANT TEMPERATURE RISE ALONG CHANNEL..... 152.76
 NPNT=PRINT EVERY NPNT STEP..... 5
 TLOF=CHARACTERISTIC TIME FOR FLOW LOSS IN LOF (SEC)..... 6
 TLOHS=TIME FOR SG LOSING HEAT FLUX IN LOHS (SEC)..... 82
 SSP=SPONTANEOUS FISSION SOURCE..... 1.11E-11

K	BT(K)	L(K)	
1	.00826	.01298	DELAYED NEUTRON
2	.07248	.03137	DELAYED NEUTRON
3	.06336	.1354	DELAYED NEUTRON
4	.12134	.3457	DELAYED NEUTRON
5	.05513	1.369	DELAYED NEUTRON
6	.01773	3.7376	DELAYED NEUTRON
7	1.6232	.1985	DECAY HEAT
8	2.094	.01437	DECAY HEAT
9	1.163	.00936	DECAY HEAT
10	.5523	.0000762	DECAY HEAT
11	.0852	9.73E-06	DECAY HEAT
12	.3521	8.88E-07	DECAY HEAT
13	-.0981	4.108	FEEDBACK(NOTE#2)
14	-.1432	2	FEEDBACK(NOTE#2)
15	.1715	.0092	FEEDBACK(NOTE#2)
16	-.1184	3.975	FEEDBACK(NOTE#2)
17	-.1184	4.108	FEEDBACK(NOTE#2)
18	-.111	.041	FEEDBACK(NOTE#2)
19	.062	4.108	FEEDBACK(NOTE#2)
20	.062	4.108	FEEDBACK(NOTE#2)
21	78.9	.01282	FLOW COLD-POOL
22	0	.01282	FLOW COLD-POOL
23	0	.001025	STEEL COLD-POOL
24	0	.01282	FLOW COLD-POOL
25	0	.00085	VESSEL COLD-POOL
26	0	.01282	FLOW COLD-POOL

Fig. 2a Input echo of TOP sample problem, part 1

27	0	.01415	FLOW HOT-POOL
28	0	.01415	FLOW HOT-POOL
29	0	.01016	STEEL HOT-POOL
30	0	.01415	FLOW HOT-POOL
31	0	.00085	VESSEL HOT-POOL
32	0	.01415	FLOW HOT-POOL

NOTE#1 : $BT(K) = BT(K) / 100$ FOR DELAYED NEUTRONS
 $BT(K) = BT(K) / 100 / (1 - BH)$ FOR DECAY HEAT

NOTE#2 : INDIVIDUAL FEEDBACK COEFFICIENTS & TIME CONSTANTS :

-DRIVING FORCE---		DELAY LOCATION----	TIME CONSTANT-----
CLAD -TEMP	FUEL ROD		4.108
OUTLET-TEMP	LOAD PAD		2
INLET-TEMP	GRID PLATE		.0092
COOLANT	STRUCTURE		3.975
FISSION POWER	FUEL ROD		4.108
HP-TEMP	CR-DRIVE		.041

----- INDIVIDUAL FEEDBACK COEFFICIENTS: BT(K) -----

DOPPLER	-.0981
AXIAL EXPANSION	-.1432
COOLANT EXPANSION	.1715
100*XMC/XAC	-.1184
GRID PLATE EXPANSION	-.1184
CR-DRIVE-LINE EXPANSION	-.111
HOT POOL VESSEL EXPANSION.....	.062
COLD POOL VESSEL EXPANSION.....	.062

----- HEAT CAPACITIES -----

CLHP=HEAT CAPACITY OF HOT-POOL SODIUM (FPS/K).....	.4613
CLCP=HEAT CAPACITY OF COLD-POOL SODIUM (FPS/K).....	.5089
CSHP=HEAT CAPACITY OF HOT-POOL STEEL (FPS/K).....	.2188
CSCP=HEAT CAPACITY OF COLD-POOL STEEL (FPS/K).....	.5422
CVHP=HEAT CAPACITY OF HOT-POOL VESSEL (FPS/K).....	.0083
CVCP=HEAT CAPACITY OF COLD-POOL VESSEL (FPS/K).....	.0205

MIN.SEC	POWER	DEC.HEAT	DTOUTLET	DTLHP	DTOHX	DTINLET	100*RO	100*RX	100*RF
0.000	100.000	5.870	0.000	0.000	0.000	0.000	0.000	0.000	0.000
0.100	110.365	5.986	14.499	0.864	0.000	0.000	4.321	10.000	-5.679
0.200	122.842	6.242	33.929	3.874	0.000	0.000	5.970	19.500	-13.530
0.300	126.136	6.453	39.749	8.086	0.277	0.006	3.864	20.000	-16.136
0.400	127.374	6.579	41.783	12.012	2.404	0.147	2.800	20.000	-17.200
BLOCK # 1	ELAPSED TIME IS .2734375 SECONDS; FISSION POWER= 1.207951								
BLOCK # 2	MAXD OF PREVIOUS BLOCK= 2.245205E-02 THUS NEW DT= 2								
0.500	127.898	6.672	43.103	15.512	6.418	0.651	2.057	20.000	-17.943
1.000	127.983	6.746	44.179	18.614	10.491	1.587	1.481	20.000	-18.519
1.100	127.770	6.805	45.137	21.375	14.162	2.865	1.019	20.000	-18.981
1.200	127.343	6.850	46.016	23.845	17.417	4.391	0.645	20.000	-19.355

Fig. 2b Rest of input echo of TOP sample problem; beginning of Output file TOP.OUT

```

BLOCK # 2   ELAPSED TIME IS .484375 SECONDS; FISSION POWER= 1.20493
BLOCK # 3   MAXD OF PREVIOUS BLOCK= 1.199882E-03   THUS NEW DT= 4
1.400 126.143 6.910 47.680 28.108 22.889 7.885 0.108 20.000 -19.892
2.000 124.532 6.934 48.988 31.645 27.321 11.628 -0.259 20.000 -20.259
2.200 122.777 6.931 50.053 34.621 30.987 15.362 -0.489 20.000 -20.489
2.400 120.980 6.907 50.901 37.154 34.065 18.942 -0.630 20.000 -20.630
BLOCK # 3   ELAPSED TIME IS .703125 SECONDS; FISSION POWER= 1.140722
BLOCK # 4   MAXD OF PREVIOUS BLOCK= 2.96753E-03   THUS NEW DT= 8
3.200 117.556 6.824 52.125 41.213 38.926 25.373 -0.743 20.000 -20.743
4.000 114.411 6.714 52.688 44.187 42.516 30.713 -0.744 20.000 -20.744
4.400 111.729 6.597 52.890 46.352 45.138 35.004 -0.680 20.000 -20.680
5.200 109.516 6.486 52.885 47.915 47.040 38.372 -0.590 20.000 -20.590
BLOCK # 4   ELAPSED TIME IS .9296875 SECONDS; FISSION POWER= 1.030302
BLOCK # 5   MAXD OF PREVIOUS BLOCK= 5.969283E-03   THUS NEW DT= 16
6.400 106.327 6.300 52.628 49.828 49.386 42.963 -0.401 20.000 -20.401
8.000 104.462 6.172 52.420 50.815 50.578 45.609 -0.240 20.000 -20.240
9.200 103.471 6.093 52.446 51.412 51.254 47.153 -0.130 20.000 -20.130
10.400 102.988 6.048 52.700 51.894 51.752 48.147 -0.065 20.000 -20.065
BLOCK # 5   ELAPSED TIME IS 1.148438 SECONDS; FISSION POWER= .969396
BLOCK # 6   MAXD OF PREVIOUS BLOCK= 7.033558E-03   THUS NEW DT= 32
13.200 102.615 6.010 53.531 52.816 52.664 49.553 -0.011 20.000 -20.011
16.000 102.514 6.000 54.705 53.929 53.755 50.878 -0.009 20.000 -20.009
18.400 102.359 5.992 55.844 55.079 54.909 52.251 -0.012 20.000 -20.012
21.200 102.169 5.984 56.886 56.170 56.011 53.583 -0.014 20.000 -20.014
BLOCK # 6   ELAPSED TIME IS 1.367188 SECONDS; FISSION POWER= .9618527
BLOCK # 7   MAXD OF PREVIOUS BLOCK= 1.694213E-03   THUS NEW DT= 64
26.400 101.792 5.964 58.562 57.964 57.839 55.850 -0.008 20.000 -20.008
32.000 101.489 5.949 60.095 59.589 59.481 57.825 -0.008 20.000 -20.008
37.200 101.236 5.937 61.379 60.952 60.856 59.490 -0.009 20.000 -20.009
42.400 101.030 5.926 62.456 62.096 62.015 60.883 -0.007 20.000 -20.007
BLOCK # 7   ELAPSED TIME IS 1.648438 SECONDS; FISSION POWER= .9510387
BLOCK # 8   MAXD OF PREVIOUS BLOCK= 1.582799E-03   THUS NEW DT= 128
53.200 100.743 5.912 64.047 63.762 63.700 62.909 -0.014 20.000 -20.014
64.000 100.515 5.900 65.221 65.026 64.972 64.433 -0.007 20.000 -20.007
74.400 100.356 5.892 66.062 65.927 65.889 65.516 -0.004 20.000 -20.004
85.200 100.248 5.886 66.661 66.567 66.541 66.280 -0.002 20.000 -20.002
BLOCK # 8   ELAPSED TIME IS 1.867188 SECONDS; FISSION POWER= .9436189
BLOCK # 9   MAXD OF PREVIOUS BLOCK= 1.566339E-03   THUS NEW DT= 256
106.400 100.122 5.880 67.368 67.319 67.344 67.186 -0.005 20.000 -20.005
128.000 100.053 5.877 67.746 67.720 67.748 67.662 -0.004 20.000 -20.004
149.200 100.012 5.874 67.936 67.923 67.949 67.904 -0.004 20.000 -20.004
170.400 99.990 5.873 68.029 68.025 68.049 68.025 -0.003 20.000 -20.003
BLOCK # 9   ELAPSED TIME IS 2.132813 SECONDS; FISSION POWER= .9411747
BLOCK # 10  MAXD OF PREVIOUS BLOCK= 8.070697E-04   THUS NEW DT= 256
192.000 99.980 5.872 68.075 68.075 68.096 68.084 -0.002 20.000 -20.002
213.200 99.975 5.871 68.097 68.100 68.117 68.112 -0.001 20.000 -20.001
234.400 99.974 5.871 68.107 68.111 68.124 68.124 -0.001 20.000 -20.001
256.000 99.975 5.871 68.111 68.115 68.125 68.128 -0.000 20.000 -20.000
BLOCK # 10  ELAPSED TIME IS 2.359375 SECONDS; FISSION POWER= .9410429
BLOCK # 11  MAXD OF PREVIOUS BLOCK= 5.038812E-04   THUS NEW DT= 256
277.200 99.977 5.871 68.113 68.117 68.124 68.128 0.000 20.000 -20.000
298.400 99.981 5.870 68.114 68.117 68.121 68.126 0.000 20.000 -20.000
320.000 99.984 5.870 68.114 68.117 68.119 68.124 0.001 20.000 -19.999
341.200 99.988 5.870 68.114 68.117 68.117 68.122 0.001 20.000 -19.999
BLOCK # 11  ELAPSED TIME IS 2.632813 SECONDS; FISSION POWER= .9411722

```

Fig. 2c Continuation of TOP.OUT

```

BLOCK # 12      MAXD OF PREVIOUS BLOCK= 3.005276E-04      THUS NEW DT= 256
362.400 99.991 5.870 68.115 68.117 68.115 68.120 0.001 20.000 -19.999
384.000 99.994 5.871 68.115 68.117 68.114 68.118 0.001 20.000 -19.999
405.200 99.997 5.871 68.116 68.117 68.113 68.117 0.001 20.000 -19.999
426.400 99.999 5.871 68.116 68.117 68.113 68.116 0.001 20.000 -19.999
BLOCK # 12      ELAPSED TIME IS 2.859375 SECONDS; FISSION POWER= .9412816
BLOCK # 13      MAXD OF PREVIOUS BLOCK= 1.736792E-04      THUS NEW DT= 256
448.000 100.000 5.871 68.117 68.117 68.114 68.116 0.001 20.000 -19.999
469.200 100.002 5.871 68.118 68.118 68.114 68.116 0.000 20.000 -20.000
490.400 100.003 5.871 68.118 68.118 68.115 68.116 0.000 20.000 -20.000
512.000 100.003 5.871 68.119 68.118 68.116 68.116 0.000 20.000 -20.000
BLOCK # 13      ELAPSED TIME IS 3.125 SECONDS; FISSION POWER= .9413248
BLOCK # 14      MAXD OF PREVIOUS BLOCK= 9.853094E-05      THUS NEW DT= 256
533.200 100.003 5.871 68.119 68.119 68.116 68.117 0.000 20.000 -20.000
554.400 100.003 5.871 68.120 68.119 68.117 68.117 0.000 20.000 -20.000
576.000 100.003 5.870 68.120 68.119 68.118 68.118 0.000 20.000 -20.000
597.200 100.003 5.870 68.120 68.120 68.119 68.118 0.000 20.000 -20.000
BLOCK # 14      ELAPSED TIME IS 3.34375 SECONDS; FISSION POWER= .9413243
BLOCK # 15      MAXD OF PREVIOUS BLOCK= 5.167553E-05      THUS NEW DT= 256
618.400 100.002 5.870 68.120 68.120 68.119 68.119 -0.000 20.000 -20.000
640.000 100.002 5.870 68.120 68.120 68.120 68.119 -0.000 20.000 -20.000
661.200 100.002 5.870 68.120 68.120 68.120 68.119 -0.000 20.000 -20.000
682.400 100.001 5.870 68.120 68.120 68.120 68.120 -0.000 20.000 -20.000
BLOCK # 15      ELAPSED TIME IS 3.5625 SECONDS; FISSION POWER= .9413103
BLOCK # 16      MAXD OF PREVIOUS BLOCK= 3.206799E-05      THUS NEW DT= 256
704.000 100.001 5.870 68.120 68.120 68.120 68.120 -0.000 20.000 -20.000
725.200 100.001 5.870 68.120 68.120 68.121 68.120 -0.000 20.000 -20.000
746.400 100.000 5.870 68.120 68.120 68.121 68.120 -0.000 20.000 -20.000
768.000 100.000 5.870 68.120 68.120 68.121 68.120 -0.000 20.000 -20.000
BLOCK # 16      ELAPSED TIME IS 3.835938 SECONDS; FISSION POWER= .9413004

```

TOTAL ELAPSED TIME FOR THIS RUN IS 6.393229E-02 MINUTES

Fig. 2d Continuation of TOP.OUT

----- POWER & REACTIVITY OUTPUT -----								
TIME(S)	100*POW	100*DC.HT	RHO(CT)	DOPPLER	AX.EXP	COOLANT	RAD.EXP	CR-ROD
0.000	100.000	5.870	0.000	0.000	0.000	0.000	0.000	0.000
10.000	110.365	5.986	4.321	-1.785	-2.605	1.243	-2.527	-0.011
20.000	122.842	6.242	5.970	-4.143	-6.048	2.909	-6.162	-0.091
30.000	126.136	6.453	3.864	-4.840	-7.065	3.409	-7.401	-0.286
40.000	127.374	6.579	2.800	-5.084	-7.422	3.595	-7.784	-0.564
BLOCK 2								
50.000	127.898	6.672	2.057	-5.234	-7.640	3.752	-8.004	-0.884
60.000	127.983	6.746	1.481	-5.343	-7.799	3.924	-8.155	-1.213
70.000	127.770	6.805	1.019	-5.429	-7.925	4.116	-8.270	-1.536
80.000	127.343	6.850	0.645	-5.500	-8.029	4.322	-8.366	-1.841
BLOCK 3								
100.000	126.143	6.910	0.108	-5.621	-8.204	4.765	-8.548	-2.385
120.000	124.532	6.934	-0.259	-5.691	-8.307	5.198	-8.705	-2.837
140.000	122.777	6.931	-0.489	-5.732	-8.367	5.609	-8.861	-3.206
160.000	120.980	6.907	-0.630	-5.751	-8.394	5.989	-9.024	-3.506
BLOCK 4								
200.000	117.556	6.824	-0.743	-5.747	-8.389	6.645	-9.382	-3.942
240.000	114.411	6.714	-0.744	-5.689	-8.304	7.152	-9.732	-4.214
280.000	111.729	6.597	-0.680	-5.612	-8.192	7.587	-10.070	-4.366
320.000	109.516	6.486	-0.590	-5.532	-8.075	7.825	-10.387	-4.429
BLOCK 5								
400.000	106.327	6.300	-0.401	-5.391	-7.870	8.197	-10.933	-4.380
480.000	104.462	6.172	-0.240	-5.303	-7.742	8.406	-11.357	-4.202
560.000	103.471	6.093	-0.130	-5.270	-7.693	8.541	-11.686	-3.974
640.000	102.988	6.048	-0.065	-5.278	-7.704	8.648	-11.946	-3.738
BLOCK 6								
800.000	102.615	6.010	-0.011	-5.346	-7.803	8.839	-12.322	-3.297
960.000	102.514	6.000	-0.009	-5.457	-7.966	9.054	-12.644	-2.925
1120.000	102.359	5.992	-0.012	-5.563	-8.121	9.269	-12.932	-2.603
1280.000	102.169	5.984	-0.014	-5.659	-8.260	9.473	-13.198	-2.314
BLOCK 7								
1600.000	101.792	5.964	-0.008	-5.810	-8.480	9.811	-13.641	-1.793
1920.000	101.489	5.949	-0.008	-5.949	-8.684	10.112	-14.040	-1.368
2240.000	101.236	5.937	-0.009	-6.066	-8.855	10.365	-14.376	-1.010
2560.000	101.030	5.926	-0.007	-6.164	-8.998	10.576	-14.657	-0.708
BLOCK 8								
3200.000	100.743	5.912	-0.014	-6.310	-9.211	10.886	-15.070	-0.234
3840.000	100.515	5.900	-0.007	-6.417	-9.367	11.118	-15.378	0.092
4480.000	100.356	5.892	-0.004	-6.494	-9.479	11.233	-15.597	0.323
5120.000	100.248	5.886	-0.002	-6.548	-9.559	11.400	-15.753	0.487
BLOCK 9								
6400.000	100.122	5.880	-0.005	-6.613	-9.653	11.538	-15.935	0.684
7680.000	100.053	5.877	-0.004	-6.648	-9.704	11.611	-16.033	0.782
8960.000	100.012	5.874	-0.004	-6.665	-9.729	11.648	-16.084	0.832
10240.000	99.990	5.873	-0.003	-6.673	-9.741	11.667	-16.109	0.858
BLOCK 10								
11520.000	99.980	5.872	-0.002	-6.677	-9.747	11.676	-16.122	0.871
12800.000	99.975	5.871	-0.001	-6.679	-9.750	11.680	-16.128	0.878
14080.000	99.974	5.871	-0.001	-6.680	-9.752	11.682	-16.131	0.881
15360.000	99.975	5.871	-0.000	-6.681	-9.752	11.683	-16.132	0.883
BLOCK 11								
16640.000	99.977	5.871	0.000	-6.681	-9.753	11.683	-16.132	0.885

Fig. 3a Beginning of Output file POWRO.TOP

%17920.000	99.981	5.870	0.000	-6.681	-9.753	11.683	-16.132	0.885
%19200.000	99.984	5.870	0.001	-6.681	-9.753	11.682	-16.132	0.886
%20480.000	99.988	5.870	0.001	-6.682	-9.753	11.682	-16.132	0.886
BLOCK 12								
%21760.000	99.991	5.870	0.001	-6.682	-9.754	11.682	-16.131	0.886
%23040.000	99.994	5.871	0.001	-6.682	-9.754	11.682	-16.131	0.886
%24320.000	99.997	5.871	0.001	-6.682	-9.754	11.682	-16.131	0.886
%25600.000	99.999	5.871	0.001	-6.682	-9.754	11.682	-16.130	0.886
BLOCK 13								
%26880.000	100.000	5.871	0.001	-6.682	-9.754	11.682	-16.130	0.886
%28160.000	100.002	5.871	0.000	-6.682	-9.755	11.682	-16.130	0.886
%29440.000	100.003	5.871	0.000	-6.682	-9.755	11.682	-16.130	0.886
%30720.000	100.003	5.871	0.000	-6.683	-9.755	11.682	-16.130	0.886
BLOCK 14								
%32000.000	100.003	5.871	0.000	-6.683	-9.755	11.682	-16.130	0.886
%33280.000	100.003	5.871	0.000	-6.683	-9.755	11.682	-16.130	0.886
%34560.000	100.003	5.870	0.000	-6.683	-9.755	11.682	-16.130	0.886
%35840.000	100.003	5.870	0.000	-6.683	-9.755	11.682	-16.130	0.886
BLOCK 15								
%37120.000	100.002	5.870	-0.000	-6.683	-9.755	11.682	-16.131	0.886
%38400.000	100.002	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886
%39680.000	100.002	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886
%40960.000	100.001	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886
BLOCK 16								
%42240.000	100.001	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886
%43520.000	100.001	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886
%44800.000	100.000	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886
%46080.000	100.000	5.870	-0.000	-6.683	-9.755	11.683	-16.131	0.886

Fig. 3b Continuation of POWRO.TOP

----- DELTA TEMPERATURE OUTPUT -----									
TIME(S)	DT-FUEL	DT-CLAD	DT-COOL	DT-STRUC	DT-CR	DTOUTLET	DTLHP	DTOHX	DTINLET
0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
10.000	18.191	9.516	7.250	3.22	0.099	14.499	0.864	0.000	0.000
20.000	42.234	22.198	16.964	16.734	0.835	33.929	3.874	0.000	0.000
30.000	49.337	25.979	19.878	19.834	2.616	39.749	8.086	0.277	0.006
40.000	51.829	27.357	20.965	20.943	5.173	41.783	12.012	2.404	0.147
BLOCK 2									
50.000	53.349	28.395	21.877	21.853	8.113	43.103	15.512	6.418	0.651
60.000	54.460	29.423	22.883	22.856	11.170	44.179	18.614	10.491	1.587
70.000	55.343	30.492	24.001	23.972	14.178	45.137	21.375	14.162	2.865
80.000	56.068	31.596	25.204	25.173	17.050	46.016	23.845	17.417	4.391
BLOCK 3									
100.000	57.294	33.894	27.783	27.750	22.244	47.680	28.108	22.889	7.885
120.000	58.011	36.045	30.308	30.277	26.678	48.988	31.645	27.321	11.628
140.000	58.431	38.035	32.708	32.678	30.425	50.053	34.621	30.987	15.362
160.000	58.619	39.829	34.921	34.895	33.596	50.901	37.154	34.065	18.942
BLOCK 4									
200.000	58.585	42.857	38.749	38.727	38.607	52.125	41.213	38.926	25.373
240.000	57.991	45.075	41.701	41.685	42.280	52.688	44.187	42.516	30.713
280.000	57.206	46.693	43.947	43.935	44.963	52.890	46.352	45.138	35.004
320.000	56.387	47.857	45.629	45.620	46.910	52.885	47.915	47.040	38.372
BLOCK 5									
400.000	54.955	49.278	47.795	47.790	49.316	52.628	49.828	49.386	42.963
480.000	54.061	50.059	49.014	49.011	50.545	52.420	50.815	50.578	45.609
560.000	53.722	50.612	49.799	49.797	51.240	52.446	51.412	51.254	47.153
640.000	53.798	51.123	50.424	50.422	51.748	52.700	51.894	51.752	48.147
BLOCK 6									
800.000	54.492	52.153	51.542	51.540	52.662	53.531	52.816	52.664	49.553
960.000	55.629	53.379	52.791	52.789	53.754	54.705	53.929	53.755	50.878
1120.000	56.713	54.599	54.047	54.045	54.906	55.844	55.079	54.909	52.251
1280.000	57.683	55.742	55.234	55.233	56.008	56.886	56.170	56.011	53.583
BLOCK 7									
1600.000	59.221	57.624	57.206	57.205	57.830	58.562	57.964	57.839	55.850
1920.000	60.642	59.308	58.960	58.959	59.475	60.095	59.199	59.481	57.825
2240.000	61.833	60.724	60.435	60.433	60.855	61.379	60.952	60.856	59.490
2560.000	62.834	61.911	61.669	61.669	62.015	62.456	62.096	62.015	60.883
BLOCK 8									
3200.000	64.320	63.652	63.478	63.477	63.696	64.047	63.762	63.700	62.909
3840.000	65.411	64.948	64.827	64.826	64.982	65.221	65.026	64.972	64.433
4480.000	66.193	65.873	65.789	65.789	65.897	66.062	65.927	65.889	65.516
5120.000	66.753	66.529	66.471	66.470	66.546	66.661	66.567	66.541	66.280
BLOCK 9									
6400.000	67.409	67.304	67.277	67.277	67.307	67.368	67.319	67.344	67.186
7680.000	67.763	67.716	67.704	67.704	67.714	67.746	67.720	67.748	67.662
8960.000	67.939	67.924	67.920	67.920	67.920	67.936	67.923	67.949	67.904
%10240.000	68.025	68.027	68.027	68.027	68.024	68.029	68.025	68.049	68.0
BLOCK 10									
%11520.000	68.067	68.077	68.080	68.080	68.075	68.075	68.075	68.096	68.0
%12800.000	68.088	68.101	68.105	68.105	68.100	68.097	68.100	68.117	68.1
%14080.000	68.097	68.112	68.116	68.116	68.112	68.107	68.111	68.124	68.1
%15360.000	68.102	68.116	68.120	68.120	68.117	68.111	68.115	68.125	68.1
BLOCK 11									
%16640.000	68.105	68.117	68.121	68.121	68.118	68.113	68.117	68.124	68.1
%17920.000	68.107	68.117	68.120	68.120	68.119	68.114	68.117	68.121	68.1

Fig. 4a Beginning of Output file DTEMP.TOP

%19200.000	68.108	68.117	68.119	68.119	68.118	68.114	68.117	68.119	68.1
%20480.000	68.110	68.116	68.118	68.118	68.118	68.114	68.117	68.117	68.1
BLOCK 12									
%21760.000	68.112	68.116	68.117	68.117	68.117	68.115	68.117	68.115	68.1
%23040.000	68.113	68.116	68.117	68.117	68.117	68.115	68.117	68.114	68.1
%24320.000	68.115	68.116	68.116	68.116	68.117	68.116	68.117	68.113	68.1
%25600.000	68.116	68.116	68.116	68.116	68.117	68.116	68.117	68.113	68.1
BLOCK 13									
%26880.000	68.117	68.117	68.116	68.116	68.117	68.117	68.117	68.114	68.1
%28160.000	68.118	68.117	68.117	68.117	68.118	68.118	68.118	68.114	68.1
%29440.000	68.119	68.118	68.117	68.117	68.118	68.118	68.118	68.115	68.1
%30720.000	68.120	68.118	68.118	68.118	68.118	68.119	68.118	68.116	68.1
BLOCK 14									
%32000.000	68.120	68.118	68.118	68.118	68.119	68.119	68.119	68.116	68.1
%33280.000	68.121	68.119	68.118	68.118	68.119	68.120	68.119	68.117	68.1
%34560.000	68.121	68.119	68.119	68.119	68.119	68.120	68.119	68.118	68.1
%35840.000	68.121	68.120	68.119	68.119	68.119	68.120	68.120	68.119	68.1
BLOCK 15									
%37120.000	68.121	68.120	68.119	68.119	68.120	68.120	68.120	68.119	68.1
%38400.000	68.121	68.120	68.120	68.120	68.120	68.120	68.120	68.120	68.1
%39680.000	68.121	68.120	68.120	68.120	68.120	68.120	68.120	68.120	68.1
%40960.000	68.121	68.120	68.120	68.120	68.120	68.120	68.120	68.120	68.1
BLOCK 16									
%42240.000	68.121	68.120	68.120	68.120	68.120	68.120	68.120	68.120	68.1
%43520.000	68.121	68.120	68.120	68.120	68.120	68.120	68.120	68.121	68.1
%44800.000	68.120	68.120	68.120	68.120	68.120	68.120	68.120	68.121	68.1
%46080.000	68.120	68.120	68.120	68.120	68.120	68.120	68.120	68.121	68.1

Fig. 4b Continuation of DTEMP.TOP

II. Comparison of Computation Times

There are two ways to run LTC: Running LTC.BAS in QuickBASIC, or run LTC.EXE under DOS. Both modes of running LTC are considered in the following comparison.

The standard problem used for the comparison of computation times is the TOP sample problem of Ref. 2. After a correction of an error in the in-core iteration, which does not affect the results, the time steps can be relaxed more than in Ref. 2. Here 256s has been used as maximum time step. The initial time step was 2s and the code was run for 16 time blocks, covering 12 hours and 48 minutes (see Figs. 2, 3 and 4). By this time, the power is practically back to its initial value (100.000%). All other results are fully converged by this time.

The GW-BASIC time on a 386/20 computer is 477.4s. Running the GW-BASIC version on a 486DX33 reduces the time to 114s.

A major acceleration is achieved by compilation, i.e. by running LTC in its QuickBASIC version, or by running the executable version directly in DOS. The running time of the QuickBASIC version on a 386/16 is 239.37s; it takes 231.21s to run it directly in DOS.

A considerable additional reduction of the running time results from the use of a *math coprocessor*. The times on a 286/12 lap-top, a 386/20 and a 486/33 are 29.0s, 13.3s, and 12.4s respectively.

These computation times can be further reduced by an astonishingly large amount by avoiding all TSRs (Terminate-and-Stay Resident programs). This means booting the computer without "CONFIG.SYS" and "AUTOEXEC.BAT." Then, running the standard problem on the 486 takes 3.84s, i.e., only 31% of the 12.1 needed in the DOS environment that is configured in the usual way.

III. Loss-of-Heat-Sink Sample Problem

The convergence of the power and temperature trajectories of the LOHS transient is considerably slower than for the TOP. It takes typically two days or more to converge this transient. But during most of this time, the changes are very slow so that the time step algorithm in LTC stretches the time step to its set maximum value of 256s. With this 6 1/2 minute time step, the program moves fairly quickly through two days of minimal variation in power.

At the neutron flux minimum, the relative fission power is less than 10^{-7} of its original value. It is then maintained by source multiplication of the spontaneous fission source. The time step size of 256s is automatically reduced to 64s during the gradual recriticality enforced by the cooling effect of the decay heat removal system (see the discussion of this phenomenon in Ref. 11)

The strong damping of the oscillation is seen in the maximum reactivity values: At the first maximum at 1303 min ($\rho=1.164\phi$), at 1559.2 min ($\rho=0.335\phi$), at 1794 min ($\rho=0.100\phi$), at 2050 min ($\rho=0.032\phi$) and at 2284.4 min ($\rho=0.012\phi$). This amounts to a damping factor of about 3.3 between successive ρ maxima.

```

===== INPUT DATA PART I =====
I.   TRANSIENT TYPE :
2    : TT           '1=TOP, 2=LOHS, 3=LOF(NOT WORKING)
II.  TIME STRUCTURE :
2    : DT(1)        'TIME STEP SIZE (SEC) OF FIRST BLOCK
20   : NM           '# OF TIME STEPS PER BLOCK
70   : BE           '# OF BLOCKS
.01  : LDB          'RELATIVE-POWER-CHANGE LIMIT FOR DT(BL)-DOUBLING
.02  : LHA          'RELATIVE-POWER-CHANGE LIMIT FOR DT(BL)-HALVING
256  : MAXDT        'MAXIMUM STEP SIZE (SEC)
III. REACTIVITY INSERTION :
1    : RG           '1=RAMP, 2=WORTH-CURVE
.01  : A            'RAMP INSERTION RATE
.2   : RM           'END-POINT REACTIVITY OF RAMP
1    : DR           'DURATION OF PARABOLIC RAMP SMOOTHING
      :             'END-POINT OF RAMP +/- DR*DT
90   : H            'CORE HEIGHT (CM)
IV.  OTHER QUANTITIES :
1    : PO           'INITIAL POWER RELATIVE TO NOMINAL POWER
24   : TL           'FLOW-TIME CORE-OUTLET TO IHX-OUTLET (SEC)
===== INPUT DATA PART II =====
V.   OTHER QUANTITIES : (FP=FULL POWER; FPS=FP SECONDS)
.0036 : DHR         'DECAY HEAT REMOVAL FROM HOT POOL (FP)
.0587 : BH          'INITIAL DECAY HEAT FRACTION (FP)
1.11E-11 : SSP      'SPONTANEOUS FISSION SOURCE (FP)
110   : ARVHP       'HOT POOL VESSEL AREA (M**2)
190   : ARVCP       'COLD POOL VESSEL AREA (M**2)
.4613 : CLHP        'HOT POOL SODIUM HEAT CAPACITY (FPS)
.5089 : CLCP        'COLD POOL SODIUM HEAT CAPACITY (FPS)
.2188 : CSHP        'HOT POOL STEEL HEAT CAPACITY (FPS)
.5422 : CSCCP       'COLD POOL STEEL HEAT CAPACITY (FPS)
.0083 : CVHP        'HOT POOL VESSEL HEAT CAPACITY (FPS)
.0205 : CVCP        'COLD POOL VESSEL HEAT CAPACITY (FPS)
.00762 : CCOR       'CORE HEAT CAPACITY (FPS)
.00271 : CFUL       'FUEL HEAT CAPACITY (FPS)
152.76 : DTCOOL     'NOMINAL COOLANT TEMPERATURE RISE (K)
89.56 : DTFCO       'NOMINAL FUEL/CLAD TEMPERATURE RISE (K)
630.56 : TVCPO      'INITIAL COLD POOL SODIUM TEMPERATURE (K)
783.33 : TVHPO      'INITIAL HOT POOL SODIUM TEMPERATURE (K)
===== INPUT DATA PART III =====
REM: BETA , BT(1) TO BT(6), DELAYED NEUTRONS
.00826,.07248,.06336,.12134,.05513,.01773
REM: BETA , BT(7) TO BT(12), DECAY HEAT
1.6232,2.094,1.163,.5523,.0852,.3521
REM: BETA , BT(13) TO BT(21), FEEDBACK (INDEX NOT CORRESPONDING TO LAMBDA)
-.0981,-0.1432,.1715,-.1184,-.1184,-.1110,.062,.062,78.9
REM: LAMDA, L(1) TO L(6), DELAYED NEUTRONS
.01298,.03137,.1354,.3457,1.369,3.7376
REM: LAMDA, L(7) TO L(12), DECAY HEAT
.1985,.01437,.009360,.0000762,.00000973,.000000888
REM: LAMDA, L(13) TO L(20), FEEDBACK (INDEX NOT CORRESPONDING TO BETA)
4.108,2.00,.0092,3.975,4.108,0.041,4.108,4.108
REM: LAMDA, L(21) TO L(32), FLOW LOOP
.01282,.01282,.001025,.01282,.00085,0.01282,0.01415,0.01415,.01016,0.01415,.0008
1415

```

Fig. 5a Input file LOH.INP for LOHS sample problem

```

REM: SPECIAL LAMBDA VALUES
18.09,4.725,6.613,13.66,44.51
===== INPUT DATA PART IV =====
REM: TEMPERATURES FOR RACS HEAT-FLUX CORRELATION
433.,495.7,577.8,681.6,753.6,810.2,857.5,898.4,951.5,1025.,1086.,1139.
REM: RACS HEAT FLUXES
5.0E-7,1.0E-6,2.0E-6,4.0E-6,6.0E-6,8.0E-6,1.0E-5,1.2E-5,1.5E-5,2.0E-5,2.5E-5,3.0
REM: TIMES FOR STEAM GENERATOR HEAT-FLUX CORRELATION
0,2,4,6,8,10,12,14,16,18,20,25,30,35,40,45,50,55
REM: STEAM GENERATOR HEAT FLUXES
1,.368,.195,.122,.084,.062,.047,.038,.031,.026,.022,.015,.011,.009,.007,.006,.00
.....
1      : PR      ' NOMINAL HEAVY REJECTION (FP)
6      : TLOF    ' CHARACTERISTIC TIME FOR FLOW LOSS IN LOF (SEC)
82     : TLOHS   ' TIME FOR SG LOOSING HEAT FLUX IN LOHS (SEC)
10     : NPNT    ' PRINT EVERY NPNT STEP
1      : INED    ' 1=ENABLE INPUT EDIT; 0=NO EDIT; 0.1=ONLY HEADING
0      : STUCK   ' STUCK=0 IF FUEL FREE TO EXPAND

```

Fig. 5b Continuation of LOH.INP

*****-- VERSION LTC-5 -----
 06-21-1992 LOHS 15:57:18
 ===== EDIT OF INPUT DATA =====

TT=TRANSIENT TYPE, 1:TOP ; 2:LOHS ; 3:LOF..... 2
 DT(1)=TIME STEP SIZE OF FIRST BLOCK (SECONDS)..... 2
 MAXDT=MAXIMUM STEP SIZE (SECONDS)..... 256
 NM=NUMBER OF TIME STEPS PER BLOCK..... 20
 BE=NUMBER OF BLOCKS..... 70
 LDB=REL.POWER-CHANGE LIMIT FOR DT(BL)-DOUBLING..... .01
 LHA=REL.POWER-CHANGE LIMIT FOR DT(BL)-HALVING..... .02
 RG=OPTION OF EXTERNAL REACTIVITY, 1:RAMP ; 2:WORTH CURVE..... 1
 A=INPUT RAMP RATE (\$/S)..... 0
 RM=MAXIMUM RAMP REACTIVITY (\$)..... 0
 DR=DURATION OF PARABOLIC RAMP SMOOTHING (+/- DR*DT(1))..... 1
 H=CORE HEIGHT (CM)..... 90
 TL=FLOW DELAY BETWEEN OUTLET AND INLET (SECONDS)..... 24
 BH=INITIAL DECAY HEAT FRACTION OF TOTAL POWER..... .0587
 PR=HEAT REJECTION RATE (FULL POWER)..... 1
 ARVHP=HOT POOL VESSEL AREA (M**2)..... 110
 ARVCP=COLD POOL VESSEL AREA (M**2)..... 190
 DHR=DECAY HEAD REMOVAL (FULL POWER)..... .0036
 DTCOOL 'NOMINAL COOLANT TEMPERATURE RISE ALONG CHANNEL..... 152.76
 NPNT=PRINT EVERY NPNT STEP..... 10
 TLOF=CHARACTERISTIC TIME FOR FLOW LOSS in LOF (SEC)..... 6
 TLOHS=TIME FOR SG LOSING HEAT FLUX IN LOHS (SEC)..... 82
 SSP=SPONTANEOUS FISSION SOURCE..... 1.11E-11

K	BT(K)	L(k)	
1	.00826	.01298	DELAYED NEUTRON
2	.07248	.03137	DELAYED NEUTRON
3	.06336	.1354	DELAYED NEUTRON
4	.12134	.3457	DELAYED NEUTRON
5	.05513	1.369	DELAYED NEUTRON
6	.01773	3.7376	DELAYED NEUTRON
7	1.6232	.1985	DECAY HEAT
8	2.094	.01437	DECAY HEAT
9	1.163	.00936	DECAY HEAT
10	.5523	.0000762	DECAY HEAT
11	.0852	9.73E-06	DECAY HEAT
12	.3521	8.88E-07	DECAY HEAT
13	-.0981	4.108	FEEDBACK(NOTE#2)
14	-.1432	2	FEEDBACK(NOTE#2)
15	.1715	.0092	FEEDBACK(NOTE#2)
16	-.1184	3.975	FEEDBACK(NOTE#2)
17	-.1184	4.108	FEEDBACK(NOTE#2)
18	-.111	.041	FEEDBACK(NOTE#2)
19	.062	4.108	FEEDBACK(NOTE#2)
20	.062	4.108	FEEDBACK(NOTE#2)
21	78.9	.01282	FLOW COLD-POOL
22	0	.01282	FLOW COLD-POOL
23	0	.001025	STEEL COLD-POOL
24	0	.01282	FLOW COLD-POOL
25	0	.00085	VESSEL COLD-POOL
26	0	.01282	FLOW COLD-POOL

Fig. 6a Input echo of LOH sample problem, part 1

27	0	.01415	FLOW HOT-POOL
28	0	.01415	FLOW HOT-POOL
29	0	.01016	STEEL HOT-POOL
30	0	.01415	FLOW HOT-POOL
31	0	.00085	VESSEL HOT-POOL
32	0	.01415	FLOW HOT-POOL

NOTE#1 : BT(K)=BT(K)/100 FOR DELAYED NEUTRONS
 BT(K)=BT(K)/100/(1-BH) FOR DECAY HEAT

NOTE#2 : INDIVIDUAL FEEDBACK COEFFICIENTS & TIME CONSTANTS :

-DRIVING FORCE---		DELAY LOCATION----	TIME CONSTANT-----
CLAD -TEMP	FUEL ROD		4.108
OUTLET-TEMP	LOAD PAD		2
INLET-TEMP	GRID PLATE		.0092
COOLANT	STRUCTURE		3.975
FISSION POWER	FUEL ROD		4.108
HP-TEMP	CR-DRIVE		.041

----- INDIVIDUAL FEEDBACK COEFFICIENTS: BT(K) -----

DOPPLER	-.0981
AXIAL EXPANSION	-.1432
COOLANT EXPANSION	.1715
100*XMC/XAC	-.1184
GRID PLATE EXPANSION	-.1184
CR-DRIVE-LINE EXPANSION	-.111
HOT POOL VESSEL EXPANSION.....	.062
COLD POOL VESSEL EXPANSION.....	.062

----- HEAT CAPACITIES -----

CLHP=HEAT CAPACITY OF HOT-POOL SODIUM (FPS/K).....	.4613
CLCP=HEAT CAPACITY OF COLD-POOL SODIUM (FPS/K).....	.5089
CSHP=HEAT CAPACITY OF HOT-POOL STEEL (FPS/K).....	.2188
CSCP=HEAT CAPACITY OF COLD-POOL STEEL (FPS/K).....	.5422
CVHP=HEAT CAPACITY OF HOT-POOL VESSEL (FPS/K).....	.0083
CVCP=HEAT CAPACITY OF COLD-POOL VESSEL (FPS/K).....	.0205

MIN.SEC	POWER	DEC.HEAT	DTOUTLET	DTLHP	DTOHX	DTINLET	100*RO	100*RX	100*RF
0.000	100.000	5.870	0.000	0.000	0.000	0.000	0.000	0.000	0.000
0.200	99.265	5.861	3.014	0.266	37.074	4.340	-0.321	0.000	-0.321
0.400	96.594	5.809	10.422	1.760	74.289	15.928	-1.063	0.000	-1.063
BLOCK # 1	ELAPSED TIME IS .171875 SECONDS; FISSION POWER=						.9078476		
BLOCK # 2	MAXD OF PREVIOUS BLOCK=						3.677941E-03		
1.200	85.681	5.532	32.611	9.792	152.445	54.913	-3.265	0.000	-3.265
2.000	70.967	5.041	50.539	22.614	166.765	94.959	-5.239	0.000	-5.239
BLOCK # 2	ELAPSED TIME IS .390625 SECONDS; FISSION POWER=						.6592568		
BLOCK # 3	MAXD OF PREVIOUS BLOCK=						1.997461E-02		
2.400	57.746	4.489	58.435	34.048	179.526	122.924	-6.366	0.000	-6.366
3.200	46.525	3.943	62.069	42.555	189.788	143.623	-7.075	0.000	-7.075

Fig. 6b Rest of input of LOH sample problem; beginning of Output file LOH.OUT

```

BLOCK # 3   ELAPSED TIME IS .6015625 SECONDS; FISSION POWER= .4258125
BLOCK # 4   MAXD OF PREVIOUS BLOCK= 2.209786E-02   THUS NEW DT= 2
3.400 41.670 3.686 62.951 45.824 193.822 151.912 -7.314 0.000 -7.314
4.000 37.336 3.443 63.518 48.536 197.212 159.065 -7.488 0.000 -7.488
BLOCK # 4   ELAPSED TIME IS .7695313 SECONDS; FISSION POWER= .3389246
BLOCK # 5   MAXD OF PREVIOUS BLOCK= 1.391402E-02   THUS NEW DT= 2
4.200 33.465 3.217 63.781 50.781 200.024 165.221 -7.601 0.000 -7.601
4.400 30.020 3.007 63.824 52.625 202.355 170.507 -7.664 0.000 -7.664
BLOCK # 5   ELAPSED TIME IS .9921875 SECONDS; FISSION POWER= .2701362
BLOCK # 6   MAXD OF PREVIOUS BLOCK= 1.103118E-02   THUS NEW DT= 2
5.000 26.965 2.814 63.701 54.127 204.273 175.037 -7.683 0.000 -7.683
5.200 24.260 2.638 63.455 55.336 205.836 178.910 -7.662 0.000 -7.662
BLOCK # 6   ELAPSED TIME IS 1.148438 SECONDS; FISSION POWER= .2162274
BLOCK # 7   MAXD OF PREVIOUS BLOCK= 1.085608E-02   THUS NEW DT= 2
5.400 21.871 2.477 63.118 56.296 207.098 182.213 -7.604 0.000 -7.604
6.000 19.761 2.332 62.714 57.045 208.103 185.023 -7.513 0.000 -7.513
BLOCK # 7   ELAPSED TIME IS 1.371094 SECONDS; FISSION POWER= .1742919
BLOCK # 8   MAXD OF PREVIOUS BLOCK= 1.051998E-02   THUS NEW DT= 2
6.200 17.902 2.201 62.265 57.614 208.890 187.407 -7.393 0.000 -7.393
6.400 16.262 2.083 61.783 58.030 209.491 189.423 -7.245 0.000 -7.245
BLOCK # 8   ELAPSED TIME IS 1.589844 SECONDS; FISSION POWER= .1417908
BLOCK # 9   MAXD OF PREVIOUS BLOCK= .0100544   THUS NEW DT= 2
7.000 14.818 1.977 61.282 58.317 209.934 191.123 -7.074 0.000 -7.074
7.200 13.545 1.883 60.769 58.494 210.243 192.550 -6.881 0.000 -6.881
BLOCK # 9   ELAPSED TIME IS 1.761719 SECONDS; FISSION POWER= .1166291
BLOCK # 10  MAXD OF PREVIOUS BLOCK= 9.484921E-03   THUS NEW DT= 4
8.000 11.428 1.722 59.727 58.582 210.538 194.734 -6.456 0.000 -6.456
8.400 9.785 1.594 58.710 58.406 210.504 196.223 -5.960 0.000 -5.960
BLOCK # 10  ELAPSED TIME IS 1.980469 SECONDS; FISSION POWER= 8.191693E-02
BLOCK # 11  MAXD OF PREVIOUS BLOCK= 1.791773E-02   THUS NEW DT= 4
9.200 8.506 1.492 57.738 58.049 210.243 197.201 -5.425 0.000 -5.425
10.000 7.509 1.411 56.823 57.571 209.826 197.807 -4.867 0.000 -4.867
BLOCK # 11  ELAPSED TIME IS 2.199219 SECONDS; FISSION POWER= 6.097584E-02
BLOCK # 12  MAXD OF PREVIOUS BLOCK= 1.480321E-02   THUS NEW DT= 4
10.400 6.731 1.347 55.973 57.019 209.309 198.145 -4.299 0.000 -4.299
11.200 6.124 1.297 55.196 56.429 208.734 198.293 -3.734 0.000 -3.734
BLOCK # 12  ELAPSED TIME IS 2.421875 SECONDS; FISSION POWER= 4.827814E-02
BLOCK # 13  MAXD OF PREVIOUS BLOCK= 1.169465E-02   THUS NEW DT= 4
12.000 5.654 1.257 54.495 55.827 208.132 198.310 -3.179 0.000 -3.179
12.400 5.293 1.225 53.874 55.236 207.528 198.240 -2.644 0.000 -2.644
BLOCK # 13  ELAPSED TIME IS 2.640625 SECONDS; FISSION POWER= 4.068434E-02
BLOCK # 14  MAXD OF PREVIOUS BLOCK= 8.666269E-03   THUS NEW DT= 8
14.000 4.811 1.181 52.862 54.140 206.384 197.968 -1.686 0.000 -1.686
15.200 4.579 1.154 52.204 53.245 205.413 197.666 -0.832 0.000 -0.832
BLOCK # 14  ELAPSED TIME IS 2.859375 SECONDS; FISSION POWER= 3.425111E-02
BLOCK # 15  MAXD OF PREVIOUS BLOCK= .0121664   THUS NEW DT= 8
16.400 4.527 1.140 51.913 52.620 204.695 197.458 -0.144 0.000 -0.144
18.000 4.609 1.136 52.000 52.309 204.280 197.423 0.366 0.000 0.366
BLOCK # 15  ELAPSED TIME IS 3.082031 SECONDS; FISSION POWER= 3.473832E-02
BLOCK # 16  MAXD OF PREVIOUS BLOCK= 2.860136E-03   THUS NEW DT= 16
20.400 5.009 1.143 53.239 52.692 204.449 198.062 0.826 0.000 0.826
23.200 5.508 1.160 55.707 54.378 205.944 199.771 0.725 0.000 0.725
BLOCK # 16  ELAPSED TIME IS 3.300781 SECONDS; FISSION POWER= 4.348476E-02
BLOCK # 17  MAXD OF PREVIOUS BLOCK= 1.010388E-02   THUS NEW DT= 16
26.000 5.796 1.172 58.811 56.995 208.444 202.434 0.270 0.000 0.270

```

Fig. 6c Continuation of LOH.OUT

28.400	5.721	1.168	61.918	59.975	211.395	205.653	-0.266	0.000	-0.266
BLOCK # 17	ELAPSED TIME IS 3.460938 SECONDS; FISSION POWER= .045527								
BLOCK # 18	MAXD OF PREVIOUS BLOCK= 7.667931E-03 THUS NEW DT= 32								
34.000	4.774	1.118	66.804	65.277	216.787	211.971	-1.018	0.000	-1.018
39.200	3.705	1.054	69.934	68.919	220.530	216.731	-1.208	0.000	-1.208
BLOCK # 18	ELAPSED TIME IS 3.679688 SECONDS; FISSION POWER= 2.651203E-02								
BLOCK # 19	MAXD OF PREVIOUS BLOCK= 2.612588E-02 THUS NEW DT= 16								
42.000	3.276	1.026	71.068	70.268	221.914	218.549	-1.147	0.000	-1.147
44.400	2.930	1.002	72.074	71.369	223.031	220.057	-1.108	0.000	-1.108
BLOCK # 19	ELAPSED TIME IS 3.898438 SECONDS; FISSION POWER= 1.928093E-02								
BLOCK # 20	MAXD OF PREVIOUS BLOCK= 1.746957E-02 THUS NEW DT= 16								
47.200	2.647	0.982	72.939	72.323	223.998	221.352	-1.045	0.000	-1.045
50.000	2.415	0.964	73.724	73.172	224.854	222.491	-0.983	0.000	-0.983
BLOCK # 20	ELAPSED TIME IS 4.121094 SECONDS; FISSION POWER= .0145109								
BLOCK # 21	MAXD OF PREVIOUS BLOCK= 1.064985E-02 THUS NEW DT= 16								
52.400	2.222	0.949	74.451	73.945	225.631	223.512	-0.930	0.000	-0.930
55.200	2.060	0.935	75.134	74.663	226.351	224.442	-0.889	0.000	-0.889
BLOCK # 21	ELAPSED TIME IS 4.339844 SECONDS; FISSION POWER= 1.124835E-02								
BLOCK # 22	MAXD OF PREVIOUS BLOCK= 8.720554E-03 THUS NEW DT= 32								
60.400	1.793	0.911	76.382	75.966	227.657	226.096	-0.858	0.000	-0.858
66.000	1.588	0.890	77.505	77.132	228.825	227.532	-0.848	0.000	-0.848
BLOCK # 22	ELAPSED TIME IS 4.558594 SECONDS; FISSION POWER= 6.977154E-03								
BLOCK # 23	MAXD OF PREVIOUS BLOCK= 1.495127E-02 THUS NEW DT= 32								
71.200	1.422	0.872	78.516	78.181	229.875	228.795	-0.868	0.000	-0.868
76.400	1.285	0.855	79.421	79.121	230.818	229.908	-0.907	0.000	-0.907
BLOCK # 23	ELAPSED TIME IS 4.78125 SECONDS; FISSION POWER= 4.300183E-03								
BLOCK # 24	MAXD OF PREVIOUS BLOCK= .011556 THUS NEW DT= 32								
82.000	1.172	0.840	80.230	79.962	231.661	230.890	-0.959	0.000	-0.959
87.200	1.078	0.826	80.955	80.715	232.416	231.757	-1.018	0.000	-1.018
BLOCK # 24	ELAPSED TIME IS 5 SECONDS; FISSION POWER= 2.522492E-03								
BLOCK # 25	MAXD OF PREVIOUS BLOCK= .0096791 THUS NEW DT= 64								
98.000	0.939	0.801	82.204	82.007	233.711	233.219	-1.162	0.000	-1.162
108.400	0.849	0.779	83.263	83.094	234.799	234.415	-1.310	0.000	-1.310
BLOCK # 25	ELAPSED TIME IS 5.21875 SECONDS; FISSION POWER= 6.967108E-04								
BLOCK # 26	MAXD OF PREVIOUS BLOCK= 1.578036E-02 THUS NEW DT= 64								
119.200	0.793	0.760	84.206	84.054	235.758	235.444	-1.478	0.000	-1.478
130.000	0.757	0.743	85.075	84.934	236.638	236.368	-1.660	0.000	-1.660
BLOCK # 26	ELAPSED TIME IS 5.441406 SECONDS; FISSION POWER= 1.380773E-04								
BLOCK # 27	MAXD OF PREVIOUS BLOCK= 8.175429E-03 THUS NEW DT= 128								
151.200	0.714	0.712	86.668	86.542	238.244	238.025	-2.049	0.000	-2.049
172.400	0.684	0.684	88.082	87.971	239.672	239.484	-2.419	0.000	-2.419
BLOCK # 27	ELAPSED TIME IS 5.660156 SECONDS; FISSION POWER= 1.882052E-06								
BLOCK # 28	MAXD OF PREVIOUS BLOCK= 7.47313E-03 THUS NEW DT= 256								
215.200	0.636	0.635	90.424	90.339	242.040	241.898	-3.056	0.000	-3.056
258.000	0.595	0.595	92.152	92.091	243.792	243.668	-3.521	0.000	-3.521
BLOCK # 28	ELAPSED TIME IS 5.878906 SECONDS; FISSION POWER= 9.463633E-08								
BLOCK # 29	MAXD OF PREVIOUS BLOCK= .0078422 THUS NEW DT= 256								
300.400	0.562	0.562	93.374	93.332	245.035	244.962	-3.846	0.000	-3.846
343.200	0.534	0.534	94.178	94.152	245.856	245.808	-4.053	0.000	-4.053
BLOCK # 29	ELAPSED TIME IS 6.101563 SECONDS; FISSION POWER= 8.132788E-08								
BLOCK # 30	MAXD OF PREVIOUS BLOCK= 6.13603E-03 THUS NEW DT= 256								
386.000	0.510	0.510	94.636	94.623	246.328	246.302	-4.164	0.000	-4.164
428.400	0.491	0.491	94.808	94.806	246.513	246.505	-4.195	0.000	-4.195
BLOCK # 30	ELAPSED TIME IS 6.320313 SECONDS; FISSION POWER= 7.823103E-08								
BLOCK # 31	MAXD OF PREVIOUS BLOCK= 4.767735E-03 THUS NEW DT= 256								

Fig. 6d Continuation of LOH.OUT

471.200	0.474	0.474	94.744	94.751	246.459	246.466	-4.159	0.000	-4.159
514.000	0.460	0.460	94.484	94.498	246.208	246.227	-4.069	0.000	-4.069
BLOCK #	31	ELAPSED TIME IS 6.539063 SECONDS; FISSION POWER= 8.040029E-08							
BLOCK #	32	MAXD OF PREVIOUS BLOCK= 3.655872E-03 THUS NEW DT= 256							
556.400	0.448	0.448	94.062	94.082	245.795	245.823	-3.734	0.000	-3.934
599.200	0.438	0.438	93.506	93.531	245.245	245.282	-3.761	0.000	-3.761
BLOCK #	32	ELAPSED TIME IS 6.761719 SECONDS; FISSION POWER= 8.674169E-08							
BLOCK #	33	MAXD OF PREVIOUS BLOCK= 2.79072E-03 THUS NEW DT= 256							
642.000	0.429	0.429	92.838	92.867	244.584	244.628	-3.557	0.000	-3.557
684.400	0.422	0.422	92.078	92.111	243.830	243.880	-3.328	0.000	-3.328
BLOCK #	33	ELAPSED TIME IS 6.96875 SECONDS; FISSION POWER= 9.769897E-08							
BLOCK #	34	MAXD OF PREVIOUS BLOCK= 2.138701E-03 THUS NEW DT= 256							
727.200	0.415	0.415	91.241	91.277	242.999	243.053	-3.076	0.000	-3.076
770.000	0.409	0.409	90.341	90.379	242.104	242.162	-2.807	0.000	-2.807
BLOCK #	34	ELAPSED TIME IS 7.191406 SECONDS; FISSION POWER= 1.151659E-07							
BLOCK #	35	MAXD OF PREVIOUS BLOCK= 1.659436E-03 THUS NEW DT= 256							
812.400	0.404	0.404	89.388	89.428	241.155	241.217	-2.524	0.000	-2.524
855.200	0.400	0.400	88.391	88.433	240.163	240.227	-2.227	0.000	-2.227
BLOCK #	35	ELAPSED TIME IS 7.410156 SECONDS; FISSION POWER= 1.436756E-07							
BLOCK #	36	MAXD OF PREVIOUS BLOCK= 1.312463E-03 THUS NEW DT= 256							
898.000	0.396	0.396	87.358	87.401	239.133	239.200	-1.921	0.000	-1.921
940.400	0.392	0.392	86.295	86.339	238.074	238.142	-1.607	0.000	-1.607
BLOCK #	36	ELAPSED TIME IS 7.628906 SECONDS; FISSION POWER= 1.946555E-07							
BLOCK #	37	MAXD OF PREVIOUS BLOCK= 1.063798E-03 THUS NEW DT= 256							
983.200	0.389	0.389	85.207	85.252	236.990	237.060	-1.285	0.000	-1.285
1026.000	0.386	0.386	84.099	84.145	235.884	235.956	-0.958	0.000	-0.958
BLOCK #	37	ELAPSED TIME IS 7.851563 SECONDS; FISSION POWER= 3.040175E-07							
BLOCK #	38	MAXD OF PREVIOUS BLOCK= 8.861225E-04 THUS NEW DT= 256							
1068.400	0.383	0.383	82.973	83.020	234.762	234.835	-0.626	0.000	-0.626
1111.200	0.380	0.380	81.834	81.881	233.627	233.700	-0.290	0.000	-0.290
BLOCK #	38	ELAPSED TIME IS 8.070313 SECONDS; FISSION POWER= 6.421604E-07							
BLOCK #	39	MAXD OF PREVIOUS BLOCK= 7.584105E-04 THUS NEW DT= 256							
1154.000	0.378	0.378	80.684	80.732	232.480	232.553	0.049	0.000	0.049
1196.400	0.376	0.375	79.526	79.574	231.325	231.399	0.389	0.000	0.389
BLOCK #	39	ELAPSED TIME IS 8.289063 SECONDS; FISSION POWER= 3.023907E-06							
BLOCK #	40	MAXD OF PREVIOUS BLOCK= 6.608534E-04 THUS NEW DT= 256							
1239.200	0.374	0.373	78.369	78.416	230.169	230.243	0.730	0.000	0.730
1282.000	0.382	0.372	77.263	77.305	229.056	229.127	1.051	0.000	1.051
BLOCK #	40	ELAPSED TIME IS 8.511719 SECONDS; FISSION POWER= 1.056717E-04							
BLOCK #	41	MAXD OF PREVIOUS BLOCK= 5.728684E-03 THUS NEW DT= 256							
1324.400	0.526	0.376	76.954	76.913	228.641	228.626	1.090	0.000	1.090
1367.200	0.760	0.387	81.314	81.121	232.851	232.554	-0.493	0.000	-0.493
BLOCK #	41	ELAPSED TIME IS 8.679688 SECONDS; FISSION POWER= 3.724686E-03							
BLOCK #	42	MAXD OF PREVIOUS BLOCK= 8.220776E-02 THUS NEW DT= 128							
1388.400	0.527	0.375	82.324	82.333	234.102	233.995	-0.689	0.000	-0.689
1410.000	0.448	0.370	82.140	82.161	233.897	233.898	-0.505	0.000	-0.505
BLOCK #	42	ELAPSED TIME IS 8.898438 SECONDS; FISSION POWER= 7.821904E-04							
BLOCK #	43	MAXD OF PREVIOUS BLOCK= 5.652427E-02 THUS NEW DT= 64							
1420.400	0.429	0.368	81.944	81.974	233.716	233.737	-0.405	0.000	-0.405
1431.200	0.417	0.367	81.752	81.785	233.528	233.563	-0.326	0.000	-0.326
BLOCK #	43	ELAPSED TIME IS 9.121094 SECONDS; FISSION POWER= 4.918298E-04							
BLOCK #	44	MAXD OF PREVIOUS BLOCK= 6.827613E-03 THUS NEW DT= 128							
1452.400	0.403	0.366	81.326	81.362	233.107	233.157	-0.175	0.000	-0.175
1474.000	0.398	0.365	80.875	80.913	232.658	232.714	-0.031	0.000	-0.031
BLOCK #	44	ELAPSED TIME IS 9.339844 SECONDS; FISSION POWER= 3.338753E-04							

Fig. 6e Continuation of LOH.OUT

BLOCK #	45	MAXD OF PREVIOUS BLOCK= 4.565966E-03						THUS NEW DT= 256	
1516.400	0.406	0.363	80.025	80.057	231.802	231.854	0.221	0.000	0.221
1559.200	0.448	0.364	79.558	79.564	231.305	231.326	0.334	0.000	0.334
BLOCK #	45	ELAPSED TIME IS 9.558594 SECONDS; FISSION POWER= 8.404999E-04							
BLOCK #	46	MAXD OF PREVIOUS BLOCK= 1.422937E-02						THUS NEW DT= 256	
1602.000	0.520	0.366	80.006	79.970	231.704	231.662	0.144	0.000	0.144
1644.400	0.512	0.364	80.888	80.862	232.596	232.549	-0.144	0.000	-0.144
BLOCK #	46	ELAPSED TIME IS 9.78125 SECONDS; FISSION POWER= 1.475635E-03							
BLOCK #	47	MAXD OF PREVIOUS BLOCK= 1.650468E-02						THUS NEW DT= 256	
1687.200	0.461	0.360	81.061	81.066	232.804	232.802	-0.154	0.000	-0.154
1730.000	0.438	0.357	80.765	80.780	232.522	232.542	-0.036	0.000	-0.036
BLOCK #	47	ELAPSED TIME IS 10 SECONDS; FISSION POWER= 8.080768E-04							
BLOCK #	48	MAXD OF PREVIOUS BLOCK= 1.145742E-02						THUS NEW DT= 256	
1772.400	0.441	0.356	80.415	80.427	232.168	232.188	0.073	0.000	0.073
1815.200	0.462	0.356	80.282	80.281	232.020	232.025	0.099	0.000	0.099
BLOCK #	48	ELAPSED TIME IS 10.21094 SECONDS; FISSION POWER= 1.061287E-03							
BLOCK #	49	MAXD OF PREVIOUS BLOCK= 5.135996E-03						THUS NEW DT= 256	
1858.000	0.480	0.355	80.445	80.435	232.172	232.159	0.032	0.000	0.032
1900.400	0.476	0.354	80.667	80.660	232.398	232.386	-0.038	0.000	-0.038
BLOCK #	49	ELAPSED TIME IS 10.42969 SECONDS; FISSION POWER= 1.221991E-03							
BLOCK #	50	MAXD OF PREVIOUS BLOCK= 5.074411E-03						THUS NEW DT= 256	
1943.200	0.462	0.352	80.710	80.711	232.450	232.450	-0.040	0.000	-0.040
1986.000	0.455	0.350	80.610	80.615	232.355	232.361	-0.002	0.000	-0.002
BLOCK #	50	ELAPSED TIME IS 10.64844 SECONDS; FISSION POWER= 1.05202E-03							
BLOCK #	51	MAXD OF PREVIOUS BLOCK= 3.112812E-03						THUS NEW DT= 256	
2028.400	0.458	0.349	80.508	80.511	232.172	232.256	0.029	0.000	0.029
2071.200	0.465	0.348	80.497	80.496	232.234	232.234	0.027	0.000	0.027
BLOCK #	51	ELAPSED TIME IS 10.87109 SECONDS; FISSION POWER= 1.172573E-03							
BLOCK #	52	MAXD OF PREVIOUS BLOCK= 1.610634E-03						THUS NEW DT= 256	
2114.000	0.468	0.347	80.558	80.556	232.294	232.290	0.004	0.000	0.004
2156.400	0.466	0.345	80.607	80.606	232.345	232.342	-0.010	0.000	-0.010
BLOCK #	52	ELAPSED TIME IS 11.03906 SECONDS; FISSION POWER= 1.203718E-03							
BLOCK #	53	MAXD OF PREVIOUS BLOCK= 1.290653E-03						THUS NEW DT= 256	
2199.200	0.462	0.344	80.602	80.603	232.342	232.343	-0.005	0.000	-0.005
2242.000	0.461	0.343	80.568	80.569	232.309	232.311	0.007	0.000	0.007
BLOCK #	53	ELAPSED TIME IS 11.30859 SECONDS; FISSION POWER= 1.185523E-03							
BLOCK #	54	MAXD OF PREVIOUS BLOCK= 8.928953E-04						THUS NEW DT= 256	
2284.400	0.463	0.341	80.550	80.550	232.289	232.290	0.012	0.000	0.012
2327.200	0.465	0.340	80.559	80.558	232.297	232.296	0.007	0.000	0.007
BLOCK #	54	ELAPSED TIME IS 11.53125 SECONDS; FISSION POWER= 1.242148E-03							
BLOCK #	55	MAXD OF PREVIOUS BLOCK= 4.71074E-04						THUS NEW DT= 256	
2370.000	0.464	0.339	80.577	80.576	232.315	232.314	0.001	0.000	0.001
2412.400	0.463	0.338	80.582	80.582	232.321	232.321	0.000	0.000	0.000
BLOCK #	55	ELAPSED TIME IS 11.69922 SECONDS; FISSION POWER= 1.254991E-03							
BLOCK #	56	MAXD OF PREVIOUS BLOCK= 2.507307E-04						THUS NEW DT= 256	
2455.200	0.463	0.337	80.575	80.575	232.314	232.315	0.003	0.000	0.003
2498.000	0.463	0.336	80.568	80.568	232.307	232.307	0.005	0.000	0.005
BLOCK #	56	ELAPSED TIME IS 11.96875 SECONDS; FISSION POWER= 1.27444E-03							
BLOCK #	57	MAXD OF PREVIOUS BLOCK= 2.208149E-04						THUS NEW DT= 256	
2540.400	0.464	0.335	80.568	80.568	232.307	232.307	0.005	0.000	0.005
2583.200	0.464	0.333	80.573	80.573	232.311	232.311	0.003	0.000	0.003
BLOCK #	57	ELAPSED TIME IS 12.19141 SECONDS; FISSION POWER= 1.303442E-03							
BLOCK #	58	MAXD OF PREVIOUS BLOCK= 1.259594E-04						THUS NEW DT= 256	
2626.000	0.464	0.332	80.576	80.576	232.315	232.315	0.002	0.000	0.002
2668.400	0.463	0.331	80.575	80.575	232.314	232.314	0.003	0.000	0.003

Fig. 6f Continuation of LOH.OUT

```

BLOCK # 58 ELAPSED TIME IS 12.35938 SECONDS; FISSION POWER= 1.320675E-03
BLOCK # 59 MAXD OF PREVIOUS BLOCK= 6.842049E-05 THUS NEW DT= 256
2711.200 0.463 0.330 80.573 80.573 232.312 232.312 0.004 0.000 0.004
2754.000 0.463 0.329 80.572 80.572 232.311 232.311 0.004 0.000 0.004
BLOCK # 59 ELAPSED TIME IS 12.62891 SECONDS; FISSION POWER= .0013436
BLOCK # 60 MAXD OF PREVIOUS BLOCK= 3.577757E-05 THUS NEW DT= 256
2796.400 0.464 0.328 80.574 80.574 232.312 232.312 0.003 0.000 0.003
2839.200 0.463 0.327 80.575 80.575 232.314 232.314 0.003 0.000 0.003
BLOCK # 60 ELAPSED TIME IS 12.85156 SECONDS; FISSION POWER= 1.364684E-03
BLOCK # 61 MAXD OF PREVIOUS BLOCK= 2.823372E-05 THUS NEW DT= 256
2882.000 0.463 0.326 80.575 80.575 232.314 232.314 0.003 0.000 0.003
2924.400 0.463 0.325 80.574 80.574 232.313 232.313 0.003 0.000 0.003
BLOCK # 61 ELAPSED TIME IS 13.07031 SECONDS; FISSION POWER= 1.384302E-03
BLOCK # 62 MAXD OF PREVIOUS BLOCK= 1.979405E-05 THUS NEW DT= 256
2967.200 0.463 0.324 80.574 80.574 232.313 232.313 0.003 0.000 0.003
3010.000 0.463 0.323 80.575 80.575 232.314 232.314 0.003 0.000 0.003
BLOCK # 62 ELAPSED TIME IS 13.28906 SECONDS; FISSION POWER= 1.404972E-03
BLOCK # 63 MAXD OF PREVIOUS BLOCK= 1.125417E-05 THUS NEW DT= 256
3052.400 0.463 0.322 80.575 80.575 232.314 232.314 0.003 0.000 0.003
3095.200 0.463 0.321 80.575 80.575 232.314 232.314 0.003 0.000 0.003
BLOCK # 63 ELAPSED TIME IS 13.51172 SECONDS; FISSION POWER= 1.424222E-03
BLOCK # 64 MAXD OF PREVIOUS BLOCK= 6.631777E-06 THUS NEW DT= 256
3138.000 0.463 0.320 80.575 80.575 232.314 232.314 0.003 0.000 0.003
3180.400 0.463 0.319 80.575 80.575 232.314 232.314 0.003 0.000 0.003
BLOCK # 64 ELAPSED TIME IS 13.73047 SECONDS; FISSION POWER= 1.443455E-03
BLOCK # 65 MAXD OF PREVIOUS BLOCK= 3.315985E-06 THUS NEW DT= 256
3223.200 0.463 0.318 80.576 80.576 232.314 232.314 0.003 0.000 0.003
3266.000 0.463 0.317 80.576 80.576 232.315 232.315 0.003 0.000 0.003
BLOCK # 65 ELAPSED TIME IS 13.94922 SECONDS; FISSION POWER= 1.462349E-03
BLOCK # 66 MAXD OF PREVIOUS BLOCK= 2.411585E-06 THUS NEW DT= 256
3308.400 0.463 0.316 80.576 80.576 232.315 232.315 0.003 0.000 0.003
3351.200 0.463 0.315 80.576 80.576 232.315 232.315 0.003 0.000 0.003
BLOCK # 66 ELAPSED TIME IS 14.17188 SECONDS; FISSION POWER= 1.480844E-03
BLOCK # 67 MAXD OF PREVIOUS BLOCK= 1.708191E-06 THUS NEW DT= 256
3394.000 0.463 0.314 80.576 80.576 232.315 232.315 0.002 0.000 0.002
3436.400 0.463 0.314 80.576 80.576 232.315 232.315 0.002 0.000 0.002
BLOCK # 67 ELAPSED TIME IS 14.39063 SECONDS; FISSION POWER= 1.49892E-03
BLOCK # 68 MAXD OF PREVIOUS BLOCK= 1.808689E-06 THUS NEW DT= 256
3479.200 0.463 0.313 80.576 80.576 232.315 232.315 0.002 0.000 0.002
3522.000 0.463 0.312 80.577 80.577 232.315 232.315 0.002 0.000 0.002
BLOCK # 68 ELAPSED TIME IS 14.60938 SECONDS; FISSION POWER= 1.516757E-03
BLOCK # 69 MAXD OF PREVIOUS BLOCK= 1.708195E-06 THUS NEW DT= 256
3564.400 0.463 0.311 80.577 80.577 232.316 232.316 0.002 0.000 0.002
3607.200 0.463 0.310 80.577 80.577 232.316 232.316 0.002 0.000 0.002
BLOCK # 69 ELAPSED TIME IS 14.83203 SECONDS; FISSION POWER= 1.534349E-03
BLOCK # 70 MAXD OF PREVIOUS BLOCK= 2.612502E-06 THUS NEW DT= 256
3650.000 0.463 0.309 80.577 80.577 232.316 232.316 0.002 0.000 0.002
3692.400 0.463 0.308 80.577 80.577 232.316 232.316 0.002 0.000 0.002
BLOCK # 70 ELAPSED TIME IS 14.99219 SECONDS; FISSION POWER= 1.551404E-03

```

TOTAL ELAPSED TIME FOR THIS RUN IS .2498698 MINUTES

Fig. 6g Continuation of LOH.OUT

----- POWER & REACTIVITY OUTPUT -----								
TIME(S)	100*POW	100*DC.HT	RHO(CT)	DOPPLER	AX.EXP	COOLANT	RAD.EXP	CR-ROD
0.000	100.000	5.870	0.000	0.000	0.000	0.000	0.000	0.000
20.000	99.265	5.861	-0.321	-0.271	-0.395	0.631	-0.283	-0.004
40.000	96.594	5.809	-1.063	-0.903	-1.318	2.260	-1.059	-0.051
BLOCK 2								
80.000	85.681	5.532	-3.265	-2.689	-3.925	7.505	-3.743	-0.481
120.000	70.967	5.041	-5.239	-3.917	-5.718	12.476	-6.766	-1.423
BLOCK 3								
160.000	57.746	4.489	-6.366	-4.214	-6.152	15.552	-9.187	-2.460
200.000	46.525	3.943	-7.075	-4.165	-6.080	17.638	-11.296	-3.234
BLOCK 4								
220.000	41.670	3.686	-7.314	-4.077	-5.951	18.425	-12.236	-3.498
240.000	37.336	3.443	-7.488	-3.976	-5.804	19.086	-13.126	-3.685
BLOCK 5								
260.000	33.465	3.217	-7.601	-3.862	-5.637	19.637	-13.944	-3.804
280.000	30.020	3.007	-7.664	-3.742	-5.462	20.094	-14.693	-3.865
BLOCK 6								
300.000	26.965	2.814	-7.683	-3.619	-5.283	20.472	-15.375	-3.876
320.000	24.260	2.638	-7.662	-3.497	-5.105	20.783	-15.992	-3.845
BLOCK 7								
340.000	21.871	2.477	-7.604	-3.378	-4.931	21.037	-16.545	-3.779
360.000	19.761	2.332	-7.513	-3.262	-4.762	21.243	-17.039	-3.682
BLOCK 8								
380.000	17.902	2.201	-7.393	-3.151	-4.600	21.409	-17.477	-3.561
400.000	16.262	2.083	-7.245	-3.045	-4.444	21.541	-17.862	-3.420
BLOCK 9								
420.000	14.818	1.977	-7.074	-2.943	-4.296	21.644	-18.199	-3.262
440.000	13.545	1.883	-6.881	-2.847	-4.156	21.722	-18.492	-3.090
BLOCK 10								
480.000	11.428	1.722	-6.456	-2.668	-3.895	21.820	-18.958	-2.717
520.000	9.785	1.594	-5.960	-2.509	-3.663	21.861	-19.292	-2.316
BLOCK 11								
560.000	8.506	1.492	-5.425	-2.368	-3.456	21.861	-19.520	-1.900
600.000	7.509	1.411	-4.867	-2.242	-3.273	21.834	-19.666	-1.479
BLOCK 12								
640.000	6.731	1.347	-4.299	-2.130	-3.110	21.791	-19.748	-1.060
680.000	6.124	1.297	-3.734	-2.032	-2.967	21.737	-19.784	-0.646
BLOCK 13								
720.000	5.654	1.257	-3.179	-1.947	-2.842	21.678	-19.787	-0.242
760.000	5.293	1.225	-2.644	-1.873	-2.733	21.619	-19.768	0.150
BLOCK 14								
840.000	4.811	1.181	-1.686	-1.756	-2.563	21.509	-19.695	0.890
920.000	4.579	1.154	-0.832	-1.683	-2.457	21.426	-19.620	1.566
BLOCK 15								
1000.000	4.527	1.140	-0.144	-1.653	-2.412	21.384	-19.577	2.172
1080.000	4.609	1.136	0.366	-1.664	-2.429	21.388	-19.587	2.708
BLOCK 16								
1240.000	5.009	1.143	0.826	-1.800	-2.628	21.549	-19.796	3.576
1400.000	5.508	1.160	0.725	-2.060	-3.007	21.907	-20.264	4.202
BLOCK 17								
1560.000	5.796	1.172	0.270	-2.375	-3.467	22.402	-20.902	4.651
1720.000	5.721	1.168	-0.266	-2.677	-3.908	22.944	-21.595	5.003
BLOCK 18								
2040.000	4.774	1.118	-1.018	-3.122	-4.558	23.905	-22.829	5.653

Fig. 7a Beginning of Output file POWRO.LOH

2360.000	3.705	1.054	-1.208	-3.391	-4.950	24.582	-23.715	6.335
BLOCK 19								
2520.000	3.276	1.026	-1.147	-3.487	-5.090	24.835	-24.043	6.671
2680.000	2.930	1.002	-1.108	-3.573	-5.215	25.050	-24.334	6.996
BLOCK 20								
2840.000	2.647	0.982	-1.045	-3.648	-5.324	25.236	-24.579	7.300
3000.000	2.415	0.964	-0.983	-3.716	-5.425	25.400	-24.796	7.580
BLOCK 21								
3160.000	2.222	0.949	-0.930	-3.781	-5.519	25.550	-24.993	7.837
3320.000	2.060	0.935	-0.889	-3.842	-5.608	25.689	-25.175	8.070
BLOCK 22								
3640.000	1.793	0.911	-0.858	-3.955	-5.773	25.937	-25.503	8.471
3960.000	1.588	0.890	-0.848	-4.057	-5.923	26.157	-25.793	8.798
BLOCK 23								
4230.000	1.422	0.872	-0.868	-4.150	-6.059	26.352	-26.051	9.065
4600.000	1.285	0.855	-0.907	-4.234	-6.181	26.525	-26.282	9.285
BLOCK 24								
4920.000	1.172	0.840	-0.959	-4.310	-6.291	26.679	-26.487	9.467
5240.000	1.078	0.826	-1.018	-4.377	-6.390	26.815	-26.671	9.619
BLOCK 25								
5880.000	0.939	0.801	-1.162	-4.495	-6.561	27.048	-26.984	9.851
6520.000	0.849	0.779	-1.310	-4.596	-6.708	27.241	-27.246	10.012
BLOCK 26								
7160.000	0.793	0.760	-1.478	-4.686	-6.840	27.410	-27.477	10.125
7800.000	0.757	0.743	-1.660	-4.770	-6.963	27.564	-27.687	10.203
BLOCK 27								
9080.000	0.714	0.712	-2.049	-4.925	-7.189	27.842	-28.070	10.299
%10360.000	0.684	0.684	-2.419	-5.062	-7.390	28.089	-28.409	10.358
BLOCK 28								
%12920.000	0.636	0.635	-3.056	-5.290	-7.722	28.497	-28.970	10.437
%15480.000	0.595	0.595	-3.521	-5.458	-7.968	28.798	-29.386	10.498
BLOCK 29								
%18040.000	0.562	0.562	-3.846	-5.577	-8.141	29.012	-29.680	10.544
%20600.000	0.534	0.534	-4.053	-5.655	-8.255	29.154	-29.874	10.580
BLOCK 30								
%23160.000	0.510	0.510	-4.164	-5.699	-8.319	29.235	-29.986	10.608
%25720.000	0.491	0.491	-4.195	-5.715	-8.343	29.268	-30.030	10.627
BLOCK 31								
%28280.000	0.474	0.474	-4.159	-5.708	-8.333	29.259	-30.017	10.641
%30840.000	0.460	0.460	-4.069	-5.682	-8.295	29.216	-29.957	10.650
BLOCK 32								
%33400.000	0.448	0.448	-3.934	-5.640	-8.234	29.145	-29.859	10.654
%35960.000	0.438	0.438	-3.761	-5.585	-8.153	29.051	-29.729	10.655
BLOCK 33								
%38520.000	0.429	0.429	-3.557	-5.520	-8.057	28.938	-29.572	10.653
%41080.000	0.422	0.422	-3.328	-5.445	-7.948	28.808	-29.393	10.649
BLOCK 34								
%43640.000	0.415	0.415	-3.076	-5.363	-7.828	28.666	-29.196	10.643
%46200.000	0.409	0.409	-2.807	-5.274	-7.699	28.512	-28.983	10.636
BLOCK 35								
%48760.000	0.404	0.404	-2.524	-5.180	-7.562	28.349	-28.758	10.627
%51320.000	0.400	0.400	-2.227	-5.082	-7.419	28.179	-28.523	10.616
BLOCK 36								
%53880.000	0.396	0.396	-1.921	-4.981	-7.271	28.002	-28.278	10.605
%56440.000	0.392	0.392	-1.607	-4.876	-7.118	27.821	-28.027	10.593

Fig. 7b Continuation of POWRO.LOH

BLOCK 37								
%59000.000	0.389	0.389	-1.285	-4.770	-6.962	27.634	-27.770	10.581
%61560.000	0.386	0.386	-0.958	-4.661	-6.803	27.445	-27.508	10.568
BLOCK 38								
%64120.000	0.383	0.383	-0.626	-4.550	-6.642	27.252	-27.242	10.555
%66680.000	0.380	0.380	-0.290	-4.438	-6.479	27.057	-26.972	10.541
BLOCK 39								
%69240.000	0.378	0.378	0.049	-4.326	-6.314	26.860	-26.700	10.527
%71800.000	0.376	0.375	0.389	-4.212	-6.148	26.662	-26.426	10.512
BLOCK 40								
%74360.000	0.374	0.373	0.730	-4.098	-5.982	26.463	-26.152	10.497
%76920.000	0.382	0.372	1.051	-3.990	-5.824	26.273	-25.889	10.480
BLOCK 41								
%79480.000	0.526	0.376	1.090	-3.965	-5.788	26.203	-25.794	10.420
%82040.000	0.760	0.387	-0.493	-4.401	-6.424	26.914	-26.792	10.207
BLOCK 42								
%83320.000	0.527	0.375	-0.689	-4.492	-6.557	27.124	-27.065	10.319
%84600.000	0.448	0.370	-0.505	-4.471	-6.526	27.100	-27.036	10.436
BLOCK 43								
%85240.000	0.429	0.368	-0.405	-4.451	-6.497	27.070	-26.992	10.468
%85880.000	0.417	0.367	-0.326	-4.432	-6.469	27.038	-26.948	10.486
BLOCK 44								
%87160.000	0.403	0.366	-0.175	-4.389	-6.407	26.967	-26.849	10.504
%88440.000	0.398	0.365	-0.031	-4.345	-6.343	26.890	-26.742	10.509
BLOCK 45								
%91000.000	0.406	0.363	0.221	-4.262	-6.221	26.744	-26.540	10.499
%93560.000	0.448	0.364	0.334	-4.218	-6.157	26.658	-26.423	10.469
BLOCK 46								
%96120.000	0.520	0.366	0.144	-4.264	-6.225	26.726	-26.518	10.421
%98680.000	0.512	0.364	-0.144	-4.350	-6.350	26.877	-26.729	10.411
BLOCK 47								
%101240.000	0.461	0.360	-0.154	-4.365	-6.372	26.914	-26.778	10.451
%103800.000	0.438	0.357	-0.036	-4.336	-6.329	26.866	-26.711	10.474
BLOCK 48								
%106360.000	0.441	0.356	0.073	-4.301	-6.279	26.806	-26.627	10.473
%108920.000	0.462	0.356	0.099	-4.289	-6.261	26.780	-26.592	10.459
BLOCK 49								
%111480.000	0.480	0.355	0.032	-4.306	-6.285	26.806	-26.628	10.444
%114040.000	0.476	0.354	-0.038	-4.327	-6.317	26.844	-26.682	10.444
BLOCK 50								
%116600.000	0.462	0.352	-0.040	-4.331	-6.322	26.853	-26.694	10.454
%119160.000	0.455	0.350	-0.002	-4.321	-6.308	26.837	-26.671	10.461
BLOCK 51								
%121720.000	0.458	0.349	0.029	-4.311	-6.293	26.820	-26.647	10.460
%124280.000	0.465	0.348	0.027	-4.310	-6.292	26.817	-26.643	10.455
BLOCK 52								
%126840.000	0.468	0.347	0.004	-4.316	-6.301	26.827	-26.657	10.452
%129400.000	0.466	0.345	-0.010	-4.321	-6.308	26.835	-26.669	10.453
BLOCK 53								
%131960.000	0.462	0.344	-0.005	-4.320	-6.307	26.835	-26.668	10.456
%134520.000	0.461	0.343	0.007	-4.317	-6.302	26.829	-26.660	10.457
BLOCK 54								
%137080.000	0.463	0.341	0.012	-4.315	-6.299	26.826	-26.656	10.456
%139640.000	0.465	0.340	0.007	-4.316	-6.301	26.827	-26.658	10.455
BLOCK 55								

Fig. 7c Continuation of POWRO.LOH

%142200.000	0.464	0.339	0.001	-4.318	-6.303	26.830	-26.662	10.454
%144760.000	0.463	0.338	0.000	-4.319	-6.304	26.831	-26.664	10.455
BLOCK 56								
%147320.000	0.463	0.337	0.003	-4.318	-6.303	26.830	-26.662	10.456
%149880.000	0.463	0.336	0.005	-4.317	-6.302	26.829	-26.660	10.456
BLOCK 57								
%152440.000	0.464	0.335	0.005	-4.317	-6.302	26.829	-26.660	10.455
%155000.000	0.464	0.333	0.003	-4.318	-6.303	26.830	-26.661	10.455
BLOCK 58								
%157560.000	0.464	0.332	0.002	-4.318	-6.303	26.830	-26.662	10.455
%160120.000	0.463	0.331	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 59								
%162680.000	0.463	0.330	0.004	-4.318	-6.303	26.830	-26.661	10.455
%165240.000	0.463	0.329	0.004	-4.318	-6.303	26.830	-26.661	10.455
BLOCK 60								
%167800.000	0.464	0.328	0.003	-4.318	-6.303	26.830	-26.661	10.455
%170360.000	0.463	0.327	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 61								
%172920.000	0.463	0.326	0.003	-4.318	-6.303	26.830	-26.662	10.455
%175480.000	0.463	0.325	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 62								
%178040.000	0.463	0.324	0.003	-4.318	-6.303	26.830	-26.662	10.455
%180600.000	0.463	0.323	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 63								
%183160.000	0.463	0.322	0.003	-4.318	-6.303	26.830	-26.662	10.455
%185720.000	0.463	0.321	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 64								
%188280.000	0.463	0.320	0.003	-4.318	-6.303	26.830	-26.662	10.455
%190840.000	0.463	0.319	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 65								
%193400.000	0.463	0.318	0.003	-4.318	-6.303	26.830	-26.662	10.455
%195960.000	0.463	0.317	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 66								
%198520.000	0.463	0.316	0.003	-4.318	-6.303	26.830	-26.662	10.455
%201080.000	0.463	0.315	0.003	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 67								
%203640.000	0.463	0.314	0.002	-4.318	-6.303	26.830	-26.662	10.455
%206200.000	0.463	0.314	0.002	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 68								
%208760.000	0.463	0.313	0.002	-4.318	-6.303	26.830	-26.662	10.455
%211320.000	0.463	0.312	0.002	-4.318	-6.303	26.830	-26.662	10.455
BLOCK 69								
%213880.000	0.463	0.311	0.002	-4.318	-6.303	26.831	-26.662	10.455
%216440.000	0.463	0.310	0.002	-4.318	-6.303	26.831	-26.662	10.455
BLOCK 70								
%219000.000	0.463	0.309	0.002	-4.318	-6.303	26.831	-26.662	10.455
%221560.000	0.463	0.308	0.002	-4.318	-6.303	26.831	-26.662	10.455

Fig. 7d Continuation of POWRO.LOH

----- DELTA TEMPERATURE OUTPUT -----									
TIME(S)	DT-FUEL	DT-CLAD	DT-COOL	DT-STRUC	DT-CR	DTOUTLET	DTLHP	DTOHX	DTINLET
0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
20.000	2.761	3.487	3.677	3.591	0.048	3.014	0.266	37.074	4.340
40.000	9.205	12.353	13.175	13.028	0.572	10.422	1.760	74.289	15.928
BLOCK 2									
80.000	27.412	40.376	43.762	43.532	5.175	32.611	9.792	152.445	54.913
120.000	39.927	65.952	72.749	72.610	15.361	50.539	22.614	166.765	94.959
BLOCK 3									
160.000	42.958	80.797	90.680	90.588	27.206	58.435	34.048	179.526	122.924
200.000	42.461	90.340	102.846	102.782	37.227	62.069	42.555	189.788	143.623
BLOCK 4									
220.000	41.557	93.789	107.432	107.378	41.273	62.951	45.824	193.822	151.912
240.000	40.528	96.636	111.291	111.247	44.704	63.518	48.536	197.212	159.065
BLOCK 5									
260.000	39.367	98.941	114.501	114.464	47.582	63.781	50.781	200.024	165.221
280.000	38.142	100.800	117.166	117.135	49.975	63.824	52.625	202.355	170.507
BLOCK 6									
300.000	36.894	102.289	119.369	119.344	51.949	63.701	54.127	204.273	175.037
320.000	35.652	103.469	121.183	121.162	53.564	63.455	55.336	205.836	178.910
BLOCK 7									
340.000	34.435	104.393	122.665	122.649	54.871	63.118	56.296	207.098	182.213
360.000	33.255	105.103	123.869	123.855	55.915	62.714	57.045	208.103	185.023
BLOCK 8									
380.000	32.121	105.634	124.836	124.825	56.736	62.265	57.614	208.890	187.407
400.000	31.036	106.018	125.603	125.595	57.366	61.783	58.030	209.491	189.423
BLOCK 9									
420.000	30.003	106.279	126.202	126.196	57.834	61.282	58.317	209.934	191.123
440.000	29.022	106.439	126.659	126.654	58.165	60.769	58.494	210.243	192.550
BLOCK 10									
480.000	27.200	106.514	127.230	127.228	58.495	59.727	58.582	210.538	194.734
520.000	25.579	106.365	127.466	127.466	58.490	58.710	58.406	210.504	196.223
BLOCK 11									
560.000	24.135	106.069	127.469	127.470	58.250	57.738	58.049	210.243	197.201
600.000	22.853	105.681	127.315	127.316	57.851	56.823	57.571	209.826	197.807
BLOCK 12									
640.000	21.718	105.243	127.059	127.061	57.348	55.973	57.019	209.309	198.145
680.000	20.717	104.786	126.745	126.747	56.784	55.196	56.429	208.734	198.293
BLOCK 13									
720.000	19.843	104.334	126.403	126.405	56.192	54.495	55.827	208.132	198.310
760.000	19.089	103.904	126.057	126.059	55.596	53.874	55.236	207.528	198.240
BLOCK 14									
840.000	17.899	103.148	125.415	125.417	54.463	52.862	54.140	206.384	197.968
920.000	17.157	102.614	124.935	124.937	53.503	52.204	53.245	205.413	197.666
BLOCK 15									
1000.000	16.846	102.352	124.685	124.686	52.793	51.913	52.620	204.695	197.458
1080.000	16.963	102.397	124.711	124.711	52.384	52.000	52.309	204.280	197.423
BLOCK 16									
1240.000	18.349	103.428	125.650	125.648	52.561	53.239	52.692	204.449	198.062
1400.000	21.000	105.633	127.739	127.735	54.061	55.707	54.378	205.944	199.771
BLOCK 17									
1560.000	24.210	108.584	130.622	130.617	56.564	58.811	56.995	208.444	202.434
1720.000	27.290	111.730	133.786	133.781	59.518	61.918	59.975	211.395	205.653
BLOCK 18									
2040.000	31.828	117.112	139.388	139.384	64.926	66.804	65.277	216.787	211.971

Fig. 8a Beginning of Output file DTEMP.LOH

2360.000	34.565	120.807	143.333	143.330	68.689	69.934	68.919	220.530	216.731
BLOCK 19									
2520.000	35.541	122.179	144.808	144.807	70.081	71.068	70.268	221.914	218.549
2680.000	36.421	123.358	146.066	146.064	71.209	72.074	71.369	223.031	220.057
BLOCK 20									
2840.000	37.182	124.372	147.146	147.144	72.184	72.939	72.323	223.998	221.352
3000.000	37.882	125.280	148.107	148.106	73.047	73.724	73.172	224.854	222.491
BLOCK 21									
3160.000	38.538	126.109	148.981	148.980	73.831	74.451	73.945	225.631	223.512
3320.000	39.161	126.877	149.788	149.787	74.556	75.134	74.663	226.351	224.442
BLOCK 22									
3640.000	40.311	128.266	151.239	151.238	75.872	76.382	75.966	227.657	226.096
3960.000	41.359	129.497	152.519	152.518	77.047	77.505	77.132	228.825	227.532
BLOCK 23									
4280.000	42.308	130.595	153.655	153.655	78.105	78.516	78.181	229.875	228.795
4600.000	43.163	131.573	154.665	154.664	79.053	79.421	79.121	230.818	229.908
BLOCK 24									
4920.000	43.931	132.441	155.560	155.559	79.901	80.230	79.962	231.661	230.890
5240.000	44.621	133.216	156.356	156.355	80.660	80.955	80.715	232.416	231.757
BLOCK 25									
5880.000	45.819	134.539	157.712	157.711	81.962	82.204	82.007	233.711	233.219
6520.000	46.845	135.645	158.839	158.839	83.055	83.263	83.094	234.799	234.415
BLOCK 26									
7160.000	47.767	136.618	159.825	159.824	84.019	84.206	84.054	235.758	235.444
7800.000	48.624	137.506	160.722	160.721	84.902	85.075	84.934	236.638	236.368
BLOCK 27									
9080.000	50.200	139.121	162.347	162.346	86.513	86.668	86.542	238.244	238.025
%10360.000	51.603	140.551	163.783	163.783	87.945	88.082	87.971	239.672	239.4
BLOCK 28									
%12920.000	53.927	142.917	166.161	166.160	90.320	90.424	90.339	242.040	241.8
%15480.000	55.641	144.667	167.920	167.920	92.077	92.152	92.091	243.792	243.6
BLOCK 29									
%18040.000	56.851	145.907	169.168	169.168	93.323	93.374	93.332	245.035	244.9
%20600.000	57.645	146.726	169.993	169.993	94.146	94.178	94.152	245.856	245.8
BLOCK 30									
%23160.000	58.094	147.196	170.469	170.469	94.620	94.636	94.623	246.328	246.3
%25720.000	58.259	147.379	170.657	170.657	94.805	94.808	94.806	246.513	246.5
BLOCK 31									
%28280.000	58.188	147.323	170.605	170.605	94.752	94.744	94.751	246.459	246.4
%30840.000	57.923	147.071	170.356	170.356	94.501	94.484	94.498	246.208	246.2
BLOCK 32									
%33400.000	57.497	146.655	169.943	169.943	94.087	94.062	94.082	245.795	245.8
%35960.000	56.937	146.104	169.394	169.394	93.536	93.506	93.531	245.245	245.2
BLOCK 33									
%38520.000	56.266	145.441	168.733	168.733	92.874	92.838	92.867	244.584	244.6
%41080.000	55.503	144.685	167.979	167.979	92.118	92.078	92.111	243.830	243.8
BLOCK 34									
%43640.000	54.664	143.852	167.147	167.147	91.285	91.241	91.277	242.999	243.0
%46200.00	53.762	142.955	166.252	166.252	90.388	90.341	90.379	242.104	242.1
BLOCK 35									
%48760.000	52.807	142.005	165.303	165.303	89.438	89.388	89.428	241.155	241.2
%51320.000	51.808	141.010	164.309	164.309	88.443	88.391	88.433	240.163	240.2
BLOCK 36									
%53880.000	50.774	139.979	163.279	163.279	87.411	87.358	87.401	239.133	239.2
%56440.000	49.709	138.918	162.219	162.219	86.350	86.295	86.339	238.074	238.1

Fig. 8b Continuation of DTEMP.LOH

BLOCK 37										
%59000.000	48.620	137.832	161.133	161.133	85.263	85.207	85.252	236.990	237.0	
%61560.000	47.510	136.725	160.027	160.027	84.155	84.099	84.145	235.884	235.9	
BLOCK 38										
%64120.000	46.384	135.601	158.904	158.904	83.031	82.973	83.020	234.762	234.8	
%66680.000	45.244	134.463	157.767	157.767	81.892	81.834	81.881	233.627	233.7	
BLOCK 39										
%69240.000	44.093	133.315	156.619	156.619	80.743	80.684	80.732	232.480	232.5	
%71800.000	42.935	132.158	155.463	155.463	79.585	79.526	79.574	231.325	231.3	
BLOCK 40										
%74360.000	41.776	131.001	154.306	154.306	78.427	78.369	78.416	230.169	230.2	
%76920.000	40.673	129.892	153.195	153.195	77.315	77.263	77.305	229.059	229.1	
BLOCK 41										
%79480.000	40.417	129.517	152.790	152.790	76.904	76.954	76.913	228.641	228.6	
%82040.000	44.863	133.724	156.934	156.933	81.076	81.314	81.121	232.851	232.5	
BLOCK 42										
%83320.000	45.788	134.887	158.160	158.160	82.337	82.324	82.333	234.102	233.9	
%84600.000	45.574	134.732	158.019	158.019	82.166	82.140	82.161	233.897	233.8	
BLOCK 43										
%85240.000	45.372	134.548	157.841	157.841	81.981	81.944	81.974	233.716	233.7	
%85880.000	45.176	134.362	157.658	157.658	81.792	81.752	81.785	233.528	233.5	
BLOCK 44										
%87160.000	44.744	133.943	157.241	157.242	81.371	81.326	81.362	233.107	233.1	
%88440.000	44.292	133.495	156.794	156.795	80.921	80.875	80.913	232.658	232.7	
BLOCK 45										
%91000.000	43.445	132.642	155.940	155.940	80.064	80.025	80.057	231.802	231.8	
%93560.000	42.993	132.154	155.442	155.442	79.565	79.558	79.564	231.305	231.3	
BLOCK 46										
%96120.000	43.467	132.563	155.834	155.834	79.961	80.006	79.970	231.704	231.6	
%98680.000	44.346	133.446	156.719	156.718	80.856	80.888	80.862	232.596	232.5	
BLOCK 47										
%101240.000	44.500	133.647	156.931	156.931	81.067	81.061	81.066	232.804	232.	
%103800.000	44.196	133.364	156.654	156.654	80.784	80.765	80.780	232.522	232.	
BLOCK 48										
%106360.000	43.847	133.012	156.301	156.301	80.429	80.415	80.427	232.168	232.	
%108920.000	43.721	132.868	156.153	156.153	80.281	80.282	80.281	232.020	232.	
BLOCK 49										
%111480.000	43.891	133.022	156.302	156.302	80.432	80.445	80.435	232.172	232.	
%114040.000	44.111	133.245	156.526	156.526	80.658	80.667	80.660	232.398	232.	
BLOCK 50										
%116600.000	44.149	133.295	156.580	156.580	80.712	80.710	80.711	232.450	232.	
%119160.000	44.047	133.200	156.486	156.486	80.616	80.610	80.615	232.355	232.	
BLOCK 51										
%121720.000	43.947	133.097	156.382	156.382	80.512	80.508	80.511	232.251	232.	
%124280.000	43.938	133.082	156.365	156.365	80.495	80.497	80.496	232.234	232.	
BLOCK 52										
%126840.000	44.000	133.141	156.424	156.424	80.555	80.558	80.556	232.294	232.	
%129400.000	44.048	133.191	156.475	156.475	80.606	80.607	80.606	232.345	232.	
BLOCK 53										
%131960.000	44.041	133.188	156.472	156.472	80.603	80.602	80.603	232.342	232.	
%134520.000	44.008	133.155	156.439	156.439	80.570	80.568	80.569	232.309	232.	
BLOCK 54										
%137080.000	43.990	133.135	156.420	156.420	80.550	80.550	80.550	232.289	232.	
%139640.000	44.000	133.144	156.428	156.428	80.558	80.559	80.558	232.297	232.	
BLOCK 55										

Fig. 8c Continuation of DTEMP.LOH

%142200.000	44.018	133.162	156.445	156.445	80.576	80.577	80.576	232.315	232.
%144760.000	44.023	133.168	156.452	156.452	80.582	80.582	80.582	232.321	232.
BLOCK 56									
%147320.000	44.015	133.161	156.445	156.445	80.576	80.575	80.575	232.314	232.
%149880.000	44.008	133.153	156.438	156.438	80.568	80.568	80.568	232.307	232.
BLOCK 57									
%152440.000	44.008	133.153	156.437	156.437	80.568	80.568	80.568	232.307	232.
%155000.000	44.013	133.158	156.442	156.442	80.573	80.573	80.573	232.311	232.
BLOCK 58									
%157560.000	44.016	133.161	156.445	156.445	80.576	80.576	80.576	232.315	232.
%160120.000	44.015	133.160	156.444	156.444	80.575	80.575	80.575	232.314	232.
BLOCK 59									
%162680.000	44.013	133.158	156.442	156.442	80.573	80.573	80.573	232.312	232.
%165240.000	44.013	133.158	156.442	156.442	80.572	80.572	80.572	232.311	232.
BLOCK 60									
%167800.000	44.014	133.159	156.443	156.443	80.574	80.574	80.574	232.312	232.
%170360.000	44.015	133.160	156.444	156.444	80.575	80.575	80.575	232.314	232.
BLOCK 61									
%172920.000	44.015	133.160	156.444	156.444	80.575	80.575	80.575	232.314	232.
%175480.000	44.015	133.160	156.444	156.444	80.574	80.574	80.574	232.313	232.
BLOCK 62									
%178040.000	44.015	133.160	156.444	156.444	80.574	80.574	80.574	232.313	232.
%180600.000	44.015	133.160	156.444	156.444	80.575	80.575	80.575	232.314	232.
BLOCK 63									
%183160.000	44.016	133.160	156.445	156.445	80.575	80.575	80.575	232.314	232.
%185720.000	44.016	133.161	156.445	156.445	80.575	80.575	80.575	232.314	232.
BLOCK 64									
%188280.000	44.016	133.161	156.445	156.445	80.575	80.575	80.575	232.314	232.
%190840.000	44.016	133.161	156.445	156.445	80.575	80.575	80.575	232.314	232.
BLOCK 65									
%193400.000	44.016	133.161	156.445	156.445	80.576	80.576	80.576	232.314	232.
%195960.000	44.016	133.161	156.445	156.445	80.576	80.576	80.576	232.315	232.
BLOCK 66									
%198520.000	44.016	133.161	156.445	156.445	80.576	80.576	80.576	232.315	232.
%201080.000	44.016	133.161	156.446	156.446	80.576	80.576	80.576	232.315	232.
BLOCK 67									
%203640.000	44.017	133.162	156.446	156.446	80.576	80.576	80.576	232.315	232.
%206200.000	44.017	133.162	156.446	156.446	80.576	80.576	80.576	232.315	232.
BLOCK 68									
%208760.000	44.017	133.162	156.446	156.446	80.576	80.576	80.576	232.315	232.
%211320.000	44.017	133.162	156.446	156.446	80.577	80.577	80.577	232.315	232.
BLOCK 69									
%213880.000	44.017	133.162	156.446	156.446	80.577	80.577	80.577	232.316	232.
%216440.000	44.017	133.162	156.446	156.446	80.577	80.577	80.577	232.316	232.
BLOCK 70									
%219000.000	44.017	133.162	156.447	156.447	80.577	80.577	80.577	232.316	232.
%221560.000	44.018	133.163	156.447	156.447	80.577	80.577	80.577	232.316	232.

Fig. 8d Continuation of DTEMP.LOH

**The following 22 pages show the
Listing of the QuickBASIC
Version of LTC.**

[illegible]

```

IF INPS = "" THEN INPS = "LTC.INP"
INPUT "DEFINE OUTPUT DATA FILE NAME <LTC.OUT>"; OUT$
IF OUT$ = "" THEN OUT$ = "LTC.OUT"
INPUT "DEFINE POWER OUTPUT DATA FILE NAME <POWRO.OUT>"; POWRO$
IF POWRO$ = "" THEN POWRO$ = "POWRO.OUT"
INPUT "DEFINE DELTA TEMPREATURE OUTPUT FILE NAME <DTEMP.OUT>"; DTEMP$
IF DTEMP$ = "" THEN DTEMP$ = "DTEMP.OUT"
OPEN INPS FOR INPUT AS #3
OPEN OUT$ FOR OUTPUT AS #4
LINE INPUT #3, T$: LINE INPUT #3, T$
'===== INPUT DATA PART I =====
REM: I. TRANSIENT TYPE :
INPUT #3, TT: LINE INPUT #3, T$ '1=TOP, 2=LOHS, 3=LOF(NOT WORKING)
REM: II. TIME STRUCTURE :
LINE INPUT #3, T$
INPUT #3, DT(1): LINE INPUT #3, T$ 'TIME STEP SIZE (SEC) OF FIRST BLOCK
INPUT #3, NM: LINE INPUT #3, T$ '# OF TIME STEPS PER BLOCK
INPUT #3, BE: LINE INPUT #3, T$ '# OF BLOCKS
INPUT #3, LDB: LINE INPUT #3, T$ 'RELATIVE-POWER-CHANGE LIMIT FOR DT(BL)
-DOUBLING
INPUT #3, LHA: LINE INPUT #3, T$ 'RELATIVE-POWER-CHANGE LIMIT FOR DT(BL)
-HALVING
INPUT #3, MAXDT: LINE INPUT #3, T$ 'MAXIMUM STEP SIZE (SEC)
LINE INPUT #3, T$
REM: III. REACTIVITY INSERTION :
INPUT #3, RG: LINE INPUT #3, T$ '1=RAMP, 2=WORTH-CURVE
INPUT #3, A: LINE INPUT #3, T$ 'RAMP INSERTION RATE
INPUT #3, RM: LINE INPUT #3, T$ 'END-POINT REACTIVITY OF RAMP
INPUT #3, DR: LINE INPUT #3, T$ 'DURATION OF PARABOLIC RAMP SMOOTHING
LINE INPUT #3, T$ 'END-POINT OF RAMP +/- DR*DT
INPUT #3, H: LINE INPUT #3, T$ 'CORE HEIGHT (CM)
LINE INPUT #3, T$
REM: IV. OTHER QUANTITIES :
INPUT #3, P0: LINE INPUT #3, T$ 'INITIAL POWER RELATIVE TO NOMINAL POWE
R
INPUT #3, TL: LINE INPUT #3, T$ 'FLOW-TIME CORE-OUTLET TO IHX-OUTLET (
SEC)
LINE INPUT #3, T$: LINE INPUT #3, T$
'===== INPUT DATA PART II =====
REM: V. OTHER QUANTITIES : (FP=FULL POWER; FPS=FP SECONDS)
INPUT #3, DHR: LINE INPUT #3, T$ 'DECAY HEAT REMOVAL FROM HOT POOL (FP)
INPUT #3, BH: LINE INPUT #3, T$ 'INITIAL DECAY HEAT FRACTION (FP)
INPUT #3, SSP: LINE INPUT #3, T$ 'SPONTANEOUS FISSION SOURCE (FP)
INPUT #3, ARVHP: LINE INPUT #3, T$ 'HOT POOL VESSEL AREA (M**2)
)
INPUT #3, ARVCP: LINE INPUT #3, T$ 'COLD POOL VESSEL AREA (M**2)
INPUT #3, CLHP: LINE INPUT #3, T$ 'HOT POOL SODIUM HEAT CAPACITY (FPS)
)
INPUT #3, CLCP: LINE INPUT #3, T$ 'COLD POOL SODIUM HEAT CAPACITY (FPS)
)
INPUT #3, CSHP: LINE INPUT #3, T$ 'HOT POOL STEEL HEAT CAPACITY (FPS)
)
INPUT #3, CSCP: LINE INPUT #3, T$ 'COLD POOL STEEL HEAT CAPACITY (FPS)
)

```

```

INPUT #3, CVHP: LINE INPUT #3, T$ 'HOT POOL VESSEL HEAT CAPACITY (FPS
)
INPUT #3, CVCP: LINE INPUT #3, T$ 'COLD POOL VESSEL HEAT CAPACITY (FPS
)
INPUT #3, CCOR: LINE INPUT #3, T$ 'CORE HEAT CAPACITY (FPS
)
INPUT #3, CFUL: LINE INPUT #3, T$ 'FUEL HEAT CAPACITY (FPS
)
INPUT #3, DTCOOL: LINE INPUT #3, T$ 'NOMINAL COOLANT TEMPERATURE RISE (
K)
INPUT #3, DTFCO: LINE INPUT #3, T$ 'NOMINAL FUEL/CLAD TEMPERATURE RISE (
K)
INPUT #3, TVCPO: LINE INPUT #3, T$ 'INITIAL COLD POOL SODIUM TEMPERATURE (
K)
INPUT #3, TVHPO: LINE INPUT #3, T$ 'INITIAL HOT POOL SODIUM TEMPERATURE (
K)
LINE INPUT #3, T$: LINE INPUT #3, T$

```

```

'===== INPUT DATA PART III =====
REM: BETA , BT(1) TO BT(6), DELAYED NEUTRONS
INPUT #3, BT(1), BT(2), BT(3), BT(4), BT(5), BT(6): LINE INPUT #3, T$
REM: BETA , BT(7) TO BT(12), DECAY HEAT
INPUT #3, BT(7), BT(8), BT(9), BT(10), BT(11), BT(12): LINE INPUT #3, T$
REM: BETA , BT(13) TO BT(21), FEEDBACK (INDEX NOT CORRESPONDING TO LAMBDA)
INPUT #3, BT(13), BT(14), BT(15), BT(16), BT(17), BT(18), BT(19), BT(20), B
T(21): LINE INPUT #3, T$
REM: LAMDA, L(1) TO L(6), DELAYED NEUTRONS
INPUT #3, L(1), L(2), L(3), L(4), L(5), L(6): LINE INPUT #3, T$
REM: LAMDA, L(7) TO L(12), DECAY HEAT
INPUT #3, L(7), L(8), L(9), L(10), L(11), L(12): LINE INPUT #3, T$
REM: LAMDA, L(13) TO L(20), FEEDBACK (INDEX NOT CORRESPONDING TO BETA)
INPUT #3, L(13), L(14), L(15), L(16), L(17), L(18), L(19), L(20): LINE INPU
T #3, T$
REM: LAMDA, L(21) TO L(32), FLOW LOOP
INPUT #3, L(21), L(22), L(23), L(24), L(25), L(26), L(27), L(28), L(29), L(
30), L(31), L(32): LINE INPUT #3, T$
REM: SPECIAL LAMBDA VALUES
INPUT #3, SLAMBDA(1), SLAMBDA(2), SLAMBDA(3), SLAMBDA(4), SLAMBDA(5): LINE
INPUT #3, T$: LINE INPUT #3, T$

```

```

'===== INPUT DATA PART IV =====
REM: TEMPERATURES FOR RACS HEAT-FLUX CORRELATION
INPUT #3, TRAC(1), TRAC(2), TRAC(3), TRAC(4), TRAC(5), TRAC(6), TRAC(7), TR
AC(8), TRAC(9), TRAC(10), TRAC(11), TRAC(12): LINE INPUT #3, T$
REM: RACS HEAT FLUXES
INPUT #3, QRAC(1), QRAC(2), QRAC(3), QRAC(4), QRAC(5), QRAC(6), QRAC(7), QR
AC(8), QRAC(9), QRAC(10), QRAC(11), QRAC(12): LINE INPUT #3, T$
REM: TIMES FOR STEAM GENERATOR HEAT-FLUX CORRELATION
INPUT #3, TLF(1), TLF(2), TLF(3), TLF(4), TLF(5), TLF(6), TLF(7), TLF(8), T
LF(9), TLF(10), TLF(11), TLF(12), TLF(13), TLF(14), TLF(15), TLF(16), TLF(1
7), TLF(18): LINE INPUT #3, T$
REM: STEAM GENERATOR HEAT FLUXES
INPUT #3, QLF(1), QLF(2), QLF(3), QLF(4), QLF(5), QLF(6), QLF(7), QLF(8), Q
LF(9), QLF(10), QLF(11), QLF(12), QLF(13), QLF(14), QLF(15), QLF(16), QLF(1
7), QLF(18): LINE INPUT #3, T$

```

```

.....
INPUT #3, PR: LINE INPUT #3, TS ' NOMINAL HEAVY REJECTION
(FP)
INPUT #3, TLOF: LINE INPUT #3, TS 'CHARACTERISTIC TIME FOR FLOW LOSS IN LO
F (SEC)
INPUT #3, TLOHS: LINE INPUT #3, TS 'TIME FOR SG LOOSING HEAT FLUX IN LOHS
(SEC)
INPUT #3, NPNT: LINE INPUT #3, TS 'PRINT EVERY NPNT STEP
INPUT #3, INED: LINE INPUT #3, TS '1=ENABLE INPUT EDIT; 0=NO EDIT; 0.1=ONL
Y HEADING
INPUT #3, STUCK: LINE INPUT #3, TS 'STUCK=0 IF FUEL FREE TO EXPAND
CLOSE #3
.....
PI# = 3.141592654#
RSLHP = CSHP / CLHP
RSLCP = CSCP / CLCP
RVLHP = CVHP / CLHP
RVLCP = CVCP / CLCP
RSLCP = CSCP / CLCP
IF TT <> 1 THEN A = 0: RM = 0
.....
BS = DT(1) * NM: REM: BLOCK SIZE OF FIRST BLOCK
IF BS < TL AND BE > 1 THEN BEEP: PRINT "BLOCK SIZE TOO SMALL!": STOP
CLS
'===== INPUT EDIT =====
IF INED = 0 GOTO 800: REM: SCIP INPUT EDIT ENTIRELY

PRINT #4, "*****-- VERSION LTC-5 -----*****"
*****
DDS = DATES$
TIM$ = TIMES$
IF TT = 1 THEN PRINT #4, " "; DDS; " TOP
"; TIM$
IF TT = 2 THEN PRINT #4, " "; DDS; " LOHS
"; TIM$
IF INED = .1 GOTO 800: REM: SCIP REMAINING INPUT EDIT

PRINT #4, "=====EDIT OF INPUT DATA=====
=="
PRINT #4,
PRINT #4, "TT=TRANSIENT TYPE, 1:TOP ; 2:LOHS ; 3:LOF..... "
; TT
PRINT #4, "DT(1)=TIME STEP SIZE OF FIRST BLOCK (SECONDS)..... "
; DT(1)
PRINT #4, "MAXDT=MAXIMUM STEP SIZE (SECONDS)..... "
; MAXDT
PRINT #4, "NM=NUMBER OF TIME STEPS PER BLOCK..... "
; NM
PRINT #4, "BE=NUMBER OF BLOCKS..... "
; BE
PRINT #4, "LDB=REL.POWER-CHANGE LIMIT FOR DT(BL)-DOUBLING..... "
; LDB
PRINT #4, "LHA=REL.POWER-CHANGE LIMIT FOR DT(BL)-HALVING..... "
; LHA
PRINT #4, "RG=OPTION OF EXTERNAL REACTIVITY, 1:RAMP ; 2:WORTH CURVE..... "

```



```

; RG
PRINT #4, "A=INPUT RAMP RATE ($/S)..... "
; A
PRINT #4, "RM=MAXIMUM RAMP REACTIVITY ($)..... "
; RM
PRINT #4, "DR=DURATION OF PARABOLIC RAMP SMOOTHING (+/- DR*DT(1))..... "
; DR
PRINT #4, "H=CORE HEIGHT (CM)..... "
; H
PRINT #4, "TL=FLOW DELAY BETWEEN OUTLET AND INLET (SECONDS)..... "
; TL
PRINT #4, "BH=INITIAL DECAY HEAT FRACTION OF TOTAL POWER..... "
; BH
PRINT #4, "PR=HEAT REJECTION RATE (FULL POWER)..... "
; PR
PRINT #4, "ARVHP=HOT POOL VESSEL AREA (M**2)..... "
; ARVHP
PRINT #4, "ARVCP=COLD POOL VESSEL AREA (M**2)..... "
; ARVCP
PRINT #4, "DHR=DECAY HEAD REMOVAL (FULL POWER)..... "
; DHR
PRINT #4, "DTCOOL 'NOMINAL COOLANT TEMPERATURE RISE ALONG CHANNEL..... "
; DTCOOL
PRINT #4, "NPNT=PRINT EVERY NPNT STEP..... "
; NPNT
PRINT #4, "TLOF=CHARACTERISTIC TIME FOR FLOW LOSS in LOF (SEC)..... "
; TLOF
PRINT #4, "TLOHS=TIME FOR SG LOSING HEAT FLUX IN LOHS (SEC)..... "
; TLOHS
PRINT #4, "SSP=SPONTANEOUS FISSION SOURCE..... "
; SSP
PRINT #4,
PRINT #4, "          K          BT(K)          L(K)          "
FOR K = 1 TO 32
FBS(K, 1) = "          " + STR$(K)
FBS(K, 2) = STR$(BT(K))
FBS(K, 3) = STR$(L(K))
IF K <= 6 THEN FBS(K, 4) = " DELAYED NEUTRON"
IF K > 6 AND K <= 12 THEN FBS(K, 4) = " DECAY HEAT"
IF K > 12 AND K <= 20 THEN FBS(K, 4) = " FEEDBACK(NOTE#2)"
IF K > 20 AND K <= 26 THEN FBS(K, 4) = " FLOW COLD-POOL"
IF K = 23 THEN FBS(K, 4) = " STEEL COLD-POOL"
IF K = 25 THEN FBS(K, 4) = " VESSEL COLD-POOL"
IF K > 26 THEN FBS(K, 4) = " FLOW HOT-POOL"
IF K = 29 THEN FBS(K, 4) = " STEEL HOT-POOL"
IF K = 31 THEN FBS(K, 4) = " VESSEL HOT-POOL"
PRINT #4, USING "\          \"; FBS(K, 1); FBS(K, 2); FBS(K, 3); FBS(K, 4)
NEXT K
PRINT #4,
PRINT #4, "NOTE#1 : BT(K)=BT(K)/100          FOR DELAYED NEUTRONS"
PRINT #4, "          BT(K)=BT(K)/100/(1-BH)    FOR DECAY HEAT"
PRINT #4,
FOR K = 13 TO 20
FBS(K - 12, 1) = STR$(BT(K))

```

```

FB$(K - 12, 2) = STR$(L(K))
NEXT K
PRINT #4,
PRINT #4, "NOTE#2 : INDIVIDUAL FEEDBACK COEFFICIENTS & TIME CONSTANTS :
"
PRINT #4,
PRINT #4, "-DRIVING FORCE---DELAY LOCATION---TIME CONSTANT-----"
PRINT #4, USING "\          \"; "CLAD -TEMP "; " FUEL ROD "; FB$(1, 2)
PRINT #4, USING "\          \"; "OUTLET-TEMP"; " LOAD PAD "; FB$(2, 2)
PRINT #4, USING "\          \"; "INLET-TEMP"; " GRID PLATE"; FB$(3, 2)
PRINT #4, USING "\          \"; "COOLANT "; " STRUCTURE "; FB$(4, 2)
PRINT #4, USING "\          \"; "FISSION POWER"; "FUEL ROD"; FB$(5, 2)
PRINT #4, USING "\          \"; "HP-TEMP "; " CR-DRIVE "; FB$(6, 2)
PRINT #4,
PRINT #4,
PRINT #4, "----- INDIVIDUAL FEEDBACK COEFFICIENTS: BT(K) -----
"
PRINT #4, "DOPPLER ..... "; BT(13)
PRINT #4, "AXIAL EXPANSION ..... "; BT(14)
PRINT #4, "COOLANT EXPANSION ..... "; BT(15)
PRINT #4, " 100*XMC/XAC ..... "; BT(16)
PRINT #4, "GRID PLATE EXPANSION ..... "; BT(17)
PRINT #4, "CR-DRIVE-LINE EXPANSION ..... "; BT(18)
PRINT #4, "HOT POOL VESSEL EXPANSION..... "; BT(19)
PRINT #4, "COLD POOL VESSEL EXPANSION..... "; BT(20)
PRINT #4,
PRINT #4,
PRINT #4,
PRINT #4,
PRINT #4, "----- HEAT CAPACITIES -----
--"
PRINT #4, "CLHP=HEAT CAPACITY OF HOT-POOL SODIUM (FPS/K)..... "
; CLHP
PRINT #4, "CLCP=HEAT CAPACITY OF COLD-POOL SODIUM (FPS/K)..... "
; CLCP
PRINT #4, "CSHP=HEAT CAPACITY OF HOT-POOL STEEL (FPS/K)..... "
; CSHP
PRINT #4, "CSCP=HEAT CAPACITY OF COLD-POOL STEEL (FPS/K)..... "
; CSCP
PRINT #4, "CVHP=HEAT CAPACITY OF HOT-POOL VESSEL (FPS/K)..... "
; CVHP
PRINT #4, "CVCP=HEAT CAPACITY OF COLD-POOL VESSEL (FPS/K)..... "
; CVCP
PRINT #4,
':----- END INPUT DATA AND EDIT -----:

/----- LAMBDA AND BETA COMBINATIONS -----
800 :
LC = SLAMBDA(1) + SLAMBDA(2)
LCF = SLAMBDA(2) / LC
LCL = SLAMBDA(1) / LC

FLN = 1 /----- TOP AND LOHS -----
LL = SLAMBDA(5) + SLAMBDA(3) + SLAMBDA(4) * FLN

```

```

LLC = SLAMBDA(5) / LL
LLS = SLAMBDA(3) / LL
LLI = SLAMBDA(4) / LL
LLL = 1 / (1 - LLC * LCL)
TLO = .5 * DTCOOL * SLAMBDA(4) / LL '-----TAU-0 -----

```

```

'::::::::::::::::::::: END INFORMATION AND INPUT :::::::::::::::::::::::

```

```

/
/ *****
/ *****
/ *
/ * INITIAL VALUES AND GENERAL PREPARATIONS *
/ *
/ *****
/ *****
/

```

```

'----- INITIAL VALUES & SLOPES -----

```

```

/----- TIME -----
BL = 1
N = 1
T(1) = 0
/----- POWER -----
PO = PO 'INITIAL POWER (INPUT)
FPO = PO * (1 - BH): DON(1) = FPO 'FISSION POWER
FPD = FPO * A: D1N(1) = FPD 'FISSION POWER DERIVATIVE
PTD = FPD 'TOTAL POWER DERIVATIVE
/----- FLOW -----
FLO = 1 'INITIAL FLOW
/----- DELAYED NEUTRONS -----
B = 0
FOR K = 1 TO 6
BT(K) = BT(K) / 100
B = B + BT(K)
V(K) = FPO 'CONVOLUTION INTEGRALS, K=1 TO 6
NEXT K
SD = B * FPO 'DELAYED NEUTRON SOURCE (NO DERIVATIVE)
/----- DECAY HEAT -----
FOR K = 7 TO 12
BT(K) = BT(K) / 100 / (1 - BH)
V(K) = FPO 'CONVOLUTION INTEGRALS, K=7 TO 12
NEXT K
DHO = PO * BH: DON(2) = DHO 'DECAY HEAT
DHD = 0: D1N(2) = DHD 'DECAY HEAT DERIVATIVE
/----- FEEDBACK REACTIVITY -----
FOR K = 13 TO 21
BT(K) = BT(K) / 100
V(K) = 0 'CONVOLUTION INTEGRALS
NEXT K
/----- TEMPERATURES -----
DTIO = 0: DON(8) = 0: DDTIO = 0: D1N(8) = 0 ' INLET
DTOO = 0: DON(3) = 0: DDTOO = 0: D1N(3) = 0 ' OUTLET
DTFO = 0: DDTFO = 0 ' FUEL
DTCO = 0: DON(11) = 0: DDTCO = 0: D1N(11) = 0 ' CLAD

```

```

DTLO = 0: DON(12) = 0: DDTLO = 0: D1N(12) = 0 ' COOLANT
DTHXO = 0: DON(7) = 0: DDTHXO = 0: D1N(7) = 0 ' HX-OUTLET
DTSCPO = 0: DON(9) = 0: DDTSCPO = 0: D1N(9) = 0 ' SS COLD POOL
DTLHPO = 0: DON(4) = 0: DDTLHPO = 0: D1N(4) = 0 ' SODIUM HOT POOL
DTSHPO = 0: DON(5) = 0: DDTSHPO = 0: D1N(5) = 0 ' SS HOT POOL
DTVHPO = 0: DON(6) = 0: DDTVHPO = 0: D1N(6) = 0 ' VESSEL HOT POOL
DTVCPO = 0: DON(10) = 0: DDTVCPO = 0: D1N(10) = 0 ' VESSEL COLD POOL
TVHP = TVHPO: TVCP = TVCPO ' VESSELS

```

```

.....
FOR M = 1 TO 13
DO(M) = DON(M): IDON(M) = DON(M)
D1(M) = D1N(M): ID1N(M) = D1N(M)
NEXT M
.....

```

```

----- HEAT REJECTION -----
GOSUB 4800 'VESSEL HEAT REJECTION
PRVHPO = PRVHP: PRVCPO = PRVCP'-----POWER REJECTED BY VESSEL

```

```

.....
===== OPEN OUTPUT FILES =====
OPEN DTEMP$ FOR OUTPUT AS #1
OPEN POWRO$ FOR OUTPUT AS #2

```

```

----- PRINT HEADER AND INITIAL VALUES -----
PRINT #4, " MIN.SEC POWER DEC.HEAT DTOUTLET DTLHP DTHX DTINLET 100*RO
100*RX 100*RF "
PRINT " MIN.SEC POWER DEC.HEAT DTOUTLET DTLHP DTHX DTINLET 100*RO 10
0*RX 100*RF "
LOCATE 2, 1
PRINT STRING$(80, "=")
VIEW PRINT 3 TO 25

```

```

PRINT #1, "----- DELTA TEMPERATURE OUTPUT -----"
PRINT #1, " TIME(S) DT-FUEL DT-CLAD DT-COOL DT-STRUC DT-CR DTOUTLET DTLHP
DTHX DTINLET"
PRINT #2, "----- POWER & REACTIVITY OUTPUT -----"

```

```

PRINT #2, " TIME(S) 100*POW 100*DC.HT RHO(CT) DOPPLER AX.EXP COOLANT RAD.E
XP CR-ROD "
PRINT #4, USING "####.###"; 0; 100 * PO; 100 * DHO; 0; 0; 0; 0; 0; 0; 0; 0
PRINT #1, USING "####.###"; 0; 0; 0; 0; 0; 0; 0; 0; 0; 0
PRINT #2, USING "####.###"; 0; 100 * PO; 100 * DHO; 0; 0; 0; 0; 0; 0; 0; 0

```

```

.....
===== BASE-POINT NOTATION OF INITIAL VALUES =====
FPO = FPO: DHO = DHO: PO = PO
FLO = FLO
DTIO = 0: DTOO = 0: DTFO = 0: DTCO = 0: DTLO = 0
DTHXO = 0: DTSCPO = 0: DTSHPO = 0: DTLHPO = 0
DTVCPO = 0: DTVHPO = 0

```

```

----- TRANSIENT SELECTION -----

```



```

.....
FOR BL = 1 TO BE'***** START OF BLOCK BL LOOP *****

IF BL = 1 GOTO 1800
'----- NEW TIME STEP, NO & NE -----
IF MAXD < LDB THEN DT(BL) = 2 * DT(BL - 1)
IF MAXD > LHA THEN DT(BL) = .5 * DT(BL - 1)
IF DT(BL) * NM < TL OR DT(BL) > MAXDT THEN DT(BL) = DT(BL - 1)
PRINT #4, " BLOCK # "; BL; " MAXD OF PREVIOUS BLOCK= "; MAXD; " THUS
NEW DT= "; DT(BL)
PRINT " BLOCK # "; BL; " MAXD OF PREVIOUS BLOCK= "; MAXD; " THUS NEW
DT= "; DT(BL)
PRINT #1, "BLOCK "; BL: PRINT #2, "BLOCK "; BL
NO(BL) = NM + 1
NE(BL) = 2 * NM
IF DT(BL) / DT(BL - 1) = 2 THEN PP = 2
IF DT(BL - 1) / DT(BL) = 2 THEN PP = 1
'----- BLOCK BL COEFFICIENTS -----
1800 :
'----- GENERAL COEFFICIENTS -----
AAP = 1 / DT(BL) / DT(BL)

FOR K = 1 TO 32
LDT(K) = L(K) * DT(BL)
EX(K) = EXP(-LDT(K))
MO(K) = 1 - EX(K)
BX(K) = BT(K) * EX(K)
M1(K) = DT(BL) - MO(K) / L(K)
M1AS = LDT(K) * DT(BL) / 2
IF M1(K) > M1AS THEN M1(K) = M1AS
IF M1(K) < 0 THEN M1(K) = M1AS
M2(K) = DT(BL) * DT(BL) - 2 * M1(K) / L(K)
M2AS = LDT(K) * DT(BL) * DT(BL) / 3
IF M2(K) > M2AS THEN M2(K) = M2AS
IF M2(K) < 0 THEN M2(K) = M2AS
AP(K) = M2(K) * AAP
NEXT K
'----- TEMPERATURE COMPONENTS -----
DTFP = DTFC0 * AP(17)
DTCP = DTFP * LCF * LLL
DTLP = DTCP * LLC
'----- DELAYED NEUTRON COEFFICIENTS -----
PSD = 0: MSD = 0: DSD = 0
FOR K = 1 TO 6
PSD = PSD + BT(K) * M2(K)
MSD = MSD + BT(K) * M1(K)
DSD = DSD + BT(K) * MO(K)
NEXT K
PSD = PSD * AAP
'----- DECAY HEAT COEFFICIENTS -----
PDH = 0: MDH = 0: DDH = 0
FOR K = 7 TO 12
PDH = PDH + BT(K) * M2(K)

```

```

MDH = MDH + BT(K) * M1(K)
DDH = DDH + BT(K) * M0(K)
NEXT K
PDH = PDH * AAP
/----- PROMPT FEEDBACK COMPONENT -----
PRF = BT(13) * DTFP + BT(14) * ((1 - STUCK) * DTFP + STUCK * DTCP) + BT(15)
* DTLF
/.....
MAXD = 0
/::::::::::::: END OF CONTROL OF BLOCKWISE POWER CALCULATION :::::::::::::::
/
/ *****
/ *****
/ *
/ *   POWER CALCULATION FOR GENERAL TIME STEP IN BLOCK BL *
/ *
/ *****
/ *****

FOR N = NO(BL) TO NE(BL) ' *** START OF TIME STEP LOOP ***

/----- PREPARATIONS FOR TIME STEP N+1 -----
T(N + 1) = T(N) + DT(BL)
FPX = DON(1) + D1N(1) * DT(BL)
AAH = -FPX * AAP
AH(17) = V(17) * EX(17) + DON(1) * M0(17) + D1N(1) * M1(17) + AAH * M2(17)
/.....
/----- HISTORICAL COMPONENT OF DELAYED NEUTRON SOURCE -----
HSD = 0
FOR K = 1 TO 6
HSD = HSD + V(K) * BX(K)
NEXT K
HSD = HSD + FPO * DSD + FPD * MSD - FPX * PSD
/.....
/----- HISTORICAL COMPONENT OF DECAY HEAT -----
HDH = 0
FOR K = 7 TO 12
HDH = HDH + V(K) * BX(K)
NEXT K
HDH = HDH + FPO * DDH + FPD * MDH - FPX * PDH
/.....
/----- EXTERNAL REACTIVITY: RX(N+1) -----
IF TT > 1 THEN RX = 0: GOTO 2070
IF RG = 1 THEN 2036: REM: RAMP
IF RG = 2 THEN 2052: REM: WORTH CURVE
2036 :
/           RHO-X SMOOTHED RAMP
/           -----
IF T(N + 1) <= T1 THEN RX = A * T(N + 1)
IF T(N + 1) >= T2 THEN RX = RM
IF T(N + 1) <= T1 THEN 2070
IF T(N + 1) >= T2 THEN 2070
RX = (A2 * (T(N + 1) - TX) + A1) * (T(N + 1) - TX) + A0
GOTO 2070
2052 :

```



```

DTCH = LLL * (LCF * DTFH + LCL * (LLS * DTS + LLI * FLN * DTIN - TLO * (FLN
- FLO)))
DTLH = LLL * (LLC * LCF * DTFH + (LLS * DTS + LLI * FLN * DTIN - TLO * (FLN
- FLO)))

```

```

'----- HISTORICAL FEEDBACK COMPONENT -----
RLP = BT(17) * DTLPEFF
HRF = BT(13) * DTFH + BT(14) * ((1 - STUCK) * DTFH + STUCK * DTCH) + BT(15)
* DTLH + RLP + BT(17) * DTGP + RCR

```

```

'----- CALCULATION OF FISSION POWER -----

```

```

'----- QUADRATIC EQUATION -----
Q = (HSD + SSP) / PRF / B
RR = (1 - RX - HRF - PSD / B) / PRF
FPN = (RR + SQR(RR * RR - 4 * Q)) / 2
IF ABS(Q / RR) < .0001 THEN FPN = (Q + (Q / RR) ^ 2) / RR

```

```

'----- APPLICATION OF NEW FISSION POWER -----

```

```

'----- DELTA-TEMPERATURE -----
DTIN = DTIN '-----DELTA T-INLET-----
DTFN = DTFH + DTFP * FPN '-----DELTA T-FUEL-----
DTS = DTS '-----DELTA T-STRUCTURE-----
DTLN = DTLH + DTLF * FPN '-----DELTA T-COOLANT-----
DTCN = DTCH + DTCF * FPN '-----DELTA T-CLAD-----
DTON = DTIN + 2 * (DTLN - DTIN) '-----DELTA T-OUTLET-----

```

```

DTLPEFF = DTLPEFF '-----EFFECTIVE DELTA T-LOAD PAD-----
DTGP = DTGP '-----DELTA T-GRID PLATE-----

```

```

'----- FEEDBACK REACTIVITIES -----

```

```

RDOP = BT(13) * DTFN '-----DOPPLER-----
RAX = BT(14) * ((1 - STUCK) * DTFN + STUCK * DTCN) '-----AXIAL EXPANSION-----
ION--
RCOL = BT(15) * DTLN '-----COOLANT-----
RLP = BT(17) * DTLPEFF '-----LOAD PAD-----
RGP = BT(17) * DTGP '-----GRID PLATE-----
RRAD = RLP + RGP '-----RADIAL EXPANSION-----
RCR = RCR '-----CR-DRIVE LINE-----

```

```

'RCR IS CALCULATED IN "HOT POOL (4718)"
'RCR INCLUDES VESSEL EXPANSION

```

```

'----- TOTAL RECTIVITY -----

```

```

RF = RDOP + RAX + RCOL + RRAD + RCR
RO = RX + RF

```

```

'----- POWER TERMS -----

```

```

FPN = FPN '-----FISSION POWER-----
DHN = PDH * FPN + HDH '-----DECAY HEAT-----
PN = FPN + DHN '-----POWER-----
SD = PSD * FPN + HSD '-----DELAYED NEUTRONS-----

```

```

'----- POWER PARABOLAS AND SLOPES -----

```

```

'THE Y0-Y2-VALUES ARE NOT USED FOR N=1
'THE Y2 & Y3-SETTINGS ARE OK FOR N=1, ALTHOUGH ONLY Y3 IS USED
'FOR N=2: Y2 & Y3 ARE TURNED INTO Y1 & Y2, Y3= NEW VALUE

```

'Y0 IS NOT USED FOR N=2

M = 1: PFLAG = 0 '----- FISSION POWER PARABOLA -----
Y0 = FPO2: Y1 = FPO1: Y2 = FPO: Y3 = FPN
GOSUB 3100

M = 2: PFLAG = 0 '----- DECAY HEAT PARABOLA -----
Y0 = DHO2: Y1 = DHO1: Y2 = DHO: Y3 = DHN
GOSUB 3100

.....
'----- TEMPERATURE PARABOLAS AND SLOPES -----
M = 3: PFLAG = 0 '----- DT-OUTLET PARABOLA -----
Y0 = DTOO2: Y1 = DTOO1: Y2 = DTOO: Y3 = DTON
GOSUB 3100

M = 11: PFLAG = 0 '----- DT-CLAD PARABOLA -----
Y0 = DTCO2: Y1 = DTCO1: Y2 = DTCO: Y3 = DTCN
GOSUB 3100
GOSUB 3100

M = 12: PFLAG = 0 '----- DT-COOLANT PARABOLA -----
Y0 = DTLO2: Y1 = DTLO1: Y2 = DTLO: Y3 = DTLN
GOSUB 3100

'===== CONVOLUTION INTEGRALS =====
'----- FISSION POWER AND POWER CONVOLUTION INTEGRALS -----
FOR K = 1 TO 12
IV(K) = V(K) * EX(K) + D0(1) * M0(K) + D1(1) * M1(K) + D2(1) * M2(K)
NEXT K

IV(17) = V(17) * EX(17) + D0(1) * M0(17) + D1(1) * M1(17) + D2(1) * M2(17)

IV(20) = V(20) * EX(20) + (D0(2) - P0) * M0(20) + D1(2) * M1(20) + D2(2) * M2(20)

.....
'----- CONVOLUTION INTEGRALS FOR TEMPERATURES -----
'CONTRIBUTION TO DELTA T-FUEL FROM DELTA T-CLAD:
IV(13) = V(13) * EX(13) + D0(11) * M0(13) + D1(11) * M1(13) + D2(11) * M2(13)
'USING L(13) & DTC-PARABOLA (M=11)

D0(13) = D0(8) + 2 * BT(21) * (D0(3) - D0(8)) 'DTLP-EFF PARABOLA COEFFICIENT
D1(13) = D1(8) + 2 * BT(21) * (D1(3) - D1(8)) 'DTLP-EFF PARABOLA COEFFICIENT
D2(13) = D2(8) + 2 * BT(21) * (D2(3) - D2(8)) 'DTLP-EFF PARABOLA COEFFICIENT

IV(14) = V(14) * EX(14) + D0(13) * M0(14) + D1(13) * M1(14) + D2(13) * M2(14)

'USING L(14) & DTLPEFF-PARABOLA (M=13) : DT-LOAD-PAD-EFF
DTLPEFF = IV(14)

IV(15) = V(15) * EX(15) + D0(8) * M0(15) + D1(8) * M1(15) + D2(8) * M2(15)
'USING L(15) & DTI-PARABOLA (M=8) : DT-GRID-PLATE

IV(16) = V(16) * EX(16) + D0(12) * M0(16) + D1(12) * M1(16) + D2(12) * M2(16)

'USING L(16) & DTL-PARABOLA (M=12) : DT-STRUCTURE
DTS = IV(16)


```

      : '::::::::::::-- END PRINTING --::::::::::::
2850 : '::::::::::::-- END OF BLOCK BL CALCULATIONS --::::::::::::
      :

```

```

IF BL = 1 GOTO 3042
IF BL = BE GOTO 3042
FOR N = 1 TO NM + 1
T(N) = T(NO(BL) - 1 + N)
DTLHP(N) = DTLHP(NO(BL) - 1 + N)
FOR I = 1 TO 4
PARLHP(N, I) = PARLHP(NO(BL) - 1 + N, I)
NEXT I
NEXT N

```

```

.....
/=====-- PRINT "ELAPSED TIME/BLOCK & FISSION POWER --=====
3042 : TBL = TIMER: TELAP = TELAP + TBL - TSTART: TSTART = TBL
PRINT #4, " BLOCK # "; BL; " ELAPSED TIME IS "; TELAP; " SECONDS;"; " FIS
SION POWER= "; FPN
PRINT " BLOCK #"; BL; "ELAPSED TIME IS "; TELAP; " SECONDS;"; " FISSION POW
ER="; FPN
'PRINT "::::::::::::::::::: "; INT(BL / BE * 100); " % FINISHED
:::::::::::::::::::"

```

```
NEXT BL '>>>>>>>>>>>>>>>----- NEXT BL ----->>>>>>>>>>>>>>>>>>>'
'/!!!!!!!!!!!!!!'
'/*****-- END OF THIS RUN --*****/
'/----- TOTAL ELAPSED TIME PRINT -----'
TELAP = TELAP / 60
PRINT #4, : PRINT #4, "TOTAL ELAPSED TIME FOR THIS RUN IS "; TELAP; " MINUTES"
CLOSE 1, 2, 4
TS = INKEY$
```

```

===== OPTIONAL PRINT OUTS =====
INPUT "DO YOU WANT TO PRINT OUT THE STANDARD OUTPUT FILE <Y/N>"; Y$
IF (Y$ = "Y") OR (Y$ = "y") THEN GOTO 1
GOTO 2
1 : OPEN OUT$ FOR INPUT AS #5
LOCATE 25, 13
PRINT "*** PRESS <ESC> TO STOP ***"
WHILE NOT EOF(5)
  T$ = INKEY$
  IF T$ = CHR$(27) THEN GOTO 2

```



```

V(21) = SLP(7) * M1(21): V(22) = (SLP(8) - SLP(9)) * L(23) * RSLCP / L(22)
* M1(22): V(24) = (SLP(8) - SLP(10)) * L(25) * RVLCP / L(24) * M1(24)
V(23) = DTSCPN: V(25) = DTVC PN: V(26) = DTIN: DTIN(8) = DTIN: DTIN(8) = SLP
(8): GOTO 2106'N=1
4100 : '----- PARABOLA BASE-TIME IDENTIFICATION -----
-----
N1 = 1
FOR I = N - 2 TO 2 STEP -1
IF T(I) >= T(N + 1) - TL GOTO 4112
IF N1 > 1 GOTO 4112
N1 = I
4112 : NEXT I
IF N1 = 1 THEN NB = N1
IF N1 > 1 THEN NB = N1 - 1
IF N1 = N - 2 THEN NB = N1
'----- INTEGRATION LIMITS -----
TB = PARLHP(NB, 1)
TU = T(N + 1) - TL - TB
IF TU < 0 THEN TU = 0
LL = TU - DT(BL)
IF TU = 0 THEN LL = 0
'----- HEAT EXCHANGER OUTLET TEMPERATURE & PARABOLA -----
IF T(N + 1) - TL >= 2 * DT(1) GOTO 4144
IF T(N + 1) - TL > 0 AND T(N + 1) - TL < DT(1) THEN DTOHXN = (DTLHP(2) - DT
LHP(1)) * (T(N + 1) - TL) / DT(1) + DTLHP(1) + DTLOHS
IF T(N + 1) - TL = DT(1) THEN DTOHXN = DTLHP(2) + DTLOHS
IF T(N + 1) - TL > DT(1) THEN DTOHXN = (DTLHP(3) - DTLHP(2)) * (T(N + 1) -
TL - DT(1)) / DT(1) + DTLHP(2) + DTLOHS
GOTO 4146
4144 : DTOHXN = PARLHP(NB, 2) + PARLHP(NB, 3) * TU + PARLHP(NB, 4) * TU * T
U + DTLOHS
4146 : M = 7: PFLAG = 0
Y0 = DTOHXO2: Y1 = DTOHXO1: Y2 = DTOHXO: Y3 = DTOHXN
GOSUB 3100
'----- FLOW TERM -----
IF TT = 1 GOTO 4158
V(21) = V(21) * EX(21) + D0(7) * M0(21) + D1(7) * M1(21) + D2(7) * M2(21):
GOTO 4164
4158 : T20 = L(21) * TU: L20 = L(21) * LL: D20 = L(21) * DT(BL)
C0 = PARLHP(NB, 2): C1 = PARLHP(NB, 3): C2 = PARLHP(NB, 4)
V(21) = V(21) * EX(21) + C0 * (1 - EXP(-D20)) + C1 * (T20 - 1 - (L20 - 1) *
EXP(-D20)) / L(21) + C2 * (T20 * T20 - 2 * T20 + 2 - (L20 * L20 - 2 * L20
+ 2) * EXP(-D20)) / L(21) / L(21)
4164 : '----- STEEL HEAT-UP TERM -----
-----
DF = (DTIO - DTSCPO) * L(23) * RSLCP / L(22)
DDF = (SLP(8) - SLP(9)) * L(23) * RSLCP / L(22)
V(22) = V(22) * EX(22) + DF * M0(22) + DDF * M1(22)
'----- VESSEL HEAT-UP TERM -----
DF = (DTIO - DTVCPO) * L(25) * RVLCP / L(24)
DDF = (SLP(8) - SLP(10)) * L(25) * RVLCP / L(24)
V(24) = V(24) * EX(24) + DF * M0(24) + DDF * M1(24)
'----- DTI FIRST CALCULATION & PARABOLA -----
DTIN = V(21) - V(22) - V(24)
M = 8: PFLAG = 0

```

Y0 = DTIO2: Y1 = DTIO1: Y2 = DTIO: Y3 = DTIN

GOSUB 3100

DTSCP CALCULATION & PARABOLA

$$V(23) = V(23) * EX(23) + DO(8) * MO(23) + D1(8) * M1(23) + D2(8) * M2(23)$$

DTSCP N = V(23)

M = 9: PFLAG = 0

Y0 = DTSCPO2: Y1 = DTSCPO1: Y2 = DTSCPO: Y3 = DTSCPN

GOSUB 3100

DTVCP CALCULATION & PARABOLA

$$V(25) = V(25) * EX(25) + D0(8) * M0(25) + D1(8) * M1(25) + D2(8) * M2(25)$$

DTVC PN JMC V(25)

$$TVCP = TVCP0 + DTVCPN$$

M = 10: PFLAG = 0

Y0 = DTVCP02: Y1 = DTVCP01: Y2 = DTVCP0: Y3 = DTVCPN

GOSUB 3100

DTI SECOND CALCULATION

$$D00 = D0(7) - (D0(8) - D0(9)) * RSLCP * L(23) / L(22) - (D0(8) - D0(10)) * RVLCP * L(25) / L(24)$$
$$D11 = D1(7) - (D1(8) - D1(9)) * RSLCP * L(23) / L(22) - (D1(8) - D1(10)) * RVLCP * L(25) / L(24)$$
$$D22 = D2(7) - (D2(8) - D2(9)) * RSLCP * L(23) / L(22) - (D2(8) - D2(10)) * RVLCP * L(25) / L(24)$$
$$V(26) = V(26) * EX(26) + D00 * M0(26) + D11 * M1(26) + D22 * M2(26)$$

DTIN = V(26)

DTI NEW PARABOLA

M = 8: PFLAG = 0

Y0 = DTIO2: Y1 = DTIO1: Y2 = DTIO: Y3 = DTIN

GOSUB 3100

' ::::::::::::::: END COLD POOL CALCULATION :::::::::::::::

GOTO 2106

SUBROUTINE: HOT POOL

4560 : '----- HOT POOL SET-UP:BL=1&N=1 -----

DTLHP(1) = 0

$$DTLHP(2) = DTON / DT(1) * M1(27); DTSHPN = DTLHP(2) / DT(1) * M1(29); DTVHP$$
$$N = DTLHP(2) / DT(1) * M1(31)$$
$$TVHP = TVHPO + DTVHPN$$

```
SLP(3) = DTON / DT(1)
```

$$SLP(4) = DTLHP(2) / DT(1)$$
$$SLP(5) = DTSHPN / DT(1) : SLP(6) = DTVHPN / DT(1)$$
$$V(27) = SLP(3) * M1(27): V(28) = (SLP(4) - SLP(5)) * L(29) * RSLHP / L(28)$$
$$* M1(28): V(30) = (SLP(4) - SLP(6)) * L(31) * RVLHP / L(30) * M1(30)$$

V(29) = DTSHPN: V(31) = DTVHPN: V(32) = DTLHP(2)

[illegible]

```

.....
4600 : ' ..... SUBROUTINE HOT POOL TEMPERATURES .....

```

[illegible]
$$V(27) = V(27) * EX(27) + D0(3) * M0(27) + D1(3) * M1(27) + D2(3) * M2(27)$$

STEEL HEAT-UP TERM

$$DF = (DTLHP(N) - DTSHPO) * L(29) * RSLHP / L(28)$$
$$DDF = (SLP(4) - SLP(5)) * L(29) * RSLHP / L(28)$$

100
100

References

1. K. O. Ott, "A Fast Reactor Transient Analysis Methodology for PCs: Vol. 1. The Computational Model," ANL/RE-91/2 Volume 1, Argonne National Laboratory (1991).
2. K. O. Ott, "A Fast Reactor Transient Analysis Methodology for PCs: Vol. 2. LTC Program Manual," ANL/RE-91/2 Volume 2, Argonne National Laboratory (1991).
3. K. O. Ott and R. J. Neuhold, "Nuclear Reactor Dynamics," American Nuclear Society, La Grange Park, Illinois, USA (1985).

END

**DATE
FILMED**

11 / 5 / 92