MASTER

FUEL COOLANT THERMAL INTERACTION PROJECT
UC 79P

Massachusetts Institute of Technology
Department of Nuclear and Mechanical Engineering

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Quarterly Progress Report No. 7

Approved July 1977

Neil E. Todreas

Neil E. Todreas
Principal Investigator

26

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Reports and Papers Published under
MIT Fuel-Coolant Interaction Project

(This project was funded until June 30, 1975 by ANL and reports issued as 31-109-38-2831-XX; starting July 1, 1975 reports were issued as COO-2781-XX)

Progress Reports (Available from National Technical Information Service, U.S. Department of Commerce, Springfield, Va. 22151)

W.F. Lenz, G. Shiralker and N. Todreas, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-1, Nov. 1975.

W.F. Lenz, G. Shiralker and N. Todreas, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-2, Feb. 1976.

G. Shiralker, W.F. Lenz and M. Corradini, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-3, April 1976.

G. Shiralker, W.F. Lenz and M. Corradini, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-5, Oct. 1976.

G. Shiralker, W.F. Lenz and M. Corradini, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-10, Dec. 1976.

M. Corradini, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-12, Jan. 1977

M. Corradini, Fuel Coolant Thermal Interaction Project UC 79P, COO-2781-13, June 1977

Reports Issued under this Contract

Topical Reports (Available from National Technical Information Service, U.S. Department of Commerce, Springfield, Va. 22151)

Mujid S. Kazimi, "Theoretical Studies on Some Aspects of Molten Fuel-Coolant Thermal Interaction," 31-109-38-2831-1TR, MITNE-155, May 1973.

Charles E. Watson, "Transient Heat Transfer Induced Pressure Fluctuations in the Fuel-Coolant Interaction," 31-109-38-2831-2TR, MITNE-156, August 1973.

Trond A. Bjornard, "An Experimental Investigation of Acoustic Cavitation as a Fragmentation Mechanism of Molten Tin Droplets in Water," 31-109-38-2831-3TR, MITNE-163, May 1974.

Glen Bjorkquist, "An Experimental Investigation of the Fragmentation of Molten Metals in Water," 31-109-38-2831-4TR, June 1975.

Roland B. Knapp, "Thermal Stress Initiated Fracture as a Fragmentation Mechanism in the UO₂-Sodium Fuel-Coolant Interaction," 31-109-38-2831-5TR, May 1975.

Michael Corradini, "Prediction of Minimum UO₂ Particle Size Based on Thermal Stress Initiated Fracture Model," COO-2781-4TR, August 1976.

M. Kazimi, C. Watson, D. Lanning, W. Rohsenow, N. Todreas, "Acoustic Cavitation as a Mechanism of Fragmentation of Hot Molten Droplets in Cool Liquids," COO-2781-6TR, November 1976.

Gautam S. Shiralkar, "An Investigation of the Fragmentation of Molten Metals Dropped into Cold Water," COO-2781-7TR, November 1976.

William F. Lenz, Jr. "Mixing Requirements for the Limiting Fuel-Coolant Interactions in Liquid Metal Fast Breeder Reactors," COO-2781-8TR, November 1976

M. Corradini, A.A. Sonin, N. Todreas, "A Proposed Heat Transfer Model for the Gas-Liquid Heat Transfer Effects Observed in the Stanford Research Institute Scaled Tests," COO-2781-9TR, December 1976.

M. Corradini, W.M. Rohsenow, N.E. Todreas, "Application of Spontaneous Nucleation Theory to Tin-H₂O Interactions," COO-2781-11TR, January 1977.

Reports Issued under this ContractPapers and Summaries

M.S. Kazimi, N.E. Todreas, D.D. Lanning and W.M. Rohsenow, "A Criterion for Free-Contact Fragmentation of Hot Molten Materials in Coolants," Transactions of the American Nuclear Society, Vol. 5, No. 2, p. 835, November 1972.

M.S. Kazimi, N.E. Todreas, W.M. Rohsenow and D.D. Lanning, "A Theoretical Study of the Dynamic Growth of a Vapor Film Around a Hot Sphere in a Coolant," Fifth International Heat Transfer Conference, Tokyo, 1974.

T.A. Bjornard, W.M. Rohsenow and N.E. Todreas, "The Pressure Behavior Accompanying the Fragmentation of Tin in Water," Transactions of the American Nuclear Society, Vol. 19, pp. 247-248, 1974.

R. Knapp and N. Todreas, "Thermal Stress Initiated Fracture as a Fragmentation Mechanism in the UO_2 -Sodium Fuel-Coolant Interaction," Nuclear Engineering and Design 35, pp. 69-85, 1975.

M. Corradini, A.A. Sonin and N.E. Todreas, "Proposed Model for Vapor Bubble-Slug Heat Transfer During LMFBR HCDAs," Transactions of the American Nuclear Society, Vol. 26, pp. 367, June 1977.

Introduction

The objective of the continued work on this project at M.I.T. is to experimentally and analytically study the dominant mechanisms in fuel coolant thermal interactions which could lead to vapor explosions. Our exploration of mechanisms is focused in two areas:

- I) Investigations in dynamics of liquid-liquid film boiling.
- II) Possible mechanisms of energy dissipation due to heat transfer during the HCDA expansion.

Work is being performed simultaneously in these areas and will be briefly described below.

I. Investigations in Dynamics of Liquid-Liquid Film Boiling (Michael Corradini)

The spontaneous nucleation theory proposes that vapor explosions can only occur when $T_I > T_{SN}$ for a hot and cold liquid pair (and for the free contact mode only when $T_{SN} < T_I < T_{CRITICAL}$). Henry's experiments demonstrate⁽¹⁾ that the explosive pressure derived from large scale interactions when $T_I > T_{SN}$ do not always match the upper pressure limit ($P_{detected} = P_{sat}(T_{INTERFACE})$). Thus there are inherent incoherencies during the explosion which tend to mitigate the consequences. Other experiments which demonstrate this incoherency are the tin-water experiments of Bjornard⁽²⁾ and Bjorkquist⁽³⁾. From previous work in this contract it was shown that the tin-water data in the free contact mode appears to satisfy the upper bound criterion of the spontaneous nucleation theory.⁽⁶⁾ An approximate transient heat transfer analysis of cooling a tin droplet was done. The results indicated that the explosive fragmentation of the tin droplets began only when $T_I \lesssim T_{CRITICAL}$. This is in agreement with the Henry theory.⁽¹⁾ But again the incoherency and lack of explosive character at higher temperatures has not been explained.

It is proposed to experimentally examine liquid-liquid film boiling behavior to try to delineate the reasons for these incoherencies. One possible cause of these incoherencies is that as T_I increases above T_{SN} the fractional area of random liquid-liquid contact decreases. Thus the chance for a coherent vapor explosion decreases. This is counter balanced by the fact that as temperature (T_I) increases the associated saturation pressure increases (this represents the maximum pressure that can be produced). These countervailing effects could be the cause of the incoherency that is noted at high temperatures. To examine these mechanisms an experimental setup like that depicted on Fig. 1 will be built to examine the frequency and duration of contact in a liquid-liquid system. Electrical probes will be used to determine these parameters.

Another parameter that must be controlled during the experiment is the oxidation of the hot material. An inert gas atmosphere will be necessary to keep oxidation to a minimum. In addition some oxidation will intentionally be allowed to examine its effect on the transition from film boiling and the effect on liquid-liquid contacts.

II. Possible Mechanisms for Heat Transfer to Cold Walls and Fluid in Reactor Vessel (Michael Corradini)

During the core expansion phase of an HCDA the possibility of transient heat transfer to both the cold liquid and solid structure should be investigated to obtain a "best estimate" analysis of the accident's possible work energy output. SRI has demonstrated that these heat transfer effects over a short timescale are large. In our past work we have developed simple heat transfer relations which agree well with Stanford's '72 tests and indicate that heat transfer effects dominate work output effects of the experiments by a ratio of 9:1. Thus even if the tests were not scaled exactly, this analysis indicates that the full scale accident would incur a substantial amount of heat transfer during the expansion phase decreasing the work energy output and the degree of possible vessel damage.

Since the last progress report the work in this general subject has been broadened in scope into four main areas:

- (1) Experimental — a simple experimental apparatus has been constructed to investigate the gas-liquid mixing phenomenon as applicable to the HCDA slug acceleration.

(2) Scaling Laws — the general scaling laws for the modeling of this phenomenon are being investigated.

(3) Analytical — the modeling of the transient heat transfer between the hot vapor and the cold liquid and solid structures are being investigated.

(4) Computer — synthesis of models into prediction of work-energy effects is the final objective.

(1) Experimental

In the original analysis of transient gas-liquid heat transfer the physical mechanism was identified as mixing of the gas-liquid near the interface as the gas expanded. This rapid mixing and area enhancement was seen to be caused by Taylor instabilities as the gas accelerated the liquid slug. The rate of mixing was taken equal to the third stage growth of a Taylor Instability so that

$$\text{Mixing Velocity} \approx C_0 \sqrt{a} L \quad (1)$$

where

a - acceleration of gas-liquid interface

L - initial disturbance wavelength

Only one series of experiments has been done in identifying this mixing behavior in 1948 by Lewis and Taylor.⁽⁵⁾ The results were for larger wavelengths and smaller accelerations than are characteristic of the HCDA events for which this is applied. To determine if the same expression is characteristic of these accelerations a simple experiment has been designed.

The specific purpose is to verify the functional dependence given in Eq. (1) and to determine the range of proportionality constants obtained for the wide acceleration ranges that could occur. The apparatus is shown in Figs. 2 and 3.

The prime variables measured will be pressure and displacement as a function of time. The upper and lower chambers are pressurized to the desired level with a level of water being held at the midpoint by a plastic membrane. A movable paddle will impose a desired standing wavelength on the top water surface. Once this is established the double rupture discs are broken below the bottom chamber. This depressurizes the bottom chambers allowing the water slug to be accelerated downward by the imposed pressure difference. A hi-speed camera and pressure transducers will record the subsequent event so that kinematic data can be gotten from the experiment to determine the desired quantities.

This experiment will hopefully confirm the mixing relationship which we feel is operative during the envisioned HCDA.

(2) Scaling Laws

To examine how this phenomenon in the scale model experiments relates to the full scale hypothetical accident the scaling laws must be examined, and identification be made as to which govern the phenomenon. For instance for the case of the SRI '72 tests with a non-condensable pressure source, the governing equations are (assuming no liquid vaporization):

$$m_{\text{slug}} \frac{d^2 X}{dt^2} = (P_g - P_\infty) A_p \quad (2)$$

$$m_{\text{gas}} \frac{dU_g}{dt} = \frac{d\dot{Q}}{dt} - P_g \frac{dV_g}{dt} \quad (3)$$

where

m_{gas} = mass of expanding gas

m_{slug} = mass of water & piston slug

P_g = pressure of gas

A_p = area of piston (D_p - diameter)

U_g = internal energy of gas

P_∞ = ambient pressure

X = distance traveled by slug

V_g = volume of gas ($= A_p X$)

$\dot{Q}$ = heat transfer from gas

If you make assumption that gas behaves as a perfect gas and that $\dot{Q}$ is described by our model,

$$\frac{d\dot{Q}}{dt} = -C_o \rho_g c_{p_g} (T_g - T_\rho) A_p \sqrt{a D_p}$$

where

T_ρ - temperature of water

a - acceleration of slug $= \ddot{X}$

then Eq. (3) becomes:

$$\left(m_{\text{gas}} \frac{R}{\gamma - 1} \right) \dot{T}_g = \dot{Q} - \dot{W} \quad (3)$$

$$\dot{Q} = -C_o m_g \left(\frac{\gamma R}{\gamma - 1} \right) (T_g - T_p) \left(\frac{\sqrt{\dot{X} D_p}}{x} \right) \quad (4)$$

$$\dot{W} = P_g A_p \dot{X} \quad (5)$$

we can make all three equations dimensionless by dividing through by

$$\frac{P_{go} V_{go}}{\tau} \quad (\text{or} \quad \frac{m_g R T_{go}}{\tau})$$

where

P_{go} = initial pressure of gas (measured quantity)

V_{go} = initial volume of gas (measured quantity)

τ = expansion time of experiment to slug impact
($V_g/V_{go} = 3.14$)

This gives:

$$\frac{dT_g^*}{dt^*} = \frac{dQ^*}{dt^*} - \frac{dW^*}{dt^*} \quad (6)$$

where

$$\frac{dQ^*}{dt^*} = -C_o \left(\frac{\gamma}{\gamma - 1} \right) \frac{(T_g - T_p)}{T_{go}} \left(\frac{\tau (X)^{1/2} \sqrt{D_p}}{x} \right)$$

$$\frac{dW^*}{dt^*} = \frac{P_g}{P_{go}} \left(\frac{\tau \dot{X} A_p}{V_{go}} \right)$$

$$T_g^* = \frac{m_g R}{(\gamma - 1)} \left(\frac{T_g}{P_{go} V_{go}} \right)$$

$$t^* = t/\tau$$

For the momentum equation (2) we get by dividing by

$$\frac{m_g V_{go}}{A_p \tau^2}$$

$$\frac{m^* d^2 X^*}{dt^{*2}} = F^* \quad (7)$$

where

$$m^* = m_{slug}/m_g$$

$$X^* = \frac{A_p X}{V_{go}}$$

$$F^* = \frac{(P_g - P_\infty) A_p^2}{m_g V_{go}^2}$$

Now Eqs. (6) and (7) apply irregardless of the scale of the event since they are dimensionless. We now can extract the scaling laws which will give the parameter variations as a function of scale. Let the ratios of a parameter α at two different scales be denoted by K_α

$$K_\alpha = \frac{\text{value of } \alpha \text{ larger scale}}{\text{value of } \alpha \text{ smaller scale}}$$

Now if we use the scaling laws of the SRI tests

$$K_{P_{go}} = 1$$

$$K_{D_p} = L \quad (L \text{ denotes an increase by the ratio of the linear geometric scale})$$

$$K_{m_{slug}} = L^3$$

$$K_\tau = L$$

we find that

$$K_Q = L^2$$

$$K_W = L^2$$

That is the ratio of heat transfer to work output remains unchanged with a change in scale. Thus it can be expected that the 9:1 ratio of heat transfer to work output during small scale slug expansion will not change with a change in scale. Thus heat transfer will still be a dominant energy dissipation mechanism.

The realistic complications of liquid vaporization and gas condensation are now being examined although the resulting conclusions are not expected to change substantially.

(3) Analytical Modeling

The heat transfer model originally developed for energy exchange with the liquid was based on the assumption that the hot gas comes to local thermal equilibrium with the cold liquid at the interface. Representative heat transfer calculations with these characteristic gas volumes indicate that this assumption is tenuous. Thus rate mechanism models are being concurrently developed. The physical picture of mixing at the interface by the entrainment of gas in liquid (and vice versa) by Taylor Instabilities is still kept as the basis of transient liquid heat transfer (Fig. 4). One such rate mechanism model assumes the entrained droplets can be characterized by spherical gas droplets in liquid. The heat transfer rate is formed by solving the standard conduction problem for a sphere

$$\dot{Q} = C_o A_p \left(1 + \sqrt{\frac{a}{L}} t \right) \frac{4 K_g (T_g - T_L)}{L} \sum_{n=1}^{\infty} e^{-n^2 \pi^2 F_o} \quad (8)$$

where

L = initial disturbance wavelength of the gas-liquid interface

K_g = thermal conductivity of gas

F_o = Fourier No. = $\frac{4 a_t g t}{L^2}$

a_t = thermal diffusivity

This model as well as others will be compared against future experiments at SRI to determine the models' applicability.

For heat transfer to the solid wall Cho⁽⁶⁾ has done an analysis for the case of solid clad (such as in the fission gas plenum) as the heat sink. Another solid structure heat sink in the reactor vessel is the instrument structure above the core. These structures can be treated as semi-infinite masses and a model for heat transfer could be something like

$$Q = \frac{A_{\text{solid}} K_{\text{solid}}}{\sqrt{\pi a_t} t} \frac{(T_g - T_{\text{solid}})}{1 + \sqrt{\frac{K \rho c_{\text{solid}}}{K \rho c_{\text{gas}}}}}$$

This is the simplest conduction model which could be used with more complicated model to be developed.

The purpose of this area of work is to develop heat transfer models which can be utilized in trying to predict the realistic work energy output of the expansion phenomenon. This

model development is the first stage. It then must be coupled either by simple analytic solution or by computer analysis to the core expansion to predict the work energy of the event.

(4) Computer Analysis

The computer will be used to couple expansion effects, heat transfer, condensation and vaporization in a mechanistic prediction of the work energy from an HCDA. At present preliminary runs are being made to eliminate any errors in the solution procedure.

References

- (1) Henry, R.E., Fauske, H.K., "Energetics of Vapor Explosions" AIChE-ASME Heat Transfer Conf., San Francisco, August 1975. 75-HT-66.
- (2) Bjornard, T.A., "An Experimental Investigation of Acoustic Cavitation as a Fragmentation Mechanism of Molten Tin Droplet in Water," MIT-COO-2831-3TR.
- (3) Bjorkquist, G.M., "An Experimental Investigation of the Fragmentation of Molten Metals in Water," TID-26826, 1975.
- (4) Corradini, M., Rohsenow, W., Todreas, N., "Application of Spontaneous Nucleation Theory to Tin-H₂O Experiments," COO-2781-12TR, February 1977.
- (5) Lewis, D.J. et al., "The Instability of Liquid Surfaces when Accelerated in the Direction Perpendicular to their Planes II," Proceedings of the Royal Society of London, A, 202:81, 1950.
- (6) Chen, W.L., Cho, D.H., "Heat Loss to Cold Structures During Fuel-Coolant Interactions," ANL/RAS 73-9, April 1973.

PROPOSED APPARATUS FOR FILM BOILING

FIGURE 1

FIGURE 2