27
7/6/77
25 to 115

UCID- 17458

Lawrence Livermore Laboratory

RECENT STUDIES CONCERNING PLASMA BUILDUP IN A MIRROR FUSION
ENGINEERING RESEARCH FACILITY (FERF)

M. Campbell

May 2, 1977

This is an informal report intended primarily for internal or limited external distribution. The opinions and conclusions stated are those of the author and may or may not be those of the laboratory.

Prepared for U.S. Energy Research & Development Administration under contract No. W-7405-Eng-48.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

RECENT STUDIES CONCERNING PLASMA BUILDUP IN
A MIRROR FUSION ENGINEERING RESEARCH FACILITY (FERF)*

ABSTRACT

Use of a finite Larmor radius buildup code has resulted in revised predictions for the fusion engineering research facility (FERF) plasma. Because of charge-exchange erosion of the plasma surface, the radial density profile is found to be quite flat, in contrast to a previously predicted cubic profile. At a given value of $n\tau$, the required beam current and the fusion neutron flux are significantly larger than previously predicted.

INTRODUCTION

In 1974, Lawrence Livermore Laboratory (LLL) published a report¹ about a possible design for a fusion engineering research facility (FERF) based on a mirror reactor. At that time, little was known either about the radial plasma density profile for such a device or about using a cool, streaming plasma to stabilize the plasma against the drift-cyclotron loss-cone (DCLC) instability. A cubic density profile was assumed and tentatively confirmed by the results of a preliminary version of a finite Larmor radius buildup code. The advent of stream stabilization and recent work to develop a more accurate finite Larmor radius code have warranted a new study to determine plasma characteristics achievable in a FERG mirror fusion reactor (possibly) stabilized by streaming plasma. This paper is a compilation of preliminary results and trends for such plasmas under various initial assumptions and represents a small first step in such a study.

THE FERF REACTOR

The preliminary design work for a FERF mirror fusion reactor is given in detail in Ref. 1; however, a brief description will be given here. Figure 1 shows the physical design of the reactor:

* Studies were performed by the author as a special project during the summer of 1976.

MASTER

Fig. 1. Vertical cross section through the FERF reactor.

- A Yin-Yang magnetic field confines the plasma in a minimum-B well inside the plasma chamber.
- The radius of the plasma, R_p , is about 25 cm; the length is about 420 cm.
- Magnetic field lines fan out through ducts of small cross-sectional area into a set of charge-collection plates. Charged particles escaping the plasma chamber follow the field lines to the collection plates; there, they are neutralized and pumped from the collection chamber by cryopanel. Very little neutral gas can reenter the plasma chamber because of the low fluid conductance of the ducts.
- Injectors are aligned as shown in Fig. 1. The portion of the injected beam that is not trapped in the plasma is allowed to hit the first wall. In steady state, it can be assumed that all passed beam and charge-exchange neutrals hitting the first wall eventually return as cold-gas molecules at the temperature of the first wall. Cold neutrals also enter the chamber because of injector gas leakage. These neutrals eventually become cold ions (via charge exchange or ionization); in about a transit time, they are accelerated out the loss cone by the plasma potential and into the collectors, where they are removed as described previously.

FERF RADIAL DENSITY PROFILES

Charge exchange between a cold neutral and a hot ion leads to plasma loss because the hot charge-exchange neutral often escapes to the wall and the cold ion is lost (as just discussed). Self-consistent solutions generated by a finite Larmor radius code developed by Stallard² indicate that this loss mechanism can cause severe erosion of the plasma surface and can greatly affect the radial density profile, particularly in the boundary region. A more detailed discussion of the effects of surface charge-exchange on plasma integrity can be found in Refs. 3 and 4.

Figure 2 compares two predictions for the density profile for the FEF plasma:

- the "old" profile and the cubic curve that was fitted to it, and
- the "new" profile obtained using Stallard's code.²

The "new" density profile is fairly flat except for a steep boundary region where the density drops a few orders of magnitude over a distance of about

Fig. 2. The "new" and "old" radial density profiles for the FERF plasma profile.

three Larmor radii. This profile is in sharp contrast to the previously predicted cubic profile. As a consequence of this flattened profile, the value of the volume integral

$$\int n^2 dV$$

is much larger (by a factor of three over the cubic case), meaning that for a given $n\tau$ the beam current

$$I = \frac{\int n^2 dV}{n\tau}$$

necessary to support the plasma is also proportionately larger. In return for greater current requirements, one obtains a plasma having more ions, a higher average density, and greater neutron flux than for the cubic case.

STREAM-STABILIZED PLASMA

It has been predicted theoretically and shown experimentally^{4,5} that a plasma with $R_p/\rho_1 \lesssim 40$ will be unstable to the DCLC mode unless stabilized by cool, streaming plasma injected along the field lines. This is particularly true near the boundary where the density gradient is quite large. As a consequence of injecting cold electrons (required for stream neutrality) the $n\tau$ of the plasma ions is reduced. Empirical formulas for calculating $n\tau$ are given in the Appendix to this report. Predicted values for $n\tau$ depend on a variety of initial assumptions. Table 1 gives equilibrium plasma parameters obtained for various interior and boundary $n\tau$'s with Stallard's finite Larmor code. (The boundary region usually has different properties and a different $n\tau$ than the interior region.)

Plots of total ion number and central plasma density versus $n\tau$ are given in Fig. 3 for a fixed value of the boundary $n\tau$. Note that the central density increases linearly with interior $n\tau$.

These equilibria are not, in general, self-consistent because the density of the streaming plasma and the $n\tau$'s are input as constants to the code and the plasma radius is calculated by the code. However, there is calculational difficulty because the correct value for the stream density depends strongly on the ratio R_p/ρ_1 and both $n\tau$ and R_p depend on the stream density.

Table 1. Equilibrium plasma parameters for various $n\tau$, where
total injected current (at 65 keV and several beam positions) = 600 A
stream plasma density = $3 \times 10 \text{ cm}^{-3}$
stream width = 60 cm
neutral gas from injector = 33 A.

Parameter	Boundary $n\tau$; Interior $n\tau$ ($10^{12} \text{ cm}^3 \cdot \text{s}$)						
	1.0; 5.6	1.0; 3.7	1.0; 2.8	1.0; 1.9	5.6; 5.6	2.8; 2.8	1.9; 1.9
Surface charge exchange (A)	46	57	53	58	62	73	66
Beam charge exchange (A)	38	50	56	71	32	48	64
Passed beam (A)	2.4	7.0	10.8	23	0.9	6.6	16.6
Coulomb loss (A)	489	451	451	416	496	463	438
Plasma chamber molecular density (10^{11} cm^{-3})	1.2	1.4	1.5	1.9	0.93	1.46	1.7
Collection chamber molecular density (10^{11} cm^{-3})	2.3	2.25	2.27	2.26	2.34	2.34	2.32
Central plasma density (10^{14} cm^{-3})	3.2	2.7	2.3	2.15	2.5	2.2	2.16
Average midplane radial density (10^{14} cm^{-3})	2.85	2.35	1.9	1.7	2.4	2	1.8
Radius to plasma boundary (cm)	26	27	26	25	34	28	27
Plasma volume (10^5 cm^3)	1.8	1.8	1.9	1.6	3.9	2.6	1.9
Total ions (10^{19})	5.7	5	4.3	3.5	9.8	5.6	4.2

Fig. 3. Density and total ion count of FERF central plasma versus $n\tau_{\text{center}}$ for 600 A injected into 65-keV plasma and $n\tau_{\text{boundary}} = 1.0 \times 10^{12} \text{ cm}^{-3} \cdot \text{s}$.

We found that if the streaming plasma extends beyond the boundary of the hot plasma, it shields the plasma surface from cold neutrals by means of electron ionization. The plasma is thus allowed to expand to a larger radius than it would without the presence of the plasma stream. It may be that by varying the stream width one can obtain different plasma radii to study DCLC criteria as a function of R_p/ρ_i . In Fig. 4, we show a plot of total ions, R_p , and central density versus the attenuation parameter, which is equivalent to the stream density times the stream thickness to the plasma boundary. Note that the central density decreases with greater attenuation due to the increase in R_p .

To find self-consistent solutions, one must pick values for the stream density and $n\tau$ that are mutually consistent and that yield an equilibrium plasma radius and plasma density that are consistent with both. Additionally, one must make some assumptions about what region(s) of the plasma will require stabilization and what electron temperature scaling should be used (this factor is discussed in the Appendix). Thus, we examined four cases for self-consistent solutions: exterior (boundary) stabilization only, both interior and exterior stabilization, and for each of these, "optimistic" and "pessimistic" electron temperature scaling.* Plasma parameters for each solution are given in Table 2.

CONCLUSIONS AND RECOMMENDATIONS

The results of this preliminary investigation can be summarized as follows:

- A flatter density profile with a steeper boundary than previously predicted should be expected in a stream-stabilized FERF. Because of this, a plasma of given radius and $n\tau$ will require much more injected beam to sustain it than would be required for the cubic density profile.
- A higher peak neutron flux and overall neutron production rate also result from the flatter profiles.
- If the streaming plasma extends beyond the hot-plasma boundary, it may be possible to use it to shield the plasma surface somewhat from charge-exchange erosion by cold neutrals.

*The terms "optimistic" and pessimistic" are defined in the Appendix.

Fig. 4. Density and total ion count of FERF central plasma versus attenuation factor for 600 A injected into 65-keV plasma and $n\tau_{\text{boundary}} = 1.0 \times 10^{12}$.

Table 2. Self-consistent equilibria for various initial assumptions,^a where injected beam (at 65 keV and several positions) = 600 A.

Parameter	Boundary or exterior stabilized; $\rho_i = 1.4$ cm		Both interior and exterior stabilized; $\rho_i = 2.4$ cm	
	Optimistic ^b	Pessimistic	Optimistic	Pessimistic
Boundary $n\tau$ ($10^{12}\text{cm}^3\cdot\text{s}$)	1.0	1.0	1.0	1.0
Interior $n\tau$ ($10^{12}\text{cm}^3\cdot\text{s}$)	3.7	2.8	3.3	1.9
Stream plasma density (10^{11}cm^{-3})	3.3	3	0.1	0.1
Surface charge exchange (A)	73	42	19	20
Beam charge exchange (A)	58	50	35	48
Passed beam (A)	11	7	1.7	6.6
Coulomb loss (A)	374	472	523	501
Plasma chamber molecular density (10^{11}cm^{-3})	1.9	2.1	9.2	1.1
Collection chamber molecular density (10^{11}cm^{-3})	2.1	2.5	2.3	2.3
Central plasma density (10^{14}cm^{-3})	3.1	2.5	3.4	2.9
Average midplane radial density (10^{14}cm^{-3})	2.6	2.7	3.1	2.5
Radius to plasma boundary (cm)	24	22	26	26
Plasma volume (10^5cm^{-3})	1.3	1.4	1.5	1.35
Total ions (10^{19})	4	3.7	5.2	4
Neutron flux at plasma surface ($10^{14}\text{cm}^{-2}\cdot\text{s}^{-1}$)	2.7	2.6	4.1	2.7
Neutron flux at first wall ($10^{13}\text{cm}^{-2}\cdot\text{s}^{-1}$)	4.8	3.9	8.6	5.7

^aThese are *not* the only possible self-consistent solutions; many others exist and these are only examples.

^bSee Appendix for definitions of "optimistic" and "pessimistic" applied to electron temperature scaling.

- Self-consistent plasmas and their properties under certain initial assumptions for FERF should be similar to those given in Table 2. The central plasma density can be expected to scale linearly with $n\tau$ as shown in Fig. 3.

Additional studies should be done to determine the optimum plasma ion energy for the stream-stabilized FERF. At higher ion energies, the fusion $\langle\sigma v\rangle$ decrease somewhat, but $n\tau$ tends to increase. If electron drag dominates, the net $n\tau$ will not change much and little will be gained in going to higher ion energies (unless beam trapping improves). On the other hand, if the Coulomb loss $n\tau_i$ is less than the electron drag loss $n\tau_e$, increasing the ion temperature will make $n\tau$ greater and increase the plasma density for a given injected current (up to a point where beam trapping begins to fall off significantly).

APPENDIX. EMPIRICAL FORMULAS FOR CALCULATING nT .

For a stream-stabilized plasma, the electron temperature is given by⁴

$$T_e \approx 3.3 \times 10^{-7} \left(\frac{n_H W_i L_p}{\eta \Delta} \right)^{1/3}$$

$$= 3.3 \times 10^{-7} \left(\frac{\beta B_{vac}^2 L_p}{8\pi \eta \Delta} \right)^{1/3} \text{ keV},$$

where

$$\eta \approx 8 \text{ (experimentally determined),}$$

$$\Delta = \frac{n_w}{n_H} = \frac{\text{stream density}}{\text{hot plasma density}},$$

$$W_i = \text{ion energy in keV,}$$

$$L_p = \text{characteristic plasma length,}$$

$$\beta = p_i / p_{\text{magnetic (vacuum)}}$$

The values for Δ were obtained from the graph shown in Fig. 1-A, which gives values for Δ as a function of β (as defined above) and the *local* value of R_p / ρ_i .⁶ Although these data are for 50-keV ions, the curves are relatively insensitive to ion energy.

Calculation of the characteristic plasma length L_p is somewhat ambiguous; it is somewhat less than $L/2$, the mirror separation half-length. The derivation of the expression for T_e given in Ref. 4 led the author to use the value given by

$$Cl \equiv \frac{L_p}{L} \approx \frac{2}{L} \int_0^{L/2} n(z) dz / n_c,$$

where $n(z)$ is the axial density function, n_c is the central density, and L is the distance between mirrors.

Fig. 1-A. Values for Δ as a function of β and the local value of R_p/ρ_i for $E_{\text{hot}} \approx 50$ keV and $E_{\text{hot}}/E_{\text{stream}} \approx 10$ (from Ref. 6).

Table 1-A gives values for Δ , and T_e for various values of R_p/ρ_i and β (using Fig. 1-A). Where $T_e > 6.5$ -keV, little or no streaming is needed to stabilize a 65-keV plasma.

Electron "drag" of ions into the loss cone has a characteristic $n\tau$ given by

$$n\tau_e \approx 4.4 \times 10^{-7} T_e^{3/2} \ln(W_i/E_h) ,$$

where

$$E_h \approx 3T_e .$$

This scaling of $n\tau_e$ is considered "optimistic" because the $\ln(W_i/E_h)$ term increases $n\tau_e$ above the value of the basic term

$$n\tau_e \approx 4.4 \times 10^{-7} T_e^{3/2} ,$$

which is considered "pessimistic" scaling. The reason for having two scaling laws is that the first (optimistic) is predicted by theory but the second (pessimistic) seems to agree better with 2XIIB experimental results.

A third scaling law can be obtained from 2XIIB experimental results for the boundary $n\tau$:

$$n\tau_B \propto T_e^{3/2} \propto (\beta B_{vac}^2 L_p / \Delta)^{1/2} ,$$

so that

$$n\tau_B = 3.3 \times 10^{11} \left[\left(\frac{\beta}{0.5} \right) \left(\frac{B_{vac}}{20 \text{ kG}} \right)^2 \left(\frac{L_p}{70 \text{ cm}} \right) \left(\frac{3 \times 10^{-3}}{\Delta} \right) \right]^{1/2} .$$

Putting in FERF parameters yields a boundary $n\tau$ of

$$n\tau_{B \text{ FERF}} \approx 1 \times 10^{12} \text{ cm}^{-3} \cdot \text{s} .$$

For plasma regions other than the boundary (or including it, if the correct β is known), one may calculate $n\tau$ by

Table 1-A. Values (from Fig. 1-A) for Cl , Δ , and T_e for various values of R_p/ρ_i and β .

R_p/ρ_i	$\beta =$	0.3	0.5	0.6	0.7	0.8
	$Cl =$	0.36	0.33	0.3	0.3	0.29
7.5	$\Delta (10^{-3})$	1.5	10	7.5	4	1.5
	T_e (keV)	0.8	1.0	1.2	1.45	2.1
10	$\Delta (10^{-3})$	10	6	4.3	1.5	0.3
	T_e (keV)	0.9	1.2	1.4	2.05	3.6
12.5	$\Delta (10^{-3})$	7	3.8	2	0.6	0.1
	T_e (keV)	1.0	1.4	1.8	2.8	5
15	$\Delta (10^{-4})$	50	24	10	2.5	0.4
	T_e (keV)	1.15	1.6	2.25	3.8	6.9
17.5	$\Delta (10^{-4})$	35	16	6.5	1.3	0.3
	T_e (keV)	1.25	1.9	2.6	4.7	7.8
20	$\Delta (10^{-4})$	25	10	3.5	0.5	0.1
	T_e (keV)	1.4	2.2	3.2	6.4	9.8

$$n\tau = (n\tau_e^{-1} + n\tau_c^{-1})^{-1} ,$$

where $n\tau_c$ is the classical Coulomb collisional $n\tau$, proportional to $W_i^{3/2} \ln(R_{\text{mirror}})$.

ACKNOWLEDGMENTS

Special thanks to G. A. Carlson, R. W. Moir, and B. W. Stallard for help in directing this research and for providing information to aid the author.

REFERENCES

1. T. H. Batzer, R. C. Burleigh, G. A. Carlson, W. L. Dexter, G. W. Hamilton, A. R. Harvey, R. G. Hickman, M. A. Hoffman, E. R. Hooper, R. W. Moir, W. J. Silver, B. H. Smith, C. E. Taylor, R. W. Wener, and T. P. Wilcox, *Conceptual Design of a Mirror Reactor for a Fusion Engineering Research Facility (FERF)*, Lawrence Livermore Laboratory, Rept. UCRL-51617 (1974).
2. B. W. Stallard, *Radial Plasma Buildup Code for Neutral Beam Injection into a Mirror Machine*, Lawrence Livermore Laboratory, Rept. UCRL-51784 (1975).
3. B. W. Stallard, Lawrence Livermore Laboratory, Internal Memorandum (September 30, 1974). Readers outside the Laboratory who desire further information on LLL internal documents should address their inquiries to the Technical Information Department, Lawrence Livermore Laboratory, Livermore, California 94550.
4. F. H. Coensgen, *MX Major Project Proposal*, Lawrence Livermore Laboratory, Rept. LLL-PROP-142 (1976).
5. D. E. Baldwin, H. L. Berk, J. A. Byers, R. H. Cohen, T. A. Cutler, N. Maron, L. D. Pearlstein, M. E. Rensink, T. Rognlien, J. J. Stewart, D. Watson, and M. Gerver, *Present Status of Mirror Stability Theory*, Lawrence Livermore Laboratory, Rept. UCID-17038, Rev. 1, (1976).
6. L. D. Pearlstein and B. W. Stallard, Lawrence Livermore Laboratory, private communication (1976).

CKM/jj/vt/jf

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research & Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately-owned rights.

NOTICE

Reference to a company or product name does not imply approval or recommendation of the product by the University of California or the U.S. Energy Research & Development Administration to the exclusion of others that may be suitable.

Printed in the United States of America
Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road
Springfield, VA 22161
Price: Printed Copy \$; Microfiche \$3.00

Page Range	Domestic Price	Page Range	Domestic Price
001-025	\$ 3.50	326-350	10.00
026-050	4.00	351-375	10.50
051-075	4.50	376-400	10.75
076-100	5.00	401-425	11.00
101-125	5.50	426-450	11.75
126-150	6.00	451-475	12.00
151-175	6.75	476-500	12.50
176-200	7.50	501-525	12.75
201-225	7.75	526-550	13.00
226-250	8.00	551-575	13.50
251-275	9.00	576-600	13.75
276-300	9.25	601-up	*
301-325	9.75		

*Add \$2.50 for each additional 100 page increment from 601 to 1,000 pages; add \$4.50 for each additional 100 page increment over 1,000 pages.