(232)
P-13
76-514

USGS-OFR-76-514

✓
UNITED STATES (DEPARTMENT OF THE INTERIOR)
GEOLOGICAL SURVEY.

[Reports - Open
file series]

Station location map and audio-magnetotelluric
data log for Summer Lake Known Geothermal
Resource Area, Oregon

T14
am
Thurs 9/1

By

✓
Robert M. Senterfit and Danny A. Dansereau ✓

Open-File Report No. 76-514
1976

This report is preliminary and has not been
edited or reviewed for conformity with U.S.
Geological Survey standards and nomenclature.

MASTER

DISTRIBUTION OFFICES FOR THE UNITED STATES

NOTICE

PORTIONS OF THIS REPORT ARE ILLEGIBLE. It
has been reproduced from the best available
copy to permit the broadest possible avail-
ability.

270789

key

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
1NS	pa	7.8	10.2	4.7	3.1	-	-	-	-	-	8.8	16.5	7.7
	N	6	8	7	8						7	1	1
	Er	1.0	3.3	0.6	0.3						0.8	-	-
1EW	pa	4.8	4.9	3.2	2.7	-	-	-	-	-	8.4	18.1	4.9
	N	4	6	7	7						7	1	1
	Er	1.7	0.8	0.3	0.3						0.4	-	-
2NS	pa	10.0	12.1	17.4	14.7	23.3	17.9	-	-	-	14.2	28.6	3.6
	N	8	7	7	6	6	1				6	1	1
	Er	1.1	2.1	2.2	3.3	1.7					2.5	-	-
2EW	pa	11.3	9.7	15.9	23.7	33.6	15.6	-	-	-	12.6	21.5	2.4
	N	7	6	8	7	6	2				8	1	1
	Er	2.4	0.6	2.2	4.0	2.8	1.5				0.9	-	-
3NS	pa	5.6	3.2	2.3	4.8	9.9	12.4	-	-	-	9.3	70.8	11.7
	N	9	3	6	7	7	7				7	1	1
	Er	1.4	0.6	0.3	0.5	0.6	1.0				1.4	-	-
3EW	pa	4.8	3.3	2.5	4.8	11.4	18.5	-	-	-	7.6	36.4	56.5
	N	6	7	6	8	8	7				7	1	1
	Er	1.4	1.2	0.4	0.2	1.0	2.5				0.3	-	-
4NS	pa	30.8	22.2	22.4	39.0	74.2	113.3	-	-	-	13.4	30.7	2.1
	N	9	6	6	5	6	7				8	1	1
	Er	14.9	4.0	4.5	10.0	13.1	14.0				0.7	-	-
4EW	pa	28.3	27.5	24.1	21.0	24.9	26.7	-	-	-	4.4	6.9	18.2
	N	6	6	6	6	7	6				7	1	1
	Er	9.2	9.0	3.9	4.4	1.1	3.7				0.6	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
5NS	pa	6.9	13.7	18.6	15.6	26.9	38.7	-	-	-	17.8	3.6	4.9
	N	3	6	6	6	7	7				7	1	1
	Er	0.9	4.5	3.3	2.5	4.7	3.5				2.8	-	-
5EW	pa	13.6	14.0	24.2	18.2	23.8	28.3	-	-	-	9.7	14.2	0.6
	N	6	6	9	7	9	7				8	1	1
	Er	1.6	2.3	3.1	2.5	1.5	2.9				1.6	-	-
6NS	pa	19.8	27.2	28.6	36.0	101.2	-	-	-	-	5.7	13.6	1.0
	N	8	6	4	4	4					4	1	1
	Er	2.3	3.9	2.9	4.2	1.5					0.4	-	-
6EW	pa	25.3	22.9	21.5	59.2	123.3	-	-	-	-	1.3	2.5	6.5
	N	6	6	4	6	6					5	1	1
	Er	4.6	3.9	1.7	6.7	8.7					0.2	-	-
7NS	pa	6.2	5.4	5.6	5.9	9.6	-	-	-	-	8.3	9.7	20.3
	N	8	6	7	6	6					5	1	1
	Er	0.6	0.7	1.0	0.3	0.5					0.3	-	-
7EW	pa	6.5	7.6	4.1	8.4	21.1	-	-	-	-	14.1	24.0	8.9
	N	8	6	6	6	6					6	1	1
	Er	9.2	2.8	0.7	2.5	1.6					0.4	-	-
8NS	pa	9.3	6.3	7.9	5.3	6.9	-	-	-	-	19.0	34.8	15.5
	N	6	4	7	6	7					5	1	1
	Er	2.5	0.7	1.5	0.4	0.4					2.2	-	-
8EW	pa	8.7	4.3	5.0	6.3	9.5	-	-	-	-	7.6	14.9	22.8
	N	6	7	7	7	3					4	1	1
	Er	1.7	0.6	0.5	0.6	0.3					0.1	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Reliuric line orientation indicated with station numbers.														
Sta. No.		FREQUENCY												
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K	
9NS	pa	2.9	4.6	3.4	2.9	4.4	3.8	-	-	-	11.0	9.1	19.6	
	N	7	6	6	6	6	6				6	1	1	
	Er	0.4	1.0	0.4	0.2	0.1	0.4				6	1	1	
9EW	pa	6.1	2.5	2.3	2.4	2.9	2.8	-	-	-	0.4	-	-	
	N	7	5	8	6	6	6				7.2	12.3	14.8	
	Er	0.7	0.4	0.2	0.5	0.4	0.1				6	1	1	
10NS	pa	20.7	21.3	19.4	18.6	-	-	-	-	-	0.2	-	-	
	N	6	7	4	5						3.2	10.5	6.8	
	Er	3.5	4.4	2.4	2.2						5	1	1	
10EW	pa	19.4	22.6	13.0	14.1	-	-	-	-	-	0.3	-	-	
	N	8	6	6	6						1.0	1.6	5.5	
	Er	3.1	4.5	1.3	3.1						6	1	1	
11NS	pa	8.8	13.1	9.5	9.2	15.4	22.2	-	-	-	0.1	-	-	
	N	9	6	6	6	6	5				9.9	14.4	6.6	
	Er	1.7	2.5	1.6	1.7	1.0	0.5				5	1	1	
11EW	pa	20.5	11.5	10.7	18.3	23.9	31.2	-	-	-	0.8	-	-	
	N	10	8	7	7	6	5				51.0	56.1	42.8	
	Er	2.4	1.3	1.3	1.4	2.4	1.1				5	1	1	
12NS	pa	3.1	5.7	4.8	6.7	9.4	12.2	-	-	-	3.7	-	-	
	N	7	6	6	6	7	6				8.6	29.8	1.9	
	Er	0.3	0.9	0.8	0.1	2.3	0.9				5	1	1	
12EW	pa	6.9	4.0	4.7	4.5	5.5	4.6	-	-	-	2.2	-	-	
	N	8	6	6	6	5	6				7.4	12.8	7.2	
	Er	1.3	0.5	0.7	0.6	0.8	0.5				5	1	1	

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
13NS	pa	10.5	12.6	9.6	8.7	14.5	16.3	-	-	-	4.7	52.0	11.9
	N	6	6	6	6	6	7				4	1	1
	Er	0.9	0.2	0.8	1.7	0.7	1.7				0.4	-	-
13EW	pa	9.6	6.3	6.3	6.2	8.0	14.5	-	-	-	5.4	15.5	13.2
	N	7	6	6	6	6	6				5	1	1
	Er	1.5	1.0	1.0	0.4	0.9	1.2				0.3	-	-
14NS	pa	15.8	-	6.5	9.1	6.9	3.7	-	-	-	3.7	-	4.6
	N	3		6	3	4	5				8		1
	Er	4.4		2.1	2.3	0.3	0.1				0.1		-
14EW	pa	24.2	15.1	12.7	12.6	9.5	6.1	-	-	-	3.5	15.8	101.4
	N	8	5	5	1	5	5				6	1	1
	Er	4.1	1.7	2.3	-	1.6	0.1				0.2	-	-
15NS	pa	60.9	45.8	28.5	23.8	23.0	11.9	-	-	-	1.6	5.6	1.4
	N	3	5	3	4	5	6				6	1	1
	Er	9.7	2.5	12.1	3.0	4.0	0.9				0.1	-	-
15EW	pa	9.5	12.6	13.1	20.4	12.4	8.2	-	-	-	2.3	5.8	2.4
	N	5	4	4	5	6	7				8	1	1
	Er	13.2	2.0	1.8	3.9	3.5	0.6				0.2	-	-
16NS	pa	5.6	7.7	15.4	13.3	25.9	28.7	-	-	-	23.1	52.0	22.7
	N	8	4	5	7	6	7				4	1	1
	Er	1.2	0.8	3.4	0.8	4.2	2.3				2.4	-	-
16EW	pa	9.6	5.9	8.8	9.5	25.4	27.7	-	-	-	3.5	9.9	3.6
	N	5	6	6	6	5	2				3	1	1
	Er	1.1	0.8	1.2	0.5	3.7	9.4				0.1	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

pa = observed apparent resistivity in ohm-metres

N = number of observations

Er = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

Sta. No.		FREQUENCY											
		7.5	10	14	27	76	285	685	1.2K	3.3K	6.7K	10.2K	18.6K
17NS	pa	6.9	9.5	18.0	13.2	9.7	4.1	-	-	-	21.1	24.6	9.0
	N	3	3	5	6	8	7				6	1	1
	Er	1.1	0.9	4.8	2.5	0.5	0.4				3.7	-	-
17EW	pa	5.7	6.7	7.9	6.4	6.4	4.3	-	-	-	15.6	57.1	42.7
	N	4	4	6	6	7	6				8	1	1
	Er	1.6	0.8	1.3	1.3	0.4	0.4				2.3	-	-
18NS	pa	12.0	7.4	18.9	27.2	63.0	48.1	-	-	-	22.8	52.0	17.8
	N	10	3	3	2	5	4				6	1	1
	Er	0.6	2.0	1.1	3.8	7.7	6.6				2.3	-	-
18EW	pa	15.0	16.3	20.4	57.3	52.2	43.1	-	-	-	10.1	28.1	133.5
	N	8	4	5	3	3	1				7	1	1
	Er	2.5	1.8	6.2	14.2	4.5	-				1.5	-	-
19NS	pa	9.9	7.9	17.1	11.6	18.4	18.6	-	-	-	23.4	6.1	25.1
	N	7	3	7	4	4	6				3	1	1
	Er	1.3	0.8	3.1	2.9	6.5	2.9				3.4	-	-
19EW	pa	13.9	7.7	12.1	14.8	29.9	43.5	-	-	-	29.2	41.9	24.8
	N	6	4	6	4	6	6				5	1	1
	Er	1.0	0.9	1.2	5.2	3.4	1.3				3.2	-	-
20NS	pa	7.1	7.4	8.9	9.3	16.9	19.4	-	-	-	55.3	29.8	24.8
	N	5	5	6	9	7	5				7	1	1
	Er	1.6	1.1	1.3	0.7	2.7	1.8				7.6	-	-
20EW	pa	8.5	3.6	6.6	7.3	10.7	13.0	-	-	-	6.5	18.4	12.2
	N	6	5	7	7	6	6				8	1	1
	Er	3.1	0.5	1.1	0.6	0.5	1.4				0.7	-	-

U.S. GEOLOGICAL SURVEY A.M.T. DATA LOG

ρ_a = observed apparent resistivity in ohm-metres

N = number of observations

E_r = standard error in ohm metres

- = no data

"NOTE" - Telluric line orientation indicated with station numbers.

[illegible]

Figure 1