10/9-28-92850

ORNL/TM-12160

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

DNA Radiation Environments Program Spring 1990 2-Meter Box Experiments and Analyses

R. T. Santoro
S. Y. Whitaker

MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

ORNL/TM--12160

DE92 041229

Engineering Physics and Mathematics Division

**DNA RADIATION ENVIRONMENTS PROGRAM
SPRING 1990 2-METER BOX EXPERIMENTS
AND ANALYSES**

R. T. Santoro

S. Y. Whitaker
Clark Atlanta University
Atlanta, GA 30314

Date Published: September 1992

Prepared by the
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC
for the
U. S. DEPARTMENT OF ENERGY
under contract DE-AC05-84OR21400

MASTER

EP

CONTENTS

	<u>Page</u>
CONTENTS	iii
LIST OF TABLES	v
ABSTRACT	ix
I. INTRODUCTION	1
II. DETAILS OF THE MEASUREMENTS	2
II.A. APRF MEASUREMENTS	3
II.B. HDL MEASUREMENTS	3
II.C. BTI/DREO MEASUREMENTS	4
II.D. ETCA MEASUREMENTS	4
II.E. COMPARISONS OF MEASURED DOSES	4
II.F. OBSERVATIONS	5
III. DETAILS OF THE CALCULATIONS	6
III.A. CALCULATIONAL INTERCOMPARISON	6
IV. COMPARISONS OF MEASURED AND CALCULATED DOSES AND REDUCTION FACTORS	8
IV.A. TLD Gamma-Ray Measurements	8
IV.A.1. Comparisons with APRF Measurements	8
IV.A.2 Comparisons with HDL Measurements	9
IV.A.3 Comparisons with BTI/DREO Measurements	9
IV.A.4 Comparisons with ETCA Measurements	10

IV.B. BD-100R Bubble Detector Neutron Measurements	10
V. CONCLUSIONS AND RECOMMENDATIONS	11
VI. REFERENCES	46
APPENDIX A	48

LIST OF TABLES

<u>Table</u>	<u>Page</u>
1. Details of the 2-Meter Box and Other Experimental Information	12
2. Details of the RT-200 Canadian Humanoid Phantom	13
3. APRF Measurements of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	14
4. HDL Measurements of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	15
5. BTI/DREO Measurement of Neutron Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	16
6. BTI/DREO Measurement of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	17
7. ETCA Measurement of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	18
8. Ratios of the Measured Gamma-Ray Doses Free-Field Measurements/Phantom Facing the Reactor	19
9. Ratios of the Measured Gamma-Ray Doses Phantom in the 2m Box/Facing the Reactor	19
10. Ratios of the Measured Gamma-Ray Doses Free-Field Measurements/Right-Side Facing the Reactor	20
11. Ratios of the Measured Gamma-Ray Doses Phantom in the 2-m Box/Right- Side Facing the Reactor	20
12. ORNL Calculations of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	21
13. ORNL Calculations of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	22

<u>Table</u>	<u>Page</u>
14. SAIC Calculations of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	23
15. SAIC Calculations of Gamma-Ray Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	24
16. Ratios of the Calculated Gamma-Ray Doses (Dose rates in mrad(Ti)/kWh)	25
17. Ratios of the Calculated Gamma-Ray Doses (Dose rates in mrad(CaF ₂)/kWh)	25
18. ORNL Calculations of Neutron Dose Rate in the Free-Field and as Function of Position on the RT-200 Humanoid Phantom	26
19. SAIC Calculations of Neutron Dose Rate in the Free-Field and as a Function of Position on the RT-200 Humanoid Phantom	27
20. Ratios of the Calculated Neutron Doses (Dose rates in mrad(Ti)kWh)	28
21. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field/Phantom Facing Reactor Comparisons with APRF TLD Measurements Doses in mrad _{Ti} /kWh	29
22. Measured and Calculated Gamma-Ray Doses and Reduction Factors In-Box/Phantom Facing Reactor Comparisons with APRF TLD Measurements Doses in mrad _{Ti} /kWh	30
23. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field/Right-Side Facing Reactor Comparisons with APRF TLD Measurements Doses in mrad _{Ti} /kWh	31
24. Measured and Calculated Gamma-Ray Doses and Reduction Factors In-Box/Right-Side Facing Reactor Comparisons with APRF TLD Measurements Doses in mrad _{Ti} /kWh	32
25. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field Phantom Facing Reactor Comparisons with HDL TLD Measurements Doses in mrad _{CaF} /kWh	33

<u>Table</u>	<u>Page</u>
26. Measured and Calculated Gamma-Ray Doses and Reduction Factors In-Box/Phantom Facing Reactor Comparisons with HDL TLD Measurements Doses in $\text{mrad}_{\text{CaF}}/\text{kWh}$	34
27. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field/Right-Side Facing Reactor Comparisons with HDL TLD Measurements Doses in $\text{mrad}_{\text{CaF}}/\text{kWh}$	35
28. Measured and Calculated Gamma-Ray Doses and Reduction Factors In-Box/Right-Side Facing Reactor Comparisons with HDL TLD Measurements Doses in $\text{mrad}_{\text{CaF}}/\text{kWh}$	36
29. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field/Phantom Facing Reactor Comparisons with BTI/DREO TLD Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	37
30. Measured and Calculated Gamma-Ray Doses and Reduction Factors In-Box/Phantom Facing Reactor Comparisons with BTI/DREO TLD Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	38
31. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field/Right-Side Facing Reactor Comparisons with BTI/DREO TLD Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	39
32. Measured and Calculated Gamma-Ray Doses and Reduction Factors In-Box/Right-Side Facing Reactor Comparisons with BTI/DREO TLD Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	40
33. Measured and Calculated Gamma-Ray Doses and Reduction Factors Free-Field/Phantom Facing Reactor Comparisons with ETCA TLD Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	41
34. Measured and Calculated Neutron Doses and Reduction Factors Free-Field/Phantom Facing Reactor Comparisons with BTI/DREO Bubble Detector Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	42
35. Measured and Calculated Neutron Doses and Reduction Factors In-Box/Phantom Facing Reactor Comparisons with BTI/DREO TLD Bubble Detector Measurements Doses in $\text{mrad}_{\text{Ti}}/\text{kWh}$	43

Table

Page

36.	Measured and Calculated Neutron Doses and Reduction Factors Free-Field/Right-Side Facing Reactor Comparisons with BTI/DREO Bubble Detector Measurements Doses in $\text{mrad}_{\text{Tl}}/\text{kWh}$	44
37.	Measured and Calculated Neutron Doses and Reduction Factors In-Box/Right-Side Facing Reactor Comparisons with BTI/DREO Bubble Detector Measurements Doses in $\text{mrad}_{\text{Tl}}/\text{kWh}$	45

ABSTRACT

This report summarizes the Spring 1990 2-m Box Experiments performed at the Army Pulse Radiation Facility (APRF) at Aberdeen Proving Ground, Maryland. These studies were sponsored by the Defense Nuclear Agency (DNA) under the Radiation Environments Program to obtain measured data for benchmarking the Adjoint Monte Carlo Code System, MASH, Version 1.0. MASH was developed as the Department of Defense and NATO code system for calculating neutron and gamma-ray radiation fields and shielding protection factors for armored vehicles and military structures against nuclear weapon radiation. In the experiments, neutron and gamma-ray dose and reduction factors were measured in the free-field and as a function of position on an anthropomorphic phantom that was placed outside and inside the steel-walled 2-m box. The data were acquired at a distance of 400-m from the APRF reactor. The measurements were performed by APRF, Bubble Technology Industries, the Defence Research Establishment Ottawa, Etablissement Technique Central de l'Armement, and Harry Diamond Laboratory. Calculations were carried out by the Oak Ridge National Laboratory and Science Applications International Corporation.

The purpose of these experiments was to measure the neutron and gamma-ray dose as a function of detector location on the phantom for cases when the phantom was standing in the free-field and inside of the box. Neutron measurements were made using a BD-100R bubble detector and gamma-ray measurements were made using thermoluminescent detectors (TLD). Calculated and measured data were compared in terms of the C/M ratio. DNA mandated that C/M values of $\pm 20\%$ define the acceptable limits for the comparison of the dose and reduction factor data and for qualifying the MASH code in replicating integral parameters.

Neutron measurements were made only by Bubble Technology Industries while gamma-ray measurements were made by all of the teams of experimentalists. The measured gamma-ray doses exhibited considerable spread and C/M ratios often exceeded 20%. The calculated gamma-ray data reported by ORNL and SAIC were consistently in agreement. The measured gamma-ray doses as a function of detector location varied significantly but when the average measured and calculated doses and reduction factors were compared, the C/M ratio was within $\pm 20\%$. The neutron doses and reduction factors showed a similar behavior but, on the average, agreement between the measured and calculated data was within the accepted tolerance. In those cases where large discrepancies occurred in the comparisons of reduction factors, the differences were traceable to disagreement in the measured and calculated free-field doses.

Accepting the $C/M \leq 20\%$ criterion and the consequences of this study, it is recommended that MASH Version 1.0 be adopted by the DOD and NATO for calculating neutron and gamma-ray doses and reduction factors for armored vehicles and other shielded structures.

I. INTRODUCTION

As part of the Radiation Environments Program (REP) sponsored by the Defense Nuclear Agency (DNA), a series of "benchmark" experiments were performed at the Army Pulse Radiation Facility (APRF) at Aberdeen Proving Grounds, Maryland. The purpose of these experiments was to measure neutron and gamma-ray differential and integral spectra, kerma, and dose in the free-field and inside a cubical shaped steel-walled box at a distance of 400 meters from the APRF reactor. The experiments were performed for different box configurations, i.e., unlined and lined and with and without a phantom positioned inside the box. The box has been accepted as the "NATO standard test bed" and the 400 meter distance is defined as the "NATO standard reference point". In all of the experiments, measured data are obtained by experimentalists from different organizations that participate in the REP. The measured data are being used to benchmark the Monte Carlo Adjoint Shielding code system - MASH⁽¹⁾ that is being validated under this effort. MASH was developed to replace the Vehicle Code System (VCS)^(2,3) for estimating radiation effects inside armored vehicles and other shielded configurations of interest to the military.

In previous reports (Refs 4-6), measured and calculated data were compared for the first in the series of experiments that were performed in the Fall of 1989. Spectra and kerma (dose) were measured using different types of detectors in both the free-field and inside the 2-meter box. This report summarizes the second in the series of experiments. Measurements of neutron and gamma-ray dose as a function of position on an RT-200 Canadian Humanoid Phantom⁽⁷⁾ (hereafter referred to as the phantom) that was placed in the standing position in the center of the 2-meter box were performed at the APRF for different box-phantom orientations. These measurements were made during the period 7 May 1990 to 18 May 1990, and are referred to as the Spring 1990 experiments. Measured data were obtained by experimentalists from APRF, Harry Diamond Laboratory (HDL), Bubble Technology Industries (BTI) Canada, the Defence Research Establishment Ottawa (DREO), and the Etablissement Technique Central de l'Armement (ETCA). Calculations were carried out by analysts from Oak Ridge National Laboratory (ORNL) and Science Applications International Corporation (SAIC). The organizations and scientists that participated in this study are identified in Appendix A.

Details of the Spring 1990 experiments and comparisons among the data acquired by the different teams of experimentalists are presented in Section II. The calculated data obtained by ORNL and SAIC are compared and discussed in Section III. The measured and calculated data are compared in Section IV and conclusions, observations, and recommendations resulting from this study are presented in Section V.

II. DETAILS OF THE MEASUREMENTS

The 2-meter box assembly used in the Spring 1990 study was the same as that used in the Fall 1989 investigation and described in Refs. 4-6 but, for this study, a phantom was placed in the standing position at the center of the box. Measurements and calculations of neutron and gamma-ray dose were made as a function of detector position on the body of the phantom with the phantom located either in the free-field or inside of the box. One face of the box was always perpendicular to the reactor-400m-test site axis and the phantom was positioned inside the box either facing the reactor or turned 90-degrees with the right shoulder facing the radiation source. All of the data were collected at the 400-m reference point. Details of the box and other information concerning the experiments are summarized in Table 1. The RT-200 phantom, including its dimensions, material composition, and the locations on the phantom where doses were measured are described in Table 2.

Ground contour and terrain details, including the position of the reactor relative to the 400 meter test site, were the same as those used in the Fall 1989 investigation and reported in Refs. 4-6. Atmospheric conditions (air temperature, barometric pressure, and relative humidity) and soil moisture content were monitored and recorded by the APRF staff during the measurements. The locations where ground moisture data were measured are shown in the inset in Table 1. Meteorological data recorded during the measurements are summarized in Ref. 8. The meteorological data are mean values obtained from observations taken at regular intervals during the course of the measurements. The soil moisture content during all experiments was relatively constant; on the order of 35% by weight of dry soil. In all cases, the reactor was operated at steady state power levels and for run durations sufficient to assure acceptable statistical accuracy in the measured data.

The APRF staff coordinated the sequence of experiments and reactor operating conditions to assure minimum interference between participating teams of experimentalists and to optimize reactor operating conditions to achieve experimental goals.

Four box-phantom orientations were studied in the sequence of measurements.

- A. Free-field measurement. Phantom located at a distance of 10-m to the side of the box in the standing position facing the reactor.
- B. Phantom inside the 2-m box in the standing position facing the reactor.
- C. Free-field measurement. Phantom located at a distance of 10-m to the side of the 2-m box in the standing position with the right shoulder facing the reactor.
- D. Phantom inside the 2-m box in the standing position with the right shoulder facing the reactor.

Measurements were also made of the free-field dose and the free-field (attenuated) dose in the box. The free-field dose was measured by placing dosimeters at a distance of 5.40-m

to the side of the 2-m box at a height of 1.15-m above the ground and a distance of 400-m from the reactor. The attenuated dose (hereafter referred to as the FF-Box dose) was measured by placing dosimeters inside the 2-m box at a height above the floor of the box of 0.68-m and at a distance of 0.70-m from the axis of symmetry of the box.

II.A. APRF MEASUREMENTS

The APRF team utilized $\text{CaF}_2\text{:Mn}$ (3.18mm x 3.18mm x 0.89mm) Harshaw thermoluminescent dosimeters (TLD) to measure the gamma-ray free-field dose, FF-Box dose, and the dose as a function of position on the phantom for the four box-phantom configurations described above. Detailed descriptions of the methods to determine the sensitivity of the TLD's for on surface and in cavity locations on the phantom and the procedure for calibrating the dosimeters using a ^{137}Cs gamma-ray source may be found in the reports by Oliver⁽⁹⁾ and Kazi⁽¹⁰⁾.

The gamma-ray dose rates in the free-field and as a function of position on the phantom for the different box-phantom configurations are summarized in Table 3. These data were obtained by placing four TLD chips at each location, averaging the integrated TLD readings (in nanocoulombs), correcting for the background, and converting to dose in units of mrad(tissue)/kWh. The APRF staff estimated the accuracy of the TLD system to be better than $\pm 10\%$ for all measurements. No corrections were made for neutron effects or effects due to the energy dependence of the gamma-ray spectrum.

II.B. HDL MEASUREMENTS

HDL employed $\text{CaF}_2\text{:Mn}$ thermoluminescent dosimeters (Harshaw TLD-400) to measure the dose as a function of position on the phantom as well as the free field and FF Box doses⁽¹¹⁾. To achieve greater sensitivity, HDL employed TLD's having dimensions of 6.35 mm x 6.35 mm x 1.78 mm, or eight times the volume of the 3.18mm x 3.18mm x 0.89mm TLD dosimeter used by the APRF team. For the free field measurements, the TLD's were enclosed in 1 g/cm²-thick aluminum capsules. For the phantom measurements, the dosimeters were wrapped in four layers of 25 μm -thick aluminum foil. The TLD's were placed adjacent to those being used by the APRF team and exposed for the same reactor power-run-times as reported in the APRF measurements. HDL did, however, correct the TLD measurements to account for the effects of thermal neutrons.

The results of the HDL gamma-ray dose rate measurements are summarized in Table 4. Note that the units of dose rate are in mrad(CaF_2) per kWh. The dose rates given in Table 4 must be multiplied by a factor of 1.149 to convert these data to dose rate in units of mrad(Ti) per kWh (Ti = tissue) for direct comparison with the results reported by APRF, BTI/DREO, and ETCA.

II.C. BTI/DREO MEASUREMENTS

Bubble Technology Industries (BTI) and DREO collaborated to measure neutron and gamma ray doses in the free field and as a function of position on the phantom. Neutron dose data were acquired using BD-100R bubble detectors developed by the BTI staff and the gamma-ray dose was measured using TLD-400 dosimeters provided by DREO. Details of the experimental procedures and related data are found in Ref. 7. The neutron dose rate as a function of position on the phantom for the different box-phantom configurations obtained with the BD-100R detectors is summarized in Table 5. The gamma-ray dose rate results obtained using TLD's are summarized in Tables 6. Only the data reported in Ref. 7 are used in these comparisons.

II.D. ETCA MEASUREMENTS

ETCA made only one measurement of the dose rate as a function of position on the RT-200 phantom: i.e., for the configuration with the phantom in the free field, facing the reactor⁽¹²⁾. ETCA used Harshaw TLD 700 dosimeters (6.4 mm x 6.4 mm). The results of the measurements are summarized in Table 7.

II.E. COMPARISONS OF MEASURED DOSES

The dose rates reported by each experimental team are compared in terms of the ratios of the measured (M) data; i.e., $(M_{\text{Team 1}}/M_{\text{Team 2}})$ ratios for the various free-field and phantom TLD locations. Only the gamma-ray results are compared here. Neutron measurements that were made by the BTI/DREO team are compared with the calculated neutron dose rate results elsewhere in this report.

The ratios of the measured gamma-ray doses, compared in terms of the APRF/HDL, APRF/BTI, APRF/ETCA, and HDL/BTI, are given in Tables 8 to 11 for the experiment configurations A through D, described above. ETCA reported results only for configuration A. To equate the data on a consistent basis, the dose rates reported by HDL (given in Table 4) have been multiplied by a factor of 1.149 to convert from units of $\text{mrad}(\text{CaF}_2)/\text{kWh}$ to $\text{mrad}(\text{Ti})/\text{kWh}$. Also reported is the average and standard deviation (STD) of the ratios of the measured TLD gamma-ray doses on the phantom.

The doses measured in the free-field with the phantom facing the reactor are shown in Table 8. The results obtained by APRF, HDL, and ETCA agree with each other on the average within nominally $\pm 20\%$ at nearly all of the detector locations. Exceptions occur at the mid-head (MH) location in the APRF/ETCA comparison where ETCA overestimates the dose relative to the APRF measurements. The BTI doses disagree with the data reported by APRF and HDL; with BTI consistently underestimating the doses.

Table 9 summarizes the in-box, phantom facing the reactor experiment. The doses measured by APRF, HDL, and BTI are in fairly good agreement for most of the locations reported for this measurement, and except for a few locations, the data agree on the average, within $\pm 20\%$. The APRF and BTI data are in slight disagreement for the free-field measurement and at the mid-gut (MG) and left wrist (LW) detector locations. The HDL and BTI data show the largest disagreement at the left wrist location.

The measured data obtained by the different teams for the free-field case with the right side of the phantom facing the reactor are compared in Table 10. The APRF and HDL dose measurements on and in the phantom are in moderately good agreement. For the case when the phantom was facing the reactor, the average of the doses agreed within 3% compared to 12% for this phantom orientation. The results obtained by the BTI team are consistently lower than the doses reported by APRF but are now in better agreement with the results reported by HDL. In the free-field results reported by all of the teams, the spread among the data are larger when the phantom is facing away from the reactor than for the case when it is facing the reactor. This may be due, in part, to the placement of the TLDs which result in the shielding of some of the detectors by others.

Finally, the measured data for the in-box measurements with the phantom's right shoulder facing the reactor are given in Table 11. For this measurement, phantom doses measured by the three teams are on the average in good agreement except at the right wrist location in the HDL/BTI comparison where BTI overestimates the dose relative to the HDL value.

II.F. OBSERVATIONS

The largest disparities in the data occur among the free-field doses with no obvious correlation with experiment. The in-box free-field data, on the other hand, are in much better agreement with the largest differences being on the order of 7%. What is most apparent is the large spread in the data and the nonuniform determinations of the dose at TLD positions on the phantom. When the phantom TLD dose ratios are averaged (see bottom of tables), however, the overall agreement among the data is noticeably improved with the exception of the APRF/BTI and HDL/BTI comparisons in Table 8 and the APRF/BTI comparison in Table 10. For all of the cases, the APRF and HDL doses are in good agreement assuming the conversion of the HDL dose from $\text{mrad}(\text{CaF}_2)/\text{kWh}$ to $\text{mrad}(\text{Ti})/\text{kWh}$ is legitimate. Correspondingly, the HDL and BTI data are in good agreement except for the free-field measurement given in Table 9.

The procedure for selecting the ratios among the data in Tables 8 - 11 was entirely arbitrary so the measured data must be carefully examined to reveal the large spread that actually exists between some of the measurements. A further discussion of the spread among the measured data is presented in Section V.

III. DETAILS OF THE CALCULATIONS

Analyses of the 2-m Box/Phantom experiments were carried out separately by researchers from the Oak Ridge National Laboratory and Science Applications International Corporation. Both teams used the MASH code to estimate the dose in the free-field and at detector locations on the phantom for the four experimental configurations described in the previous section. The purpose of conducting two separate analyses was to provide a cross-check of the analytic results and to assure a consistent application of the MASH code system in the benchmarking process.

All of the calculations were performed using the MASH code system, Version 1.0⁽¹⁾ that is maintained on the Los Alamos National Laboratory (LANL) CRAY computer. At present, this is the only authorized version of the code system. The transport calculations were carried out using the DABL69 (ENDF/B-V) cross-section library⁽¹³⁾ (P₃) that is also maintained on the LANL CRAY computer. The experimental geometry, including the 2-m Box and the RT-200 Phantom were replicated in detail using the combinatorial geometry options in the MASH code system. The box and phantom geometries are described in detail in Ref. 8. ORNL and SAIC each used slightly different approaches to calculate the doses in the phantom but both approaches were within the existing capability of the MASH code system.

Air-over-ground calculations used to estimate the neutron and gamma-ray fluence in the free-field and on a coupling surface surrounding the box took into account the air and soil moisture content at the time of the measurements. The Monte Carlo (MORSE) calculations to determine the doses at the detector positions on the phantom both inside and outside the box generated and tracked a sufficiently large number of primary source particles to assure adequate sampling over all energy groups. Energy dependent relative importance factors were used to increase the frequency of sampling the adjoint source particles from energy groups having the most significant effect on the dose response function. The secondary particle production probability was set to 1.0 for all regions and energy groups and the in-group energy biasing option in MORSE was turned on for all calculations. Region dependent and energy independent splitting and Russian Roulette parameters were used to improve the statistical accuracy of the Monte Carlo calculations. These options produced an escaping particle to source particle ratio of nominally one.

Statistical uncertainties on the integral neutron and gamma-ray doses were consistently less than 3% for all calculations.

IIIA. CALCULATIONAL INTERCOMPARISON

The TLD gamma-ray doses calculated by ORNL and SAIC as a function of detector location are given in Tables 12 - 15. Tables 12 and 14 report the calculated dose rates in units of mrad(Tissue) per kWh while the data in Tables 13 and 15 summarize the calculated dose rates in units of mrad(CaF₂) per kWh. Also given in each table are the averages and standard deviations of the dose rates on the phantom. These are simple averages and no attempt was made to justify the doses as a function of TLD location on the phantom.

Table 16 compares the data in Tables 12 (ORNL) and 14 (SAIC) in terms of the ratio of the dose rates calculated by ORNL to the dose rates calculated by SAIC. The ratios of the calculated dose rates from Tables 13 (ORNL) and 15 (SAIC) are summarized in Table 17. The estimates of the dose rates on the phantom are generally in very good agreement.

Tables 18 and 19 show the calculated neutron dose rates as a function of experiment and detector location on the phantom obtained by ORNL and SAIC, respectively and Table 20 compares these data in terms of the ratios of the ORNL results to the SAIC results.

The neutron and gamma-ray dose rates calculated by each team are in very good agreement and indicate consistent replication of the experimental configuration, reactor source term, and consistent application of the MASH code system and data.

IV. COMPARISONS OF MEASURED AND CALCULATED DOSES AND REDUCTION FACTORS

A considerable amount of data were acquired by each team of experimentalists in the investigation of the four box-phantom configurations. To facilitate the comparisons of the measured and calculated doses and reduction factors, the analytic results are compared with the measured results separately as a function of the team of experimentalist and box-phantom configuration. Given in the following tables are the measured and calculated doses and reduction factors and the calculated-to-measured, C/M, ratios. Also given in the tables are the averages of the measured and calculated doses and reduction factors and C/M ratios for the seven detector locations on the phantom.

IV.A. TLD Gamma-Ray Measurements

IV.A.1. Comparisons with APRF Measurements

The measured gamma-ray doses and reduction factors obtained by the APRF team for the four experiments are compared with the calculated data reported by ORNL and SAIC data in Tables 21 -24. The doses are compared in units of mrad(Ti)/kWh . For the measurement with the phantom in the free-field facing the reactor, the results shown in Table 21 indicate that the MASH code system favorably replicates the APRF TLD measurements for detector locations on the phantom. However, the calculated data are in poor agreement with the free-field dose and in-box measurements. The same trend is also observed for the reduction factors. The ORNL calculation poorly replicates the free-field doses and reduction factors while results obtained by SAIC are somewhat better, albeit only marginally. The ORNL and SAIC calculations of the doses and reduction factors as a function of position on the phantom are, on the average, in good agreement with the measurements for this case.

The results obtained for the case when the phantom is in the box and facing the reactor are shown in Table 22. The calculated free-field results are again in marginal agreement with the measurements while the dose estimates for detector locations on the phantom are in good agreement with the measurements. Neither analytic team does a commendatory job in reproducing the reduction factors for this configuration. The reason for the disparity among the reduction factors arises mainly from the large difference between the measured and calculated values of the free-field dose.

For the case when the phantom is in the free-field with the right side facing the reactor, the results given in Table 23 show a very similar behavior to those in Table 21. The free-field data are in poor agreement while the calculated doses for the detector locations on the phantom are in good agreement with the experimental data. The reduction factors obtained by both analytic teams are in good agreement with the measured results for this case.

Table 24 compares the measured and calculated doses and reduction factors for the case when the phantom is in the box with the right side facing the reactor. The agreement between the calculated and measured free-field doses are again poor compared with the

correlation for the detectors located on the phantom. For these detectors, the calculations and measurements agree within $\pm 20\%$. The calculations, however, do not reproduce the measured reduction factors very well for this case.

IV.A.2. Comparisons with HDL Measurements

The comparisons of the calculated TLD gamma-ray doses and reduction factors with the measured data obtained by the HDL team are compared in Tables 25 - 28. The doses are compared in units of mrad(CaF_2) per kWh. For the case when the phantom is in the free-field facing the reactor (see Table 25) good agreement is achieved by both ORNL and SAIC for the detector locations on the phantom. The ORNL in-box free-field dose is, however, in marginal agreement with the measured data while the SAIC results are in good agreement. ORNL and SAIC both do a good job of replicating the out of box phantom free-field dose. The reduction factors reported by ORNL and SAIC are in marginal to good agreement with the measured reduction factors.

For the case where the phantom is located in the box facing the reactor, the results given in Table 26 show a considerable improvement in the comparisons among the free-field data but the doses as a function of location on the phantom are now poor to marginal. The spread in measured doses on the phantom are smaller than in the previous case. Examination of the results given in Tables 27 and 28, where the right shoulder of the phantom is facing the reactor, show borderline agreement between the analytic and measured results. The free-field data are in good agreement, the in-box free-field data are in marginal to poor agreement, and, in all cases, marginal to poor agreement is achieved by both teams for the TLD detectors on the phantom.

IV.A.3. Comparisons with BTI/DREO Measurements

The ORNL and SAIC calculated doses and reduction factors are compared with measured data reported by BTI/DREO in Tables 29 - 32. Tables 29 and 30 compare the results for the cases where the phantom is in the free-field and in the box facing the reactor, respectively. For these cases, good agreement with the measured data is reported by both analytic teams for the free-field, in-box free-field, and at most detector locations on the phantom.

The corresponding experiments for the case when the right side of the phantom is facing the reactor are presented in Tables 31 and 32. The measurements and calculations are again in good agreement at almost all detector locations. In all of the comparisons of calculated doses with the BTI measurements, the largest disparity

consistently occurs at the mid-gut (MG) location in the phantom where both ORNL and SAIC predict a larger value for the dose than reported by the experimentalists.

IV.A.4. Comparisons with ETCA Measurements

The ETCA team participated in only one measurement; for the free-field, phantom facing the reactor. The comparisons between the measured and calculated data are summarized in Table 33 and in all cases, the doses in the free-field and on the phantom are in poor agreement. The reduction factors, however, are in good agreement.

IV.B. BD-100R Bubble Detector Neutron Measurements

The calculated neutron doses in units of mrad(Ti) per kWh and concomitant reduction factors are compared with the BTI/DREO BD-100R bubble detector measurements in Tables 34 through 37. In all of the experimental configurations, the agreement between the analytic and experimental free-field doses range from marginal to poor. Both analytic teams consistently overestimate the dose. The comparison of the doses on the phantom display a wide range of differences and scatter among the data. For the cases when the phantom is in the free-field, in both orientations the agreement between the calculated and measured doses for the on-surface detectors is generally good. However, for the detector locations in the mid-head and mid-gut, and the back belt position when the phantom is facing the reactor, large differences between the experimental and analytic data occur. For both cases when the phantom is in the box, the correlation between calculations and measurement is improved. Also, the scatter among the data is smaller.

The neutron reduction factor results also exhibit a large spread and the agreement between the calculated and measured data is generally poor.

The average values of the phantom dose given in the tables should be treated cautiously. The averages are strongly influenced by the doses at detector locations inside the phantom where the neutron attenuation is large.

V. CONCLUSIONS AND RECOMMENDATIONS

The authors of this document were tasked by the Defense Nuclear Agency to examine the results reported by the experimentalists and analysts in an unbiased approach. No attempt was made to filter inconsistent data or otherwise intervene by adjusting or recalculating doses or reduction factors. In attempting to determine the capability of the MASH code system in replicating the Spring 1990 experiment sequence, it was determined that the best course of action was to examine the plethora of measured and calculated data on a case-by-case basis and report the results.

The results summarized in the tables presented here show agreement between the measured and calculated gamma-ray and neutron doses and reduction factors that range from very good to poor depending on the experimental configuration, detector location (free-field and on-phantom), and the experimental or analytic team reporting the results. The gamma-ray doses reported by the different experimental teams exhibit a large spread among the data for both the free-field and in phantom data. The large scatter among the data is manifested in correspondingly large fluctuations ($>25\%$) in the reported reduction factors. The calculated gamma-ray doses reported by ORNL and SAIC, on the other hand, are consistently in good agreement for all of the experimental configurations for both the free-field and in phantom detector locations. When the in-phantom doses and reduction factors are averaged, agreement is considerably improved and in all cases fall within the $\pm 20\%$ tolerance that was defined as the acceptable limit for these comparisons. Only one experimental team reported neutron doses and reduction factor data. The calculations replicate these results, on the average.

One of the difficulties that arose in tabulating and comparing the gamma-ray doses was that several of the experimental teams reported dose data in different units. The procedure adopted here was to use a simple conversion process to obtain consistency in units of dose. No attempt is made to defend this approach but only to compare the measured and calculated data on a consistent basis. It is strongly recommended that in future DNA sponsored experiments where several teams participate, that the experimentalists review response functions, conversion factors, etc. and report the results in a compatible format. At a minimum, this would reduce confusion and at a maximum might isolate extraneous differences among the data.

The principal purpose for developing the MASH code system was to provide the U.S. Army and in particular the U. S. Army Nuclear and Chemical Agency (USANCA) with the capability to calculate reduction factors of armored vehicle shielding materials against neutron and gamma-rays produced in nuclear weapon explosions. The C/M results obtained here show that the MASH code replicates integral data within the accepted tolerance and that MASH version 1.0 can be used to estimate neutron and gamma-ray reduction factors for armored vehicles and other shielded configurations.

Table 1. Details of the 2-Meter Box and Other Experimental Information.

2-Meter Box		Box Disposition	
Shape	Cubic	Reactor to Box	400 m
Interior Dimensions	2.0 m	400-m Site Elevation	10.45 m
Wall Thickness	0.1016 m	Reactor Pad Elevation	13.58 m
Wall Material	Steel	Reactor Center Elevation	26.78 m

400 METER MOISTURE MEASUREMENTS

7 MAY 1990 1-2 PM

Table 2. Details of the RT-200 Canadian Humanoid Phantom.

Composition				Physical Parameters		
Element	Lung	Tissue	Bone			
(atoms/cm ³)						
H	1.65x10 ⁻²	5.88x10 ⁻²	6.14x10 ⁻²	Height		175 cm
C	1.18x10 ⁻²	3.36x10 ⁻²	1.79x10 ⁻²	Chest	(Depth)	21.4
N	1.02x10 ⁻³	1.99x10 ⁻³	1.84x10 ⁻³	Chest	(Width)	33.8
O	3.82x10 ⁻³	7.72x10 ⁻³	2.52x10 ⁻²	Head	(Depth)	20.8
Na		2.32x10 ⁻⁷	1.20x10 ⁻⁴	Head	(Width)	14.8
Mg			3.88x10 ⁻⁵			
Al	1.31x10 ⁻⁹	2.29x10 ⁻⁹		Mass		74 kg
Si			6.00x10 ⁻⁷			
P			1.39x10 ⁻³			
S			4.55x10 ⁻⁵			
Cl	7.13x10 ⁻⁸	2.35x10 ⁻⁸	3.40x10 ⁻⁵			
K			3.30x10 ⁻⁵			
Ca			2.14x10 ⁻³			
Fe			1.20x10 ⁻⁶			
Detector Legend						
Free-Field		Outside				
FF in Box		FF Box				
Mid Head		MH				
Mid Gut		MG				
Left Chest		LC				
Left Wrist		LW				
Rt. Wrist		RW				
Front Belt		FB				
Back Belt		BB				

Table 3. APRF Measurements of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132,133,134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- mrad _{Ti} /kWh	----- mrad _{Ti} /kWh	----- mrad _{Ti} /kWh	----- mrad _{Ti} /kWh
Free Field Dose					
	Outside	1.70	1.69	1.72	1.71
	FF Box	0.31	0.39	0.32	0.33
Dose in Phantom	MH	2.15	0.91	2.29	0.74
	MG	2.14	0.79	2.00	0.72
	LC	2.08	0.59	1.97	0.49
	LW	1.83	0.49	1.31	0.37
	RW	1.95	0.52	1.84	0.45
	FB	2.08	0.61	1.90	0.49
	BB	1.68	0.56	1.91	0.52

Table 4. HDL Measurements of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh	-----mra- d _{CaF} /kWh
Free Field Dose	Outside	1.33	1.32	1.31	1.31
	FF Box	0.29	0.33	0.30	0.27
Dose in Phantom	MH	1.90	0.66	1.70	0.64
	MG	1.91	0.63	1.53	0.57
	LC	1.90	0.53	1.45	0.53
	LW	1.74	0.43	1.12	0.38
	RW	1.91	0.47	1.56	0.27
	FB	2.10	0.49	1.47	0.41
	BB	1.85	0.52	1.44	0.40

Table 5. BTI/DREO Measurement of Neutron Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/135
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing ----- mrem/kWh	In-Box Facing ----- mrem/kWh	FF Right Side ----- mrem/kWh	In-Box Right Side ----- mrem/kWh
Free Field Dose	Outside	46.81	48.84	47.59	40.87
	FF Box		27.75		28.40
Dose in Phantom	MH	10.35	3.62	9.28	4.87
	MG	7.91	2.79	5.74	2.00
	LC	42.00	26.25	27.98	19.68
	LW	37.09	23.04	21.10	20.39
	RW	47.66	26.46	41.02	28.72
	FB	38.64	21.50	27.99	19.46
	BB	17.91	13.94	23.97	18.93
		FF Facing ----- mrad(Ti)/kWh	In-Box Facing ----- mrad(Ti)/kWh	FF Right Side ----- mrad(Ti)/kWh	In-Box Right Side ----- mrad(Ti)/kWh
Free Field Dose	Outside	4.09	4.27	4.16	3.57
	FF Box		2.46		2.52
Dose in Phantom	MH	0.90	0.32	0.81	0.43
	MG	0.69	0.25	0.50	0.18
	LC	3.67	2.33	2.45	1.75
	LW	3.24	2.05	1.84	1.81
	RW	4.17	2.35	3.59	2.55
	FB	3.38	1.91	2.45	1.73
	BB	1.57	1.24	2.10	1.68

Table 6. BTI/DREO Measurement of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing ----- mrad _{Ti} /kWh	In-Box Facing ----- mrad _{Ti} /kWh	FF Right Side ----- mrad _{Ti} /kWh	In-Box Right Side ----- mrad _{Ti} /kWh
Free Field Dose	Outside	1.24	1.37	1.37	1.32
	FF Box		0.42		0.33
Dose in Phantom	MH	1.81	0.81	1.68	0.70
	MG	1.54	0.64	1.37	0.56
	LC	1.77	0.71	1.63	0.59
	LW	1.42	0.72	1.40	0.39
	RW	1.54	0.49	1.58	0.44
	FB	1.76	0.64	1.55	0.52
	BB	1.29	0.66	1.68	0.50

Table 7. ETCA Measurement of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130
Length		50 kWh
FF Facing		-----
		mrad _{T₁} /kWh
Free Field Dose	Outside	1.83
FF Box		
Dose in Phantom	MH	3.17
	MG	2.41
	LC	2.23
	LW	2.04
	RW	2.12
	FB	2.29
	BB	1.85

Table 8. Ratios of the Measured Gamma-Ray Doses
Free-Field Measurements/Phantom Facing the Reactor

Run Number	129/130	FF Facing			
Run Length	50 kWh				
		APRF/HDL	APRF/BTI	APRF/ETCA	HDL/BTI
Free Field Dose	Outside FF Box	1.11 0.93	1.37	0.93	1.23
Dose in the Phantom					
	MH	0.98	1.19	0.68	1.21
	MG	0.97	1.39	0.89	1.43
	LC	0.95	1.18	0.93	1.23
	LW	0.92	1.29	0.90	1.41
	RW	0.89	1.27	0.92	1.43
	FB	0.86	1.18	0.91	1.37
	BB	0.79	1.30	0.91	1.65
	Average*	0.91	1.26	0.88	1.39
	STD	0.07	0.08	0.09	0.15

* Average of the Ratios in the Phantom.

Table 9. Ratios of the Measured Gamma-Ray Doses
Phantom in the 2-m Box/Facing the Reactor

Run Number	127/128	In Box Facing			
Run Length	50 kWh				
		APRF/HDL	APRF/BTI	APRF/ETCA	HDL/BTI
Free Field Dose	Outside FF Box	1.11 1.03	1.23 0.93		1.11 0.90
Dose in the Phantom					
	MH	1.20	1.12		0.94
	MG	1.09	1.23		1.13
	LC	0.97	0.83		0.86
	LW	0.99	0.68		0.69
	RW	0.96	1.06		1.10
	FB	1.08	0.95		0.88
	BB	0.94	0.85		0.90
	Average*	1.03	0.96		0.93
	STD	0.09	0.19		0.15

* Average of the Ratios in the Phantom.

Table 10. Ratios of the Measured Gamma-Ray Doses
Free-Field Measurements/Right-Side Facing the Reactor

Run Number	132/133/134	FF Right Side			
Run Length	35.2 kWh				
		APRF/HDL	APRF/BTI	APRF/ETCA	HDL/BTI
Free Field Dose	Outside FF Box	1.14 0.93	1.26		1.10
Dose in the Phantom					
	MH	1.17	1.36		1.16
	MG	1.14	1.46		1.28
	LC	1.18	1.21		1.02
	LW	1.02	0.94		0.92
	RW	1.03	1.16		1.13
	FB	1.12	1.23		1.09
	BB	1.15	1.14		0.99
	Average*	1.12	1.21		1.08
	STD	0.07	0.17		0.12

* Average of the Ratios in the Phantom.

Table 11. Ratios of the Measured Gamma-Ray Doses
Phantom in the 2-m Box/Right-Side Facing the Reactor

Run Number	135/136	In Box Right Side Facing			
Run Length	23.8 kWh				
		APRF/HDL	APRF/BTI	APRF/ETCA	HDL/BTI
Free Field Dose	Outside FF Box	1.14 1.06	1.29 1.00		1.14 0.94
Dose in the Phantom					
	MH	1.01	1.06		1.05
	MG	1.10	1.29		1.17
	LC	0.80	0.83		1.03
	LW	0.85	0.95		1.12
	RW	1.45	1.02		0.70
	FB	1.04	0.94		0.91
	BB	1.13	1.04		0.92
	Average*	1.05	1.02		0.99
	STD	0.21	0.14		0.16

* Average of the Ratios in the Phantom.

Table 12. ORNL Calculations of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing ----- mrad _{Ti} /kWh	In-Box Facing ----- mrad _{Ti} /kWh	FF Right Side ----- mrad _{Ti} /kWh	In-Box Right Side ----- mrad _{Ti} /kWh
Free Field Dose	Outside	1.34	1.33	1.34	1.32
	FF Box	0.38	0.38	0.38	0.35
Dose in Phantom	MH	1.93	0.93	1.98	0.81
	MG	1.92	0.85	1.73	0.73
	LC	1.84	0.66	1.58	0.55
	LW	1.51	0.47	1.19	0.39
	RW	1.61	0.52	1.63	0.49
	FB	1.93	0.69	1.68	0.58
	BB	1.48	0.63	1.72	0.58
Average		1.75	0.68	1.64	0.59
STD		0.20	0.17	0.24	0.14

Table 13. ORNL Calculations of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh
Free Field Dose	Outside	1.36	1.34	1.36	1.34
	FF Box	0.35	0.36	0.35	0.32
Dose in Phantom	MH	2.01	0.88	2.05	0.76
	MG	2.08	0.83	1.88	0.71
	LC	1.93	0.62	1.66	0.52
	LW	1.58	0.44	1.28	0.36
	RW	1.68	0.48	1.70	0.46
	FB	2.04	0.65	1.77	0.56
	BB	1.55	0.60	1.79	0.55
Average		1.84	0.64	1.73	0.56
STD		0.23	0.16	0.24	0.14

Table 14. SAIC Calculations of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing ----- mrad _{Ti} /kWh	In-Box Facing ----- mrad _{Ti} /kWh	FF Right Side ----- mrad _{Ti} /kWh	In-Box Right Side ----- mrad _{Ti} /kWh
Free Field Dose	Outside	1.33	1.27	1.34	1.33
	FF Box	0.36	0.37	0.32	0.36
Dose in Phantom	MH	1.89	0.87	1.96	0.77
	MG	1.89	0.87	1.73	0.82
	LC	1.72	0.68	1.56	0.57
	LW	1.51	0.55	1.19	0.48
	RW	1.54	0.51	1.61	0.50
	FB	1.85	0.73	1.68	0.50
	BB	1.49	0.54	1.70	0.57
Average		1.70	0.68	1.63	0.60
STD		0.18	0.15	0.23	0.14

Table 15. SAIC Calculations of Gamma-Ray Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh	----- mrad _{CaF} /kWh
Free Field Dose	Outside	1.46	1.41	1.45	1.50
	FF Box	0.31	0.37	0.32	0.35
Dose in Phantom	MH	2.16	0.84	2.24	0.73
	MG	2.26	0.85	2.08	0.80
	LC	1.96	0.65	1.76	0.56
	LW	1.70	0.54	1.37	0.47
	RW	1.73	0.50	1.80	0.49
	FB	2.08	0.72	1.88	0.49
	BB	1.72	0.52	1.94	0.55
Average		1.94	0.66	1.87	0.58
STD		0.23	0.15	0.27	0.13

Table 16. Ratios of the Calculated Gamma-Ray Doses
(Dose rates in mrad(Ti)/kWh.)

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- ORNL/SAIC	----- ORNL/SAIC	----- ORNL/SAIC	----- ORNL/SAIC
Free Field Dose					
	Outside	1.01	1.05	1.00	0.99
	FF Box	1.06	1.03	1.19	0.97
Dose in Phantom					
	MH	1.02	1.07	1.01	1.05
	MG	1.02	0.98	1.00	0.89
	LC	1.07	0.97	1.01	0.96
	LW	1.00	0.85	1.00	0.81
	RW	1.05	1.02	1.01	0.98
	FB	1.04	0.95	1.00	1.16
	BB	0.99	1.17	1.01	1.02

Table 17. Ratios of the Calculated Gamma-Ray Doses
(Dose rates in mrad(CaF₂)/kWh.)

Run Number		129/130	127/128	132/133/134	135/136
Run Length		50 kWh	50 kWh	35.2 kWh	23.8 kWh
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- ORNL/SAIC	----- ORNL/SAIC	----- ORNL/SAIC	----- ORNL/SAIC
Free Field Dose					
	Outside	0.93	0.95	0.94	0.89
	FF Box	1.13	0.97	1.09	0.91
Dose in Phantom					
	MH	0.93	1.05	0.92	1.04
	MG	0.92	0.98	0.90	0.89
	LC	0.98	0.95	0.94	0.93
	LW	0.93	0.81	0.93	0.77
	RW	0.97	0.96	0.94	0.94
	FB	0.98	0.90	0.94	1.14
	BB	0.90	1.15	0.92	1.00

Table 18. ORNL Calculations of Neutron Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		120	122/123	119	124/125
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- mrad _{Ti} /kWh	----- mrad _{Ti} /kWh	----- mrad _{Ti} /kWh	----- mrad _{Ti} /kWh
Free Field Dose	Outside	4.90	4.90	4.90	4.90
	FF Box	3.03	2.82	3.03	2.82
Dose in Phantom	MH	1.20	0.41	1.38	0.44
	MG	0.74	0.20	0.44	0.16
	LC	4.52	2.35	3.17	1.91
	LW	4.35	2.45	2.34	1.97
	RW	4.40	2.36	4.47	2.49
	FB	4.47	2.27	3.39	1.90
	BB	1.62	1.47	3.29	1.90
Average		3.04	1.63	2.64	1.54
STD		1.76	1.03	1.36	0.88

Table 19. SAIC Calculations of Neutron Dose Rate in the Free-Field
and as a Function of Position on the RT-200 Humanoid Phantom.

Run Number		120	122/123	119	124/125
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- mrad _{T_V} /kWh	----- mrad _{T_V} /kWh	----- mrad _{T_V} /kWh	----- mrad _{T_V} /kWh
Free Field Dose	Outside	5.01	5.19	5.02	5.29
	FF Box	2.99	2.86	3.00	2.91
Dose in Phantom	MH	1.10	0.45	1.27	0.53
	MG	0.83	0.22	0.45	0.18
	LC	4.58	2.50	3.02	2.17
	LW	4.09	2.44	2.27	1.91
	RW	4.12	2.49	4.63	2.76
	FB	4.49	2.32	3.37	2.08
	BB	1.57	1.63	2.79	2.17
Average		2.97	1.72	2.54	1.69
STD		1.71	1.00	1.38	0.95

Table 20. Ratios of the Calculated Neutron Doses
(Dose rates in mrad(Ti)/kWh.)

Run Number		120	122/123	119	124/125
		FF Facing	In-Box Facing	FF Right Side	In-Box Right Side
		----- ORNL/SAIC	----- ORNL/SAIC	----- ORNL/SAIC	----- ORNL/SAIC
Free Field Dose	Outside	0.98	0.94	0.98	0.93
	FF Box	1.01	0.99	1.01	0.97
Dose in Phantom	MH	1.09	0.91	1.08	0.83
	MG	0.89	0.90	0.98	0.89
	LC	0.98	0.94	1.05	0.88
	LW	1.06	1.00	1.03	1.03
	RW	0.99	0.95	0.97	0.91
	FB	0.99	0.95	0.97	0.91
	BB	1.03	0.90	1.17	0.88

Table 21. Measured and Calculated Gamma-Ray Doses and Reduction Factors
Free-Field/Phantom Facing Reactor
Comparisons with APRF TLD Measurements
Doses in mrad_{Ti}/kWh.

Run Number 129/130						50 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.70	1.34	0.79	1.33	0.78					
						5.48	3.53	0.64	3.69	0.67
Box	0.31	0.38	1.23	0.36	1.16					
Doses in Phantom										
MH	2.15	1.93	0.90	1.89	0.88	0.79	0.69	0.87	0.70	0.89
MG	2.14	1.92	0.90	1.89	0.88	0.79	0.70	0.89	0.70	0.89
LC	2.08	1.84	0.88	1.72	0.83	0.82	0.73	0.89	0.77	0.94
LW	1.83	1.51	0.83	1.51	0.83	0.93	0.88	0.95	0.88	0.95
RW	1.95	1.61	0.83	1.54	0.80	0.87	0.83	0.95	0.86	0.99
FB	2.08	1.93	0.93	1.85	0.89	0.82	0.69	0.84	0.72	0.88
BB	1.68	1.48	0.88	1.49	0.89	1.01	0.91	0.90	0.89	0.88
AVG	1.99	1.75	0.88	1.70	0.86	0.86	0.78	0.90	0.79	0.92
STD	0.18	0.20	0.04	0.18	0.04	0.08	0.10	0.04	0.09	0.04

Table 22. Measured and Calculated Gamma-Ray Doses and Reduction Factors
In-Box/Phantom Facing Reactor
Comparisons with APRF TLD Measurements
Doses in mrad_{Ti}/kWh.

Run Number 127/128						50 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.69	1.33	0.79	1.27	0.75					
						4.33	3.50	0.81	3.43	0.79
Box	0.39	0.38	0.97	0.37	0.95					
Doses in Phantom										
MH	0.91	0.93	1.02	0.87	0.96	1.86	1.43	0.77	1.46	0.78
MG	0.79	0.85	1.08	0.87	1.10	2.14	1.56	0.73	1.46	0.68
LC	0.59	0.66	1.12	0.68	1.15	2.86	2.01	0.70	1.87	0.65
LW	0.49	0.47	0.96	0.55	1.12	3.45	2.81	0.81	2.31	0.67
RW	0.52	0.52	1.00	0.51	0.98	3.25	2.58	0.79	2.49	0.77
FB	0.61	0.69	1.13	0.73	1.20	2.77	1.94	0.70	1.74	0.63
BB	0.56	0.63	1.13	0.54	0.96	3.02	2.10	0.70	2.35	0.78
AVG	0.64	0.68	1.06	0.68	1.07	2.76	2.06	0.74	1.95	0.71
STD	0.15	0.17	0.07	0.15	0.10	0.58	0.50	0.05	0.43	0.07

Table 23. Measured and Calculated Gamma-Ray Doses and Reduction Factors
Free-Field/Right-Side Facing Reactor
Comparisons with APRF TLD Measurements
Doses in mrad_T/kWh.

Run Number 132/133/134 35.2 kWh										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.72	1.34	0.78	1.34	0.78					
						5.38	3.53	0.66	4.19	0.78
Box	0.32	0.38	1.19	0.32	1.00					
Doses in Phantom										
MH	2.29	1.98	0.86	1.96	0.86	0.75	0.68	0.91	0.68	0.91
MG	2.00	1.73	0.87	1.73	0.87	0.86	0.77	0.90	0.77	0.90
LC	1.97	1.58	0.80	1.56	0.79	0.87	0.85	0.98	0.86	0.99
LW	1.31	1.19	0.91	1.19	0.91	1.31	1.12	0.85	1.13	0.86
RW	1.84	1.63	0.89	1.61	0.88	0.93	0.82	0.88	0.83	0.89
FB	1.90	1.68	0.88	1.68	0.88	0.91	0.80	0.88	0.80	0.88
BB	1.91	1.72	0.90	1.70	0.89	0.90	0.78	0.87	0.79	0.88
AVG	1.89	1.64	0.87	1.63	0.87	0.93	0.83	0.90	0.84	0.90
STD	0.29	0.24	0.04	0.23	0.04	0.18	0.14	0.04	0.14	0.04

Table 24. Measured and Calculated Gamma-Ray Doses and Reduction Factors
In-Box/Right-Side Facing Reactor
Comparisons with APRF TLD Measurements
Doses in $\text{mrad}_{\text{Tl}}/\text{kWh}$.

Run Number 135/136						23.8 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.71	1.32	0.77	1.33	0.78					
						5.18	3.77	0.73	3.69	0.71
Box	0.33	0.35	1.06	0.36	1.09					
Doses in Phantom										
MH	0.74	0.81	1.09	0.77	1.04	2.31	1.64	0.71	1.73	0.75
MG	0.72	0.73	1.01	0.82	1.14	2.38	1.80	0.76	1.62	0.68
LC	0.49	0.55	1.12	0.57	1.16	3.49	2.39	0.68	2.33	0.67
LW	0.37	0.39	1.05	0.48	1.30	4.62	3.38	0.73	2.77	0.60
RW	0.45	0.49	1.09	0.50	1.11	3.80	2.70	0.71	2.66	0.70
FB	0.49	0.58	1.18	0.50	1.02	3.49	2.26	0.65	2.66	0.76
BB	0.52	0.58	1.12	0.57	1.10	3.29	2.26	0.69	2.33	0.71
AVG	0.54	0.59	1.09	0.60	1.12	3.34	2.35	0.70	2.30	0.70
STD	0.14	0.14	0.05	0.14	0.09	0.80	0.58	0.04	0.46	0.05

Table 25. Measured and Calculated Gamma-Ray Doses and Reduction Factors
Free-Field/Phantom Facing Reactor
Comparisons with HDL TLD Measurements
Doses in mrad_{CaF} /kWh.

Run Number 129/130						50 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.33	1.36	1.02	1.46	1.10					
						4.59	3.89	0.85	4.71	1.03
Box	0.29	0.35	1.21	0.31	1.07					
Doses in Phantom										
MH	1.90	2.01	1.06	2.16	1.14	0.70	0.68	0.97	0.68	0.97
MG	1.91	2.08	1.09	2.26	1.18	0.70	0.65	0.93	0.65	0.93
LC	1.90	1.93	1.02	1.96	1.03	0.70	0.70	1.00	0.74	1.06
LW	1.74	1.58	0.91	1.70	0.98	0.76	0.86	1.13	0.86	1.13
RW	1.91	1.68	0.88	1.73	0.91	0.70	0.81	1.16	0.84	1.20
FB	2.10	2.04	0.97	2.08	0.99	0.63	0.67	1.06	0.70	1.11
BB	1.85	1.55	0.84	1.72	0.93	0.72	0.88	1.22	0.85	1.18
AVG	1.90	1.84	0.97	1.94	1.02	0.70	0.75	1.07	0.76	1.08
STD	0.11	0.23	0.09	0.23	0.10	0.04	0.10	0.11	0.09	0.10

Table 26. Measured and Calculated Gamma-Ray Doses and Reduction Factors
In-Box/Phantom Facing Reactor
Comparisons with HDL TLD Measurements
Doses in $\text{mrad}_{\text{CaF}}/\text{kWh}$.

Run Number 127/128 50 kWh										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.32	1.34	1.02	1.41	1.07					
						4.00	3.72	0.93	3.81	0.95
Box	0.33	0.36	1.09	0.37	1.12					
Doses in Phantom										
MH	0.66	0.88	1.33	0.84	1.27	2.00	1.53	0.77	1.68	0.84
MG	0.63	0.83	1.32	0.85	1.35	2.10	1.62	0.77	1.66	0.79
LC	0.53	0.62	1.17	0.65	1.23	2.49	2.17	0.87	2.17	0.87
LW	0.43	0.44	1.02	0.54	1.26	3.07	3.05	0.99	2.61	0.85
RW	0.47	0.48	1.02	0.50	1.06	2.81	2.77	0.99	2.82	1.00
FB	0.49	0.65	1.33	0.72	1.47	2.69	2.05	0.76	1.96	0.73
BB	0.52	0.60	1.15	0.52	1.00	2.54	2.24	0.88	2.71	1.07
AVG	0.53	0.64	1.19	0.66	1.23	2.53	2.20	0.86	2.23	0.88
STD	0.08	0.16	0.14	0.15	0.16	0.38	0.56	0.10	0.49	0.12

Table 27. Measured and Calculated Gamma-Ray Doses and Reduction Factors
Free-Field/Right-Side Facing Reactor
Comparisons with HDL TLD Measurements
Doses in mrad_{CaF}/kWh.

Run Number 132/133/134 35.2 kWh										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.31	1.36	1.04	1.45	1.11					
						4.37	3.89	0.89	4.53	1.04
Box	0.30	0.35	1.17	0.32	1.07					
Doses in Phantom										
MH	1.70	2.05	1.21	2.24	1.32	0.77	0.66	0.86	0.65	0.84
MG	1.53	1.88	1.23	2.08	1.36	0.86	0.72	0.84	0.70	0.81
LC	1.45	1.66	1.14	1.76	1.21	0.90	0.82	0.91	0.82	0.91
LW	1.12	1.28	1.14	1.37	1.22	1.17	1.06	0.91	1.06	0.91
RW	1.56	1.70	1.09	1.80	1.15	0.84	0.80	0.95	0.81	0.96
FB	1.47	1.77	1.20	1.88	1.28	0.89	0.76	0.85	0.77	0.87
BB	1.44	1.79	1.24	1.94	1.35	0.91	0.76	0.84	0.75	0.82
AVG	1.47	1.73	1.18	1.87	1.27	0.91	0.80	0.88	0.79	0.87
STD	0.18	0.24	0.06	0.27	0.08	0.13	0.13	0.04	0.13	0.06

Table 28. Measured and Calculated Gamma-Ray Doses and Reduction Factors
In-Box/Right-Side Facing Reactor
Comparisons with HDL TLD Measurements
Doses in $\text{mrad}_{\text{CaF}}/\text{kWh}$.

Run Number 135/136						23.8 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.31	1.34	1.02	1.50	1.15					
						4.85	4.19	0.86	4.29	0.88
Box	0.27	0.32	1.19	0.35	1.30					
Doses in Phantom										
MH	0.64	0.76	1.19	0.73	1.14	2.05	1.76	0.86	2.05	1.00
MG	0.57	0.71	1.25	0.80	1.40	2.30	1.88	0.82	1.88	0.82
LC	0.53	0.52	0.98	0.56	1.06	2.47	2.59	1.05	2.68	1.08
LW	0.38	0.36	0.95	0.47	1.24	3.45	3.69	1.07	3.19	0.93
RW	0.27	0.46	1.70	0.49	1.81	4.85	2.92	0.60	3.06	0.63
FB	0.41	0.56	1.37	0.49	1.20	3.20	2.41	0.75	3.06	0.96
BB	0.40	0.55	1.38	0.55	1.38	3.28	2.44	0.74	2.73	0.83
AVG	0.46	0.56	1.26	0.58	1.32	3.09	2.53	0.84	2.66	0.89
STD	0.13	0.14	0.26	0.13	0.25	0.95	0.65	0.17	0.51	0.15

Table 29. Measured and Calculated Gamma-Ray Doses and Reduction Factors
Free-Field/Phantom Facing Reactor
Comparisons with BTI/DREO TLD Measurements
Doses in mrad_{Ti}/kWh.

Run Number 129/130						50 kWh				
Dose	OR	C/M	SAI	C/M		RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.24	1.34	1.08	1.33	1.07					
							3.53		3.69	
Box		0.38		0.36						
Doses in Phantom										
MH	1.81	1.93	1.07	1.89	1.04	0.69	0.69	1.00	0.70	1.01
MG	1.54	1.92	1.25	1.89	1.23	0.81	0.70	0.86	0.70	0.86
LC	1.77	1.84	1.04	1.72	0.97	0.70	0.73	1.04	0.77	1.10
LW	1.42	1.51	1.06	1.51	1.06	0.87	0.88	1.01	0.88	1.01
RW	1.54	1.61	1.05	1.54	1.00	0.81	0.83	1.02	0.86	1.06
FB	1.76	1.93	1.10	1.85	1.05	0.70	0.69	0.99	0.72	1.03
BB	1.29	1.48	1.15	1.49	1.16	0.96	0.91	0.95	0.89	0.93
AVG	1.59	1.75	1.10	1.70	1.07	0.79	0.78	0.98	0.79	1.00
STD	0.20	0.20	0.07	0.18	0.09	0.10	0.10	0.06	0.09	0.08

Table 30. Measured and Calculated Gamma-Ray Doses and Reduction Factors
In-Box/Phantom Facing Reactor
Comparisons with BTI/DREO TLD Measurements
Doses in mrad_{Ti}/kWh.

Run Number 127/128						50 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.37	1.33	0.97	1.27	0.93					
						3.26	3.50	1.07	3.43	1.05
Box	0.42	0.38	0.90	0.37	0.88					
Doses in Phantom										
MH	0.81	0.93	1.15	0.87	1.07	1.69	1.43	0.85	1.46	0.86
MG	0.64	0.85	1.33	0.87	1.36	2.14	1.56	0.73	1.46	0.68
LC	0.71	0.66	0.93	0.68	0.96	1.93	2.01	1.04	1.87	0.97
LW	0.72	0.47	0.65	0.55	0.76	1.90	2.81	1.48	2.31	1.22
RW	0.49	0.52	1.06	0.51	1.04	2.80	2.58	0.92	2.49	0.89
FB	0.64	0.69	1.08	0.73	1.14	2.14	1.94	0.91	1.74	0.81
BB	0.66	0.63	0.95	0.54	0.82	2.08	2.10	1.01	2.35	1.13
AVG	0.67	0.68	1.02	0.68	1.02	2.10	2.06	0.96	1.95	0.94
STD	0.10	0.17	0.21	0.15	0.20	0.35	0.50	0.26	0.43	0.19

Table 31. Measured and Calculated Gamma-Ray Doses and Reduction Factors
 Free-Field/Right-Side Facing Reactor
 Comparisons with BTI/DREO TLD Measurements
 Doses in mrad_{Ti}/kWh.

Run Number 132/133/134 35.2 kWh										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.37	1.34	0.98	1.34	0.96					
							3.53		4.19	
Box		0.38		0.32						
Doses in Phantom										
MH	1.68	1.98	1.18	1.96	1.17	0.82	0.68	0.83	0.68	0.83
MG	1.37	1.73	1.26	1.73	1.26	1.00	0.77	0.77	0.77	0.77
	1.63	1.58	0.97	1.56	0.96	0.84	0.85	1.01	0.86	1.02
LW	1.40	1.19	0.85	1.19	0.85	0.98	1.12	1.14	1.13	1.15
RW	1.58	1.63	1.03	1.61	1.02	0.87	0.82	0.94	0.83	0.95
FB	1.55	1.68	1.08	1.68	1.08	0.88	0.80	0.91	0.80	0.91
BB	1.68	1.72	1.02	1.70	1.01	0.82	0.78	0.95	0.79	0.96
AVG	1.56	1.64	1.06	1.63	1.05	0.89	0.83	0.94	0.84	0.94
STD	0.13	0.24	0.14	0.23	0.14	0.07	0.14	0.12	0.14	0.12

Table 32. Measured and Calculated Gamma-Ray Doses and Reduction Factors
In-Box/Right-Side Facing Reactor
Comparisons with BTI/DREO TLD Measurements
Doses in mrad_{Ti}/kWh.

Run Number 135/136						23.8 kWh				
Dose	OR	C/M	SAI	C/M		RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.32	1.32	1.00	1.33	1.04					
						4.00	3.77	0.94	3.69	0.92
Box	0.33	0.35	1.06	0.36	1.06					
Doses in Phantom										
MH	0.70	0.81	1.16	0.77	1.10	1.89	1.64	0.87	1.73	0.92
MG	0.56	0.73	1.30	0.82	1.46	2.36	1.80	0.76	1.62	0.69
LC	0.59	0.55	0.93	0.57	0.97	2.24	2.39	1.07	2.33	1.04
LW	0.39	0.39	1.00	0.48	1.23	3.38	3.38	1.00	2.77	0.82
RW	0.44	0.49	1.11	0.50	1.14	3.00	2.70	0.90	2.66	0.89
FB	0.52	0.58	1.12	0.50	0.96	2.54	2.26	0.89	2.66	1.05
BB	0.50	0.58	1.16	0.57	1.14	2.64	2.26	0.86	2.33	0.88
AVG	0.53	0.59	1.11	0.60	1.13	2.58	2.35	0.91	2.30	0.90
STD	0.10	0.14	0.12	0.14	0.17	0.49	0.58	0.10	0.46	0.12

Table 33. Measured and Calculated Gamma-Ray Doses and Reduction Factors
Free-Field/Phantom Facing Reactor
Comparisons with ETCA TLD Measurements
Doses in $\text{mrad}_{\text{Tl}}/\text{kWh}$.

Run Number 129/130						50 kWh				
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	1.83	1.34	0.73	1.33	0.73					
							3.53		3.69	
Box		0.38		0.36						
Doses in Phantom										
MH	3.17	1.93	0.61	1.89	0.60	0.58	0.69	1.19	0.70	1.21
MG	2.41	1.92	0.80	1.89	0.78	0.76	0.70	0.92	0.70	0.92
LC	2.23	1.84	0.83	1.72	0.77	0.82	0.73	0.89	0.77	0.94
LW	2.04	1.51	0.74	1.51	0.74	0.90	0.88	0.98	0.88	0.98
RW	2.12	1.61	0.76	1.54	0.73	0.86	0.83	0.97	0.86	1.00
FB	2.29	1.93	0.84	1.85	0.81	0.80	0.69	0.86	0.72	0.90
BB	1.85	1.48	0.80	1.49	0.81	0.99	0.91	0.92	0.89	0.90
AVG	2.30	1.75	0.77	1.70	0.75	0.82	0.78	0.96	0.79	0.98
STD	0.42	0.20	0.08	0.18	0.07	0.13	0.10	0.11	0.09	0.11

Table 34. Measured and Calculated Neutron Doses and Reduction Factors
Free-Field/Phantom Facing Reactor
Comparisons with BTI/DREO Bubble Detector Measurements
Doses in $\text{mrad}_{\text{Tl}}/\text{kWh}$.

Run Number 120										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	4.09	4.90	1.20	5.01	1.22					
							1.62		1.67	
Box		3.03		2.99						
Doses in Phantom										
MH	0.90	1.20	1.33	1.10	1.22	4.54	4.08	0.90	4.55	1.00
MG	0.69	0.74	1.07	0.83	1.20	5.93	6.62	1.12	6.04	1.02
LC	3.67	4.52	1.23	4.58	1.25	1.11	1.08	0.97	1.09	0.98
LW	3.24	4.35	1.34	4.09	1.26	1.26	1.13	0.90	1.22	0.97
RW	4.17	4.40	1.06	4.12	0.99	0.98	1.11	1.13	1.22	1.24
FB	3.38	4.47	1.32	4.49	1.33	1.21	1.10	0.91	1.11	0.92
BB	1.57	1.62	1.03	1.57	1.00	2.61	3.02	1.16	3.19	1.22
AVG	2.52	3.04	1.19	2.97	1.18	1.62	1.61	1.01	1.43	1.05
STD	1.42	1.76	0.12	1.71	0.13	2.86	2.79	0.12	2.78	0.13

Table 35. Measured and Calculated Neutron Doses and Reduction Factors
In-Box/Phantom Facing Reactor
Comparisons with BTI/DREO Bubble Detector Measurements
Doses in mrad_{Ti}/kWh.

Run Number 122/123										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	4.27	4.90	1.15	5.19	1.22					
						1.74	1.74	1.00	1.81	1.04
Box	2.46	2.82	1.15	2.86	1.16					
Doses in Phantom										
MH	0.32	0.41	1.28	0.45	1.41	13.34	11.95	0.90	11.53	0.86
MG	0.25	0.20	0.80	0.22	0.88	17.08	24.50	1.43	23.59	1.38
LC	2.33	2.35	1.01	2.50	1.07	1.83	2.09	1.14	2.08	1.14
LW	2.05	2.45	1.20	2.44	1.19	2.08	2.00	0.96	2.13	1.02
RW	2.35	2.36	1.00	2.49	1.06	1.82	2.08	1.14	2.08	1.14
FB	1.91	2.27	1.19	2.32	1.21	2.24	2.16	0.96	2.24	1.00
BB	1.24	1.47	1.19	1.63	1.31	3.44	3.33	0.97	3.18	0.92
AVG	1.49	1.63	1.10	1.72	1.16	2.86	2.98	1.07	3.02	1.07
STD	0.90	1.03	0.17	1.00	0.18	4.72	5.04	0.19	5.22	0.17

Table 36. Measured and Calculated Neutron Doses and Reduction Factors
Free-Field/Right Side Facing Reactor
Comparisons with BTI/DREO Bubble Detector Measurements
Doses in mrad_T/kWh.

Run Number 119										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	4.16	4.90	1.18	5.02	1.21					
							1.62		1.68	
Box		3.03		3.00						
Doses in Phantom										
MH	0.81	1.38	1.70	1.27	1.57	5.14	3.55	0.69	3.95	0.77
MG	0.50	0.44	0.88	0.45	0.90	8.32	11.14	1.34	11.16	1.34
LC	2.45	3.17	1.29	3.02	1.23	1.70	1.55	0.91	1.66	0.98
LW	1.84	2.34	1.27	2.27	1.23	2.26	2.09	0.92	2.21	0.98
RW	3.59	4.47	1.25	4.63	1.29	1.16	1.10	0.95	1.08	0.93
FB	2.45	3.39	1.38	3.37	1.38	1.70	1.45	0.85	1.49	0.88
BB	2.10	3.29	1.57	2.79	1.33	1.98	1.49	0.75	1.80	0.91
AVG	1.96	2.64	1.33	2.54	1.28	3.18	3.20	0.92	3.34	0.97
STD	1.05	1.36	0.26	1.38	0.20	2.61	3.59	0.21	3.57	0.18

Table 37. Measured and Calculated Neutron Doses and Reduction Factors
In-Box/Right Side Facing Reactor
Comparisons with BTI/DREO Bubble Detector Measurements
Doses in mrad_{T₀}/kWh.

Run Number 124/125										
	Dose	OR	C/M	SAI	C/M	RF	OR	C/M	SAI	C/M
Free-Field Doses										
Out	3.57	4.90	1.37	5.29	1.48					
						1.42	1.74	1.23	1.81	1.27
Box	2.52	2.82	1.12	2.91	1.15					
Doses in Phantom										
MH	0.43	0.44	1.02	0.53	1.23	8.30	11.14	1.34	9.98	1.20
MG	0.18	0.16	0.89	0.18	1.00	19.83	30.63	1.54	29.39	1.48
LC	1.75	1.91	1.09	2.17	1.24	2.04	2.57	1.26	2.44	1.20
LW	1.81	1.97	1.09	1.91	1.06	1.97	2.48	1.26	2.77	1.41
RW	2.55	2.49	0.98	2.76	1.08	1.40	1.97	1.41	1.92	1.37
FB	1.73	1.90	1.10	2.08	1.20	2.06	2.58	1.25	2.54	1.23
BB	1.68	1.90	1.13	2.17	1.29	2.13	2.58	1.21	2.44	1.15
AVG	1.45	1.54	1.04	1.69	1.16	5.39	7.71	1.32	7.35	1.29
STD	0.84	0.88	0.08	0.95	0.11	6.80	10.62	0.12	10.12	0.13

REFERENCES

1. J. O. Johnson, "A User's Manual for MASH 1.0 - A Monte Carlo Adjoint Shielding Code System," Oak Ridge National Laboratory, ORNL/TM-11778, (March 1991)
2. W. A. Rhoades and M. B. Emmett et al., Vehicle Code System (VCS) User's Manual," Oak Ridge National Laboratory, ORNL/TM-4648, (August 1974)
3. W. A. Rhoades et. al., "Development of a Code System for Determining Radiation Protection of Armored Vehicles (The VCS Code)," Oak Ridge National Laboratory, ORNL/TM-4664, (October 1974)
4. J. O. Johnson, J. D. Drischler, and J. M. Barnes, "Analysis of the Fall-1989 Two-Meter Box Test Bed Experiments Performed at the Army Pulse Radiation Facility (APRF)," Oak Ridge National Laboratory, ORNL/TM-11777, (May 1991)
5. Dean C. Kaul and Stephen D. Egbert, "Radiation Environments Program (REP) The Verification & Validation of MASH 1991, 1990, 1989," presented at the REP Program Meeting, WWD, Munster, Germany, 28-29 July 1992 (Unpublished)
6. R. T. Santoro et. el., "DNA Radiation Environments Program Fall 1989 2-Meter Box Experiments and Analysis," Oak Ridge National Laboratory, ORNL/TM-11840, (May 1991)
7. K. Tremblay, H. Ing, and R. A. Noulty, "Anthropomorphic Phantom Radiation Dosimetry Measurements," Bubble Technology Industries, Inc., BTI-90/6-6, (1992)
8. J. O. Johnson, J. D. Drischler, and J. M. Barnes, "Analysis of the Spring 1990 Two-Meter Box Test Bed Experiments Performed at the Army Pulse Radiation Facility (APRF)," Oak Ridge National Laboratory, ORNL/TM-11917, (August 1992)
9. Mark A. Oliver, "APRF Gamma Dose Measurements," Letter Report (Unpublished)
10. A. H. Kazi, "The Phantom In-A-Box Experiment of MAY 1990," Slide presentation made to the 1991 Radiation Environments Program Review, (Unpublished)
11. K. G. Kerris, "HDL Gamma Dose Measurements Using $\text{CaF}_2\text{:Mn}$ TLD's," Diamond Laboratories, October 1990, (Unpublished)
12. Guy Nurdin, "Neutron and Gamma Fields in the Vicinity of the APRF Reactor with an Anthropomorphic Source and the Real Profile of the Ground," Establisement Technique Central del'Armement, Centre'd Etudes du Bouchet, 94114 Arcueil, France, (Unpublished)

13. D. T. Ingersoll, R. W. Roussin, C. Y. Fu, and J. E. White, "DABL69: A Broad Group Neutron/Photon Cross-Section Library for Defense Nuclear Applications," ORNL/TM-10568 Oak Ridge National Laboratory, (June 1989)

APPENDIX A

SPRING 1990 2-METER BOX EXPERIMENTS
List of Participants by Organization

EXPERIMENTALISTS

Army Pulse Radiation Facility
Aberdeen Proving Ground, Maryland, USA 21005-5059
C. H. Heimbach, M. A. Oliver, A. H. Kazi

Bubble Technology Industries
Ottawa, Canada K0J1J0
H. Ing, K. Trembly

Defence Research Establishment Ottawa
Ottawa, Canada K1A024
T. F. Cousins, B. E. Hoffarth

Etablissement Technique Central del'Armement
Centre'd Etudes du Bouchet
94114 Arcueil, France
J. Dhermain, G. Nurdin, J. Laugier

Harry Diamond Laboratory
2300 Powder Mill Road
Adelphi, Maryland, USA
K. Kerris

ANALYSTS

Oak Ridge National Laboratory
P.O. Box 2008
Oak Ridge, Tennessee, USA 37831
J. M. Barnes, J. D. Drischler, J. O. Johnson

Science Applications International Corporation
San Diego, California USA 92121
S. D. Egbert, D. C. Kaul

INTERNAL DISTRIBUTION

1. B. R. Appleton	24. R. C. Ward
2. J. M. Barnes	25-26. EPMD Reports Office
3. T. J. Burns	27-28. Laboratory Records
4. J. D. Drischler	Department
5. C. M. Haaland	29. Laboratory Records
6. D. T. Ingersoll	ORNL-RC
7-11. J. O. Johnson	30. Document Reference
12. J. V. Pace	Section
13. W. A. Rhoades	31. Central Research
14. R. W. Roussin	Library
15-23. R. T. Santoro	32. ORNL Patent Section

EXTERNAL DISTRIBUTION

33. Director, Defense Nuclear Agency
ATTN: RARP (Dr. D. L. Auton)
6801 Telegraph Road
Alexandria, VA 22310-3398
34. Dr. Roger W. Brockett
Wang Professor of Electrical Engineering
and Computer Science
Division of Applied Science
Harvard University
Cambridge, Massachusetts 02138
35. Dr. N. Ricky Byrn
Nicholes Research Corp.
4040 So. Memorial Parkway
Huntsville, AL 35802
36. Director, Harry Diamond Laboratory
ATTN: SLCHD-NW-P (Mr. John Corrigan)
2800 Powder Mill Road
Adelphi, MD 20783-1197

37. Electronics Division, NES
ATTN: Dr. Tom Cousins
Defence Research Establishment Ottawa
Ottawa, Ontario, Canada, K1A 0Z4
38. Commander, U.S. Army Nuclear & Chemical Agency
ATTN: MONA-ZB (Dr. David Bash)
7500 Backlick Rd., Bldg. 2073
Springfield, VA 22150-3198
39. Etablissement Technique Central de l' Armement
ATTN: Dr. Joel Dhermain
Centre d'Etudes du Boucher
16 bis Avenue Prieur de la Cote d'or
94114 Arcueil-Cedex, France
40. Dr. John J. Dorning
Department of Nuclear Engineering & Engineering Physics
Thorton Hall, McCormick Road
University of Virginia
Charlottesville, Va 22901
41. Science Applications International Corporation
ATTN: Dr. Stephen Egbert
10260 Campus Point Drive
San Diego, CA 92121
42. Commander, U.S. Army Combat Systems Test Activity
ATTN: STECS-NE (Mr. John Gerdes)
Aberdeen Proving Ground, MD 21005-5059
43. Ministry of Defence, Atomic Weapons Establishment
ATTN: Dr. Kevin G. Harrison
Building A72, Aldermaston,
Reading, Berkshire, United Kingdom, RG7 4PR
44. Commander, U.S. Army Combat Systems Test Activity
ATTN: STECS-NE (Dr. C. Heimbach)
Aberdeen Proving Ground, MD 21005-5059
45. Director, Bubble Technology Industries, Inc.
ATTN: Dr. Harry Ing
Highway 17
Chalk River, Ontario, Canada, KOJ 1JO
46. Science Applications International Corporation
ATTN: Mr. Dean C. Kaul
10260 Campus Point Drive
San Diego, CA 92121

47. Commander, U.S. Army Combat Systems Test Activity
ATTN: STECS-NE (Dr. A. Halim Kazi)
Aberdeen Proving Ground, MD 21005-5059
48. Director, Armed Forces Radiobiology Research Institute
ATTN: MRAD (CDR Kearsly)
Bethesda, MD 20814-5145
49. Director, Defense Nuclear Agency
ATTN: RARP (MAJ Robert Kehlet)
6801 Telegraph Road
Alexandria, VA 22310-3398
50. Director, Harry Diamond Laboratory
ATTN: SLCHD-NW-P (Mr. Klaus Kerris)
2800 Powder Mill Road
Adelphi, MD 20783-1197
51. US Army Center for EQ/RSTA
ATTN: AMSEL-RSK (Dr. Stanley Kronenberg)
Fort Monmouth, NY 07703
52. Establissement Technique Central de l' Armement
ATTN: Dr. Jacques Laugier
Centre d'Etudes du Boucher
16 bis Avenue Prieur de la Cote d'or
94114 Arcueil-Cedex, France
53. Dr. James E. Leiss
Route 2, Box 142C
Broadway, VA 22815
54. Dr. Neville Moray
Department of Mechanical and Industrial Engineering
University of Illinois
1206 West Green Street
Urbana, IL 61801
55. Director, Defense Nuclear Agency
ATTN: RARP (Ms. Joan Ma Pierre)
6801 Telegraph Road
Alexandria, VA 22310-3398
56. Naval Surface Warfare Center
ATTN: CODE R41 (Mr. Gordon Reil)
New Hampshire Road
White Oak, MD 20903-5000

57. Commander, U.S. Army Foreign Science & Technology Center
ATTN: UVA (Dr. Roger Rydin)
220 7th Street NE
Charlottesville, VA 22901-5396
58. HEAD, Nuclear Radiation Effects
ATTN: Dr. Ludwig Schaenzler
Wehrwissenschaftliche Dienststelle
Postfach 1320
3042 Munster
Federal Republic of Germany
59. David L. Tilson
U.S. Army SDC
ATTN: CSSD-SA-EV
P.O. Box 1500
Huntsville, AL 35807
60. Commander, U.S. Army Foreign Science & Technology Center
ATTN: AIFRTA (Mr. Charles Ward)
220 7th Street NE
Charlottesville, VA 22901-5396
61. Dr. Mary F. Wheeler
Department of Mathematical Sciences
Rice University
P. O. Box 1892
Houston, Tx 77204-3476
62. Commander, U.S. Army Tank Automotive Command
ATTN: AMSTA-RSK (Mr. Greg Wolfe)
Bldg. 200
Warren, MI 48317-5000
63. Director, Defense Nuclear Agency
ATTN: RARP (Dr. Robert Young)
6801 Telegraph Road
Alexandria, VA 22310-3398
64. Office of the Assistant Manager for Energy
Research and Development
Department of Energy, Oak Ridge Operations
P.O. Box 2001
Oak Ridge, TN 37831
- 65-74. Office of Scientific and Technical Information
P.O. Box 62
Oak Ridge, TN 37830

75-77. S. Y. Whitaker
1830 Delphine Drive
Decatur, GA 30032

END

**DATE
FILMED**

10 / 22 / 92