AIM

Association for Information and Image Management

1100 Wayne Avenue, Suite 1100
Silver Spring, Maryland 20910
301/587-8202

Centimeter

Inches

MANUFACTURED TO AIM STANDARDS
BY APPLIED IMAGE, INC.

1 of 1

BNL-48950
INFORMAL REPORT

Six Dimensional Tracking Simulator for H⁻ Injection

S.Y. Lee and S. Tepikian

April 27, 1993

Informal Report

AGS Department

Brookhaven National Laboratory
Associated Universities, Inc.
Upton, Long Island, New York 11973
Under contract No. DE-AC02-76CH00016 with the

UNITED STATES DEPARTMENT OF ENERGY

RECEIVED

JUN 17 1993

OSTI

MASTER

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

BNL-48950
AGS/AD/93-7
UC-414

Six Dimensional Tracking Simulator for H⁻ Injection

S.Y. Lee and S. Tepikian

April 27, 1993

Informal Report

AGS Department

Brookhaven National Laboratory
Associated Universities, Inc.
Upton, Long Island, New York 11973
Under contract No. DE-AC02-76CH00016 with the

UNITED STATES DEPARTMENT OF ENERGY

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

SIX DIMENSIONAL TRACKING SIMULATION for H^- INJECTION IN AGS BOOSTER

S. Y. Lee and S. Tepikian

Abstract

The effect of Coulomb multipole scattering on the beam emittance is studied with the 6 dimensional injection program ARCHSIM by A. Thiessen.¹ Since the energy loss due to Bhabha scattering is small, the six dimensional simulation can be approximated into transverse 4 dimensional and longitudinal 2 dimensional tracking. The emittance growth agrees well with the multiple scattering theory. The beam loss occurs mainly in the adiabatic capture process in the longitudinal phase space.

I. Introduction

During the H^- injection process, the incident beam passes through the foil many times. The multiple Coulomb scattering between the incident particle and the stripper gives rise to emittance growth or beam loss. To control the emittance growth, one may need orbit bump manipulation in minimizing the effect of multiple scattering.

Besides the multiple Coulomb scattering, the particle in the low energy synchrotron would experience strong space charge force. Tracking with space charge has been extensively studied previously.^{2,3} We thus shall not repeat the calculation. This report concentrates on the emittance growth due to the multiple Coulomb scattering.

$$\epsilon = \frac{x^2 + (\alpha x + \beta x')^2}{\beta} \quad (6)$$

The emittance growth becomes (see appendix)

$$\Delta\epsilon = 2\beta x \langle \Phi^2 \rangle = 2\beta n \langle \theta^2 \rangle N \quad (7)$$

Thus, the emittance growth is proportional to N and the β -amplitude at the stripper location. For the AGS Booster, we expect $\Delta\epsilon_y \approx 0.1 N \pi \text{ mm mrad}$.

III. Numerical Simulation

A six dimensional simulation program was written by Thiessen et al.¹ to simulate the multiturn injection. The process includes energy loss mechanism due to Bhabha scattering and the Coulomb multiple scattering. The machine parameter at the stripper location is:

$$\begin{aligned} \beta_x &= 9.8939 \text{ m} \\ \alpha_x &= 1.4535 \\ \beta_y &= 5.4126 \text{ m} \\ \alpha_y &= 0.9565 \\ x_p &= 2.5147 \text{ m} \\ x_p' &= 0.3903 \\ Q_x &= 4.82 \\ Q_y &= 4.83 \\ \gamma T &= 4.8812 \end{aligned}$$

The injection beam has emittance $\epsilon = 6\pi \text{ mm mrad}$ from the 200 MeV LINAC. The pulse length is about $100 \mu\text{s}$. Thus, the number of turns in the injection process is about 80. In our simulation, we choose 2000 particles divided into N turns injections.

Figure 1 shows the final beam emittance vs N , the number of turns in the injection process. The upper curve shows the final emittance vs N in multiple Coulomb scattering. The emittance increases very fast in the first few turns of the injection process. This is due mainly to the broad distribution of the Coulomb scattering in Eq.(1). After $N=5$, or $Nn \approx 30$ interactions, the emittance grows linearly with N . Figure 1 indicates that $\Delta\epsilon \approx 0.1 N \pi \text{ mm mrad}$. This is in reasonable agreement with the estimate of Eq. (7).

The lower part of Fig. 1 shows the time saving feature of the ARCHSIM program, where the $\theta_{\min}$ is multiplied by a bugger factor $f_B = 2.5$. This bugger factor decreases the total cross-section σ_T by 6.25 times. Since

$$\begin{aligned} n &\propto \sigma_T \propto \theta_{\min}^{-2} f_B^{-2} \\ \langle \theta^2 \rangle &\propto \theta_{\min}^2 f_B^2, \end{aligned}$$

Equation (7) should be independent of the bugger factor f_B . The resulting emittance growth in the lower curve of Figure 1 shows clearly similar behaviour as that of $f_B = 1$ in the upper curve, $\Delta\epsilon \approx 0.07N \pi \text{ mmmrad}$.

Let us assume that the beam profile can be represented by a Gaussian distribution, i.e.

$$\rho(x, x') = \frac{1}{\pi \epsilon_0} e^{-\frac{x^2 + (\alpha x + \beta x')^2}{\beta \epsilon_0}} \quad (\text{A.1})$$

where ϵ_0 is the emittance of the beam.

The passage of the beam through the foil can be represented by the kick angle θ of a Coulomb scattering, i.e.,

$$x' \rightarrow x' + \theta \quad (\text{A.2})$$

with a Gaussian distribution function,

$$f(\theta) = \frac{1}{\sqrt{2\pi}\sigma_\theta} e^{-\theta^2/2\sigma_\theta^2} \quad (\text{A.3})$$

The final distribution function after a passage through the foil becomes

$$\begin{aligned} \bar{\rho}(x, x') &= \frac{1}{\pi \epsilon_0} \frac{1}{\sqrt{2\pi}\sigma_\theta} \int_{-\infty}^{\infty} e^{-\frac{x^2 + (\alpha x + \beta x' + \beta \theta)^2}{\beta \epsilon_0}} e^{-\frac{\theta^2}{2\sigma_\theta^2}} d\theta \\ &= \frac{1}{\pi \epsilon_0} \frac{\tilde{\sigma}_\theta}{\sigma_\theta} e^{-\frac{x^2 + (\alpha x + \beta x') \left(1 - \frac{2\sigma_\theta^2 f}{\epsilon_0}\right)}{\beta \epsilon_0}} \end{aligned} \quad (\text{A.4})$$

where

$$\tilde{\sigma}_\theta^{-2} = \sigma_\theta^{-2} + 2 \frac{\beta}{\epsilon_0} \approx \sigma_\theta^{-2} \quad (\text{A.5})$$

Note that the distribution (A.4) does not change the x distribution due to the multiple kick, i.e., the multiple kicks change only the x' distribution. The Ellipse in the exponent of Eq. (A.4) is not a constant of motion but encompassed by an ellipse with emittance

$$\epsilon = \epsilon_0 / \left(1 - 2 \frac{\tilde{\sigma}_\theta^2 \beta}{\epsilon_0}\right) \approx \epsilon_0 + 2 \tilde{\sigma}_\theta^2 \beta \quad (\text{A.6})$$

We thus obtain

$$\Delta\epsilon / \Delta N = 2 \beta \tilde{\sigma}_\theta^2 \approx 2 \beta n \langle \theta^2 \rangle \quad (\text{A.7})$$

Figure 2

**DATE
FILMED**

8 / 19 / 93

END