15 cm DuoPIGatron Ion Source

W. L. Stirling
C. C. Tsai
P. M. Ryan

MASTER

OAK RIDGE NATIONAL LABORATORY

OPERATED BY UNION CARBIDE CORPORATION FOR THE ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

DISTRIBUTION STATEMENT 3

27
11-11-76
25 D 7115

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Printed in the United States of America. Available from
National Technical Information Service
U.S. Department of Commerce
5285 Port Royal Road, Springfield, Virginia 22161
Price: Printed Copy \$4.00; Microfiche \$2.25

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration/United States Nuclear Regulatory Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Contract No. W-7405-eng-26

THERMONUCLEAR DIVISION

15 cm DUOPIGATRON ION SOURCE

W. L. Stirling, C. C. Tsai, and P. M. Ryan

(to be published in The Review of Scientific Instruments)

Date Published: October 1976

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

NOTICE This document contains information of a preliminary nature and was prepared primarily for internal use at the Oak Ridge National Laboratory. It is subject to revision or correction and therefore does not represent a final report.

OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37830
operated by
UNION CARBIDE CORPORATION
for the
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

TABLE OF CONTENTS

Abstract	v
Introduction	1
Source Operation	2
Source Performance	4
Future Improvements.	5
Acknowledgments	7
References	9
Figure Captions.	11
Table Caption.	11
Figures	13
Table I.	17
Distribution	19

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

15 CM DUOPIGATRON ION SOURCE*

W. L. Stirling, C. C. Tsai, and P. M. Ryan
Oak Ridge National Laboratory
Oak Ridge, Tennessee 37830

ABSTRACT

The 10 cm (grid diameter) duoPIGatron ion source¹ produces pulsed hydrogen ion beams of 10 to 15 A beam current in the 20 to 40 keV energy range for a duration of a few tenths of a second. To fulfill the requirements of the next generation of high-power neutral beam injectors for heating plasmas in CTR devices, this source has been enlarged to a version 15 cm in grid diameter. In addition, by utilizing a magnetic multipole line cusp field confinement method, the plasma created is characterized over the 15 cm grid diameter by a noise level within $\pm 10\%$ and spatial density variations within $\pm 5\%$ at a density on the order of 10^{12} cm^{-3} . This larger source has operated reliably and produced a beam current exceeding 30 A of hydrogen at 27 keV. Initial operation of a 20 cm version of this source employing line cusp confinement has produced an extraction current of 60 A at 33 keV.

*Research sponsored by the Energy Research and Development Administration under contract with Union Carbide Corporation.

INTRODUCTION

Neutral beam injection heating experiments in ATC, ORMAK, and TFR have demonstrated that energetic neutral beams can heat the toroidal plasma significantly.^{2,3} To heat the plasma in CTR devices to reactor temperatures requires high-power energetic neutral beams with tens of amperes of hydrogen (or deuterium) beam current of energy range 10 to 100 keV. For this application, the plasma source should be capable of producing a quiescent, uniform, and dense plasma in order to produce a well collimated, high current density beam; for example, the noise level and spatial density variations should be well below $\pm 10\%$ over several hundreds of square centimeters at a density of a few times 10^{12} cm^{-3} . The other desired features are high gas and power efficiencies and source reliability. Plasma sources such as the multi-filament source developed at Lawrence Berkeley Laboratory and the duo-PIGatron ion source developed at Oak Ridge National Laboratory are able to fulfill some of these basic requirements. They are being seriously considered for use in the development of future high-power neutral beam injectors for PLT, PDX, and TFTR at PPPL, Doublet III at GA, and ORMAK Upgrade and TNS at Oak Ridge.

In the present state of technology, the plasma source requires at least 1 kW of arc power to produce 1 ampere of beam current. In order to raise the arc power efficiency, it is necessary to improve spatial uniformity and noise level of the source plasma. We have undertaken a study to improve the plasma properties of a duoPIGatron ion source modified with line cusp confinement, bearing in mind that the magnetic multipole line cusp containment device⁴ developed at UCLA is capable of

producing a desirable quiescent and uniform plasma in argon. The modified source has a magnetic multipole line cusp confining field around the arc chamber just above the target cathode. Preliminary results from a modified 15 cm duoPIGatron ion source indicate that it is capable of generating a desirable, quiescent, uniform, and dense plasma for producing 30 A of hydrogen ion current at 27 keV energy at a beam current density of above 300 mA cm^{-2} .

After a brief review of the source operation, we will describe recent progress and some envisaged future improvements.

SOURCE OPERATION

Figure 1 shows the sketch of a conventional duoPIGatron ion source^{5,6} with a 15 cm grid diameter. Figure 2 shows the modified duoPIGatron with the line cusp added. (It should be acknowledged that our arc chamber is a variation of the magnetic multipole containment device⁴ which was developed at UCLA by MacKenzie and associates.) The line cusp field arrangement is made of 12 columns of permanent magnets about 15 cm long, magnetized radially with opposite polarity for the adjacent columns. The columns lie on a circle having a diameter of 25 cm. The magnets (0.96 cm square by 2.54 cm long; maximum magnetic field $B \approx 4 \text{ kG}$) have been set in the slots on the walls of the arc chamber and just above the target cathode. The plasma generator consists of hot cathodes, intermediate electrode, anode 1, anode 2, and target cathode as in the standard duoPIGatron. The target cathode is sometimes referred to as the plasma electrode or screen electrode. The intermediate electrode serves as a magnetic pole to provide an axial magnetic field, the

source field, in the anode region. A pulsed arc voltage is applied between the anodes and hot cathodes. The intermediate electrode and target cathode are returned to the arc supply positive terminal through resistances of 1 K Ω and 250 Ω respectively.

In conventional source operation, the source contains a cathode plasma and a PIG plasma separated by a double layer. The cathode plasma is produced within the intermediate electrode chamber by primary electrons emitted from the hot cathodes. In this region of zero magnetic field, the plasma density is determined essentially by the arc current and gas pressure because of the low electron kinetic energy (<30 eV).

The PIG plasma is produced in the region enclosed by the anodes, intermediate electrode, and target cathode. This plasma is created essentially by energetic electrons which originate from the cathode plasma and which are accelerated through the double layer. The electrons are then constrained by the applied magnetic field and oscillate between the intermediate electrode and the target cathode. They initiate a "Penning ion gauge" (PIG) discharge, which is the principal ionization mechanism. Because of their high energy and long path length, they create a dense PIG plasma; consequently, the density of the PIG plasma is mainly affected by the applied magnetic field, gas pressure, arc voltage, and arc current.

While the cathode plasma works as an electron source and supplies ionizing electrons to the PIG discharge, the PIG plasma works as an ion source and supplies ions to the extraction electrodes in order to form a high-current ion beam. The double layer works as a controlling mechanism which determines the PIG plasma uniformity and the source reliability.⁵

In the case of the modified duoPIGatron, the applied source field is much weaker and plasma confinement is accomplished by the line cusp magnetic field. The line cusp field also reduces the direct loss to the second anode of ionizing electrons in the PIG discharge. In this way the modified duoPIGatron provides magnetic field free containment over the extraction area and hence an easily achieved, uniform, dense PIG plasma.

SOURCE PERFORMANCE

Figure 3 shows a comparison of the density profiles for the conventional duoPIGatron, labeled NORMAL, and the modified duoPIGatron, labeled CUSP. Plasma density was determined from ion saturation current measured by a Langmuir probe located about 0.6 cm above the target cathode. In the conventional duoPIGatron, the noise level is below $\pm 10\%$ and the plasma density variation over the 15 cm grid diameter is within $\pm 15\%$ at a density of above $2 \times 10^{12} \text{ cm}^{-3}$. The source has been operated reliably to produce a hydrogen ion beam of 20 A at 25 keV. Maximum density can be increased by increasing the source magnetic field, but the uniformity is impaired and high voltage spitting becomes severe. Uniformity can be improved by lowering the magnetic field, but the density is then too low to produce high-current ion beams because the weak magnetic field cannot effectively confine the energetic ionizing electrons within the PIG arc column. In addition, the weaker magnetic field increases the loss rate of charged particles from the PIG plasma to the anode walls.

The confinement and uniformity problems have both been alleviated in the modified duoPIGatron source. The line cusp magnetic field effectively confines both the energetic ionizing electrons and the charged particles within the PIG plasma. The modified 15 cm source has been operated reliably while producing a hydrogen ion beam with a current exceeding 30 A at 27 keV. Both the current and voltage of the ion beam were limited by the associated electrical supplies: high-voltage power supply, high-voltage modulator, and arc power supply.

Some characteristics of the conventional and the modified 15 cm sources are listed in Table 1. The column denoted by NORMAL is for the conventional source and that denoted by CUSP is for the modified source. For the modified source, the applied magnetic field represented by I_{sm} is weaker, and the potential difference between the anode and the target cathode, $V_A - V_{TC}$, is lower than that for the conventional source. The electron temperature, T_e , is higher and plasma uniformity, Δn , is improved over the grid diameter. The plasma density and uniformity appear more sensitive to the effect of pressure in the modified source; this increased sensitivity is probably caused by the lower applied magnetic field. The cusp field arrangement in the modified source plays a crucial role⁴ in improving the plasma density and uniformity.

FUTURE IMPROVEMENTS

Preliminary values for plasma density and uniformity were reported in the previous section. On the basis of the discharge model for the duoPIGatron and the information given by Table 1, these values may be further improved by the following modifications:

1) Optimizing the arrangement of line cusp magnetic field. According to MacKenzie and associates,⁴ the magnetic multipole confinement is a very effective way of confining a dense, uniform, large-volume, and quiescent plasma. This is because such an arrangement can effectively confine both the primary electrons and the charged particles in the plasma. However, as the number of magnetic multipoles is increased, the plasma density is lowered and the plasma uniformity is improved. A similar effect may exist in the source plasma in the modified duoPIGatron. By optimizing the length and number of columns in the line cusp magnetic field, and by adding a flux return path for the magnets, the source performance may eventually be improved.

2) Optimizing the source electrodes, particularly in dimension, configuration, and relative position. This will improve both the radial distribution of the ionizing electrons in the PIG discharge and their ionization efficiency. It may also reduce the loss rate of plasma to the electrodes and could lead to improvement in plasma density and uniformity. The source performance and reliability may also be improved.

3) Biasing the target cathode negative to the potential at which it floats when the source operates as a normal duoPIGatron. This should reduce the rate of PIG discharge ionizing electrons lost to the target cathode. The ionization efficiency of the ionizing electrons should thus be improved and the PIG discharge intensified. This modification may raise the plasma density without impairing the plasma uniformity.

The associated electrical supplies limitation mentioned earlier has been removed by installing a 60 kV/60 A high-voltage power supply, a 60 kV/60 A modulator, and a 100 VDC/800 A arc power supply.

In addition to developing the modified 15 cm source we have enlarged the duoPIGatron to a 20 cm diameter utilizing the line cusp confinement geometry. Initial operation has produced a 60 A beam of hydrogen at 33 keV. Optimization of the source parameters is proceeding with a goal of 60 A at 40 keV. We also have 22 cm and 25 cm ion source components in fabrication. It seems certain, therefore, that the duoPIGatron ion source, suitably modified and upgraded, is capable of development for use in future high-power beam injectors.

ACKNOWLEDGMENTS

The authors would like to express their appreciation to R. C. Davis for his valuable technical assistance. We also acknowledge helpful discussions with L. R. Grisham, H. H. Haselton, D. E. Schechter, G. Schilling, and L. D. Stewart.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

REFERENCES

1. L. D. Stewart et al., "Neutral Beam Injector Research and Development Work in the USA," paper to be presented at the 6th Conference on Plasma Physics and Controlled Nuclear Fusion, Berchtesgaden, October 6-13, 1976.
2. O. B. Morgan, Paper VI-1, and T. C. Jernigan et al., Paper VI-9, in Proc. Second Symposium on Ion Sources and Formation in Ion Beams, Berkeley, California, October, 1974.
3. J. D. Callen, Paper 7R, and L. A. Berry, Papers 7A1, 2, 3, Bull. Am. Phys. Soc. Series II, 20, (October, 1975).
4. R. Limpaecher and K. R. MacKenzie, Rev. Sci. Instrum. 44, 726 (1973); K. N. Leung et al., Phys. Let. 51A (8) 490 (1975).
5. C. C. Tsai et al., ORNL/TM-5292 (1976).
6. R. C. Davis et al., Rev. Sci. Instrum. 46, 576 (1975).

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

FIGURE CAPTIONS

1. 15 cm Prototype DuoPIGatron Ion Source
2. Modified 15 cm DuoPIGatron Ion Source with Magnetic Multipole Line Cusp Confining Field
3. Typical Density Profiles of Conventional and Modified 15 cm Ion Source

TABLE CAPTION

1. Source Characteristics of Conventional and Modified 15 cm DuoPIGatron Ion Source

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

Fig. 1. 15 cm Prototype DuoPIGatron Ion Source.

Fig. 2. Modified 15 cm DuoPIGatron Ion Source with Magnetic Multipole Line Cusp Confining Field.

ORNL-DWG 75-11295R

Fig. 3. Typical Density Profiles of Conventional and Modified 15 cm Ion Source.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

TABLE I

SOURCE CHARACTERISTICS

	NORMAL	CUSP
I_{SM}	70 TO 80 A	20 TO 40 A
I_{ARC}	UP TO 400 A	UP TO 450 A
V_{ARC}	UP TO 150 V	UP TO 150 V
$V_A - V_{TC}$	≥ 50 V	≤ 30 V
kT_E	~ 6 eV	~ 12 eV
$\Delta n / 15$ cm DIAM	$\geq 15\%$	$\leq \pm 5\%$
P_{TC}	~ 10 mTorr	~ 10 mTorr

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

INTERNAL DISTRIBUTION

1. G. C. Barber	21. N. S. Ponte
2. L. A. Berry	22. M. Roberts
3. J. D. Callen	23. J. A. Rome
4. J. F. Clarke	24. M. W. Rosenthal
5. W. K. Dagenhart	25. P. M. Ryan
6. R. A. Dandl	26. D. E. Schechter
7. R. C. Davis	27. G. Schilling
8. C. A. Foster	28. D. Steiner
9. L. R. Grisham	29. L. D. Stewart
10. H. H. Haselton	30. W. L. Stirling
11. P. N. Haubenreich	31-41. C. Tsai
12. T. C. Jernigan	42. J. H. Whealton
13. G. G. Kelley	43. R. E. Wright
14. J. Kim	44-45. Central Research Library
15. H. M. Long	46. Document Reference Section
16. J. F. Lyon	47-48. Laboratory Records Department
17. F. B. Marcus	49. Laboratory Records, ORNL R. C.
18. D. G. McAlees	50. Patent Office
19. S. L. Milora	51-52. Thermonuclear Division Library
20. O. B. Morgan	53-79. Technical Information Center
Oak Ridge

EXTERNAL DISTRIBUTION

80. J. W. Beal, Development & Technology, Division of Controlled Thermo-nuclear Research, Energy Research and Development Administration, Washington, DC 20545.
81. Dr. Klaus Berkner, University of California, Lawrence Berkeley Laboratory, Berkeley, CA 94720.
82. Dr. A. Cole, Culham Laboratory, IAEA Research Group, Abingdon, Oxfordshire, OX14 3DB ENGLAND.
83. Dr. W. S. Cooper, University of California, Lawrence Berkeley Laboratory, Berkeley, CA 94720.
84. S. O. Dean, Assistant Director, Office of Confinement Systems, Division of Controlled Thermonuclear Research, Energy Research and Development Administration, Washington, DC 20545.
85. Harold K. Forsen, Exxon Nuclear Co., Inc., 777 106th Ave., NE, Bellevue, WA 98004.
86. T. K. Fowler, University of California, Lawrence Livermore Laboratory, P. O. Box 808, Livermore, CA 94551.
87. H. P. Furth, Plasma Physics Laboratory, Princeton University, Princeton, NJ 08540.

88. Dr. C. Geller, CEA - Centre d'Etudes Nucleaire, Division of Plasma Physics, Grenoble, FRANCE.
89. Dr. T. S. Green, Culham Laboratory, UKAEA Research Group, Abingdon, Oxfordshire, OX14 3DB ENGLAND.
90. R. L. Hirsch, Director, Controlled Thermonuclear Research, Division of Research, Energy Research and Development Administration, Washington, DC 20545.
91. Dr. E. H. Hooper, University of California, Lawrence Livermore Laboratory, P. O. Box 808, Livermore, CA 94550.
92. Dr. J. Junker, Max-Planck Institut fur Plasmaphysik, Abteilung E2, 8046 Garching bei Munchen, Federal Republic of Germany.
93. Librarian, Culham Laboratory, UK Atomic Energy Authority, Abingdon, Berkshire, ENGLAND.
94. Librarian, Max-Planck Institute fur Plasmaphysik, Abteilung E2, 8046 Garching bei Munchen, Federal Republic of Germany.
95. Plasma Physics Library, Plasma Physics Laboratory, Princeton University, P. O. Box 451, Princeton, NJ 08540.
96. Shinzaburo Matsuda, Thermonuclear Laboratory, Japan Atomic Energy Research Institute, Tikai, Naka, Ibaraki, JAPAN.
97. T. Ohkawa, Gulf-General Atomic, Inc., P. O. Box 608, San Diego, CA 92112.
98. Dr. K. Prelec, Brookhaven National Laboratory, Upton, Long Island, NY 11973.
99. Dr. R. V. Pyle, University of California, Lawrence Berkeley, Laboratory, Berkeley, CA 94720.
100. D. J. Rose, Department of Nuclear Engineering, Massachusetts Institute of Technology, Cambridge, MA 02139.
101. F. R. Scott, Electrical Power and Research Institute, 3412 Hillview Ave., P. O. Box 10412, Palo Alto, CA 94303.
102. N. N. Semashko, Kurchatov Atomic Energy Institute, Moscow, USSR.
103. TH. J. M. Sluyters, Brookhaven National Laboratory, Upton, Long Island, NY 11973.
104. D. R. Sweetman, Culham Laboratory, UKAEA Research Group, Abingdon, Oxfordshire, OX14 3DB ENGLAND.

105. E. Thompson, Culham Laboratory, UKAEA Research Group, Abingdon, Oxfordshire, OX14 3DB ENGLAND.
106. V. M. Tucheich, (Attn: V. E. Golant), A. F. Ioffe Physical-Institute of the Academy of Sciences of the U.S.S.R., Leningrad K-21, U.S.S.R.
- 107-
110. Dr. F. Valcx, DOH-PFC, Centre d'Etudes Nucleaires, BP No. 6, Fontenay-aux-Roses (Seine), FRANCE.
111. J. M. Williams, Assistant Director, Development and Technology, Division of Controlled Thermonuclear Research, Energy Research and Development Administration, Washington, DC 20545.
112. J. T. Woo, Massachusetts Institute for Technology, Rm 38-176, Cambridge, MA 02139.
113. Dr. Herbert H. Woodson, Chairman, Department of Electrical Engineering, The University of Texas at Austin, Austin, TX 78712.
114. Director, Research and Technical Support Division, ERDA, ORO.