ANNUAL PROGRESS REPORT

DE-FG02-91ER40669

"Inverse Free Electron Laser Beat-Wave Accelerator Research"

T.C. Marshall and A. Bhattacharjee

Columbia University

August, 1992

DOE/ER/40669--2

DE93 002770

I. Summary

In the past twelve-month period, we have completed our experimental study of the inverse-FEL autoaccelerator. The IFEL accelerates electrons by stimulated absorption of a laser pulse passing along an electron beam in an undulator; the autoaccelerator is a configuration we have developed at Columbia to test the principle of resonant absorption and acceleration.

The experiment uses the Columbia pulseline accelerator, which provides an electron beam at 800kV, 200A. This single beam passes through an undulator which is made up of two parts, in series. The first section of the undulator is a constant period section, which, together with a pair of mirrors, generates about 5MW of power at a wavelength ~ 1.5 mm. The electrons then enter a second section of undulator where the electromagnetic wave is partly absorbed by acceleration of a group of resonant, trapped electrons. This undulator has a period somewhat longer than the first section, and the period is also increased progressively along the electron beam. We have observed absorption of $\sim 50\%$ of the 1.5mm power and we have observed a group of electrons accelerated to energy >1 MeV. These results have been presented at recent conferences [Beams

MASTER

ep

‘92, Washington, May 1992; and the Workshop on Advanced Accelerator Concepts, Port Jefferson, June, 1992]. A thesis and technical report have been completed.

The Columbia IFE $\dot{L}$ A provided an accelerating gradient of 8kV/cm. Using the same codes, but using a conservative design, one can project a gradient ~ 1 MV/cm in an accelerator module which uses a CO₂ laser pulse, a stronger undulator field, and a 50MV electron beam. A module about 50cm in length would be required. Such a project which could test the technical ideas in a typical accelerator environment using state of the art equipment; the Columbia experiment tests the principle, and indeed was the first to do so, however, high accelerating gradients were not possible in our experiment because of the lower laser power and undulator field.

The experiment was modeled extensively by a numerical program which incorporates the finite structure of the EM waves and finite beam filling-factor, and one-dimensional electron motion together with realistic parallel momentum spread. A travelling-wave (single pass) computation was done, taking initial conditions provided by experimental measurements. Using this code, we have been able to understand the various results we have obtained experimentally.

In the preprint of the workshop paper which is included as part II of this report, figure 1 shows the experimental arrangement that was used, including the electron energy spectrometer. Figure 4 of the preprint shows a spectrum of the accelerated electrons (data points). The solid line is the prediction of the numerical model, and the broken line is the injected

energy spectrum of bunched electrons into the accelerator section. The numerical model was used to design the proper taper of the accelerator undulator.

This research relates to the development of new accelerator technology. Given the limitations of rf-linac technology (about 10MV/m gradient), a number of techniques have been proposed that will increase the gradient by one or more orders of magnitude. These include the development of higher power and/or shorter wavelength rf power sources, IFEL, Plasma Beat Wave Accelerator, etc. Some of these new ideas, including the IFEL here, have undergone preliminary experiments to test some of the new principles, with varying degrees of success and promise. The direction of future work would involve, in the case of the IFEL, a relevant test of the technology in an accelerator laboratory context. For example, one might attempt to accelerate a 50MV electron beam obtained from an rf linac to 100MV, using an external laser pulse [perhaps obtained from a Free Electron Laser] as described above. This demonstration would require the integration of the various technologies. In addition, there are some physics questions involving the transport and guiding of radiation along an electron beam where distances longer than the Rayleigh Range of the optical beam are necessary, for example the quasi-optical waveguide. Measurement of the electron beam quality of the accelerated beam and comparison with codes is also an important piece of physics that could be carried out in this new project. We show [following page] results from our numerical study of such a proposed IFEL experiment, where the electron beam is “prebunched” in an undulator with a low power laser wave, and then accelerated in a tapered undulator by a constant-intensity

Acceleration of a 50MV electron beam in an IFEL by a 10u laser.

Acceleration is in two sections: first, a constant-period undulator (period, 2.5cm, length 25cm, field 1.5T) together with a lower-power laser signal of $10E10$ watt/cm², followed by a 75cm section of tapered undulator ($dl/dz = .077$) together with a higher-power laser signal of constant intensity $8 \times 10E11$ w/cm². The first section is a buncher and is needed to trap most of the electrons. A significant number of electrons are accelerated to 100MV.

high power laser beam at the same wavelength. A large fraction of the particles are trapped, and most are accelerated to a well-defined energy.

There are other ideas which can be tested that involve the IFEL technology, notably the IFEL Beat Wave Accelerator. In this proposed device, a low energy electron beam is used to generate a high-power FEL signal and a bunched electron beam in an undulator; a high energy pulse of electrons may then be injected into the beamline in such a phase that the high energy electrons will be accelerated by the space charge of the bunches formed by the beat wave. The phase velocity of the bunches (and therefore the velocity of the accelerated high energy electrons) can be manipulated by tapering the radius of the drift tube. The principle of the IFEL-BWA differs from the IFEL; the latter device accelerates electrons by trapping the particles in the beat wave, and then accelerating them by varying the undulator parameters in such a way as to cause the beat wave to move slightly faster than the beam. As part of this project we plan to make measurements of the accelerating field and to do certain theoretical calculations, as outlined in our original proposal, in the next year.

The DOE has, in addition to supporting a portion of the IFELA (begun by the NSF), provided funding for improving the laboratory instrumentation. This has been very helpful in completing the IFELA in a timely and successful way. Specifically, two digital oscilloscopes have been installed, together with a dedicated computer which handles, stores, and processes all the data. Since January 1, we have changed the configuration of the experiment so that research involving 24GHz FEL physics can be carried out. The lower frequency has the advantage that now we can use a

coherent source (40kW magnetron) as a travelling-wave signal input to a new undulator that has a 4cm period. This makes possible measurements which require a fixed phase reference, specifically the phase velocity and field strength of the space charge wave in the electron bunches. This FEL is now operating, and we have observed travelling-wave gain as well as oscillator power.

The experiment is currently "on schedule", and we should be making measurements on the FEL space charge waves in the second year of this two-year project. These measurements relate to the application of the FEL in a "two-beam" accelerator, where a low energy high intensity electron beam is bunched by the FEL mechanism, and then a second higher-energy beam is injected into the space-charge field bunches so that it becomes accelerated as we vary the phase velocity of the space charge wave by tapering the diameter of the drift tube.

Two students are being supported by DOE on this project: an experimenter, involved with measurements of the space charge fields in the 24GHz FEL, and a theoretician, who has recently started working on the problem of non-adiabatic separatrix crossings of nearly (or slightly) trapped electrons.

Part II of this report is a preprint of our paper presented at the Port Jefferson Workshop. A Technical Report covering all details of this work was distributed in July 1992 .

Publications and Presentations

1. "An Inverse FEL Autoaccelerator", I. Wernick and TC Marshall, paper PG-33 at "Beams '92, Ninth International Conference on High-Power Particle Beams", May 25-29, 1992, Washington DC
2. "Experimental Test of the Inverse Free Electron Laser Accelerator Principle", Iddo Wernick and TC Marshall, accepted for publication in Physical Review A46, September 15, [1992]
3. "An Inverse FEL Accelerator Experiment", Iddo Wernick and TC Marshall, presented at the Third Workshop on Advanced Accelerator Concepts, Port Jefferson NY, 14-20 June 1992; published as a paper in the AIP Conference Proceedings Series.
4. Technical Report, "Acceleration of Electrons Using an Inverse Free Electron Laser Auto-Accelerator", doctoral thesis of Iddo Wernick [July, 1992]; report DOE/ER/40669-1

Conf. paper Cycled Separately .

END

**DATE
FILMED**

12 / 10 / 92