

27  
12-28-76  
25 CG. b. NTIS

# 1976 Intercomparison of Personnel Dosimeters

L. W. Gilley  
H. W. Dickson  
D. J. Christian

**MASTER**

**OAK RIDGE NATIONAL LABORATORY**

OPERATED BY UNION CARBIDE CORPORATION FOR THE ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

## **DISCLAIMER**

**This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.**

## **DISCLAIMER**

**Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.**

Printed in the United States of America. Available from  
National Technical Information Service  
U.S. Department of Commerce  
5285 Port Royal Road, Springfield, Virginia 22161  
Price: Printed Copy \$4.00; Microfiche \$3.00

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration/United States Nuclear Regulatory Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Contract No. W-7405-eng-26

HEALTH PHYSICS DIVISION

1976 INTERCOMPARISON OF PERSONNEL DOSIMETERS

L. W. Gilley, H. W. Dickson and D. J. Christian

**NOTICE**  
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Date Published: December 1976

**NOTICE** This document contains information of a preliminary nature. It is subject to revision or correction and therefore does not represent a final report.

OAK RIDGE NATIONAL LABORATORY  
Oak Ridge, Tennessee 37830  
operated by  
UNION CARBIDE CORPORATION  
for the  
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

**MASTER**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED  
EP

**THIS PAGE  
WAS INTENTIONALLY  
LEFT BLANK**

CONTENTS

	Page
TABLES . . . . .	iv
FIGURES . . . . .	v
ABSTRACT . . . . .	1
REFERENCES . . . . .	6
APPENDIX A . . . . .	7-8
List of Participants Personnel Dosimeter Intercomparison Study . . . . .	7-8

## TABLES

	Page
1. Summary of Reactor Operations for Intercomparison . . . . .	9
2. Dosimeters Used by Participants . . . . .	9
3. Calculation of HPRR Spectrum for NAD Intercomparison . . . . .	10
4. Dose Conversion Factors and Average Quality Factors for HPRR Spectra . . . . .	11
5. Neutron Absorbed Dose and Dose Equivalent Calculated from HPRR Fission Yields . . . . .	11
6. Reference Values of Dose and Dose Equivalent . . . . .	12
7. Results of Personnel Dosimetry Intercomparison, February 18-19, 1976 - Unshielded . . . . .	13
8. Results of Personnel Dosimetry Intercomparison, February 18-19, 1976 - Lucite Shield . . . . .	14
9. Results of Personnel Dosimetry Intercomparison, February 18-19, 1976 - Steel Shield . . . . .	15
10. Summary of Results of Front Exposures . . . . .	16



FIGURES

	Page
Fig. 1. A Typical Placement of Dosimeters on the Front of Phantoms . . . . .	17
Fig. 2. A Typical Experimental Setup with the Steel Shield in Place . . . . .	18

## 1976 INTERCOMPARISON OF PERSONNEL DOSIMETERS\*

L. W. Gilley, H. W. Dickson and D. J. Christian

### ABSTRACT

1976 INTERCOMPARISON OF PERSONNEL DOSIMETERS--The second Personnel Dosimeter Intercomparison Study (PDIS) was conducted at Oak Ridge National Laboratory's DOSAR Facility during the period February 18-19, 1976. Eleven independent organizations participated in an intercomparison of neutron and gamma-ray dosimeters used for routine personnel dosimetry. The dosimeters, which were shipped to the DOSAR Facility, were exposed at the Health Physics Research Reactor to one of three "standardized" radiation fields which have been used for the past several years for intercomparing nuclear accident dosimeters. The results of PDIS reveal that estimates of dose equivalent vary over a wide range. For a given radiation field these dose estimates may vary by more than a factor of 2, indicating the need for continued evaluation of the response of personnel dosimeters used in mixed fields of neutron and gamma radiation.

---

\*Research sponsored by the Energy Research and Development Administration under contract with Union Carbide Corporation.

The second Personnel Dosimetry Intercomparison Study<sup>1</sup> (PDIS) was conducted at Oak Ridge National Laboratory's DOSAR Facility during the period February 18-19, 1976, with eleven groups participating. Two other groups irradiated dosimeters under essentially identical conditions a few days later and their results are included in this report. The participants are listed in Appendix A. The Health Physics Research Reactor was used to produce radiation fields with known energy spectra and intensities. These fields were produced under conditions similar to those previously used for other intercomparison studies<sup>2,3</sup> and, as such, are considered "standard" fields. The bare, unshielded reactor or the reactor used with either of two shields, a 12-cm-thick Lucite shield or a 13-cm-thick steel shield, provides three different neutron and gamma-ray spectra. A 14 MeV neutron generator was also used to expose dosimeters, but the generator failed to operate properly and produced a neutron dose less than 4 mrad and a gamma dose less than 3 mrad. Therefore, the results of the 14 MeV exposures are not included in this report.

In order to produce the levels and spectra likely to be encountered in routine personnel monitoring, the reactor was operated as shown in Table 1. All badges were placed on water-filled trunk portions of Bomab phantoms at three meters. The placement of dosimeters on the phantoms is shown in Fig. 1 and a typical experimental arrangement with the steel shield in place is shown in Fig. 2.

Generally, the dosimeters were mailed or shipped to the DOSAR a few days in advance of the intercomparison. The dosimeters were returned in a similar manner the day after the intercomparison exposures were completed. Local laboratories hand carried their dosimeters back and forth. Dosimeters from two participants arrived late and, therefore, an additional "identical" exposure was made. The types of dosimeters used by the participants are listed in Table 2. The participants were provided with information on the position of their dosimeters as shown in Fig. 1.

Sulfur pellets exposed at a standard location on the reactor during the intercomparison gave kerma estimates for the three meter positions of 41, 47, and 44 mrad for the unshielded, steel-shielded, and Lucite-shielded runs, respectively. Hurst detector measurements yielded corresponding values of 43, 55, and 43 mrad. A standard deviation of about  $\pm 10\%$  is to be expected due to counting statistics and other sources of error. The dose also can be calculated based on the HPRR neutron spectra<sup>4</sup> for the three exposure configurations used and the dose conversion factors which have been calculated<sup>1</sup> previously for these spectra. Average quality factors determined by Murthy et al.<sup>5</sup> were used for calculating dose equivalent. These values also are given in Table 4. Using the fission yield and the calculated leakage<sup>6</sup> of the HPRR, the neutron fluence was calculated for each reactor run. By applying the previously determined dose conversion factors and average quality factors, the dose and dose equivalent were calculated and are given in Table 5.

Results of gamma dose measurements were less satisfactory due primarily to a very large background exposure of many dosimeters. It is felt this exposure came from inadvertent exposure at the shipping storage area at ORNL. The participants reported higher doses than those measured by the DOSAR group. This may be explained by the difficulty in making corrections for this elevated background. The DOSAR dosimeters were not exposed to any appreciable background. Furthermore, the neutron-to-gamma ratio of the DOSAR data is in reasonable agreement with past measurements, while the participants data exhibits large variations in this ratio.

Reference values of dose and dose equivalent as measured or calculated by DOSAR personnel are given in Table 6. Results reported by eleven participating groups are given in Tables 7, 8, and 9 for unshielded, Lucited-shielded, and steel-shielded configurations, respectively. A summary of the results is shown in Table 10. Data of two experimenters were not included in the summary because the dosimeters of one experimenter were in the development stage and the other experimenter felt he did not have good background corrections. There is a relatively large variation in dose determination among the participants as shown by the standard deviations in Table 10 and the raw data in Tables 7, 8, and 9. If one arbitrarily eliminates the extreme data points of the neutron dose for the three configurations the standard deviations reduce from a range of  $\pm 30\%$  to  $\pm 40\%$  to about  $\pm 15\%$  to  $\pm 25\%$ .

This intercomparison study appears to be of value in view of the wide range of results obtained. Some of the badges were apparently in

a developmental stage rather than in routine use. It would be helpful in the future if all such badges could be clearly identified or exposed on separate runs. This facility will provide such exposures on a mail-in basis to qualified experimenters throughout the year. It is anticipated that this type of dosimetry intercomparison study will be worthwhile on an annual basis until the problems in dosimetry response and interpretation have been identified and solved.

## REFERENCES

1. H. W. Dickson, W. F. Fox, and F. F. Haywood, 1974 Intercomparison of Personnel Dosimeters, ORNL-TM-4786, January 1976.
2. J. W. Poston and F. F. Haywood, 1972 Intercomparison of Nuclear Accident Dosimetry Systems at the Oak Ridge National Laboratory, ORNL-TM-4387, July 1972.
3. H. W. Dickson, F. F. Haywood, and K. Becker, Tenth Dosimetry Intercomparison Study, ORNL-TM-4566, March 1975.
4. J. W. Poston, J. R. Knight, and G. E. Whitesides, "Calculation of the HPRR Neutron Spectrum for Simulated Nuclear Accident Conditions," Health Phys. 26, 217 (1974).
5. D. R. Johnson and J. W. Poston, Radiation Dosimetry Studies at the Health Physics Research Reactor, ORNL-4113, June 1967.
6. M. S. S. Murthy, R. C. Bhatt, and S. S. Shinde, "Estimation of Quality Factor and RBE for Degraded Fission Neutron Spectra", Health Phys. 27, 9 (1974).

## APPENDIX A

## PERSONNEL DOSIMETER INTERCOMPARISON STUDY

February 18-19, 1976

<u>Name</u>	<u>Affiliation</u>
Harry Ing	Atomic Energy of Canada, Ltd. Chalk River Nuclear Laboratory Chalk River, Ontario, CANADA
Al. Doles	Eberline Instrument Corporation P. O. Box 2108 Santa Fe, NM 87501
Mehdi Sohrabi	Georgia Institute of Technology School of Nuclear Engineering Atlanta, GA 30332
Ernst Piesch	Kernforschungszentrum Karlsruhe Postfach 3640 75 Karlsruhe, GERMANY
Thomas R. Crites Dale E. Hankins	Lawrence Livermore Laboratory P. O. Box 808 Livermore, CA 94550
H. W. Dickson E. Gupton	Oak Ridge National Laboratory Health Physics Division P. O. Box X Oak Ridge, TN 37830
Robert B. Falk	Rockwell International Rocky Flats Plant P. O. Box 464 Golden, CO 80401
R. V. Wheeler	R. S. Landauer, Jr., and Co. Glenwood Science Park Glenwood, IL 60425
C. N. Wright	Savannah River Laboratory Radiological Science Division Aiken, SC 29802
B. F. Rutherford	Union Carbide Nuclear Division Y-12 Plant Oak Ridge, TN 37830



APPENDIX A (cont.)

<u>Name</u>	<u>Affiliation</u>
W. C. Baumgartner	U. S. Testing Company 2800 George Washington Way Richland, WA 99352

Table 1

## SUMMARY OF REACTOR OPERATIONS FOR INTERCOMPARISON.

Run No.	Shield	Power (watts)	Time (min.)	Fissions ( $\times 10^{13}$ )
1	Unshielded	2	3.12	1.16
2	Lucite	2	16.5	6.14
3	Steel	2	8.68	3.23

Table 2

## DOSIMETERS USED BY PARTICIPANTS

Group	Dosimeter Type	
	Neutron	Gamma
A	Thorium	TLD
B	TLD	TLD
C	Polycarbonate film	---
E-1	TLD	TLD
E-2	TLD	TLD
E-3	TLD	TLD
F	NTA Film	TLD
G	TLD	---
H	NTA Film	Film
I	TLD	TLD
J	Film	TLD
K	NTA Film	---

Table 3. Calculation of HPRR Spectrum for NAD Intercomparisons

Group	Upper Energy (ev)	Mid Energy (ev)	N(E)ΔE*		
			No Shield	Lucite Shield	Steel Shield
1	1.49 E7	1.22 E7	9.53 E7	3.31 E7	1.35 E7
2	1.0 E7	8.19 E6	1.18 E9	3.63 E8	1.5 E7
3	6.7 E6	5.77 E6	3.43 E9	4.29 E8	3.8 E8
4	4.97 E6	3.87 E6	1.44 E10	2.58 E9	1.57 E9
5	3.01 E6	2.12 E6	3.76 E10	5.56 E9	7.94 E9
6	1.5 E6	1.16 E6	3.16 E10	3.19 E9	1.21 E10
7	9.07 E5	6.08 E5	4.61 E10	3.69 E9	3.34 E10
8	4.08 E5	2.13 E5	3.39 E10	3.08 E9	5.02 E10
9	1.11 E5	9.80 E4	2.60 E9	4.18 E8	2.13 E9
10	8.65 E4	7.64 E4	2.0 E9	3.81 E8	2.91 E9
11	6.74 E4	5.95 E4	1.5 E9	3.49 E8	1.41 E9
12	5.25 E4	4.63 E4	1.21 E9	3.24 E8	1.25 E9
13	4.09 E4	3.61 E4	9.71 E8	3.05 E8	5.61 E8
14	3.18 E4	2.81 E4	8.40 E8	2.98 E8	6.64 E8
15	2.48 E4	2.19 E4	7.35 E8	2.76 E8	2.5 E8
16	1.93 E4	1.70 E4	6.37 E8	2.66 E8	1.01 E8
17	1.50 E4	1.03 E4	1.58 E9	7.60 E8	1.14 E8
18	7.10 E3	4.88 E3	1.39 E9	7.23 E8	1.02 E8
19	3.35 E3	2.03 E3	1.62 E9	9.48 E8	1.16 E9
20	1.23 E3	8.48 E2	1.04 E9	6.97 E8	4.2 E8
21	5.83 E2	3.54 E2	1.24 E9	9.21 E8	4.47 E8
22	2.14 E2	1.47 E2	8.45 E8	6.91 E8	3.14 E8
23	1.01 E2	6.96 E1	7.76 E8	6.90 E8	2.88 E8
24	4.79 E1	3.73 E1	4.72 E8	4.59 E8	1.69 E8
25	2.90 E1	2.26 E1	4.54 E8	4.60 E8	1.67 E8
26	1.76 E1	1.37 E1	4.34 E8	4.61 E8	1.61 E8
27	1.07 E1	7.34	6.09 E8	6.93 E8	2.11 E8
28	5.04	3.93	3.82 E8	4.58 E8	1.28 E8
29	3.06	2.18	4.84 E8	6.11 E8	1.71 E8
30	1.56	1.25	3.04 E8	3.79 E8	1.12 E8
31	1.0	8.06 E-1	2.81 E8	3.41 E8	9.16 E7
32	0.65	5.41 E-1	2.42 E8	2.86 E8	7.83 E7
33	0.45	2.12 E-1	1.78 E9	2.67 E9	5.63 E8
34	0.1	2.24 E-2	3.36 E9	1.95 E10	1.09 E9
	5.0 E-3				

\* This number is the area of the histogram for each energy interval.

Table 4

DOSE CONVERSION FACTORS AND AVERAGE  
QUALITY FACTORS FOR HPRR SPECTRA

Shield	Dose Conversion Factor (mrad/cm <sup>2</sup> x 10 <sup>-7</sup> )	$\overline{QF}$
Unshielded	25.5	9.4
Steel	17.9	9.5
Lucite	14.6	8.9

Table 5

NEUTRON ABSORBED DOSE AND DOSE EQUIVALENT CALCULATED  
FROM HPRR FISSION YIELDS

Reactor Run	Shield	Fissions (x 10 <sup>12</sup> )	Fluence (cm <sup>-2</sup> x 10 <sup>-7</sup> )	Dose (mrad)	Dose Equi- valent (mrem)
1	Unshielded	11.6	2.28	58	545
2	Steel	32.3	3.91	70	665
3	Lucite	61.4	3.26	48	427

Table 6

## REFERENCE VALUES OF DOSE AND DOSE EQUIVALENT

Run	Shield	Neutron Dose (mrad)		Neutron Dose Equivalent (mrem)		Gamma Dose Equivalent
		Calculated	Measured	Calculated	Calculated from Measured	Measured (mrem)
1	Unshielded	58	43 ± 4.3	545	404	16 ± 1.6
2	Steel	70	55 ± 5.5	665	523	8 ± 1.2
3	Lucite	48	43 ± 4.3	427	383	41 ± 4.1

Table 7  
 RESULTS OF PERSONNEL DOSIMETER INTERCOMPARISON  
 February 18-19, 1976 - Unshielded

Group	Location on Phantom	Phantom No. 1		Phantom No. 2		Phantom No. 3	
		n(mrem)	$\gamma$ (mrem)	n(mrem)	$\gamma$ (mrem)	n(mrem)	$\gamma$ (mrem)
A	Front	210	72	210	72	210	72
B	Front	470	20	470	20		
B	Back	90	5	90	5		
C	Front					81	
D	Front	705	105				
E-1	Front	560	15	560	15	560	15
E-2	Front	620	23	620	23	620	23
E-3	Front	1000	35	1000	35	1000	35
F	Front					640	40
F	Back	90	20				
G	Front	486		486		486	
H	Front			497	10		
H	Back					54	
I	Front			330	25	305	20
J-1	Front						25
J-1	Back				6		
J-2	Front						16
J-2	Back				6		
K	Front	200					
K	Back					30	

Table 8

## RESULTS OF PERSONNEL DOSIMETRY INTERCOMPARISON

February 18-19, 1976 - LUCITE SHIELD

Group	Location on Phantom	Phantom No. 1		Phantom No. 2		Phantom No. 3	
		n(mrem)	$\gamma$ (mrem)	n(mrem)	$\gamma$ (mrem)	n(mrem)	$\gamma$ (mrem)
A	Front	260	164	260	164	260	164
B	Front	720	60	720	60		
B	Back	40	20	40	20		
C	Front					102	
D	Front	418	157				
E-1	Front	560	43	560	43	560	43
E-2	Front	720	48	720	48	720	48
E-3	Front	700	80	700	80	700	80
F	Front					570	90
F	Back	120	30				
G	Front	432		432		432	
H	Front			532	120		
H	Back					95	33
I	Front			395	65	420	70
J-1	Front						100
J-1	Back				30		
J-2	Front						48
J-2	Back				18		
K	Front	260					
K	Back					30	

Table 9  
 RESULTS OF PERSONNEL DOSIMETRY INTERCOMPARISON  
 February 18-19, 1976 - Steel Shield

Group	Location on Phantom	Phantom No. 1		Phantom No. 2		Phantom No. 3	
		n(mrem)	$\gamma$ (mrem)	n(mrem)	$\gamma$ (mrem)	n(mrem)	$\gamma$ (mrem)
A	Front	510	54	510	54	510	54
B	Front	560	5	560	5		
B	Back	160	3	160	3		
C	Front					38	
D	Front	710	105				
E-1	Front	740	20	740	20	740	20
E-2	Front	840	26	840	26	840	26
E-3	Front	1300	35	1300	35	1300	35
F	Front					770	30
F	Back	100	20				
G	Front	842		842			
H	Front			542			
H	Back					158	
I	Front			700	10	730	15
J-1	Front						12
J-1	Back				6		
J-2	Front						9
J-2	Back				5		
K	Front	120					
K	Back					30	



Table 10

## SUMMARY OF RESULTS OF FRONT EXPOSURES

Exposure Condition	Neutron Dose Equivalent (mrem)	Gamma Dose Equivalent (mrem)
Unshielded Reactor	550 $\pm$ 217	35 $\pm$ 29
Steel Shielded Reactor	753 $\pm$ 226	31 $\pm$ 30
Lucite Shielded Reactor	532 $\pm$ 154	86 $\pm$ 46




Fig. 1. A Typical Placement of Dosimeters on the Front of Phantoms.






Fig. 2. A Typical Experimental Setup with the Steel Shield in Place.

Internal Distribution

- 1-2. Central Research Library
3. Document Reference Section
- 4-5. Laboratory Records Department
6. Laboratory Records, ORNL R.C.
7. ORNL Patent Office
8. J. A. Auxier
9. D. J. Christian
10. R. L. Clark
11. D. M. Davis
12. H. W. Dickson
13. R. B. Gammage
14. L. W. Gilley
15. E. D. Gupton
16. F. F. Haywood
17. R. F. Hibbs
18. D. G. Jacobs
19. G. D. Kerr
20. J. R. Muir
21. W. W. Parkinson
22. H. Postma
23. J. W. Poston
24. C. R. Richmond
25. B. F. Rutherford (Y-12)
26. J. H. Thorngate

27. J. E. Turner
28. D. R. Ward
29. C. M. West (Y-12)
- 30-60. DOSAR (files)

External Distribution

61. Research and Technical Support Division, ERDA-OR0
62. W. C. Baumgartner, U.S. Testing Company, 2800 George Washington Way, Richland, WA 99352
63. R. L. Butenhoff, ERDA, Washington, D.C. 20545
64. G. Cowper, Health Physics Branch, Atomic Energy of Canada, Ltd., Chalk River Nuclear Laboratories, Chalk River, Ontario, Canada
65. T. R. Crites, Lawrence Livermore Laboratory, P. O. Box 808, Livermore, California 94550
66. L. J. Deal, Assistant Director of Safety Protection, Division of Operational Safety, ERDA, Washington, D.C. 20545
67. C. H. Distenfeld, Health Physics and Safety Division, Brookhaven National Laboratory, Upton, N.Y. 11973
68. Al Doles, Eberline Instrument Corporation, P. O. Box 2108, Santa Fe, NM 87501
69. W. P. Ellis, Standards and Procedures Branch, Division of Compliance, NRC, Washington, D.C. 20555
70. R. B. Falk, Rocky Flats Division, Dow Chemical Company, P. O. Box 888, Golden, Colorado 80401
71. R. Griffith, Lawrence Livermore Laboratory, P. O. Box 808, Livermore, California 94550
72. D. E. Hankins, Lawrence Livermore Laboratory, P. O. Box 808, Livermore, California 94550
73. J. E. Hoy, Radiological Sciences Division, Savannah River Laboratory, Aiken, S.C. 29802
74. Harry Ing, Atomic Energy of Canada, Ltd., Chalk River Nuclear Laboratory, Chalk River, Ontario, Canada

75. S. A. McGuire, Office of Standards Development, NRC, Washington, D.C. 20555
  76. Leigh Phillips, Health Physics and Safety Division, Brookhaven National Laboratory, Upton, New York 11973
  77. E. Piesch, Kernforschungszentrum Karlsruhe, Postfach 3640, 75 Karlsruhe, Germany
  78. C. F. Sanders, Westinghouse Nuclear Fuel Division, P. O. Drawer R, Columbia, South Carolina 29205
  79. Mehdi Sohrabi, Georgia Institute of Technology, School of Nuclear Engineering, Atlanta, Georgia 30332
  80. Joseph Wang, Naval Surface Weapons Center, White Oak Laboratory, Silver Springs, Maryland 20910
  81. R. V. Wheeler, R. S. Landauer, Jr., and Company, Glenwood Science Park, Glenwood, Illinois 60425
  82. R. W. Wood, Division of Biomedical and Environmental Research, ERDA, Washington, D.C. 20545
  83. C. N. Wright, Radiological Sciences Division, Savannah River Laboratory, Aiken, South Carolina 29802
- 84-110. Technical Information Center, ERDA-Oak Ridge, Tennessee