ANNUAL PERFORMANCE REPORT

15 September 1991 - 14 September 1992

**RESERVOIR CHARACTERIZATION BY CROSSHOLE SEISMIC
IMAGING**

M. Nafi Toksöz, Principal Investigator

Roger M. Turpening, Co-Principal Investigator

**Earth Resources Laboratory
Department of Earth, Atmospheric, and Planetary Sciences
Massachusetts Institute of Technology
Cambridge, Massachusetts 02139**

**DOE Report Number — DOE/ER/14084-3
DOE Contract Number — DOE-FG02-89ER14084**

10 June 1992

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DM

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

RESERVOIR CHARACTERIZATION BY CROSS HOLE MEASUREMENTS

SEMI-ANNUAL PROGRESS REPORT

Roger Turpening
Earth Resources Laboratory
Massachusetts Institute of Technology
Cambridge, Massachusetts

BACKGROUND

The Earth Resources Laboratory (ERL) at the Massachusetts Institute of Technology (MIT) has completed two and one half years of a four year research effort. This program of investigation in conjunction with the companion effort at the Sandia National Laboratories is focused on the field use of cross hole measurements in reservoir characterization. ERL through its industrial support has a research facility in the Northern Michigan Reef Trend. Deep (6,500 ft.) holes have been placed on opposite sides (2,000 ft. apart) of a producing reef. Since the holes are much deeper (see Figure 1) than the reservoir (at 4,700 ft.) they provide an opportunity better than that usually found in industry for the use of cross hole techniques.

The original plan for the four year effort was stated as follows:

Year One--Preparation

Year Two--Use of vertically polarized shear waves (SV)

Year Three--Addition of horizontally polarized shear waves (SH)

Year Four--Present static image of reservoir properties and

--Observe time varying phenomena in the reservoir by
reshooting high frequency compressional (P) survey

This report covers the first six months of the third year. The major accomplishment during that period has been the observation of clear SV signals from the Sandia source over a distance of 1,900 ft.

Data Acquisition

The geologic column at the ERL's Research Facility typical of the Michigan Basin. Limestones, dolomites, salts, and calcareous shales are found over all depth intervals. The Silurian reefs are the hydrocarbon reservoirs here and they occur on the Grey Niagaran limestone. The data acquisition plan was to deploy the Sandia source and the Halliburton Logging Services array at shallow depth first and then to proceed down to the depth of the reservoir. For reasons that will be discussed later, the source did not perform at depths greater than approximately 1600 ft. and therefore the available time, which was already short, was spent at these shallow depths. Figures 1 and 2 show cross sections of the Research Facility. The levels of deployment for both the source (950 ft. down to 1,600 ft. in 50 ft. intervals) and receivers (sondes at 1,300, 1,325, and 1,350 ft.) are given in each figure. The first figure displays the engineering details of our boreholes while the second figure shows the borehole geometry. Notice that the source positions occupy a region of slight borehole deviation. Extensive use of gyroscope surveys in both of our holes gives us the location of these holes in three dimensional space.

The figures show that the three component receivers were positioned in the Traverse Limestone (S wave velocity of approximately 9,100 ft./sec.) while the source moved from the Antrim Shale (S wave velocity of approximately 5,500 ft./sec.) to the Traverse Formation (S wave velocity of approximately 8,000 ft./sec.) and into the Traverse Limestone. Our boreholes are approximately 1,910 ft. apart at these depths.

Televiewer data and our nine-component, zero-offset VSP data both indicate that this entire interval is fractured with near vertical fractures. Thus orthorhombic anisotropy should be expected in the Antrim Shale and azimuthal anisotropy should be anticipated in the Traverse Formation and Traverse Limestone. Although seismic attenuation is expected to be low in these very hard formations the fractures will increase the apparent attenuation.

Data

Figures 3 and 4 display the data obtained on one vertical component and one horizontal geophone. Eight, four second sweeps were stacked in each case. Weak P waves can be seen on the horizontal geophone in Figure 4 at levels commensurate with traditional radiation patterns.

The spectrum of the sweep (when the source was at the 1,400 ft. level) is shown in Figure 5. Note that usable signal power exists only out to about 140 Hz. This also evident in the spectra of the SV arrivals themselves.

Obviously the signal to noise ratio is best when the seismic wave propagation is confined to the Traverse Limestone. When the signals must cut across interfaces energy is lost. In these plots the noise level seems to rise as the signal levels decrease but this is only a result of the fact that each trace is independently gained to meet individual trace maxima. Although these signals are not strong and source improvements must be made these results are encouraging since no signal at all was expected over these distance ranges.

Figures 6 and 7 display the spectra of two different SV signals. In figure 6 the signal has propagated 1,940 ft. The result is a narrow band signal having less than one octave of bandwidth. In Figure 7 the source is in the Traverse Limestone along with the receiver. The propagation distance is nearly the same (1,900 ft.) but a much broader spectrum of two octaves occurs. Preliminary examination of the data from the 3,000 ft. level in these boreholes shows no signal at all.

Source Resonance

Although one could easily explain a loss of high frequency energy by postulating lower Q's in the Antrim Shale this does not explain the apparent loss of the low side of the spectrum when the source is at a shallower depth. This observation highlights a question that will be examined in detail this year. The question is "what is the behavior of the sweep as a function of depth?"

Recall that this source was designed to operate around a natural resonance of its mechanical system, in fact it derived much of its power from that resonance. As the source is deployed at deeper and deeper levels it appears that the resonance is first damped and then lost entirely (see the 1,600 ft. data in Figure 1). This is the first observation of this phenomena and that is not surprising since all previous tests of this source were done at depths less than 1,000 ft. Since this is the only downhole SV source in the world that can be deployed in a fluid filled borehole it is important to understand this problem and engineer a solution.

Future Work

Given the modest success of this source and the fact that it is the only SV source that can operate in a fluid filled borehole it is important to improve this source for future work. The resonance peak should be suppressed but not to the point of complete signal extinction. Modifications to the tool done in past to speedup data acquisition may have to be undone and new solutions found. Hopefully this engineering can be done in time for the summer 1993 field period at MIT's Research Facility. With these

modifications we should be able to work at the depth of the hydrocarbon reservoir and thus achieve the goals outlined in the statement of work, albeit one year behind schedule. The technology for the reillumination of the reservoir with P waves is at hand and can be performed at any time.

Summary

The Sandia downhole vertical vibrator was tested in September 1991 at depths and over interwell distances never attempted, by this source, before. It was known at the outset that time and funding constraints precluded the collection of a full tomographic data set. The usual field difficulties reduced the time even further however reasonable shear wave (SV) signals were obtained at depths greater than previously attempted. This success together with modifications to the source by Sandia and/or contractors to Sandia will allow us to operate the Sandia source at and below the depth of the hydrocarbon reservoir in 1993. This would allow the statement of work to be met. The reillumination of the reservoir with P waves, to detect any time varying changes, can be done at any time.

EARTH RESOURCES LABORATORY RESERVOIR DELINEATION RESEARCH FACILITY

Sept. 1991

Figure 1. Location of source and receiver positions. Borehole engineering is shown.

EARTH RESOURCES LABORATORY RESERVOIR DELINEATION RESEARCH FACILITY

Figure 2. Location of source and receiver positions. Borehole geometry is shown

Figure 3. SV signals on the vertical component geophone at a depth of 1300 ft. Each trace is individually scaled.

Figure 4. SV and P wave signals on one, non rotated horizontal geophone in the upper most sonde (1300 ft.)

Figure 5. Spectrum of raw sweep of Sandia source when the sonde was at a depth of 1400 ft.

Figure 7. Spectrum of shear wave (SV) wavelet on a vertical component geophone when the Sandia source was at the 1400 ft. level. The receiver is the upper most sonde (1300 ft.) in the Halliburton array. Total path length is 1900 ft.

END

**DATE
FILMED
9/01/92**