10
9-30-92950

ORNL/Sub/88-22042/2

**OAK RIDGE
NATIONAL
LABORATORY**

MARTIN MARIETTA

Effect of Translucence of Engineering Ceramics on Heat Transfer in Diesel Engines

Final Report

**S. Wahiduzzaman
T. Morel**

**CERAMIC TECHNOLOGY FOR
ADVANCED HEAT ENGINES**

**MANAGED BY
MARTIN MARIETTA ENERGY SYSTEMS, INC.
FOR THE UNITED STATES
DEPARTMENT OF ENERGY**

1. DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P.O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401, FTS 626-8401.

Available to the public from the National Technical Information Service, U.S. Department of Commerce, 5235 Port Royal Rd., Springfield, VA 22161.

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

**EFFECT OF TRANSLUCENCE OF ENGINEERING CERAMICS
ON HEAT TRANSFER IN DIESEL ENGINES**

S. Wahiduzzaman and Thomas Morel

Date Published-April 1992

FINAL REPORT

**Prepared by
Integral Technologies Incorporated
645 Blackhawk Drive
Westmont, Illinois 60559
86X-22042V**

**Funded by
Office of Transportation Materials
Office of Transportation Technologies
the Assistant Secretary for Conservation and Renewable Energy
U.S. Department of Energy
EE 51 01 00 0**

**for
OAK RIDGE NATIONAL LABORATORY
Oak Ridge, Tennessee 37831
managed by
MARTIN MARIETTA ENERGY SYSTEMS, INC.
for the
U.S. DEPARTMENT OF ENERGY
under Contract DE-AC05-84OR21400**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ACKNOWLEDGEMENT

Research sponsored by the U.S. Department of Energy, Assistant Secretary for Conservation and Renewable Energy, Office of Transportation Technologies, as part of the Ceramic Technology Project of the Advanced Materials Development Program, under contract DE-AC05-84OR21400 with Martin Marietta Energy Systems, Inc. The authors also acknowledge the helpful suggestions provided by the contract manager, Dr. David L. McElroy, Oak Ridge National Laboratory, and the assistance of Prof. David P. DeWitt, Purdue University, who served as a consultant.

CONTENTS

ABSTRACT	1
INTRODUCTION	2
METHODOLOGY	4
FOUR FLUX MODEL	5
TWO FLUX MODEL	8
EXPERIMENTAL DATA AND THEIR ANALYSIS	10
RADIATIVE MEASUREMENTS	10
ANALYSIS OF CONSISTENCY OF THE EXPERIMENTAL DATA	11
PARAMETER INVERSION	12
FOUR FLUX MODEL VS. TWO FLUX MODEL	14
RECOMMENDATION FOR FUTURE MEASUREMENTS	14
ANALYSIS OF TRANSLUCENCE EFFECTS ON HEAT TRANSFER	16
APPROACH	16
EFFECTIVENESS OF INVESTIGATED CERAMICS AS HEAT BARRIER MATERIALS	17
EFFECT OF SURFACE CONDITIONS	19
MODELING OF SOOT EFFECT	20
DISCUSSION	23
CONCLUSIONS	26
NOMENCLATURE	28
REFERENCES	30
TABLES	31
FIGURES	34
APPENDIX	69

FINAL REPORT

EFFECT OF TRANSLUCENCE OF ENGINEERING CERAMICS ON HEAT TRANSFER IN DIESEL ENGINES

PART II

EXPERIMENTS ON RADIATIVE PROPERTIES OF CERAMICS

S. Wahiduzzaman and T. Morel

ABSTRACT

This report describes the experimental portion of a broader study undertaken to assess the effects of translucence of ceramic materials used as thermal barrier coatings in diesel engines. In an earlier analytical work a parametric study was performed, varying several radiative properties over ranges typical of engineering ceramics, thereby identifying the most important radiative properties and their impact on in-cylinder heat transfer. In the current study these properties were experimentally determined for several specific zirconia coatings considered for thermal barrier applications in diesel engines.

The methodology of this study involved formulation of a model capable of describing radiative transfer through a semitransparent medium as a function of three independent model parameters, ie, absorption coefficient, scattering coefficient and refractive index. A set of radiative measurements was then fitted to this model by optimization of the above model parameters. The radiative measurements were comprised of hemispherical reflectance and transmittance spectra from samples of several different thicknesses of each ceramic under collimated (unidirectional) illumination. A four-flux model was required to extract accurate radiative properties from the measurements.

For the zirconia-based ceramics investigated in this study, it was concluded that for usual coating thicknesses (1.5-2.5 mm) these ceramics are optically thick and hence, are effective as radiative heat transfer barriers. These ceramics possess high scattering coefficients and low absorption coefficients causing them to be highly reflective (60-80%) in the spectral region where thermal radiation is important. As a consequence, only a small portion of the incident energy is captured by the coating system and transmitted to the metal substrate via conduction.

The convective heat flux, which is driven by the temperature differential between the gas and the ceramic-gas interface, was found to be highly dependent on the location where radiative energy is absorbed. If a significant amount of energy is absorbed near the surface, as is the case for ceramics investigated, surface temperature is raised causing convective heat flux to be decreased. On the other hand, for ceramics that are transparent the radiative energy is absorbed at the ceramic/metal interface

and consequently, the gas/ceramic interface remains relatively cool promoting convective heat transfer.

The performance of the investigated ceramics and the mechanism of heat transfer were found to depend on surface condition, specifically on soot deposition. If the surface fouling is small, the ceramics behaved as described above, i.e., as optically thick materials characterized by high scattering coefficient and low absorption coefficient. In this case, the energy transport is primarily due to convective heat transfer since only a small fraction of the incident radiant energy can be trapped by the coating. On the other hand, if the coating surface is totally covered by soot, its performance will be similar to that of a clean optically thick material characterized by small scattering coefficient and high absorption coefficient. In this case, there will be a significant increase in radiation heat transfer absorbed at the surface with an associated decrease in convective heat transfer.

Although the coatings investigated in this study were found to be optically thick at or near nominal thicknesses (2.5 mm), this is by no means representative of all engineering ceramics. For example, based on available literature data, monolithic ceramics have been found to be more transparent than the ceramics investigated in this study and, consequently, are less effective as radiation heat transfer barriers.

Based on the results, it is concluded that ceramics with high scattering and low absorption coefficients are the most suitable for engine applications where in-cylinder surfaces can be expected to remain clean. If surfaces are expected to be sooted an opaque ceramic characterized by either high scattering coefficient and/or high absorption coefficient should be chosen in order to bring about a substantial decrease in convective heat flux. Thus, to insure the optimum thermal barrier operation for either clean or heavily sooted surfaces, a ceramic material with high scattering coefficient provides the best choice.

INTRODUCTION

Ceramic materials are being developed for application as heat barrier materials in insulated diesel engines. Their purpose is to reduce the heat transfer rate from the gases to the walls, with the twin benefits of increased engine efficiency and of lower heat rejection to the coolant.

The idea of a heat barrier layer is to create a path of high resistance to heat transfer, and this is accomplished by using high temperature materials which have low thermal conductivity. Certain ceramics, e.g. zirconia, combine these properties with the potential for low material cost, which accounts for the interest in their development for this application. Computer simulations of in-cylinder heat transfer processes and of the heat conduction through the structural components of the engine indicate that ceramics can indeed provide very substantial reductions in engine heat transfer, translating into important thermal efficiency gains, reduced heat rejection to coolant and increased exhaust energy availability.¹

However, it is increasingly being realized that some of the ceramics proposed for diesel engine thermal barriers are partially transparent in the spectral region where most of the thermal energy associated with the combustion process is concentrated (Liebert^{2,3} and Makino et al⁴). This causes concern about the effectiveness of such ceramic layers in reducing heat transfer in insulated diesel engines, where it is known that radiation can account for a significant portion of the total heat transfer.⁶

The gas-to-wall heat transfer in diesel engines is produced by convection from cylinder gases and by radiation from the soot-laden burning zone. In the high output turbocharged engines typically used in highway truck applications, the heat radiation accounts for some 20 percent of the total heat transfer from gases to walls at the rated engine conditions. When the combustion chamber is insulated, the convective component of the heat transfer is selectively reduced. The proportion of heat transfer that is due to radiation then rises to over 50 percent, thereby becoming a much more significant fraction of⁵ the overall heat rejection and a more important design consideration.

In all simulations of diesel engine heat transfer processes reported to date, the assumption has been made that the absorption coefficient of the ceramic is very large so that all of the incident radiation is deposited at the gas/ceramic interface -- i.e., the radiation has not been allowed to penetrate into the interior. This is a carryover from studies of metallic engines where this treatment provides a fairly accurate description of the actual process. However, since some ceramics of engineering interest are known to be translucent, especially at infrared radiation wavelengths, this approximation may be quite incorrect.

The work carried out on this contract is divided into two parts. A previous report⁷ described the results of the first part, which concerned an analytical study of the radiation process within engineering ceramics, and showed how heat transfer is affected by the radiation properties of ceramics (absorption coefficient, scattering coefficient, index of refraction and surface reflectivities). This report presents the results of the second part of the work concentrating on an experimental determination of the radiative properties of some specific ceramics, and then predicting their effectiveness as heat barrier materials when used in a diesel engine environment.

There were three principal aspects to work described in this report. The first was the selection and implementation of an appropriate methodology to determine the radiative properties of the ceramic materials. The second was the use of the method to determine the radiative properties of several existing coatings that have been developed for diesel engine application. The last was an analysis of the heat transfer through a ceramic-coated wall of a diesel engine, including all three heat transfer mechanisms -- convection, radiation and conduction -- and through it an assessment of the effectiveness of these specific ceramics as heat barrier materials.

METHODOLOGY

The principal parameters required to describe radiative transport in a semitransparent medium are the absorption coefficient (k), scattering coefficient (s), refractive index (n) and scattering phase function (p). For many ceramic materials in which scattering can be assumed to be isotropic, the first three parameters are adequate to describe radiative transport, and in this work we concentrate on these three. An additional assumption, implicit in this description, is that the interfacial reflectivities are known or can be determined using Fresnel's equation. The latter approach is chosen for this study which requires that the interfaces are optically smooth.

The approach adopted here to determine these parameters for a given material is to take radiative measurements of several samples of that material fashioned into thin coupons of different thicknesses. A model describing the radiative transfer in semi-transparent media can be then fitted to the acquired data to determine the above radiative properties. The parameter inversion process involves matching the measured reflectance and transmittance data of a set of coupons of different thicknesses with the model computed values. An objective function based on a sum of squares of normalized differences between measured and computed reflectance and transmittance values can be minimized to obtain the values of n , k and s which give the best correspondence between measurement and model predictions.

The approach discussed above was implemented using measurements obtained at two different locations (wavelengths of 0. to 2.5 μm at NBS* and 2.0 to 20.0 at Willey Corporation**). In both laboratories hemispherical reflectance and transmittance spectra were measured under collimated illumination and consequently include contributions of the collimated flux in addition to the diffuse flux which can be created from the collimated flux undergoing multiple scattering. This necessitates the use of a radiation model capable of describing decay of the collimated flux into a diffuse flux due to multiple scattering unless the incident radiation is diffuse to begin with. A four flux model as opposed to a two flux model is better equipped to handle the problem at hand. Initially a two flux model was used for parameter inversion and was soon discovered to be inadequate at low scattering levels and was discarded in favor of a four flux model. However, for the sake of completeness both models will be discussed below and a comparison of the model performances will be presented in a later section.

---

*Center for Radiation Research, National Measurement Laboratory, National Bureau of Standards, Gaithersburg, Maryland 20899.

**Willey Corporation, P.O. Box 670, Melbourne, Florida 32901.

FOUR FLUX MODEL

The model chosen in this study is the four-flux model, which predicts specular and diffuse reflectivity and transmissivity for a planar medium illuminated by diffuse and/or collimated flux. The parameters k , s , n and the material thickness are the only inputs to the model. The model (Ishimaru⁵ and Makino and Kunitomo⁴) assumes that the radiation transport in a cold (non-emitting) medium can be described by four fluxes. Two of these are a diffuse forward flux and a diffuse backward flux, both of which remain diffuse upon interfacial reflection and scattering. The other two fluxes are a collimated forward and a collimated backward flux which undergo isotropic scattering, thereby contributing equally to the forward and backward diffuse fluxes. The collimated fluxes are assumed to remain collimated after specular (mirror-like) interfacial reflections. Under these assumptions the governing equations and associated boundary conditions are (Figure 1):

governing equations:

$$\frac{dD^+}{dx} = -(2k+s) D^+ + sD^- + \frac{s}{2} C^+ + \frac{s}{2} C^- \quad (1)$$

$$-\frac{dD^-}{dx} = -(2k+s) D^- + sD^+ + \frac{s}{2} C^- + \frac{s}{2} C^+ \quad (2)$$

$$\frac{dC^+}{dx} = -(k+s) C^+ \quad (3)$$

$$-\frac{dC^-}{dx} = -(k+s) C^- \quad (4)$$

boundary conditions:

$$D^+(0) = (1-R_{do}) F_d + R_{di} D^-(0) \quad (5)$$

$$D^-(d) = R_{di} D^+(d) \quad (6)$$

$$C^+(0) = (1-R_{co}) F_c + R_{ci} C^-(0) \quad (7)$$

$$C^-(d) = R_{ci} C^+(d) \quad (8)$$

where 0 and d denotes front and back surface, respectively.

A general solution to the above set of equations is:

$$D^+(x) = \alpha_1 A e^{-\tau} + \alpha_2 B e^{\tau} + \alpha_3 (1+\beta) e^{-2\beta\tau} + \alpha_4 (1-\beta) e^{2\beta\tau} \quad (9)$$

$$D^-(x) = \alpha_1 B e^{-\tau} + \alpha_2 A e^{\tau} + \alpha_3 (1-\beta) e^{-2\beta\tau} + \alpha_4 (1+\beta) e^{2\beta\tau} \quad (10)$$

$$C^+(x) = \alpha_1 e^{-\tau} \quad (11)$$

$$C^-(x) = \alpha_2 e^{\tau} \quad (12)$$

where

- A = $3\omega/(8\beta^2-2)$
- B = $A/3$
- C^+ = collimated forward flux
- C^- = collimated backward flux
- d = depth of the layer
- D^+ = diffuse forward flux
- D^- = diffuse backward flux
- F_d = diffuse incident flux
- F_c = collimated incident flux
- k = absorption coefficient
- R_{di} = diffuse interfacial internal reflection
- R_{do} = diffuse interfacial external reflection
- R_{ci} = collimated interfacial internal reflection
- R_{co} = collimated interfacial external reflection
- s = scattering coefficient
- $\beta = \sqrt{1-\omega}$
- λ = wavelength
- $\omega = s/(s+k)$ = albedo
- E = $s+k$ = extinction coefficient
- $\tau = (k+s)x$ = optical depth at x
- $\tau_d = (k+s)d$ = optical thickness of the translucent layer

The coefficients α_1 , α_2 , α_3 and α_4 are determined by solving the following simultaneous equations obtained using the boundary conditions:

$$\begin{bmatrix}
1 & -R_{ci} & 0 & 0 \\
-R_{ci}e^{-\tau d} & e^{\tau d} & 0 & 0 \\
(A-R_{di}B)e & (B-R_{di}A)e & (1+\beta) & (1-\beta) \\
(B-R_{di}A)e^{-\tau d} & (A-R_{di}B)e^{\tau d} & -(1-\beta)R_{di} & -(1+\beta)R_{di} \\
& & [(1-\beta) & [(1+\beta) \\
& & -(1+\beta)R_{di}]e^{-2\tau d} & -(1-\beta)R_{di}]e^{2\tau d}
\end{bmatrix}
\begin{bmatrix}
\alpha_1 \\
\alpha_2 \\
\alpha_3 \\
\alpha_4
\end{bmatrix}$$

$$= \begin{bmatrix}
(1-R_{co}) F_c \\
0 \\
(1-R_{do}) F_d \\
0
\end{bmatrix} \quad (13)$$

Then collimated and diffused reflected fluxes at the inside front surface can be calculated after substitution of Eqs. (10) and (12) in the following equations:

$$S_c = R_{co} F_c + (1-R_{ci})C^-(0) \quad (14)$$

$$S_d = R_{do} F_d + (1-R_{di})D^-(0) \quad (15)$$

respectively.

Similarly, the collimated and diffused transmitted fluxes at the back surface of the ceramic are obtained after substituting Eqs. (9) and (11) in the following equations:

$$H_c = (1-R_{ci}) C^+(d) \quad (16)$$

$$H_d = (1-R_{di}) D^+(d) \quad (17)$$

From these fluxes reflectance and transmittance can be appropriately defined as follows:

$$R_h = (S_c + H_c)/(F_d + F_c) \quad (18)$$

$$T_h = (S_d + H_d)/(F_d + F_c) \quad (19)$$

TWO FLUX MODEL

Under purely diffuse illumination, only two diffuse fluxes are necessary to describe radiative transport in a planar medium provided assumptions previously made are still valid. It was assumed that a collimated flux transforms into diffuse forward and backward fluxes by undergoing isotropic scattering. If the scattering level is high this conversion will happen early and a simpler two (diffuse) flux model can then be used as a further approximation of the radiative transport in such media. The flux equations and the boundary conditions for the model can be written as:

$$\frac{dD^+}{dx} = -(2k+s)D^+ + sD^- \quad (20)$$

$$-\frac{dD^-}{dx} = -(2k+s)D^- + sD^+ \quad (21)$$

The accompanying boundary conditions are:

$$D^+(0) = (1-R_{do})F_d + R_{di}D^-(0) \quad (22)$$

$$D^-(d) = R_{di}D^+(d) \quad (23)$$

It should be noted here that the above equations are identical to those obtained from the four flux model under purely diffuse illumination.

The general solution to the above equations is:

$$D^+ = \alpha_3(1+\beta)e^{-2\beta r} + \alpha_4(1-\beta)e^{2\beta r}$$

$$D^- = \alpha_3(1-\beta)e^{-2\beta r} + \alpha_4(1+\beta)e^{2\beta r}$$

The coefficients α_3 and α_4 are then determined from the boundary conditions as follows:

$$\begin{bmatrix} (1+\beta) - (1-\beta)R_{di} & (1-\beta) - (1+\beta)R_{di} \\ [(1-\beta) - (1+\beta)R_{di}]e^{-2\beta r_d} & [(1+\beta) - (1-\beta)R_{di}]e^{2\beta r_d} \end{bmatrix} \begin{bmatrix} \alpha_3 \\ \alpha_4 \end{bmatrix} = \begin{bmatrix} (1-R_{do})F_d \\ 0 \end{bmatrix} \quad (24)$$

After solution one obtains

$$\alpha_3 = \frac{F_d(1-R_{do})Ue^{2\beta r_d}}{U_e^2 e^{2\beta r_d} - V_e^2 e^{-2\beta r_d}} \quad (25)$$

$$\alpha_4 = \frac{-F_d(1-R_{do})Ve^{-2\beta r_d}}{U_e^2 e^{2\beta r_d} - V_e^2 e^{-2\beta r_d}} \quad (26)$$

where

$$U = (1+\beta) - R_{di}(1-\beta)$$

$$V = (1-\beta) - R_{di}(1+\beta)$$

The reflected and transmitted fluxes are:

$$S_d = R_{do}F_d + (1-R_{di})D^-(0) \quad (27)$$

$$H_d = (1-R_{di})D^+(d) \quad (28)$$

Then the reflectance is given by:

$$\begin{aligned} R_d &= S_d/F_d \\ &= R_{do} + (1-R_{do})(1-R_{di}) \frac{(1-\beta)Ue^{2\beta r_d} - (1+\beta)Ve^{-2\beta r_d}}{U_e^2 e^{2\beta r_d} - V_e^2 e^{-2\beta r_d}} \end{aligned} \quad (29)$$

and the transmittance is given by:

$$T_d = H_d/F_d$$

$$= (1-R_{do})(1-R_{dl}) \frac{(1+\beta)U - (1-\beta)V}{U_e^2 e^{2\beta r_d} - V_e^2 e^{-2\beta r_d}} \quad (30)$$

It should be noted here that the reflectance and transmittance in equations 18, 19, 29 and 30 are spectral quantities (i.e., have unique values for each wavelength).

The essence of the method involves minimizing the differences between the computed reflectance and transmittance spectra using these equations with the measured spectra by suitable choice of model parameter in order to obtain spectral distributions for these parameters.

EXPERIMENTAL DATA AND THEIR ANALYSIS

RADIATIVE MEASUREMENTS

Four different ceramics were available for radiative parameter inversion. These included plasma sprayed zirconia (PSZ) (13% Yttria stabilized) from Plasma Technics*, PSZ and TZP (Tridiagonal Zirconia Polycrystals) from Oak Ridge National Laboratory** and PSZ (24% Ceria stabilized) from Caterpillar***. The success of the above procedure, i.e. obtaining the radiative properties of a given ceramic, depends on acquiring a set of experimental data which are independent of each other. This requires measurement of reflectances and transmittances at sufficiently distinct optical depths. Hence, it is desirable to select thicknesses of samples such that an optically thin, an optically thick and an intermediate optical thickness are included in the set of samples. However, without a priori information, which was the case in the present study, one can only guess at the best thicknesses for this purpose. Based on feasibility of fabrication of the thinnest samples, mechanical strength, and literature values of properties of similar materials, three to four thicknesses were specified and fabricated for each of the four ceramics investigated in this study. All of these samples are labeled and described in the Table I.

---

*Plasma Technics Inc., 1143 West Newport Center Drive, Deerfield Beach, Florida 33442.

**Oak Ridge National Laboratory, P. O. Box 2008, Oak Ridge, Tennessee 37831.

***Caterpillar Inc., Technical Center, P.O. Box 1875, Peoria, Illinois 61656-1875.

The original plans were to obtain normal incidence diffuse reflectance for all thirteen samples. The transmittance measurements were planned only for nine samples, excluding the thickest sample of each set which were expected to be too thick to allow any transmission. The first set of measurements was made over a wavelength band spanning 2 μm to 20 μm at Willey Corporation, a private firm specializing in radiometry. In this wavelength range meaningful transmittance measurement could be obtained only for seven samples, because only the thinnest sample of the PSZ samples from Caterpillar (set D) transmitted enough energy to obtain reliable transmittance data.

The measurements at lower wavelength, extending from 0.25 to 2.5 μm , were conducted at the National Bureau of Standards. Again for some of the samples (A2, D11, D12) poor transmittance results were obtained owing to low signal-to-noise ratio. In addition, sample A1 was found to be broken during transit and no transmittance measurement could be obtained from this sample. The matrix of radiative measurements carried out by Willey Corporation and NBS are summarized in Table II.

ANALYSIS OF CONSISTENCY OF THE EXPERIMENTAL DATA

In this study, the emphasis of the analysis was placed on the wavelength range from the visible (0.4 μm) to 5 μm where thermal radiative energy is important in diesel engine applications. (Note that the peak radiant intensity of a blackbody occurs at 2.9 μm at 1000K and at 1.45 μm at 2000K.) This wavelength band contains the overlap region (2.0 μm to 2.5 μm) where data was obtained at both laboratories. The agreement between the data in the overlap range was examined from the two sources and it was found satisfactory. (It should be noted that the data from Willey Corporation exhibited noise inherent to the measuring instrument⁸ and had to be smoothed.) The composite plots of data belonging to both sources are shown in Figures 2 to 5. (The unsmoothed data from Willey Corporation is presented in the Appendix.)

The available data were carefully scrutinized to determine their suitability for radiative parameter inversion. The following observations of unusual trends were made:

- (1) Sample sets B and C from Oak Ridge exhibited very similar reflectance and transmittance spectra despite different composition (Figures 3 and 4). This similarity was evident in the data obtained at both Willey and NBS. It was concluded that the two sets are radiatively identical.
- (2) The qualitative trend of the reflectance data of sample C9 was markedly different than those of thinner samples of the same material (C7 and C8). The differences include a) lower reflectance values below 0.5 μm , b) relatively constant reflectance values between 0.5 μm and 2.5 μm and c) most importantly, a dip in the reflectance values around 2.75 μm (Figure 4b). These characteristic differences suggest that the

sample C9 may have been contaminated during its fabrication. Hence it was necessary to exclude the data from this sample from parameter inversion analysis for set C. A similar conclusion can be made for sample B4 as evidenced in Figure 3a.

- (3) Reflectance spectra for samples belonging to set D exhibited an inconsistent trend with thickness. The spectra of samples D10 and D13 possessed characteristics which are absent in the spectra for samples D11 and D12 (Figure 5b). These characteristics include a dip at $2\text{ }\mu\text{m}$ and high reflectance values beyond $3\text{ }\mu\text{m}$. Since transmittance data were available for sample D10, it was decided that only data from samples D10 and D13 would be used for parameter inversion for set D. The choice D11 and D13 would only provide two sets of measurements as opposed to three sets of measurements for the choice made.

After careful consideration of the above factors, consistent sets of data from the two laboratories were merged. Since data obtained at Willey Corporation are less reliable in the overlap region ($2\text{ }\mu\text{m}$ to $2.5\text{ }\mu\text{m}$), the data from NBS were given higher weight in this band during merger. Figures 6 to 8 show merged data for sample sets B, C and D. It can again be noted here, allowing for the measurement uncertainties, sets B and C possess identical spectra.

Unfortunately, the data for sample A is too sparse for parameter inversion. It can be seen in Figure 2(b) that reflectance is nearly identical for all three samples (A1, A2, A3). (The spectrum A1 presented here was measured from a damaged sample and as such NBS has not certified this data.) This signifies that even at the smallest thickness (0.51 mm) the ceramic is optically thick and therefore the samples do not produce sufficiently independent information required for parameter inversion. It should be noted that transmittance spectrum of A1 is unreliable since it was measured from a damaged sample. Despite the deficiencies in the measurements, some conclusions can still be drawn for this material and will be discussed in a later section.

PARAMETER INVERSION

As discussed in the previous section, for sets B and/or C we have two reflectance and two transmittance spectra that are consistent within each set. For the set D, there are only two reflectance and one transmittance spectra that have consistency. Thus, for both sets, the number of spectra available for parameter inversion is rather small. It was found that it is a difficult, if not impossible, task to extract three independent radiative parameters from such a sparse input data set. Initial analysis showed that of the three chosen parameters (n , k , s), the refractive index n is the least sensitive. Upon analysis, one observes that the refractive index affects radiative transport in two ways; through interfacial reflectivities (Fresnel's reflectivity) and through the self-emission term. Since the ceramics studied here possess high scattering coefficients, interfacial reflectivities have little contribution to layer reflectances. In addition, reflectance and transmittance of the samples were measured at

room temperature, consequently, the self-emission term is negligible in comparison to other fluxes and may be dropped from the transport equation. Under these circumstances, it was decided to keep the refractive index fixed at 1.58 and to determine only the remaining two parameters (s and k) through the parameter inversion procedure. This value of refractive index is based on previous observations and trends observed during current data analysis. It was reported in previous investigations (e.g. Makino and Kunitomo⁴), that refractive index remains nearly constant from 0.5 μm to 5 μm . Its value is expected to be between 1.2 to 2.5. In yet another study (Matthews⁹) involving a similar nonlinear parameter inversion technique, the refractive index of zirconia was estimated to be 1.6. Thus the value of 1.58 chosen for this study is expected to be close to the actual value of the parameter. The total uncertainty on the remaining parameters introduced by this range in refractive index is of the order of 25% and 35% for scattering and absorption coefficient, respectively.

With the above restrictions, the parameter inversion model was applied to data obtained for sample sets B and C. The results are shown in Figures 9 and 10. As expected, two samples exhibited nearly identical radiative properties. The scattering coefficient is found to be high in the visible band, and it steadily decreases as wavelength is increased. On the other hand, absorption coefficient is relatively small and remains constant except in the visible band (0.4-0.7 μm), and beyond 4 μm where it starts to increase very sharply. Figures 11a and 11b show model-predicted reflectance and transmittance for sample set C using the k and s values deduced from the data. It can be observed that the predicted reflectances and transmittance are in good agreement with the experiment except for the 10 mm sample (Figure 4b). It may be recalled that the measured reflectance spectrum for this sample was excluded from the data analysis owing to its inconsistent characteristics.

Analysis was also performed on the data belonging to set D. The inverted parameters are shown in Figures 12a and 12b. The predicted reflectance and transmittance are shown in Figure 13a. There is good agreement between measured (Figure 13b) and predicted (Figure 13a) transmittance values, however, the predicted reflectances for the two different thicknesses are nearly identical to the measured reflectance of the thinnest sample (D10). If an absorptance spectrum is computed for this sample from the measured reflectance and transmittance (Absorptance = 1 - Transmittance - Reflectance) spectra, it can be readily observed that for much of the spectrum the optical depth of the sample is high. Hence, there is no reason to believe that for higher thickness reflectance will be markedly different, contrary to the trends suggested by the data. Rather, it is likely that the apparent differences in the measured reflectance spectra are due to variations in surface preparations.

The scattering coefficients for set D possess the same qualitative trend as those of set B and C except their values are about twice as high. On the other hand, the absorption spectrum shows a distinctive peak at 3 μm corresponding to the valleys in the reflectance and transmittance spectra. In general, set D is more opaque than B and C due to its higher scattering and absorption coefficients.

It is worth noting here that the radiative parameters obtained in this study are derived from room temperature measurements. However, in a previous study Makino and Kunitomo⁴ did not observe any major dependence of radiative properties on temperature for zirconia and alumina. Hence, it is believed that the parameter values reported here will be valid for diesel engine applications where temperatures (1000 K) are not too dissimilar to the range investigated in the referenced study (~300 K to 700 K).

FOUR FLUX MODEL VS. TWO FLUX MODEL

The parameter inversion procedure discussed in the previous section utilizes a four flux radiation model. However, initially a two flux radiation model was used before it was discarded in favor of the four flux model. The experimental measurements described earlier were made under collimated (near normal beam) illumination. The two flux model is inadequate for describing propagation of collimated flux through a semi-transparent medium. However, if the fraction of incident energy that penetrated the medium is properly calculated (using directional reflectivities), the two flux model may still be valid for a medium where collimated flux undergoes quick transformation into diffuse flux due to high scattering level. On the other hand, for samples having small optical depths where the extinction coefficient is of the order of unity the contribution of the internal collimated flux on total transmittance and reflectance will be comparable to the contribution from the internal diffuse flux. Hence, in this case it is necessary to solve for both collimated and diffuse fluxes simultaneously, which the two flux model cannot accomplish.

In order to remove this weakness in the originally planned radiative parameter inversion model, replacement of the the two flux model by a four flux model was essential as it was confirmed by comparisons of parameters evaluated by both models. (Both of these models have been described in previous sections.) Initial results obtained using the original two-flux inversion model revealed that for ceramics under study the scattering level tapers off at higher wavelength. It seemed likely that the validity of two-flux model will break down at these high wavelengths. The revised model utilizing a four-flux model was applied to the available experimental data. The radiative parameters thus deduced were compared against the parameters from the two-flux model. Figures 14a and 14b show a comparison of radiative parameters obtained using both models for ceramic D. It was observed that the two-flux model underpredicted the scattering coefficient by as much as 50% at higher wavelengths, whereas the absorption coefficient remained almost unchanged.

RECOMMENDATION FOR FUTURE MEASUREMENTS

It is evident that the proper choice of the sample thicknesses is an essential prerequisite for successful parameter inversion. However, prior knowledge regarding optical thickness is required to make such choices. Hence the recommended procedure would be to make preliminary transmittance

measurements to obtain some knowledge about the opacity of the sample, or making a larger number of samples (at least 5) of various thicknesses to increase the likelihood of capturing the right sample thickness range. The recommended set of optical thicknesses is $kL = 0.5, 1.0, 1.5, 2.0$ and 2.5 which assures that meaningful values of transmittance and reflectance can be attained. For example if a material has an extinction coefficient of $10,000 \text{ m}^{-1}$ in the wavelength region of interest, the required samples will have thicknesses of 0.05 mm to 0.25 mm . If samples that thin cannot be fabricated, a thicker set of samples may be substituted, but a lower accuracy will result.

As discussed earlier, the refractive index is the least sensitive of the chosen parameters. In order to extract this parameter, one needs measurement techniques which possess stronger dependence. One approach could be a separate measurement of the diffuse and directional reflectance and transmittance (in the present case the sum of the diffuse and directional values was measured). However, this would require greater attention to surface preparation; the sample surfaces should be smooth, parallel and consistent from sample to sample. Another approach would measure polarized components of this reflectance.

Further, the number of samples should be as large as possible. A large number of samples is often necessary (eight for Makino¹⁰) to obtain reliably at least three linearly independent measurements. As for the data reduction method, it is recommended that it be based on the four-flux radiation model (or a higher order model) which has been shown here to be better capable of dealing with radiative properties of typical engineering ceramics than the two-flux model.

ANALYSIS OF TRANSLUCENCE EFFECTS ON HEAT TRANSFER

APPROACH

The general scheme of evaluating the heat transfer in diesel engines involves the solution of the energy equation (heat transfer) within the wall under appropriate gas side and coolant side boundary conditions. In the present study the cylinder walls were assumed to be composed of two layers: an insulating ceramic wall facing the combustion gas and a metallic substrate. The energy equation is a one-dimensional conduction equation with an additional source term representing radiation energy absorbed/emitted within the medium. This energy equation was solved for two distinct regions: a semitransparent region within the ceramic, and a fully opaque region within the substrate. A two-flux radiative transport equation was solved to compute the radiative heat flux vector. Since the radiation process in a diesel engine has no collimated component, both the two-flux model and four-flux yield the same result. However, equations 1, 2, 20 and 21 do not contain a self emission term. This term was included since the wall temperature of ceramics in diesel engine applications is expected to be in a region where self emission begins to be important. The resulting equation is given in a previous report (Wahiduzzaman and Morel⁷).

The gas side boundary conditions were established by computer simulation of in-cylinder processes taking place in a heavy duty truck diesel engine operating at rated conditions using IRIS engine design analysis code¹¹. This provides cyclic histories of radiation/convection temperatures, heat transfer coefficients and the products of soot volume fractions and radiation path length. These histories are shown in Figures 15a, 15b and 15c. The coolant side boundary condition consisted of a fixed coolant temperature (640K) and a very high heat transfer coefficient to impose a temperature of about 650K at the ceramic/metal interface. Details of the implementation of the energy equation and the boundary conditions were given in an earlier report describing the analytical phase of the study (Wahiduzzaman and Morel⁷). It is worth noting here that during the part of the cycle when no radiating combustion gas is present, it was assumed that the volumetric and surface emission outward from the ceramic is exactly balanced by the energy received from the other walls. This is equivalent to the assumption of equal radiosity for all walls.

For typical radiation temperatures encountered during combustion ($T_{\text{gas}} = 1800\text{-}2500\text{K}$), the fraction of total radiation energy existing beyond $5\text{ }\mu\text{m}$ is small (5-11%). At the same time, it was also evident from the experimental results that the ceramics under study become highly opaque beyond this wavelength. Hence, the ceramic layer can be assumed to have an opaque band from $5\text{ }\mu\text{m}$ to ∞ , where the absorption and emission of radiation energy beyond $5\text{ }\mu\text{m}$ is accounted for as a surface phenomenon. For the rest of the wavelength domain, the absorption and scattering coefficient spectra were discretized into a number of bands having constant radiative properties within each band. The number of bands was carefully chosen so as to preserve a satisfactory match with the original spectra, without imposing an excessive computational burden in the subsequent analysis. The band

model representation of absorption and scattering coefficient spectra is summarized in the following tables.

Ceramic B and C

λ (μm)	0.0-0.5	0.5-1.0	1.0-1.5	1.5-2.5	2.5-4.0	4.0-5.0
k (1/m)	150.0	35.0	20.0	20.0	20.0	112.0
s (1/m)	35000.	27400.	10700.	7200.	6200.	4600.

Ceramic D

λ (μm)	0-1.5	1.0-1.5	1.5-2.75	2.75-3.5	3.5-5.0
k (1/m)	710.0	300.0	10.0	1570.0	14.0
s (1/m)	45200.	45200.	30600.	14300.	20400.

The thermophysical properties (conductivity and heat capacity) of the ceramic samples were not available and their determination was beyond the scope of the present study. It was shown earlier (Wahiduzzaman and Morel⁶) that thermal conductivity is an important parameter influencing the relative sensitivity to translucence. Presently, in the absence of such data, nominal values of 0.8 W/mK and 2.91×10^6 J/Km³, pertaining to Plasma Technics plasma sprayed PSZ, were used for thermal conductivity and volumetric heat capacity, respectively, of all the materials considered in this study.

Heat transfer analysis was carried out for several thicknesses of ceramic coatings ranging from 0.04 mm to 5.0 mm, where 2.5 mm (~0.100 inches) is chosen as the nominal thickness for most of the calculation to be discussed later on. The grid points in the ceramic and the substrate were generated in such a manner that the grid spacing was compact near the gas-ceramic and ceramic-substrate interfaces. The smallest elements were located at either side of the ceramic-substrate interface and at the gas-ceramic interface, and they were 0.015 mm (0.0006 inch) thick. There were twenty-one grid points in the insulating ceramic layer.

EFFECTIVENESS OF INVESTIGATED CERAMICS AS HEAT BARRIER MATERIALS

The effectiveness of the ceramics under study to act as a barrier to thermal radiation was investigated by subjecting these and three idealized (limiting-case) ceramics to identical boundary conditions. The results of these simulations are summarized in Table III. The idealized ceramics were either completely transparent or completely opaque. The opaque limiting cases were of two types, ie, ceramics characterized either by high scattering coefficient ($>10^7$ m⁻¹) and negligible absorption coefficient (denoted as opaque (s) in Table III) or by high absorption coefficient ($>10^7$ m⁻¹) and negligible scattering coefficient (denoted as opaque (a) in

Table III). All five ceramics had a thickness of 2.5 mm, and the nominal thermophysical properties discussed above. The resulting temporal history of various components of the total heat flux for ceramics C and D is shown in Figures 16a and 16b. The solid curve represents the net radiation flux just inside the ceramic at node #1. The dashed line represents the amount of this flux transmitted to the ceramic/metal interface. The dotted line represents the radiation flux comprising the reflected and emitted radiation from the ceramic coating to the gas. The remaining line represents the convective heat flux to the ceramic coating.

It may be noted that the total flux for the clean C case is only one quarter of the metal case. This is due to the much higher surface temperature which reduces the convective heat transfer. On the other hand the swing is about three times as high, and that is due to the lower value of the product $\rho c k$.

It can be seen from Table III that the effectiveness of the two actual ceramic coatings (each 2.5 mm thick) as a barrier to total heat transfer is about the same. However, the ratio of the radiative heat flux to convective heat flux is different. For the more opaque ceramic (D), much of the radiation is absorbed near the surface, raising the mean surface temperature. This lowers the effective temperature difference between the combustion gas and the surface, and the convective heat flux is reduced. It is interesting to note that the radiative heat flux through ceramic C is less than that with ceramic D, despite the fact that C is more transparent than D. This is a consequence of differences in reflectance between the two materials. Since both materials have a high scattering coefficient, the one which has a lower absorption coefficient scatters more energy out of the coating before it can be absorbed. Hence ceramic C has a higher total reflectance than ceramic D. Consequently, less net radiation energy is absorbed in ceramic C than D.

If the thicknesses of the samples are sufficiently reduced this trend can be reversed; since for the ceramic C more of the radiation energy will reach the ceramic-substrate interface and be absorbed there before being scattered back out. Figures 17a and 17b show distributions of radiative and total heat fluxes as a function of layer thickness, and show that this reversal happens at around a thickness of 1.25 mm. In either case, however, the heat flux decreases with increasing layer thickness. It may be noted that the total heat fluxes for the two ceramics appear to not converge as the coating thickness is reduced towards zero. That is not really so, because in the limit the two curves must coincide. However, at even very small thicknesses, e.g., 0.05 mm for these specific ceramics, the product of the scattering coefficient and the layer thickness is large enough to produce significant scattering which augments the reflected component of radiation heat flux. Since the scattering coefficient of ceramic D is greater than that of ceramic C its net radiative flux is smaller and this persists to even quite small thicknesses.

In terms of the total heat flux, it appears from Table III that the ceramics under study are much closer to both opaque limiting cases than to the transparent limiting case. However, the mechanism of the heat transfer

process is closer to the opaque(s) limit; in this opaque limit most of the heat transfer is due to the convective flux, since very little radiative flux can penetrate the coating due to high reflectance caused by its high scattering and low absorption coefficients. In ceramics C and D a large fraction of incident radiant energy will be reflected away for the same reason. Consequently, a smaller fraction of the radiation energy can be trapped by the coating system and the surface temperature only increases moderately due to absorption of this radiation energy. This in turn will cause a small reduction of the convective heat flux from the maximum value obtainable in the fully transparent case. For the opaque (a) limiting case much of the incident radiation will be absorbed at the surface raising its temperature which will cause a larger reduction in the convective heat flux at the cost of an increased radiative heat transfer.

In the case of the ideal transparent case, both radiative and convective heat fluxes are high. Since there is no scattering, a very small portion of the incoming radiative energy is reflected (due to interfacial Fresnel's reflectivity) and most of the energy is absorbed at the ceramic-substrate interface. This leaves the gas-ceramic interface at a relatively lower temperature, which increases the convective heat transfer.

EFFECT OF SURFACE CONDITIONS

In the preceding analysis it is implicitly assumed that the surface of the ceramic thermal barrier is the same as that of the samples obtained for our analysis. Further it is assumed that it remains free of soot and other deposits and that its surface layer does not become impregnated with foreign materials and/or discolored.

These are very significant assumptions and one needs to understand how do the results obtained here translate to situations where the surface condition is different from that found on the supplied test samples. In an operating diesel engine it is expected that surface fouling will occur and degree of which will depend on the particular engine and the operating condition. This surface fouling could be due to absorption of moisture/fuel by the coating and/or deposition of solid particulates in the ceramic surface. The absorption of solid and liquid particulates can be expected to affect the thermophysical and radiative properties of the coating. The effect of this change is difficult to anticipate or model. In terms of radiative properties, the absorption of combustion products by the coating will tend to make the coating more radiatively opaque and the opaque (a) limit of the coating will provide an indication of its effect on heat transfer.

If the ceramic surface departs from being optically smooth ($l/\lambda < 1$, where l is rms value of surface roughness) more and more incident radiation will be trapped thereby reducing effective reflectance and increasing hemispherical emissivity. In general, this will tend to promote radiation heat transfer. It is difficult, if not impossible, to predict the effect of impregnated surface impurities. It will, most likely, be dependent on the nature of impurities. It can however be speculated that impurities will also alter the surface finish and make it optically rough and thereby will have a

similar impact on radiant heat transfer as surface roughness. However, definitive conclusions can only be made if reflectance measurements are made for the ceramic coatings before and after being exposed to the engine environment.

MODELING OF SOOT EFFECT

The effect of soot deposit is one that can be modeled. Let us consider a thin layer of soot deposited on the coating. Since this deposit layer will be composed mostly of carbonaceous material it will readily absorb radiative heat flux incident on it. This layer can be modeled as a thin coating of negligible thermal capacity (uniform temperature) and having a negligible thermal resistance between the layer and the ceramic coating. Under these assumptions, in order to compute radiative and convective heat flux, it is sufficient to modify the boundary condition imposed on the first ceramic node point. A modification of the boundary condition has to be constructed, which is capable of modeling any state of fouling between clean to completely soot-covered ceramic coating. In the first limiting case the ceramic is clean and the incident radiation penetrates directly into the ceramic without first being absorbed by intervening deposit layer. In the second limiting case the incident radiation is totally absorbed by the deposit and the deposit reradiates into the ceramic coating. Intermediate levels of fouling are represented by a fouling factor (G) which can take any value between 0 and 1. A value of one for the fouling factor represents fully sooted surface and a value of zero represent clean surface. The intermediate values can be thought of as a representation of soot layer with varying degrees of surface coverage. The detail of the requisite boundary conditions representing this physical situation is described below.

Radiation energy passing through at the gas-soot layer interface (node #1)

$$Q(0) = q_1 - q_2 - q_3 + q_4 \quad (31)$$

where

$$q_1 = \int_0^{\lambda_c} (1-R_{do})(1-G) q_i d\lambda \quad (31a)$$

$$q_2 = \int_0^{\lambda_c} GE_{b\lambda} d\lambda \quad (31b)$$

$$q_3 = \int_0^{\lambda_c} (1-R_{di})(1-G)F^-(0) d\lambda \quad (31c)$$

$$q_4 = \int_{\lambda_c}^{\infty} (\alpha + G(1-\alpha))(q_1 - E_{b\lambda}) d\lambda \quad (31d)$$

$E_{b\lambda}$ - blackbody emissive power

G - fouling factor

q_1 - incident radiation

λ - wavelength

λ_c - 5 μm - cutoff wavelength for transparent/opaque bands

α - surface absorptance in the opaque band

The first term of equation (31) represents the fraction of the incident energy within the transparent band of the ceramic (0 to λ_c) that will be either absorbed or pass through the gas/ceramic interface. The second term represents emission of the soot deposit back to the radiating gas. The contribution of this term will be present only if there is a soot layer on the surface. The third term represents emitted and scattered radiation from within the coating escaping to the gas. Here again if the surface is fully sooted no radiation will escape and consequently this term will vanish. The final term of the equation (31) is the fraction of the incident energy within the opaque band (λ_c to ∞) that is absorbed at the surface. This term is composed of the difference between the net incident energy (incident energy - reflected energy) and the emitted energy from the surface.

This deposited energy at the first node will be transported to the interior node by either conduction or radiation. The radiation flux at node #1 is given by

$$q_r(0) = F^+(0) - F^-(0) \quad (32)$$

where

$$F^+(0) = q_5 + q_6 + q_7 \quad (33)$$

$$q_5 = \int_0^{\lambda_c} (1-R_{do})(1-G)q_1 d\lambda \quad (33a)$$

$$q_6 = \int_0^{\lambda_c} G n_1^2 E_{b\lambda} d\lambda \quad (33b)$$

$$q_7 = \int_0^{\lambda_c} R_{di} F^-(0) (1-G) d\lambda \quad (33c)$$

$F^+(0)$ - toward diffuse flux at node 1 (pointing to the interior)

$F^-(0)$ - backward diffuse flux at node 1 (pointing to the exterior)

The first term in equation (33) is the fraction of the incident radiation within the transparent band that passes through the gas/ceramic interface. (Note that this term is different from q_1 inasmuch as it does not include the radiation absorbed at the surface.) The second term is the radiation energy within the transparent band ($0-\lambda_c$) that is emitted by the surface into the coating. The final term is the portion of the backward flux that reflected back into the coating by the front interface. (This is the complementary term of q_3 .)

The conduction flux at node #1 is the difference between the total flux passing through the surface and the radiation flux at that node

$$q_c(0) = Q(0) - q_r(0) + h_g (T_g - T_w) \quad (36)$$

The other boundary conditions (e.g. at ceramic/metal interface and coolant/metal interface) were given in a previous report (Wahiduzzaman and Morel⁶) and are only summarized here. The continuity condition for temperature at the ceramic/metal substrate is given by

$$T_c(d) = T_m(d) \quad (37)$$

where T_c and T_m are ceramic side and metal side temperatures respectively. The radiative flux boundary condition at ceramic/metal interface is

$$\int_0^{\lambda_c} F^-(d) d\lambda = \int_0^{\lambda_c} (\rho_s F^+(d) + \epsilon_s E_{b\lambda}) d\lambda \quad (38)$$

and at the gas/ceramic interface it is

$$\int_0^{\lambda_c} F^+(0) d\lambda = \int_0^{\lambda_c} (R_{di} (1-G) F^-(0) + (1-R_{do}) (1-G) q_1) d\lambda \quad (39)$$

This model was checked by setting it to zero to obtain clean ceramic results. It should be noted here that the above integrations are performed over several discrete bands, as discussed in a previous section.

The results obtained with this model are presented in Table III. With G set to unity (fully sooted case) the results labeled "sooted" were generated. It can be seen that the presence of the soot layer produced a variety of changes. The surface temperature was increased, one big reason being the elimination of surface reflectivity by the presence of black soot and the resultant higher radiative flux. A larger change is seen in the surface swing, this being caused by the absorption right at the surface rather than sub-surface. The convective flux was reduced due to the higher surface temperature. Finally, the total heat flux was generally slightly increased, except for the fully transparent case where a 10% reduction was seen due to the reduction in convective flux. It is very interesting to see that even though the soot reduced the differences in total heat flux between the fully transparent and the fully opaque cases from 70 to 49 kW/m^2 , there remained a substantial difference between them. This indicates that if the ceramic surface temperature is high, exceeding 1000K, the time-averaged radiation produced by the soot layer with its high emissivity, approaches and can exceed that produced by the much hotter diesel flame, which however persists for only a short fraction of time. It is also interesting to note that for the two opaque limits soot deposit produces identical results. This is because in the opaque(s) case soot emitted radiation is reabsorbed by the soot layer after being scattered back to the soot/ceramic interface. This is very similar to the situation existing in opaque (a) case where soot radiation is quickly absorbed by the coating close to the soot/ceramic interface.

The distributions of the radiative, convective and total heat fluxes computed for different levels of fouling on a 2.5 mm ceramic (type C) coating are given in Figure 18. As the fouling level is increased, the radiative transport increases sharply, accompanied by a decrease in the convective heat flux. This decrease in convective heat flux is due to increase in surface temperature caused by the absorption of radiative energy at the surface. As expected, at the highest fouling level ceramic C behaves more like the sooted opaque limiting case rather than the transparent one (Table III). This is again due to absorption of radiative energy at or very near the surface as in opaque limiting case. There is a small increase in total heat flux with increasing surface fouling, indicating that although the mechanism of the heat transfer changes with surface fouling, its impact on total heat transfer is moderate at least for the boundary conditions used in this study.

DISCUSSION

The radiative properties of several existing ceramic coating materials were determined experimentally. This involved measuring reflectance and transmittance spectra of the ceramic samples of different thicknesses. A model describing the radiative transport process in semitransparent media was then fitted to the measured data sets. An optimization technique was used to adjust the radiative parameters until the best fit to the measured data was obtained.

The model describes the radiative transport within a medium using three parameters, namely scattering coefficient, absorption coefficient and

refractive index. This involves some implicit assumptions about interfacial reflectivities and phase function for the material. It was assumed that the interfacial reflectivities can be approximated by Fresnel's equations which is strictly valid for optically smooth surfaces ($l/\lambda < 1$, where l is the rms value of the surface roughness). It was determined a posteriori that accurate determination of the surface reflectivities was not critical in view of the high scattering coefficients of the studied ceramics. Another assumption regards the phase function. Since the grains of the ceramic are densely packed and randomly oriented, there will not be any preferred direction of scattering. Consequently, a uniform scattering phase function was used. In addition, a fixed value of refractive index, as discussed earlier, was used for all parameter inversion. This constraint had to be imposed due to the small number of independent data points available, keeping in mind that the results are relatively insensitive to this parameter (Wahiduzzaman and Morel⁷).

In order to perform a systematic error analysis on the inverted parameter, the variability of the measured quantities (reflectance and transmittance spectra) are needed. This in turn depends on the repeatability of the sample preparation and uncertainty associated with the measuring instrument. Unfortunately, such study was beyond the scope of this program, since the number of samples of each material used in this study was limited and no repeat measurements with identical samples were made. Nevertheless, based on the assumptions involved in the technique and an expected variability in measured data, an assessment can be made of the uncertainty in the values of the inverted parameters. For errors of $\pm 5\%$ in transmittance, $\pm 5\%$ in reflectance and $\pm 25\%$ in refractive index, maximum error over the entire spectral range was found to be of the order of 53% for scattering coefficients and 40% for absorption coefficient. Although this uncertainty appears to be large, the calculated heat transfer is affected only moderately over this range. Thus despite the uncertainty in the properties, the basic results of this work, as discussed below, should be unchanged.

The ceramic samples used in this study were found to be highly reflective (reflectance on the order of 0.6-0.8) and optically thick even at thicknesses of the order of 2 mm. In particular, the reflectance spectrum of the 0.51 mm sample (A1) of PSZ obtained from Plasma Technics was nearly identical to the corresponding spectra belonging to 1.092 and 5.74 mm samples (A2 and A3) indicating that even the thinnest sample is optically thick. It should be noted here that the level of reflectances of the material A are of same order as for materials B and C, and thus the scattering coefficients are probably of similar magnitude. However, the ceramics B and C are less optically dense than the ceramic A, based on the fact that their reflectances display dependence on thickness between 0.5 and 1 mm not seen in ceramic A. Thus one may make the indirect inference that the ceramic A has much higher absorption coefficients than ceramics B and C.

Ceramics B and C (PSZ and TZF from Oak Ridge Laboratory) were found to be radiatively identical. The reflectance and transmittance spectra of both materials were nearly identical and consequently, inverted properties were

also the same for both materials. The absorption coefficients of ceramics B, C and D were found to be much smaller than the scattering coefficients (high scattering albedo). Material B and C possessed lower scattering and absorption coefficients in comparison to material D and hence, were optically less dense than D. In any event, a nominal thickness of 2 mm of any of the studied ceramics would be sufficient to prevent any appreciable radiation energy from reaching the metal substrate.

The radiative parameters of the materials studied here exhibited both qualitative and quantitative agreement with previous measurements (Makino et al⁴) made on a number of monolithic ceramics including zirconia (85% ZrO₂ by weight, with Y₂O₃, SiO₃ and Al₂O₃). The scattering coefficients obtained in that study displayed similar decreasing trends at higher wavelengths, although the values of the coefficients were lower (12000 m⁻¹ at shorter wavelengths). The absorption coefficients were of similar order of magnitude as those found here and the spectrum contained sharp rise around 4 μm, similar to that evidenced in the spectrum of ceramic C. The lower scattering coefficient found for the monolithic ceramics by Makino et al can be attributed primarily to the difference in microstructure of the two ceramics. To quantify the differences between the present coatings and Makino's monolithics, an analysis was carried out of the heat barrier effectiveness of a monolithic ceramic 2.5 mm thick subject to the same boundary conditions as done for the coatings in Table III. The results showed that for Makino's monolithic ceramics the radiation heat transfer was larger by 30% and the total heat transfer was 8% higher. This shows that these ceramics were less optically opaque and thus less effective as barriers to heat radiation than the present coatings (at the same thickness and assuming the same thermal conductivity and heat capacity).

A heat transfer analysis based on these radiative parameters showed that at the larger thicknesses (above 1.25 mm) materials C and B are more effective against radiative heat transfer than material D of same thickness. At lower thicknesses the situation is reversed. This trend is a consequence of reflectivity of the coatings which can be substantially influenced by the ceramic/metal interface depending on the coating thickness.

In general, the studied ceramics exhibited similar characteristics in terms of preventing radiative heat transfer. The scattering albedo of these ceramics were found to be large, causing them to be fairly reflective (60-80%) and optically thick at conventional coating thicknesses (1 to 2 mm). As a result, most of the radiation that penetrates the coating is absorbed within the coating as opposed to at ceramic/metal interface. Since a significant portion of this absorption occurs at or near the surface, the surface temperature is increased. This has a beneficial effect of reducing the convective component of the total heat transfer.

In an operating engine, the coating surface will lose a lot of its reflectivity due to carbonaceous deposits. In such a case the incident radiant energy will be readily absorbed by the deposit layer causing the surface temperature to go up even higher. This will further reduce the convective heat flux and partially compensate for the increased radiant heat transfer at the surface (less reflected radiation). On the other

hand, the radiation of the surface deposit layer towards the interior of the ceramic increases rapidly with the increasing surface temperature and at high enough temperature could exceed the radiation from the flame (because it has high emissivity and acts all the time, whereas the gas radiates only some 5-7 percent of the time). It should be mentioned that when the surface temperature becomes sufficiently high the soot particles in the deposit layer will tend to burn off. Thus the ceramic will tend to return to its original clean state, probably before the point of excessive surface radiation is reached.

Based on the present results and the above observations, one can speculate on the ideal thermal barrier for engine applications. To prevent radiant heat transfer, the coating should be highly reflective, for example through a combination of high scattering coefficient ($>20000 \text{ m}^{-1}$) and low absorption coefficient. If a homogeneous ceramic satisfying these conditions could not be found, one could contemplate a composite ceramic, or one having a thin reflective and opaque metallic coating on the surface. However, if significant soot deposition occurs at the coating surface a large portion of the incident radiation energy will be trapped by the deposit layer causing a substantial increase in radiation heat transfer. As mentioned previously, this will be associated with an increase in surface temperature. The level of this increase will depend on the location where the energy reradiated by the deposit layer is absorbed. If the coating is opaque it will be absorbed at or near the interface and the increase in surface temperature will be large which will in turn cause a large reduction in convective heat flux. This opacity could be achieved, as evidenced in Table III, either through high scattering coefficient or high absorption coefficient or a combination of both. In the case of transparent ceramic the reradiated energy will be absorbed at the coating/metal interface, leaving the surface at a lower temperature (Table III) and consequently the reduction in the convective heat flux will be small. Hence, to insure the best thermal barrier for either clean or heavily sooted surfaces, a ceramic material with high scattering and low absorption coefficient provides the best choice. To reduce the convective heat transfer relatively independently of the radiant heat transfer, one can follow the conventional approach of choosing a material having low thermal conductivity and as large as practicable coating thickness.

CONCLUSIONS

- 1) An experimental study was carried out to determine the radiative properties of four ceramics; A (PSZ, 13% yttria stabilized), B (PSZ), C (TZP) and D (PSZ, 24% ceria stabilized). Ceramics B and C were found to possess high scattering coefficient (in excess of 30000 m^{-1} in short wavelengths) and low absorption coefficients. Ceramic D had even higher scattering coefficients (in excess of 40000 m^{-1} at short wavelengths) and moderate absorption coefficients (2000 m^{-1} at $3 \mu\text{m}$). Although parameter inversion was not possible for material A, a comparison of its reflection spectra with corresponding spectra of other ceramics tested indicates it to be the most optically dense material in the group.

2. In terms of overall radiation effect, these coatings were found to be highly reflective (reflectance around 0.6-0.8) due to their high scattering coefficients. They also were found optically thick even at thicknesses of 2 mm, i.e., permitting only a small fraction of radiation to pass through to the substrate. Comparison to literature data on monolithic zirconia ceramics showed those to be more transparent and thus less effective as barriers to heat radiation.
3. When compared to the limiting cases of completely transparent and completely opaque, the total heat transfer through the studied ceramics for 2.5 mm thickness was substantially closer to either of the opaque limits than to the transparent limit. However, when the surface is clean, the mechanism of the heat transfer more closely approached the opaque(s) limit rather than the opaque(a) limit. On the other hand, for a sooted surface, both opaque limits converged into a single limit.
- 4) With regard to the most desirable ceramic properties for diesel engine applications, it was concluded that a highly scattering ceramic with low absorption coefficient would be the best heat barrier material for blocking thermal radiation. An alternative would be a composite ceramic coated with an opaque high reflectance surface layer. From the point of view of convective heat transfer, any scheme aimed at raising surface temperature will be effective in reducing convective heat transfer, and low thermal conductivity is an essential element in this respect. However, other factors such as volumetric efficiency, thermal stress, etc. have to be considered in selection of an appropriate insulation package.
- 5) In experimental determination of radiative properties of ceramics it is highly desirable to perform preliminary transmittance measurements to obtain some knowledge on the opacity of the material. This knowledge can then be used for proper selection of material thicknesses to obtain samples ranging from optically thin to optically thick. In order to extract the refractive index, alternate type of measurements are recommended. These may include separate measurements of diffuse and directional reflectance and transmittance, and/or measurement of polarized components of the reflectance.
- 6) Both four-flux and two-flux methods were used and it was concluded that the four-flux method is more appropriate for parameter inversion models than the simpler two-flux method. This method is better equipped to handle collimated illumination and has the ability to predict both diffuse and directional quantities. It was found that the two-flux model underpredicts scattering coefficient substantially when the scattering level is low.

NOMENCLATURE*

A	-	$3\omega/(8\beta^2-2)$
B	-	A/3
C ⁺	-	collimated forward flux
C ⁻	-	collimated backward flux
d	-	depth of the layer
D ⁺	-	diffuse forward flux
D ⁻	-	diffuse backward flux
E	-	s+k - extinction coefficient
E _{bλ}	-	blackbody emissive power
F _d	-	diffuse incident flux
F _c	-	collimated incident flux
G	-	fouling factor
h _g	-	heat transfer coefficient
k	-	absorption coefficient
n	-	refractive index
p	-	phase function
q _i	-	incident radiation
R _{di}	-	diffuse interfacial internal reflection
R _{do}	-	diffuse interfacial external reflection
R _{ci}	-	collimated interfacial internal reflection
R _{co}	-	collimated interfacial external reflection
R _d	-	diffuse reflectance
R _h	-	hemispherical reflectance
S _c	-	reflected collimated flux
S _d	-	reflected diffuse flux
s	-	scattering coefficient
T _c	-	ceramic side temperature at the interface
T _d	-	diffuse transmittance
T _g	-	gas temperature
T _h	-	hemispherical transmittance
T _m	-	metal side temperature at the interface

*All variables are in S.I. units except where noted.

T_w - surface temperature of the wall
 α - surface absorptance in the opaque band
 α_1 - linear constant for flux equation
 α_2 - linear constant for flux equation
 α_3 - linear constant for flux equation
 α_4 - linear constant for flux equation
 β - $\sqrt{1-\omega}$
 λ - wavelength
 ω - $s/(s+k)$ - albedo
 τ - $(k+s)x$ - optical depth at x
 τ_d - $(k+s)d$ - optical thickness of the entire translucent layer
 λ - wavelength
 λ_c - $5 \mu m$ - cutoff wavelength for transparent/opaque bands

REFERENCES

1. T. Morel, R. Keribar, P. N. Blumberg and E. F. Fort (1984), "Methods for the Integrated Analysis of Heat Transfer, Component Temperatures and Performance in Insulated Engines", ATD-CCM, Dearborn, Michigan, 1984.
2. Liebert, C. H. (1965), "Spectral Emittance of Aluminum Oxide and Zinc Oxide on Opaque Substrates", NASA TN D-3115.
3. Liebert, C. H. (1978), "Emittance and Absorptance of NASA Ceramic Thermal Barrier Coating System", NASA Technical Paper 1190; also in Thin Solid Films, 53, pp. 235-240, 1978.
4. Makino, T. and Kunitomo, T. (1984), "Thermal Radiation Properties of Ceramic Materials", Transaction of the Japan Society of Mechanical Engineers, Vol. 50, No. 452, pp. 1045-1052.
5. Ishimaru, A. (1978), Wave Propagation and Scattering in Random Media Volume 1, Academic Press, 111 Fifth Avenue, NY, NY 10003.
6. T. Morel and R. Keribar, "Heat Radiation in DI Diesel Engines", SAE Paper 860445.
7. S. Wahiduzzaman and T. Morel (1987), "Effect of Translucence of Engineering Ceramics on Heat Transfer in Diesel Engines", ORNL Report ORNL/Sub/86-22042/1, October 1987.
8. R. Willey (1976), "Fourier Transform Infrared Spectrometer for Transmittance and Diffuse Reflectance Measurements", Applied Spectroscopy, 30, No. 5.
9. Matthews, L. K. (1982), "Experimental and Theoretical Analysis of the High Flux - High Temperature Field in a Dielectric Subjected to Intense Solar Radiation," PhD Thesis, Purdue University, West Lafayette, Indiana, p. 94.
10. Makino, T. (1986), personal communication.
11. Morel, T., Rackmil, C. I., Keribar, R. and Jennings, M. J. (1988), "A New Approach to Integrating Engine Performance and Component Design Analysis Through Simulation", SAE Paper 880131.

Table I. List of Ceramic Samples

<u>Set</u>	<u>Sample #</u>	<u>Material</u>	<u>Supplier</u>	<u>Thickness (mm)</u>
A	1	PSZ	Plasma Tech	0.51
A	2	PSZ	Plasma Tech	1.02
A	3	PSZ	Plasma Tech	5.74
B	4	TZP	Oak Ridge Lab	0.50
B	5	TZP	Oak Ridge Lab	1.00
B	6	TZP	Oak Ridge Lab	10.00
C	7	PSZ	Oak Ridge Lab	0.50
C	8	PSZ	Oak Ridge Lab	1.00
C	9	PSZ	Oak Ridge Lab	10.00
D	10	PSZ	Caterpillar	0.41
D	11	PSZ	Caterpillar	0.58
D	12	PSZ	Caterpillar	1.04
D	13	PSZ	Caterpillar	2.49

Table II. Matrix of Radiative Measurements

<u>Sample ID</u>	<u>Reflectance</u>		<u>Transmittance</u>	
	<2.5 μm	2-20 μm	<2.5 μm	2-20 μm
A1	✓	✓	s/u	✓
A2	✓	✓	l/s	✓
A3	✓	✓	n/r	n/r
B4	✓	✓	✓	✓
B5	✓	✓	✓	✓
B6	✓	✓	n/r	n/r
C7	✓	✓	✓	✓
C8	✓	✓	✓	✓
C9	✓	✓	n/r	n/r
D10	✓	✓	✓	✓
D11	✓	✓	l/s	l/s
D12	✓	✓	l/s	l/s
D13	✓	✓	n/r	n/r

Key: ✓ - measurement made; s/u - sample unavailable; n/r - measurement not requested; l/s - measurement attempted but failed due to low signal-to-noise ratio.

Table III. Effect of Ceramic Properties and Surface Fouling on Time-Averaged Heat Flux and Temperatures

<u>Ceramic</u>	<u>Surface Temp.</u>	<u>Indepth*</u> <u>Temp.</u>	<u>Surface Swing</u>	<u>Radiative Flux</u>	<u>Convective Flux</u>	<u>Total Flux</u>
	K		K	kW/m ²	kW/m ²	kW/m ²
Metal baseline	701.9		25.2	86.5	316.2	402.8
Clean C	943.5	650.0	90.7	22.0	84.0	106.0
Clean D	953.7	649.5	90.4	25.8	75.2	101.0
Transparent	937.5	657.0	91.7	91.3	89.2	180.5
Opaque (a) #	995.2	650.0	116.6	82.2	28.1	110.3
Opaque (s) #	935.3	648.6	92.1	0.7	91.1	91.8
Sooted C	1001.4	651.0	122.3	97.4	20.6	118.0
Sooted D	1001.3	650.7	121.4	96.8	18.1	114.9
Sooted trans.	948.8	655.2	131.9	97.6	65.2	162.8
Sooted opaque (a)	1005.8	650.6	121.2	96.4	17.1	113.5
Sooted opaque (s)	1005.6	650.6	121.2	96.5	17.1	113.6

*Temperature at the ceramic/metal interface, i.e. at a depth of 2.5 mm from the surface.

#Opaque (a) is the opaque limit attained by high absorption and negligible scattering.

#Opaque (s) is the opaque limit attained by high scattering and negligible absorption.

Figure 1. Physical model of the insulating coating.

Figure 2(a). Transmittance spectra of material A (PSZ, 13 yttria stabilized) from Plasma Techniques.

Figure 2(b). Reflectance spectra of material A.

Figure 3(a). Transmittance spectra of material C (PSZ) from Oak Ridge National Laboratory.

Figure 3(b). Reflectance spectra of material C.

Figure 4(a). Transmittance spectra of material C (PSZ) from Oak Ridge National Laboratory.

Figure 4(b). Reflectance spectra of material C.

Figure 5(a). Transmittance spectra of material D (PSZ, 241 ceria stabilized) from Caterpillar.

Figure 5(b). Reflectance spectra of material D.

Figure 6(a). Merged transmittance spectra of material B used for parameter inversion.

Figure 6(b). Merged reflectance spectra of material B used for parameter inversion.

Figure 7(a). Merged transmittance spectra of material C used for parameter inversion.

Figure 7(b). Merged reflectance spectra of material C used for parameter inversion.

Figure 8(a). Inverted scattering coefficient spectrum of material B.

Figure 8(b). Inverted absorption coefficient spectrum of material B.

Figure 9(a). Inverted scattering coefficient spectrum of material B.

Figure 9(b). Inverted absorption coefficient spectrum of material B.

Figure 10 (a). Inverted scattering coefficient spectrum of material C.

Figure 10 (b). Inverted absorption coefficient spectrum of material C.

Figure 11(a). Calculated transmittance spectra of material C.

Figure 11(b). Calculated reflectance spectra of material C.

Figure 12(a). Inverted scattering coefficient spectrum of material D.

Figure 12(b). Inverted absorption coefficient spectrum of material D.

Figure 13(a). Calculated transmittance and reflectance spectra of material D.

Figure 13(b). Measured transmittance and reflectance spectra of material D.

Figure 14(a). Comparison of inverted scattering coefficient spectrum of material D for four flux and two flux models.

Figure 14(b). Comparison of inverted absorption coefficient spectrum of material D for four flux and two flux models.

Figure 15(a). Gas and radiation temperature history used as gas side boundary condition on the heat barrier coating.

Figure 15(b). Heat transfer coefficient history used as gas side boundary condition on the heat barrier coating.

Figure 15(c). History of soot volume fraction times radiation path length used as gas side boundary condition on the heat barrier coating.

Figure 16(a). Time dependent fluxes computed for 2.5 mm heat barrier coating using radiative properties of material C.

Figure 16(b). Time dependent fluxes computed for 2.5 mm heat barrier coating using radiative properties of material D.

Figure 17(a). Time averaged radiative heat flux for ceramics C and D as a function of thickness.

Figure 17(b). Time averaged total heat flux for ceramics C and D as a function of thickness.

Figure 18. Effect of soot fouling for 2.5 mm Ceramic C coating used as heat barrier on time averaged fluxes.

APPENDIX

The reflectance and transmittance measurements at short to long infrared regions ($2\text{ }\mu\text{m}$ to $20\text{ }\mu\text{m}$) were measured at the Willey Corporation. The data obtained were quite noisy at shorter wavelengths and necessitated smoothing. The smoothed profiles shown in the text have been used in the analysis. However, for reference purposes, the unsmoothed data is also presented in the following figures. (Note: Per instruction from the Willey Corporation the values in the reflectance spectra need to be divided by 0.95). The corresponding NBS measurements carried out in the range $0.25\text{ }\mu\text{m}$ to $2.5\text{ }\mu\text{m}$ were furnished in tabular form and plots obtained from these tables are presented without modification in the general text of this report and will not be repeated here.

HILLEY 318P 11-07-1987 21:33:21 ITI 1 A .020 IN. REFL

Figure A-1 Unsmoothed Reflectance Spectra of Sample A1

Figure A-2 Unsmoothed Reflectance Spectra of Sample A2

Figure A-3 Unsmoothed Reflectance Spectra of Sample A3

Figure A-4 Unsmoothed Reflectance Spectra of Sample B4

WILLEY 318P 11-09-1987 19:27:11 ITI 5 B 1.0MM REFL

Figure A-5 Unsmoothed Reflectance Spectra of Sample B5

HILLEY B18P 11-09-1987 20:12:02 ITI 6 B 10.0MM REFL

Figure A-6 Unsmoothed Reflectance Spectra of Sample B6

WILLEY 318P 11-07-1987 19:26:50 ITI 7 C 0.5MM REFL

Figure A-7 Unsmoothed Reflectance Spectra of Sample C7

WILLEY 318P 11-07-1987 19:48:16 ITI 8 C 1.0MM REFL

Figure A-8 Unsmoothed Reflectance Spectra of Sample C8

Figure A-9 Unsmoothed Reflectance Spectra of Sample C9

Figure A-10 Unsmoothed Reflectance Spectra of Sample D10

HILLEY 318P 11-07-1987 22:13:47 ITI 11 D .023 IN. REFL

Figure A-11 Unsmoothed Reflectance Spectra of Sample D11

WILLEY 318P 11-07-1987 22:48:33 ITI 12 D⁰⁴ IN. REFL

Figure A-12 Unsmoothed Reflectance Spectra of Sample D12

WILLEY 318P 11-07-1987 23:30:35 ITI 13 D .098 IN. REFL

Figure A-13 Unsmoothed Reflectance Spectra of Sample D13

Figure A-14 Unsmoothed Reflectance Spectra of Sample A1

Figure A-15 Unsmoothed Reflectance Spectra of Sample A2

Figure A-16 Unsmoothed Reflectance Spectra of Sample B4

Figure A-17 Unsmoothed Reflectance Spectra of Sample B5

Figure A-18 Unsmoothed Reflectance Spectra of Sample C7

Figure A-19 Unsmoothed Reflectance Spectra of Sample C8

Figure A-20 Unsmoothed Reflectance Spectra of Sample D10

INTERNAL DISTRIBUTION

1-2.	Central Research Library	42.	M. G. Jenkins
3.	Document Reference Section	43.	D. R. Johnson
4-5.	Laboratory Records Department	44.	W. F. Jones
6.	Laboratory Records, ORNL RC	45.	D. Joslin
7.	ORNL Patent Section	46.	R. R. Judkins
8-10.	M&C Records Office	47.	M. A. Karnitz
11.	L. F. Allard, Jr.	48.	M. R. Kass
12.	L. D. Armstrong	49-53.	B. L. P. Keyes
13.	P. F. Becher	54.	H. D. Kimrey, Jr.
14.	R. F. Bernal	55.	T. G. Kollie
15.	T. M. Besmann	56.	K. C. Liu
16.	P. J. Biau	57.	E. L. Long, Jr.
17.	A. Bleier	58.	W. D. Manly
18.	E. E. Bloom	59.	R. W. McClung
19.	K. W. Boling	60.	D. J. McGuire
20.	R. A. Bradley	61.	J. R. Merriman
21.	C. R. Brinkman	62.	D. L. Moses
22.	V. R. Bullington	63.	T. A. Nolan
23.	R. S. Carlsmith	64.	A. E. Pasto
24.	P. T. Carlson	65.	J. L. Rich
25.	G. M. Caton	66.	C. R. Richmond
26.	S. J. Chang	67.	J. M. Robbins
27.	R. H. Cooper, Jr.	68.	M. L. Santella
28.	B. L. Cox	69.	A. C. Schaffhauser
29.	D. F. Craig	70.	S. Scott
30.	S. A. David	71.	G. M. Slaughter
31.	J. H. DeVan	72.	E. J. Soderstrom
32.	J. L. Ding	73.	D. P. Stinton
33.	M. K. Ferber	74.	R. W. Swindeman
34.	F. M. Foust	75.	V. J. Tennery
35.	W. Fulkerson	76.	T. N. Tiegs
36.	R. L. Graves	77.	J. R. Weir, Jr.
37.	D. L. Greene	78.	B. H. West
38.	M. H. Harris	79.	F. W. Wiffen
39.	E. E. Hoffman	80.	S. G. Winslow
40.	C. R. Hubbard	81.	J. M. Wyrick
41.	M. A. Janney	82.	C. S. Yust

EXTERNAL DISTRIBUTION

83. James H. Adair University of Florida Materials Science and Engineering 317 MAE Bldg. Gainesville, FL 32611-2066	91. Richard T. Alpaugh U.S. Department of Energy Advanced Propulsion Division CE-322, Forrestal Building Washington, DC 20585
84. Donald F. Adams University of Wyoming Mechanical Engineering Department P. O. Box 3295 Laramie, WY 82071	92. Joseph E. Amaral Instron Corporation Corporate Engineering Office 100 Royale Street Canton, MA 02021
85. Jalees Ahmad AdTech Systems Research, Inc. 1342 North Fairfield Road Dayton, OH 45432-2698	93. Edward M. Anderson Aluminum Company of America North American Industrial Chemicals Division P.O. Box 300 Bauxite, AR 72011
86. Yoshio Akimune NISSAN Motor Co., Ltd. Materials Research Laboratory 1 Natsushima-Cho Yokosuka 237 JAPAN AIR MAIL	94. Norman C. Anderson Ceradyne, Inc. Ceramic-to-Metal Division 3169 Redhill Avenue Costa Mesa, CA 92626
87. Mufit Akinc Iowa State University 322 Spedding Hall Ames, IA 50011	95. Don Anson Battelle Columbus Laboratories Thermal Power Systems 505 King Avenue Columbus, OH 43201-2693
88. Ilhan A. Aksay University of Washington Materials Science and Engineering Department, FB-10 Seattle, WA 98195	96. Thomas Arbanas G.B.C. Materials Corporation 580 Monastery Drive Latrobe, PA 15650-2698
89. R. G. Alexander BASE 26 Malvern Close Kettering Northants NN16 8JP UNITED KINGDOM AIR MAIL	97. Frank Armatiss 3M Company 3M Center Building 60-1N-01 St. Paul, MN 55144-1000
90. Richard L. Allor Ford Motor Company Material Systems Reliability Department 20000 Rotunda Drive P.O. Box 2053, Room S-2031 Dearborn, MI 48121-2053	98. Everett B. Arnold Detroit Diesel Corporation Mechanical Systems Technology 13400 Outer Drive, West Detroit, MI 48239-4001
	99. Richard M. Arons PA Consulting Group 279 Princeton Road Highstown, NJ 08550

100. Bertil Aronsson
Sandvik AB
S-12680
Stockholm Lerkrogsvagen 19
SWEDEN AIR MAIL
101. Dennis Assanis
University of Illinois
Department of Mechanical
Engineering
1206 W. Green Street
Urbana, IL 61801
102. William H. Atwell
Dow Corning Corporation
3901 South Saginaw Road
MS:540
Midland, MI 48686-0995
103. V. S. Avva
North Carolina A&T State
University
Department of Mechanical
Engineering
Greensboro, NC 27411
104. Patrick Badgley
Adiabatics, Inc.
3385 Commerce Drive
Columbus, IN 47201
105. Sunggi Baik
Pohang Institute of Science
& Technology
Department of Materials
Science and Engineering
P.O. Box 125
Pohang 790-600
KOREA AIR MAIL
106. John M. Bailey
Caterpillar, Inc.
Technical Center
Building L
P.O. Box 1875
Peoria, IL 61656-1875
107. Bob Baker
Ceradyne, Inc.
3169 Redhill Avenue
Costa Mesa, CA 92626
108. Frank Baker
Aluminum Company of America
Alcoa Technical Center
Alcoa Center, PA 15069
109. J. G. Baldoni
GTE Laboratories Inc.
40 Sylvan Road
Waltham, MA 02254
110. Clifford P. Ballard
Allied-Signal, Inc.
Ceramics Program
P.O. Box 1021
Morristown, NJ 07962-1021
111. M. Balu
Amoco Performance Products Inc.
4500 McGinnis Ferry Road
Alpharetta, GA 30202
112. B. P. Bandyopadhyay
Toyohashi University of Technology
School of Production Systems
Engineering
Tempaku-Cho Toyohashi 440
JAPAN AIR MAIL
113. P. M. Barnard
Ruston Gas Turbines Limited
Metallurgical Laboratory
P. O. Box 1
Lincoln LN2 5DJ
ENGLAND AIR MAIL
114. Harold N. Barr
Hittman Corporation
9190 Red Branch Road
Columbia, MD 21045
115. Renald D. Bartoe
Vesuvius McDanel
510 Ninth Avenue
Box 560
Beaver Falls, PA 15010-0560
116. Donald M. Bartos
Dow Corning Corporation
Advanced Ceramics Program
Midland, MI 48686-0995

117. David L. Baty
Babcock & Wilcox-LRC
P.O. Box 11165
Lynchburg, VA 24506-1165
118. Donald F. Baxter, Jr.
ASM International
Advanced Materials and
Processes
Materials Park, OH 44073-0002
119. M. Brad Beardsley
Caterpillar, Inc.
Advanced Materials Technology
Technical Center Bldg. E
P.O. Box 1875
Peoria, IL 61656-1875
120. Robert Beck
Teledyne CAE
Materials Engineering/Programs
1330 Laskey Road
P.O. Box 6971
Toledo, OH 43612
121. John C. Bell
Shell Research Limited
Thornton Research Centre
P.O. Box 1
Chester, Ch1 3SH
ENGLAND   AIR MAIL
122. Albert H. Bell, III
General Motors Technical Center
30200 Mound Road
Engineering Building/W3 Turbine
Warren, MI 48090-9010
123. M. Bentele
Xamag, Inc.
259 Melville Avenue
Fairfield, CT 06430
124. Larry D. Bentsen
BF Goodrich Company
R&D Center
9921 Brecksville Road
Brecksville, OH 44141
125. Joseph C. Bentz
ENCERATEC
2525 Sandcrest Drive
Columbus, IN 47203
126. Louis Beregszazi
Defiance Precision Products
P.O. Drawer 428
Defiance, OH 43512
127. Tom Bernecki
Northwestern University
BIRL
1801 Maple Avenue
Evanston, IL 60201-3135
128. Charles F. Bersch
Institute for Defense Analyses
1801 North Beauregard Street
Alexandria, VA 22311
129. Ram Bhatt
NASA Lewis Research Center
21000 Brookpark Road
Cleveland, OH 44135
130. Deane I. Biehler
Caterpillar, Inc.
Engineering and Research
Materials
Technical Center, Building E
P.O. Box 1875
Peoria, IL 61656-1875
131. John. W. Bjerklie
Consolidated Natural Gas
Service Co., Inc.
Research Department
CNG Tower
Pittsburgh, PA 15222-3199
132. William D. Bjorndahl
TRW, Inc.
One Space Park
Building 01, Room 2040
Redondo Beach, CA 90278
133. Keith A. Blakely
Advanced Refractory
Technologies, Inc.
699 Hertel Avenue
Buffalo, NY 14207
134. Edward G. Blanchard
Netzsch Inc.
119 Pickering Way
Exton, PA 19341

135. Keith Blandford
Boride Products, Inc.
2879 Aero Park Drive
Traverse City, MI 49684
136. Bruce Boardman
Deere and Company Technical
Center
3300 River Drive
Moline, IL 61265
137. Russell Bockstedt
Hoechst Celanese Corporation
150 JFK Parkway
Short Hills, NJ 07078
138. M. Boehmer
DLR German Aerospace Research
Establishment
Postfach 90 60 58
D-5000 Koln 90
GERMANY AIR MAIL
139. Lawrence P. Boesch
EER Systems Corp.
1593 Spring Hill Road
Vienna, VA 22182-2239
140. Donald H. Boone
Boone & Associates
2412 Cascade Drive
Walnut Creek, CA 94598-4313
141. Tom Booth
Allied-Signal Aerospace
Company
AiResearch Los Angeles
Division
2525 West 190th Street
Torrance, CA 90509-2960
142. Tibor Bornemisza
Sundstrand Power Systems
4400 Ruffin Road
San Diego, CA 92186-5757
143. J.A.M. Boulet
University of Tennessee
Department of Engineering
Science and Mechanics
310 Perkins Hall
Knoxville, TN 37996-2030
144. H. Kent Bowen
Massachusetts Institute of
Technology
77 Massachusetts Avenue
Room E40-434
Cambridge, MA 02139
145. Leslie J. Bowen
Materials Systems
53 Hillcrest-Road
Concord, MA 01742
146. Steven C. Boyce
Air Force Office of
Scientific Research
AFOSR/NA Bldg. 410
Bolling AFB DC 20332-6448
147. Gary L. Boyd
CEC
400 Howell Avenue, No. 4
Warland, WY 82401
148. Steve Bradley
UOP Research Center
50 East Algonquin Road
Des Plaines, IL 60017-6187
149. Michael C. Brands
Cummins Engine Company, Inc.
P.O. Box 3005
Mail Code 50179
Columbus, IN 47201
150. Raymond J. Bratton
Westinghouse Science and
Technology Center
1310 Beulah Road
Pittsburgh, PA 15235
151. John J. Brennan
United Technologies Corporation
Research Center
Silver Lane, MS:24
East Hartford, CT 06108
152. Jeff D. Bright
Ceramatec, Inc.
2425 South 900 West
Salt Lake City, UT 84108

153. Terrence K. Brog
Coors Ceramics Company
Corporate Development and
Technology
4545 McIntyre Street
Golden, CO 80403
154. Gunnar Broman
317 Fairlane Drive
Spartanburg, SC 29302
155. Al Brown
High-Tech Materials Alert
P.O. Box 882
Dayton, NJ 08810
156. Jesse Brown
Virginia Polytechnic Institute
and State University
Center for Advanced Ceramic
Materials
Blacksburg, VA 24061-0256
157. Sherman D. Brown
University of Illinois
Materials Science and
Engineering Department
105 South Goodwin Avenue
204 Ceramics Building
Urbana, IL 61801
158. S. L. Bruner
Ceramatec, Inc.
2425 South 900 West
Salt Lake City, UT 84119
159. Adolfo Brusaferrro
Keramont Corporation
4231 South Fremont Avenue
Tucson, AZ 85714
160. W. Bryzik
U.S. Army Tank Automotive
Command
R&D Center
Propulsion Systems Division
Warren, MI 48397-5000
161. S. T. Buljan
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
162. S. J. Burden
GTE Valenite
1711 Thunderbird
Troy, MI 48084
163. Curt V. Burkland
AMERCOM, Inc.
8928 Fullbright Avenue
Chatsworth, CA 91311
164. Bill Bustamante
AMERCOM, Inc.
8928 Fullbright Street
Chatsworth, CA 91311
165. Oral Buyukozturk
Massachusetts Institute of
Technology
77 Massachusetts Avenue
Room 1-280
Cambridge, MA 02139
166. David A. Caillet
Ethyl Corporation
451 Florida Street
Baton Rouge, LA 70801
167. Frederick J. Calnan
Heany Industries, Inc.
249 Briarwood Lane
P.O. Box 38
Scottsville, NY 14546
168. Roger Cannon
Rutgers University
Ceramics Department
P.O. Box 909
Piscataway, NJ 08855-0909
169. Scott Cannon
P.O. Box 567254
Atlanta, GA 30356
170. Harry W. Carpenter
19945 Acre Street
Northridge, CA 91324
171. David Carruthers
Kyocera Industrial Ceramics
Company
P.O. Box 2279
Vancouver, WA 98668-2279

172. Calvin H. Carter, Jr.
Cree Research, Inc.
2810 Meridian Parkway
Durham, NC 27713
173. J. David Casey
35 Atlantis Street
West Roxbury, MA 02132
174. Jere G. Castor
J. C. Enterprise
5078 North 83rd Street
Scottsdale, AZ 85250
175. James D. Cawley
Case Western Reserve University
Materials Science and
Engineering Department
Cleveland, OH 44106
176. Thomas C. Chadwick
Den-Mat Corporation
P.O. Box 1729
Santa Maria, CA 93456
177. Ronald H. Chand
Chand Kare Technical Ceramics
2 Coppage Drive
Worcester, MA 01603
178. Robert E. Chaney
EG&G Idaho, Inc.
Idaho National Engineering
Laboratory
P.O. Box 1625
Idaho Falls, ID 83415-3525
179. Frank C. Chang
U.S. Army Materials
Technology Laboratory
AMTL-EMM
405 Arsenal Street
Watertown, MA 02172
180. Robert M. Chapman
Allied-Signal Aerospace
Company
1530 Wilson Boulevard,
10th Floor
Arlington, VA 22209
181. William Chapman
Williams International
Corporation
2280 West Maple Road
Walled Lake, MI 48390-0200
182. Charlie Chen
LECO Corporation
P.O. Box 211688
Augusta, GA 30917
183. Albert A. Chesnes
U.S. Department of Energy
Transportation Technologies
CE-30, Forrestal Building,
6B-094
Washington, DC 20585
184. Kaiyin Chia
Carborundum Company
P.O. Box 832
Niagara Falls, NY 14302
185. Frank Childs
EG&G Idaho, Inc.
Idaho National Engineering
Laboratory
P.O. Box 1625
Idaho Falls, ID 83415-3527
186. William J. Chmura
Torrington Company
59 Field Street
Torrington, CT 06790-4942
187. Tsu-Wei Chou
University of Delaware
Center for Composite
Materials
201 Spencer Laboratory
Newark, DE 19716
188. R. J. Christopher
Ricardo Consulting Engineers
Bridge Works
Shoreham-By-Sea West Sussex
BN43 5FG
ENGLAND   AIR MAIL
189. Joel P. Clark
Massachusetts Institute of
Technology
Room 8-409
Cambridge, MA 02139

190. Giorgio Clarotti
Commission of the European
Communities
DGXII-C3, M075, 1-53;
200 Rue de la Loi
B-1049 Brussels
BELGIUM AIR MAIL
191. W. J. Clegg
ICI Advanced Materials
P.O. Box 11
The Heath, Runcorn Cheshire
WA7 4QE
ENGLAND AIR MAIL
192. Joseph Cleveland
GTE Products Corporation
Hawes Street
Towanda, PA 18848-0504
193. Gloria M. Collins
ASTM
1916 Race Street
Philadelphia, PA 19103
194. William C. Connors
Sundstrand Aviation Operations
Materials Science and
Engineering Department
4747 Harrison Avenue
P.O. Box 7002
Rockford, IL 61125-7002
195. John A. Coppola
Carborundum Company
P.O. Box 156
Niagara Falls, NY 14302
196. Normand D. Corbin
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
197. Douglas Corey
Allied-Signal Aerospace
Company
2525 West 190th Street
MS:T52
Torrance, CA 90504-6099
198. Keith P. Costello
Chand/Kare Technical Ceramics
2 Coppage Drive
Worcester, MA 01603-1252
199. Ed L. Courtright
Pacific Northwest
Laboratory
MS:K3-59
Richland, WA 99352
200. Anna Cox
Mitchell Market Reports
P.O. Box 23
Monmouth Gwent NP5 4YG
UNITED KINGDOM AIR MAIL
201. Thomas Coyle
Unocal Corporation
Unocal Science & Technology
Division
376 South Valencia Avenue
Brea, CA 92621
202. Art Cozens
Instron Corporation
3414 Snowden Avenue
Long Beach, CA 90808
203. Robert C. Craft
American Ceramic
Society, Inc.
757 Brooksedge Plaza Drive
Westerville, OH 43081
204. Mark Crawford
New Technology Week
4604 Monterey Drive
Annandale, VA 22003
205. Richard A. Cree
Markets & Products, Inc.
P.O. Box 14328
Columbus, OH 43214-0328
206. Les Crittenden
Vesuvius McDanel
Box 560
Beaver Falls, PA 15010

207. William J. Croft
U.S. Army Materials
Technology Laboratory
405 Arsenal Street
Watertown, MA 02172
208. M. J. Cronin
Mechanical Technology, Inc.
968 Albany-Shaker Road
Latham, NY 12110
209. Gary M. Crosbie
Ford Motor Company
1430 Culver Avenue
S-2079, SRL Building
Dearborn, MI 48121-4036
210. Floyd W. Crouse, Jr.
U.S. Department of Energy
Morgantown Energy
Technology Center
Collins Ferry Road
P.O. Box 880
Morgantown, WV 26505
211. John Cuccio
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
P.O. Box 5227, MS:1302-2Q
Phoenix, AZ 85010
212. Raymond Cutler
Ceramatec, Inc.
2425 South 900 West
Salt Lake City, UT 84119
213. Charles D'Angelo
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02154
214. Stephen C. Danforth
Rutgers University
Ceramic Engineering Department
P.O. Box 909
Piscataway, NJ 08855-0909
215. Sankar Das Gupta
Electrofuel Manufacturing
Co., Ltd.
9 Hanna Avenue
Toronto Ontario MGK-1W8
CANADA AIR MAIL
216. Charles Davis
Sverdrup Technology,
Inc., MSFC
620 Discovery Drive
Huntsville, AL 35806
217. Frank Davis
Allied Signal Aerospace Co.
7550 Lucerne Dr., # 203
Middleburg Heights, OH 44130
218. Robert F. Davis
North Carolina State
University
Materials Engineering
Department
229 Riddick Laboratory
P.O. Box 7907
Raleigh, NC 27695
219. Thomas DeAngelis
Carborundum Company
Niagara Falls R&D Center
P.O. Box 832
Niagara Falls, NY 14302
220. George DeBell
Ford Motor Company
Material Systems Reliability
Department
20000 Rotunda Drive
P.O. Box 2053, Room S-2023
Dearborn, MI 48121-2053
221. Michael DeLuca
AMP-AKZO
West Lane
Aquebogue, NY 11931
222. Gerald L. DePoorter
Colorado School of Mines
Metallurgical and Materials
Engineering Department
Golden, CO 80401

223. J. F. DeRidder
Omni Electro Motive, Inc.,
12 Seely Hill Road
Newfield, NY 14867
224. Nick C. Dellow
Materials Technology
Publications
40 Sotheron Road
Watford Herts WD1 2QA
UNITED KINGDOM AIR MAIL
225. L. R. Dharani
University of Missouri-Rolla
224 M.E.
Rolla, MO 65401
226. Douglas A. Dickerson
Union Carbide Specialty
Powders
1555 Main Street
Indianapolis, IN 46224
227. John Dodsworth
Vesuvius Research &
Development
Technical Ceramics Group
Box 560
Beaver Falls, PA 15010
228. B. Dogan
Institut fur Werkstofforschung
GKSS-Forschungszentrum
Geesthacht GmbH
Max-Planck-Strasse
D-2054 Geesthacht
GERMANY AIR MAIL
229. Jean-Marie Drapier
FN Moteurs S.A.
Material and Processing
B-4041 Milmort (Herstal)
BELGIUM AIR MAIL
230. Kenneth C. Dreitlein
United Technologies
Research Center
Silver Lane
East Hartford, CT 06108
231. Robin A.L. Drew
McGill University
Department of Mining and
Metallurgical Engineering
3450 University Street
Montreal Quebec H3A 2A7
CANADA AIR MAIL
232. Winston H. Duckworth
BCL
Columbus Division
505 King Avenue
Columbus, OH 43201-2693
233. Edmund M. Dunn
Texel Company
6 Third Street
Lexington, MA 02173
234. Bill Durako
Sundstrand Aviation Operations
Department 789-6
4747 Harrison Avenue
P.O. Box 7002
Rockford, IL 61125-7002
235. Ernest J. Duwell
212 Elm Street
Hudson, WI 54016
236. Chuck J. Dziedzic
Coors Ceramics Company
Structural Products Group
17750 West 32nd Avenue
Golden, CO 80401
237. Robert J. Eagan
Sandia National Laboratories
Engineered Materials &
Processes Center
Org 1700
P.O. Box 5800
Albuquerque, NM 87185-5800
238. Jeffrey Eagleson
Lanxide Corporation
1001 Connecticut Avenue, N.W.
Washington, DC 20036

239. Harry E. Eaton
United Technologies Corporation
Research Center
Silver Lane
East Hartford, CT 06108
240. Harvill C. Eaton
Louisiana State
University
Office of Research
and Economic Development
240 Thomas Boyd Hall
Baton Rouge, LA 70803
241. Christopher A. Ebel
Carborundum Company
Technology Division
P.O. Box 337
Niagara Falls, NY 14302
242. J. J. Eberhardt
U.S. Department of Energy
Office of Transportation
Materials
CE-34, Forrestal Building
Washington, DC 20585
243. Jim Edler
Eaton Corporation
26201 Northwestern
Highway
P.O. Box 766
Southfield, MI 48037
244. William A. Ellingson
Argonne National Laboratory
Materials Science & Technology
Division
9700 South Cass Avenue
Argonne, IL 60439
245. William S. Ellis
Machined Ceramics
629 N. Graham St.
N. Industrial Park
Bowling Green, KY 42101
246. Glen B. Engle
Nuclear & Aerospace Materials
Corporation
16716 Martincoit Road
Poway, CA 92064
247. Jeff Epstein
Ceramic Technologies, Inc.
2107 Jamara Lane
Houston, TX 77077
248. Kenneth A. Epstein
Dow Chemical U.S.A.
Ceramics and Advanced
Materials
800 Building
Midland, MI 48667
249. Art Erdemir
Argonne National Laboratory
Materials and Components
Technology Division
9700 South Cass Avenue
Argonne, IL 60439
250. E. M. Erwin
Lubrizol Corporation
1819 East 225th Street
Euclid, OH 44117
251. Kenji Esaki
Toyota Technical Center
U.S.A., Inc.
2000 Town Center, Suite 500
Southfield, MI 48075
252. Jose L. Escalante
Anglo-Mex-Tech. Inc.
3923 N.W. 24th Street
Miami, FL 33142
253. John N. Eustis
U.S. Department of Energy
Industrial Energy Efficiency
Division
CE-221, Forrestal Building
Washington, DC 20585
254. Robert C. Evans
NASA Lewis Research Center
Terrestrial Propulsion Office
21000 Brookpark Road, MS:86-6
Cleveland, OH 44135
255. W. L. Everitt
Kyocera International, Inc.
8611 Balboa Avenue
San Diego, CA 92123

256. Gordon Q. Evison
332 South Michigan Avenue
Suite 1730
Chicago, IL 60604
257. John W. Fairbanks
U.S. Department of Energy
Advanced Propulsion Division
CE-322, Forrestal Building
Washington, DC 20585
258. Tim Fawcett
Dow Chemical Company
Central Research, Advanced
Ceramics Laboratory
1776 Building
Midland, MI 48674
259. Robert W. Fawley
Sundstrand Power Systems
Division of Sundstrand
Corporation
4400 Ruffin Road
P.O. Box 85757
San Diego, CA 92186-5757
260. John J. Fedorchak
GTE Products Corporation
Hawes Street
Towanda, PA 18848-0504
261. Jeff T. Fenton
Vista Chemical Company
900 Threadneedle
Houston, TX 77079
262. Larry Ferrell
Babcock & Wilcox
Old Forest Road
Lynchburg, VA 24505
263. Raymond R. Fessler
BIRL
Industrial Research Lab
1801 Maple Avenue
Evanston, IL 60201
264. Michelle Finch
E. I. DuPont de Nemours &
Company, Inc.
Experimental Station
Information Center E302/301
Wilmington, DE 19898
265. Arthur D. Fine
United Technologies Corporation
Pratt & Whitney Aircraft
400 Main Street
MS:163-10
East Hartford, CT 06108
266. Ross F. Firestone
Ross Firestone Company
188 Mary Street
Winnetka, IL 60093-1520
267. Sharon L. Fletcher
Arthur D. Little, Inc.
15 Acorn Park
Cambridge, MA 02140-2390
268. Thomas F. Foltz
Textron Specialty Materials
2 Industrial Avenue
Lowell, MA 01851
269. Renee G. Ford
Materials and Processing Report
P.O. Box 72
Harrison, NY 10528
270. John Formica
Supermaterials
2020 Lakeside Avenue
Cleveland, OH 44114
271. Jennifer M. Fox
Dyson Refractories Limited
R&D Laboratory
Owler Bar
Sheffield S17 3BJ
UNITED KINGDOM   AIR MAIL
272. Edwin Frame
Southwest Research Institute
Division 2
P.O. Drawer 28510
San Antonio, TX 78284
273. Armanet Francois
French Scientific Mission
4101 Reservoir Road, N.W.
Washington DC 20007-2176
274. R. G. Frank
Technology Assessment Group
10793 Bentley Pass Lane
Loveland, OH 45140

275. David J. Franus
Forecast International
22 Commerce Road
Newtown, CT 06470
276. Marc R. Freedman
NASA Lewis Research Center
21000 Brookpark Road
MS:49-3
Cleveland, OH 44135
277. Douglas Freitag
LTV Missiles Division
P.O. Box 650003
MS:WT-21
Dallas, TX 75265
278. Brian R.T. Frost
Argonne National Laboratory
9700 South Cass Avenue
Building 900
Argonne, IL 60439
279. Lawrence R. Frost
Instron Corporation
100 Royall Street
Canton, MA 02021
280. George A. Fryburg
Norton/TRW Ceramics
7A-4 Raymond Avenue
Salem, NH 03079
281. Xiren Fu
Shanghai Institute of Ceramics
Chinese Academy of Sciences
1295 Ding-xi Road
Shanghai 200050
CHINA AIR MAIL
282. John Gahimer
P.O. Box 1302
Dublin, OH 43017
283. J. P. Gallagher
University of Dayton Research
Institute
300 College Park, JPC-250
Dayton, OH 45469-0120
284. Tom Garritano
University of Tennessee
Science Alliance
101 South College
Knoxville, TN 37996-1328
285. Joy A. Garwood
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
286. H. Maury Gatewood
Reynolds Metals Company
Corporate R&D
Fourth and Canal Streets
P.O. Box 27003
Richmond, VA 23261
287. L. J. Gauckler
ETH-Zurich
Sonneggstrasse 5
CH-8092 Zurich 8092
SWITZERLAND AIR MAIL
288. Peter A. Gaydos
Battelle Columbus Laboratories
505 King Avenue
Columbus, OH 43201
289. George E. Gazza
U.S. Army Materials
Technology Laboratory
Ceramics Research Division
405 Arsenal Street
Watertown, MA 02172-0001
290. D. Gerster
CEA-DCOM
33 Rue De La Federation
Paris 75015
FRANCE AIR MAIL
291. John Ghinazzi
Coors Technical Ceramics
Company
1100 Commerce Park Drive
Oak Ridge, TN 37830

292. Robert Giddings
General Electric Company
Research Laboratory
P.O. Box 8
Schenectady, NY 12301
293. A. M. Glaeser
University of California
Materials Science and Mineral
Engineering
Lawrence Berkeley Laboratory
Hearst Mining Building
Berkeley, CA 94720
294. Paul Glance
Concept Analysis
R&D
950 Stephenson Highway
Dupont Automotive Development
Building
Troy, MI 48007-7013
295. Joseph W. Glatz
Naval Air Propulsion Center
Systems Engineering Division
P.O. Box 7176, PE24
Trenton, NJ 08628
296. W. M. Goldberger
Superior Graphite Company
R&D
2175 East Broad Street
Columbus, OH 43209
297. Allan E. Goldman
U.S. Graphite, Inc.
907 West Outer Drive
Oak Ridge, TN 37830
298. Stephen T. Gonczy
Allied Signal Research
P.O. Box 5016
Des Plaines, IL 60017
299. Jeffrey M. Gonzales
GTE Products Corporation
Hawes Street
Towanda, PA 18848-0504
300. Robert J. Gottschall
U.S. Department of Energy
ER-131, MS:G-236
Washington, DC 20545
301. Earl Graham
Cleveland State University
Department of Chemical
Engineering
Euclid Avenue at
East 24th Street
Cleveland, OH 44115
302. William A. Graham
Lanxide Corporation
P.O. Box 6077
Newark, DE 19714-6077
303. Robert E. Green, Jr.
Johns Hopkins University
Materials Science and
Engineering Department
Baltimore, MD 21218
304. Lance Groseclose
General Motors Corporation
Allison Gas Turbine Division
P.O. Box 420, MS:W-5
Indianapolis, IN 46206
305. Mark F. Gruninger
Union Carbide Corporation
Specialty Powder Business
1555 Main Street
Indianapolis, IN 46224
306. Ernst Gugel
Cremer Forschungsinstitut
GmbH&Co.KG
Oeslauer Strasse 35
D-8633 Roedental 8633
GERMANY AIR MAIL
307. Donald L. Guile
Corning Glass Works
SP-DV-1-9
Corning, NY 14831
308. Bimleshwar P. Gupta
Solar Energy Research
Institute
Mechanical and Industrial
Technology Division
1617 Cole Boulevard
Golden, CO 80401

309. John P. Gyekenyesi
NASA Lewis Research Center
21000 Brookpark Road, MS:6-1
Cleveland, OH 44135
310. Nabil S. Hakim
Detroit Diesel Corporation
13400 West Outer Drive
Detroit, MI 48239
311. Philip J. Haley
General Motors Corporation
Vehicular Engineering
P.O. Box 420, MS:T12A
Indianapolis, IN 46236
312. Judith Hall
Fiber Materials, Inc.
Biddeford Industrial Park
5 Morin Street
Biddeford, ME 04005
313. Y. Harada
IIT Research Institute
Nometallic Materials and
Composites
10 West 35th Street
Chicago, IL 60616
314. R. A. Harmon
25 Schalren Drive
Latham, NY 12110
315. Amy Harmon-Barrett
Martin Marietta Laboratories
1450 South Rolling Road
Baltimore, MD 21227
316. Norman H. Harris
Hughes Aircraft Company
P.O. Box 800520
Saugus, CA 91380-0520
317. Alan Hart
Dow Chemical Company
Advanced Ceramics Laboratory
1776 Building
Midland, MI 48674
318. Pat E. Hart
Battelle Pacific Northwest
Laboratories
Ceramics and Polymers
Development Section
P.O. Box 999
Richland, WA 99352
319. Stephen D. Hartline
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
320. Michael H. Haselkorn
Caterpillar, Inc.
Engineering Research Materials
Technical Center, Building E
P.O. Box 1875
Peoria, IL 61656-1875
321. N. B. Havewala
Corning, Inc.
SP-PR-11
Corning, NY 14831
322. John Haygarth
Teledyne WAA Chang Albany
P.O. Box 460
Albany, OR 97321
323. Norman L. Hecht
University of Dayton Research
Institute
300 College Park
Dayton, OH 45469-0172
324. Peter W. Heitman
General Motors Corporation
Allison Gas Turbine Division
P.O. Box 420, MS:W-5
Indianapolis, IN 46206-0420
325. Robert W. Hendricks
Virginia Polytechnic Institute
and State University
Materials Engineering
Department
210 Holden Hall
Blacksburg, VA 24061-0237

326. Wynne Henley
Hertel Cutting Technologies, Inc.
1000 Clearview Court
Oak Ridge, TN 37830
327. Thomas L. Henson
GTE Products Corporation
Chemical & Metallurgical
Division
Hawes Street
Towanda, PA 18848
328. Thomas P. Herbell
NASA Lewis Research Center
21000 Brookpark Road
MS:49-3
Cleveland, OH 44135
329. Marlene Heroux
Rolls-Royce, Inc.
2849 Paces Ferry Road
Suite 450
Atlanta, GA 30339-3769
330. Robert L. Hershey
Science Management Corporation
1255 New Hampshire Ave., N.W.
Suite 1033
Washington, DC 20036
331. Hendrik Heystek
Bureau of Mines
Tuscaloosa Research Center
P.O. Box L
University, AL 35486
332. Wallace C. Higgins
Norwal Unlimited
P.O. Box 1258
Alfred, NY 14802
333. Robert V. Hillery
GE Aircraft Engines
One Neumann Way, M.D. H85
Cincinnati, OH 45215
334. Arthur Hindman
Instron Corporation
100 Royall Street
Canton, MA 02021
335. Jon Hines
American Ceramic Society, Inc.
757 Brooksedge Plaza Drive
Westerville, OH 43081-6136
336. Hans Erich Hintermann
CSEM
Materials and Micromechanics
Division
Rue Breguet-2
Neuchatel 2000
SWITZERLAND AIR MAIL
337. Shinichi Hirano
Mazda R&D of North
America, Inc.
1203 Woodridge Avenue
Ann Arbor, MI 48105
338. Tommy Hiraoka
NGK Locke, Inc.
1000 Town Center
Southfield, MI 48075
339. John M. Hobday
U.S. Department of Energy
Morgantown Energy Technology
Center
Collins Ferry Road
P.O. Box 880
Morgantown, WV 26507
340. Greg Hoenes
Vista Chemical Company
900 Threadneedle
P.O. Box 19029
Houston, TX 77079-2990
341. Clarence Hoenig
Lawrence Livermore National
Laboratory
P.O. Box 808, Mail Code L-369
Livermore, CA 94550
342. Thomas Hollstein
Fraunhofer-Institut fur
Werkstoffmechanik IWM
Wohlerstrabe 11
D-7800 Freiburg
GERMANY AIR MAIL

343. Richard Holt
National Research Council
of Canada
Structures and Materials
Laboratory
Ottawa Ontario K1A 0R6
CANADA AIR MAIL
344. Joseph Homeny
University of Illinois
Department of Materials Science
and Engineering
105 South Goodwin Avenue
Ceramics Building
Urbana, IL 61801
345. A. T. Hopper
Battelle Columbus
Laboratories
Metals and Ceramics Department
505 King Avenue
Columbus, OH 43201-2693
346. Michael Horgan
Materials Engineering Magazine
1100 Superior Avenue
Cleveland, OH 44114
347. Woodie Howe
Coors Technical Ceramics
Company
1100 Commerce Park Drive
Oak Ridge, TN 37830
348. Stephen M. Hsu
National Institute of
Standards and Technology
Gaithersburg, MD 20899
349. Hann S. Huang
Argonne National Laboratory
9700 South Cass Avenue
Argonne, IL 60439-4815
350. Gene Huber
Precision Ferrites & Ceramics
5576 Corporate Drive
Cypress, CA 90630
351. M. L. Huckabee
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
352. Harold A. Huckins
Princeton Advanced
Technology, Inc.
56 Finley Road
Princeton, NJ 08540
353. Fred R. Huettig
Advanced Magnetics, Inc.
45 Corey Lane
Mendham, NJ- 07945
354. Bill Huffman
Zircar
110 North Main Street
Florida, NY 10921
355. Brian K. Humphrey
Lubrizol Petroleum
Chemicals Co.
3000 Town Center, Suite 1340
Southfield, MI 48075-1201
356. Robert M. Humrick
Dylon Ceramic Technologies
3100 Edgehill Road
Cleveland Heights, OH 44118
357. Lorretta Inglehart
National Science Foundation
Division of Materials Research
1800 "G" Street, N.W.,
Room 408
Washington, DC 20550
358. Michael S. Inoue
Kyocera International, Inc.
KII Library
8611 Balboa Avenue
San Diego, CA 92123-1580
359. Osama Jadaan
University of Wisconsin-
Platteville
General Engineering Division
1 University Plaza
Platteville, WI 53818
360. Curtis A. Johnson
General Electric Company
Corporate R&D
Room MB-187
P.O. Box 8
Schenectady, NY 12301

361. Sylvia Johnson
SRI International
333 Ravenswood Avenue
Menlo Park, CA 94025
362. Thomas A. Johnson
Lanxide Corporation
1300 Marrows Road
P.O. Box 6077
Newark, DE 19714-6077
363. W. S. Johnson
Indiana University
One City Centre, Suite 200
Bloomington, IN 47405
364. Jill E. Jonkouski
U.S. Department of Energy
9800 South Cass Avenue
Argonne, IL 60439-4899
365. L. A. Joo
Great Lakes Research
Corporation
P.O. Box 1031
Elizabethton, TN 37643
366. A. D. Joseph
SPX Corporation
700 Terrace Point
Muskegon, MI 49443
367. Adam Jostsons
Australian Nuclear Science &
Technology Organization
Lucas Heights Research
Laboratories
New Illawarra Road
Lucas Heights New South Wales
AUSTRALIA AIR MAIL
368. Matthew K. Juneau
Ethyl Corporation
451 Florida Street
Baton Rouge, LA 70801
369. Hartmut Kainer
Didier-Werke AG
Anlagentechnik Wiesbaden
Abraham-Lincoln-Str. 16
D-62 Wiesbaden
GERMANY AIR MAIL
370. Tom Kalamasz
Norton/TRW Ceramics
7A-4 Raymond Avenue
Salem, NH 03079
371. Lyle R. Kallenbach
Phillips Petroleum Company
R&D
Mail Drop:123AL
Bartlesville, OK 74004
372. Nick Kamiya
Kyocera Industrial Ceramics
Corporation
2700 River Road
Des Plaines, IL 60018
373. Roy Kamo
Adiabatics, Inc.
3385 Commerce Park Drive
Columbus, IN 47201
374. S. Kang
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
375. Chih-Chun Kao
Industrial Technology Research
Institute
Materials Research
Laboratories
195 Chung-Hsing Road, Sec. 4
Chutung Hsinchu 31015 R.O.C.
TAIWAN AIR MAIL
376. Keith R. Karasek
Allied-Signal, Inc.
Engineered Materials Research
Center
50 East Algonquin Road
P.O. Box 5016
Des Plaines, IL 60017-5016
377. Robert E. Kassel
Ceradyne, Inc.
3169 Redhill Avenue
Costa Mesa, CA 92626
378. Allan Katz
Wright Laboratory
Metals and Ceramics Division
WL/MLLM
Wright-Patterson AFB, OH 45433

379. R. Nathan Katz
Worcester Polytechnic
Institute
Dept. of Mechanical
Engineering
100 Institute Road
Worcester, MA 01609
380. Ted Kawaguchi
Tokai Carbon America, Inc.
375 Park Avenue, Suite 3802
New York, NY 10152
381. Noritsugu Kawashima
TOSHIBA Corporation
Mechanical Engineering
Laboratory
4-1 Ukishima-Cho
Kawasaki-Ku Kawasaki 210
JAPAN AIR MAIL
382. Lisa Kempfer
Penton Publishing
Materials Engineering
1100 Superior Avenue
Cleveland, OH 44114-2543
383. Frederick L. Kennard, III
General Motors Corporation
AC Rochester
Department 32-24, EB
1300 North Dort Highway
Flint, MI 48556
384. David O. Kennedy
Lester B. Knight Cast
Metals Inc.
549 West Randolph Street
Chicago, IL 60661
385. George Keros
Photon Physics
3175 Penobscot Building
Detroit, MI 48226
386. Pramod K. Khandelwal
General Motors Corporation
Allison Gas Turbine
Division
P.O. Box 420, MS:W05
Indianapolis, IN 46206
387. Jim R. Kidwell
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
P.O. Box 5227
Phoenix, AZ 85010
388. Han J. Kim
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
389. Shin Kim
Korea Institute of Machinery
& Metals
66 Sangnam-dong, Changwon
Kyungnam 641-010
KOREA AIR MAIL
390. W. C. King
Mack Truck, Z-41
1999 Pennsylvania Avenue
Hagerstown, MD 21740
391. Carol Kirkpatrick
MSE, Inc.
CDIF Technical Library
P.O. Box 3767
Butte, MT 59702
392. Tony Kirn
Caterpillar, Inc.
Defense Products Department, JB7
Peoria, IL 61629
393. James D. Kiser
NASA Lewis Research Center
21000 Brookpark Road, MS:49-3
Cleveland, OH 44135
394. Max Klein
Gas Research Institute
Thermodynamics
8600 West Bryn Mawr Avenue
Chicago, IL 60631
395. Richard N. Kleiner
Coors Ceramics Company
4545 McIntyre Street
Golden, CO 80403

396. Stanley J. Klima
NASA Lewis Research Center
21000 Brookpark Road
MS:6-1
Cleveland, OH 44135
397. Chris E. Knapp
Norton Advanced Ceramics
of Canada Ltd.
8001 Daly Street
Niagara Falls, Ontario L2G 6S2
CANADA AIR MAIL
398. Albert S. Kobayashi
University of Washington
Mechanical Engineering
Department
MS:FU10
Seattle, WA 98195
399. Shigeki Kobayashi
Toyota Central Research
Labs, Inc.
Nagakute Aichi 480-11
JAPAN AIR MAIL
400. Richard A. Kole
Z-Tech Corporation
8 Dow Road
Bow, NH 03304
401. E. Kostiner
University of Connecticut
Chemistry Department, U-60
Storrs, CT 06269-3060
402. Kenneth A. Kovaly
Technical Insights, Inc.
P.O. Box 1304
Fort Lee, NJ 07024-9967
403. Ralph G. Kraft
Spraying Systems Company
North Avenue at Schmale Road
Wheaton, IL 60189-7900
404. Saunders B. Kramer
U.S. Department of Energy
Advanced Propulsion Division
CE-322, Forrestal Building
Washington, DC 20585
405. Arthur Kranish
Trends Publishing, Inc.
1079 National Press Building
Washington, DC 20045
406. A. S. Krieger
Radiation Science, Inc.
P.O. Box 293
Belmont, MA 02178
407. Pieter Krijgsman
Ceramic Design International
Holding B.V.
P.O. Box 68
Hattem 8050-AB
THE NETHERLANDS AIR MAIL
408. Waltraud M. Kriven
University of Illinois
Materials Science and
Engineering Department
105 South Goodwin Avenue
Urbana, IL 61801
409. Edward J. Kubel, Jr.
ASM International Advanced
Materials & Processes
Materials Park, OH 44073
410. Dave Kupperman
Argonne National Laboratory
9700 South Cass Avenue
Argonne, IL 60439
411. Oh-Hun Kwon
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
412. W. J. Lackey
Georgia Institute of Technology
Materials Science and
Technology
Atlanta, GA 30332
413. Jai Lala
Tenmat Ltd.
40 Somers Road
Rugby Warwickshire CV22 7DH
ENGLAND AIR MAIL

414. Hari S. Lamba
General Motors Corporation
Electro-Motive Division
9301 West 55th Street
LaGrange, IL 60525
415. Richard L. Landingham
Lawrence Livermore National
Laboratory
Ceramics, Corrosion, and
Thermochemistry
P.O. Box 808, L-369
Livermore, CA 94550
416. Charles J. Landry
Chand Kare Technical Ceramics
712 Flat Hill Road
Lumburg, MA 01462
417. Manfred W. Langer
Volkswagen AG
Material Technology
3180 Wolfsburg 1
GERMANY AIR MAIL
418. James Lankford
Southwest Research Institute
Department of Materials
Sciences
6220 Culebra Road
San Antonio, TX 78228-0510
419. Stanley B. Lasday
Business News Publishing Co.
Manor Oak One
1910 Cochran Road, Suite 630
Pittsburgh, PA 15220
420. Mark S. Laser
Solar Turbines, Inc.
2211 Erie Street
San Diego, CA 92110
421. S. K. Lau
Carborundum Company
Technology Division
P.O. Box 832, B-100
Niagara Falls, NY 14302
422. Edward A. Lauder
Advanced Composite Materials
Corporation
1525 South Buncombe Road
Greer, SC 29651-9208
423. J. Lawrence Lauderdale
Babcock & Wilcox
Contract Research Division
1850 "K" Street, Suite 950
Washington, DC 20006
424. Harry A. Lawler
Carborundum Company
Technology Division
P.O. Box 832
Niagara Falls, NY 14302
425. Jean F. LeCostaouec
Textron Speciality Materials
2 Industrial Avenue
Lowell, MA 01851
426. Benson P. Lee
Interscience, Inc.
9718 Lake Shore Boulevard
Cleveland, OH 44108
427. Burtrand I. Lee
Clemson University
Department of Ceramic
Engineering
Olin Hall
Clemson, SC 29634-0907
428. June-Gunn Lee
KIST
Structural Ceramic Lab
P.O. Box 131, Cheong-Ryang
Seoul 130-650
KOREA AIR MAIL
429. Ran-Rong Lee
Ceramics Process Systems
Corporation
155 Fortune Boulevard
Milford, MA 01757
430. Stan Levine
NASA Lewis Research Center
21000 Brookpark Road
MS:49-3
Cleveland, OH 44135
431. Alan V. Levy
Lawrence Berkeley Laboratory
One Cyclotron Road, MS:62-203
Berkeley, CA 94720

432. Ai-Kang Li
Materials Research
Laboratories, ITRI
195-5 Chung-Hsing Road, Sec. 4
Chutung Hsinchu 31015 R.O.C.
TAIWAN AIR MAIL
433. Winston W. Liang
Heng Kong Industrial
Technology Centre Co. Ltd.
78 Tat Chee Avenue
4/F, HKPC Building
Howloon
HONG KONG AIR MAIL
434. Robert Licht
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
435. E. Lilley
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
436. Laura J. Lindberg
Allied-Signal Aerospace
Company
Garrett Fluid Systems Division
1300 West Warner
MS: 93-901-1207-4TT
P.O. Box 22200
Tempe, AZ 85284-2200
437. Leonard C. Lindgren
General Motors Corporation
Allison Gas Turbine Division
P.O. Box 420, Speed Code:T-20A
Indianapolis, IN 46206-0420
438. Hans A. Lindner
Cremer Forschungsinstitut
GmbH&Co.KG
Oeslauer Strasse 35
D-8633 Rodental 8866
GERMANY AIR MAIL
439. Ronald E. Loehman
Sandia National Laboratories
Chemistry & Ceramics
Department 1840
P.O. Box 5800
Albuquerque, NM 87185
440. Jeffrey C. Logas
Winona State University
Composite Materials
Engineering
115 Pasteur Hall
Winona, MN 55987
441. Bill Long
Babcock & Wilcox
P.O. Box 11165
Lynchburg, VA 24506
442. William D. Long
Wacker Chemicals (USA), Inc.
ESK Engineered Ceramics
50 Locust Avenue
New Canaan, CT 06840
443. L. A. Lott
EG&G Idaho, Inc.
Idaho National Engineering
Laboratory
P.O. Box 1625
Idaho Falls, ID 83415-2209
444. Raouf O. Loutfy
MER Corporation
7960 South Kolb Road
Tucson, AZ 85706
445. Gordon R. Love
Aluminum Company of America
Alcoa Technical Center
Alcoa Center, PA 15069
446. Lydia Luckevich
Ortech International
2395 Speakman Drive
Mississauga Ontario L5K 1B3
CANADA AIR MAIL

447. James W. MacBeth
Carborundum Company
Structural Ceramics Division
P.O. Box 1054
Niagara Falls, NY 14302
448. H. MacLaren
General Electric Company
Thomson Laboratory, Materials
Engineering 36807
1000 Western Avenue
Lynn, MA 01910
449. George Maczura
Aluminum Company of America
Industrial Chemicals Division
670 One Allegheny Square
Pittsburgh, PA 15212
450. David Maginnis
Tinker AFB
OC-ALC/LIIRE
Tinker AFB OK 73145-5989
451. Frank Maginnis
Aspen Research, Inc.
220 Industrial Boulevard
Moore, OK 73160
452. Tai-il Mah
Universal Energy Systems, Inc.
Ceramics and Composites
Research
4401 Dayton-Xenia Road
Dayton, OH 45432
453. Kenneth M. Maillar
Barbour Stockwell Company
83 Linskey Way
Cambridge, MA 02142
454. Lorenzo Majno
Instron Corporation
100 Royall Street
Canton, MA 02021
455. S. G. Malghan
National Institute of Standards
and Technology
I-270 & Clopper Road
Gaithersburg, MD 20899
456. Lars Malmrup
United Turbine AB
Box 13027
Malmo S-200 44
SWEDEN AIR MAIL
457. John Mangels
Ceradyne, Inc.
3169 Redhill Avenue
Costa Mesa, CA 92626
458. Russell V. Mann
Matec Applied Sciences, Inc.
75 South Street
Hopkinton, MA 01748
459. William R. Manning
Champion Aviation Products
Division
Old Norris Road
P.O. Box 686
Liberty, SC 29657
460. Ken Marnoch
Amercom, Inc.
8928 Fullbright Avenue
Chatsworth, CA 91311
461. Robert A. Marra
Aluminum Company of America
Alcoa Technical Center
Advanced Ceramics Center - E
Alcoa Center, PA 15069
462. Chauncey L. Martin
3M Company
3M Center, Building 60-1N-01
St. Paul, MN 55144
463. Steven C. Martin
Advanced Refractory
Technologies, Inc.
699 Hertel Avenue
Buffalo, NY 14207
464. Kelly J. Mather
Williams International
Corporation
2280 West Maple Road
P.O. Box 200
Walled Lake, MI 48088

465. James P. Mathers
3M Company
3M Center
Building 201-3M-06
St. Paul, MN 55144
466. Marshall Mayer
Instron Corporation
3815 Presidential Parkway,
Suite 100
Atlanta, GA 30340
467. Ron Mayville
Arthur D. Little, Inc.
15-163 Acorn Park
Cambridge, MA 02140
468. F. N. Mazadarany
General Electric Company
Research Laboratory
Building K-1, Room MB-159
P.O. Box 8
Schenectady, NY 12301
469. James W. McCauley
Alfred University
NYS College of Ceramics
Binns-Merrill Hall
Alfred, NY 14802
470. Carolyn McCormick
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
Bldg. 1303-206
P.O. Box 5227, MS:9317-2
Phoenix, AZ 85010
471. Louis R. McCreight
2763 San Ramon Drive
Rancho Palos Verdes, CA 90274
472. Colin F. McDonald
McDonald Thermal Engineering
1730 Castellana Road
La Jolla, CA 92037
473. B. J. McEntire
Norton Company, TRW Ceramics
Goddard Road
Northboro, MA 01532-1545
474. Chuck McFadden
Coors Ceramics Company
600 9th Street
Golden CO 80401
475. Henry McFadden
Magnetic Bearings, Inc.
Engineering Library
609 Rock Road
Radford, VA- 24141
476. Thomas D. McGee
Iowa State University
Materials Science and
Engineering Department
110 Engineering Annex
Ames, IA 50011
477. Carol McGill
Corning Inc.
Sullivan Park, FR-02-08
Corning, NY 14831
478. T. C. McLaren
Cameron Forged Products
Company
P.O. Box 1212
Houston, TX 77251-1212
479. James McLaughlin
Sundstrand Power Systems
4400 Ruffin Road
P.O. Box 85757
San Diego, CA 92186-5757
480. Arthur F. McLean
6225 North Camino Almonte
Tucson, AZ 85718
481. Matt McMonigle
U.S. Department of Energy
Improved Energy Productivity
Division
Forrestal Building,
CE-231
Washington, DC 20585
482. Dennis McMurtry
EG&G Idaho, Inc.
Idaho National Engineering
Laboratory
P.O. Box 1625
Idaho Falls, ID 83415

483. D. B. Meadowcroft
National Power Technology
and Environmental Centre
Kelvin Avenue
Leatherhead Surrey
KT22 7SE
ENGLAND AIR MAIL
484. Jo Meglen
11004 Birdfoot Court
Reston, VA 22091
485. Pankaj K. Mehrotra
Kennametal, Inc.
P.O. Box 639
Greensburg, PA 15601
486. Joseph J. Meindl
Reynolds International, Inc.
6603 West Broad Street
P.O. Box 27002
Richmond, VA 23261-7003
487. Michael D. Meiser
Allied-Signal Aerospace Company
Garrett Ceramic Components
Division
19800 South Van Ness Avenue
Torrance, CA 90509
488. George Messenger
National Research Council of
Canada
Engine Laboratory
Building M-7
Ottawa Ontario K1A 0R6
CANADA AIR MAIL
489. D. Messier
U.S. Army Materials Technology
Laboratory
SLCMT-EMC
405 Arsenal Street
Watertown, MA 02172-0001
490. Gary L. Messing
Pennsylvania State University
Ceramic Science and Engineering
Department
119 Steidle Building
University Park, PA 16802
491. Arthur G. Metcalfe
Arthur G. Metcalfe and
Associates, Inc.
2108 East 24th Street
National City, CA 91950
492. R. Metselaar
Eindhoven University
Centre for Technical Ceramics
P.O. Box 513
Eindhoven 5600 MB
THE NETHERLANDS AIR MAIL
493. Nancy S. Meyers
U.S. Department of Energy
Transportation Technologies
CE-30, Forrestal Building
6B-094
Washington, DC 20585
494. David J. Michael
Harbison-Walker Refractories
Company
P.O. Box 98037
Pittsburgh, PA 15227
495. Ken Michaels
Chrysler Motors Corporation
Ceramics Development
Metallurgical Processes
P.O. Box 1118, CIMS:418-17-09
Detroit, MI 48288
496. Bernd Michel
Institute of Mechanics
Fracture and Micromechanics
Department
P.O. Box 408
D-9010 Chemnitz
GERMANY AIR MAIL
497. David E. Miles
Commission of the European
Communities
rue de la Loi, 200
B-1049 Brussels
BELGIUM AIR MAIL
498. John V. Milewski
Superkinetics, Inc.
P.O. Box 8029
Santa Fe, NM 87504

499. Carl E. Miller
AC Rochester
1300 North Dort Highway,
MS:32-31
Engineering Building B
Flint, MI 48556
500. Mike Miller
McGraw-Hill Aviation Week
Performance Materials
1156 15th Street, N.W.
Washington, DC 20005
501. Charles W. Miller, Jr.
Centorr Furnaces/Vacuum
Industries
542 Amherst Street
Nashua, NH 03063
502. R. Mininni
Enichem America
2000 Cornwall Road
Monmouth Junction, NJ 08852
503. Michele V. Mitchell
Allied-Signal Aerospace
Company
Garrett Ceramic Components
Division
19800 South Van Ness Avenue
Torrance, CA 90501-1149
504. Howard Mizuhara
GTE - WESGO
477 Harbor Boulevard
Belmont, CA 94002
505. Helen Moeller
Babcock & Wilcox
P.O. Box 11165
Lynchburg, VA 24506-1165
506. Francois R. Mollard
Metalworking Technology, Inc.
1450 Scalp Avenue
Johnstown, PA 15904
507. Phil Mooney
Panametrics
NDE Division
221 Crescent Street
Waltham, MA 02254
508. Thomas Morel
Ricardo North America
645 Blackhawk Drive
Westmont, IL 60559
509. Geoffrey P. Morris
3M Company
3M Traffic Control Materials
Division
Bldg. 209-BW-10, 3M Center
St. Paul, MN 55144-1000
510. Jay A. Morrison
Rolls-Royce, Inc.
Engineering and Information
Center, Overlook 1
2849 Paces Ferry Road,
Suite 450
Atlanta, GA 30339-3769
511. Joel P. Moskowitz
Ceradyne, Inc.
3169 Redhill Avenue
Costa Mesa, CA 92626
512. Brij Moudgil
University of Florida
Material Science and
Engineering
Gainesville, FL 32611
513. Christoph J. Mueller
Sprehsaal Publishing
Group
P.O. Box 2962, Mauer 2
D-8630 Coburg
GERMANY AIR MAIL
514. Thomas W. Mullan
Vapor Technologies Inc.
345 Route 17 South
Upper Saddle River, NJ 07458
515. M. K. Murthy
MKM Consultants International
10 Avoca Avenue, Unit 1906
Toronto Ontario M4T 2B7
CANADA AIR MAIL
516. Solomon Musikant
TransCon Technologies, Inc.
Materials Science & Engineering
1508 Waynesboro Road
Paoli, PA 19301

517. David L. Mustoe
Custom Technical Ceramics
8041 West I-70 Service Road,
Unit 6
Arvada, CO 80002
518. Curtis V. Nakaishi
U.S. Department of Energy
Morgantown Energy Technology
Center
Collins Ferry Road
P.O. Box 880
Morgantown, WV 26507-0880
519. Yoshio Nakamura
Faicera Research Institute
2-5-8 Hiyakunin-cho Shinjuku-Ko
Tokyo
JAPAN   AIR MAIL
520. K. S. Narasimhan
Hoeganaes Corporation
River Road
Riverton, NJ 08077
521. Samuel Natanson
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
522. Robert Naum
Applied Resources, Inc.
P.O. Box 241
Pittsford, NY 14534
523. Malcolm Naylor
Cummins Engine Company, Inc.
P.O. Box 3005, Mail Code 50183
Columbus, IN 47202-3005
524. Jeffrey Neil
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
525. Fred A. Nichols
Argonne National Laboratory
9700 South Cass Avenue
MCT - Building 212
Argonne, IL 60439
526. H. Nickel
Forschungszentrum Jülich (KFA)
P.O. Box 1913
Jülich 1-5170 BRD NRW
GERMANY   AIR MAIL
527. Dale E. Niesz
Rutgers University
Center for Ceramic Research
P.O. Box 909
Piscataway, NJ 08855-0909
528. David M. Nissley
United Technologies Corporation
Pratt & Whitney Aircraft
400 Main Street, MS:163-10
East Hartford, CT 06108
529. Richard D. Nixdorf
ReMaxCo Technologies, Inc.
11317 Snyder Road
Knoxville, TN 37932
530. Bernard North
Kennametal, Inc.
P.O. Box 639
Greensburg, PA 15601
531. Bruce E. Novich
Ceramics Process Systems
Corporation
155 Fortune Boulevard
Milford, MA 01757
532. Daniel Oblas
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
533. Don Ohanehi
Magnetic Bearings, Inc.
1908 Sussex Road
Blacksburg, VA 24060
534. Robert Orenstein
General Electric Company
55-112, River Road
Schenectady, NY 12345

535. Norb Osborn
Aerodyne Dallas
151 Regal Row,
Suite 120
Dallas, TX 75247
536. A. M. Paddick
BP International Limited
BP Research Centre, Main
Library
Chertsey Road
Sunbury-on-Thames
Middlesex TW16 7LN
UNITED KINGDOM AIR MAIL
537. Russell J. Page
Kanthal-Artcor
3001 Redhill Avenue, II-109
Costa Mesa, CA 92705
538. Richard Palicka
Cercom, Inc.
1960 Watson Way
Vista, CA 92083
539. Muktesh Paliwal
GTE Products Corporation
Hawes Street
Towanda, PA 18848
540. Joseph E. Palko
General Electric Company
55-113, River Road
Schenectady, NY 12345
541. Hayne Palmour, III
North Carolina State
University
Materials Science and
Engineering Dept.
Raleigh, NC 27605-7905
542. Joseph N. Panzarino
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
543. Pellegrino Papa
Corning Inc.
MP-WX-02-1
Corning, NY 14831
544. E. Beth Pardue
Technology for Energy
Corporation
One Energy Center
P.O. Box 22996
Knoxville, TN 37933-0996
545. Soon C. Park
3M Company
3M Center
Building 142-4N-02
P.O. Box 2963
St. Paul, MN 55144
546. Hartmut Paschke
Schott Glaswerke
Christoph-Dorner-Strasse 29
D-8300 Landshut
GERMANY AIR MAIL
547. Marina R. Pascucci
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
548. James W. Patten
Cummins Engine
Company, Inc.
Materials Engineering
P.O. Box 3005, Mail
Code 50183
Columbus, IN 47202-3005
549. Robert A. Penty
Eastman Kodak Company
KAD/D73 - 35612
901 Elmgrove Road
Rochester, NY 14653
550. Robert W. Pepper
Textron Specialty Materials
2 Industrial Avenue
Lowell, MA 01851
551. Peter Perdue
Detroit Diesel Corporation
Research Advanced Development
Group
13400 West Outer Drive,
Speed Code A-07
Detroit, MI 48239-4001

552. Bruce Peters
Dow Chemical Company
Building 52
Midland, MI 48667
553. John J. Petrovic
Los Alamos National Laboratory
Group MST-4, MS:6771
Los Alamos, NM 87545
554. Frederick S. Pettit
University of Pittsburgh
Pittsburgh, PA 15261
555. Ben A. Phillips
Phillips Engineering Company
721 Pleasant Street
St. Joseph, MI 49085
556. Richard C. Phoenix
Ohmtek, Inc.
2160 Liberty Drive
Niagara Falls, NY 14302
557. Bruce J. Pletka
Michigan Technological
University
Metallurgical and Materials
Engineering Department
Houghton, MI 49931
558. John P. Pollinger
Garrett Ceramic Components
19800 Van Ness Avenue
Torrance, CA 90501
559. P. Popper
High Technology Ceramics
International Journal
22 Pembroke Drive
Westlands Newcastle-under-Lyme
Staffs ST5 2JN
ENGLAND AIR MAIL
560. F. Porz
Universitat Karlsruhe
Institut für Keramik Im
Maschinendau
Postfach 6980
D-7500 Karlsruhe
GERMANY AIR MAIL
561. Harry L. Potma
Royal Netherlands Embassy
Science and Technology
4200 Linnean Avenue, N.W.
Washington, DC 20008
562. Bob R. Powell
General Motors Research
Laboratories
Metallurgy Department
30500 Mound Road
Box 9055
Warren, MI 48090-9055
563. Stephen C. Pred
ICD Group, Inc.
1100 Valley Brook Avenue
Lyndhurst, NJ 07071
564. Karl M. Prewo
United Technologies Research
Center
411 Silver Lane
MS:24
East Hartford, CT 06108
565. Peter E. Price
Industrial Materials
Technology, Inc.
P.O. Box 9565
Andover, MA 01810
566. Joseph M. Proud
GTE Laboratories, Inc.
Materials Science Laboratory
40 Sylvan Road
Waltham, MA 02254
567. Vimal K. Pujari
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
568. George Quinn
National Institute of
Standards and Technology
Ceramics Division, Bldg. 223
Gaithersburg, MD 20899

569. Ramas V. Raman
Ceracon, Inc.
1101 North Market Boulevard,
Suite 9
Sacramento, CA 95834
570. Charles F. Rapp
Owens Corning Fiberglass
2790 Columbus Road
Granville, OH 43023-1200
571. Dennis W. Readey
Colorado School of Mines
Department of Metallurgy
and Materials Engineering
Golden, CO 80401
572. Wilfred J. Rebello
PAR Enterprises, Inc.
12601 Clifton Hunt Lane
Clifton, VA 22024
573. Harold Rechter
Chicago Fire Brick Company
R&D
7531 South Ashland Avenue
Chicago, IL 60620
574. Robert R. Reeber
U.S. Army Research Office
P.O. Box 12211
Research Triangle Park, NC 27709
575. K. L. Reifsnider
Virginia Polytechnic Institute
and State University
Department of Engineering
Science and Mechanics
Blacksburg, VA 24061
576. Paul E. Rempes
McDonnell Douglass Missile
Systems Company
P.O. Box 516,
Mail Code:1066086
St. Louis, MO 63166-0516
577. Gopal S. Revankar
John Deere Company
Metals Research
3300 River Drive
Moline, IL 61265
578. K. T. Rhee
Rutgers University
Mechanical Engineering
P.O. Box 909
Piscataway, NJ 08854
579. James Rhodes
Advanced Composite Materials
Corporation
1525 South Buncombe Road
Greer, SC 29651
580. Roy W. Rice
W. R. Grace and Company
7379 Route 32
Columbia, MD 21044
581. David W. Richerson
2093 East Delmont Drive
Salt Lake City, UT 84117
582. Tomas Richter
J. H. France Refractories
1944 Clarence Road
Snow Shoe, PA 16874
583. Michel Rigaud
Ecole Polytechnique
Campus Universite De Montreal
P.O. Box 6079, Station A
Montreal, P.Q. Quebec H3C 3A7
CANADA AIR MAIL
584. R. E. Riman
Rutgers University
Ceramics Engineering
Department
P.O. Box 909
Piscataway, NJ 08855-0909
585. Barry Ringstrom
Superior Graphite Company
P.O. Box 2373
Smyrna, GA 30081
586. John E. Ritter
University of Massachusetts
Mechanical Engineering
Department
Amherst, MA 01003

587. Frank L. Roberge
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
P.O. Box 5227
Phoenix, AZ 85010
588. W. Eric Roberts
Advanced Ceramic
Technology, Inc.
990 "F" Enterprise Street
Orange, CA 92667
589. Martha Rohr
U.S. Department of Energy
DOE Oak Ridge Field Office
Building 4500N
P.O. Box 2008, MS:6269
Oak Ridge, TN 37831-6269
590. Y. G. Roman
TNO TPD Keramick
P.O. Box 595
Eindhoven 5600 AN
HOLLAND AIR MAIL
591. Mark D. Roos
Carborundum Company
P.O. Box 156
Niagara Falls, NY 14302
592. Michael Rossetti
Arthur D. Little, Inc.
15 Acorn Park
Cambridge, MA 01240
593. Barry R. Rossing
Lanxide Corporation
1300 Marrows Road
Newark, DE 19714-6077
594. Steven L. Rotz
Lubrizol Corporation
29400 Lakeland Boulevard
Wickliffe, OH 44092
595. Bruce Rubinger
Global Competitiveness, Inc.
One Devonshire Place,
Suite 1011
Boston, MA 02109
596. Robert Ruh
Wright Laboratory
WL/MLLM
Wright-Patterson AFB, OH 45433
597. Robert J. Russell
17 Highgate Road
Framingham, MA 01701
598. L. William Sahley
Supermaterials Company
24400 Highland Road
Richmond Heights, OH 44143
599. Jon Salem
NASA Lewis Research Center
21000 Brookpark Center
Cleveland, OH 44135
600. W. A. Sanders
NASA Lewis Research Center
21000 Brookpark Road,
MS:49-3
Cleveland, OH 44135
601. J. Sankar
North Carolina A&T State
University
Department of Mechanical
Engineering
Greensboro, NC 27411
602. Yasushi Sato
NGK Spark Plugs (U.S.A.), Inc.
1200 Business Center Drive,
Suite 300
Mt. Prospect, IL 60056
603. Maxine L. Savitz
Allied-Signal Aerospace
Company
Garrett Ceramic Components
Division
19800 South Van Ness Avenue
Torrance, CA 90501
604. Ashok Saxena
Georgia Institute of
Technology
Materials Engineering
Atlanta, GA 30332-0245

605. David W. Scanlon
Instron Corporation
100 Royall Street
Canton, MA 02021
606. Charles A. Schacht
Schacht Consulting Services
12 Holland Road
Pittsburgh, PA 15235
607. James Schienle
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
2739 East Washington Street
P.O. Box 5227, MS:1302-2P
Phoenix, AZ 85010
608. John C. Schneider
San Juan Technologies
P.O. Box 49326
Colorado Springs, CO 80949-9326
609. Gary Schnittgrund
Rocketdyne, BA05
6633 Canoga Avenue
Canoga Park, CA 91303
610. Mark Schomp
Lonza, Inc.
Corporate Headquarters
17-17 Route 208
Fair Lann, NJ 07410
611. Joop Schoonman
Delft University of Technology
Laboratory for Inorganic
Chemistry
P.O. Box 5045
2600 GA Delft
THE NETHERLANDS   AIR MAIL
612. John Schuldies
Industrial Ceramic
Technology, Inc.
37 Enterprise Drive
Ann Arbor, MI 48103
613. Robert B. Schulz
U.S. Department of Energy
Office of Transportation
Materials
CE-34, Forrestal Building
Washington, DC 20585
614. Murray A. Schwartz
Materials Technology
Consulting, Inc.
30 Orchard Way, North
Potomac, MD 20854
615. Peter Schwarzkopf
SRI International
333 Ravenswood Avenue
Menlo Park, CA 94025
616. Thomas C. Schweizer
Princeton Economic
Research, Inc.
12300 Twinbrook Pkwy.,
Suite 650
Rockville, MD 20852
617. William T. Schwessinger
Multi-Arc Scientific
Coatings
1064 Chicago Road
Troy, MI 48083-4297
618. W. D. Scott
University of Washington
Materials Science Department
Mail Stop:FB10
Seattle, WA 98195
619. Nancy Scoville
Thermo Electron Technologies
74 West Street
P.O. Box 9046
Waltham, MA 02254-9046
620. Brian Seegmiller
Coors Ceramics Company
600 9th Street
Golden, CO 80401

621. T. B. Selover
AICRE/DIPPR
3575 Traver Road
Shaker Heights, OH 44122
622. J. H. Selverian
GTE Laboratories, Inc.
40 Sylvan Road
Waltham, MA 02254
623. Charles E. Semler
Semler Materials Services
4160 Mumford Court
Columbus, OH 43220
624. Thomas Service
Service Engineering Laboratory
324 Wells Street
Greenfield, MA 01301
625. Kish Seth
Ethyl Corporation
R&D Laboratories
P.O. Box 341
Baton Rouge, LA 70821
626. Karleen Seybold
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
P.O. Box 5227
Phoenix, AZ 85010
627. William J. Shack
Argonne National Laboratory
9700 South Cass Avenue
Building 212
Argonne, IL 60439
628. Peter T. B. Shaffer
Technical Ceramics
Laboratories, Inc.
4045 Nine/McFarland Drive
Alpharetta, GA 30201
629. Richard K. Shaltens
NASA Lewis Research Center
21000 Brookpark Road,
MS:301-2
Cleveland, OH 44135
630. Robert S. Shane
238 Hemlock Road
Wynnewood, PA 19096
631. Daniel Shanefield
Rutgers University
Ceramics Engineering
Department
P.O. Box 909
Piscataway, NJ 08855-0909
632. Ravi Shankar
Chromalloy
Research and Technology
Division
Blaisdell Road
Orangeburg, NY 10962
633. Terence Sheehan
Alpex Wheel Company
727 Berkley Street
New Milford, NJ 07646
634. Dinesh K. Shetty
University of Utah
304 EMRO, Dept. of Materials
Science and Engineering
Salt Lake City, UT 84112
635. Masahide Shimizu
Ceramic Society of Japan
2-2-503 Takiyama 6-chome
Higashikurume-Shi Tokyo 203
JAPAN AIR MAIL
636. John Shipinski
Toyota Technical Center
U.S.A., Inc.
Technical Research Department
2000 Town Center, Suite 500
Southfield, MI 48075
637. Thomas Shreves
American Ceramic Society, Inc.
Library
757 Brooksedge Plaza Drive
Westerville, OH 43081-2821
638. Jack D. Sibold
Coors Ceramics Company
Contracts for Corporate
Technology
4545 McIntyre Street
Golden, CO 80403

705. Janet Wade
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division, Department 93-772
P.O. Box 5227, MS:1303-2
Phoenix, AZ 85010
706. Richard L. Wagner
Ceramic Technologies, Inc.
537 Turtle Creek South Drive,
Suite 24D
Indianapolis, IN 46227
707. J. Bruce Wagner, Jr.
Arizona State University
Center for Solid State
Science
Tempe, AZ 85287-1704
708. Daniel J. Wahlen
Kohler, Co.
444 Highland Drive
Kohler, WI 53044
709. Ingrid Wahlgren
Royal Institute of Technology
Studsvik Library
S-611 82 Nykoping
SWEDEN AIR MAIL
710. Ron H. Walecki
Allied-Signal Aerospace
Company
Garrett Ceramic Components
Division
19800 South Van Ness Avenue
Torrance, CA 90501
711. Michael S. Walsh
Vapor Technologies Inc.
2100 Central Avenue
Boulder, CO 80301
712. Chien-Min Wang
Industrial Technology Research
Institute
Materials Research Laboratories
195 Chung-Hsing Road, Sec. 4
Chutung Hsinchu 31015 R.O.C.
TAIWAN AIR MAIL
713. Robert M. Washburn
ASMT
11203 Colima Road
Whittier, CA 90604
714. Gerald Q. Weaver
Carborundum Specialty Products
42 Linus Allain Avenue
Gardner, MA 01440-2478
715. Karen E. Weber
Detroit Diesel Corporation
Technology and Planning
13400 West Outer Drive
Detroit, MI 48239-4001
716. R. W. Weeks
Argonne National Laboratory
MCT-212
9700 South Cass Avenue
Argonne, IL 60439
717. Ludwig Weiler
ASEA Brown Boveri AG
Corporate Research
Eppelheimer Str. 82
D-6900 Heidelberg
GERMANY AIR MAIL
718. James Wessel
Dow Corning Corporation
1800 "M" Street, N.W.,
Suite 325 South
Washington, DC 20036
719. Robert D. West
Therm Advanced Ceramics
P.O. Box 220
Ithaca, NY 14851
720. Thomas J. Whalen
Ford Motor Company
26362 Harriet
Dearborn Heights, MI 48127
721. Ian A. White
Hoeganaes Corporation
River Road
Riverton, NJ 08077

689. L. J. Trostel, Jr.
Box 199
Princeton, MA 01541
690. W. T. Tucker
General Electric Company
Corporate R&D
Building K1-4C35
P.O. Box 8
Schenectady, NY 12301
691. Masanori Ueki
Nippon Steel Corporation
Central R&D Bureau
1618 Ida
Nakahara-Ku Kawasaki 211
JAPAN AIR MAIL
692. Filippo M. Ugolini
ATA Studio
Via Degli Scipioni, 268A
ROMA 00192
ITALY AIR MAIL
693. Donald L. Vaccari
Allison Gas Turbines
P.O. Box 420
Speed Code S49
Indianapolis, IN 46206-0420
694. Carl F. Van Conant
Boride Products, Inc.
2879 Aero Park Drive
Traverse City, MI 49684
695. Marcel H. Van De Voorde
Commission of the European
Communities
Institute for Advanced
Materials
Joint Research Centre
P.O. Box 2
1755 ZG Petten
THE NETHERLANDS AIR MAIL
696. O. Van Der Biest
Katholieke Universiteit Leuven
Departement Metaalkunde en
Toegepaste
de Croylaan 2
B-3030 Leuven
BELGIUM AIR MAIL
697. Michael Vannier
Washington University,
St. Louis
Mallinckrodt Institute of
Radiology
510 South Kings Highway
St. Louis, MO 63110
698. Stan Venkatesan
Southern Coke & Coal
Corporation
P.O. Box 52383
Knoxville, TN 37950
699. V. Venkateswaran
Carborundum Company
Niagara Falls R&D Center
P.O. Box 832
Niagara Falls, NY 14302
700. Dennis Viechnicki
U.S. Army Materials Technology
Laboratory
405 Arsenal Street
Watertown, MA 02172-0001
701. Ted Vojnovich
U.S. Department of Energy
Office of Energy Research,
ER-42
Washington, DC 20585
702. John D. Volt
E. I. Dupont de Nemours &
Company, Inc.
P.O. Box 80262
Wilmington, DE 19880
703. John B. Wachtman
Rutgers University
Ceramics Department
P.O. Box 909
Piscataway, NJ 08855
704. Shigetaka Wada
Toyota Central Research
Labs, Inc.
Nagakute Aichi 480-11
JAPAN AIR MAIL

672. Patrick L. Sutton
U.S. Department of Energy
Advanced Propulsion Division
CE-322, Forrestal Building
Washington, DC 20585
673. Willard H. Sutton
United Technologies
Corporation
Research Center, MS:24
Silver Lane
East Hartford, CT 06108
674. Ron Sviben
100 Indel Avenue
Rancocas, NJ 08073
675. J. J. Swab
U.S. Army Materials Technology
Laboratory
Ceramics Research Division
SLCMT-EMC
405 Arsenal Street
Watertown, MA 02172
676. Robert E. Swanson
Metalworking Technology, Inc.
1450 Scalp Avenue
Johnstown, PA 15904
677. Scott L. Swartz
Battelle Columbus
Laboratories
Metals and Ceramics
505 King Avenue
Columbus, OH 43201
678. Steve Szaruga
Air Force Wright Aeronautical
Laboratory
Materials Directorate
WL/MLBC
Wright-Patterson
AFB, OH 45433-6533
679. Yo Tajima
NGK Spark Plug Company, Ltd.
NTK Technical Ceramic Division
2808 Iwasaki
Komaki-shi Aichi-ken 485
JAPAN AIR MAIL
680. Fred Teeter
5 Tralee Terrace
East Amherst, NY 14051
681. Monika O. Ten Eyck
Carborundum Company
Technology Division
P.O. Box 832
Niagara Falls, NY 14302
682. David F. Thompson
Corning Glass Works
SP-DV-02-1
Corning, NY 14831
683. Merle L. Thorpe
Hobart Tafa Technologies, Inc.
146 Pembroke Road
Concord, NH 03301
684. Eberhard Tiefenbacher
Daimler-Benz AG Abt. FIS
Mercedes-Strabe 136
Stuttgart 60
GERMANY AIR MAIL
685. T. Y. Tien
University of Michigan
Materials Science and
Engineering Department
Dow Building
Ann Arbor, MI 48103
686. Julian M. Tishkoff
Air Force Office of Scientific
Research
AFOSR/NA
Bolling AFB, DC 20332-6448
687. D. M. Tracey
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
688. Dick Trippett
General Motors Corporation
Allison Gas Turbine Division
P.O. Box 420, MS:W-16
Indianapolis, IN 46206-0420

639. George H. Siegel
Point North Associates, Inc.
P.O. Box 907
Madison, NJ 07940
640. Richard Silberglitt
Technology Assessment and
Transfer, Inc.
133 Defense Highway, #212
Annapolis, MD 21401
641. Mary Silverberg
Norton Company
Advanced Ceramics Library
Goddard Road
Northboro, MA 01532-1545
642. Gurpreet Singh
Department of the Navy
Internal Combustion & Gas
Turbine Engine Division
Code 56X31
Washington, DC 20362-5101
643. Maurice J. Sinnott
University of Michigan
Chemical and Metallurgical
Engineering
5106 IST Building
Ann Arbor, MI 48109-2099
644. John Skildum
3M Company
3M Center
Building 224-2S-25
St. Paul, MN 55144
645. David P. Smith
Hoskins, Rees & Smith
1910 Cochran Road
Manor Oak II, Suite 658
Pittsburgh, PA 15220
646. Richard H. Smoak
Smoak & Associates
3554 Hollyslope Road
Altadena, CA 91001-3923
647. Jay R. Smyth
Allied-Signal Aerospace
Company
Garrett Auxiliary Power
Division
2739 East Washington Street
P.O. Box 5227
MS:93-173/1303-207
Phoenix, AZ 85010
648. Edward A. Snajdr
Premier Refractories
and Chemicals, Inc.
P.O. Box 392
Findlay, OH 44815
649. Rafal A. Sobotowski
British Petroleum Company
Technical Center, Broadway
3092 Broadway Avenue
Cleveland, OH 44115
650. A. G. Solomah
SAC International Ltd.
1445 Bonhill Road, # 13
Mississauga Ontario L5T 1V3
CANADA AIR MAIL
651. S. Somiya
Nishi Tokyo University
3-7-19 Seijo, Setagaya
Tokyo 157
JAPAN AIR MAIL
652. Boyd W. Sorenson
DuPont Lanxide Composites
1300 Marrows Road
P.O. Box 6077
Neward, DE 19707
653. Charles A. Sorrell
U.S. Department of Energy
Advanced Industrial
Concepts Division
CE-232, Forrestal
Building
Washington, DC 20585

654. C. Spencer
EA Technology
Capenhurst Chester
CH1 6ES
UNITED KINGDOM   AIR MAIL
655. Allen Spizzo
Hercules, Inc.
Hercules Plaza
Wilmington, DE 19894
656. Richard M. Spriggs
Alfred University
Center for Advanced Ceramic
Technology
Alfred, NY 14802
657. Charles Spuckler
NASA Lewis Research Center
21000 Brookpark Road
MS: 5-11
Cleveland, OH 44135-3191
658. M. Srinivasan
Material Solutions
P.O. Box 663
Grand Island, NY 14702-0663
659. Gordon L. Starr
Cummins Engine Company, Inc.
Design & Technology
P.O. Box 3005
Mail Code 50182
Columbus, IN 47202-3005
660. Jim Stevenson
Windrock, Incorporated
154 Fairbanks Plaza
Oak Ridge, TN 37830
661. Tom Stillwagon
Allied-Signal Aerospace
Company
Garrett Ceramic Components
Division
19800 South Van Ness Avenue
Torrance, CA 90501
662. Harold L. Stocker
General Motors Corporation
Allison Gas Turbine Division
P.O. Box 420
Indianapolis, IN 46206
663. Paul D. Stone
Dow Chemical USA
1776 "Eye" Street, N.W.,
Suite 575
Washington, DC 20006
664. Roger S. Storm
Carborundum Company
Technology Division
P.O. Box 337
Niagara Falls, NY 14302-0337
665. Peter A. Stranges
4 Chittenden Lane
Owings Mills, MD 21117
666. F. W. Stringer
Aero & Industrial
Technology Ltd.
P.O. Box 46, Wood Top
Burnley Lancashire BB11 4BX
UNITED KINGDOM   AIR MAIL
667. Thomas N. Strom
NASA Lewis Research Center
21000 Brookpark Road
MS:86-6
Cleveland, OH 44135
668. M. F. Stroosnijder
Institute for Advanced
Materials
Joint Research Centre
21020 Ispra (VA)
ITALY   AIR MAIL
669. Karsten Styhr
30604 Ganado Drive
Rancho Palos Verdes, CA 90274
670. T. S. Sudarshan
Materials Modification, Inc.
2929-P1 Eskridge Center
Fairfax, VA 22031
671. M. J. Sundaresan
University of Miami
Mechanical Engineering
Department
P.O. Box 248294
Coral Gables, FL 33124

722. Alan Whitehead
General Electric Company
1 River Road, 55-111
Schenectady, NY 12345
723. Sheldon M. Wiederhorn
National Institute of
Standards and Technology
Building 223, Room A329
Gaithersburg, MD 20899
724. John F. Wight
Alfred University
McMahon Building
Alfred, NY 14802
725. D. S. Wilkinson
McMaster University
Materials Science and
Engineering Department
1280 Main Street, West
Hamilton Ontario L8S 4L7
CANADA AIR MAIL
726. James C. Williams
General Electric Company
Engineering Materials
Technology Labs
One Neumann Way
Mail Drop: H85
Cincinnati, OH 45215-6301
727. Janette R. Williams
Kollmorgen Corporation
PCK Technology Division
150 Motor Parkway, # 262
Hauppauge, NY 11788-5108
728. Steve J. Williams
RCG Hagler Bailly, Inc.
1530 Wilson Boulevard,
Suite 900
Arlington, VA 22209-2406
729. Craig A. Willkens
Norton Company
Advanced Ceramics
Goddard Road
Northboro, MA 01532-1545
730. Roger R. Wills
TRW, Inc.
Valve Division
1455 East 185th Street
Cleveland, OH 44110
731. David Gordon Wilson
Massachusetts Institute of
Technology
Mechanical-Engineering
Department
77 Massachusetts Avenue,
Room 3-455
Cambridge, MA 02139
732. Matthew F. Winkler
Seaworthy Systems, Inc.
P.O. Box 965
Essex, CT 06426
733. Gerhard Winter
Hermann C. Starck Berlin GmbH,
Werk Goslar
P.O. Box 25 40
D-3380 Goslar 3380
GERMANY AIR MAIL
734. W. L. Winterbottom
Ford Motor Company
Material Systems Reliability
Department
20000 Rotunda Drive
SRL, Room E-3182
P.O. Box 2053
Dearborn, MI 48121
735. David G. Wirth
Coors Ceramics Company
600 9th Street
Golden, CO 80401
736. Thomas J. Wissing
Eaton Corporation
Engineering & Research Center
P.O. Box 766
Southfield, MI 48037
737. James C. Withers
MER Corporation
7960 South Kolb Road
Building F
Tucson, AZ 85706

738. Dale E. Wittmer
Southern Illinois University
Mechanical Engineering
Department
Carbondale, IL 62901
739. Warren W. Wolf
Owens Corning Fiberglass
2790 Columbus Road, Route 16
Granville, OH 43023
740. George W. Wolter
Howmet Turbine Components
Corporation
Technical Center
699 Benston Road
Whitehall, MI 49461
741. James C. Wood
NASA Lewis Research Center
21000 Brookpark Road
MS:86-6
Cleveland, OH 44135
742. Marrill Wood
LECO Corporation
Augusta Division
P.O. Box 211688
Augusta, GA 30917-1688
743. Wayne L. Worrell
University of Pennsylvania
Department of Materials
Science and Engineering
3231 Walnut Street
Philadelphia, PA 19104
744. John F. Wosinski
Corning Inc.
ME-2 E-5 H8
Corning, NY 14830
745. Ian G. Wright
Battelle Columbus Laboratories
505 King Avenue
Columbus, OH 43201
746. Ruth Wroe
ERDC
Metals & Materials Industries
Division
Capenhurst Chester CH1 6ES
ENGLAND AIR MAIL
747. Bernard J. Wrona
Advanced Composite Materials
Corporation
1525 South Buncombe Road
Greer, SC 29651
748. Carl C. M. Wu
Naval Research Laboratory
Ceramic Branch, Code 6373
Washington, DC 20375
749. John C. Wurst
University of Dayton Research
Institute
300 College Park
Dayton, OH 45469-0101
750. Neil Wyant
ARCH Development Corp.
9700 South Cass Avenue
Building 202
Argonne, IL 60439
751. Roy Yamamoto
Texaco Inc.
P.O. Box 509
Beacon, NY 12508-0509
752. John Yamanis
Allied-Signal, Inc.
Ceramics Program
P.O. Box 1021
Morristown, NJ 07962-1021
753. Harry C. Yeh
Allied-Signal Aerospace
Company
Garrett Ceramic Components
Division
19800 South Van Ness Avenue
Torrance, CA 90509
754. Hiroshi Yokoyama
Hitachi Research Lab
4026 Kuji-Cho
Hitachi-shi Ibaraki 319-12
JAPAN AIR MAIL
755. Thomas M. Yonushonis
Cummins Engine Company, Inc.
P.O. Box 3005
Mail Code 50183
Columbus, IN 47202-3005

756. Thomas J. Yost
Corning, Inc.
Technical Products Division,
Main Plant 21-1-2
Corning, NY 14831
757. Jong Yung
Sundstrand Aviation
Operations
Department 789-6
4747 Harrison Avenue
Rockford, IL 61125
758. A. L. Zadoks
Caterpillar Inc.
Technical Center, Building L
P.O. Box 1875
Peoria, IL 61656-1875
759. Avi Zangvil
University of Illinois
Materials Research Laboratory
104 South Goodwin Avenue
Urbana, IL 61801
760. Charles H. Zenuk
Transtech
6529 East Calle Cavalier
Tucson, AZ 85715
761. Anne Marie Zerega
U.S. Department of Energy
Office of Energy Research,
ER-42
Washington, DC 20585
762. Ken Zillmer
Applied Test Systems, Inc.
2571 Mt. Gallant Road
Rock Hill, SC 29730
763. Carl Zweben
General Electric Company
P.O. Box 8555, VFSC/V4019
Philadelphia, PA 19101
764. Klaus M. Zwilsky
National Research Council
National Materials
Advisory Board
2101 Constitution Avenue
Washington, DC 20418
765. Department of Energy
DOE Field Office, Oak Ridge
Assistant Manager for Energy
Research and Development
P.O. Box 2001
Oak Ridge, TN 37831-8501
- 766-775. Department of Energy
Office of Scientific and
Technical Information
Office of Information
Services
P.O. Box 62
Oak Ridge, TN 37831
- For distribution by microfiche
as shown in DOE/OSTI-4500,
Distribution Category UC-332
(Ceramics/Advanced Materials).

END

**DATE
FILMED**

10 / 26 / 92