27/20.76
25 21T 15

An Investigation of the Shallow Depth Explosions

Minao Kamegai

May 6, 1976

May 6, 1976

MASTER

and conclusions stated are those of the author and may or may not be those of the laboratory.

Prepared for U.S. Energy Research & Development Administration under contract No. W-7405-Eng-48.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

An Investigation of the Shallow Depth Explosions

Minao Kamegai

Abstract

An investigation of the nuclear explosions at shallow depth is made. A combination of an explosion code and an effects code proves to be an excellent tool for this study. A numerical simulation of "Johnie Boy" shows that the energy coupling to the air takes place in two stages; first by a rising mound, and then by a vented source. The thermal effects are examined for a 1 Kt source at three depths of burial. The "mushroom effect" leaves a hot radiative plasma in the upper level and cold materials in the lower region of the debris. The temperature and the energy density of the debris can give an upper limit on the thermal output.

I. Introduction

An investigation of the shallow depth nuclear detonations is conducted. The objectives are to examine the phenomenology of the shallow depth explosions and to study the energy coupling process to the atmosphere.

A combination of a LLL explosion code and an effects code, CEL⁽¹⁾, proved to be an excellent tool for this study. As a preliminary step, a numerical simulation of the Johnie Boy Event⁽²⁾ was made for 500 μ sec. The energy coupling to the atmosphere takes place in two stages; first, by a hydrodynamic coupling by a rising mound and subsequently by a direct radiative coupling by the energy source upon venting. The formation of the air shock and the crater lip is well reproduced.

Also shown is a study of the thermal energy for the explosions at shallow depths. Computation was performed for a standard 1 Kt source at three depths of burial. An explosion in the free atmosphere loses as much as 30 to 40% of its energy by radiative process⁽³⁾. In the case of subsurface

explosions, the radiative process is inhibited by the optically opaque vaporized soil and other high Z materials. Some quantitative results are obtained.

II. Computational Technique

Computation was done with a combination of two codes. First, the energy source was defined by an explosion code which is a 2-D Lagrangian code. It calculates the initiation of nuclear detonation and its environment. The results are then linked to an effects code, CEL.

CEL is a 2-D hydrocode with radiation diffusion. It couples the Eulerian and Lagrangian grids, utilizing the advantages of both schemes. The Lagrangian formalism is inherently more accurate than the Eulerian scheme for resolution of shock variables ⁽⁴⁾. However, when there is a strong mixing of materials, the use of the Eulerian grid alleviates many computational difficulties. Therefore, CEL is most suitable where there is a strong interaction of gaseous materials with solids.

III. Numerical Simulation of the Johnie Boy Event

"Johnie Boy" is a half Kt device detonated at 23" (58 cm) below the ground surface. The over pressure of the airblast and the wave profiles were measured on the ground level.

The initial phase which was calculated on the explosion code is shown in Figure 1. The calculation is then linked to CEL at 6 μ sec. Figures 2, 3, and 4 are the snapshots at 27 μ sec, 55 μ sec, and 103 μ sec, respectively. The energy source is mapped in a Lagrangian grid. The atmosphere and a portion of the ground surrounding the source are given by an Eulerian mesh. The rest of the ground is described by a Lagrangian grid. The tracer line is a soil-air interface.

At 55 μ sec, the source is about to penetrate the ground surface. Upon venting, the source will come in direct contact with the atmosphere. At 110 μ sec, the source has radiated more than 95% of its energy into the environment. At this point, the source grid is eliminated, and, thus, the energy source loses its identity. The computation was carried to a half m sec (see Figure 5). The crater lip is well formed.

The energy coupled to the atmosphere is plotted in Figure 6. The energy is coupled in two stages; first by a hydrodynamic process by a rising mound, and then by a direct radiative process by the source upon venting. At venting, the temperature of the source is about 20 eV, and probably the thermal output is a dominant radiation.

IV. Study of the Thermal Effects

The thermal output from the shallow explosions is an important subject which can be addressed properly with the present scheme. Using a 1 Kt standard source, the explosions at three depths of burial (0.5 m, 1.5 m, and 3 m) are being studied. Figure 7 shows the configuration of the problems.

These shallow explosions quickly communicate with the ground surface, and the energy source preferentially moves in an upward direction resulting in a "mushroom effect". The airblast appears as if it originated from a virtual point of explosion located about 20 m above the ground surface. Therefore, the center of the Lagrangian arcs describing the atmosphere is located at 20 m above the surface. Since the ground motion is of little

NOTICE
This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

interest at this time, the ground is entirely represented by a Eulerian mesh. This alleviates computational difficulties at the expense of accuracy. The tracer line marks an air-soil interface.

The source rapidly moves upward, and it penetrates the ground surface (see Figure 8). After the source radiates more than 95% of its energy, the grid is eliminated. The "mushroom effect" leaves hot plasma at an upper level and cold materials in a lower region. Figure 9 shows the wave shape at 7 msec. The shape of the Lagrangian grid near the ground surface suggests the existence of a Mach stem. Figures 10 and 11 show, respectively, the vertical temperature and pressure profiles near the axis. The "mushroom effect" is quite evident.

Figures 12 and 13 are the horizontal pressure and temperature profiles at 5 m above the ground surface. The separation of an air shock from the expanding debris is clearly observed.

The explosion at 0.5 m DOB was calculated for 3 msec, and the computation of the 3 m DOB is at 2 msec at this time. The calculation must be carried out further.

V. Summary

We have calculated the shock variables for the shallow depth explosions. From the material temperature and the energy density of the debris, the upper limit on the thermal effects may be estimated. It is possible to calculate the thermal output in the atmosphere from the shallow depth explosions if a 2-D radiation transport code is available to us. At present, we do not possess the capability.

Figure Captions

- Figure 1. Initial Configuration of "Johnnie Boy".
- Figure 2. Calculation of "Johnnie Boy" at 27 μ sec.
- Figure 3. Calculation of "Johnnie Boy" at 55 μ sec.
- Figure 4. Calculation of "Johnnie Boy" at 103 μ sec.
- Figure 5. Calculation of "Johnnie Boy" at 511 μ sec.
- Figure 6. Total Energy Coupled to the Air.
- Figure 7. Thermal Effects Study.
- Figure 8. Shallow Depth Explosion at 370 μ sec, DOB = 1.5 m.
- Figure 9. Airblast at 7 msec for BOB = 1.5 m.
- Figure 10. Vertical Temperature Profile Near the Axis, DOB = 1.5 m.
- Figure 11. Vertical Pressure Profile Near the Axis, DOB = 1.5 m.
- Figure 12. Horizontal Pressure Profiles at 5 m, DOB = 1.5 m.
- Figure 13. Horizontal Temperature Profiles at 5 m, DOB = 1.5 m.

CALCULATION OF "JOHNIE BOY" AT $27\mu\text{sec}$

CALCULATION OF "JOHNIE BOY" AT 55 μ sec

CALCULATION OF "JOHNIE BOY" AT $103 \mu\text{sec}$

CALCULATION OF "JOHNIE BOY" AT 511 μ sec

THERMAL EFFECTS STUDY

370 μ sec, DOB=1.5 m

AIRBLAST AT 7msec FOR DOB = 1.5m

Acknowledgement

The author wishes to thank the H-Division management for a strong support given to him. He is particularly indebted to the code development group in H-Division, L. Edwards, T. Michels, R. Hickman, and J. Hobson, for their generous support and encouragement in operating CEL code for this study. The discussion with G. Nutt of D-Division is greatly appreciated. J. Perez and S. Link have given assistance for computer production.

References

- (1) W.F. Noh, A Time Dependent, Two Space Dimensional, Coupled Eulerian-Lagrange Code, UCRL-7463, August, 1963.
- (2) D. Maxwell, J. Reaugh, and B. Gerber, Johnie Boy Crater Calculations, Physics International Co. Report, DNA 3048F, April, 1973.
- (3) Ya B. Zel'dovich and Yu P. Raizer, Physics of Shock Waves and High-Temperature Hydrodynamic Phenomena, Academic Press, 1967, Vol. 2.
- (4) F.H. Harlow and A.A. Amsden, Fluid Dynamics, A LASL Monograph, LA-4700, June, 1971.

Distribution

Internal:

M. Wilkins L-450
D. Norris L-450
M. Kamegai L-450 (10)
L. Edwards L-450
T. Michells L-450
J. Hobson L-450
R. Hickman L-450
G. Nutt L-96

TID (15)

Oak Ridge (27)

External:

Major Robert Wiley
AFTAC
Patrick AFB, Florida 32925

Dr. Dale Sappenfield
Mission Research
P.O. Drawer 719
Santa Barbara, Ca. 93102

Captain Jerry Stockton
SPSS
Defense Nuclear Agency
Washington, D.C. 20305

Dr. Eugene Sevin
SPSS
Defense Nuclear Agency
Washington, D.C. 20305

NOTICE

"This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research & Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately-owned rights."

Technical Information Department

LAWRENCE LIVERMORE LABORATORY

University of California | Livermore, California | 94550