RECEIVED
USDOE/PETC

90 APR -9 AM 11:24

ACQUISITION & ASSISTANCE DIV.

April 2, 1990

DOE/PC/79887--T12

DE92 040297

Project Title: Extraction, Separation and Analysis of High Sulfur Coal

DOE Contract: DE-AC22-87PC79887

Report Compiled by: Dr. Susan V. Olesik

Technical Progress Report: 11

Reporting Period: January 1, 1990 to March 21, 1990

Technical Progress Report:

Two studies were undertaken during this quarter 1) the selective solvolysis reactions of supercritical ethanol on model coal compounds was monitored by gas chromatography/mass spectrometry and 2) the reaction products produced by the oxidative interaction of an aqueous solution of cupric chloride with model coal compounds.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

db
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

Selective Solvolysis Studies:

Procedure

The purity of each model coal compound was verified by GC/MS analysis. The identity of all impurities was determined and the level of each impurity quantified. Stainless steel 40 ml or 4 ml extraction cells were used throughout these studies. In every case the quantity of sample added was such so that the concentration of sample in the supercritical ethanol solution was always 6.25 vol./vol. %. The pressurized liquid ethanol was then placed in the vessel under pressure conditions that were lower than the final reaction conditions. The vessel was heated to the desired temperature. The vessel pressure was then raised to the final reaction conditions. The fluid was allowed to interaction with the model coal compound for a period of 30 minutes. After this period the extraction cell was cooled to room temperature and the contents of the vessel were exhausted into a liquid ethanol solution. The reaction vessel was flushed with liquid ethanol and the resultant extracts were combined in a receiving vessel. The total volume of the solution in the receiving vessel was then diluted to 20 mls. An 1 microliter aliquot of this solution was then injected onto the capillary gas chromatographic column. The reactant products were then identified by GC/MS.

Reaction conditions for all model coal compounds with supercritical ethanol.

($P_c = 1154$ psi, $T_c = 240$ C)

- 1) 275°C and 3000 psi These low temperature conditions were chosen for point of comparison with the higher temperature data. Free radical bond cleavage was deemed highly unlikely under these condition.
- 2) 320°C and 3500 psi
- 3) 350°C and 3500 psi
- 4) 400°C and 3500 psi
- 5) 425°C and 3500 psi
- 6) Samples were heated to 350°C but not extracted with supercritical ethanol. The reaction products under these conditions were completely due to thermal degradation unlike the other conditions studied in which thermal degradation and solvolysis reactions were both probable.

RESULTS

1) *Phenyl sulfide* (98 % pure) Impurities were dibenzothiophene and biphenyl.

Reaction conditions	Reaction Products	% Conversion of Reactants to Products
275°C, 3000 psi	Diphenyldisulfide	ca. 5 %
320°C, 3500 psi	Diphenyldisulfide	ca. 1 %
350°C, 3500 psi	Diphenyldisulfide	ca. 1 %
400°C, 3500 psi	no reaction products	
425°C, 3500 psi	no reaction products	

Heating sample at 350°C produced no reaction products

RESULTS (cont.)

2) *Thiophenol* (97% pure) Impurities were diphenyldisulfide and iodobenzene.

Reaction conditions	Reaction Products	% Conversion of Reactants to Products
275°C, 3000 psi	Ethylthiobenzene	ca. 10%
	Diphenyldisulfide	ca. 10 %
	Phenylsulfide	ca. 2 %
320°C, 3500 psi	Ethylthiobenzene	ca. 7 %
	Diphenyldisulfide	ca. 3 %
	Phenylsulfide	ca. 3 %
3500°C, 3500 psi	Ethylthiobenzene	ca. 12 %
	Diphenyldisulfide	ca. 5 %
	Phenylsulfide	ca. 10 %
400°C, 3500 psi	Ethylthiobenzene	ca. 20 %
	Phenylsulfide	ca. 40 %
425°C, 3500 psi	Ethylthiobenzene	ca. 20 %
	Phenylsulfide	ca. 50 %
Heating sample	Diphenylsulfide	ca. 5%
at 350°C	Phenylsulfide	ca. 15%

RESULTS (cont.)

3) *Cyclohexyl mercaptan* (99 % pure) Impurities were dicyclohexyl propandinitrile.

Reaction conditions	Reaction Products	% Conversion of Reactants to Products
275°C, 3000 psi	No reaction products	
320°C, 3500 psi	Ethyl thiocyclohexane	< 4 %
350°C, 3500 psi	Ethyl thiocyclohexane	< 4 %
400°C, 3500 psi	no reaction products	
425°C, 3500 psi	no reaction products	
Heating sample to 350°C	no reaction products	

4) *Methyl p-tolylsulfide* (99.9 % pure) Impurity was Ethyl p-tolylsulfide

Reaction conditions	Reaction Products	% Conversion of Reactants to Products
275°C, 3000 psi	benzene acetic acid	1 %
	phenyl sulfide	0.5 %
320°C, 3500 psi	no reaction products	
400°C, 3500 psi	no reaction products	
425°C, 3500 psi	no reaction products	

Heating sample to 350°C resulted in no reaction products

5) *Dibenzothiophene* (98 % pure) No impurities found.

No reaction products were found under the conditions studied.

DISCUSSION

In summary, significant bond cleavage was found only for thiophenol under the supercritical conditions studied. Less than 5 % yield was found for the observed reaction products for all the other organosulfur compounds. The hydrogen sulfur bond in thiophenol is clearly the weakest of those studied and therefore it is the easiest to rupture. Also a general trend was observed the solvolysis reaction products such as ethylthiobenzene were the products initially formed at lower temperatures. But with higher temperatures the reaction product were those typically produced from the bimolecular association of free-radicals, such as phenylsulfide for the thiophenol sample. This type of reaction would be expected in pyrolysis reactions.

Bimolecular reactions between organosulfur compounds would not be expected when the reaction is occurring at the surface of the solid coal matrix. The probability of the extracted organosulfur radicals having such bimolecular reactions is quite low. However, the reactions that are observed from the interaction of supercritical ethanol and the model coal compounds are not ones that show obvious indications of desulfurization of the compound.

PLANS FOR NEXT QUARTER

Nevertheless, published work on the interaction of supercritical ethanol and bituminous coals has indicated the occurrence of coal desulfurization. Possible causes of this dichotomy are the following:

- 1) Their work or ours is wrong.
- 2) Reactions of model coal compounds are poor indicators of the reactions found in coals.
- 3) The interaction of supercritical alcohols with coal is a process whereby much of the mobile portion of the coal (compounds intercalated into the coal structure with molecular weights ranging from 50-800 amu) is dissolved and removed from the solid polymeric structure.

We will assume that possibility #1 is unlikely because we have found our results to be quite reproducible and have no reason to believe that the published results were not taken with as much care. To try to discriminate between possibilities #2 and #3 we intend to try to solvate these intercalated compounds and determine their identity. Supercritical carbon dioxide and supercritical ethane are capable of solvating PAH compounds of this size range. However, ethane is not as accessible to the interior pore structure of the coal as is carbon dioxide. A comparison of the extraction products from both of these experiments should contribute strongly to the understanding of compound intercalation in coals.

The coals that are exhaustively extracted will then be exposed to supercritical ethanol and the extent of desulfurization measured with our sulfur chemiluminescence detector. Similar desulfurization studies will all be done on coal that was not exposed to supercritical carbon dioxide or ethane prior to interaction with the supercritical ethanol.

We have obtained samples of Illinois #6 (hvB) 100 mesh from the premium coal sample bank at the Argonne National Labs. We plan to monitor the selective extraction effects of supercritical ethanol and the interaction of cupric chloride with the coal samples. The same reaction conditions will be used as was studied for the model coal compounds. Additional precautions will be taken with the coal samples to insure the reliability of the results.

We will pack a tube in the same fashion that we would pack a stationary phase into a tube and then exhaustively flush supercritical carbon dioxide through the column of coal. Any extracted material will be bubble into a liquid which will be placed at the end of the flow restrictor. Two extraction conditions will be considered: 1) 40°C, 3500 psi and 2) 100°C, 3500 psi. The same exhaustive extraction experiment will be tried using supercritical ethane at comparable conditions.

The mass balance of the process will be carefully monitored. Any extraction products will be determined by GC/MS and/or SFC/MS. If these results are not conclusive the group also has capabilities of SFC/FTIR and SFC/NMR that we can use.

The coal columns will then be flushed with supercritical ethanol. The reactor products of this will also be determine by SFC/MS and/or GC/MS and any other ancillary techniques that are necessary.

REACTION OF CUPRIC CHLORIDE WITH MODEL COAL COMPOUNDS

Of great interest to us is under what conditions does cupric chloride desulfurize coals?. To help answer this question we have studied the reaction of cupric chloride on model coal compounds in aqueous solutions. The extraction system was the same as described above. In these studies the reaction products were analyzed by GC/MS. The results follow.

When methyl p-tolysulfide was treated with a 50% wt/wt. solution of cupric chloride in water at 200°C, the primary reaction product was methylmercaptan ortho-benzaldehyde and methylmercaptan meta-benzaldehyde.

When dibenzothiophene was treated with 50% wt/wt cupric chloride solution in water at 200°C hydroxyl substitution at both carbons that are adjacent to the sulfur linkage occurred.

1.
When diphenyldisulfide was treated with 50% wt./wt. cupric chloride at 200°C one sulfur was converted to a sulfone.

Of the reactions described the yield was highest for the methyl p-tolylsulfide. The second highest yield was the reaction of the dibenzothiophene followed by the diphenyldisulfide.

Discussion of Data and Work Planned for Next Quarter

The reaction products described above look similar to intermediates expected in the Pummerer reactions in which nucleophilic substitution occurs alpha to the sulfur atom oxidation at the alpha carbon occurs. If the Pummerer reaction is a reasonable approximate description of the reaction mechanisms that are in effect here, then increasing the temperature of the reaction should cause cleavage at the alpha C-S bond and formation of the aldehyde.

The reaction of the remaining model coal compounds will be studied. The reactions that have already been studied will also be retried at higher temperatures to see if desulfurization can be forced.

The best reaction conditions found for product formation for the model coal compounds will then be used on the extraction of Illinois #6 coal. The coal that has been exhaustively extracted with carbon dioxide will be used in these studies as well as the solvolysis studies.

END

**DATE
FILMED**

10 / 27 / 92