**THERMAL CYCLE LIMITS FOR TRITIUM HYDRIDE BEDS
(U)**

by
J. E. Klein
Westinghouse Savannah River Company
Savannah River Site
Aiken, South Carolina 29808

RECEIVED
AUG 05 1993
OSTI

DOE Contract No. **DE-AC09-89SR18035**

This paper was prepared in connection with work done under the above contract number with the U. S. Department of Energy. By acceptance of this paper, the publisher and/or recipient acknowledges the U. S. Government's right to retain a nonexclusive, royalty-free license in and to any copyright covering this paper, along with the right to reproduce and to authorize others to reproduce all or part of the copyrighted paper.

MASTER
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

This report has been reproduced directly from the best available copy.

Available to DOE and DOE contractors from the Office of Scientific and Technical Information, P. O. Box 62, Oak Ridge, TN 37831; prices available from (615) 576-8401.

Available to the public from the National Technical Information Service, U. S. Department of Commerce, 5285 Port Royal Rd., Springfield, VA 22161.

SUMMARY

During revision of the Tritium Facility Technical Standards, a thermal cycle limit was added to the "Hydride Vessels" Technical Standard. A limit of 1,000 cycles was added since the metallurgical effect of repeated thermal cycling of the stainless steel hydride beds was not known. Procedures would require modifications to record the number of thermal cycles a bed has experienced during its life-time.

The calculations in this report show that the operations of the hydride beds in the Tritium Facilities can experience at least 10,000 thermal cycles. Maximum temperature differences across the walls of the hydride beds were calculated to determine the cycle limits. The calculated temperature differentials were less than 50% of the temperature differentials which would require a 10,000 cycle limit.

10,000 cycles is equivalent to cycling the bed over nine times per day for the next three years or five times per day for the next five years. If the expected number of bed cycles for the beds are to be less than 10,000 cycles, the number of thermal cycles for the beds do not need to be recorded or logged. Not logging or tracking the number of thermal cycles for the beds will greatly reduce the administrative burden of operating these vessels.

These results are based ultimately on the pressure drop of nitrogen through the hydride bed cooling coils which is controlled by the liquid nitrogen dewer's 22 psig relief valve. This 22 psi differential for flow and the conservative assumptions made in the calculations gave maximum temperature differentials less than 50 percent of the values allowed for the 10,000 cycle limit. Changes which would increase the liquid nitrogen supply pressure for the beds would need to be reviewed to verify that the conclusions of this report were to remain valid.

INTRODUCTION

Hydride Bed Description

The Tritium Facilities use metal hydride beds within the facilities. The hydride beds are cylindrical stainless steel vessels which are used to contain the metal hydride material. Process connections allow the beds to absorb and desorb hydrogen isotopes.

To absorb hydrogen isotopes from a bed, the bed is cooled by flowing liquid nitrogen through a copper cooling coil attached to external walls of the bed. Heaterwells, also made of copper tubing, are coiled around and attached to the outside of the bed. Electric heater elements inserted into these heaterwells are energized to heat the bed and desorb the hydrogen isotopes.

Thermal Stress Analysis

Thermal fatigue and failure of a material may occur due to thermal cycling. The extent of the fatigue caused by thermal stresses is a function of the type of material and the magnitude of the thermal stresses. Thermal fatigue design of vessels is covered in the ASME Boiler and Pressure Vessel Code, Section VIII, Division 2¹. In Section AD-160 of the code dealing with Fatigue Evaluation, the extent of thermal stress for a cylindrical geometry is determined by the maximum temperature difference, at any given time, across the bed container wall during heating or cooling. This will be referred to as ΔT_{max} .

ΔT_{max} allowable as a function of the number of thermal cycles for the beds was calculated in a corresponding memo². To determine the number of allowable thermal cycles for the hydride beds, ΔT_{max} needed to be calculated.

In calculating ΔT_{max} , it was assumed that the change from heating to cooling would generate a larger thermal gradient across the walls of the beds than a change from cooling to heating. This was based on the belief that the response time of the heater elements was slower than that of a step-change in liquid nitrogen flow rate. The calculated results show this is a reasonable assumption since the largest thermal gradient across the bed wall occurred within one to four seconds after applying liquid nitrogen to the bed cooling coils.

DISCUSSION

Bed Descriptions

Dimensions

The dimensions of the metal hydride beds analyzed are given in Table 1. In Table 2, the description of the copper cooling coils is given. Radii are included in the tables since the computer program inputs are in terms of radius instead of diameter. The length of copper tubing, L_t , is estimated using the following formula:

$$L_t = N \pi O.D._b 1.25 \quad (1)$$

where N is the number of turns of the copper tubing and $O.D._b$ is the outside diameter of the bed. The term 1.25 was used to approximately compensate for the additional length of tubing present due to the pitch spacing of the tubing wrapped along the length of the bed.

Heat Transfer Areas

The external heat area of the hydride bed, $A_{b,ex}$, was calculated using

$$A_{b,ex} = \pi O.D._b L_b \quad (2)$$

The area of the copper coiling coils in thermal contact with the bed, $A_{t,ex}$, was assumed to be one-half the outside area of the tubing and is calculated using

$$A_{t,ex} = \pi \frac{O.D._t}{2} L_t \quad (3)$$

The internal heat transfer area for the coiling coils, $A_{t,in}$, was calculated using

$$A_{t,in} = \pi I.D._t L_t \quad (4)$$

These areas are summarized in Table 3 and are normalized per length of bed.

Table 1. Hydride Bed Dimensions

Bed	Pipe Size (in.)	Pipe Sch.	L_b , Bed Length (in.)	O.D. (in.)	I.D. (in.)	I.R. (in.)	O.R. (in.)
0.5L	1.5	40	15	1.900	1.610	0.805	0.950
0.23L	1.5	80	9	1.900	1.500	0.750	0.950
1.0L	2.0	40	10.5	2.375	2.067	1.0335	1.1875
0.7L	2.0	80	16	2.375	1.939	0.9695	1.1875

Table 2. Hydride Bed Cooling Coil Dimensions

Bed	Tubing Size (in.)	L_t , Tubing Length (in.)	O.D. (in.)	I.D. (in.)	I.R. (in.)	O.R. (in.)
0.5L	3/8	67.2	0.375	0.315	0.1575	0.1875
0.23L	1/4	44.8	0.250	0.190	0.0950	0.1250
1.0L	3/8	111.9	0.375	0.315	0.1575	0.1875
0.7L	3/8	83.9	0.375	0.315	0.1575	0.1875

*Tubing length calculated using Equation 1.

Table 3. Hydride Bed/Cooling Coil Heat Transfer Areas

Bed	$A_{b,ex}$ (cm^2)	$A_{t,ex}$ (cm^2)	$A_{t,ig}$ (cm^2)	$A_{b,ex}/L_b$ (cm^2/cm)	$A_{t,ex}/L_b$ (cm^2/cm)	$A_{t,ig}/L_b$ (cm^2/cm)
0.5L	578	255	429	15.2	6.70	11.3
0.23L	347	113	172	15.2	4.96	7.54
1.0L	505	425	715	19.0	16.0	26.8
0.7L	770	319	536	19.0	7.85	13.2

Liquid Nitrogen Flow Rates

Liquid nitrogen is supplied by a liquid nitrogen Dewar flask fitted with a relief valve set at 22 psig. The dewar is outside the process room containing the hydride beds and tubing passing into the room supplies liquid nitrogen to the beds. As the liquid nitrogen flows through the cooling coil of a bed, it vaporizes and cools the bed. The nitrogen is then exhausted from the cooling coil at atmospheric pressure.

The rate of cooling of a hydride bed is limited by the rate at which nitrogen can be supplied to the hydride bed. The flow rate is limited by the supply pressure of the nitrogen. The maximum flow rate for the nitrogen, and thus the maximum bed cooling rate, was calculated two ways. The first method was to assume the entire flow was liquid nitrogen. The other method was to assume the entire flow was vaporized nitrogen and then compute an equivalent liquid nitrogen flow rate. These calculations are described in the following sections.

Karman Number for Friction Factor Determinations

To analyze flow problems where the loss-work term is known, but the flow rate is not, a parameter called the Karman number is used to obtain the friction factor needed for flow rate calculations³. The Karman number, Λ , is defined as follows:

$$\Lambda = Re\sqrt{f} = \frac{D\rho}{\mu} \sqrt{\frac{lw_f g_c D}{2L}} \quad (5)$$

where Re is the Reynolds number, f is the fanning friction factor, D is the pipe I.D., ρ is fluid density, μ is the fluid viscosity, lw_f is the loss-work due to friction, L the length of pipe, and g_c a unit conversion factor.

The mechanical energy balance written for steady-state flow of an incompressible fluid is

$$\frac{\Delta v^2}{2g_c} + \frac{g}{g_c} \Delta z + \frac{\Delta P}{\rho} + lw_f + \eta_p W_s = 0 \quad (6)$$

where v is the fluid velocity, g is the gravitational constant, ΔP is the pressure drop in the line, η_p is the pump efficiency, and W_s is the shaft-work done by the pump.

The shaft-work and gravity terms can be deleted for this analysis. By neglecting the contribution of the velocity term, the lw_f term is given by

$$lw_f = -\frac{\Delta P}{\rho} \quad (7)$$

The Karman number can then be written as

$$\Lambda = Re\sqrt{f} = \frac{D\rho}{\mu} \sqrt{\frac{\Delta P g_c D}{2\rho L}} \quad (8)$$

Equation 8 is used to calculate the Karman number. By knowing the Karman number and the roughness of the piping, the friction factor can be read from standard charts³ correlating f with the Karman number.

Volumetric Flow Rates

Knowing the friction factor and the pressure drop through the system, the fluid velocity and thus the volumetric flow rate, through the system can be calculated using

$$\frac{\Delta P}{\rho} = N \frac{v^2}{2g_c}, \quad N = 4f \frac{L}{D} \quad (9)$$

where N is the number of velocity heads. For circular pipes, v can be written as

$$v = \frac{4Q}{\pi D^2} \quad (10)$$

where Q is the volumetric flow rate. Using this in the previous the equation, Q is given by

$$Q = \sqrt{\frac{\Delta P \pi^2 g_c D^5}{32 \rho f L}} \quad (11)$$

To distinguish between liquid and vapor flows, subscripts l and v will be used. To calculate liquid flows, Equation 11 is used with physical property values for the liquid. To calculate vapor flows, physical property values for the vapor are used.

For liquid flow rates, Q_l , the properties of liquid nitrogen were taken at its boiling point: -196°C . The density was taken as 0.808 g/cm^3 ⁴ and the viscosity was taken as 0.16 c-Poise ⁵. The length of tubing was taken from Table 2, the internal tubing diameter taken from Table 3, and ΔP was taken to be 22 psi. To get an equivalent vapor flow rate, $Q_{v,eq}$, the liquid flow was converted to a vapor flow using

$$Q_{v,eq} = Q_l \frac{\rho_l}{MW} \frac{22.4 L}{\text{mole}} \quad (12)$$

where MW is the molecular weight of nitrogen.

For vapor flow rates, Q_v , the temperature of the vapor was assumed to be the average of the boiling point of liquid nitrogen and 190°C : the design temperature of three of the hydride beds. The pressure used to calculate the ideal gas density was taken to be 25.7 psia: the average between the relief valve setting and atmospheric pressure. This with the molecular weight of nitrogen gave a gas density of 0.00221 g/cm^3 and the viscosity used was 0.0175 c-Poise ⁶. The same tubing diameters and lengths were used to calculate Q_v as were used to calculate Q_l . Q_v values in L/min. were converted to flows in SLPM.

To convert Q_v to an equivalent liquid flow, $Q_{l,eq}$, the following equation was used:

$$Q_{l,eq} \left(\frac{L}{\text{min}} \right) = Q_v \left(\frac{L}{\text{min}} \right) \frac{\rho_v}{\rho_l} \quad (13)$$

Nitrogen flow rates calculated for a 22 psi pressure drop are summarized in Table 4. Column 2 shows the liquid flow Q_l calculated from Equation 11 while column 3 shows the equivalent vaporized flow through the coil calculated from Equation 12. Similarly, column 4 in Table 4 shows the calculated vapor flow Q_v calculated from Equation 11 while column 5 shows the equivalent condensed liquid flow calculated from Equation 13.

The data in Table 4 show that the maximum vapor flow through the bed tubing, Q_v , is smaller than the vaporized liquid nitrogen flow rate, $Q_{v,eq}$. Q_v sets the upper limit on the flow rate of vaporized nitrogen, and thus liquid nitrogen, through the tubing. The maximum cooling rate of a hydride bed will be limited to the mass flow rate corresponding to $Q_{l,eq}$ for column 5 of Table 4, times the sum of the heat of vaporization for nitrogen and the sensible heat gain of the vaporized nitrogen stream.

Table 4. Flow Rates Through Hydride Bed Cooling Coil for $\Delta P = 22$ psi^a.

Bed	Q_l^b (L/min)	$Q_{v,eq}^c$ (SLPM)	Q_v^d (SLPM)	$Q_{l,eq}^e$ (L/min.)
0.5L	32.1 (0.0039)	20,700	1045 (0.0042)	1.62
0.23L	10.2 (0.0046)	6,610	349 (0.0045)	0.540
1.0L	24.9 (0.0039)	16,100	810 (0.0042)	1.25
0.7L	28.7 (0.0039)	18,600	935 (0.0042)	1.45

^aFanning friction factors shown in parenthesis for the calculated flow rate.^bCalculated using Equation 11.^cCalculated using Equation 12.^dCalculated using Equation 11 and converted to SLPM.^eCalculated using Equation 13.

Maximum Bed Wall Temperature Differential Calculations

To calculate the maximum bed wall temperature difference when a hydride bed is switched from heating to full cooling, a finite difference program was developed to calculate this temperature difference⁷. The parameters and boundary conditions used to calculate the temperature difference are described below.

Initial Conditions

The initial temperature of the hydride bed and its cooling coil was assumed to be at the upper design temperature of the bed. For the 0.5L, 0.23L, and the 1.0L beds, this was 190°C while it was 204°C for the 0.7L bed. At time zero, the liquid nitrogen was assumed to start flowing through the cooling coils. The boundary condition in the cooling coils will be discussed below.

Boundary Conditions

For the bed/cooling coil system, four boundary conditions need to be discussed: the boundary condition at the inside of the bed, the two boundary conditions relating the bed external and cooling coil external temperatures and energy fluxes, and the boundary condition at the inside of the cooling coil.

Internal Bed Wall Boundary Condition

Convective energy transport was assumed to occur between the hydride inside the bed and the internal wall of the bed. The temperature of the hydride material was assumed to be constant and equal to the upper design temperature of the bed. The heat transfer coefficient between the inside of the bed and the wall of the bed was assumed to 10 BTU/hr-ft²-°F (56.7 watts/m²-°C).

The actual value used for the heat transfer coefficient at the inside of the bed did not significantly alter the calculated $\Delta T_{\max}$ values. This occurred because the time at which $\Delta T_{\max}$ occurred was so short that the boundary condition at the inside of the bed wall did not have time to influence inside wall temperature of the bed.

Bed Wall/Cooling Coil Boundary Conditions

At the boundary between the outside of the cooling coil and the bed, the outside wall of the bed and the cooling coil are assumed to be at the same temperatures. The heat transfer areas were taken from Table 3, columns 5 and 6, and used as input to the program⁷.

Internal Cooling Coil Wall Boundary Condition

To determine the boundary condition at the inside of the cooling coils, the maximum heat loaded that could be removed, q , was calculated using

$$q = Q_{l,eq} \rho_l [\lambda + C_{p,v}(T_{wall} - T_{N2})] \quad (14)$$

where λ is the heat of vaporization for liquid nitrogen, $C_{p,v}$ is the heat capacity of gaseous nitrogen, T_{wall} is the cooling coil wall temperature, and T_{N2} is the boiling point of liquid nitrogen. The maximum heat load was converted to an energy flux by dividing q by the heat transfer area taken from Table 3, column 7 and using this boundary condition in the finite difference program subroutine "FFOUT"⁷.

The initial cooling rates calculated using $Q_{l,eq}$ from Table 4 in Equation 14 ranged from over 4300 watts for the 0.23L Bed to over 13,000 watts for the 0.5L Bed. These liquid nitrogen cooling power levels exceed heating power levels generated by nominal 8 Ω electric heaters used in SRTC prototype hydride beds with designs similar to the Tritium Facility hydride beds. By using cooling rates instead of heating rates, "worse-case" ΔT_{max} values will be obtained.

Physical Properties

The physical properties for the material were assumed to be constant. For a stainless steel bed, the thermal conductivity was taken to be 16.26 watts/m-°C (9.4 BTU/hr-ft²-°F/ft), the density used was 7.83 g/cm³, and the heat capacity was assumed to be 0.12 cal/g-°C. For the copper, the thermal conductivity used was 398 watts/m-°C (230 BTU/hr-ft²-°F/ft), the density was taken to be 8.92 g/cm³, and the heat capacity used was 0.0924 cal/g-°C.

Grid Size and Time Step

For the finite difference spacial parameters, the thickness of the hydride vessel wall was divided into 20 equal size elements ($N_b = 20$). For the cooling coils, the wall thickness was divided into 5 equal size elements ($N_t = 5$).

The finite difference time-step size, Δt , was estimated using

$$\Delta t \approx \text{minimum of} \left[2 \frac{\Delta r_b^2}{\left(\frac{k_b}{\rho_b C_{p,b}} \right)}, \quad 2 \frac{\Delta r_t^2}{\left(\frac{k_t}{\rho_t C_{p,t}} \right)} \right] \quad (15)$$

where k , ρ , and C_p have their usual meanings and Δr is the size of the grid spacing. ΔT was rounded to the nearest power of ten to perform the calculations. As will be discussed later, using different grid sizes and time step parameters did not significantly alter the computed results.

$\Delta T_{\max}$ Results

Figure 1 shows the bed wall and cooling coil wall temperatures as a function of time for the 0.5 L bed at $Q_{l,cq} = 1.62$ L.min. As can be seen from this figure, the temperature difference across the wall of the bed appears almost constant shortly after the start of the liquid nitrogen flow and it is difficult to determine when $\Delta T_{\max}$ occurs. Figure 2 shows the bed wall temperature differential and shows the minimum occurs approximately two seconds after the start of the liquid nitrogen flow.

In Figure 3, the lines show $\Delta T_{\max}$ as a function of liquid nitrogen flow rate for the beds. For each bed, $\Delta T_{\max}$ based on $Q_{l,cq}$ from column 5 of Table 4 are shown as symbols in Figure 3. The results shown in Figure 3 were typically obtained in less than five seconds after starting the liquid nitrogen flow.

As stated previously, the allowable $\Delta T_{\max}$ values for the beds as a function of the number of thermal cycles was reported elsewhere². These are $\Delta T_{\max}$ limits are shown in Figure 3 for 1,000; 5,000; and 10,000 thermal cycles. As seen in Figure 3, $\Delta T_{\max}$ values calculated for the beds in this document are well below the $\Delta T_{\max}$ values allowable for a 10,000 cycle limit.

To estimate the service life of a bed with a 10,000 thermal cycle limit, estimates were made on how many times a bed could be

Figure 1. 0.5 Bed We and Tubing Temperatures

Figure 1 (a) Sec We Temperature Differential Versus Time

Figure 3. Hydro Bed With Temperature Differentials

cycled per day. The number of cycles a bed will experience in continuous operation is given by

$$\text{No. of Cycles} = X \frac{\text{cycles}}{\text{day}} \times 365.25 \frac{\text{days}}{\text{year}} \times Y \text{ years}$$

The product of the number of cycles per day, X , and the number of years the bed is operated, Y , for a 10,000 cycle limit is equal to 27.4. For example, if a bed is expected to last five years ($Y = 5$), the bed may experience up to 5 ($X = 5.5$) cycles per day for the entire five years before the 10,000 cycle limit is reached. Use of the bed on a less frequent basis during its service life will guarantee the bed will not exceed its thermal cycle limit.

The effect of grid size for the bed and cooling coils can be seen in Figure 4. Combination of $N_b \geq 10$ and $N_l \geq 5$ give $\Delta T_{\max}$ results of sufficient accuracy. For $N_b = 10$ and $N_l = 10$, $\Delta T_{\max}$ results using Δt ranging from 1×10^{-4} to 0.1 seconds gave results within 0.05°C of one another indicating that Δt calculated from Equation 15 is sufficient for the computations.

CONCLUSIONS

The cooling rates of the hydride bed in the Tritium Facilities is limited by the flow of the vaporized liquid nitrogen through the 22 psi differential. The flow rates calculated were based on an estimated length of the copper cooling coils attached to the beds and did not include other flow limiters such as the nitrogen supply lines between the Dewar flask and the beds or valves in these lines. The flow rates calculated can be assumed to be conservative maximums while actual flows may be lower due to other flow restrictions.

The accuracy of calculating the nitrogen flows is only slightly affected by the ability to read friction factors from the standard charts correlating f versus Λ . The cooling rates calculated from these flows were theoretical maximums since they assumed that the gaseous nitrogen was in thermal equilibrium with the bed as it left the cooling coil. This makes the $\Delta T_{\max}$ values calculated "worse-case" values. Initial cooling energy fluxes calculated using Equation 14 were found to exceed electric heater power densities thus supporting the assumption that "worse-case" $\Delta T_{\max}$ values are obtained during cooling operations.

Figure 4. Effect of Grid Size on 0.5% Bed Results

The $\Delta T_{\max}$ values calculated were based on constant physical properties for the materials. A test computation was made for the 0.5 Liter bed at a $Q_{l,cq} = 1.62$ L/min where the thermal conductivities of the materials were changed by +10% and the heat capacities were changed by -10% of their previously stated values. As might be anticipated, the calculated value of $\Delta T_{\max}$ changed by less than 10%. Using constant physical properties values in the computations does not alter the conclusions of this report.

The finite difference program used to calculate the $\Delta T_{\max}$ values had been previously tested for accuracy. Changes in the number of grid points above reasonable minimums did not significantly alter the computations. Changes in time step size had almost no impact on $\Delta T_{\max}$ results.

The calculations in this report show that $\Delta T_{\max}$ values calculated for flows limited to a 22 psi differential are significantly less than that imposed for a 10,000 cycle limit: less than 50% of this limit. Using the expected life of the bed, the maximum number of thermal cycles per day for the bed can be calculated to determine whether or not the number of thermal cycles a bed experiences need be recorded or logged. If the bed will be used less than its allowable thermal cycle limit, the number of cycles need not be recorded. Not logging or tracking the number of thermal cycles for the beds will greatly reduce the administrative burden of operating these vessels.

END

**DATE
FILMED**

9/20/93