A POSSIBLE FUSION REACTOR

BY

SOICHI YOSHIKAWA

**PLASMA PHYSICS
LABORATORY****MASTER**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

**PRINCETON UNIVERSITY
PRINCETON, NEW JERSEY**

This work was supported by U. S. Energy Research and Development Administration Contract E(11-1)-3073. Reproduction, translation, publication, use and disposal, in whole or in part, by or for the United States Government is permitted.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

Printed in the United States of America.

Available from
National Technical Information Service
U. S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22151

Price: Printed Copy \$ * ; Microfiche \$1.45

<u>*Pages</u>	<u>NTIS Selling Price</u>
1-50	\$ 4.00
51-150	5.45
151-325	7.60
326-500	10.60
501-1000	13.60

A POSSIBLE FUSION REACTOR

by

Shoichi Yoshikawa

Plasma Physics Laboratory
Princeton University
Princeton, New Jersey 08540

ABSTRACT

A scheme to improve performance characteristics of a tokamak-type fusion reactor is proposed. Basically, the tokamak-type plasma could be moved around so that the plasma could be heated by compression, brought to the region where the blanket surrounds the plasma, and moved so as to keep wall loading below the acceptable limit. This idea should be able to help to economize a fusion reactor.

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Energy Research and Development Administration, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

In designing a fusion reactor, it is useful to have many options so that the cost associated with a successful reactor can be minimized. One of the factors is the possibility of moving a plasma in a reactor chamber, which is, so far, ignored in various design studies.

The configuration we discuss here is shown in Fig. 1. This is one of various possibilities, as detailed engineering studies are necessary to find an optimum configuration. The idea of this scheme is to separate the location where plasmas are formed and the location where the plasma undergoes the D-T reaction. This way, we can efficiently utilize the tritium breeding blanket and minimize the escape of neutrons through the holes.

Initially, the tokamak plasma is formed at location A with ohmic heating, with subsequent auxiliary heatings such as neutral beam injection and/or rf. The temperature of the plasma at A may be less than 5 keV, so that the D-T reaction rate may not be too high. Alternatively, the D-T reaction may be completely eliminated here by using pure deuterium plasma at this point. Then, using the vertical and horizontal fields, the plasma is brought to location B. At this point, because the major radius is reduced,¹ the temperature can be increased to 8~10 keV and D-T reaction starts. Hopefully, the ignition condition could be achieved. If pure deuterium plasma is used at A, at this point tritium can be injected. The ohmic heating current and the plasma position may be maintained by the set of coils which provide vertical and horizontal fields.

Two shutters made of lead may be closed (with time constant of 1 to 2 sec.) while the plasma is at B. The shutters may be perforated to allow pumping while keeping neutrons reflected away. The plasma can be moved vertically up and down so that neutron flux can be distributed approximately equally on the vacuum wall. This way, we can control the wall loading within the material limit. After several hundred seconds, when the ohmic heating current can no longer be maintained, the plasma can be moved to C where the plasma is extinguished. A new plasma is formed at this time in A and the whole cycle repeated.

There are a number of advantages in this scheme. They are:

1. Better Utilization of Neutrons

As the plasma is heated in location A, at B there will be no holes for neutron injection, etc.

Therefore, neutron economy will be improved.

2. Control of Wall Loading

By moving the plasma up and down, wall loading could be controlled. This way, we may be able to build a reactor with smaller radius and greater plasma density.

3. Better Aspect Ratio

Since the ohmic heating coil to start up the plasma is not located at B, the aspect ratio can be improved.

4. Reduction of Auxiliary Heating Requirements

Since compression takes up heating by perhaps a factor of two or more, the auxiliary heating

requirement such as neutral injection is reduced at least by that factor. (Note that ohmic heating is more effective at lower plasma temperature.) Furthermore, since the ratio of the density before and after compression is inversely proportional to C^2 where C is the major radius compression ratio, and the plasma radius ratio is proportional to $C^{1/2}$, the line density is proportional to $C^{-3/2}$. This means that neutral injection can penetrate more at A than at B. This should make it easier to inject a lower energy neutral beam.

5. Compression and Decompression

Plasma compression is a quite effective way of raising the plasma pressure, and since the plasma could be moved to location C to be decompressed, energy could be recovered as an electric power, including the energy of α -particles.

6. Improvement of the Duty Cycle

Since the plasma formation chamber is different from the D-T reaction chamber, chamber A can be pumped while the plasma is at B or C. Thus, the next plasma could be formed to be ready to be injected as soon as chamber B is cleared. Besides, either chamber A or C can be used as a vacuum pump, depending upon how pumping proceeds in these chambers.

7. Assembly-Disassembly

Since the blanket can be made without many holes penetrating it, the disassembly and assembly should not be too difficult. Neutral injectors and other heating equipment may not have too much difficulty with neutrons and radiations as the plasma is not reacting at A.

8. Plasma Shutdown and Vacuum Wall Protection

Since plasma energy is taken away by decompression, the energy remaining in the plasma for shutdown is low. Thus, the problem associated with the shutoff should be less. Besides, the burial chamber C wall can be made thick enough to absorb any heat load.

9. Reduction in Peak Power Need for Startup

Since the spent plasma is dumped when the next plasma is about to start up, energy recovered from the first plasma can be directly coupled to the second plasma. This way, it should be possible to reduce the peak power requirement during the plasma startup.

There may well be other advantages, but this scheme, of course, has drawbacks.

They are:

A. Plasma Handling

Since the plasma must be moved, this requires more complicated controls; however, experiments indicate that this could be accomplished.²

B. Toroidal Field Coil

The energy associated with the toroidal field coil is increased and this, of course, requires more cost. But it seems that the various advantages probably outweigh this disadvantage.

VARIATION

A somewhat less elaborate scheme may be more useful for a reactor if the increase in magnetic field energy and vacuum volume turns out to be too expensive. In this case, the plasma does not undergo compression and decompression but is moved vertically in an elongated vacuum vessel. The neutral injectors may be placed on one part of the side wall (see Fig. 2). Once the plasma is formed, it is moved to the region surrounded by blankets; of course, it could be moved gradually to reduce wall loading, if desired.

The effectiveness of this scheme could be calculated. The solid angle seen from the center of the plasma was calculated assuming that the aspect ratio $R/a \rightarrow \infty$, i.e., for a straight rectangular vacuum vessel. For the case where the full side wall was used for locating the neutral injection port, f , the fraction of solid angle as a function of p , is expressed as

$$f = 2 [G(1 + p) + G(1 - p)]$$
$$G(x) \equiv \frac{1}{\pi} \sin^{-1} \left(\frac{x^2}{1 + x^2} \right)^{1/2}$$

and p is the added vacuum height in unit of the plasma radius.

In the case of the half side wall, the fraction is given as

$$f = 2 - 4 [F(1+p) + G(p)]$$

with

$$F(x) \equiv \frac{1}{\pi} \cos^{-1} \left(\frac{x^2}{1+x^2} \right)^{1/2}$$

The fractions are plotted vs. $h (\equiv 1+p)$ in Fig. 2. It can be seen from Fig. 2 that the neutron flux impinging on the region where the neutral injectors are located could be cut by a factor of three or more with a moderate elongation of the vacuum vessel.

CONCLUSIONS

The advantages outlined here seem to be good enough to seriously consider this scheme for an experimental power reactor (EPR) or an eventual reactor. As prediction of the reactor size is dependent so much on the plasma scaling law, etc., it is difficult to formulate. But it may be possible to reach $n\tau = 2 \times 10^{14}$ at $n = 2 \times 10^{14}/\text{cc}$ $\tau = 1$ sec. with a (plasma radius) = 1.5 m. If the aspect ratio can be made to $R/a = 2.5$, and if $\beta_p = 2$, $q = 2.5$ is possible; this amounts to $\beta \approx 5\%$. Thus, if $T_i = T_e = 10$ keV, $B = 60$ kgauss is sufficient to keep this plasma. The thermal output of this reactor for $n_D = n_T = 10^{14}$ is $\approx 9 \times 10^8$ w th.

ACKNOWLEDGMENT

This work was supported by U. S. Energy Research and Development Administration Contract E(11-1)-3073.

REFERENCES

- [1] FURTH, H. P. and YOSHIKAWA, S., Phys. Fluids 13, 2593 (1970).
- [2] BOL, K., ELLIS, R. A., EUBANK, H., FURTH, H. P., JACOBSEN, R. A., JOHNSON, L. C., MAZZUCATO, E., STODIEK, W., and TOLNAS, E. L., Phys. Rev. Letters 29, 1495 (1972).

Fig. 1. Scheme of a reactor. The plasma is produced at A and goes through B to C.

763238

MODEL CALCULATION FOR RECTANGULAR CROSS SECTION III (FULL SIDE WALL)

763372

Fig. 2a. The fraction of the neutron loss flux through the neutral injector hole as the plasmas are lowered. Inserts show the location of the neutral beam injector (hatched area) and the size of the vacuum vessel. ($R/a \rightarrow \infty$). Neutral injectors are distributed at the full side wall. Here, $h \equiv 1+p$; p is defined in the text.

MODEL CALCULATION FOR RECTANGULAR CROSS SECTION II (HALF SIDE WALL)

763373

Fig. 2b. The fraction of the neutron loss flux through the neutral injector hole as the plasmas are lowered. Inserts show the location of the neutral beam injector (hatched area) and the size of the vacuum vessel. ($R/a \rightarrow \infty$). Neutral injectors are distributed at the upper half of the side wall. Here, $h \equiv 1+p$; p is defined in the text.