COO-2781-2

FUEL COOLANT THERMAL INTERACTION PROJECT

UC 79P

Massachusetts Institute of Technology
Departments of Nuclear and Mechanical Engineering

Quarterly Progress Report No. 2

October 1, 1975 - December 31, 1975

MASTER

Approved March 1976

Neil E. Todreas
Principal Investigator

CONTRACT NO. E(11-1)-2781
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED
DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED *ep*

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Reports and Papers Published Under
MIT Fuel-Coolant Interaction Project

(This Project was funded until June 30, 1975 by ANL and reports issued as 31-109-38-2831-XX; Starting July 1, 1975 reports were issued as COO-2781-XX.)

Progress Reports (Available from National Technical
Information Service, U.S. Department
of Commerce, Springfield, Va. 22151)

W. F. Lenz, G. Shiralker, and N. Todreas, Fuel Coolant
Thermal Interaction Project UC 79P, COO-2781-1, Nov. 1975.

W. F. Lenz, G. Shiralker, and N. Todreas, Fuel Coolant
Thermal Interaction Project UC 79P, COO-2781-2, Feb. 1976.

Topical Reports (Available from National Technical
Information Service, U.S. Department
of Commerce, Springfield, Va. 22151)

Mujid, S. Kazimi, "Theoretical Studies on Some Aspects of
Molten Fuel-Coolant Thermal Interaction," 31-109-38-2831-1 TR,
MITNE-155, May 1973.

Charles E. Watson, "Transient Heat Transfer Induced Pressure
Fluctuations in the Fuel-Coolant Interaction" 31-109-38-
2831-2 TR, MITNE-156, August 1973.

Trond A. Bjornard, "An Experimental Investigation of Acoustic
Cavitation as a Fragmentation Mechanism of Molten Tin
Droplets in Water," 31-109-38-2831-3 TR, MITNE-163, May 1974.

Glen M. Bjorkquist, "An Experimental Investigation of the
Fragmentation of Molten Metals in Water," 31-109-38-2831-4 TR,
June 1975.

Roland B. Knapp, "Thermal Stress Initiated Fracture as a
Fragmentation Mechanism in the UO_2 -Sodium Fuel-Coolant
Interaction," 31-109-38-2831-5 TR, May 1975.

Papers and Summaries

M. S. Kazimi, N. E. Todreas, D.D. Lanning and W.M. Rohsenow, "A Criterion for Free-Contact Fragmentation of Hot Molten Materials in Coolants," Transactions of the American Nuclear Society, Vol. 15, No. 2, p. 835, November 1972.

M. S. Kazimi, N. E. Todreas, W. M. Rohsenow and D.D. Lanning, "A Theoretical Study of the Dynamic Growth of a Vapor Film Around a Hot Sphere in a Coolant," Fifth International Heat Transfer Conference, Tokyo, 1974.

T. A. Bjornard, W.M. Rohsenow and N.E. Todreas, "The Pressure Behavior Accompanying the Fragmentation of Tin in Water," American Nuclear Society Transactions, Vol. 19, pp. 247-249, 1974.

R. Knapp and N. Todreas, "Thermal Stress Initiated Fracture as a Fragmentation Mechanism in the UO-Sodium Fuel-Coolant Interaction," Nuclear Engineering and Design 35 (1975) 69-85.

Introduction

The objective of the continued work on this project at M.I.T. is to experimentally and analytically study the dominant mechanisms in fuel coolant thermal interactions which could lead to vapor explosions. Our exploration of mechanisms is focused in two areas:

- a) Mechanisms responsible for fragmentation in molten metal droplet experiments (here we will include assessment of the validity of the proposed Spontaneous Nucleation Mechanism),
- b) Thermal Stress Initiated Fracture as a fragmentation mechanism (this mechanism is not considered responsible for the fragmentation of molten metal drops - see Knapp's work).

Work is being performed in both these areas simultaneously and will be briefly described below.

I. Mechanisms Responsible for Fragmentation
in Molten Metal Droplet Experiments
(Gautam Shiralkar)

A. Gas Solubility Hypothesis

The primary effort in this task is to assess the validity of gas solubility hypothesis proposed by M. Epstein¹.

Preliminary experiments of tin heated in prepurified nitrogen gas (99.98% pure) in as short a time as possible (less than a minute) and dropped into water, indicated fragmentation similar to those experiments using air as an atmosphere.

It is believed, however, that water vapor coming off the furnace walls and present as an impurity in the nitrogen could be responsible since it is possible for this gas to become dissolved in the tin during the required heating time.

To overcome this problem, design of an experiment whereby the heating could be carried out in a vacuum was undertaken. At the time of writing, the apparatus is ready and in working condition, suitable for dropping molten metal into cold liquids with low vapor pressure at ordinary (room) temperature. An adjustment will be made shortly to enable dropping metal into coolants with higher vapor pressure, such as water and a series of experiments will be initiated to check the hypothesis.

¹Epstein, M., "Thermal Fragmentation--Gas Release Phenomenon", Nuclear Science & Engineering, Vol. 5, pps. 462-467. 1974.

B. Magnitude of the Pressure Pulses during Fragmentation

An experimental check was made of the formula relating the amplitudes of pressure traces recorded on tape, by a transducer placed some distance away in the water from the drop entry, to the amplitude of the pressure extrapolated to the drop surface.

This formula is:

$$P_d = P_t(d/r)$$

where P_d - pressure at drop surface

P_t - pressure recorded by transducer

d - distance of transducer from drop
at time of interaction

r - radius of drop.

The experiment was run using two recorders and two transducers simultaneously. The results indicate a fairly wide scatter around the values predicted by the above equation.

A simple calculation indicates that reflections of the pressure waves from the container sides should not be a problem. The consistency of the pressure traces also supports this view. This discrepancy will be investigated further in case check of future hypotheses are sensitive to the numerical magnitude of the pressure at the drop surface. However, the consistency of the interaction characteristics together with the important difference between pressure traces from liquid

versus initially solid drops (which identify the "bigbang" as particular to liquid drops) indicate the value of even the qualitative pressure results of recordings.

II. Thermal Stress Initiated Fracture

(W. Fred Lenz)

At the November meeting at Argonne, the direction of the work being carried out at MIT on this aspect of the fuel coolant interaction program was shifted somewhat. Before the meeting, the work was directed towards carrying thru a mechanistic approach based upon the thermal stress mechanism to determine the final particle size distribution. The current work considers the thermal stress mechanism as a mechanism that may be shown to limit the rate of a fuel coolant interaction thus demonstrating why an energetic reaction is seen not to occur in most experiments carried out with UO_2 and Na.

The reason for this shift in direction was due to several factors. First of all, it was recognized by the meeting participants that a purely mechanistic approach based on following cracks as they grow and fork, represents a very complicated task. Secondly, due to wide range of experimental results, almost any final particle size determined by a mechanistic approach could be supported by experimental data.

In our effort to investigate the thermal stress mechanism as a limiting process, we will investigate those physical phenomenon which limit the stress induced fragmentation. Much of the work for this period has involved the development of computer codes to study one of these phenomenon, the effect of the solidification under various possible boundary condition assumptions. It is hoped that from study of these phenomena, small time scales for heat transfer in a fuel coolant interaction can be neglected as physically impossible resulting in lower expected interaction work energies.

The ANL fuel coolant interaction computer model written by Cho, et al., will be used to generate curves of constant work energy as a function of the mixing time constant and the final particle size with assumed parameters that will represent what is believed to be the worst case situation in the FFTF. Once this is accomplished, the results of solidification limited process will be used to effectively cut out certain areas of the graph that are physically impossible.

In an effort to establish if the stress induced fragmentation mechanism is capable of producing a particle size distribution found in the molten fuel-coolant experiments to date, some analyses will also be performed to determine if the stress levels in the solidifying fuel material are sufficient to produce characteristic particle sizes. This work

should show the smallest particle size possible thereby verifying that the thermal stress induced fragmentation mechanism is capable of producing fragments within the final observed particle size distribution.