DOE/CE/15440--T5

DOE/CE/15440--T5

DE92 018709

Sponsored by
U.S. Department of Energy
Office of Energy Related Inventions

FINAL TECHNICAL REPORT

9 July 1992

Identification Number: 90CE15440

Program/Project Title: Microtube Strip Heat Exchanger

Doty Scientific, Inc.
700 Clemson Rd.
Columbia, SC 29223

(803) 788-6497

F. David Doty, Principal Investigator

"The views and conclusions contained in this document are those of the authors and should not be interpreted as representing the official policies, either express or implied of the Department of Energy of the U.S. Government."

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

INTRODUCTION

The purpose of this contract has been to explore the limits of miniaturization of heat exchangers with the goals of (1) improving the theoretical understanding of laminar heat exchangers, (2) evaluating various manufacturing difficulties, and (3) identifying major applications for the technology.

A low-cost, ultra-compact heat exchanger could have an enormous impact on industry in the areas of cryocoolers and energy conversion. Compact cryocoolers based on the reverse Brayton cycle (RBC) would become practical with the availability of compact heat exchangers of the type we have been developing.

Many experts in computer systems believe that hardware advances in personal computer technology will rapidly slow down in four to six years unless low-cost, portable cryocoolers suitable for the desktop supercomputer can be developed. Compact refrigeration systems would permit dramatic advances in high-performance computer work stations even with "conventional" microprocessors operating at 150 K, and low-cost cryocoolers below 77 K could enable even more dramatic advances using high temperature superconductors. The chairman of the Federal High Performance Computing Program, Paul Huray, has expressed enthusiastic interest in this cryocooler application. NASA has also expressed strong interest in our MTS exchanger for space-based RBC cryocoolers for sensor cooling.

To help put the potential of RBC refrigerators into perspective, it should be noted that while the cold-head of available Gifford-McMahon cryocoolers may be quite small, it is attached via high pressure hoses to a massive, noisy compressor. On the other hand, a complete RBC cryocooler suitable for a desktop supercomputer could fit easily into the standard desktop computer cabinet and run silently. We have been making suitable RBC microturbine expanders (for other applications) for several years now; suitable microturbine compressors are under development; but the system will not materialize without advances in compact heat exchangers of the type investigated in this study.

Major applications for compact heat exchangers were also identified in recuperated gas turbines for applications ranging from automobiles to ships and planes. The modular approach we have taken appears to offer advantages over the standard alternative - the rotating ceramic honeycomb regenerator. The advantages and drawbacks are discussed in some detail elsewhere.

CeramPhysics, a small company developing solid state oxygen generators, plans to begin producing oxygen generators for space-based systems this fall incorporating our microtube exchanger. Many additional applications for ultra-compact heat exchangers would also exist if sufficiently low-cost manufacturing techniques could be developed.

During the course of this project, we have developed a more realistic appreciation for the complexity of the various steps involved in the manufacture of our microtube exchanger. We now have a more accurate under-

standing of the practical limits to miniaturization and the cost of developing an automated manufacturing process.

Heat exchanger design always involves a compromise between at least three objectives: maximizing the heat exchanger effectiveness; minimizing the work required to overcome fluid friction in the heat exchanger; and minimizing the manufacturing and material costs of the exchanger. Often a fourth objective, minimizing the heat exchanger mass, is crucial. In the past the third objective has pushed design in the direction of high turbulence heat exchangers, to take advantage of the high heat transfer coefficient associated with turbulent flow. But with respect to the first two objectives this is a poor choice: turbulent flow extracts a disproportionately high penalty in pumping work.

We are addressing applications in which the fourth objective - minimizing mass - is of paramount importance. Hence, we define a critical parameter to be maximized: specific conductance, or power density. We define specific conductance (W/kgK) as the exchange power per mean degree difference of the counterflowing streams per exchanger mass for a laminar flow gas. We show elsewhere that this parameter is essentially independent of both flow velocity and pressure for fully laminar conditions. For normalized comparisons by simple laboratory techniques, we use helium gas at 350 K. The specific conductance then scales linearly with the gas thermal conductivity, which generally is proportional to the two-thirds power of temperature. Although specific conductance has not customarily been reported in the literature, we deduce that the best prior compact recuperators achieve normalized specific conductance near 60 W/kgK , and typical values for compact exchangers have often been below 10 W/kgK . Our prototypes show that at least 300 W/kgK is practical, and we expect some further improvements will be possible.

Deriving laminar flow heat transfer theory with the perspective of modern manufacturing technology has resulted in two theoretical conclusions along with a technologically revolutionary design concept. Specifically, (1) An optimum heat exchanger must have fully laminar and extremely low velocity flow - typically 2% of the speed of sound; (2) The flow path length should be minimized, subject to the constraints of manufacturability, flow uniformity, and longitudinal conduction losses; (3) Precision micro-tubing, under 0.7-mm outside diameter and 200-mm length, can be automatically assembled to produce low cost heat exchangers with 5 to 30 times the specific conductance of current, compact designs. By taking advantage of modern manufacturing techniques, heat exchanger designs which were impossible to produce at the time current design practices evolved are now potentially feasible, but some manufacturing practices must be pressed somewhat beyond the current state of the art.

Figure 1. Schematic representation of the counterflow MTS module.

THE MICRO-TUBE STRIP (MTS) HEAT EXCHANGER DESIGN

Both the viscosity and the specific heat of a gas are essentially independent of the static pressure. Thus, it is desirable to operate at high static pressures (1 to 5 MPa) to minimize flow velocities for low pumping losses. Mechanical stress considerations clearly dictate a tubular design.

The primary feature of our work that allows order-of-magnitude increases in specific conductance is the understanding (not novel, but often forgotten) that the heat exchange capacity of a tube under laminar flow conditions is independent of the tube diameter and gas velocity.

We approached the analysis of the counterflow gas-to-gas MTS module as shown in Figures 1 and 2 as follows. Assume that the thermal conductivity of the tube material is large compared to the thermal conductivity of the gas (this is easily the case for all gases, even for hydrogen). The heat transfer power W_x for this module under laminar flow conditions can be shown to be¹

$$W_x = 4\pi n L k_1 k_2 T_\delta / (a k_1 + b k_2), \quad (1)$$

where k_1 and k_2 are the thermal conductivities (W/mK) of the inner (tube-side) and outer (shell-side) gases respectively, n is the number of small tubes of length L , T_δ is the mean temperature difference between the counter-flowing streams, and a and b are dimensionless coefficients on the order of unity that are functions of tube inner and outer diameters and tube spacing. For tube inner diameter d and tube centers spaced $2d$ with tube wall $w = 0.2d$, a is approximately 0.7 and b is unity. We will assume these geometric relationships and will assume $k_1 = k_2$.

The tube-side pumping power loss W_p can be expressed in terms of the tube-side mass flow rate G (kg/s) or velocity v (m/s) as follows:

$$W_p = 128\mu L (G/\rho)^2 / (n\pi d^4) = 8\pi\mu n L v^2, \quad (2)$$

Figure 2. A typical stainless steel counterflow heat exchanger module as shown (without counterflow shell) contains 408 parallel microtubes, each 150 mm long, with 0.55-mm outside diameter and 0.8 mm between centers.

It is straightforward to show that the pumping power W_p is proportional to $v^2 W_x / T_\delta$, where v is the flow velocity, W_x is the heat exchange power, and T_δ is the mean temperature difference between counterflowing streams. As the tube diameter is reduced, the velocity must be kept small by increasing the number of parallel tubes by the square of the diameter ratio. The tube length and the total exchanger volume are reduced by the same factor (d_2^2/d_1^2) to maintain constant thermal and pumping powers.

In most cryogenics and power generation applications, it is critical that high effectiveness be achieved. This further imposes the requirements of (a) low longitudinal conduction losses and (b) uniform flow - both shell-side and tube-side.

As the tube length L is reduced, the longitudinal thermal conduction loss of the tube metal from the hot end to the cool end becomes more significant. It is predominately this loss mechanism which establishes the theoretical limit to specific conductance (by limiting minimum tube diameter) in high efficiency counterflow exchangers. For 95% effectiveness in a typical stainless steel helium recuperator between 300 K and 700 K, the minimum tube length is about 140d. For 99% effectiveness between 10 K and 50 K, the minimum tube length is about 1000d. It is desirable to minimize d until pumping power losses and axial conduction losses become unacceptable. To facilitate uniform shell-side flow, it is necessary to depart from the disc shaped header tubesheet normally used in shell-and-tube heat exchangers and instead to use a rectangular header tubestrip with fewer than ten rows of tubes as shown in Figure 1. Thus, we refer to the design as the Micro-Tube Strip, or MTS, design. Uniform tube spacing is maintained by including several spacer strips with triangular holes to position the tubes while allowing adequate shell-side flow around the tubes. Shell-side flow enters in cross-flow fashion between the headers and is then turned and constrained to flow axially over the tubes before exiting in like manner. The resistance to cross flow is much lower than the resistance to longitudinal flow. Hence, uniform shell-side axial flow is quickly established, and highly uniform counterflow conditions exist over about 90% of the tube length.

A more detailed discussion of the theory and some experimental data may be found in the two papers appended to this report.

MANUFACTURING PROCESS DEVELOPMENT

As the manufacturing processes and experiments are described in detail in the references, only a brief overview of some of the work is reported here.

For a stainless-steel heat exchanger with helium as the working fluid at 1 MPa, operating between 400 and 1000 K, the theoretical lower limit on the tube inner diameter can be shown to be approximately 0.2 mm for 5% total losses (the sum of pumping power and longitudinal conduction) and the theoretical limit is even smaller for a cryogenic recuperator. However, there are very real manufacturing problems that limit the minimum practical tube outside diameter to approximately 0.6 mm.

The most important experiment in the past year was one that failed. We found it impossible to achieve the effectiveness we had expected as we reduced the spacing aspect ratio β (microtube center-to-center spacing divided by microtube outside diameter) from 2 to 1.4 for tube diameters below 0.6 mm. Subsequent analysis suggested that we could expect manufacturing stochastic effects to generate maldistribution at least proportional to $\beta/(\beta-1)^3$, which gives a factor of 11 for the above reduction in β . This was roughly in agreement with our experiments, where we saw minimum flow maldistribution of about 2% for $\beta=2$ and over 20% for $\beta=1.4$.

We must keep in mind that the major motivation for the project is not high effectiveness ϵ but rather high specific conductance (SC) - heat transfer per mass per temperature difference, W/kgK. As long as flow maldistribution, relative pressure drops, and axial conduction losses are small compared to $1-\epsilon$, specific conductance alone determines the mass of a laminar-flow exchanger for any given application. Furthermore, under such conditions, exchanger mass is inversely proportional to $1-\epsilon$. When effectiveness above 95% is required, it is generally necessary to connect several modules in series with mixing stations between them.

It now appears that the practical limit to normalized specific conductance (helium-to-helium at 350 K) with our microtube design is about 400 W/kgK, which is a factor of six higher than the best aerospace-grade high-temperature recuperators (to our knowledge) and a factor of 20 higher than typical compact exchangers currently available.

The sharp increase in flow maldistribution as β decreases negates the specific conductance advantage of small β . It appears that optimum β will always be greater than 1.8 - and greater than 2.3 for applications with low shell-side pressure. This makes it possible to achieve extremely uniform tube spacing by including several spacer sheets without adding excessive shell-side flow constriction. The increased tube spacing also simplifies two major manufacturing problems - the tubestrip fineblanking and array encapsulation (required for support while pressing the tubestrips onto the tubes).

Diffusion-Welded Tube-to-Tubestrip Joints. The high level of success we achieved initially with 0.64-mm tubes on 1.3-mm spacings was not replicated when we dropped to 0.57-mm tubes on 0.8-mm centers. We attribute the unacceptable leak rates of the latter experiments to (1) out-of-roundness in the holes from tubestrip distortion and (2) highly variable interference from improper tube finishing. The fineblanking subcontractor had expected roundness problems, since minimum web thickness between holes was only 0.23 mm and the tubestrip thickness was 0.4 mm. More experiments are required to determine the minimum ratio of web to strip thickness, but a ratio greater than 1.4 has been shown to be satisfactory, and values approaching 1.1 may work.

The major contributor to the failures in recent diffusion-welding experiments was inadequate control over tube length and the electrochemical chamfering of the tube ends. Minor changes in the mold and pressing fixturing allow relaxed tube length and chamfer tolerances. At the same time, minor changes in tube finishing processes can achieve higher precision. Hence, this problem appears easy to solve.

One possible method of addressing many difficult manufacturing problems simultaneously would be to substitute laser welding for diffusion welding. This obviates the need for the interference fit and its requirements of superprecision fineblanking and fusible alloy encapsulation. However, it would require superprecision machine vision to compensate for thermal expansion during the welding process, and laser welding is a much slower process that would add to the welding cost but would reduce other complications.

Fineblanking limitations. To prevent die rupture in the high-density pattern (408 0.57-mm diameter holes on 0.8-mm centers) it was necessary to resort to a multiple-hit approach. Five strokes punched sixteen groups of five holes for a total of 80 holes per stroke. The pattern was such that no nearest-neighbors were punched in the same stroke. When the pattern was repeated five times, it completed 400 closely spaced holes with four holes missing at each end. A final hit with a separate punch was required to punch these eight holes.

Although the multiple-hit technique was not able to achieve the hole location accuracy that had been expected (partially because of part growth and partially because of die play), its positioning accuracy of ± 0.03 mm appears to be adequate from the perspective of tube alignment. However, the hole distortion problem is worsened, making it impossible to obtain leak-tight diffusion welds - at least with small β .

Whether or not the multiple-hit technique would work with β greater than 2 is still in doubt for another important reason. Even with the most precise blanking, small breakout burrs are produced on the back side of the hole. With the multiple-hit technique, these burrs get pressed back into the hole on a subsequent hit. Electrochemical deburring is extremely difficult to control sufficiently to maintain hole size tolerances because of the unavoidable variability in the burrs that results from the variable number of hits experienced by the different burrs. Mechanical deburring using

multiple, high-speed micro-spindles may be a satisfactory alternative. The substantial die cost savings afforded by the multiple-hit technique suggests that further development will be supported at some point in the future using multiple-spindle mechanical deburring of tubestrips with β greater than 2.

The fineblanking subcontractor, SFB, does not believe single-hit dies can be built for β less than 2 with hole sizes in the 0.62 to 0.68-mm range. The greater the number of rows of holes, the thinner the tubestrip material (or the lower its shear strength) must be to avoid die rupture. Experiments with five rows of 0.64-mm holes on 1.3-mm centers were successful for Haynes alloy 230 (shear strength 600 MPa, R_B hardness 93) 0.4-mm thick. During experiments on 0.56-mm-thick Haynes C-22 (shear strength 550 MPa, R_B hardness 90), punch pins failed but the die survived. The die and the pins were made from either tool alloy M-2 or M-42. Several tool steels (especially T-15) offer higher strength and hardness but at increased grinding difficulty.

When additional funding becomes available, the next work will be with a 1000-hole, single-hit die, suitable for production. We will begin by punching a large number of tubestrips from soft, 0.35-mm-thick SS304 before risking the dies on heavier and harder materials. The most promising option for the harder materials is a sequential-shearing technique that uses a complete set of holes with pins of various lengths so that they penetrate the material at different times during the stroke. It appears that this technique will be limited only by the strength of the pins and will permit punching strips of thickness comparable to the minimum web dimension or hole diameter, whichever is smaller.

Tube Array Encapsulation. Pressing the tubestrips onto the tubes in interference fit sufficient for effective diffusion welding has only been possible consistently when the tubes were completely encapsulated (except near the ends) in a fusible alloy to prevent tube flexing. Reducing the tube clearance from 0.66 mm in the initial modules to 0.23 mm in the latter work greatly complicated this process. The vacuum injection technique still produced satisfactory encapsulation, but the molten alloy had to be much cleaner to allow free flow between the tubes.

Major problems arose during removal of the potting material following the pressing operation. Melting under boiling water with ultrasonic vibration removed less than 80% of the material. Acid etching was not effective in removing this material without mechanical assistance in the form of manual scraping. Substantial amounts of potting alloy and presumably insoluble oxides and hydroxides of the potting constituents from reactions with the acid etch bath remained trapped between the tubes. Careful cleaning of the molten alloy by filtering through ceramic frits prior to vacuum injection did not solve this problem. Coating the tubes with a release agent (WD-40 spray oil) helped to some extent, but it appears that the source of the problem is fundamentally related to the surface tension of the alloy and the tube spacing dimensions. The alloy removal problem is relatively easy with tube clearances of 0.66 mm, but it is a show-stopper at 0.23 mm. Hence, we began investigating alternatives.

Several tubestrip pressing experiments with 100-tube modules of 0.64-mm tubes on 1.3-mm centers gave promising results without alloy encapsulation. Seven tube-spacer forms along the tube length prevented flexing during pressing when tube finishing and hole chamfering were optimum. We are not presently optimistic about achieving consistent diffusion welds without the use of the potting metal because of the much tighter tolerance requirements with the dry method, but some further work will be supported in an effort to eliminate the complex potting and cleaning process. One approach being studied is laser welding in place of diffusion welding, as discussed previously.

CONCLUSIONS

- * We have demonstrated feasibility of higher specific conductance by a factor of five than any other work in high-temperature gas-to-gas exchangers.
- * These laminar-flow, microtube exchangers exhibit extremely low pressure drop compared to alternative compact designs under similar conditions because of their much shorter flow length and larger total flow area for lower flow velocities.
- * The design appears to be amenable to mass production techniques, but considerable process development remains.
- * The reduction in materials usage and the improved heat exchanger performance promise to be of enormous significance in advanced engine designs and in cryogenics.

BIBLIOGRAPHY

- F. D. Doty, G. S. Hosford, and J. B. Spitzmesser, Trans. Seventh Symp. on Space Nuc. Power Sys., "MTS Heat Exchangers for Space Power", NM (1990).
- F. D. Doty and J. D. Jones, Proceedings, IECEC-90, "A New Look at the Closed Brayton Cycle", (1990).
- F. D. Doty, G. Hosford, J. D. Jones, and J. B. Spitzmesser, Proceedings, IECEC-90, "A Laminar Flow Heat Exchanger", (1990).
- F. D. Doty and J. D. Jones, Heat Transfer Engr., 12, 3, "The Micro-Tube Strip Heat Exchanger", (1991).
- F. D. Doty, B. L. Miller, G. S. Hosford, D. G. Wilson, W. Huanbo, and J. D. Jones, Proceedings, IECEC-91, "High Efficiency Microturbine Technology", (1991).

F. D. Doty, G. S. Hosford, J. B. Spitzmesser, and J. R. Bittner, to appear in Adv. in Cry. Engr., "An Ultra-Compact, Laminar-Flow Cryogenic Heat Exchanger", presented June, 1991, CEC, Huntsville, AL.

F. David Doty and J. B. Spitzmesser, Proceedings, XVIIIth International Congress of Refrigeration, "Progress in the Development of a Manufacturing Process for a Compact, Laminar-Flow Cryogenic Heat Exchanger", Montreal, (August, 1991).

U. S. Patents

F. D. Doty, "Microtube-Strip (MTS) Heat Exchanger," 4,676,305 (1987)

J. B. Spitzmesser, R. J. Cameron, F. D. Doty, and B. L. Miller, "Method of Assembling Tube Arrays, 4,896,410 (1990).

J. B. Spitzmesser and F. D. Doty, "MTS Surface Exchangers," 4,928,755 (1990).

F. D. Doty, G. S. Hosford, and J. B. Spitzmesser, "Microtube Array Space Radiator," pending.

Recently Submitted Proposals

U.S. Army, SBIR A91-191. Solicitation for compact, light-weight heat exchangers for aircraft gas turbine engines.
Proposal Title: Micro-Tube Recuperators for Aircraft Brayton Cycle Engines.

NASA, SBIR 11.12. Solicitation for advanced space propulsion concepts.
Proposal Title: Ultra-Compact Exchangers for Closed-Loop Nuclear Thermal Propulsion.

NIST ATP 91-01. Concepts likely to have broad industrial significance.
Proposal Title: Low-Cost Manufacture of High-Performance Universal Heat Exchangers.

END

**DATE
FILMED
9/28/92**