DOE/PC/91297--3

DE92 017973

DOE/PC/91297-13

Quarterly Technical Progress Report

(March 1, 1992 to May 31, 1992)

**A COMPUTATIONAL MODEL FOR
COAL TRANSPORT AND COMBUSTION**

Grant Number: DE-FG22-91PC91297

Goodarz Ahmadi

Department of Mechanical and Aeronautical Engineering

Clarkson University

Submitted to

U.S. Department of Energy

Pittsburgh Energy Technology Center

Attention:

Dr. Mehrdad Massoudi

Project Officer

MASTER

RECEIVED

MAY 27 1992

**Division of Research
Clarkson University**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

A COMPUTATIONAL MODEL FOR COAL TRANSPORT AND COMBUSTION

Grant Number: DE-FG22-91PC91297

Project Period: September 1, 1991 to August 31, 1994

Contract Recipient: Clarkson University

Project Principal Investigator: Goodarz Ahmadi

DOE Project Officer: Dr. Mehrdad Massoudi

SUMMARY

In the period of March 1, 1992 to May 30, 1992 considerable progress has been made in the development of the stress transport model for rapid granular flows in a rotating frame of reference. The derivation of thermodynamically consistent constitutive equations were completed. It was shown that the model contains the existing kinetic theories as special limiting cases. The model predictions for the special case of rapid simple shear flows were evaluated and the results are compared with the simulation data.

Progress also has been made in formulation of the thermodynamically consistent rate dependent model for turbulent two-phase flows. The thermodynamically admissible constitutive equations were derived, and the case of a simple shear flow was also studied.

The kinetic model for rapid flows of granular materials, which includes frictional losses, was used and the special case of gravity flows down an inclined chute was studied.

The computational modeling for rapid granular flows in complex geometries was further developed. The design for the experimental simple shear flow device was further improved, and the construction of the device has started.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

A STRESS TRANSPORT MODEL FOR RAPID GRANULAR FLOWS IN A ROTATING FRAME

Formulation of a thermodynamically consistent stress transport model for rapid granular flows is studied. The density-weighted averaged balance laws including the averaged form of the Clausius-Duhem inequality for rapid granular materials is considered and the thermodynamics of the mean motion is studied. Based on the averaged entropy inequality, thermodynamically consistent expressions for collisional stress tensor, pressure-strain correlation tensor and heat, energy and deviatoric stress fluxes are also formulated. The closed equations governing the mean granular motion including a transport equation for the kinetic stresses are derived. The model is used to study rapid simple shear flow of an assembly of spherical nearly elastic particles.

BALANCE LAWS

The density-weighted averaged balance laws for granular materials in a rotating frame of reference are given as

Mass

$$\frac{\partial \bar{\rho}}{\partial t} + (\bar{\rho} \bar{v})_{i,i} = 0, \quad (1)$$

Linear Momentum

$$\bar{\rho} \dot{\bar{v}}_i = \bar{t}_{j,i,j} + \tau_{j,i,j}^k + \tau_{j,i,j}^e + \bar{\rho} f_i - 2\bar{\rho} e_{ijk} \Omega_j \bar{v}_k, \quad (2)$$

Energy

$$\bar{\rho} \dot{\bar{e}} = \bar{q}_{i,i} + q_{i,i}^T + \bar{t}_{ij} \bar{v}_{j,i} + \bar{\rho} \epsilon + h, \quad (3)$$

Fluctuation Kinetic Energy

$$\bar{\rho} \dot{\bar{k}} = (\tau_{ij}^k + \tau_{ij}^e) \bar{v}_{j,i} + K_{i,i} - \bar{\rho} \epsilon, \quad (4)$$

Clausius-Duhem Inequality

$$\bar{\rho} \dot{\bar{\eta}} - (\bar{q}_i \bar{\eta})_{i,i} - R_{i,i}^T - h \bar{\eta} + \bar{\rho} \dot{\bar{\eta}}^T - S_{i,i}^T \geq 0. \quad (5)$$

Here, ρ is the mass density, v_i is the velocity vector, t_{ij} is the stress tensor, τ_{ij}^k and τ_{ij}^c are the kinetic and collisional stress tensors, respectively, f_i is the body force (including the centrifugal force) per unit mass, Ω_j is the constant angular velocity of the frame of reference relative to an inertial frame, ϵ_{ijk} is the permutation tensor, e is the internal energy per unit mass, q_i is the heat flux vector pointing outward of an enclosed volume, K_i is the kinetic energy flux vector, h is the internal heat source per unit volume, η is the mean thermal entropy per unit mass, η^T is the entropy of the granular fluctuation, S_i^T is the turbulent entropy flux vector, R_i^T is the heat flux-coldness correlation vector, ϵ is the dissipation rate (including the diagonal part of the pressure-strain tensor) and ϑ is the coldness which is defined as the inverse of temperature θ .

In equations (1)-(5), a bar or a tilde on the top of a letter stands respectively for the ensemble average or the density-weighted average, and a superscript T identifies a fluctuating (turbulence) quantity while superscripts k and c refer to kinetic and collisional parts. Throughout this work, the regular Cartesian tensor notation with Latin subscripts is employed.

Transport equation for the deviatoric part of the kinetic stress tensor in a rotating frame is given as

$$\begin{aligned} \bar{\rho} \dot{a}_{ij}^D &= \hat{P}_{ij}^D - \hat{\Pi}_{ij} + \lambda_{ijk,k}^D \\ &- (\tau_{ik} \tilde{W}_{jk} + \tau_{jk} \tilde{W}_{ik}) - (\tau_{ik} e_{mkj} \Omega_m + \tau_{jk} e_{mki} \Omega_m), \end{aligned} \quad (6)$$

where

$$\tau_{ij} = \tau_{ij}^k + \tau_{ij}^c, \quad \bar{\rho} a_{ij} = \tau_{ij}^k = -\overline{\rho v_i'' v_j''}, \quad (7)$$

and

$$\begin{aligned} \hat{P}_{ij}^D &= -(\tau_{ik} \tilde{d}_{jk} + \tau_{jk} \tilde{d}_{ik} - \frac{2}{3} \tau_{kl} \tilde{d}_{kl} \delta_{ij}), \quad \tilde{W}_{ij} = \tilde{\omega}_{ij} + e_{mji} \Omega_m, \\ \hat{\Pi}_{ij} &= \Pi_{ij} - \rho \left(\epsilon_{ij} - \frac{2}{3} \epsilon \delta_{ij} \right), \quad \rho \epsilon = \frac{1}{2} (\rho \epsilon_{ii} - \Pi_{ii}), \end{aligned} \quad (8)$$

where v_i'' is the fluctuation velocity relative to the density-weighted mean velocity. In equations (6)-(8), Π_{ij} is the pressure-strain tensor, λ_{kij} is the diffusion of the stress tensor, ϵ_{ij} is the dissipation rate of the stress tensor, and $\tilde{W}_{ij}$ is the intrinsic (absolute) mean vorticity tensor. The mean deformation rate and spin tensors are, respectively, defined as

$$\tilde{d}_{ij} = \frac{1}{2}(\tilde{v}_{i,j} + \tilde{v}_{j,i}), \quad \tilde{\omega}_{ij} = \frac{1}{2}(\tilde{v}_{i,j} - \tilde{v}_{j,i}). \quad (9)$$

The last term in parenthesis in equation (6) is the contribution of the Coriolis acceleration.

Based on the averaged Clausius-Duhem inequality, the following set of constitutive equations are proposed:

$$\tilde{t}_{ij} = -\bar{p}\delta_{ij} + 2\mu\tilde{d}_{ij}^D, \quad (10)$$

$$\tau_{ij}^c = (-p^c + \lambda^c\tilde{d}_{kk})\delta_{ij} + 2\mu^c\tilde{d}_{ij}, \quad (11)$$

$$Q_i = (\kappa + \bar{C}\frac{\mu^T}{\sigma^\theta})\hat{\theta}_{,i}, \quad (12)$$

$$K_i = \kappa^T \left[k_{,i} - \frac{k}{\epsilon}\epsilon_{,i} \right], \quad (13)$$

$$\lambda_{kij}^D = \frac{\mu^T}{\sigma^t} \frac{\partial a_{ij}^D}{\partial x_k}, \quad (14)$$

$$\begin{aligned} \hat{\Pi}_{ij} = & \frac{\alpha_1\epsilon}{k} \left[\left(2 + \frac{\alpha_3}{k^2} a_{mk}^D a_{mk}^D \right) \bar{p} a_{ij}^D + \frac{\alpha_2\bar{p}}{k} (a_{ik}^D a_{kj}^D - \frac{1}{3} a_{lk}^D a_{lk}^D \delta_{ij}) \right] \\ & - \gamma_1 (\tau_{ik}\tilde{d}_{kj} + \tau_{jk}\tilde{d}_{ki} - \frac{2}{3} \tau_{kl}\tilde{d}_{lk}\delta_{ij}) + \alpha_4 \bar{p} k \tilde{d}_{ij}^D \\ & - \beta_1 \bar{p} (a_{ik}\tilde{W}_{jk} + a_{jk}\tilde{W}_{ik}) + \beta_2 \bar{p} (a_{ik}a_{kl}\tilde{W}_{jl} + a_{jk}a_{kl}\tilde{W}_{il}). \end{aligned} \quad (15)$$

Here, μ is the coefficient of viscosity, $\bar{C}$ is the heat capacity, κ is the heat conductivity, λ^c and μ^c are the collisional viscosities, μ^T is the combined collisional and kinetic viscosity, σ^θ , and σ^t are the turbulent Prandtl numbers, and α_1 , α_2 , α_3 , α_4 , γ_1 , β_1 and β_2 are material parameters which are functions of Δ^a , k , ϵ , $\hat{\theta}$ and ν and physical properties of particles.

For granular flows in complex geometries, a transport equation for dissipation rate of granular fluctuation energy from the entropy inequality may be derived. However, in most

granular flow models, an algebraic expression for ϵ is used. Such an equation which is consistent with entropy inequality is given as

$$\epsilon = a^e k^{\frac{3}{2}} + \alpha_5 \bar{\rho} k \bar{d}_{kk}, \quad (16)$$

where α_5 is a parameter and a^e is an inverse length scale. These are, in general, functions of solid volume fraction, restitution coefficient and particle size.

The entropy inequality imposes the following restrictions on the material coefficients:

$$\begin{aligned} \mu \geq 0, \quad \kappa \geq 0, \quad \mu^T \geq 0, \quad \kappa^T \geq 0, \quad 3\lambda^e + 2\mu^e \geq 0, \\ \sigma^\theta \geq 0, \quad \sigma^t \geq 0, \quad \alpha_1 \geq 0, \quad \alpha_3 \geq 0, \quad \alpha_4 \geq 0, \\ |\alpha_2|^2 \leq 48\alpha_3. \end{aligned} \quad (17)$$

SUMMARY OF THE GOVERNING EQUATIONS

Using the constitutive equations in the equations of balance, the explicit equations governing the mean motion of a granular material in a rotating frame of reference follows. These are:

Mass

$$\frac{\partial \nu}{\partial t} + \nabla \cdot (\nu \underline{\underline{v}}) = 0, \quad (18)$$

Linear Momentum

$$\rho_0 \nu \dot{\underline{\underline{v}}} = -\nabla[\bar{p} + p^T] + \mu \nabla^2 \underline{\underline{v}} + \nabla \cdot (\underline{\underline{\tau}}^e + \bar{\rho} \underline{\underline{a}}^D) + \bar{\rho} \underline{\underline{f}} - 2\bar{\rho} \underline{\underline{\Omega}} \times \underline{\underline{v}}, \quad (19)$$

Stress Transport

$$\begin{aligned} \bar{\rho} \dot{\underline{\underline{a}}}^D = & -(1 - \gamma)(\underline{\underline{\tau}} \cdot \underline{\underline{d}} + \underline{\underline{d}} \cdot \underline{\underline{\tau}})^D - \frac{\alpha_1 \epsilon}{k} \left[\left(2 + \frac{\alpha_3}{k^2} \underline{\underline{a}}^D : \underline{\underline{a}}^D \right) \bar{\rho} \underline{\underline{a}}^D + \frac{\alpha_2 \bar{\rho}}{k} (\underline{\underline{a}}^D \cdot \underline{\underline{a}}^D)^D \right] \\ & - \alpha_4 \bar{\rho} k \underline{\underline{d}}^D + (1 - \beta_1) \bar{\rho} (\underline{\underline{a}}^D \cdot \underline{\underline{W}} - \underline{\underline{W}} \cdot \underline{\underline{a}}^D) + \beta_2 \bar{\rho} (\underline{\underline{a}}^D \cdot \underline{\underline{a}}^D \cdot \underline{\underline{W}} - \underline{\underline{W}} \cdot \underline{\underline{a}}^D \cdot \underline{\underline{a}}^D) \\ & + (\underline{\underline{\tau}}^D \times \underline{\underline{\Omega}} - \underline{\underline{\Omega}} \times \underline{\underline{\tau}}^D) + (\underline{\underline{\tau}}^{eD} \cdot \underline{\underline{W}} - \underline{\underline{W}} \cdot \underline{\underline{\tau}}^{eD}) + \nabla \cdot \left[\frac{\mu^T}{\sigma^T} \nabla \underline{\underline{a}}^D \right]. \end{aligned} \quad (20)$$

Fluctuation Energy

$$\bar{\rho} \dot{k} = \bar{\rho} \underline{\underline{\tau}} : \underline{\underline{\dot{d}}} + \nabla \cdot \left[\kappa^T (\nabla k - \frac{k}{\epsilon} \nabla \epsilon) \right] - \rho \epsilon, \quad (21)$$

where $\bar{\rho} = \rho_0 \nu$.

SIMPLE SHEAR FLOWS

For a steady simple shear flow, the velocity components are given as

$$u(y) = \dot{\gamma} y, \quad v = w = 0, \quad (22)$$

where $\dot{\gamma}$ is the constant shearing rate.

The deviatoric normal and shear stresses are now given as:

$$\tau_{11}^D = \tau_{11}^{kD} = -\frac{k}{\alpha_1 \epsilon} \left(\frac{4}{3} - \frac{\gamma_1}{3} \right) P, \quad (23)$$

$$\tau_{22}^D = \tau_{22}^{kD} = \frac{k}{\alpha_1 \epsilon} \left(\frac{2}{3} + \frac{\gamma_1}{3} \right) P, \quad (24)$$

$$\tau_{33}^D = \tau_{33}^{kD} = \frac{k}{\alpha_1 \epsilon} \left(\frac{2}{3} - \frac{2\gamma_1}{3} \right) P, \quad (25)$$

and

$$\tau_{12}^k = \frac{k}{\alpha_1 \epsilon} \left[\frac{\gamma_1}{2} \tau_{11} + \left(\frac{\gamma_1}{2} - 1 \right) \tau_{22} - \frac{\alpha_4}{2} \bar{\rho} k \right] \dot{\gamma}, \quad (26)$$

where

$$P = \tau_{12} \dot{\gamma} = \bar{\rho} \epsilon. \quad (27)$$

Note that the deviatoric part of the normal component of the collisional stress tensor is zero.

The first and second normal stress differences are then given by

$$\psi_1 = \tau_{22}^D - \tau_{11}^D = \frac{2T}{\alpha_1} P, \quad (28)$$

and

$$\psi_2 = \tau_{33}^D - \tau_{22}^D = -\frac{\gamma_1 T}{\alpha_1} P. \quad (29)$$

These equations may be restated in a nondimensional form as

$$\bar{\tau}_{11}^D = \frac{\tau_{11}^D}{p^T} = -3.33 \frac{1-r}{(3-r) \left[\frac{2}{3} + \frac{4}{3} \nu \chi (1+r) \right]} \left(\frac{4}{3} - \frac{\gamma_1}{3} \right), \quad (30)$$

$$\bar{\tau}_{22}^D = \frac{\tau_{22}^D}{p^T} = 3.33 \frac{1-r}{(3-r) \left[\frac{2}{3} + \frac{4}{3} \nu \chi (1+r) \right]} \left(\frac{2}{3} + \frac{\gamma_1}{3} \right), \quad (31)$$

$$\bar{\tau}_{33}^D = \frac{\tau_{33}^D}{p^T} = 3.33 \frac{1-r}{(3-r) \left[\frac{2}{3} + \frac{4}{3} \nu \chi (1+r) \right]} \left(\frac{2}{3} - \frac{2\gamma_1}{3} \right), \quad (32)$$

$$\bar{\psi}_1 = \frac{\psi_1}{p^T} = 6.667 \frac{1-r}{(3-r) \left[\frac{2}{3} + \frac{4}{3} \nu \chi (1+r) \right]}, \quad (33)$$

$$\bar{\psi}_2 = \frac{\psi_2}{p^T} = -3.333 \gamma_1 \frac{1-r}{(3-r) \left[\frac{2}{3} + \frac{4}{3} \nu \chi (1+r) \right]}. \quad (34)$$

COMPARISONS

Predictions of the present model for normal stress components and normal stress differences are presented and compared with the simulation data of Hopkins and Shen.

Recently, Hopkins and Shen reported a series of simulation studies for a collection of smooth inelastic spheres. Comparisons of the present model predictions for first and second normal stress differences and normal stress components with their Monte Carlo simulation results are shown in Figs. 1-4. These figures show qualitative agreement between the model predictions and the simulation data. As expected, the agreement improves as the particle becomes more elastic.

Figure 1. Variations of nondimensional first normal stress component with solid volume fraction.

Figure 2. Variations of nondimensional second normal stress component with solid volume fraction.

Figure 3. Variations of nondimensional first normal stress difference with solid volume fraction.

Figure 4. Variations of nondimensional second normal stress difference with solid volume fraction.

COMPUTATIONAL MODEL DEVELOPMENT

Granular Flow

Progress has been made in the application of the discrete element procedure for analyzing rapid granular flows down a chute.

Two-Phase Flow

Formulation of appropriate computational scheme of solution is being studied. It is recognized that for developing an appropriate two-fluid computational code the starting single phase code need to be compressible. A compressible flow code is being studied for extension to two-phase flows solid-liquid or gas flows.

Figure 5. Top view of the final design of the simple shear flow device.

EXPERIMENTAL STUDY

The main objective of the experimental effort is to verify the foundation of the thermodynamical formulation. The other main goals are to provide reliable data for velocity, concentration and fluctuation energy profiles for a simple shear flow of granular materials and/or turbulent two-phase flows in order to verify the theoretical predictions.

Figure 6. Side view of the final design of the simple shear flow device.

Progress has been made in the construction of the simple shear flow setup. Figure 5 represents the top view, and figure 6 shows the side view of the final design of the device. The frame for the device was constructed from 2 in x 0.5 in tubular steel, which houses the rigid center shaft, and supports the 31 in diameter, clear plexiglass, bottom most circular disk. Two coaxial cylinders were constructed of clear plexiglass. The top cylinder has an outside diameter of 30 in, and a 4 in piece of Lexan flexible plexiglass will be affixed

around the circumference of the cylinder, providing the outside wall of the control volume. The bottom cylinder has a 24 in diameter, providing the inside wall of the control volume. Between the top and bottom coaxial cylinders, a rigid plexiglass plate will be placed to encapsulate the cellular assembly, and to permit a single monogranular layer. The two coaxial cylinders and the plexiglass plate will be reinforced by 8 in diameter aluminum disks in the center, and by 0.25 in flat steel on their upper and lower surfaces. The reinforcements will allow lock and collar type bearings to be pressure-fitted into the cylinders and the plate, so that they may be affixed to the center shaft.

A 1.5 Hp motor will drive the system by means of timing belts. A double sided timing belt will turn the inner cylinder clockwise, and the drive shaft counterclockwise. The drive shaft will then rotate the outer cylinder by a single sided timing belt, in the opposite direction of the inner cylinder. This will enable the device to generate various desired inner and outer rotations of the cylinder.

END

**DATE
FILMED
9 / 3 / 92**