NOTICE

**CERTAIN DATA
CONTAINED IN THIS
DOCUMENT MAY BE
DIFFICULT TO READ
IN MICROFICHE
PRODUCTS.**

ANNUAL PROGRESS REPORT
for the
Grant Period
15 September 1991 - 14 September 1992

DOE/ER/53188--9

DE93 002654

DOE Grant #DE-FG02-84ER53188

"Experimental Investigations
of Electron Capture from Atomic
Hydrogen and Deuterium by Alpha Particles"

T.J. Gay
J.T. Park

Division of Applied Plasma Physics
Experimental Plasma Research

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

42

CONTENTS

INTRODUCTION	1
PROGRESS DURING THE LAST GRANT PERIOD	2
A. Test Bench	3
B. He ⁺⁺ Source Tests	4
RESEARCH PLAN	6
REFERENCES	7
APPENDICES	
A	A1
B	B1
C	C1
D	D1
E	E1
F	F1

ABSTRACT

We report progress made during the period 15 September 1991 - 14 September 1992 on the project "Experimental Investigations of Electron Capture from Atomic Hydrogen and Deuterium by Alpha Particles". In the past year we have developed reliable, narrow energy spread, high-current sources of He^{++} based on direct-current magnetron and electron-cyclotron resonance discharges. These sources have been proven on our test bench accelerator which has been upgraded to also allow us to test atomic hydrogen effusive targets. We have thus made substantial progress toward our goal of studying single electron capture from atomic hydrogen by doubly-ionized helium.

A research plan for the upcoming year is also presented.

I. INTRODUCTION

We report herein progress made during the period 15 September 1991 - 14 September 1992 on our project "Experimental Investigations of Electron Capture from Atomic Hydrogen and Deuterium by Alpha Particles", which has been funded by the Division of Applied Plasma Physics since September 1984. In Appendices A, B, and C, a general discussion of the experimental apparatus we have developed to carry out this experimental project is presented. Progress made in the last year toward the development of suitable atomic hydrogen targets and sources of doubly-ionized helium beams for our experiments is reported in the next section. During the last grant period, three papers based on the work supported by this grant have been written. One has been published in the Reviews of Modern Physics, one has been submitted for publication in the Review of Scientific Instruments, and one which will be submitted to the Physical Review A is undergoing final editing prior to submission. These papers are contained in Appendices D, E, and F, respectively.

In May of this year, Victor Irby, who had done his thesis work investigating the charge-capture reaction

received his Ph.D. He is presently working at Oak Ridge National Laboratory. The student who replaced him, Mr. Win Htwe, decided to work with another group this summer. He was replaced by a first-year graduate student, Ms. Tammy Langford.

This July we were informed that funds for this contract would not be renewed. We have

thus requested and received a no-cost 12-month extension, so that the remaining money in the grant can be spent. Plans for research we will do in the next year, supported by these funds, are outlined in section III.

II. PROGRESS DURING THE LAST GRANT PERIOD

Our primary goal has been to measure state-selective single-electron capture cross-sections for the collision process

First experiments on reaction (1) revealed the extreme difficulty of using a Colutron ion source for the production of He^{++} (see Appendix F). Typical usable currents of He^{++} from the Colutron are ~ 0.1 nA, making this source marginal, at best, for these measurements. A second problem we have encountered is associated with the use of our resistively heated atomic hydrogen target for use in investigating collision (2)¹. While we have taken some preliminary data with this target², it is very difficult to align properly and must be completely rebuilt when it burns out. Burnout typically occurs after one week of use. This means that new targets must be built, installed and aligned on a regular basis, cutting into the available data-taking time by a significant fraction. These problems also exacerbate scheduling difficulties on the main spectrometer; to be time-efficient, atomic hydrogen runs must be planned for extended periods to the exclusion of other experiments.

Consequently, in the last year, we have devoted all of our laboratory effort to the

development of improved sources for He^{++} , and of a target chamber for testing microwave and RF atomic hydrogen targets.

A. Test Bench

The facility we have used in these tests is illustrated in figure 1. The ion source is connected directly to a 2 kV extraction electrode and einzel lens, followed by a Wien filter mass analyzer³. The mass-selected beam is deflected as needed and collimated before it passes into the test chamber. The test chamber, which has been built over the last year, consists of a target, which can be either a static gas cell or an effusive beam, electrostatic deceleration optics, a parallel-plate electrostatic energy analyzer, and an electron-multiplier particle detector.

In source testing, the total source current can be measured by a Faraday cup prior to the test chamber. The energy spread of the beam can be measured with the energy analyzer. Atomic hydrogen dissociators will be tested by attaching them to a flange on the top of the test chamber. The effusive beam of H and H_2 emerging from their end nozzles will cross a proton or alpha particle beam from the source, whose energy-loss spectrum will subsequently be determined in the parallel-plate analyzer. Since H and H_2 produce distinct energy-loss signatures⁴, the dissociation fraction of the target beam will be able to be determined. The density of the beam, also an important parameter for target development, will be inferred from known cross sections and the ratio of incident to inelastically scattered beam.⁵

B. He^{++} Source Tests

The target chamber/analyzer described above has worked well in our tests of new sources for He^{++} . During the past year we have tested more than ten different source configurations. The operational requirements for these sources have been:

a) Currents of He^{++} greater than 1 nA. Our previous experience (Appendix F) with the Colutron source in our studies of collision (1) led us to conclude that any He^{++} current, as measured after mass analysis, of less than 0.5 nA represented a marginal case, and that for ease of acceleration and tuning that at least 1 nA was necessary.

b) Long source life. In order to produce any He^{++} at all, the Colutron source filament must be run at very high power, yielding a maximum useable source lifetime on the order of four hours. In combination with the low currents of He^{++} , this made experiments extremely difficult. We wanted to develop a source which would last for at least a week of continuous running.

c) Low energy spread. To resolve the $\text{He}^+ n = 3$ peak from the $n = 2$ and $n = 4$ peaks, the combined analyzer/source energy resolution must be less than 3 eV, although only about 7 eV resolution is necessary to separate the $n = 2$ from the $n = 3$ peak.

We have developed one source configuration, which can be operated in one of two modes, which satisfies the above criteria. Its basic design is shown in figure 2. Either a microwave or DC discharge is struck in a stainless-steel cylindrical cavity, and ions produced in the plasma are extracted from two sequential apertures at the end of the cavity. When microwave power (at 2.4 GHz) is injected, a magnetic field, produced by two cylindrical coils placed immediately outside the cylinder, is used to produce an electron cyclotron resonance (ECR)

condition in part of the plasma. Thus the applied power increases the electron energy (and hence their ability to produce highly-stripped ions), while not increasing appreciably the kinetic energy, and hence the energy spread, of the ions.

A second mode of operation, which has proved to be better from the standpoint of both He^{++} current intensity and stability, is that of a DC magnetron (DCM) discharge. In this mode, a nominal DC voltage of 300 V is placed between the center electrode and the extraction anode, while the magnetic field of ~ 1 kG is tuned to maximize a given ion species current. Electrons in this mode undergo non-resonant cycloidal motion, and produce copious numbers of secondary electrons at the walls of the cylinder.

In order to measure the energy-spread of the beam extracted from the source, ΔE , we use the parallel-plate analyzer shown in figure 1. Since this analyzer has an instrumental energy resolution, ΔW , the measured width of the beam, ΔM , is a convolution of ΔE and ΔW :

$$(\Delta M)^2 = (\Delta E)^2 + (\Delta W)^2. \quad (3)$$

The instrumental width of the analyzer is proportional to the mean incident beam energy E . Thus the measured beam width is given by

$$(\Delta M)^2 = (\Delta E)^2 + a^2 E^2, \quad (4)$$

or

$$\Delta E = [(\Delta M)^2 - a^2 E^2]^{1/2}, \quad (5)$$

where a is a constant associated with the analyzer. The analyzer constant a , and the true beam width ΔE can be measured by decelerating the beam prior to its entrance into the analyzer, thus varying E . A plot of $(\Delta M)^2$ vs. E^2 subsequently yields both a and ΔE from the slope and intercept of a straight-line fit to the data. [The goodness of fit of this line serves as a check of the validity of equation (3).]

A plot of this type, made using a He^{++} beam from the DCM source is shown in figure 3. To provide a range of incident beam energies, a decelerating potential between 0 and 1700 volts was provided by the zoom-lens system prior to the analyzer. Several zoom-lens designs were analyzed and tried before a suitable configuration, capable of this range of deceleration voltages with acceptable transmission, was adopted. The y-intercept of the graph in figure 3 yields the square of the actual beam width, $(\Delta E)^2$.

From experiments of this type, we characterized the operation of the two good source design modes discussed above. These results are listed in Table 1. Using the DCM source to produce He^{++} , we took several energy spectra with static He and Ar targets and easily observed single-capture energy gain events, thus demonstrating that studies of collision (1) with this source should be straightforward. The ECR source would also be suitable for such measurements. Because of its somewhat higher He^{++} currents and significantly better energy spread, however, we expect to use the DCM configuration for most of our experiments. In either case, both designs are dramatically superior to the Colutron.

III. RESEARCH PLAN

Now that we have usable sources of He^{++} , we will turn our efforts toward the

development of an effusive atomic hydrogen target. In the next year, we will concentrate on two promising general target designs: a DC-discharge Wood's tube of the type used successfully by a number of groups⁶, and a microwave discharge source, which has also been proven in numerous experiments.⁷ We already have in our lab the discharge tube for a microwave target. In each case, the dissociator nozzle will be placed just above the source focus point of the entrance/deceleration optics of the parallel-plate analyzer, replacing the static target cell we are presently using.

Dissociation fractions will be measured using proton beams by comparing the area of the energy-loss peak due to H_2 , at 12.5 eV, and H, at 10.2 eV.⁴ The ratio of these two peak areas yield the H/ H_2 ratio. In principle, targets that have only modest dissociation fractions (25%-50%) are acceptable because we now have sources with sufficiently good energy resolution that capture from H_2 can be distinguished from capture from H. Other parameters of relevance for the target are constancy over time of the dissociation fraction, ease of cleaning the discharge tubes (this appears from the literature to be a critical procedure), and H number density just below the effusive nozzle.

Once a suitable target is operational, we will attempt to make some angle-integrated measurements of cross-sections for reaction (1) at energies less than 5 keV to test targets and sources together, as well as to provide some data in this energy range. We will then proceed with experiments on the main ion energy-loss spectrometer.

REFERENCES

- 1) J.T. Park, E. Redd, T.J. Kvale, and E. Rille, Rev. Sci. Instrum. 54, 1247 (1983).

- 2) Technical Progress Report, this grant (DE-FG02-84ER53188), 15 September 1990 - 14 September 1991.
- 3) G2 ion gun and mass filter manufactured by the Colutron Corporation.
- 4) J.T. Park, J.E. Aldag, J.M. George, and J.L. Peacher, Phys. Rev. A 14, 608 (1976).
- 5) Atomic Data for Fusion, C.F. Barnett (ORNL Report 6086, Volume 1, published 1990).
- 6) See, e.g., J.M.B. Kellogg, I.I. Rabi, and J.R. Zacharias, Phys. Rev. 50, 472 (1936).
- 7) See, e.g., E.J. Murphy and J.H. Brophy, Rev. Sci. Instrum. 50, 635 (1979).

Sources	Typical Ion Beam Current		Energy Spread (He ⁺⁺)	Lifetime		Gas Pressure (mTorr)	Stability	Remarks
	H ⁺	He ⁺⁺		H ⁺	He ⁺⁺			
Colutron	30 nA	100 pA	3 eV	5-7 days	4 hrs	100 - 200	Poor	Filament and anode need to be replaced.
ECR	400 nA	1 nA	4 eV	20 days	20 days	40 - 100	Fair	No replacement parts but need to be cleaned.
DCM	100 nA	1.5 nA	<1 eV	20 days	20 days	100 - 200	Good	No replacement parts but need to be cleaned.

Table 1. Comparison of the Ion Sources (on the Test Bench)

ECR - Electron Cyclotron Resonance

DCM - D.C. Magnetron Discharge (Cold Cathode)

FIGURE CAPTIONS

- 1) Test bench facility for ion source and atomic hydrogen target analysis showing: 1) ion source; 2) Colutron extraction and focusing optics and Wien mass filter; 3) deflection plate chamber; 4) insertable faraday cup and final source collimator; 5) target and analyzer vacuum chamber; 6) electron-multiplier ion detector; 7) parallel-plate electrostatic analyzer; 8) focusing and deceleration optics prior to analyzer; 9) effusive atomic target.
- 2) New source electrical/mechanical configuration showing cylindrical plasma region, DC, microwave, or RF power input (labeled "RF Input"), and magnets.
- 3) Measured energy spread (FWHM) squared $[(\Delta M)^2]$ vs. He^{++} beam energy squared. Units of both axes are eV squared.

Figure 1

New ECR Ion Source

Figure 2

Data from "DCM ALPHA SOURCE"

Figure 3

APPENDIX A

INTRODUCTION

We have undertaken a program at the University of Missouri-Rolla to experimentally determine cross sections for ion-atom collisions of interest in fusion reactor development. During the last grant period, we finished measurements of total cross sections for the alpha single-capture reaction

and we propose to study

this year.

Accurate knowledge of these cross sections is fundamental for modeling of neutral-hydrogen beam penetration in fusion plasmas as well as for spectroscopic diagnostics of alpha densities and velocity distributions, especially for the case of capture into the $n = 4$ state of the projectile $\text{He}^{+1,2}$

Our measurements are made using a unique collision spectrometer³⁻⁵ discussed below. Reaction (1) was studied for alpha energies between 45 and 135 keV, using the technique of ion-energy spectroscopy.³⁻⁷ This technique has two major advantages over optical measurements. First, cascading corrections are avoided because the fast collision partner is detected, rather than a secondary photon. Second, no knowledge of detector efficiencies is required, because a ratio of the scattered to incident beam counting rates is measured. Two sources of possible systematic error in the determination of final cross sections are thereby eliminated. Moreover, we have studied the angular dependence of cross sections for (1), and can thus be certain that the measured total cross sections are not low due to incomplete angular acceptance of the apparatus, a problem known to exist in some previous total cross section measurements of this type. To date, Reaction (1) had been studied experimentally only for $n = 1$ and the sum of $n = 2, 3$, and 4 states, for energies at and below 15 keV/amu.⁸ In that work, no angular measurements were made.

Our ultimate goal is to measure total and differential cross sections for (2) to 10 percent accuracy. This reaction has been investigated between 1 and 10 keV/amu, using optical detection to provide n state information.⁹ Our studies will cover the range 13 to 130 keV/amu. Studies of (1) have required the ability to make charge-changing energy-loss measurements using $^3\text{He}^{++}$ beams (see below). The final step to studying collision (2) will be the implementation of an H oven target.

APPARATUS AND EXPERIMENTAL METHOD

The apparatus employed in this research has been described extensively in the literature.^{3-7,10-12} During the last twenty years, it has been used in pioneering studies of a large number of ion-atom and ion-molecule collisions systems, and is currently the only machine in the world capable of ion energy spectroscopy (IES) with electron-volt resolution in the 20 to 200 keV range. A scale diagram of the apparatus is shown in Figure 1. Ions produced in a Colutron ion source are mass-selected in a Wien filter, focused, collimated, and accelerated. They pass through removable collimation slits and enter the scattering chamber. The atomic hydrogen oven¹¹ and static (e.g., He) target¹² are shown in Figures 2 and 3. Ions which are neutralized in the scattering chamber pass undeflected through the switching magnet and into a neutral detector consisting of solid-angle defining slits and an S.R.C. 1701 electron multiplier. The magnet deflects ions into the decelerator column, where their energy is ultimately lowered to 1 keV. They then pass through a 10" radius cylindrical electrostatic analyzer or a retarding-field analyzer and are detected by a Johnston Labs electron multiplier.

Figure 1.

Schematic diagram of the UMR ion energy-loss/gain spectrometer. Horizontal dimension is about 35 ft. Note positions of variable resistor assembly (VRA) and precision voltage divider (PVD; see text).

Ion spectra energy are obtained by varying the offset voltage ΔV , between the accelerator and decelerator terminals. A projectile which suffers an inelastic energy loss ΔE upon scattering can be detected only if $\Delta E = q\Delta V + 1 \text{ keV}$, in the case of the cylindrical analyzer, or, when the retarding field analyzer is being used, if it has retained enough energy to surmount the final potential grid before the electron multiplier. In this way, all electrostatic elements downstream from the target can be kept at constant potential during a run. This ensures that the ion "detector", consisting of the deflection magnet, decelerator, analyzer, and electron multiplier, maintains a constant overall detection efficiency. We note that, unlike other IES systems used at lower energies,¹³ our apparatus has the ability to measure ion spectra differentially in angle. This is accomplished by pivoting the entire accelerator/source assembly about the scattering center.⁷ We can thus ensure that our total cross section values are not systematically low due to incomplete angular acceptance of the decelerator.

Figure 2.

The atomic hydrogen oven (Ref. 11). Operating temperature is $\sim 2700^\circ\text{K}$ and dissociation fractions are $> 95\%$.

Figure 3.

The non-reactive static gas target.

In the standard configuration of the apparatus, both accelerator and decelerator terminals are always at very nearly equal potentials, being separated in voltage by the energy loss (gain) value ΔV . An electrical schematic of this arrangement is shown in Figure 4. As a result, only collisions in which the charge of the projectile ion remains unchanged can be studied. To study Reactions (1) and (2), it is necessary to vary the accelerator/deceleration voltage ratio between unity and 0.5. This has been accomplished by modifying the apparatus as shown schematically in Figure 5. We have constructed, installed, and tested a high voltage (200 kV), high power (1000 W) variable resistor between the two terminals (Appendix B). The accelerator terminal can thus be effectively at an adjustable (electrical) point in a voltage divider between the decelerator and ground. Because the ratio between accelerator and decelerator voltages is constant for a given setting of the variable resistor, voltage fluctuations of the high-voltage power supply do not cause drifting of the spectrometer's energy loss setting. The electrical modifications to the apparatus also include two precision voltage-divider strings (Appendix C), and, because of the now large potential difference between the accelerator and decelerator, a second isolation transformer. Successful investigation of collisions (1) and (2) relies primarily on the stability and precision of the variable resistor assembly and precision voltage divider during operation. These components have proven to be extremely reliable, thus justifying the care which went into their

design and construction. In the following section, we discuss the details of the measurements we have made with the apparatus to date.

Figure 4. Original electrical configuration of the spectrometer. The high voltage power supply (HV; 2mA @ 200 kV), 4V power supply, and the constant offset voltage (V_0) supply used for extraction from the ion source are shown. Note single isolation transformer and precision voltage-divider chain.

Figure 5. New electrical configuration of the apparatus. For one electron capture by He^{++} , the variable resistance R_1 must equal the combined resistance of R_2 , R_3 , and R_4 to ground.

REFERENCES

- 1) See e.g., R. J. Fonck, *Rev. Sci. Instrum.* **56**, 885 (1985).
- 2) S. J. Zweben, *Rev. Sci. Instrum.* **57**, 1723 (1986); see also H. P. Summers, *Comm. At. Mol. Phys.* **21**, 277 (1988).
- 3) J. T. Park, *Adv. At. Mol. Phys.* **19**, 67 (1983).
- 4) J. T. Park and F. D. Schowengerdt, *Rev. Sci. Instrum.* **40**, 753 (1969).
- 5) J. T. Park and F. D. Schowengerdt, *Phys. Rev.* **185**, 152 (1969).
- 6) J. T. Park, J. G. Aldag, J. M. George, and J. L. Peacher, *Phys. Rev.* **A14**, 608 (1976).
- 7) J. T. Park, J. M. George, J. L. Peacher, and J. E. Aldag, *Phys. Rev.* **A18**, 48 (1978).
- 8) V. V. Afrosimov, A. A. Basalaev, G. A. Lieko, and M. N. Panov, *Sov. Phys. JETP* **47**, 837 (1978).
- 9) D. Ciric, D. Dijkkamp, E. Vlieg, and F. J. de Heer, *J. Phys. B* **18**, 4745 (1985).
- 10) E. Rille, R. E. Olson, J. L. Peacher, D. M. Blankenship, T. J. Kvale, E. Redd, and J. T. Park, *Phys. Rev. Lett.* **49**, 1819 (1982).
- 11) J. T. Park, E. Redd, T. J. Kvale, and E. Rille, *Rev. Sci. Instrum.* **54**, 1247 (1983).
- 12) T. J. Kvale, D. G. Seely, D. M. Blankenship, E. Redd, T. J. Gay, M. Kimura, E. Rille, J. L. Peacher, and J. T. Park, *Phys. Rev.* **A32**, 1369 (1985).

APPENDIX B

VARIABLE RESISTOR ASSEMBLY

The design criteria for the variable resistor assembly (VRA) were that it:

- 1) Allow us, for maximum flexibility in the future, to investigate charge changing collisions in which the incoming to outgoing charge ratio, q_{in}/q_{out} , is ≤ 3 (e.g., $Li^{3+} + Ar \rightarrow Li^{+} + Ar^{2+}$). For a reaction in which $q_{in}/q_{out} = 3$, the VRA must be set at a nominal value of $1.6G\Omega$; we have a design capability of $2G\Omega$.
- 2) Have a conservative voltage rating of 200kV.
- 3) Have good resistance stability against voltage and temperature fluctuations.

After a number of preliminary design ideas were proposed and rejected (most often because of unsatisfactory provisions for mechanical motion), the basic configuration shown schematically in Figure 1 was adopted. This design employs three resistor sub-assemblies connected in series, which use, respectively, 100 20M resistors

Figure 1. Assembly drawing and electrical schematic of the VRA.

in series, 24 2M Ω resistors in series, and a Beckman Helipot E-5 2.5M Ω precision potentiometer. The resistors in each of the first two sub-assemblies, to be designated here as the "coarse control" and "fine control" strings, are connected between 3/4 in hemispherical corona caps mounted on vertical axes in 3/4 in thick Lucite disks. In each case, a spring-loaded stainless-steel wiper on either side of a given Lucite "stack" (Fig. 1) is rotated across the heads of the corona caps, making a "make-before-break" sliding contact with the resistor assembly.

The discrete resistors used in the VRA have been purchased from the Dale Resistor Corporation and are of the metal oxide film type, with voltage ratings of 45 kV each, power ratings of 10W, and temperature coefficients (TC's) of less than 50 ppm/ $^{\circ}$ C per resistor. The large voltage ratings were chosen in order to minimize the voltage coefficients (VC's) of resistance. In practice, individual resistors will never have more than 5kV across them. By careful selection of individual resistors, we have assembled resistor stacks with minimal TC's. It is important that the resistance ratio of the variable resistor to the accelerator-to-ground resistance be as insensitive to temperature differences as possible. The worst case for power dissipation would be in a $q_{in}/q_{out} = 3$, 66.7 kV acceleration voltage experiment. The maximum power dissipated by each 20m Ω resistor would be .14W. Given the 10W ratings of these components, resistance change due to thermal fluctuation is minimal. Voltage coefficients are not of critical importance for the VRA.

The VRA is contained in a cylindrical steel container (41 in diameter, 57 in high) filled with Shell DIALA-AX transformer oil to act as a dielectric insulator between the ground potential of the can and the resistor high voltage components. The oil thermally stabilizes the resistor strings and acts as a lubricant for mechanical motion. There is a minimum of 6 in of Lucite and/or oil between individual stacks and the sides of the container. While the resistor corona caps subtend only about 230 $^{\circ}$ of arc on the circumference of the Lucite disks, other corona caps are placed along the remaining angle of the circumference and are connected to points of increasing potential along the resistor string on the other side of the disk. In this way the potential varies smoothly around the perimeter of each disk, and from stack to stack, thereby minimizing voltage stress throughout the design.

The resistor assembly components are located in the tank in such a way that the lowest voltage rating (corresponding to the region of highest electrical stress near the coarse stack corona cap terminators) is ~ 1.46 MV, giving a minimum safety factor of 7.3 (at 200 kV). Typical safety factors throughout the oil volume are about 50. This high degree of conservatism in design was felt to be necessary given the potential difficulties that could result from even small amounts of corona discharge.

The VRA must, of course, be operated remotely during a run. The coarse and fine controls, as well as the Helipot, are adjusted by stepping motors. In the case of the coarse and fine controls, precision worm gear assemblies are used to increase the torque delivered to the center rods. Adjustment of the VRA can be accomplished automatically by a microprocessor-controlled stepping motor circuit if desired. We also have the capability to automatically adjust the Helipot on a continuous basis through a feedback loop to maintain constant accelerator voltage during long runs. All of the stepping motor and microprocessor electronics are housed in one box. The software and hardware for this circuitry has been completely designed, built, and tested.

APPENDIX C

PRECISION VOLTAGE DIVIDER

Accurate measurement of both accelerator and decelerator terminal voltages is critical. This can be illustrated by considering how measurements of the He^+ energy-loss (gain) spectra are made. With the accelerator and decelerator terminals electrically shorted at, for example 100 keV, He^+ ions are selected from the source, passed through the scattering chamber, where their current is measured accurately, and then, following deceleration, detected. The machine's "detection efficiency" for 200 keV He^+ ions is thus established. At this point, the ion source is switched to production of He^{++} and the variable resistance is increased from 0Ω to $\sim 800\text{M}\Omega$, putting the accelerator terminal at 50 kV. Before the energy spectrum of the He^+ produced by charge transfer can be measured, it is necessary to find the location of the energy loss peaks by scanning the ΔV power supply. For this technique to be useful, however, it is necessary to be in the "ballpark", i.e., the decelerator voltage minus twice the accelerator voltage must be comparable to the spread (in ΔV) of the energy-loss peaks we expect to see. This requires relative terminal voltage measurements with accuracies of the order of one part in 10^4 .

We measure terminal voltages with the voltage divider circuit shown schematically in Figure 1. Both divider strings are housed in the same oil bath to minimize problems associated with temperature fluctuations. Each string consists of 50 $200\text{M}\Omega$

and 6 $2\text{M}\Omega$ Dale metal oxide film 1% resistors of the type described in Appendix A. Terminal voltages are determined by measuring the voltage across the lower $1\text{M}\Omega$ (two $2\text{M}\Omega$ in parallel) resistors, using twin Fluke 8840A digital multimeters ($>10\text{G}\Omega$ input impedance). We have the ability to insert in series a $5.3\text{M}\Omega$, 40 turn trimming potentiometer (Beckman Helipot Series "E") in either string. This enables us to set the two Fluke voltage readings equal when the accelerator and decelerator terminals are at the same potential. As an alternative approach, we have the ability to measure accelerator/decelerator voltage ratios very precisely by making null current measurements between nodes of the two resistor strings. In the case of $q = 2 \rightarrow q = 1$ collisions, for example, an ammeter would be put between sections 2 and 6 (Fig. 1), and the VRA adjusted until a null reading was obtained. The ammeter signal can also be fed back to our microprocessor-based stepping motor controller.

Figure 1. Electrical schematic of the PVD.

The two resistor strings are arranged in cylindrical stacks, in a fashion similar to the VRA. Mechanical design was simplified significantly because no moving parts were required. As with the VRA, a great deal of care was taken during design of the PVD to minimize voltage stress throughout the assembly. This has resulted in a mini-mum safety factor for the PVD of 9.2 in dielectric strength, with typical values of 40 or higher. Again, maximum stress occurs near the final high voltage corona cap on each string. The PVD oil container is a cylindrical can 40 in deep with a diameter of 30 in.

APPENDIX D

Electron production in proton collisions with atoms and molecules: energy distributions

M. E. Rudd

Department of Physics and Astronomy, Behlen Laboratory, University of Nebraska, Lincoln, Nebraska 68586

Y.-K. Kim

National Institute of Standards and Technology, Gaithersburg, Maryland 20899

D. H. Madison and T. J. Gay

Physics Department and Laboratory for Atomic and Molecular Research, University of Missouri-Rolla, Rolla, Missouri 65401

All known data on the energy distribution of secondary electrons from collisions of protons with atoms and molecules have been reviewed and differential cross sections have been collected. The two experimental methods used to obtain the data are discussed and possible sources of error pointed out. Theoretical treatments are reviewed and several methods of checking the consistency of the data are discussed. Two semiempirical models have been chosen to represent the differential cross sections, and parameters for these models are given which fit the average of the experimental data, subject to known constraints. Recommended values of differential cross sections are given for ten target gases by means of these models.

CONTENTS

I. Introduction	442
II. Definitions	442
III. Qualitative Considerations	443
A. Sign of charge	443
B. Projectile momentum	443
C. Energy transferred to an ejected electron	443
D. Slow incident particles	444
E. Rutherford cross section	444
F. Binary collision peak	444
G. Soft and hard collisions	446
H. Optical (zero-momentum-transfer) limit	447
I. Semi-classical treatment and the plane-wave Born approximation	448
IV. Theoretical Treatments	448
A. Binary-encounter approximation	448
B. Classical-trajectory Monte Carlo method	449
C. Quantum-mechanical methods	449
1. Weak initial- and final-state electron-projectile interactions	450
2. Strong initial-state interactions and weak final-state interactions	450
3. Strong electron-projectile interactions	450
a. Consequence-distorted-wave method	451
b. Other methods for strong electron-projectile interactions	451
D. Comparisons of experiment and theory	452
V. Consistency Checks	453
A. Bethe theory	453
B. Platzman plots	454
C. Comparison with electron-impact data	455
D. Comparison with photoionization data	455
E. Comparison with total ionization cross sections	455
F. Relationship with stopping cross sections	456
VI. Semiempirical Models	456
A. Miller's model	456
B. Dillner-Jackson model	457
C. Kim's model	457
D. Rudd's model	462
VII. Experimental Methods	465
A. Analysis of ejected electrons	466

B. Ion energy-loss spectroscopy	467
VIII. Error Analysis	467
A. Analysis of ejected electrons	467
1. Total signal and background counts, N_s and N_b	467
2. Number density of target gas, n	467
3. The "absorption" coefficient σ_e	467
4. Number of protons N_p	467
5. Integrated path length/solid angle $(\mu\Omega)/\omega$	467
6. Energy width-transmission product of the analyzer, $\Delta E/\omega$	467
7. Detection efficiency ϵ	467
B. Ion energy-loss spectroscopy	467
1. The beam-related signal-background difference $N_s - N_b$	467
2. The target length-density product nl	467
3. The number of incident protons N_p	467
IX. Recommended Values of Slagly-Differential Cross Sections	467
A. Choice of model	467
B. Data adjustment	467
C. Fitting of the Rudd model	467
D. Table of parameters in the Rudd model	467
E. Recommended values	467
X. Discussion of Slagly-Differential Cross-Section Data for Individual Targets	467
A. Helium	467
B. Neon	467
C. Argon	467
D. Krypton	467
E. Molecular hydrogen	467
F. Molecular nitrogen	467
G. Molecular oxygen	467
H. Carbon dioxide	467
I. Water vapor	467
J. Methane	467
K. Other targets	467
XI. Recommendations for future work	467
Acknowledgments	467
Appendix A: Maximum Energy Transferred to an Electron at Rest	467
Appendix B: Binary Peak Angle	467
References	467

1. INTRODUCTION

When an energetic ion such as a proton collides with an atom or a molecule, several inelastic processes can take place in addition to elastic scattering. The basic ones are excitation of the target, electron capture, and the ejection of free electrons from the target. The last process, often called "direct ionization," involves the greatest exchange of energy and is also the most probable process for collision velocities exceeding the orbital velocity of the electron in the target. This process is the subject of the present review.

Because of the relatively large energy transfer, ionization is a very important process for any study involving the energy loss of particles traversing matter and for investigations of the deposition of energy in matter. Examples are the radiation damage of biological and other materials, radiation detection devices, and investigations of the aurora borealis and other upper atmospheric phenomena. Studies of magnetic and inertial-confinement fusion and of stellar atmospheres also make use of ionization data.

Knowledge of the total ionization cross section as a function of incident energy suffices for some purposes. In an earlier paper Rudd, Kim, Madison, and Gallagher (1985) made a critical review of total cross-section measurements for proton-impact ionization. In that review recommendations were made for values of cross sections over a wide energy range for 13 target gases, the theoretical and semiempirical methods available for calculation of these cross sections were discussed, and a semiempirical equation was given along with parameters to enable the cross sections to be easily computed for a given energy.

The present paper extends that review to differential cross sections, which are crucial for a wide variety of problems. In the calculation of radiation damage, for example, it is necessary to take into account the ionization caused by the secondary electrons themselves. For such purposes, the energy spectrum of secondary electrons is needed. This information is contained in the singly-differential cross sections (SDCS's), i.e., cross sections as functions of the secondary-electron energy. For other purposes, such as studies of track structure and radial dose distributions, the angular distribution of electrons with a given energy is also needed. This requires doubly-differential cross sections (DDCS's), i.e., cross sections differential in both the angle and the energy of the ejected secondary electrons. There is also another SDCS, namely the cross section as a function of angle only, which may be obtained by integrating DDCS data over electron energy. However, this cross section has found fewer applications in the above-mentioned areas.

Unfortunately, there is no reliable and direct way to measure energy distributions of secondary electrons. The most popular method is to measure the DDCS over a wide range of angles and then to integrate it over the electron ejection angle. However, this method is often

marred by uncertainties in the forward and backward directions and in the spectra of slow ejected electrons. The latter uncertainty is more serious because slow electrons significantly contribute to the total ionization cross section.

Differential cross sections for electron ejection are not only of interest because of their many applications, but are also important in their own right, since they provide more detailed information about basic ionization processes than do total cross sections.

The basic mechanisms of electron ejection are known, and theoretical treatments exist that will yield the required cross sections over some ranges of parameters. However, no universal method of calculation exists that yields accurate cross sections for all primary and secondary energies and for all targets. This makes it necessary to rely on experimental data and on semiempirical models. Even though there is general agreement among most of the existing experimental data sets, there are significant discrepancies. As a result, a potential user is often faced with the problem of choosing from conflicting sets of data often covering different ranges of parameters. In the present review the experimental data are critically evaluated in the light of well-established theoretical results and of their consistency with other related data. Recommended values for the SDCS's for ten common target gases are presented.

In Sec. II basic cross sections are defined and in Sec. III qualitative features of the differential cross sections are discussed. *Ab initio* theoretical treatments and their limitations are discussed in Sec. IV, and the various methods for making consistency checks on experimental data are considered in Sec. V. Semiempirical models for SDCS's are discussed in Sec. VI. In Secs. VII and VIII experimental methods are presented and sources of error analyzed. The recommended values of the SDCS's are given in Sec. IX. Section X contains a discussion of the SDCS data for individual targets and gives the results in graphical form. Recommendations for future work are offered in Sec. XI.

II. DEFINITIONS

The collision of a fast charged particle with a neutral atom or molecule may result in the ejection of one or more secondary electrons, which, in the case of proton impact, must come from the target. These electrons are ejected over a range of energies and directions.

The differential cross section is usually measured by directing a beam, in this case of protons, through a gas target with low number density n , and measuring the electrons having an energy W that are ejected in a given direction from a known length of path l . If one measures the number N of electrons ejected into a solid angle $\Delta\Omega$ with energies W to $W + \Delta W$, then the doubly-differential cross section is defined by the equation

$$d^2\sigma/dW d\Omega = N/(N_0 l \Delta\Omega \Delta W), \quad (1)$$

energy W is

$$f_W = (1/\sigma) \int_W^\infty \frac{d\sigma}{dW'} dW'.$$

This quantity is especially useful in finding the fraction of electrons with $W \geq I$, since such electrons can cause further ionization.

III. QUALITATIVE CONSIDERATIONS

In this section, we consider qualitatively the basic physics of proton-impact ionization. We also consider electron-impact ionization, because comparisons between electron and proton data have proven very useful in evaluating and understanding proton measurements.

A. Sign of charge

The plane-wave Born approximation (PWBA), which the incident particle is represented by a plane wave, predicts that both excitation and ionization cross sections will be proportional to Z^2 , where Z is the projectile charge. As a result, the PWBA predicts the same cross section for a charged particle of a given mass and velocity regardless of its sign of charge. In the high energy region where the PWBA is valid and does not depend on projectile mass, only the velocity of the particle is relevant. For example, antiprotons and positrons at the same high speed produce the same target ionization. At intermediate to low energies, however, mass-charge-sign differences, e.g., between protons and electrons, cause cross-section differences. Experimental data with fast projectiles are often scrutinized for these expected trends as signs of their consistency and reliability.

B. Projectile momentum

Since a proton is 1836 times more massive than an electron, an incident proton carries that much more momentum than an electron of the same speed. Description of a continuum wave function depends on momentum k , rather than the speed v , of the projectile and the proton wave function approaches a plane wave at the same momentum in the limit of high k . As a result, the PWBA, which uses plane waves for the projectile, works better for proton-impact cross sections than for electrons of the same speed, for projectile speeds below the high-energy region discussed in Sec. III A.

C. Energy transferred to an ejected electron

An incident proton can transfer most of its energy to a bound electron, but in practice the energy transfer is usually far less than the incident energy. The case of electron-impact ionization is different, however, since it cannot distinguish the two or more electrons ejected after an ionizing collision. As a result, an operational

where N_0 is the number of incident particles. For unpolarized beams and targets, the cross section is independent of the azimuthal angle ϕ and depends only on the polar angle θ measured relative to the forward direction of the incident beam. In this case, the DDCS is a function only of θ and W .

If the DDCS is measured over a sufficiently wide range of angles and energies, then one may obtain by numerical integration the SDCS representing the energy distribution,

$$\frac{d\sigma}{dW} = \int \frac{d^2\sigma}{dW d\Omega} d\Omega, \quad (2)$$

or the SDCS giving the angular distribution,

$$\frac{d\sigma}{d\Omega} = \int_0^\infty \frac{d^2\sigma}{dW d\Omega} dW, \quad (3)$$

where $W_{\text{max}} = T_0 - I$ is the maximum kinetic energy of the ejected electrons, T_0 is the energy of the incident proton, and I is the ionization potential. The total cross section for electron ejection is obtained by integrating the DDCS twice:

$$\sigma = \int_0^\infty \int_0^\infty \frac{d^2\sigma}{dW d\Omega} dW d\Omega. \quad (4)$$

While other methods have been used to measure the total cross section (Rudd *et al.*, 1985), no direct measurements have been reported of singly-differential cross sections for proton impact except for those of Park and co-workers (Park and Schwenker, 1969b; Park *et al.*, 1977). Vroom *et al.* (1977) have devised a method for direct SDCS measurements with electron impact. This technique has not been pursued, however, and few data thus obtained exist.

Knowledge of the differential cross sections, especially $d\sigma/dW$, makes possible the calculation of several additional quantities that are of interest in studies of radiation effects and in other areas where the deposition of energy by fast charged particles needs to be known. The average energy of secondary electrons is

$$W_{\text{av}} = (1/\sigma) \int_0^\infty W \frac{d\sigma}{dW} dW. \quad (5)$$

The stopping cross section due to ionization is

$$\sigma_s = (1/R) \int_0^\infty (W + I) \frac{d\sigma}{dW} dW, \quad (6)$$

where R is the rydberg energy (13.6 eV). If there is more than one shell in the target, this equation must be replaced by the summation

$$\sigma_s = (1/R) \sum_i \int_0^{W_{\text{max}}} (W + I_i) \frac{d\sigma_i}{dW} dW, \quad (7)$$

where I_i is the binding energy of the i th shell, W_{max} is the maximum kinetic energy of electrons ejected from the i th shell, and $d\sigma_i/dW$ is the partial cross section for ejecting an electron from the i th shell. The fraction f_W of electrons ejected with an energy greater than a given

tion is made between the primary (fast) electron and secondary (slow) electron by requiring the maximum energy transferred $W_{\max}$ to be one-half of the incident energy T_0 after subtracting the required binding energy I .

$$W_{\text{max}}(e^-) = (T_0 - I)/2. \quad (9)$$

This choice of $W_{\text{max}}(e^-)$ assumes that the electron exchange effect between the incident and ejected electrons has been properly treated.

For incident protons, conservation of energy and momentum restricts the maximum energy transfer to an unbound electron at rest to (see Appendix A)

$$W_{\text{max}}(p) = 2mv_0^2 = 4T, \quad (10)$$

where m is the electron mass, v_0 is the incident-proton speed, and $T = mv_0^2/2$. This limit is independent of the projectile mass M (assuming $M \gg m$) and is known as the free-electron limit for energy transfer by heavy projectiles. In reality, a bound electron can exceed this limit because the ion core can recoil, imparting additional momentum and hence higher kinetic energy to the ejected electron. We emphasize here that the recoil of the ion core involves large momentum because of the ion mass, but that the recoil ion does not receive an appreciable amount of kinetic energy from the incident proton. As will be demonstrated later in numerous examples, the production of very energetic electrons by fast incident protons drops sharply beyond this free-electron limit. From Eq. (B7) of Appendix B we see that the free-electron energy limit for electrons ejected in directions other than that of the incident beam will be less than the maximum given by Eq. (10), which is, in turn, far less than the incident energy of the proton, T_0 .

D. Slow Incident Particles

When projectile speeds are sufficiently low ($v \lesssim 3$ a.u.), the "two-center" (ionized target plus receding projectile) nature of the collision complex has an important effect on the dynamics of electron ejection. While negative projectiles such as electrons repel ionized target electrons, protons attract them, causing an enhancement in the doubly-differential cross sections at forward-ejection angles. This attraction results in two mechanisms, or "channels", for ionization unavailable to negative-projectile collision complexes: charge transfer to the continuum (more recently labeled electron capture to the continuum—see, for example, Crooks and Rudd, 1970; Maeck, 1970), in which the ejected electron has a velocity closely matching that of the projectile, and "saddle-point" ionization (Olson *et al.*, 1987), where electrons stranded on or near the saddle point of the electric potential between the positive target ion and receding projectile emerge with roughly half the projectile velocity. While ionization due to charge transfer to the continuum contributes little to the total cross section, a saddle-

point mechanism provides a significant fraction of the ionized electrons and is responsible for differences in the cross sections for, say, protons and antiprotons (see Kikura and Inokuti, 1988; Okon and Gay, 1988; Fainstein *et al.*, 1989b; Schultz, 1989).

E. Rutherford cross section

The collision of a charged particle with another at rest is described by the Rutherford scattering formula, which can be written

$$\frac{d\sigma}{dW} = (4\pi\alpha_0^2 / TWR/W)^2, \quad (11)$$

where W is the kinetic energy of the target particle after the collision, T is the kinetic energy of an electron with the same speed as the incident particle [$T = (m/M)T_0$ and hence $T = T_0$ only for incident electrons or positrons; see Appendix A], and a_0 is the Bohr radius (0.529 Å). This formula is obtained from the usual expression for the Rutherford scattering cross section in terms of θ (Landau and Lifshitz, 1965) by assuming all momentum transferred to the target electron remains with it upon ejection from the atom, as would be the case for a free electron. This is the correct quantum-mechanical result for electrons at rest, which is singular at $W=0$. A bound atomic electron, however, is not at rest, and part of the energy transfer must be used to overcome the binding, with the remainder going into kinetic energy. Consequently it is logical to replace W by the energy transfer E needed to eject an electron of energy W , i.e.,

$$\mathbf{E} = \mathbf{W} + \mathbf{I}. \quad (12)$$

With this substitution, the singularity in the original Rutherford cross section is removed. The modified Rutherford cross section, which is an *approximation* to the original but singular Rutherford scattering cross section, is given by

$$\frac{d\sigma_R}{dW} = (4\pi\epsilon_0^2/T^2)(R/E)^2. \quad (13)$$

We shall refer to the "modified" Rutherford cross section, Eq. (13), as the Rutherford cross section hereafter for brevity, while Eq. (11) will be referred to as the "original" Rutherford cross section. The modified Rutherford cross section will, of course, approach the original Rutherford cross section when $W \gg I$. For a target atom or molecule with complex shell structure, Eq. (12) is not unique because most experiments measure only W without distinguishing the shell from which an ejected electron comes. As is shown later, Eq. (12) must be expanded and E must be defined for each subshell in such a case. The expanded form will be used, however, only to help in the understanding of the qualitative behavior of single-differential cross sections.

F. Binary collision peak

In doubly-differential cross-section measurements, the energy and angular distributions of the ejected electrons

TABLE I. Binding (I) and kinetic (U) energies (eV) and occupation number (N) of some rare gases and diatomic molecules. Binding energies are experimental data, and the kinetic energies are those calculated from nonrelativistic Hartree-Fock wave functions.

Shell	He	Ne	Ar	Kr	Xe	N
1s	I	I	I	I	I	2
	24.59	39.51	4192.9	14325.6	3456.4	38899.6
2s	I	I	I	I	I	2
	48.7	141.88	683.1	3406.9	5432.8	9240.0
2p	I	I	I	I	I	6
	21.60	116.02	249.18	3375.0	4889.4	8229.7
3s	I	I	I	I	I	2
	29.24	103.5	295.2	829.8	1093.2	2481.8
3p	I	I	I	I	I	6
	15.82	78.07	216.8	773.7	937.7	2412.9
3d	I	I	I	I	I	10
						2283.8
4s	I	I	I	I	I	2
						696.9
4p	I	I	I	I	I	6
						635.3
4d	I	I	I	I	I	10
						495.7
5s	I	I	I	I	I	2
						110.4
5p	I	I	I	I	I	6
						79.74

TABLE IIb. Binding (ϵ) and kinetic (U) energies (eV) and occupation number (N) of some polyatomic molecules. The binding energies are mostly experimental values, and the kinetic energies are calculated values using DZP (double ζ + polarization) basis sets [for the DZP basis set, see Stevens *et al.* (1984)] for SF₆ and TeF₆, and Dunning and Hay (1977), pp. 1-27] MO molecular orbital [Experimental values are marked by an asterisk. [Most experimental binding energies (vertical ionization potentials) are from Berkowitz (1976) except for NH₃ (Gibson *et al.*, 1985), CH₄ (Dyke *et al.*, 1976), CO₂ (Samson and Gardner, 1973), SF₆ (Potts *et al.*, 1990), and C₂H₂ (Nikolic and Vilesov, 1974)].

MO	I	U	N	MO	I	U
NH ₃	423.8	1204.6	2	C ₂ H ₆	290.2°	871.1
	1a ₁ (N 1s)		2		1a _{1g} (C 1s)	871.4
	30.09	100.9	2		1e _{1g} (C 1s)	872.2
	17.47	72.25	2		1e _{2g} (C 1s)	872.6
	16.1	87.96	2		1b _{1g} (C 1s)	718.86
	3e ₁	46.86	1		2a _{1g}	85.31
CH ₄	11.14°				1e _{1g}	22.7°
					2e _{1g}	19.0°
	305.5	872.0	2		3e _{1g}	50.21
	24.57	68.84	2		2b _{1g}	69.15
	52.74	52.74	4		1b _{2g}	76.97
	9.84°	29.73	1		3e _{1g}	64.50
C ₂ H ₂				NH ₃	12.3°	47.90
	291.1°	870.9	2		1a _{1g}	11.8°
	291.1°	873.0	2		3e _{2g}	74.98
	23.5°	98.16	2		1e _{1g}	56.37
	18.38°	66.12	2		1a ₁ (N 1s)	1204.1
	16.36°	64.50	2		2a ₁	98.03
C ₂ H ₄	11.40°	57.24	4		1e	71.33
					3e ₁	84.84
				CH ₄	10.88°	
					290.7°	871.8
					23°	66.68
					14.35°	51.72
C ₂ H ₆				C ₂ H ₆	290.9°	871.4
	290.5°	871.6	2		1a _{1g} (C 1s)	872.4
	290.5°	872.0	2		2a ₁	
	23.6°	69.16	2		1f ₂	
	20.16°	67.73	2			
	15.4°	48.56	4			
C ₂ H ₆	13.5°	65.05	2			
	12.36°	56.26	4			

are determined, while the angular distribution and energy losses of the scattered particles (primary protons) are integrated over. The angular distribution of fast ejected electrons exhibits a prominent peak, known as the binary peak, and the fractional width of the peak narrows as the electron energy increases. This is a direct consequence of billiard-ball-like collisions between the incident particles and the target electrons. We can again use a simple model of a free electron initially at rest to predict the angle θ_0 at which the binary peak will appear (see Appendix B):

$$\theta_{\text{c}} = \cos^{-1} \left[\frac{1}{2} (MW/mT_c)^{1/2} \right] \quad (\text{proton impact}) \quad (14)$$

$$= \cos^{-1} [(W/T)^{1/2}] \quad (\text{electron impact}). \quad (15)$$

An electron bound in an atom or molecule has its own initial momentum distribution, which will be superimposed on the delta-function angular distribution at θ_0 . The actual shape of the binary peak, which is known as the Compton profile, will depend on this initial momentum distribution: it will be wide if the initial momentum dis-

tribution is broad, and narrow if the target momenta are small compared to the momentum of the ejected electron. The binding energy of an ejected electron is only a rough indication of the initial momentum of the electron because electrons in an orbital that has many nodes have high average momentum but low binding energies. To estimate the width of the peak, one should use the average kinetic energy of a bound electron, as opposed to its binding energy [see Tables (a) and (b)].

G. Soft and hard collisions

Proton-atom collisions can be divided into two qualitatively different types: a soft (or a glancing) collision and a hard (or binary) collision. In a soft collision, momentum transfer is small, the impact parameter is large, and the proton's trajectory hardly deviates from a straight line. Most collisions, particularly for fast protons, are of this type.

In a hard collision, momentum transfer is large with a

TABLE 1(b). (Continued).

MO	I	U	N	MO	I	U
	23.68°	81.87	2	1 _{1/2}	19.9°	147.6
	19.1°	67.79	2	2 _g	18.6°	166.8
	15.87°	50.19	2	1 _{1/2}	16.9°	178.0
	14.66°	68.19	2	3 _{1/2}	16.9°	176.8
	12.85°	57.35	2	1 _{1/2}	15.8°	191.2
	10.51°	52.36	2		(CH ₃) ₂ NH (dimethylamine)	
				1e ⁻ (N ls)	422.7	1206.1
H ₂ O	539.7°	1589.5	2	1e ⁻ (C ls)	871.9	871.9
	32.2°	142.0	2	2e ⁻ (C ls)	305.8	871.9
	18.55°	97.39	2	3e ⁻	32.62	93.69
	14.73°	118.4	2	2e ⁻	25.79	74.49
	12.61°	122.9	2	4e ⁻	23.26	75.44
				5e ⁻	16.70	62.30
CO ₂				6e ⁻	15.49°	53.86
	541.0°	1589.6	2	3e ⁻	15.05°	62.74
	541.0°	1589.7	2	4e ⁻	13.85°	55.14
	297.5°	872.1	2	7e ⁻	13.27°	66.22
	38.6°	151.0	2	5e ⁻	12.64°	68.12
	37.0°	154.2	2	8e ⁻	8.94°	86.74
	19.4°	148.3	2			
	18.08°	140.2	2			
	17.60°	100.1	4	1e _{1/2}	47.61	52.12
	13.79°	128.6	4	1 _{1/2}	45.85	61.44
				1 _g	45.01	65.31
				2e _{1/2}	27.55	93.45
SF ₆ (K shell of F and K and L shells of S omitted)				2 _{1/2}	23.05	129.2
	45.66		2	1 _{1/2}	21.17	151.0
	44.2°	60.79	6	1 _{1/2}	19.74	170.2
	41.2°	67.94	4	3 _{1/2}	19.46	171.0
	39.3°	67.94	4	2e _g	19.31	167.5
	26.8°	93.62	2		18.97	180.9
	22.5°	124.1	6	1 _{1/2}		

small impact parameter, and the proton's trajectory is significantly altered. The basic characteristics of a hard collision are similar to those of an elastic collision between two billiard balls, in spite of the fact that energy is lost, since the energy loss is small relative to the total energy. Hard collisions correspond to "direct hits" in the classical sense, and for these collisions there is a large energy transfer to the electrons, which then emerge from the collision in a sharp peak (known as the binary peak, see Sec. III F), which is easily predicted using classical mechanics. Since these collisions are basically classical in nature, they are well described by the Rutherford formula, as described in Sec. III E. The contribution of hard collisions to a total ionization cross section is more significant for slow incident protons than for fast protons.

H Optical (zero-momentum-transfer) limit

^a In the plane-wave Born approximation, the generalized oscillator strength, which is basically the form factor

describing a collision, reduces to the dipole oscillator strength in the limit of zero momentum transfer. As discussed by Rudd *et al.* (1985) for the case of ionization cross sections, this connection between the generalized oscillator strengths and dipole oscillator strength for singly-differential cross sections can be used to check the consistency of experimental SDCS's by formulating semiempirical models for SDCS's (see IV). Although the zero-momentum-transfer limit is reached in an inelastic collision, the physically all minimum momentum transfer becomes very small for fast projectiles. Hence this dipole contribution is significant for soft collisions with fast protons, even dominating the SDCS at incident energies of a few eV and above. In the optical limit, collisions with fast ions correspond to the atom absorbing a photon. A free electron, however, cannot absorb a photon because the total momentum cannot be conserved as a third body (the nucleus in a real atom) to recoil. As a result, classical methods treating atomic electrons as free electrons (even with momentum distributions asso-

with the electrons)—such as those described in Sec. V—cannot properly account for this dipole contribution and therefore are unreliable for collisions with fast protons.

Semiclassical treatment and the plane-wave Born approximation

Although an ideal formulation of a collision theory could be based on quantum mechanics, one can treat the trajectory of heavy projectiles classically, while describing the interaction between the projectile and a target atom or molecule using quantum mechanics. This approach is called semiclassical collision theory. The basic assumptions for the validity of the semiclassical theory are (a) that the projectile has high momentum, $k_0 \gg 1$, and (b) that the projectile energy is far greater than any interaction potential V_{int} it will encounter, i.e., $T_0 \gg V_{int}$. Under these assumptions, an integrated cross section obtained from a semiclassical theory by integrating over the scattering angle reduces to the integrated cross section derived from the plane-wave Born approximation (Bethe and Jakiw, 1966).

Both assumptions (a) and (b) above are easily satisfied by a slow but heavy projectile such as a proton because of its large mass and the fact that it has a large kinetic energy compared to the usual energy loss involved in an ionizing collision. The normal criterion for validity of the PWBA is $T \gg E$, where T is the energy of an electron with the same speed. For protons, condition (b) can be satisfied although the usual validity condition for the PWBA is not satisfied. This is the reason that the PWBA cross sections for slow (< 1 a.u.) protons agree well with experiment, even though this would not be anticipated from the normal PWBA condition.

IV. THEORETICAL TREATMENTS

The theoretical calculations of singly-differential cross sections for proton-impact ionization fall into three general categories, the classical binary-encounter approximation, the classical-trajectory Monte Carlo approach, and quantum-mechanical methods.

A. Binary-encounter approximation

The approximation made in this method is to treat the collision as a classical one between the projectile and a single electron in the target; the nucleus and the remaining electrons in the target play no part except that of providing a binding energy for the electron being ejected. In this model the energy transfer E and the energy W of the ejected electron are related by Eq. (12). The justification for using a classical model lies in the fact that differential cross sections (angular distributions) for Coulomb scattering of unlike particles are the same when calculated using either classical physics or quantum mechanics

(Mott and Massey, 1965).

Thomson (1912) utilized the results of the Rutherford scattering theory and derived an expression that may be converted into the Rutherford cross section of Eq. (11). For the Thomson result, the target electron was assumed to be at rest before the collision. This restriction was removed in the work of Williams (1927) and in the more general treatment of Thomas (1927). The results of Thomas (1927) are given for the case of proton impact in a particularly compact form by Vriens (1967). While the binary-encounter-approximation results of Vriens may be evaluated by using a delta-function distribution for the initial momentum of the atomic electron, better results are obtained by using a more realistic distribution of momenta, which must then be integrated over. Rudd *et al.* (1971) calculated binary-encounter-approximation results using the quantum-mechanical Fock hydrogenic momentum distribution. Some of these results are shown in Fig. 1, where it is seen that the agreement with experiment is quite good at high primary energies but deteriorates at lower energies. It should be noted that the Fock distribution depends upon a parameter that is the average initial electron velocity for the atomic electron. For the results shown in Fig. 1, the binding energy was used to calculate this average velocity. In some cases, a small improvement may be effected by using Slater's rules (Slater, 1930; Clementi and Raimondi, 1963; Clementi, Raimondi, and Reinhardt, 1967) or some other method to obtain this average velocity.

A simpler form of the binary-encounter theory leads to a singly-differential cross section of the form (Thomas, 1927; Vriens, 1967; Inokuti, 1971)

$$d\sigma_{BE}/dW = (d\sigma_B/dW)K[1 + 4U/3E] \quad (16a)$$

for $E_{min} \leq E \leq E_{max}$.

$$d\sigma_{BE}/dW = (d\sigma_B/dW)K U/6E [(4T/U)^{1/2}]^2 + [1 - (1 + E/U)^{1/2}]^2 \quad (16b)$$

FIG. 1. Comparison of experiment and the binary-encounter approximation for the singly-differential cross sections for ionization of helium by 10 to 100 keV protons. The binary-encounter approximation was obtained by integrating over a Fock distribution of energies for the atomic electron.

$$\begin{aligned} \text{for } E_{-} \leq E \leq E_{+} \text{, and} \\ d\sigma_{BE}/dW = 0 \quad (16c) \\ \text{for } E > E_{+} \text{, where } U \text{ is the kinetic energy of the target electron and} \\ E_{\pm} = 4T \pm 4(U)^{1/2}. \quad (16d) \end{aligned}$$

It is tempting to equate the minimum energy transfer E_{min} to the ionization threshold 1, but the quantum-mechanical derivation of Eq. (16a) assumes that $U < E$ (Inokuti, 1971). Also, the fact that the target electron must gain energy after a binary collision requires that $T \geq U$. Since most atoms and molecules have a U value of the order of 1–4 atomic units for valence electrons, the minimum T for which Eqs. (16a) and (16b) are valid is of the order of 25–100 keV for incident protons.

Again, the relationship between E , W , and U must be redefined for multishell atoms. Binary-encounter theory does not properly account for the logarithmic dependence of ionization cross sections on T or T_0 , which arises from the dipole interaction and dominates ionization cross sections at high incident energies.

B. Classical-trajectory Monte Carlo method

The binary-encounter approximation discussed in Sec. IV.A treats atomic ionization as a binary collision between the incident proton and the electron to be ionized, without involving the rest of the atom (Gryzinski, 1959; 1965a, 1965b, 1965c; Gerjuoy, 1966; Vriens, 1969; Bonseq and Vriens, 1970). This early model was extended by Abrines and Percival (1966a, 1966b) to incorporate more realistic three-body dynamics. Such a treatment, which has become known as the classical-trajectory Monte Carlo method, has been applied to atomic ionization by Bonseq and Banks (1971), Olson and Salop (1977), Olson (1983), Reinhold and Falcon (1986), Olson *et al.* (1987), Reinhold *et al.* (1987), Olson and Gay (1988), and Reinhold and Olson (1989).

In the classical-trajectory Monte Carlo method, the initial state of the ionized electron is represented by a momentum distribution chosen in such a way that it is at least a sensible representation of the momentum distribution one would get from quantum-mechanical wave functions (for the case of scattering from hydrogen, this momentum distribution is exact). The rest of the atom is treated as an inert core represented either by a screened Coulomb potential or by a model potential. In both cases, the independent-electron model (Hanstee and Moschick, 1972; McGuire and Weaver, 1977) is used for electron ejection from many-electron atoms. In the independent-electron model, correlations between the atomic electrons are neglected and it is assumed that each electron can be regarded as being independent.

The calculation proceeds by randomly choosing the phase-space coordinates (i.e., position and momentum) for the atomic electron, using the above momentum distribution, and by randomly choosing an impact param-

eter for the incident proton. The evolution of the collision system is then found by integrating the classical equations of motion for the three-body system of projectile target electron, and atomic core from a large initial projectile-target separation to a large final separation. The relative energies and positions of the particles are then used to determine scattering angles and which reaction, if any, has occurred. This procedure is repeated a large number ($\sim 10^5$) of times. After a sufficiently large ensemble of projectile-target configurations has been sampled, the differential cross sections are determined. Although there have been numerous classical-trajectory Monte Carlo calculations performed for various scattering processes, in the case of singly-differential cross sections for proton-impact ionization, the most complete calculations reported to date are for atomic hydrogen (Olson, 1983; Reinhold *et al.*, 1987) and helium target (Abrines and Percival, 1966; Reinhold and Falcon, 1986; Olson *et al.*, 1987; Olson and Gay, 1988; Reinhold and Olson, 1989).

C. Quantum-mechanical methods

The quantum-mechanical treatments for atomic ionization by proton impact fall into three different classes: (1) those which treat the electron-target interaction as a strong interaction and the electron-projectile interaction as a weak interaction; (2) those which treat the electron-target interaction as strong and the electron-projectile interaction as weak for the incoming proton and as weak for the outgoing proton; and (3) those which treat both the electron-target and electron-projectile interactions as strong interactions. Clearly, treatments of type (1) will be valid when the outgoing electron and projectile have significantly different speeds or outgoing directions. Treatments of type (3) will be required if the ejected electron and projectile have similar speeds and are leaving the collision region in similar directions.

1. Weak initial- and final-state electron-projectile interactions

If the electron-projectile interaction is weak, this interaction may be treated perturbatively. Theoretically, this is accomplished by expressing the wave function for the electron as a single-center wave function whose origin is located at the target nucleus. The interaction between the electron and projectile is ignored in the formation of the electron wave function and, as a result, this interaction appears only in the interaction potential in the transition matrix element, which is treated perturbatively.

The calculations that have been performed within this framework have assumed either that the projectile is undeflected and moves in a classical trajectory or that the projectile wave function can be expressed as a plane wave. The former approach of assigning a classical trajectory to the heavy projectile and treating the rest of the problem quantum-mechanically is known as the semiclassical

sical approximation (Bang and Hansteen, 1959), and the latter approach is called the plane-wave Born approximation (PWBA). Although there has been considerable use of the semiclassical approximation for total cross sections for inner-shell ionization (Madison and Merzbacher, 1975), there have been relatively limited applications to singly-differential cross sections for proton impact (Mukoyama *et al.*, 1985). It can be shown that the semiclassical approximation and PWBA yield identical results for energy distributions of the ejected electron in heavy-particle ionization (Bethé and Jastrow, 1968; Madison and Merzbacher, 1975). Most of the work germane to this review has been performed within the PWBA.

The PWBA (or standard straight-line trajectory semiclassical approximation) will certainly be invalid if the proton is deflected through a large angle ($> 1^\circ$). However, for the types of experiment germane to this review, this is a good approximation, since the results are integrated over proton scattering angles, and the major contributions to the cross section come from very small proton scattering angles. The distinction between different calculations of this type then lies in the treatment of the ejected-electron wave function. For the calculations that have typically been labeled PWBA's, the ejected-electron wave function is approximated as a plane wave, and for the distorted-wave Born approximation (DWBA), the ejected-electron wave function is calculated as an eigenfunction of some model potential representing the residual target ion.

In the standard theoretical development, a partial-wave expansion is made for the final-state ejected-electron wave function. The radial part of this wave function $\chi(k, r)$ for a partial wave with angular momentum l for the ejected electron is a solution of the Schrödinger equation,

$$\left[\frac{d^2}{dr^2} - \frac{l(l+1)}{r^2} - V(r) + k^2 \right] \chi_l(k, r) = 0, \quad (17)$$

where $V(r)$ is a (spherically symmetric) potential representing the residual ion. Over the years, there have been various choices made for this potential ranging from so potential (PWBA) to a Coulomb potential for some effective charge or a numerical potential obtained from Hartree-Fock wave functions for the atom in question. In terms of nomenclature, the effective-Coulomb-field choice would appropriately be called the Coulomb-Born approximation and the numerical Hartree-Fock-potential choice would be called the DWBA. The difference between the Coulomb-Born and DWBA is most pronounced in the doubly-differential cross section at large scattering angles. In general, it is best to use a DWBA even for the singly-differential cross section, since significant differences between the two approaches can be observed.

The DWBA approach was discussed by Rudd *et al.* (1985), and the formulas for the SDSCs are contained therein; we shall not repeat that presentation here. The interested reader is referred to that review for a discussion of the philosophy of the Born approximation, a description of the calculation of self-consistent-field wave functions and potentials, orthogonality requirements, different types of DWBA calculations, conditions for validity of the DWBA, the numerical problems associated with a DWBA calculation, the connection between incident protons and electrons, the connection between proton- and photon-impact ionization, and the low-energy behavior of the cross sections.

2. Strong initial-state interactions and weak final-state interactions

The Glauber approximation (Glauber, 1959) is designed to include a strong electron-projectile interaction in the initial state. It is very similar to the Born approximation except that instead of using a plane wave for the initial projectile state, it uses an eikonal approximation for the exact wave function. In the eikonal approximation, the initial state is a plane wave modified by a phase factor which is proportional to the average of the perturbing potential over the trajectory of the particle. When used in the scattering amplitude, it can be seen that this eikonal wave function generates the first Born amplitude exactly and higher Born amplitudes approximately. The Glauber approximation is obtained from the eikonal amplitude by choosing a particular trajectory for the projectile. For the final state of the system, the typical Glauber calculation would use the same type of wave function as the typical Born calculation. Consequently, in terms of the strengths of interactions, the Glauber approximation assumes a stronger initial-state electron-projectile interaction than does the Born and the same weak final-state electron-projectile interaction. As a result, in similarity to the Born approximation, the Glauber approximation would not be expected to be valid for those cases in which the electron is ejected near the projectile and with the same speed.

The Glauber approximation was first applied to atomic physics problems by Franco (1968). Golden and McGuire (1974, 1977) and McGuire (1982) applied the Glauber approach to the problem of atomic ionization by heavy projectiles and found that it yielded accurate total ionization cross sections at high energy. Limited results have been reported for the singly-differential cross section, which is of interest here.

3. Strong electron-projectile interactions

a. Continuum-distorted-wave method

The PWBA, DWBA, or Glauber methods would not be expected to be valid when the ejected electron leaves the collision with approximately the same velocity as the projectile proton, since there would then be a strong final-state interaction that is treated only to first order in the perturbation expansion. When this happens, the at-

tractive nature of this force will cause an enhancement of the electrons being scattered in the direction of the proton. This effect has been observed in double-differential cross-section measurements and has been called both charge transfer to the continuum and, more recently, electron capture to the continuum, as was discussed in Sec. III.D.

Over the last several years, there has been a significant effort directed towards the development of theoretical models that take into account both the final-state electron-target interaction and the final-state electron-projectile interaction in a symmetrical manner (Ryufuku, 1982). Such treatments by definition require a two-center final-state wave function, since one part of the electronic wave function must be centered on the target and another part on the projectile. A review of the experimental observation and theoretical treatment of two-center effects has recently been given by Fainstein *et al.* (1991). One theoretical model that has been successful in its treatment of two-center effects is the "continuum-distorted-wave" approach. Cheshire (1964) developed this model for charge-exchange scattering, and Belkic (1978) applied it to atomic ionization by heavy particles. The primary characteristic of a continuum-distorted-wave calculation is that all two-particle Coulomb interactions are contained explicitly in the initial- and final-state wave functions. As a result, the final-state wave function in the continuum-distorted-wave approach is represented as a product of a Coulomb wave function for the electron-target subsystem, a Coulomb wave function for the electron-projectile subsystem, and a Coulomb wave function for the projectile-target subsystem. The initial-state wave function is expressed in a similar fashion except that the electron-target wave function is an initial bound state for this case.

A modified version of the continuum distorted wave was proposed by Garibotti and Miraglia (1980), who used the final state described above but assumed a weak electron-projectile interaction in the incident channel. As a result, the initial-state wave function in that work was chosen to be a product of a plane wave for the projectile and a bound state for the electron (the same type of choice is made in the PWBA). Previously, however, Belkic (1978) found that it was important in general to assume a strong electron-projectile interaction in the initial state also. Crothers and McCann (1983) developed the continuum-distorted-wave method within the framework of the semiclassical impact-parameter time-dependent approach. For heavy projectiles it is expected that the impact-parameter method should be essentially equivalent to full quantal methods. In fact, Belkic (1978) demonstrated the equivalence for forward scattering and very massive targets. In the Crothers and McCann (1983) work, the final state is treated in the standard continuum-distorted-wave fashion and the initial state is represented as an eikonal approximation to the initial-state continuum distorted wave. Using the eikonal initial state has proven to be very successful, and this type of

calculation is now called the CDW-EIS (continuum-distorted-wave eikonal-initial-state) approximation. Fainstein *et al.* (1988a) extended the CDW-EIS approximation from the case of ionization of a molecular target by a bare ion to the multielectronic case, which there is a single active electron, and have successfully applied it to the problem of proton and antiproton ionization of heavier atoms (Fainstein *et al.*, 1988b, 1989a, 1989b). The primary interest and motivation most of the continuum-distorted-wave work has been desire to understand and interpret experimental DE results, but some SDSC results have also been reported (Fainstein *et al.*, 1988, 1989b; Crothers and McCann, 1983; Belkic, 1978).

b. Other methods for strong electron-projectile interactions

In addition to the continuum-distorted-wave method there are other theoretical approaches that contain nonperturbative strong electron-projectile interaction. This interaction is included exactly in the classical trajectory Monte Carlo method described in Sec. 1. Two other approaches also deserve mention — coupled-channels approach and direct integration of time-dependent Schrödinger equation.

Shakeshaft (1978) performed a coupled-state calculation for proton-hydrogen scattering that used wave functions centered on both the target and the projectile. This work, the standard time-dependent impact-parameter coupled-state method was used and 35 bound functions centered on both the projectile and the target were used in the expansion of the electron wave function. Singly-differential cross sections were not reported that work, but it was noted that for energies less than about 75 keV, charge-transfer-to-the-continuum effects are significant, to the extent that theories neglect them, such as the PWBA or DWBA, should be in quite below that energy. There have been numerous other coupled-channels calculations for atomic ionization by heavy projectiles, but the focus of those works is outside the scope of this review (see, for example, Reading *et al.*, 1979, 1981; Reading and Ford, 1979, 1987; Janey and Presnyakov, 1980; Ford *et al.*, 1981; Fritsch and Lin, 1983; Paul and Obermann, 1983; Winter and Lin, 1984).

The last method we shall mention, which automatically includes a strong electron-projectile interaction, is direct integration of the time-dependent Schrödinger equation by Butcher (1982). In this work, it was assumed that the projectile was a bare nucleus moving with a uniform velocity in a straight line. The time-dependent Schrödinger equation was then propagated from the initial state to the final state and cross sections for excitation, capture into bound states, direct ionization, a charge transfer to the continuum were determined from the resulting final states. Although only total cross sections were reported in this work, it does represent an interesting theoretical development.

D. Comparison of experiment and theory

At present, *ab initio* theories are limited in their validity to certain ranges of proton energies and/or to certain targets. Similarly, available experimental data are limited in the ranges of ejected-electron energies and/or incident-proton energies. Often the missing parts in the experimental data are supplemented using semiempirical models. Section VI of this review will show that the experimental single-differential cross-section data can be expressed in terms of analytic formulae with target-dependent adjustable parameters. The recommended experimental data for He expressed in this parameterized form are compared with the DWBA calculations described by Rudd *et al.* (1985) and the classical-trajectory Monte Carlo calculations of Schultz and Reinhold (1989) at incident proton energies of 100 keV, 400 keV, and 1 MeV in Figs. 2-4. As was noted earlier, Shakeshaft (1978) demonstrated that the effects of charge transfer to the continuum start to become significant below 75 keV, so the DWBA would not be expected to be valid for much lower energies, since charge-transfer-to-the-continuum effects are included only to first order in a perturbation expansion. In general, both theories give a reasonably good representation of the experimental data. At 1 MeV the DWBA is in very good agreement with experiment over the entire energy range of the ejected electron. At this energy, the classical-trajectory Monte Carlo result is in excellent agreement with experiment for the higher electron energies but falls below the experiment for the lower energies, where the cross sections are larger.

This problem with the slow electrons is a manifestation of the fact that the classical calculations give an asymptotic proton energy behavior of T_0^{-1} instead of the quantum-mechanical $T_0^{-1} \ln T_0$ behavior, a dependence that has been well verified experimentally. The failure of the classical-trajectory Monte Carlo approach for large T_0 is a direct result of the fact that the classical calculations

FIG. 2. Singly-differential cross sections for ionization of helium by 100-keV proton. The solid curve represents the best fit to experimental data; long-dashed curve, distorted-wave Born approximation; short-dashed curve, classical-trajectory Monte Carlo.

FIG. 3. Same as Fig. 2 except for 400-keV proton.

tions do not contain the dipole contribution to the scattering process, which is the source of the $T_0^{-1} \ln T_0$ energy dependence. While the dipole contribution is significant for large T_0 , nondipole terms are larger than the dipole term at intermediate T_0 , which explains why the classical calculations are better in this energy region. At 400 keV the classical-trajectory Monte Carlo result is in better agreement with experiment than the DWBA. Here the classical-trajectory Monte Carlo calculation is in excellent agreement with experiment over the entire secondary-electron energy range, while the DWBA is somewhat too large for low electron energies. At the lowest incident energy considered, 100 keV, the DWBA is again in somewhat better agreement with experiment than the classical-trajectory Monte Carlo approach. We note, however, that these Monte Carlo calculations were performed using a screened Coulomb potential to represent the target core, and that Reinhold and Falcon (1986) have shown that the use of a model potential interaction brings the classical-trajectory Monte Carlo result into better agreement with experiment at lower secondary-electron energies.

In general, the DWBA will be in very good agreement with experiment for high proton energies ($T_0 \geq 1$ MeV), in reasonably good agreement for intermediate energies

FIG. 4. Same as Fig. 2 except for 1-MeV proton.

molecules by charged-particle impact. In this momentum work, he introduced the generalized oscillator strength, which is basically a collision form factor that reduces to the dipole oscillator strength f in the limit of zero-momentum transfer and that satisfies a sum rule similar to that for f . The generalized oscillator strength for a given transition is a function of momentum transfer which is determined by the angular distribution of the scattered particle. Bethe showed further that the cross section to excite an atom to state n , σ_n , depends on $T = (m/M)T_0$, i.e., on the velocity of the incident particle. The cross section integrated over the scattering angle of the incident particle is conveniently expanded as a function of T :

$$\sigma_n = (4\pi a_0^2 R / T) [a_n \ln(T/R) + b_n + c_n R / T + \dots] \quad (1)$$

where a_n , b_n , and c_n are constants that depend on the initial and final states of the target but not on the projectile energy. Note that T , not T_0 , is used in Eq. (18) regardless of the projectile mass. In particular, a_n has a simple relationship to the dipole oscillator strength f_n and excitation energy E_n :

$$a_n = f_n R / E_n \quad (10)$$

For the singly-differential cross section, Eqs. (18) and (10) become

$$d\sigma / dW = (4\pi a_0^2 R / T) [a(E) \ln(T/R) + b(E) + c(E) R / T + \dots] \quad (2)$$

$$a(E) = (d f / dE) (E / R) \quad (21)$$

and $E = W + I$ is now the excitation energy to a specific continuum final state. Note that the singly-differential cross sections discussed in this review are differential in the energy of the ejected electron and are expressed in units of $(\text{area}) \times (\text{energy})^{-1}$. This implies that $a(E)$, $b(E)$, and $c(E)$ have the dimension of $(\text{energy})^{-1}$.

Another important conclusion from Bethe's work is that the essential part of the PWBA is the first two terms in the square brackets of Eqs. (18) and (20). Moreover, these two terms are the same for incident protons and electrons of equal speeds. Other physical effects not included in the Bethe theory—such as the distortion of the projectile wave function and the polarization of the target charge distribution—may introduce a T dependence that can be more important than the T^{-1} terms associated with c_n or $c(E)$ for fast projectiles. Differential cross sections for protons with $T_0 < 100$ keV, for example, may be altered significantly by charge transfer to the continuum, a process not included in the Bethe theory. Experimental data for neutral atoms indicate that the $c(E)$ term for ionization is small for incident protons of a few hundred keV and higher.

For a multishell atom or molecule, Eqs. (20) and (21) must be generalized to accommodate electrons ejected with the same kinetic energy W but from different shells.

V. CONSISTENCY CHECKS

Most measurements of singly-differential cross sections are indirect, i.e., SDCS's are deduced by integrating DDSCS's over the electron-ejection angle. Moreover, a DDSCS must be consistent with the corresponding total ionization cross section when the SDCS is integrated over the electron energy.

The measurement of a DDSCS for an atom or molecule involves many continuous variables, such as the incident electron energy, the secondary electron energy, and the electron ejection angle. The data thus tend to be incomplete if one wishes to perform integrations to obtain a DDSCS. Therefore it is important to identify methods for checking the consistency of existing data and to supplement missing parts by comparison with other available information.

For instance, if Eq. (4) does not agree with a known value of the total ionization cross section, it is desirable to know if some part of $d^2\sigma/dWd\Omega$ may be causing the discrepancy rather than simply to renormalize $d^2\sigma/dWd\Omega$ uniformly. One can also interpolate and extrapolate experimental $d\sigma/dW$ in both W and T_0 if it can be established that the observed $d\sigma/dW$ exhibits qualitative trends expected from theoretical considerations.

In this section, we discuss several powerful consistency checks for identifying qualitative trends in $d\sigma/dW$. Although these trends are based on the PWBA and are hence valid only for fast incident protons ($T_0 > 300$ keV), they are nevertheless very useful in detecting problems in experimental data and in supplementing missing parts in such data.

A. Bethe theory

Bethe (1930) derived the basic framework of the Born approximation for ionization and excitation of atoms and

In the usual experimental situation, where the initial electron shell is unknown and contributions from individual shells must be summed over, Eq. (20) is thus replaced by

$$d\sigma/dW = (4\pi\epsilon_0^2 R^2/T) \sum_j [a_j(E_j) \ln(T/R) + b_j(E_j) + c_j(E_j)/R + \dots] \quad (22)$$

with

$$E_j = W + I_j, \quad (23)$$

where I_j is the binding energy of the j th orbital, and

$$a_j(E_j) = (df/dE_j)(E_j/R). \quad (24)$$

In principle, $a_j(E_j)$, $b_j(E_j)$, and $c_j(E_j)$ can be calculated if the corresponding wave functions are known (Kim and Inokuti, 1971), but a systematic study of $a_j(E_j)$ and $b_j(E_j)$ has been carried out only for the ionization of the hydrogen atom (Inokuti, 1971).

The T dependence described in Eq. (22) is valid only when T is larger than the average (orbital) kinetic energies of the bound electrons being ionized [see Tables I(a) and I(b)]. For multishell atoms, the average kinetic energies of the valence and core orbitals are so different that the $T^{-1} \ln T$ dependence predicted by the PWBA may be valid for the ionization of the valence electrons but not for the core electrons. Over most of the range of secondary energies, the contributions from inner shells to $d\sigma/dW$ are small compared to those from outer shells. The T dependence predicted by the PWBA is often observed in experimental cross sections with incident proton energies of a few hundred keV.

8. Platzman plots

The Rutherford cross section, Eq. (13), is the singly-differential cross section for a single bound electron. Hence, if we divide the SDCS by the "modified" Rutherford cross section, the result can be interpreted as the effective number of electrons in the target atom or molecule which participate in the ionizing collision of interest. This is the underlying idea for the Platzman plot (Miller and Platzman, 1957). In this plot, the ratio Y of the actual SDCS to the Rutherford cross section [Eq. (13)] is plotted as a function of R/E ,

$$Y = [d\sigma/dW]_{\text{expt}}/[d\sigma_R/dW] \\ = \frac{T}{4\pi\epsilon_0^2 R^2} [d\sigma/dW]_{\text{expt}}. \quad (25)$$

The choice of R/E as the abscissa makes the area under the Platzman plot proportional to the total ionization cross section:

$$\sigma_{\text{ion}} = \int_0^W [d\sigma/dW]_{\text{expt}} dW \\ = \frac{4\pi\epsilon_0^2 R^2}{T} \int_0^W Y d(R/E), \quad (26)$$

where I_1 is the binding energy of the outermost shell and

$$E_{\text{max}} = W_{\text{max}} + I_1.$$

As was discussed in Sec. III.C, W_{max} for a collision with a free electron is $4T = 4(m/M)T_0$. For a bound electron, however, $W_{\text{max}} \gg 4T$, since the ion core can recoil and impart extra momentum to the electron. Therefore the lower limit of the integral in Eq. (26) is practically zero for protons of a few hundred keV and above. We present an example of a Platzman plot for the ionization of Ar by 1 MeV protons in Fig. 5. The matching continuum dipole function, $E(df/dE)$, is plotted in Fig. 6.

The Platzman plot is a powerful tool for analyzing and identifying distinct features in the SDCS (Kim, 1975a, 1975b, 1975c; 1983). For instance, the dominance of the dipole term in the proton-impact data is evident in Fig. 5. The dip near $R/E \approx 0.3$ in Fig. 6 is known as the Cooper minimum (Fano and Cooper, 1968), and the sharp peak near $R/E \approx 0.07$ in Fig. 5 includes peaks arising from the LMM Auger electrons.

By integrating the area under the SDCS curve from the threshold ($R/E = 0.87$) to $R/E = 0$, one can verify the normalization of the proton-impact data, which, in this example, falls within 10% of the total ionization cross section recommended by Rudd *et al.* (1985). If we assume that only the M -shell electrons participate in ionizing collisions, then the height of the singly-differential cross section near $R/E \approx 0.3$ should be 8, since the dipole interaction essentially vanishes here, and hence the ordinate in the Platzman plot should equal the number of free electrons in the participating shell. In reality, the SDCS in Fig. 5 has $Y \approx 10$, indicating that there are addi-

FIG. 5. Platzman plots of proton- and electron-impact singly-differential cross sections for Ar. The ordinate is the ratio of the SDCS to the Rutherford cross section [see Eq. (25)], and the abscissa is the inverse of the energy transfer, $E = W + I_1$ [see Eq. (23)], where W is the secondary-electron energy and I_1 is the first ionization potential (I_1 is the rydberg). O: 1-MeV ($T = 545$ eV) proton-impact data of Toburen *et al.* (1972); Δ : 500-eV electron-impact data of Opal *et al.* (1972). The solid curve is the recommended SDCS based on Kim's model, discussed in Sec. V.C. The sharp peaks in the proton- and electron-impact data at $R/E = 0.06$ are due to LMM Auger electrons.

by the PWBA should apply to global properties rather than to local details.

D. Comparison with photoionization data

Another prediction of the PWBA is that the leading term in $d\sigma/dW$ at higher energies is the logarithmic term in Eq. (22). This term represents contributions to soft collisions (Sec. III.G) and is directly associated with the continuum oscillator strength df/dE , which can be deduced from photoionization cross sections. As will be shown in the following section, the dipole function a defined in Eq. (24) is distinct from one target to another and its main features remain clearly discernible in the singly-differential cross section even at lower T , where the Bethe formula defined in Eq. (22) is inadequate.

To be useful for consistency checks as well as for modeling of proton- and electron-impact SDCS's, photoionization cross sections for individual shells are needed. Photoionization cross sections usually have energy resolutions far better than those necessary for model SDCS's. Coincidence measurements in electron energy loss or photoelectron spectra in which the energy transfer and the kinetic energy of ejected electrons are identical are needed for this type of consistency check.

E. Comparison with total ionization cross sections

Deducing accurate total ionization cross sections, [Eq. (4)], from experimental doubly-differential cross sections is not straightforward, since experimental DDCS's often do not cover all ranges of θ and W for which $d^2\sigma/dW d\Omega$ contributes significantly to σ_{ion} . In particular, contributions to σ_{ion} from slow ejected electrons are very important. In most cases, about two-thirds of the total ionization cross section for W less than the first ionization potential, yet the experimental cross sections for $W < 1$ eV are often unreliable or unavailable.

This low-energy region is where the Platzman plot combination with photoionization data, can play a special role in providing the missing information needed to perform the integration over W such that σ_{ion} is consistent with the total ionization cross sections measured directly. In fact, one can normalize $d\sigma/dW$ to a known value of σ_{ion} , even if part of the $d\sigma/dW$ is missing, by using the Platzman plot and known values of df/dE . Examples are given in the next section on semiempirical models. The solid curve in Fig. 5 illustrates a Platzman plot in which the area under the curve has been normalized to the total ionization cross section.

F. Relationship with stopping cross sections

A frequently used quantity in radiation physics is the "W value," which is the average energy needed to create an ion. This "W value" is usually determined by

FIG. 6. The dipole function $E(df/dE)$ of Ar as a function of the inverse of the photon energy ($1/E$) in rydbergs (R): O, experimental data compiled by Berkowitz (1979); solid curve, a fit to smoothed experimental data using Gaussian functions and power series (see Sec. V.C). The structure near $R/E = 0.5$ arises from the $3s$ - np window resonances, the dip near $R/E = 0.3$ is the Cooper minimum, and the sharp rise near $R/E = 0.05$ is the onset of the L -shell ionization. The onset of the K -shell ionization appears as another peak near $R/E = 0$.

tional electrons ejected from the L shell and that there are contributions due to the fact that the target electrons are not free but bound with their own momentum distributions, described by the binary-encounter term.

G. Comparison with electron-impact data

As was mentioned in Sec. V.A, the leading terms of proton- and electron-impact cross sections are equal when both projectiles are fast and have equal speed. This equality, which is one of the most significant conclusions of the PWBA, has been observed in numerous examples of proton- and electron-impact ionization and has served as a consistency check between experimental data sets.

The actual range of T for which this resemblance holds depends on the target. For targets with simple shell structures, such as H, He, and H_2 , the singly-differential cross sections for electron and proton impact agree to better than 10% for $T > 1$ keV, while much higher T is needed for targets with inner shells. Proton-impact cross sections for electron-impact ionization and has served as a consistency check between experimental data sets. The actual range of T for which this resemblance holds depends on the target. For targets with simple shell structures, such as H, He, and H_2 , the singly-differential cross sections for electron and proton impact agree to better than 10% for $T > 1$ keV, while much higher T is needed for targets with inner shells. Proton-impact cross sections for electron-impact ionization and has served as a consistency check between experimental data sets.

Since the incident proton energy, $T_0 = (M/m)T$, is almost 2000 times that of an electron with equal velocity, a proton can eject secondary electrons of much higher kinetic energies than those ejected by an incident electron with energy T . In this respect, the resemblance predicted

ing the energy loss of a projectile in a medium by the number of ions it generated—a gross measure of difficulty it is to ionize the medium. The W value of a set is higher than its lowest ionization potential because (a) some of the energy deposited by the projectile is in discrete excitations without producing any ions and (b) the energy lost by the projectile in ionizing collisions normally exceeds the lowest ionization potential. The kinetic energy gained by the ejected electron in the medium can also ionize other targets in the medium and produce additional secondary electrons through successive inelastic collisions until their kinetic energy drops below the lowest ionization potential.

The stopping cross section for ionization, σ_a [Eq. (6)], accounts for ionizing collisions but not for discrete excitations. The total stopping cross section, however, must include both discrete and continuum excitations (Inokuti, 1971). The σ_a defined by Eq. (6), therefore, is a lower bound for the total stopping cross section and constitutes the dominant component in the theoretical determination of the value, although other factors, such as excitations by incident proton and subsequent collisions by secondary electrons, must also be taken into consideration.

SEMIEMPIRICAL MODELS

With the exception of the work of Park et al., all experiments to establish differential ionization cross sections by proton impact have measured angular distributions of ejected electrons as functions of the electron energy. Then, the cross sections were integrated over angle to deduce the singly-differential cross section. Although it is difficult to measure electrons ejected in the extreme forward and backward directions, the integrated cross sections are not sensitive to these angles, since the solid-angle element $\sin\theta d\theta d\phi$ reduces the contributions from the extreme angles. If one wishes to obtain total ionization cross sections, a more serious problem presented by existing experimental data stems from the measurements of slow electrons ($W \leq 10$ eV). Measurements are difficult and often unreliable for slow electrons (see Secs. II and VIII), while their contributions to the total ionization cross section are very important (20–40%). Semiempirical models can successfully supplement missing parts of SDCS's and provide consistency checks between SDCS's and total ionization cross sections.

Using the close relationship between the optical dipole oscillator strengths and the Bethe cross section (see Sec. V A), Kim has shown (Kim, 1975b, 1975d, 1976) that SDCS's for proton-impact ionization can be expressed qualitatively as the sum of a dipole term and the Rutherford cross section. This dipole term is not the same as the $\sigma(E)$ defined by Eq. (21), but rather is scaled by a function of E that depends on the target. This qualitative behavior is best understood through the Platzman plot discussed in Sec. V B. Some of the semiempirical models presented below take advantage of these qualitative

As is implied by limiting the T dependence in the square brackets of Eq. (27) to the logarithmic term, the model is not meant to represent singly-differential cross sections for low T . When there is more than one dominant shell, h in Eqs. (28)–(30) must be defined for each shell, and $A(W)$ and $B(W)$ must be determined for each shell with different power series.

Inokuti et al. (1987) used Eqs. (27)–(30) and fitted proton-impact singly-differential cross sections of CH_4 , NH_3 , and H_2O . The power series in h [Eqs. (28) and (29)] reproduces qualitative features in $A(W)$ and $B(W)$ reasonably well when the incident proton energy is high. This method is thus well suited to represent gross features in SDCS's at high T . The structure of the power series, however, is too simple to reproduce details in $A(W)$, which often serve to distinguish one target molecule from another.

C. Kim's model

In order to provide more flexibility to the semiempirical models based on the Bethe theory allowing its application to lower proton energies and to reproduce the shape of the SDCS more faithfully, a new model is presented below, which expands on the models discussed above (Secs. VI A and VI B).

For fast protons ($T_0 > 0.5$ MeV), the dipole term, $g_1(E)$ in Eq. (22), dominates the singly-differential cross section and is largely responsible for individual differences amongst various targets. The continuum oscillator strengths d^2/dE in Eq. (24) can be deduced from experimental or theoretical photoionization cross sections, though theoretical data near ionization threshold are often unreliable. Once the continuum oscillator strengths are known for a wide range of excitation energies E_j , one can fit formulas similar to Eq. (22) to known SDCS's by assuming simplified forms for functions $b_j(E)$, $c_j(E)$, etc. Contributions from different shells must be evaluated separately for multishell atoms and molecules.

The dipole term is sometimes referred to as the soft-collision term, since the dipole interaction is dominated by impact parameters much larger than the target size. In contrast, the $b_j(E)$ term is known as the hard-collision term, representing the contribution of hard collisions with small impact parameters (see Sec. III G). In reality, $b_j(E)$ includes contributions from binary collisions described by the Rutherford cross section, Eq. (13), and from another term loosely related to the cutoff momentum transfer beyond which the dipole interaction

$$Y_M = \frac{(E d^2/dE) \ln(4JT/R) \{1 + gR/T + h(R/T)^2\} + Y_{\text{Be}} + N}{1 + \exp[k(E - 4T)/R]} \quad (34)$$

for the valence shells of Ar and N_2 , where f , g , h , and k are fitting parameters and N is the electron occupation number of the shell.

The additional T dependence in the square brackets of

diminishes rapidly. While this dipole-interaction cutoff term is proportional to $\sigma_1(E)$, it is also a function of E , which results in an E dependence that is difficult to predict, although it is independent of the incident energy. We emphasize the fact that the knowledge of the dipole oscillator strengths alone will not be sufficient to determine proton-impact cross sections because of this cutoff momentum transfer, which must be included in $b_j(E)$.

Kim's model is designed to take advantage of the Platzman plot, i.e., a plot of the ratio Y defined by Eq. (25) versus R/E . When we divide the Bethe cross section, Eq. (22), by the Rutherford cross section, Eq. (13), then we have

$$Y_{\text{Bethe}} = E(d^2/dE) \ln(T/R) + (E/R)^2 b(E) + (E/R)^2 c(E)/T + \dots \quad (31)$$

indicating the dominant role played by the dipole function $E(d^2/dE)$ as T increases. In the absence of the dipole interaction, $(E/R)^2 b(E)$ approaches the occupation number of each shell participating in the ionizing collision as E increases (Kim, 1975a). The model described below uses these properties and introduces additional T -dependent terms to provide the flexibility needed to represent cross sections at lower T than other models discussed above. Moreover, the dipole function, $E(d^2/dE)$, is fitted by compact analytic expressions that retain all the major features specific to individual atoms and molecules. These analytic expressions provide a far simpler alternative to cumbersome numerical tables of experimental or theoretical differential oscillator strengths.

To illustrate the importance of the dipole interaction in the singly-differential cross section for fast protons, Kim has extracted continuum oscillator strengths d^2/dE from known photoionization cross sections for Ar (Berkowitz, 1979) and N_2 (Berkowitz, 1979; Samson et al., 1987). Then d^2/dE was fitted with a linear combination of Gaussian functions

$$E(d^2/dE) = \sum_i a_i \exp[-(iR/E - b_i)^2/c_i^2] (R/E)^d \quad (32)$$

where a_i , b_i , c_i , and d_i are fitting parameters (see Table II), or with a four-term power series,

$$E(d^2/dE) = \sum_i c_i (R/E)^{d_i} \quad (33)$$

where c_i , $i = 1-4$ are fitting parameters (see Table II). Using these d^2/dE , Kim has fitted experimental SDCS's of Ar and N_2 to a form

the numerator in Eq. (34) allows for a departure from the $\ln T$ dependence predicted by the PWBA, as discussed by Kim and Desciaux (1988). The term Y_{Be} is introduced to account for the fact that target electrons are bound

TABLE II. Parameters for fitting photoionization cross sections of Ar and N₂ with Gaussian functions [Eq. (32)] or power series [Eq. (33)]. The actual fitting was carried out on $E(d\sigma/dE)$, a dimensionless quantity. Binding energies I_p used in converting W into E_p are also listed.

Target	Index i in Eq. (31)	a_i	b_i	c_i	d_i^a	
Ar, M shell	1	7	0.505	0.12	0.01	
	2	12	0.07	0.13	1	
	3	0.3	0.6	0.05	1	
	4	11.3	0.72	0.19	3	
N_2 , L_{α} shell ^b	5	10	0.63	0.1	3	
	1	5.5	0.465	0.155	0	
	2	0.8	0.59	0.035	0	
	3	3.4	0.71	0.14	0	
N_2 , L_{β} shell ^b	4	1.3	0.81	0.09	0	
	5	1.6	0.26	0.08	0	
	6	10	0.11	0.1	1.1	
	1	1.6	0.26	0.06	0	
Ar, L shell	2	0.7	0.36	0.055	0	
	3	0.5	0.525	0.02	2	
	4	0.5	0.47	0.08	1	
	5	0.6	0.12	0.08	0.1	
Shell	6	0.4	0.18	0.05	1	
	Target	[see Eq. (33)]	e_1	e_2	e_3	e_4
	Ar, L shell	48.67	745.6	-141200	616300	
	N_2 , $1\sigma_g + 1\sigma_u$	2.99	5813	30506	-1987000	
Shell	Ar, M	Ar, L	N_2 , L_{α} ^b	N_2 , L_{β} ^b	N_2 , K	
Binding energy, I_p (eV)	15.82	249.18	15.59	28.8	410	

^aMore careful fitting of the d_i parameters is required to reproduce the correct asymptotic (high-energy) behavior of $E(d\sigma/dE)$.

^b $L_{\alpha} = 3\sigma_g + 1\sigma_u + 2\sigma_u$; $L_{\beta} = 2\sigma_g$.

and have intrinsic momentum distributions:

$$Y_{\text{eg}} = (NU/E) [1 - (U/(W+U))^p], \quad (35)$$

where U is the average kinetic energy of the bound electrons [see Table I(a)] and p is a fitting parameter. A value of 8 was assigned to the occupation number N in Eq. (34) for the M shell of Ar and for the L_{α} group ($3\sigma_g, 1\sigma_u$, and $2\sigma_u$ orbitals) of N₂; a value of 2 was assigned for the L_{β} group ($2\sigma_g$ orbital) of N₂. The denominator $W+U$ in Eq. (35) simulates the classical cutoff in energy transfer (see Sec. III C).

The continuum oscillator strengths for the M shell of Ar and the L_{α} and L_{β} groups of N₂ were fitted with five

or six Gaussian functions. Contributions from orbitals with similar binding energies are combined, since small differences in these binding energies are insignificant for the modest level of accuracy attainable with this model.

The contributions to $d\sigma/dE$ from the L shell of Ar and the 1σ shells of N₂ are hydrogenic in shape and were fitted to a power series, Eq. (33). Various binding energies I_p used in relating photoelectron energy W to the photon energy, $E_p = W + I_p$, are also listed in Table II.

The K shell of Ar is ignored in the following discussion because it contributes very little to the ionization cross sections. It will, however, play more significant roles for the stopping power or any other quantity that involves

TABLE III. Parameters for fitting singly-differential cross sections to the Kim model, Eqs. (34)-(36).

Target/shell	f	g	h	k	p	q	r	N
Ar, M shell	0.053	-5	20	0.1	0.3	0.25	0.1	8
Ar, L shell								8
N ₂ , L_{α} shell ^b	0.3	-8	25	0.1	0.2			8
N ₂ , L_{β} shell ^b	0.3	-8	25	0.1	0.2			2
N ₂ , $1\sigma_g + 1\sigma_u$						1.0	0.1	4

^a $L_{\alpha} = 3\sigma_g + 1\sigma_u + 2\sigma_u$; $L_{\beta} = 2\sigma_g$.

TABLE IV. Experimental absolute proton-impact doubly-differential cross sections. All published absolute cross sections known to the authors are listed here.

Investigations	Primary energies (keV)
Hydrogen (H) Park <i>et al.</i> , 1977	25,50,75,145,200
Helium (He) Blauth, 1957	11.8,49
Rudd and Jorgensen, 1963	50,100,150
Rudd <i>et al.</i> , 1966	100,200,300
Park and Schweninger, 1966	100
Toburen, 1971	2000
Stollerfoht, 1971a	200,300,400,500
Stollerfoht, 1971b	150
Stollerfoht and Madson, 1975	300,1000,1500
Stollerfoht and Madson, 1976	5,7,10,15,20,30,50,70,100
Stollerfoht, 1975	4200,5000
Rudd and Andersen, 1979	225,1225
Tokoro and Oda, 1985	10
Gibson and Reid, 1985, 1986	20,30,40,50,60,80,100
Schader <i>et al.</i> , 1986	400,800,1100,1700,2000
Olson <i>et al.</i> , 1987	60,100,150
Bernardi <i>et al.</i> , 1988	150,200
Irby <i>et al.</i> , 1988	60,100
Bernardi <i>et al.</i> , 1989	50,100
Cheng <i>et al.</i> , 1989a	7.5,10,15,20,30,50,70,100,150
Bernardi <i>et al.</i> , 1989b	100
Gay <i>et al.</i> , 1990	100
Neon (Ne) Blauth, 1957	49
Crooks and Rudd, 1971	50,100,150,200,250,300
Toburen <i>et al.</i> , 1978	300,1000,1500
Cheng <i>et al.</i> , 1989a	7.5,10,15,20,30,50,70,100,150
Bernardi <i>et al.</i> , 1990	100
Gay <i>et al.</i> , 1990	100
Argon (Ar) Blauth, 1957	11.8,49
Crooks and Rudd, 1971	50,100,150,200,250,300
Gabler, 1974	300,400,500,600,5000
Criswell <i>et al.</i> , 1977	5,10,20,50
Rudd, 1977	5,7,10,15,20,30,50,70
Toburen <i>et al.</i> , 1978	250,300,500,1000,1500
Toburen <i>et al.</i> , 1978	2000,3000,3672,4200
Saitaka, Urahara, and Oda, 1979	5,20
Gibson and Reid, 1987a,1987b	50
Krypton (Kr) Blauth, 1957	8.8,11.8,49
Manson and Toburen, 1977	1500,2000,3000,3672,4200
Cheng <i>et al.</i> , 1989a	7.5,10,15,20,30,50,70,100,150
Xenon (Xe) Toburen, 1974	300,1000,2000
Hydrogen (H ₂) Blauth, 1957	8.8,11.8,49
Kuyatt and Jorgensen, 1963	50,75,100
Rudd and Jorgensen, 1963	100
Rudd <i>et al.</i> , 1966	100,150,200,300
Toburen and Wilson, 1972	300,500,750,1000,1500

TABLE IV. (Continued).

Investigators	Primary energies (keV)
Rudd, 1979	5.7, 10, 15, 20, 30, 50, 70, 100
Gibson and Reid, 1987a, 1987b	50
Nitrogen (N ₂)	
Blauth, 1957	11.8, 22.3, 49
Toburen, 1971	300, 500, 1000, 1400, 1700
Crooks and Rudd, 1971	50, 100, 150, 200, 250, 300
Stolterfoht, 1971b	200, 300, 400, 500
Toburen and Wilson, 1975	300, 500, 1000, 1400, 1700
Rudd, 1979	5.7, 10, 15, 20, 30, 50, 70
Gibson and Reid, 1987a, 1987b	50
Oxygen (O ₂)	
Crooks and Rudd, 1971	50, 100, 150, 200, 250, 300
Gibson and Reid, 1987a, 1987b	50
Cheng <i>et al.</i> , 1989b	7.5, 10, 15, 20, 30, 50, 70, 100, 150
Carbon dioxide (CO ₂)	
Gibson and Reid, 1987a, 1987b	50
Cheng <i>et al.</i> , 1989b	7.5, 10, 15, 20, 30, 50, 70, 100, 150
Water vapor (H ₂ O)	
Toburen and Wilson, 1977	300, 500, 1000, 1500
Wilson <i>et al.</i> , 1984	300, 4200
Bolzatzsch and Rudd, 1986	15, 20, 30, 50, 70, 100, 150
Gibson and Reid, 1987a, 1987b	50
Ammonia (NH ₃)	
Lynch <i>et al.</i> , 1976	250, 1000, 2000
Wilson <i>et al.</i> , 1984	300, 4200
Sulfur Hexafluoride (SF ₆)	
Toburen <i>et al.</i> , 1977	300, 500, 1000, 1800
Tellurium Hexafluoride (TeF ₆)	
Toburen <i>et al.</i> , 1977	300, 500, 1000, 1800
Methane (CH ₄)	
Stolterfoht, 1971a	200, 300, 400
Wilson and Toburen, 1975	300, 1000, 2000
Lynch <i>et al.</i> , 1976	250, 1000, 2000
Wilson <i>et al.</i> , 1984	300, 4200
Gibson and Reid, 1987a, 1987b	50
Monomethylamine (CH ₃ NH ₂)	
Lynch <i>et al.</i> , 1976	250, 1000, 2000
Dimethylamine [(CH ₃) ₂ NH]	
Lynch <i>et al.</i> , 1976	250, 1000, 2000
Acetylene (C ₂ H ₂)	
Wilson and Toburen, 1975	300, 1000, 2000
Ethylene (C ₂ H ₄)	
Wilson and Toburen, 1975	300, 1000, 2000
Ethane (C ₂ H ₆)	
Wilson and Toburen, 1975	300, 1000, 2000
Benzene (C ₆ H ₆)	
Wilson and Toburen, 1975	300, 1000, 2000

large energy losses of the incident particle. It is difficult to extend the same type of analysis to the *K* shell of Ar at present for lack of experimental singly-differential cross sections specific to that shell.

Kim used a somewhat simpler form of *Y* for the *L* shell of Ar and the two *1s* shells of N₂:

$$Y_L = \frac{(E df/dE) \ln(4qTE/R^2) + Y_{SE} + N}{1 + \exp[(E - 4T)/R]} \quad (36)$$

with fitting parameters *q* and *r*. For the *L* shell of Ar, *N* = 8, while *N* = 4 for the *1s* shell of N₂ (*1s_g* + *1s_u*). The actual values of the fitting parameters are listed in Table III. The *Y* function for the entire target is obtained by summing *Y_M* and *Y_L*.

Experimental singly-differential cross-section data for Ar and N₂ (see Table IV) were used to determine the values of these fitting parameters so that the major

$$d\sigma/dW = (4\pi q_0^2/\beta^2) \sum_j (a_j(E_j) \ln[\beta^2/(1-\beta^2)] - \beta^2 |b_j(E_j) + \dots|) \quad (22a)$$

with

$$b_j(E_j) = b_j(E_j) - 2a_j(E_j) \ln \alpha \quad (22b)$$

where $\alpha = \frac{1}{2}(1 + \beta^2)$ is the fine-structure constant.

The optical functions *E*(*df/dE*) of Ar and N₂ obtained from this model are presented in Figs. 6 and 7, respectively. Fitted singly-differential cross sections are presented in Platzman plots in Figs. 8–11 and compared with available experimental data.

Peaks in experimental data for Ar that are associated with Auger electrons released following the ionization of *L*-shell electrons (near *R/E* = 0.07) are not included in Kim's model; they appear as sharp peaks in the Platzman

FIG. 7. The dipole function *E*(*df/dE*) of N₂ as a function of the inverse of the photon energy in rydbergs. The solid curve is a fit to the smoothed experimental data of Samson *et al.* (1987) and those compiled by Berkowitz (1979): O, direct ionization resulting in N₂⁺; Δ, dissociative ionization resulting in N⁺ and N.

features in the profiles of the Platzman plots are faithfully represented and the integrated cross sections (total ionization cross sections) are consistent with those recommended in Rudd *et al.* (1985). The many fitting parameters are independent of the ejected-electron energy as well as of the incident-proton energy for the entire range of *W* and for *T₀* > 200 keV. Since this model is consistent with the Bethe theory and uses realistic oscillator strengths, it is also expected to be reliable for very fast protons (*T₀* ≥ 10 MeV), though relativistic effects are not included in this model and will eventually dominate at extremely high incident energies.

For protons of relativistic velocity *v*, or $\beta = v/c > 0$, where *c* is the speed of light, relativistic expressions for kinematic variables such as energy and momentum must be used and an additional interaction between the proton and bound electrons must be included. The net result is that Eq. (22) is rewritten as

plot and add little to the total ionization cross section (Figs. 8 and 9). Experimental and model values are in excellent agreement for Ar except for slow ejected electrons (*W* < 10 eV) at *T₀* = 300 keV.

Similar comparisons for N₂ data (Figs. 10 and 11) do not show agreement equal to that observed for Ar. It is likely that the quality of available experimental data for N₂ with fast protons (*T₀* > 0.5 MeV) is poorer than that

FIG. 8. Platzman plot of proton-impact (*T₀* = 300 keV) singly-differential cross section of Ar. The solid curve is the recommended SDCS based on Kim's model: O, *L*-shell contribution; □, experimental data of Crooks and Rudd (1971); Δ, experimental data of Toburen, Manson, and Kim (1978). The sharp peak near *R/E* = 0.07 consists of several peaks due to the LMM Auger transitions. The peak expected at *R/E* = 0.07 from charge transfer to the continuum is masked by the Auger peaks, but the former, although it is expected to be broader, is not noticeable. The dashed curve is the SDCS based on Rudd's model, discussed in Sec. VI D.

FIG. 9. Plaitzman plot of proton-impact ($T_0 = 1$ MeV) SDCS of Ar. See Fig. 8 for the legend.

or Ar (Toburen, 1990). As a result, fitted formulas for v_i have greater uncertainty, but the model should adequately represent the systematics of the singly-differential cross sections for fast protons. Auger electrons emitted following K-shell ionization appear as sharp peaks near $R/E = 0.03$, again contributing little to the total ionization cross section.

For moderate to slow incident protons ($T_0 < 500$ keV), charge transfer to the continuum (see Sec. III.D) becomes apparent. This contribution is localized near electron speeds matching that of the incident proton (e.g., $w = 160$ eV for $T_0 = 300$ keV), but it is difficult to describe theoretically and hence was omitted in Kim's model. A continuum-charge-transfer "hump" can be seen in the vicinity of $R/E = 0.15$ in Fig. 10 for N_2 . A similar

FIG. 10. Plaitzman plot of proton-impact ($T_0 = 300$ keV) singly-differential cross section of N_2 . The solid curve is the recommended SDCS based on Kim's model. $\circ$: contribution from the $2p$ subshell; Δ : experimental data of Toburen (1971), which was later improved by Toburen and Wilson (1973); $\square$: data of Crooks and Rudd (1971). The broad peak at $R/E = 0.1$ arises from charge transfer to the continuum, and the sharp peak at $R/E = 0.03$ is due to KLL Auger electrons. The broken curve is the SDCS based on Rudd's model.

FIG. 11. Plaitzman plot of proton-impact ($T_0 = 1$ MeV) SDCS of N_2 . See Fig. 10 for the legend.

hump in Ar is not visible in Fig. 8; it may have been masked by the Auger peaks in the vicinity.

At much lower incident-proton energies ($T_0 < 300$ keV), the dipole interaction does not dominate and the Bethe theory, on which Kim's model is based, becomes inadequate. There is no definitive theory for this region. The fitting formulas shown above should not be used for $T_0 < 200$ keV.

Kim's model can be extended to other targets for which experimental data are available to determine the fitting parameters. Helium, neon, krypton, xenon, molecular hydrogen, water, ammonia, and methane are candidates for detailed future studies. Photoionization cross sections for these atoms and molecules are known with better accuracy than the corresponding proton-impact singly-differential cross sections. Kim's model should also be applicable to electron-impact ionization of atoms and molecules with minor adjustments of the fitting parameters.

Kim's model and that of Miller *et al.* (Sec. VI.A) have equivalent major features, but Kim's model includes additional T -dependent terms that extend its applicability toward lower proton energies. However, these additional T -dependent terms specifically depend on the type of projectile, thus making it necessary to introduce different fitting parameters for electron-impact and proton-impact ionization cross sections.

D. Rudd's model

This model (Rudd 1987, 1988) is designed to provide an analytic representation of the differential cross sections over a wide range of primary and secondary energies. It requires experimental data to determine its parameters, but successfully bridges large gaps in intermediate energy ranges. An important advantage of this model is that it has no restrictions on primary and secondary energies and therefore is useful even at impact velocities well below the target's orbital velocity.

This model assumes that the cross section for ejection

of an electron depends only on the secondary energy, the binding energy of the electron, and the projectile velocity. This leads to the relation

$$\frac{d\sigma}{dW} = \sum_i N_i / (W, T, I_i). \quad (37)$$

where N_i is the number of electrons in a shell with binding energy I_i , W is the energy of the ejected electron, and $T = (m/M)T_0$, where T_0 is the proton energy. The sum is taken over all shells of the target. It further assumes that the ratios of the primary and secondary energies to the binding energy are the important quantities. This assumption and other considerations lead to the relation

$$\frac{d\sigma}{dW} = \sum_i (N_i / I_i^2) f(w_i, v_i). \quad (38)$$

where

$$w_i = W/I_i \text{ and } v_i = (T/I_i)^{1/2}. \quad (39)$$

Using this notation, we may write a general cross-section equation for a single shell:

$$\frac{d\sigma}{dW} = (S/I_i N F_1 + F_2 w)/(1 + w). \quad (40)$$

where $S = 4\pi a_0^2 W(R/I_i)^2$. In Eq. (40), the units of $d\sigma/dW$ are determined solely by the choice of units for S and I_i , since the remaining terms are dimensionless.

The results of Ruetherford (1911) and Thomson (1912) on the scattering of charged particles from atoms may be used to obtain an equation for the cross section assuming that each target electron is initially at rest (see Sec. III.E). This relation is given by Eq. (40) with $F_1 = F_2 = 1/v_i^2$, which then becomes Eq. (13). Williams (1927) took into account the initial motion of the target electron and obtained a result that may also be put into the form of Eq. (40) but with $F_1 = 7/3v_i^2$ and $F_2 = 1/v_i^2$. This choice leads to Eq. (16) with $U = I_i$, which holds exactly for the hydrogen atom and one-electron ions and as an approximation for other targets.

In the Rudd model, F_1 and F_2 are taken to be adjustable fitting parameters that are functions of v determined

from experimental data. In addition, it is required that $F_1 \rightarrow (1/v^2) \log(v^2)$ and $F_2 \rightarrow 1/v^2$ for $v \gg 1$, thus reproducing the well-verified asymptotic energy dependence of the Bethe theory.

Equation (40), however, does not give the proper dependence on secondary-electron energy above the kinematic cutoff. This is corrected in the model by the addition of a factor derived from the molecular promotion model (Rudd, 1979, 1988). The final equation is then

$$\sigma(w) = \frac{(S/I_i F_1 + F_2 w)(1 + w)^{-1}}{1 + \exp[\alpha(w - w_c)/v]} \quad (41)$$

where α is a dimensionless parameter near unity related to the size of the target and w_c , the energy at the cutoff, is

$$w_c = 4v^2 - 2v - R/I_i. \quad (42)$$

The first term on the right-hand side represents the free-electron limit, $4T$, discussed in Appendix A, the second term represents the correction due to electron binding (Rudd, 1988), and the third term gives the correct dependence for $v \ll 1$.

The quantities F_1 , F_2 , and α constitute the three adjustable parameters in the model for each secondary-electron spectrum at a given primary energy. The quantity α resulting from the fitting turns out to be essentially independent of primary energy and is taken to be a constant for each target. The other two quantities are functions of the primary energy that may be fitted to the experimental data, subject to the asymptotic energy dependence given above, by the equations

$$F_1(v) = L_1 + H_1 \quad (43)$$

and

$$F_2(v) = L_2 H_2 / (L_2 + H_2). \quad (44)$$

with

$$H_i = A_i \ln(1 + v^2 / (v_i^2 + B_i / v^2)). \quad (45)$$

TABLE V. Parameters for fitting singly-differential cross sections to the Rudd model, Eq. (41)-(48).

	He	Ne	Ar	Kr	H ₂	N ₂	O ₂	H ₂ O	CO ₂	CH ₄	Inner shells
A_1	1.02	0.58	1.20	1.46	0.96	1.05	1.02	0.97	1.09	1.15	1.25
B_1	2.4	65	8.0	5.7	2.6	12.0	50	82	25	14	0.50
C_1	0.70	0.23	0.86	0.65	0.38	0.74	0.40	0.40	0.75	0.35	1.00
D_1	1.15	0.55	0	-0.55	0.23	-0.39	0.12	-0.30	0.75	0.50	1.00
E_1	0.70	0.16	0.80	1.00	2.2	0.80	0.30	0.38	0.65	3.0	3.0
A_2	0.84	1.40	0.90	1.30	1.04	0.95	1.00	1.04	0.78	0.60	1.10
B_2	6.0	0	2.7	22	5.9	1.20	5.0	17.3	3.0	3.8	1.30
C_2	0.70	0.72	0.95	0.95	1.15	1.00	0.55	0.76	0.70	1.20	1.00
D_2	0.90	1.35	0.80	-1.00	0.20	1.30	0	0.04	0.85	0.45	0
α	0.86	0.57	0.71	0.78	0.87	0.70	0.59	0.64	0.53	0.61	0.66

$$L_1 = C_1 v^0 / (1 + E_1 v^0 / v^0),$$

$$H_1 = A_1 / v^2 + B_1 / v^0,$$

and

$$L_2 = C_2 v^0.$$

TABLE VI. Summary of experimental apparatuses by laboratory. That of Redford and Andersen (1979) is not included in this listing. Substantial changes in apparatus are indicated by different numbers, as are separate apparatuses. The "overall estimated error" category contains the most conservative errors quoted by the authors in a given series of references associated with the specific apparatus. Generally, the authors referenced here have made the common mistake of combining systematic errors quadratically, instead of linearly. Where possible, i.e., when individual systematic errors are specified, we have quoted a more conservative linear error. A comprehensive reference list of all known absolute doubly-differential cross sections is contained in Table IV.

10 doubly-differential cross sections it contained in Table 1.

Laboratory	Apparatus	References	Proton-energy range (keV)/targets	Analyzer	
University of Nebraska, Lincoln, NE [apparatus 2 constructed at Concordia College, Moorhead, MN, where the work of Rudd <i>et al.</i> (1966) was done]	1	Kuyatt and Jorgensen (1963)	50-100; H ₂	127	
	2	Rudd and Jorgensen (1963) Rudd <i>et al.</i> (1976)	50-150; H ₂ , He	127	
	3	Rudd <i>et al.</i> (1966) Rudd <i>et al.</i> (1976)	100-300; H ₂ , He	Parallel-plate	
	4	Crooks and Rudd (1971) Rudd <i>et al.</i> (1979)	50-300; N ₂ , O ₂ , Ne, Ar	127	
	5	Rudd and Madison (1976) Rudd <i>et al.</i> (1976, 1979) Rudd (1977) Rudd (1979) Bolorizadeh and Rudd (1986) Cheng <i>et al.</i> (1989a, 1989b) Gay <i>et al.</i> (1990)	5-150; He N ₂ , H ₂ , Ar, H ₂ O, Ne, Kr, O ₂ , CO ₂ Xe	127/ Parallel-plate	
Laboratory	Apparatus	Target type	Detector type	Quoted magnetic fields (T)	Analyzer pre- or post-accelerator
University of Nebraska, Lincoln, NE	1	Gas fills vacuum chamber (static)	Electron multiplier (From PM tube)	10 ⁻¹ ; Helmholtz coils	Both
	2	Static	Electron multiplier (From PM tube)	5 × 10 ⁻¹ ; Helmholtz coils	Both
	3	Static	Electron multiplier	5 × 10 ⁻¹ ; Helmholtz coils	Both
	4	Static	Electron multiplier	< 5 × 10 ⁻¹ ; Helmholtz coils	Both
	5	Static	Electron multiplier	< 5 × 10 ⁻¹ ; Helmholtz coils	Post only

The ten basic parameters $A_1, \dots, E_1, A_2, \dots, D_2$ and α for a given target suffice to specify the cross section at any combination of primary and secondary energies.

A different but universal set of parameters was found to be more appropriate for inner-shell orbitals. Inner shells are defined for this purpose as those whose binding energy I exceeds twice the binding energy of the least tightly bound orbital. These parameters are listed in Table V for ten targets. The quantities A_1 and A_2 , which are approximately unity, are related to the first Bethe coefficient, $\alpha(E)$ of Eq. (20) and (21), and thus to the integrated optical oscillator strength obtainable from photoionization data. The relations are

$$A_1 = \frac{2\alpha(E)}{\sum_i N_i R_i / I_i}$$

and

$$A_2 = 2 - A_1.$$

VII. EXPERIMENTAL METHODS

Two general experimental techniques have been used to determine the singly-differential cross sections reported in this article. The first involves measurement of the

TABLE VI. (Continued).

Laboratory	Apparatus	Electron-energy range (eV)	Electron-specimen-angle range	Overall estimated error	Comments
University of Nebraska, Lincoln, NE	1	1-500	23°-152°	4% relative	Rubber zipper chamber
	2	1-500	10°-160°	~25% systematic	<10% relative error
	3	2-1000	10°-160°	30% absolute	Vacuum/Target essentially that of apparatus 2 above
	4	15-1057	10°-160°	~25% absolute	Ar measurements made with parallel-plate analyzer
	5	1-300	10°-60°	~25% absolute >50% below 10 eV	
Laboratory	Apparatus	References	Proton-energy range (keV)/targets	Analyzer	
Battelle Pacific Northwest Laboratory, Richland, WA	1	Toburen (1971,1974) Toburen and Wilson (1972,1977) Wilson and Toburen (1975) Manson <i>et al.</i> (1975) Lynch <i>et al.</i> (1976) Rudd <i>et al.</i> (1976) Criswell <i>et al.</i> (1977) Toburen <i>et al.</i> (1977,1978) Wilson <i>et al.</i> (1984)	250-5000; N ₂ H ₂ , He, Xe CH ₄ , C ₂ H ₆ C ₃ H ₈ , C ₄ H ₁₀ C ₂ H ₆ , NH ₃ CH ₃ NH ₂ (CH ₃) ₂ NH H ₂ O, Ar Ne SF ₆ , TeF ₆	Cylindrical-mirror analyzer (CMA)	
	2	Toburen and Wilson (1975) Lynch <i>et al.</i> (1976) Criswell <i>et al.</i> (1977) Toburen <i>et al.</i> (1977,1978) Wilson <i>et al.</i> (1984)	50-4200; N ₂ CH ₄ , NH ₃ CH ₃ NH ₂ (CH ₃) ₂ NH Ar, He, Ne SF ₆ , TeF ₆ , H ₂ O 5-100; Ar	Time-of-flight	
	3	Criswell <i>et al.</i> (1977) Rudd <i>et al.</i> (1979)		CMA	

energy and angle of ejection for ionized electrons, i.e., doubly-differential cross sections. These can be integrated to yield cross sections differential either in energy or angle. The second method is ion-energy-loss spectroscopy, in which the proton energy is analyzed following the collision. Those protons which lose energy greater than that corresponding to the ionization limit of the target contribute to the ionization cross section, except when the energy is lost to dissociation or photon production. Measurements made to date using this technique yield directly cross sections that are singly differential in energy. Almost all of the data reported here have been taken using the first method.

A. Analysis of ejected electrons

A schematic diagram of the generic apparatus employed in the electron-analysis method is shown in Fig. 12. (Table VI lists specific characteristics of most of the apparatuses used in the work considered in this review.) Proton beams with typical ion-source energy spreads (< 100 eV) are magnetically analyzed and directed toward the scattering apparatus. At the entrance of the scattering chamber they are collimated and pass through the target region. Collimation is necessary to properly define the scattering geometry, but it can cause secondary and tertiary problems. Secondary electrons produced at

the edges of the collimating apertures must be prevented from entering the scattering volume. This is usually accomplished by a suppressor biased at a negative voltage (-100 V is generally sufficient) after the last collimator. Alternatively, the last collimator may be biased positively. Electric fields from the biased aperture or collimator must now be kept from the scattering volume so that ionized-electron trajectories will not be disturbed. This is accomplished with a grounded, conducting shield, which also helps stop slit-scattered ions from reaching the collision volume.

Three basic scattering volume/target configurations

TABLE VI. (Continued).

Laboratory	Apparatus	Target type	Detector type	Quoted magnetic fields (T)	Analyzer pre- or post-acceleration
Battelle Pacific Northwest Laboratory, Richland, WA	1	Static gas cell	Channel-electron multiplier (CEM)	$\sim 2 \times 10^{-1}$ Helmholtz coils [$< 2 \times 10^{-6}$ in Töburen and Wilson (1977)]	None
	2	Gas beam from multicapillary array	CEM	$< 2 \times 10^{-1}$ magnetic shield plus Helmholtz coils	Post
	3	Gas beam from multicapillary array	CEM	$< 5 \times 10^{-1}$ magnetic shield plus Helmholtz coils	Both
Laboratory	Apparatus	Target type	Detector type	Quoted magnetic fields (T)	Analyzer pre- or post-acceleration
Battelle Pacific Northwest Laboratory, Richland, WA	1	Electron-energy range (eV)	Electron-ejection angle range	Overall estimated error	Comments
	1	0-4000	15°-130°	$\sim 25\%$ absolute > 50% (statistical) at high ejection energies	Nominally 50 V acceleration into CEM
	2	0-500	50°-130°	$\sim 10\%$ relative > 20 eV; > 50% relative < 1 eV (statistical)	
	3	0-225	30°-145°	$\sim 10\%$ relative > 25% absolute (normalized with apparatus 1)	

Laboratory	Apparatus	References	Proton-energy range (keV)	Analyzer
Hahn-Meitner Institute, Berlin, Germany	1	Stolterfoht (1971a, 1971b, 1975) Stolterfoht <i>et al.</i> (1976) Gabler (1974)	200-5000; He, CH ₄ , N ₂ Ar	Parallel-plate
Lucas Heights Research Laboratory, Sutherland, Australia	1	Gibson and Reid (1984, 1985, 1986, 1987a, 1987b)	20-100; H ₂ , He, O ₂ , N ₂ , CO ₂ , CH ₄ , H ₂ O, Ar	Fountain parallel-plate
Université Paul Sabatier, Toulouse, France	1	Bordenave-Montesquieu (1973) Bordenave-Montesquieu <i>et al.</i> (1973, 1982) Benoit-Cattin <i>et al.</i> (1973)	14-150; He	127°
Tokyo Institute of Technology, Tokyo, Japan	1	Sataka <i>et al.</i> (1979) Tokoro and Oda (1985)	5-30; He, Ar	Parallel-plate

Laboratory	Apparatus	Target type	Detector type	Quoted magnetic fields (T)	Analyzer pre- or post-acceleration
Hahn-Meitner Institute, Berlin, Germany	1	Static (for absolute measurements) and gas beam from single capillary	Electron multiplier	$< 1 \times 10^{-1}$ magnetic shield	None (Preacceleration used prior to 1975)
Lucas Heights Research Laboratory, Sutherland, Australia	1	Gas beam from multicapillary array	CEMs and an electron multiplier at 0°	$< 10^{-6}$ Helmholtz coils	None
Université Paul Sabatier, Toulouse, France	1	Static	CEM	5×10^{-1} Helmholtz coils	Post
Tokyo Institute of Technology, Tokyo, Japan	1	Gas beam from multicapillary array	CEM	$< 5 \times 10^{-1}$ Magnetic shield (after 1980) and Helmholtz coils	Not specified

analyzed pass through a radial tube in the outer chamber before entering the analyzer. This tube contains a radial port for differential pumping. The observation of this design are fixed; to change angles the entire apparatus is raised to atmospheric pressure and the radiator and analyzer chamber are demounted and reinstalled in the next port. A modification of this arrangement has been used by Stollerfoht (1971a, 1971b; Fig. 1) and Gabler (1974), and Bordenave-Montesquieu and co-workers (1973, 1982; Benoit-Cattin *et al.*, 1973), in which the entire vacuum vessel containing the analyzer is raised with target gas. In the latter case, the analyzer is contained in a box rotatable about the collision center

and pumped separately through a flexible tube. One advantage of this design is the ease with which observation angles can be changed. An early apparatus of this type was described by Kuyatt and Jorgensen (1963) and Cook (1955). In their design, the ejection angle is varied by rotating the scattering chamber and analyzer about the target center, with the incident ion beam fixed in space. A sliding seal over the proton entrance port is made with two grease-impregnated rubber diaphragms. While this design also has the advantage of not requiring a break in the vacuum to change ejection angles, the diaphragms limit the base vacuum in the target cell to about 10^{-4} Torr. Significant

electric charge can also build up on their insulating surfaces, making measurements at low ejection energies unreliable.

A second type of target has been developed by Toburen and co-workers (e.g., Toburen *et al.*, 1971, 1974; Toburen and Wilson, 1972; Criswell *et al.*, 1977), in which the target gas is introduced into a relatively small triangular target cell (Fig. 15). A narrow slit is cut at the apex of the cell, through which the proton beam passes and ionized electrons escape. In such a target, the gas is well localized and the analyzer/detector operates at correspondingly lower pressures.

In the work of Oda and co-workers (Satake *et al.*, 1979; Tokoro and Oda, 1985), Gibson and Reid (1984, 1985, 1986, 1987a, 1987b; Fig. 16), and some of the work of Toburen *et al.* (e.g., Toburen and Wilson, 1973; Lynch *et al.*, 1976; Criswell *et al.*, 1977; Fig. 17), and Stollerfoht *et al.* (1971a, 1971b; Gabler, 1974), a gas beam target was used. In these cases, the proton beam passes in close proximity to the surface of a multicapillary array (which is either made of metal or has a conducting coating on its surface), through which the target gas is effusing. The gas beam is directed immediately into a pump. Atomic densities in such cases are typically an or-

TABLE VI. (Continued).

Laboratory	Apparatus	Target type	Detector type	Quoted magnetic fields (T)	Analyzer pre- or post-acceleration
Centro Atomico Bariloche, Argentina	1	Gas beam from single capillary	CEM	$< 7 \times 10^{-7}$ single current coil	Post only
Institut für Kernphysik, Frankfurt, Germany	1	Gas beam from single capillary	CEM	Not specified	Not specified
Technische Hochschule, Karlsruhe, Germany	1	Static	Geiger-Müller tube	Not specified	None
University of Missouri, Rolla, MO	1	Gas beam from single capillary array	CEM	$< 10^{-6}$ Magnetic shield plus Helmholtz coils	Post only
Laboratory	Apparatus	Electron-energy range (eV)	Electron-ejection angle range	Overall estimated error	Comments
Centro Atomico Bariloche, Argentina	1	5-300	0°-90°	15% relative	Integrated totals normalized to Rudd <i>et al.</i> (1985)
Institut für Kernphysik, Frankfurt, Germany	1	20-2000	0°-60°	30% absolute	Normalized to Rudd <i>et al.</i> (1976, 1979)
Technische Hochschule, Karlsruhe, Germany	1	2-1000	54.5°	Not specified	First measurements of proton DDCS; significant background for electron energies above 100 eV
University of Missouri, Rolla, MO	1	5-150	17°-90°	10% relative; normalized to Rudd and Jorgensen (1963)	Apparatus of Atreani and Schlachter (1987)

TABLE VI. (Continued).

Laboratory	Apparatus	Electron-energy range (eV)	Electron-ejection angle range	Overall estimated error	Comments
Hahn-Meitner Institute, Berlin, Germany	1	1-8600	18°-155°	~20% absolute; <10% statistical	Preacceleration in 1971 work thought to cause artificially high-cross sections below 20 eV
Lucas Heights Research Laboratory, Sutherland, Australia	1	5-150	0°-100°	13% relative above 10 eV; 80% at 5 eV	
Université Paul Sabatier, Toulouse, France	1	33	16.5°-160°	~30% absolute, normalized to Rudd and Jorgensen (1963)	
Tokyo Institute of Technology, Tokyo, Japan	1	2-200	30°-90°	~30% absolute, normalized to Criswell <i>et al.</i> (1977)	
Laboratory	Apparatus	References	Proton-energy range (keV)/targets	Analyzer	
Centro Atomico Bariloche, Argentina	1	Bernardi <i>et al.</i> (1983,1989,1990)	50-200; He,Ne	Coaxial cylinder	
Institut für Kernphysik, Frankfurt, Germany	1	Schader <i>et al.</i> (1986)	400-2000; He	Magnetic-sector momentum analyzer	
Technischen Hochschule, Karlsruhe, Germany	1	Blauth (1957)	8.8-49; H ₂ , He, N ₂ , Ne, Ar, Kr	Coaxial cylinder	
University of Missouri, Rolla, MO	1	Olson <i>et al.</i> (1987) Irby <i>et al.</i> (1988)	60-150; He	Parallel-plate

FIG. 12. Schematic diagram of generic apparatus employed in measurements of doubly-differential cross sections for electron emission. 1, proton entrance port; 2, collimator; 3, electron suppressor and shield; 4, Faraday cup and shield; 5 and 6, solid-angle defining analyzer entrance slits; 7, preanalyzer acceleration slit; 8, preacceleration slit; 9, detector focusing electrode; 10, detector focusing electrode; 11, preacceleration slit; 12, cylindrical analyzer; 13, analyzer exit slit; 14, detector focusing electrode; 15, electron multiplier.

der of magnitude higher in the region where the gas and proton beams intersect than in the surrounding vacuum chamber. This results in relatively high electron production rates without attendant high pressure in the analyzer region and without the potentially disturbing influence of target cell exit apertures. Measurements using the gas

FIG. 13. Schematic diagram of apparatus used by Rudd and co-workers and described in detail by Rudd and Jorgensen (1983): 1, proton entrance port; 2, collimator; 3, electron suppressor; 4, inner gas-containment cylinder; 5, Faraday cup and shield; 6, outer vacuum-chamber wall; 7, analyzer entrance tube; 8, differential-pumping and solid-angle-defining aperture; 9, differential pumping ports; 10, analyzer entrance and solid-angle-defining slit; 11, preacceleration slit; 12, cylindrical analyzer; 13, analyzer exit slit; 14, detector focusing electrode; 15, electron multiplier.

FIG. 14. Schematic diagram of the apparatus used by Stoffer *et al.* (1976, 1979): 1, Effusive gas-target beam; 2, preanalyzer acceleration grids; 3, electron shield/analyzer housing; 4, parallel-plate analyzer; 5, fringe-field correlation electrodes; 6, spurious-electron discriminator grids; 7, electron multiplier; 8, ring for rotation about center line of analyzer assembly. The indicated proton beam is emerging from the plane of the diagram.

beam technique, however, are difficult to put on an absolute scale due to the uncertainty in the target density-length product nl (see next section). Stoffer *et al.* (1971a, 1971b) and Gabler (1974), as well as Bernardi *et al.* (1988, 1989, 1990), Schader *et al.* (1986), and Olson *et al.* (1987) used a single capillary to produce effusive

FIG. 15. Schematic diagram of apparatus described by Toburen (1971): 1, collimating apertures; 2, electron-suppression electrode; 3, Faraday shield; 4, inangular target cell showing crumpled high-transmission mesh acting as an electron trap. The segment below the beam line represents a slit through which ejected electrons may leave the target chamber. 5 and 6, Faraday cup with electron-suppression electrode; 7, solid-angle-defining apertures; 8, cylindrical-mirror analyzer with back electrode formed from wire for background reduction; 9, channel-electron multiplier; 10, isometric projection of the target cell, showing detail of electron-emission slit. Arrow represents proton beam.

FIG. 16. Schematic diagram of the 'fountain' analyzer used by Gibson and Reid (top and side views of the apparatus are shown in the top and bottom of the figure, respectively): 1, ion-beam collimating slits; 2, effusive gas-target beam produced by a multicapillary array; 3, analyzer entrance annular slit; 4, analyzer top plate; 5, solid-angle-defining aperture; 6, channel-electron multiplier (CEM); 7, fringe-field correction electrodes; 8, analyzer back plate made of stainless steel mesh. For high count rates, the θ electron detector can be replaced by an electron multiplier. An array of nine CEM's (three of which are shown in the top view) is rotated among 16 angular positions to measure the electron-emission cross sections.

Having traversed the target region, the proton beam is stopped in a Faraday cup and its current measured. When fast ions are stopped, they can produce both secondary electrons and sputtered ions. At 100 keV incident energy, for example, each proton produces about one electron (see, for example, Thomas, 1985) and 2×10^{-3} ions (Andersen and Bay, 1981) with a copper target. Thus, while sputtered ions do not represent a serious problem, the secondary electrons must be prevented from entering the scattering volume. This is accomplished by inserting a negatively-biased element upstream of the

FIG. 17. Schematic diagram of the time-of-flight apparatus described by Toburen and Wilson (1975): 1, 40 kV, 3.33 MHz RF oscillator for beam rastering; 2, collimating apertures and electrostatic shield for electron suppressor; 3, electron suppressor; 4, channel-plate gas-beam target (beam is perpendicular to the plane of the diagram); 5, Faraday cup shield; 6, Faraday cup; 7, collimating apertures and accelerating electrode; 8, channel-electron multiplier.

beam stop or by biasing the cup positively and shielding it from the interaction region. Other potential problems can be caused by reflected protons (Mashkova and Michanov, 1985; Thomas, 1985) and proton-induced x-rays or UV photons (e.g., Palmer, Thompson, and Townsen, 1970).

Electrons ejected from the target volume at a given polar angle θ are energy analyzed and detected. Prior to the analyzer section, the electrons pass through solid angle defining slits, except in the work of Gibson and Reid, which we shall discuss below. Either time-of-flight magnetic, or electrostatic energy analyzers are used to determine the electron's velocity (Table VI).

Most of the work discussed here has employed 127° cylindrical-mirror, or parallel-plate electrostatic analyzers, with the exceptions of the time-of-flight analyzer used by Toburen *et al.* and the magnetic-sector analyzer used by Schader *et al.* (see Table VI). To avoid uncertainties due to fringing fields in the analyzer, as well as spurious magnetic fields (including that of the earth) electrons are sometimes preaccelerated before entering the analyzer. This is done by running the analyzer section, including the entrance slit, at a small positive bias (typically +10 V) relative to the scattering center. While this procedure can significantly improve the transmission of low-energy electrons through the analyzer, it has the potential disadvantage of producing focusing effects at the analyzer entrance, which can distort the solid-angle acceptance of the device (Kuyatt *et al.*, 1971a, 1971b).

Following passage through the analyzer, the electrons are detected by either a channel-electron multiplier, discrete-dynode multiplier, or a Geiger-Müller tube (Blauth, 1957). It is very important that the detection efficiency ϵ of these devices be a well defined function of incident-electron energy. A constant function is the best possibility. To this end, the electrons are generally accelerated by 100 to 400 V prior to striking the detector. At these energies, ϵ is relatively insensitive to energy and is extremely critical that the voltages applied to various elements of the analyzer/detector section, including the high voltage required for operation of the detector, be well shielded from the scattering region.

A novel 'fountain' parallel-plate analyzer design shown in Fig. 16, has been employed by Gibson and Reid (1984, 1985, 1986, 1987a, 1987b) to measure double differential cross sections. The device consists of two parallel plates across which the analyzing voltage is placed. A collimated proton beam crosses a vertically directed multicapillary effusive target, making an angle of θ with respect to the analyzer-plate normal. Ionized electrons created in the target region with polar angles θ relative to the beam direction between θ' and 120° enter the analyzer volume through an annular slit. Electron trajectories follow appropriate energy follow trajectories pass through holes evenly spaced on a circle in the top plate and are detected by an array of channel-electron multi-

ions located at several of these exit apertures. Protons leave the bottom plate through an exit hole and are collected in a Faraday cup. This design has the distinct advantage that data for a number of emission angles up to 90° can be taken simultaneously. In addition, electrons emitted at 0° can be analyzed. This is more difficult to accomplish with the other configurations we have considered. Unfortunately, the "fountain" design does not permit measurement of cross sections.

low absolute measurement errors than 10 eV, accurate measurements become difficult because of the unpredictable effects of stray electric fields in electrostatic analyzers. To surmount this problem, the technique of time-of-flight velocity analysis has been applied to doubly-differential cross-section measurements by Toburen and Wilson (1975). In their apparatus, shown in Fig. 17, the proton beam is chopped by passing it through deflection plates, across which is placed an oscillating high voltage (typically ± 20 kV at 3 MHz). Proton pulses of duration less than 1 ns are thus produced as the beam is swept across the collimating slits. Electrons produced in the interaction region pass through two solid-angle defining apertures and are accelerated just prior to being detected by a channel-electron multiplier enclosed in a shielding box. Typical flight times for the electrons are 30–300 nanoseconds, and energies as low as 0.5 eV can be reliably measured, owing primarily to the absence of large stray electric fields in the analysis region.

The importance of eliminating or minimizing spurious electrostatic fields in the analysis of electron beams for electric and magnetic fields in these measurements cannot be overemphasized. Constant magnetic fields such as the earth's can be reduced to less than 5 mG in the interaction region by orthogonal pairs of Helmholtz coils. Commonly occurring ac magnetic fields, most typically with a frequency of 60 Hz, can be reduced using the same coils with a small ac component added to the dc current. Random or transient magnetic fields can only be eliminated by the use of magnetic shields. In terms of apparatus construction, the use of magnetic materials, such as 400-series stainless steels, must be stringently avoided. Electric patch fields can be minimized by using titanium and molybdenum in electron-optical components and by gold plating apertures through which electrons will pass. Gold plating is especially useful, since it eliminates the formation of surface oxides, which can become electrostatically charged, thus deflecting electron trajectories.

9 Ion energy-loss spectroscopy

In this method, the occurrence of ionization is determined by analysis of the proton's energy loss, as opposed to the detection of an emitted electron. The only measurements using this technique which have been reported were for an atomic-hydrogen target (Park *et al.*, 1977) and a He target (Park and Schweninger, 1969b). The apparatus, developed over a number of years by Park and co-workers (Park and Schweninger, 1969a, 1969b; Park *et al.*, 1976, 1978), is shown schematically in Fig. 18. A

FIG. 18. Schematic diagram of the ion energy-loss spectrometer described by Park *et al.* (1977): 1, Coultron ion source; 2, Wien filter for mass selection; 3, accelerator high-voltage terminal; 4, accelerator column; 5, target center about which the entrance accelerator assembly can pivot; 6, analyzing magnet; 7, decelerator column; 8, decelerator high-voltage terminal containing cylindrical electrostatic analyzer, ΔV high-voltage supply, which is varied to tune an energy-loss spectrum; and 9, the electron-multipplier ion detector.

collimated beam of protons is produced with very low (~ 1 eV) energy spread in a Colutron ion source. It traverses a room-temperature target cell or one that is relatively heated to dissociate molecular hydrogen (Park *et al.*, 1983). The scattered beam is deflected by an analyzing magnet to separate the post-collision charges. Scattered protons are then decelerated to an energy of 2 keV and detected after passing through a 127 cylindrical analyzer. In a typical run, an energy-loss spectrum is taken by changing the acceleration voltage by an amount ΔV and then recording the detected proton count rate after the analyzer as a function of ΔV . In this way, all magnetic and electrostatic elements following the accelerator are kept constant. To be detected, i.e., to be decelerated to precisely the electrostatic analyzer pass energy of 1 keV, the proton must lose an amount of energy $\Delta W = e\Delta V$ in the scattering volume. By measuring the count rate for detected protons as a function of ΔV above the target's ionization limit, one can extract the singly-differential cross section for proton-induced ionization. Electron-capture processes are excluded by the analyzing magnet.

The ion energy-loss method has two general advantages over the electron-analysis technique. First, because the high-energy massive proton is the particle being analyzed, the measured cross sections are much less susceptible to spurious fields. Second, since the proton scattering angles are small, essentially the entire beam is analyzed, and singly-differential cross sections are determined directly. This eliminates potential systematic errors caused, for example, by angle-dependent solid-angle acceptance coefficients (see next section).

Cross-section information obtained in ion energy-loss spectroscopy is not directly comparable with that ob-

obtained by analysis of the ejected electrons, except in the case of atomic hydrogen. For other targets, proton energy can be lost simultaneously to excitation and/or molecular dissociation.

VIII ERROR ANALYSIS

A Analysis of ejected electrons

The absolute differential cross section for electron emission with energy W into a polar angle θ is obtained from experimental measurements by using the following equation:

$$\frac{D^2 \sigma(W, \theta)}{D^2 W D^2 \theta} = \frac{[N_5 \exp(\sigma, n_x) - N_B]}{N_0 / (W / n) \Delta \epsilon} \quad (51)$$

in this expression, N_S and N_B are the number of total signal and background counts, respectively, σ_i is the total scattering cross section for ejected electrons of energy W , n is the number density of target atoms, and N_0 is the number of incident protons which produce the signal N_S . The energy spread of electrons (with mean energy W) is passed by the analyzer with a transmission coefficient τ ($\Delta W/W$), and they are detected with efficiency ϵ . The "effective" integral of solid angle times path length, $\int \Omega dl$, is the β -dependent product of differential proton path length times local target number density times subtended solid angle of detection, integrated over all proton path segments viewed by the detector. Finally, x is the effective path length between the collision volume and the detector, given by

$$x = \int_0^L \frac{L_N(\tau)}{N} d\tau, \quad (52)$$

where L is the length of the geometric unscattered electron trajectory, r is the distance from the collision point to a given point along that trajectory, and $n(r)$ is the gas density at that point. Note that Eq. (51) is equivalent to Eq. (1), but states explicitly the experimentally determined quantities that must be taken into account.

Each of these quantities must be carefully measured or calculated for an accurate absolute measurement: relative measurements do not require absolute values of N_0 , dW , ϵ , t , or $(n/\Omega)_0$. We now consider the determination of each of these quantities in detail, and the corresponding experimental systematic errors that can affect the ultimate absolute or relative accuracy of the cross-section values. Table VI gives an overview of the experimental parameters associated with apparatuses used by various investigators to study ejected electrons.

 N_s : Total signal and background counts, N_s and N_B

The number of counts registered by the electron-detection circuit for a given number of incident protons is N_2 . The background signal N_0 results from any process other than simple ejection and subsequent detection

of electrons from target-gas atoms caused by the incident protons. If count rates are high and the dead time of the detection circuit is not corrected for, or if the electrons are deflected by spurious electric and magnetic fields, χ_s can be too low. The only papers that mention dead-time corrections are those of Rudd and Jorgensen (1963) and Rudd and Madison (1976), who applied a maximum correction of 7% for this effect. Later measurements are presumably less affected by dead-time loss than earlier ones, since the effective pulse-pair resolution of standard counting electronics has improved significantly over the last three decades.

Strong electric fields due to contact potential differences, patch effects, and the proximity of charged insulating surfaces, as well as magnetic fields due to the earth or magnetized materials, are ubiquitous (see, for example, Moore *et al.*, 1983). They become particularly serious when electron trajectories pass close to objects such as defining slits and analyzer surfaces. Spurious electric fields are generally minimized by the use of proper materials and the scrupulous avoidance of insulating components within the line of sight of electron trajectories. Insulating layers of diffusion pump oil can be particularly troublesome in this regard. Effective vacuum pump trapping is thus important and appears to have been adequately considered in all the work reported here. While it is difficult to assess the effects of such electric fields on individual data sets, we note that the results of Kuyat and Jorgensen (1963) are probably affected by these problems more than those of other workers due to their use of a "zipper" chamber containing large areas of greased rubber surfaces. The data of Schader *et al.* (1986), taken with a magnetic-field analyzer, are restricted to electron energies above 20 eV. The use of a time-of-flight analyzer by the Pacific Northwest Laboratories (PNL) group significantly reduces residual field problems because of its relatively open structure. Field effects can also be reduced by accelerating the electrons before they enter the analyzer. This procedure must be undertaken carefully, however, because it can make $(m/\Omega)_a$ difficult to calculate (see below).

Most researchers used Helmholtz coils to eliminate the spatially large-scale ac and dc magnetic fields in their chambers. The experiments of Olsson *et al.*, Oda *et al.*, Stollterhoft and Gabler, and Toburen and co-workers, involving time-of-flight measurements or electrostatic analysis with proton energies ≤ 100 keV, used shields to minimize the magnetic field in the chamber. Such shields reduce variable as well as steady-state fields. Stollterhoft used an electron gun to prove that his electron measurements were not affected by magnetic fields within his experimental error. In all the experiments discussed in this review, the residual magnetic fields were reported to be < 20 mG. In a typical experiment, e.g., that discussed by Stollterhoft (1971a, 1971b), such a field could deflect a 5-eV electron by as much as 1 cm over its path, causing, in principle, a significant systematic error.

We note that both dead-time corrections and the

effects of spurious fields are most important for low-energy electron measurements. This is true in the former case because of the relatively high cross sections, and subsequently large count rates, associated with low-energy electron production.

The background signal can be separated into beam-related and beam-unrelated counts. The latter category includes "dark counts" from the electron multiplier and noise associated with its attendant electronic circuitry. Both of these signals are time independent. Elimination of beam-related background is generally much more difficult. Such counts can be due to ejection of electrons from fast H or H⁻ created upstream in the beam line or by direct ionization of the target by H or H⁻. Electrons ejected from the target by spurious photons, secondary electrons created in slit scattering, or protons reflected by the Faraday cup also cause beam-related background, as do ultraviolet photons created in the target. Finally, secondary scattering of electrons emitted from the target by chamber walls or residual gas adds to the background. (Direct emission of electrons from the residual gas or secondary emission from slits also contributes but is easily subtracted.)

The formation of neutral- and negative-ion contaminants can be reduced by maintaining good vacuum in the beam line preceding the chamber and by reducing the target volume (gas-beam targets are best for this). Typical beam-line pressures of 2×10^{-4} Torr and lengths of 2 m yield neutralization fractions of less than 1% for a 10^{-16} cm² cross section. The Nebraska group mentions corrections for beam neutralization starting with Crooks and Rudd (1971); Criswell *et al.* (1977); Satake *et al.* (1979); Bordenave-Montesquieu *et al.* (1982); Schader *et al.* (1986); and Bernardi *et al.* (1988, 1989) also mention the problem. At high energy (> 200 keV), it is probable that none of the data are affected by this problem due to the small neutralization and negative-ion formation cross sections.

Electrons created in the target by H, H⁻, photons, secondary electrons, or backscattered protons are essentially indistinguishable from the "real" signal. In general, their numbers can be shown to be negligible (Cheng *et al.*, 1989b). Photons created in the target by the incident beams, however, are a demonstrably serious source of background, and have been observed by Rudd *et al.* (1966). In that work, photon detection was minimized by coating the back plate of the parallel-plate analyzer they used with nonreflecting colloidal graphite. Ultimately, this background was subtracted from the signal by eliminating the electron counts with a large analyzer voltage (to sweep the electrons away from the detector entrance aperture) and subsequently determining the photon count rate alone.

Potentially the most serious cause of background is the scattering of ejected electrons by target and residual gas and by chamber walls. While background due to direct production of electrons in the ambient gas can be elim-

inated by simply removing the target gas and measuring the count rate with beam on, no equivalent procedure exists for the elimination of secondary-scattering background. A quadratic dependence of signal on target pressure would constitute evidence for the scattering of electrons from ambient or target gas, while scattering from walls would exhibit a linear pressure dependence. Most workers mention investigating the pressure dependence of their signals and finding it to be linear after correcting for absorption effects (see below).

To reduce background, several approaches have been taken. The Nebraska group coated their chamber walls with colloidal graphite and added baffles to impede scattered electrons. These precautions produced no significant differences from previous data (Rudd *et al.*, 1966; Cheng *et al.*, 1989b). The Pacific Northwest Laboratories group crumpled fine wire mesh and inserted it directly behind the proton beam in their target cell to prevent reflected electrons from leaving the cell (see Fig. 15). Both the cylindrical-mirror analyzer used by the PNL group and the "fountain" analyzer of Gibson and Reid used back plates made of wire mesh to minimize electron reflection. Stollerfoht and Gabler enclosed their analyzer in a tight box with negatively biased grids placed across the pumping ports. They also used discriminator grids in front of their electron multiplier to eliminate low-energy multiply scattered electrons.

2. Number density of target gas, n

The target density is an important factor in both the absorption correction term, $\exp(-\sigma_s n x)$, and $(n/\Omega)_{\text{eff}}$. In all the work reported here, it is determined from the target pressure P , measured either with an ionization gauge or a capacitance manometer. These devices are in turn calibrated by a McLeod gauge or, in some of the cases involving capacitance manometers, a direct dead-weight force measurement performed by the manometer's manufacturer. Care must be taken to account for the effects of thermal gradients and finite conductance between the point of measurement and the target region (Knudsen, 1910; Blaauw *et al.*, 1980). Calibration measurements using a McLeod gauge must also avoid error due to inadvertent gas pumping by streaming mercury vapor. [These considerations have been discussed in detail by Rudd *et al.* (1985); see also Schram *et al.*, 1965, and references therein.] In their later work Rudd and co-workers used a differential capacitance manometer with a correction for nonzero reference pressure. Töburen initially checked his capacitance manometer readings by placing a second manometer directly at the target cell, and found his calculated pressure differential to be accurate.

Target pressures in these experiments range between 4×10^{-5} and 3×10^{-2} Torr. No quadratic pressure dependence of the results is reported. Error estimates for the measurement of the pressure range between 5 and

12%. Absolute knowledge of the pressure is irrelevant, of course, for relative measurements, but relative values must be known precisely and must be reproducible.

In the early experiments at Nebraska, great care was taken to purify target gases. In more recent work, these precautions have been relaxed somewhat, with the simple use of research purity gas and all-metal pressure regulators and transfer lines.

3. The "absorption" coefficient σ_s

When electrons are ejected from the target by incident protons, they can be prevented from entering the electron multiplier by scattering from another gas atom. "Target gas" in this context refers to any gas atom that is in the chamber as a result of opening the target-gas valve; these atoms need not be in a volume intersected by the proton beam. "Absorption" of the ejected electrons can thus occur at any point along their trajectory prior to striking the first surface of the detector. The absorption process is of course closely related to secondary scattering. One detector's uncounted, absorbed electron is another detector's background. If N counts would be observed by a detector in the absence of absorption, N_s is given by $N_s = N \exp(-\sigma_s n x)$, where σ_s is the total scattering cross section, which is dependent on electron energy and target-gas species. (In principle, σ_s should be taken as an "effective" scattering cross section that does not include the contributions of forward scattering into the detector solid angle.) Generally, σ_s decreases with increasing electron energy. The effective path length x is given by Eq. (52).

The absorption factor can either be measured or calculated. Stollerfoht observed an exponential decrease in detected electron count rate with increasing target-gas pressure, independent of proton energy or ejection angle, when he used a static target. He was thus able to show a maximum absorption of 30% for 1-eV electrons and could experimentally correct his data for this effect. The Nebraska and Pacific Northwest Laboratories groups have calculated the $\exp(-\sigma_s n x)$ factor using data for the total cross sections compiled in various references (Brüche, 1927; Normand, 1930; Golden and Bandel, 1965; Golden *et al.*, 1966). Such calculations are difficult, especially for the PNL target, given the complicated vacuum geometry of the slits, tubes, and apertures that surround the electron trajectory. The PNL group found upon making this correction (which was occasionally as large as 25%), however, that the measured cross section values were rendered independent of pressure for various angles and electron energies, indicating that the correction had been made properly.

Bordenave-Montesquieu *et al.* ran at sufficiently low pressures ($< 10^{-4}$ Torr) that absorption corrections could be neglected.

The absorption correction has been neglected in the case of effusive gas-beam targets. This neglect is probably justifiable, given the much better localization of tar-

get gas and the generally lower values of n at the target center in this case.

4. Number of protons N_p

This quantity is measured by integrating the proton charge collected in the Faraday cup and dividing by the proton charge. Errors in this factor can result from electron capture downstream from the target region by the protons, failure to eliminate secondary-electron emission from the Faraday cup, faulty charge integration, failure to capture all of the incident beam in the cup, an reflection of protons from the cup back into the interaction region. These last two problems are most severe at low proton energies (≤ 10 keV), where large-angle scattering is more probable and susceptibility to stray magnetic fields is greater. Potential errors from the effects can be checked by varying the Faraday cup position and the size of its entrance aperture and by steering the beam electrostatically into the center of the cup (Kuyatt and Jorgensen, 1963; Rudd and Jorgensen, 1963).

The problem of beam neutralization by the target gas is more severe for static targets, but it is mentioned by Rudd and co-workers after 1971, and by Bordenave-Montesquieu *et al.* Attempts to eliminate secondary electron emission from the cup must be made with care since fields from suppressor grids can leak into the interaction region (Rudd and Madison, 1976). Faulty integration of the proton current is unlikely to cause error larger than a few percent; Töburen and Cheng, Rudd and Hsu have calibrated their ammeters with standard current sources. The question of proton reflection has not been addressed, except by Rudd, who finds the effect to be negligible at 50 keV. Sputtering effects should also be negligible.

5. Integrated path length/solid angle $(n\Omega)_{\text{eff}}$

Accuracy in this term depends critically on knowledge of the target-gas pressure profile over the incident-beam path, and the solid-angle acceptance of the analyzer. It is given by

$$(n/\Omega)_{\text{eff}}(\theta) = \int \Omega(z, \theta) n(z) dz,$$

where the integral is over the proton-beam path, dz is element of length along that path, and Ω is the solid angle subtended by the analyzer and detector for a given path element and electron-ejection angle. For the six gas targets of Rudd *et al.*, Stollerfoht *et al.*, a Bordenave-Montesquieu *et al.*, $n(z)$ is a constant over the acceptance window of the analyzers for all angles investigated. Thus $(n/\Omega)_{\text{eff}} = n \int \Omega(z, \theta) dz$. This integral purely geometric quantity, has been evaluated in terms of slit sizes and positions by Kuyatt (1968). The pressure profile of the PNL target is complicated by the longitudinal slit in the target cell. This group has determined n by using the same procedure used to calculate x . The

perimentally verified the accuracy of the calculation by measuring K-Auger electrons from N_2 as a function of θ . Since these electrons are emitted isotropically, properly corrected data will have no dependence on θ , as was found to be the case. For relative measurements, only knowledge of the functional form of $n(z)$ is important.

The use of gas-beam targets essentially precludes the possibility of absolute measurements because of the uncertainty in the beam density. Moreover, unless the length of the beam path viewed is so small that $n(z)$ is constant for all θ , or is so large that the entire proton path in the target is viewed by the analyzer at any angle, even relative measurements will suffer some angular systematic error. This problem is not discussed by any of the researchers using gas-beam targets except Gibson and Reid and may be a source of significant error. In this regard, we mention the systematic differences in the measured angular dependence of doubly-differential cross sections between Gibson and Reid, 1986, and Cheng *et al.*, 1989b. It appears that the poorly characterized shape of the effusive gas target in Gibson and Reid's "fountain" spectrometer allows a significant angular dependence of $(n/\Omega)_d$ that was not accounted for in the analysis. Interestingly, the angular discrepancies in the DDSCS measurements do not yield corresponding discrepancies in the SDCS, as will be seen in Sec. X.

The problem of determining $d\Omega$ is also difficult. The effective solid angle subtended by the detector can be altered by spurious fields and by focusing effects due to intentional preacceleration of the ejected electrons prior to their entrance into the analyzer (Kuyatt and Jorgensen, 1963). The effect of preacceleration on solid-angle acceptance (as well as energy resolution) has been considered extensively by Stollerfoht, Rudd, Toburen and co-workers, who find it to be most important for electron energies < 10 eV (Manson *et al.*, 1975). The finite diameter of the proton beam must also be considered in calculating the solid angle. All of the proton beams in the experiments reported here were ≤ 2 mm in diameter.

We note that estimates in the uncertainty in $(n/\Omega)_d$ are typically of the order of 10%, meaning that this factor contributes significantly to the overall uncertainty of the cross-section measurements.

6. Energy width-transmission product of the analyzer, ΔW

If we consider illumination of the entrance slit of an aberration-free electrostatic analyzer with electrons uniformly distributed in energy and angle (within the acceptance angle of the device), the output distribution of electrons versus their energy will be either trapezoidal or triangular in shape, with the peak of the distribution centered on the mean pass energy W . The base and top widths of the distribution depend only on the geometric dimensions of the analyzer (Rudd, 1972). The full width at half-maximum of the distribution is then defined as

ΔW , and its height taken to be the "transmission" t . Thus, for a "white" incident-electron flux of J electrons per unit energy interval, the analyzer will pass $J\Delta W/t$ electrons. Remarkably, the area under the transmission curve does not change even when angular aberration effects are considered (Kuyatt, 1968; Rudd, 1972). Since ΔW is a purely geometric quantity, it can be calculated. Toburen (1971) has measured ΔW by investigating Auger electrons; Rudd and Jorgensen (1963), Kuyatt and Jorgensen (1963), and Stollerfoht (1971a, 1971b) have used electron guns to verify their calculated values of ΔW .

7. Detection efficiency ϵ

This factor represents the percentage of electrons that, upon traversing the analyzer, produce recorded pulses. It includes the transmission of the discriminator/pulse-counting circuit and can be measured in a number of ways. The first absolute determination of ϵ in work of this type was reported by Rudd and Jorgensen (1963). They replaced their analyzer and detector with a Faraday cup and measured the electron flux emitted from the target at a given angle. By integrating the data taken with the electron multiplier and analyzer in the pulse-counting mode over electron energy, and comparing this result with the Faraday-cup value, they extracted ϵ with an uncertainty of about 10%. A similar technique, described by Stollerfoht (1971a), Rudd and Madison (1976), and Cacak and Jorgensen (1970) involves replacement of the target by a defocused electron gun. The electron flux entering the analyzer is determined either by measuring the emission current from the thermionic filament directly or by measuring the current density from the gun through a larger aperture of well-known area using a Faraday cup. In the latter case, a smaller aperture is subsequently placed in front of the analyzer and the electron flux is counted directly. These procedures also yield uncertainties in ϵ of about 10%.

Toburen (1971) directly calibrated a channeltron for incident-electron energies of 600 eV by comparing the channeltron count rate with that of a windowless-flow proportional counter operated in the Geiger region, whose efficiency was taken to be unity. Cheng *et al.* (1989a) have described a novel method for determining the discriminator transmission and electron-multiplier efficiency separately. The integral pulse-height spectrum from the counting circuit is obtained and a linear fit to the region of minimum slope is made. The zero-pulse-height intercept of this fit is divided into the value of the spectrum at the discriminator setting used for measurements, and the ratio is taken as the discriminator transmission. In addition, the efficiency of the multiplier is obtained by measuring its gain, which is used to infer the gain per dynode stage. If the electron-emission process at each dynode is assumed to obey Poisson statistics, the probability of no electrons reaching the collector anode, equal to $1 - \epsilon$, is easily calculated.

Gibson and Reid used several channeltrons and a

discrete-dynode electron multiplier simultaneously to detect scattered electrons. While they did not attempt to make absolute measurements, a knowledge of the relative efficiencies of their various detectors was required to provide accurate angular distributions. This was accomplished by rotating the detector array *in situ* to measure various parts of the angular distribution with several detectors, and cross-correlating the relative count rates at a given angle.

One possible cause of serious systematic error lies in the variation of ϵ with incident-electron energy. Some researchers appear to have neglected this problem, although knowledge of this dependence is crucial even for relative cross-section measurements. In general, the dependence must be determined experimentally, as has been done in some of the experiments discussed here. The variation of ϵ can be minimized by accelerating the electrons to ~ 100 eV after passage through the analyzer. The efficiency vs energy curve above this voltage is relatively flat for both channeltrons and discrete dynode devices; variations of $\sim 10\%$ are typical between 500 and 2000 eV (see, for example, Bordon, 1971; Toburen, 1971).

In all cases discussed above, determinations of ϵ have yielded values between 0.27 and 0.98. This range is due primarily to the different types and conditions of the detectors themselves, although some variation due to the incident secondary-electron energy has been observed. Both relative and absolute uncertainties between about 5% and 10% have been quoted.

Finally, we note that space charge of the positive ionized core of target gas can, in principle, cause systematic variations in the energy of the ejected electrons. Such effects can be significant if the differential cross section is falling rapidly with electron energy. For the experiments reported here, typical beam currents (~ 1 μ A) would result in negligible electron-energy shifts.

B. Ion energy-loss spectroscopy

In the technique developed by Park and co-workers, the singly-differential cross section $d\sigma/dW$ is measured directly and is given by the equation

$$N_5(W) - N_5(W) = nN_0 \int_0^W d\sigma/dW' \Phi(W - W') dW'. \quad (54)$$

where N_5 and N_6 are the number of protons detected with energy loss W , with and without target gas, respectively, for an incident number of protons N_0 ; n and l are the target number density and length; and $\Phi(W)$ is the energy profile of the incident beam (Park and Schwengerdt, 1969b; Park *et al.*, 1977).

Implicit in Eq. (54) are two assumptions. First, no correction for multiple scattering of the proton is included. This correction has been experimentally demonstrated to be small in both the He and the H experiments. Second, $d\sigma/dW$ is taken to be the complete, angle-

integrated singly-differential cross section. For this assumption to be correct, essentially all of the protons scattered in the target must ultimately be detected. Park *et al.* were able to demonstrate complete angular acceptance in their measurements of total cross sections with He by showing that the sum of the energy-loss, elastic, and charge-transfer signals was equal to the incident proton flux within their measurement uncertainty. This observation was consistent with theoretical calculations showing that protons scattered to angles greater than the instrumental angular acceptance of $\sim 10^{-3}$ rad would not affect the integrated cross section. It should be pointed out, however, that the fraction of protons scattered outside a given angle of acceptance is generally a function of W . Thus failure to attain complete angular acceptance in regions of W where the SDCS does not contribute significantly to the total cross section would not affect the above summation, but would result in systematic errors in the cross sections for those values of W . The report of the later H measurements (Park *et al.*, 1977) does not mention angular acceptance checks. With the caveat that the smaller singly-differential cross sections could, in principle, have some systematic error due to incomplete angular acceptance, there is strong circumstantial evidence to indicate at least the total cross sections do not suffer from this problem (Park, 1983).

If $d\sigma/dW$ varies slowly with W , as it does in the smooth energy-loss ionization continuum, then $\Phi(W)$, which varies rapidly about its central energy, can be taken as a δ function in Eq. (54), yielding

$$d\sigma/dW = [N_5(W) - N_6(W)]/nN_0. \quad (55)$$

Several important issues relating to the quantities in Eq. (55) are as follows.

1. The beam-related signal-background difference $N_5 - N_6$

The ion energy-loss signal includes, in general, processes other than those contributing to the electron signal discussed in the preceding section, except for H targets. In addition to simple single ionization, electron-analysis experiments will detect electrons resulting from multiple ionization and from transfer ionization that yields fast neutral hydrogen. The ion energy-loss experiments detect not only simple multiple ionization in addition to single ionization, but also energy loss resulting from simultaneous target excitation and/or dissociation. Moreover, collisions with more than one electron ejected are weighted more heavily in the electron-analysis method than single ionization [Rudd *et al.* (1983), p. 966]. Thus cross sections measured by the two methods are comparable only when multiple and transfer ionization, as well as excitation and dissociation, are negligible. Typically, such cross sections are at least an order of magnitude smaller than those for single-electron ejection (see, for example, DuBois, 1985, 1986 and DuBois and Manson, 1987, and references therein).

The background signal N_B includes contributions from background gas (most typically N_2) and reflections of the incident beam from the back (positive voltage) cylinder segment of the analyzer. With H targets, it is also necessary to eliminate the signal from undissociated H_2 in the target oven. This is done indirectly by determining the ratio of the energy-loss signals at 10.2 and 12.5 eV, corresponding to excitation of $H(n=2)$ and of the Lyman α bands of H_2 , respectively. This ratio yields the target dissociation fraction and allows a correction for H_2 ionization. The dissociation fraction for H is reported by Park et al. to be better than 97%, so this correction is small.

2. The target length-density product nl

The target length-density product nl is difficult to determine with H targets, due to the high temperatures and open structure of the H furnace. As a result, the H results of Park et al. have been integrated and subsequently normalized to the Born approximation for the total ionization cross section at 200 keV. A long-differentially pumped target cell with small entrance and exit apertures has been used in the He work, and nl can be calculated to a high degree of accuracy (Park and Schwengardt, 1969b).

3. The number of incident protons N_p

This number is measured by integrating the incident ion beam over its energy spread. Since the beam is detected by the complete "detector" following the target cell, as is the product signal N_S , all factors regarding detector efficiency, angular acceptance, and ion-related secondary-electron detection cancel out in the ratio of Eq. (54). This canceling of factors is a significant advantage of the ion energy-loss method.

IX. RECOMMENDED VALUES OF SINGLY-DIFFERENTIAL CROSS SECTIONS

The tables of double-differential cross-section data that have accumulated are quite voluminous. For example, Toburen's data for one target gas at a single proton energy typically involved measurements at 200–300 electron energies for each of 11 angles. Even the singly-differential cross-section data are rather extensive when many combinations of proton energy, electron energy, and target are involved. Generally only a small fraction of the data appears in published form, and even the tables that have been published (Rudd et al., 1976, 1979) contain condensations or selections of the data.

For the purposes of this review, we have obtained tables of the original data from most of the authors. While data from different laboratories are in good general agreement, there are areas of disagreement. Inter-comparison of many data sets indicates systematic variations with proton and electron energy and target, which

enable us to choose among divergent data.

The presentation of recommended values of singly-differential cross sections in tabular form is difficult because the pertinent ranges of electron energies change with proton energy. An electron-energy range for which the cross section is changing slowly at one proton energy may be one where it is varying rapidly at a different proton energy.

These three problems, the large volume of data, the discrepancies among different data sets, and the difficulty of presenting data in tabular form, are solved in this review by the use of semiempirical models. Model parameters are determined by fitting the models to experimental data. Averaging and/or selection were done with respect to the parameters rather than the original data. As a result, the recommended singly-differential cross-section values are expressed in the form of reasonably simple equations with a small number of parameters.

A. Choice of model

As discussed in Sec. VI, there are several semiempirical models to choose from, each having its own advantages and disadvantages. For instance, Kim's model is able to reproduce many details in the singly-differential cross sections of Ar and N_2 for a limited range of T_0 , and the resulting SDCS's can serve as normalization standards for experiments. For most practical applications, however, a model is needed that reproduces only gross features of the SDCS over a wide range of primary energies, since experimental data are available from 5 keV to 5 MeV. The only model presently available that represents the energy distributions over the entire range of primary as well as secondary energies is the one proposed by Rudd (1987, 1988). The parameters in this model must be determined from experimental data. Sufficient data are presently available for this determination for ten of the common gases. The model has been successfully fitted to all of these targets, thus determining its parameters.

The Rudd model reproduces gross features of the singly-differential cross sections of all targets reasonably well for low and intermediate energy collisions. It is also accurate at high energies for single-shell targets such as He and H_2 , but the form of the equation is not flexible enough to reproduce the fine details of SDCS's in different multishell targets. For quantitative reproduction of $\sigma(W)$ at $T_0 \geq 300$ keV, models that incorporate individual details of the dipole term are preferred. As described earlier, parameters for the model proposed by Kim are available only for argon and nitrogen.

B. Data adjustment

Kim's model depends mostly on the dipole function [Eq. (24)] and on the binary-encounter term [Eq. (35)] to reproduce the global shape of singly-differential cross

sections. Only parts of the experimental data that exhibit the expected shape are used to determine the mixture of dipole and nondipole contributions, to avoid distortions that may be introduced by uncertain parts of the experimental results. Thus it is unnecessary to modify any experimental data to determine adjustable parameters in Kim's model. On the other hand, the parameters in Rudd's model are sensitive to the shape and magnitude of the original data, and it is desirable before parameters are fitted to modify data deemed to be seriously inaccurate. We describe below how some of the experimental results were adjusted before applying Rudd's model.

Since total ionization cross sections have generally been determined to a higher accuracy than differential ones, and since recommended values of these total cross sections are readily available (Rudd et al., 1985), each experimental set of singly-differential cross sections was first adjusted to be consistent with the total cross sections. Two methods, both one-parameter adjustments, were used. In the first method, all SDCS's in a set were adjusted by a single multiplicative factor. In the second method, most of the adjustment was made on the larger low-energy cross sections. The equation used in this method was

$$\sigma(W)/\sigma_a(0) = [1 + K_c \sigma_a(W)/\sigma_a(0)]^{1/K_c - 1}, \quad (56)$$

where $\sigma(W)$ is the adjusted cross section, $\sigma_a(W)$ is the uncorrected cross section, and $\sigma_a(0)$ is its uncorrected value at the lowest measured secondary energy; generally 2 eV. The value of K_c was varied until the adjusted cross section yielded an integral equal to the recommended total cross section.

An example of this second form of adjustment is shown in Fig. 19. In (a) the original, unadjusted data are shown from two experiments. The agreement is quite good above about 20 or 30 eV, but the run of Crooks and Rudd (1971) yields an integral smaller than the recommended total cross sections of Rudd et al. (1985). The discrepancy appears due to the falloff of the cross section

FIG. 19. Plot of electron-energy distributions from 200-keV $H^+ + N_2$ to show the effect of data adjustment: $\square$, data of Stolterfoht (1971b); $\circ$, data of Crooks and Rudd (1971); solid line, Rudd model. (a) Original, unadjusted data. (b) Data adjusted by Eq. (56).

at the lowest energies. On the other hand, the data of Stolterfoht (1971b) integrate to too high a value, most likely because of cross sections that are too high below about 20 eV. When Eq. (56) is applied to the two sets of data and the values of K_c are chosen to give the correct integrated value, the resulting adjusted data are brought into much better agreement, as shown in Fig. 19(b).

Each of the runs of the data analyzed in this paper was subjected to the adjustment procedure of Eq. (56) before fitting. An exception was made for the data of Toburen and his collaborators. In their data, time-of-flight analysis was used to improve the low-energy accuracy, so that the relative uncertainty was virtually constant over the entire range. Therefore the first method of adjustment was used. Except for a few runs at low proton energies, the adjustments in the data were small.

C. Fitting of the Rudd model

A nonlinear least-squares program was adapted from the CURFIT program of Bevington (1969). The three parameters F_1 , F_2 , and α of the Rudd model were varied to provide the best fit for each energy spectrum at a given proton energy. As discussed in Sec. VI.D, the values of F_1 and F_2 for all subshells with $l < 2l_i$ were determined from Eqs. (43) and (44) using the same set of target parameters. For the inner subshells a single set of parameters was used for all targets. The inner-shell parameters were difficult to determine with any accuracy, but approximate values were sufficient, since inner shells generally do not contribute much to the overall cross sections. These values were estimated by fitting at the high-energy tails of the energy distributions, where inner-shell contributions predominate. Also, the known total cross sections for inner-shell ionization were used in differential cross-section data for specific inner shells becomes available in the future, the inner-shell parameter can be determined more accurately.

The values of α were found to be independent of proton energy within experimental uncertainty and were taken to be constant for a given target. The parameters F_1 and F_2 vary smoothly with proton energy, allowing fit by the functions in Eqs. (43)–(48). There appear to be two maxima in the graph of F_1 for several of the targets as seen in the example in Fig. 20.

D. Table of parameters in the Rudd model

The values of the target parameters for Eqs. (43) and (44) are given in Table V. It can be seen that the value of A_1 are not far from unity, and the sums $A_1 + A_2$ are not far from 2, as expected on the basis of the Bethe theory. The parameter α always falls between 0.5 and 0.9. The parameters C_1 and C_2 , which determine the magnitudes of F_1 and F_2 at low proton energies, are typically in the range of 0.2 to 1. The values of D_1 and D_2 which determine the slope of the cross sections with pro-

FIG. 20. Plot of the parameters F_1 , F_2 , and α obtained in fitting the data for 5–1500 keV $H^+ + H_2$ collisions. Data from Rudd (1979), Rudd and Jorgensen (1983), Rudd et al. (1966), and Toburen and Wilson (1972). The lines for F_1 and F_2 are the best fits to Eqs. (43) and (44). The line for α is a constant equal to the average of the fitted values.

E. Recommended values

Having fitted the model to the data for ten different target gases, it is possible to calculate cross sections for any combination of primary and secondary energy for any of those targets from parameters of the model Eq. (41). The following is a sample computation for the case of 8-eV electrons ejected in $H^+ + He$ collisions at 50 keV. With $F_1 = 24.6$ eV and $N = 2$, we have $w = 0.325$, $v = 1.05$, and $S = 2.15 \text{ \AA}^2$. From the parameters in Table II, we have $L_1 = 0.389$, $H_1 = 0.232$, $L_2 = 0.718$, and $H_2 = 5.65$, giving $F_1 = 0.621$ and $F_2 = 0.637$. The cutoff energy is $w_c = 4w^2 - 2w - R/AJ = 2.19$, whence $\exp[\alpha(w - w_c)/w] = 0.219$. Moreover, $(F_1 + F_2 w)/(1 + w) = 0.356$. The cross section is then $0.0255 \text{ \AA}^2/\text{eV}$. For comparison, integrated experimental results of Rudd and Madison (1976) and Rudd and Jorgensen (1983) are 0.0341 and $0.0251 \text{ \AA}^2/\text{eV}$, respectively; Gibson and Reid's value (interpolated) is $0.024 \text{ \AA}^2/\text{eV}$.

Additional samples of recommended cross sections are given in Table VII for selected combinations of primary and secondary energies with hydrogen (H_2) as a target. Table VIII gives the total and partial cross sections for the various subshells of argon at 300-keV proton energy. Figure 21 shows these data compared with the results of Toburen et al. (1978). The same quantities are plotted as Y in Fig. 22.

At the cost of somewhat greater complexity, the Kim

TABLE VII. Sample of recommended cross sections (in $\text{\AA}^2/\text{eV}$) for $H^+ + H_2$ calculated from Eq. (41). The notation 5.52(-2) denotes 5.52×10^{-2} .

w (eV)	10 keV	30 keV	100 keV	300 keV	1000 keV	3000 keV
0	5.52(-2)	9.19(-2)	1.24(-1)	7.78(-2)	3.47(-2)	1.50(-2)
1.5	5.12(-2)	8.98(-2)	1.06(-1)	6.24(-2)	2.71(-2)	1.16(-2)
2	4.94(-2)	8.84(-2)	1.01(-1)	5.83(-2)	2.51(-2)	1.07(-2)
3	4.56(-2)	8.48(-2)	9.25(-2)	5.11(-2)	2.17(-2)	9.25(-3)
5	3.76(-2)	7.64(-2)	7.73(-2)	4.02(-2)	1.66(-2)	6.99(-3)
7	3.04(-2)	6.79(-2)	6.55(-2)	3.24(-2)	1.30(-2)	5.53(-3)
10	2.15(-2)	5.61(-2)	5.23(-2)	2.43(-2)	9.46(-3)	3.88(-3)
15	1.17(-2)	4.06(-2)	3.76(-2)	1.62(-2)	6.02(-3)	2.42(-3)
20	6.25(-3)	2.94(-2)	2.82(-2)	1.16(-2)	4.13(-3)	1.63(-3)
30	1.75(-3)	1.54(-2)	1.75(-2)	6.73(-3)	2.26(-3)	8.66(-4)
50	1.44(-4)	4.08(-3)	8.58(-3)	3.07(-3)	9.58(-4)	3.51(-4)
70	1.33(-5)	1.00(-3)	4.95(-3)	1.75(-3)	5.21(-4)	1.85(-4)
100	4.40(-7)	1.19(-4)	2.49(-3)	9.34(-4)	2.66(-4)	9.23(-5)
150	1.91(-9)	3.95(-6)	7.98(-4)	4.44(-4)	1.21(-4)	4.09(-5)
200	9.92(-12)	1.52(-7)	1.83(-4)	2.58(-4)	6.92(-5)	2.28(-5)
300	3.00(-16)	3.00(-10)	5.36(-6)	1.17(-4)	3.10(-5)	1.00(-5)
500	3.52(-16)	1.96(-15)	5.03(-9)	3.10(-5)	1.25(-5)	3.71(-6)
700	7.50(-25)	1.76(-20)	1.57(-6)	1.57(-6)	5.74(-6)	1.80(-6)
1000			6.44(-12)	4.58(-9)	2.81(-6)	8.81(-7)
1500			3.90(-16)	3.52(-13)	1.24(-6)	3.89(-7)
2000			5.26(-17)	3.40(-17)	3.39(-7)	2.18(-7)
3000			4.40(-20)	4.40(-20)	2.17(-11)	9.69(-8)
5000					3.47(-8)	2.36(-10)
7000						8.40(-18)
10000						

on energy at low energies, have a greater variation, even becoming negative for some targets. The parameters B_1 , B_2 , E_1 , and E_2 are less easily interpreted and have greater variations, since they merely determine connections between the low- and high-energy regions.

TABLE VIII. Cross sections (in $\text{\AA}^2/\text{eV}$) by subshell for 300 keV $H^+ + Ar$ calculated from Eq. (41). The notation 1.97(-1) denotes 1.97×10^{-1} .

w (eV)	3p	3s	2p	2s	1s	Total
2	1.97(-1)	1.58(-2)	1.44(-4)	1.89(-5)	3.00(-9)	2.14(-1)
4	1.50(-1)	1.36(-2)	1.42(-4)	1.87(-5)	3.00(-9)	1.64(-1)
6	1.18(-1)	1.18(-2)	1.39(-4)	1.84(-5)	3.00(-9)	1.50(-1)
10	7.71(-2)	9.19(-3)	1.34(-4)	1.79(-5)	3.00(-9)	8.64(-2)
15	4.98(-2)	6.95(-3)	1.29(-4)	1.73(-5)	2.99(-9)	5.64(-2)
20	3.46(-2)	5.44(-3)	1.23(-4)	1.68(-5)	2.99(-9)	4.01(-2)
30	1.92(-2)	3.57(-3)	1.13(-4)	1.57(-5)	2.98(-9)	2.59(-2)
50	8.32(-3)	1.87(-3)	9.64(-5)	1.38(-5)	2.96(-9)	1.01(-2)
75	4.04(-3)	1.02(-3)	7.96(-5)	1.19(-5)	2.94(-9)	5.16(-3)
100	2.37(-3)	6.43(-4)	6.55(-5)	1.02(-5)	2.92(-9)	3.09(-3)
150	1.09(-3)	3.19(-4)	4.76(-5)	7.74(-6)	2.86(-9)	1.37(-3)
250	3.99(-4)	1.22(-4)	2.61(-5)	4.62(-6)	2.73(-9)	5.52(-4)
300	2.75(-4)	8.30(-5)	1.98(-5)	3.62(-6)	2.66(-9)	3.31(-4)
500	6.85(-5)	1.86(-5)	7.05(-6)	1.45(-6)	2.34(-9)	9.56(-5)
750	2.61(-6)	1.27(-6)	2.10(-6)	4.96(-7)	1.93(-9)	6.48(-6)

low-energy electrons. Measurements of DDCS by Redbro and Andersen (1979), Saitaka, Urakawa, and Oda (1979), Tokoro and Oda (1985), and Olson et al. (1987) are too limited to permit SDCS calculations. The DDCS data of Bernardi et al. (1988, 1989, 1990) and Schader et al. (1986) are probably extensive enough for calculation of SDCS's, but were not published in tabular form. Furthermore, their cross sections were normalized to the data of Rudd et al. (1976).

The only data for atomic hydrogen at the present time are those of Park et al. (1977). Unfortunately, their electron energy range extended only to 20 eV, insufficient to provide information about the parameter α . Furthermore, the proton energy range is not sufficient to allow unambiguous determination of the parameters in a model that relates high and low energies. For this reason, atomic hydrogen was not included in our analysis and fitting.

A. Helium

Thirty-eight runs in the range 5–5000 keV from different data sets were fitted. The value of A_1 from the

FIG. 22. The same as Fig. 21 plotted as Y/E , the ratio of the cross sections to the Rutherford cross section.

FIG. 21. Partial cross sections (dashed lines) from the subshells of argon, as calculated from Eq. (41), along with the total (solid line) for 300 keV. Also shown are the corresponding experimental data from Toburen et al. (1978).

fit was 1.02, 15% higher than the 0.89 value obtained from oscillator-strength data. The values of the parameters in Table V fit the total cross sections with an average deviation of 3%.

A large downward adjustment was needed in the low-energy data (especially those of Rudd and Madison, 1976) to match the recommended total cross sections. The charge transfer to the continuum (CTC) peak results in a discrepancy for the runs at the intermediate energies of 40–150 keV in all data sets, the peaks being especially prominent in the data of Gibson and Reid (1985, 1986). There is also a discrepancy near the cutoff energy between the model calculations and the data of Rudd and Jorgensen (1963) and of Rudd *et al.* (1966). This stems from the size of the angular mesh, which was too coarse to reproduce the binary-encounter peak in the experiment at high energies. The data of Toburen (1971) and of Stollerfoht (1971a) taken with smaller angular steps do not have this discrepancy. The data of Park and Schwengerdt (1969b) agrees well with other data just below the cutoff but falls too low at lower energies.

The average overall accuracy of the fit is estimated to be $\pm 10\%$. Samples of the data are shown in Fig. 23, where Y , the ratio of the cross section to the Rutherford

FIG. 23. Energy distribution of secondary electrons from proton collisions on helium, shown as a ratio of SDCS to the Rutherford cross section (see text): $\circ$, Rudd and Madison (1976); $\bullet$, Rudd and Jorgensen (1963); Δ , Rudd *et al.* (1966); $\times$, Toburen *et al.* (1978); $+$, Cheng *et al.* (1989a); $\square$, Park and Schwengerdt (1969b); $\square$, Manson *et al.* (1975); Δ , Gibson and Reid (1985, 1986). Lines are the model with parameters given in Table III. Vertical arrows indicate the expected position of the peaks from charge transfer to the continuum.

cross section, is plotted against the secondary energy W for various primary energies from 10 to 4200 keV.

B. Neon

Three sets of data combine to cover T_0 from 7.5 to 1500 keV, with a gap between 300 and 1000 keV. While the individual runs were fitted fairly well by the model, it was difficult to find parameters that agreed with the singly-differential cross sections and also gave the correct asymptotic total cross sections at high and low energies. The value $A_1 = 0.75$ from the total cross sections is too large to fit the higher-energy SDCS's. The value 0.58 was chosen as the best compromise. The data and fit of the model are shown in Fig. 24.

The discrepancy between the model and the SDCS's due to the CTC peak begins to appear at about 30 keV and is quite prominent at 150–300 keV. At 300 keV and above, another peak (in Y but not in $d\sigma/dW$) comes at a somewhat lower secondary energy, $W \sim 50$ eV. This peak, which represents an enhancement of the continuum-dipole interaction, grows as the proton energy is increased (Kim, 1976).

At primary energies of 50–300 keV, the data above the cutoff are generally higher than the model. This may result from our arbitrary classification of the 2s subshell as an "inner shell," since $I(2s) > 2I(2p)$. If the parameter A_1 had been given the lower value of 0.57 for the outer shells rather than the larger value (0.66) characteristic of the inner shells, this discrepancy would have been much smaller. Nevertheless, the model should provide SDCS's with an average error of about 15%.

C. Argon

Six sets of data cover the energies 5–5000 keV. These are shown for representative primary energies in Fig. 25. At low energies the data of Criswell and Toburen (Cris-

FIG. 24. Energy distribution of secondary electrons from proton collisions on neon: $\bullet$, Criswell and Rudd (1971). The rest of legend as in Fig. 23.

FIG. 25. Energy distribution of secondary electrons from proton collisions on argon: $\circ$, Rudd's data from Criswell *et al.* (1977); $\bullet$, Criswell and Rudd (1971); $\times$, 10 keV, Criswell's data in Criswell *et al.* (1977); $\times$, high energies, Toburen *et al.* (1978); $\square$, Gabler (1974). The rest of legend as in Fig. 23.

well *et al.*, 1977) agree quite well with those of Rudd (1977) after both are adjusted to match the recommended total cross sections. Below 50 keV none of the runs were carried to sufficiently high secondary energies for the $n=2$ shell contribution to be appreciable. The fit of the 3p and 3s subshells to the Rudd model is very good, with an estimated average uncertainty of 10%. Figure 22 shows model calculations for the separate and combined subshells.

In the range of 50 to 500 keV the $n=2$ contribution is apparent beyond the cutoff for the outer shell and may be compared with the Rudd model, where data are available. In some cases the model calculations for the $n=2$ contribution are in good agreement with the data or are slightly lower. However, in most cases the model results beyond the $n=3$ cutoff are too high. For the 50–500 keV energies the Rudd model yields results that are probably accurate to 10–15% below the $n=3$ cutoff, but the error increases to about 50% above this cutoff.

Above 1000 keV, the $n=2$ contribution actually exceeds that of the 3s electrons at some energies below the cutoff, and at 2000 keV it begins to exceed that of the 3p electrons. Above 4200 keV the $n=2$ contribution is dominant over a large fraction of the secondary-energy range.

The Cooper minimum appears as a dip in Y at about 30 eV for impact energies greater than 300 keV and is clearly seen in Figs. 22 and 25. The CTC peak is barely noticeable in most of the data and is most prominent in the data of Gibson and Reid (1987a, 1987b).

The accuracy of Rudd's model above 500 keV is es-

imated at 20% except near the Cooper minimum and above the $n=3$ cutoff, where the agreement is worse (see Figs. 8, 9, 22, and 25). For applications that require details of $d\sigma/dW$, Kim's model, discussed in Sec. VI C gives a more accurate fit and should be used for $T_0 \geq 20$ keV (cf. Figs. 8 and 9).

D. Krypton

The two data sets for krypton cover T_0 from 7.5 to 4200 keV, with a gap from 150 to 1500 keV. However, because the model fits smoothly both the low- and high-energy data sets, the missing energies can be filled in quite accurately and there is little need to take additional data to obtain SDCS's. Only small adjustments to the experimental data were required except at the very lowest proton energies (below 20 keV); the model fits well nearly everywhere. One exception lies at the highest secondary energy for the two lowest primary-energy runs where the model results are somewhat too high. The other discrepancy occurs in the highest-energy run (4200 keV) where the experimental data are suspect here, since their pattern differs abruptly from that of other runs in the same data set.

The model should be accurate to 10–15% with the exceptions noted. The value of $A_1 = 1.46$ is 12% higher than the value expected from oscillator-strength data. Figure 26 shows the data for representative energies along with the model.

E. Molecular hydrogen

Twenty runs from five sets of data were individually fitted with an average deviation of 10%. The value of A_1 calculated from oscillator strength (0.80) was too small to fit the SDCS data and was replaced by 0.96. Cross sec-

FIG. 26. Energy distribution of secondary electrons from proton collisions on krypton. Legend as in Fig. 23.

tions computed with the parameters given in the table agreed with the measured data with an average deviation of 15%.

The data by Rudd (1979) required the largest adjustment, especially at the lowest energies, but were fitted well after adjustment. The single run at 50 keV by Gibson and Reid (1987a, 1987b) had an average deviation of 30% due to the CTC peak. This peak also showed up, but to a lesser extent, in the other data sets. In the Rudd *et al.* (1996b) data, a discrepancy occurs in the 200- and 300-keV runs near the cutoff, owing to the coarseness of the angular mesh, mentioned earlier. A discrepancy between the model and the data of Toburen *et al.* at ≥ 1000 keV occurs near the cutoff. Since the cutoff is very sharp at high energies, cross sections obtained by integrating data over a limited number of angles are apt to be inaccurate. The cross sections given by the model are estimated to have an accuracy of 10%. Data and the fit are shown in Fig. 27.

F. Molecular nitrogen

Sets of data from several laboratories over the range of $T_0 = 5$ to 1700 keV are available for nitrogen. The best value for A_1 , 1.05, coincides with that predicted by the oscillator strength. The lowest-energy data would be fitted better with a slightly smaller value of α (say, 0.60 instead of 0.70), while some of the runs at higher energies would have benefited from a somewhat larger value (e.g., $\alpha = 0.80$). However, the three highest-energy runs did not extend far enough past the cutoff to give any information on α .

The cross sections in Stollerfoht's 500-keV run (Stollerfoht 1971b), and to a lesser extent in his 400- and 300-keV runs, tend to drop too fast at energies approaching cutoff, as compared to the corresponding data of To-

FIG. 27. Energy distribution of secondary electrons from proton collisions on molecular hydrogen; O, Rudd (1979); X, Toburen and Wilson (1972). Rest of legend as in Fig. 23.

FIG. 28. Energy distribution of secondary electrons from proton collisions on molecular nitrogen; O, Rudd (1979); X, Toburen (1971); □, Stollerfoht (1971b). Rest of legend as in Fig. 23.

G. Molecular oxygen

Three sets of data cover the range of 7.5 to 300 keV. With guidance from total cross sections, the parameters were estimated over the full range of energies. The major discrepancies between model and data were at $v_e = v_0$, due to CTC. Smaller discrepancies occur at the highest secondary energies. These may be due to a poor set of parameters for the inner shells, but more likely to fluctuations and incorrect background subtraction in the experimental data. The model should be accurate to 15%. Figure 29 shows the results. The value of A_1 is 1.02, very close to the 1.04 calculated from the oscillator strength.

FIG. 29. Energy distribution of secondary electrons from proton collisions on molecular oxygen; +, Cheng *et al.* (1989b); ●, Crooks and Rudd (1971). Rest of legend as in Fig. 23.

FIG. 30. Energy distribution of secondary electrons from proton collisions on carbon dioxide; +, Cheng *et al.* (1989b). Rest of legend as in Fig. 23.

H. Carbon dioxide

Few data are available for this target, namely, those of Cheng *et al.* (1989b) and the single run at 50 keV by Gibson and Reid (1987a, 1987b). Parameters determined from those data can nevertheless be extrapolated, with guidance from total cross sections, to yield reasonably reliable SDCS's over a much wider range of energies. Fitting each run individually yields an average deviation of 9%, which increases to 14% when the parameters are determined by Eqs. (43)–(48). Part of this deviation is due to the CTC peak, which appears at 30 keV and above. Otherwise, most of the deviation represents random scatter. None of the data sets required a large adjustment to achieve consistency with the recommended total cross sections. Results are shown in Fig. 30. The value 1.09 for A_1 is about 4% lower than that required to fit the total cross sections (1.13). The value calculated from the oscillator strength is still lower, namely, 0.93.

I. Water vapor

The data for water vapor comprise 11 runs from $T_0 = 15$ to 1500 keV. Those by Bolorizadeh and Rudd (1986) at low proton energies show a leveling off at high secondary energies which is probably spurious. This high-energy tail was ignored in the fitting. A relatively small adjustment was needed to bring the various runs into agreement with the recommended total cross sections. The average deviation of the individual fits from the model was 9% and rose only to 10% for parameters calculated by Eqs. (47) and (48). The 1500-keV run was omitted from the averaging, since its low-energy portion is evidently in error. The model fits the rest of the data very well (see Fig. 31).

J. Methane

At the time the fitting was done, data sets were available for methane only at four proton energies, one at $T_0 = 50$ keV by Gibson and Reid (1987a, 1987b), and runs at 300, 400, and 500 keV by Stollerfoht (1971a). While this range of energies is not large enough to provide reliable parameters, a set that should be approximately correct has been selected with the help of the total cross sections. The results are estimated to have a 25% uncertainty above 50 keV and 40% below. Figure 32 shows some of the results.

K. Other targets

None of the other targets had data over a sufficient energy range to yield parameters for the Rudd model.

FIG. 31. Energy distribution of secondary electrons from proton collisions on water vapor; O, Bolorizadeh and Rudd (1986); X, Toburen and Wilson (1977). Rest of legend as in Fig. 23.

FIG. 32. Energy distribution of secondary electrons from proton collisions on methane: Δ , Gibson and Reid (1987a,b); $\square$, Stollerfoht (1971a).

XI. RECOMMENDATIONS FOR FUTURE WORK

In this section we briefly review what appear to be the most promising and important avenues for future theoretical and experimental investigations.

Perhaps the most serious drawback in the theory of proton-impact ionization is the lack of convenient theoretical methods to predict cross sections for slow incident protons, i.e., $T_0 \leq 300$ keV. In addition to the fact that the usual perturbative calculations fail for slow protons, the "two-center" aspects of the collision can now be very important. This necessitates the use of quasimolecular models or theories, which explicitly include the interaction between the ionized electron and the two positive ions, such as the Coulomb distorted-wave method. One approach that is likely to work well in this regime is the classical-trajectory Monte Carlo method described in Sec. IV.B. Hence a systematic study of the doubly- and singly-differential cross sections based on the classical-trajectory Monte Carlo method for a variety of targets is desirable. Such a study could identify systematics and make it possible to develop more realistic theoretical models that could effectively cover slow incident protons. In general, DDCS measurements made at very low ($T_0 < 50$ keV) energies, where two-center effects are most prominent, have large uncertainties. This is partly due to the fact that the secondary electrons have corresponding lower energy and are thus difficult to measure accurately, and partly due to the fact that low-energy proton beams are more difficult to characterize and control. It would thus be desirable, from the standpoint of developing theory in this difficult region, to make several careful "benchmark" measurements of SDCS's.

Although first-order perturbation theory such as the Born approximation is valid for fast protons, it is unrealistic to use the PWBA to calculate doubly-differential or

singly-differential cross sections for molecules because of the complexity in calculating continuum wave functions for such targets. With the possible exception of H_2 , it is safer to rely on a combination of semiempirical models and some selective experimental data for the time being. Models based on the Bethe theory (see Sec. VI) will be able to provide reliable predictions for high-energy protons as long as realistic dipole oscillator strengths are used. Such models, however, cannot be built from optical data alone; the models contain parameters that can be determined only if actual proton-impact cross sections are known for some strategic incident energies, e.g., $T_0 = 300, 1000, 3000$, and 5000 keV. When reliable absolute values of the total ionization cross sections are known, experimental DDCS's or SDCS's need not be absolute, since relative cross sections can easily be normalized using Platzman plots. Hence experimental data for DDCS's that emphasize the correct shape rather than absolute magnitude are desirable for targets whose total ionization cross sections and dipole oscillator strengths are well known. Experimental photoionization cross sections, including partial cross sections that identify different ionic states, are also needed to provide differential oscillator strengths for this type of normalization, as well as for modeling collisions with fast incident protons.

Another weak link in the theory concerns multiple ionization. Multiple ionizations that result from a series of single ionization events (such as the ionization of an inner-shell electron followed by Auger electrons created in filling the inner-shell vacancy) can be handled within existing theory. However, no good theory exists for true multiple ionizations, i.e., when two or more electrons from a given subshell are ejected as a result of a single collision. Such multiple ionization is a manifestation of electron-correlation effects, which are inherently nonlinear. Any attempt to describe multiple ionization as a series of single collisions, e.g., the first ejected electron hitting and ionizing another in the same subshell, and so on, will not be sufficient unless such a model includes all orders of perturbation. The development of a true multiple-ionization theory is a worthwhile challenge; such a theory might share the same basis as a nonperturbative theory of multiphoton ionization. Experimentally, measurements of SDCS that are shell specific would be beneficial here. Such data would also be very helpful in providing input parameters for semiempirical models. The level of complexity of such experiments, however, is significantly greater than that of those described in this review, since coincidence detection would be required.

As we have mentioned earlier, experimental difficulties so far have hindered the determination of accurate DDCS's for slow ejected electrons, $W \leq 10$ eV. The development of any theory that can predict an accurate DDCS for slow electrons ejected from, say, He will provide a valuable tool that not only yields sorely needed data but also serves as a gauge with which experimental distortions can be identified. In combination with such a

theory, more extensive measurements of low-energy electrons using the time-of-flight technique would dramatically improve the existing data sets.

A judicious application of the theory for Compton profiles may lead to a reliable method to predict the singly-differential cross sections of very fast ejected electrons beyond the classical cutoff. Such electrons contribute little to the total ionization cross sections, but their role becomes more significant in modeling energy deposition by energetic protons.

Experimentally, a number of technical possibilities and challenges exist that hold promise for major improvements in the SDCS data base. As mentioned earlier, benchmark measurements at low primary energy and extensive time-of-flight measurements at low secondary energies are highly desirable. In addition, the technology for measuring subshell-specific DDCS's is currently available, using coincidence measurements, and such measurements should be performed. Two techniques for measuring SDCS's directly—ion energy-loss spectroscopy (Park *et al.*) and the angle-integrating method of Vroom *et al.* (1977)—have found only limited use to date. The analyzer of Vroom *et al.* could be adapted easily for incident-proton measurements. Ion energy-loss measurements, which have been made for a limited range of both primary and secondary energies, for only atomic hydrogen and helium targets, could provide a broad range of direct, reliable SDCS's. While the cross sections measured with ion energy-loss spectroscopy are not strictly equivalent to those measured by secondary-electron analysis, the energy regions where valid comparisons can be made are large, and the two techniques could provide important consistency checks for each other.

If realized, the theoretical and experimental advances just mentioned will significantly improve the applicability of basic ionization physics to problems that need these results. One of the most important of these is radiation damage in biological systems. In this field, more doubly-differential and singly-differential cross sections for a range of hydrocarbon targets would be immediately useful.

ACKNOWLEDGMENTS

The authors would like to thank Dr. Dave Schultz and Dr. C. O. Reinhold for providing the classical-trajectory Monte Carlo results for helium, Dr. L. H. Toburen for providing numerical tables of his experimental results and for suggested changes in the manuscript, Dr. W. Stevens for providing theoretical energies in Tables I(a) and I(b), and Dr. J. Berkowitz for references to experimental binding energies. This work was supported in part by NSF Grants PHY-8701905 and PHY-9020529 (M.E.R.) and PHY-9045643 (D.H.M.), and the Office of Fusion Energy of the DOE (Y.-K.K. and T.J.G.).

APPENDIX A: MAXIMUM ENERGY TRANSFERRED TO AN ELECTRON AT REST

Consider a head-on, linear collision between an incident proton and a free electron initially at rest. Then,

the conservation of energy and momentum requires

$$Mv_0^2/2 = Mv_f^2/2 + mv_e^2/2, \quad (A.1)$$

$$Mv_0 = Mv_f + mv_e, \quad (A.2)$$

where M is the proton mass, v_0 its incident speed, v_f its speed after the collision, m the electron mass, and v_e the electron speed after the collision. From Eqs. (A.1) and (A.2), we get

$$v_0 + v_f = v_e. \quad (A.3)$$

However, energy conservation prohibits the proton from moving faster after the collision than its initial speed, i.e., $v_f \leq v_0$:

$$v_e \leq 2v_0. \quad (A.4)$$

Thus the maximum energy the free electron can gain from the incident proton is

$$W_{\max}(p) = mv_e(\max)^2/2 = 2mv_0^2 = 4T, \quad (A.5)$$

where

$$T = mv_0^2/2 \quad (A.6)$$

is the kinetic energy of an electron moving with the same speed as the incident proton.

Note that (a) $W_{\max}(p)$ given by Eq. (A.5) is independent of the proton mass and indeed applies to all heavy incident particles [see Eq. (10)]; (b) this limit is far smaller than the actual incident energy, $T_0 = (M/m)T$; and (c) the maximum kinetic energy of an electron ejected as a result of the incident beam direction will be even less than 4T because, in such a case, the momentum transferred to the electron will be smaller.

APPENDIX B: BINARY PEAK ANGLE

Consider the collision of an incident particle of energy T_0 and momentum k_0 with an electron at rest (see Fig. 33). After the collision, the electron recoils at an angle ϕ with kinetic energy W and corresponding momentum k_e , while the proton is scattered at an angle θ with kinetic energy $T_p = T_0 - W$ and corresponding momentum k_p . From momentum conservation, we have

$$k_p \cos \theta + k_e \cos \phi = k_0, \quad (B.1)$$

$$k_p \sin \theta = k_e \sin \phi. \quad (B.2)$$

By eliminating ϕ in Eqs. (B.1) and (B.2), we get

$$2k_0 k_e \cos \theta = k_0^2 + k_e^2 - k_p^2, \quad (B.3)$$

while

$$k_0^2 = 2MT_0, \quad k_e^2 = 2mW, \quad (B.4)$$

$$k_p^2 = 2MT_p = 2M(T_0 - W).$$

Substitution of Eq. (B4) into Eq. (B3) results in

IG. 33. Momenta in the collision of a proton with an electron at rest. k_p , incident proton momentum; k_p' , scattered proton momentum; k_e , ejected electron momentum.

$$\cos \theta_p = (W/T_0)^{1/2} \text{ if } M = m, \quad (B5)$$

$$= \frac{1}{2} (MW/mT_0)^{1/2} \text{ if } M \gg m, \quad (B6)$$

where θ_p is the angle to which the (secondary) electron is ejected. Since the target electron was at rest initially, θ_p is the only direction it can go, i.e., it has a delta-function angular distribution.

From Eq. (B6), we get

$$W = 4T \cos^2 \theta_p. \quad (B7)$$

Hence an electron ejected in the forward direction has the maximum energy $W_{\max} = 4T$.

REFERENCES

- Abrines, R., and I. C. Percival, 1966a, *Proc. Phys. Soc. London* **88**, 861.
- Abrines, R., and I. C. Percival, 1966b, *Proc. Phys. Soc. London* **88**, 873.
- Anderson, H. H., and H. L. Bay, 1981, in *Sputtering by Particle Bombardment I*, Springer Topics in Applied Physics No. 47, edited by R. Behrisch (Springer, Berlin).
- Arcuni, P. W., and D. Schneider, 1987, *Phys. Rev. A* **36**, 3059, and references 1 and 23 therein.
- Bang, J., and J. M. Hansen, 1959, K. Dan. Vidensk. Selsk. Mat. Fys. Medd. **31**, No. 13.
- Belkic, D., 1978, *J. Phys. B* **11**, 3529.
- Benoit-Cattin, P., D. Blanc, A. Bordenave-Montesquieu, A. Gleizes, M. Rodiere, and S. Sohanian, 1973, *J. Phys. E* **6**, 1.
- Berkowitz, J., 1979, *Photoabsorption, Photoionization, and Photoelectron Spectroscopy* (Academic, New York).
- Bernardi, G., P. Faustein, C. R. Garibotti, and S. Suarez, 1990, *J. Phys. B* **23**, L139.
- Bernardi, G., S. Suarez, P. Focke, and W. Meckbach, 1988, *Nucl. Instrum. Methods* **B** **33**, 321.
- Bernardi, G., S. Suarez, P. D. Faustein, C. R. Garibotti, W. Meckbach, and P. Focke, 1989, *Phys. Rev. A* **40**, 6863.
- Bethe, H. A., 1930, *Ann. Phys. (Leipzig)* **5**, 323.
- Bethe, H. A., and R. W. Jackiw, 1986, *Intermediate Quantum Mechanics*, 3rd ed. (Benjamin, New York).
- Bevington, Philip R., 1969, *Data Reduction and Error Analysis for the Physical Sciences* (McGraw-Hill, New York).
- Blaauw, H. J., R. W. Wagenaar, D. H. Barends, and F. J. de Heer, 1980, *J. Phys. B* **13**, 359.
- Blauth, E., 1957, *Z. Phys.* **147**, 228.
- Bolotovskich, M. A., and M. E. Rudd, 1986, *Phys. Rev. A* **33**, 885.
- Bonsen, T. F. M., and D. Banks, 1971, *J. Phys. B* **4**, 706.
- Bonsen, T. F. M., and L. Vrems, 1970, *Physica* **47**, 307.
- Bordenave-Montesquieu, A., A. Gleizes, and P. Benoit-Cattin, 1982, *Phys. Rev. A* **25**, 245.
- Bordenave-Montesquieu, A., A. Gleizes, M. Rodiere, and P. Benoit-Cattin, 1973, *J. Phys. B* **6**, 1997.
- Bordoni, F., 1971, *Nucl. Instrum. Methods* **97**, 405.
- Botcher, C., 1982, *Phys. Rev. Lett.* **48**, 85.
- Brüche, E., 1927, *Ann. Phys. (Leipzig)* **83**, 1065.
- Cacik, R. K., and T. Jorgensen, Jr., 1970, *Phys. Rev. A* **2**, 1322.
- Cheng, W.-Q., M. E. Rudd, and Y.-Y. Hsu, 1989a, *Phys. Rev. A* **39**, 2359.
- Cheng, W.-Q., M. E. Rudd, and Y.-Y. Hsu, 1989b, *Phys. Rev. A* **40**, 3599.
- Clementi, I. M., 1964, *Proc. Phys. Soc. London* **84**, 89.
- Clementi, E., and D. L. Raimondi, 1963, *J. Chem. Phys.* **38**, 2686.
- Clementi, E., D. L. Raimondi, and W. P. Reinhardt, 1967, *J. Chem. Phys.* **47**, 1300.
- Cook, C. J., 1955, *Rev. Sci. Instrum.* **26**, 92.
- Crawell, T. L., L. H. Toburen, and M. E. Rudd, 1977, *Phys. Rev. A* **16**, 508.
- Crooks, J. B., and M. E. Rudd, 1970, *Phys. Rev. Lett.* **25**, 1599.
- Crooks, J. B., and M. E. Rudd, 1971, *Phys. Rev. A* **3**, 1628.
- Crothers, D. S. F., and J. F. McCann, 1983, *J. Phys. B* **16**, 3229.
- DuBois, R. D., 1985, *Phys. Rev. A* **32**, 3319.
- DuBois, R. D., 1986, *Phys. Rev. A* **34**, 2738.
- DuBois, R. D., and S. T. Manson, 1987, *Phys. Rev. A* **35**, 2007.
- Dunning, T. H., and P. J. Hay, 1977, in *Methods of Electronic Structure Theory*, edited by H. F. Shuster III (Plenum, New York), p. 1.
- Dyke, J. N., Jonathan, E. Lee, and A. Morris, 1976, *J. Chem. Soc. Faraday Trans. II* **72**, 1385.
- Faustein, P. D., V. H. Ponce, and R. D. Rivaola, 1988a, *J. Phys. B* **21**, 287.
- Faustein, P. D., V. H. Ponce, and R. D. Rivaola, 1988b, *J. Phys. B* **21**, 2989.
- Faustein, P. D., V. H. Ponce, and R. D. Rivaola, 1989a, *Phys. Rev. A* **40**, 2828.
- Faustein, P. D., V. H. Ponce, and R. D. Rivaola, 1989b, *J. Phys. B* **22**, L559.
- Faustein, P. D., V. H. Ponce, and R. D. Rivaola, 1991, *J. Phys. B* **24**, 3091.
- Fano, U., and J. W. Cooper, 1968, *Rev. Mod. Phys.* **40**, 441.
- Ford, A. L., J. F. Reading, and R. L. Becker, 1981, *Phys. Rev. A* **23**, 510.
- France, V., 1968, *Phys. Rev. Lett.* **20**, 709.
- Fritsch, W., and C. D. Lin, 1983, *Phys. Rev. A* **27**, 3361.
- Gabler, H., 1974, Ph.D. thesis, Free University, Berlin.
- Garibotti, C. R., and J. E. Miraglia, 1980, *Phys. Rev. A* **21**, 572.
- Gay, T. J., M. W. Gealy, and M. E. Rudd, 1990, *J. Phys. B* **23**, L823.
- Gerjuoy, E., 1966, *Phys. Rev.* **148**, 54.
- Gibson, D. K., and I. D. Reid, 1984, *J. Phys. E* **17**, 1227.
- Gibson, D. K., and I. D. Reid, 1985, *Australian Atomic Energy Commission Report AAEC/E608*.
- Gibson, D. K., and I. D. Reid, 1986, *J. Phys. B* **19**, 3265.
- Gibson, D. K., and I. D. Reid, 1987a, *Australian Atomic Energy Commission Report AAEC/E659*.
- Gibson, D. K., and I. D. Reid, 1987b, *Radiat. Res.* **112**, 418.
- Gibson, S. T., J. P. Greene, and J. Berkowitz, 1985, *J. Chem. Phys.* **83**, 4319.

- Glauber, R. J., 1959, in *Lectures in Theoretical Physics*, Vol. 1, edited by W. E. Brittin and L. G. Dunham (Interscience, New York), p. 315.
- Golden, D. E., and H. W. Bandel, 1965, *Phys. Rev.* **138**, 14A.
- Golden, D. E., H. W. Bandel, and J. A. Salerno, 1966, *Phys. Rev.* **166**, 40.
- Golden, J. E., and J. H. McGuire, 1974, *Phys. Rev. Lett.* **32**, 1218.
- Golden, J. E., and J. H. McGuire, 1977, *Phys. Rev. A* **15**, 499.
- Gryzinski, M., 1959, *Phys. Rev.* **115**, 374.
- Gryzinski, M., 1965a, *Phys. Rev.* **138**, 305A.
- Gryzinski, M., 1965b, *Phys. Rev.* **138**, 327A.
- Gryzinski, M., 1965c, *Phys. Rev.* **138**, 336A.
- Hamstein, J. M., and O. P. Morsebeck, 1972, *Phys. Rev. Lett.* **29**, 1361.
- Inokuti, M., 1971, *Rev. Mod. Phys.* **43**, 297.
- Inokuti, M., M. A. Dillon, J. H. Miller, and K. Omidvar, 1987, *J. Chem. Phys.* **87**, 6967.
- Irb, V. D., T. J. Gay, J. W. Edwards, E. B. Hale, M. L. McKenzie, and R. E. Olson, 1988, *Phys. Rev. A* **37**, 3612.
- Janer, R. K., and L. P. Presnyakov, 1980, *J. Phys. B* **13**, 4233.
- Kim, Y.-K., 1975a, *Radiat. Res.* **61**, 21.
- Kim, Y.-K., 1975b, *Radiat. Res.* **64**, 96.
- Kim, Y.-K., 1975c, *Radiat. Res.* **64**, 205.
- Kim, Y.-K., 1975d, *Int. J. Radiat. Phys. Chem.* **7**, 77.
- Kim, Y.-K., 1976, in *The Physics of Electronic and Atomic Collisions*, edited by J. R. Risky and R. Geballe (University of Washington, Seattle), p. 741.
- Kim, Y.-K., 1983, in *Physics of Ion-Ion and Electron-Ion Collisions*, edited by J. B. Broutin and J. W. McGowan (Plenum, New York), p. 101.
- Kim, Y.-K., and J. P. Desclaux, 1988, *Phys. Rev. A* **38**, 1805.
- Kim, Y.-K., and M. Inokuti, 1971, *Phys. Rev. A* **3**, 665.
- Kimura, M., and M. Inokuti, 1988, *Phys. Rev. A* **38**, 3801.
- Knudsen, M., 1910, *Ann. Phys. (Leipzig)* **31**, 205.
- Kuyatt, C. E., 1968, in *Methods of Experimental Physics*, Vol. 7, Part A, edited by Benjamin Bederson and Wade L. Fite (Academic, New York), p. 1.
- Kuyatt, C. E., and T. Jorgensen, Jr., 1963, *Phys. Rev.* **130**, 1444.
- Landau, L., and E. M. Lifshitz, 1965, *Quantum Mechanics. Non-Relativistic Theory*, 2nd ed. (Pergamon, London), p. 519.
- Lynch, D. J., L. H. Toburen, and W. E. Wilson, 1976, *J. Chem. Phys.* **64**, 2616.
- Mack, J., 1970, *Phys. Rev. A* **1**, 235.
- Manson, S. T., and L. H. Toburen, 1977, in *Tenth International Conference on the Physics of Electronic and Atomic Collisions*, Abstracts Commission à l'Energie Atomique, Paris, p. 990.
- Manson, S. T., L. H. Toburen, D. H. Madison, and N. Stolterfoht, 1975, *Phys. Rev. A* **12**, 60.
- Mashova, E. S., and V. A. Molchanov, 1985, *Medium-Energy Ion Reflection from Solids* (North-Holland, Amsterdam).
- McGuire, J. H., 1982, *Phys. Rev. A* **26**, 143.
- McGuire, J. H., and L. Weaver, 1977, *Phys. Rev. A* **16**, 41.
- Miller, J. H., W. E. Wilson, S. T. Manson, and M. E. Rudd, 1987, *J. Chem. Phys.* **86**, 157.
- Miller, W. F., and R. L. Platzman, 1957, *Proc. Phys. Soc. London, Ser. A* **70**, 299.
- Moore, J. H., C. C. Davis, and M. A. Coplan, 1983, *Building Scientific Apparatus* (Addison-Wesley, London).
- Mott, N. F., and H. S. W. Massey, 1965, *The Theory of Atomic Collisions* (Oxford University, New York/London), Chap. III.
- Mutoyama, T., C. D. Lin, and W. Fritsch, 1985, *Phys. Rev. A* **32**, 2490.
- Normand, C. E., 1930, *Phys. Rev.* **35**, 1217.
- Olson, R. E., 1983, *Phys. Rev. A* **27**, 1871.
- Olson, R. E., and T. J. Gay, 1988, *Phys. Rev. Lett.* **61**, 302.
- Olson, R. E., T. J. Gay, R. G. Berry, E. B. Hale, and V. D. Irb, 1987, *Phys. Rev. Lett.* **59**, 36.
- Olson, R. E., and A. Salop, 1977, *Phys. Rev. A* **16**, 531.
- Opal, C. B., C. E. Beatty, and W. K. Peterson, 1972, *At. Data* **4**, 209.
- Palmer, D. W., M. W. Thompson, and P. D. Townsend, 1970, Eds., *Atomic Collision Phenomena in Solids* (North Holland/American Elsevier, Amsterdam/New York).
- Parke, J. T., 1983, *Adv. At. Mol. Phys.* **19**, 67.
- Parke, J. T., J. E. Aldag, J. M. George, and J. L. Peacher, 1976, *Phys. Rev. A* **14**, 608.
- Parke, J. T., J. E. Aldag, J. M. George, J. L. Peacher, and J. H. McGuire, 1977, *Phys. Rev. A* **15**, 502.
- Parke, J. T., J. M. George, J. L. Peacher, and J. E. Aldag, 1978, *Phys. Rev. A* **18**, 48.
- Parke, J. T., E. Redd, T. J. Kvale, and E. Rille, 1983, *Rev. Sci. Instrum.* **54**, 1247.
- Parke, J. T., and F. D. Schwengerdt, 1969a, *Rev. Sci. Instrum.* **40**, 753.
- Parke, J. T., and F. D. Schwengerdt, 1969b, *Phys. Rev.* **185**, 152.
- Paul, H., and W. Obermann, 1983, *Nucl. Instrum. Methods* **216**, 15.
- Potts, A. W., H. J. Lempha, D. G. Streets, and W. C. Price, 1970, *Philos. Trans. R. Soc. London, Ser. A* **268**, 59.
- Reading, J. F., and A. L. Ford, 1979, *J. Phys. B* **12**, 1367.
- Reading, J. F., and A. L. Ford, 1987, *J. Phys. B* **20**, 3747.
- Reading, J. F., A. L. Ford, and R. L. Becker, 1981, *J. Phys. B* **14**, 1995.
- Reading, J. F., A. L. Ford, G. L. Snafield, and A. Fritchard, 1979, *Phys. Rev. A* **20**, 130.
- Reinhold, C. O., and C. A. Falcon, 1986, *Phys. Rev. A* **33**, 3859.
- Reinhold, C. O., C. A. Falcon, and J. E. Miraglia, 1987, *J. Phys. B* **20**, 3737.
- Reinhold, C. O., and R. E. Olson, 1989, *Phys. Rev. A* **39**, 3861.
- Redbro, M., and F. D. Andersen, 1979, *J. Phys. B* **12**, 2883.
- Rudd, M. E., 1972, in *Low Energy Electron Spectrometry* by Kenneth D. Sevier (Wiley-Interscience, New York), p. 17.
- Rudd, M. E., 1977, data listed in Criswell et al., 1977, and Rudd et al., 1979.
- Rudd, M. E., 1979, *Phys. Rev. A* **20**, 787.
- Rudd, M. E., 1987, *Radiat. Res.* **109**, 1.
- Rudd, M. E., 1988, *Phys. Rev. A* **38**, 6129.
- Rudd, M. E., D. Gregoire, and J. B. Crooks, 1971, *Phys. Rev. A* **3**, 1635.
- Rudd, M. E., and T. Jorgensen, Jr., 1963, *Phys. Rev.* **131**, 666.
- Rudd, M. E., Y.-K. Kim, D. H. Madison, and J. W. Gallagher, 1985, *Rev. Mod. Phys.* **57**, 965.
- Rudd, M. E., and D. H. Madison, 1976, *Phys. Rev. A* **14**, 128.
- Rudd, M. E., C. A. Sauter, and C. L. Bailey, 1966, *Phys. Rev. A* **1**, 20.
- Rudd, M. E., L. H. Toburen, and N. Stolterfoht, 1976, *At. Data Nucl. Data Tables* **18**, 413.
- Rudd, M. E., L. H. Toburen, and N. Stolterfoht, 1979, *At. Data Nucl. Data Tables* **23**, 405.
- Rutherford, E., 1911, *Philos. Mag.* **21**, 669.
- Ryufuku, H., 1982, *Phys. Rev. A* **25**, 720.
- Sanson, J. A. R., and J. L. Gardner, 1973, *J. Geophys. Res.* **78**, 3663.
- Sanson, J. A. R., T. Masuoka, P. N. Paré, and G. C. Angel

- 1987, *J. Chem. Phys.* **86**, 6128.
- Sasaki, M., J. Uehara, and N. Oda, 1979, *J. Phys.* **B 12**, L729.
- Schäfer, J., R. Latz, M. Burkhardt, H. J. Frischhorn, D. Hofmann, P. Kocchar, K. O. Groeneveld, D. Berenyi, A. Követ, and Gy. Szabo, 1986, *Il Nuovo Cimento* **7**, 219, and references therein.
- Schram, B. L., A. J. H. Boerboom, W. Kleene, and J. Kistemaker, 1965, *Physica* **32**, 749.
- Schultz, D. R., 1989, *Phys. Rev. A* **40**, 2130.
- Schultz, D. R., and C. O. Renhold, 1989, private communication.
- Shakelhaft, R., 1978, *Phys. Rev. A* **18**, 1930.
- Slater, J. C., 1930, *Phys. Rev.* **36**, 57.
- Sorensen, W. J., H. Basch, and M. Krauss, 1984, *J. Chem. Phys.* **81**, 6026.
- Stoerferfoht, N., 1971a, *Z. Phys.* **248**, 81.
- Stoerferfoht, N., 1971b, *Z. Phys.* **248**, 92.
- Stoerferfoht, N., 1975, data listed in Manson *et al.*, 1975.
- Stoerferfoht, N., H. Gabler, and U. Leithäuser, 1976, 1979, data listed in Rudd *et al.*, 1979.
- Thomas, E. W., 1985, *Atomic Data for Controlled Fusion Research Vol. III: Particle Interaction with Surfaces*, Oak Ridge National Laboratory Report No. ORNL-6088/V3.
- Thomas, L. H., 1927, *Proc. Cambridge Philos. Soc.* **23**, 713.
- Thomson, J. J., 1912, *Philos. Mag.* **23**, 449.
- Toburen, L. H., 1971, *Phys. Rev. A* **3**, 216.
- Toburen, L. H., 1974, *Phys. Rev. A* **9**, 2505.
- Toburen, L. H., 1980, private communication.
- Toburen, L. H., S. T. Manson, and Y.-K. Kim, 1978, *Phys. Rev. A* **17**, 148.
- Toburen, L. H., and W. E. Wilson, 1972, *Phys. Rev. A* **5**, 247.
- Toburen, L. H., and W. E. Wilson, 1975, *Rev. Sci. Instrum.* **46**, 851.
- Toburen, L. H., and W. E. Wilson, 1977, *J. Chem. Phys.* **66**, 5202.
- Toburen, L. H., W. E. Wilson, and L. E. Porter, 1977, *J. Chem. Phys.* **67**, 4212.
- Tokuro, N., and N. Oda, 1985, *J. Phys.* **B 18**, 1771.
- Yonva, V. I., and F. I. Vilesov, 1974, *Opt. Spectrosc.* **36**, 436.
- Vriens, L., 1967, *Proc. Phys. Soc. London* **90**, 935.
- Vriens, L., 1969, in *Case Studies in Atomic Physics*, Vol. 1, edited by E. W. McDowell and M. R. C. McDowell (North-Holland, Amsterdam), p. 335.
- Vroom, D. A., R. L. Palmer, and J. Wm. McGowan, 1977, *J. Chem. Phys.* **66**, 647.
- Williams, E. J., 1972, *Nature* **239**, 489.
- Wilson, W. E., 1972, *Radiat. Res.* **49**, 36.
- Wilson, W. E., and L. H. Toburen, 1975, *Phys. Rev. A* **11**, 1303.
- Wilson, W. E., J. H. Miller, L. H. Toburen, and S. T. Manson, 1984, *J. Chem. Phys.* **80**, 5631.
- Winter, T. G., and C. D. Lin, 1984, *Phys. Rev. A* **29**, 3071.

APPENDIX E

A HIGH - VOLTAGE VARIABLE RESISTOR FOR CHARGE - TRANSFER PROJECTILE - ION ENERGY SPECTROSCOPY

T.J. Gay, V.D. Irby*, and S. P. Yallaly†
Physics Department and Laboratory for
Atomic and Molecular Research

University of Missouri-Rolla, Rolla, Missouri 65401 U.S.A.

ABSTRACT

We have designed, built, and implemented a high-voltage variable resistor to modify an ion-energy spectrometer for the study of ion-atom collisions in which the projectiles change charge. The resistor is remotely switchable from 0 to 2050 MΩ and has a voltage rating of 200 kV. Our design criteria and the electrical and mechanical details of the apparatus are discussed. The design and construction of an ancillary device, comprising two precision resistive-divider voltmeters, are also discussed.

PACS #’s - 06.90.+v, 07.50.+f

I. INTRODUCTION

Projectile-ion (or "translational") energy spectroscopy is a useful method for the study of ion-atom collisions.¹⁻⁷ If state-specific information about the collision products is required, its use is unavoidable when characteristic photons are not emitted by the collision partners or if such emission is not easily induced by techniques such as electric-field quenching.⁸ In the case of the collision

for example, production cross sections for the He(2¹S) state can be measured only by ion energy-loss spectroscopy.⁹ Even if photons are emitted by the final state of interest, allowing cross sections to be determined using fluorescence detection¹⁰, the energy-spectroscopic method has several advantages. Because the projectile is energy-analyzed and detected directly, the need for cascading corrections due to population of higher-lying states is eliminated. When inelastic processes without charge transfer (as in the reaction above) are studied, the cross section is given by

$$\sigma = I'/Inf, \quad (2)$$

where I' is the detected intensity of scattered projectiles which have suffered an energy loss associated with the excited

ate in question, I is the detected incident projectile density, and n and I are the target's volume number density and length, respectively. Since I' and I can be measured with the same detector at a set particle energy¹, the dependence on the detector efficiency, ϵ , of I' and I cancel in (2), eliminating the need for accurate knowledge of this quantity. For charge-transfer collisions, in which the incident and final charge states of the projectile (q and q') are not equal, the detector efficiency no longer cancels in (2). However, the relative values of cross sections for discrete states with a given final q' will be independent of detector efficiency. In the collision

where n and ℓ in this context are quantum numbers of the He^+ , fluorescence measurements of $\sigma(n\ell)$ depend individually on the photon detection efficiency at the various wavelengths associated with $n\ell$ sublevels, as well as on the detection efficiency for the incident beam. Only an overall detection efficiency factor $\epsilon(q')/\epsilon(q)$ is needed for absolute measurements with ion-energy spectroscopy. This factor can approach unity at high projectile energies.¹¹

An apparatus for the study of intermediate (20-200 keV) energy ion-atom collisions by projectile-ion energy spectroscopy, developed between 1963 and 1978 in our lab, is shown in figure 1.1,12-14 An electrical schematic of this apparatus is

shown in figure 2. Positive ion beams with a nominal energy spread of 1 eV are produced at high potential in the accelerator terminal. The ions are accelerated to the requisite collision energy, and are steered and focused into the target chamber, which is at ground potential. Ions emerging from the target chamber are mass analyzed and decelerated, prior to electrostatic energy analysis and detection in the decelerator high-voltage terminal.

Ion-energy spectra are obtained by monitoring the ion detector signal as a function of the output voltage of a " ΔV " power supply (housed in the decelerator terminal) which, in conjunction with the main high-voltage (HV) and " V_0 " power supplies, determines the potential of the ion source relative to ground. The electrostatic energy analyzer in the decelerator terminal will pass only ions of a given energy E_0 . Ion energies immediately following a collision with the target are $q(V_0 + \text{HV} + \Delta V) - \Delta E$, where V_0 is the extraction voltage of the ion source, HV is the voltage output of the main high-voltage power supply, ΔV is the output of the ΔV supply, and ΔE is the energy lost in the collision. In order for an ion to be detected, its energy at ground (target) potential must equal $q(\text{HV}) + E_0$. Thus by setting $E_0 = qV_0$, and $\Delta V = \Delta E/q$, only ions which have lost an energy ΔE are detected, with an efficiency independent of ΔE , because all ions passed by the electrostatic analyzer strike the detector with energy E_0 . An example of an energy-loss spectrum for reaction (1) is shown in figure 3.

One of the major goals in building this apparatus was the study of collisions between protons and atomic hydrogen in the intermediate energy range, where the incident projectile and atomic electron have comparable speeds. This energy regime is important from the theoretical standpoint, because neither Born nor molecular-orbital close-coupling approximations are generally valid in analyzing the collisions^{1,15}. It is also a range of particular interest for the atomic physics of fusion reactors, specifically with regard to issues relating to diagnostic techniques, plasma burning, and neutral-beam heating¹⁶⁻²¹.

Concerns about the high pumping speed and electrical current requirements of an atomic hydrogen furnace target and the large size and current requirements of an analyzing magnet for 200 keV protons led to an early design decision to place the ion source and analyzer/detector (as opposed to the target chamber) at high voltage. In this configuration, the use of a common main high-voltage power supply for both the accelerator and decelerator terminals is required; in order to achieve the desired overall instrumental energy resolution of ~1eV required for high-quality energy spectra, the stability, including both regulation and ripple, of two independent accelerator and decelerator high voltage supplies would have to be better than 0.001% at 100 keV, an impractically low figure at such voltages. Thus the electrical configuration shown in figure 2 was adopted for the apparatus.

The use of a common high-voltage main power supply has one serious drawback: collisions with $q^+ q^-$ cannot be studied. A

desire to study collisions of type (3) prompted us to consider ways to modify our apparatus to allow energy spectra to be acquired for charge-changing collisions. Energy spectra for low-energy charge-changing collisions can be obtained by using separate power supplies to accelerate and decelerate the projectile ions by different voltages (see, e.g., refs. 2 and 3). Unfortunately, this method will not work for the voltage range in which we are interested because of the power supply stability problems just mentioned. Thus an alternate solution was developed.

An electrical schematic of our modified apparatus is shown in figure 4. Essentially, we have inserted a high-voltage variable resistor between the decelerator and accelerator terminals, which can be used to lower the ion source potential to a given fraction of that of the ion energy analyzer. Because the accelerator and decelerator terminals will now generally be at significantly different potentials, two separate resistive divider networks are needed to measure their respective voltages, and a second isolation transformer is also required to provide power to the various components at high-voltage.

An advantage of this approach is that the insensitivity of the apparatus to power supply fluctuations is preserved. Consider, as an example, an experiment involving collision (3). For the energy gain of the He^{++} in the accelerator section to be comparable to the He^+ energy loss in the decelerator, the accelerator terminal voltage must be held at half that of the decelerator terminal. This is accomplished by adjusting the

collisions can be studied.

II. APPARATUS

A. Design Considerations

In designing a variable resistor for our apparatus, the primary consideration was the range of q/q' we wished to investigate. While our first experimental goal was to study single-electron capture by He^{++} [i.e. reaction (3)] in which $q/q' = 2$, we decided to build a device with a maximum resistance that would allow studies of collisions in which $q/q' = 3$, such as $\text{Li}^{3+} + \text{X} \rightarrow \text{Li}^{+} + \text{X}^{2+}$ or $\text{C}^{6+} + \text{X} \rightarrow \text{C}^{2+} + \text{X}^{4+}$. Thus the variable resistor must have a maximum resistance equal to at least twice that of the total resistance between the accelerator terminal and ground. This resistance, R_A , consists of a parallel combination of the accelerator column resistor string and three other resistor strings to ground, located in the two mechanical supports of the accelerator terminal and along the power cable leading to the isolation transformer (figure 2). (One of the former strings had been used as a voltage divider to monitor acceleration potential). The value of R_A was determined by measuring the current drawn from the HV power supply at a number of voltages, and was found, assuming that the resistance was ohmic, to be $800 \pm 10 \text{ M}\Omega$. We thus designed the variable resistor assembly (VRA) to have a maximum $2G\Omega$ impedance.

Voltage (and hence beam energy) stability was a second

variable resistor to a value equal to that between the accelerator terminal and ground. Since $q = 2e$ and $q' = e$, the energy immediately after the target is equal to $2e[V_0 + 1/2(V + \delta + \Delta V)] - \Delta E$, where δ is a general, time dependent variation in the HV supply output. The energy lost under deceleration is $e(HV + \delta)$. Thus the He^+ energy immediately exceeding the electrostatic energy analyzer is $V_0 + e\Delta V - \Delta E$ (which must equal the analyzer pass energy E_0 or the ions to be detected), independent of any main power supply voltage fluctuations.

Such a solution is not without disadvantages. Apart from the electrical and mechanical design and construction of a high-voltage, high-precision variable resistor, the potential difficulties associated with this scheme are apparent, especially when one considers that several new possible sources of voltage fluctuation have been added to the apparatus. For example, the variable resistor and the resistors between the accelerator terminal and ground will have different temperature coefficients of resistance. Thus thermal gradients in the laboratory can, in principle, cause uncompensated beam-energy fluctuations. Projectile beam-current fluctuations will now result in changes in the accelerator potential, as will any corona leakage in the variable resistor or voltage divider networks. Successful implementation of a variable resistor circuit requires the resolution of these and other problems. In this report, we describe the apparatus we have used successfully to modify our ion-energy spectrometer so that charge-changing ion-atom

crucial design criterion. Three potential sources of voltage fluctuations are introduced when a variable resistor and its attendant components are added to the electrical circuit. First, intermittent corona leakage from any of the new components could cause the accelerator potential, V_A , to vary. The sensitivity of V_A to corona loss in the VRA, for example, depends on R_A , the VRA resistance R_{VRA} , and the point (or points) in the VRA where the loss occurs. In a worst case R_{VRA}/R_A would equal two. Assuming that the HV power supply is not current limited, and that losses occur at the low-voltage end of the VRA, a 2nA corona current would cause V_A to change by a volt. In this case, 2nA is less than 0.01% of the bias current through the resistors when HV = 200 kV.

Consequently, every effort was made to minimize or eliminate corona currents emitted from the electrical circuitry. To this end, the geometric configuration of the apparatus was dictated primarily by considerations relating to the minimization of electric field throughout the design. Our HV power supply and accelerator and decelerator terminal configurations limit us to a maximum high voltage of 200 kV. We also assumed that electrical components at high voltage would be submerged in dielectric oil (Shell DIALA-AX) with a minimum dielectric breakdown strength of about 140kV/cm. To minimize the possibility of corona currents, we set a design limit of 30 kV/cm as a maximum allowable electric field. While this value was somewhat arbitrary, its choice was guided in part by a tendency for field-aided emission from electrodes to begin at about

one-fifth of the breakdown field²², and in part by our observation that this seemed to be a much more conservative value than that employed in the design of many pieces of oil-immersed high-voltage apparatus with which we were familiar. It should also be noted that more conservative ratings would have begun to require prohibitively large dimensions for the VRA and its associated components.

A second, related source of fluctuation in V_A is variation in ion-beam current from the source. When V_A is maintained directly by high-voltage power supplies, as in the configuration shown in figure 2, this is not a problem. In a divider configuration, however, changes of I_A in beam current can cause V_A to vary by large fractions of a volt. Unfortunately, such effects are unavoidable, and care must simply be taken to keep beam current fluctuations as small as possible.

Finally, variation in V_A can result from time-dependent temperatures and/or temperature gradients in the lab. Since

$$V_A = (HV) \left[\frac{R_A}{(R_A + R_{VRA})} \right], \quad (4)$$

any change in the relative values of R_A and R_{VRA} due to temperature-dependent resistance variations, after R_{VRA} has been initially set, will cause drifts in V_A . To minimize these, the composite temperature coefficients of resistance of R_A and R_{VRA} should be as close as possible. Alternatively, the VRA could be temperature-stabilized relative to the accelerator resistors, or

adjusted on a continuous basis to compensate for temperature variations.

A last significant design concern was the possible effect of voltage coefficients of resistance on comparative measurements of accelerator and decelerator terminal potentials. We decided to construct two new matched precision voltage divider (PVD) strings to measure V_A and the decelerator potential, HV. The voltage readout from these would be used to set R_{VRA} for a given experiment. As we shall discuss in Section III.A., a standard cross section measurement first involves the transmission through the entire spectrometer of a beam of "final state" ions [He^+ in the case of reaction (3)] with the accelerator and decelerator terminals at the same potential ($R_{VRA} = 0$). Following this, R_{VRA} is increased until $R_A/(R_{VRA} + R_A) \approx q'/q$, as determined from the PVD readouts. When the voltage across the accelerator divider string decreases, the resistance ratio of the main voltage dropping resistor (R) to the resistor across which the readout voltmeter is placed (R_V) will change if the voltage coefficients of resistance differ for the two resistances or, if they are equal, when the individual component resistors making up R have different voltage drops across them (i.e. have different resistances) than does R_V .

This problem can be illustrated by considering worst-case experiments where $q/q' = 3$. It is desirable for $(R + R_V)$ to be comparable to or larger than R_A to minimize current (and the attendant ripple, proportional to current) drawn from the HV power supply, as well as power dissipation in the PVD strings.

Conversely, R_V and hence R , should not be so high that the input impedance of the voltmeter affects the PVD readout. (This latter problem cannot be solved by the use of small values of R_V without running the risk of reducing the readout voltage to unacceptably low levels.) Consider $R = 10G\Omega$, made up from ten $1G\Omega$ resistors in series, and $R_V = 1M\Omega$ using a single resistor. If we assume that individual resistors have the same voltage coefficients of resistance, C_V , equal to $-1ppm/V$, and that R and R_V are the resistance values with 200 kV across the PVD string, corresponding to approximately 20,000 V and 20 V across the $1G\Omega$ and $1M\Omega$ resistors respectively, then when $V_A = 66.7$ kV the ratio of R_V to $R = 0.98 \times 10^{-4}$, as opposed to 1.00×10^{-4} . This corresponds to a PVD reading error for V_A of ~ 1300 V. Since it is impractical to search for a (possibly very small) charge-transfer peak in an ion-energy spectrum by varying ΔV over a range greater than a few hundred volts, a reading error this large, which would result in a correspondingly inaccurate setting of V_A , is unacceptable. In reality, C_V 's generally increase monotonically with resistance value, which exacerbates this problem.

The problem of voltage coefficients of resistance are minimized first, obviously, by picking resistors with low values of C_V . Additionally, it is advantageous to have as many individual resistors as possible make up the composite resistance R , because this minimizes the voltage drop across a given resistor. Our design goal was to achieve PVD accuracies at all voltages of one part in 10^3 , which is somewhat better than

the specified accuracies of commercial devices³, but

significantly poorer than those claimed by some authors in the literature.^{24,25} An accuracy of 0.1% would guarantee that ΔV would not have to be varied by more than 100 volts to detect quanta once RyRA had been set. (In principle, RyRA could also be varied to search for charge-transfer peaks, but this would be more difficult; see sections II.B. and III.A.)

Finally, it is important to remember that the considerations discussed earlier regarding corona currents and temperature coefficients of resistance apply, at least partially, to the design of the PVD apparatus as well as that of the VRA.

B. Electrical and Mechanical Design

The modifications to our ion-energy spectrometer, shown schematically in figure 4, consist essentially of the addition to the original apparatus of a variable resistor assembly (VRA), two precision voltage divider networks housed together in one high-voltage tank (PVD), and a second isolation transformer. In this section, we discuss in detail the electrical and mechanical construction of the VRA and PVD, the ancillary electrical equipment needed for the modification, and several aspects of the installation of this apparatus.

1. Variable Resistor Assembly (VRA)

The VRA is adjustable from a shorted position, with zero resistance, to a maximum value of about 2050 Ω . It comprises three sub-assemblies, each with variable resistance: 1) A "coarse-adjustment stack", consisting of 100 20M Ω resistors in series, which are in turn divided into two sets of 50 resistors each. These individual sets are mounted in a zig-zag fashion around the periphery of each of two plexiglass cylinders 81.3 cm in diameter (figure 5). 2) An "intermediate adjustment stack" consisting of 24 2M Ω resistors, mounted similarly to those of the coarse stack around a 39.4 cm diameter plexiglass cylinder.

3) A "fine adjustment" resistor, which is a 40-turn 2.5M Ω potentiometer. All three subassemblies are housed in a plexiglass support structure, which is suspended from the lid of a mild steel oil tank 104 cm in diameter and 145 cm high. The tank, manufactured by the Nooter Corporation, holds about 300 gallons of Shell DIALA-AX dielectric insulating oil with the VRA components in place.

The three resistor sub-assemblies are connected in series between the accelerator and decelerator terminals, as shown in figures 4 and 6. The series resistance of the coarse and intermediate stacks is varied by sliding spring-loaded polished steel make-before-break wipers over corona caps at the junctions of the individual resistors in the stacks (figure 7). These corona caps are arranged in a circular pattern. The wipers are mounted in radial plexiglass arms connected to vertical shafts

which pass through the centers of the resistor stacks. The wipers can thus be moved by rotating the shafts, which emerge through the oil tank lid. A similar shaft is attached directly to the fine-adjustment resistor.

The quasi-cylindrical geometry of the VRA was considered the best design both for mechanical wiper motion and reduction of electrical fields. A number of alternatives including linear and helical arrangements of the resistors were considered before the present configuration was adopted. The dimensions, placement, and wiring of the resistor stacks were carefully analyzed to minimize electric fields using, as discussed above, 10 kV/cm as a maximum acceptable value. The resistor stack diameters, for example, represent a compromise between the reduction of fields between individual corona caps, and fields between stacks and/or the grounded oil tanks.

The highest fields in the tank occur near the corona cap terminating the high voltage ends of the two coarse adjustment stacks. Approximating the caps as spheres 1.9 cm in diameter, the field at the surface of an isolated cap at 200 kV is 10 kV/cm, or about a factor of seven too large for our design limit. By placing the caps in the stack along a circle segment, the maximum field is reduced dramatically, although if the angle subtended by the arc segment becomes too large, then fields along the circle's tangent between the corona caps at the high and low-voltage ends of the string increase prohibitively. Another large reduction in the fields near the high-voltage corona cap is achieved by placing "dummy" corona caps on the circle between

the stack's high and low voltage ends. These are maintained at incremental, intermediate voltages by connecting them to corresponding resistor junctions across the diameter of the circle. This basic arrangement is illustrated in figure 8.

(Figure 8 actually shows a resistive stack in the PVD; see section III.B.2 below. The equipotential contours in figure 8 were calculated by solving Laplace's equation in two dimensions for the potential distributions indicated.)

The electrical connections as shown in figure 6 also serve to minimize electric fields, because equipotential points on the two strings are vertically above each other in the tank. Moreover, resistors and caps not in series in the circuit "float-up" to approximately V_A , which further decreases voltage differences across the stack's horizontal dimensions. Finally, the intermediate and fine-control resistors are placed near the low-voltage end of the coarse stack.

Given the VRA configuration shown in figures 5 and 6, our best estimate of the maximum electric field in the VRA with HV = 200 kV and no oil in the tank is ~24 kV/cm. This field, which is a factor of 5.9 below the breakdown field for DIALA-AX oil, is at the surface of the 200 kV corona cap at the bottom of the coarse stack and points toward the bottom corner of the oil tank.

Our design decisions were based on approximate, analytical calculations of electric-field strengths using standard geometries (cylinder-cylinder, cylinder-plane, sphere-plane)²⁶ coupled with a significant amount of guesswork. In retrospect, a better approach might have been to make a series of

two-dimensional relaxation calculations solving Laplace's equation in the tank for various resistor geometries and planar sections. An optimum configuration could then have been obtained by trial and error. Having noted this, it is probably true that our design is close to the best possible solution; the few relaxation calculations we did confirmed our approximate analytic estimates of various fields in the tank.

The dielectric strength of insulating oil can be severely compromised by particulate and chemical contaminants^{22,27}. We took a number of precautions to reduce such contamination to a minimum. The oil tank, which was shipped still containing copious amounts of welding leak-detection fluid, was cleaned first with perchlorethylene and rinsed with methanol. All plastic components were cleaned with soap and water followed by a methanol rinse. Latex gloves were worn during all assembly procedures, especially when the high-voltage resistors were being handled. Dust is prevented from easily entering the tank with a combination of foam-rubber seals and tightly constricted or covered openings.

The inevitable arcing which occurs between the sliding contact and the resistor chain when Ryra is changed in discrete steps will act to breakdown the oil into components with lower dielectric strength, and will cause bubble formation which also reduces the minimum breakdown field. Thus arcing must be kept to an absolute minimum. For this reason, the sliding wiper was made long enough that it can touch two adjacent corona caps simultaneously ("make-before-break"), and the number of resistors

in the coarse stack was chosen to be as large as possible, consistent with the requirement of minimizing electric fields between the caps.

The discrete resistors used for the coarse and intermediate stacks are of the metal-oxide film type specifically designed for oil bath operation (Dale model ROX-6). Units with maximum power and voltage ratings (10W and 45kV, respectively) were chosen in order to minimize their voltage coefficients and temperature increase under load.²⁸ (The maximum steady state power dissipation in the 20 MΩ resistors is 0.18W.) The temperature coefficients of resistance for all resistors are less than 50 ppm/°C, and are typically about 20 ppm/°C (these values were measured for individual resistors by the manufacturer). Because these values did not match those of the carbon-film resistors already in place on the accelerator, which had estimated values of ~500 ppm/°C, we considered the options of temperature stabilization of the VRA oil, and active control of the fine and intermediate resistors to compensate for temperature drifts. The former possibility was not pursued because of concerns about convective stirring of particulate contaminants which would otherwise settle to the bottom of the oil tank, and which could reduce the oil's dielectric strength. The second option was developed but did not need to be implemented (see sections II.B.2 and III.A).

Fine resistance adjustment is provided by a Beckman Halipot Series E 2.5 MΩ 40-turn wirewound potentiometer rated at 20 W and 1000 V. Although this unit was not certified by Beckman

to be oil-compatible, we found it to be so. Two 6 mm holes were drilled in the top and bottom of the phenolic case to permit free circulation of oil over the windings. The potentiometer's coefficient of resistance is comparable to those of the fixed resistors (~ 20 ppm/ $^{\circ}$ C).

All structural components in the oil tank are made of plexiglass, with the exception of a few PVC nuts. (Nylon components were not used because of their tendency to absorb water.) Plexiglass has a somewhat higher dielectric strength (~ 160 kV/cm) than does DIALA-AX. The two coarse stacks as a single unit and the intermediate stack are each supported independently from the lid by three solid plexiglass rods 5.1 cm and 2.5 cm in diameter, respectively (figure 5). Two 1.3 cm diameter rods supported the fine adjustment potentiometer. The resistance of each subsection is adjusted by rotation of rods which emerge from the lids and are coupled to stepping motors. The coarse stack uses a 60:1 right-angle gear reducer between the 5.1 cm diameter shaft and motor (Superior Electric (SE) Co. M112-FJ12; 0.61 Nm torque) to increase the torque available to turn the wiper arms. The intermediate stack uses a smaller motor (SE M091-FD06; 0.08 Nm torque applied to a 2.5 cm diameter shaft) and a 40:1 reducer. Another M901 turns the potentiometer 1.3 cm diameter shaft directly.

In initial mechanical tests of the VRA, carried out with the oil tank empty, severe binding of the intermediate and coarse wiper arms and shafts occurred, caused mainly by the friction between the sliding wipers and the corona caps. While

this problem was ameliorated to some extent by the "brute-force" measure of using gear reducers, the greatest improvement resulted from stiffening the entire plexiglass structure, especially at the points where the wiper arms attached to the rotating rods. Binding was finally eliminated entirely by application of a thin layer of DIALA-AX oil to the wipers and corona caps.

The high-voltage cables leading into and out of the VRA are rated at 300 kVDC and have a semiconductor core shield for corona suppression (Dielectric Sciences #2077). They have a 3.8 cm O.D. and are mechanically restrained by aluminum clamps mounted on the lid.

2. Precision Voltage Divider (PVD)

The PVD and VRA are similar in many respects. Both accelerator and decelerator PVD strings are housed in an oil tank 102 cm high and 79 cm in diameter. A common oil bath is used to minimize temperature-related voltage measurement errors. Each string has 50-200 M Ω and 6-2M Ω metal-oxide film resistors (Dale ROX-6). The 200 M Ω resistors are in series and the 2 M Ω resistors are connected in parallel to form three 1 M Ω composite resistors in each string (figure 9). The choice of the number and values of these resistors represents a compromise between a number of competing requirements mentioned earlier. For a given total string resistance, the number of individual resistors should be as large as possible; this minimizes their

individual voltage-coefficients and the voltage drop across each one, thereby reducing voltage coefficient readout errors in two ways. Power dissipation across each resistor is concomitantly reduced. The primary factor tending to limit the number of resistors is the maximum field limitation, e.g. between corona caps. Finally, the total string resistance should be large enough that it does not significantly reduce the resistances of the accelerator or decelerator to ground, but should not be so large that resistance across which the voltage readout is made is comparable to the input impedance of the sensing voltmeter.

Each resistor string is mounted around the periphery of a 40.6 cm diameter plexiglass "stack", in much the same fashion as the discrete resistors in the VRA. The stacks are supported from the tank lid by three 5.1 cm diameter solid plexiglass rods. In order to reduce electric fields, corona caps at intermediate voltages are placed on the circle segment between the high and low voltage ends of the strings (figure 8). We estimate that the maximum field in the PVD tank with no oil at 200 kV is 30 kV/cm. This value is somewhat higher than the corresponding maximum in the VRA because the PVD tank is smaller than that of the VRA, and the voltage drop across a given stack is a full 200 kV in the PVD, instead of 133 kV.

The 1 MΩ composite resistors at the low-voltage ends of the strings are connected in a way that allows PVD readings to be taken in one of two modes (figure 9). In the standard read-out mode, two Fluke 8840A 5-1/2 digit voltmeters are connected across each of the bottom 1 MΩ resistors (connections 1, 2, 13,

and 14). A multirange precision potentiometer can be inserted in either the accelerator or decelerator strings. When the VRA is shorted, the potentiometer is adjusted to make the two Fluke readings the same. The two output voltages are then used to set the VRA with 1 volt (1 digit) precision. The PVD resistances were chosen such that the 20 V scale could be used on the Flukes, giving these devices an input impedance $>10^{10} \Omega$ with correspondingly negligible loading error on the PVD readout. A second possible readout method, which we have not used to date, would involve measurement of current through a shunt connecting the two divider strings. In a $q/q' = 3$ experiment, for example, an ammeter would be placed between connections 1/2 and 8/9 (figure 9), and the VRA would be set in correspondence with a null reading of the meter. As can be seen from figure 4, this null reading would be unaffected by changes in ΔV . The output from the ammeter could also be used as feedback to a stepper-motor driver which controlled the VRA. In such a manner, temperature drifting between R_A and R_{VRA} could be compensated. This latter readout technique has the advantage that errors due to finite input impedance of a readout voltmeter are eliminated.

The high-voltage connections from the accelerator and decelerator were made to the PVD stacks in the same manner as the VRA, using 300 kV cable. External connections to the low-voltage node points (1-14 in figure 9) were made using 40 kV cable (Belden 8866) connected to SHV bulkhead connectors mounted on the PVD lid. Care was taken to keep these latter cables in regions of the tank at relatively low potential.

C. Installation

Modification of the ion-energy spectrometer occurred in three steps. First, the AC power line to the decelerator was disconnected and a new power line was run from the second isolation transformer (Del 3CTR250-21; 3kVA at 250 kV) to the decelerator. As shipped, the isolation transformer had a two-leg, two-cable high-voltage power line emerging from its oil tank. We replaced this line with a single, coaxial 250 kV power line (Chester Cable Corp. #1965, which is no longer manufactured) to avoid any 60 Hz magnetic fields which would result from a two-wire arrangement.

The VRA and PVD were then attached to the system, as indicated in figure 4, after breaking the direct electrical connection between the accelerator and decelerator terminals. The new connections required approximately 200 ft. of high-voltage cable. Care was taken to run the cable along existing resistor-graded potential paths (accelerator/decelerator columns or supports) when its outer-casing potential went from ground to high voltage.

Finally, voltage breakdown tests and the last mechanical tests were made prior to putting oil in the tanks. No arcing problems were noted up to terminal voltages of 75 kV. The PVD and VRA tanks were then filled using a cleaned polyethylene hand pump.

III. EXPERIMENTAL PROTOCOL AND RESULTS

In our initial experiments with the VRA, we considered only the reaction

This collision avoided the experimental difficulty of producing an atomic hydrogen target, while providing a good test of our newly modified apparatus. We used a Colutron DC-discharge ion source in these experiments, which does not readily produce beams with charge state greater than +2.²⁹ Being thus limited to measurements in which $q/q' = 2$, we decided to modify the connections of the VRA coarse stacks for these studies to further reduce electric field stress in the oil tank during switching. This was accomplished by bypassing the upper coarse stack altogether, meaning that coarse resistor increments were now 20 MΩ instead of 40 MΩ (figure 6). The upper stack was connected electrically to the low voltage end of the lower stack.

An ion-energy spectrum for collision (5) is taken as follows. (For this discussion, we will assume 100 keV He^{++} projectiles.) The apparatus downstream from the target is first tuned for transmission of a He^+ beam. With the VRA shorted and $\text{HV} = 100$ kV, a He^+ beam from the ion source is selected by a Wien filter in the accelerator terminal. This beam is accelerated and directed through the (empty) target cell, and is then guided into the decelerator where it is focused and steered to the ion

detector following energy analysis. Once the detected He^+ signal has been optimized, the Wien filter fields are changed to select He^{++} , and the VRA is unshorted and adjusted so that the accelerator voltage, as read by the appropriate PVD voltmeter, is half (50kV) that of the decelerator. At this point, the He^{++} beam is directed onto the He target, and the ΔV power supply (or, alternately, the fine control of the VRA) is adjusted to search for a He^+ signal corresponding to single-electron capture from the target by He^{++} ions.

A spectrum thus obtained, with 90 keV He^{++} , is shown in figure 10. The peak at the left corresponds to superelastic capture into the He^+ ($n = 1$) state. Most capture, associated with the large central peak, corresponds to an $n = 2$ state of either the projectile or ionized target and an $n = 1$ state of the other collision partner. Neither collisions involving higher levels of either the projectile or target ions, nor transfer ionization processes, in which the target is doubly ionized with one of the electrons placed in a continuum state, are readily observable. The two features at about 3 and 20 eV of energy loss do not correspond to any known collision process, and are thought to result from spurious reflections in the ion-energy analyzer.

As taken, a spectrum of this type yields relative cross sections for the various capture channels, but does not provide an absolute cross section for the sum of all single-capture channels. Such information can be obtained by expanding the experimental procedure just described to include an absolute

determination of He^+ beam current incident on the target when the VRA is shorted, while noting the corresponding ion-detector current when the decelerated He^+ signal is optimized. This procedure calibrates the efficiency of the He^+ "detector", consisting of post-target ion optics, analyzing magnet, decelerator, energy analyzer, and electron multiplier. Thus with known target density and length and incident He^{++} current, an absolute single-capture cross section can be measured.

In practice, we have found that the procedure discussed above, and in particular steps involving the VRA and PVD, are (somewhat surprisingly) straightforward. Once the VRA is set, we observe no variations of the PVD voltmeter readouts by more than half a digit, or about one volt, over periods approaching one hour. Thus temperature-related resistance fluctuations in R_A and R_{VRA} (or the PVD divider strings) appear to be quite small. This obviates the need for temperature control of the lab or the resistors themselves, or active feedback adjustment of the VRA. Short-term variations, which might be caused, for example, by unstable corona discharge, have not been observed either.

We find that the system stability and the controls of the VRA are such that we can obtain any desired reading of the accelerator PVD voltmeter at will, precise to the last digit, or ± 1 volt. We also find, however, that upon setting the VRA resistance to the value where, e.g., the main $n = 2$ charge-transfer peak should be observed, that the ΔV power supply must typically be adjusted to negative values by between 20 and 50 V before He^+ ions are actually detected. This is

presumably due in large part to the voltage coefficient effect discussed earlier. The 200 M Ω PVD resistors have voltage coefficients of resistance of about $-1.3 \text{ ppm/V}^{.30}$. Thus, when V_A is dropped from, e.g., 100 kV to 50 kV, the accelerator PVD string resistance increases by roughly one part in 10^3 , or about 10 M Ω . Thus the accelerator voltmeter will read approximately 50 V low. Other reading errors could be caused by steady-state current leakage between the resistor strings in the PVD through the oil, or from the strings to ground, or by temperature variations between the PVD strings. We calculate both of these effects to be much smaller, however, than that due to the voltage coefficients of resistance.

Two problems of note have occurred with the VRA since its installation. During preliminary runs, the windings of two successive fine-adjustment potentiometers were destroyed by what appeared to be high-voltage arcing. Insofar as the voltage across these resistors was far less than their maximum rated value, and no external damage to the potentiometer casings, which would have indicated external breakdown, was visible, the cause of this problem is not understood. As an alternative, we replaced the potentiometer in the oil tank with a 1 M Ω , single-turn unit in the decelerator terminal. It is connected in series between the ΔV power supply and the VRA coarse-adjustment stack, and is controlled manually by means of a long, insulating rod extending to ground potential. While a fine-adjustment resistance value of 1 M Ω is not sufficient to bridge the 2 M Ω increments of the medium-adjustment stack, V_A is still settable to

arbitrary values by adjustment of ΔV . The arcing problems have not recurred since the adoption of this alternate technique.

At one point, after oil had been put in the VRA, a coarse-stack resistor lead broke at the point where it was connected by a screw terminal to a corona cap and an adjacent resistor. To replace the lead would have required a complete disassembly of the coarse stack and hence the entire VRA. Instead of doing this, we lifted the stack out of the oil and cleaned the corona cap terminal and broken resistor lead with methanol. The break in the lead was sufficiently close to the terminal, and the lead itself was sufficiently rigid, that a new electrical connection could be made by filling the upward-facing "well" of the cap (figure 7) with nickel paint. After the paint had thoroughly dried, the stack was resubmersed in oil. No degradation in the performance of the VRA was observed.

IV. CONCLUSION

We have successfully designed and applied a high-voltage variable resistor to studies of ion-atom collision processes in which the projectile ion changes charge. No serious problems were encountered in the apparatus operation. The relative potentials of the accelerator and decelerator terminals of the ion-energy spectrometer are easily set and remain constant with a precision better than two volts. The potentials can be read with an absolute accuracy better than 0.1%. We attribute these successful results at least in part to the high degree of

conservatism practiced during the design phase of this project.

ACKNOWLEDGEMENTS

We would like to thank D.M. Blankenship, J.D. Morgan, E.R. Redd, and especially J.T. Park for useful discussions. C.A. McWhorter built much of the VRA and PVD, and B.W. Stiritz performed the Laplace equation calculations. This work was supported by the U.S. Department of Energy Office of Fusion Energy under grant #DE-FG02-84ER53188.

REFERENCES

- * Present Address: Physics Division, Oak Ridge National Laboratory, Oak Ridge, TN 37831
- † Present Address: McDonnell Aircraft Company, P.O. Box 516, St. Louis, MO 63166-0516
- 1. J.T. Park, Adv. At. Mol. Phys. **19**, 67 (1983).
- 2. J.H. Moore, Jr., J. Chem. Phys. **55**, 2760 (1971).
- 3. M. Lennon, R.W. McCullough, and H.B. Gilbody, J. Phys. B **16**, 2191 (1983).
- 4. V.V. Afrosimov, A.A. Basalaev, G.A. Leiko, and M.N. Panov, Sov. Phys. JETP **47**, 837 (1978).
- 5. E.H. Nielsen, L.H. Andersen, A. Bárány, H. Cederquist, J. Heinemeier, P. Hvelplund, H. Knudsen, K.B. MacAdam, and J. Sorensen, J. Phys. B **18**, 1789 (1985).

- 6. S. Ohtani, Y. Kaneko, M. Kimura, N. Kobayashi, T. Iwai, A. Matsumoto, K. Okuno, S. Takagi, H. Tawara, and S. Tsurubuchi, J. Phys. B. **15**, L533 (1982).
- 7. For further references to projectile, or translational, ion-energy spectroscopy, see, e.g., R.K. Janev and H. Winter, Phys. Repts. **117**, 265 (1985), and C.L. Cocke and R.E. Olson, *ibid*, **205**, 154 (1991).
- 8. See, e.g., Y.P. Chong and W.L. Fite, Phys. Rev. A **16**, 933 (1977).
- 9. T.J. Kvale, D.G. Seely, D.M. Blankenship, E. Redd, T.J. Gay, M. Kimura, E. Rille, J.L. Peacher, and J.T. Park, Phys. Rev. A **32**, 1369 (1985).
- 10. See, e.g., R. Hoekstra, F.J. deHeer, and R. Morgenstern, J. Phys. B **24**, 4025 (1991).
- 11. D.H. Crandall, J.A. Ray, and C. Cisneros, Rev. Sci. Instrum. **46**, 562 (1975), and references therein.
- 12. J.T. Park and F.D. Schowengardt, Rev. Sci. Instrum. **40**, 753 (1969).
- 13. J.T. Park and F.D. Schowengardt, Phys. Rev. **182**, 152 (1969).
- 14. J.T. Park, J.M. George, J.L. Peacher, and J.E. Aldag, Phys. Rev. A **18**, 48 (1978).
- 15. See, e.g., B.H. Bransden, *Atomic Collision Theory* (2nd ed; Benjamin Cummings, Reading, 1983), chs. 9 and 10.
- 16. D.E. Post, L.R. Grisham, and R.J. Fonck, *Physica Scripta T3*, 135 (1983).
- 17. R.J. Fonck, D.S. Darrow, and K.P. Jaehnig, Phys. Rev. A **29**, 3288 (1984).

18. R.C. Isler, Nucl. Instrum. and Meth. **B2**, 673 (1985).
 19. A.J.H. Donné and F.J. de Heer, Nucl. Instrum. and Meth. **B21**, 219 (1987).
 20. M. von Kellersmann, W. Mandl, H.P. Summers, A. Boileau, R. Hoekstra, F.J. de Heer, and J. Frieling, Plas. Phys. and Cont. Fus. **31**, 1805 (1991).
 21. See, e.g., the Proceedings of the 8th Topical Conference on High Temperature Plasma Diagnostics, Rev. Sci. Instrum. **61**, pp. 2733-3316 (1990) and references therein.
 22. T.J. Lewis in *High Voltage Technology*, ed. L.L. Alston (Oxford, London, 1968) ch. 6.
 23. High-voltage DC resistive divider networks with specified accuracies of between 3% and 0.25% are available from, e.g., Glassman High Voltage, Universal Voltronics, Spellman High Voltage, Hippotronics, and Del Electronics.
 24. T.B. Rymer and K.H.R. Wright, J. Sci. Instr. **22**, 139 (1952).
 25. J.H. Park, J. Res. Nat. B. Stand. C, **66C**, 19 (1962).
 26. L.L. Alston, chapter 1 of reference 22.
 27. See, e.g., E. Kuffel and M. Abdulllah, *High-Voltage Engineering* (Pergamon, Oxford, 1970) and also chapter 7 of reference 22 (written by Z. Krasucki).
 28. Dale ROX metal-oxide resistors have negative voltage coefficients of resistance which are roughly inversely proportional to their voltage ratings, and whose absolute values increase approximately as the one-third power of their resistances.
 29. M. Menzinger and L. Wählén, Rev. Sci. Instrum. **40**, 102 (1969).
 30. This value is obtained by the linear extrapolation of values for average voltage coefficients of resistance quoted by the manufacturer for metal-oxide film resistors with lower voltage and power ratings (Dale catalog vol. 4, rev. 829, p. 185). See also ref. 28.
- FIGURE CAPTIONS**
- 1) Scale layout diagram of the ion-energy spectrometer at the University of Missouri-Rolla. Scattering data differential in angle are obtained by rotation of the entire ion source and accelerator about an axis through the target chamber perpendicular to the plane of the diagram. Both the accelerator and decelerator terminals are isolated in cages during operation. The locations of the variable resistor assembly (VRA), precision voltage divider (PVD), and second isolation transformer discussed in the text are indicated.
 - 2) Electrical schematic for the initial configuration of the ion-energy spectrometer. The main high-voltage (HV), energy-loss (ΔV), and extraction voltage (V_0) power supplies are indicated, as is the resistance-divider voltmeter (V) used to measure the ion-source potential. Resistances between the target chamber and the accelerator and decelerator terminals are those of the accelerator and decelerator columns; all other sources of resistance to

ground are indicated by the two remaining vertical resistance symbols.

3) Proton energy-loss spectrum for $50 \text{ keV H}^+ + \text{He}(1^1\text{S})$ collisions (see ref. 9). Peaks corresponding to excitation of $n = 2$ and $n = 3$ He target states, as well as that for elastic scattering, are indicated. The inelastic detector signal is multiplied by 10 or 100.

4) Electrical schematic for the modified ion-energy spectrometer, showing the variable resistor assembly (VRA) and second isolation transformer. Two resistive-divider voltmeters (V) are now used, although they are physically housed in one oil tank.

5) Scale assembly drawing of the variable resistor assembly (VRA). Shown are: 1) fine-adjustment resistor (40-turn wirewound $2.5 \text{ M}\Omega$ potentiometer); 2) intermediate-adjustment resistor stack (24- $2 \text{ M}\Omega$ resistors and rotary wiper); 3) two coarse-adjustment resistor stacks (each consisting of 50- $20 \text{ M}\Omega$ resistors and rotary wiper);

4) oil tank. The rotary wipers are turned by plexiglass rods as indicated. For simplicity, cable connections between the stacks and potentiometer, and external cable connections and clamps are not shown. The surface of the oil in the tank is about 2 cm below the lid.

6) Electrical schematic of the variable resistor assembly (VRA).

7) Detail of coarse-adjustment resistor stack periphery showing make-before-break spring-loaded wipers: 1) cross-sectional

view of rotating plexiglass wiper arm; 2) spring-loaded wiper with electrical connection; 3) corona caps; 4) two-piece plexiglass corona cap disks; 5) metal oxide-film resistors.

8) Precision voltage divider (PVD) potential surfaces calculated for the case of no oil in the tank ($\epsilon = 1$) by solving Laplace's equation in two dimensions using the finite-element relaxation technique. The dielectric effects of the plexiglass support structure have been neglected. Because the oil and plexiglass have similar dielectric constants, these potential curves should be fairly representative of the equivalent curves when the tank is filled with oil. An input potential of 200 kV is assumed. Corona caps, 1.9 cm in diameter, have centers placed at 8° or 16° intervals on a 37.5 cm diameter circle. These caps are labeled with their respective voltages (in units of kV); the caps labeled to be at zero, the value used in the calculation, are actually at potentials of less than 50 V associated with the $2 \text{ M}\Omega$ voltage-sensing resistors (see figure 9 and the text). Corona caps with 16° gaps between them are "dummy" electrodes used to reduce internal electric fields in the design. The outer circular boundary is the oil tank, taken to be at ground.

9) Electrical schematic of the precision voltage divider (PVD; see text).

10) Energy gain/loss spectrum for single-electron capture by 90 keV He^{++} incident on a ground-state helium target

(collision 5). The energy-gain peak at the left (~ 29 eV energy loss) corresponds to superelastic scattering into the projectile He^+ ($n = 1$) state, while the major central energy-loss peak is associated with either the projectile or target ion in an $n = 2$ state, while the partner ion is in its ground state. The $n = 3$ energy-loss position and transfer ionization limits are indicated as well (see text).

UNRIELS JULY '92 AD CALS

Figure 3

Figure 2

Figure 5

Figure 4

Figure 6

Figure 7

Figure 9

Figure 8

Figure 10

APPENDIX F

SUPERELASTIC ION ATOM STATE SELECTIVE
ELECTRON CAPTURE

V.D. Irbay*, I.J. Gay, J.T. Park, S.W. Gross, A.D. Gaus,
D.O. Seely, and J.L. Peacher

Laboratory for Atomic and Molecular Physics
Physics Department
University of Missouri-Rolla
Rolla, Missouri 65401

*Present address: Physics Division
Oak Ridge National Laboratory
Oak Ridge, TN 37831

ABSTRACT

Experimental studies have been made on the superelastic and inelastic collision processes for the state-selective single-electron capture reaction

where n and n' are the final states of the collision products.

Total cross sections have been measured by examining the energy gain/loss of the fast $^3\text{He}^{+}$ ion for capture into the superelastic $n=n'=1$ channel, and sum of the inelastic $n=2$, $n'=1$ and $n=1$, $n'=2$ states for projectile energies of 15, 30, and 45 keV/amu.

Introduction

The University of Missouri/Rolla is for Energy Loss Spectrometer (UMRILLS) has been modified to study state-selective electron capture reactions for bare ions incident on atomic or molecular targets. The main goal of these modifications is to study the reaction

which has been proposed as a diagnostic tool for fusion-plasma research. Total cross sections for this reaction can be obtained by observing the line radiation, λ , emitted from the He^+ excited states e.g.

or from the energy gain/loss of the He^+ projectile. Energy gain/loss measurements have two distinct advantages over the optical method. First, cascading corrections are avoided because the fast collision partner is detected, rather than a secondary photon. These corrections come about due to the possibility of the electron emitting more than one photon in, for example, the decay process

The second advantage of the energy gain/loss method is that no knowledge of detector efficiencies is required because ratios of specific n levels can be directly obtained from energy gain/loss spectra. This is due to the fact that the detector

efficiency for the He^+ ions is the same for all n levels. In contrast, the detector efficiency of most photon detectors depends upon the wavelength of the observed photon. Thus, two sources of possible systematic error in the determination of final cross sections are thereby eliminated.

In order to develop the necessary technology needed to study collision (1), without the further experimental problems associated with a hydrogen target, the first experimental work and the topic of this paper, involves state selective capture by He^{2+} from He targets:

Here n and n' represent the final states of the projectile and target respectively. Though the target species in reaction (4) is different from reaction (1), it involves much of the same physics, and knowledge of these cross sections are also important in the energy balance in fusion plasmas.

Figure 1 illustrates the energy levels of the $^3\text{He}^{2+}$ and He system. By using conservation of energy, one can show that the kinetic energy gained or lost in this collision is given by

$$E = 2 \left[\frac{1}{n} + \frac{1}{n'} \right] - I_p - 2 \quad \text{a.u.} \quad (5)$$

where I_p is the single-ionization energy of He and energy gain results in $E > 0$. The only superelastic channel with energy gain positive is for $n=n'=1$. Since the He target is considered at rest in the laboratory frame, energy lost in the collision must come from the kinetic energy of the projectile. The

Figure 1. Schematic diagram for the energy levels of the He and He^{2+} system. The numbers in parenthesis represent particular n states. The transition pictured represents the superelastic $n=n'=1$ capture process. The initial binding energy is 79 eV for He. The final state consists of two He^+ ions with a net binding energy of 108.8 eV. The difference in potential energy of the two states is converted into kinetic energy.

superelastic channel involves an energy release of about 30 eV. In the center of mass coordinates of the system the target and projectile share in the release of energy of the superelastic collision with the projectile and target energy gains ΔE_p and ΔE_t given by:

$$\Delta E_p = (20 \text{ eV}) m_t / (m_t + m_p) \quad (6)$$

$$\Delta E_t = (20 \text{ eV}) m_p / (m_t + m_p)$$

where m_t and m_p are the masses of the target and projectile respectively. (The mass of the transferred electron is ignored). When one transforms back to the laboratory frame, one sees that the increase in kinetic energy of the target depends upon the projectile scattering angle, θ , since

$$\Delta E_t = \frac{2 m_p m_t E_0 (1 - \gamma \cos \theta)}{(m_p + m_t)^2} + \frac{m_p Q}{(m_p + m_t)}$$

$$\gamma = \left[1 + \frac{(m_p + m_t) Q}{m_t E_0} \right]^{1/2} \quad (7)$$

where $Q = 20 \text{ eV}$ and E_0 is the incident projectile energy. Since the projectile scattering angle is on the order of 1 to

20 degrees for projectile energies of 30-200 eV, the increase in kinetic energy of the target is negligible for these small scattering angles, and the projectile carries away essentially all the excess energy. Interchange of the n and n' indices results in the same energy losses. For instance, when an electron is captured into the $n=2$ state of the projectile and the target is left in the $n'=1$ state, the energy loss is the same as for capture into the $n=1$ level of the projectile with the target left in the excited $n'=2$ level. Thus, the energy gain/loss method is inadequate for extracting specific target or projectile state-selective capture cross sections from this system. Nonetheless, this method can still yield information on the superelastic channel and limited information for higher n and n' values.

Extensive measurements have been carried out for total single capture cross sections, summed over all n and n' states, for reaction (4). Experimental data from the work of Shah et al.², and the work of Dubois³ are illustrated in Fig. 2. The total single capture cross section for the reaction

exhibits a maximum at an incident projectile velocity near 30 keV/amu. Another important process which can occur in the collision of alpha particles with He is "transfer ionization", (11)

in which one electron is "transferred" to the projectile and

Figure 2. Total single capture and transfer ionization cross sections. Upper curves represent single capture while the lower curves are for transfer ionization. Solid triangles are from the data of Shah *et al.* Solid squares are from the work of Dubois. (See Refs. 6 and 7.)

the remaining electron is "ionized" leaving the He target stripped of electrons. The 1f mechanism will be observed in the energy gain/loss spectrum corresponding to $n = \infty$ in Eq. (5). In order to extract absolute state-selective capture cross sections for this system, the energy gain/loss spectrum obtained must be integrated over all He^+ ion energies and normalized to the sum of the cross sections for reactions (8) and (9). This is because in making an energy gain/loss measurement on the fast He^+ projectiles in reaction (4), we cannot discriminate between reactions (8) and (9).

The only experimental data that exists for state selective electron capture for reaction (4) was obtained in 1978 by Afrosimov *et al.*³ Their experimental method involved energy gain/loss measurements and the results are illustrated in Fig. 3.

Due to the resolution of their parallel plate ion energy analyzer the experimental data covers only the low-projectile energy regime of 2 keV to 50 keV. The high energy resolution capabilities of the UMRIELS have allowed us to make the only existing measurements of reaction (4) for projectile energies ranging from 50 keV up to 135 keV.

A Experimental Apparatus

The University of Missouri/Rolla Ion Energy Loss Spectrometer, (UMRIELS), used in this work is illustrated in Fig. 4. The UMRIELS has been extensively described in the

3

Figure 3. Experimental data for state-selective single electron capture by Afrosimov *et al.*³

Cross sections displayed represent reactions in which one of the collision partners is found in the specific n state denoted, while the other is left in the ground state. The only exception is the $n, n' > 2$ reaction in which both collision partners are left in excited states.

4
Figure 8. The University of Missouri-Rolla Ion Energy Loss Spectrometer (UMRIELS). (See text).

UVR ION ENERGY LOSS SPECTROMETER

UVR ION ENERGY LOSS SPECTROMETER

literature, so only a brief description will be given here. The apparatus consists of a 15-200 kV variable-angle ion accelerator, scattering chamber housing, switching magnet, deceleration optics and either a cylindrical or retarding field ion-energy analyzer. Since the accelerator and decelerator are both electrically connected to the same high voltage power supply, voltage fluctuations do not effect the energy loss spectra. The variable-angle accelerator is pivoted about the center of the scattering chamber housing with the angular position controlled by a stepping motor rotating a precision-threaded rod attached to the undercarriage of the ion accelerator. A post scattering analysis magnet is used to separate out specific charge states after the collision region. The post scattering magnet and ion-energy analyzer, which is housed in the decelerator, remain stationary.

The projectile ions used in this work were produced in a commercially available electron-impact ion source manufactured by Colutron Corporation. The ions are extracted by a 2kV acceleration potential and passed through an Einzel lens focusing element before entering a Wien velocity filter. The mass selected ions then enter the main acceleration region, where a column focus and extraction system focus the incident beam onto the entrance of the scattering target. After passing through the scattering target, ions are deflected into the deceleration region by an analyzing magnet. Ions neutralized in the target region pass undeflected through

the magnet and into a neutral-detector chamber. This arrangement allows simultaneous measurement of both neutral and charged ions resulting in the collision process.

After the ions are decelerated, they are then energy analyzed by either a cylindrical or retarding field analyzer. It was later found that the cylindrical analyzer is inadequate for this work and a retarding field analyzer was installed which enabled completion of this experiment. The shortcomings of the cylindrical analyzer and a description of the retarding field analyzer will be discussed in detail in sections B and C. (To maintain clarity the following descriptions will only involve the cylindrical analyzer.)

Following deceleration the ions pass through the entrance slits of the cylindrical analyzer which are electrically set at the same potential as the decelerator. The cylindrical analyzer is nominally set for a pass energy of V_0 , where V_0 is the source extraction voltage, and q_0 is the initial charge of the ion after the collision. From Fig. 3, which illustrates the initial electrical configuration of the apparatus, one can see that the ions which enter the analyzer have a kinetic energy of $q_0 V_0 + q_0 \Delta V + q_0 V_0 - q_0 V_0 - E_{\text{loss}}$, where q_0 is the initial charge of the ion before the collision, V_0 the power supply high voltage, ΔV the precision offset voltage applied to the accelerator terminal voltage, and E_{loss} the energy lost in the collision. In this

5

Figure 3. Original electrical configuration of the UMRIELS. V_0 is the high voltage applied to the apparatus, ΔV is the precision offset voltage applied to the accelerator and V_c is the source extraction voltage. The total acceleration voltage is $V_0 + \Delta V + V_c$.

configuration, the only way for the ions to negotiate the analyzer is if the final charge of the ion is equal to the charge before the collision and $q_1 V_1 = q_2 V_2$. Both ions and neutral particles are detected by Johnston Laboratory electron multipliers.

Ion spectra are obtained by varying the offset voltage ΔV between the accelerator and decelerator terminals. In this way, all electrostatic elements downstream of the target can be kept at constant potential during a run. This ensures that the ion "detector", consisting of the magnet, decelerator and cylindrical analyzer, maintains a constant overall detection efficiency. Since the entire accelerator system can be moved in angle, this also ensures that our cross sections will not be too low due to incomplete angular acceptance of the detector.

In order to study the single electron capture reaction

the accelerator/decelerator system has been modified as shown schematically in Fig. 6. In this configuration the potential on the accelerator can be adjusted to be as low as one third of the voltage on the decelerator, while the decelerator potential remains constant. This was accomplished by utilizing the voltage dividing action of a Variable Resistor Assembly, VRA, placed between the decelerator and accelerator terminals. To set up a single capture run, the VRA is first shorted, ensuring that the accelerator and decelerator are at the same

6
 Figure 1. Electrical schematic illustrating modified UMRIELS. 1. Variable Resistor
 Assembly. 2. Precision Voltage Dividing resistor strings for accelerator and decelerator.

potential, and a $^3\text{He}^+$ beam is guided through the system into the cylindrical analyzer. Once this is accomplished, the "detector", consisting of the magnet, decelerator and analyzer, is adjusted to accept $^3\text{He}^+$ ions at an energy of eV_0 , where V_0 is the power supply high voltage. The VRA resistance is then increased so that the accelerator voltage is near one half the decelerator voltage. Now $^3\text{He}^{2+}$ ions are extracted and passed through the target. The $^3\text{He}^+$ product beam formed from collisions between the alpha particles and the target gas can then be guided into the analyzer, since the energy of the $^3\text{He}^+$ ions is $2e(V_0/2)$. In order to accurately determine the accelerator/decelerator voltage ratio, a Precision Voltage Divider, PVD, network has been constructed and installed in the system. Utilization of twin Fluke 8840A digital multimeters enables one to easily set the the accelerator voltage to within one volt of the desired value. Since there now exists a large potential difference between the accelerator and decelerator, a second isolation transformer has also been installed.

B. Preliminary Results

Figures 7 and 8 illustrate energy gain/loss: single capture spectra for $^3\text{He}^{2+}$ incident on He and Ar. Both spectra were taken with target pressures of 40 to 60 microns. For the He target, the $n=1$ and $n=2$ capture channels are clearly seen and

Figure 8. Energy gain/loss spectrum of $^3\text{He}^+$ formed through collisions of 30 keV/amu $^3\text{He}^{2+}$ ions incident on He.

Figure 22. Energy gain/loss spectrum of ${}^3\text{He}^+$ formed through the collisions of 30 keV/amu ${}^3\text{He}^{2+}$ ions incident on Ar.

The separation is as expected. One must remember that these plots include channels for $n=1$, and either $n=1$, $n=2$ or $n=2$ and $n=1$. Capture into the $n=2$ and higher states was observed to be negligible. Structure is also observed past the $n=1$, $n=\infty$ transfer ionization position. The anomalous features occurring between the $n=1$ and $n=2$ channels were observed to be quite reproducible though not in agreement with the expected energy gain/loss values of the system. Possible causes of these anomalous peaks will be discussed in a few more paragraphs.

For Ar targets the superelastic $n=1$ channel (energy gain of 38 eV) was observed to be negligible. If we assume that relative energy gain/loss peak heights will be correlated roughly with their associated energy defect, this result is understandable in comparison with the superelastic $n=n'=1$ peak observed with He targets, where the energy gain is 50 eV.¹⁰ The $n=2$ and $n=3$ TI peaks are also observed. Background spectra for both He and Ar were essentially zero.

Extreme experimental difficulties were encountered in the acquisition of energy gain/loss spectra. Due to the low alpha beam currents, low count rates, and short lifetime of the ion source, which was ~ 5 hours due to the increased power required for alpha particle production, it became very difficult to properly guide the product He^+ beam into the analyzer within the available operating time of the ion source. Typical experimental runs required 8 to 12 hours of set up time and,

to 60 to 70 % of all runs, the ion source failed before data acquisition could be properly accomplished.

Since typical count rates for He targets were on the order of 20 to 30 Hz at target pressures of 40 to 50 microns, pressure tests to ensure single collision conditions could not be properly done. Some of the anomalous peaks between the $n=1$ and $n=2$ capture positions of He may be attributed to double collisions within the scattering target due to the high target pressures required to see appreciable "product" signal. If, for instance, an alpha particle collides with He and captures the electron in the $n=1$ state, a secondary collision with another He atom could result in a secondary energy loss of 20 % or higher due to single or double excitation of the second atom. The net result would be other peaks occurring in the energy gain/loss spectra between the $n=1$ and 2 levels.

To complicate matters further, the angular acceptance of the cylindrical analyzer was not known. Thus, to obtain absolute state selective capture cross sections, angular scans "all" features in the He spectrum had to be performed. Due to the low count rates and limited ion source lifetime, this was virtually impossible.

Further experimental measurements established that the energy acceptance ^{width} of the cylindrical analyzer was adequate for this work. Figure 9 illustrates an energy loss spectrum for $^3\text{He}^+$ impact excitation of He. A large anomalous peak, which was 25 % of the incident beam, occurred at 65 eV

q

Figure 9. Energy-loss spectrum of 30 keV/amu $^3\text{He}^+$ incident on He. The anomalous peak near 65 eV was observed to be independent of target pressure. The first two peaks are caused by N_2 background. The peaks starting at 20 eV are due to excitation of the He target while the peak occurring at 40 eV is due to excitation of the $^3\text{He}^+$ projectile to the $n=2$ state.

energy loss and was observed to be independent of target pressure. It was discovered that this peak was produced by impact of the incident $^3\text{He}^+$ ion beam with the back plate of the analyzer. The energy acceptance ^{range} width of the analyzer was calculated, using the radii of the inner and outer plates, to be ± 50 eV for a pass energy of 2 keV. Ions outside this energy region will strike the inner or outer plates of the analyzer resulting in spurious signal. Since the energy gain/loss scans for state-selective capture have to extend over a 120 eV energy range, the analyzer proved to be inappropriate for this work. Some of the anomalous peaks in Fig. 7 may also be attributable to ions striking the inner or outer plates of the analyzer, e.g. the structure occurring at 80 eV in Fig. 7 is caused by $n=1$ ions striking the back plate of the analyzer.

Due to the extreme experimental difficulties encountered with the cylindrical analyzer, a retarding field energy analyzer was designed, constructed and installed on the apparatus. The next section deals with the new analyzer and illustrates spectra obtained.

C. Retarding Field Analyzer

Due to the problems encountered with the cylindrical analyzer, it became necessary to try an alternative approach to acquire data. The low beam currents caused great difficulty

in guiding the ion beam into the analyzer. In addition, it was discovered that the energy acceptance ^{range} ~~width~~ was inadequate for this work. Lastly, because of the large beam transmission losses through the analyzer, count rates were unacceptably low. Thus, it became desirable to investigate the use of a retarding field analyzer.

The retarding field analyzer. RFA, eliminates, in principle, the problems encountered with the cylindrical analyzer: it should be easier to guide the ion beam into it, the transmission of the ions would be improved, and it would not have a limited energy acceptance ^{range} ~~width~~. Retarding field analyzers have been used extensively to measure electron energies.^{11,12} In the present case, a retarding field analyzer will be used to measure energies of heavy ions. One may seriously question the feasibility of using one of these devices for ions of such high energy since it is difficult to take fast heavy ions and bring them to a dead stop within a space of 2 meters without having serious focussing problems. Because we are examining heavy ions instead of electrons, stray electric and magnetic fields pose less of a problem. In addition, the spectrum of interest does not contain an "incident" ion beam since the incident $^{3}\text{He}^{2+}$ ions are separated out by the switching magnet. (In energy loss measurements in which the charge of the projectile does not change during a collision, there is no way to separate out the incident beam from the signal of interest.) One must also

remember that in the present configuration of the apparatus, ion energies are already reduced from 180 keV to 2 keV in the decelerator before entering the cylindrical analyzer. Thus focussing problems in the deceleration region are already present. In this sense, the apparatus is already a limited RFA.

The retarding field analyzer used in this work consisted of 4 major components: a main deceleration region, a zoom lens, a set of retarding field grids and a Johnston Laboratory particle multiplier. (See figures 10 and 11). After passing through the target region and switching magnet, ions that entered the main deceleration region were reduced to an energy of approximately 400 eV, where they then entered the zoom lens. All lens elements z-2 through z-7 were held at the decelerator potential. This provided a field-free drift region for the ions and also established a well-defined potential before the retarding field. Since the resolution of a retarding analyzer depends critically on the values of momenta perpendicular to the retarding field and beam axis, an aperture was installed in zoom lens element z-7 to discriminate against ions with large components of perpendicular velocity. Zoom lens element z-6 consisted of cylindrical steering segments to help guide the ion beam through the 1/16 inch diameter aperture. After passing through the aperture, the ions were then subjected to the retarding field. A dual set of wire grids, which were

10
Figure 28. Retarding-field ion-energy analyzer (RFA).

//
Figure 18. Close-up of the retarding-field ion-energy analyzer illustrating the zoom lens
(see text). The individual zoom lens elements are labeled z1 through z7.

electrically connected, provided the retarding potential. The distance between the grids was approximately 1/4 inch. Ions with sufficient energy to overcome the potential barrier of the first grid drifted across the field free region and exited out the second grid. Since the Johnston Lab detector was operated with the first dynode, or collector plate, at -4000 volts with respect to the decelerator potential, ions exiting from the second retarding grid were strongly accelerated and focussed onto the detector. Before striking the first dynode on the Johnston Lab detector ions passed through an electron suppression grid that was biased negatively with respect to the first dynode. This grid eliminated secondary-electron emission from the first dynode which would tend to reduce ion detection efficiency. The high voltage applied to the detector also ensured that all ions striking the first dynode of the detector had roughly the same kinetic energy.

Figure 12 illustrates a retarding voltage scan of the product $^3\text{He}^+$ produced in alpha-helium collisions for a projectile energy of 30 keV/amu. The full $^3\text{He}^+$ ion beam is detected at 150 V. As the retarding voltage is increased, ions suffering from transfer ionization energy losses begin to be blocked by 210 V, and the signal decreases. At 270 V, only the $n=1$ and $n=2$ capture channels have enough energy to overcome the retarding barrier, and when the voltage reaches 290 V, only the $n=1$ superelastic ions remain.

In order to make a comparison with spectra obtained with

12

Figure 12. Retardation voltage spectrum of $^3\text{He}^+$ formed in collisions of $^3\text{He}^{2+}$ incident on He. (Incident projectile energy was 30 keV/amu.) The ion signal was normalized to the measured neutral signal, which varies linearly with the incident beam for constant pressures. The spectrum depicted represents an average of three separate data runs. Each spectra was first normalized to the neutrals and then the average was taken at each voltage and the results are plotted.

the cylindrical analyzer, the spectrum in Fig. 7 was integrated and plotted in Fig. 13. (Both spectra were taken with the same energy.) One can readily see that the positioning and magnitudes of the features in both spectra agree very well. If the anomalous peaks previously observed between the $n=1$ and $n=2$ channels were real, the slope on the retardation scans to the left of the $n=1$ cutoff position would have a negative value. Since the measured slope is essentially zero it can be safely concluded that the anomalous features were not associated with the actual collision mechanisms in which we are interested.

Retardation spectra were taken for Ar and Ne targets with projectile energies of 30 keV/amu and are illustrated in Figs. 14 and 15. The Ar spectrum shows that the $n=1$ superelastic channel is negligible, while transfer ionization is enhanced, which agrees with the previous cylindrical analyzer spectra. Ionization energies for He, Ne, and Ar are 24.5, 21.6, and 15.8 eV respectively. Since a resonant zero energy-loss capture process will occur if the binding energy of the target is equal to the 13.6 eV binding energy of the $n=2$ level of He^+ , one may expect that the ratio of the $n=1/n=2$ capture signals will be suppressed when the ionization potential of the target is near the $n=2$ binding energy. This is in qualitative agreement with the spectra¹⁰.

Since the count rates are now in the 1000 Hz range, pressure tests to ensure single collision conditions can be

13
Figure 20. The Energy gain/loss spectrum illustrated in Fig. 21 was integrated and plotted for comparison with the equivalent retardation voltage spectrum. Integrated signal represents the ion count rate, from Fig. 21, integrated over energy. Since the spectrum only covered a 100 volt range in Fig. 21, a straight line was added to simulate the rest of the spectrum. The positioning of the plotted spectrum was chosen arbitrarily for comparison.

Figure 24. Retarding voltage spectrum for Ar targets for projectile energy of 30keV/amu.

Figure 2. Retardation spectra for Ne target, with projectile energy of 30 kev/amu.

properly done. After energy scans were taken for He targets, retardation voltage positions of the $n=1,2$ and $n=all$ levels were recorded and the retardation voltage was fixed at these values. While monitoring the $^3\text{He}^{2+}$ incident beam, count rates versus pressure were recorded and the results indicated that single collision conditions were ensured for target pressures below 40 microns. (Subsequent data runs involved target pressures between 15 and 20 microns.)

Angular scans of the features in the retardation spectra were performed next to study the angular acceptance of the analyzer, and the results indicated that the angular features of all n channels were the same. This implies that either the individual differential cross sections for each channel were the same, or that the RFA detector has full angular acceptance of the $^3\text{He}^{2+}$ ions. In either case, this shows that the state-selective cross sections in which we are interested in can be obtained by retardation voltage scans alone.

The major experimental difficulties encountered with the cylindrical analyzer have ~~been~~ been overcome. The time required to maneuver the $^3\text{He}^{2+}$ product beam into the analyzer has been reduced from a few hours to about 10 minutes. The count rates have been increased by a factor of a thousand. Finally, the anomalous features previously observed have been eliminated. Thus, the retarding field ion energy analyzer has proved to be a marked success in this experimental endeavor.

D RESULTS

Final results for capture into the $n=n'=1$ state and capture into the sum of the states $n=2$, $n'=1$ and $n=1$, $n'=2$ are listed in Table 1. Relative cross sections were obtained from the RFA background corrected spectra and were put on an absolute scale by normalizing to the total single-capture and transfer ionization data of Shah et. al and Dubois.^{2,3} Figure 14 compares the final results to the experimental data of Afrosimov et. al.³ and good agreement is seen for the low 45 keV energy position. Since Afrosimov's data is the sum of the $n=2,2$ and 4 capture levels, it is expected that our cross section for $n=2$ should be slightly less than his value, and this is also in agreement. As the experimental data shows, capture into the higher $n=3$ and 4 levels is negligible for the higher energies. Calculations of the cross section for the $n=1$ channel by the impact parameter method obtained by Fulton and Mittleman¹³ are also shown. The calculations utilized wavefunctions for only 3 states: $[\text{He}^{2+} + \text{He}(1s)]$, $[\text{He}(1s) + \text{He}^{2+}]$, and $[\text{He}^{2+}(1s) + \text{He}^{2+}(1s)]$. They are in good agreement with experiment. (At this time these are the only theoretical calculations known for this system).

From the experimental cross sections measured for He targets, and examination of the spectra for Neon and Argon, it appears that electrons are preferentially captured into n

1

Table 1. Final state selective single-electron capture results for ${}^3\text{He}^2$ incident on He. The states $n=1$, and $n=2$ depict electron capture into the $n=n'=1$, and either $n=2$, $n'=1$ or $n=1$, $n'=2$ states respectively. Uncertainties given represent relative error. Overall error due to normalization is about 22%.

Energy (keV/amu)	$n=1$ ($\times 10^{-17} \text{ cm}^2$)	$n=2$ ($\times 10^{-16} \text{ cm}^2$)
15	$4.46 \pm .16$	$.884 \pm .035$
30	$6.89 \pm .26$	$1.50 \pm .06$
45	$5.64 \pm .24$	$1.45 \pm .06$

Figure 1. State selective capture cross sections for ${}^3\text{He}^{2+}$ incident on He. Relative errors are less than 5 %. Overall errors are about 22 % due to normalization to data of Shah *et al.* and Dubois. Dashed lines indicate theoretical calculations from Ref. 13.

states that have binding energies close to that of the single ionization potential of the target. In addition, the closer the ionization potential of the target is to the $n=2$ energy of He⁺, the more diminished the $n=1$ capture channel becomes. For hydrogen targets, the ionization potential is exactly equal to that of the $n=2$ state of He⁺. Thus, one may predict that the superelastic $n=1$ channel will be greatly diminished, with capture occurring predominately into the "resonant" $n=2$ state. Since the superelastic channel will be diminished, one may hope that capture into the $n=3$ state, which plays an importance in the diagnostic technique for fusion reactors, will have a higher probability for H targets compared to He.

The authors gratefully acknowledge funding for this work
by DOE grant # DOE DE FG02 84ER53188.

REFERENCES

REFERENCES (cont.)

- 1.) I.F. Stratton, "Plasma Diagnostic Techniques", edited by R.H. Huddleston and S.L. Leonard (Academic, New York, 1965).
- 2.) M.B. Shah, P. McCallion, and H.B. Gilbody, J. Phys. B: At. Mol. Opt. Phys. 22, 3037, (1989).
- 3.) R.D. Dubois, Phys. Rev. A, 36, 6, 2585, (1987).
- 4.) V.V. Afrosimov, A.A. Basalaev, G.A. Leiko, and M.N. Panov, Sov. Phys. JETP, 47 (5), 837, (1978).
- 5.) J.T. Park, J.M. George, J.L. Peacher, and J.E. Aldag, Phys. Rev. A 18, 48 (1978).
- 6.) J.T. Park, J.E. Aldag, J.M. George, and J.L. Peacher, Phys. Rev. A 14, 608 (1976).
- 7.) J.E. Aldag, J.L. Peacher, F.J. Martin, V. Sutcliffe, J. George, E. Redd, T.J. Kvale, D.M. Blankenship, and J.T. Park, Phys. Rev. A 23, 1062 (1981).
- 8.) J.T. Park, and F.D. Schowengerdt, Rev. Sci. Instrum. 40, 753 (1969).
- 9.) V.D. Irby, Ph.D. thesis, University of Missouri-Rolla, 1991 (unpublished).
- 10.) R.E. Olson, private communication.
- 11.) J.A. Simpson, Rev. Sci. Instrum. 32, 12, 1283 (1961).
- 12.) T. Gimpal and O. Richardson, Proc. Roy. Soc. (London) A 182, 17 (1943).
- 13.) M.J. Fulton and M.H. Mittleman, Proc. Phys. Sci. 87, 669 (1966).

**DATE
FILMED
12/24/92**