Los Alamos National Laboratory is operated by the University of California for the United States Department of Energy under contract W-7405-ENG-36

LA-UR-88-820

TI88 007894

TITLE: U.S. TEAM MEASUREMENTS DURING THE JUNE 1987 EXPERIMENTAL HT
RELEASE AT THE CHALK RIVER NUCLEAR LABORATORIES, ONTARIO, CANADA

AUTHOR(S): Roland A. Jalbert
Charles E. Murphy

SUBMITTED TO M. L. Rogers
Mound Laboratory
P.O. Box 32
Miamisburg, OH 45342

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

By acceptance of this article the publisher recognizes that the U.S. Government retains a nonexclusive, royalty free license to publish or reproduce the published form of this contribution or to allow others to do so, for U.S. Government purposes.

The Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Department of Energy.

Los Alamos Los Alamos National Laboratory
Los Alamos, New Mexico 87545

MASTER

U.S. TEAM MEASUREMENTS DURING THE JUNE 1987 EXPERIMENTAL HT RELEASE
AT THE CHALK RIVER NUCLEAR LABORATORIES,
ONTARIO, CANADA

Roland A. Jalbert
Los Alamos National Laboratory
Los Alamos, NM 87532
(505) 667-0434

Charles E. Murphy
Savannah River Laboratory
Aiken, SC 29808
(803) 725-5224

ABSTRACT

In June 1987, an experiment was performed at the Chalk River Nuclear Laboratories in Ontario, Canada, to study the oxidation of HT in the environment. The experiment involved a 30-minute release of 100 Ci of HT to the atmosphere at an elevation of one meter. The HTO/HT ratios were shown to slowly increase downwind ($\sim 4 \times 10^{-5}$ at 50 meters to almost 10^{-3} at 400 meters) as conversion of HT takes place. For several days after the release, HTO concentrations in the atmosphere remained elevated. Freeze-dried water from vegetation samples was found to be very low in HTO immediately after the release suggesting a very low direct uptake of HTO in air by vegetation. The tritiated water concentration increased during the first day, peaking during the second day (about 400-600 pCi/ml of water at 50 meters from the source) and decreasing by the end of the second day. The organically bound tritium continued to accumulate during the period following exposure (about 10 pCi/gm dry weight at 50 meters after two days).

INTRODUCTION

The second in a series of recent major experimental tritium release experiments was performed in June 1987 at the Chalk River Nuclear Laboratories in Ontario, Canada. The purpose of these experiments was to study the fate of elemental tritium in the environment. Scientists from six countries took part in the experiment. United States participants focused their attention on measuring HT and HTO concentrations in air during and after the release in addition to analyzing vegetation samples after the release for free water tritium and organically bound tritium (OBT).

THE EXPERIMENT

A detailed description of the field site, pertinent meteorological data and of the release itself may be found elsewhere. Briefly, the release site was an open field approximately 400 meters on the long axis and 200 meters at the widest point on the other

axis. Most of the field was covered with grass and moss with occasional small trees. At the end of the field farthest from the point of release, the surface soil had been removed leaving an area with very little vegetation. The field was surrounded by a stand of mixed conifer and hardwood trees (Fig. 1).

Fig. 1. Downwind view of the experimental field.

One hundred curies of HT were released at an elevation of 1 meter from the ground between 1520 and 1550 EDT on 10 June 1987. Wind speed during the release varied between 2.2 and 3.5 m/s with a mean value of about 2.4 m/s. The direction varied from about eight degrees south of the centerline (300°) during the first 5-10 minutes of the release to $\sim 25^\circ$ north of the centerline during the remainder of the release. During the evening and through most of the following day when additional air and vegetation measurements were made, the wind direction did not markedly change, remaining within 240° and 340°. The wind speed likewise maintained its strength (2-3 m/s) except at night (2130, 10 June to 0800, 11 June) when it dropped to ~ 1 m/s. Light rain began to fall at about 1500 of the second day (11 June) and continued on and off during the remainder of the day. This did not affect the U.S. air measurements, which had been concluded by that time.

water-bubbler-type air samplers were designed and built by the Los Alamos National Laboratory (LANL) especially for this experiment. Each sampler consisted of three small bubblers in series (for HTO) followed by a heated catalyst, three more bubblers (for HT), flowmeter and pump (Fig. 2). The bubblers were 20-mL low-background-glass liquid scintillation vials filled with 10 mL of water. The catalyst cartridge consisted of a copper tube filled initially with brass chips followed by a precious metal catalyst heated to 400°C. Following the catalyst, cooling coil and HT bubblers were a flowmeter and an air pump. The bubbler flow rate of 1.0 Lpm was checked after each sampling run. The catalyst heaters were turned on by plugging them into a local power outlet at least 30 minutes before the sampling began. The sampling during the release was controlled by starting and stopping the pumps remotely through cables. Only the first two bubblers were used for the HTO determination in order to eliminate the possibility of adding backstreaming tritium from the catalyst. For the HT determination, the total tritium collected during the release was determined by adding all the tritium collected in the HT bubblers during the sampling runs including the two runs after the end of the release. In addition, the remaining tritium trapped on the catalyst and associated plumbing was leached out at Los Alamos and added to the tritium collected in the vials. The solubility of the tritium in the HTO bubblers limited the HTO/HT ratio that could be determined to a minimum of about 1:10. Three LANL samplers were placed close together at 50 meters downwind from the source at the center line. Three more, also close together, were located at 96 meters and the remaining two at 183 meters downwind and 18

meters apart. The reason for bunching the samplers at 50 and 96 meters was to attempt to get a time profile of the tritium air concentration during the release.

Air sampling by the Savannah River Laboratory (SRL) was done with two HTO/HT samplers (Fig. 3) based on the Oslund-Mason design modified for high volume sampling.² The system consists of a pump which draws 50 liters of air per minute through two collection cylinders each filled with 350 grams of Davison 4A molecular sieve. Hydrogen carrier gas is added to the sampled air stream (150 cc/min) before the air enters the first cylinder, which contains uncoated molecular sieve for trapping the HTO. The second cylinder contains palladium-covered molecular sieve for HT. The palladium catalyzes the oxidation of hydrogen (including HT) to water, which is collected on the sieve. The samplers were run for a period of one hour. At the end of a sampling period the pump was stopped, the collection cylinders were removed and sealed, and fresh collection cylinders were installed on the samplers. The used molecular sieve was transferred in the field to glass jars which were sealed for later laboratory analysis. The two samplers were located near the centerline at 183 m and 350 m from the release point.

Fig. 3. Test area looking upwind toward the release point. An SRL air sampler is shown in the foreground.

After the release, samples of vegetation were taken at 50, 180, 350 and 400 meters downwind from the point of release and sealed in plastic bags. At SRL the samples were vacuum distilled to remove the free water, which was collected in a cold trap and saved for later counting. The dry samples were then combusted in a furnace using an oxygen and argon gas mixture. The activity of the OBT was determined by liquid scintillation counting.

RESULTS

Table 1 shows the results of the air

Fig. 2. Sketch of LANL field air sampler.

TABLE 1. Results of LANL and SRL air sampling during and after the release.

Sampler Number	Location ⁽¹⁾ x,y,z (m)	Sampling Time ⁽²⁾ H + (hr:min)	[HT] ₃ Bq/m ³	[HTO] Bq/m ³	[HTO]/[HT]
LANL 1	50.5,3.5,0.9	H+(0:1 to 0:10.6)	3.0E+06	1.6E+02	5.2E-05
2	50.5,3.5,0.9	H+(0:10.6 to 0:20.1)	3.2E+06	1.1E+02	3.5E-05
3	50.5,3.5,0.9	H+(0:20.1 to 0:29.6)	1.7E+06	5.9E+01	3.4E-05
4	96,2.0,0.9	H+(0:2 to 0:11.6)	1.3E+05	1.1E+02	8.7E-04
5	96,2.0,0.9	H+(0:11.6 to 0:21.1)	5.7E+05	3.8E+01	6.7E-05
6	96,2.0,0.9	H+(0:21.1 to 0:30.8)	5.6E+05	9.8E+01	1.8E-04
7	183,-10,1.0	H+(0:2 to 0:32)	5.1E+04	2.5E+01	4.9E-04
8	183, 8,1.0	H+(0:2 to 0:32)	6.5E+04	8.5E+01	1.3E-03
1	50.5,3.5,0.9	H+(1:50 to 2:58)	-	2.6E+02	-
2	50.5,3.5,0.9	H+(1:50 to 2:58)	-	2.4E+02	-
3	50.5,3.5,0.9	H+(2:58 to 3:58)	-	2.0E+02	-
4	96,2.0,0.9	H+(1:50 to 2:58)	-	8.3E+01	-
5	96,2.0,0.9	H+(1:50 to 2:58)	-	7.0E+01	-
6	96,2.0,0.9	H+(2:58 to 3:58)	-	1.0E+02	-
7	183,-10,1.0	H+(1:50 to 2:58)	-	1.4E+01	-
8	183,8,1.0	H+(1:50 to 2:58)	-	4.0E+01	-
1	50.5,3.5,0.9	H+(18:59 to 19:59)	-	2.9E+02	-
2	50.5,3.5,0.4	H+(18:59 to 19:59)	-	3.6E+02	-
3	50.5,3.5,0.07	H+(18:59 to 19:59)	-	4.6E+02	-
4	96,2.0,0.9	H+(18:59 to 19:59)	-	7.4E+01	-
5	96,2.0,0.4	H+(18:59 to 19:59)	-	9.0E+01	-
6	96,2.0,0.09	H+(18:59 to 19:59)	-	1.1E+02	-
7	183, 10,1.0	H+(18:59 to 19:59)	-	2.4E+01	-
8	183,8,1.0	H+(18:59 to 19:59)	-	3.4E+01	-
SRL 1	180,10,0.75	H (24:32 to 23:51)	5.00E-01	5.22E+00	1.04E+01
2	400,30,0.5	H (24:28 to 23:47)	1.81E-01	4.48E+00	1.17E+01
1	180,10,0.75	H(00:00 to 00:38)	2.47E+05	2.89E+01	1.17E-04
2	400,30,0.5	H(19:12 to 19:43)	5.00E+04	4.00E+01	8.00E-04
1	180,10,0.75	H(19:09 to 19:40)	2.11E+01	8.25E+00	3.19E-01
2	400,30,0.5	H(19:15 to 19:44)	5.87E+00	3.12E+00	5.32E-01

Notes: ⁽¹⁾ X is the distance from the source along the centerline. Y (+) is toward the north, Z is the vertical distance from the ground to the sampler intake.

⁽²⁾ H refers to time release began: 15:20 (EDT), 10 June 1987

sampling by LANL and SRL. The first two S.L. samples were taken before the release and can be considered background for the combination of location and the samplers. All of the samples taken during the release show the expected decrease in concentration of HT with distance from the release. The samples taken during the release show an increase in the concentration of HTO with distance. The increase in the HTO/HT ratio is greater than would be predicted by HT to HTO conversion rates in air determined by small scale laboratory experiments. However, the rate of oxidation is much smaller than suggested by an early French experiment but consistent with what might be expected from oxidation in the soil. Measurements taken on the following day show that the concentration

of HTO in the air remains elevated over that found before the release. The source of this HTO is likely to be HT oxidized and remaining in the soil and vegetation. This has important implications for dose calculations resulting from releases of HT during the seasons when soil bacteria are active.

The concentrations of HT also remained slightly elevated. This could result from some HT absorbed into soil and vegetation. However it is also possible that it is an artifact caused by slow release of HT sorbed on the metal surfaces of the air samplers.

Table 2 shows the location of the vegetation samples and the results of the analysis.

TABLE 2. Tritium activity in vegetation samples.

Location of Sample x,y (m)	Sampling Date Mo., Day	Sampling Time ⁽¹⁾ (Hours)	Free H ₂ O Bq/L	OBP Tritium Bq/L
50,10	6,10	-6.83	2.25E+01	3.91E+02
50,10	6,10	0.68	1.71E+03	4.64E+02
50,10	6,11	17.67	3.00E+04	2.07E+03
50,10	6,11	23.77	1.83E+04	3.00E+03
50,10	6,19	186.17	2.52E+03	1.13E+03
180,0	6,10	-7.13	2.52E+01	
180,0	6,10	0.57	2.12E+02	
180,0	6,11	17.37	2.13E+03	
180,0	6,11	23.44	1.22E+03	
400,-15	6,10	-7.33	6.90E+01	
400,-15	6,10	0.50	9.70E+01	
400,-15	6,11	17.17	5.60E+02	
400,-15	6,11	23.33	1.70E+02	
50,0	6,10	-6.93	6.72E+01	6.77E+02
50,0	6,10	0.65	4.48E+03	6.58E+02
50,0	6,11	17.57	1.50E+04	9.85E+02
50,0	6,11	23.66	1.33E+04	1.02E+03
50,0	6,19	186.17	2.37E+03	3.43E+02
180,-40	6,10	-7.03	6.72E+01	
180,-40	6,10	0.61	1.47E+02	
180,-40	6,11	17.47	1.69E+03	
180,-40	6,11	23.55	9.69E+02	
350, 100	6,10	7.23	2.79E+01	
350, 100	6,10	0.54	5.47E+01	
350, 100	6,11	17.27	3.17E+02	
350, 100	6,11	23.22	1.69E+02	

⁽¹⁾ Measured from end of release 1550 (EDT), 10 June 1987.

Results for the free water H₂O samples are illustrated in Fig. 4. As expected, the concentration of H₂O in the vegetation decreases with distance from the release point. This is a result of the lower air concentration to which the soil and vegetation were exposed during the release. At all of the sites the concentration in the vegetation is very low immediately following the release. This suggests that little H₂O in air is picked up by and leaves through exchange and that oxidation of HT in the vegetation is small. Five days later there is a significant increase in vegetation H₂O concentration. The source of the H₂O is the soil where oxidation had taken place during the release. The last samples taken at 50 meters were air dried before vacuum distillation and may not be as reliable as the earlier samples but they do show the expected pattern of decrease as the HT in the soil is depleted.

Fig. 4. Vegetation free H₂O at three distances. At a given distance the solid lines represent the northernmost samples. (Refer to Table 2 for location of samples.)

Only at the 50 meter site were the concentrations of organically bound tritium high enough to be detectable above background using γ techniques. The OBT concentration in the organic material is higher than that found in plant free-water. This may reflect the story of tritium releases in the area. It is so possible that this is another demonstration of higher tritium of combustion than free-water tritium under natural environmental conditions. The organically bound tritium increased during the first two days after the release (Fig. 5). Organically bound tritium is still increasing after the vegetation HTO has begun to decrease. Organically bound tritium is a much slower turnover than HTO in the vegetation free-water. It is likely that most of the OBT tritium is the result of photosynthetic fixation of tritium from the plant HTO. Therefore it is not surprising that by the second week, the concentration of organically bound tritium has decreased considerably. The decrease can be explained by the transport of some of the labeled compounds to other parts of the plant and the dilution of the labeled plant material with new growth which is not as highly labeled because of the decreasing HTO content in the vegetation.

Fig. 5. Organically bound tritium content of vegetation 50 m.

DISCUSSION

Apart from the discrepancy at 100 m between the LAMB and SRL air samples, the results of all the air analyses are internally consistent. It is clear that the air concentrations are higher than would be predicted by ordinary tritium conversion experiments. But much lower than had apparently resulted during the only French experiment. It appears from the recent experiment and other recent similar release experiments in Canada and France, an

field experiments involving soils that soil bacteria play an important role in elevating the concentration of HTO in the area of an HT release. In spite of the uncertainties in the HTO data presented here, there appears to be little doubt that the numbers are valid within a factor of 2 or 3 at the most.

Figure 6 shows the relationship of HT concentration in air measured by SRL during the release and HTO concentration in the vegetation five hours after the release. The slopes of the concentrations (on log-log paper) are nearly identical to those expected if soil HT oxidation is proportional to air HT concentration. This adds confidence to the rate of decrease in HT measured by the air monitors. Indirectly it also adds credence to the assertion that conversion in air of HT downwind of the release is occurring at a slow rate.

Fig. 6. Comparison of the decrease of HT with distance during the release and the decrease of peak plant free HTO.

REFERENCES

1. Canadian report in this issue of Fusion Technology.
2. A. S. Mason and H. G. Ostlund, "Atmospheric HT and HTO: Distribution and Large Scale Circulation," in Behavior of Tritium in the Environment, (IAEA, Vienna 1979), pp. 3-15.
3. C. E. Easterly, H. Gerschlager, and M. R. Bennett, "Low Concentration Conversion of Tritium Gas to Tritiated Water," Fusion Tech., Vol. 9 #2 Part 2 (1985), pp. 2564-2568.
4. G. Bardolle, "Etude des lois de diffusion du tritium et de l'eau tritiée dans l'atmosphère," Note CEA N 2107, (Fevrier 1981).