EGG-GEO--10329

DE92 019760

1

**FLAME - A FINITE ELEMENT COMPUTER CODE FOR
CONTAMINANT TRANSPORT IN VARIABLY-SATURATED MEDIA**

**Robert G. Baca
Sven O. Magnuson**

**Subsurface and Environmental Modeling Unit
Geosciences Group**

June 1992

**Idaho National Engineering Laboratory
EG&G Idaho, Inc.
P. O. Box 1625
Idaho Falls, Idaho 83415**

**Prepared for the
U. S. Department of Energy
Office of Environmental Restoration and Waste Management
Under DOE Idaho Field Office Contract No. DE-AC07-76ID01570**

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

ABSTRACT

A numerical model was developed for use in performance assessment studies at the INEL. The numerical model, referred to as the FLAME computer code, is designed to simulate subsurface contaminant transport in a variably-saturated media. The code can be applied to model two-dimensional contaminant transport in an arid site vadose zone or in an unconfined aquifer. In addition, the code has the capability to describe transport processes in a porous media with discrete fractures. This report presents the following:

- o description of the conceptual framework and mathematical theory,*
- o derivations of the finite element techniques and algorithms,*
- o computational examples that illustrate the capability of the code, and*
- o input instructions for the general use of the code.*

The development of the FLAME computer code is aimed at providing environmental scientists at the INEL with a predictive tool for the subsurface water pathway. This numerical model is expected to be widely used in performance assessments for: (1) the Remedial Investigation/Feasibility Study process and (2) compliance studies required by the U. S. Department of Energy Order 5820.2A.

Table of Contents

	Page
List of Figures	ii
1.0 INTRODUCTION	1
1.1 Background	1
1.2 Motivation	3
1.3 Objectives and Scope	4
2.0 CONCEPTUAL FRAMEWORK	5
2.1 Waste-Soil System	5
2.2 Dissolved Phase Transport	7
2.3 Colioidal Phase Transport	7
3.0 MATHEMATICAL MODELS AND ASSUMPTIONS	9
3.1 Introduction	9
3.2 Mass Transport Equation	9
3.3 Modified Governing Equation	12
4.0 FINITE ELEMENT FORMULATION	15
4.1 Computational Approach	15
4.2 Delta Form of Modified Transport Equation	17
4.3 Galerkin Weak Statement	18
4.4 Solution of Finite Element Matrix Equations	19
5.0 COMPUTATIONAL EXAMPLES	21
5.1 One-Dimensional Solute Transport	21
5.2 Two-Dimensional Transport from a Line Source	25
6.0 INPUT GUIDE	29
6.1 Introduction	29
6.2 Summary of Command Instructions	30
6.3 Description of Input Stream	30
ACKNOWLEDGMENTS	39
REFERENCES	40
APPENDIX I - SAMPLE INPUT FILES FOR TEST PROBLEMS	44
DISTRIBUTION LIST	48

Table of Contents (Continued)

List of Figures

		Page
1	Location of INEL Site and Facilities	2
2	Conceptual Model of Transport in Soil-Waste System	6
3	Types of Finite Elements used in Constructing a Computational Mesh	15
4	Superposition of Finite Elements	17
5	Imbibition and Solute Transport in a Horizontal Soil Column	21
6	Comparison of Pressure Head and Concentration Profiles computed with FLASH and PORFLOW codes	24
7	Domain and Boundary Conditions for Two-Dimensional Solute Transport Problem	25
8	Comparison of FLAME Predictions with Analytical Solution	28
9	Sample Finite Element Mesh	35

1.0 INTRODUCTION

1.1 Background

The Idaho National Engineering Laboratory (INEL), located in south central Idaho, has historically been a site of nuclear reactor and waste management research. More recently, technical programs have been focused on assessing the impact of past disposal practices and developing site clean-up plans. As part of these environmental restoration activities, technical evaluations are being conducted for the low-level radioactive, hazardous, and mixed-waste sites such as those at the Radioactive Waste Management Complex (RWMC), Test Area North (TAN), Test Reactor Area (TRA), and others, see Figure 1. These evaluations contribute to: (1) the Remedial Investigation/Feasibility Study (RI/FS) process and (2) compliance studies required by the U. S. Department of Energy (DOE) Order 5820.2A.

An important part of these evaluations, referred to as the performance assessment, is the analysis of contaminant movement from waste sites through the atmospheric, biotic, and water pathways. At the INEL, like at other DOE sites, the water pathway is the most significant (Case et al., 1989; RAE, 1990). Because of the absence of natural, surface-water features at the INEL, these performance assessments generally focus on the issue of subsurface contaminant movement in the vadose zone and in the Snake River Plain aquifer. Specific goals of the performance assessments generally include:

- o understanding the role of physical and chemical transport mechanisms,
- o assessing the rate, direction and extent of plume movement, and
- o predicting contaminant concentrations and evaluating compliance with prescribed limits.

With this information, informed decisions can be made regarding the selection of alternative actions for site clean-up and environmental restoration.

Numerical models are playing a central role in performance assessments at the INEL because of their usefulness in predicting migration of diverse contaminants in dissolved, gaseous and colloidal phases. Recent model applications for the RWMC, for example, have provided insight to: (1) water infiltration and travel times through the vadose zone (Baca et al., 1992), (2) possible effects of site flooding on migration of actinide elements (Rawson et al., 1991) and (3) assessment of organic vapor generation and movement (Walton et al., 1989).

Figure 1. Location of the INEL Site and Facilities

Flow and transport models were originally developed for use in performance assessments of waste sites at the RWMC. Recently, these models were generalized for application to other facilities at the INEL. This report describes the finite element, mass transport model referred to as the FLAME computer code. This numerical model is designed to simulate two-dimensional, solute transport in a variably-saturated hydrologic system. Some of the primary code capabilities are:

- o models mass transport in either time-dependent or steady-state flow fields,
- o accommodates advection-dominated mass transport,
- o describes mass transfer between the porous media and discrete fractures, and
- o accommodates heterogeneous media with complex stratigraphy.

The FLAME code is executed after the flow field has been defined by the companion numerical model referred to as the FLASH computer code (Baca and Magnuson, 1992).

1.2 Motivation

A large number of numerical models have been developed by the scientific community for the purpose of analyzing subsurface fluid flow and contaminant transport problems. These numerical models are described in the literature (Bachmat et al., 1980; Oster, 1982) and many are available through the International Groundwater Modeling Center, the National Water Well Association, and other sources. Most of the existing models, however, were developed for specific applications and therefore have distinct limitations. For example, many of the available transport models are limited in that they:

- o do not work well for flow regimes typical of arid sites,
- o do not accommodate strata with complex geometry, and
- o are not applicable to fractured-porous media.

Recent code testing and code benchmark studies (Magnuson et al., 1990; Baca and Magnuson, 1990) performed at the INEL suggests that relatively few mass transport models work well for a wide class of hydrogeologic conditions. Moreover, many of the existing models have limited documentation, have not been independently verified or benchmark tested, and/or are not maintained under a software quality assurance or configuration control program. Such limitations place in question the reliability of these numerical models, and therefore, on the conclusions drawn in a performance assessment.

To avoid potential model limitations and questions of reliability, the FLAME code (like its counterpart FLASH) was developed for general use at the INEL. The code is extension and refinement of a transport code (Baca and Langford, 1986; Kline et al., 1986) originally

developed by the principal author for transport modeling studies at the Hanford Site. The FLAME computer code has been thoroughly tested using the INEL's CRAFT and FORWARN FORTRAN analyzers. These tools thoroughly "interrogate" FORTRAN source code in terms of internal consistency, undefined variables, and non-standard coding. In addition, the code is currently being independently verified and benchmark tested by researchers at Washington State University. The source code is maintained under a formal software control procedure (Baca, 1990).

The development of the FLAME code is aimed at providing environmental scientists with a versatile and reliable predictive tool. This numerical model, and its counterpart, are expected to have wide applications to performance assessments and environmental restoration studies at the INEL.

1.3 Objectives and Scope

The primary objective of this report is to provide formal documentation for the FLAME computer code, Version 1.0. The scope of the documentation includes:

- o a description of the conceptual models for which the numerical model is applicable,
- o discussion of the mathematical theory and assumptions,
- o derivations of the numerical techniques and algorithms used in the code,
- o presentation of computational examples to illustrate the capability of the numerical model, and
- o input instructions for general use of the computer code.

Input files for computational examples are presented in an appendix and can be used to gain familiarity with the use of the computer code.

2.0 CONCEPTUAL FRAMEWORK

The applicability of a numerical model to diverse physical settings greatly depends on the generality of the assumed conceptual model. A useful conceptualization of how various contaminants move through the subsurface environment at the INEL can be developed by considering: (1) the dominant hydrogeologic and geochemical characteristics of the waste-soil system, (2) physical, chemical and nuclear reactions that may occur and (3) the basic assumptions needed to simplify the formulation of mathematical models. In this section, the conceptual framework used in developing the FLAME computer code is presented and explained.

2.1 Waste-Soil System

From the mid-1950's to 1970, waste management practices at the INEL generally utilized the surficial sediments for disposal of various wastes including low-level radioactive mixed-wastes, transuranic, and hazardous wastes (Vigil, 1989). At the Radioactive Waste Management Complex (RWMC), for example, wastes primarily in drums and wooden boxes were disposed of in shallow pits and trenches, and then backfilled and covered with low conductivity soils. However, recent field data indicates that various contaminants have migrated away from certain disposal sites (Laney et al., 1988). Rawson et al. (1991) has summarized radionuclide data from samples collected beneath a pit. These data show well defined activity profiles of actinide element concentrations that decrease monotonically with depth. Other field data at the RWMC confirm that trace amounts of actinide elements have been transported downward as far as the so-called 110 foot (34 m) interbed.

It is, therefore, realistic and conservative to assume that the buried waste is in direct contact with the pore-water in the surficial sediments. This assumption is also supported by direct observations of container integrity made in retrieval demonstrations (McKinley and McKinney, 1978). How fast the contaminants may be moving away from the disposal sites is an important performance assessment issue. To predict these release rates, a numerical model must describe the contaminant release rate as a direct function of such factors as:

- o infiltration rate and moisture content level,
- o phase(s) of the contaminants and nature of chemical reactions, and
- o solubility and sorption properties of the chemical species,

A conceptual representation of the important transport and chemical phenomena in the soil-waste system is illustrated in Figure 2.

Figure 2. Conceptual Model of Transport in Soil-Waste System

Recharge waters from rain fall, snow melt and, in rare instances, from site flooding result in leaching of the wastes and mobilization of dissolved phase contaminants. Rapid infiltration of meteoric waters can create suspensions of contaminants in colloidal phases. Similarly, diffusive transport of gaseous phase contaminants (eg., chlorinated hydrocarbons) may be enhanced by the movement of wetting fronts through the vadose zone. Consequently, the patterns of contaminant transport in all three phases are highly dependent on the rates and directions of pore-water movement. It is presently believed that, under unsaturated conditions, pore-water will move through the rock matrix; while, in saturated conditions, the water will preferentially move through interconnected fractures.

2.2 Dissolved Phase Transport

The mechanics of solute transport in porous media (Bear, 1972) have been studied by researchers for many years and individual processes are relatively well defined. A number of distinct conceptual approaches have been proposed to describe solute transport in fractured-permeable media. Two primary approaches that have been widely used to model solute transport in variably saturated, fractured-media are: (1) equivalent porous continuum and (2) discontinuum or discrete fracture networks with parallel plate analogy. The latter approach is adopted in the FLAME code. In utilizing the discontinuum approach, it is usually necessary to assume that each fracture behaves like a one-dimensional porous medium with hydraulic properties typical of a highly conductive and drainable material.

In both porous and fractured media, the accepted conceptualization (Cushman, 1990) of dissolved phase transport considers the following processes:

- o Leaching of contaminants from the waste form,
- o Advection and hydrodynamic dispersion in hydraulically interconnected pores and fractures,
- o Attenuation by chemical reaction, i.e., adsorption and desorption, and
- o Loss by radioactive decay.

Since advection and dispersion are functions of the pore-water velocity, the flow field through the medium is assumed to be known.

2.3 Colloidal Phase Transport

Contaminants in colloidal form, i.e., small particles typically less than 1 μm in diameter, can be transported through porous media as particulate suspensions (McDowell-Boyer et al., 1986). Rapid transport of radiocolloids have been observed at the Oak Ridge National Laboratory, Los Alamos National Laboratories and other waste sites. Natural colloids are also capable of mediating the transport of heavy metals and transuranics because of their high sorptive capability, (McCarthy and Zachara, 1989). At the INEL, the trace levels of americium and plutonium found in soil samples from the 110 ft interbed may also be due to colloid transport (Rawson et al., 1991).

Colloids moving in pore-water are subject to a variety of interactions which influence their transport rates. Available studies (Sharma and Yortsos, 1987; McDowell-Boyer et al., 1986) suggest that these interactions include:

- o colloid formation by hydrolysis and condensation,
- o colloid-colloid interaction and agglomeration,

- o attachment and de-attachment on surfaces of immobile soil particles,
- o filtration or particle trapping, and
- o advection and dispersion.

Most math models of radiocolloid transport (Travis and Nuttall, 1985) in porous media and in discrete fractures (Bonano and Beyeler, 1989) have utilized some variation of the simple "filtration model" (Herzig et al., 1970). In this modeling approach, colloid transport is modeled as a advection-dispersion equation with a single attenuation mechanism, i.e., particle loss or trapping.

3.0 MATHEMATICAL MODELS AND ASSUMPTIONS

3.1 Introduction

Performance assessment of waste sites often involves predicting the movement of diverse contaminants in various chemical forms and phases, i.e., dissolved, gaseous, and/or colloidal phases. Subsurface transport of contaminants in these different phases is described by the single and multicomponent forms of the "advection-dispersion" equation. The FLAME code is designed to solve the advection-dispersion equation in two-dimensions, in Cartesian or radial coordinates, for transient or steady-state conditions. The FLAME code produces computations of contaminant concentrations at the node or mesh points. Contaminant fluxes at specific boundaries can be computed separately by post-processing the code results.

3.2 Mass Transport Equation

Mathematical models of contaminant transport in variably-saturated porous media are generally based on the mass conservation principle, an analog to Fickian diffusion (Bear, 1972) and the chemical laws applicable to the particular contaminant species. The application of these concepts and consideration of various attenuation mechanisms (i.e., sorption, decay, chemical transformations, etc) produce a advection-dispersion equation. In general multicomponent form, this equation for a contaminant dissolved in the pore-fluid is given by:

$$R_{di} \frac{\partial(\theta C_i)}{\partial t} + \nabla \cdot (\bar{q} C_i) = \nabla \cdot (\bar{D} \nabla C_i) - R_{di} \theta \lambda_i C_i + \dot{M}_i \quad (1)$$

where

C_i is the concentration (g/cm³) of the i-th component,

R_{di} is the retardation factor for i-th component,

θ is the volumetric moisture content,

$\bar{q}$ is the Darcian flux vector (cm/s),

$\bar{D}$ is the hydrodynamic dispersion tensor (cm²/s),

λ_i is the decay rate (1/s), and

$\dot{M}_i$ is a generalized source/sink term (g/cm³-s).

The source/sink term is given by the formula:

$$\dot{M}_i = m_i + \sum_{j=1}^N f_{ij} \lambda_j R_{dj} \theta C_j \quad (2)$$

with N designating the number of other components decaying to i -th component, f_{ij} fraction of component j which decays to component i , and m_i is the volumetric source term ($\text{g}/\text{cm}^3\text{-s}$).

The two-dimensional, single-component form of the governing equation written in Cartesian coordinates for the vertical plane is:

$$\begin{aligned} R_d \frac{\partial(\theta C)}{\partial t} + \frac{\partial}{\partial x}(q_x C) + \frac{\partial}{\partial z}(q_z C) = \frac{\partial}{\partial x} \left(D_{xx} \theta \frac{\partial C}{\partial x} \right) + \frac{\partial}{\partial x} \left(D_{xz} \theta \frac{\partial C}{\partial z} \right) \\ + \frac{\partial}{\partial z} \left(D_{zx} \theta \frac{\partial C}{\partial x} \right) + \frac{\partial}{\partial z} \left(D_{zz} \theta \frac{\partial C}{\partial z} \right) - R_d \theta \lambda C + \dot{m} \end{aligned} \quad (3)$$

Individual terms in this equation will be discussed first and will be followed by the underlying assumptions. The retardation coefficient R_d accounts for the fraction of contaminant mass adsorbed onto the solid phase. For a porous medium this coefficient is defined by

$$R_d = 1 + \frac{\rho_b k_d}{\theta} \quad (4)$$

where k_d is the material dependent distribution coefficient (cm^3/g) and ρ_b is the bulk density of the porous medium (g/cm^3). In discrete fractures, the degree of adsorption is less because of reduced surface area. In this case, the retardation factor is best approximated by

$$R_d = 1 + \frac{2k_a}{b} \quad (5)$$

where k_a is the distribution coefficient on a per-unit-surface area basis (Freeze and Cherry, 1979, p. 410) and b is the average fracture aperture.

The dispersion tensor $\overline{D}$ accounts for both mechanical dispersion and molecular diffusion. Components of the tensor are computed using the relationship (Scheidegger, 1961; Bear, 1972):

$$D_{xx} = \frac{\alpha_L}{\theta} \frac{q_x^2}{|q|} + \frac{\alpha_T}{\theta} \frac{q_z^2}{|q|} + \tau_x D_m \quad (6)$$

$$D_{zz} = \frac{\alpha_L}{\theta} \frac{q_z^2}{|q|} + \frac{\alpha_T}{\theta} \frac{q_x^2}{|q|} + \tau_z D_m \quad (7)$$

$$D_{xx} = D_{xx} = \frac{(\alpha_L - \alpha_T) q_x q_z}{\theta |q|} \quad (8)$$

where α_L and α_T are the longitudinal and transverse dispersivities (cm), $|q|$ is the absolute value (magnitude) of the Darcian flux vector (cm/s), τ_x and τ_z are the tortuosities in the x- and z-directions, and D_m is the molecular diffusion coefficient of the contaminant in water (cm²/s)

Detailed derivations of the advection-dispersion equation can be found in various porous media textbooks (Bear, 1972) and in the technical literature (van Genuchten, 1988; Celia, et al., 1990). With regards to the transport and interaction of the contaminant, the above mathematical theory makes several assumptions. Some of the fundamental assumptions are:

- o Contaminant concentrations are low enough that the fluid flow is independent of solute concentrations,
- o Dispersion induced by fluid flow is described by a Fickian type flux law,
- o Sorption of the contaminant onto the porous medium is an equilibrium process described by a linear isotherm,
- o Fluid properties are independent of temperature, and
- o Transport properties of the porous continuum are volume averages.

It is also assumed that the flow field is known so that the Darcy flux vector can be specified as an input quantity. The above model also applies to areal groundwater flow systems under the assumption that the changes in the water level elevation are small compared to the total head.

To complete the mathematical formulation, boundary conditions must be specified. The code accommodates the following two types of boundary conditions:

1. Dirichlet or specified concentrations

$$C = C(x_b, z_b, t) \quad (9)$$

2. Neumann or prescribed mass flux

$$\begin{aligned} -\theta \left(D_{xx} \frac{\partial C}{\partial x} + D_{xz} \frac{\partial C}{\partial z} \right) n_x - \theta \left(D_{zx} \frac{\partial C}{\partial x} + D_{zz} \frac{\partial C}{\partial z} \right) n_z \\ + (q_x C) n_x + (q_z C) n_z = m_f \end{aligned} \quad (10)$$

where x_b and z_b are the coordinates of the boundary with Dirichlet boundary conditions; n_x and n_z are the components of the outward pointing unit normal; m_f is the net mass flux across the domain boundary.

By properly defining the coefficients of the advection-dispersion equation, the FLAME code can be applied to model transport of contaminants in gaseous and colloidal phases. For example, Walton et al. (1989) modeled the transport of organic vapors from INEL's Radioactive Waste Management Complex using a advection-dispersion formulation.

3.3 Modified Governing Equation

Numerical solution of the advection-dispersion equation using conventional computational techniques generally exhibit oscillations (Pinder and Gray, 1977). These oscillations are most severe when the convective flux is substantially greater than the dispersive flux. Numerical problems associated with advection dominated transport can be reduced by using the "modified equation approach" of computational fluid dynamics (Fletcher, 1988). This approach builds in a dissipation mechanism into the governing equation, which when approximated by a finite element method, will produce an algorithm that damps out spurious oscillations.

In deriving the semi-discrete modified transport equation, the approach of Donea (1984) has been used. A derivation for the two-dimensional case is presented here to explain the approach. Begin by considering transport equation for pure advection:

$$\frac{\partial C}{\partial t} + u \frac{\partial C}{\partial x} + v \frac{\partial C}{\partial z} = 0 \quad (11)$$

where

$$u = \frac{q_x}{R_d \theta} \quad v = \frac{q_z}{R_d \theta} \quad (12)$$

The spatial variation of the fluid velocity u and v are assumed to be negligible. The above transport equation, written in subscript notation, is

$$C_t + u C_x + v C_z = 0 \quad (13)$$

Next, the state variable C is expressed by the following Taylor series

$$C^{n+1} = C^n + \Delta t C_t^n + \frac{\Delta t^2}{2} C_{tt}^n + \frac{\Delta t^3}{6} C_{ttt}^n + \dots \quad (14)$$

and

$$C^n = C^{n+1} - \Delta t C_t^{n+1} + \frac{\Delta t^2}{2} C_{tt}^{n+1} - \frac{\Delta t^3}{6} C_{ttt}^{n+1} + \dots \quad (15)$$

A discretized form of C_t is developed by subtracting the two Taylor series

$$\frac{C^{n+1} - C^n}{\Delta t} = \frac{1}{2}(C_t^n + C_t^{n+1}) + \frac{\Delta t}{4}(C_{tt}^n - C_{tt}^{n+1}) + \frac{\Delta t^2}{12}(C_{ttt}^n + C_{ttt}^{n+1}) \quad (16)$$

Expressions for the time derivatives C_t , C_{tt} and C_{ttt} are derived using the original partial differential equation. For example, the first derivative of C is obtained by simply rearranging equation (11),

$$C_t = -u C_x - v C_z \quad (17)$$

It follows that the second derivative term is

$$C_{tt} = u^2 C_{xx} + 2uv C_{xz} + v^2 C_{zz} \quad (18)$$

Similarly, the third derivative is

$$C_{ttt} = u^2(C_t)_{xx} + 2uv(C_t)_{xz} + v^2(C_t)_{zz} \quad (19)$$

Inserting the above expressions into equation (16), then one obtains the expression

$$\begin{aligned} \frac{C^{n+1} - C^n}{\Delta t} = & -\frac{1}{2}[u(C_x^n + C_x^{n+1}) + v(C_z^n + C_z^{n+1})] \\ & + \frac{\Delta t}{4}[u^2(C_{xx}^n - C_{xx}^{n+1}) + 2uv(C_{xz}^n - C_{xz}^{n+1}) + v^2(C_{zz}^n - C_{zz}^{n+1})] \\ & + \frac{\Delta t^2}{12}[u^2(C_t^n + C_t^{n+1})_{xx} + 2uv(C_t^n + C_t^{n+1})_{xz} + v^2(C_t^n + C_t^{n+1})_{zz}] \end{aligned} \quad (20)$$

In the above equation, the velocities are treated as locally fixed in time. The discretized time derivative can be related to continuous derivatives by

$$\frac{1}{2}(C_t^n + C_t^{n+1}) \approx \frac{C^{n+1} - C^n}{\Delta t} \quad (21)$$

which, in essence, is the Crank-Nicolson approximation. With the above expressions, the modified convective-transport equation is written in a semi-discrete form as

$$\begin{aligned} \left(1 - \frac{u^2 \Delta t^2}{6} \partial_{xx} - \frac{uv \Delta t^2}{3} \partial_x \partial_z - \frac{v^2 \Delta t^2}{6} \partial_{zz}\right) \frac{C^{n+1} - C^n}{\Delta t} = & -\frac{1}{2}[u(C_x^n + C_x^{n+1}) + v(C_z^n + C_z^{n+1})] \\ & + \frac{\Delta t}{4}[u^2(C_{xx}^n - C_{xx}^{n+1}) + 2uv(C_{xz}^n - C_{xz}^{n+1}) + v^2(C_{zz}^n - C_{zz}^{n+1})] \end{aligned} \quad (22)$$

The final modified governing equation is obtained by introducing the contributions for hydrodynamic dispersion, radioactive decay and mass sources. Thus, the previous equation becomes:

$$\begin{aligned}
& \left(1 - \frac{u^2 \Delta t^2}{6} \partial_{xx} - \frac{uv \Delta t^2}{3} \partial_x \partial_z - \frac{v^2 \Delta t^2}{6} \partial_{zz} \right) \frac{C^{n+1} - C^n}{\Delta t} = -\frac{1}{2} [u(C_x^n + C_x^{n+1}) + v(C_z^n + C_z^{n+1})] \\
& + \frac{\Delta t}{4} [u^2(C_{xx}^n - C_{xx}^{n+1}) + 2uv(C_{xz}^n - C_{xz}^{n+1}) + v^2(C_{zz}^n - C_{zz}^{n+1})] \\
& + \frac{1}{2} (D_{xx} C_x^n + D_{xx} C_x^{n+1})_x + \frac{1}{2} (D_{xz} C_z^n + D_{xz} C_z^{n+1})_x \\
& + \frac{1}{2} (D_{zx} C_x^n + D_{zx} C_x^{n+1})_z + \frac{1}{2} (D_{zz} C_z^n + D_{zz} C_z^{n+1})_z \\
& - \frac{\lambda}{2} (C^n + C^{n+1}) + \dot{m}
\end{aligned} \tag{23}$$

It should be noted that the expressions in equation (1) containing dispersion, decay and mass sources have been divided by $R_d \theta$.

The new terms that appear in this modified equation play a major role in assuring a stable numerical algorithm and in damping oscillations. From a von Neumann analysis for the one-dimensional equation, Donea (1984) has shown that the above formulation is unconditionally stable and fourth-order accurate. This modified equation can also be derived using the more general Taylor Weak Statement approach of Baker and Kim (1987).

4.0 FINITE ELEMENT FORMULATION

The computational approach implemented in the FLAME code is based on the Galerkin finite element method (Fletcher, 1984). This finite method used in conjunction with the modified partial differential equation for mass transport. This combination of techniques was selected because of their superior capabilities to accommodate the complex geometries and to yield accurate solutions for advection dominated transport. This section describes the basic aspects of the computational approach, numerical techniques and selected aspects of computer implementation.

4.1 Computational Approach

The finite element method (Burnett, 1987) is an integral based method for constructing computational algorithms for solving linear and nonlinear partial differential equations. The algorithms produce approximate solutions on a computational mesh composed of an appropriate combination of quadrilateral, triangular and/or linear elements. In the FLAME computer code, these elements may have straight or curved sides. These computational elements are illustrated in the Figure 3.

Figure 3. Types of Finite Elements used in Constructing a Computational Mesh

The finite element algorithm was developed by applying the Galerkin method of weighted residuals (Baker, 1983) for the mass transport equation. The fundamental concept is to form a functional χ as the integral of the product of the residual error ϵ and a set of weighting functions ω_j . The Galerkin functional is

$$\chi = \int_{\mathfrak{R}} \epsilon \omega_j d\bar{x} \quad (1)$$

where $\mathfrak{R}$ is the domain of interest, ϵ is formed directly from the governing equations, and $\bar{x}$ represents the generalized spatial coordinates (x, y, z) . Baca et al. (1984) demonstrated that a direct superposition approach can be used to construct a functional equation that specifically applies to flow and transport in a "fractured-porous" media.

A Galerkin weak statement specifically applicable to fractured-porous media χ_{fp} was formulated as

$$\chi_{fp} = \int_{\Omega_c} \epsilon^c \omega_j dR + \int_{\Omega_d} \epsilon^d \omega_j dl \quad (2)$$

where ϵ^c and ϵ^d are the residual error terms for the continuum domain Ω_c and discrete domain Ω_d , respectively.

In accordance with the finite element procedure (Burnett, 1987), the weak statement is partitioned into subdomains or finite elements so that

$$\chi_{fp} = \chi_{fp,1} + \chi_{fp,2} + \chi_{fp,3} + \dots + \chi_{fp,M} = \sum_{i=1}^M \chi_{fp,i} \quad (3)$$

where M is the total number of elements. Setting $\chi_{fp} = 0$ imposes a requirement of orthogonality so that the weak statement becomes an error distribution principle (Collatz, 1960) by which the residual ϵ is minimized over the domain $\mathfrak{R} = \Omega_c \cup \Omega_d$.

In this approach, the continuum domain is represented by a mesh of two-dimensional, isoparametric, finite elements (eg., quadrilaterals and/or triangles) whereas, the discrete domain is represented by a network of line elements. The computational mesh used in this approach is the same as any standard finite element mesh with the exception that the line elements are superimposed along the boundaries of the two-dimensional elements, as shown in Figure 4. Because the two types of elements share the same nodes, mass balance between the two elements is automatically enforced.

Figure 4. Superposition of Finite Elements

4.2 Delta Form of Modified Transport Equation

Prior to applying the Galerkin finite element procedure, it is advantageous to cast the modified governing equation in a "delta form." The delta form, as used here, refers to the incremental change in the state variable. Thus, the new state variable is defined as

$$\delta = C^{n+1} - C^n \quad (4)$$

Using this definition, the modified governing equation (23) (in section 3.3) is written as:

$$\begin{aligned} \left(1 - \frac{u^2 \Delta t^2}{6} \partial_{xx} - \frac{uv \Delta t^2}{3} \partial_x \partial_z - \frac{v^2 \Delta t^2}{6} \partial_{zz} \right) \frac{\delta}{\Delta t} = & -\frac{1}{2} [u(C_x^n + C_x^{n+1}) + v(C_z^n + C_z^{n+1})] \\ & - \frac{\Delta t}{4} [u^2 \delta_{xx} + 2uv \delta_{xz} + v^2 \delta_{zz}] \\ & + \frac{1}{2} (D_{xx} C_x^n + D_{xx} C_x^{n+1})_x + \frac{1}{2} (D_{xz} C_z^n + D_{xz} C_z^{n+1})_x \\ & + \frac{1}{2} (D_{zx} C_x^n + D_{zx} C_x^{n+1})_z + \frac{1}{2} (D_{zz} C_z^n + D_{zz} C_z^{n+1})_z \\ & - \frac{\lambda}{2} (C^n + C^{n+1}) + \dot{m} \end{aligned} \quad (5)$$

Adding and subtracting the appropriate quantities from the right-hand side produces the compact expression

$$\begin{aligned} & \left(1 - \frac{u^2 \Delta t^2}{6} \partial_{xx} - \frac{uv \Delta t^2}{3} \partial_x \partial_z - \frac{v^2 \Delta t^2}{6} \partial_{zz}\right) \frac{\delta}{\Delta t} - \frac{1}{2} [u \delta_x + v \delta_z] \\ & + \frac{1}{2} \left(D_{xx} - \frac{u^2 \Delta t}{2}\right) \delta_{xx} + \left(D_{xz} - \frac{uv \Delta t}{4}\right) \delta_{xz} + \frac{1}{2} \left(D_{zz} - \frac{v^2 \Delta t}{2}\right) \delta_{zz} - \frac{\lambda}{2} \delta + \dot{m} \\ & - u C_x^n - v C_z^n + (D_{xx} C_x^n + D_{xz} C_z^n)_x + (D_{xz} C_x^n + D_{zz} C_z^n)_z - \lambda C^n + \dot{m} \end{aligned} \quad (6)$$

After solving this equation by the finite element method, the solution for concentration at the node points is recovered from the simple formula:

$$C^{n+1} = C^n + \delta \quad (7)$$

The above delta formulation has a number of advantages relative to computer implementation. Two of the more important ones are associated with computational accuracy and incorporation of Dirichlet boundary conditions in the matrix equations.

4.3 Galerkin Weak Statement

The weak statement for the modified governing equation is developed from the Galerkin functional equation:

$$\begin{aligned} & \int_{\Omega_e} \left\{ \left(1 - \frac{u^2 \Delta t^2}{6} \partial_{xx} - \frac{uv \Delta t^2}{3} \partial_x \partial_z - \frac{v^2 \Delta t^2}{6} \partial_{zz}\right) \frac{\delta}{\Delta t} + \frac{1}{2} (u \delta_x + v \delta_z) \right\} \omega_j d\bar{x} \\ & - \int_{\Omega_e} \left\{ \frac{1}{2} \left(D_{xx} - \frac{u^2 \Delta t}{2}\right) \delta_{xx} + \left(D_{xz} - \frac{uv \Delta t}{4}\right) \delta_{xz} + \frac{1}{2} \left(D_{zz} - \frac{v^2 \Delta t}{2}\right) \delta_{zz} - \frac{\lambda}{2} \delta \right\} \omega_j d\bar{x} \\ & - \int_{\Omega_e} \left\{ -u C_x^n - v C_z^n + (D_{xx} C_x^n + D_{xz} C_z^n)_x + (D_{xz} C_x^n + D_{zz} C_z^n)_z - \lambda C^n + \dot{m} \right\} \omega_j d\bar{x} \end{aligned} \quad (8)$$

Applying the divergence theorem to reduce the second-order derivatives, the final form of the Galerkin weak statement is obtained:

$$\begin{aligned}
& \int_{\Omega_e} \frac{1}{\Delta t} \left\{ \omega_j \delta + \frac{u^2 \Delta t^2}{6} \frac{\partial \omega_j}{\partial x} \frac{\partial \delta}{\partial x} + \frac{uv \Delta t^2}{6} \left(\frac{\partial \omega_j}{\partial x} \frac{\partial \delta}{\partial z} + \frac{\partial \omega_j}{\partial z} \frac{\partial \delta}{\partial x} \right) + \frac{v^2 \Delta t^2}{6} \frac{\partial \omega_j}{\partial z} \frac{\partial \delta}{\partial z} \right\} d\bar{x} \\
& + \frac{1}{2} \int_{\Omega_e} \omega_j \left(u \frac{\partial \delta}{\partial x} + v \frac{\partial \delta}{\partial z} \right) d\bar{x} \\
& + \frac{1}{2} \int_{\Omega_e} \left\{ \left(D_{xx} - \frac{u^2 \Delta t}{2} \right) \frac{\partial \omega_j}{\partial x} \frac{\partial \delta}{\partial x} + \left(D_{xx} - \frac{uv \Delta t}{4} \right) \left(\frac{\partial \omega_j}{\partial x} \frac{\partial \delta}{\partial z} + \frac{\partial \omega_j}{\partial z} \frac{\partial \delta}{\partial x} \right) + \left(D_{xx} - \frac{v^2 \Delta t}{2} \right) \frac{\partial \omega_j}{\partial z} \frac{\partial \delta}{\partial z} + \lambda \omega_j \delta \right\} d\bar{x} \\
& + \int_{\Omega_e} \omega_j \left\{ u C_x^n + v C_z^n - (D_{xx} C_x^n + D_{xz} C_z^n)_x - (D_{xz} C_x^n + D_{zz} C_z^n)_z + \lambda C^n - \dot{m} \right\} d\bar{x} \\
& - \int_{\partial \Omega_e} \omega_j \left\{ \left(D_{xx} \frac{\partial \delta}{\partial x} + D_{xz} \frac{\partial \delta}{\partial z} \right) n_x + \left(D_{xz} \frac{\partial \delta}{\partial x} + D_{zz} \frac{\partial \delta}{\partial z} \right) n_z \right\} dS = 0 \quad (9)
\end{aligned}$$

The area integrals, in the above equation apply to each finite element in the domain Ω_e ; whereas, the surface integral applies to that portion of the element boundary $\partial \Omega_e$ where mass fluxes are specified.

In the above equation, the concentration distribution over each finite element is approximated by

$$C(\bar{x}, t) = \sum_{i=1}^N \omega_i C_i \quad (10)$$

where N is number of node points, ω_i is the set of basis functions and C_i is the set of concentration values at the node points. The basis functions are selected to be the same as the weighting functions, as required by the Galerkin procedure. Integration of these expressions are performed using Gauss-Legendre quadrature.

4.4 Solution of Finite Element Matrix Equations

The numerical integration of the finite element equations produces a large system of algebraic equations of the form

$$[A] \{x\} = \{b\} \quad (11)$$

The coefficient matrix $[A]$ is a banded, sparse matrix which contains the assembly of the elemental matrices for all finite elements in the mesh. The $\{x\}$ and $\{b\}$ vectors are the solution vector and load vector, respectively. For the advection-dispersion equation, the

finite element method produces a coefficient matrix that is banded and unsymmetric. The resulting system of equations are solved by a Gaussian elimination procedure without pivoting.

Two distinct algorithms are implemented in the computer code. The first method is a standard band solver algorithm that utilizes a skyline storage scheme (Tewarson, 1973). This solver is very fast but can be limited by the bandwidth of the $[A]$; the bandwidth is direct function of the node numbering. The second method is referred to as the frontal method (Hinton and Owen, 1977; Hood, 1976). This method, in general, is slower than the band solver but has the advantage that it is independent of bandwidth and requires much less storage. In the frontal method, the elimination process is carried out according to the element numbering.

Algorithms for minimizing matrix bandwidth (Cuthill, 1972; Gibbs et al., 1976) exist that use strategies for optimizing the node number ordering. Similarly, techniques for minimizing the front width are based on reordering of element numbers (King, 1970). For problems with very large matrices, these minimization techniques often produce significant reductions of simulation run times.

5.0 COMPUTATIONAL EXAMPLES

A set of computational examples are provided in this section to demonstrate the basic capability of the FLAME computer code. These examples illustrate applications to contaminant transport problems in both partially saturated and fully saturated regimes. Solutions generated by the FLAME code are compared to those obtained with analytical or benchmark numerical solutions. The input files for these computational examples are presented in Appendix I.

5.1 One-Dimensional Solute Transport During Imbibition

5.1.1 Problem Statement

As a first computational example, flow and transport in a horizontal, unsaturated, soil-column is considered. The physical setting is depicted in Figure 5. Water carrying a conservative solute is imbibed into the homogeneous soil resulting in the propagation of wetting and solute fronts. The rate of wetting front propagation is controlled by the soil-hydraulic properties and the action of capillary forces. The solute front propagates and spreads in response to the fluid velocity, moisture content level, and the diffusion process.

This computational example was originally used by Huyakorn et al. (1985) to test the mass balance accuracy and efficiency of finite element techniques. The example is a good test case because it requires tracking sharp wetting and solute fronts. Sharp fronts are a common characteristic of most practical model applications, particularly in arid site vadose zones.

Figure 5. Imbibition and Solute Transport in a Horizontal Soil Column

Unsaturated flow and solute transport processes in the soil column are mathematically described by the one-dimensional form of Richards' equation for flow and the advection-diffusion equation for the solute transport. Purely horizontal flow in the porous medium is described by:

$$c(\psi) \frac{\partial \psi}{\partial t} = \frac{\partial}{\partial x} \left[K(\psi) \frac{\partial \psi}{\partial x} \right]$$

where ψ is the pressure head, $K(\psi)$ is the unsaturated hydraulic conductivity, t is time, and x is the horizontal distance along the column. The specific moisture capacity $c(\psi)$ is defined by $c(\psi) = \partial \theta / \partial \psi$; θ is the volumetric moisture content. The boundary conditions are

$$\psi(0, t) = \psi_b$$

$$\psi(L, t) = \psi_i$$

where L is the length of the soil column. As indicated above, the left boundary is fixed at a pressure head of ψ_b , whereas, the right boundary is held at the initial value ψ_i .

The numerical solution of the flow equation defines the fluid velocity throughout the soil column. Fluid flux, q_x , is evaluated at node points using the computed pressure head values and Darcy's law:

$$q_x = -K(\psi) \frac{\partial \psi}{\partial x}$$

Solute transport in the one-dimensional soil column is a simplified form of the general mass transport equation:

$$\frac{\partial(\theta C)}{\partial t} + \frac{\partial}{\partial x}(q_x C) = \frac{\partial}{\partial x} \left(D_m \theta \frac{\partial C}{\partial x} \right)$$

where θ is the moisture content, q_x is the Darcian flux in the x -direction, and D_m is the molecular diffusion coefficient. Applicable boundary conditions are

$$C(0, t) = C_o$$

$$\frac{\partial C(L, t)}{\partial x} = 0$$

with C_o and C_i are the boundary and initial solute concentrations, respectively.

5.1.2 Benchmark Numerical Solution

Huyakorn et al. (1985) have presented numerical solutions and graphical results for this computational example. However, for the purpose of making more direct comparisons, the PORFLOW code developed by Runchal and Sagar (1991) was used to simulate this problem and provide a benchmark numerical solution. For simplicity, the 20 cm model domain was subdivided into 100 elements with a 0.20 cm grid node spacing. The PORFLOW code was run with a constant time-step of 200 seconds to produce the pressure head and solute concentration profiles at selected time planes.

Hydraulic properties assigned to the idealized soil column were taken from Huyakorn, et al. (1985). For convenience, the analytical functions for the characteristic and hydraulic conductivity curves used by the authors were converted to equivalent van Genuchten/Mualem formulas (van Genuchten, 1980). These formulas are given by:

$$\theta(\psi) = \theta_r + \frac{\theta_s - \theta_r}{[1 + (\alpha |\psi|)^n]^m}$$
$$K(\psi) = K_s \frac{\{1 - (\alpha |\psi|)^{n-1} [1 + (\alpha |\psi|)^n]^m\}^2}{[1 + (\alpha |\psi|)^n]^{m/2}}$$

where θ is the volumetric moisture content, θ_r is the residual moisture content, θ_s is the saturated water content or porosity, and the α , n and m are fitting parameters.

Specific values used in this computational example were $\alpha = .0242$, $n = 1.9756$, $\theta_s = 0.45$ and $\theta_r = 10^{-4}$. The fitting parameter m is computed from $m = 1 - 1/n$. The specific storage, S_s , saturated hydraulic conductivity, K_s , were set to values of $1 \times 10^{-5} \text{ cm}^{-1}$ and $1.1574 \times 10^{-5} \text{ cm/s}$ (1 cm/day), respectively. The inlet and outlet boundary pressure heads were set at $\psi_b = 0.0 \text{ cm}$ and $\psi_i = -83.33 \text{ cm}$, respectively. The molecular diffusion coefficient was $D_m = 1.1574 \times 10^{-5} \text{ cm}^2/\text{s}$ (1 cm²/day).

5.1.3 Numerical Solution

The FLAME computer code was setup to simulate the one-dimensional solute transport problem for the required simulation period. A finite element mesh composed of equally spaced, line-elements was superimposed on the domain of the soil column. The time varying Darcy flux and moisture content for the domain were generated separately by the FLASH code (Baca and Magnuson, 1992) and used as input to the FLAME code. In the numerical simulation, the time steps were automatically varied by the code. Comparisons of the numerical and benchmark results are shown in Figure 6.

Figure 6. Comparison of Pressure Head and Concentration Profiles computed with FLASH and PORFLOW codes

Pressure heads and solute concentration profiles computed with the FLASH and FLAME codes were compared with those of the benchmark solution. Comparisons of the two numerical solutions was made for three specific time planes: $t = 5 \times 10^3$, 5×10^4 , and 1×10^5 seconds. Exceptionally good agreement was indicated for both pressure head and relative solute concentration computations.

5.2 Two-Dimensional Transport from a Line Source

5.2.1 Problem Statement

This computational example considers the problem of modeling two-dimensional transport in a saturated porous medium. The domain is a rectangular region with unidirectional, steady-state flow. Inflow and outflow occur at the lateral boundaries; the top and bottom of the domain are no flux boundaries. Solute is introduced along a slot, labeled "b", at the inflow boundary, as illustrated in Figure 7. A solute plume evolves from the slot and spreads as it moves towards the outflow boundary. This computational example is a good test of the codes' capability to describe advection and dispersion in two-dimensions.

Figure 7. Domain and Boundary Conditions for Two-Dimensional Solute Transport Problem

Formulated as boundary value problem, the mass transfer is modeled by a advection-dispersion equation of the form:

$$\frac{\partial C}{\partial t} + u \frac{\partial C}{\partial x} = D_{xx} \frac{\partial^2 C}{\partial x^2} + D_{zz} \frac{\partial^2 C}{\partial z^2}$$

Fluid flow in the saturated porous domain is assumed to be known with pore fluid velocities of $u = \text{constant}$ and $v = 0$. The initial and boundary conditions are

$$C(x, z, 0) = 0$$

$$C(0, z, t) = C_o \quad \text{for } 0 \leq z \leq b$$

$$C(0, z, t) = 0 \quad \text{for } b < z \leq B$$

$$\frac{\partial C(x, 0, t)}{\partial z} = 0$$

$$\frac{\partial C(x, B, t)}{\partial z} = 0$$

The length parameters b and B are defined in Figure 7. The analytical solution for this boundary value problem was evaluated at selected grid points for comparison to the numerical solution generated by the FLAME code.

5.2.2 Analytical Solution

This transient, two-dimensional boundary value problem was solved analytically by Bruch and Street (1967). The solution consists of an infinite series of the form:

$$\begin{aligned} C(x, z, t) = & \frac{bC_o}{2B} \operatorname{erfc} \left[\frac{x - ut}{2(D_{xx}t)^{1/2}} \right] + \frac{bC_o}{2B} \exp \left(\frac{ux}{D_{xx}} \right) \operatorname{erfc} \left[\frac{x + ut}{2(D_{xx}t)^{1/2}} \right] \\ & + \frac{1}{2} \sum_{n=1}^{\infty} \left(F_n \cos \frac{n\pi z}{B} \right) \exp \left[\frac{1}{2} \left(\frac{u}{D_{xx}} - J_n \right) x \right] \operatorname{erfc} \left[\frac{x - J_n D_{xx} t}{2(D_{xx}t)^{1/2}} \right] \\ & + \frac{1}{2} \sum_{n=1}^{\infty} \left(F_n \cos \frac{n\pi z}{B} \right) \exp \left[\frac{1}{2} \left(\frac{u}{D_{xx}} + J_n \right) x \right] \operatorname{erfc} \left[\frac{x + J_n D_{xx} t}{2(D_{xx}t)^{1/2}} \right] \end{aligned}$$

In this expansion, the coefficients J_n and F_n are given by

$$J_n = \left[\left(\frac{u}{D_{xx}} \right)^2 + \frac{4n^2\pi^2 D_{zz}}{B^2 D_{xx}} \right]^{1/2}$$

$$F_n = \frac{2C_o}{\pi n} \sin \frac{n\pi b}{B}$$

The above analytical solution was evaluated using the following geometric parameter values:

$$b = 1 \text{ cm}$$

$$B = 6 \text{ cm}$$

$$L = 30 \text{ cm}$$

Transport parameters were set at values of

$$u = 0.2 \text{ cm/s}$$

$$D_{xx} = 50 \text{ cm}^2/\text{s}$$

$$D_{zz} = 5 \text{ cm}^2/\text{s}$$

$$D_{xz} = D_{zx} = 0$$

A computer program, EXACT, was written to evaluate the analytical solution. The analytical solution was evaluated on a rectangular grid for the purpose of comparison to the numerical model.

5.2.3 Numerical Solution

The FLAME computer code was setup to simulate the processes of advection and diffusion in the rectangular domain. Dirichlet and zero flux boundary conditions were specified as indicated in Figure 7. The FLASH code (Baca and Magnuson, 1992) was also setup and run in steady-state mode to provide the input velocity field.

A regular finite grid, composed of 8-node quadrilateral elements, was superimposed on the domain. The finite element grid, consisting of 15 elements in the x-direction and 12 elements in the z-direction, was finer in the vicinity of the line source. The FLAME code was run to provide simulation results for two time planes: $t = 10$ and 30 seconds.

Comparisons between the FLAME code and the Bruch and Street (1967) analytical solution are shown in Figure 8. These results show very close agreement for the early time. However, as the plume nears the outflow boundary, the difference between the two results increases. This difference is primarily due to the presence of the "finite" outflow boundary. Better results could be obtained by moving the outflow boundary to a greater distance.

Figure 8. Comparison of FLAME Predictions with Analytical Solution

6.0 INPUT GUIDE

6.1 Introduction

To model subsurface contaminant transport with the FLAME code, the user constructs an ASCII input file designated as 'flame.crd'. This file specifies the unique characteristics of the simulation which generally include: chemical properties of the contaminant, hydraulic and transport properties of the porous medium, initial and boundary conditions, computational grid, and solution procedure. The input file is constructed using a narrative style command sequence. The code reads the file using an input scheme that is designed with three basic objectives in mind: (1) to permit the user to incorporate detailed documentation of input data, (2) provide a flexible assembly of the data stream, and (3) allow the user to easily construct input files for new applications using existing data files.

These objectives were met by a general and user-friendly input scheme with the following features:

- o comment lines may be inserted in any location to document data sources, units, assumptions and conditions,
- o data are entered as free-form, case and order independent,
- o simulation specified by use of command instructions and special keywords,
- o soil properties, initial conditions, and computational mesh may be input from external files,
- o default parameters are set for unspecified input, and
- o input data is processed and checked for consistency with general specifications.

The above features minimize, to a great degree, the need to refer to the input guide during data file preparation. The following conventions are used in constructing the input data file for a subsurface transport simulation:

- o In using the planar coordinates (x, z) or radial coordinates (r, z), the z -coordinate is positive upwards,
- o All physical, chemical and transport properties are in units of grams, centimeters and seconds with one exception; half-lives are in units of years
- o Numerical values are input in a list-directed format,
- o Command instructions and keywords start in the first three columns of the file, and
- o The pound sign (#) is used to designate a comment or text line.

Sample input files for two computational test cases are presented in Appendix I.

6.2 Summary of Command Instructions

In the present version of the FLAME code, version 1.1, the input file is constructed using up to sixteen (16) unique command instructions. The available commands are listed and briefly explained below:

- o ECHO - specifies the requirement for echo of the input file
- o TITLE - declares a unique run identifier
- o TEXT - declares a sequence of text lines
- o CONTROL - specifies the simulation control parameters
- o FILES - declares the use of external files
- o SOLVE - specifies the solution control parameters
- o TIME PLANE - lists the time subintervals and output planes
- o INITIAL CONDITION - keys the input of initial conditions
- o FIXEDBC - keys input of Dirichlet boundary conditions
- o FLUXBC - keys input of point sources of contaminant
- o GRID - keys input of finite element grid
- o PROPERTIES - keys input of transport and basic hydraulic properties
- o TABLES - keys input of characteristic and hydraulic conductivity curve data
- o TRANSPORT - keys input of contaminant transport parameters
- o MASS FLUX - defines planes for computation of mass fluxes
- o OUTPUT - defines hard copy output requirements

Of the above command instructions, the ECHO, TEXT, MASS FLUX and OUTPUT commands are optional. The GRID and TABLES commands may be omitted when these particular data blocks are read from external files. More detailed descriptions and representative examples of the individual command instructions and keywords are presented in the next subsection.

6.3 Description of Input Stream

The input file, designated as 'flame.crd', is constructed using a combination of the above command instructions. Each unique command is used by the computer code to specify the nature of the input data and keywords that follow. The keywords can be used with other narrative descriptions. In addition, the input is both case and order independent. With few exceptions, unspecified data, parameters and/or unused keywords are assigned default values. The keywords described in the following subsections are shown in *italics*.

6.3.1 ECHO Command

The ECHO command is utilized to produce an exact echo of the ASCII input data file, 'flame.crd'. This listing is inserted at the top of the hard copy output file (designated as 'flame.rpt') which is generated by the computer code. The echo of the input file can be eliminated by use of the command ECHO SUPPRESS or SUPPRESS ECHO.

6.3.2 TITLE Command

The TITLE command line is usually the first input line in the data file. This line is followed by single line of text which becomes the unique title and run identifier. This title is written to the report file and to all binary output files as a file header. Also written to these output files is a numerical identifier which is a combination of the date and time. Additional lines of text may be placed after the title, however, these lines of text are not used elsewhere.

6.3.3 TEXT Command

The TEXT command keys the input routine that a block of text will follow; the purpose of this text is to document the unique aspects of the input data or simulation. Any number of text lines can be inserted following the TEXT command. It is recommended that this option be used to identify the user, explain the nature of the simulation, identify the particular case or run number, date of the computer run, list key assumptions, etc.

6.3.4 CONTROL Command

Specification of the simulation problem and solution procedure is accomplished using the CONTROL command. Following this command, the user utilizes various keywords to define: (1) type of transport simulation, (2) characteristics of the boundary value problem, (3) computational solution procedures, (4) coordinate system to be used, and (5) output print control.

Two types of transport simulations can be performed using the following alternative keywords:

- o *Time-dependent or Transient Mode*
- o *Steady-State Mode*

In the above specifications, the keyword *Mode* must always appear in the text line.

Definition of the boundary value problem is accomplished with the use of the following keywords:

- o *Uniform or Nonuniform Initial Condition*
- o *Specified Boundary Conditions*

- o *Point Sources*

With regards to the point sources, constant or time varying mass sources can be specified (see MASS FLUX command). These point sources can also be used to prescribe Neumann or flux boundary conditions.

In order to define the computational solution procedure, the user enters numerical values for: number of finite elements, number of nodes, number of iterations (usually set to 1), and initial start time. In addition, the user selects: (1) matrix solution method and (2) type of finite element shape functions. The following keywords can be used:

- o *Band or Frontal Solver*
- o *Linear or Quadratic Shape Functions*

The above are optional specifications; the code uses the following default specifications: (1) band solver and (2) quadratic shape functions.

The code has the capability to solve the governing equations in either Cartesian or radial coordinates. Appropriate specification of the coordinate system is accomplished by use of the keywords: *Cartesian* (x,z) or *Radial* (r,z) Coordinates. If not specified, the code defaults to a Cartesian coordinate system.

The default orientation of the simulation is vertical. For a horizontal simulation the keywords are *Horizontal* or *Planar*.

Control of printed output is achieved by use of such keywords as: *Echo All*, *Minimum Echo*, *Full Echo*. The latter specification should only be used for data debugging purposes.

6.3.5 FILES Command

Use of the FILE command indicates that next lines of input will define the use of external files. External files are defined for specific input and/or output functions. For example, the code allows the user to read or write restart files, output numerical solutions for post-processing, read the finite element grid (i.e., element-node table and node coordinates), initial conditions, soil-hydraulic property tables, and flow field (computed by the FLASH code). The following are examples of the applicable keywords:

- o *Read Restart* Input or *Write Restart* Output File
- o *Write Simulation* Results File
- o *Read Mesh* Input File
- o *Read Initial Conditions* or *Write Initial Conditions* File
- o *Read Soil* Properties File
- o *Read Pressure Head* Input Data File

o *Read Velocity* Input Data File

To define the flow-field, the user must either: (1) specify a velocity file (i.e., *Read Velocity*) or (2) soil properties and pressure head file (i.e., *Read Head*). The soil properties can be input from an external file (i.e., *Read Soil*) or specified in the input stream (see **PROPERTIES** command). Any of the above input or output operations can be suppressed by preceding the keyword with: *No*, *Dont*, or *Don't*. The code defaults to setting of no external inputs or outputs with one exception; the default specification for the flow field is to *Read* the *Velocity* file.

6.3.6 SOLVE Command

The **SOLVE** command is used to indicate the input of five parameters that are used in the solution procedure. These parameters consist of: (1) the time integration factor, α , (2) minimum change in concentration, τ_L , (3) maximum change in concentration, τ_H , (4) grid scale factor in the x-direction, s_x and (5) grid scale factor in the y-direction, s_y . These numerical values are read as list-direct input.

6.3.7 TIME PLANE Command

The **TIME PLANE** command is used to specify the time domain for a time-dependent simulation of heat or fluid flow. This command is followed by two columns of numerical input consisting: (1) number of subintervals and (2) output time plane in days. Each time plane defines an interval of time referenced to the initial start time or the previous interval. If the user enters a value of 1 for the number of subintervals, the computer code will calculate the appropriate number from the first interval. Time-stepping within a given time interval is automatically varied while maintaining the change in concentration within prescribed bounds.

An example of the **TIME PLANE** command and input is shown below:

```
TIME PLANE
# No. Steps  Time (days)
      10      0.1
       1      1.0
```

If the steady-state simulation option is selected under the **CONTROL** command, these data are simply ignored.

6.3.8 INITIAL CONDITIONS Command

Time-dependent simulations require the specification of initial conditions for each computational node. This specification is accomplished using the **INITIAL CONDITIONS**

command. The command is followed by two columns of numerical input consisting of: (1) node number, (2) initial concentration, g/cm^2 . This command is typically used to specify uniform initial conditions. An example is shown below:

INITIAL CONDITIONS

#	N	C (g/cm ³)
1		C_o

For cases where the initial conditions vary over the entire grid, the use of external file input (see the FILES command) is recommended.

6.3.9 FIXEDBC Command

To define the boundary value problem, the user will usually need to input the Dirichlet boundary conditions, i.e., the known concentration values at specific nodes. The FIXEDBC command is used to queue the input of node points with fixed values. The command is followed by numerical values consisting of: (1) node number, n (2) concentration value C_B . An example is shown below:

FIXEDBC

#	n	C (g/cm ³)
1		C_B

The above information is repeated for the complete list of nodes that have fixed concentration values.

6.3.10 FLUXBC Command

In certain practical applications, the user will need to account for contaminant sources at specific locations. The FLUXBC command is used to key the input of point sources of contaminant. It is assumed that the finite element grid has been constructed with nodes placed at the same locations as the point sources. The command is followed by three columns of numerical values consisting of: (1) time application, T_{ps} (days), (2) node number, N_{ps} , (3) mass source rate, $\dot{m}_{ps}$ (g/s). An example of the input is given below:

FLUXBC

#	Tps (days)	Nps	Mdot
	0.0	50	100.
	0.0	51	400.
	10.0	50	100.
	10.0	51	400.

No flux boundary conditions are automatically set by the code. This type of boundary condition is imposed on nodes along the grid boundary that are not designated as Dirichlet

boundary condition nodes, under the FIXEDBC command. Neumann or prescribed flux boundary conditions can be specified using the point source approach, however, the user must distribute the point sources in the appropriate manner in order to establish the correct flux value. Setting flux boundary conditions using point sources is explained in Istok (1989).

6.3.11 GRID Command

The computer code solves the governing equations on a finite element mesh composed of line, triangular, and/or quadrilateral elements. This mesh is defined in terms of an element-node table and list of node coordinates. This information can be entered into the input file using the GRID command. Following this command, the 11 column table consisting of: (1) the element number, (2) the corresponding node numbers listed in counter-clockwise order, (3) the element material number, and (4) element ordering index is entered. The last entry in the table must be entered to complete the input block; however, it is only used if the frontal solver option is selected under the CONTROL command. This index defines the order in which the frontal matrix solver will proceed (Hinton and Owen, 1977). The element-node table is followed by a 3 column input block consisting of: (1) node number, (2) x-coordinate location, and (3) z-coordinate location. A three element mesh which consists of a quadrilateral, triangle, and a line element superimposed between the these two elements is shown in Figure 9.

Figure 9. Sample Finite Element Mesh

The corresponding GRID input is shown below:

GRID

Element-node table for example FE mesh

#	m	N1	N2	N3	N4	N5	N6	N7	N8	km	k
1	1	1	2	3	7	11	10	9	6	1	1
2	3	3	4	5	8	11	7	0	0	1	2
3	3	3	7	11	0	0	0	0	0	1	3

```

# Node point locations
#  N   X (cm)  Z(cm)
   1    0.0    0.0
   2    0.5    0.0
   3    1.0    0.0
   4    1.5    0.0
   5    2.0    0.0
  etc   etc    etc

```

The above data are loaded into the code using a list-directed read. In practical applications, the mesh is composed of thousands of elements and nodes; thus, it is more convenient to read the above information from an external file using the FILES command. The code is designed to read the external file in either ASCII or binary format.

6.3.12 PROPERTIES Command

The stratigraphic features of the porous medium generally exhibit distinct hydraulic and transport properties. The PROPERTIES command is used to enter these properties for each material type. Following this command, the following data are entered: (1) material number, (2) longitudinal dispersivity D_L (cm), (3) transverse dispersivity D_T (cm), (4) saturated hydraulic conductivity K_x (cm/s), (5) saturated hydraulic conductivity K_z (cm/s), (6) saturated moisture content θ , or porosity, and (7) line-element width b (cm). An example input is shown below:

```

PROPERTIES
#  km    DL    DT    Kx    Kz    Theta    b
   1    0.5    0.5  1.0E-03  1.0E-03  0.25    1.0

```

A line of data is entered for each material type and designated by the material number km.

6.3.13 TABLES Command

The TABLES command is used to input the characteristic and relative hydraulic conductivity curve data. These data are typically generated by first fitting van Genuchten (1980), Campbell (1974), or Brooks and Corey (1966) formulas to laboratory data. These analytical formulas are then evaluated to produce the tabular data. The tabular data consists of three columns: (1) pressure head ψ , (2) volumetric moisture content θ , and (3) relative hydraulic conductivity K_r .

Typically, the tabular data should be ordered from zero pressure head to the lowest (i.e., most negative) pressure head. However, the input routine will accept pressure head as a positive quantity and will automatically sort the data and add the appropriate sign to the pressure head. It is highly recommended that the data be generated uniformly in the log

space and that each variable be calculated from the analytical formulas to at least five significant figures. One table for each material type must be entered following the TABLES command. An example input table is shown below:

TABLES

Material Properties for soil type 1

#	Shi (cm)	Theta	Kr
	0.00000E+00	0.25000	1.00000E+00
	-1.00000E-01	0.24999	9.99999E-01
	-2.00000E-01	0.24990	9.99950E-01
	-3.00000E-01	0.24910	9.99100E-01
	etc	etc	etc

The keyword *Material* must appear in the comment card before the tabular data.

Alternate keywords such as *Soil-Hydraulic*, *Soil Hydraulic*, *Soil-Properties*, *Soil Properties*, and *Characteristic* can also be used. It is recommended that 30 or more points be used in defining the characteristic and relative conductivity curves. For practical applications with several tables, it is more convenient to load these data using an external file (see FILES command).

6.3.14 TRANSPORT Command

In most model applications of practical interest, it is important to account for the processes of sorption, decay and molecular diffusion. The TRANSPORT command allows the user to enter tabular data characterizing these chemical and physical processes.

Following this command, six columns of data are entered: (1) material number, (2) retardation factor, (3) half-life λ (yrs), (4) molecular diffusion coefficient D_m (cm/s), (5) tortuosity in the x-direction τ_x , and (6) tortuosity in the z-direction τ_z . An example of this command is given below

TRANSPORT

#	km	Rd	Lambda (yrs)	Dm	Taux	Tauz
1		1.0	10.	1.0E-05	0.5	0.5

6.3.15 MASS FLUX Command

In the analysis of contaminant releases from a disposal facility, it is useful to compute the mass fluxes across selected planes such as a facility boundary. The MASS FLUX command is an optional command that can be used to define planes for such calculations.

The code computes and prints a table of the advective, dispersive/diffusive and net contaminant flux. A plane is defined by a line of node points. The list of individual flux planes must be terminated by a slash (/). A simple example of this command is given below:

MASS FLUX

#	Line		Corner	Nodes		
	1	12	14	16	18	/
	2	20	22	24	26	/
	3	35	37	39	41	/

The convention used in the computation of fluxes is positive to the right of the node numbering progression.

6.3.16 OUTPUT Command

The OUTPUT command, which is optional, can be used by the user to **suppress** selected portions of the report file. For example, the usually lengthy element-node table and node point coordinates can be suppressed by following this command with the keyword *Grid*. Similarly, the lengthy list of initial conditions can be suppressed using the keyword *Initial*.

ACKNOWLEDGMENTS

The authors wish to thank a number of individuals that contributed to this project. First and foremost, the authors thank Ms. M. Beth Sussman, Technology Programs, for her patience during the conduct of this study. The authors acknowledge the contributions of Ms. Annette Schafer-Perini for her detailed review and comments on the draft report. The authors also thank Mr. Tony R. Moser for his assistance with preparation of graphs and illustrations.

REFERENCES

- Baca, R. G., and D. W. Langford, "CHAINT - A Numerical Model for Radionuclide Transport with Decay Chains in Fractured-Porous Media: Model Theory, Numerical Methods, and Computational Tests," (Draft), Rockwell Hanford Operations, Richland, WA (1986).
- Baca, R. G., R. C. Arnett, and D. W. Langford, "Modelling Fluid Flow in Fractured-Porous Masses by Finite Element Techniques," *International Journal for Numerical Methods in Fluids*, **4**, 337-348 (1984).
- Baca, R. G., "Configuration Management and Software Control Procedure for Subsurface Flow and Transport Simulation Codes," *EGG-WM-9103*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Baca, R. G. and S. O. Magnuson, "Independent Verification and Benchmark Testing of the UNSAT-H Computer Code, Version 2.0," *EGG-BEG-8811*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Baca, R. G., S. O. Magnuson, H. D. Nguyen, and P. Martian, "A Modeling Study of Water Flow in the Vadose Zone Beneath the Radioactive Waste Management Complex," *EGG-GEO-10068*, EG&G Idaho, Inc., Idaho Falls, ID (1992).
- Baca, R. G. and S. O. Magnuson, "FLASH - A Finite Element Computer Code for Variably Saturated Flow," *EGG-GEO-10274*, EG&G Idaho, Inc., Idaho Falls, ID (1992).
- Bachmat, Y., J. Bredehoeft, B. Andrews, D. Holt, and S. Sebastian, *Ground-Water Management: The Use of Numerical Models*, Water Resources Monograph 5, American Geophysical Union, Washington, DC (1980).
- Baker, A. J. and J. W. Kim, *Finite Element Computational Fluid Mechanics*, Hemisphere Publishing Corporation, New York, NY (1983).
- Baker, A. J. and J. W. Kim, A Taylor Weak-Statement Algorithm for Hyperbolic Conservation Laws, *International Journal for Numerical Methods in Engineering*, **7**, 489-520 (1987).
- Bear, J., *Dynamics of Fluids in Porous Media*, (1988 Edition), Dover Publishing Co., New York, NY (1972).
- Bonano, E. J. and W. E. Beyeler, "Transport and Capture of Colloidal Particles in Single Fractures," *Materials Research Society Symposium Proceedings*, **44**, Materials Research Society, Boston (1989).

- Burnett, D. S., *Finite Element Analysis*, Addison-Wesley Publishing Company, Reading, MA (1987).
- Brooks, R. H. and A. T. Corey, Properties of Porous Media Affecting Fluid Flow, *Journal of Irrigation Drainage Div.*, ASCE 92(IR2), p. 61-88, (1966).
- Bruch, J. C. and R. L. Street, Two-Dimensional Dispersion, *Journal of Sanitary Engineering Division*, proceedings of the ASCE, 93(SA6), 17-38, (1967).
- Campbell, G. S., A Simple Method for Determining Unsaturated Conductivity from Moisture Retention Data, *Soil Science*, 117(6), pp. 311-314, (1974).
- Case, M. J., S. J. Maheras, M. A. McKenzie-Carter, M. E. Sussman, and P. Voilleque, "Radioactive Waste Management Complex Performance Assessment," EGG-WM-8773, EG&G Idaho, Inc., Idaho Falls, ID (1989).
- Celia, M. A., E. T. Bouloutas, and R. L. Zarba, "A General Mass-Conservative Numerical Solution for the Unsaturated Flow Equation," *Water Resources Research*, 25(7), 1483-1496 (1990).
- Collatz, L., *The Numerical Treatment of Differential Equations*, Springer-Verlag, Berlin, Germany (1960).
- Cushman, J. H. (Editor), *Dynamics of Fluids in Hierarchical Porous Media*, Academic Press, New York, NY (1990).
- Cuthill, E., "Several Strategies for Reducing the Bandwidth of Matrices," in *Sparse Matrices and their Applications*, eds. D. J. Rose and R. A. Willoughby, Plenum Press, New York, NY (1972).
- Donea, J., A Taylor-Galerkin Method for Convective Transport Problems, *International Journal for Numerical Methods in Engineering*, 20, 101-119 (1984).
- Fletcher, C. A. J., *Computational Galerkin Methods*, Springer-Verlag, New York, NY (1984).
- Fletcher, C. A. J., *Computational Techniques for Fluid Dynamics*, Vol. 1, Springer-Verlag, New York, NY (1988).
- Freeze, R. J. and J. A. Cherry, *Groundwater*, Prentice-Hall, Inc., Englewood Cliffs, NJ (1979).
- Gibbs, N. E., W. G. Poole, Jr., and P. K. Stockmeyer, "A Comparison of Several Bandwidth and Profile Reduction Algorithms," *Association for Computing Machinery Transactions of Mathematical Software*, 2, 322-330 (1976).
- Herzig, J. P., D. M. Leclerc, and P. Le Goff, "Flow of Suspensions Through Porous Media - Application to Deep Filtration," *Industrial and Chemical Engineering*, 62, 8-35 (1970).

- Hinton, E. and D. R. J. Owen, *Finite Element Programming*, Academic Press, New York, NY (1977).
- Hood, P., "Frontal Solution Program for Unsymmetric Matrices," *International Journal for Numerical Methods in Engineering*, **10**, 329-400 (1976).
- Huyakorn, P. S., J. W. Mercer, and D. S. Ward, "Finite Element Matrix and Mass Balance Computational Schemes for Transport Variably Saturated Porous Media," *Water Resources Research*, **21**(3), 346-358 (1985).
- Istok, J., *Groundwater Modeling by the Finite Element Method*, AGU Water Resources Monograph, American Geophysical Union, Washington, DC (1989).
- King, I. P., "An Automatic Reordering Scheme for Simultaneous Equations derived from Network Analysis," *International Journal for Numerical Methods in Engineering*, **2**, 525-533 (1970).
- Kline, N. W., R. L. England, and R. G. Baca, "CHAI NT Computer Code: User's Guide," *RHO-CR-144 P*, Rockwell Hanford Operations, Richland, WA (1986).
- Laney, P. T., S. C. Minkin, R. G. Baca, D. L. McElroy, J. M. Hubbell, L. C. Hull, B. F. Russell, G. J. Stormberg, and J. R. Pittman, "Annual Progress Report: FY-1987--Subsurface Investigations Program at the Radioactive Waste Management Complex of the Idaho National Engineering Laboratory," *DOE/ID-10183*, prepared by EG&G Idaho, Inc., Idaho Falls, ID (1988).
- Magnuson, S. O., R. G. Baca, and A. J. Sondrup, "Independent Verification and Benchmark Testing of the PORFLO-3 Computer Code, Version 1.0," *EGG-BG-9175*, EG&G Idaho, Inc., Idaho Falls, ID (1990).
- McCarthy, J. F. and J. M. Zachara, Subsurface Transport of Contaminants," *Environmental Science and Technology*, **23**(5), 496-502, (1989).
- McDowell-Boyer, L. M., J. R. Hunt, and N. Sitar, "Particle Transport Through Porous Media," *Water Resources Research*, **22**(13), pp. 1901-1921, (1986).
- McKinley, K. B. and J. D. McKinney, "Initial Drum Retrieval Final Report," *TREE-1286*, prepared by EG&G Idaho, Inc. for the U.S. Department of Energy, (1978).
- Oster, C. A., "Review of Ground-Water Flow and Transport Models in the Unsaturated Zone," *NUREG/CR-2917*, PNL-4427, Battelle-Pacific Northwest Laboratory, Richland, WA (1982).
- Pinder, G. F. and W. G. Gray, *Finite Element Simulation in Surface and Subsurface Hydrology*, Academic Press, Inc., New York, NY (1977).

- RAE (Rogers and Associates Engineering), "DOE Site Performance Assessment Activities," DOE/LLW-99, prepared for EG&G Idaho, Inc., Idaho Falls, ID (1990).
- Rawson, S. A., J. C. Walton, and R. G. Baca, "Migration of Actinides from a Transuranic Waste Disposal Site in the Vadose Zone," *Radiochemica Acta*, **52/53**, 477-486 (1991).
- Runchal, A. K. and B. Sagar, "PORFLOW: A Model for Fluid Flow, Heat, and Mass Transport in Multifluid, Multiphase Fractured or Porous Media: User's Manual-Version 2.39," Analytic and Computation Research, Inc, Los Angeles, CA (1991).
- Scheidegger, A. E., "General Theory of Dispersion in Porous Media, *Journal of Geophysical Research*, **66**(10), 3273-3278 (1961).
- Sharma, M. M. and Y. C. Yortsos, "Transport of Particulate Suspensions in Porous Media: Model Formulation," *American Institute of Chemical Engineers Journal*, **33**(10), 1636-1643 (1987).
- Tewarson, R. P., *Sparse Matrices*, Academic Press, New York, NY (1973).
- Travis, B. J. and H. E. Nuttall, "A Transport Code for Radiocolloid Migration, with an Assessment of an Actual Low-Level Waste Site," *Materials Research Society Symposium Proceedings-IX*, Materials Research Society, Boston, 969-976 (1985).
- van Genuchten, M. T., "A Closed-Form Equation for Predicting the Hydraulic Conductivity of Unsaturated Soils," *Soil Science Society of America Journal*, **44**, 892-898 (1980).
- Vigil, M. J., "Subsurface Disposal Area (SDA) Waste Identification (1952-1970)," EGG-WM-8727, EG&G Idaho, Inc., Idaho Falls, ID (1989).
- Walton, J. C., A. S. Rood, R. G. Baca, and M. D. Otis, "Model for Estimation of Chlorinated Solvent Release from Waste Disposal Sites," *Journal of Hazardous Materials*, Vol. 21, pp. 15-24 (1989).

APPENDIX I - SAMPLE INPUT FILES FOR TEST PROBLEMS

This appendix presents condensed versions of the input files prepared for two of the computational examples described in section 5.0. The two examples consist of: (1) one-dimensional solute transport in partially saturated flow and (2) two-dimensional transport in saturated flow. Certain portions of the input files have been omitted because of their length. These portions, which include the grid definition and soil property tables, can be easily reconstructed by the user from information given in section 5.0.

A-1 Summary of Input File for Computational Example 1

ECHO

TITLE

VT-1c: Imbibition in a Horizontal Column - Huyakorn problem

TEXT

FLAME Computer Code Simulation:
Flow field generated by FLASH computer code
Finite Element mesh composed of "Line Elements" only

CONTROL

NE NP ITERLM SSF
100 201 1 0.

Time-dependent mode
Cartesian coordinates
Uniform initial conditions
Specified boundary conditions
Echo all data
Don't print velocity output

FILES

Don't Read Restart file
Write Simulation Results
Don't Write Restart Data
Don't Read Input Mesh File
No Initial Conditions File
Don't Write Initial Conditions
No Soil Properties File
Read Velocity Input File

SOLVE

Alfa TauL TauH Scalex Scaley
1.6 0.01 5.0 1. 1.

TIME PLANE

Nts Time (days)
25 0.05787
1 0.5787
1 1.1574

INITIAL CONDITIONS

N C(1)
1 0.0

FIXEDBC
N BCS(1)
1 1.

GRID
ELEMENT-NODE TABLE
N ----- NOP ----- IMAT NFIXH
1 1 2 3 0 0 0 0 0 1 1
2 3 4 5 0 0 0 0 0 1 2
3 5 6 7 0 0 0 0 0 1 3
4 7 8 9 0 0 0 0 0 1 4
5 9 10 11 0 0 0 0 0 1 5

(Lines Omitted)

98	195	196	197	0	0	0	0	0	1	98
99	197	198	199	0	0	0	0	0	1	99
100	199	200	201	0	0	0	0	0	1	100
1		0.000	0.000			0.00		0.00		
2		0.100	0.000			0.00		0.00		
3		0.200	0.000			0.00		0.00		
4		0.300	0.000			0.00		0.00		
5		0.400	0.000			0.00		0.00		
6		0.500	0.000			0.00		0.00		
7		0.600	0.000			0.00		0.00		
8		0.700	0.000			0.00		0.00		
9		0.800	0.000			0.00		0.00		
10		0.900	0.000			0.00		0.00		
11		1.000	0.000			0.00		0.00		
12		1.100	0.000			0.00		0.00		

(Lines Omitted)

190	18.900	0.000	0.00	0.00
191	19.000	0.000	0.00	0.00
192	19.100	0.000	0.00	0.00
193	19.200	0.000	0.00	0.00
194	19.300	0.000	0.00	0.00
195	19.400	0.000	0.00	0.00
196	19.500	0.000	0.00	0.00
197	19.600	0.000	0.00	0.00
198	19.700	0.000	0.00	0.00
199	19.800	0.000	0.00	0.00
200	19.900	0.000	0.00	0.00
201	20.000	0.000	0.00	0.00

PROPERTIES
L Dispx Dispy Satkx Satky Poros Width
= =====
1 0.0 0.0 1.157E-05 1.157E-05 0.450 1.

TRANSPORT
L Sorption Half-Life Diffusion Tortx Torty
= =====
1 0. 0. 1.157E-05 1.00 1.00

OUTPUT
Echo all Input Data

A-2 Summary of Input File for Computational Example 3

ECHO

TITLE

Two-Dimensional Plume from Line Source

TEXT

FLAME Computer Code Simulation:

=====

This computational example considers the problem of transient mass transport from a line source in a rectangular region. The flow field is unidirectional and at steady-state. To define the flow field, the FLASH computer code was run in steady-state mode. The numerical solution obtained with the FLAME code can be compared to the analytical solution derived by Bruch and Street (1967).

CONTROL

NE NP ITERLM SSF
40 147 1 0.

Time-dependent mode

Band Solver

Planar Geometry

Cartesian coordinates

Uniform conditions

Specified boundary conditions

Echo all data

Don't print velocity output

FILES

Don't Read Restart file

Don't Write Simulation Results

Don't Write Restart Data

Don't Read Input Mesh File

No Initial Conditions File

Don't Write Initial Conditions

No Soil Properties File

Read Velocity Input File

SOLVE

Alfa TauL TauH Scalex Scaley
1.6 0.01 5.0 1. 1.

TIME PLANE

Nts Time
20 1.15741E-04
1 2.31481E-04
1 3.47222E-04

INITIAL CONDITIONS

N T(1)
1 0.0

FIXEDBC

N BCS(1)
1 1.
18 1.
27 1.
44 1.
53 0.

GRID

ELEMENT-NODE TABLE

#	N	NOP										IMAT	NFIXH
1	1	2	3	19	29	28	27	18	1	1			
2	3	4	5	20	31	30	29	19	1	2			
3	5	6	7	21	33	32	31	20	1	3			
4	7	8	9	22	35	34	33	21	1	4			
5	9	10	11	23	37	36	35	22	1	5			

(Lines Omitted)

38	115	116	117	128	143	142	141	127	1	38
39	117	118	119	129	145	144	143	128	1	39
40	119	120	121	130	147	146	145	129	1	40
1	0.000		0.000		0.00		0.00			
2	2.000		0.000		0.00		0.00			
3	4.000		0.000		0.00		0.00			
4	6.000		0.000		0.00		0.00			
5	8.000		0.000		0.00		0.00			

(Lines Omitted)

143	24.000	6.000		0.00	0.00
144	26.000	6.000		0.00	0.00
145	28.000	6.000		0.00	0.00
146	30.000	6.000		0.00	0.00
147	32.000	6.000		0.00	0.00

PROPERTIES

#	L	Dispx	Dispy	Satkx	Satky	Poros	Width
#	=	=====	=====	=====	=====	=====	=====
1	0.0	0.0	10.0	10.0	0.5	1.	

TRANSPORT

#	L	Sorption	Half-Life	Diffusion	Tortx	Torty
#	=	=====	=====	=====	=====	=====
1	0.	0.	1.0	50.0	5.0	

OUTPUT

Echo all Input Data

DISTRIBUTION LIST

OFFSITE

D. J. Alexander
U. S. Department of Energy
Forrestal Bldg., MS RW-23-2
Washington, DC 20585

W. Barrish
INEL Oversight Program
1410 N. Hilton
Boise, ID 83706

J. S. Baldwin
Martin Marietta
Central Waste Management
Oak Ridge, TN 37831

A. J. Baker
Engineering Science and Mechanics
University of Tennessee
Knoxville, TN 37996-2030

A. K. Bhattacharyya
Department of Environmental Resources
Bureau of Radiation Protection
P. O. Box 2063
Harrisburg, PA 17120

K. H. Birdsell
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

G. C. Biswas
Converse Consultants NW
18 W. Mercer, Suite 300
Seattle, WA, 98119

T. N. Blandford
HydroGeoLogic, Inc.
1165 Herndon Pkwy, Suite 900
Herndon VA, 22070

G. Bloomsburg
Agricultural Engineering Department
University of Idaho
Moscow, ID 83843

A. Bumb
Fluor Daniel, Inc.
100 Fluor Daniel Drive
Greenville, SC 29607

T. C. Chee
U. S. Department of Energy
Research and Management Division
DP-123, A237
Germantown, MD 20545

D. L. Chery, Jr.
U. S. Nuclear Regulatory Commission
MS-4H3
Washington, DC 20555

J. N. Chung
Mechanical and Material Engineering
Washington State University
Pullman, WA 99164-2920

R. B. Codell
U. S. Nuclear Regulatory Commission
MS-4H3
Washington, DC 20555

J. R. Cook
Westinghouse Savannah River Company
Savannah River Laboratory
P. O. Box 616, Bldg. 773-43A
Aiken, SC 29802

J. C. Corey
Westinghouse Savannah River Site
P. O. Box A
Aiken, SC 29808

M. Cunnane
Golder Associates, Inc.
4104 148th Avenue NE
Redmond, WA 98052

J. Davis
Westinghouse Hanford
450 Hills St.
Richland, WA 99352

P. A. Davis
Sandia National Laboratories
Division 6416
P. O. Box 5800
Albuquerque, NM 87185

P. Dickman
U. S. Department of Energy
Waste Management Project Office
P. O. Box 14100
Las Vegas, NV 89114

M. R. Dolenc
Reynolds Electrical and Engineering Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

F. H. Dove
IT Corporation
5301 Central Ave, N.E., Suite 700
Albuquerque, NM 87108

R. R. Eaton
Sandia National Laboratories
Fluid Mechanics and Heat Transfer Div.
Albuquerque, NM 87185

M. Ebra
Westinghouse Savannah River Company
Environmental Restoration Program
P. O. Box 616
Aiken, SC 29802

L. Ebeling
Reynolds Electrical and Engineering Co.
P. O. Box 98521
Las Vegas, NV 89193-8521

A. I. El-Kadi
Univ. of Hawaii at Manoa
Dept. of Geology and Geophysics
2525 Correa Road
Honolulu, HI 96822

C. G. Enfield
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

M. J. Fayer
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

J. I. Finnie
Civil Engineering Department
University of Idaho
Moscow, ID 83843

R. A. Freeze
Department of Geological Sciences
University of British Columbia
Vancouver, BC V6T 2B4, Canada

G. W. Gee
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

M. Th. van Genuchten
USDA-ARS, U.S. Salinity Laboratory
4500 Glenwood Drive
Riverside, CA 92501

T. C. Gunderson
Los Alamos National Laboratory
P. O. Box 1663, MS K491
Los Alamos, NM 87545

P. van der Heijde
International Groundwater Modeling Center
Colorado School of Mines
Golden, CO 80401-1887

D. Hillel
Dept. of Plant and Soil Science
University of Massachusetts
12A Stockbridge Hall
Amherst, MA 01003

C. Y. Hung
U. S. Environmental Protection Agency
Office of Radiation Programs, ANR-460
401 M Street, S. W.
Washington, DC 20460

P. S. Huyakorn
HydroGeoLogic, Inc.
1165 Herndon Pkwy, Suite 900
Herndon, VA 22070

V. Ichimura
Chem-Nuclear Systems
P. O. Box 726
Barnwell, SC 29182

B. Izadi
Agricultural Engineering Dept.
Univ. of Idaho
Moscow, ID 83843

T. L. Jones
Department of Agronomy
and Horticulture
New Mexico State University
Las Cruces, NM 88003-0003

W. A. Jury
Department of Soils
University of California
at Riverside
Riverside, CA 90024

P. Kears
Oak Ridge National Laboratory
Grand Junction Office
Grand Junction, CO 81502

K. Kersch
SAIC, Inc.
101 Convention Ctr. Drive,
Suite 407
Las Vegas, NV 89109

C. T. Kincaid
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

R. G. Knowlton
Sandia National Laboratories
P.O. Box 5800, Div 6416
Albuquerque, NM 87185

C. P. Liou
Civil Engineering Department
University of Idaho
Moscow, ID 83843

J. T. McCord
Sandia National Laboratories
Division 6416
Albuquerque, NM 85185-5800

L. M. McDowell-Boyer
Oak Ridge National Laboratory
Grand Junction Office
Grand Junction, CO 81502

C. McLane
ENVIRON International Corp.
4350 N. Fairfax Dr., Suite 300
Arlington, VA 22203

D. B. McLaughlin
Department of Civil Engineering
Massachusetts Institute of Technology
Room 48-329
Cambridge, MA 02139

S. A. Mizell
Desert Research Institute
P. O. Box 60220
Reno, NV 89506

D. J. Mulla
Soils Department
Washington State University
Pullman, WA 99164

S. P. Neuman
Dept. of Hydrology and Water Resources
University of Arizona
Tucson, AZ 85721

W. Newberry
U. S. Department of Energy
Nuclear Energy LLW Management
Program, NE-24
Washington, DC 20545

T. J. Nicholson
U. S. Nuclear Regulatory Commission
Division of Engineering Safety
MS NL-005
Washington, DC 20555

J. W. Nyhan
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

U. S. Park
Science Applications International Corp.
101 Convention Center Drive
Las Vegas, NV 89109

F. L. Parker
4400 Iroquois
Nashville, TN 37205

D. M. Peterson
INTERA Associates, Inc.
8100 Mountain Road NE, Suite 213
Albuquerque, NM

O. A. Plumb
Mechanical and Material Engineering
Washington State University
Pullman, WA 99164-2920

J. Pope
Westinghouse Savannah River Company
Environmental Restoration Program
P. O. Box 616
Aiken, SC 29802

R. W. Prindle
Sandia National Laboratories
Division 6312
P. O. Box 5800
Albuquerque, NM 87185

T. C. Rasmussen
Dept. of Hydrology and Water Resources
University of Arizona
Tucson, AZ 85721

M. Reeves
INTERA Associates, Inc.
6850 Austin Cntr. Blvd.,
Suite 300
Austin, TX 78731

B. L. Roberts
EG&G Rocky Flats, Inc.
P. O. Box 464
Golden, CO 80402-0464

M. L. Rockhold
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

V. C. Rogers
Rogers & Associates Engineering Corp.
P. O. Box 330
Salt Lake City, UT 84110

A. K. Runchal
ACR, Inc.
3106 Inglewood Blvd.
Los Angeles, CA 90066

B. Sagar
Center for Nuclear Waste Repository
Analyses
Southwest Research Institute
6220 Culebra Rd.
P. O. Drawer 28510
San Antonio, TX 78284

S. G. Schmelling
U. S. Environmental Protection Agency
Robert S. Kerr Environmental Lab
P. O. Box 1198
Ada, OK 74820

M. Silberberg
U. S. Nuclear Regulatory Commission
Office Nuclear Regulatory Research
Washington, DC 20555

J. L. Smoot
Pacific Northwest Laboratory
P. O. Box 999, MS K6-77
Richland, WA 99352

C. J. Suen
Brookhaven National Laboratory
Nuclear Waste and Materials
Technology Division
Upton, Long Island, NY 11973

R. J. Starmer
ERM-Program Management Corp
7926 Jones Branch Drive, Suite 210
McLean, VA 22102

Technical Library
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

Technical Library
Oak Ridge National Laboratory
P. O. Box X
Oak Ridge, TN 37830

Technical Library
Savannah River Laboratory
P. O. Box 616
Aiken, SC 29802

B. J. Travis
Los Alamos National Laboratory
P. O. Box 1663
Los Alamos, NM 87545

B. Troutman
Dames and Moore, Inc.
1970 E. 17th St, Suite 111
Idaho Falls, ID 83401

S. W. Tyler
Water Resources Center
Desert Research Institute
P. O. Box 60220
Reno, NV 89506-0220

J. Wang
Lawrence Berkely Laboratory
Earth Sciences Division
1 Cyclotron Road,
Berkely, CA 94720

A. W. Warrick
University of Arizona
Dept. of Soil and Water Science
Tucson, AZ 85721

E. P. Weeks
U. S. Geological Survey
Federal Center, MS 413
Denver, CO 80225

M. Weinstein
U. S. Nuclear Regulatory Commission
MS NL/S-260
Washington, DC 20555

P. J. Wierenga
University of Arizona
Dept. of Soil and Water Science
Tucson, AZ 85721

D. C. Wiggert
Michigan State University
A120 Engineering Research Complex
East Lansing, Michigan 48824

J. L. Wilson
New Mexico Institute of Mining
and Technology
Dept. of Geosciences
Socorro, NM 87801

Westinghouse Hanford Company
P. O. Box 1970
Richland, WA 99352

J. D. Davis, MS H4-54
R. Khaleel, MS H4-54
J. C. Sonnichsen, MS H4-54

A. Yu
Westinghouse Savannah River Company
Savannah River Laboratory
P. O. Box 616
Aiken, SC 29802

ONSITE

DOE-ID

M. C. Bennett
L. A. Green

EG&G Idaho, Inc.

R. C. Arnett
J. M. Hubbell
J. A. Logan
S. O. Magnuson
S. J. Maheras
P. Martian
J. N. McCarthy
J. W. McConnell
R. L. Nitschke
H. D. Nguyen
R. R. Seitz
A. L. Schafer-Perini
J. B. Sisson
C. S. Smith
A. J. Sondrup
L. V. Street

INEL Technical Library

Westinghouse Idaho Nuclear Co., Inc.

T. R. Thomas

U.S. Geological Survey

J. R. Pittman
L. J. Mann

END

**DATE
FILMED**

10 / 29 / 92