EGG-WM-8724
September 1989

**Idaho
National
Engineering
Laboratory**

*Managed
by the U.S.
Department
of Energy*

INFORMAL REPORT

BASIC RADIOLOGICAL STUDIES
CONTAMINATION CONTROL EXPERIMENTS

S. W. Duce
M. R. Winberg
A. L. Freeman

*Work performed under
DOE Contract
No. DE-AC07-76ID01570*

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This book was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights. References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

EGG-WM--8724

DE92 019479

**BASIC RADIOLOGICAL STUDIES
CONTAMINATION CONTROL EXPERIMENTS**

S. W. DUCE, M. R. WINBERG, AND A. L. FREEMAN

July 1989

Idaho National Engineering Laboratory

EG&G Idaho, Inc.,

Idaho Falls, ID 83415

MASTER

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

BASIC RADIOLOGICAL STUDIES
CONTAINMENT CONTROL EXPERIMENTS

S. W. Duce, M. R. Winberg, A. L. Freeman

September 1989

Approved by:

S. P. Fogdall, RDP Manager

9-8-89

Date

Reviewed by:

R. G. Thompson, ERP Quality

9-21-89

Date

J. H. McDaniel, RDP Facility

9/7/89

Date

L. D. Goodrich, ERP-DIRC

9/7/89

Date

W. D. Schofield, ERP-Safety

9/7/89

Date

ABSTRACT

This report describes the results of experiments relating to contamination control performed in support of the Environmental Restoration Programs Retrieval Project. During the years 1950 to 1970 waste contaminated with plutonium and other transuranic radionuclides was disposed of in shallow land-filled pits and trenches at the Idaho National Engineering Laboratory. Due to potential for migration of radionuclides to an existing aquifer the feasibility of retrieving and repackaging the waste for placement in a final repository is being examined as part of a retrieval project. Contamination control experiments were conducted to determine expected respirable and nonrespirable plutonium contaminated dust fractions and the effectiveness of various dust suppression techniques. Three soil types were tested to determine respirable fractions: Rocky Flats Plant generic soil, Radioactive Waste Management Complex generic soil, and a 1:1 blend of the two soil types. Overall, the average respirable fraction of airborne dust was 5.4% by weight. Three contamination control techniques were studied: soil fixative sprays, misting agents, and dust suppression agents. All of the tested agents proved to be effective in reducing dust in the air. Details of product performance and recommended usage are discussed.

EXECUTIVE SUMMARY

During the years 1950 to 1970 approximately two million cubic feet of transuranic (TRU) contaminated waste was buried in pits and trenches at the Radioactive Waste Management Complex (RWMC) at the Idaho National Engineering Laboratory (INEL). The waste was contained in 55-gallon metal drums, plywood boxes, cardboard boxes, and other miscellaneous containers. As a demonstration project, waste in one of the pits will be retrieved and repackaged to await final disposition at a facility designed to safely hold TRU wastes. It is anticipated that years of waste burial have degraded container integrity and that TRU wastes are no longer containerized with significant fractions of the backfill material becoming cross contaminated. Therefore, during the waste retrieval effort there will be a high probability for TRU contamination spread via direct (soil spills) and indirect (airborne) pathways. The As Low As Reasonably Achievable (ALARA) philosophy and EG&G's concern for the environment require that the spread of TRU-contaminated materials be minimized. To this end, the TRU waste retrieval effort includes investigation of appropriate methods for contamination control.

A series of contamination control experiments were designed and conducted to test: (a) the airborne characteristics of the anticipated TRU contaminated soil, (b) potential benefits of soil fixatives, (c) potential benefits of misting agent sprays, and (d) potential benefits of dust suppression agents. All tests were designed and conducted to meet the objectives of the "Environmental Restoration Program Retrieval Demonstration Project Contamination Control Background Studies Sampling and Analysis Plan."

Generic soil types from the Rocky Flats Plant (RFP), Radioactive Waste Management Complex (RWMC), and a 1:1 blended RFP and RWMC soil were tested to determine respirable soil fractions (i.e., that fraction of airborne dust particles having an aerodynamic mean diameter of <5 micron). It was found that the respirable portion of each soil type and 1:1 blend were 2.4%, 8.4%, and 5.5% by weight for the RFP, RWMC and blended soils, respectively, with an overall average of 5.4%.

Additionally, the RFP and RWMC soils were sieved to determine the as-received particle size distribution. Sieved sizes were >2000, 710 to 2000, 150 to 710, 75 to 150, 45 to 75, and <45 microns. Particle size distributions of the as-received RFP and RWMC soils showed that 0.6 and 0.4% of the total soil mass resides in <45 micron size particles.

The RFP soil had TRU radionuclide contamination at approximately 1000 pCi/g, therefore, selected fractions were analyzed for ^{239}Pu and ^{241}Am concentrations. Results of these analyses showed that <4% of the TRU activity was associated with <45 micron size particles. This value was determined using soil fractions that were <710 microns in size. To clarify this, the <45 micron particles have a high specific activity (pCi/g) but are a low fractional percent of the total soil. Results of soil emissions testing on RWMC soil was that soil with 8.3% surface moisture did not have an appreciable emission factor. This helps to quantify a conclusion drawn from earlier tests, that moist soil was not easily aerosolized. Therefore, minimizing natural moisture loss from the dig face is important for controlling airborne contamination.

Knowing that a particle has to be <20 microns to become airborne and keeping in mind the above results, these values should be considered when airborne concentration limits are established for personnel access to the dig area. The implication is that for the mixed soil in the pits and trenches the total respirable TRU contaminated soil is probably <4% and likely <<1% of the total soil mass. Of the total airborne dust generated during the retrieval effort approximately 5% would be respirable. Therefore setting airborne radioactive dust working limits on respirable fractions rather than on total airborne dust would allow for an increase of at least 20 in the airborne limit. For example if the upper limit for total airborne contamination concentration was at 10,000 times MPC (maximum permissible concentration) the new limit would be 200,000 times MPC. By taking advantage of the small respirable fraction and low amount of TRU attached to the respirable fraction the higher limits if adopted could save considerable money by reducing unnecessary shutdowns. Therefore, the authors recommend that the retrieval project consider this strategy of increasing the allowable concentration limits.

Behavior of Pu in the environment can be affected considerably by its chemical form and valence state. In these tests Pu was environmentally aged, having been exposed to the environment for several years as a constituent of the surface soil at Rocky Flats, and was therefore in one of the more stable forms. It can be anticipated that the Pu in the pits and trenches will have had sufficient time to have aged returning to the Pu^{+4} valence state. Further it can be anticipated that the aged Pu has had sufficient time to interact with the backfill soils and to have been tied up by the high ionic exchange capacity clay component. Therefore, these tests were simulating soil that should behave similarly enough to the pit and trench soils to have confidence in the test results.

Two 3M fixant products, Foamer and Penetrant, were tested to determine dust suppression and moisture retention factors. Both products performed equally well for dust suppression. Foamer provided the best moisture retention factor, holding soil moisture nine times better than bare soil in a horizontal configuration. Penetrant moisture retention was estimated to be two to three times better than bare soil. However, Penetrant has a definite advantage, its ability to be retained in a soil column when applied to a vertical face. Although not tested in this study Foamer has application schemes that can also be applied to a vertical face. This needs to be determined through further testing because of the superior moisture retention features of Foamer.

Two misting techniques, Microfoam and Dry Fog, were evaluated for their ability to suppress airborne dust. Deter Microfoam is a foam product which has the texture of shaving cream. Dry Fog is a finely atomized water mist. Both products proved to be equally effective when applied at minimum rates (3 gpm foam and 10 gph water), but when Dry Fog was applied at twice the minimum rate it proved to be a better product for large area applications. Deter Microfoam would be an effective dust suppressant in small area applications within closed systems (i.e., covered conveyor or enclosed systems). Overall, the Dry Fog system should cost less to install and operate.

Two dust suppression agents, Coherex and Semi-Pave, were evaluated for their capability to minimize dust in areas of vehicular traffic. Although both products proved effective for total dust suppression, Semi-Pave outperformed Coherex in suppressing respirable dust. Vendor test data support this conclusion. Recommended application parameters and cost of Semi-Pave are 1:7 dilution with water and application rate of 0.75 gal/yd² at a cost of \$.37/yd².

In conclusion several products and application systems have been identified, tested, and proven effective for minimizing airborne concentrations of dust. In the case of TRU waste retrieval this dust has potential for bearing TRU radionuclides, primarily the alpha emitting ²³⁹Pu and ²⁴¹Am. Proper application of these products should provide a work environment that will allow for rapid personnel entry dressed in limited anti-contamination clothing (i.e., nominally EG&G Zone 2 or 3 dress). Application costs are not trivial but can be minimized through proper matching of product to application and engineering design. Much of the engineering design could be readily obtained through the different product and system vendors. As a general rule, products having relatively inexpensive application costs should be used for applications on larger areas.

Organic vapor suppression, although a side benefit, could be obtained from the use of the 3M products Foamer and Penetrant. Application of these products to the vertical and horizontal dig surfaces following digging could help suppress outgassing of organic vapors.

Further engineering scale testing of the candidate product(s) and applicator system(s) is required to determine the best use of these products and proper application rates. These tests are currently scheduled to be performed in FY-1990.

CONTENTS

ABSTRACT	i
EXECUTIVE SUMMARY	ii
ABBREVIATIONS/ACRONYMS	viii
1. INTRODUCTION	1
2. METHODS	2
2.1 Test Chamber Description	2
2.2 Test Soil Descriptions	5
2.3 Methods for Testing Respirable and Nonrespirable Dry Soil Fractions	9
2.4 Testing Methods for Soil Fixative Sprays	13
2.4.1 Foamer Testing	13
2.4.2 3M Penetrant	15
2.5 Misting Agent Sprays	16
2.5.1 DeTer Microfoam Tests	16
2.5.2 Dry Fog Tests	18
2.6 Dust Suppression Agents	20
2.6.1 Coherex	20
2.6.2 Semi-Pave	21
3. EXPERIMENTAL RESULTS	22
3.1 Respirable and Nonrespirable Dry Soil Characteristics	22
3.2 Soil Fixatives	28
3.3 Misting Agent Sprays	29
3.4 Dust Suppression Agents	31
4. DISCUSSION AND RECOMMENDATIONS	34
4.1 Respirable and Nonrespirable Dry Soil Characteristics	34
4.2 Soil Fixatives	36
4.3 Misting Agent Sprays	38
4.4 Dust Suppression Agents	39
5. CONCLUSIONS	41
6. REFERENCES	42

APPENDIX

Appendix A	WITCO Test Results	A-1
Appendix B	BOOTS and COOTS Information	B-1

LIST OF FIGURES

2.1	Schematic of Test Chamber 1	3
2.2	Photograph of Test Chamber 1	3
2.3	Measured linear velocities at a flow rate of 3 lfpm for Test Chamber 1	4
2.4	Schematic of Test Chamber 2	6
2.5	Photograph of Test Chamber 2	6
2.6	Measured linear velocities for four different cross sections in Test Chamber 2	7
2.7	Measured linear velocities at centerline for Test Chamber 2	8

LIST OF TABLES

2.1	Size Distribution of RWMC and RFP Soil by Weight	10
3.1	Airborne Dust Concentrations for Different Fractions	23
3.2	Plutonium and Americium Soil Concentrations for Blended RWMC/RFP and RFP Soils for the MSA Cyclone Sampler Components	24
3.3	²³⁹ Pu and ²⁴¹ Am Sample Analysis Results from UNC Geotech (pCi/g)	26
3.4	Summary of Deter Microfoam Tests	30
3.5	Summary of Dry Fog Tests (10 gph)	32
3.6	Summary of Dry Fog Tests (20 gph)	32
3.7	Airborne Concentrations and Suppression Factors for Coherex and Semi-Pave	33

ABBREVIATIONS

cfm	cubic feet per minute
lpm	liters per minute

ACRONYMS

ALARA	As Low As Reasonably Achievable
AMD	Aerodynamic Mean Diameter
ASTM	American Society for Testing Materials
CAM	Constant Air Monitor
DI	Demineralized
EPA	Environmental Protection Agency
HEPA	High Efficiency Particulate Air
Hi-Vol	High Volume Typically >10 cfm
INEL	Idaho National Engineering Laboratory
LAMS	Lifting and Moving System
LLW	Low Level Waste
Lo-Vol	Low Volume Typically ≤ 2 cfm
MPC	Maximum Permissible Concentration
MSA	Mine Safety Appliance
RFP	Rocky Flats Plant
TRU	Transuranic

1. INTRODUCTION

During the years 1950 to 1970 approximately two million cubic feet of transuranic (TRU) contaminated waste were buried in pits and trenches at the Radioactive Waste Management Complex (RWMC) at the Idaho National Engineering Laboratory (INEL). The waste was contained in 55-gallon metal drums, plywood boxes, cardboard boxes, and other miscellaneous containers. One of the strategies for long term management of this waste is to retrieve and repackage it for final disposition at a facility designed to safely hold TRU wastes. It is anticipated that waste containers have degraded over the years and that significant fractions of the backfill material have become contaminated with TRU wastes. Therefore, during the waste retrieval effort there will be a high probability for TRU contamination spread via direct (soil spills) and indirect (airborne) pathways. The As Low As Reasonably Achievable (ALARA) philosophy and EG&G's concern for the environment require that the spread of TRU-contaminated materials be minimized. To this end, the TRU waste retrieval effort includes investigation of appropriate methods for contamination control.

The purpose of this report is: (a) to document the results of experiments conducted in the area of contamination control for the TRU buried waste retrieval program and (b) to provide recommendations for contamination control techniques. A series of experiments were designed to test: (a) the characteristics of the anticipated contaminated soil, specifically the movement of TRU nuclides, (b) potential benefits of soil fixatives, (c) potential benefits of misting agent sprays, and (d) potential benefits of dust suppression agents. Some of these tests represent a larger scale application of previous laboratory bench scale tests^[2] while others are applications of vendor supplied materials and equipment.

All tests were designed and conducted to meet the objectives of the "Environmental Restoration Program Retrieval Demonstration Project Contamination Control Background Studies Sampling and Analysis Plan".^[1] The data quality objective statements outlined in that document were adhered to during all aspects of the testing program.

2. METHODS

2.1 Test Chamber Description

Two test chambers were designed and constructed during the course of the experiments to allow scaled testing of various contamination control aspects.

The smaller of the two test chambers which was used to test fixant and suppression agents was constructed of 1/2 in. plexiglass sheeting and had outside dimensions of 24 x 60 x 30 in. Three glove ports provided access inside of the chamber during testing. An air inlet and exhaust port was located on either end of the glove box. Figures 2.1 and 2.2 are a schematic and actual picture of the chamber. Both the inlet and exhaust air were filtered using high efficiency particulate air filter paper (99.9 retention) to prevent dust from entering the chamber from the room environment and to minimize the amount of contaminated dust that could be released in the laboratory during testing operations. Air movement through the test chamber was provided by a Sierra-Misco Hi-Volume air sampler which was connected to the exhaust port with flexible duct. A control circuit allowed the Hi-Vol sampler to provide a constant flow of air through the chamber regardless of exhaust filter dust loadings.

Linear air flow through the chamber was determined using a Solomat hot wire anemometer. The anemometer has a small sensor which minimized air flow disturbance. The Solomat had been calibrated at the factory within the last year. Air flow patterns were determined in the chamber by passing the anemometer into the glove box through a glove port and then sealing the glove port. The Hi-Vol was started and the flow adjusted to a calculated 3 lfpm (linear feet per minute). Cross-sectional wind speed was measured at each glove port. While conducting other tests the linear velocity was increased to as high as a calculated 10 lfpm. Figure 2.3 shows the linear flow pattern for the 3 lfpm flow rate. Note that actual linear velocities differ from calculated velocities.

Figure 2.1. Schematic of Test Chamber 1.

Figure 2.2. Photograph of Test Chamber 1.

Figure 2.3. Measured linear velocities at a flow rate of 3 lpm for Test Chamber 1.

The larger second chamber which was used to test misting agents was a wood framed structure 8 x 8 x 6 ft covered with heavy plastic sheeting (see Figures 2.4 and 2.5). Air was introduced into the chamber approximately 16 in. up from the floor on one side through a wooden box which contained a soil aerosolizer. Air was exhausted from the chamber on the opposite wall using a 12 in. flexible duct that was connected to a nominally rated 1500 cfm (cubic feet per minute) HEPA filtered exhaust blower. Actual air flow through the chamber was reduced to approximately 400 cfm due to dust loading of the HEPA filters. The flexible duct was installed approximately 1 ft from the ceiling and centerline of the wall. The inlet/exhaust arrangement enabled air to enter low in the chamber, flow diagonally upward across the chamber, and be exhausted near the ceiling. Inside the test chamber a catch basin was constructed which was approximately 5 x 8 ft x 16 in. This basin was used to capture the spent misting agents during test duration, which in the case of the DeTer Microfoam was as much as 45 gal of foam. Access into the chamber was provided through two curtained doorways. Airborne dust loadings were measured on the inlet and exhaust side using a series of five MSA (Mine Safety Appliance) cyclone air samplers and a Lo-Vol air sampler on each side. Linear flow patterns were also measured for the one exhaust air flow rate that could be obtained with the exhaust blower. Figure 2.6 and 2.7 shows the measured linear velocities within the test box at four different cross-sections and at centerline.

2.2 Test Soil Descriptions

Two soil types used in the conduct of these series of experiments were RWMC and Rocky Flat Plant (RFP). The RWMC soil was obtained near an RWMC cold test pit from an exposed 5-8 ft vertical cut. The soil, which was naturally dry, has a high clay content and when dry is very friable, being easily crushed. The soil was sieved through five screens to determine particle size distribution with sieve sizes of 2000, 710, 150, 75, and 45 micron. RFP soil, which has a high silica and low clay content, was obtained downwind from a former drum storage area. The Pu originated 20 years ago from leaking drums that contained contaminated cutting oil. The

Figure 2.4. Schematic of Test Chamber 2.

Figure 2.5 Photograph of Test Chamber 2.

Figure 2.6 Measured linear velocity at four axial positions.

Figure 2.7 Measured linear velocity at four center line positions.

oil held a suspension of $<3\mu\text{m}$ Pu particles. This area was decontaminated in 1969 and covered with an asphalt pad.[3]

This soil, obtained with the assistance of RFP personnel, was contaminated with ^{239}Pu near a 1000 pCi/g concentration which is a factor of 10 lower than the INEL low level waste (LLW) definition. RFP soil was dried and sieved to determine particle size distribution, the same as RWMC soil. Table 2.1 lists particle sizes and weight percents for both soil types.

In this report the terms respirable and nonrespirable are frequently used. These terms as applied to soil characteristics in this report will be defined as follows: (a) respirable means airborne dust that has a aerodynamic mean diameter (AMD) particle size of ≤ 5 microns, (b) nonrespirable means airborne dust that has an AMD of between 5 and 20 microns. Particle size limits for airborne dust range from 0.1 to 20 microns. Cember[3] indicates that most deep pulmonary deposition occurs with particles having AMDs between 1 and 5 microns and that most dust particles are ≤ 10 microns in size. As can be seen in Table 2.1, the smallest particle sieve size was <45 micron which was nominally 0.5% of the total soil by weight. Therefore, when respirable and nonrespirable percents are presented they represent a fraction of the <20 micron soil component. "Lo-Vol" or Lo-Vol sample as used in this report refers to a total airborne concentration.

2.3 Methods for Testing Respirable and Nonrespirable Dry Soil Fractions

Experiments were performed to determine respirable and nonrespirable fractions of RWMC soil, RFP (Rocky Flats Plant) soil, and blended RFP/RWMC soil. These tests were conducted using the 24 x 60 x 30 in. plexiglass glove box. A plexiglass tray was constructed to hold the test soil sample and a woven mat of punctured tygon tube comprised the dust aerosolizing unit. Glove box surfaces were wiped down prior to each test to prevent cross contamination of soils between tests.

TABLE 2.1 SIZE DISTRIBUTION OF RWMC SOIL BY WEIGHT

<u>Size in Microns</u>	<u>Percentage*</u>	
	<u>RWMC</u>	<u>RFP</u>
> 2000	39	36
710 to 2000	34	27
150 to 710	19	31
75 to 150	7	5
45 to 75	0.7	1.4
< 45	0.4	0.6

* This percentage was determined by dividing two scale measured values. The accuracy of the scale was 0.0001g.

Additionally, a 50 lb sample of RWMC soil was sent to National Environmental Service Company, a fugitive dust consulting firm, to determine emission factors due to impact events. These tests were performed to provide further test data about the fraction of the RWMC soil that may become airborne during the retrieval effort. The soil was tested as received (8.3% surface moisture) and after being air dried (0% surface moisture). Soil emission factors were measured through the use of a soil impact drop test, an ASTM approved method.^[6] This method simulates impact events such as scraping, backfilling, digging, and soil falling.

MSA cyclone samplers were used in all tests to determine respirable and nonrespirable airborne dust fractions. The cyclone sampler used a 0.45 micron pore size 37 mm diameter filter to collect respirable airborne dust fractions while the collector cap was designed to collect any nonrespirable dust fractions. In preliminary testing five cyclones were each assigned a number and glovebox location. The filters and nonrespirable cyclone collector caps were always weighed on a calibrated balance before and after each test with weights recorded in a lab notebook. Before each test the cyclone samplers were cleaned and refurbished with a new membrane filter inserted in each filter holder. The filter holder was then reassembled and the seam sealed with a cellulose band. The collector cap was screwed onto the cyclone body and the filter holder was attached using a small piece of tygon tubing. The completed sampler was then attached to its designated air sampling line in the glove box. Samplers were positioned as follows: three were centered directly above the test bed at heights of 6, 15 and 23 in. and two others were located 15 in. above the glovebox floor 24 and 36 in. downstream of the test bed. A Lo-Vol sampler, used to determine total airborne dust concentrations, was located 15 in. above and 24 in. downstream of the test bed.

Scoping tests were performed using RWMC soil to evaluate glove box characteristics and to predetermine optimal testing conditions. Eleven tests were performed each using 4 kg of RWMC soil at varying Hi-Vol flow rates. Results were recorded in the experiment logbook and entered into the

PC database for analyses. It was determined that a 10 to 13 cfm Hi-Vol flow rate for 15 minutes would be adequate to see measurable quantities of dust on the caps and filters of the MSA cyclone samplers.

The following procedure was used with each test: (a) proper flow rate of 2 lpm (liters per minute) through each MSA cyclone sampler was established, (b) flow rate through the Lo-Vol particulate filter was established at 7 lpm, (c) exhaust air flow from the test chamber was set at approximately 10 cfm using the Hi-Vol, (d) air flow in the aerosolizer mat was set at 6-8 cfm at 30 psig, and (e) all flow rates and start times were recorded in the logbook. Flow rates of samplers and aerosolizer were adjusted as required throughout each test to maintain initial test conditions for the duration of the test, which was typically about 15 minutes. After each test, the cyclone samplers, the 2 cfm sampler, the bed air, and then the Hi-Vol were turned off. Flow rates and start and stop times were recorded. Caps and filters were weighed, the weights were recorded in the logbook, and then the samples were submitted for radiochemical analysis.

Three tests using approximately 3 kg of Rocky Flats Plant (RFP) Pu-contaminated soil and four tests using a 50:50 mix of RWMC and RFP soil were performed. Results were recorded in the experiment logbook and data were entered into a PC data base for analysis.

Archived samples from several of the tests were sent to UNC Geotech at Grand Junction, Colorado for Pu and Am analysis. Samples sent were from tests involving RFP and RFP/RWMC soils. Also a few samples were analyzed via gamma ray spectrometry at the INEL to determine ^{241}Am content.

Health Physics recommendations were followed for tests using RFP and RFP/RWMC soils during the experiment and when opening the glove box. An alpha CAM (constant air monitor) was operated in the immediate area to determine the presence of airborne alpha contamination. For all tests visible dust was allowed to settle prior to opening up the glove box to retrieve the cyclone and Lo-Vol samplers. During the RFP and RFP/RWMC soil

tests an HP technician was present during the opening of the glove box and monitored the samplers for contamination as they were retrieved. Inner surfaces of the glove box were also monitored for contamination levels to determine proper clothing requirements prior to cleaning between tests. Success of the contamination control methods used was attested to by the absence of alpha contamination (neither airborne or smearable) outside of the glove box during any operation. The alpha CAM alarmed during testing on two days but the alarm was due to high radon concentrations experienced during inversion conditions. This was confirmed by the HP technician who had the CAM filter analyzed for radon and thoron daughter.

2.4 Testing Methods for Soil Fixative Sprays

The purpose of the following experiments was to determine if the 3M products Foamer and Penetrant were suitable for use in fixing surface contamination and maintaining natural moisture in a soil column. Earlier studies^[7] showed that soil moisture significantly reduced airborne dust. Both Foamer and Penetrant were developed by 3M to act as a moisture and vapor barrier for hazardous waste cleanup sites. These products have proven to be effective in restricting the offgas of organic and other hazardous vapors from waste sites where they have been applied.

2.4.1 Foamer Testing

The 3M product Foamer is a chemical reaction product generated using a mixture of foamer (FX-9162), foam stabilizer (FX-9161), and water. The mixture ratios are 6% foamer, 6% stabilizer, and 88% water. The solution was mixed in a blender for 15 seconds and immediately poured onto the desired surface. This product produces a thick yellow foam which sets up within 2 minutes forming a thick barrier which completely covers the soil. Texture of the foam is similar to that of a small bubble sponge mat. The fresh product mat is light and airy but with time (more than three days) the product changes to a leathery mat. Even after more than 50 days, the mat, though leathery, still controls dust. The product has good sealing capabilities but can be easily torn.

Scoping tests were performed with Foamer to determine the appropriate batch size and method of application. The amount of Foamer was determined to be 100 ml or 200 ml depending on the size of the test area. Foamer was mixed in a blender and poured on a test bed to observe the behavior of the Foamer on the soil and to determine drying times. Scoping tests were also performed to determine weight loss of the foam during a simulated 24 hr test period to account for the moisture loss from the foam. Average weight loss of a 200 ml batch of foam during a 24 hr test period was determined to be $58 \pm 2\%$ by weight.

All tests of this product were performed in the plexiglass glove box. To evaluate Foamer's capability to control dust in the air, two 200 ml batches of Foamer were poured over the open surface of the test pan (13 x 22 x 1.75 in. plexiglass pan filled with RWMC soil) and allowed to set up for a period of 1 hour. The test pan was placed in the glove box and the soil aerosolizer mat (a framework 15 x 24 in. laced with tygon tubing punched with small holes) was placed over the test pan. Two MSA cyclone samplers were placed in the glove box: one 15 in. directly above the test bed and the second 15 in. above and 24 in. downstream of the test bed with a Lo-Vol filter located near the second MSA cyclone. The samplers and Lo-Vol were used to verify average dust concentration during the test. Flow rates for the cyclone and Lo-Vol samplers were 2 lpm and 7 lpm, respectively. All filters and caps for the cyclones and filter for the Lo-Vol were weighed before and after each test to determine dust concentrations. Air was blown onto the test pan for a period of 24 hr to determine if any breakdown of the foam layer would occur and to allow the soil underneath to become airborne. During the entire test the Hi-Vol fan ran at 10 cfm to create air flow across the test bed. All weights, flows, and setup parameters were recorded in the experiment logbook and entered into the PC database for further analysis.

In conjunction with the above test, a test to determine moisture retention capability of Foamer was conducted. Pre-moistened soil was placed in four 8 x 8 x 3 in. aluminum foil baking pans and the pans were weighed. Two pans were left exposed to the air in the glove box and the other two

pan were each covered with 200 ml of Foamer. All four pans were placed downstream of the 13 x 22 x 1.75 in. test pan. They were left in the glove box with the Hi-Vol fan running at 10 cfm for a period of 24 hr after which the pans were weighed to determine the loss of moisture from both the covered and uncovered soils.

Three tests were run under these conditions to determine reproducibility of test results.

2.4.2 3M Penetrant

The 3M product Penetrant is a chemical reaction product consisting of a mixture of penetrant (FX-9164), foam stabilizer (FX-9161), and water. Mix ratios were 1% penetrant, 6% stabilizer, and 93% water. The solution was stirred for 15 seconds and poured and/or sprayed onto the desired surface. Penetrant is a light yellow liquid which penetrates into the soil and sets up quickly forming a semi-hard dry surface. The dry soil surface resists erosion from moderate abrasive pressure but will readily breakup with greater pressure.

Scoping tests were performed to determine proper batch size and suitable application rate. These tests were conducted in the lab on a large area of soil. Batches of Penetrant were mixed and sprayed onto a test bed to determine application rate, speed of drying, and depth of material penetration. It was determined that a 100 ml batch sprayed at a rate of 0.067 gal/ft² provided good coverage and penetration. The test area was determined to be 1.99 ft² which resulted in 0.098 gal (370 ml) being sprayed on the test bed for each test.

Soil retention tests were performed with the test pan in the plexiglass glove box using the same setup, time, and flow conditions as were used to test Foamer.

Penetrant was also subjected to tests to determine the ability of the product to reduce moisture loss on a vertical face. An 8 x 24 x 6 in. vertical face of moistened soil was constructed near the outlet end of the glove box. A "cookie-cut" sample was taken on both the top and vertical faces of the soil 2 in. in diameter and 1 in. deep and weighed to determine moisture content. Penetrant was then applied to one-half of the soil with the other half left exposed to air. Two tests of 24 and 72 -hr duration were performed. After each test, the layer of Penetrant and an equal depth of the untreated soil were removed. Soil samples of the same size as the pretest were taken from both the top and vertical face of each side to determine moisture loss from the treated and untreated sides. All test results and observations were recorded in the experiment logbook and entered into the PC database for analysis.

2.5 Misting Agent Sprays

A series of tests were conducted to determine the effectiveness of airborne dust suppression for two different product applicators and misting agents. These tests concentrated on the ability of a misting agent/applicator to effectively reduce airborne concentrations of respirable and nonrespirable dust as a dust-laden air stream passed through a mist curtain. Linear flow through the chamber was maximized (see Figure 2.4 for flow pattern) but was limited by the exhaust blower. The following subsections describe the methods used to test two products: DeTer Microfoam and Dry Fog.

2.5.1 DeTer Microfoam Tests

A dust arresting system (Microfoam Model 5000 series) manufactured by DeTer Company, Inc., was tested for reduction of airborne dust in the large test chamber described in Section 2.1. A series of five tests were conducted to determine the effectiveness of Microfoam to suppress dust.

The Microfoam equipment consisted of a metering unit, a valve control system, and plastic hoses. Compressed air, water, and surfactant (sudsing agent) were combined within the DeTer MicroFoam Generating equipment to create a pressure foam. Pressure foam is by nature a viscous material resembling shaving cream or heavy whipping cream.

Air, aerosol, and water pressure were regulated to achieve consistent spray. The manufacturer recommended that air pressure be set from 90 to 100 psi and aerosol pressure be set at 40 psi with the water pressure at 20-30 psi or 5 psi less than the aerosol pressure. The manufacturer also suggested that tubing from the foam generator not exceed 10 ft. Our experimental setup required two hoses, one 18 ft and one 13 ft long. Therefore, slight pressure adjustments were necessary but they proved to be effective. Air pressure was set at 82 psi, aerosol pressure was set at 58 psi, and water pressure was set at 38 psi. Foam output to the test chamber was controlled to approximately 3 gpm by three valves which enabled regulation of output volume for each spray nozzle with the third valve controlling a blow down or discharge line. The discharge line was used to blow down any excess foam produced during the experiments and to rinse and clean system lines after each test.

Generated foam flowed through the hoses to two nozzles where it was released as two overlapping fans of foam. The nozzles were pointed towards one another inside the test enclosure at a height of 5 ft 6 in. and were separated by a distance of 8 ft. The two resulting sheets of spray created a foam curtain which settled into a 5 x 8 ft x 16 in. high basin constructed in the center of the enclosure. In a 15-minute period the basin was almost overflowing with foam (~45 gal). A fan blowing air on the foam would dissipate it in about an hour leaving approximately 13 gal of liquid in the basin.

Each fifteen minute test was run with five cyclone filters and one Lo-Vol filter placed on each side of the foam curtain. Cyclone samplers A-1 to A-5 and Lo-Vol Filter A were placed on the inlet side and cyclone samplers B-1 to B-5 and Lo-Vol Filter B were positioned on the outlet side

of the test enclosure (see Figure 2.3a). Cyclone samplers A-1, A-3, and A-5 were suspended 52 in. from the ceiling and cyclones A-2 and A-4 were suspended 35 in. from the ceiling. Cyclone samplers B-1, B-3, and B-5 were suspended 17 in. from the ceiling and cyclones B-2 and B-4 were suspended 35 in. from the ceiling. Differences in placement height were based upon air flow patterns inside the chamber which were lower on the inlet side and higher on the outlet side. A-side cyclones were 12 in. away from one another and positioned 9 in. away from the inlet wall with the A-3 cyclone centered in front of the dust inlet. B-side cyclones were positioned 12 in. apart from one another 9 in. away from the outlet wall with Cyclone B-3 centered in front of the exhaust outlet. Lo-Vol Filter A was centered on the wall in the front of the dust inlet and Lo-Vol Filter B was placed near the outlet. Dust was generated and pulled into the room with the exhaust blower drawing the suspended dust and air, past the A-side filters, through the foam curtain, and then past the B-side filters and into the exhaust blower with HEPA filters (see Figure 2.3). At the end of each test the foam generator and delivery lines were cleaned of foam by two steps (a) running pressurized water for several minutes and b) blowing pressurized air for approximately one minute.

Linear air flow through the test chamber is shown in Figure 2.4. Air flow through the chamber could not be increased as the exhaust blower was operating at full capacity. It was not possible, therefore, to determine the effect of increased air speed on dust suppression efficiencies.

Nonrespirable fractions were determined from dust in the cyclone caps and respirable fractions were determined from dust particles residing on the cyclone filters. Data for total dust concentrations were also obtained from Lo-Vol filter A and B. Cyclone and Lo-Vol filter air pressures were noted and recorded at five minute intervals during each test.

2.5.2 Dry Fog Tests

Dry Fog, a fine water spray misting system which uses an ultrasonic nozzle to atomize water in air, was also tested in the large plastic sheeted chamber. This nozzle works on the principle that water entering an air

stream that is moving at sonic velocity will be atomized into very fine moisture droplets and then discharged to the air. Six tests were conducted to determine its effectiveness in dust suppression.

Equipment consisted of a 3 gal container for demineralized (DI) water, two ultrasonic misting heads, and plastic hoses. DI water is required to prevent plugging of the nozzle by entrained solids. Compressed air at 65-70 psi and DI water with a cover gas pressure of 9 or 15 psi were combined to create a fine mist with delivery rates of 5 or 10 gph for each Dry Fog nozzle. This relatively small flow rate will probably result in a requirement for only a few hundred gallons per week of DI water. This volume of water could be commercially obtained without DI facility on site. Another option is to use a commercially available ultra-pure water filter system. Air and water pressure were regulated to achieve a consistent spray out of the two ultrasonic spray nozzles. The nozzles were positioned on opposite sides of the room and separated by a distance of 8 ft. They were vertically offset, one 5 ft 6 in. and the other 3 ft 6 in. above the floor, with one nozzle spraying above and towards the other one. The two circular sprays created a fine ~4 ft wide curtain of mist which settled into a 5 ft x 8 ft x 16 in. basin constructed in the center of the enclosure. In a 15-minute period 2.5 gal or 5 gal of DI water, depending upon water head pressure, settled in the basin.

Each test ran for fifteen minutes with five cyclone filters and one Lo-Vol filter placed on each side of the mist. Cyclone samplers A-1 to A-5 and Lo-Vol Filter A were placed on the input side and cyclone samplers B-1 to B-5 and Lo-Vol Filter B were positioned on the output side of the test enclosure. Cyclone samplers and Lo-Vol filters were positioned and suspended as described in Section 2.4.1 for the Microfoam tests. Dust was generated and sucked into the room with the exhaust blower drawing the suspended dust and air past the A-side filters, through the Dry Fog curtain, then past the B-side filters, into the exhaust housing (see Figure 2.3). During these tests a furnace filter was placed in front of the exhaust port to reduce the dust loading on the exhaust blower assembly. Three tests were run at the 5 gph water application rate and three at the 10 gph application rate.

Linear air flow through the glove box is shown in Section 2.4.1. Due to the single flow rate with the exhaust blower operating at full capacity, it was not possible to determine the effect of increased air speed on dust suppression efficiencies.

Nonrespirable fractions were determined from cyclone cap dust mass loading and respirable fractions were determined from the mass of dust particles residing on the cyclone filters. Data were also obtained from Lo-Vol filter A and B pre- and post-weight measurements. Cyclone and Lo-Vol filter air pressures were noted and recorded at five minute intervals during each test.

2.6 Dust Suppression Agents

The purpose of these experiments was to determine the performance of Witco dust suppression agents, Coherex and Semi-Pave. Coherex and Semi-Pave are water soluble emulsions designed to penetrate into soil and create a hard surface in heavy traffic. These products were designed for mining, logging on dirt roads, or digging areas where heavy equipment is in use. Tests on these products were performed in the plexiglass glove box using the same parameters that were used during the soil movement tests described in Section 2.3.

Additionally, a 50 lb sample of RWMC soil was sent to Witco for testing to determine soil characteristics and recommended dilution and application rates of both products. Results of this analysis are discussed in Sections 3.4 and 4.4 and are listed in Appendix A of this report.

2.6.1 Coherex

Coherex is a yellow, slightly viscous, water soluble emulsion. The manufacturer recommends a 4:1 dilution with water at a .50 to 1 gal/yd² application rate. Scoping tests were performed to determine the appropriate application rate for Coherex on RWMC soil. Coherex was mixed at a 4:1 ratio and applied at .5 and .75 gal/yd² to a test bed

of RWMC soil to observe penetration and drying times. The best method of application for laboratory purposes was a garden sprinkler head attached to a plastic bottle. The application rate for the glove box test for Coherex was 0.75 gal/yd² or 468 ml to the glove box test bed. Initial penetration time was 20-40 s and drying required approximately 20 minutes.

The plexiglass glove box setup, testing time, and flow conditions were identical to those used for the soil movement tests described in Section 2.2. Tests were performed at 25, 50, and 100% of the maximum application rate (i.e., 0.75 gal/yd²). In addition, visual observations were made of the test bed during and after each test to check for product breakdown. All sample information and visual observations were recorded in the logbook and results were entered into the PC data base for analysis.

2.6.2 Semi-Pave

Semi-Pave is a yellow, viscous, water soluble emulsion. It is more viscous than Coherex. The manufacturer recommends a 7:1 dilution with water at a 0.50 to 1 gal/yd² application rate. Scoping tests were performed to determine the appropriate application rate for Semi-Pave on RWMC soil. Semi-Pave was mixed at a 7:1 ratio and applied at 0.5 and 0.75 gal/yd² to a test bed of RWMC soil to observe penetration and drying times. The best method of application for laboratory purposes was a garden sprinkler head attached to a plastic bottle. The application rate was 0.75 gal/yd² or 468 ml to the glove box test bed. Drying time was approximately 20 minutes.

Glove box setup, testing time, and flow conditions were identical to those used for the Coherex tests. Tests were performed at 25, 50, and 100 percent of the determined application rate. In addition, visual observations were made of the test bed during and after each test to observe any breakdown of the product. All sample information and visual observations were recorded in the experiment logbook and results entered into the PC database for analysis.

3. EXPERIMENTAL RESULTS

3.1 Respirable and Nonrespirable Dry Soil Characteristics

The results of the soil characteristic studies showed that respirable fractions of all soil types tested allow a safety factor of at least 10 and possibly 20 to be easily achieved for the allowed maximum permissible concentration (MPC) of plutonium and other TRU nuclides in the atmosphere. Experimental results for the air samplers (soil concentrations and the Pu-239 and Am-241 concentrations) are listed in Tables 3.1 and 3.2. The increase in safety factor is due to the small fraction (average 5.4%) of airborne material that actually could result in deep lung deposition, i.e., soil particles having a mean AMD (aerodynamic mean diameter) of ≤ 1 micron. This fraction ranged from 5.5% for the RWMC soil to 8.4% for the blended RWMC/RFP soil. On average, 2.4% of the airborne RFP soil was respirable. The fraction of radionuclide activity associated with the respirable dust fraction agrees well with the RFP respirable soil fraction which indicates that Pu-239 and Am-241 are randomly attached to the soil particles and, therefore, have the same effective particle size distribution as the commingled soil.

Total airborne dust loading, as measured with the Lo-Vol sampler, was in good agreement with airborne soil loading obtained by adding the respirable and nonrespirable concentrations measured with the MSA cyclone samplers. As a general rule, total airborne soil concentration decreased with distance from the point of generation both vertically and horizontally. The nonrespirable concentration decreased on average approximately a factor of three and the respirable concentration decreased on average a factor of two over a horizontal distance of 3 ft. This decrease was driven by gravitational settling (dry deposition) of the dust particles. However, differential settling of larger particles resulted in an increase of the respirable fraction even though the absolute airborne concentration decreased. Generally the increase was less than a factor of two in the horizontal direction.

TABLE 3.1. AIRBORNE DUST CONCENTRATIONS FOR DIFFERENT FRACTIONS (pCi/g)

SOIL TYPE	AVERAGE RESPIRABLE	RANGE	AVERAGE NONRESPIRABLE	RANGE	AVERAGE LO-VOL	RANGE
RWMC	$1.2 \pm 0.7E-7^*$	3.8E-8 to 2.3E-7	$2.1 \pm 1.3E-6$	4.4E-7 to 5.1E-6	$1.2 \pm 0.8E-6$	2.6E-7 to 2.3E-6
RFP	$4.2 \pm 1.1E-8$	3.6E-8 to 5.5E-8	$1.7 \pm 0.5E-6$	1.2E-6 to 2.1E-6	$9.3 \pm 6.1E-7$	4.1E-7 to 1.6E-6
RFP/RWMC	$1.2 \pm 0.2E-7$	9.7E-8 to 1.3E-7	$1.3 \pm 0.3E-6$	1.1E-6 to 1.8E-6	$1.4 \pm 0.4E-6$	7.9E-7 to 1.8E-6
PERCENT RESPIRABLE						
RWMC	5.5					
RFP	2.4					
RFP/RWMC	8.4					
$\bar{X}$	5.4 ± 3.0					

*Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

TABLE 3.2. PLUTONIUM AND AMERICIUM SOIL CONCENTRATIONS FOR BLENDED RWMC/RFP AND RFP SOILS
FOR THE MSA CYCLONE SAMPLER COMPONENTS

TEST INFORMATION	CYCLONE NO.	²³⁹ Pu (pCi/g)		²⁴¹ Am (pCi/g)		RATIO Pu/Am	
		CYCLONE CAP	CYCLONE FILTER	CYCLONE CAP	CYCLONE FILTER	CAP	FILTER
BLENDED SOIL	1	ND	210±27	ND	20±10		10.5
	2	125±15	33±13	18±5	0	6.9	
	3	ND	203±32	ND	21±13		9.7
	4	125±19	235±35	24±10	28±16	5.2	8.4
	5	208±23	223±30	29±12	25±15	7.2	8.9
	$\bar{X}$	153±8*	181±12	24±5	23±7	6.4	9.4
RFP SOIL	1	832±108	464±86	136±15	71±35	6.2	6.5
	2	922±129	2956±295	112±11	424±89	8.3	7.0
	3	1140±134	840±133	172±18	80±33	6.6	10.5
	4	1780±210	1815±242	202±21	285±73	8.8	6.4
	5	1166±177	1940±200	145±25	217±42	8.0	8.9
	$\bar{X}$	1168±70	1603±92	153±8	215±26	7.6	7.9
RFP SOIL	1	ND	1246±144	ND	813±55	ND	6.8
	2	ND	504±68	ND	80±28	ND	6.3
	3	ND	1716±215	ND	215±54	ND	8.0
	4	ND	1310±180	ND	190±60	ND	6.9
	5	ND	1980±300	ND	264±91	ND	7.5
	$\bar{X}$		1351±88		186±27		7.1

ND = not detected

*Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

Aerosolizing and stirring of the test bed tended to break down the larger conglomerate particles into finer particles; however, this did not enhance respirable fractions during the later series of the twelve tests. This was also true of soil used in the misting agent tests. It can be implied from these visual observations that mechanical agitation of soil does not seem to significantly increase the respirable airborne fraction. Because of the implications that this has for operations during the retrieval effort particle size distribution versus soil agitation should be tested.

Samples of the cyclone filters and cap deposits were analyzed via gamma ray spectrometry at the INEL to determine ^{241}Am content and then were sent to UNC Geotech at Grand Junction, Colorado for ^{239}Pu and ^{241}Am analysis. Results of these analyses and calculated correlation factors of Pu to Am are listed in Table 3.3. In reviewing the data it is obvious that there is a constant ratio between Pu and Am. The average ratio is 7.4 ± 1.5 which differs from earlier estimates of the Pu to Am ratio^[8,9] in the buried waste. Also there is good agreement between the two Am results indicating that gamma ray spectroscopy may also be useful as a screening technique or an analysis tool.

Soil emission factors test results from National Environmental Service Company were: (a) for the as-recieved soil (8.3% surface moisture) impact activities caused no appreciable soil emission, (b) for the air dried soil (0% surface moisture) the average emission factor was 0.088 ± 0.0014 lbs/ton. Measured emission factors ranged from 0.0709 to 0.109 lbs/ton. These factors agree with estimated emission factors for the types of mechanical forces that will occur during the retrieval effort.

TABLE 3.3. ^{239}Pu and ^{241}Am SAMPLE ANALYSIS RESULTS FROM UNC GEOTECH
(pCi/g)

Sample Description	^{241}Am	^{239}Pu	^{241}Am Gamma	Ratio Pu/Am
RFP Cap 1-12	136±15	832±108	128±9	6.1
2-12	112±11	922±129	160±14	8.2
3-12	172±18	1140±134	180±16	6.6
4-12	202±21	1780±210	175±45	8.8
5-12	145±25	1166±177	263±27	8.0
RFP Cap 1-13	109±10	1004±109	64±9	9.2
2-13	114±12	722±105	105±18	6.8
3-13	109±13	685±90	133±12	6.3
4-13	145±18	969±132	192±75	6.7
5-13	116±19	974±112		8.4
RFP/RWMC 2-19	18±5	125±15		6.9
CAP 4-19	24±10	125±19		5.2
5-19	29±12	208±23		7.2
RFP FIL 1-12	71±35	464±86		6.5
2-12	424±89	2956±296		7.0
3-12	80±33	840±133		10.5
4-12	285±73	1815±242		6.4
5-12	217±42	1942±200		8.9
RFP FIL 1-14	183±55	1246±144		6.8
2-14	80±28	504±68		6.3
3-14	215±54	1716±215		8.0
4-14	190±60	1310±180		6.1
5-14	264±91	1980±300		7.5
RFP/RWMC 1-16	147±41	1035±153		7.0
FIL 2-16	110±31	674±111		7.0
3-16	75±33	280±48		3.7
4-16	108±28	610±68		5.6
5-16	93±29	710±87		7.6
RFP/RWMC 1-19	20±10	210±27		10.5
FIL 2-19	ND	33±13		
3-19	21±13	203±32		9.7
4-19	28±16	235±35		8.4
5-19	25±15	223±30		8.9

$$\bar{X} = 7.4 \pm 1.5$$

ND = Not detected

TABLE 3.3. ^{239}Pu and ^{241}Am SAMPLE ANALYSIS RESULTS FROM UNC GEOTECH
(pCi/g) (Cont'd)

<u>Soil Fractions Analysis Results</u>					
<u>Particle Size</u>	<u>Frac %*</u>	<u>^{241}Am</u>	<u>Gamma Scan</u>	<u>$^{239+240}\text{Pu}$</u>	<u>Ratio</u>
150<x<710	31	52±10	87±2	344±44	6.4
75<x<150	5	104±21	102±5	844±79	8.1
45<x<75	1.4	98±13	111±4	683±61	7.0
x<45	0.6	133±18	110±4	1064±105	8.0

* Fraction of the as recieved soil.

<u>Standards Analysis Results</u>		
<u>Standard Description</u>	<u>Known Value</u>	<u>Measured Value</u>
RWMC ^{239}Pu	102.3±1.4	98±15
RWMC ^{241}Am	52±5	57±11
Blank	<0.2	<0.2

Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

3.2 Soil Fixatives

Two different soil fixatives were tested to determine their effectiveness in suppressing soil suspension and in enhancing moisture retention in the soil column. Both products, Foamer and Penetrant, were obtained from 3M Company and performed equally well in suppressing the soil suspension from a horizontal bed. No visible or measurable dust was generated during 24 hr tests.

The two products however, did not perform equally well in retaining moisture in horizontal and vertical soil columns. The 3M foam product, when applied on a horizontal surface, allowed on average a 1.5% moisture loss from a soil column in 24 hr where a non-foamed surface experienced a 13.5% moisture loss. The penetrant product was not tested on a horizontal surface since the moisture loss fraction due to curing and that loss due to soil column evaporation could not be distinguished. Instead a second test was performed where a water saturated soil block was formed with the horizontal surface and a vertical face exposed to the air. Penetrant was applied to half of the vertical and horizontal faces, and air was allowed to flow over the test bed for 24 hr. At the end of the 24 hr period the soil and soil/penetrant was removed to a depth of 1/2 in. A soil sample was removed from each half of the block and was weighed to compare moisture loss. These tests showed little difference in moisture loss between the treated and nontreated surfaces. One difference that indicates these moisture loss test results are highly suspect is the large moisture loss fraction (77%) of the untreated surface. This was grossly different than the 13% moisture loss experienced during the Foamer test with untreated soil in a horizontal bed. The block bed should have experienced less moisture loss from below a 1/2 in. cover than a 1 in. thick bed in a tray. Therefore, these moisture retention tests using Penetrant are inconclusive due to sampling problems and should be rerun once a better sampling technique is determined. Penetrant provided a stable and somewhat wear-resistant surface on both the vertical and horizontal components of the soil block penetrating to a depth of approximately 1/4 to 1/2 in.

3.3 Misting Agent Sprays

Two different misting agents (Deter Microfoam and water) and their appropriate application nozzles were tested to determine their effectiveness for dust suppression. The application nozzles included a 90°-angle fan spray nozzle used with the DeTer Microfoam product and a Dry Fog water application nozzle that was developed and marketed by Sonic Development Corporation.

By comparing air samples upstream and downstream of the curtain of DeTer Microfoam spray, it was determined that 36.7% of the respirable dust was removed from the dust cloud by the misting agent. The DeTer Microfoam product is an commercially available organic solution to which wetting agents have been added. The organic solution (concentrated detergent) has been approved for environmental applications. As applied, the solution was metered into a water stream and then passed through a Microfoam generator which produced a fine foam having a texture similar to shaving cream. This material was sprayed from a nozzle at approximately 6 psi and formed a curtain of foam. The fine foam bubbles are of a size that they readily wet the dust in the air and cause it to settle out of the airstream. Foam application rate in gallons per hour of foam was approximately 180 gph. Table 3.4 lists data for the tests performed and calculated suppression factors as determined from both cyclone and Lo-Vol data. The column labeled "Total" is based on calculations which used the sum of the respirable and nonrespirable concentrations (g/l). Suppression factors were calculated by dividing the inlet concentration by the outlet concentration (i.e, g/l inlet + g/l outlet). Average suppression factors were: 5.2 for nonrespirable cyclone data, 2.4 for respirable cyclone data, and 2.4 for Lo-Vol data. The suppression factor for nonrespirable cyclone data translates into 76% of the airborne dust was washed out of the air as it passed through a curtain of foam. For respirable and Lo-Vol data the results translate into 36.7% of the airborne dust was washed out of the air as it passed through a curtain of foam.

TABLE 3.4. SUMMARY OF DETER MICROFOAM TESTS

TEST NO.	SUPPRESSION FACTOR				CLEANUP FACTOR (%)			
	RESPIRABLE	NON-RESP.	LO-VOL	TOTAL	RESPIRABLE	NON-RESP.	LO-VOL	TOTAL
1	1.6	3.3	2.1	3.3	37	70	52	70
2	3.3	5.1	2.2	5.1	70	80	55	80
3	6.5	7.7	1.5	7.7	85	87	33	87
4	1.0	4.2	2.0	4.1	0	76	50	76
5	1.0	5.7	4.3	5.7	0	82	77	82
$\bar{X}$	2.7±2.3	5.2±1.7	3.8±2.1	5.2±1.7	38±39	79±6	53±16	79±6

Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

The Dry Fog misting system produced suppression factor results on the same order of magnitude as the DeTer Microfoam. The Dry Fog misting system uses an ultrasonic nozzle to generate a fine particle size fog. The micro-sized moisture droplets can readily wet airborne dusts and remove them from the air with a minimum water injection rate. The nozzle design uses 7 scfm of air at 65 psi pressure to atomize a water stream. Water use for each nozzle is determined by the head pressure on the water column. At 7-9 psi the flow rate is 5 gph and at 15-20 psi the flow rate is 10 gph. Tables 3.5 and 3.6 list test results for the Dry Fog system and calculated suppression factors for both the cyclone and Lo-Vol sample data for a 10 gph and 20 gph total water use rate, respectively. For three tests run at 10 gph, average suppression factors were: 1.7 for respirable, 5.2 for nonrespirable, and 1.7 for the Lo-Vol. For three tests at 20 gph, average suppression factors were: 3.2 for respirable, 11.4 for nonrespirable, and 6.2 for the Lo-Vol. If the first test results which appear to be unusually high due to potential experimental error are deleted the average nonrespirable value is 20.5 which more closely agrees with the other data. The 10 gph removal factors for each component were: 35%, 79%, and 40% for respirable, nonrespirable, and Lo-Vol fractions respectively. The 20 gph removal factors for each component are: 67%, 88%, and 82%. The 10 gph suppression factors are comparable to the DeTer Microfoam results but were achieved with much lower water application rates. Whereas the 20 gph suppression factors are approximately twice the DeTer microfoam results.

3.4 Dust Suppression Agents

Two different dust suppression agents were tested for effectiveness for use within the inner building where there is moving equipment. These agents were Coherex and Semi-Pave, both Witco Corporation products. During a series of tests each product was applied to a test bed at 25, 50, and 100% of the vendor recommended rates. Test duration was 15 min for the 25 and 50% applications and >20-hr for the 100% application. Test results are listed in Table 3.7. In addition to these tests, a 50 lb sample of RWMC soil was sent to the Witco laboratories for characterization and testing to determine optimum materials application rates. For purposes of the INEL laboratory tests, the suppression factor is calculated by dividing the dry test average airborne concentration by the product test airborne concentration for each fraction respectively.

TABLE 3.5. SUMMARY OF DRY FOG TESTS (10 gph)

TEST NO.	SUPPRESSION FACTOR			CLEANUP FACTOR (%)		
	RESPIRABLE	NON-RESP.	LO-VOL	TOTAL	RESPIRABLE	NON-RESP.
1	1.2	4.1	1.4	3.8	17	76
2	1.4	4.0	1.9	3.6	29	75
3	2.4	7.4	1.8	6.7	58	86
$\bar{X}$	1.7±0.6	5.2±1.9	1.7±0.3	4.7±1.7	35±21	79±6
						40±9
						77±7

Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

TABLE 3.6. SUMMARY OF DRY FOG TESTS (20 gph)

TEST NO.	SUPPRESSION FACTOR			CLEANUP FACTOR (%)		
	RESPIRABLE	NON-RESP.	LO-VOL	TOTAL	RESPIRABLE	NON-RESP.
1	4.0	>300	4.5	>222	75	99.7
2	3.2	2.9	9.0	3.0	69	66
3	2.4	38	5.1	26	58	97
$\bar{X}$	3.2±0.8	114±162	6.2±2.4	84±120	67±9	88±19
						82±6
						87±18

Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

TABLE 3.7. AIRBORNE CONCENTRATIONS AND SUPPRESSION FACTORS FOR COHEREX AND SEMI-PAVE

SOIL TREATMENT	AVERAGE RESPIRABLE	RANGE	AVERAGE NONRESPIRABLE	RANGE	LO-VOL	SUPPRESSION FACTOR	
						RESP.	NONRESP.
RWMC Soil	1.2±0.7E-7	3.8E-8 to 2.3E-7	2.1±1.3E-6	4.4E-7 to 5.1E-6	1.2±0.8E-6		
25% Coherex	1.5±0.7E-8	1.0E-8 to 2.3E-8	1.7±0.7E-7	1.2E-7 to 2.7E-7	1.5±0.1E-7	8.0	3.8
50% Coherex	1.3±0.7E-8	6.7E-9 to 1.3E-8	2.0±0.9E-8	1.0E-8 to 2.7E-8	ND	9.2	105
100% Coherex	4.0±0.7E-10	7.9E-11 to 2.0E-10	0	0	1.3±0.1E-9	300	>1000
25% Semi-Pave	6.7±0.3E-9	3.3E-9 to 1.0E-8	5.5±0.5E-8	2.3E-8 to 1.1E-7	3.9±0.4E-8	18	38
50% Semi-Pave	1.0±0.5E-8	3.3E-9 to 1.7E-8	2.8±1.8E-8	1.7E-8 to 6.0E-8	ND	12	75
100% Semi-Pave	0	0	3.5±0.4E-11	0	1.0±0.1E-11	>1000	60,000

TOTAL SF^a RATIO OF SEMI-PAVE TO COHEREX

% OF APPLICATION	EG&G ^a	GAL/YD ² ^b	WITCO ^c
25	3.5	0.5	1.8
50	0.9	0.75	>1.8
100	150	1.00	>1.4

a. Average of Lo-Vol and respirable plus nonrespirable.

b. Dilution ratio 1:7.

c. Note upper limit of WITCO data 110 mph.

ND = No Data

Errors listed in this table represent a 67% confidence interval or a 1 sigma confidence interval.

Respirable cyclone fraction results for Coherex and Semi-Pave testing indicate that, overall, the Semi-Pave outperforms Coherex when applied to RWMC type soil. This conclusion can be verified with the Witco laboratory test results. However, the Witco researcher's final qualitative judgement was that Coherex was the better product since it demonstrated better soil surface penetration. Improving the suppression factor for the respirable fraction is the more significant for our purposes than improving the overall suppression factor since minimizing the respirable fraction is most critical for worker protection. Suppression factors were calculated and are listed in Table 3.7 for the tests run at the INEL and for one series of tests performed by Witco for the two Witco products. The uncertainties are one sigma standard deviations of the listed data. The remainder of the Witco data are included in Appendix A.

For application at 100% of the manufacturer's recommended application rate the Coherex suppression factor was 300 and >1000 for the respirable and nonrespirable fractions respectively while Semi-Pave had suppression factors of >1000 and 60,000. Overall suppression performance, as measured with the Lo-Vol, was 923 and 120,000 for Coherex and Semi-Pave, respectively. Witco test results are listed in Appendix A as wind speed required to cause initial movement of the test bed when peeling or blasting occurs. The better performance of Semi-Pave is indicated by the higher wind velocities required to show movement of the test bed for similar product application rates.

4. DISCUSSION AND RECOMMENDATIONS

4.1 Respirable and Nonrespirable Dry Soil Characteristics

The most significant results from the soil migration/suspension tests are: (a) that the average respirable fraction for all soil types used in this study was 5.4% and (b) that <4% of the TRU activity in the RFP soil was associated with <45 micron particles of which the respirable size particles are a smaller fraction. In terms of personnel protection (i.e., organ dose)

this indicates that the total allowed airborne concentration of TRU material could be increased by a factor of twenty without decreasing the margin of safety to the worker. For example neglecting the difference between respirable and nonrespirable the airborne concentration upper limit for continued operation is 10,000 times maximum permissible concentration (MPC). By applying this limit to the respirable fraction only, the limit could be increased to 200,000 times MPC. This is consistent with the philosophy used when MPC limits were first established. It is the authors recommendation that the retrieval project adopt the higher limit to avoid unnecessary shutdowns without reducing safety factors.

The behavior of Pu in the environment can be significantly affected by its chemical form and valence state. In these tests Pu was environmentally aged, having been exposed to the environment for several years as a constituent of the surface soil at Rocky Flats, and was therefore in one of the more stable forms. It can be assumed that the Pu in the trenches will have had sufficient time to return to the Pu^{+4} valence state. Further it can be anticipated that the aged Pu has had sufficient time to interact with the backfill soils and to have been tied up by the clay component of the soil, which has a high ionic exchange capacity. The fact that these tests were performed using aged soil provides reasonable confidence that the test results can be applied to the behavior of the TRU wastes buried at the RWMC.

Analytical results for the concentrations of ^{239}Pu and ^{241}Am were used to calculate the ratio of ^{239}Pu to ^{241}Am . The average ratio was 7.5 ± 1.1 . The source of the activity in the RFP soil was probably due to soil blown from the area where leaking drums of Pu-contaminated cutting oil/cleaning solutions were stored on an asphalt pad. This ratio may be of benefit in resolving the controversy [8,9] over the amount of TRU activity in the trenches.

Results of soils emissions testing for the RWMC soil performed by National Environmental Service Company were: (a) for the as-received soil (8.3% surface moisture) impact activities caused no appreciable soil emission, (b) for the air-dried soil (0% surface moisture) the average

emission factor was 0.088 ± 0.014 lb/ton of soil. The range of test results was 0.0709 to 0.109 lb/ton. These compare favorably to estimated EPA-AP42 emission factors^[10] of 0.058 lb/ton for scraping operations and 0.012 lb/ton for backfilling operations. However, the more significant finding was that soil with 8.3% surface moisture did not have an appreciable emission factor. This helps to quantify a conclusion drawn from earlier tests,^[7] that moist soil was not easily aerosolized. Therefore, minimizing natural moisture loss from the dig face is important for controlling airborne contamination.

4.2 Soil Fixatives

Results of testing of the 3M products Foamer and Penetrant show these two products are excellent in suppressing dust from treated horizontal surfaces. Dust suppression factors of >10,000 were calculated using the test results. In reviewing the ability of these products to suppress moisture loss from a treated surface it was found that the product Foamer reduced moisture loss from a horizontal surface by a factor of 9 over untreated surfaces. In two tests the foamed surface lost an average of 1.5% water by weight where the untreated soil lost an average 13% water by weight. The tests performed with the product Penetrant were flawed in the respect that the sampling technique was inadequate. Therefore, there are no good laboratory test data to address the performance of the product Penetrant. However, some information can be implied from laboratory observations made during the scoping tests and actual tests. During scoping tests it was noted that soil underlying the penetrant test area did not dry out as rapidly as the untreated surfaces. During the plexiglass glove box tests, it was again noted that there was a minor difference in the moisture content of the soil on the treated side. This difference was not quantified but was noted as an observation. Also Penetrant was developed by 3M to resist organic vapor loss from the soil. Therefore, in the researcher's opinion, the product Penetrant does not perform as well as Foamer in preventing moisture loss. However, Penetrant should limit some moisture loss and perform within a factor of 3 (i.e., expected moisture loss of 5 to 7%) of Foamer.

Application of either product to a vertical face is the ultimate test as this is the envisioned final use of these products. Only Penetrant as tested satisfied the criteria of being able to be applied to a vertical face to provide dust and moisture suppression capability. Penetrant was developed specifically to readily penetrate to a depth of 1/4 to 1/2 in. and establish a rubberized film within one to two minutes which would resist mild abrasion and suppress organic vapor loss. Lab tests showed this product to readily penetrate premoistened soil. Foamer on the other hand required a 1.5 to 2 min. set time and, therefore, ran off a vertical face before curing was completed. Scoping tests showed that it would adhere to a mild slope (6 to 10%) and still form an acceptable barrier; but that as the slope increased, the product would puddle at the bottom of the slope to a greater extent. The researchers reviewed the 3M product applicator for potential modification and discussed methods for solving the dilemma of how to apply Foamer to a vertical face. Discussions were held with 3M personnel which led to a contact with a company called Boots and Coots who specialize in applications of 3M products. During a discussion with B. J. Smith, one of Boots and Coots' application engineers, the researchers found that Foamer had been applied to a vertical face at a waste site in California. In order to get Foamer to stick to a vertical face the application nozzle was modified and the product formulation was changed to allow for faster curing time. The product was applied in thin coats much like applying furniture finish to a surface, until a 1/8 to 1/4 in. film was built up. Limited product information was obtained from Mr. Smith for our review and is included in Appendix B. Technology is available to successfully apply Foamer to a vertical face.

Application rates and costs are not well defined at this time. The exact technology, product, and application method has yet to be identified. However, in terms of actual cost of product to obtain similar soil and moisture retention capabilities, Penetrant will be less expensive as the product mix is more dilute. Application with penetrant will probably be easier than Foamer as the product sinks into the soil column readily and has minor runoff. However, larger scale tests on vertical surfaces need to be performed to determine actual application costs and product performance for both Foamer and Penetrant.

4.3 Misting Agent Sprays

Test results indicate that Deter Microfoam (applied through two nozzles at a total rate of 3 gpm of water) and Dry Fog (applied through two nozzles at a total rate of 10 gph of water) have essentially the same performance. Average suppression factors were: (a) for the Microfoam 2.7 ± 2.3 , 5.2 ± 1.7 , 3.8 ± 2.1 , and 5.2 ± 1.7 for the respirable, nonrespirable, Lo-Vol, and total fractions, respectively; and (b) for the Dry Fog 1.7 ± 0.6 , 5.2 ± 1.9 , 1.7 ± 0.3 , and 4.7 ± 1.7 for the respirable, nonrespirable, Lo-Vol, and total fractions, respectively. However, when the Dry Fog application rate was increased to 20 gph all of the suppression factors increased, but the more important increase was that of the respirable suppression factor, which nearly doubled. Suppression factors for the higher water application rate were: 3.2 ± 0.8 , 114 ± 162 , 6.2 ± 2.4 , and 84 ± 120 for the corresponding fractions listed above. The large uncertainty of the nonrespirable and total fractions is driven by a large-greater than value observed in one test. If these values are ignored then the suppression factors become 20 and 14 for nonrespirable and total. These suppression factors translate into removal factors which range from 67% to 88% for the 20 gph Dry Fog, 35% to 79% for the 10 gph Dry Fog, and 38% to 79% for Deter Microfoam.

Each of these products has advantages that could be used in several different application situations. Application costs will be significantly less with Dry Fog as the main expenses will be incurred when procuring the nozzles, plumbing the nozzles to a source of demineralized water, and providing a compressor which can supply pressure to the demineralized water storage tank and air to the nozzles. This product should be used where large volume mists will be required (i.e., the dig excavation and loading chutes). With Deter Microfoam, costs will include those associated with the procurement of an applicator system (\$7000 to \$10,000), plumbing of the system to the applicator heads, and procuring the sudsing agent. One disadvantage of Microfoam is that the product is messy to apply, but it rapidly disperses upon contact with soil. This may affect the use of remote TV used to view retrieval operations. Therefore, it is recommended that

this product be used inside a closed system (i.e., enclosed conveyors or transfer chutes). The spray nozzle for the Microfoam may be useful, however, when wetting down a dig face with water. Observations of the water fan formed during cleanup of the Microfoam delivery system showed that the spray nozzle delivered a wide (6 ft high) fan of fine water spray. This would be useful when spraying the active dig face during excavation operations to suppress moisture loss from the soil column.

Rate of application, number of nozzles and total discharge flow rate will be determined by testing at engineering scale for actual applications. Scale tests performed during the current work were limited to a single flow rate of dust through a misting curtain. Actual application will require the suppression of dust that is moving at several velocities such as the air escaping out of a loading chute, the 40 linear feet per minute in the dig area, or the dust boiling up as the soil is transferred to a sorting table. Therefore, each application will require engineering of the suppression head configuration. Much of this engineering would be better supplied by product vendor personnel who have more experience with their equipment and its applications.

4.4 Dust Suppression Agents

Dust suppression agents, Coherex and Semi-Pave, were tested to determine the performance of each product with RWMC soil. Results of the laboratory tests indicate that the Semi-Pave product provided better soil suspension control during glove box tests. Semi-Pave was applied in a 1:7 ratio solution using a rate of 0.75 gal/yd² and Coherex was applied in a 1:4 ratio solution at the same rate. Suppression control was measured at 25%, 50%, and 100% of 0.75 gal/yd². Final suppression factors for each product when applied at 100% were 120,000 and 923 (Lo-Vol results) for the Semi-Pave and Coherex, respectively. Penetration depth into the test bed was similar for both products with the exception that Semi-Pave required approximately 2 min for total absorption as opposed to 30 to 40 s for Coherex. Witco performed tests of the two products on RWMC soil at their facility. Their test results were expressed as wind velocity versus

erosion. Their recommendation, based on test results of the two products, was to use Coherex at a 1:7 solution mixture applied at a rate of 1 gal/yd². This recommendation was based on their observation that Semi-Pave did not achieve good penetration.

What then should be the conclusion based on these seemingly conflicting recommendations? One of the primary objectives of the contamination control program is to limit airborne concentration of respirable dust. Witco tests showed both products will perform adequately. EG&G test results show that Semi-Pave provides a greater suppression factor for the respirable fraction. Therefore, it is recommended that Semi-Pave be used and applied in a 1:7 solution mixture at a rate of .75 gal/yd². Semi-Pave should be applied to the uncovered trench floor as the TRU waste is removed and should be reapplied as equipment wear breaks down the treated soil. Vendor literature indicates that Semi-Pave will "create a near pavement-like surface ... with heavy machinery traffic. ...It is non-toxic, non-corrosive and is environmentally safe..." With this product multiple refresher applications are minimized by increasing surface traffic due to the compacting of the soil/Semi-Pave on the roadway surface.

Product application could be easily accomplished through the use of an applicator nozzle operated from the lifting and moving system (LAMS). The product could be mixed and stored in a tank outside of the inner building and could be delivered to the LAMS through a hose. A second option for application may be manual application by personnel dressed in appropriate anticontamination clothing. These personnel could apply the product to the soil. Use of either product on the prepared concrete floor should be discouraged at this time as it is anticipated that without a substrate to be absorbed by either product would form a tacky floor which may be more difficult to decontaminate than natural concrete. Product application costs should be \$0.37 per yd².

5. CONCLUSIONS

During retrieval of TRU pits and trenches considerable amounts of dust is expected to be generated and waste plutonium and americium particles are expected to cling to this dust. Therefore controlling the spread of plutonium and americium contamination is initially tied to controlling the generated dust. This study has identified and tested in glove box scale several excellent candidate products for dust suppression and fixation agents. In addition misting agents have been identified and tested in a subscale but larger-than-glove box scale. Proper application of these products should provide a work environment that will allow rapid personnel entry dressed in personnel protective equipment commensurate with that environment. Application costs are not trivial but can be minimized through proper matching of product to application and engineering design. Much of the engineering design could be readily obtained through the different product and system vendors. As a general rule, products having relatively inexpensive application costs should be used for larger area applications.

Organic vapor suppression, although a side benefit, could be obtained from the use of the 3M products Foamer and Penetrant. Application of these products to the vertical and horizontal dig surfaces once active digging in an area is completed could help suppress outgassing of organic vapors.

Further engineering scale testing of the candidate product(s) and applicator system(s) is required to determine the best use of these products and proper application rates. Future test design will be reviewed against guidance provided in the EPA's "Handbook of Dust Control at Hazardous Waste Sites,"^[11] These tests are currently scheduled to be performed in FY-1990.

6. REFERENCES

1. G. G. Loomis, P. G. Shaw, S. W. Duce, Environmental Restoration Program Retrieval Demonstration Project Contamination Control Background Studies Sampling and Analysis Plan, EGG-WM-8584, June 1984.
2. P. G. Shaw, G. G. Loomis, Plutonium Contamination Control Studies During A Glove Box Scale Simulated Excavation Of TRU Buried Waste, EGG-WM-8289, October 1988.
3. G. Langer, "Wind Resuspension of Trace Amounts of Plutonium Particles From Soil in a Semi-Arid Climate," 1st International Aerosol Conference, Minneapolis, Minnesota, 1984, pp. 484-487.
4. H. Cember, "Air Sampling Techniques," Air Sampling Training Course, Washington D. C., February 18-19, 1988.
5. F. W. Whicker and V. Schultz, Radioecology: Nuclear Energy And The Environment, to be published.
6. Standard Test Method For Measuring The Dustiness Of Coal and Coke, ASTM D547-41, 1947.
7. S. W. Duce, P. G. Shaw, M. R. Winberg, Effect Of Soil Freezing On Particulate Resuspension, EGG-PHY-8208, August 1988.
8. G. G. Loomis, "Revised TRU Content of SDA Pits And Trenches," GGL-17-88, November 15, 1988.
9. G. G. Loomis, "TRU Content Of Pit 9," GGL-03-89, January 30, 1989.
10. EPA, Compilation Of Air Pollutant Emission Factors, EPA-AP42, 1988, pp. 8.24-1 to 8.24-11.
11. K. D. Rosbury, Handbook of Dust Control At Hazardous Waste Sites, EPA/540/2-85/003, November 1985.

APPENDIX A

WITCO TESTS RESULTS

**Waco
Corporation
Golden Bear Division**

TECHNICAL SERVICE REPORT

Report No.: A2/890526-2
Customer: EG & G Idaho, Inc.
Subject: Dust Control
Date: June 15, 1989

INTRODUCTION

Gene Claussen wrote RLW 1801 to request the determination of the proper application and dilution rates of Coherex® and Semi-Pave to control dust. Soil samples were taken from an AEC site and submitted by EG & G Idaho, Inc.

EXPERIMENTAL

The soil sample was screened to remove everything failing to pass a No. 16 sieve. The soil was treated with either Coherex® or Semi-Pave at varying application and dilution rates. These samples were oven-dried overnight and subjected to wind testing. Appendix A describes the test procedure. Table I records test results.

CONCLUSION

Test results indicate that treatment using a 1.0 gallon per square yard of 1:7 dilute Coherex® provided >110 mph protection from surface movement. Although many of the Semi-Pave treatments also provided this protection, good penetration was not achieved. These treatments appeared to have provided only a surface coating.

Robert L. Staugaard 06-22-89
Robert L. Staugaard Date

Distribution:

<u>S. J. Escobar, Los Angeles</u>	<u>G. W. Trzaska, Oildale</u>
<u>E. W. Burgin, Chandler</u>	<u>J. L. Davis, Oildale</u>
<u>G. A. Claussen, Billings (2)</u>	

RLS/brs

TABLE I

RESULTS OF WIND TESTING OF TREATED EG & G IDAHO, INC. SOIL

Agent	Application Gal/Yd ²	Dilution Ratio Agent : Water	Wind Velocity, mph		Penetration Time (Min : Sec)
			Initial Movement	Peeling or Blasting	
CohereX®	0.50	1 : 7	50	90	<0 : 10
CohereX®	0.75	1 : 7	60	110	<0 : 10
CohereX®	1.00	1 : 7	80	>110	<0 : 10
CohereX®	0.50	1 : 4	50	90	<0 : 10
CohereX®	0.75	1 : 4	70	110	<0 : 10
CohereX®	1.00	1 : 4	>110	>110	<0 : 10
Semi-Pave	0.50	1 : 20	70	>110	0 : 11
Semi-Pave	0.75	1 : 20	>110	>110	1 : 24
Semi-Pave	1.00	1 : 20	>110	>110	2 : 04
Semi-Pave	0.50	1 : 10	80	>110	0 : 27
Semi-Pave	0.75	1 : 10	>110	>110	1 : 32
Semi-Pave	1.00	1 : 10	>110	>110	3 : 04
Semi-Pave	0.50	1 : 7	90	>110	0 : 35
Semi-Pave	0.75	1 : 7	>110	>110	1 : 50
Semi-Pave	1.00	1 : 7	>110	>110	6 : 35
Semi-Pave	0.50	1 : 4	90	>110	0 : 38
Semi-Pave	0.75	1 : 4	>110	>110	5 : 55
Semi-Pave	1.00	1 : 4	>110	>110	8 : 05

APPENDIX A

TEST METHOD - RESISTANCE OF TREATED SOILS TO WIND EROSION

I. SCOPE

- A. This method describes a procedure for measuring the relative resistance of soils to erosion by wind. It is used for evaluating the cohesiveness or binding quality imparted by use of soil treatments.
- B. The equipment used is compact, simple and inexpensive. Figures A1 and A2 show the apparatus in calibrating and in testing positions, respectively. Maximum wind velocity attainable is 120 mph.

II. APPARATUS

- A. Blower Assembly, a vacuum cleaner blower unit with a hose attachment tightly sealed to the inlet hole in one end of the wind tunnel.
- B. Variable Transformer, 25-ampere capacity, to control voltage input to the blowers.
- C. Hose, vacuum cleaner with adapter to fit inlet of wind tunnel.
- D. Miniature Wind Machine, Figures A1 and A2, constructed from wood as a square tube, 12 inches long, having an internal cross section 1-inch square containing two aluminum flow-straightening grids made from thin 1-inch long sheets placed $\frac{1}{4}$ inch apart and fitted into the tube during construction. One end constructed to accept the adapter of the hose from the blower and the other end fitted with a thin plate which extends 2 inches beyond the box to minimize eddy currents from the air stream.
- E. Air Speed Indicator, with Pitot tube for calibration.
- F. Specimen Holders for Compacted Soils, constructed by assembling a box from $\frac{1}{8}$ -inch thick acrylic sheeting, $1\frac{1}{8}$ inches high and 2 inches by 6 inches inside width and length with a "base" set inside the walls to make a $\frac{3}{8}$ -inch deep bin and a $\frac{1}{8}$ -inch deep bin.

III. CALIBRATION - Place the Pitot tube 2 inches from the outlet end of the wind tunnel and calibrate airspeeds corresponding to voltages identified by transformer dial. REMOVE THE PITOT TUBE FROM THE AIR STREAM BEFORE TESTING! (The tube causes turbulence which would interfere with maintaining uniform test conditions.)

IV. PREPARATION OF SPECIMENS

- A. Pour loose, or treated, soil into specimen holder in excess of the amount required. Strike off the excess by rolling a $\frac{1}{4}$ -inch rod from one end to the other of the specimen holder. Lightly tap the surface with a spatula to form a smooth and uniform surface.
- B. Place the filled specimen holder longitudinally in the air stream at the outlet end of the wind machine. Adjust the wind machine so that the thin plate is flush and level with the surface of the test specimen.

V. PROCEDURE - Subject the specimen to wind velocity in 10-MPH increments, starting at 30 mph, using voltages determined by previous calibration. Maintain each increment of wind velocity for 30 seconds or until failure occurs. Record wind velocity at which the soil begins to blast away.

Figure A1. Calibration of Miniature Wind Machine.

Figure A2. Test Assembly of Miniature Wind Machine.

APPENDIX B

BOOTS AND COOTS INFORMATION

BOOTS & COOTS

HAZARDOUS EMISSIONS CONTROL SYSTEMS

**FOAM PROPORTIONING EQUIPMENT, SPECIFICALLY DESIGNED FOR APPLYING
3M BRAND VAPOR SUPPRESSING FOAMS.**

MODEL #80

Portable, skid mounted unit, incorporating our Patented Foam Proportioning Control System, preconnected to a gasoline powered Booster Pump.

The Model #80 is designed to operate utilizing 5 gallon containers of FX-9161 and FX-9162 3M Brand Vapor Suppressing Foam Concentrates.

Cover and Secure 500 FT² per minute of Hazardous or Odorous material through 100 feet of Discharge Hose and Special Air Aspirating Nozzles.

The contractor should provide a reliable source of water supply to the intake of the Booster Pump on the Model #80, (e.g., Water Tanker Truck, Water Hydrant or Static Water Tank).

The Model #80 is generally recommended for use when the exposed surface area of the waste material is considered minimal or when only an occasional application of foam is anticipated.

Weight = 350 Pounds

Dimensions = 3' X 4' X 2' - 24 Cubic Feet

Please contact us for current prices, lease agreements and additional information on this and other available models.

**B.J. SMITH
535 WEST SIXTH STREET
ONTARIO, CALIFORNIA 91762
(714) 983-2788**

END

DATE
FILMED

10/29/92