Fourth Quarterly Report

DOE/PC/79938--T8

DE92 040281

~~July, August, September, 1988~~

Studies of Coupled Chemical and Catalytic Coal Conversion Methods

Contract 22-87PC79938

Department of Chemistry

At The University of Chicago

Chicago, Illinois 60637

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Leon M. Stock, Principal Investigator

Kuntal Chatterjee, Michael Ettinger, and Francis Flores

Research Staff

MASTER

Introduction

This research is directed toward the discovery of a two step liquefaction process. The first step in the sequence will involve a very low severity chemical transformation of the coal that converts the wholly insoluble and intractable coal molecules into materials that are 70-80% soluble in conventional organic solvents. The second step in the sequence will involve catalytic dihydrogen addition to the solubilized coal macromolecules that will produce an even more freely soluble liquid product.

Progress

People. Visiting Associate Professor Mikio Miyake has returned to Japan. Mr. Francis Flores, who recently obtained his BA degree in chemistry from the University of Chicago, accepted admission to the University of California at Santa Cruz in late August. Mr. Kuntal Chatterjee and Mr. Michael Ettinger who are graduate students at the University of Chicago joined the project in the summer.

Direction and Accomplishment. Several considerations prompted us to begin our research with oxygen-poor coal. This tactic enabled us to assess the reactivity patterns of the carbon-rich macromolecules in the absence of the complicating phenolic substances. Considerable progress has been made on the assessment of the utility of non-reductive alkylation for solubilization in pyridine.

A preprint describing the initial accomplishments was submitted as the Second Quarterly Report. That article has been accepted for publication in the Journal of Energy and Fuels. A second preprint describing other recent accomplishments was submitted as the report for the Third Quarterly

Report. This report related the discovery that reaction systems using n-butyllithium and potassium-t-butoxide are very effective for the solubilization of a high ranking bituminous coal.

The emphasis of the experimental work is now shifting to lower ranking Wyodak and Illinois No. 6 coals and the methods for the hydrogenation of the solubilized product. The Fourth Quarterly Report relates the new strategy that is being used in this investigation.

DIHYDROGEN ADDITION STRATEGY

INTRODUCTION:

More efficient coal conversion is being investigated based on the concept that catalytic dihydrogenation addition transformations of the coal molecule will be accelerated if the catalytic agents are covalently incorporated into the coal molecules such that there is an intimate relationship between the catalyst and the target molecule. Exploratory research is being conducted concerning such issues as catalyst selection, the discovery of suitable chemical procedures for the incorporation of the catalysts within the coal, and tests of the hydrogen distribution reactions and the dihydrogen addition reaction.

Selection of the catalyst:

Recently much attention has been focused on the highly dispersed metal species on the catalytic liquifaction of coal¹⁻⁶. Tin compounds have been shown to be one of the metal species effective in the catalytic liquification process. Thus we selected a series of organotin compounds as the initial catalysts to be investigated.

Method of incorporation of the catalyst:

A method for the selective O-alkylation of bituminous coal under mild conditions has been developed^{7,8}. This valuable procedure, which has been used for the synthesis of a variety of modified coals⁷⁻⁹, employs tetrabutylammonium hydroxide or potassium hydroxide as the basic catalyst and an alkyl halide as the alkylation agent.

RESULTS AND DISCUSSION:

The series of organotin compounds to be synthesized will contain three simple alkyl ligands and one primary alkyl halide ligand in order to fulfill the alkyl halide requirement for the O-alkylation reaction.

(iodomethyl)trimethyltin was successfully synthesized according to the method of Seyferth et al.¹⁰ The NMR spectra is shown in Figure 1. In order to test the stability and feasibility of the reaction of (iodomethyl)trimethyltin under the reaction conditions, a model O-alkylation study was carried out using o-cresol as a representative oxygen site that would be found in coal. The reactions were carried out using both potassium hydroxide and tetrabutylammonium hydroxide as the basic catalysts. As expected the reaction using tetrabutylammonium hydroxide gave a pure product of the expected ether in high yield. The reaction using potassium hydroxide gave a lower yield as well as unreacted starting material. The NMR and IR spectra of the pure ether are shown in Figure 2. The IR spectrum shows a characteristic tin-alkyl absorption in the 700-850 cm^{-1} range that will be very diagnostic in analyzing the IR spectra of the coal for alkylation. Following the successful model compound study, the O-alkylation of the coal with (iodomethyl)trimethyltin was attempted. The O-alkylation of coal proved to be successful and was judged so based on three pieces of evidence. First, the elemental analysis of the coals shown in Table 1 gave a tin %wt content of 7.25% and 14.66% (dry basis) for the potassium hydroxide and tetrabutylammonium hydroxide reactions, respectively. These values correspond to an incorporation of 1 and 2 mol of organotin groups per 100 mol carbon. Second, the hydroxyl absorptions in the region 3600-3200 cm^{-1} in the IR spectra of the alkylated coals shown in Figure 3 were markedly less intense as would be expected with the alkylation of these sites. Thirdly, the IR spectra of these alkylated coal samples displayed the very characteristic tin-alkyl absorption that was displayed in the IR spectrum of the pure cresol organotin ether.

Table I. Elemental Analysis of $(\text{CH}_3)_3\text{SnCH}_2\text{-O-Coal}$

Product Composition, %			
Catalyst	Carbon	Hydrogen	Tin
KOH	61.22	4.54	7.25
Bu_4NOH	55.95	4.51	14.66

Figure 1. (a) NMR Spectra of (iodomethyl)trimethyltin.

Figure 2. (a) NMR Spectrum of $o\text{-CH}_3\text{C}_6\text{H}_4\text{OCH}_2\text{Sn}(\text{CH}_3)_3$
(b) IR Spectrum of $o\text{-CH}_3\text{C}_6\text{H}_4\text{OCH}_2\text{Sn}(\text{CH}_3)_3$

Figure 3. IR Spectra of $(\text{CH}_3)_3\text{SnCH}_2\text{-O-Coal}$ using
(a) Potassium Hydroxide as Basic Catalyst
(b) Tetrabutylammonium Hydroxide as Basic Catalyst

EXPERIMENTAL:

A sample of Illinois No. 6 coal was obtained from the Argonne National Laboratory premium coal sample program. Analysis of the coal : C, 77.8%; H, 5.7%; S, 2.6%; ash 16.2%; O (by difference), 9.1%. Tetrahydrofuran was refluxed over potassium metal and distilled prior to use. Zinc, cupric acetate monohydrate, diiodomethane, trimethyltinchloride and tetrabutylammonium hydroxide (1.54 M aqueous solution) were obtained from Aldrich Chemical Co. Infrared spectra were recorded on a Nicolet Model 20SX spectrophotometer. Potassium bromide pellets of the coal products (1-2 wt %) were dried at 110°C for 24 hours before recording the spectrum. Proton NMR spectra were recorded on the University of Chicago 500-MHz spectrometer. Gas chromatographic analysis was carried out on a Perkin-Elmer gas chromatograph Model Sigma 3B fitted with a FID detector. Mass spectrometry analysis was carried out on a VG 7070E mass spectrometer.

Synthesis of (Iodomethyl)trimethyltin:

Granular zinc (2.6 g, 40.0 mg-atom) was added to a hot solution of cupric acetate monohydrate (0.04 g, 0.2 mmole) in glacial acetic acid (4 ml). The hot solution was shaken for 1-2 minutes while heating was continued. The acetic acid was decanted from the settled couple; fresh acetic acid (4 ml) was added and shaken hot for 1-2 minutes and again decanted. The cooled couple was similarly washed three times with portions (8 ml) of diethyl ether. The couple was dried under a stream of nitrogen. To a solution of the dried couple in dry tetrahydrofuran (7 ml) was added a few drops of diiodomethane to initiate the reaction followed by an additional 13 ml of tetrahydrofuran, followed by the dropwise addition of a solution of

diiodomethane (10.75g, 40.2 mmoles) in tetrahydrofuran (7 ml). The reaction was carried out for 150 minutes, occasionally applying mild heating during the last hour, and subsequently was cooled using an ice bath. The solution was filtered using a Schlenk-type apparatus into another flask to which a solution of trimethyltin chloride (4.25g, 21.3 mmoles) in tetrahydrofuran (10ml) was added dropwise over 30 minutes at 40°C. The reaction was carried out for 3 hours. Toluene (25ml) was added to the reaction mixture, followed by extraction with four portions (50 ml) of 5% hydrochloric acid. The organic phase was dried (magnesium sulfate), filtered, concentrated, and the (iodomethyl)trimethyltin was isolated by fractional distillation, b.p. 29-31°C / 1.0 mmHg. ^1H NMR (CDCl_3) δ 0.21 (9 H, s), 1.96 (2 H, s); mass spectrum, m/e 306.

Alkylation of o-Cresol using Tetrabutylammonium Hydroxide :

A solution of tetrabutylammonium hydroxide (1.5 M, 3.9 ml) was added to a solution of o-cresol (0.54g, 5 mmoles) in 15 ml of tetrahydrofuran and was allowed to stir for 30 minutes under nitrogen. A solution of the organotin halide (1.83 g, 6 mmoles) in tetrahydrofuran (3 ml) was added to the mixture and stirred for 48 hours. The mixture was acidified with 2 N HCl, and the tetrahydrofuran was removed on the rotovapor. The oil was taken up in ether and washed with water, and then dried (magnesium sulfate) and concentrated. ^1H NMR (CDCl_3) δ 0.18 (9 H, s), 2.18 (3 H, s), 4.14 (2 H, s), 6.76-7.16 (4 H, m); mass spectrum, m/e 286.

Alkylation of o-Cresol using Potassium Hydroxide:

A freshly prepared solution of potassium hydroxide (1.5 M, 3.9 ml) was added to a solution of o-cresol (0.54 g, 5 mmoles) in 25 ml tetrahydrofuran and

was allowed to stir under nitrogen for thirty minutes. A solution of the organotin halide (1.83g, 6 mmoles) in tetrahydrofuran (5 ml) was added to the mixture and stirred for 48 hours. During workup the mixture was acidified with 2N HCl and the tetrahydrofuran was removed on the rotovapor. The oil was taken up in ether and washed with water. The organic layer was dried (magnesium sulfate) and concentrated. ^1H NMR (CDCl_3) δ 0.18 (9 H, s), 2.18 (3 H, s), 4.14 (2 H, s), 6.76-7.16 (4 H, m); mass spectrum, m/e 286.

Alkylation of Coal using Tetrabutylammonium Hydroxide :

A solution of tetrabutylammonium hydroxide (1.5 M, 2.6 ml) was added to a suspension of coal (1g) in tetrahydrofuran (25 ml) and the mixture was stirred under nitrogen for 6 hours. A solution of the organotin halide (6.1g, 20mmoles) in tetrahydrofuran (5 ml) was added to the mixture and stirred for 48 hours. During workup the mixture was acidified (pH 2) with 2N HCl and the tetrahydrofuran was removed on the rotovapor. The residue was transferred on to a membrane filter (pore size $.8\mu\text{M}$) and washed with water (100 ml), 80% methanol-water mixture (100 ml) and then methanol (100 ml). The coal samples were dried under vacuum (110°C) to a constant weight.

Alkylation of Coal using Potassium Hydroxide:

A freshly prepared solution of potassium hydroxide (1.5 M, 2.6 ml) was added to a suspension of coal (1g) in tetrahydrofuran (25 ml) and the mixture was stirred for 6 hours. A solution of the organotin halide (6.1 g , 20 mmoles) in tetrahydrofuran (5 ml) was added to the mixture and stirred for 48 hours. During workup the mixture was acidified (pH 2) with 2N hydrochloric acid and the tetrahydrofuran was removed on the rotovapor. The residue was transferred on to a membrane filter (pore size $0.8\mu\text{M}$) and washed with

water (100 ml) , then 80% methanol-water mixture (100 ml), followed by methanol (100 ml). The coal samples were dried under vacuum (110 °C) to a constant weight.

REFERENCES:

1. Kamiya, Y., Nagae, S., Yao, T., Hirai, H. and Fukushima, A., Fuel, 1982, **61**, 906.
2. Cassidy, P.J., Herten, P.A., Jackson, W.R., Larkins, F.P., and Rash, D., Fuel, 1982, **61**, 940.
3. Garg, D. and Given, E.N., Fuel Process Tech., 1983, **7**, 59.
4. Chien, P.L., Chao, H. and Weller, S. W., I &EC, Process Des. Dev., 1983, **22**, 662.
5. Cook, P.S., Cashion, J.D., and Cassidy, P.J., Fuel, 1985, **64**, 1121.
6. Suzuki, T., Ando, T., Yamada, O., and Watanabe, T., Fuel, 1986, **65**, 786.
7. Liotta, R.J., Am. Chem. Soc., 1981, **103**, 1735.
8. Ettinger, M., Nardin, R., Ray Mahasay, S., Stock, L. M., J. Org. Chem., 1986, **51**, 2840.
9. Rose, G. R., Zabransky, R. F., Stock, L. M., Huang, C., Srinivas, V. R., and Tse, K. W., Fuel, 1984, **63**, 1339.
10. Seyferth, D. and Andrews, S. B., J. Organometal. Chem., 1971, **30**, 151.

END

**DATE
FILMED**

10 / 28 / 92