168
2-24-76

Dr-2120

ANCR-1255

UC-2

DATE PUBLISHED — FEBRUARY 1976

MASTER

IDAHO NATIONAL ENGINEERING LABORATORY

NUCLEAR TECHNOLOGY DIVISION
ANNUAL PROGRESS REPORT
FOR PERIOD ENDING JUNE 30, 1975

PREPARED BY AEROJET NUCLEAR COMPANY FOR
ENERGY RESEARCH AND DEVELOPMENT ADMINISTRATION

IDAHO OPERATIONS OFFICE UNDER CONTRACT E(10-1)-1375

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency Thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

DISCLAIMER

Portions of this document may be illegible in electronic image products. Images are produced from the best available original document.

Printed in the United States of America
Available from
National Technical Information Service
U. S. Department of Commerce
5285 Port Royal Road
Springfield, Virginia 22161
Price: Printed Copy \$12.75; Microfiche \$2.25

NOTICE

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the Energy Research and Development Administration, nor the Nuclear Regulatory Commission, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

ANCR-1255

DISTRIBUTION UNDER CATEGORY:
UC-2
General, Miscellaneous, and
Progress Reports (Nuclear)
TID-4500, R63

NUCLEAR TECHNOLOGY DIVISION ANNUAL PROGRESS REPORT
FOR PERIOD ENDING JUNE 30, 1975

R. L. Heath
Nuclear Physics
Branch

J. W. Henscheid
Reactor Technology
Branch

G. L. Smith
Instrumentation and
Measurement Branch

AEROJET NUCLEAR COMPANY

Date Published - February 1976

PREPARED FOR THE U.S. ENERGY RESEARCH & DEVELOPMENT ADMINISTRATION
IDAHO OPERATIONS OFFICE
UNDER CONTRACT NO. E (10-1)-1375

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

FOREWORD

This document is a report of progress on technical programs of the Nuclear Technology Division of Aerojet Nuclear Company for FY 75 ending June 30, 1975. It contains abstracts or expansions of abstracts of papers which have been published within the year. In these cases, preprints or reprints of the articles are available. Results of work in progress are also reported; since this work is of a preliminary nature, the authors should be contacted before including any reference to these works in other publications.

CONTENTS

FOREWORD.	ii
A. NUCLEAR PHYSICS	1
Nuclear Structure	3
Energy Levels of ^{250}Cf Populated in the Decay of ^{250}Bk	5
Level Structure of ^{172}Yb from the ^{171}Yb (n, γ) Reaction.	6
Decay of ^{128}Ba	8
Decay of ^{131}Ba	14
Half-life Measurements of ^{134}La , ^{132}Ce , ^{133}Ce , ^{134}Ce , and ^{135}Ce	21
Expanded Data Content for the Radioactive-Nuclide Decay Data for ENDF/B	25
Decay Data Master File at INEL.	27
Radiation Measurements.	33
Reevaluation of Precise Gamma-Ray Energies for Calibration of Ge(Li) Spectrometers	35
Relative Gamma-Ray Intensity Measurements with a Ge(Li) Spectrometer	43
Analysis of 4π β - γ Coincidence Data From Radionuclides with Short Half-Lives	44
Fast Neutron Damage Effects in Silicon Surface Barrier Detectors.	47
Collection and Recovery of Milligram Quantities of Mass- Separated Isotopes	51
Preparation of Radioactive Sources with the Electromagnetic Isotope Separator.	56
Isotope Separator Laboratory Development and Upgrade.	60
Development of an On-Line Isotope Separator Facility for Fission-Product Decay Studies Using a ^{252}Cf Spontaneous Fission Source	65
High Rate 4π β - γ Coincidence Electronics.	76
High Rate Gated Baseline Restorer for Ge(Li) Detector Systems	78
Automation of Radiation Measurements Laboratory Operations.	79
Bulk Monitoring of Soil for Low Level Transuranic Contamination.	81
Design of a Monitor for Large Boxes Containing Low Level Transuranic Wastes	88
The INEL Radiation Measurements Laboratory.	96
B. APPLIED REACTOR PHYSICS	97
Experimental Measurements	99
Manganese Bath Systematic Effects in Measurements of nu-bar and eta.	101
Measurement of the Ratio of the Absorption Cross Sections for Manganese and Hydrogen	104
^{94}Nb Cross Section Measurements for CTR Technology.	106

Fission Product Reaction Rates for ^{235}U in NBS Thermal Facility	108
Gamma Scan of PBF Fuel Rod Stacks	112
Intercomparison of Gamma Analysis of PBF Fuel Sample.	117
Experimental Results of Non-Destructive Analysis Measurements of LWBR Rods in the ARMF	120
Model and Code Development.	123
Hybrid Simulation of a Loss of Coolant Accident in a Pressurized Water Reactor.	125
Validation of KENO Code for HTGR Criticality Safety Calculations	129
Thermal Data Testing of ENDF/B Version IV Data.	131
The ETOP-14 Code for the Generation of Version IV ENDF/B Multigroup Cross-Section Libraries of PHROG II	134
REMFAP Computer Code	141
Modification to RELAP/4 Computer Code	142
Correlation Effects in the RAFFLE Monte Carlo Code.	144
Digital Program for Inverse Solution of the Reactor Kinetics Equations.	149
PWR Waste Gas Treatment System Dose Evaluations Under Upset Conditions	151
A Perturbation Code for PDQ-7	152
Some Auxiliary Codes for PDQ Synthesis Calculations	154
An Empirical Model for ATR Physics Parameters	155
Preliminary Codes for the ATR Empirical Model	157
Supplemental Computer Codes for ATR Core Safety Assurance Data Reduction	158
RELAP/4 Benchmark Summary	159
A Digital Simulation of the LOFT Reactor Coolant Pumping System	160
Safety Analysis for the LOFT Final Safety Analysis Report	162
GRIST Loop Modeling and Simulation.	163
Implementation of TAF (Time and Frequency) Simulation Program on CDC 7600 Computer	165
A 360/75 Fortran Program to Generate A Sequence Control Pattern.	166
Fortran Program to Tabulate Gamma Ray and Internal Conversion Data	167
360 Assembly Language Programs to Convert Between Paper Tape and Cards.	170
Reactor Experiment Design Studies	171
Preliminary Feasibility Design Study for a Thorium-Cycle Pebble Bed Breeder Reactor.	173
Feasibility Studies for Shaping the Axial Power Distribution in a 25-Rod Flow Blockage Test in PBF	176
Power Level and Distribution in Widely Spaced Clusters of PWR Type Rods for Gap-Conductance Tests in PBF	179
Power Change in a BWR/6 Fuel Bundle Following a Complete Flow Blockage	184
Power Level and Distribution in Widely Spaced Clusters of PWR Rods in PBF for Irradiation Effects and Simulation Tests.	187

Physics Studies for a PBF Reload Core for Steady-State Testing.	189
Preliminary Physics Calculations for GRIST program in ETR.	191
Shaped Burst Feasibility for N-Series Test in PBF	195
Proposed Modifications to the Coupled Fast Reactivity Measurement Facility for Raising the Power Level to 100 kW.	196
Calculations.	199
Criticality Calculations on HTGR Primary Burner	201
ARMF Phase-II Cask Shielding.	202
 C. EXPERIMENTAL TECHNIQUES & INSTRUMENTATION	 203
Linear Electronic Device Models for ECAP.	205
Experimental Test Results for a pv^2 Probe Employing a Drag Screen.	210
Two-Beam γ Densitometer Interpretation Procedure.	217
Irradiation Test on Metal-to-Ceramic Seals Used in the LOFT Liquid Level Probe	220
Correction of Temperature Effects in ANC Free Field Pressure Transducers.	224
Domain Reflectometry for Dynamic Fuel Rod Cladding Deformation Measurements	225
Steam Temperature Transducer Development.	227
Small Diameter, 200 psi, 1100°F Pressure Transducer	231
High Temperature Magnetic Turbine Pickup.	234
Drag-disk with Insensitivity to Pressure and Temperature Transients	237
Strain Gage "Switch" for PWR Environment.	240
Four Tungsten Alloys for use as Ultrasonic Thermometer Sensors.	244
Zircaloy-to-Stainless Steel Thermocouple Splice	247
Laser Weld Attachment of Zircaloy-Sheathed Thermocouples to Zircaloy Fuel Rod Cladding	249
Improved Ta/SST Transition Thermocouple	251
Thermocouple Correlation Flowmeter: Preliminary Experiments in Semiscale.	253
A Conductivity Sensitive Liquid Level Probe for Semiscale Transient Flood Tests.	257
Cross-Assemblers for Minicomputers.	259
A Remotely-Controlled Nuclear Pulse-Height Analyzer for Environmental Monitoring	260
A Computerized Coulter Counter Blood Analysis System at Johnson Spacecraft Center.	262
Temperature Characteristics of a Sodium Iodide Detector with a Light Emitting Diode	263
An Ultrasonic Detector for Measuring Small Volumetric Flow Rates at the Chemical Processing Plant (CPP)	268
A Pulsed Eddy Current Inspection System	271

D. PROGRAM SUPPORT	273
Test Reactor Operations Support	275
Reactor Critical Electrical Load Transfer Analysis.	277
Criticality of Hot Cell Transfer Casks.	278
TRA Fuel Storage.	279
Reactor Physics Calculations in Support of the ETR Technical Specifications	280
Experimental Technical Support for the ETR Requalification Tests.	285
The Nuclear Kinetics Analysis for the ETR Technical Specifications	287
Neutron Noise Measurements for the Requalification of ETR	289
Safety Assurance Calculations in Support of the ATR	290
A Summary of ATR Shim Predictions	291
ATR Power Variation Surveillance.	293
ETR Plant Protection System Upgrade	294
Power Burst Facility.	295
Upgrading the ATR Clad Gage Inspection System	297
Digital Control for a Solid State MOR	300
R-2R Ladder Network for Digitally Controlled Programmable Gain for an Operational Amplifier.	303
Reliability Study for the ATR Plant Protection System Upgrade.	309
ATR Resistance Temperature Detector Response Study.	313
Computation of Temperature Coefficients, Boron Worth, and Control Rod Worth at BOL and 1000 EFPH Using XYZ Synthesis in PDQ-7	317
PBF Reactor Responses to Rod Motion	318
PBF Power Fluctuation Diagnostics	324
PBF Gap Conductance Measurements.	335
Power Distribution for the Nine-Rod Lead Test in PBF.	339
Single Rod Power Levels in PBF for the PCM-20 Test Series	341
Loss of Fluid Test.	343
Computation of the Uniform Moderator Void Coefficient (LOFT-I: Beginning of Core Life).	345
Energy Deposition in the LOFT Reactor at 54.71 MW	348
Three-Dimensional PDQ-7 Calculations with Thermal Feedback for LOFT-I with Depletion to 2000 EFPH	349
Three-Dimensional Synthesis Calculations for the LOFT-I Stuck Rod Accident (Shutdown Margins, Power Distributions and Recritical Temperatures)	351
Computation of k_{eff} as a Function of the Fuel Loading Sequence in LOFT-I.	353
Critical Boron Concentration Versus Control Rod Position in LOFT-I.	354
Three-Dimensional PDQ-7 Calculations for Replacement of the LOFT-I Central Fuel Module After 200 EFPH.	355
Effect of Fuel Burnup on LOFT Temperature Coefficients, Boron Worth, and Control Rod Worth	356
PBF Fuel Rod Motion Sensors	357

Fabrication of Internally Instrumented Zircaloy Clad Fuel Rods	358
Ti/Inconel Fuel Rod End Cap Testing	361
Thermal Cycling and Calibration of Zircaloy-Sheathed Cladding Thermocouple.	362
Semiscale	363
Effects of Cable Length on LOFT DTT Performance	365
LOFT Suppression Tank Simulation Testing in Semiscale Facility	369
Semiscale Heater Power Monitor System	370
Semiscale Test Operational Modifications and Start Up	371
Infrared Scan Evaluation of Semiscale Heater Rods	372
Semiscale Downcomer ECC Performance	375
Non-Nuclear Programs.	377
Conceptual Design of Liquid Fuel and Temperature Measurements System for the CPP Waste Storage Tank Farm	379
Conversion of a 400-in ³ I.C. Engine to Operate on Hydrogen	383
Geothermal Steam Plant Modeling and Power Trade-Off Studies.	384
Heat flow Measurements in Snow Fields Covering Prospective Geothermal Areas	385
Radon Emission Distribution Near Raft River Geothermal Areas.	388
Effects of Geothermal Power Plant Cooling Water Wells of Raft River Basin Cold Water Aquifer Hydrology.	389
Southeastern Idaho Wind Power Scoping Calculation	394
Sythetic Fuels from Coal Studies.	396
Schlumberger Measurement Field Pack	398
 E. RELATED ACTIVITIES OF DIVISION PERSONNEL.	 399
Professional Activities of Division Personnel	401
Reports Issued During FY 1975	402
Presentation of Technical Papers.	403
Papers Published in the Open Literature	407

FIGURES

A. NUCLEAR PHYSICS

. Level scheme for ^{172}Yb based upon the $^{171}\text{Yb}(n,\gamma)$ reaction studies with our proposed grouping of states into rotational bands.	7
. Proposed decay scheme of ^{128}Ba	13
. Gamma-ray spectrum of ^{131}Ba taken with a 65 cm^3 $\text{Ge}(\text{Li})$ detector at a 10 cm source-detector distance	18
. Spectrum of ^{131}Ba γ rays in coincidence with the 216-keV γ ray.	19
. Decay scheme of ^{131}Ba	20
. Block diagram of electronics used to observe time spectrum of coincidence events in a pair of Si surface barrier detectors.	48
. Spectra taken when (a) no fast neutron damage had occurred and (b) when the detectors had been exposed to $\sim 10^{13}$ n/cm ²	49
. Time spectra showing effects of changes in field strength and depletion depth.	50
. Block diagram illustration of an on-line isotope separator which utilizes a gas-jet transport system.	71
. Schematic illustration of gas-jet transport system used for series-I measurements.	72
. Schematic illustration of gas-jet transport system used for series-II measurements	73
. Range curves in helium for heavy-mass-peak fission fragments from spontaneous fission of ^{252}Cf	74
. Range curves in helium for light-mass-peak fission fragments from spontaneous fission of ^{252}Cf	75
. Top view of sample - detector geometry showing source locations.	87
. Conceptual layout of waste box monitor	92
. Slab neutron detector design	93
. Geometry for calculating approximate response of slab detector array to a centered line source	94

. Calculated response of cylindrical detector array to a line neutron source.	95
B. APPLIED REACTOR PHYSICS	
. ARMF core.	121
. Reactivity worth of LWBR Calibration rods.	122
. Schematic of plant system as subdivided for analysis	127
. Program schematic.	128
. Previous RAFFLE initialization strategy.	146
. X random numbers initialized at each history	147
. Last random number of problem 1 input as first random number of problem 2.	148
. Closed-loop solution of reactor kinetics for ΔK	150
. LOFT primary coolant pumping system.	161
. Schematic of spherical geometry pebble bed reactors.	175
. RAFFLE model 25-Rod BWR-6 test in PBF.	177
. Effect of stainless steel shaper for axial power flattening in the blocked flow case	178
. BWR/6 test pin power (uncorrected) vs. w/o enrichment. . . .	181
. RAFFLE model 4-in-1 hardware	182
. Relative power for RAFFLE region sets 15% enriched rod in the PBF 4-in-test (σ')	183
. Representative section of BWR/6 core	186
. RAFFLE model of PBF in-pile tube region with quad hardware	188
. Analytical model of the Grist Loop located outside of the double pressure vessel	194
. Flow diagram for reactor coolant for CFRMF when operating at a power level of 100 kW	195

C. EXPERIMENTAL TECHNIQUES & INSTRUMENTATION

. Ebers-Moll small signal transistor model	208
. The mathematical model for the IC operational amplifier.	208
. ECAP model of the operational amplifier.	209
. Modified ρv^2 probe with drag screen.	212
. Flow calibration curve for drag screen ρv^2	213
. Flow calibration curve for drag disk ρv^2	214
. Force calibration curve for drag screen ρv^2	215
. Force calibration curve for drag disk ρv^2	216
. Geometry of the two-beam gamma densitometer which was analyzed	219
. Cross-Section of Metal-to-Ceramic Seal Area.	223
. TDR response for various diametrical changes of the central rod.	226
. TDR response	226
. Steam temperature probe.	229
. Steam temperature probe.	230
. The Basic Components of the Eddy Current Read-out.	232
. Eddy Current Coil Assembly	233
. Individual Parts of Magnetic Pickup.	235
. Assembled Magnetic Pickup.	236
. Individual Parts of Drag Disk.	238
. Assembled Drag Disk.	239
. Leaf spring sensor for piston position monitor, shown in both strained and unstrained states	242
. Block diagram of piston position monitor signal conditioning electronics	243
. Diagram of ultrasonic thermometer and associated temperature-dependent signal	245

. Completed Zircaloy-stainless steel thermocouple sheath splice, utilizing explosion-bonded titanium/Inconel splice sleeve.	248
. Photograph of Zircaloy-sheathed thermocouple measuring junction, lazer-welded to Zircaloy fuel rod cladding	250
. Components of Ta/SST transition thermocouple prior to assembly	252
. Radiograph of the splice area of the fully assembled Ta/SST transition thermocouple.	254
. Location of thermocouples in Semiscale core.	255
. Power spectral density curves from tape channels 7 and 8, 1 to 11 seconds after the beginning of blowdown.	256
. Semiscale Liquid Level Probe	258
. Peak positions as a function of temperature.	266
. Energy Equivalent of LED pulse as a function of Temperature.	267
. Ultrasonic transit time flowmeter block diagram.	269
. Photograph of the fitting and Piezoelectric crystals that make up the transmitt and receive transducers.	270
. A portion of the data trace from irradiated fuel rod "835".	272
 D. PROGRAM SUPPORT	
. ETRC calculated versus ETRC measured percent core powers at xenon equilibrium conditions.	284
. ATR Clad gage inspection system.	299
. Block diagram of digital system.	302
. 4 bit R-2R ladder.	306
. R-2R ladder hookup with inverting operational amplifier. . .	306
. System of digitally programmed gain change	307
. R-2R in feedback	307
. R-2R Ladder for generating inverse function.	308
. Typical PPS configuration.	312

. Shim withdrawal accident	315
. RTD response to shim withdrawal accident	316
. Comparison of PBF power reduction transients of run 75B with simulated transients.	320
. PBF frequency at a nominal power of 0.46 MW.	321
. PBF frequency response at a nominal power of 5.0 MW.	322
. PBF frequency response at a nominal power of 7.6 MW.	323
. Power spectral density functions of PBF neutron power fluctuations	329
. PBF power fluctuation RMS/mean ratios as a function of nominal power.	330
. Time traces of temperature signal from instrumented fuel pin in PBF reactor	331
. Run 75 power history	332
. Summary of cladding temperature fluctuations on Test Rod 9 as measured by TC #6 during Run 75	333
. Comparison of the cladding surface fluctuations on Test Rod 9 at various power levels.	334
. Nine-rod PBF experiment.	340
. Test space portion of the SCAMP model (single rod tests) . .	342
. Reactivity of LOFT reactor as a function of Moderator Void Fraction	346
. LOFT reactivity with stuck rod	352
. Schematic diagram of PCM-20 fuel rod end cap	360
. Schematic of DTT VRT system.	368
. Transient tests.	373
. Representative scan of high power heater	374
. Conceptual design of CPP tank farm instrumentation system	381
. Temperature profiles at the three test sites	387

. Gird overlay of Raft River Valley defining the aquifer boundary and the approximate location of a proposed 10 megawatt power station	391
--	-----

TABLES

A. NUCLEAR PHYSICS

. Energies and Intensities of γ Rays from ^{128}Ba	11
. Summary of γ - γ Coincidence Results	12
. Energies and Relative Intensities of γ Rays from the Decay of ^{131}Ba	17
. The Measured Half-Lives of ^{134}La and $^{132-135}\text{Ce}$ from the Present Investigation.	23
. Comparison of Half-Life Values from the Present Investigation to Those from Previous Studies	24
. Input Format for the Decay Data Master File.	29
. Quantities from Adjustments of the Fundamental Constants . .	38
. Comparison of some Bent-Crystal Measurements	39
. Analysis of γ -Ray Energies from ^{192}Ir Decay.	40
. Summary of γ -Ray Energies.	41
. Chemical Procedure for Rare Earth Recovery	54
. Isotopic Enrichment of Nd Samples.	55
. Isotope Separation of Tb, Ba, and Ce Radioactive Samples.	59
. Summary of Operation with Surface Ionization ION Source. . .	64
. Summary of Gas-Jet Transmission Experiments: Series I . . .	69
. Summary of Gas-Jet Transmission Experiments: Series II. . .	70
. Shaping Time - 6 μsec to Peak 1.33 MeV Co^{60} Peak	80
. Plutonium and Americium Standards.	84
. Results of Measurements on Simulated Contaminated Dirt . . .	85
. Expected Uncertainties for 30 Second Run Using 3" x 3" NaI(Tl) Detector on 12" x 12" x 3" Dirt Sample	86

B. APPLIED REACTOR PHYSICS

. Reanalyzed η Values.	102
. Decay Parameters	107
. Parameters of ^{235}U -1 Foil and the γ -Ray Counting	109
. Consistency of Reaction Rates - ^{103}Ru	110
. ^{235}U Reaction Rates for NBS Thermal Irradiation.	111
. Measured Gamma-Ray Intensities from Fuel Rod Stack #2838 . .	114
. Measured Gamma-Ray Intensities from Fuel Rod Stack #2341 . .	115
. Relative Gamma-Ray Intensities from Fuel Rod Stack #2838 . .	116
. Average Results of our Four Measurements	118
. Results of RML Measurements.	119
. Calculated k_{eff} of Uranium Thorium Critical Experiments. . .	130
. Calculated Values of Neutron Multiplication (k_{eff}), for Selected Thermal Reactor Benchmarks, Using ENDF/B Version IV Data.	133
. Example of the Printout.	168
. Parameters for Grist Mixed Oxide Pellet.	192

C. EXPERIMENTAL TECHNIQUES & INSTRUMENTATION

. M3-3 In-Pile Loop Operating Conditions	221
. LLT Electrode Impedance in X1000 OHMS in the M3-3 Loop During the ETR Test.	222
. Flow Resistance Test Data.	228
. Summary of UT Temperature Sensitivity Data Versus Material and Frequency.	246

D. PROGRAM SUPPORT

. Reactivity Worth of Aluminum Void Simulators in ETRC	283
. Inverse Function f	305
. Summary of Run 72 TC Temperature Data.	328
. Data from the Thermal Oscillator Feasibility Test.	337

. Comparison of Rod Power Fractions for Nine-Rod Lead Test	339
. Comparison of Present Loft Design with Design Used in Previous Calculations.	345
. Cable Properties	367
. Change in Water Table Height After 10 Years of Pumping and Re-Injection at 3000 GAL/MIN at Each Indicated Well Location	392
. Change in Water Table Height After 10 Years of Pumping and Re-Injection at 3000 GAL/MIN at Each Indicated Well Location	393

A. NUCLEAR PHYSICS

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

Nuclear Structure

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

ENERGY LEVELS OF ^{250}Cf POPULATED IN THE DECAY OF ^{250}Bk

C. W. Reich, R. G. Helmer

The level scheme of ^{250}Cf has been investigated by studying the γ radiation emitted following the decay of 3.2-h ^{250}Bk . The ^{250}Bk activity was produced in the α decay of 276-d ^{254}Es . Previous studies (see, e.g., ref. (1)) of the ^{250}Bk decay have identified 7 γ -ray transitions and led to the proposal of a ^{250}Cf level scheme consisting of the $I^\pi = 0^+, 2^+$ and 4^+ members of the ground-state band and the $I^\pi = 2^+$ and 3^- members of the γ -vibrational band.

In the present investigation, the γ radiation has been studied using a variety of large-volume $\text{Ge}(\text{Li})$ spectrometers and, for the low-energy (~ 0.1 MeV) photon spectrum, a $30\text{ mm}^3 \times 3\text{ mm}$ $\text{Si}(\text{Li})$ detector. In addition, $\gamma\gamma$ coincidence measurements have been carried out with gates set on all the prominent γ rays and selected "background" regions of the spectrum. Analysis of these data has revealed the existence of ~ 40 γ ray transitions and has led to the construction of a level scheme for ^{250}Cf which at present contains 13 excited states. Among the interesting features of the ^{250}Cf level structure which have thus far emerged from the analysis of these data is the location of a $K^\pi = 2^-$ band, presumably an octupole vibrational excitation, at 871 keV. As such, this band represents the lowest-energy intrinsic (i.e., nonrotational) state thus far observed in ^{250}Cf .

(1) P. H. Stelson, R. W. Lide and C. R. Bingham, Nucl. Phys. A144 (1970) 254.

LEVEL STRUCTURE OF ^{172}Yb FROM THE $^{171}\text{Yb}(n,\gamma)$ REACTION

R. C. Greenwood, C. W. Reich, S. H. Vegors, Jr.*

The following is the abstract of a paper which has been accepted for publication in Nuclear Physics A. The ^{172}Yb level scheme which has been proposed as a result of this investigation is shown in fig. 1.

The energy-level structure of the nucleus ^{172}Yb has been studied using the $^{171}\text{Yb}(n,\gamma)$ reaction with both thermal and 2-keV neutrons. Gamma-ray energy and intensity measurements were made using Ge(Li) detectors. From these data, a neutron separation energy of 8020.1 ± 0.5 keV has been determined for ^{172}Yb . In addition, a level scheme is proposed for ^{172}Yb . Where possible, these states have been grouped into rotational bands. A total of 14 such rotational bands with band-head energies below 2.2 MeV are contained in the proposed level scheme. Because of the averaging feature of the 2-keV neutron-capture data, it is believed that all the positive-parity states with $I=0, 1$ and 2 with energies below 2.3 MeV in ^{172}Yb have been identified in this study. Other noteworthy features of the level scheme are the following. Octupole-vibrational bands with $K^\pi=0^-, 1^-, 2^-$ and 3^- are observed, with band-head energies of 1599, 1154, 1757 and 2030 keV, respectively. Four excited $K^\pi=0^+$ bands, with band-head energies of 1042, 1404, 1794 and 1894 keV, have been located; and it is proposed that these constitute all the excited 0^+ bands below 2.3 MeV in ^{172}Yb . Two bands, having $K^\pi=1^+$ are established, with band-head energies of 2010 and 2194 keV. A Coriolis-mixing analysis has been made of the energy-level structure of the $K^\pi=0^--3^-$ octupole bands, and good fits to the observed level energies have been obtained. The E1 γ -ray branching to the ground-state band of the $I^\pi=1^-$ and 3^- members of the $K^\pi=1^-$ band is observed to deviate markedly from the Alaga-rule predictions. These branching ratios can be accounted for quite well in this analysis assuming a value of $+(0.028 \pm 0.001)$ for Z , the ratio of the intrinsic E1 matrix element with $|\Delta K|=1$ to that with $\Delta K=0$.

* Physics Department, Idaho State University, Pocatello, Idaho 83201.

Level scheme for ^{172}Yb based upon the $^{171}\text{Yb}(n, \gamma)$ reaction studies with our proposed grouping of states into rotational bands. An arrow into a level indicates population by primary γ -ray transitions. Solid triangles associated with a level indicate that the level is populated by charged particle reactions: upper left indicates (d,p) population; lower left indicates (d,t) population; upper right indicates (d,d') population; and lower right indicates (p,t) population. Open triangles indicate tentative assignments.

DECAY OF ^{128}Ba

R. G. Helmer, R. J. Gehrke,
R. C. Greenwood, C. W. Reich, L. D. McIsaac^(*)

An experimental program has been undertaken to carry out nuclear structure studies on neutron-deficient isotopes off the line-of-stability. As part of this program several ^{128}Ba samples were produced by the irradiation of praseodymium metal foils with ~ 800 MeV protons in C. P. Anderson Meson Physics Facility (LAMPF). Typical irradiations were for 5-15 $\mu\text{A}\cdot\text{h}$ with a target of 0.3 gm of Pr. The activated foils were shipped from LAMPF to the INEL where the experiments were performed.

The initial measurements were carried out with chemically purified barium samples in which the only activities observed were $^{128}\text{Ba}(2.4\text{d}) \rightarrow ^{128}\text{Cs}(3.9\text{m})$, $^{131}\text{Ba}(11.7\text{d})$ and $^{133}\text{Ba}(10.4\text{y})$. Subsequent measurements were made with ^{128}Ba samples that were isotope separated after they were chemically purified. In all of these measurements, the ^{128}Cs was in equilibrium with the ^{128}Ba parent. The final set of measurements was made on samples while a continuous Ba-Cs separation was being performed by means of the differences in solubility of the Ba and Cs ions on a BaSO_4 column. By using the column as the source, an enhancement of the Ba/Cs activity ratio between 2 and 7 was obtained.

By comparison of the γ -ray intensities observed in spectra from the Ba enhanced sample to those for samples at equilibrium, it was shown that the γ rays at 215, 229, 273, 359 and 374 keV are definitely associated with the ^{128}Ba decay. These data also suggest that the lines at 101, 129, 143, 159, 187 and 317 keV are from the ^{128}Ba decay. Previously⁽¹⁻³⁾ only the 273-keV transition has been assigned to the Ba decay. The γ -ray energies and relative intensities determined for these transitions are given in Table I. The energies of the stronger lines (i.e., 215, 229, 273, 359 and 374 keV) were determined primarily from isotope separated samples with the ^{128}Cs in equilibrium. These spectra were calibrated with known-energy lines from other sources. The energies of the weaker lines come from measurements with the Ba-enhanced samples and were only calibrated with the known energies in ^{128}Ba - ^{128}Cs . The intensities of the weaker lines also come from the Ba-enhanced measurements, while those of the stronger lines come from both types of sources. The analyses of the 187-keV line indicate that it is a doublet since it is wider than expected for a single γ ray.

The conversion of the relative γ -ray intensities to absolute values involved several measurements including data for the daughter activity. From the photon spectrum of an equilibrium source measured with Si detector, the decomposition of the total K x ray peak into its Xe and Cs contributions was determined. A measurement on a Ge(Li) detector was used to determine the relative intensity of the 273-keV γ ray and the total K x ray intensity. From an average over several spectra on two detectors, we obtained the relative intensities of the parent and daughter γ -rays (i.e., 273, and 442 keV) and the 511-keV positron annihilation photons. In determining the positron intensity from the

*Allied Chemical

511-keV photon intensity we have used an estimate⁽⁴⁾ that about 3.8% of the positrons annihilate in flight (in Be absorbers around the source).

The ^{128}Cs decay has a Q value⁽⁵⁾ of 3.9 MeV and > 90% of the beta decay is to states below 0.5 MeV⁽³⁾. Therefore, the average (K capture/total capture) ratio⁽⁶⁾ can be estimated accurately to be 0.885. In the ^{128}Cs decay, the absolute intensity AI of the ground state transition is then:

$$\text{AI}(442) = 0.258 \pm 0.013 \text{ per decay.}$$

The absolute intensities in the ^{128}Ba decay are then simply given by:

$$\text{AI}(273) = \text{AI}(442) \frac{I(273)}{I(442)} = 0.145 \pm 0.007 \text{ per decay.}$$

Gamma-gamma coincidence measurements were carried out with both equilibrium and Ba-enhanced sources. The expected coincidence rate for certain possible cascades was calculated by comparison with the measured coincidence rate for the 442-526 keV cascade in the ^{128}Cs decay relative to the number of gate pulses (of 442 keV) and the intensity of the 526-keV γ ray relative to that of the 442-keV transition. From measured limits on the number of coincidence counts for particular ^{128}Ba cascades several possible cascade relationships were ruled out. These results are shown in Table II.

Attempts were made to determine the decay energy for ^{128}Ba by measurement of the coincidence summing of the Cs K x rays and the 273-keV γ ray. This was done for a source-detector distance 1 to 3 cm on a Ge(Li) detector. The results were not sufficient to determine the Q value.

From the above results, the decay scheme shown in Figure 1 is proposed. The intensities of the electron-capture branches were deduced from the absolute γ -ray transition intensities with all of the multipolarities assumed to be M1. Without an experimental decay energy available, the log ft values, calculated with the computer program described in Ref. 6, are shown for an arbitrary energy of 700 keV. The Wapstra-Gove Tables⁽⁵⁾ give 700 keV, which would not increase the log ft values enough to change any interpretation.

These log ft values and the 0^+ spin and parity of the ^{128}Ba ground state suggest that all of the excited states, except possible 187 keV, have $I^\pi = 0^\pm, 1^\pm$. More explicitly the rules for spin and parity assignments given by Ramon and Gove⁽⁷⁾ suggest $I^\pi = 1^+$ for the levels at 0 and 273 keV (i.e., log ft < 5.9 with $Z < 80$). The remaining states might have any of these four possibilities although 0^+ is least likely due to the tendency of $0^+ \rightarrow 0^+$ transition to have log ft values > 9.

- (1) J. M. Hollander and M. I. Kalkstein, Phys. Rev. 98 (1955)pg. 260.
- (2) G. M. Julian, S. Jha, A. S. Johnston, Phys. Rev. 163 (1967) pg. 1323.
- (3) T. Kucarova, V. Zvolská, B. Dračík and A. Maštálka, Czech. J. Physics B18 (1968) pg. 24.
- (4) J. Kantele and M. Valkonen., Nucl. Instr. and Meth. 112 (1973) pg. 501.

- (5) A. H. Wapstra and N. B. Gove, Nucl. Data Tables A9 (1971) pg. 265.
- (6) N. B. Gove and M. J. Martin, Nucl. Data Tables 10 (1971) pg. 205.
- (7) S. Ramon and N. B. Gove, Phys. Rev. C7 (1973) pg. 1995.

TABLE I
ENERGIES AND INTENSITIES OF γ RAYS FROM ^{128}Ba

Energy (keV)	Intensity	
	Relative	Absolute (/100 decays)
101.72 $\pm$ 0.20	0.13 $\pm$ 0.03	0.019 $\pm$ 0.004
129.24 $\pm$ 0.20	0.11 $\pm$ 0.03	0.016 $\pm$ 0.004
143.80 $\pm$ 0.20	0.07 $\pm$ 0.03	0.010 $\pm$ 0.004
159.72 $\pm$ 0.10	0.09 $\pm$ 0.03	0.013 $\pm$ 0.004
187 doublet	$\sim$ 0.26	$\sim$ 0.038
215.47 $\pm$ 0.04	0.48 $\pm$ 0.04	0.070 $\pm$ 0.007
229.50 $\pm$ 0.06	0.73 $\pm$ 0.06	0.106 $\pm$ 0.010
273.44 $\pm$ 0.01	100.00	14.5 $\pm$ 0.7
317.16 $\pm$ 0.10	0.22 $\pm$ 0.04	0.032 $\pm$ 0.006
359.10 $\pm$ 0.04	0.66 $\pm$ 0.05	0.096 $\pm$ 0.009
374.99 $\pm$ 0.02	2.13 $\pm$ 0.10	0.309 $\pm$ 0.021

TABLE II
SUMMARY OF γ - γ COINCIDENCE RESULTS

<u>Gate Transitions (keV)</u>	<u>Coincident γ-Rays (keV)</u>	<u>Non-coincident γ-Rays (keV)</u>
375	--	all 215-359
359	--	all 102-375
273	102	all 129-375

Figure 1. Proposed decay scheme of ^{128}Ba . The energies are keV and the electron-capture intensities are per 100 decays.

DECAY OF ^{131}Ba

R. J. Gehrke, R. G. Helmer
C. W. Reich, R. C. Greenwood, R. A. Anderl

There are several investigations(1-6) of the decay of ^{131}Ba (11.7 d) reported in the literature. These contain a number of disagreements regarding the existence of γ rays. Further, the only reported measurement of the Q-value of the ^{131}Ba decay is 1165 ± 15 keV⁽⁷⁾ and this value was reported as an abstract in the APS Bulletin. In their 1971 Atomic Mass Evaluation, Wapstra and Gove⁽⁸⁾ point out that this value is lower by ~ 200 keV than that computed from other mass-related information and they adjusted the Q-value upwards to 1340 keV. We have undertaken this study in an attempt to resolve the question of the existence of certain γ rays as well as the discrepancy in the Q value.

The ^{131}Ba activity was produced at the Clinton P. Anderson Meson Physics Facility (LAMPF) by the spallation reaction with 600-800 MeV protons bombarding praseodymium metal foils. Isotopically pure ^{131}Ba was obtained by chemical extraction of barium followed by isotope separation. Gamma-ray singles spectra were measured with a five-sided coaxial Ge(Li) detector with an energy resolution ~ 2 keV (FWHM) at 1 MeV and a volume of ~ 65 cm³. A typical γ -ray spectrum of ^{131}Ba is shown in Figure 1. Gamma-ray spectra of four sources were each measured over a period of about one month to assure that all of the γ rays decayed with the ^{131}Ba half-life.

The energies of the stronger γ rays were determined from spectra containing lines from ^{131}Ba and various sources which emit γ rays whose energies are known precisely^(9,10). The uncertainty in each γ -ray energy was determined by adding in quadrature the average error in the peak location with a standard reference error (13 ppm < 350 keV and 19 ppm > 350 keV). In cases where these computed uncertainties were the same as those of the energy calibration lines, these uncertainties were arbitrarily adjusted upward one or two eV. The energies of the weaker γ rays were determined using the stronger ^{131}Ba γ rays as energy standards.

The absolute full-energy peak efficiency of the Ge(Li) detector was determined using the techniques described in Refs. 11 and 12. From most of the γ rays the relative intensities were determined from a weighted average of five measurements. The corresponding uncertainties were computed by adding in quadrature the statistical uncertainty in the mean intensity and the estimated error in the ratio of the efficiency to that at 496 keV. A minimum uncertainty of 1.0% is quoted for the relative intensities of the stronger γ rays and a minimum uncertainty of 2.5% is quoted for γ rays with intensities $< 1\%$ of the 496-keV γ ray. A list of the γ -ray energies and their relative intensities is given in Table I.

Coincidence measurements were made using a 50-cm³ five sided coaxial Ge(Li) detector to gate on the γ ray of interest (with a single channel analyzer) and a 55-cm³ open-ended coaxial Ge(Li) detector to

accumulate the coincident γ -ray spectrum (in a multichannel analyzer). Gamma-ray spectra were accumulated with single-channel gates at the peaks at 123, 133, 216, 373, 585 and 620 keV. An example of the coincidence data is given in Figure 2. Interpretation of the coincidence spectra was accomplished by visual and computer analyses.

Figure 2 illustrates the spectrum of γ rays in coincidence with the 216-keV ground state transition. Since the 216-keV level is directly fed by electron capture in a significant fraction of the decays (see the proposed scheme in Figure 3), these coincidence data can be used to obtain an upper limit on the β^+ intensity and thereby an estimate of the Q value.

The proposed decay scheme in Figure 3 is consistent with the coincidence data and the measured γ -ray energies and relative intensities of the present experiment.

As a result of the present investigation previously unreported levels in ^{131}Cs have been identified at 919, 1170 and 1241 keV. These levels are based on the placement of previously unreported γ rays of 128, 546, 703, 795, 919, 1046, 1126, 1170, 1208 and 1341 keV and on previously reported⁽⁴⁾ but unplaced γ rays at 797 and 954 keV. The γ -ray spectra in coincidence with the 216-keV and 373-keV gates indicate that the 546- and 954-keV γ rays decay from 919-keV level, the 797- and 954-keV γ rays decay from 1170-keV level and the 1126-keV γ ray decays from the 1341-keV level. A newly reported γ ray at 369 keV feeding the 216 keV level from 585 keV level has been placed in the decay scheme on the basis of coincidence information and its energy. Gamma rays at 128, 550, 795, 1170, 1208 and 1341 keV were placed in the level scheme on the basis of their energy. Possible peaks at 334 and 585 keV were observed in the γ -ray spectrum in coincidence with the 585-keV gate and are tentatively placed feeding the 585-keV level. The existence of 137-keV γ ray as reported and placed by Horen *et al.*⁽¹⁾ is confirmed. The γ ray at 563 keV which was previously reported by Kucarova *et al.*⁽³⁾ but not placed in their proposed decay scheme has been confirmed and placed in the proposed decay scheme on the basis of coincidence information. The existence of reported γ rays at 323⁽²⁾ and 508⁽³⁾ keV could not be verified. Upper limits on the relative intensities of these γ rays are reported in Table I. The results of the coincidence measurements of the present experiment are indicated in the level scheme of Figure 3 by dots at the heads of the γ -ray transition symbols. These dots indicate the γ rays entering the level which are in coincidence with the ground-state transition.

The intensities of the electron-capture branches were determined from the intensity balances of the transitions populating and the depopulating each of the ^{131}Cs levels. The multipolarities were taken from Horen *et al.*⁽¹⁾ and were used to determine the conversion coefficients. Where no definitive multipolarity assignments were reported by them, we used their relative electron intensities and our relative γ -ray intensities to determine the conversion coefficients. The sum of the relative electron intensities of the K + L₁ + L₂ + L₃ shells⁽³⁾ associated with the 123-keV γ ray were normalized to a 95% E2 + 5% M1 multipolarity.

For the positron branch feeding the 216-keV level we measured the ϵ/β^+ ratio to be $(4.7 \pm 2.3) \times 10^4$. From the Log-f tables of Gove and Martin¹³⁾ this corresponds to a β^+ endpoint energy for an allowed transition of 134 ± 18 . This gives a Q value for the decay of ^{131}Ba of 1372 ± 18 keV. Our measured value deviates from the previous measured Q value⁷⁾ of 1165 and supports the upward adjustment of the Q value by Wapstra and Gove⁸⁾. The log ft values given in Figure 3 were calculated using the intensities of the electron capture branches and the Q value (1372 keV) determined from the present experiment.

The spins and parities of the ^{131}Cs levels are summarized in Fig. 3. Those of the previously reported levels are taken from refs. 4 and 5; those of the previously unreported level are discussed here. The 919-keV level is depopulated by γ -ray transitions which feed levels with spins of $1/2^+$, $3/2^+$ and $5/2^+$. This suggests that the 919-keV level has a spin of $1/2$, $3/2$ or $5/2$. The 919-keV level is apparently not directly fed by electron capture; it is thus suggesting that it has a spin of $5/2$ although of course this does not definitely exclude the other two possibilities. The 1170- and 1341-keV levels are depopulated by γ -ray transitions which feed levels with spins of $1/2^+$, $3/2^+$, $5/2^+$ and of $3/2^+$, $5/2^+$ respectively. Since both of these levels are fed by electron capture, the levels have a spin of $1/2$ or $3/2$. At present we are comparing the features of this ^{131}Cs level scheme with the results of theoretical calculations¹⁴⁾ utilizing a quasiparticle-phonon coupling model. These calculations have been carried out by G. J. Mathews of the University of Maryland.

- (1) D. J. Horen, J. M. Hollander and R. L. Graham, Phys. Rev. 135 (1964) B301.
- (2) K. Karlsson, Arkiv For Fysik 33, (1966) 47.
- (3) I. Kucarova, B. Kracik and V. Zvoliska, Soviet Journal of Nuclear Physics (a translation of Yadernava Fizika 7, (1968) 433.
- (4) L. Hasselgren, S. Antman, H. S. Sahota and J. E. Thun, Nucl Phys. A153 (1970) 625.
- (5) R. Strum, F. W. Thiele, R. Thielman and E. Grunberg, Z. Physik 252 (1972) 312.
- (6) R. Singh, C. Rangacharyul and G. K. Mehta, Z Physik 258 (1973) 12.
- (7) B. L. Robinson, Bull. Am. Phys. Soc. 7, (1962) 541.
- (8) A. H. Wapstra and N. B. Gove, Nuclear Data Tables A9, (1971) Nos. 4 and 5.
- (9) R. C. Greenwood, R. G. Helmer and R. G. Gehrke, Nucl. Instr. and Meth. 77, (1970) 141.
- (10) R. G. Helmer, R. C. Greenwood and R. J. Gehrke, Nucl. Instr. and Me Meth. 96, (1971) 173.
- (11) R. C. Greenwood, USAEC report ANCR-1088 (1972) 396.
- (12) R. G. Helmer and R. C. Greenwood, USAEC report ANCR-1088 (1972) 396.
- (13) N. B. Gove and M. J. Martin, Nucl. Data Tables A10 (1971).
- (14) G. J. Mathews, private communication.

TABLE I

ENERGIES AND RELATIVE INTENSITIES OF γ RAYS FROM THE DECAY OF ^{131}Ba

Energy (keV)	γ -ray Relative Intensity ^a	Energy (keV)	γ -ray Relative Intensity ^a
54.96 $\pm$ 0.11	0.198 $\pm$ 0.010	508 ^b	<0.02
78.764 $\pm$ 0.016	1.56 $\pm$ 0.05	546.27 $\pm$ 0.09	0.011 $\pm$ 0.002
82 ^b	<0.4	550.75 $\pm$ 0.32	0.009 $\pm$ 0.002
92.289 $\pm$ 0.014	1.37 $\pm$ 0.18	563.06 $\pm$ 0.24	0.009 $\pm$ 0.002
123.802 $\pm$ 0.008	61.9 $\pm$ 1.8	572.672 $\pm$ 0.015	0.332 $\pm$ 0.009
128.09 $\pm$ 0.14	0.037 $\pm$ 0.012	585.026 $\pm$ 0.015	2.61 ^c
133.612 $\pm$ 0.014	4.61 $\pm$ 0.13	620.095 $\pm$ 0.017	2.91 $\pm$ 0.18
137.357 $\pm$ 0.039	0.058 $\pm$ 0.004	674.415 $\pm$ 0.020	0.285 $\pm$ 0.007
157.147 $\pm$ 0.009	0.406 $\pm$ 0.011	696.470 $\pm$ 0.020	0.317 $\pm$ 0.010
216.073 $\pm$ 0.008	42.2 $\pm$ 0.9	703.42 $\pm$ 0.08	0.015 $\pm$ 0.001
239.623 $\pm$ 0.008	5.13 $\pm$ 0.09	795.8 $\pm$ 0.5	0.016 $\pm$ 0.004
246.879 $\pm$ 0.012	1.37 $\pm$ 0.04	797.43 $\pm$ 0.06	0.075 $\pm$ 0.004
249.426 $\pm$ 0.009	6.03 $\pm$ 0.12	831.599 $\pm$ 0.031	0.494 $\pm$ 0.013
294.508 $\pm$ 0.020	0.356 $\pm$ 0.009	914.050 $\pm$ 0.021	0.098 $\pm$ 0.003
323 ^b	<0.004	919.78 $\pm$ 0.15	0.019 $\pm$ 0.004
351.188 $\pm$ 0.024	0.218 $\pm$ 0.014	923.846 $\pm$ 0.022	1.56 $\pm$ 0.04
369.11 $\pm$ 0.13	0.051 $\pm$ 0.010	954.590 $\pm$ 0.026	0.71 $\pm$ 0.002
373.237 $\pm$ 0.011	29.9 $\pm$ 0.8	968.918 $\pm$ 0.026	0.072 $\pm$ 0.002
404.036 $\pm$ 0.011	2.79 $\pm$ 0.03	1047.571 $\pm$ 0.025	2.84 ^d
427.559 $\pm$ 0.017	0.210 $\pm$ 0.006	1125.94 $\pm$ 0.16	0.0051 $\pm$ 0.0003
451.407 $\pm$ 0.015	0.088 $\pm$ 0.004	1170.5 $\pm$ 0.5	0.0036 $\pm$ 0.0010
461.246 $\pm$ 0.024	0.220 ^f	1208.7 $\pm$ 0.3	0.0047 $\pm$ 0.0010
480.395 $\pm$ 0.013	0.691 $\pm$ 0.017	1341.85 $\pm$ 0.15	0.0027 $\pm$ 0.008
486.510 $\pm$ 0.012	4.43 $\pm$ 0.05		
496.313 $\pm$ 0.013	$\approx$ 100		

^a47.4 $\pm$ 1.0% of the 11.7 d ^{131}Ba decays through the 496-keV γ ray.^bNot observed in singles spectra of present experiment.^cNo error assigned to intensity because peak is an unresolved doublet.^dNo error assigned to intensity because peak is an unresolved doublet.
The intensity ratio of the 1046.9 keV: 1047.6 keV γ ray is about 1:8.

Figure 1. Gamma-ray spectrum of ^{131}Ba taken with a $65\text{ cm}^3\text{ Ge(Li)}$ detector at a 10 cm source-detector distance. The source was placed between 0.357 g/cm^2 poly.

Figure 2. Spectrum of ^{131}Ba γ rays in coincidence with the 216-keV γ ray. Peaks labelled "RC" result from random coincidences; those labelled "BS" result from backscattering between the detectors (the energy of the primary γ ray is given in parentheses).

Figure 3. Decay scheme of ^{131}Ba .

HALF-LIFE MEASUREMENTS OF ^{134}La , ^{132}Ce , ^{133}Ce , ^{134}Ce AND ^{135}Ce

R. J. Gehrke

While carrying out nuclear structure studies of neutron-deficient isotopes produced at the Clinton P. Anderson Meson Physics Facility (LAMPF) at Los Alamos, the half-lives of ^{134}La , ^{132}Ce , ^{133}Ce , ^{134}Ce and ^{135}Ce were determined. The sources were produced by the spallation reaction with 600-800 MeV protons bombarding praseodymium metal foils. Isotopically pure sources of the cerium radionuclides were obtained by chemical extraction⁽¹⁾ followed by isotope separation⁽²⁾. The ^{134}La source was obtained by chemically separating the lanthanum from the ^{134}Ce activity.

The half-lives of these isotopes were measured with Ge(Li) spectrometers by following their decay and were determined for the cerium isotopes from the peak areas of the stronger γ -ray peaks in the spectrum. For the ^{134}La activity the entire spectrum was counted with a scaler.

The ^{134}La and ^{135}Ce radionuclides were counted for the same preset clock times and the sources were not moved until each set of runs was complete. The ^{134}La activity was followed for over an hour to establish the background level, which was subsequently removed from the gross counts of each run. The ^{134}La data were not corrected for random summing because of the effect was negligible. The ^{135}Ce data were corrected for the fractional analyzer "live" time and for random summing.

The ^{132}Ce , ^{133}Ce and ^{134}Ce sources were each counted for the same preset "live" times and were positioned with respect to the detector at specified distances before each run. The "clock" time of each run was recorded by the analyzer along with the "live" time. The data were corrected for decay of the source during the "clock" count time, for the fractional analyzer "live" time and for random summing.

Weighted ($w = 1/\sigma^2$) linear least-squares fits⁽³⁾ were made to the corrected data with a function which is the Napierian logarithm of the counting rate.

The standard deviation, σ , is determined by adding in quadrature the statistical uncertainties in the gross counting rate and the background counting rate. In those cases where the source was positioned before each run, the statistical uncertainty in the data was adjusted to be a minimum of 2% to account for variations in the source position. The number of data points and the number of half-lives over which the least-squares fit extends are given in Table I along with the half-life values obtained for each γ -ray measured. A weighted ($w = 1/\sigma$) average of these individual measurements was taken to obtain our reported half-life. An estimate of the systematic uncertainty was made and combined linearly with the statistical uncertainty. The systematic error includes estimates of possible errors introduced by the counting

and analysis techniques of the present experiment and of the uncertainty caused by variation in the source-detector geometry when the source was positioned before each count. Table 2 gives a comparison of previously reported measurements with our values.

- (1) Chemical Separations performed by L. D. McIsaac and J. D. Baker, Allied Chemical Corporation, Idaho National Engineering Laboratory.
- (2) Isotope separation performed by R. A. Anderl.
- (3) Least-squares fit computer program written by R. L. Bunting.
- (4) B. Stover, Phys. Rev. 81, (1951) 8.
- (5) R. K. Girgis, and R. Van Lieshout, Nucl. Phys. 12 (1959) 672.
- (6) A. Abdul-Malek and R. A. Naumann, Nucl. Phys. A108 (1968) 401.
- (7) G. M. Julian and T. E. Fessler, Phys. Rev. 172 (1968).
- (8) W. R. Ware and E. O. Wiig, Phys. Rev. 117 (1960) 191.
- (9) C. Gershel and G. Albouy, Compt. Rend. 264B (1967) 183.
- (10) F. I. Pavlotskaia, and A. K. Laurukhina, Zhur Eksptl, i Teoret Fiz. 34 (1958) 1058.
- (11) E. Grigor'ev, O. Larionov, M. Nikitin, S. Sakharov and V. Sergeev, Transactions of the second Conference on Nuclear Spectroscopy on Neutron-Deficient Rare Earth Isotopes, Part 3, 40, Dubna 1958.
- (12) E. I. Birykov, V. T. Vovikov and N. S. Shimanskaya, Izv. Akad., Nauk SSSR, Ser. Fiz. 29 (1965) 151; Bull. Acad. Sci. USSR, Phys. Ser. 29 (1966) 148.
- (13) V. R. Burmistrov, Y. A. Andreev, A. D. Vongai, S. P. Karetskaya, G. D. Latyshev and O. D. Kovrigin, Izv. Akad. Nauk. SSSR, Ser. Fiz. 29 (1965) 144; Bull. Acad. Sci. USSR, Phys. Ser. 29 (1966) 142.
- (14) Y. Gono, M. Ishihara and M. Sakai, Phys. Soc. Japan 23 (1967) 145.
- (15) V. S. Aleksandrov, B. S. Dzhelepov, A. I. Medvedev, V. E. Ter-Nersesyants, I. F. Uchevatkin and S. A. Shestopalova, Izv. Akad., Phys. Ser. 37 No. 5 (1974) 186.
- (16) J. B. Chubbuch and I. Perlman, Phys. Rev. 74 (1948) 982.
- (17) B. S. Dzhelepov, B. K. Preobrazhenskii, I. M. Roguchev and P. A. Tishkin, Izv. Akad. Nauk SSSR. Ser. Fiz. 22 (1958) 931.
- (18) B. S. Dzhelepov, A. I. Medvedev, I. F. Uchevatkin and S. A. Shestopalova, Izv. Akad., Nauk SSSR, Ser. 27 (1964) 214.
- (19) V. A. Balakaev, S. S. Dzhelepov, A. I. Medvedev, I. F. Uchevatkin and S. A. Shestopalova, Izv. Akad. Nauk SSSR. Ser. Fiz. 29 (1965) 2205; Bull. Acad. Sci. USSR, Phys. Ser. 29 (1966) 2042.
- (20) D. Takahashi, M. Fjioka and K. Hisa ake, J. Phys. Soc. Japan 19 (1964) 2014.
- (21) S. Ingelman, C. Ekstron, M. Ulsmats and B. Wannberg, Phys. Sci. 7 (1973) 24.
- (22) B. S. Dzhelepov and I. F. Uchevatkin - priv. comm. (Jan. 1974) Nuclear Data Sheets.

TABLE I

THE MEASURED HALF-LIVES OF ^{134}La AND
 $^{132-135}\text{Ce}$ FROM THE PRESENT INVESTIGATION

Isotope	# of Data Points fit	Drop in Activity	γ -ray peak Fit [E(keV)]	Half life From Least-squares fit of data	χ^2 of Fit	Average Error Components (hr)		Half Life
						Statistical	Systematic	
^{134}Ce	11	568	511	75.80 ± 0.09 h	4.96			
			563	76.64 ± 1.59 h	0.90	0.15	0.76	75.9 ± 0.9 h
			604	76.23 ± 0.31 h	2.12			
^{135}Ce	14	5	206	17.731 ± 0.038 h	1.02			
			265	17.756 ± 0.016 h	0.93	0.013	0.18	17.76 ± 0.31 h
			300	17.787 ± 0.025 h	1.17			
^{132}Ce	5	2300	155	3.51 ± 0.10 h	4.18			
			180	3.51 ± 0.05 h	3.69	0.05	0.06	3.51 ± 0.11 h
^{135}Ce	3	765	130	4.91 ± 0.05 h	0.35			
			785	5.17 ± 0.26 h	11.6			
			1584	4.94 ± 0.18 h	0.57	0.06	0.33	4.93 ± 0.39 h
			2016	4.80 ± 0.19 h	0.54			
^{134}La	80	22	Total Spectrum	6.45 ± 0.06 m	0.84	0.06 m	0.10 m	6.45 ± 0.16 m

TABLE II
COMPARISON OF HALF-LIFE VALUES FROM THE
PRESENT INVESTIGATION TO THOSE FROM PREVIOUS STUDIES

<u>Isotope</u>	<u>Value</u>	<u>Reference</u>	<u>Date</u>
^{134}La	6.50 ± 0.25 m	4	1951
	6.8 ± 0.2 m	5	1959
	6.67 ± 0.02 m	6	1968
	6.82 ± 0.08 m	7	1968
	6.45 ± 0.16 m	Present Experiment	
^{132}Ce	4.2 ± 0.2 h	8	1960
	3.51 ± 0.11 h	Present Experiment	
^{133}Ce	6.3 ± 0.1 h	4	1951
	5.4 ± 0.05 h	9	1967
	4.93 ± 0.39 h	Present Experiment	
^{134}Ce	72.0 ± 0.5 h	4	1951
	84 h	10	1958
	71.5 h	11	1958
	81 ± 2 h	12	1965
	78 ± 1 h	13	196
	85 ± 5 h	14	1967
	76 ± 2 h	15	1973
	75.9 ± 0.9 h	Present Experiment	
^{135}Ce	16 h	16	1948
	22 h	4	1951
	17 h	17	1958
	17.0 ± 0.2 h	18	1963
	17.3 ± 0.2 h	19	1965
	17.6 ± 0.4 h	20	1964
	22 ± 0.7 h	14	1967
	19.5 ± 0.2 h	21	1973
	17.5 ± 0.4 h	22	1974
	17.76 ± 0.31 h	Present Experiment	

EXPANDED DATA CONTENT FOR THE RADIOACTIVE-
NUCLIDE DECAY DATA FOR ENDF/B

C. W. Reich, R. G. Helmer, and R. L. Bunting

The content of the Decay-Data file (1) which we set up for Version IV of ENDF/B has been expanded. This expanded content will form the basis of the file of decay data for Version V of ENDF/B. The thrust of this expansion has been to provide a more detailed accounting of the energy release associated with the processes of internal conversion, x-ray emission, and annihilation-radiation emission than was done for the Version IV data file. In addition, a number of other additions to and revisions of the data content have been carried out. Here, we briefly discuss these changes.

At the request of a number of users, we have incorporated the spin and parity of the parent-nucleus state. Energy and intensity information for discrete-electron radiation and for x- and annihilation radiation are now included in the file, under radiation types '8' and '9', respectively. In electron-capture + positron decay (radiation-type 2), both the electron-capture and positron energy and intensity information can be incorporated. In addition, for radiations (other than $\beta^\pm$) whose energy spectra contain both a discrete and a continuous component (e.g., delayed neutrons), a means is provided for listing both components.

Average energies are computed and listed separately for each radiation type. These are then suitably grouped to give the overall average-energy values. The grouping of these latter quantities as $\langle E_\beta \rangle$, $\langle E_\gamma \rangle$, and $\langle E_\alpha \rangle$ in the Version IV file has been retained, but their definition has been modified. By $\langle E_\beta \rangle$ we now mean the sum of the average energies of all the processes in which electrons are emitted, including β^- and β^+ decay, conversion-electron and Auger-electron emission and internal-pair production. $\langle E_\gamma \rangle$ now includes not only the average of γ -ray energy, but also that associated with decay processes, such as x-ray and annihilation-radiation emission, in which photons are produced which do not arise as a result of transitions between nuclear levels. By $\langle E_\alpha \rangle$ is now meant the average energy associated with the emission of "heavy" charged particles, such as α particles and protons. Also included in this value is the average energy of the emitted neutrons.

A means of indicating delayed radiation, emanating from an intermediate state (or states) whose half-life is too short (< 0.1 sec.) to warrant separate inclusion in the file, has been incorporated into the "Decay Mode" cards(1). This is done by listing in the Decay-Mode columns, in order of the sequentially-emitted radiations, integers corresponding to the respective radiation types. For example, β^- decay and α decay are denoted by the integers 1 and 4, respectively; the process of β^- delayed α emission (as occurs, e.g., in ^{16}N decay) is thus indicated by the notation 14. In this new notation, delayed-neutron emission is denoted as 15, rather than simply 5 as in the earlier format, thus providing a more consistent treatment of these

delayed radiations.

In addition, a capability has been included for "flagging" the various individual transitions within a given radiation spectrum to indicate their origin. For example, γ radiation following β^- decay is flagged with 1 while that emitted from a nucleus formed following delayed-neutron emission is flagged with 15. In this way from inspection of a list of, say, γ -ray transitions for a nuclide with more than one decay mode, it is possible to determine with which daughter nuclides a given γ ray is associated.

-
- (1) C. W. Reich, R. G. Helmer, and M. H. Putnam, Radioactive-Nuclide Decay Data for ENDF/B, ANCR-1157 (ENDF-210), August, 1974.

DECAY DATA MASTER FILE AT INEL

R. L. Bunting, R. G. Helmer, C. W. Reich

We have established a computer file of evaluated decay scheme information, the Decay Data Master File (DDMF). This file includes gamma-ray, beta and charged particle energies and intensities. Also included are half-life and other pertinent nuclear and atomic properties associated with the parent activity. The data base is primarily experimental and considerable effort has been made to include appropriate normalization factors to deduce absolute particle and photon intensities for the specified decay modes and the associated uncertainties for all entries. The DDMF will combine the existing ENDF/B⁽¹⁾ and INEL "Table of the Isotopes" file⁽²⁾. The purpose of this file will be to provide the data base necessary to generate; (a) updates of our GAUSS-VI⁽³⁾ nuclide identification library, (b) revisions of the "Table of the Isotopes", (c) an expanded working file for ENDF/B and (d) other specialized decay-data and dosimetry files.

The DDMF information is assembled from available evaluated sources supplemented with open literature where necessary. The primary sources to data are ENDF/B, ILRR⁽⁴⁾, Radioactive Atoms⁽⁵⁾ and the ORNL Decay Data Library⁽⁶⁾. The latter source exists as a nuclear structure oriented file and will require further computer code development before conversion to the DDMF format is possible.

The file is ordered by increasing atomic number (Z) within a given (Z), the nuclides are arranged by increasing atomic number (A). Isomeric activities ($T_{1/2} > 0.1$ sec) are treated separately and appear immediately after their associated ground state entry.

Each DDMF line entry contains a type (formatting) specification. This feature allows the data block length for each nuclide to be kept at an absolute minimum. (e.g., Only two lines are required to include the neutron-capture cross section for a stable nuclide or a special GAUSS-VI entry may be prepared in (n+4) lines for n, γ -ray entries.) The format for the DDMF are summarized in Table I.

DDMF entries denoted as average values (e.g., average beta and gamma energies) will be generated and edited into the DDMF by auxillary processing codes. The conversion electron and x-ray spectra (line type 78 & 79) can be generated from the electron capture and γ -ray multipolarity data contained in the files. These calculations require theoretical internal conversion coefficients, fluorescent yields and x-ray energy tables which will be incorporated into file processing codes.

Presently the DDMF contains 39 nuclides and is used as a gamma-ray energy and absolute intensity file. The data based will be expanded with 75 additional entries from ENDF/B and the total number of entries should exceed 200 when the processing codes are completed for the ORNL Decay Data Library.

- (1) C. W. Reich, R. G. Helmer and M. H. Putnam, "Radioactive-Nuclide Decay Data for ENDF/B, ANCR-1157 (ENDF-210), August 1974.
- (2) R. L. Heath, "Table of the Isotopes" prepared for the Handbook of Chemistry and Physics 55th Edition 1974-1975. CRC Press Cleveland, Ohio.
- (3) J. E. Cline, M. H. Putnam and R. G. Helmer, "Gauss-VI, A Computer Program for the Automatic Batch Analysis of Gamma-ray Spectra from Ge(Li) Spectrometers", ANCR-1113 UE-32 (1973).
- (4) R. G. Helmer and R. C. Greenwood, "Evaluated Decay Scheme Data", Nuclear Technology 25 258 (1975).
- (5) M. J. Martin and P. H. Blichert-Toft, "Radioactive Atoms" Nuclear Data A8 1 (1970) and M. J. Martin, "Radioactive Atoms-Supplement 1", ORNL-4923 November 1973.
- (6) Nuclear Data Group, "ORNL Decay Data Library", P. C. April, 1975 continuing, and Nuclear Data Sheets continuing.

TABLE I
INPUT FORMAT FOR THE DECAY DATA MASTER FILE

Line Specification	Columns	Description
10	<u>Nuclide Identification</u> (First line)	
	1-3	Z (atomic number) Right adjusted
	4-6	A (mass number) Right adjusted
	7	Isomer Tag
		Blank (or zero) indicated the ground state;
		1, (2) indicate the first, (second) isomeric state, etc.
	9-10	Chemical Symbol
	11-20	File Status (FINAL-key right adjusted denotes distribution status)
	26-29	Spin (decaying state)
	30	Parity
	31-40	[†] Number of comment cards to follow
	41-70	Production modes (specific format pending)
	71-21	Line-type 10
20	<u>Comment Cards</u> (Any number)	
	1-66	First line only; cols 21-28 data cols 41-50 Compiler
	71-72	Line-type 20
30	<u>Half-Life</u>	
	1-10	Half-life
	11-20	Uncertainty in half-life
	30	Units (S, M, H, D, Y)
	40	[†] Number of decay modes of parent state this is equal to the number of decay mode lines (type 40)..
	50	[†] Number of "spectra" or data lists.
	71-72	Line-type 30
31	<u>Atomic Constants</u>	
	1-10	Atomic abundance
	11-20	Atomic mass
	21-30	μ_N Nuclear magnetic moment
	31-40	Q_M Nuclear electric quadrupole moment
	71-72	Line-type 31
32	<u>Reaction Constants</u>	
	1-10	Reaction cross-section
	11-20	Uncertainty
	21-30	Reaction (n, γ), etc.

TABLE I (continued)

Line Specification	Columns	Description
	31-40 71-72	Reaction product Line-type 32
40	<u>Decay Mode Cards</u>	(One line for each mode)
	10	Decay mode 1 = β^- 2 = β^+ 3 = isomeric transition 4 = alpha particle 5 = delayed neutron 6 = spontaneous fission 7 = proton emission 8 = electron emission (other than β^+) 9 = x-ray plus annihilation 0 = γ decay
	20	Is an isomeric state fed in the daughter nucleus 0 = no 1, (2) = first, (second) isomeric state is fed.
	21-30	Q-value for the decay. For isomeric transition decay, this will be the energy of the isomeric state.
	31-40	Uncertainty in Q-value
	41-50	Percent branching of this decay mode.
	51-60	Uncertainty in branching ratio
	71-72	Line-type 40
50	<u>Average Energy</u>	
	1-10	Average beta energy
	11-20	Uncertainty
	21-30	Average gamma energy
	31-40	Uncertainty
	41-50	Average charged particle energy
	51-60	Uncertainty
	71-72	Line-type 50
6X	<u>Intensity Normalization</u>	(One type 6X line to be followed by any number of 7X lines; any number of such groups).
	(Possible X-designations: 1, 2, 4, 5, 7, 8, 9. these correspond to column 10 line type 40)	

TABLE I (continued)

Line Specification	Columns	Description
	1-10	Normalization factor (absolute intensity/relative intensity) for list to follow in type-7X lines.
	11-20	Uncertainty in the normalization factor
	21-30	[†] Number of transition to follow
	40	[†] Radiation type X (same numerical designation as in column 10 of line type 40).
	41-50	Average energy (this radiation type only)
	51-60	Uncertainty in average energy
	71-72	Line-type 6X
7X	<u>Energy and Intensity Information</u>	(One per line in increasing energy order; any number of lines).
	1-10	X = 1, 2, 4, 5, 7, 8,; E (radiation type X) X = 9, I (K, x-ray).
	11-20	Uncertainty in these quantities
	21-30	X = 1, 8; I (radiation type X) X = 2; I (electron capture) X = 4, 5, 6; I (discrete, radiation type X).
	31-40	X = 9, I (L, x-ray).
	41-50	Uncertainty in these quantities X = 2; I (positron) X = 4, 5, 7; I (continuous radiation type X).
	51-60	X = 9; I ($\gamma^{\pm}$)
	51-60	Uncertainty in these quantities
	66-67	X = 1, 2; β -spectrum shape, blank or 1U.
	68-70	Source or production tag.
	71-72	Line-type 7X.
80	<u>Gamma-ray Data</u>	
	1-10	Intensity normalization factor (abs/rel).
	11-20	Uncertainty
	21-30	[†] Number of transitions to follow on type 90 cards.
	40	[†] Radiation type 0
	41-50	Average γ -ray energy
	51-60	Uncertainty
	71-72	Line-type 80

TABLE I (continued)

Line Specification	Columns	Description
90	<u>Gamma-ray Intensity and Energy Data</u>	(Any number of lines in order of increasing E_γ)
	1-10	Gamma-ray energy
	11-20	Uncertainty
	21-30	Gamma-ray intensity
	31-40	Uncertainty
	41-65	Gamma-ray multipolarity
	66	GAUSS VI intensity code
	67	Gamma-Ray Spectrum Catalogue intensity code
	68-70	Source or production tag
	71-72	Line-type 90
91	<u>Internal Conversion Information</u>	(One line to follow associated 90 line type)
	1-10	Blank
	11-20	K - ICC (α_K)
	21-30	Uncertainty
	31-40	L - ICC (α_L)
	41-50	Uncertainty
	51-60	M - ICC (α_M)
	61-70	Uncertainty
	71-72	Line-type 91
92	<u>Internal Pair Production Data</u>	(One line to follow associated 90 or 91 line type.)
	1-10	Blank
	11-20	Internal pair production coefficient
	21-30	Uncertainty
	71-72	Line-type 92

[†]These entries are not required for DDMF based processing codes.

Radiation Measurements

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

REEVALUATION OF PRECISE GAMMA-RAY ENERGIES
FOR CALIBRATION OF Ge(Li) SPECTROMETERS

R. G. Helmer, R. C. Greenwood, R. J. Gehrke

In two papers^(1,2), the authors have reported the results of comparison and measurement of the energies of many γ rays that are useful as energy standards for calibration of Ge(Li) spectrometers. Intercomparison of a number of previously reported energies, especially below 400 keV were made together with new measurements up to 1300 keV. In all cases, these energies are based, in a traceable manner, either on the energy scale referenced to the $W\text{K}\alpha_1$ x-ray energy, or on that referenced to the electron rest mass, m_0c^2 .

The work described herein has two facets. First, an adjustment of the energies reported in references 1 and 2 is made so that they correspond to the 1973 set of fundamental constants of Cohen and Taylor⁽³⁾ (instead of the 1969 fundamental constants of Taylor *et al.*⁽⁴⁾). Second, we have included in this reevaluation several new bent-crystal measurements by other authors.⁵⁻⁸

In γ -ray spectrometry, energies have been measured commonly on two different scales. The first group of γ -ray energies has been measured with respect to the energies, or wavelengths, of the atomic x rays. The second group of energies have been measured with respect to a scale based on the energy equivalent of the mass of the electron, m_0c^2 .

The values of $E(m_0c^2)$ and $E(W\text{K}\alpha_1)$ from the last two adjustments of the fundamental constants are given in Table I. The newest value of $E(W\text{K}\alpha_1)$ is a change of -2.9 ppm, from the 1969 value and the latest value of m_0c^2 is reduced by only 1.4 ppm from the previous value. The basic measurement on the latter energy scale is the determination^[9,10] of the energy of the 411-keV line from the decay of ^{198}Au relative to the m_0c^2 value as observed in positronium annihilation. We compute the energies of this ^{198}Au line to be 411.794(7) keV; this error is 17 ppm. Since all of the other energies on this scale have been measured relative to this ^{198}Au line (and not the m_0c^2 energy), the reference errors in this scale is taken to be this 17 ppm.

In our work, a distinction has been made between two components of the uncertainty. These are (1) the contribution from the reference energy defining the energy scale, σ_r , and (2) that from the specific measurements, σ_m . These components are combined in quadrature to obtain the total error, σ_t .

For primary calibration for our γ -ray energy measurements on Ge(Li) spectrometers, a set of precisely known γ -ray energies, measured by other techniques, was compiled. Besides having the necessary precision, only those data were included which were available with sufficient detail to allow reevaluation to correspond to the current set of fundamental constants.

Two groups have recently provided precise measurements⁽⁵⁻⁸⁾ of energies from bent-crystal (diffraction) spectrometers. Some of these new values are quoted with very high precision. It is, therefore, of interest to test the consistency of these precise new values before making use of the results. For the values for ^{182}Ta and ^{192}Ir a comparison is given in Table II. The individual measurement errors have been combined in quadrature to determine the uncertainty for the discrepancy. There are 20 entries in the table comparing the results of Kern et al. and Borchert et al. Although the discrepancies are somewhat larger than would be expected statistically, the level of agreement seems to be quite reasonable.

These data also indicate that for ^{182}Ta any systematic errors (i.e., constant fractional shift) is quite small. However, in eight of the 11 entries, the Kern et al. values are higher. For ^{192}Ir , it is clear that the Borchert et al. values are larger. Here the systematic difference is 5-10 ppm.

The older results of Reidy⁽¹¹⁾ are shown to be in excellent agreement with those of Borchert et al.⁽⁸⁾ for the seven cases in Table II.

As an example of our treatment of the data in the literature, the sets of experimental γ -ray energies used here for the ^{192}Ir decay are shown in Table III. The data from Piller et al.⁽⁵⁾, Reidy⁽¹¹⁾ and Borchert et al.⁽⁸⁾ are from measurements made with bent-crystal spectrometers, those of Murray et al.⁽¹⁰⁾ and Daniel et al.⁽¹²⁾ are from electron spectrometer measurements and that in Inoue and Yoshizawa⁽¹³⁾ is from a Ge(Li) spectrometer. The results from references 5, 10, 11 and 8 were calibrated directly with Au-411 line, while the reference 13 value is on the WK_{α_1} scale.

After averaging the various values, the average energies were used in a least-squares fit to the decay scheme to obtain the "best" level energies. These level energies were then used to recompute the γ -ray energy values shown in Table III, the input to the least-squares determination of the level energies included two γ -ray energy differences. These were the measured [on a Ge(Li) detector] 588-604 and 588-612 differences from reference 2.

Similar analyses of the reported measurements were carried out for ^{182}Ta and ^{183}Ta since new precise values were available for these isotopes. Values for 23 lines from 14 other isotopes were also tallied without least-squares fits to the level scheme.

The goal of our measurements of γ -ray energies has been to extend the set of calibration energies available, especially in the region above 400 keV. All of our measurements have been made on Ge(Li) spectrometers. Most of our measurements have been of the difference in energy between closely spaced lines, one of which has a "known" energy. These energy differences have been used to determine the energy of the "unknown" member of the pair. In many cases, cascade-crossover relationships have been used to compute the energy of one of the transitions involved.

The results of our energy difference measurements are given in references 1 and 2. These results and the revised calibration γ -ray energies discussed above have been combined to redetermine the γ -ray energies for 79 lines from 26 isotopes.

In summary, we have collected in Table IV, a complete list of all of these energies. Since the energies in Table IV are intended for use in calibration of Ge(Li) spectrometers, a number of the line energies for ^{183}Ta have been omitted. These lines are involved in multiple peaks in spectra from Ge(Li) detectors.

-
- (1) R. C. Greenwood, R. G. Helmer, and R. J. Gehrke, Nucl. Instr. and Meth. 77 (1970) 141.
 - (2) R. G. Helmer, R. C. Greenwood and R. J. Gehrke, Nucl. Instr. and Meth. 96 (1971) 1973.
 - (3) E. R. Cohen and B. N. Taylor, J. Phys. Chem. Ref. Data 2 (1973) 663.
 - (4) B. N. Taylor, W. H. Parker and D. N. Langenberg, Rev. Mod. Phys. 41 (1969) 375.
 - (5) O. Piller, W. Beer and J. Kern, Nucl. Instr. and Meth. 107 (1973) 61.
 - (6) W. Beer and J. Kern, Nucl. Instr. and Meth. 117 (1974) 183.
 - (7) G. L. Borchert, W. Scheck and O. W. B. Schult, Nucl. Instr. and Meth. 124 (1975) 107.
 - (8) G. L. Borchert, W. Scheck and K. P. Wieder, private communication.
 - (9) G. Murray, R. L. Graham and J. S. Geiger, Nucl. Phys. 45 (1963) 177.
 - (10) G. Murray, R. L. Graham and J. S. Geiger, Nucl. Phys. 63 (1965) 353.
 - (11) J. J. Reidy, private communication.
 - (12) H. Daniel, P. Jahn and W. Todt, Bull. Akad. Sci. USSR, Phys. Ser. 30 (1966) 2107; P. Jahn, W. Todt and H. Daniel, Phys. Letters 20 (1966) 395.
 - (13) H. Inoue and Y. Yoshizawa, Nucl. Instr. and Meth. 108 (1973) 385.

TABLE I

Quantities from adjustments of the fundamental constants

<u>Quantity</u>	<u>Value</u>	
	<u>Taylor et al.⁴ 1969</u>	<u>Cohen & Taylor³ 1973</u>
Electron rest mass, $m_0 c^2$ (keV)	511.0041(16)	511.0034(14)
Energy-wavelength conversion $E \cdot \lambda$ (keV·Å)	12.398301(73)	12.398266(70)
Wavelength $W_{K\alpha_1}$ (Å)	0.2090100	0.2090100
Energy $W_{K\alpha_1}$ (keV)	59.31918(35)	59.31901(33)

TABLE II
COMPARISON OF SOME BENT-CRYSTAL MEASUREMENTS

The uncertainties given are the measurement contribution.

Parent Isotope	Ref.	Energy (keV)	Ref.	Energy (keV)	Discrepancy (eV)
^{182}Ta	Piller, Beer and Kern ⁵	65.7219(2)	Borchert <u>et al.</u> ⁷	65.72082(15)	1.08(25)
		67.7496(2)		67.74826(13)	1.34(24)
		100.1067(3)		100.10399(6)	2.71(31)
		113.6673(12)		113.66959(26)	-2.29(123)
		152.4285(14)		152.42678(27)	1.72(143)
		156.3821(12)		156.38365(35)	-1.55(125)
		179.3909(18)		179.39042(53)	0.48(188)
		198.3483(22)		198.24771(44)	0.59(224)
		222.1013(24)		222.10387(45)	-2.57(244)
		229.3162(30)		229.31617(63)	0.03(307)
^{192}Ir	Beer & Kern ⁶	264.0711(52)	Borchert <u>et al.</u> ⁸	264.06906(61)	2.04(524)
		136.3398(7)		136.3403(7)	-0.5(10)
		295.9486(15)		295.9510(5)	-2.4(16)
		308.4467(17)		308.4473(22)	-0.6(28)
		316.4982(16)		316.5005(3)	-2.3(16)
		416.452(5)		416.4601(30)	-8.1(58)
		468.052(4)		468.0602(6)	-8.2(40)
		588.551(8)		588.5730(40)	-22.0(89)
		604.396(8)		604.3981(22)	-2.1(83)
^{203}Hg	Reidy ¹¹	612.446(9)	Borchert <u>et al.</u> ⁸	612.4513(26)	-5.3(94)
		279.1892(28)		279.1897(10)	-0.5(30)
^{51}Cr	Reidy ¹¹	320.0775(49)	Borchert <u>et al.</u> ⁸	320.0761(4)	1.4(49)
^{192}Ir	Reidy ¹¹	205.7890(14)	Borchert <u>et al.</u> ⁸	205.7909(6)	-1.9(15)
		295.9512(26)		295.9510(5)	0.2(26)
		308.4505(35)		308.4473(22)	3.2(41)
		316.4998(24)		316.5005(3)	-0.7(24)
		468.065(6)		468.0602(6)	4.8(60)

TABLE III

Analysis of γ -ray energies from ^{192}Ir decay. Unless otherwise noted, the measurement, or relative, errors are given. The least-squares fit included two energy differences as input.

Beer and Kern ^{6a}	Murray et al. ^{10b}	Experimental values (keV)				Least-Squares				
		Reidy ¹¹	Daniel et al. ¹²	Inoue et al. ^{13d}	Borchert et al. ⁸	Average Value (keV)	ϵ^2	Value ^f (keV)	σ_m	Errors (eV) σ_r^g σ_t
136.3398(7)					136.3403(7)	136.3400(5)	0.3	136.3398	0.5	2.3 2.4
		205.7390(14)			205.7909(6)	205.7903(8)	1.8		0.8	3.5 3.6
295.9486(15)	295.938(4)	295.9512(26)		295.948(2)	295.9510(5)	295.9494(13)	4.4	295.9496	1.0	5.0 5.1
308.4467(17)	308.433(5)	308.4505(35)			308.4473(22)	308.4457(24)	3.4	308.4491	1.1	5.2 5.3
316.4982(16)	316.489(5)	316.4998(24)			316.5005(3)	316.4996(10)	4.9	316.4994	0.9	5.4 5.5
416.452(5)					416.4601(30)	416.4572(37)	1.9	416.4602	1.4	7.1 7.2
468.052(4)	468.054(3)	468.055(6)	468.064(3)		468.0602(6)	468.0598(13)	2.2	468.0588	1.0	8.0 8.1
					484.5646(18)	484.5646(18)			1.8	8.2 8.4
588.551(8)	588.569(10)				588.5730(40)	588.5664(66)	3.2	588.5692	1.1	10.0 10.1
604.396(8)	604.390(11)				604.3981(22)	604.3966(26)	0.4	604.3982	1.0	10.3 10.3
612.446(9)	612.442(11)				612.4513(26)	612.4489(30)	0.7	612.4485	1.0	10.4 10.5
884.513(24)						834.513(24)		884.5179	1.8	15.0 15.1

^aReported values, except σ_m includes 4 ppm error for Au-411 peak measurement error.

^bValues included only internal-conversion data which has been reevaluated to new fundamental constants and atomic electron binding energies.

^cRelative momenta of internal-conversion-electron lines were normalized to match the average 295, 308 and 316 energies.

^dMeasurement is 295-291 (^{183}Ta) energy difference with Ge(Li) detector.

^eAverage weighted by $1/\sigma$.

^fThe ϵ^2 value is 0.60 for this fit. The input to fit included energy differences of 15.829(1) for 588-604 and 23.879(1) for 588-612 pairs.

^gAu-411 scale.

TABLE IV

Summary of γ -Ray Energies

The total uncertainties are given.

Parent Isotope	γ -ray Energy (keV)	Parent Isotope	γ -ray Energy (keV)
^{183}Ta	46.4843(6)		1230.991(24)
	52.5951(6)		1257.394(24)
	82.9191(7)		1273.705(25)
	84.7138(7)		1289.130(25)
	99.0794(6)		1373.809(26)
	107.9312(7)		1387.374(26)
	120.3678(9)		
	144.1223(10)	$^{153}\text{Sm, Gd}$	69.674(2)
	192.6450(12)		97.431(2)
	291.7243(17)		103.179(2)
	353.9888(21)	^{133}Ba	80.996(3)
	365.6078(21)		276.398(6)
	406.5838(24)		302.849(8)
^{241}Am	59.537(1)		356.004(9)
			383.848(8)
^{75}Se	66.060(9)	^{170}Tm	84.2529(15)
	96.732(2)		
	121.115(3)	^{160}Tb	86.7860(15)
	136.000(5)		93.917(6)
	198.591(7)		197.0303(34)
	264.651(8)		215.6410(38)
	279.528(7)		298.5724(54)
	303.915(6)		879.359(15)
	400.647(7)		962.290(17)
			966.145(17)
			1177.929(20)
^{182}Ta	67.7490(13)		1271.846(23)
	84.6793(15)	^{109}Cd	88.036(3)
	100.1044(18)		
	113.6694(19)	^{177}Lu	112.953(3)
	116.4157(22)		208.361(10)
	152.4282(27)	^{57}Co	122.063(3)
	156.3836(26)		136.473(3)
	179.3905(30)		
	198.3486(34)		
	222.1047(38)		
	229.3164(40)		
	264.0697(45)		
	1121.278(22)		
	1189.027(23)		
	1221.382(24)		

Table IV (continued)

Parent Isotope	γ -ray Energy (keV)	Parent Isotope	γ -ray Energy (keV)
^{185}Os	125.357(4)	^{51}Cr	320.076(5)
	162.850(6)	^{113}Sn	391.690(8)
	234.155(8)		
	592.060(11)	^{198}Au	411.794(7)
	646.111(14)		675.877(18)
	717.416(13)		1087.669(24)
	874.808(16)	^7Be	477.592(9)
	880.265(16)		
^{192}Ir	136.3398(24)	^{207}Bi	569.685(10)
	205.7903(36)		1063.641(21)
	295.9496(51)	^{228}Th	583.174(10)
	308.4491(53)		
	316.4994(55)	$^{110\text{m}}\text{Ag}$	657.748(16)
	416.460(7)		706.663(14)
	468.059(8)		744.249(19)
	484.565(8)		763.923(18)
	588.569(10)		818.014(20)
	604.398(10)		884.662(16)
	612.448(10)		937.475(20)
	884.518(15)		
^{59}Fe	142.648(3)	^{137}Cs	661.646(19)
	192.344(5)		
	1099.230(22)	^{94}Nb	702.625(13)
	1291.570(25)		871.094(15)
^{141}Ce	145.4405(28)	$^{95}\text{Zr-Nb}$	724.178(14)
^{199}Au	158.3751(27)		756.710(18)
	208.2005(35)		765.781(18)
^{139}Ce	164.853(7)	^{58}Co	810.753(20)
$^{95\text{m}}\text{Tc}$	204.112(5)	^{56}Co	846.741(16)
	253.064(7)	^{46}Sc	889.253(16)
	582.065(10)		1120.522(22)
	786.176(14)	^{88}Y	898.017(16)
	820.599(16)		
	835.123(16)	^{65}Zn	1115.525(22)
	1039.237(19)		
$^{203}\text{Hg, Pb}$	279.189(5)	^{60}Co	1173.207(20)
	401.315(12)		
	680.502(15)	^{22}Na	1274.517(25)

RELATIVE GAMMA-RAY INTENSITY MEASUREMENTS WITH A Ge(Li) SPECTROMETER

R. J. Gehrke, R. C. Greenwood

The effort continues to measure precisely the relative γ -ray intensities of selected radioisotopic sources with the standard laboratory detectors OR-5 and ND-5. Radioisotopes for which such measurements have been made include ^{56}Co , ^{75}Se , ^{82}Br , $^{110\text{m}}\text{Ag}$, ^{124}Sb , ^{133}Ba , ^{140}Ba - ^{140}La (equilibrium), ^{144}Ce , ^{152}Eu , $^{166\text{m}}\text{Ho}$, ^{169}Yb , $^{177\text{m}}\text{Lu}$, ^{182}Ta and ^{228}Th . The analysis of these data will be complete as soon as we finish calculating the corrections to the γ -ray peaks for true γ -ray coincidence summing with the effect of angular correlation included. The resulting relative intensities will be generally useful for the measurement of the relative efficiency of other γ -ray detectors.

ANALYSIS OF $4\pi\beta\text{-}\gamma$ COINCIDENCE DATA FROM RADIONUCLIDES WITH SHORT HALF-LIVES

R. J. Gehrke, R. G. Helmer

A computer program is being developed to analyze $4\pi\beta\text{-}\gamma$ coincidence data from short lived radionuclides. Radionuclide sources, which initially are intensely radioactive ($> 100,000$ c/s) are periodically counted by the $4\pi\beta\text{-}\gamma$ system over a period of many half-lives (> 15) until the count rates are at background levels. The beta, gamma and coincidence data are analyzed by a nonlinear least squares fitting program which was originally developed by D. W. Marquardt⁽¹⁾ and subsequently revised by M. A. Lintner. The fitting function, its partial derivatives and the fitting parameters are coded by the user in subroutines of the main fitting program. The fitting routine takes advantage of the rapid initial convergence obtainable with the gradient method and then uses the Taylor series approximation which converges rapidly in the vicinity of the minimum (the gradient method converges very slowly in the vicinity of the minimum).

The program fits the β - and γ - counts with the following function:

$$C_i = \left\{ \frac{N_0 \epsilon_i e^{-\lambda t} (1 - e^{-\lambda T})}{\lambda} + B_i T \right\} \left\{ 1 - \tau_i \left[\left(\frac{1 - e^{-\lambda T}}{T \lambda} \right) (N_0 \epsilon_i e^{-\lambda t}) + B_i \right] \right\}$$

where;

- C_i = observed counts for counting period from time t to $t + T$,
- N_0 = disintegration rate of source at $t = 0$,
- ϵ_i = efficiency of detector,
- T = count time,
- B_i = background count rate,
- τ_i = dead time,
- $\lambda = \frac{\ln 2}{T_{1/2}}$ = decay constant of source
- $T_{1/2}$ = half life of source, and
- $i_{1/2}$ = β or γ .

This function corrects for source decay from an initial time $t = 0$, source decay during the count time, background counts and dead time of the counting system. The program requires that initial estimates are made for the parameters which are varied during the fit, i.e., $N_0 \epsilon_i$, τ_i , B_i and $T_{1/2}$. The values of these parameters are output by the program along with their respective uncertainties when the convergence criteria are met. The fitting function assumes that the source strength is such that the probability of three pulse pile-up occurring can be neglected compared with the probability of two pulse pile-up.

After the β and γ data have been fit, the $\beta\gamma$ -coincidence data are fit by the following function:

$$N'_C = \left[\frac{N_C e^{-\lambda t} (1 - e^{-\lambda T})}{T\lambda} + N_{CBG} T \right] \left\{ 1 - \tau_\beta \left[\left(\frac{(1 - e^{-\lambda T})}{T\lambda} \right) (N_0 \epsilon_\beta e^{-\lambda t}) + N_{\beta BG} \right] \right\} \\ \left\{ 1 - \tau_\gamma \left[\left(\frac{(1 - e^{-\lambda T})}{T\lambda} \right) (N_0 \epsilon_\gamma e^{-\lambda t}) + N_{\gamma BG} \right] \right\} + \tau_C N_0^2 \epsilon_\beta \epsilon_\gamma \left[\frac{(1 - e^{-\lambda T})}{T\lambda} e^{-\lambda t} \right]^2 \\ \left[1 - N_0 \epsilon_\beta \tau_\beta \left(\frac{(1 - e^{-\lambda T})}{T\lambda} e^{-\lambda t} \right) \right] \left[1 - N_0 \epsilon_\gamma \tau_\gamma \left(\frac{(1 - e^{-\lambda T})}{T\lambda} e^{-\lambda t} \right) \right] \\ \left[2 - (1 - N_0 \epsilon_\beta \tau_\beta) \left(\frac{(1 - e^{-\lambda T}) e^{-\lambda t}}{T\lambda} \right) \epsilon_\beta - (1 - N_0 \epsilon_\gamma \tau_\gamma) \left(\frac{(1 - e^{-\lambda T}) e^{-\lambda t}}{T\lambda} \right) \epsilon_\gamma \right],$$

where:

N'_C = observed coincidence counts,

N_C = true coincidence rate,

N_{CBG} , $N_{\beta BG}$, $N_{\gamma BG}$ = the background count rates of the coincidence beta and γ channels respectively,

τ_C = resolving time of the coincidence circuit,

τ_β and τ_γ = dead time of the β and γ channels

ϵ_β and ϵ_γ are the efficiencies of the beta and γ detectors.

The parameters $T_{1/2}$, $N_{\beta BG}$, $N_{\gamma BG}$, τ_β and τ_γ are fixed parameters obtained from previous fits to the β and γ data and N , N_{CBG} and τ_C are the parameters which vary during the fit to the coincidence data. Initial estimates of these parameters must be provided as input. Estimates of ϵ_γ and ϵ_β are also required as input for fitting the coincidence data.

The source disintegration rate, N_0 , the dead times (τ_i) of the β and γ channels, the resolving time (τ_C) of the coincidence circuit the background levels (B_i) and the half life are the parameters determined from the nonlinear least-squares fits to the data.

Presently, we are in the process of evaluating the adequacy of the present functions in describing the data and the precision that can be obtained with the nonlinear least squares fitting program. In order to improve the quality of fit the next version of the program will use a function which considers three pulse pile up. A future version of the program will be written for a high count rate system being developed by L. O. Johnson(2) in which the dead time of each run will be measured and included as one of the input values. Also under consideration is the development of a fitting function which allows for two radionuclides in the source which decay independently of one another. Initial tests indicate that the parameters can be determined to $\sim 0.1\%$ when the fitting function properly describes the data. Some problems

have occurred in the fitting routine converging to the minimum χ^2 .
These problems are presently under investigation.

- (1) D. W. Marquardt, IBM Share Library Distribution No. 309401, NLIN2, August 1965.
- (2) L. O. Johnson, High Rate $4\pi\beta\text{-}\gamma$ Coincidence Electronics, this report.

FAST NEUTRON DAMAGE EFFECTS IN SILICON SURFACE BARRIER DETECTORS

J W Rogers, L. O. Johnson

Silicon surface barrier detectors used in ^6Li fast neutron spectrometry undergo radiation damage due to the interactions of the fast neutrons with the Si. These damage effects are observed by the increase in the reverse leakage current and noise of the detector, broadening of resolution and distortions of energy spectra. During the course of some fast neutron spectrum measurement in CFRMF, where pairs of Si surface barrier detectors were used in a ^6Li spectrometer with constant fraction discrimination timing, the time spectra was observed to be dependent on this damage. This is important in the assessment of the radiation damage effects on coincidence timing of experiments which require coincident events from two detectors within a limited range to be analyzed.

During the routine testing of the ^6Li spectrometer performance throughout the fast neutron radiation exposure during CFRMF neutron spectrum measurements gated time spectra were taken. These were obtained by gating the TPHC output with a timing SCA through a linear gate as shown in Figure 1. Figure 2 shows two time spectra one taken when no fast neutron damage had occurred and one taken when the detectors had been exposed to $\sim 10^{13}$ n/cm². The double peaking of the time spectrum became more distinct as the exposure to fast neutrons increased and is clearly an indicator of damage. The changing shape of the time spectrum is apparently related to the pulse rise time because using a CFTD with slow rise time pulse rejection (ORTEC-473) eliminated the double peak.

The bias voltages on the detectors were varied to test the time spectrum response to this. Figure 3 shows the results which clearly show how the time spectrum shape is altered by small changes in field strength and depletion depth. Comparisons of energy spectra taken at these different bias levels showed no shifts, distortions or change in the number of events.

Figure 1. Block diagram of electronics used to observe time spectrum of coincidence events in a pair of Si surface barrier detectors.

Figure 2. Spectra taken when (a) no fast neutron damage had occurred and (b) when the detectors had been exposed to $\sim 10^{13}$ n/cm².

Figure 3. Time spectra showing effects of changes in field strength and depletion depth.

COLLECTION AND RECOVERY OF MILLIGRAM QUANTITIES OF MASS-SEPARATED ISOTOPES

R. A. Anderl, E. H. Turk

Milligram quantities of isotopically pure rare earth (RE) samples are needed for several integral cross-section measurements to be performed as part of the FBR Physics Constants Program. Reported here is progress on the development of apparatus and techniques for collection and recovery of milligram quantities of RE isotopes produced with the Nuclear Physics Branch electromagnetic isotope separator. In addition progress on the enrichment of Nd samples is included.

As described earlier⁽¹⁾, the approach taken to achieve collection of milligram quantities of mass-separated isotopes is based on the use of a pocket collector lined with suitable collection foils. In earlier work, tantalum foil was used to line the collector pocket and the mass-separated RE material was recovered by first leaching the foils with 6N HCl and then gathering it as the hydroxide precipitate. Only very low recovery yields were achieved by this approach.

To improve on this approach, 0.5 mil-high-purity aluminum foil was selected to line the collector pocket. It was then necessary to dissolve both the aluminum foil and the RE material as the initial step to recovery of the mass-separated material. Consequently, chemical procedures suitable for isolating and recovering milligram quantities of RE material in the presence of gram quantities of aluminum in the dissolver solution were required.

Efforts to develop suitable chemical procedures were divided into two phases: (1) collection of several samples of mass-separated RE isotopes in the pocket collector followed by dissolution of the foils and RE material, chemical isolation and recovery of the RE, and where possible a determination of the recovery yield and chemical and isotopic purity for each sample, (2) refinement of the chemical procedures to optimize the yield and chemical purity of milligram quantities of RE material recovered from dissolver solutions containing gram quantities of aluminum. Yield determinations were based on weight measurements performed with an analytical balance for the recovered RE material and, where applicable, for the original quantity of RE material added to the dissolver solution. In phase 1 the original quantity of RE material present in the dissolver solution was estimated from a measurement of the total charge collected for the mass-separated sample. Chemical purity of the recovered RE material was determined by spectrochemical analysis of the residue by the analytical chemistry group at ICPP. Isotopic purity was determined by mass spectrometric analysis of the residue by the mass spectrometry group at ICPP.

In the first phase of these efforts, La_2O_3 and Nd_2O_3 , both with RE atoms present in natural abundance, were used as source material for the ion source. Approximately 860 μg and 250 μg samples of mass-separated ^{139}La and ^{144}La , respectively, were collected on different

sets of aluminum foil lining the pocket collector. The chemical procedure applied to these samples was as follows: (1) dissolution of the foil and RE material in 6N HCl, (2) precipitation of the $\text{RE}(\text{OH})_3$ in excess NaOH, (3) isolation and washing of the precipitate, (4) dissolution of the $\text{RE}(\text{OH})_3$ in HCl, (5) precipitation of the $\text{RE}(\text{OH})_3$ using NH_4OH , (6) isolation and washing of the precipitate with H_2O and ethanol (7) drying of the $\text{RE}(\text{OH})_3$ residue. A yield determination and spectrochemical analysis performed for the recovered La residue indicated the presence of Fe, Pt, Si and Al at levels of 2%-11% by weight in addition to the dominant RE fraction which was recovered with a yield of $\sim 40\%$. For the Nd collection and recovery tests, isotopic purity and chemical purity of the recovered Nd residue were determined. Mass spectrometric analysis indicated an enrichment of ^{144}Nd from 23.9% in the source material to 99.90% in the recovered mass-separated material. Corresponding concentrations of ^{143}Nd and ^{145}Nd were reduced from 12.2% and 8.3% in the source material to $< .03\%$ in the mass-separated sample. The enrichment factors characterizing the quality of the mass separation were estimated from the above relative concentrations to be ~ 1700 for ^{144}Nd relative to ^{143}Nd and ~ 1150 for ^{144}Nd relative to ^{145}Nd . Spectrochemical analysis of the recovered Nd indicated the presence of large quantities of Si ($\sim 28\%$ by weight) in addition to the RE fraction.

Considerable progress was made in refining the chemical procedures to optimize the yield and chemical purity of the RE material recovered from the dissolver solution. These procedures were developed and tested using ~ 1.5 mg quantities of Nd with ~ 1.0 gm of high purity aluminum foil. Weight measurements and spectrochemical analyses were performed on the recovered residue to determine the yield and chemical purity achieved by the different procedures tested. The chemical procedure outlined in Table I routinely gave yields of 80 $\sim$ 95% with most chemical impurities present at levels of less than 0.1% and Si present at a maximum level of 0.8%.

Included in the list of fission product isotopes for which integral cross sections are required for the LMFBR development effort are stable rare earth isotopes ^{143}Nd , ^{145}Nd , ^{147}Sm and ^{149}Sm . Cross sections for these isotopes cannot be measured by standard activation methods because the reaction products, in this case, ^{144}Nd , ^{146}Nd , ^{148}Sm and ^{150}Sm , are also stable. The cross sections, however, can be determined by mass spectrometric techniques if the isotopic abundances of ^{143}Nd , ^{144}Nd , etc., in the sample can be accurately measured before and after irradiation of the sample in a fast neutron field. The approach requires highly enriched samples ($\sim 99.999\%$), a high neutron flux ($\sim 10^{15}$ n/cm²-sec), and the use of a mass spectrometer with an abundance sensitivity of better than 10^5 .

Highly enriched samples of ^{143}Nd and ^{145}Nd have been produced with the electromagnetic isotope separator. Table 2 summarizes the pertinent information related to the enrichment of the samples.

For these separations the high temperature surface ionization ion source was used. Source material for the ion source crucible was approximately 1.5 mg of Nd_2O_3 for each run. Up to eleven separate runs

were required for each highly enriched sample. The original source material, acquired from ORNL, had been enriched previously from natural abundance levels to the original enrichments indicated above. The pocket collector, lined with 0.5 mil high purity aluminum foil was used to collect the highly enriched ^{143}Nd and ^{145}Nd samples. The expected enrichments were estimated from the earlier measurements of the isotope separation of Nd using natural Nd_2O_3 as source material. An estimation of the mass collected for each separated isotope was determined from a measurement of the total charge collected for the separation time.

Chemical recovery of the highly enriched ^{143}Nd and ^{145}Nd is underway at the present time and preparation of highly enriched samples of ^{147}Sm and ^{149}Sm with the isotope separator is in progress.

In summary, the apparatus and techniques have been developed for the collection and chemical recovery of milligram quantities of mass-separated isotopes produced with the isotope separator. Approximately 2 mg samples each of ^{143}Nd and ^{145}Nd enriched to $\sim 99.998\%$ have been produced for cross section measurements to be performed as part of the FBR Physics Constants Program.

-
- (1) R. A. Anderl, Y. D. Harker, E. H. Turk, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1974, USAEC Report, ANCR-1177 (1974) pg. 432.

TABLE I
CHEMICAL PROCEDURE FOR RARE EARTH RECOVERY

-
- A. Dissolution
1. Dissolve aluminum foil and RE material in 6N HCl.
 2. Add a few drops of concentrated HNO_3 to dissolve silicon metal
- B. Isolation and Initial Purification
1. Add 10 mg Fe^{+3} as a scavenger
 2. Coprecipitate RE and Fe hydroxides in excess NaOH
 3. Collect precipitate on Whatman #41 filter paper
 4. Wash precipitate with H_2O and a drop of NH_4OH
 5. Dissolve precipitate with 2N HCl
 6. Repeat steps 2-5 two times
- C. Final Purification and Recovery
1. Precipitate RE and Fe hydroxides with NH_4OH
 2. Collect precipitate on Whatman #41 filter paper
 3. Wash precipitate with H_2O and a drop of NH_4OH
 4. Dissolve precipitate in 2N HCl
 5. Repeat steps 1-4
 6. Add solution to top of Dowex 50 x 8 (100-200 mesh) ion exchange column
 7. Wash column with 2N HCl
 8. Elute the RE ions from the column with 6N HCl collecting the elutant in a quartz container
 9. Evaporate elutant to dryness
 10. Recover RE material from quartz container after heating for 1 hour at 800°C .
-

TABLE II
ISOTOPIC ENRICHMENT OF Nd SAMPLES

Sample	Original Enrichment (%)	Separation Time (hr)	Average Ion Current (μ A)	Average Yield (%)	Mass Collected (mg)	Expected Enrichment (%)
^{143}Nd	91.06	40.4	9.8	17.1	2.12	99.998
^{145}Nd	89.67	41.3	9.9	17.4	2.21	99.998

PREPARATION OF RADIOACTIVE SOURCES WITH THE ELECTROMAGNETIC ISOTOPE SEPARATOR

R. A. Anderl, J. D. Baker* , L. O. McIsaac *

The isotope separator in the Nuclear Physics Branch has been used for the preparation of pure samples of radioactive isotopes of xenon, barium, cerium and terbium. Six isotopically pure samples of ^{133}Xe were prepared at the request of a radiochemistry group at ICPP. The barium, cerium and terbium sources were prepared for the Decay Schemes Program in the Nuclear Physics Branch and were used in gamma spectroscopy measurements.

In preparation of the ^{133}Xe samples, the oscillating electron ion source for the mass separator was used. A gas dilution apparatus was used to mix the radioactive species with natural xenon gas which served as a carrier gas and mass marker during the separation. Atoms of the separated isotope were imbedded in a aluminum foil which was shipped to ICPP. Typical source strengths for these sources were ~ 5 R/hr β - γ at the surface as measured with a Cutie Pie.

The radioactive isotopes of barium, cerium and terbium used in the preparation of mass-separated sources were produced as spallation products by proton irradiation of praseodymium and tantalum foils at the LAMPF. Extensive chemical recovery and purification techniques were required to isolate and recover the elemental fractions of the reaction products from the target foils and to prepare them in a form suitable for isotope separation with the surface ionization ion source.

Using the following chemical procedures barium and cerium isotopes were recovered from the praseodymium foils and terbium from the tantalum foils.

Cerium

The praseodymium foils were dissolved in 5 M HCl. Following dissolution, 1 mg of Ce^{+3} carrier was added and $\text{Pr}(\text{OH})_3$ was precipitated. The $\text{Pr}(\text{OH})_3$ was washed with H_2O and converted to the nitrate by thrice heating to near dryness with conc. HNO_3 . The Pr salts were dissolved in a 10 M HNO_3 -0.1 M NaBrO_3 solution and the oxidized Ce^{+4} was extracted into 0.3 M di-2-ethylhexhylphosphoric acid (HDEHP) in heptane. Cerium was further purified by twice washing the HDEHP with 10 M HNO_3 -0.1 M NaBrO_3 , back extracting with 6 M HNO_3 containing several drops of 30% H_2O_2 and scrubbing the strip solution with heptane. Finally $\text{Ce}(\text{OH})_3$ was precipitated and washed twice with H_2O and twice with ethyl alcohol.

Barium

The supernatant liquid from the original $\text{Pr}(\text{OH})_3$ precipitation (above), was scavenged with $\text{Fe}(\text{OH})_3$. The liquor from this precipitation was cooled in an ice water bath and 1 mg of preformed $\text{Ba}(\text{CO}_3)$ crystals was added. This solution was kept in the ice bath and continually stirred for 20 min. The $\text{Ba}(\text{CO}_3)$ was gathered, dissolved in 5 M HCl and further

*Allied Chemical Co.

purified on an anion exchange column. $\text{Ba}(\text{SO}_4)$ was then precipitated by the addition of several drops of conc. H_2SO_4 . This precipitate was washed twice with H_2O and twice with ethyl alcohol.

Terbium

The tantalum foils were dissolved in a conc. HF and HNO_3 mixture. This solution was filtered and 2 mg of Ce^{+3} was added to the filtrate. The CeF_3 precipitate was gathered, washed with 1 M HNO_3 , dissolved in conc. H_3BO_3 - HNO_3 , and $\text{Ce}(\text{OH})_3$ was precipitated. The $\text{Ce}(\text{OH})_3$ was washed with H_2O and heated to near dryness twice with conc. HNO_3 . The cerium salts were dissolved in 10 M HNO_3 -0.1 M NaBrO_3 and extracted into a 0.3 M HDEHP in heptane solution. The terbium was coprecipitated from the aqueous phase using $\text{Fe}(\text{OH})_3$. This precipitate was washed once with H_2O and Tb was separated from the iron on an anion exchange column. The Tb fraction from the anion exchange column was heated to dryness twice with conc. HNO_3 and finally dissolved in 0.1 ml of 0.2 M HNO_3 . This solution was loaded onto a stationary phase HDEHP column⁽³⁾, and the rare earth elements eluted sequentially with 0.7 M HNO_3 . The terbium fraction was determined by gamma-ray analysis, and 1 mg of Gd^{+3} or Tb^{+3} carrier was added. $\text{Tb}(\text{OH})_3$ was precipitated and washed twice with H_2O and twice with ethyl alcohol.

Each of the purified samples from the final step of the above procedures was dried before transfer to the ion source crucible. Transfer was made using several 25 λ aliquots of ethanol and a specially constructed glass pipette. Isotope separation for each sample was subsequently made using the surface ionization ion source with the mass separator. Table I summarizes some of the information pertinent to these source preparations.

Although the mass separator and ion source generally performed well for the Ce and Ba separations, considerable difficulty was encountered for the Tb separation runs. Reliable ion source operation was not attained in any reproducible manner for any of the Tb runs. However, usable radioactive sources were obtained from the separations for gamma singles measurements.

Some of the results of studies using these radioactive sources are reported elsewhere in the report(4,5,6).

The electromagnetic isotope separator has been used successfully in the preparation of isotopically pure radioactive sources of ^{133}Xe , $^{151,152,153}\text{Tb}$, $^{132,133,134,135,137}\text{Ce}$ and $^{128,131,133\text{m}}\text{Ba}$. The Tb, Ce and Ba source preparations required extensive chemical isolation, purification and recovery procedures for the pre-isotope separation sample preparation. These source preparations illustrated the power in combined chemical isolation procedures with electromagnetic mass separations to facilitate the accumulation of nuclear decay data and the construction of nuclear decay schemes.

-
- (2) J. R. Berreth and Y. D. Harker, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1973, USAEC Report ANCR-1129 (1973) pg. 24.
 - (3) R. J. Sochacka, S. Siekierski, "Reversed-Phase Partition Chromatography With Di-(2-Ethylhexyl) Orthophosphoric Acid as the Stationary Phase, Part 1, Separation of Rare Earths.", J. Chromatog, 16 (1964) pg. 375-384.
 - (4) R. G. Helmer, "Decay of ^{128}Ba ", this report.
 - (5) R. J. Gehrke, "Decay of ^{131}Ba ", this report.
 - (6) R. J. Gehrke, "Half-Life Measurements", this report.

TABLE I
Isotope Separation of Tb, Ba, and Ce Radioactive Samples

Sample	No. of Runs	Average run time (hr)	Average yield (%)	Isotopic Sources Obtained
Tb(OH) ₃	4	2.2	4.3 ^a	151,152,153Tb
Ce(OH) ₃	4	1.1	29.9 ^a	132,133,134,135,137Ce
BaSO ₄	2	4.2	14.8 ^b	128,131,133mBa

^a Determined from pre- and post-separation gamma measurements for 2 of the runs.

^b Determined from pre- and post-separation gamma measurements for 1 run.

ISOTOPE SEPARATOR LABORATORY DEVELOPMENT AND UPGRADE

R. A. Anderl

Essential to maintaining and upgrading the capability of the isotope separator laboratory in the Nuclear Physics Branch is the development of the appropriate hardware, instrumentation, techniques and procedures which facilitate the ease of operation of the separator, improve the stability and reliability for long-term separation, optimize throughput yields, and extend the mass-separator application to new elements and uses. Included here is progress made toward an upgrade of the separator instrumentation, improvements related to ion source operation, the development of an ion source test bench, and the development of an advanced collector system. Reported elsewhere in this publication are efforts related to the collection and recovery of milligram quantities of mass-separated isotopes⁽¹⁾ and the development of an "on-line" isotope separator capability⁽²⁾.

Improvements in the separator instrumentation have been made in the quadrupole lens power supply, the beam-scanning probe electronics, and in the telemetry circuitry. A voltage divider has been installed on the output of the quadrupole lens power supply to permit a variation of the potential on the upper horizontal plate of the lens with respect to that of the lower horizontal plate. This adjustment is used to deflect the ion beam in the vertical plane for proper vertical alignment of the ion beam on the collector.

Tuning of the ion source and ion optics parameters to obtain a high resolution ion beam is dependent on either a direct visual observation of the beam shape as produced on the KBr fluorescent screen or an indirect view of the beam profile as produced by scanning the beam with an electronically-driven vibrating probe and displaying the current signal picked up by the probe as an oscilloscope trace.

Modifications to the probe electronics were made to correct a non-linearity in the amplifier which provided the driving signal for the probe. This non-linearity has caused a distorted beam image on the oscilloscope screen and impeded precise tuning of the ion beam parameters.

Because the power supplies required for operation of the oscillating electron ion source and the lens system are floating on the acceleration potential (up to 60 kV), a telemetering system is used to transmit voltage and current signals from these supplies to meters mounted on the separator console. Essential to reliable measurements with this system is the calibration of the voltage to frequency converter boards which are used to transmit and receive the respective signals via electrically isolating light pipes. The calibration of these electronic units has been in question.

The converter boards associated with transmitting voltage signals from the anode, cathode, source magnet and extraction power supplies have been calibrated and tested. Similarly, the converter boards associated

with transmitting current signals for each of the above supplies, except the source magnet supply, have been calibrated and tested. Increased sensitivity in operation was especially noticed in the response of the extraction supply leakage current meter to a defocused ion beam impinging on the extraction cone. This permitted more precise tuning of the ion beam shape.

The surface ionization ion source⁽³⁾ has been tested and used extensively in the isotope separation of both radioactive and stable samples. Mass separations of the stable isotopes of Eu, Gd, La and Nd, using the oxides as source material, were performed as part of the development efforts related to the collection and recovery of mass-separated samples for the FBR Physics Constants cross-section measurement program. Radioactive reaction products of Ce, Tb, and Ba, chemically extracted from targets irradiated at the LAMPF, were combined with corresponding stable materials and subsequently mass separated to prepare isotopically pure radioactive sources for gamma spectroscopy studies. Table I summarizes the yield information acquired for these separator runs.

For the runs with stable source material the yield was calculated from a measurement of the total charge collected for a given isotope and a calculation of the quantity of that isotope in the source material. Measurements of the gamma ray spectrum for the gross source material and the gamma ray spectra for the mass-separated fractions were made to determine the yield values for the runs with radioactive material.

Several factors in addition to the crucible depth were found to affect the operation and attainable yield with this ion source. The presence of oxide beams, in addition to the metal ion beams, for the lower Z rare earth elements reduced the yield for the monitored metal ion beam. The addition of graphite to the crucible with the source material aided in reduction of the metal oxide species within the crucible cavity and reduced the metal oxide ion beam considerably. Previous use of a crucible which resulted in material buildup at the base of the crucible cavity or a deterioration of the orifice through the crucible cap contributed to lower yields in subsequent runs with the crucible because of insufficient regulation of the rate of effusion from the crucible for the vaporized source material. Attainable yields were also found to be sensitive to the quantity of source material used. Efficient vaporization and ionization was achieved more reliably with smaller quantities of source material (< 1 mg) than with larger quantities (~ 2 mg). Limitations on the maximum power input to the crucible with stable ion source operation also contributed to reduced yields.

Limitations to maximum power input to the crucible were observed as sudden updrifts in the bombardment supply leakage current, a reduction in the potential difference between the filament and crucible and a reduction in monitored ion beam intensity. The cause of this difficulty in achieving stable ion source operation at high power inputs to the crucible (> 550 watts) was traced to two probable sources. A conductive film on the standoff and feedthrough insulators due to plate out of

vaporized tungsten was suspected as leading to additional current leakage paths at high temperatures (high power input to the crucible). This problem was reduced by removing the film from the insulators with an abrasive cleaning unit and installing additional shadow shielding around the insulators to minimize future plate out of tungsten vapors. Also suspected as contributing to a limitation on the maximum power input to the crucible was incorrect positioning of the crucible with respect to the edge of the exit hole through the shield can surrounding the filament and crucible. For positions of the crucible too close to the surrounding shield can orifice, the leakage current became unstable and drifted to higher values. However, for a larger separation between the crucible cap and the shield can orifice, no leakage current updrift occurred, even for power input to the crucible greater than 600 watts. The cause of the leakage current updrift in this case was interpreted as being due to an increase in the total electron current to the crucible because of heating of portions of the tantalum shield can to temperatures for which electron emission was significant. (Normally the only significant source of electrons streaming to the crucible originate from the heated filament.) The correction of these problem sources has resulted in more stable and reliable operation of the high temperature surface ionization ion source.

Essential to the development of new ion sources which extend the capability of the isotope separator laboratory is a test bench for testing new designs. Such a facility is being developed to include a multiport vacuum chamber with associated vacuum pump system and the necessary power supplies and instrumentation for operating an ion source and measuring the various operational parameters.

A vacuum chamber for this system has been fabricated and a vacuum pumping system has been made operational. The chamber has ports to permit storage of up to three ion sources, a fourth port for mounting the ion source in a configuration for operation and testing, and an access opening, normally covered by a bell jar, through which ion optics and current measuring hardware can easily be installed inside the chamber. The vacuum pumping system is a rebuilt Kinney system with a six inch oil diffusion pump with a water-cooled or liquid nitrogen-cooled baffle to minimize backstreaming and a 30 CFM mechanical pump for roughing the system and backing the diffusion pump.

An advanced collector system has been designed which incorporates the following features:

- a. Mounting of up to three separate collection foils (or two foils and one collimating slit foil, etc.).
- b. Mounting of a transmission fluorescent screen on the assembly such that it can be easily rotated into position for viewing directly, or with a TV camera, the ion beam shape at the plane of collection of the ions.
- c. Incorporation of a grid arrangement for suppression of secondary electron emission from the collection foil to permit more accurate measurement of the ion beam current.
- d. Incorporation of a platform which permits the use of single- or multi-isotopic pocket collectors with or without additional

collimating slits. Some components of this system have been fabricated.

Summarized in this report were efforts made to maintain and upgrade the capability of the isotope separator laboratory in the Nuclear Physics Branch. Instrumentation improvements were made in the quadrupole lens supply to permit adjustments in the vertical position of the ion beam, in the probe electronics to provide an undistorted trace of the ion beam shape, and in the telemetry system to calibrate the console meters. In addition operational experience with the surface ionization ion source resulting in more stable operation and improved yields was included. Finally, progress on the development of an ion source test bench and an advanced collector system was summarized.

-
- (1) R. A. Anderl, E. H. Turk, "Collection and Recovery of Milligram Quantities of Mass-Separated Isotopes", this report.
 - (2) R. A. Anderl, R. C. Greenwood, R. J. Gehrke, R. L. Bunting, C. W. Reich, "Development of an On-Line Isotope Separator Facility for Fission Product Decay Studies Using a ^{252}Cf Spontaneous Fission Source", this report.
 - (3) R. A. Anderl, Y. D. Harker, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1975, USAEC Report ANCR-1177 (1974) p. 425.

TABLE I
SUMMARY OF OPERATION WITH SURFACE IONIZATION ION SOURCE

Source Material	No. of Runs	Crucible Depths (Inches)	Efficiency	
			Range (%)	Average (%)
La ₂ O ₃	8	20/32, 22/32	5.7-36.0	18.9
Nd ₂ O ₃	6	20/32, 22/32	16.8-31.3	23.7
Nd ₂ O ₃ ^a	11	21/32	7.0-22.8	17.1
Nd ₂ O ₃ ^b	10	21/32	7.0-22.0	17.4
Tb ₄ O ₇	3	20/32, 24/32	3.2-12.0	6.2
Ce(OH) ₃ ^c	2	22/32	25.7-34.1	29.9
Tb(OH) ₃ ^c	2	20/32, 24/32	4.0-4.6	4.3
BaSO ₄ ^c	1	25/32	14.8	14.8

^a Enriched to 91.06% ¹⁴³Nd.

^b Enriched to 89.67% ¹⁴⁵Nd.

^c Radioactive source material.

DEVELOPMENT OF AN ON-LINE ISOTOPE SEPARATOR FACILITY FOR
FISSION-PRODUCT DECAY STUDIES USING A ^{252}Cf SPONTANEOUS
FISSION SOURCE

R. A. Anderl, R. C. Greenwood, R. G. Gehrke, R. L. Bunting,
C. W. Reich

Introduction

The decay properties of fission-product nuclides are of principal importance in the assessment of certain questions related to reactor safety and the impact of the nuclear power program on the environment. Of particular interest, for example, to a realistic estimation of the decay-heat source term, which is important in the assessment of loss of coolant accidents, are absolute β - and γ -ray branching ratios for the short-lived ($t_{1/2} < 1$ m) fission products. Because of the inherent limitations in the traditional radiochemical techniques to achieve specific and rapid separation of these isotopes for β - and γ -ray measurements, many of these data are either unknown or poorly determined.

A powerful technique for studying the decay properties of short-lived fission-product nuclides is to produce these fission fragments in, or rapidly transport them to, an ion source of a mass separator, perform mass separation, and make the necessary measurements at the mass collector with an on-line data acquisition system. Although this technique is easily applied to the rare gas fission-product, its successful application to the non-gaseous fission-products requires a more sophisticated transport system and a specially-designed ion source.

A promising approach to developing an on-line isotope separator facility which is applicable to non-gaseous fission-products is the coupling of the fission source to the ion source of an isotope separator by means of a gas-jet transport system. Such a facility is functionally illustrated in Figure 1. A regulated flow of carrier gas, typically helium at 10-20 torr-cc/sec, is made to pass through a cluster generator, where heavy mass ($\sim 10^8$ amu) molecular clusters (aerosols of H_2O , CCl_4 , oil, etc.) are formed and added as impurities, and to flow into a chamber containing the ^{252}Cf fission source. The volume and gas pressure inside the source chamber is so established that fission products from the ^{252}Cf source thermalize in the gaseous volume and become attached to the heavy mass clusters. The carrier gas, with the entrained clusters and attached fission fragments, are pumped through the capillary tubing (~ 1 mm ID) such that sonic flow is reached at the entrance to the skimmer chamber. Upon exiting from the capillary the helium transport gas expands rapidly and is pumped away with the high capacity vacuum pump system. On the other hand, the flow of the clusters, which has concentrated along the capillary axis, diverges very little upon exiting from the capillary. A conical skimmer cone with a small axial hole is so aligned with respect to the capillary that the cluster jet is transported from the high pressure side of the skimmer chamber into a low pressure portion

coupled to the ion source of the isotope separator. The molecular clusters disintegrate in the ion source and release the fission products which are ionized and subsequently mass-separated.

During this past year our efforts have concentrated on building a gas-jet transport system, performing transport experiments with helium gas loaded with H_2O or CCl_4 molecular clusters, developing a high capacity vacuum pump system and studying the problems associated with coupling such a system to an ion source of an isotope separator.

Gas-Jet Transport Experiments

Our first series of transport experiments were conducted with a system illustrated in Figure 2. Volumes of the collection, source, and cluster generator chambers were approximately 880 cm^3 , 290 cm^3 , and 310 cm^3 , respectively. The distance from the $7\text{ }\mu\text{g}$ ^{252}Cf source foil situated at the bottom of the chamber to the top of the chamber was 6.35 cm . A 1.13 mg/cm^2 nickel foil was placed over the ^{252}Cf source to prevent migration of recoil Cf atoms throughout the chamber. Pressures in the source and collection chambers were measured with a 30" - 0-30 psig Bourdon tube gauge and a McLeod gauge, respectively. Matheson Model 602 Rotameters were used to measure the flow rates of the commercial grade high purity helium. A model 11 SC-1 PEN-RAY UV lamp was used to stimulate the formation of the molecular clusters. A 50 CFM Stokes Microvac pump was used to evacuate the collection chamber. Helium gas was transported from the source chamber to the collection chamber through a 1-m 20-gauge (0.87 mm ID) teflon capillary tubing positioned $\sim 2\text{ mm}$ from the collection foil.

The operating conditions and results for this first series of experiments are summarized in Table I. A single run consisted in mounting an aluminum collection foil in the collector chamber, establishing the pressure and gas flow operating conditions, collecting transported activity for 30 minutes, and removing the foil for a 30-minute wait before measuring the γ -ray spectrum for 30 minutes with a Ge(Li) detector. Transmission efficiencies were determined from a quantitative comparison of peak areas in this spectrum with corresponding peak areas in a spectrum taken for fission products collected on an aluminum foil placed directly above the ^{252}Cf source. The peaks used were identified as due to gamma transitions in the decays of isotopes of Te, Ba, Tc, Pr, La, Sb and Cs. For each run, the average transmission efficiency was computed as the average of the values determined for each of the individual peaks used per run.

Although a maximum average transmission efficiency of 12.4% was measured for one set of conditions, this result was not reproducible in these series of experiments. Furthermore, an expected increase in transmission efficiency because of increased thermalization in the source chamber, from run 3 to run 5 was not observed. The importance of the use of UV light to stimulate cluster formation is illustrated by the results of runs 2 and 3 and runs 4 and 5.

A second series of experiments was conducted with an improved gas-jet transport system illustrated in Figure 3. Major improvements in the system were the use of separate chambers for vapor mixing and for operating the UV light, the use of a collection foil injector rod and vacuum interlock assembly and more rigid mounting of the collection chamber to minimize the transmission of pump vibration to the capillary. The use of the injection rod-vacuum interlock assembly permitted easy installation and removal of the collection foils from run to run without introducing air into the system or changing the operational conditions. A 3-m length of 20-gauge (0.87 mm ID) Teflon tubing used as the capillary was positioned ~ 8 mm from the collection foil.

A summary of the transmission experiments with this system is given in Table II. In order to establish reproducible initial conditions for these runs, the system back to and including the source chamber was evacuated and pumped on for at least one hour and was then flushed with dry helium for another hour before any collection experiments were begun. This procedure was considered necessary to flush any air from the chambers and lines in the transport system. Runs 1-6, 7-11, and 12-16 were made on three different days. A typical run consisted in establishing the flow-, vapor-mixing-, UV-, and pressure-conditions, inserting an aluminum collection foil, collecting for 15 minutes, and removing the foil for a 15 minute wait before measuring the gross β -activity with a gas filled ionization chamber. Transmission efficiencies were determined from a quantitative comparison of this gross β activity with that from the fission products deposited on an aluminum foil placed directly above the ^{252}Cf source. Collection and wait times were identical for the reference activity measurements.

With this series of transmission experiments, reproducibility and a systematic response of the system to variation of individual parameters was achieved. Reproducible results are indicated for runs 9 and 11 and runs 5 and 10. The variation in the transmission efficiency due to changing concentration of H_2O vapor is indicated by the results from runs 2, 4, 5, 6, and 12. The systematic increase in transmission from run 2 to run 5 is expected to be due to a systematic increase in the concentration of water clusters. The results from runs 10, 8, and 9 show a systematic increase in transmission efficiency with increasing source chamber pressure. This increase is expected from a consideration of the range of the fission fragments in helium at different pressures as illustrated in Figures 4 and 5. These curves were calculated using the mean energies and mean masses of the light and heavy mass peaks from spontaneous fission of ^{252}Cf and the range tables of Northcliffe and Schilling³. The range curves for fragments whose energies have been degraded by a 1.13 mg/cm^2 nickel foil (that used in these transmission experiments) show that there is less plate-out of some of the fragments on the walls of the source chamber (a distance of ~ 6.35 cm from the ^{252}Cf source foil) at ~ 1.51 atmospheres (run 9) than at ~ 1.2 atmospheres (run 8) or at ~ 1.0 atmospheres (run 10). Another systematic response is the apparent increase in transmission efficiency with increasing temperature of the UV chamber. This is illustrated by runs 7, 10, and 13 for which the chamber temperature varied from

220 C to 470C. Some variation of the transmission efficiency with vapor pressure of the additive is indicated by a comparison of the runs made with CCl_4 (15, 16) with comparable runs made with H_2O (13, 4).

These semi-quantitative experiments provide a firm base of experience for further design of improved apparatus and experiments to increase the transmission efficiency of our gas-jet transport system.

A high capacity vacuum pump system is being developed for the gas-jet transport system and for its use when coupled to the ion source of the isotope separator. The basic components of this system, a WS-1000 Roots pump (~ 660 CFM at 0.1 Torr) and a DK-200 rotary piston pump (130 CFM), have been procured from Leybold Heraeus.

Summary

In summary, a gas-jet transport system has been developed and tested using a ^{252}Cf fission source, helium transport gas, and vapor additions of H_2O and CCl_4 . Reproducible results have been achieved and semi-quantitative experiments have been performed to study the response of the system to a systematic variation of individual parameters of the system. A maximum transmission efficiency of 33% has been achieved. The basic components of a high capacity pumping system (600 CFM at 0.1 Torr) have been procured.

Our efforts in the coming fiscal year will be concerned mainly with extending the transport measurements to different gases and vapor additives, developing a cluster generator which is not dependent on the use of a UV light, and developing the hardware for interfacing the gas-jet system to an ion source of the isotope separator.

-
- (1) R. C. Greenwood, R. A. Anderl, C. W. Reich, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1974, USAEC Report ANCR-1177 (1974) pg. 410.
 - (2) E. K. Hyde, The Nuclear Properties of the Heavy Elements, Vol. III, Fission Phenomena, Chapters 4 and 6.
 - (3) L. C. Northcliffe and R. F. Schilling, Nuclear Data Tables, Vol. 7, Numbers 3-4, January, 1970.

TABLE I
SUMMARY OF GAS-JET TRANSMISSION
EXPERIMENTS: SERIES I

Run	Flow Rate (cc/sec)	Mixing Ratio (%)	UV Light	Source Chamber Pressure (Torr)	Collection Chamber Pressure (Torr)	Average Transmission Efficiency (%)
1	19.5	0 ^a	Off	754	4.8	0
2	7.8	100 ^b	Off	465	2.2	2.5
3	8.0	100 ^b	On	470	2.2	12.4
4	20.3	100 ^b	Off	857	6.1	0
5	20.5	100 ^b	On	868	6.5	1.8
6	9.8	8 ^c	On	567	3.0	4.0

a Dry Helium only

b Helium bubbled through H₂O

c Dry Helium mixed with Helium bubbled through H₂O

TABLE II
SUMMARY OF GAS-JET TRANSMISSION
EXPERIMENTS: SERIES II

Run	Flow Rate (cc/sec)	Mixing Ratio (%)	UV Light	Source Chamber Pressure (Torr)	Collection Chamber Pressure (Torr)	Average Transmission Efficiency (%)
1	16	0 ^a	Off	713	1.3	0
2	16	0 ^a	On	713	1.3	0.7
3	16.2	100 ^b	Off	726	1.3	0
4	16.2	100 ^b	On	726	1.3	3.8
5	16	100 ^c	On	726	1.3	6.7
6	16.4	15 ^d	On	726	1.3	4.1
7	15.5	100 ^c	On	713	1.25	1.0
8	19.4	100 ^c	On	920	1.75	11.0
9	~ 21	100 ^c	On	1155	2.25	33.0
10	16	100 ^c	On	752	1.4	4.7
11	~ 21	100 ^c	On	1155	2.3	33.0
12	16	100 ^e	On	713	1.3	4.1
13	16	100 ^b	On	713	1.3	13.7
14	16	100 ^b	Off	713	1.3	.96
15	15.5	100 ^f	On	713	1.3	9.6
16	15.5	100 ^f	On	713	1.3	13.7

a By-pass vapor mixer, dry helium only

b Through vapor mixer, helium above H₂O additive

c Through vapor mixer, helium above H₂O and bubbled through H₂O

d Dry helium from by-pass mixed with helium bubbled through H₂O

e Through vapor mixer, helium bubbled through H₂O

f Through vapor mixer, helium above CCl₄ additive

Figure 1. Block diagram illustration of an on-line isotope separator which utilizes a gas-jet transport system.

Figure 2. Schematic illustration of gas-jet transport system used for series-I measurements.

Figure 3. Schematic illustration of gas-jet transport system used for series-II measurements.

Figure 4. Range curves in helium for heavy-mass-peak fission fragments from spontaneous fission of ^{252}Cf .

Figure 5. Range curves in helium for light-mass-peak fission fragments from spontaneous fission of ^{252}Cf .

HIGH RATE 4π β - γ COINCIDENCE ELECTRONICS

L. O. Johnson

The possibility of operating a 4π β - γ coincidence system at high disintegration rates ($> 100,000$ disintegrations/sec) is being investigated. Operating at these rates requires both fast new electronics to minimize count rate related corrections and the development of a suitable set of correction equations applicable to the new electronics system. The interest in high rate operation stems from two sources; 1) requirements for measuring accurately disintegration rates and beta branching ratios of short lived isotopes, 2) if the 4π β - γ system may be operated accurately at $> 100,000$ dps, the possibility of introducing a Ge(Li) detector into the system to obtain simultaneously gamma ray spectrum information for determining beta branching ratios.

The electronics system presently being investigated consists of:

1. Current sensitive preamplifiers for both β and γ channels.
2. High speed, high sensitivity emitter-coupled discriminators.
3. Discriminator pulse shaping which makes each pulse as wide as the discriminator pulse for pulses whose width is > 250 ns and $= 250$ ns for all pulses whose width is < 250 ns.
4. Dead-time circuits which deliver dead-time (or pulse width) information for each channel.
5. Overlap coincidence circuitry so that no dead-time is introduced via the coincidence circuit.
6. A second system whose parameters are degraded such that classical correction equations are applicable up to moderate rates.

Current sensitive preamplifiers were chosen so that minimum pulse width for a given detector could be obtained. The pulse width is equal to the current collection time in the detectors and is thus the shortest possible pulse width (and dead time) obtainable with the detectors used. A ^{60}Co source in the present system yields an average β pulse width of ~ 450 NS and the average γ pulse width of ~ 800 NS. Thus, at $100,000$ cps β , the rate correction is less than 5%.

Baseline restores at the preamplifier output essentially eliminate the slow ion current contribution to the current pulse from the proportional counter (β channel) so that only the width of the electron current pulse is reflected in the β channel output.

A Time-Amplitude converter spectrum of the timing between the β and γ pulses indicates that $2\tau < 500$ NS. Therefore, by setting a minimum pulse width of 150 NS for each channel, no coincident events are lost in an overlap coincidence circuit.

By recording the dead time for each channel simultaneously with each data run, rate associated corrections may be made accurately and with no approximations.

Initial indications are that this system may be operated up to 500,000 disintegrations/sec with better than .5% accuracy.

HIGH RATE GATED BASELINE RESTORER FOR Ge(Li) DETECTOR SYSTEMS

L. O. Johnson

Gamma-ray spectrometry applications for gamma-gamma coincidence systems and short-lived isotope analysis require shaping electronics with high counting rate capability. One problem area is counting rate performance of the baseline restorer.

A gated baseline restorer has been designed and built that is capable of performing acceptably at any count rate up to the preamplifier charge-loop saturation point for conventional resistive feedback preamplifiers. It was built to be suitable for use with pulsed optical feedback preamplifiers in that the restorer action may be gated off during the large amplitude negative reset pulse.

It is an asymmetrical restorer whose droop rate is adjustable from ~ 10 volts/sec to ~ 100 volts/sec to control baseline microphonics and whose restoring sensitivity is ~ 20 amps/volt into 2 μ f or 10 volts/ μ sec for a one volt baseline excursion. D.C. temperature drift is less than 10 μ v/ $^{\circ}$ C. The rate performance of the restorer is listed in the following table

AUTOMATION OF RADIATION MEASUREMENTS LABORATORY OPERATIONS

W. R. Myers, G. O. English, R. A. Coates, E. E. Owen, R. C. Davies

The Aerojet Nuclear Company Radiation Measurements Laboratory, located in the Test Reactor Area at the Idaho National Engineering Laboratory, is a supporting experimental facility providing technical assistance and routine services in the fields of effluent monitoring, radiation measurements and radiation data acquisition systems support.

Laboratory instrumentation includes a versatile PDP-15 computer system for on-line data analysis, control and acquisition of laboratory data, and communication with remote and remotely-controlled data acquisition systems. The computer supports activities of RML personnel in all phases of laboratory services.

The computer hardware includes 32,768 words of core memory, more than 5 million words of disk memory, two industry-compatible magnetic tape transports, several DECtape transports and a 200 line-per-minute line printer. Laboratory personnel interact with the system through two teletypewriters, a data-display oscilloscope, and a programmable keyboard and control panel. The PDP-15 system includes auto-answer, auto-dial telephone interfaces for transmission and receipt of data and control information over dial-up telephone lines at 110 and 1200 baud. The system is interfaced to several data sources in the Radiation Measurements Laboratory including three Ge(Li) systems, two NaI(Tl) analyzers, a two-channel alpha spectrometer, and a four-channel automatic beta-counting system. It is also interfaced over high-speed communication lines to a PDP-8 computer with several data interfaces including a Ge(Li) gamma-ray spectrometer, and a PDP-9 data acquisition system with interactive graphics capability. The PDP-15 is controlled by real-time multi-task operating system software. Up to five data analysis procedures may be executing simultaneously with any number of data transfers from laboratory or remote data systems. Fundamental data analysis operations, such as least-squares regression analysis, automatic peak searching and isotope library merging are written in assembly language to optimize computer performance. Utilization of the basic analysis modules, report generation and special data analysis procedures are written by laboratory personnel using high-level control and analysis languages.

Libraries of analysis control procedures and analysis programs, detector efficiency and analyzer system linearity tables, NaI(Tl) standard spectra, and recently measured data from laboratory and remote spectrometers and counting systems are maintained on-line on random-access bulk storage.

TABLE I

SHAPING TIME - 6 μ sec TO PEAK 1.33 MeV Co⁶⁰ PEAK

<u>Count Rate</u> <u>(cps)</u>	<u>Peak location</u> <u>(channel)</u>	<u>Resolution</u> <u>(keV FWHM)</u>
1,000	4080.0	1.80
10,000	4080.0	1.80
25,000	4079.9	1.90
50,000	4079.9	1.95
90,000	4079.9	2.55

BULK MONITORING OF SOIL FOR LOW LEVEL TRANSURANIC CONTAMINATION

J. W. Mandler, P. D. Randolph

In the past, barrels containing transuranic waste material (primarily ^{239}Pu and ^{241}Am) have been buried at the INEL radioactive waste management complex. These barrels are currently being retrieved for repackaging and above ground storage on an ITSA pad. Many of these barrels have been in the ground for more than ten years and can be expected to have disintegrated to a great extent. The dirt surrounding these barrels, therefore, must be surveyed to determine if it is contaminated. Current regulations require that dirt containing more than 10 nanocuries of transuranics per gram must be treated as hot waste and stored accordingly. Dirt containing less than 10 nCi/gm of transuranics is considered uncontaminated and can be returned to the ground.

A system utilizing passive gamma-ray analyses is currently being developed to survey the dirt surrounding retrieved barrels. Current efforts have been focused on demonstrating that the technique possess adequate sensitivity with bulk samples and can achieve sufficient throughput. This has been accomplished using a laboratory detector and small dirt samples.

The initial feasibility experiments were performed using a 3 inch x 3 inch NaI(Tl) detector and dirt samples doped with various activities of ^{239}Pu and ^{241}Am . The dirt used was representative of that at the radioactive waste management complex site. Six samples of dirt (total mass of 9788 gm) were obtained from different "clean" locations just outside the perimeter of the site. The density of the dirt was measured to be 1.19 gm/cm³. These samples were counted using the NaI detector to insure that they were not contaminated with transuranics. Counting indicated only the normal background components from ^{40}K and members of the natural thorium decay chain. The dirt was therefore judged to be "clean".

A series of ^{239}Pu and ^{241}Am standards were made to be used in doping dirt to simulate various contamination levels. The ^{239}Pu - ^{241}Am sources were made from ^{239}Pu which is about 20 years old and contained 0.48% ^{241}Pu when first made. At this age, about 10% of the activity should be due to ^{241}Am . The ^{239}Pu standards were made after separation of the ^{241}Am from this material. The ^{241}Am standards were made from separated americium. All of the standards were sealed in 1-5/16 inch diameter by 3/8 inch thick epoxy disks, with the activity located on axis about 1 mm below the front surface. Table I lists the amounts of ^{239}Pu and ^{241}Am in those standards together with activities determined by gamma-ray accounting at the RML. These activities were selected so that contamination levels of ^{239}Pu ranging from about 5 to 50 nCi/gm and levels of ^{241}Am ranging from about 1 to 10 nCi/gm could be simulated by using various combinations of source disks located throughout a 12 inch x 12 inch x 3 inch thick dirt sample (8430 gm mass).

Experiments were performed by suspending the NaI(Tl) detector above the dirt sample with the crystal face located 2 inches above the surface of the dirt. Sources were placed so that the activity was located at coordinates (2,2,1.5), (6,2,1.5), (10,2,1.5), (2,6,1.5), (6,6,1.5), (10,6,1.5), (2,10,1.5), (6,10,1.5), and (10,10,1.5), where the entries are the x, y and z coordinates measured in inches from a corner on the top surface of the sample (see figure 1). The doped dirt samples were counted for 2000 seconds and the spectra obtained. The counts in the windows 44-67 keV and 82-138 keV were integrated. These windows were selected so that the first one would contain the 51.6 keV peak from ^{239}Pu together with the 59.5 keV peak from ^{241}Am while the second window would contain the 129.3 keV gamma peak and the x-ray peaks from ^{239}Pu .

The count rates obtained in the two windows for the various doping levels are listed in Table II. The background has been subtracted from these count rates. Note that the ^{241}Am sources produce a count rate in window 2. This is due to random summing of the 59.5 keV gamma-ray pulses. Using the results from Table II, the following calibration equations were obtained:

$$A(\text{Pu}) = 1.074 W2 \text{ corr}$$

$$A(\text{Am}) = \frac{W1 - 0.310 W2 \text{ corr}}{272.9}$$

where $A(\text{Pu})$ and $A(\text{Am})$ are the activities of Pu and Am, respectively, in nCi/gm, $W1$ is the count rate (in cps) in the 44-67 keV window and $W2 \text{ corr}$ is the count rate (in cps) in the 82-138 keV window after correction for random summing of the 59.5 keV gamma rays. A curve of the random summing correction was obtained as a function of the count rate in the 44-67 keV window by counting a series of ^{241}Am sources of different strengths.

The calibration equations were tested by considering Pu-Am sources 1-9 and Pu sources 37-45 to be unknowns. They were placed in the dirt sample and counted. Results were 11.4 nCi/gm ^{239}Pu and 1.17 nCi/gm ^{241}Am for sources 1-9 (actual activities were 10.3 nCi/gm ^{239}Pu and 1.0 nCi/gm ^{241}Am) and 38.1 nCi/gm ^{239}Pu for sources 37-45 (actual activity was 39.9 nCi/gm). These results indicate that the calibration is satisfactory.

Using the calibration equations and the measured background count rates (i.e., 3.32 cps in the 44-67 keV window and 9.25 cps in the 82-138 keV window) the expected uncertainties for a 30 second run were calculated for the 3 inch x 3 inch NaI(Tl) and a 12 inch x 12 inch x 3 inch thick dirt sample. Table III contains the results of these calculations. Shown are the expected 1σ uncertainties for various ^{239}Pu and ^{241}Am contamination levels. Ten percent uncertainties in the random summing correction factor and in the coefficients in the calibration equation were assumed. The results indicate that in 30 seconds 5 nCi/gm ^{239}Pu plus 0.5 nCi/gm ^{241}Am can be detected with a 1σ uncertainty of 27%.

The results in Table III are very encouraging, for they indicate that under the conditions used, 5 nCi/gm of transuranics is easily detectable in 30 seconds. The actual detection limit that can be expected for an optimized system at the radioactive waste management complex should be lower (assuming that sufficient shielding is used to keep the background at the level detected during the laboratory studies). For example, sensitivity can probably be increased by replacing the 3 inch x 3 inch detector with an array of 5 inch x 1/2 inch detectors. Throughput using the 3 inch x 3 inch detector, a 12 inch x 12 inch x 3 inch thick sample (8430 gm for $\rho = 1.19 \text{ gm/cm}^3$), and a 30 second sample time would be 0.5 ft³ of dirt per minute (or 150 ft³ per five hour day). Throughput can be increased by using an array of detectors and a larger volume dirt sample.

Further studies will be made with the 3 inch x 3 inch detector being replaced by a 5 inch x 1/2 inch detector. The effect of using an array of detectors will also be investigated together with methods to handle a background count rate which varies with time.

TABLE I

PLUTONIUM AND AMERICIUM STANDARDS

Source Numbers	Type of Activity	^{239}Pu Mass (μgm)	^{241}Am Mass (μgm)	Measured ^{239}Pu	Activities (μCi) ^{241}Am
1-9	Pu-Am	162	a	10.1	~ 1
10-27	Pu	81.5	---	5.1	---
28-36	Pu	163	---	10.1	---
37-45	Pu	625	---	39	---
46-54	Am	---	0.3	---	1.03
55-63	Am	---	0.6	---	2.06
64-72	Am	---	1.8	---	6.2
73-81	Am	---	3.0	---	10.3

^aValue has not been determined.

TABLE II

RESULTS OF MEASUREMENTS ON SIMULATED CONTAMINATED DIRT

Contamination Level (nCi/gm)		Count Rate (cps) in Window ^a	
<u>²³⁹Pu</u>	<u>²⁴¹Am</u>	<u>#1</u>	<u>#2</u>
10.4	0	2.864	9.548
5.2	0	1.646	4.980
0	1.06	247.6	1.509
0	2.1	562.8	3.645
0	6.3	1771.5	17.427

^aWindow #1 was 44-67 keV. Window #2 was 82-138 keV.

TABLE III

EXPECTED UNCERTAINTIES FOR 30 SECOND RUN USING 3" x 3" NaI(Tl)
DETECTOR ON 12" x 12" x 3" DIRT SAMPLE

Activity (nCi/gm)		Uncertainty (%)
^{239}Pu	^{241}Am	
1.0	0.1	91
2.0	0.2	50
3.0	0.3	36
4.0	0.4	30
5.0	0.5	27
6.0	0.6	24
7.0	0.7	22
8.0	0.8	20
9.0	0.9	20
10.0	1.0	19
0.0	10.0	48
1.0	9.0	38
2.0	8.0	33
3.0	7.0	30
4.0	6.0	26
5.0	5.0	23
6.0	4.0	21
7.0	3.0	20
8.0	2.0	20
9.0	1.0	20

X - Source location
- All source located 1.5 inches below top surface of dirt sample

Figure 1. Top view of sample - detector geometry showing source locations

DESIGN OF A MONITOR FOR LARGE BOXES
CONTAINING LOW LEVEL TRANSURANIC WASTES

P. D. Randolph, E. B. Nieschmidt

Low level transuranic wastes are regularly received from off-site for interim recoverable storage at the INEL waste management complex. This waste arrives in 55-gallon barrels and in large boxes (4' X 4' X 7'). The amounts of transuranics in a container are usually ≤ 5 gms, but on occasion is much greater. These packaged wastes are stored above ground on a large asphalt pad called the Idaho Transuranic Storage Area (ITSA). Barrels are stacked four high within walls built up from the large boxes. Each layer is covered with plastic sheets and plywood and the top surface is covered with a final plastic sheet and with ≈ 18 " of soil. Since this forms a very large array, it is important that there be assurance that no criticality hazard exists.

The transuranics contained are plutonium and americium. For criticality hazard assessment the amount of concern is 200 gms of plutonium. Amounts less than this present no criticality hazard and containers can be stacked in arbitrary array regardless of the matrix of waste materials that are contaminated.

Instrumentation for assay of 55-gallon steel barrels at the 200 gm level can be obtained from commercial suppliers, however, no such devices have been developed for the large boxes.

The objective is to develop a box monitor capable of acting as a go-no go device for plutonium at the 200 gm level and that should also be able to yield a rough assay ($\sim \pm 25\%$) for amounts above 200 gms. It is meant only for criticality hazard assessment, not for accountability. The monitor should be able to handle ~ 15 boxes per day and be operable by non-technically trained personnel in an outdoor environment on a year-round basis.

The wastes contained in a box are generally objects too large to fit in a 55-gallon barrel but are not limited to these. It consists of such medium Z objects as pipe, valves, metal ducting, small tools, disassembled machine tools, and low Z materials in the form of construction wastes such as wall board, wood, and broken concrete block. Heavy metals, usually lead, can also be present in the form of batteries or pieces of lead shielding. The average atomic number for the wastes is in general not known. Also, box loading can range from extreme heterogeneity to almost homogeneous.

Methods of non-destructive assay for plutonium can use passive counting of Pu gamma rays, passive neutron counting, or active neutron interrogation. Of these methods passive neutron counting appeared to be most practicable. Passive gamma counting was eliminated because the useful gamma rays from Pu (375-413 keV) have rather low penetrability through high Z materials, and because the waste matrix can be highly heterogeneous. The active neutron interrogation method uses a neutron source to induce fissions in the ^{239}Pu and the resulting fission

neutrons are counted. Due to the size of the box, an interrogating source such as ^{252}Cf or ^{124}Sb -Be would have to be large and the associated shielding would be very massive. Though this method may be technically feasible, it is quite expensive and did not appear warranted for initial development.

The method chosen, passive neutron counting, is based on detecting neutrons arising from two processes. The processes are spontaneous fission of the ^{240}Pu (470 fissions/gm sec) and (α, n) neutrons caused by radioactive decay α 's interacting with molecularly bound oxygen in PuO_2 . The neutron yields of interest are given in Table I. The isotopic makeup of the plutonium is approximately 94% ^{239}Pu , 5.5% ^{240}Pu and 0.5% ^{241}Pu , and the actual values will be known fairly accurately for any given waste-box. Generally, the fluorides which have the highest (α, n) yield are not expected to be present. The major sources are, therefore, $^{239}\text{PuO}_2$, ^{240}Pu metal and $^{240}\text{PuO}_2$. Assuming the material is all PuO_2 , then 108 neutrons/sec gm Pu will be emitted using the above isotopic abundances. This neutron fluence should be quite adequate for $\text{Pu} \geq 100$ gms.

The basic idea is to pass the box (with the 7-foot dimension horizontal) through a rectangularly shaped annular ring of fast neutron detectors and use the count integrated over the length of travel to determine the level of Pu in it.

Figure 1 is a sketch of the layout. It is based on the LASL designed fast neutron "Slab detector."⁽²⁾ Figure 2 shows a sketch of the slab detector. Each uses 15 BF_3 neutron detectors two inches in diameter with a 36" active length. Fill pressure is 70 cm BF_3 enriched in ^{10}B . The axis of the individual detectors is parallel to the long dimension of the waste box. Total thickness of the polyethylene slab is 5 inches. The slab is covered with 0.020" of cadmium to stop thermal neutrons. The side of the slab facing the box is slightly undermoderated to allow for the presence of moderating materials in the box. Since a waste box could contain large amounts of moderator in the form of concrete or wood, the final design may also have to incorporate bare thermal neutron detectors. The efficiency, ϵ , for fast neutron detection of this type detector for a point source 30 inches away is about 1%.⁽²⁾ The approximate solid angle fraction for a point at the center subtended by a cylindrical ring of detectors 36 inches long of radius 30 inches is $f_\Omega \sim 0.51$. The expected counting rate, I , for a point source of 200 gms of PuO_2 with no absorption or self shielding would then be

$$I = N_0 \epsilon f_\Omega = 108 \times 200 \times .01 \times .51 = 110 \text{ cts/sec}$$

This is a quite adequate count rate, however, the expected distribution of Pu is heterogeneous.

A simplest estimate of the effects of having a distributed source in a box can be obtained in analytic form by assuming the emitting material is uniformly distributed along a line centered in the box and

parallel to its long edge. Again, no attenuation effects are considered.

Figure 3 shows the geometry for a cylindrical ring of detectors of length, ℓ , located on a radius, a , from and parallel to the line source of length, L . One end of the line source is at a distance X_0 from the center of the detector array. The response of the array of efficiency E to a source of strength $\rho(X_1)$ per unit length is for a given value of X_0 .

$$I(X_0) = E \int_0^L \rho(X_1) dX_1 \frac{dA}{4\pi r^2}$$

$$r^2 = (X_1 + X_0 - X)^2 + a^2$$

$$dA = \text{elemental area} = a d\phi dX \cos\theta = a d\phi dX \frac{a}{r}$$

$$I(X_0) = E \frac{a^2}{2} \int_0^L \rho(X_1) X_1 \int_{-\ell/2}^{\ell/2} \frac{dX}{r^3}$$

for a uniform line source of total strength ρ_0 neutrons/sec

$$\rho(X_1) = \frac{\rho_0}{L}$$

The result of integration is

$$I(X_0) = \frac{E\rho_0}{2L} \left\{ \sqrt{\left(X_0 + L + \frac{\ell}{2}\right)^2 + a^2} - \sqrt{\left(X_0 + \frac{\ell}{2}\right)^2 + a^2} \right. \\ \left. - \sqrt{\left(X_0 + L - \frac{\ell}{2}\right)^2 + a^2} + \sqrt{\left(X_0 - \frac{\ell}{2}\right)^2 + a^2} \right\}$$

The maximum response occurs when the line source length is centered in the array, i.e., $X_0 = -\frac{L}{2}$

$$I_{\max} = I\left(-\frac{L}{2}\right) = \frac{E\rho_0}{L} \left\{ \sqrt{\left(\frac{L+\ell}{2}\right)^2 + a^2} - \sqrt{\left(\frac{L-\ell}{2}\right)^2 + a^2} \right\}$$

Figure 4 shows a plot of $I(X_0)/I_{\max}$ as a function of source position in units of source length L . The value $I_{\max}$ is 34.1% that of a point source of the same total strength ρ_0 located at the center. It is seen that at $X_0 = +0.5 L$ the count rate is only about 10% that at $X_0 = -0.5 L$. The total count obtained in moving such a source through the detector array at some fixed speed is proportional to the integral

of the $I(X_0)/I_{\max}$ curve from the initial to the final X_0 . From Figure 4 it is seen that when the source is at $X_0 = 2L$ the intensity is insignificant, so that the integral of the curve from $X_0 = -.5L$ to $X_0 = +2L$ gives the maximum count that is meaningful, i.e.,

$$A_{\max} \equiv A(2L) = \int_{-.5L}^{2L} \frac{I(X_0)}{I_{\max}} X_0$$

The inset of Figure 4 shows the fraction of this maximum obtained by moving the source from $-.5L$ to an arbitrary stopping point X'_0 :

$$F(X'_0) = \frac{1}{A_{\max}} \int_{-.5L}^{X'_0} \frac{I(X_0)}{I_{\max}} dX_0$$

Thus, when a box has moved at constant speed from a position centered in the detector by one full box length to $X'_0 = +.5L$ the total accumulated count of 90% of the maximum. To count boxes where the sources are truly heterogeneous the system should, therefore, be at least three box lengths long.

Sufficient polyethylene has been obtained to make two of the four slab detectors needed and 16 of the approximately 61 detectors required have been purchased. For initial work these are arranged so that each of the slabs has a detector in every other hole. This will provide $\leq 25\%$ of the count rates obtainable with the full system, but should be enough to test the design. Sealed one gallon volume standards containing plutonium in various waste matrices have been obtained that cover the anticipated range expected. These will be used to determine the effects of source location and will be surrounded with additional waste materials to determine their effects. Hydrogenous wastes will also be used to assess moderation effects.

-
- (1) R. H. Augustson and T. D. Reilly, "Fundamentals of Passive Non-Destructive Assay of Fissionable Material," LASL, LA-5651-M, September 1974.
 - (2) L. V. East and R. B. Walton, "Polyethylene Moderated ^3He Neutron Detectors," Nuclear Instr. & Meth. 72 161 (1969).

Figure 1. Conceptual layout of waste box monitor.

Number Required: 4

Weight Each: ~325 lbs

Material: 2. 2" Thick, Low Density, Stress Relieved Polyethylene Slabs
1. 1" Thick, Low Density, Stress Relieved Polyethylene Slab

ANC-A-6231

Figure 2. Slab neutron detector design.

Figure 3. Geometry for calculating approximate response of slab detector array to a centered line source.

Figure 4. Calculated response of cylindrical detector array to a line neutron source.

THE INEL RADIATION MEASUREMENTS LABORATORY

O. D. Simpson

The Aerojet Nuclear Company Radiation Measurements Laboratory, located in the Test Reactor Area at the Idaho National Engineering Laboratory, is a supporting experimental facility providing technical assistance and routine services in the fields of effluent monitoring, radiation measurements and radiation data acquisition systems development.

Radiation measurements services from simple gross counting to complex state-of-the-art gamma-ray remote monitoring under computer control are available upon request. Aerojet Nuclear Company, the prime contractor at the Idaho National Engineering Laboratory provides this service with an up-to-date computerized counting laboratory and a well-staffed research group. Major personnel responsibilities include the operation of nuclear counting laboratories, maintenance of radiation measurement standards, measurement of flux distributions, gamma heating, other in-pile measurements in the test reactors and associated loop experiments, and the development of measurement techniques required in support of reactor programs. The central counting facility is presently equipped with a variety of pulse-height analyzers, alpha, beta and gamma-ray spectrometers, a 4π beta-gamma coincidence apparatus for radioactive source standardization, several multi-channel counting systems for analysis of large numbers of activated foils and wires, automated wire scanners for flux traverse determinations, a standard exponential pile for neutron flux standardization, and numerous pieces of apparatus required to support Health Physics activities.

Laboratory instrumentation includes a versatile PDP-15 computer system for on-line data analysis control and acquisition of laboratory data, and communication with remote and remotely-controlled data acquisition systems.

Routine services include NaI(Tl) and Ge(Li) gamma-ray spectroscopy in health physics applications, for measurement of reactor neutron flux distributions, for environmental, effluent, and reactor operation monitoring, and in support of fundamental nuclear physics programs. Activation techniques are used in trace element analysis and for measurement of neutron flux distributions in critical facilities and power reactors. Alpha spectroscopy and alpha, beta and gamma gross counting techniques are routinely used when appropriate. Routine services include analysis and evaluation of data, maintenance of records and generation of immediate and summary reports as required.

B. APPLIED REACTOR PHYSICS

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

Experimental Measurements

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

MANGANESE BATH SYSTEMATIC EFFECTS IN MEASUREMENTS OF $\bar{\nu}$ -BAR AND η A[†]

J. R. Smith

For several years there has persisted a discrepancy in measured values of $\bar{\nu}$ for ^{252}Cf . This discrepancy has from time to time been declared resolved,^(1,2) but continues to cause concern. One way to view this discrepancy is to examine the results of pertinent measurements made using the manganese bath. DeVolpi et al⁽³⁾ and Axton et al⁽⁴⁾ have both measured $\bar{\nu}$, the average number of neutrons per fission, for ^{252}Cf . Both have obtained the value 3.725, and both estimate errors of slightly less than 0.5%. Macklin and deSaussure^(5,6) and Smith et al^(7,8) measured η , the average number of neutrons per absorption, for the fissile nuclei. Their results agree well, and again accuracies of 0.5% are claimed.

Values of $\bar{\nu}$ for the fissile nuclei are derived from measurements of their ratios to $\bar{\nu}$ for ^{252}Cf . Then α , the absorption-to-fission ratio, can be used to connect $\bar{\nu}$ and η through the well-known relation

$$\bar{\nu} = \eta(1+\alpha). \quad (1)$$

By way of Eq. (1), using the values for α and the $\bar{\nu}$ which were input to the 1968 IAEA evaluation of the fission constants,⁽⁹⁾ we can derive the values for $\bar{\nu}$ for ^{252}Cf which are consistent with the η measurements. The average value thus derived for ^{252}Cf is 3.776. This is about 1.4% higher than the value measured directly by DeVolpi and Axton. Thus, the "hard core" of the discrepancy is of the order of 1%.

The problem of reducing the residual 1% spread is a difficult one. It may be that no single source of error is present in any experiment, but a composite of several small differences in several experiments. In view of efforts to attribute the problem primarily to errors in the η measurements,^(1,4) it seemed appropriate to reexamine the systematics of the experiments. The investigation has the following three principal lines of inquiry.

1. The data from source strength measurements in the MTR manganese bath of a ^{252}Cf source, previously calibrated in the ANL bath, were carefully examined. The purpose was to look for any evidence that the MTR bath had an intrinsically greater sensitivity to neutrons, real or spurious, which might explain the difference between the η and $\bar{\nu}$ results. No indication of such a systematic difference was found.

2. Careful consideration was given to the recommendations of DeVolpi⁽¹⁾ for modifying the MTR η values for the fissile nuclei using revisions of three manganese bath corrections. Some justification was found for using a slightly modified value for the combined effects

[†]This is a summary of a paper presented at the Conference on Nuclear Cross Sections and Technology, Washington, D. C., March 3-7, 1975.

of the correction for leakage and high energy parasitic absorption. However, the suggested change in the correction for manganese resonance absorption was due to an erroneous interpretation for this correction as applied to the η measurements. DeVolpi's intended modification would produce a rise in η of 0.2% when correctly applied, just balancing the effects of changes in the other two corrections. Thus, DeVolpi's corrected recommendations would result in no net change in the MTR η values.

3. A detailed comparison was made of the corrections to the MTR η experiments, as originally applied⁽⁷⁾, with those indicated by the Monte Carlo calculation performed by Mitchell and Emert⁽⁹⁾. This calculation agreed very well with the original analysis overall, but there remained the question of whether this agreement was really good throughout the experiment or merely resulted from chance compensation of differences in individual corrections.

As a result of this study, some of the manganese bath corrections to the measurements were given modified values. The changes were mainly small and of fairly random sign. With the revised corrections, the η data were reanalyzed by the reanalysis for the data at 0.0253 eV. The 0.060 eV data have not yet been reanalyzed. Shown in separate columns are the results for the original 0.0253 eV data, the data taken in 1967 when the ^{241}Pu measurements were made, and a composite analysis including both sets of data simultaneously. Since the third set of values comes for a separate least-squares run, it does not necessarily represent averages from the first two columns.

TABLE I
REANALYZED η VALUES

<u>Nucleus</u>	<u>η (1964 data)</u>	<u>η (1967 data)</u>	<u>η (All data)</u>
^{233}U	$2.298 \pm .009$	$2.291 \pm .010$	$2.295 \pm .009$
^{235}U	$2.080 \pm .010$	$2.082 \pm .009$	$2.081 \pm .009$
^{239}Pu	$2.110 \pm .008$	$2.106 \pm .009$	$2.110 \pm .008$
^{241}Pu	not measured	$2.166 \pm .010$	$2.165 \pm .010$

The differences between the revised values and the originally published values are not statistically significant. This study revealed no justification for either lowering the η values or for expanding their errors to allow better agreement with the manganese bath measurements of $\bar{\nu}$ for ^{252}Cf . The discrepancy of 1% remains.

- (1) A. DeVolpi, Discrepancies and Possible Adjustments in the 2200-M/S Fission Parameters, ANL-7830 (1971).
- (2) J. W. Boldeman, Nucl. Sci. Eng. 55 (1974) 188.
- (3) A DeVolpi and K. G. Porges, Phys. Rev. C 1 (1970) 683.
- (4) E. J. Axton, IAEA, Vienna (1974) 261.
- (5) R. L. Macklin et. al. Nucl. Sci. Eng. 8 (1960) 210.
- (6) R. L. Macklin et. al. Nucl. Sci. Eng. 14 (1962) 101.
- (7) J. R. Smith et. al., Measurement of the Absolute Value of Eta for U-233, U-235, and Pu-239 Using Monochromatic Neutrons, IDO-17083 (1966).
- (8) J. R. Smith and S. D. Reeder, Neutron Cross Sections and Technology, NBS Spec. Publ. 299 1 (1968) 590.
- (9) J. A. Mitchell and C. J. Emert, Proc. 3rd Conf. Neutron Cross Sections and Technology, CONF-710301 (Vol. 2) (1971) 605.

MEASUREMENT OF THE RATIO OF THE ABSORPTION CROSS SECTIONS FOR MANGANESE AND HYDROGEN

J. R. Smith, S. D. Reeder
B. M. Coursey*, I. G. Schröder*, V. Spiegel*

The manganese bath technique is perhaps the foremost method presently available for determining absolute yields for neutron sources. The principle of the method is quite simple. Neutrons from the source are completely absorbed in a surrounding solution of Mn SO_4 dissolved in water. The absorbed neutrons induce in the solution an activity of ^{56}Mn proportional to the strength of the source.

There are a number of corrections that must be applied to the ^{56}Mn activity observed before the source strength is deduced. The present study is concerned primarily with just one of these: the fact that not all of the absorbed neutrons produce ^{56}Mn . Even in a saturated solution the fraction absorbed in manganese is less than 60%. In commonly used concentrations, the fraction ranges between 35% and 50% with most of the remainder absorbed in hydrogen. The accuracy with which the fractional absorption in manganese can be determined, therefore, depends upon the accuracy with which the ratio of the absorption cross sections of manganese and hydrogen can be established.

Axton⁽¹⁾ developed the technique of varying the concentration of the manganese bath and extrapolating measurements to zero hydrogen content. From such measurements the source strength can be derived without reference to separately measured cross sections for hydrogen and manganese. However, the hydrogen-to-manganese cross-section ratio can be derived from the concentration-dependent manganese bath activation data. It is determined from the ratio of the slope to the intercept of the linear curve obtained from plotting the reciprocal of the ^{56}Mn activity observed against the hydrogen-to-manganese atomic density numerical ratio of the solution.

DeVolpi⁽²⁾ has also made concentration-dependent measurements, obtaining hydrogen-to-manganese cross-section ratios differing from the Axton data by about 1.4%. This does not necessarily imply a corresponding error in source strength measurements, but it suggests the existence of unresolved problems in the systematics of the measurement. For example, Axton and DeVolpi disagree on the values of some of the manganese bath corrections, which must be applied to linearize the relationship between inverse ^{56}Mn activity and the H/Mn numerical ratio. The principal corrections in question are those for leakage, manganese resonance absorption, and high energy parasitic absorption in oxygen and sulfur. Because of the implications for ^{252}Cf $\bar{\nu}$ measurements by the manganese bath technique, it was thought important to make a concentration-dependence study for a neutron source for which these effects are negligible. Such a source is a neutron beam well below the manganese resonance energies and the thresholds of the $^{16}\text{O}(n,\alpha)^{13}\text{C}$ and $^{32}\text{S}(n,p)^{32}\text{P}$ reactions.

*National Bureau of Standards

At the National Bureau of Standards Reactor an experiment is in progress to determine the hydrogen-to-manganese cross-section ratio in a manganese bath using a low-energy neutron beam and the concentration variation technique. A Bragg beam of approximately 0.02 eV is obtained by reflection of the reactor beam from a crystal of pyrolytic graphite. Neutrons coming from higher order Bragg reflections or from potential scattering in the crystal are suppressed by filters of pyrolytic graphite and quartz crystals. The Bragg beam first passes through a manganese-aluminum monitor foil and then into the bath. The ratio of solution to monitor activity provides a measure of neutron-induced activity independent of reactor fluctuations.

The concentration of the solution is varied over a range from 30 to 530 grams of Mn SO_4 per liter of solution. Because preliminary investigations indicated that the disagreement between Axton and DeVolpi might be traceable to concentration determinations, the concentration is being measured three ways: by evaporation of a sample of solution and weighing of the residual salt, by measuring the density and comparing with a density-vs.-concentration curve, and by titration of a sample of solution with EDTA.

The efficiency of counting ^{56}Mn activity in a solution varies with the concentration. Therefore, counter calibrations are carried out at each concentration. Calibrations are performed by counting in the manganese bath counting system an aliquot of ^{56}Mn sample whose absolute disintegration rate has been determined in the NBS ion chamber.

Measurements have thus far been made at four concentrations. At least that many additional points will be required for a reliable determination of the hydrogen-to-manganese cross-section ratio.

-
- (1) E. J. Axton et al, J. Nucl. Energy Parts A/B 19, (1965) 409.
 - (2) A. DeVolpi and K. G. Porges, Metrologia 5, (1969) 128.

^{94}Nb CROSS SECTION MEASUREMENTS FOR CTR TECHNOLOGY

Y. D. Harker, E. H. Turk, R. L. Heath

The use of Nb metal has been proposed as a material of construction for the Controlled Thermonuclear Reactor. Niobium activation by neutrons produces long-lived ^{94}Nb ($T_{1/2} = 2.0 \times 10^4$ y). This product can then react with neutrons to produce a short lived product ^{95}Nb ($t_{1/2} = 35.1$ d). This last product because of its short half life may present gamma-ray heating problems. To evaluate the magnitude of this effect a measurement of the integral cross section of ^{94}Nb was made in the neutron spectra of the CFRMF. Two samples of Nb metal containing 4% ^{94}Nb (0.1336 mg TOTAL) were sealed in quartz ampoules and irradiated in the CFRMF at the reactor midplane. The length of irradiation was 76.67 hours at a reactor power level of 10 KW. Two gold monitors, one above the samples and one below, were used to monitor the neutron flux.

After irradiation the samples were allowed to cool for 72.8 hours. The induced radioactivity in the combined two samples were measured for 40000 sec counting periods over 500 hours of decay time using a Ge-Li calibrated gamma detector (ND6).

The gamma counting data were analyzed using the Gauss VI program and the IBM 360 computer.

Analysis of the counting data showed the presence of ^{95}Nb but no evidence was found of the production of ^{95m}Nb .

The nuclear decay data used to analyze the ^{94}Nb data for cross section values are presented in Table I.

The ^{94}Nb content of the samples used were measured by the gamma emission rate using a calibrated Ge-Li detector and the nuclear data shown in Table I. The two samples used contained a total of 0.1336 mg ^{94}Nb .

Analysis of the counting data using a nonlinear least squares procedure gave a cross section of 242 millibarns for the reaction $^{94}\text{Nb}(n,\gamma)^{95}\text{Nb}$. For this value fifteen individual measurements were used which spanned a total decay time of 500 hours.

TABLE I
DECAY PARAMETERS

Nuclide	Gamma (keV)	Branching Ratio	T 1/2
^{94}Nb	702.5	100%	$2.0 \times 10^4 \text{ y}$
	871.1	100%	
$^{95\text{m}}\text{Nb}$	234.7	26.4%	86.6 H
^{95}Nb	765.8	99.79%	35.15 d

FISSION PRODUCT REACTION RATES FOR ^{235}U IN NBS THERMAL FACILITY

R. G. Helmer, R. C. Greenwood

Part of the Interlaboratory LMFBR Reaction Rate (ILRR) program involves the determination of the rate of production of fission products from neutron irradiation of fissile materials. For this purpose a high-purity, thin ^{235}U foil (^{235}U -1) was irradiated October 15-16, 1973 in the 12 inch cavity in the thermal column of the NBS reactor. The physical parameters of this foil are given in Table I. Over a period of 3 to 141 days after this irradiation, 14 γ -ray spectra were measured for this foil. The ranges of some of the counting parameters and of the corrections to the measured data are also given in Table I. Two of the 14 spectra gave reaction rates that were low by 2-8% and have been omitted from the results quoted here.

The individual data for ^{103}Ru are given in Table II. This shows a typical level of consistency, $\epsilon^2 = \text{reduced } \chi^2 = 1.76$. In this case, a small discrepancy between the two detectors, ND-5 and OR-5, is indicated since the separate reaction rates differ by $\sim 0.7\%$. The uncertainties shown for the individual values are relative errors (i.e., no branching ratio or efficiency contribution) that do not include any contribution from the foil mass.

Because of interferences from peaks from other isotopes, the following data were rejected: 724-keV line of ^{95}Zr before 30 days decay and 134- and 696-keV lines of ^{144}Ce before 120 days decay. Care must be exercised in the use of the remaining data for these lines since some peak impurity contribution may still be present. The resulting reaction rates are given in Table III. The ϵ^2 values for the average calculations indicate that the sets of reaction rates are reasonably consistent. The three uncertainties (in %) represent the total error (σ_3), the relative error (σ_2) and the relative error excluding the foil mass and external absorber contributions (σ_1). Where more than one γ ray is used, σ_1 is given for each value and σ_2 and σ_3 for the average.

These ^{95}Zr data suggest that a small (0.3%) adjustment in each of the branching ratios would produce much better agreement. This would be legitimate since the errors in these values are 0.5%. The same result is obtained by averaging the two values. Similarly, the spread in the three values for ^{144}Ce may be due in part to errors in the branching ratios.

These results indicate the magnitude of the uncertainties, both relative and absolute, that are involved in reaction rate determinations for fission foils with a moderate activity level. The fact that some results do not meet the ILRR goal of $\pm 5\%$, namely ^{132}Te and $^{144}\text{Ce-Pr}$, is due primarily to the errors in the γ -ray branching ratios.

TABLE I

PARAMETERS OF ^{235}U -1 FOIL AND THE γ -RAY COUNTING

<u>Parameter</u>	<u>Value</u>
foil mass	0.006330 grams
atomic mass	235.044
abundance ^{235}U	0.99336 - isotopic and purity
foil thickness	0.00011 inches
number of spectra	12 - excluding two rejected ones
Ge(Li) detectors	ND5 and OR5
source - detector distances	10, 25 and 35 cm
correction factor	
- random summing	0.942-0.999
- real summing	0.9988-1.0000-1.0008
- γ self absorption	0.9915-0.9999
- external absorber	1.000 except ^{97}Zr at 0.444

TABLE II

CONSISTENCY OF REACTION RATES - ^{103}Ru

Both uncertainties are relative values excluding foil mass contributions.

<u>Decay Time</u> <u>(days)</u>	<u>Reaction Rate</u> <u>(10^{-12} atoms/atom-sec)</u>	<u>Error</u> <u>(%)</u>
17.09	1.271(16)	1.27
23.09	1.287(12)	0.96
41.41	1.301(4)	0.32
44.41	1.286(4)	0.32
83.41	1.294(4)	0.32
85.41	1.297(4)	0.29
135.37	1.285(6)	0.43
136.37	1.304(9)	0.72
141.35	1.301(9)	0.67
Average	1.294(2)	0.18
$\epsilon^2 = 1.76$		

TABLE III

 ^{235}U REACTION RATES FOR NBS THERMAL IRRADIATION

Isotope	Decay Range (days)	No. of Spectra	E_γ (keV)	ϵ^2	Reaction Rate (10^{-12} atom/atom-sec)		Uncertainty (%)		
					Value	Average	σ_1^a	σ_2^b	σ_3^c
^{97}Zr	3.2	1	743	--	2.547 ^d		1.10	3.2 ^e	3.6
^{132}Te	9-15	2	228	0.6	1.804		0.86	1.00	7.0
$^{140}\text{Ba-La}$	9-41	5	1596	1.6	2.664		0.32	0.59	1.6
^{103}Ru	17-141	9	497	1.8	1.294		0.18	0.53	3.8
^{95}Zr	41-141	7	724	1.6	2.787	2.778	0.19	0.52	1.7
	23-141	8	756	1.0	2.771		0.15		
^{137}Cs	44-141	6	661	0.5	2.588		0.47	0.85 ^f	1.8
$^{144}\text{Ce-Pr}$	135-141	3	134	1.7	2.498	2.31 ^g	0.33	5. ^g	7. ^g
	135-141	3	696	1.2	2.272		0.82		
	44-141	6	2185	1.5	2.170		0.94		

^aRelative uncertainty excluding contribution from foil mass (and for ^{97}Zr , the external absorber).

^bRelative uncertainty, with foil mass error taken to be 0.5%.

^cTotal uncertainty.

^dNo ILRR evaluated decay scheme parameters are available for this nuclide.

^eIncludes 3% uncertainty in external absorption correction.

^fIncludes a contribution of 0.5% for the subtraction of the ^{137}Cs observed in the room background.

^gUnweighted average and arbitrary assignment for σ_2 and σ_3 .

GAMMA SCAN OF PBF FUEL ROD STACKS

J. W. Mandler

Gamma-ray scans of PBF fuel stacks #2341 and #2838 were made using a Ge(Li) detector at the TRA hot cell facility. The Ge(Li) detector viewed the fuel rod through the same slit collimator used by the NaI(Tl) scan system. Gamma-ray spectra were obtained from positions located 3, 9, 14.3, 15, 21, 27, 30 and 33 inches from the top of the fuel rod stack #2838 and from positions located 21 and 30 inches from the top of fuel rod stack #2341. Count times were varied from 600 seconds (when looking at the hotter regions of stack #2838) to 4000 seconds (when looking at stack #2341) so that the counting statistics would be comparable for all the runs. The Ge(Li) detector was removed while each fuel rod was positioned in the drive mechanism and then replaced at the same position in the collimator. Reproducibility of the rod to detector distance is estimated to be about ± 0.5 mm.

Background gamma-ray spectra were obtained both with no fuel rod stack in the drive mechanism and with stack #2838 positioned so that the detector was viewing a position 37.25 inches from the top of the stack (a region containing no fuel since the fuel rod stacks have a length of 36 inches). These spectra exhibited identical structure. Intense peaks due to ^{134}Cs , ^{137}Cs and ^{60}Co were prominent features in both. The intensity of the ^{137}Cs source in the background made it impossible for us to measure the ^{137}Cs in the fuel rod stacks.

Examination of the spectra obtained from the various locations on the fuel rod stacks indicated that they all exhibit the same shape but varying intensities. The differences in intensities are due to both source strength and count times. Lines due to the fission products ^{103}Ru , ^{95}Zr - ^{95}Nb , and ^{140}Ba - ^{140}La together with the background lines from ^{134}Cs , ^{137}Cs and ^{60}Co comprise the strongest elements in the structure of the spectra.

Tables I and II contain the measured gamma-ray intensities for several selected fission products (i.e., ^{95}Zr , ^{95}Nb , ^{103}Ru , ^{140}La). These gamma-ray intensities have all been decay corrected to a single time (i.e., 1400 on 4/2/75). Plots of the individual gamma-ray intensities for each isotope as a function of position on fuel rod stack #2838 were made and examined. The general shapes of the curves were the same and no gross deviations from the general shape were apparent. Table III contains the relative gamma-ray intensities obtained from the various positions on fuel rod stack #2838. The intensities for each gamma-ray were normalized to that obtained from the position located 21 inches from the top of the stack (i.e., the position which yielded the highest intensity).

The ratio of the gamma-ray intensities of ^{95}Zr and ^{103}Ru relative to ^{140}La were obtained and examined for the various positions investigated on fuel rod stack #2838. The $^{103}\text{Ru}:^{140}\text{La}$ and $^{95}\text{Zr}:^{140}\text{La}$ ratios were found to be constant (to within the experimental uncertainties) with position. The ratios for the position located 14.3 inches from the top

of the stack did not exhibit any abnormalities even though a void exists at this location.

TABLE I

MEASURED GAMMA-RAY INTENSITIES FROM FUEL ROD STACK #2838

Gamma Ray	Gamma Intensity (cps) from position (distance from top of stack)							
	3"	9"	14.3"	15"	21"	27"	30"	33"
487 keV ^{140}La	3.23±.05	6.10±.09	8.60±.10	8.22±.15	9.68±.24	7.95±.12	7.57±.17	4.75±.08
497 keV ^{103}Ru	1.93±.07	3.61±.11	5.15±.10	5.36±.14	5.93±.12	4.67±.17	4.65±.07	2.94±.06
724 keV ^{95}Zr	1.29±.05	2.51±.05	3.80±.20	3.52±.20	3.89±.13	3.34±.08	2.99±.11	2.04±.05
756 keV ^{95}Zr	1.54±.04	2.86±.11	4.32±.08	3.87±.11	4.62±.11	3.86±.08	3.59±.08	2.36±.05
765 keV ^{95}Nb	1.12±.03	2.16±.05	3.45±.06	2.88±.08	3.22±.08	2.89±.07	2.79±.04	1.68±.05
1596 keV ^{140}La	3.94±.09	7.70±.19	10.70±.30	10.64±.23	12.02±.27	10.20±.14	9.69±.27	6.22±.13
Sum 724+756 keV ^{95}Zr	2.83±.06	5.37±.12	8.12±.22	7.39±.23	8.51±.17	7.20±.11	6.58±.14	4.40±.07

TABLE II

MEASURED GAMMA-RAY INTENSITIES FROM FUEL ROD STACK #2341

Gamma Ray	Gamma Intensity (cps) from Position (distance from top of stack)	
	21"	30"
487 keV ^{140}La	$3.00 \pm .06$	$2.33 \pm .08$
497 keV ^{103}Ru	$1.90 \pm .03$	$1.42 \pm .03$
724 keV ^{95}Zr	$1.33 \pm .03$	$0.96 \pm .05$
756 keV ^{95}Zr	$1.52 \pm .04$	$1.12 \pm .04$
765 keV ^{95}Nb	$1.21 \pm .03$	$0.87 \pm .03$
1596 keV ^{140}La	$3.92 \pm .07$	$2.79 \pm .06$
Sum 724+756 keV ^{95}Zr	$2.85 \pm .05$	$2.08 \pm .06$

TABLE III

RELATIVE GAMMA-RAY INTENSITIES FROM FUEL ROD STACK #2838

Gamma Ray	Relative Intensity from Position (distance from top of stack)							
	3"	9"	14.3"	15"	21"	27"	30"	33"
487 keV ^{140}La	0.334±.013	0.630±.025	0.888±.032	0.849±.037	1.0	0.821±.033	0.782±.037	0.491±.021
497 keV ^{103}Ru	0.325±.018	0.609±.031	0.868±.034	0.904±.042	1.0	0.788±.044	0.784±.028	0.496±.020
724 keV ^{95}Zr	0.332±.024	0.645±.034	0.977±.084	0.905±.081	1.0	0.859±.049	0.769±.054	0.524±.030
756 keV ^{95}Zr	0.333±.017	0.619±.039	0.935±.040	0.838±.044	1.0	0.835±.037	0.777±.036	0.511±.023
765 keV ^{95}Nb	0.348±.013	0.671±.032	1.071±.045	0.894±.047	1.0	0.898±.044	0.866±.034	0.522±.029
1596 keV ^{140}La	0.328±.015	0.641±.031	0.890±.045	0.885±.040	1.0	0.849±.031	0.806±.041	0.517±.023
Sum 724+756 keV ^{95}Zr	0.333±.014	0.631±.027	0.954±.045	0.868±.044	1.0	0.846±.030	0.773±.032	0.517±.019

INTERCOMPARISON OF GAMMA ANALYSIS OF PBF FUEL SAMPLES

J. W. Mandler

Comparisons of the results of earlier burnup analyses of PBF fuel samples from the FOM tests indicated a constant systematic difference between the values obtained by the Chemical Processing Plant and the Nuclear Technology Division. Since the two facilities analyzed adjacent fuel pellets which came from regions of uniform flux, their results were expected to agree. In an effort to determine the reason for the discrepancy, a fuel sample was sent to us for analysis so that the two techniques could be compared using the same sample.

The fuel sample used for the intercomparison measurements was made by crushing a PBF fuel rod pellet, mixing the powder, and then forming it into a 3/4-inch-diameter disk. It weighed 0.02455 gram and had a uranium content of 0.271955 gm U/gm material. Irradiation was performed on October 25, 1974.

We counted this sample four times with a source-detector distance of 25 cm. Two spectra were obtained on each of two Ge(Li) detectors. The agreement between the measurements was good. For the average of the four measurements, we obtained the following results:

isotope	^{103}Ru	^{95}Zr
gamma energy (keV)	497	724
gamma/sec at 1318 on March 3, 1975	74,010	117,320
fissions in sample	1.265×10^{14}	1.285×10^{14}
fission/gm U	1.895×10^{16}	1.925×10^{16}

These values do not include the small corrections for random summing (about 1% effect), decay during counting time, decay during irradiation, and gamma absorption in the sample. All of these corrections are small and would increase the values of the results. Also the ^{95}Zr value includes the small amount produced from activation of ^{94}Zr in the cold fuel.

Table I gives the average gamma-ray intensities and disintegration rates obtained from our four measurements. The fuel sample was also sent to the RML for analysis. These results are given in Table II. In order to facilitate a comparison with the results from the Chemical Processing Plant, we used the same branching ratios as did the Chemical Processing Plant. Comparison of our results with those obtained by the Chemical Plant indicated agreement within 3%. The most meaningful comparison was for the gamma/sec values, since they do not involve the different branching ratios and fission yields used in obtaining the other results. We, therefore, conclude that the discrepancy between our burnup results and those of the Chemical Processing Plant are not due to differences in gamma-ray analysis techniques.

TABLE I
AVERAGE RESULTS OF OUR FOUR MEASUREMENTS

E_{γ} (keV)	Isotope	Gammas per second at 1318 on 3/3/75	Disintegrations per second at 1318 on 3/3/75
133	^{144}Ce	1.64×10^4	1.51×10^5
145	^{141}Ce	5.73×10^4	1.16×10^5
497	^{103}Ru	7.40×10^4	8.39×10^4
661	^{137}Cs	4.81×10^3	5.61×10^3
724	^{95}Zr	1.17×10^5	2.66×10^5
1596	^{140}La	5.20×10^3	5.39×10^3

TABLE II
RESULTS OF RML MEASUREMENT

E_{γ} (keV)	Isotope	Gammas per second at 1318 on 3/3/75	Disintegration per second at 1318 on 3/3/75
133	^{144}Ce	1.52×10^4	1.40×10^5
145	^{141}Ce	5.51×10^4	1.12×10^5
497	^{103}Ru	7.36×10^4	8.35×10^4
661	^{137}Cs	4.85×10^3	5.66×10^3
724	^{95}Zr	1.165×10^5	2.64×10^5
1596	^{140}La	5.04×10^3	5.22×10^3

EXPERIMENTAL RESULTS OF NON-DESTRUCTIVE ANALYSIS MEASUREMENTS OF LWBR RODS IN THE ARMF

I. E. Stepan, D. H. Suckling, C. R. Suter

Rods similar to those that are to be loaded in the Shipping Port Reactor for the Light Water Breeder Reactor test have been measured in the ARMF. The purpose of the test was to determine if the reactivity method is sensitive enough to measure the fissile material that will be in the pins at the end of the experiment.

A series of rods containing varying amounts of ^{233}U in thorium were measured in the reactor using the sample withdrawal technique⁽¹⁾. A filter containing natural boron carbide was used. The purpose of the filter was to minimize the effect of the thorium thus leaving the fissile material as the major contributing factor for the reactivity change. It also eliminated all self-shielding. The filter and configuration of the core used is shown in Figure 1.

The pins had a total length of 105 inches and weighed approximately 3400 grams. The ^{233}U content varied between 16 and 55 grams. The ARMF facility had to be modified to accommodate the long pins. The results of the experiment are shown in Figure 2.

The stability of the ARMF core was also tested to determine if there would be any drift over long time intervals. A sample similar to those used in the experiment but heavily loaded with ^{235}U was measured several times over an extended period of time. The worth of the sample was $108.93 \pm .48$ when measured six times in one day. The worth of the same sample measured 29 times over a period of three months was $108.79 \pm .42$ indicating no drift within the accuracy of the measurements.

Poison worth data of stable nuclides was also obtained. The materials measured were chosen to bracket the expected worth of the fission products. Materials measured included cerium, lanthanum, yttrium, barium, neodymium, praseodymium, cesium iodide, zirconium and molybdenum. The net reactivity worth of these materials was small when compared to the worth of ^{233}U .

(1) I. E. Stepan, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1974, ANCR-1177 (1975) 141-152.

Figure 1. ARMF core.

Figure 2. Reactivity worth of LWBR calibration rods.

Model and Code Development

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

HYBRID SIMULATION OF A LOSS OF COOLANT ACCIDENT IN A PRESSURIZED WATER REACTOR

F. K. Hyer

A hybrid computer program is being developed which will simulate small-break blowdown accidents and which will run in a 1:1 time scale or better. This program will have additional utility in the analysis of larger breaks, anticipated transients without scram (ATWS), and secondary blowdown accidents. Cost analysis has shown that a hybrid computer will enable small-break blowdown accident analyses to be performed at reasonable cost. Existing, all-digital computer codes incur prohibitive costs for this analysis because of very slow running times.

A schematic diagram of the reactor plant system for analysis of small breaks is given in Figure 1. The significant features of this model are:

1. The U-tube configuration of the flow loop is represented to obtain analysis of phase separation.
2. Predominant structural features are represented to facilitate the evaluation of heat transfer to structure.
3. Detail of the model in the active core region is adequate to account for axial distribution of power.
4. Primary pump torque and head characteristics are represented explicitly from the applicable four-quadrant curves.
5. Energy balances and heat transfer calculations are performed in the digital processor to accommodate the logic necessary for selection of heat transfer modes according to correlations for subcooled, nucleate, and film boiling regimes.
6. The dynamics of single or two-phase flow is programmed on the analog consoles to represent the characteristics of "stiff" systems.

The model equations for the fluid are derived from the partial differential equations of conservation by approximating the spatial derivatives with discrete values of the fluid variables for each control volume.

The consideration of slip velocity is superimposed upon the homogeneous model to affect the enthalpy of the flows at a given fluid volume but not the net magnitude or direction of mass flow. Therefore, only the energy equations are affected by slip velocity.

The fluid energy equation is solved by the digital processor with time advancement accomplished by the explicit one-step method. This method places an upper limit on the cycle time of the digital program and determines the time scale of the analog solutions. A 1:1 time scale for analog solution is anticipated, and faster time scaling will be investigated.

The momentum, mass balance, and state equations are implemented on the analog console. This method converts the solution of the state equation from a digital iterative process to a continuous algebraic operation accomplished with the capabilities of high-gain operational amplifiers. The solution of the equation is instantaneous but the overall computer program is limited in solution time by the cycle time of the digital processor program.

The heat transferred internally in the fuel pins is modeled by the diffusion equations in one radial dimension normal to the clad surface. The equations are programmed with analog integrators in the conventional manner. This approach limits the detail of the model to the number of analog integrators devoted to this portion of the model. This limitation is imposed to reduce developmental time. Hybrid techniques are available to solve the partial differential equations of diffusion in continuous space and could be implemented with additional developmental effort.

The hydraulic torque and head of the primary pump are obtained from the four-quadrant curves as a function of pump speed and volumetric flow. The moment of inertia of the fly wheel is reflected to pump shaft speed. Two-phase degradation factors are applied to the pump characteristics.

The steam generator secondary is programmed in the same manner as a primary fluid region. Steam flow is computed from the characteristics of the main steam control valve. Feed flow magnitude and enthalpy is provided as input to the program. A boiling heat transfer coefficient is used on the shell side of the tubes.

The pressurizer is also programmed as another fluid region. The surge flow, spray flow, and heater power drive the pressurizer response.

The accumulator provides a mass flow and boron reactivity to the primary fluid.

A schematic of the program functions is shown in Figure 2. An energy balance, a momentum balance, and a mass balance are computed for each of the eleven primary fluid regions.

The running time of the program is dependent upon the update time of the digital algorithms for solution of the energy balances.

This program is presently in development and will be operational in the last quarter of calendar year 1975.

Figure 1 Schematic of plant system as subdivided for analysis.

Figure 2. Program schematic.

VALIDATION OF KENO CODE FOR HTGR CRITICALITY
SAFETY CALCULATIONS

T. Watanabe

In order to establish the validity and area of applicability of the KENO code⁽¹⁾ for criticality calculations on the HTGR fuel reprocessing primary burner, it was necessary to validate the code. Because the KENO code is based on Monte Carlo technique, geometric approximations are minor and the validation work was mainly to determine the adequacy of the cross-section data used with the KENO code.

As others⁽²⁾ have shown that the uranium cross-section set in the Hansen & Roach⁽³⁾ library to be adequate for criticality calculations with the KENO code, the present validation work was to test the thorium cross-section set in the Hansen & Roach library.

To validate the thorium cross-section set and the KENO code, seven critical experiments were used as benchmarks. The critical experiments all contained uranium and thorium and had hydrogen (in the form of H₂O or polyethylene) as moderator. The average of the calculated k_{eff} 's (Table I) was determined to be $1.022 \pm .008$. The hydrogen to uranium-235 ratio (H/X) ranged from 27 to 160. Since the calculated k_{eff} were all in excess of unity, the expected calculational bias of uranium-thorium system is expected to be on the conservative side.

-
- (1) G. E. Whitesides and N. F. Cross, KENO - A Multigroup Monte Carlo Criticality Program, CTC-5, (September 10, 1969)
 - (2) G. R. Handley and C. M. Hopper, Validation of the KENO Code for Nuclear Criticality Safety Calculations of Moderated, Low Enriched Uranium System, Y-1948 (1974).
 - (3) G. E. Hansen and W. H. Roach, Six and Sixteen-Group Cross Sections for Fast and Intermediate Critical Assemblies, LAMS-2543, (November 1961).
 - (4) M. L. Batch and N. L. Snidow, Consolidated Edison Thorium Reactor Critical Experiments with Oxide Fuel Pins, BAW-119, Rev. 1, (July 1960).
 - (5) L. A. Montford and E. H. A. Morewitz, Nuclear Science & Engineering 21, 421 (1965).
 - (6) G. G. Smith, et. al., Annular Seed-Blanket Reactor Critical Experiments, WAPD-TM-621, (February 1967).
 - (7) S. Milani and S. H. Weiss, Small Uranium-233 Fueled Seed-and-Blanket Critical Experiments, WAPD-TM-614, (November 1967).

TABLE I

CALCULATED k_{eff} OF URANIUM THORIUM CRITICAL EXPERIMENTS

Name	Experiment	$k_{\text{eff}} \pm \sigma$	Generations	Reference
CETR	7A 4771 pins H/X = 74 Sq. Pitch	.99902 $\pm$.00697	31	4
CETR	9B 1941 pins H/X = 160 Sq. Pitch	1.0008 $\pm$.0044	31	4
AETR	Core 1 Test Regions: U235 Homogeneous	1.0358 $\pm$.0061	43	5
AETR	Core 2 Test Region: U233 & Th232 Homogeneous	1.0335 $\pm$.0071	50	5
AETR	Core 3 Test Region: U235 & Th232 Homogeneous	1.0507 $\pm$.008	50	5
WAPD Annular Seed Blanket	One Module 816 Pins H/X = 27 H/Th = 3.3 Triangular Pitch	1.010 $\pm$.011	21	6
WAPD Small Uranium 233 Fueled Seed and Blanket	SBI U235Th 576 Seed pin H/X = 37 H/Th = 4.4 Sq. Pitch	1.022 $\pm$.0136	25	7

THERMAL DATA TESTING OF ENDF/B VERSION IV DATA

F. J. Wheeler

The Cross Sections Evaluation Working Group (CSEWG) was formed to provide direction toward establishment of an Evaluated Nuclear Data File (ENDF) comprising data for all isotopes important to the nuclear industry. The group is coordinated through BNL and participants include members from all the national laboratories and major commercial facilities. One part of the ENDF system, referred to as ENDF/B, consists of evaluated nuclear data to be used for reactor design calculations. Aerojet Nuclear Company contributes to this data file through experimental effort, evaluation, data testing and participation in the CSEWG organizational activities. This summary briefly describes ANC's recent activities in the area of thermal data testing of ENDF/B Version IV data.

Data testing is beneficial to both the participant and to the national effort and serves the following purposes:

1. Provides comparison with measured values and therefore a test of the applicability of the ENDF/B data and feedback for future versions of the file.
2. Provides for checkout of the methods and codes used for reactor application.
3. Allows for a detailed comparison of the results obtained by each participant and therefore, an assessment of the effects on the computational results of the use of alternate methods and codes.

ENDF/B data, as received from BNL, cannot be used directly for reactor calculations in most instances. The data must first be processed into multigroup library files. At ANC this processing was performed by the ETOP⁽¹⁾ code, for the fast energy range, and by the FLANGE II⁽²⁾ code in the thermal energy range. The FLANGE II code required only simple coding modifications for implementation of Version IV processing. The ETOP code, however, was extensively modified by Nuclear Technology personnel to incorporate the changes in format and data approximation selected for Version IV data and to improve the numerical algorithms employed in the code. The processed multigroup files, after appropriate resonance self-shielding, spatial and energy coalescing are used in reactor calculations to obtain calculated values of neutron multiplication, flux distributions, reaction rates, kinetics parameters, etc., required for design and analysis.

Thermal-reactor benchmarks selected for analysis, using Version IV data, were the ORNL uranium spheres, the PNL plutonium spheres and the TRX uranium-metal lattices. The calculated neutron multiplication factors for the critical assemblies are listed in Table 1. The results indicate a slight improvement, in the comparison with experiment for these lattices, over Version III data. Results for the ORNL spheres (highly-enriched, hydrogenous uranium systems) are very good indicating that thermal data for U-235, B-10 and the slowing-down and thermalization in H₂O is well-represented by Version IV data. The thermal

data for Pu-239 and Pu-240 is more in question as is evidenced by the relatively high overestimation of k_{eff} for these well-moderated spheres.

The TRX lattices are comprised of aluminum-clad, 48-inch-high uranium-metal fuel rods having a U-235 enrichment of approximately 1.3%. The lattices are H₂O moderated and reflected. A comparison with experiment points out the discrepancy between measured differential U-238 data and results obtained using this data in reactor application. Apparently the epithermal capture in U-238 is being overestimated in the calculations and results in low predicted values of neutron multiplication. The errors, reported in the literature, for U-238 data do not allow for adjustment of the capture cross section such that good comparison with experiments is achieved. A re-evaluation of the differential measurements and detailed comparisons of the methods and codes used for reactor application is presently underway and hopefully this discrepancy will be non-existent for Version V data.

-
- (1) G. L. Singer, Internal Report.
 - (2) H. C. Honeck and D. R. Finch, FLANGE-II (Version 71-1), A Code to Process Thermal Neutron Data from an ENDF/B Tape, DP-1278 (October 1971).

TABLE 1

Calculated Values of Neutron Multiplication (k_{eff}), for Selected Thermal Reactor Benchmarks, Using ENDF/B Version IV Data

Experiment	k_{eff}	
	meas.	calc.
ORNL-1	1.00026	1.0025
ORNL-2	.99975	1.0018
ORNL-3	.99994	.9984
ORNL-4	.99924	.9998
ORNL-10	1.00031	.9988
PNL-1	1.0	1.0232
PNL-2	1.0	1.0196
PNL-3	1.0	1.0028
PNL-4	1.0	1.0105
PNL-5	1.0	1.0160
TRX-1	1.0	.9827
TRX-2	1.0	.9893

THE ETOP-14 CODE FOR THE GENERATION OF
VERSION IV ENDF/B MULTIGROUP CROSS-SECTION LIBRARIES FOR PHROG II

R. A. Grimesey, D. A. Millsap

The ETOP-14 code has evolved after many years from the original ETOG(1) code which was developed to process ENDF/B data to the MUFT, GAM, and ANISN library formats. With the evaluation of the PHROG II(2) fast spectrum code to adapt to the many format changes in ENDF/B data over the years, ETOP-13 had undergone many modifications in order to digest ENDF/B Version III data. Version IV of ENDF/B required many additional modifications in order to process the angular distributions accompanying the discrete level inelastic scattering data and the additional formats present in Version IV for tabulated secondary energy distributions for neutrons scattered from the continuum region.

All versions of ETOP prior to ETOP-14 treated discrete level inelastic scattering as isotropic in LAB coordinates without recoil of the target nucleus. In principle, the original ETOG subroutines for the calculation of elastic scattering matrices could have been modified to treat level inelastic scattering, but this modification would have resulted in a very inefficient algorithm for inelastic scattering.

The principal difficulty in treating inelastic (or n-2n) scattering with the ETOP code was that the original algorithms in ETOG were written to treat elastic scattering angular distributions as Legendre distributions in the center of mass only. Thus, Equation (1) is the basis for the numerical computation of the elastic matrices in the ETOP subroutines TRAN, GRID, DINT, SINT along with the logic for the six two-dimensional domains of integration possible with elastic scattering.

$$\sigma^{\ell}(E_0 \rightarrow E) = (2\ell+1) \frac{\gamma(A+1)^2}{4E_0} \sigma_S(E_0) P_{\ell}[\mu_0(E_0 \rightarrow E)]$$

$$\text{times} \sum_{\ell'=0}^{N_{\ell}'} (2\ell'+1) f_{\ell'}(E_0) P_{\ell'}(\mu) \quad (1)$$

$$\text{where (3)} \quad \gamma = \frac{1}{A \sqrt{1 + \frac{A+1}{A} \frac{Q}{E_0}}}, \quad = \frac{1}{A} \text{ elastic} \quad (2)$$

E_0 is the energy of the incident neutron

$f_{\ell'}$ = CM Legendre expansion coefficients for normalized angular distribution

$\ell' =$ CM Legendre order index

$\ell =$ LAB Legendre order index

$Q =$ Exoergic energy for the reaction

In addition to Equation (1), a LAB to CM transformation matrix was required to transform the Legendre coefficients from LAB to CM coordinates for the general case.

This is Equation (3) with $Q = 0$ for elastic scattering.

$$T = \begin{pmatrix} 1 & 0 & 0 & 0 & 0 & 0 & 0 & \dots \\ 2\gamma & 1 - \frac{3}{5}\gamma^2 & -\frac{2}{5}\gamma & \frac{9}{35}\gamma^2 & 0 & 0 & 0 & \dots \\ \gamma^2 & 2\gamma & 1 - \frac{11}{7}\gamma^2 & -\frac{6}{7}\gamma & \frac{16}{21}\gamma^2 & 0 & 0 & \dots \\ 0 & \frac{8}{5}\gamma^2 & \frac{12}{5}\gamma & 1 - \frac{46}{15}\gamma^2 & -\frac{4}{3}\gamma & \frac{50}{33}\gamma^2 & 0 & \dots \\ 0 & 0 & \frac{18}{7}\gamma^2 & \frac{20}{7}\gamma & 1 - \frac{390}{77}\gamma^2 & -\frac{20}{11}\gamma & \frac{360}{143}\gamma^2 & \dots \\ 0 & 0 & 0 & \frac{80}{21}\gamma^2 & \frac{30}{9}\gamma & 1 - \frac{295}{39}\gamma^2 & -\frac{30}{13}\gamma & \dots \\ 0 & 0 & 0 & 0 & \frac{2275}{429}\gamma^2 & \frac{42}{11}\gamma & 1 - \frac{581}{55}\gamma^2 & \dots \\ \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \vdots & \ddots \end{pmatrix} \quad (3)$$

The above matrix is a good approximation for $\gamma < 0.5$.

For the elastic scattering case γ reduces to $1/A$ and Equation (3) is energy independent. This is a great simplification for elastic scattering and the transformation matrix is given at the head of the angular distributions in file 4 of ENDF/B.

For the general case of non-elastic scattering, no transformation matrix is given since γ varies with each Q Level value and is energy dependent for each incident energy of the neutron. Thus, Equation (3) would have to be constructed and applied at each incident energy of the neutron if the ENDF/B angular data for non-elastic scattering happened to be given in LAB coordinates, the usual case for non-elastic scattering. The construction and application of Equation (3) would be quite time consuming since upwards to 100 energy points are required for the integration mesh for a single PHROG group using Equation (1).

This in itself is bad enough if the angular data is given as Legendre coefficients in LAB coordinates in ENDF/B file 4. If the angular distributions are given as tabular pointwise data in $\cos(\mu_0)$ space, then it would have to be first fit to Legendre expansion coefficients before Equation (3) could be applied. This second process of least-square fitting of a set of 20 Legendre expansion coefficients to a tabular distribution is even more time consuming than the application of Equation (3) to obtain the coefficients necessary for use in Equation (1). In ETOP, a subroutine LEGEND is called to obtain Legendre expansion coefficients f_ℓ from a given tabular distribution. For elastic scattering, the angular distributions in file 4 are almost always given as Legendre coefficients in CM coordinates. However, for non-elastic scattering the data is most generally given as tabular distributions in LAB coordinates.

In addition to the above considerations, upwards to 40 individual inelastic levels may be specified for a single material in ENDF/B where only one elastic scattering calculation is required and logic for 14 domains of integration are required whereas only 6 domains of integration are possible for elastic scattering.

Using the algorithm in ETOP-13 resulting from Equation (1) for non-elastic scattering would then result in a very time consuming calculation for non-elastic matrices.

In view of the above considerations, we decided to develop a simpler algorithm for treating the non-elastic scattering matrices. Central to this algorithm would be avoidance of the necessity to manufacture the transformation matrix, Equation (3), and the necessity to manufacture Legendre coefficients from tabular distribution.

DIRECT ANGULAR OVERLAY ALGORITHM

Equation (1) was obtained by the transformation of dependent variables to the CM coordinate system. This equation is

$$P(E_0, \mu) d\mu = P(E_0, \mu_0) d\mu_0 \quad (4)$$

where

$P(E_0, \mu) d\mu$ is the differential probability of scattering through an angle into $d\mu$ from E_0 .

μ = cosine of CM scattering angle.

μ_0 = Corresponding cosine of LAB scattering angle.

From Equation (4) the transformation from CM to LAB coordinates was obtained as:

$$P(E_0, \mu_0)_{\text{LAB}} = P(E_0, \mu)_{\text{CM}} \left| \frac{d\mu}{d\mu_0} \right| \quad (5)$$

$$\text{where (4)} \quad \left| \frac{d\mu}{d\mu_0} \right| = \frac{(1 + \gamma^2 + 2\gamma\mu)^{\frac{3}{2}}}{|1 + \gamma\mu|} \quad (6)$$

and $P(E_0, \mu_0)$ is the corresponding normalized angular distribution in LAB coordinates. Equation (1) results directly from the transformation Equation (5) and a similar transformation from $d\mu$ to dE so the integrals from Equation (1) can be performed in energy space.

Examining Equation (1), it is seen that the outscatter integrals may be calculated in either μ or μ_0 space. Equation (1) can be applied directly in either CM or LAB coordinates depending on how the angular data is represented in file 4 of ENDF/B. Therefore, no angular data transformations are required. In addition to this, it is not required to manufacture Legendre expansion coefficients if tabular distributions are given in file 4.

1. CM

A Tabular, $P(E_0, \mu)$ given in file 4

$$B \text{ Legendre, } P(E_0, \mu) = \sum_{\ell'}^{NL'} \frac{2\ell'+1}{2} f_{\ell'} P_{\ell'}(\mu) \quad (7)$$

2. LAB

A Tabular, $P(E_0, \mu_0)$ given in file 4

$$B \text{ Legendre, } P(E_0, \mu_0) = \sum_{\ell}^{NL} \frac{2\ell+1}{2} f_{\ell} P_{\ell}(\mu_0) \quad (8)$$

Thus, $P(E_0, \text{Beta})$ can be constructed directly on a Beta integration mesh in a single pass depending on how the data is represented in File 4. The Beta integral for the scattering matrix is then performed directly on the same Beta mesh regardless of whether Beta is the CM or LAB cosine. The Beta integral is always performed between the limits $\text{Beta} = +1.0 \rightarrow -1.0$. The above is true regardless of whether we are treating elastic or non-elastic scattering. The absolute energies corresponding to $\text{Beta} = \pm 1.0$ are independent of which coordinate system the integral is performed in.

$$\text{for } \beta = +1.0, \text{ EMAX} = \frac{E_0}{(A+1)^2} \left(\frac{\gamma+1}{\gamma} \right)^2 \quad (9)$$

$$\text{for } \beta = -1.0, \text{EMIN} = \frac{E_0}{(A+1)^2} \left(\frac{\gamma-1}{\gamma} \right)^2 \quad (10)$$

μ_0 and the energy group boundaries which fall between EMAX and EMIN, of course, depend on which coordinate system Beta represents if Beta is always represented on the same mesh over JMUPTS. The downscatter energy group boundaries may be located on the Beta mesh with the following equations for two cases.

1. Beta $\rightarrow$ CM

EK = energy of Kth group boundary

$$\text{Beta } K = \frac{\gamma}{2} \left[\frac{EK}{E_0} (A+1)^2 - \left(1 + \frac{1}{\gamma^2} \right) \right] \quad (11)$$

2. Beta $\rightarrow$ LAB

$$(\mu K)_{\text{CM}} = \frac{\gamma}{2} \left[\frac{EK}{E_0} (A+1)^2 - \left(1 + \frac{1}{\gamma^2} \right) \right] \quad (12)$$

$$\text{Beta } K = \frac{\mu K + \gamma}{\sqrt{1 + \gamma^2 + 2\gamma\mu K}} \quad (13)$$

Equation (13) was obtained by integrating Equation (6). Equation (6) is not easily derived, however, once obtained, it is easily integrated to obtain Equation (13). Equation (13) is the transformation equation to obtain LAB scattering angles from the corresponding scattering angle in CM coordinates. For $Q=0$, Equation (13) reduces to the familiar transformation equation for elastic scattering.

$$\mu_0 = \frac{A\mu + 1}{\sqrt{1 + 2A\mu + A^2}} \quad (14)$$

Equations (11) and (13) locate the downscatter energy group boundaries EK on the Beta integration mesh. An integral of Equation (4) will now give the fractional probability for scattering into each group falling between Beta = +1.0 and -1.0. If Equation (4) is normalized to the ℓ th Legendre moment of the scattering cross section, we have,

$$\phi(E_0) \sigma^\ell(E_0 \rightarrow E) = (2\ell+1) \phi(E_0) \sigma(E_0) P_\ell(\mu_0) P(E_0, \text{Beta}) d\text{Beta} \quad (15)$$

where (E_0) is the elastic or non-elastic scattering cross section and $\phi(E_0)$ is the incident neutron weighting flux.

If Equation (15) is integrated over all exit scattering angles Beta, and all incident energies E_0 for a single Phrog group, one column of the scattering matrix results

$$\sigma_{ij}^{\ell} = \frac{(2\ell+1) \int_{E_i}^{E_i+1} \phi(E_0) \sigma(E_0) dE_0 \int_{\text{Beta}(j)}^{\text{Beta}(j+1)} P_{\ell}(\mu_0) P(E_0, \text{Beta}) d\text{Beta}}{\int_{E_i}^{E_i+1} \phi(E_0) dE_0} \quad (16)$$

If a uniform integration mesh for Beta is defined for JMUPTS on Beta and for IEPNTS on E_0 , Equation (16) can be obtained from a simple trapezoidal integral

$$\sigma_{ij}^{\ell} = \frac{(2\ell+1) \sum_{\text{IEPNTS}} \Delta(E_i) \phi(E_i) \sigma(E_i) \sum_{j=\text{JMIN}}^{j=\text{JMAX}} P(\mu_{0j}) P[E_i, \text{Beta}(j)] \Delta \text{Beta}_j}{\sum_{\text{IEPNTS}} \phi(E_i) \Delta E_i} \quad (17)$$

The new algorithm is now complete and ready to be reduced to subroutines.

1. The first sum in Equation (17) is the outer integral over the energy mesh for incident neutrons E_0 . This outer integral defines the S.R. OUTER.
2. The second sum in Equation (17) is the inner integral over the Beta mesh for each incident neutron energy E_i . It produces a contribution to the outscatter groups falling between the limits $\text{Beta} = +1.0$ to -1.0 for each incident energy point E_i on the outer integral integration mesh. The inner integral in Equation (17) is performed in S.R. INNER for each incident neutron energy on the integration mesh.

The use of Equation (1) for the calculation of non-elastic scattering matrices would require 14 domains of integration for the two dimensional integrals encountered for each non-elastic level as opposed to 6 domains of integration for the simpler case of elastic scattering. With the Direct Angular Overlay Algorithm, the domains of integration are automatically mapped as the incident neutron energy varies. The absolute bounds for the inner integral are given by Equations (9) and (10) as a function of E_0 and γ . The curve for the energy bounds is a hyperbola in E_0, E space. This is a tremendous simplification compared to the complicated domains of integration normally encountered for non-elastic scattering using the ETOG algorithm.

The new algorithm has been applied to all Version IV ENDF/B materials processed for the PHROG II code through P_3 elastic and P_1 non-elastic matrices. The ETOG algorithm has been retained for resonance range calculations and as an option for anisotropic elastic scattering comparisons. The new algorithm is a factor of 4 faster than the ETOG algorithm for elastic scattering even in the most favorable cases for ETOG, i.e., Legendre data in CM coordinates. Excellent accuracy can be obtained using trapezoidal integration with 100 points each for the E_0 and BETA meshes except near the threshold of non-elastic level data where the errors are insignificant because of the small value for the non-elastic cross section. The use of Gauss-Legendre quadrature as an alternative to trapezoidal integration for the inner BETA integral of Equation (16) is presently being investigated to further improve efficiency of the new algorithm.

1. D. E. Kusner and R. A. Dannels, ETOG-1, A Fortran IV Program to Process Data from the ENDF/B file to the MUFT, GAM, and ANISN Formats, WCAP-3845-1, Westinghouse Electric Corp. (1969).
2. R. L. Curtis et. al., PHROG--A Fortran IV Program to Generate Fast Neutron Spectra and Average Multigroup Constants, IN-1435, Idaho Nuclear Corp. (April 1971).
3. R. D. Evans, The Atomic Nucleus, 410, McGraw-Hill Book Company, New York (1955).
4. Leonard Schiff, Quantum Mechanics, 99, McGraw-Hill Book Company, Inc., New York (1955).

REMFRAP COMPUTER CODE

R. C. Young

The REMFRAP code is a calculational tool for the prediction of fuel rod behavior in a transient situation. It is intended for use as part of an Evaluation Model (EM) in the licensing procedures for a nuclear power plant. REMFRAP was adapted from the transient fuel rod analysis program FRAP-T⁽¹⁾.

The larger calculational tool in the Water Reactor Evaluation Model (WREM)⁽²⁾ is RELAP4-EM. However, the primary emphasis of RELAP4⁽³⁾ is on the thermal hydraulic behavior of the entire reactor coolant system, with models for other components as they affect the coolant. REMFRAP and FRAP-T concentrate on a fuel rod in the reactor core, with consideration only of the coolant conditions in the channel adjacent to the fuel rod, and most or all of these conditions provided by input data. REMFRAP is much smaller and cheaper to run than RELAP4-EM, and will be used in hot-channel analyses and other parametric studies with common coolant conditions.

Several of the models concerning swelling and rupture of the fuel rod cladding had been transferred from FRAP-T to RELAP4-EM in the last year by the present author. However, there were several changes in order to meet EM criteria, for added conservation and other reasons. Other models describing the interaction of the fuel rod and coolant had been added to RELAP4-EM or significantly upgraded by the larger development effort on RELAP. All these had to be adjusted in order to obtain a fuel rod code for EM use. Some of these changes were also incorporated into FRAP-T.⁽⁴⁾ Some new models were added and revisions made nearly simultaneously to both RELAP4 and REMFRAP. Whenever possible, steps were taken to increase the modularity (interchangeable components) between RELAP4-EM and REMFRAP. An auxiliary interface program was also written which permits the transfer of the time dependent coolant conditions in the reactor core from a RELAP4 calculation to either REMFRAP or FRAP-T.

-
- (1) J. A. Dearien, L. J. Siefken, FRAP-T: A Computer Code for the Transient Analysis of Oxide Fuel Rods, Interim Report I-243-3-51.1, ANC (July, 1974).
 - (2) WREM: Water Reactor Evaluation Model, Nuclear Regulatory Commission, NUREG-75/056 (May 1975).
 - (3) K. V. Moore, W. H. Rettig, RELAP4 - A Computer Program for Transient Thermal-Hydraulic Analysis, ANCR-1127 (December 1973). See also: Modifications to RELAP4 Computer Code, this report.
 - (4) J. A. Dearien, L. J. Siefken, M. P. Bohn, R. C. Young, R. L. Benedetti, FRAP-T: A Computer Code for the Transient Analysis of Oxide Fuel Rods, report I-309-3-53.1, Aerojet Nuclear Company, (July, 1975)

MODIFICATIONS TO RELAP/4 COMPUTER CODE

R. C. Young

The RELAP4 computer code⁽¹⁾ calculates the coupled thermo-hydraulic behavior of a water piping system with various sources and sinks of fluid and of heat. The main application is to a transient situation involving the primary coolant loop of a nuclear power reactor. One option that is now in the code, and is required for an Evaluation Model (EM) Calculation⁽²⁾ provides additional detail on the behavior of the fuel rods in the reactor core. Further improvements to this portion of the code have been made in the past year.

The driving force for swelling and perhaps rupture of the fuel rod cladding is produced by the internal gas pressure within the rod. This pressure is determined by the amount of gas, the volume available to it, and the temperatures of various portions of the gas. A complex but important volume is the gas plenum within the fuel rod. It provides expansion space for the fuel as it heats up, and also lessens the pressure buildup from gas released by the fuel as it is used. The gas temperature within the plenum is important, because the plenum contains about 30 percent of the gas in the rod. The early simple model used the adjacent coolant temperature for the plenum gas temperature. However, this was found to be inadequate because 1) during steady flow the plenum should be several degrees above coolant temperature, the simple pressure is too low; and 2) during flow reversal the core coolant can get quite hot for brief intervals - the simple model yields a pressure spike with premature rupture of the clad predicted. The true gas temperature should show some lag time and have a lower peak than the coolant. The fuel rod plenum temperature model developed by Benedetti⁽³⁾ was adapted for use in RELAP4, along with certain other features needed for EM calculations.

The following new options are now available for any core heat slab:

- a) A gas plenum with a hold-down spring having heat capacity and heated by gamma flux and with heat conduction from the adjacent fuel. This would normally be at the top or both ends of the rod. The effective temperature differences from the fuel may be reduced by an input factor to simulate an insulator pellet on the end of the fuel stack.
- b) A large interior void in the fuel stack. It is expected that such a core region will also have reduced power generation and modified geometry.
- c) Small gas volumes distributed radially through the fuel such as in the dished ends of the pellets or interior cracks.
- d) Fuel surface cracks in addition to those calculated by the code. Such fuel cracks are common due to thermal cycling and radiation stress prior to the LOCA.
- e) Thin voids along the centerline of the fuel; these are also common in old fuel rods.

The above options are mutually exclusive in one slab. The special heat conduction model is used only in case a); in the others the gas in this volume is set to the fuel temperature. A radial average fuel temperature is calculated for cases a) - c), the fuel surface temperature used for d), and the fuel centerline temperature for e).

Another new option is a fuel swell increment which for each slab is added to the fuel outer radius otherwise calculated for that slab. This permits one to model an axial variation in fuel pellet diameter as might be expected in old fuel rods. Data for this effect can be obtained from a code such as FRAP-S⁽⁴⁾, as well as fill gas composition and cladding creep.

The gas conductivity routine was revised to obtain modularity with other work on fuel rod properties. This includes a rearrangement of the order of gases as specified on the input card to a more aesthetic order: helium, argon, krypton, xenon, hydrogen, nitrogen, steam. When a slab ruptures its gas mixture is replaced by steam and the conduction calculation proceeds as usual.

In studying the plenum model with the preliminary RELAP-EM version, plots were obtained of internal pin pressure which showed anomalous steps. This effect was traced to the GAPCON expansion model used for the fuel, which produces occasional sudden changes in fuel pellet radius. As used in RELAP-EM, these changes are rather large and probably cause significant perturbations of the gap conductance. The calculation was revised so that 50 radial nodes are always used for the calculation of pellet expansion as in the GAPCON code, which reduces the jumps to acceptable size.

-
- (1) W. H. Rettig, RELAP4 - A Computer Program for Transient Thermal-Hydraulic Analysis, ANCR-1127 (December 1973).
 - (2) WREM: Water Reactor Evaluation Model, Nuclear Regulatory Commission, NUREG-75/056 (May 1975).
 - (3) R. L. Benedetti, Aerojet internal report, (May 1975).
 - (4) J. A. Dearien, et al, FRAP-S: A Computer Code for the Steady State Analysis of Oxide Fuel Rods, Interim Report I-309-13.1, Aerojet Nuclear Company (January 1975).

CORRELATION EFFECTS IN THE RAFFLE MONTE CARLO CODE

D. Wessol

Because RAFFLE does not possess restart capabilities, the user may want to combine results of several shorter independent RAFFLE runs rather than make one very long run. When combining these shorter runs using the previous RAFFLE strategy, a different value for the number of random numbers initially rejected, NREJEC, was entered for each individual run. This strategy has been recently found to introduce strong positive correlation among the successive runs to be combined for a certain class of problems thus invalidating the supposition of independence among runs. Figure 1 clearly illustrates this correlation for a thermal fixed source with fission type of problem.

The results of the two cases shown in Figure 1 may not be statistically combined to obtain a result with a variance smaller than either of the two cases. Strong positive correlation was observed even when NREJEC differed by more than 4000 between runs. These results provide evidence to support the consensus of many Monte Carlo experts that correlation will be observed in certain neutron transport type problems using this strategy since the random number sequence of the two or more runs to be combined will walk into one another after a few generations, especially when NREJEC is small compared to the total number of histories to be followed⁽¹⁾⁽²⁾. Two candidate methods of reducing the correlation were examined with RAFFLE.

The first method examined initialized the random number generator X times prior to the beginning of each neutron history. Thus the random number sequence is perturbed at the start of each history. The value for X need only be incremented by 1 in each run for correlation to be acceptable as Figure 2 illustrates. CPU time was not notably increased for $X \leq 10$ in the problems studied where approximately 75K histories were followed.

The second method considered input the last random number of the first run as the first random number of the next run. This strategy will produce an uninterruptable random number sequence among the runs to be combined. Theoretically no correlation is introduced with this method, as is seemingly verified by Figure 3, and running times will not be affected between runs.

In addition to the visual inspections for correlation (Figures 1-3) both candidate methods and the current RAFFLE method were checked for correlation using the expression:

$$r = \frac{S_{k_1 k_2}}{S_{k_1}^2 S_{k_2}^2}$$

as the estimate of the population correlation coefficient. Here subscripts k_1 and k_2 refer to the neutron multiplication by generation, $S_{k_1 k_2}$ is the co-variance, and $S_{k_1}^2$ and $S_{k_2}^2$ are the estimates of the population variance of the two runs to be combined. The correlation coefficient of both candidates were statistically within zero where the correlation coefficient of the previous

method shows r nearly equal to unity for all but the early generations. Typically about 100 generations were used to calculate r .

The second candidate method was selected only to cross check the first method. Even though the second method truly does not introduce correlation it should be avoided in actual practice due to its susceptibility to user error. Since the first method is verified as reasonable by the second method it is recommended that the first method be adopted in RAFFLE where the maximum allowable of value $\underline{X}$ is of the order of 10 so that CPU time will not be significantly increased.

-
- (1) R. C. Gast - private communications
 - (2) E. M. Gelbard - private communications

Figure 1. Previous RAFFLE initialization strategy.

Figure 2 X random numbers initialized at each history.

Figure 3. Last random number of problem 1 input as first random number of problem 2.

DIGITAL PROGRAM FOR INVERSE SOLUTION OF THE REACTOR KINETICS EQUATIONS

W. M. Yarbrough

The HIGN4 (high gain) reactor kinetics program was developed to facilitate reactivity measurements in the test reactors and critical facilities. This program is the digital counterpart of an analog transient reactivity meter (TRM) in that it performs a closed-loop calculation of reactivity (Δk) using a neutron level signal (from one or two detector channels) as input. This process is illustrated in Figure 1. The validity of this calculational method is seen in the fundamental relationship of servo theory:

$$\Delta k = \frac{G(S)}{1 + G(S) H(S)} \phi_{in}$$

$$\lim_{|G(S)| \rightarrow \infty} \Delta k = H^{-1}(S) \phi_{in}$$

HIGN4 differs essentially from its analog counterpart only in that $|G|$ is precisely controlled at each calculational time step in order to maintain stability of the difference equations with respect to roundoff error. However, for certain applications HIGN4 has a considerable advantage over the TRM in that it will detect and correct for range switching of the neutron level input. This capability enables the program, for example, to compute smoothly through several decades of the neutron level following a rod drop or scram.

By virtue of its inherent closed-loop stability, HIGN4 computes accurately using the simple Euler numerical integration scheme. This mathematical simplicity minimizes the program running time required for a single calculational time step. This, in turn, makes feasible the sampling of input data at a rate consistent with the nature of the reactivity transient. That is, for typical rod drop measurements (~20 to 40-Hz data), sampling rates can be in the range of 100 to 200 samples per second--for accurate description of the neutron level transient--without incurring excessive computer time. For typical maneuvering transients (e.g., rod bumps, thermal reactivity transients, etc.) sampling rates can be an order of magnitude lower.

HIGN4, in its current IBM-360/75 version, is designed to accept automated input from digital magnetic tape written in the MAC/RAN III system format. This format results from the use of existing programs to create IBM 360-compatible digital tape from analog tape-recorded data. However, for additional flexibility, one can input card data to HIGN4 by use of a companion program, MAFHIT (MAC/RAN Formatted HIGN4 Input Tape). HIGN4, although in the final stage of checkout, has successfully analyzed neutron level data to determine control rod worths in support of the ETR Requalification program.

ϕ_{in} = Input Neutron Level

$G(S)$ = Forward Transference of the Loop (or high gain integrator)

Δk = reactivity (β)

$H(S)$ = Feedback Transference of the Loop (or forward reactor kinetics operator)

ϕ_{comp} = Computed Neutron Level ($H(S)\Delta k = \phi_{comp}$)

Figure 1. Closed-loop solution of reactor kinetics for ΔK .

PWR WASTE GAS TREATMENT SYSTEM DOSE EVALUATIONS UNDER UPSET CONDITIONS

N. C. Dyer, J. E. Baston

A calculational study of the radiation dose has been made for upset conditions causing a rupture of the waste gas decay tanks for a pressurized water power reactor. This study was done at the request of Standards Development, USNRC. Radiation dose calculations were made for an individual at the 300-meter boundary fence. The whole body immersion radiation dose, separated into its beta and gamma components, was calculated for a ruptured waste gas decay tank and a broken input line to the tank from the gas stripper. The thyroid, bone and lung doses due to inhalation of released radionuclides were also calculated. Parametric relationships were determined between input flow rates to the decay tanks, fill and hold-up times for the decay tanks and rupture time of the decay tanks during their operational period. Variations were investigated in the calculated doses with different fractional releases of the noble gas daughters produced in the waste gas decay tanks through radioactive decay. A semi-infinite cloud model with a ground level release was assumed.

For a waste gas decay tank rupture, the calculated gamma immersion dose varies from 0.014 milli-rad to 7.2 rad, depending upon the operational parameters concerned. For the direct release from the gas stripper output, the gamma immersion dose was calculated to be from 6.4 to 146 milli-rads. The thyroid dose due to inhalation of released radioiodine was calculated to vary from 0.25 micro-rem to 27 rem for a waste gas decay tank rupture and from 1.8 to 135 milli-rem for a direct release from the gas-stripper output. For the rupture of a waste gas decay tank, the lung dose was calculated to be from 14 micro-rem to 18 milli-rem while the bone dose was calculated to be from 31 micro-rem to 38 milli-rem.

A PERTURBATION CODE FOR PDQ-7

G. E. Putnam, M. H. Putnam

Evaluating the reactivity difference caused by a given perturbation in the physical state of a nuclear reactor is a common problem in reactor physics. Ordinarily, reactivity differences are computed in one of two different ways:

1. A reactor neutronics code (such as PDQ-7)⁽¹⁾ is run to compute the eigenvalues for both the unperturbed reactor state and the perturbed state, and the reactivity difference is then evaluated in terms of the difference in the two eigenvalues.
2. A reactor neutronics code is run to compute the flux for the unperturbed state and the adjoint function for the perturbed state (or vice versa). Then the reactivity difference is computed by means of a perturbation theory formula using volume integrals of the perturbations (in the neutron constants) weighted by products of adjoint and flux functions.

When the latter method is used, there is the advantage that (in addition to obtaining the exact reactivity difference for the given perturbation) one can obtain quite accurate values for the reactivity differences of other perturbations by repeating only the integration part of the calculation with the same flux and adjoint solutions. Since the solutions for flux and adjoint functions can be expensive and time consuming, the approximate evaluations of reactivity differences by perturbation theory methods can be done at a small fraction of the cost of evaluation by the first method. Moreover, the perturbation theory formula gives the difference in reactivity directly--as opposed to formulas that require the subtraction of one eigenvalue from another. Hence, the calculations to obtain the fluxes and the adjoints with codes like PDQ-7 need not be very tightly converged, while the same PDQ-7 calculations would have to be converged quite tightly to obtain eigenvalues accurate enough for the calculation of a reliable difference between them.

The PERP code was programmed to retrieve adjoint and flux solutions from PDQ-7 history files and compute reactivity differences and other related quantities according to perturbation theory. Arbitrary perturbations in the neutron group constants are input to the code, then perturbation theory is used to compute the difference in reactivity "contributed" by each user-specified part of the reactor volume. "Specific reactivity" (reactivity per unit volume) is computed for each mesh point at user-specified planes and these data can be edited or plotted as contour maps for any area of a plane. One-, two-, or three-dimensional problems are handled.

Since the PERP code can generate contour maps and printed output of reactivity-related pointwise distributions (for designated planes of a reactor), the reactor analyst is also provided a useful tool for gaining insight into the source and nature of reactivity differences. Application of the code should result in significant savings in those cases where detailed two- and three-dimensional PDQ-7 models are being used to analyze INEL reactors.

PERP is written in Fortran IV and operates on IBM-360-370 machines utilizing the INEL Environmental Subroutine Manual.⁽²⁾ Variable dimensioning is used and the core storage requirements (edited by the program) can be altered at execution time by the user. Running time for a 154 X 156 mesh two-dimensional problem on an IBM 360/75 with OS/360 and MVT required about 8 min. CPU and 6 min. WAIT time. Running time is roughly linear with total mesh size.

-
- (1) W. R. Cadwell, PDQ-7 Reference Manual, WAPD-TM-678, June 1967.
 - (2) R. J. Wagner, et. al., INEL Environmental Subroutine Manual, ANC Computer Science Library.

SOME AUXILIARY CODES FOR PDQ SYNTHESIS CALCULATIONS

M. W. Holm

Three-dimensional calculations of reactor core properties with PDQ-7 codes require six hours or more on the INEL IBM 360/75 system. Since 2-D PDQ calculations require roughly one-twentieth as much computer time, considerable effort has been expended on devising techniques for simulating 3-D calculations with 2-D data. One of the more successful methods involves a variational technique, flux synthesis. To minimize the labor and time involved in the preparation of input data from 2-D problem output fluxes, several procedures have been programmed to process the fluxes and evaluate problem parameters. Three of these are described briefly in the following paragraphs.

FNP - Flux Normalization Procedure

FNP was written to aid in the preparation of trial functions for 3-D synthesis calculations by normalizing output fluxes from 2-D problems. Any or all fluxes from a 2-D PDQ calculation may be selected for processing. Fluxes can be normalized to the largest value in the particular group, or all fluxes of a group can be multiplied by a normalization factor specified by the user. Fluxes from up to four PDQ output tapes can be normalized during one run of this program. The output tape is identical to a PDQ-7 output tape containing only flux edits.

PDQD - Flux Differencing Procedure

PDQD was also written to aid in the preparation of trial functions for 3-D PDQ synthesis calculations. The output fluxes from two 2-D calculations can be combined in a number of ways such as adding them together, or subtracting one from the other. The two sets of 2-D fluxes may be on the same tape, or they may be on separate tapes. The PDQD output tape is identical in format to a PDQ-7 tape containing only flux edits.

CPL - Coupling Coefficient Plotting Procedure

CPL provides a visual display of the normalized products of coupling coefficients in reactor-core Z-space. Output is on 35-mm film, with one frame for the trial functions of each flux group. Zone boundaries are shown as vertical dashed lines. Data cards are listed by the printer for reference. The curves permit rapid evaluation of the choices of 3-D synthesis parameters and indicate regions where modification may be desirable.

LCFT - LOFT Concentration File Transform Procedure

LCFT was developed as a time-saving aid to the preparation of input data for LOFT calculations in half-core geometry. Concentration files for quarter-core geometry are reflected about the zero column to produce simulated half-core concentration files. Block depletion is assumed. The LCFT output tape format is identical to that of a PDQ-7 output tape containing only concentration edits.

AN EMPIRICAL MODEL FOR ATR PHYSICS PARAMETERS

A. W. Brown, M. H. Holm, D. T. Neill, A. E. Wilson, V. P. Charyula

The basic structure of an ATR empirical model was developed for predicting ATR critical shim positions and reactivity lifetime. The model is based on coupled core equations with the reactor divided into the standard five lobes.

The basic equations used to describe the core are

$$k = \frac{1}{P_i} \sum_{j=1}^5 P_j \alpha_{ij} \quad i = 1, 2, \dots, 5$$

where k is the core reactivity ($k = 1.0$ for just critical)

P_i is the source neutron population in lobe i

α_{ij} is the coupling coefficient from lobe j to lobe i

The coupling coefficients can be determined empirically from experimental measurements or from fixed source or one iteration calculations on the ATR core using the relationship

$$\alpha_{ij} = \frac{S_{n+1}^{i \leftarrow j}}{S_n^j}$$

where

S_n^j = generation n source neutrons in lobe j

$S_{n+1}^{i \leftarrow j}$ = generation $n+1$ source neutrons in lobe i produced by generation n source neutrons in lobe j .

To easily use the equations the assumption was made that the α_{ij} are independent of control position for i not equal to j . The assumption was tested by calculating the α_{ij} at several different positions of the outer control cylinders. A small dependence was found on cylinder position and the assumption may have to be modified if, with use, the accuracy of the calculations proves to be insufficient.

To use the coupled core equations with experimental data from the ATRC, several modifications were made. The self coupling coefficient, α_{ii} , which is allowed to vary with control position was defined as

$$\alpha_{ii} = \alpha_{ii}^{RI} + AWR^i$$

where α_{ii}^{RI} is the coupling with all controls inserted,

and AWR^i the "Actual Rod Worth", is assumed to vary with control position.

For the just critical core the coupled equations can be written in the form:

$$1 - \alpha_{ii} = \sum_{j \neq i} \frac{P_j}{P_i} \alpha_{ij}$$

If a "Critical Rod Worth" is then defined as

$$CWR^i = 1 - \alpha_{ii}^{Ri}$$

the coupled core equations become

$$CWR^i - ARW^i = \sum_{j \neq i} \frac{P_j}{P_i} \alpha_{ij}$$

The CRW^i are assumed to be independent of control position and dependent upon experiment configuration, and fuel and boron loading in lobe i . The ARW^i are assumed to depend only on control configuration in lobe i .

The assumption was then made that the shape of the ARW^i versus outer control cylinder position is given by the control cylinder calibration curves and the magnitude is modified according to the neck shim configuration. With these assumptions values of α_{ij} were statistically determined from a number of ATRC runs where lobe power versus control position was recorded. The four codes discussed in Section C-12 of this report were then used to evaluate the accuracy of the calculation against the ATRC data. In general quite good results were obtained over the range of outer control positions for a given core and neck shim configuration but poorer results were obtained in going to a different boron loading in the fuel elements or to different neck shim configurations. The results were still judged to be adequate for initial shim predictions. Coupling coefficients obtained from PDQ full core calculations (with a quite different experiment configuration) and normalized to the statistically fitted coefficients gave similar results.

The basic model appears to be adequate for the intended purposes and must next be extended so that the CRW^i can be modified for different experiment configurations and for different fuel and boron contents of the fuel elements.

PRELIMINARY CODES FOR THE ATR EMPIRICAL MODEL

M. W. Holm

The 3-D calculations necessary to predict ATR startup parameters for a given core configuration using PDQ-7 on the INEL IBM System 360/75 are time-consuming and expensive. An attempt was made to devise an empirical model permitting reasonably accurate estimations of the startup parameters to be made using very little computer time. The procedures developed during this study are described briefly below.

CRW - Critical Rod Worths

The ATR is treated as a five-lobe coupled core, the coupling being described by an empirically determined matrix of coupling coefficients. CRW calculates the critical rod worths in terms of the coupling coefficients, shim positions and burnup factors for a "reference core" that is just-critical.

ARW - Actual Rod Worths

Input to ARW is the power split, burnup factors and a set of critical rod worths calculated for a reference core and suitably modified to reflect changes in fuel and experiments. ARW then calculates the drum shim positions at which the ATR is just critical.

CAR - CRW and ARW

CAR combines CRW and ATR calculations into a single computer run. Input data for a reference core is followed by sets of data cards describing other core configurations and specifying changes to be made to the reference-core critical rod worths to reflect the differences between the reference core and the new or "problem" cores. There is no limit on the number of "new" core configurations which can be calculated from the reference core.

PSRW - Power Split/Rod Worth Calculation

PSRW calculates the power split and balanced outer shim positions for a given ATR core configuration using the critical rod worths calculated for a reference core by CRW and suitably modified to take into account the differences between the configurations of the given and reference cores.

SUPPLEMENTAL COMPUTER CODES FOR ATR CORE SAFETY
ASSURANCE DATA REDUCTION

A. C. Smith, J. E. Brasier, W. C. Cook

The following computer codes were written to help in the reduction of data for ATR Core Safety Assurance.

LIMFIS computer program is used to generate plots of the peak fission density for an ATR fuel element during a cycle depletion based on PDQ data. Peak fission density data for all 40 fuel elements for two or more time steps are input to the program. Utilizing this data, plots of the peak fission density for each element are generated for Plates 1 and 19 of the Standard fuel elements and Plates 5 and 15 of the 7F fuel elements. The program selects the controlling element, plate, and edge in each of the five lobes and generates a plot for the cycle being analyzed. LIMFIS calculates the burnup limits for each element (1.8×10^{21} fission/cc of meat) in terms of lobe MWd during cycle depletion using a straight-line extrapolation from the last two calculated time points. LIMFIS also determines the buildup rates for each core position.

PQMAP provides ATR fuel element maps showing fuel element powers, the specified lobe power range (MW), the calculated lobe power (MW), and the MWd burnup limit. Fuel element and lobe power data are obtained from PDQ-7 calculations.

RELAP/4 BENCHMARK SUMMARY

T. E. Brake

The objective of the study was to determine the feasibility of using RELAP/4 for the analysis of hard transients in the 250-psia range in a water-moderated plate-type reactor. Feasibility was based on the ability of RELAP/4 to predict transients initiated in the SPERT III reactor. Specifically, the study included transients initiated by fast insertions of reactivity ($\$15/\text{sec}$) with maximums of $\$1.10$ to $\$1.25$.

The SPERT III-C core reached criticality in 1958. It consisted of 52 fuel assemblies in a cylindrical configuration. The diameter of the core was approximately 2 feet; the active height was 36 inches. Each fuel plate contained .020-inch-thick fuel volume composed of UO_2 (93.2% enriched) uniformly dispersed in a matrix of sintered 304L stainless steel powder. The fuel meat was clad with .005 inches of 304L stainless steel. Plates were spaced within the fuel assemblies at 0.158-inch intervals.

Several SPERT III transients were selected for RELAP analysis. Selections included various flow rates (0 - 18 ft/sec) as well as maximum reactivity insertions in the $\$1.10$ to $\$1.25$ range. A detailed RELAP/4 model of the SPERT III-C core was constructed and run. The calculated peak powers were 25% to 70% higher than reported by the SPERT project. The integrated powers, i.e., energy release, were 16% to 50% higher than those measured during actual SPERT III transients. Code running times for calculations were on the order of 10 minutes for the IBM system 360/75 and 75 seconds for the CDC System 7600. Based on the conservative results and encouraging RELAP running costs, it was concluded that it is feasible to use RELAP/4 for hard transient analysis.

A DIGITAL SIMULATION OF THE LOFT REACTOR COOLANT PUMPING SYSTEM

J. J. Feeley

A digital simulation was developed to analyze the dynamic performance of the reactor coolant pumping system used in the Loss-of-Fluid Test (LOFT) Facility. Simulation results were used in the safety analysis for the LOFT FSAR and in control studies of the reactor coolant pumping system.

The LOFT plant essentially consists of a 55-megawatt pressurized-water reactor, an active coolant loop containing a steam generator and paralleled reactor coolant pumps, and a blowdown loop containing the necessary equipment to conduct a loss-of-coolant experiment (LOCE). The reactor coolant pumping system is depicted in Figure 1.

The drive train for each centrifugal pump consists of a prime mover induction motor, fluid coupling, synchronous generator, flywheel, and canned rotor induction motor. The input speed to the fluid coupling is determined by the slip of the six-pole (1200 RPM synchronous speed) prime mover induction motor. The output speed of the fluid coupling, generator shaft speed, is controlled by positioning a scoop regulating the amount of oil in the fluid coupling working circuit. Generator shaft speed and field excitation determine the amplitude and frequency of the voltage applied to the reactor coolant pump motor. The flywheel acts as a reservoir of rotational kinetic energy. The eight-pole synchronous generator generates 60 Hz alternating current at a rotor speed of 900 RPM. The synchronous speed of the two-pole coolant pump induction motor is 3600 RPM at 60 Hz.

The digital model simulates each of the components in the pumping system and the fluid dynamics of the reactor coolant loop. The program is written using IBM S/360 CSMP simulation language and is easily modified, without special digital programming expertise, to simulate a large variety of transients. Nonlinear fluid coupling characteristics, generator saturation, and generator, motor, feeder cable, and pump losses are all accounted for. The simulation is not limited to unidirectional power flow, and may be used regardless of whether power is being transferred from the pump to the coolant or vice-versa. A representative set of transients, including one-and two-pump flow coastdowns and various pump starting techniques, has been studied using the simulation. Flow coastdown results agree within 5% with results of independent hybrid computer analysis.⁽¹⁾ The use of a simple automatic flow controller has also been demonstrated.

(1) F. K. Hyer, Internal Report, October 12, 1973.

Figure 1. LOFT primary coolant pumping system.

SAFETY ANALYSIS FOR THE LOFT FINAL SAFETY ANALYSIS REPORT

F. K. Hyer, J. J. Feeley

The safety analysis required for the LOFT Final Safety Analysis Report was completed during 1975. The analysis results are documented in Chapter 15 of the LOFT FSAR and have been submitted for approval.

The majority of the analyses were performed using the LOFT hybrid computer simulation. The simulation has been updated to reflect the latest LOFT plant design and parameter values. The accidents studied with the hybrid simulation include reactivity insertions, loss of reactor coolant flow, loss of steam load, oversteam demand, excessive feedwater addition, failure of pressure control, and loss of commercial power. Hybrid computer results were used as input data to detailed thermal hydraulic and fuel pin digital codes, COBRA-IIIC and FRAP-I, respectively, to compute departure from nucleate boiling ratios and fuel pin temperatures. The loss of coolant analyses were performed using the digital code RELAP 4.

The analyses indicate that the LOFT plant can be safely operated at the design power of 55 MW and the design flow of 3.6 million lbs/hr. Future analyses will investigate the ability of the plant to operate safely at lower reactor coolant flow rates.

GRIST LOOP MODELING AND SIMULATION

J. D. Miller

A dynamic model of the GRIST loop has been developed as a tool for loop systems analyses and controls design. The model was mechanized using the Time And Frequency (TAF) digital simulation language and the CDC 7600 digital computer and used to determine initial steady-state conditions and transient responses. A comparison was made of simulation costs for the entire GRIST program for computation schemes utilizing either an all-digital approach or a hybrid computer with digital support. The hybrid plus digital scheme was found to offer very substantial cost and operational advantages.

The loop model is being used, in conjunction with a detailed thermo-hydraulic model of the GRIST core section, to explore loop capabilities for physical simulation of GCFR plant transients, to determine loop and core response to malfunction transients and to design loop and controls components. The model evolved substantially during the year to incorporate updated and improved core and circulator simulation and to simplify and speed up the flow calculations.

The IPT model is a single-pin simplification of the symmetry sector model used for detailed core analysis. Nuclear heat is input to two radial nodes in the fuel pin, and gamma heating is input to the hex can enclosing the 37-pin bundle and to the inner pressure boundary. The primary helium flow cools the fuel (clad) outer surface and the hex can inner surface, and the attemperation helium flow cools the inner surface of the inner pressure boundary. The core is divided into 3 axial sections, resulting in a total of 12 energy storage nodes.

The model includes circulator characteristics which have been modified to include the inlet valve and piping losses. The four circulators and their bypasses are modeled separately, permitting simulation of the 3 on-line units and the transient changeover to replace a malfunctioning circulator with the standby unit.

The coolers and the electric heater have been sized and modeled to take advantage of SLSF and ATR gas loop component designs.

The flow system incorporates the resistance of standard flow elements and is modeled by storing mass at each pressure node, energy at most pressure nodes and by neglecting the fluid inertia. A compressibility factor is applied to modify the perfect gas equation.

The model includes the depressurization system but not the circulator speed dynamics, the helium make-up and bleed-off system and actuators and control. These items will be added in the future.

The model is 59th order and includes time constants ranging from 0.32 milliseç to 8 to 14 seconds for the inner fuel nodes.

The model is mechanized using the Time And Frequency (TAF) digital simulation language and the CDC 7600 computer. This code provides:

- a) Transient simulation at \$8/second of real time.
- b) Direct evaluation of steady states by matrix techniques.
- c) State matrix and Bode plot representation of the linearized system for use in controls design.

An initial definition of the design steady state and the flow, power and pressure transients have been made. Transient response is dominated by the fuel pin inner node with a 8-14 sec time constant.

A comparison was made of computation costs for the current simulation versus the use of a hybrid computer for transient simulation combined with the existing TAF code for support and verification. The comparison was based on:

- a) A matrix of runs of various durations involving a number of cycles of design and malfunction transients and controls design evaluations.
- b) Digital simulation cost of \$4/second of real time for the fully expanded model, allowing for model simplification.
- c) Hybrid simulation at \$300/hour of real time using a terminal to a remote computer since ANC facilities are inadequate. A "non-productive" time of 5 minutes per run was allowed for verification, review of results, set-up of the next run, etc.
- d) A digital support (steady state, frequency response, model variation and verification) cost of \$5000 was assumed for each of the two computation schemes.

The total direct computer charges were found to be \$83000 for the all-digital approach versus \$25000 for the hybrid + digital approach. Hybrid programming costs were assumed to be more than offset by the increase in analyst productivity.

A 59th order dynamic model of the GRIST loop has been developed and implemented within the TAF digital simulation language. Initial steady state and transient response computations have been made. Computation costs can be substantially reduced and analyst productivity increased by providing for a hybrid simulation to be complimented by the existing digital simulation.

IMPLEMENTATION OF TAF (TIME AND FREQUENCY)
SIMULATION PROGRAM ON CDC 7600 COMPUTER

J. D. Miller

The TAF simulation language has been made operative on the Berkeley CDC 7600 computer. This language is used in conjunction with user-prepared subroutines unique to the particular physical system being investigated. The resulting code provides three capabilities: a) transient simulation, b) evaluation of steady states by matrix techniques and c) dynamic characterization of the linearized system in both state matrix and Bode plot formats.

The TAF code (Reference 1) was written at Los Alamos in 1966 and used extensively in the nuclear rocket program and in the power reactor field. The user codes several Fortran subroutines to describe his system in terms of first-order non-linear differential equations, algebraic equations, tabulated functions and LaPlace expressions, and to provide for input and output. The user subroutines are then used in conjunction with TAF subroutines for matrix operations, interpolation, iteration, integration and printed and plotted output.

The code currently provides for integration by either the modified 4th order Runge-Kutta fixed-increment method or the Runge-Kutta-Amerson variable-increment method. The code is currently limited to a 60th order system although this limit is easily changed. Transient plot capability is available. Current limitations are the lack of a Bode plot subroutine and a complete users guide.

A transient simulation code is available which additionally provides for direct evaluation of steady states and for linearized system representation in state matrix or Bode plot format.

-
- (1) T. E. Springer, O. A. Farmer, TAF - A Steady State, Frequency Response and Time Response Simulation Program, Los Alamos Scientific Laboratory paper presented in Fall Joint Computer Conference, San Francisco, CA, (December 1968).

A 360/75 FORTRAN PROGRAM TO GENERATE A SEQUENCE CONTROL PATTERN

J. E. Baston, W. R. Myers

Acquisition of data from several sensors having different sample rate requirements requires implementation of a randomly addressable multiplexer and a "scan control pattern" which specifies the sensor sampling sequence. If there are several sets of sensors, each of which is to be sampled at a different frequency, manual generation of the control pattern is tedious and error-prone.

PATTERN is a 360/75 program written in Fortran IV designed to distribute sensor identifiers into a sequence control pattern according to the number of sensors in each set and their corresponding sampling frequency.

PATTERN is given the sampling frequency and the number of sensors at that frequency for each set in the sequence. It then calculates a pattern length and sampling time and uses an iterative algorithm to assign sensor identifiers to the appropriate multiplexer channels. If for some reason the requested pattern is not feasible, error messages and the existing partial pattern are printed.

The final printout lists the sensor sampling sequence and the required sampling rate. The sequence is also punched on paper tape for transfer to programmable data acquisition systems.

FORTTRAN PROGRAM TO TABULATE GAMMA RAY
AND INTERNAL CONVERSION DATA

J. E. Baston, R. C. Greenwood

LIST was developed to print tables of gamma ray and internal conversion data. These tables contain for each gamma ray, its energy, the error in intensity, the conversion electron intensity and origin (K, L, etc.), the error in conversion electron intensity, K calculated from these intensities, the error in K, and the corresponding theoretical K values. An example of the printout is given in Table I.

The internal conversion coefficient E1, E2 and M1 are calculated using a spline interpolation⁽¹⁾ with the appropriate constants for the various tables. LIST uses the Hager-Seltzer Tables⁽²⁾ for gamma rays from 0 to 1550 keV, the Sliv and Band Tables⁽³⁾ for gamma rays from 1550 to 2500 keV, and the Trusov Tables⁽⁴⁾ for gamma rays above 1500 keV.

- (1) R. S. Hager and E. C. Seltzer, K-, L-, M-Shell, Katharine Way, Editor, Internal Conversion Coefficients for Multipolarities E1, . . . , E4, M1, . . . , M4, Atomic and Nuclear Data Reprints, Academic Press, (1973) 7-11.
- (2) Op. Cit., 13-237.
- (3) L. A. Sliv and I. M. Band, issued in USA as Report 57 ICC K1, Physics Department, University of Illinois.
- (4) V. F. Trusov, Internal Conversion Coefficients for High-Energy Transitions; Katharine Day, Editor, Internal Conversion Coefficients for Multipolarities E1, . . . , E4, M1, . . . , M4, Atomic and Nuclear Data Reprints, Academic Press, (1973) 477-510.

TABLE I
EXAMPLE OF THE PRINTOUT

GAMMA RAY				ELECTRON			ALPHA K		THEORETICAL ALPHA K		
ENERGY KEV	ERROR KEV	RELATIVE INTENSITY	ERROR %	INTENSITY		ERROR %	EXPERIMENT	ERROR %	E1	E2	M1
563.22	0.013	86.7	2.	10.6	K	19.0	7.49E-03	20.	2.15E-03	6.04E-03	8.54E-03
592.57	0.038	3.98	7.						1.92E-03	5.30E-03	7.54E-03
604.69	0.012	1218.7	2.	100.0	K	0.0	5.03E-03	2.0	1.83E-03	5.03E-03	7.18E-03
659.85	0.09	0.62	10.						1.52E-03	4.04E-03	5.81E-03
718.70	0.028	2.90	7.						1.27E-03	3.29E-03	4.74E-03
795.90	0.032	1.83	7.						1.03E-03	2.58E-03	3.72E-03
861.28	0.047	0.99	10.						8.78E-04	2.16E-03	3.09E-03
920.34	0.024	4.32	5.						7.72E-04	1.86E-03	2.65E-03
991.72	0.042	1.38	7.						6.69E-04	1.58E-03	2.22E-03
1038.68	0.05	0.91	7.						6.13E-04	1.43E-03	2.00E-03
1103.5	0.5	0.2	50.						5.48E-04	1.26E-03	1.74E-03
1155.82	0.028	4.68	5.	0.13	K	46.0	1.70E-03	47.	5.04E-04	1.15E-03	1.56E-03
1168.10	0.028	23.75	2.	0.50	K	24.0	1.29E-03	25.	4.94E-04	1.12E-03	1.53E-03
1184.92	0.12	0.42	15.						4.82E-04	1.09E-03	1.48E-03
1211.14	0.026	28.59	2.	0.66	K	30.0	1.42E-03	31.	4.63E-04	1.04E-03	1.41E-03
1243.84	0.21	0.54	20.						4.42E-04	9.87E-04	1.33E-03
1255.06	0.26	0.35	40.						4.35E-04	9.69E-04	1.30E-03
1260.1	0.6	0.35	40.						4.32E-04	9.61E-04	1.29E-03
1307.0	0.7	0.18	50.						4.05E-04	8.93E-04	1.19E-03
1320.70	0.028	19.80	2.	0.35	K	17.0	1.08E-03	18.	3.98E-04	9.75E-04	1.16E-03
1347.34	0.05	1.18	5.						3.84E-04	9.41E-04	1.11E-03
1368.96	0.07	0.74	10.						3.74E-04	8.15E-04	1.07E-03
1396.73	0.029	8.55	2.	0.19	K	21.0	1.36E-03	22.	3.61E-04	7.93E-04	1.02E-03
1402.88	0.034	2.47	5.						3.59E-04	7.77E-04	1.01E-03
1424.50	0.030	45.4	2.	0.78	K	23.0	1.05E-03	24.	3.49E-04	7.54E-04	9.80E-04
1431.35	0.13	0.54	20.						3.46E-04	7.47E-04	9.69E-04
1483.51	0.031	35.9	2.*	0.55	K	15.0	9.12E-04	16.	3.26E-04	6.96E-04	8.96E-04
1488.29	0.27	1.05	23.*						3.24E-04	6.92E-04	8.90E-04
1528.54	0.07	0.64	10.						3.10E-04	6.57E-04	8.40E-04
1554.93	0.032	100.0	2.*	1.21	K	18.0	7.33E-04	19.	3.03E-04	6.38E-04	8.01E-04
1560.42	0.48	1.18	30.*						3.01E-04	6.34E-04	7.95E-04
1579.92	0.15	1.14	20.						2.95E-04	6.19E-04	7.74E-04
1591.1	1.1	0.22	30.						2.91E-04	6.11E-04	7.62E-04
1649.68	0.16	0.29	15.						2.75E-04	5.70E-04	7.04E-04
1660.57	0.07	0.73	10.						2.72E-04	5.63E-04	6.94E-04
1674.6	0.5	0.14	40.						2.68E-04	5.54E-04	6.81E-04
1683.33	0.07	0.77	10.						2.66E-04	5.49E-04	6.74E-04
1719.04	0.05	1.50	5.						2.57E-04	5.28E-04	6.43E-04
1732.12	0.03	56.6	2.	0.50	K	16.0	5.42E-04	17.	2.54E-04	5.20E-04	6.33E-04
1749.41	0.13	0.34	15.						2.50E-04	5.10E-04	6.19E-04

TABLE I (continued)

1759.9	0.7	<	0.2	1.73	K	12.0		2.47E-04	5.05E-04	6.12E-04
1765.71	0.22		0.53 20.					2.46E-04	5.02E-04	6.07E-04
1774.35	0.036		11.55 2.	0.14	K	21.0	7.43E-04	22.	2.44E-04	4.97E-04
1800.8	0.5		0.08 40.						2.39E-04	4.84E-04
1836.43	0.15		0.40 15.						2.31E-04	4.66E-04
1859.43	0.06		0.36 7.						2.26E-04	4.56E-04
1883.74	0.12		0.79 15.						2.22E-04	4.45E-04
1893.20	0.08		0.56 10.						2.20E-04	4.41E-04
1918.0	0.5		0.18 40.						2.15E-04	4.30E-04
1932.16	0.06		1.07 7.						2.13E-04	4.25E-04
1959.95	0.043		23.55 2.*	0.18	K	17.0	4.49E-04	18.	2.08E-04	4.14E-04
1966.07	0.12		1.03 15.*						2.07E-04	4.11E-04
1995.13	0.044		21.57 2.	0.21	K	33.0	5.97E-04	34.	2.02E-04	4.00E-04
2029.19	0.044		9.81 2.	0.08	K	25.0	5.00E-04	26.	1.97E-04	3.88E-04
2051.55	0.10		1.42 10.						1.94E-04	3.80E-04
2064.4	0.5		0.15 30.						1.92E-04	3.76E-04
2088.24	0.05		14.4 5.						1.89E-04	3.69E-04
2091.99	0.10		2.38 10.						1.88E-04	3.67E-04
2104.11	0.06		0.75 7.						1.86E-04	3.63E-04
2124.48	0.050		7.50 2.						1.84E-04	3.57E-04
2143.22	0.050		3.87 5.	0.03	K	24.0	4.75E-04	25.	1.81E-04	3.51E-04
2156.03	0.06		1.01 10.						1.80E-04	3.49E-04
2159.5	0.5		0.7 50.						1.79E-04	3.47E-04
2223.78	0.048		4.38 2.	0.03	K	33.0	4.20E-04	34.	1.71E-04	3.29E-04
2240.4	0.6		0.12 30.						1.69E-04	3.24E-04
2246.67	0.35		0.13 30.						1.69E-04	3.23E-04
2282.29	0.054		2.12 5.						1.65E-04	3.14E-04
2312.91	0.07		0.54 7.						1.61E-04	3.06E-04
2334.7	0.4		0.45 20.						1.59E-04	3.01E-04
2335.0	3.0	<	0.45	0.02	K	50.0			1.59E-04	3.01E-04
2345.56	0.21		0.15 15.						1.58E-04	2.99E-04
2379.6	1.5	<	0.1	0.19	K	21.0			1.55E-04	2.91E-04
2442.68	0.26		0.10 20.						1.49E-04	2.78E-04
2464.15	0.13		0.17 15.						1.47E-04	2.74E-04
2482.24	0.17		0.14 15.						1.45E-04	2.70E-04
2487.0	1.5	<	0.1	0.09	K	22.0			1.45E-04	2.69E-04
2564.84	0.07		1.38 7.*	0.02	K	41.0	2.08E-04	42.	-1.00E 00	-1.00E 00
2570.87	0.054		4.51 2.*						-1.00E 00	-1.00E 00
2599.84	0.06		0.68 7.						-1.00E 00	-1.00E 00

360 ASSEMBLY LANGUAGE PROGRAMS TO CONVERT BETWEEN PAPER TAPE AND CARDS

J. E. Baston, W. R. Myers

Conversion of alphanumeric data from ASCII punched paper tape to EBCDIC punched cards, or from cards to paper tape, is often required in laboratory data applications and minicomputer programming activities. Programs to perform the conversions have been written for the INEL IBM-360/75; they are written in assembly language to assure efficient operation and minimal turn-around time. The programs convert cards to paper tape in seven-level ASCII format with even parity, mark, or null in the eighth level, with trailing blank suppression, tab insertion control, and leader and trailer. Seven-level ASCII tapes are converted to punched cards with tabulation interpretation and sequence punches in columns 73-80. Card duplication is also implemented and all operations produce listings of the alphanumeric data. Source and destination devices are specified by Job Control Language Data Definition (DD) statements.

Reactor Experiment Design Studies

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

PRELIMINARY FEASIBILITY DESIGN STUDY
FOR A THORIUM-CYCLE PEBBLE BED BREEDER REACTOR

J. H. Lofthouse, E. Fast, A. J. Scott

Recent petroleum fuel shortages and the high cost of fuel imports has highlighted the necessity of U.S. energy independence. One option available in the U.S. is the use of breeder fission reactors which produce more nuclear fuel than they burn. A concept which holds some promise, both as a high-temperature process heat source and also for electrical power production, is a Pebble Bed Breeder Reactor which converts thorium-232 into uranium-233, a fissionable isotope. Although the concept is not new, very little work has been done to date to determine if a design capable of producing an acceptable breeding ratio and fuel doubling time is possible. If these two parameters can be shown to be acceptable then it should be possible to design a reactor which eliminates some of the undesirable features of a liquid metal fast breeder reactor.

A pebble bed reactor would consist of pebbles of uranium carbide and thorium carbide particles contained in a graphite matrix. The pebbles are contained in concentric graphite vessels which also serves as a neutron reflector. This configuration results in a cavity reactor concept with outward radial flow of a coolant such as helium. Figure 1 shows a calculational model.

Calculations were performed using spherical geometry, with the MONA diffusion theory code. Cross-section sets, using a thirty-two-group energy format with 10 thermal groups were generated with PHROG and INCITE for the reactor constituents. Since a wide range of Th-232 concentrations were used for the various cores considered in the calculations, a MONA cross-section library was generated for each concentration.

Various configurations and thorium loadings were calculated searching on the U-233 concentration to give a critical system. Both zoned and un-zoned cores were investigated. No depletion calculations were performed, and the breeding ratios and fissile load results are for the beginning of life. The breeding ratio was computed as the ratio of the neutron captures in the thorium to the neutron absorptions in the U-233.

For this study the core outside diameter was held constant at 24 feet. A series of calculations were performed by varying the initial thorium loadings from 5 kg/ft³ to 40 kg/ft³ for a core inside diameter of 12 feet. This was followed by a series of calculations holding the thorium loading constant at 10 kg/ft³ and varying the core inside diameter from 0 to 20 feet. Zoned cores were investigated for a core with a 12-foot inside diameter by dividing the 6-foot-thick annulus into four 1.5-foot-thick zone annuli and then varying the thorium loading by zone.

A quite wide range of breeding ratio is obtained for the configurations investigated. Breeding ratios as high as 1.19 were calculated for some of the zoned core configurations with properly arranged thorium loadings. It is not clear by inspection of the data which configuration will give the best breeding performance over the lifetime of the reactor core. This can only be determined with burn-up calculations. This series of calculations does serve as a launching point for further investigations on the effects of thorium loadings and zoned core configurations. Follow-on work is planned to explore these effects, followed by burn-up calculations in an attempt to optimize a nuclear design.

Figure 1. Schematic of spherical geometry pebble bed reactors.

FEASIBILITY STUDIES FOR SHAPING THE AXIAL POWER
DISTRIBUTION IN A 25-ROD FLOW BLOCKAGE TEST IN PBF

A. J. Scott, E. Fast, J. H. Lofthouse

Flow blockage experiments with a 25-pin cluster of BWR type fuel in PBF have been proposed by ANC's Thermal Fuel Behavior Program to evaluate computer models for predicting fuel rod behavior resulting from postulated BWR flow blockage accidents. In support of this test series, reactor physics calculations were done to determine the feasibility of shaping the axial power distribution to achieve a flat profile over a central 18-inch section of the test under blocked flow conditions. The test geometry is shown in Figure 1. The results of 97-group RAFFLE⁽¹⁾ Monte Carlo calculations showed that the stainless steel shaper shown in Figure 1 will effect the desired power shape. Axial dimensions and placement of the shaper, as determined by 4-group RZ PDQ-7⁽²⁾ calculations, are shown in Figure 2.

-
- (1) W. E. Vesely, F. J. Wheeler, R. S. Marsden, RAFFLE - A Multipurpose Monte Carlo Code, ANCR 1022, (April, 1973).
 - (2) A. W. Brown, J. A. McClure, R. J. Wagner, Summary of PDQ-7 (IBM-360-370 Version) Input Data Requirements and Operating Procedures, ANCR-1061, (March 1972).

ANC-A-6291

Figure 1. RAFFLE model 25-Rod BWR-6 test in PBF.

POWER LEVEL AND DISTRIBUTION IN WIDELY SPACED CLUSTERS OF
PWR TYPE RODS FOR GAP-CONDUCTANCE TESTS IN PBF

F. J. Wheeler

Reactor physics calculations were completed to determine enrichment and rod spacings required to provide desired power levels for a 4-in-1 BWR/6 test in the PBF facilities test space. Monte Carlo calculations, providing the relationship between neutron currents at the inner surface of the in-pile-tube and test power level as well as detailed power distributions in the test, were performed by Nuclear Technology personnel. Calculations employing transport theory and two-dimensional diffusion theory, to provide neutron currents, axial power distributions and the effect on test performance of core conditions, were performed by Computer Science personnel. Radial, azimuthal, and axial power distributions in the test pins were calculated for steady-state operation with the control rods at 14 inches of core insertion and the transient rods at 10 inches of insertion. The asymptotic axial distribution approached after transient rod withdrawal for the RIA test was also provided as well as detailed power distributions in the core. Integral rod worth curves were obtained which agree with experimental results much better than previously calculated results.

The testing procedure will entail operation at 10 MW core power and a maximum test power of 13 kW/ft to attain steady-state temperature distributions in the test pins. After establishment of the steady-state temperatures a reactivity excursion will be initiated by transient-rod ejection. Resulting experimental data and comparison with calculational results will be helpful in the development of theories for the calculation of gap-conductances as well as other effects.

The test hardware was designed such that each of the four rods is isolated from one another and data is simultaneously generated for four independent single-rod tests.

With the core at a steady-state power of 10 MW and with 14 inches of control-rod poison and 10 inches of transient-rod poison in the core, an enrichment of about 13-17 w/o should be required in the BWR test pins if a maximum power of 13 kW/ft is to be achieved in the 4-in-1 test hardware. Figure 1 shows the relationship between average test power and test pin enrichment. The data displayed in this figure were taken from calculations using a clean-core model with no correction for migration of energy-bearing particles resulting from fission in the test and core. Corrections, necessary to account for rod positions, shim pins and the distribution of energy deposition were generated and must be applied on a case-to-case basis.

The Monte Carlo computations were performed using the RAFFLE⁽¹⁾ code. A typical problem required about 30 minutes on an IBM 360/195 system to process ~ 175,000 neutron histories having about 4 million collisions. The overall fractional standard deviation on total test power was typically about 0.7%. A diagram of the two-dimensional geometrical representation of the test space in the RAFFLE model is shown in Figure 2. The type of output generated from the RAFFLE problems is shown in Figure 3 where relative power distributions for a 15% enriched test are given. On this figure σ' ($=1.645\sigma$) is the fractional statistical deviation computed for a 90% confidence interval.

-
- (1) W. E. Vesely, F. J. Wheeler and R. S. Marsden, The RAFFLE General Purpose Monte Carlo Code, ANCR-1022, (April 1973).

Figure 1. BWR/6 test pin power (uncorrected) vs. w/o enrichment.

	Outside Radius (cm)
Fuel	0.53131
Void	0.54143
Clad	0.628057
Water	0.92
Zr	1.2253
Water	6.0485
Zr	6.3669
Water	7.791

ANC-A-6292

Figure 2. RAFFLE model 4-in-1 hardware.

Figure 3. Relative power for RAFFLE region sets 15% enriched rod in the PBF 4-in-1 test (σ').

POWER CHANGE IN A BWR/6 FUEL BUNDLE FOLLOWING
A COMPLETE FLOW BLOCKAGE

A. J. Scott, E. Fast

One of the Power-Cooling-Mismatch (PCM) test series planned for PBF concerns a postulated blockage of coolant flow at the inlet orifice of a nuclear fuel bundle in an operating BWR reactor. To provide information for the proposed Thermal Fuel Behavior Program's flow-block experiments with BWR type fuel pin clusters in PBF, reactor physics calculations were done to determine the effect of 100% flow blockage on the power distribution and power level in a fuel bundle of a BWR reactor. The results showed that the power distribution existing within a fuel bundle under normal flow conditions would not change significantly after a 100% flow blockage. The power level would drop due to the lack of moderator in the blocked bundle; however, the results indicated that the assembly power drop should be less than 45%.

To investigate the power distribution change, Monte Carlo calculations were done with the RAFFLE⁽¹⁾ code for both normal and blocked flow conditions. Sixty-four fuel pins were represented along with the fuel bundle cannister and intervening bypass channel water. The RAFFLE solution region is shown by dashed lines in Figure 1 where symmetry boundary conditions were imposed. Water rods and control rods were not included in the model. An eigenvalue type calculation was done with 97 neutron energy groups with all quadrants flooded (water density = 23 lbs/ft³) and then with one quadrant steam filled (water density 1 lb/ft³). The relative pin powers changed by less than 3.7%.

The power level drop was computed with 4-group PDQ-7⁽²⁾ calculations in XY geometry for a large array of fuel bundles. The central bundle of the array was then assumed to be blocked. For the blocked assembly, absorption and fission homogenized group constants for PDQ were obtained from the RAFFLE coalesced output fluxes and reaction rates. The slowing-down cross sections, diffusion coefficients and all other region constants were computed with the LEOPARD⁽³⁾, PHROG⁽⁴⁾, and INCITE⁽⁵⁾ codes. The temperature and void fraction conditions of the flooded bundles corresponded to those that would exist near the bottom of a BWR and near the axial mid-plane. For an axial section near the bottom, the power drop was computed to be about 45%. For a representative midplane axial section, the computed power drop was about 30%.

-
- (1) W. E. Vesely, F. J. Wheeler, and R. S. Marsden, RAFFLE - A Multipurpose Monte Carlo Code, ANCR-1022, (1973)
 - (2) A. W. Brown, et. al., Summary of PDQ-7 (IBM-360-75 Version) Input Data Requirements and Operating Procedures, ANCR-1061, (March 1972).
 - (3) R. F. Barry, LEOPARD - A Spectrum Dependent Non-Spatial Depletion Code for the IBM-7094 USAEC Report, WCAP-3269-26, (September 1963).
 - (4) R. L. Curtis, R. A. Grimesey, G. L. Singer, and F. J. Wheeler, PHROG-- A FORTRAN IV Program to Generate Fast Neutron Spectra and Average Multigroup Constants, IN-1435, Idaho Nuclear Corporation, (April 1971).

- (5) R. L. Curtis and R. A. Grimesey, INCITE--A FORTRAN IV Program to Generate Thermal Neutron Spectra and Multigroup Constants Using Arbitrary Scattering Kernals, IN-1062, Idaho Nuclear Corporation, 1967

Dim. Identification	A	B	C	D	E	F	G	H	I	J
Dim. Inches	12.0	5.278	0.241	0.260	0.120	0.147	0.1525	0.640		

Dim. Identification	K	L	M	N	O	P	Q	R	S	
Dim. Inches	4.875	0.241	1.553						0.400	

Figure 1. Representative section of BWR/6 core.

POWER LEVEL AND DISTRIBUTION IN WIDELY SPACED CLUSTERS
OF PWR RODS IN PBF FOR IRRADIATION EFFECTS AND SIMULATION TESTS

A. J. Scott, E. Fast

In support of the Thermal Fuel Behavior Program's Irradiation Effects and Simulation Test Series, reactor physics calculations have been done for two irradiated PWR type rods and two fresh rods to be tested simultaneously in the four-rod (quad) hardware in PBF. The quad test geometry is shown in Figure 1. The rods are 9.5 w/o enriched UO_2 with the irradiated rods depleted to an average burnup of about 15,800 MWd/MTU. The quad hardware contains each of the four pins in individual flow shrouds that are normally 0.918 in. outside diameter, 60 mils thick Zircaloy-4 (Zr-4) tubes. However, since the experiment requires that all four rods have equal peak-power densities, the fresh rods will be shrouded by steel for these tests. The results show that to balance the fresh and depleted rod powers, the steel shrouds should have the same dimensions as the Zr-4 shrouds. The results further show that the required peak linear power density of 20-21 kW/ft can be achieved with a PBF core power of 35 MW. In the modified quad hardware, detailed power distributions within each pin were computed for further test analysis.

The calculations were done with 97-group Monte Carlo methods using the RAFFLE(1) code in conjunction with 32-group SN calculations using SCAMP(2). The SCAMP calculations were done in radial geometry for the whole reactor to determine the steel shroud thickness required and to furnish a neutron current source for the RAFFLE calculations.

Using neutron currents computed by SCAMP at the inner surface of the in-pile tube as an external source, RAFFLE calculations were then made in general two-dimensional geometry to predict the test-pin power distribution in the modified quad hardware.

-
- (1) W. E. Vesely, F. J. Wheeler, R. S. Marsden, RAFFLE - A Multipurpose Monte Carlo Code, ANCR-1022, (1973).
 - (2) SCAMP has not been published but it is essentially a multigroup version of TOPIC: G. E. Putnam, TOPIC -- FORTRAN Program for Calculating Transport of Particles in Cylinders, IDO-16968, Phillips Petroleum Company, (April 1964).

ANC-A-6288

Figure 1. RAFFLE model of PBF in-pile tube region with quad hardware.

PHYSICS STUDIES FOR A PBF RELOAD CORE FOR
STEADY-STATE TESTING

F. J. Wheeler

Feasibility studies were performed to determine the effect, on test performance and operational characteristics, of a steady-state reload core for PBF. Plate-type elements (ATR, ETR, HFIR) have been considered as fuel for the driver core and will provide extremely high test-power densities. Because of the cost and schedule inherent with this relatively major modification, however, it was found to be desirable to pursue a design which would be attainable over a shorter period of time. Recent studies have focused on oxide fuel rods as the driver fuel to maintain maximum compatibility with core 1 such that cost, procurement time, and core interchange time would be minimized.

Calculational results were obtained using one-dimensional multigroup diffusion theory and one-dimensional and two-dimensional few-group diffusion theory. Verification of some of the results was made with an accurate one-dimensional, multigroup transport-theory model.

The studies identified four actions that would significantly increase test performance, over that obtainable with core 1, and remain within constraints of the guidelines established for the reload oxide core. These are:

1. Replacement of the present approximately 7/8-inch Inconel-718 in-pile-tube (IPT) with either a thinner IPT of the same composition or a zirconium-alloy IPT. The calculations indicate an increase in test performance of 35-60% depending upon the thickness and composition of a replacement IPT. Use of a zirconium-alloy IPT has a further advantage in that the large positive reactivity insertion observed for an Inconel IPT, due to voiding an H_2O -filled test space, is greatly reduced.
2. Reduction of core volume while maintaining total core power. This obviously increases test power (test power is nearly proportional to core volumetric power density for a large driver core) due to the increase in the fission source near the test. The result of this modification, however, has a large impact on the design of a reload core since test coupling is increased, control-rod worth is decreased, and heat-removal requirements become more severe.
3. An increase in total plant power. This also obviously increases test power (essentially a linear relationship) but may require increased capacity of external systems and more severe heat removal requirements in the core.
4. Tailoring of the axial flux profile by axial-loading of the driver-core pellet stack to attain the desired 1.2 axial peak-to-average power in the test. The test requirements currently specify this 1.2 peak-to-average power and a uniformly-loaded core provides an axial peak-to-average power of about 1.4. For a uniform core therefore some type of shaper material would be required to attain the desired axial power shape at the expense of overall test power.

If the desired axial shape were provided by an axial loaded core an advantage in overall test power would be seen. This modification, however, may not be desirable because of the added complexity of the design and manufacture of the core.

The use of commercial-type oxide fuel pins results in a reduction of test power and control-rod worth due to the reduced neutron path lengths in this type of fuel compared to the present dilute fuel. Test performance could be enhanced by removal of water from the driver core, however, the present core has a very tight lattice and it is probably infeasible to specify a water fraction for the reload core as being less than for core 1. The use of the oxide rod with no insulator has the advantage however, in that higher volumetric power densities can be attained.

The calculational results indicate, quite strongly, that the present control system will not be adequate for a reload core. One scheme which could provide control requirements with only minor modification would incorporate the present transient rod locations into the control system and use four of the outer-rod positions for transient control.

PRELIMINARY PHYSICS CALCULATIONS FOR GRIST PROGRAM IN ETR

J. E. Brasier, A. W. Brown

A preliminary physics feasibility study was conducted in support of the proposed Gas Reactor In-Pile Safety Test (GRIST). Basic neutron physics data were obtained for engineering design and to determine the adequacy of the Engineering Test Reactor (ETR) to meet the functional requirements for a series of fuel pin tests. The primary objectives were: (1) choose a thermal neutron filter (hafnium or cadmium) and location (inside or outside the test loop); (2) obtain approximate enrichments in a 37-pin test to get a flat radial power distribution within the test; and (3) obtain source currents for detailed Monte Carlo (RAFFLE) calculations.

One-dimensional calculations with the MONA⁽¹⁾ diffusion-theory code were started in order to choose an analytical model for pin enrichment studies. Figure 1 shows one of the 1-D analytical models chosen for the GRIST loop with a cadmium filter located outside of the double pressure vessel. Table 1 shows the parameters used for the GRIST mixed oxide fuel pellet. Preliminary GRIST fuel pin enrichments were also chosen. MONA calculations showed that changes in the calculational model outside the GRIST loop had little effect on the neutron spectrum inside of the test loop and also showed how sensitive pin enrichments are to these models. Those basic 1-D calculations also indicate that the pin enrichments chosen for the outside fuel rows should be increased. Transport theory calculations will use the reactor models from MONA calculations to plot power tilts across the pins and to obtain changes in relative pin power with changes in filter type.

The final choice of the thermal neutron filter will depend upon obtaining the maximum GRIST test power while maintaining an acceptable power tilt across each fuel pin (inside edge versus outside edge of pin). If the outside annulus of fuel pins is lost, an acceptable power increase must be maintained for the inside fuel pins. Preliminary calculations indicate that a 50-mil cadmium neutron filter bonded to the outside pressure vessel wall is better than a hafnium neutron filter inside the loop (hafnium must be used inside the loop due to high internal helium temperature).

(1) G. E. Putnam, MONA - A Multigroup One-Dimensional Neutronics Analysis Code, ANCR-1051, (March 1972).

TABLE I
PARAMETERS FOR GRIST MIXED OXIDE PELLET

Average Temperature	1500°F
PuO ₂ Weight Percent	15.0
UO ₂ Weight Percent	85.0
Pu Atomic Fractions	
Pu-238	.0007
Pu-239	.8600
Pu-240	.1170
Pu-241	.0205
Pu-242	.0018
PuO ₂ Theoretical Density	11.46 gm/cm ³
UO ₂ Theoretical Density (Natural U)	10.96 gm/cm ³
Natural Uranium Atomic Fractions	
U-235	.0072
U-238	.9928
Atomic Weights	
U-235	235.0439
U-238	238.0508
Pu-238	238.0495
Pu-239	239.0522
Pu-240	240.0540
Pu-241	241.056
Pu-242	242.0587
Natural U (AVG)	238.0292
Pu (AVG)	239.2152
Avogadro's Number =	0.60228 X 10 ²⁴
Fuel Pellet Density =	.91% of theoretical
Fraction of 240 inch O.D. Solid-right cylinder occupied by oxide fuel =	0.9339
Fuel Density Smeared to clad (cold) =	$(0.9339) (.91) \left(\frac{.240}{.244}\right)^2 = .822$

TABLE I
(con't)

$$\text{Fuel Density Smeared to Clad (Hot)} = (.9339) (.91) \left(\frac{.240}{.2474} \right)^2 = 0.800$$

$$\begin{aligned} \text{Cold Pellet Density} = & \frac{1}{\frac{.15}{(11.46)(.91)(.9339)} + \frac{.85}{(10.96)(.91)(.9339)}} = 9.3757 \\ & \text{(0.240" O.D. Solid right cylinder with Natural Uranium)} \end{aligned}$$

$$\begin{aligned} \text{Atomic Density of Pu (Total)} &= (0.15) (9.3757) \frac{(.60228 \times 10^{24})}{239.2152} \\ &= .0035408 \times 10^{24} \text{ atoms/cm}^3 \end{aligned}$$

$$\begin{aligned} \text{Atomic Density of U (Total)} &= (0.85 \times 9.3757) \frac{(.60228 \times 10^{24})}{238.0292} \\ &= .020165 \times 10^{24} \text{ atoms/cm}^3 \end{aligned}$$

$$\text{Atomic Density of Oxygen} = .047411 \times 10^{24} \text{ atoms/cm}^3$$

Figure 1. Analytical model of the Grist Loop located outside of the double pressure vessel.

SHAPED BURST FEASIBILITY FOR N-SERIES TESTS IN PBF

W. R. Carpenter

The proposed N-Series tests in the Power Burst Facility concern testing LMFBR fuel pins in a sodium environment under failure-mode conditions in the PBF test space. One means of simulating failure-mode conditions in the test space is to run the PBF parent core at very high power levels for short periods of time in order to establish initial power profile conditions in the LMFBR pins, then "hit" the test with a step transient. This mode of operation is referred to as the shaped burst or transient rod velocity mode. The initial high-power conditions are actually established by bursting the reactor up to a specified power level, then holding the power against Doppler shutdown by means of the transient rods. The purpose of the feasibility study was to determine whether the PBF parent core could tolerate a number of proposed N-Series tests with initial power levels of 100 MW to 400 MW for time durations of 1.0 sec. to 5.2 sec. Total reactivity insertion, i.e., that required to establish the initial power level plus that used for the step transient, was \$3.65.

In general, the results of the study indicate that PBF can be successfully operated in the shaped burst mode provided the reactor can be scrammed within 250 msec following peak power. The most severe transient conditions encountered resulted from power shaping of 200 MW for 1.8 sec. followed by a \$1.45 step reactivity insertion. This transient had a minimum period of 3.1 msec, a peak power of 5616 MW, and a total energy release of 1330 MW sec.

PROPOSED MODIFICATIONS TO THE COUPLED
FAST REACTIVITY MEASUREMENT FACILITY
FOR RAISING THE POWER LEVEL TO 100 kW

I. E. Stepan, C. R. Suter, Y. D. Harker

The CFRMF will be modified to provide heat removal capacity and shielding necessary to upgrade the maximum operating power to 100 kW. The project consists of the following:

- A. Provide and install a new heat exchanger and pump to remove 100 kW of heat from the CFRMF.
- B. Provide and install a shield around the top of the reactor.
- C. Provide a plenum chamber beneath the reactor to direct flow and contain the heat generated by the reactor.
- D. Provide and install motor drives on the startup channels.

The CFRMF is a spectral shaping insert which has been installed in the core of ARMF-II for the purpose of providing a fast neutron spectrum for integral measurements in support of the Fast Breeder Reactor Physics Constants Program. The design of the system has proven to quite successful. However, the facility has been limited on making cross section measurements on specific isotopes which are important to the FBR Program. Many of these isotopes are separated on the mass separator and after irradiation in the CFRMF, a spectrometric analysis is made. The quantities of these samples are usually very small which in turn requires higher fluxes. Increased power will provide the fluxes needed.

The function of the reactor coolant system is to maintain the canal water temperature constant while the CFRMF is being operated at high powers so that reactivity measurements can be made in ARMF-I.

The plenum will surround the area below the fuel elements. It will contain the heat generated by the CFRMF and direct the flow to the heat exchanger as shown in Figure I. The pump for the system will be suspended in the canal with the motor above water. A two inch line will carry the water from the plenum to the heat exchanger and return it to the canal. The heat exchanger will be all stainless steel, full counter flow, shell and tube. The required capacity can be realized with an envelope consisting of a six inch nominal size pipe shell approximately 20 feet long. It will be located in the facility utility trench and the secondary coolant will be TRF well water.

Shielding of carbon steel will be provided above the canal. It will be in sections weighing less than five tons for easy access and provided with stepped joints to prevent a direct path for shine. It will be divided into two major areas; one consisting of over-decking of the control platform and another area supported by the inside of the east and west parapet wall. The shielding will be 3-3/8 inch thick. This thickness will reduce the gamma radiation to less than 50 mr/hr while at full power.

Modification of the reactor instrumentation is necessary to

prevent the start-up channels from going off scale during start-up before the intermediate channel comes on scale. This will be accomplished by providing each of the two fission chambers with drives that will raise the chambers within the instrument thimbles as the recorders approach full scale.

Figure 1. Flow diagram for reactor coolant for CFRMF when operating at a power level of 100 kW.

Calculations

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

CRITICALITY CALCULATIONS ON HTGR PRIMARY BURNER

T. Watanabe

In the HTGR fuel reprocessing cycle, the HTGR fuel is fed from the crusher into the primary burner where excess graphite is burned off before going to the classifier where fissile and fertile particles are separated. As prevention of criticality in the primary burner is to be maintained by geometric design, criticality calculations were required in support of the design of the HTGR primary burner.

A series of scoping and parametric calculations was made using the KENO code (1) to provide criticality data for a design guide-line (in form of graphs). Parameters considered were hydrogen-to-uranium 235 ratio (H/X), carbon-to-uranium ratio (C/X) and burner diameter.

Within the scope of the investigation, it was established that criticality could be controlled by geometric means. For the change to be expected in criticality due to presence of hydrogenous material, the calculations showed little change in criticality for a range of H/X from 0 to 1.

-
- (1) G. E. Whitesides and N. F. Cross, KENO - A Multigroup Monte Carlo Criticality Program, CTC-5, (September 10, 1975).

ARMF PHASE-II CASK SHIELDING

T. E. Young

Dose rates due to gamma rays from irradiated LWBR fuel rods were calculated for various locations on the surface of an ARMF Modification Phase II Cask. Various cask thicknesses were considered.

The gamma ray source strength was computed with the ISOSHL⁽¹⁾ code, and the dose rates were then computed with the QAD-P5A^(2,3) point-kernel shielding code. The cask loading consisted of 18 fuel pins of .306" diameter and 84" active length. These pins were irradiated at an average power of 3.9 kW/ft for 1-1/2 years and then allowed to decay for 1/2 year before being loaded in the cask. The power distribution during irradiation was assumed to follow a cosine distribution which went to 0. at a point 52" from the center of the active portions of the rods. During irradiation, 20g of fission products were produced in each rod. The cask consisted of a cylinder closed at top and bottom with the same material of which the walls of the cask were constructed. The cask was lined with 1/2" of steel and had an outer casing of 3/4" of steel. The space between the steel was filled with lead, and the dose rates were calculated for various thicknesses of the lead filler.

The maximum dose rate exists at the center of the active length of the fuel pins (the peak of the cosine distribution) and is .77 R/hr for 4" of lead, .17 R/hr for 5" of lead, .042 R/hr for 6" of lead, and .011 R/hr for 7" of lead. Dose rates at other locations on the surface of the cask are as low as 4% of these values.

-
- (1) R. L. Engel, J. Greenborg, and M. M. Hendrickson, ISOSHL - A Computer Code for General Purpose Isotope Shielding Analysis, BNWL-326, (June 1966).
 - (2) E. Solomito and J. Stockton, Modifications of the Point-Kernel Code QAD-P5A: Conversion to the IBM-360 Computer and Incorporation of Additional Geometry Routine, ORNL-4181, (July 1968).
 - (3) R. E. Malenfant, Qad: A Series of Point-Kernel General-Purpose Shielding Programs, LA-3575, (April 1967).

C. EXPERIMENTAL TECHNIQUES & INSTRUMENTATION

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

LINEAR ELECTRONIC DEVICE MODELS FOR ECAP

J. L. Morrison

The electronic circuit analysis program ECAP is a powerful design tool that allows the electronic designer to easily perform linear analysis on complex electronic circuits. The program will perform DC analysis, AC analysis, and transient analysis. All this analytical power is useless unless that designer can convert his device data sheets into a linear circuit model that the computer can accept. This report provides techniques for obtaining such models for some of the more common solid state devices that are utilized in regions where they behave linearly. The models presented are adequate for most transient and AC analysis requirements.

The first device considered is the silicon transistor. The Ebers-Moll common base model is utilized. Figure 1 shows the configuration.

The parameters of the device can be obtained from relationships involving the following parameters that are usually specified.

<u>Parameter</u>	<u>Description</u>
h_{fe}	Small Signal Current Gain
f_t	Transistor Gain Crossover Frequency
C_{ob}	Collector-base capacitance at some specified V_{cb} bias voltage
h_{oe} or h_{ob}	Common emitter or common base output impedance

The model parameters can be obtained from the data sheet parameters through the following relationships.

$$\alpha = \frac{h_{fe}}{1+h_{fe}}$$

$$R_e = \frac{V_T}{I_E}$$

$V_T = 26 \text{ mV @ } 25^\circ\text{C}$ and is proportional to ABS temp.

$I_E = \text{Quiescent emitter current}$

$R_\alpha = h_{ob}$ expressed in ohms - Sometimes h_{ob} or h_{oe} is given in ohms and ECAP does not recognize conductance.

$R_\alpha = h_{oe}(1+\beta)$ where h_{oe} is expressed in ohms

$$C_e = \frac{1}{2 R_{eff_t}} \quad f_t \text{ is expressed in Hz}$$

$$C_b = C_{ob} \sqrt{\frac{1+V_{cb} \text{ Operating Point}}{1+V_{cb} \text{ Spec. Point}}}$$

The ECAP small signal model for the Zener diode is its dynamic impedance which is usually specified. A typical value is between 10 and 20 ohms.

The ECAP small signal model for a silicon diode is its dynamic impedance as given by the following.

$$Z_{\text{diode}} = \frac{V_T}{I_D} \quad V_T = 26 \text{ mV @ } 25^\circ\text{C}$$

I_D = Quiescent diode current

The typical IC operational amplifier is usually described adequately on its data sheet such that the parameters for the mathematical model illustrated in Figure 2 can be obtained.

A description of these parameters is as follows.

<u>Parameter</u>	<u>Description</u>
C_{IN}	Input capacitance typically around 2 pf
R_{IN}	Input impedance typically 1 meg for bipolar devices and 10^{10} to $10^{12} \Omega$ for FET devices.
A_0	DC open loop gain typically around 10^6
F_0, F_1	Low frequency and high frequency break points. The first depends on compensation the second depends on type of device typical values are 5 Hz and 1 mHz.
R_{OUT}	Output impedance typically between 50 and 200 ohms.

The mathematical model of Figure 2 is to be converted into the following ECAP model. This is done because ECAP is set up for dependent current sources. Figure 3 shows the 2 pole ECAP model developed from the mathematical model.

The parameters for the model are obtained as follows.

$$B_1 = B_2 = 1 \quad \text{The first two dependent current sources have unity gain.}$$

C_{IN} , R_{IN} , R_{OUT} all as before.

$B_3 = A_0 \frac{R_{IN}}{R_{OUT}}$ The third current source sets the DC gain.

$$C_0 = \frac{1}{2\pi f_0} \quad C_1 = \frac{1}{2\pi f_1}$$

These capacitance expressions were developed from the relationship

$$f_{\text{break freq.}} = \frac{1}{2\pi RC} \quad \text{where } R = 1\Omega$$

The above models have all been utilized by the writer and adequate results obtained.

Figure 1. Ebers-Moll small signal transistor model.

$$A(jf) = \frac{A_0}{(j\frac{f}{f_0} + 1)(j\frac{f}{f_1} + 1)}$$

Figure 2. The mathematical model for the IC operational amplifier.

Figure 3. ECAP model of the operational amplifier.

EXPERIMENTAL TEST RESULTS FOR A ρv^2 PROBE EMPLOYING A DRAG SCREEN

C. J. Buchenauer

To meet the two-phase fluid density measurement requirements of the LOFT program, single phase (water) flow tests were performed at the Wyle Laboratories on a modified (Drag Screen, Fig. #1), and conventional (Drag Disc) ρv^2 probes. These tests were initiated because the currently used model incorporating the drag disc, have large errors in their response and tests performed by Combustion Engineering on the Drag Screen in a two-phase air-water flow loop were encouraging.

The resulting data from the Wyle Laboratories are graphically presented in figures 2 through 5. The calibration data for the drag screen (ρv^2 probe #12) and a conventional drag disk (ρv^2 probe # 15) are shown in Figures 2 and 3. Some of the nonlinearity is due to the dragging of the retaining wire at the end of the VRT core. This shows up in the force calibration curve of figures 4 and 5.

The curve drag disk VRT output versus fluid velocity square (figure 5) shows a discontinuous change in slope at zero velocity. The slope for reverse flow is 40% below that for forward flow at 10 ft/sec. Both of these effects are apparently due to flow shadowing caused by the turbine and its support structure. The curve drag screen VRT output versus fluid velocity squared (figure 4) shows no discontinuity in slope at zero velocity. However, the slope for reverse flow is still 25% below that for forward flow at 10 ft/sec.

The fact that the drag screen is not entirely insensitive to flow shadowing effects is rather surprising considering the design of the screen and the bearing hub cones. In accounting for the observed effects, it would appear that the turbine causes a considerable redistribution of fluid flow within the flow shroud. Fluid flow near the center of the flow shroud must be decreased as it passes through the turbine, while the fluid which does not pass through the turbine near the outer surface of the shroud must be accelerated. Since the drag screen covers nearly the same area as the turbine, the measured momentum flux would be smaller in reverse flow. The shadowing errors could be eliminated if the screen were enlarged to cover the entire area of flow shroud, and the wire grid spacing were made sufficiently small. However, the velocity measurement errors which must accompany the flow redistribution by the turbine would still remain.

The behavior of the turbine response for both drag screen and drag disk type ρv^2 probes was compared.⁽¹⁾ No significant differences were observed for the two different probes. No asymmetry in the response curves for forward and reverse flow was observed as it has been in cavitating flow.⁽²⁾ Therefore, it would appear that significant cavitation could not have occurred during these low velocity tests.

It is this author's conclusion that the Wyle tests revealed that the

drag screen would have only slight advantages over the drag disk in single phase flow. No conclusions regarding performance in two phase flow can be drawn from the Wyle tests.

(1) G. L. Smith, private communication.

(2) C. J. Buchenauer, private communication.

Figure 1. Modified ρv^2 probe with drag screen.

Figure 2. Flow calibration curve for drag screen ρv^2 .

Figure 3. Flow calibration curve for drag disk ρV^2 .

Figure 4. Force calibration curve for drag screen ρv^2 .

Figure 5. Force calibration curve for drag disk pv^2 .

G. D. Lassahn

Work supported by the Semiscale Project was done to increase understanding of gamma densitometers in general and to analyze a particular Semiscale Project densitometer.

The primary application of gamma densitometers is two pipes carrying an inhomogeneous mixture of liquid and gaseous water. Usually the distribution of the two phases in the pipe is not known and without knowing this distribution, it is usually not possible to interpret unambiguously the reading from a single-beam gamma densitometer. Therefore, several gamma beams are used simultaneously to try to determine the liquid-gas distribution, or flow regime, and the density distribution inside the pipe. It is not very realistic to expect an unambiguous determination of an arbitrary density distribution with a finite number of gamma beams. However, a few beams can be expected to distinguish between the several flow regimes which actually occur in real two-phase systems and to give a reasonably accurate indication of the fluid density average across the pipe.

The system analyzed is shown in Figure 1. The pipe is three-inch, schedule 80 spore, 316 stainless steel. The radiation source contains 30 curies of cesium-137, which yield about 9.5×10^{10} gamma photons per second. The detectors are scintillation crystal-photomultiplier assemblies, which detect about 25% of the incident gamma photons. The collimators are made of tungsten, lead, and steel. For this analysis the collimator materials are assumed to be perfect absorbers.

Two types of fluid flow were considered: a simple stratified flow, with liquid in the bottom of the pipe and foam in the top, with a flop interface between the two fluids; and simple annular flow, with liquid covering the inside surface of the pipe and a circular cross section region of foam centered in the pipe. The foam in each case is assumed to have a void fraction variable from zero to one.

For these flow regimes, the response of each detector was calculated separately, for various stratified liquid depths, annulus inner radii, and foam void, fractions. The sensor output was normalized so that the reading was unity for an empty pipe.

Other realistic cases include stratified liquid-gas flow with a curved interface, and annular liquid-gas flow with the gas core centered above the pipe center. Both of these geometries can be described by specifying the depth of the liquid above the center of the bottom of the pipe and the radius of curvature of the liquid-gas interface.

Apart from uncertainty in the interpretation of the two-beam densitometer output, some consideration of the expected errors is in order. The two major sources of error are expected to be shot noise, or statistical fluctuations in the radiation beam intensities, and radiation scattering.

The major source of error in using gamma densitometers is due to lack of knowledge of the distribution of the fluid mass in the pipe. If the general nature of the fluid distribution (the flow regime) is known, then a simple graphical scheme can be used to determine the average fluid density and some details of the fluid distribution from the densitometer readings. If the flow regime is not known before hand, the interpretation of the densitometer readings is subject to considerable ambiguity, which can result in errors of about 0.15 g/cc in the determination of the average density of the fluid in the pipe for the particular system studied here.

ANC-A-4486

Figure 1. Geometry of the two-beam gamma densitometer which was analyzed.

IRRADIATION TEST ON METAL-TO-CERAMIC SEALS USED
IN THE LOFT LIQUID LEVEL PROBE

A. E. Arave

An irradiation resistance test was made on eight metal-to-ceramic seals used in the LOFT conductivity liquid level probe. The test was conducted in the ETR reactor. The total radiation exposure⁽¹⁾ was a total dose of 1.75×10^{12} R gamma and a total fast neutron dose of 2.7×10^{19} nvt and a total thermal neutron dose of 5.6×10^{20} nvt. The composition of the ceramic is shown in Table I. A summary of electrode impedance versus time is shown in Table II.

At the end of the 1848-hour test the metal-to-ceramic seal was examined for deterioration, the cross-section of a typical seal after the test is shown in Figure 1. The only deterioration noted was corrosion of the ceramic surface exposed to the 600°F, 2200 psi water. The only notable metallurgical difference between the irradiated Durock 199 ceramic structure and the non-irradiated structure was that the polishing behavior of the cross sections appeared to be slightly different in the irradiated ceramic with island areas polishing in relief.

The corrosion extended to depth 33% deeper than in previous autoclave tests, but the increase cannot be attributed to radiation alone.

The electrical resistance data taken during the reactor experiment showed that two of the seals had leaked. The same two seals showed corrosion on the inside due to leaks when cross sectioned.

(1) A.E. Arave, J.M. Beeston, Internal Material.

TABLE I

M3-3 In-Pile Loop Operating Conditions

Water Temperature	450 to 550 ⁰ F
Pressure	2000 psig nominal
Flow	50-125 gpm
PH at 77 ⁰ F	10.0 to 10.3
Lithium	0.2 to 2.0 to maintain PH
Electrical Conductivity	15/50 micromhos/cm at 77 ⁰ F
Oxygen	<0.1 ppm
Chloride	<0.15 ppm
Fluoride	<0.10 ppm
Total Suspended Solids on 0.45 μ filter	<1.0 ppm

TABLE II

LLT ELECTRODE IMPEDANCE IN X1000 OHMS IN THE M3-3 LOOP DURING THE ETR TEST

Date	Water Temp.	ELECTRODE NUMBER							
		1	2	3	4	5	6	7	8
9/1/72	70°F	20.0	20.0	20.0	20.0	20.0	20.0	20.0	∞
9/8/72	150	1.5	1.5	1.5	1.5	1.5	1.5	1.5	∞
9/10/72	458	0.2	0.4	0.4	0.4	0.4	0.4	0.4	∞
9/15/72	100	1.6	2.0	2.0	2.0	2.0	2.0	2.0	∞
9/18/72	450	0.2	0.4	0.5	0.5	0.5	0.5	0.5	∞
9/21/72	70	1.1	1.7	2.0	2.0	2.0	2.0	2.0	∞
9/28/72	330	0.1	0.2	0.4	0.5	0.5	0.5	0.5	∞
10/8/72	470	0.1	0.2	0.4	0.4	0.5	0.5	0.5	∞
10/17/72	400	0.0	0.3	0.4	0.4	0.5	0.5	0.5	∞
10/18/72	470	0.0	0.2	0.4	0.4	0.4	0.4	0.4	∞
11/29/72	533	0.1	0.3	0.3	0.3	0.3	0.3	0.0	∞
11/21/72	530	0.0	0.3	0.3	0.3	0.3	0.3	0.0	∞
12/28/72	525	0.1	0.3	0.3	0.3	0.3	0.3	0.0	∞
1/4/73	520	0.0	0.2	0.2	0.2	0.2	0.2	0.0	∞
1/24/73	470	0.1	0.4	0.4	0.4	0.4	0.4	0.1	∞
2/5/73	486	0.1	0.4	0.4	0.4	0.4	0.4	0.1	∞
2/7/73	70°F	4.6	6.9	12.3	9.0	12.6	12.6	2.0	∞

Fig. 1 Cross-Section of Metal-to-Ceramic Seal Area

CORRECTION OF TEMPERATURE EFFECTS
IN ANC FREE FIELD PRESSURE TRANSDUCERS

T. B. Klingler

An experimental measurement requirement of the LOFT program is to measure transient pressure in the area just above the reactor core and in the pressure vessel downcomer. In order to make this measurement with its low millisecond response requirement, a free field pressure transducer was developed by ANC. A report of this development effort is included in the "Instrumentation and Control Branch Annual Report 1971", ANCR-1074. The original concept in making this measurement was to use the free field pressure transducers to measure the very rapid pressure decay during the sub-cooled decompression portion of the LOCA test. The pressure during the much slower response, saturated blowdown portion of the test would be monitored with more conventional measurement systems.

Tests of the free field transducers verified that they were fast enough to adequately monitor the sub-cooled decompression decay and showed possibilities of being able to monitor the entire LOCA pressure profile. The transducer response fell well within the accuracy specifications for several seconds then drifted in the positive direction to an ultimate error of approximately 100 psi.

An error analysis of the deviation indicated that it was due to temperature sensitivity effects on the strain post during the temperature transient. A special transducer was fabricated with thermocouples on the strain post and a temperature profile was obtained during an autoclave blowdown test. Using this data, the location of the strain gages on the strain post and manufacturers data on temperature effects on the resistance and gage factor of the strain gages, a calculated error was derived. The calculated ultimate error was 92.2 psi, virtually identical to the measured error.

A redesign of the transducer based on the above information has been suggested. The redesign would relocate the strain gages from the present location, i.e., approximately midway between the strain post centerline and the transducer end plates, to a location at the midpoint of the strain post. The present location places them at the steepest strain post temperature gradient during transient operation. Temperature differential across the strain gages exceed 20°F. The proposed location would place the strain gages on the flat portion of the curve at the strain post centerline and locate the temperature compensating strain gages such that the remaining temperature effects would be cancelled out in the bridge network. The calculated ultimate error based on the proposed configuration was 1.3 psi.

The proposed configuration could, if tests confirm the calculation, provide a single transducer which would provide the rapid response and signal accuracy required throughout the entire LOCA test cycle.

DOMAIN REFLECTOMETRY FOR
DYNAMIC FUEL ROD CLADDING DEFORMATION MEASUREMENTS

C. J. Buchenauer

The use of time domain reflectometry has been investigated for use in dynamic fuel rod cladding deformation measurements in fuel behavior experiments at TFB. A transmission line is formed from a cluster of parallel fuel rods. Waves reflected along this transmission line reveal information about displacements and diametrical changes in the fuel rods.

The use of time domain reflectometry has been investigated for use in dynamic fuel rod cladding deformation measurements. The technique may be used in gas or steam with fuel rod bundles where no mechanical penetration of the region between the rods can be tolerated.

Laboratory feasibility experiments were performed on simulated 0.422 inch diameter fuel rods arranged in a square lattice with a 0.563 inch lattice spacing. A single fuel rod was connected at one end to the inner conductor of a coaxial transmission line. The ends of the remaining fuel rods were connected to the sheath of the coaxial cable. The fuel bundle constituted a second transmission line.

The composite transmission line was monitored with a time domain reflectometer (TDR) with a spacial resolution of 0.5 inches. Waves reflected from discontinuities in the line could be displayed on a CRT, an X-Y recorder, or feed into a high speed tape recording system. As many as 1000 sweeps of the fuel bundle per second can be achieved with slightly modified TDR units.

Measurements of reflections caused by diametrical changes and displacements of the fuel rods revealed that the transmission line impedance was primarily sensitive to the average distance between the surface of the central rod and the surfaces of its four nearest neighbors. Sensitivity to motions of the next neighbor rods was lower by a factor of ten (see Figures 1 and 2).

The TDR output could be easily interpreted to determine the location, length, and size of simple diametrical changes in the central rod for reductions in the nearest neighbor surface displacements of as much as 50%. For larger displacements or very complex or periodic diametrical changes, multiple reflections prevented the data from being interpreted by visual inspection. However, computer processing of these data can then be used to recover the desired information.

Figure 1. TDR response for various diametrical changes of the central rod. (a) $D=0.422$ inches (no change), (b) $D=0.502$ inches, and (c) $D=0.625$ inches. $\rho=0.422$ inches and $\sigma=0.563$ inches.

Figure 2. TDR response.

STEAM TEMPERATURE TRANSDUCER DEVELOPMENT

G. D. Lassahn

A performance test was made on a prototype steam temperature transducer (Figures 1 and 2) designed to measure the temperature of steam flowing out of the Semiscale Project core. This steam temperature measurement must not be affected by the presence of subcooled water drops in the steam or by radiant heat transfer to or from the steam thermocouple.

Three separate performance tests were conducted: flow resistance, heat transfer to the steam thermocouple, and liquid-gas separation.

The air flow rate was measured with a Fischer-Porter rotameter type flowmeter, and the pressure drop was measured with a simple water manometer. The flow resistance was measured with the probe mounted in two different tubes with inside diameter of 4.36 cm (1.72 in) and 6.65 cm (2.62 in). The results are given in Table I.

The limited tests done are not definitive, but they do indicate that the heat transfer is probably negligible (less than 5°F error in the steam thermocouple reading) if the pipe temperature is less than about 380°F, the flow rate is greater than about 0.1 ft³/sec., and the air temperature is within a few degrees of room temperature. This flow velocity (0.1 ft/sec) is 0.2% of the maximum expected steam flow velocity. The suggestion is strong that radiation and conduction between the pipe and the steam thermocouple are negligible throughout almost all of the steam flow velocity range.

A moisture sensor was constructed by suspending a piece of string between two wires about 1 mm apart. As the string becomes wet, its electrical resistance decreases. This device is sensitive only to liquid water, not to water vapor.

In these tests, if there was any liquid water in the flow, there was a fine mist. Sometimes there were also larger liquid drops, large enough so that single drops could be seen with the unaided eye, but these were always accompanied by the mist.

It was found that the probe did not prevent liquid water from entering the region in which the steam thermocouple was supposed to sense only gas. When the moisture sensor was placed next to this thermocouple, it became wet only slightly more slowly than when it was outside the probe, in the unseparated air-water mixture. This difference in wetting rates may have been due only to a lower fluid flow rate inside the probe, caused by the flow resistance of the turbine blades.

This prototype probe does not satisfy the liquid-gas separation requirement, and is therefore unacceptable in its present form, for the flow conditions of this test. It seems safest to conclude that the liquid-gas separation aspect of the steam temperature probe needs further development work.

The flow resistance and thermal radiation sheilding aspects of this prototype steam temperature probe seem acceptable.

TABLE 1: FLOW RESISTANCE TEST DATA

Tube Inside Diameter (inches)	1.72	2.62
Flow Meter Reading	63½	154
Actual Flow Rate (ft ³ /sec)	0.348	0.843
Manometer Reading (inches of water)	5/16	1/8
Pressure Drop (psid)	0.0113	0.00451
Flow Resistance, R'	1.49	0.0905

Probe with Downstream Shroud Removed

Figure 1. Steam temperature probe.

Figure 2. Steam temperature probe.

SMALL DIAMETER, 200 PSI, 1100°F PRESSURE TRANSDUCER

T. C. Piper

Breeder reactors, where moderation is not required or wished, operate at temperatures to 1400°F enabling greater thermal efficiency. To minimize the fuel pin centerline temperature and to maximize the power/output per foot of reactor length, fuel pins as small as .230" diameter are used. In experiments run to determine rod failure mechanisms, several important parameters are measured. Of the various measurements, the internal pressure of each rod in the test is usually one of the most important. The requirement that the response be fast, that the measurements be made on each of several adjacent rods, and that no significant flow blockage occur leads to the need for a .230" diameter pressure transducer. The transducer described is .230" diameter and it performs well at temperatures to 1100°F.

Figure 1 shows the basic components of the eddy current read-out, and Inconel 718 bellows. The right hand tube is welded, in use, to the fuel pin, and internal pressure causes the bellows length to grow about 10 mils per 200 psi. The two coil balanced eddy current system utilizing a constant current 100 kHz bridge drive senses the distance of the copper target attached to the bellows from the front of the sense coil. The sense coils are wound on a ceramic spool ground from high density Al_2O_3 . Figure 2 shows the coil form with the two coils and the copper dummy target in place.

Results of testing the assembled transducer gave quite close to linear output versus pressure and a zero shift of .015% of f.s. per degree Fahrenheit. Full scale output was 5 volts at 200 psi for the electronics used. Above 1100°F the electronics continued to function properly even at 1300°F but the Inconel 718 bellows exhibited creep properties whenever any pressure was applied to it. Work continues to develop a bellows useful to 1400°F.

Figure 1: The Basic Components of the Eddy Current Read-out.

Figure 2: Eddy Current Coil Assembly.

HIGH TEMPERATURE MAGNETIC TURBINE PICKUP

T. C. Piper

Need for small turbine flowmeters that can be operated submerged in water at 650°F in the presence of nuclear radiation frequently occurs in the instrumentation of nuclear fuel rod tests. The typical 650°F, 2250 psi pressurized water environment naturally precludes use of epoxy and similar types of hermetic seals. The magnetic pickup described utilizes ceramic insulation, stainless steel sheathed cable, and high temperature braze and TIG welding sealing techniques.

Figures 1 and 2 illustrate respectively the individual parts and the completely assembled magnetic pickup. The coil spool is sand-blasted and sprayed with Al_2O_3 by the Rokide process. Ceramic insulated wire fired to 1500°F and held in place with ceramic cement holds a coil which is nearly immune to radiation and completely capable of long term operation at 650°F. The magnetic field on the coil to detect changes in magnetic flux with turbine blade passage is established by an AINICO V magnet.

Results with this pickup have been good. Although use of the relatively thick ceramic insulation on the coil wire preclude large pick-up output due to the relatively small number of coil turns (560), good isolation of the output from ground allows electrical amplification of the signal with no problem with background noise.

Figure 1. Individual Parts of Magnetic Pickup

Figure 2. Assembled Magnetic Pickup

DRAG-DISK WITH INSENSITIVITY TO PRESSURE AND TEMPERATURE TRANSIENTS

T. C. Piper

In the Pressurized Water Reactor (PWR) industry, considerable interest is presently centered on the amount of core damage that may result from the loss of fluid by a large coolant leak. Naturally, emergency core coolant (ECC) is intended to prevent or at least minimize the damage. Experimental tests with measurement of coolant velocity, mass flow, etc., are presently carried out in large numbers in different configurations to verify computer codes written to predict the consequence of line rupture at various locations. Transducers used to measure fluid velocity, pressure, density momentum flux, temperature, etc., thus, must be designed to give legitimate data while the ambient is changing rapidly. The drag-disk is often used to measure momentum flux, ρv^2 , of the fluid passing it. The only commercially available drag disk utilizes the pressure boundary as the drag restoring force element. A unit such as this ranged to small full scale values of ρv^2 (~100 to 200 lb ft²/sec²) suffers so much pressure and temperature sensitivity offsets during loss of coolant that its output is of little value. The unit described below, when properly installed, largely eliminates pressure and temperature sensitivities.

Figures 1 and 2 illustrate a 2000 ρv^2 unit in pieces and assembled respectively. A torsion bar drag disk restoring force gives the unit insensitivity to pressure changes. The special alloy torsion bar and a water cooled temperature compensated variable reluctance transducer⁽¹⁾ (VRT) gives the unit insensitivity to temperature changes. The VRT axis is oriented such that it is perpendicular to a line drawn from the torsion bar to the mid-point of the VRT so to first order there is no transverse motion of the core. The unit is assembled carefully so that the only point of contact of the drag-disk, arm, and VRT-core with the body is the location of the weld of the torsion bar to the body. With no water inside the unit, the drag-disk assembly freely oscillates for several cycles in the body mount when set into motion. Water, naturally, severely dampens this resonant motion. The one-inch diameter shank of the body is inserted through a drilled out one-inch Swedge Loc mount on a pipe such that the drag-disk is centered inside the pipe.

Results with the unit have been very good when the unit is placed in a horizontal pipe from the bottom side so there is no tendency for convection currents to develop between the 600 water in the pipe and the colder water in the water cooled portion of the transducer. No pressure sensitivity is evident, and about .7% of full scale change in null position occurs as the water in the test pipe is heated to 600°F.

(1) T. C. Piper and J. B. Colson, Internal Report (November 1973).

Figure 1. Individual Parts of Drag Disk

Figure 2. Assembled Drag Disk

STRAIN GAGE "SWITCH" FOR PWR ENVIRONMENT

J. D. Schmutz

There is often a need to sense position of components in a pressurized water reactor (PWR) environment. This information is used both for control and for measurement of reactor phenomena. The position sensing device must be stable with temperature and pressure and must resist the corrosive effects of the hot water. In addition, it must provide a positive unmistakable signal to the outside world. A sensor with these properties has been developed for use in the Power Burst Facility (PBF) thermal swell accumulators (TSA's).

Each TSA consists of a large cylinder containing a free-floating piston. One side of the piston is in contact with the loop coolant, nominally 600°F and 2250 psi water, and the other side is exposed to nitrogen. The piston is sealed by O-rings. In normal operation the nitrogen pressure keeps the piston against a stop at the loop coolant end of the vessel. In this position, a set of valves bleeds the space between the O-rings to remove water or nitrogen leaking past the seals. During a thermal transient, when the loop water swells, this piston is forced toward the nitrogen end of the vessel, thus absorbing the thermal swell. It was necessary to develop a system for controlling the bleed valves - to open them when the piston is on the stop, and to close them at other times.

The piston position monitor (PPM) that was developed consists of a sensor in the TSA and a signal conditioning unit. The sensor is a compound leaf spring of Inconel 718 mounted so that the piston deflects it about $\frac{1}{2}$ -inch when at the stop (see Figure 1). The leaf spring is instrumented with an Ailtech weldable strain gage. When the leaf spring deflects, the strain gage produces a signal. The signal conditioner block diagram is shown in Figure 2. It consists of a power supply for the strain gage with bridge completion and balancing network, an amplifier, an active filter, and comparators. The strain gage signal is amplified and noise is removed by a low pass active filter. The filtered signal is compared to a set point, and if it is above the set point, a relay is activated to open the bleed valves. A second comparator has two set points which set a band just larger than the normal signal range of the strain gage. If the gage fails and produces a signal either too high or too low to be normal, a relay is activated to turn on an annunciator that warns of the abnormal condition.

Both parts of the system were rigorously tested. The leaf spring was cycled through its full range deflection in excess of ten thousand times, about half of those cycles being made at or above 600°F and 2200 psi in the autoclave. The signal conditioning unit was used to monitor the leaf spring test, and was subsequently tested in an environmental chamber at temperature extremes from 50°F to 140°F and humidity to 95%. Through all of these tests the entire system performed according to the design requirements, switching the valve control relay within 1 sec after

the leaf spring strain passed the set point.

Two systems have been installed in the two TSAs at PBF and will shortly undergo installation tests prior to being placed in operation.

In summary, a system for detecting position in the PWR environment has been developed. The system employs a direct contact strain indicating sensor and operates reliably through the range of pressure and temperature encountered in PWR coolant.

Figure 1. Leaf spring sensor for piston position monitor, shown in both strained and unstrained states.

Figure 2. Block diagram of piston position monitor signal conditioning electronics.

FOUR TUNGSTEN ALLOYS FOR USE AS ULTRASONIC THERMOMETER SENSORS

A. E. Arave

Design of the high-temperature ultrasonic thermometer transducer and sensor for the Loss-of Fluid Test (LOFT) and Power Burst Facility (PBF)⁽¹⁾ reactors at the Idaho National Engineering Laboratory (INEL) was conducted in 1969 and 1970. In 1972 an ultrasonic thermometer was provided by Aerojet Nuclear Company for a Westinghouse Hanford Irradiation experiment.^(2,3) In 1973 and 1974, development of the ultrasonic thermometer was continued in support of fuel rod centerline temperature measurements for the PBF in-pile experiments.

Use of an ultrasonic thermometer sensor up to 2,700°C requires the use of rhenium, tungsten, an alloy of these materials alloyed with thorium. Four candidate materials for use as ultrasonic thermometer sensors were selected for a comparison test to determine some design parameters: (a) tungsten, (b) tungsten-1% thorium, (c) tungsten-2% thorium, and (d) tungsten-26% rhenium. Four parameters were checked: (1) temperature sensitivity, (2) signal attenuation as a function of temperature, (3) temperature sensitivity as a function of frequency, and (4) relative signal attenuation as a function of frequency.

The ultrasonic thermometer (UT) utilizes the temperature-dependent ultrasonic propagation velocity in a wire thin sensor as a temperature transducing mechanism. Since the propagation velocity is temperature dependent, the device can be calibrated and used as a thermometer. Reflections of ultrasonic pulses that travel a known distance are used to determine the average propagation velocity in the wire. In actual practice reflection of the ultrasonic waves occurs from the discontinuity where the sensor wire is attached to the lead-on wire and from the end of the sensor wire. Sensor length is normally about two inches, and thus the average temperature over this length is measured. A functional diagram of an ultrasonic thermometer and associated temperature-dependent signal is shown in Figure 1.

Some important design parameters for tungsten alloy sensors have been defined by this collection of UT data. Table I lists some of the constants defined. The following conclusions can be drawn from these data.

- (1) Tungsten-2% thorium exhibits very little change in attenuation over the temperature range 20° to 2700°C. On the other hand, tungsten-26% rhenium exhibits a large increase in attenuation above 1600°C.
- (2) Tungsten-26% rhenium has a larger temperature sensitivity than tungsten-2% thorium.

- (3) Tungsten-2% thoria has about the same temperature sensitivity as tungsten.
- (4) The attenuation and temperature sensitivity for all the materials is not a strong function of frequency over the range considered.

-
- (1) A. E. Arave and R. H. Meservey, Internal Report (August 1970).
 - (2) L. A. Lawrence, F. E. Panisko, and J. A. Christensen, Engineering Test Plan Measurement of Fuel Center Temperature, W/FFTF/72260, HEDL, Richland, Washington (December 1971).
 - (3) A. E. Arave, Internal Report (October 1972).
 - (4) A. E. Arave, Internal Report (June 1975).

Figure 1. Diagram of ultrasonic thermometer and associated temperature-dependent signal.

TABLE I

Summary of UT Temperature Sensitivity Data Versus Material and Frequency

Frequency and Temperature Range ($\Delta^{\circ}\text{C}$)	Material and Figure Number							
	$\Delta V_p / \Delta^{\circ}\text{C} \times 10^{-3} \text{ } \mu\text{sec}/^{\circ}\text{C}$							
	W	Fig. No.	W-1% ThO ₂	Fig. No.	W-2% ThO ₂	Fig. No.	W-26% Re	Fig. No.
<u>800-1,600$^{\circ}\text{C}$</u>								
160 kHz	3.3	21	3.1	24	3.3	27	4.3	30
250 kHz	3.5	22	3.2	25	3.2	28	3.6	31
320 kHz	3.0	23	3.1	26	3.2	29	4.3	32
<u>1,600-2,300$^{\circ}\text{C}$</u>								
160 kHz	4.9	21	5.7	24	5.1	27	6.1	30
250 kHz	5.0	22	5.6	25	5.1	28	6.1	31
320 kHz	5.1	23	6.0	26	5.2	29	6.5	32
<u>2,300-2,800$^{\circ}\text{C}$</u>								
160 kHz	7.6	21	7.4	24	8.1	27	11.8	30
250 kHz	7.9	22	8.0	25	8.5	28	11.8	31
320 kHz	7.9	23	8.5	26	8.0	29	11.3	32

ZIRCALOY-TO-STAINLESS STEEL THERMOCOUPLE SPLICE

S. C. Wilkins, J. D. Schmutz

Zircaloy-sheathed fuel rod cladding thermocouples have been spliced to stainless steel-sheathed thermocouple extension cables for use in a pressurized water environment. The use of stainless steel-sheathed extension cable facilitates reactor penetration through a stainless steel braze plug. The more expensive Zircaloy-sheathed cable is then used only for direct attachment to the Zircaloy fuel rod cladding.

The sheaths of the two types of thermocouple cable are spliced by means of an intermediate sleeve machined from an explosion-bonded titanium/Inconel block. The Inconel end of the splice sleeve is welded to the stainless steel cable sheath with a series of overlapping spots from a pulsed laser, extending completely around the circumference of the thermocouple cable. Likewise, the titanium end of the splice sleeve is welded to the Zircaloy cable. Figure 1 shows a sample of a completed sheath splice prior to autoclave testing. Samples have been autoclaved at 650°F (343°C) and 2500 psi (170 atmospheres) in water for periods up to 1000 hours without evidence of leakage or corrosion. Such splices have been used successfully in-pile in the Power Burst Facility (PBF).

The difficult transition between incompatible materials utilizes an intermediate sleeve of two explosively bonded materials. The titanium/Inconel explosion-bonded sleeve is laser-welded at its ends to the Zircaloy cable and the stainless steel cable, respectively. Such splices have been used successfully in-pile in a pressurized water environment in the Power Burst Facility.

Figure 1. Completed Zircaloy-stainless steel thermocouple sheath splice, utilizing explosion-bonded titanium/Inconel splice sleeve. The Zircaloy/titanium laser weld is at the left end of the sleeve, and the Inconel/stainless steel weld at the right end.

LASER WELD ATTACHMENT OF ZIRCALOY-SHEATHED
THERMOCOUPLES TO ZIRCALOY FUEL ROD CLADDING

S. C. Wilkins

The accuracy with which a temperature measurement can be made with a thermocouple depends in part upon the extent to which the measuring junction of the thermocouple is an integral part of the substance whose temperature it is measuring. Fuel clad temperature measurements have been aided in the Power Burst Facility (PBF) by laser-welding the junction end of Zircaloy-sheathed thermocouples to the Zircaloy fuel rod cladding.

Intimate contact of the thermocouple measuring junction is achieved by this means and coolant flow under the measuring junction is prevented. Figure 1 shows a photograph of a sample laser-welded thermocouple attachment. The Zircaloy thermocouple cable is laid against the Zircaloy cladding and a series of overlapping spots from a pulsed laser made, using Zircaloy filler wire. The weld extends approximately $3/16$ inch (0.48cm) along both sides of the thermocouple sheath and around the junction tip.

Improved thermal contact is achieved by laser-welding completely around the junction end of a Zircaloy-sheathed fuel cladding thermocouple. The influence of coolant flow past the measuring junction is decreased, and a rugged attachment to the fuel rod results.

Figure 1. Photograph of Zircaloy-sheathed thermocouple measuring junction, laser-welded to Zircaloy fuel rod cladding. Approximately 10x.

IMPROVED TA/SST TRANSITION THERMOCOUPLE

S. C. Wilkins

Critical high temperature measurements require the use of reliable refractory thermocouples. Nuclear fuel behavior experiments in the Power Burst Facility (PBF) utilize tantalum/stainless steel transition thermocouples for many of the fuel centerline temperature measurements. Increased reliability in these instruments has been achieved by including a loose coil in each high temperature thermoelement to compensate for differential thermal expansion of the component materials.

A high-temperature thermocouple section consisting of a tantalum sheath of 0.062-inch (1.59-mm) outside diameter, high-fired BeO insulation, and stranded tungsten - 5% rhenium/tungsten - 26% rhenium (W5Re/W26Re) thermoelements. This section is spliced to a stainless steel-sheathed extension cable with compensating wires. A high failure rate was encountered during the initial calibration cycle of these instruments. The failures have generally been open circuits in the W5Re wire, the component with the smallest coefficient of thermal expansion. Accommodation for differential thermal expansion among the component materials has been made by using a 0.250-inch diameter splice sleeve which houses a loose coil in each W/Re wire. Each coil fits within a 1/16-inch diameter hole of a two-hole Al₂O₃ insulator. Figure 1 shows the component parts of the improved thermocouple prior to assembly. The thermoelements are brazed in the cut-out portion of the large Al₂O₃ splice insulator. Figure 2 shows a radiograph of the splice area after assembly, with the two coiled thermoelements within the splice insulator.

Calibration of these units has been conducted to 4000°F (2205°C) and has not experienced open circuit or shorting failures. In addition, the shift in calibration following the initial thermal cycle has been found to be less severe. A detailed study of this calibration shift has not been completed.

Tantalum-sheathed W5Re/W26Re thermocouples with BeO insulation have been fabricated which show great improvement in failure rate during calibration, when compared with previous instruments of the same type. The addition of expansion coils in each of the two high-temperature thermoelements has eliminated open-circuit failures during calibration cycles to 4000°F (2205°C).

Figure 1. Components of Ta/SST transition thermocouple prior to assembly. At the left is the stainless steel-sheathed extension cable, and at the right the tantalum sheath of the high temperature section. W5Re/W26Re wires have been inserted in BeO insulators. The thermoelement coils fit within the double bore of the Al_2O_3 splice insulator (note the cut-out portion), which in turn is housed in the stainless steel splice sleeve.

┌-----┐

THERMOCOUPLE CORRELATION FLOWMETER:
PRELIMINARY EXPERIMENTS IN SEMISCALE

G. D. Lassahn

One technique for measuring the flow velocity of a fluid is to measure a transit time, the time required for the fluid to travel some known distance. Transit time techniques require that the fluid have some sort of inhomogeneities which move with the fluid and which can be observed with appropriate sensors. A transit time is determined with a pair of these sensors, one placed a known distance downstream from the other. Because there may be noise present and because the characteristics of an inhomogeneity may change as it travels between the sensors, it may be necessary to use cross-correlation analysis to obtain the transit time. The cross-correlation curve calculated from the two sensors' signals will have a peak at the delay time equal to the fluid transit time. This cross-correlation analysis might be done either on line or after the experiment, from a tape recording of the sensors' signals.

Current interest is in a transit time system in which thermocouples are used to sense the passing of local temperature fluctuations. Experiments done so far use standard (not heated) thermocouples to sense naturally occurring temperature fluctuations. This work may be extended to include studies with heated thermocouples or studies with artificially introduced temperature fluctuations.

An experiment in the Semiscale Blowdown Facility was done using two pairs of thermocouples installed in the core, as indicated in Figure 1. These are 0.64 mm (25 mil), grounded junction, stainless steel sheathed, chromel-alumel thermocouples. Data was recorded from these thermocouples during two blowdown tests. The data were recorded on magnetic tape and later analyzed using a Time Data 100 system.

Some quite well-defined cross-correlation peaks have been obtained from some of the data (Figure 2). However, it is not certain that these peaks are velocity indicators. The signal conditioning circuitry is probably not optimized, and the information necessary for this optimizing is not contained in the available data. There is an intolerable amount of noise interfering with the thermocouple signals in most flow conditions.

Figure 2. Radiograph of the splice area of the fully assembled Ta/SSt transition thermocouple. The coiled thermoelements are within the double bore of an Al_2O_3 insulator.

Figure 1. Location of thermocouples in Semiscale core.

Figure 2. Power spectral density curves from tape channels 7 and 8, 1 to 11 seconds after the beginning of blowdown.

A CONDUCTIVITY SENSITIVE LIQUID LEVEL PROBE
FOR SEMISCALE TRANSIENT FLOOD TESTS

A. E. Arave

A conductivity sensitive liquid level probe similar to the LOFT probes (1) was designed for a Semiscale transient flood test. The probe was designed to monitor a 4 inch per second flood rate of a electrically heated semiscale core used to simulate a reactor core.

Three rows of flood holes in the protective tube are on one side facing away from the hot core (see Figure 1). The probe is designed to isolate each electrode chamber so that it floods and drains separately. The design has an 8 inch per second flood rate and a 5 inch per second drain rate.

With a 200 Hz signal applied to the probe electrode the electrode impedance was measured to be 666 ohms for tap water with a conductivity of 325 $\mu\text{mho/cm}$ and 6,666 ohms for distilled water with a conductivity of 8.35 $\mu\text{mho/cm}$.

The probe has an ID of .421 inches compared to .440 inches for similar LOFT probes. A varied electrode spacing was used. Thirteen electrodes has spacings from 4-1/2 inches at the bottom to 17 inches at the top.

The probe is currently installed in the Semiscale facility. No data have been accumulated yet.

(1) A. E. Arave, Internal Report, (January 1975).

Fig. 1 Semiscale Liquid Level Probe.

CROSS-ASSEMBLERS FOR MINICOMPUTERS

W. R. Myers, M. S. Cole, R. C. Davies, E. W. Killian, A. D. Bennett*

Several fast relatively small cross-assemblers and a source text (card image) editor, operating on an IBM-360 computer system, have been written for popular minicomputers to reduce software development costs and turn-around time where it is necessary or desirable to utilize the large system in support of minicomputer programming activities. The assemblers and editor are written in 360 assembly language using all optional instruction sets to maximize performance. Assemblers have been written for Digital Equipment Corporation PDP-8, 9, 11, and 15 computers, Data General Corporation NOVA series, and the Nuclear Data ND-812. The assemblers produce absolute (non-relocatable) binary output in punched paper format, full assembly listings, and (optionally) cross-reference symbol tables from standard format source text on card images. The text editor provides several operations to facilitate maintenance of source text in 360 data sets. The assemblers are variable in size depending on the number of user symbols; a typical assembly of a 3000 card program with 400 user symbols will require approximately 40 kbytes of 360 memory and 4 seconds of CPU time on a 360/75. The editor requires 32 kbytes and processes 3500 cards per second.

A large machine that is available for program preparation for small machines can reduce many of the frustrations inherent in the editing and assembly process. Assembly language assemblers are faster but perhaps harder to modify than the slower higher level language assemblers. We have found the BAL assemblers for the IBM 360/75 to be by far the most cost effective method of assembling absolute code for our minicomputers and, because of their "common" origin, they are relatively easy to maintain.

* Member of Programming and Analysis Branch, Technical Services Division.

A REMOTELY-CONTROLLED NUCLEAR PULSE-HEIGHT ANALYZER
FOR ENVIRONMENTAL MONITORING

E. W. Killian, R. A. Coates, R. J. Gehrke, R. L. Heath, W. R. Myers

Effective monitoring of effluent streams from nuclear plants is essential to assure safe operation and minimal impact on the environment. For several years, the Nuclear Physics Branch of Aerojet Nuclear Company has been developing systems to enable the quantitative assay of radionuclides through gamma ray spectroscopy with Ge(Li) detectors. In the last few years, a program to develop remotely-controlled spectrometer systems for effluent monitoring has evolved through several stages with a ultimate goal of achieving a reliable minimal-cost design suitable for commercial production on release of the design reports to the general public.

The operating of large nuclear installations involves significant inventories of radioactive materials. Effective monitoring of effluent streams to permit evaluation of potential hazards which might result from discharge of radioisotopes is a requirement for safe operation of such facilities. Programs are being conducted at the Idaho National Engineering Laboratory (INEL) to apply gamma-ray spectrometry to real-time isotopic monitoring of nuclear installations.

The development of such a system requires a reliable method of data accumulation remote from a larger computer system which has the responsibility for verification, analysis, and interpretation of the data. In designing such a system, three goals were established:

1. The data accumulation and transfer of data must be completely automated and under control of a central processor. The automation of the data transfer is essential for routine monitoring of a source. Manual manipulation of the large amounts of data is time consuming and error prone.
2. The remote system must be able to monitor and verify its own operation. Operation of gamma-ray spectrometers is subject to several types of problems which effect the quality of the data being acquired. Among them are power failures, gain and zero shifts, and other effects due to wide variation in the intensity of radiation incident upon the detector. The remote system should be able to detect these problems and report them upon command.
3. The remote system must be able to control external devices. Several applications of the remote system in an industrial environment require control of the source of data that is being acquired, such as the routing of gas or liquids from various parts of the plant to the detector. Moreover, if quantitative analysis is to be performed, the remote system has to be able to provide information from flow meters, pressure gauges, etc.

To accomplish these goals, a multiphase development schedule was established. The first hardware configuration served as a development and feasibility prototype in the effort to design an inexpensive integrated monitoring device. The system consists of a stripped commercial 4096-channel pulse-height analyzer, a detector system and an in-house developed remote control logic and modem interface. The control logic for the remote analyzer performs the same functions as the manual control switches on a multi-channel pulse-height analyzer. It receives and executes commands, transmits data or status by command from the central processor via telephone using a 1200 Baud asynchronous, half-duplex, auto-answer modem. The capability of this system was demonstrated by using it to collect about 100 spectra over a period of 800 hours of ATR operation.

The phase II spectrometer design includes a programmable (mini-computer) system at the remote end to provide extended capability in data reliability monitoring, optimized data formatting and communication, and additional remote functions. An existing PDP-8/e was utilized on a temporary basis to construct the prototype system to reduce the developmental costs. The standard PDP-8/e minicomputer is programmed for operation from read-only memory. The spectrometer is implemented as a 4096-channel analyzer with a capacity of over a million counts per channel. A 1200-baud telephone interface for transmission of data and receipt of control information, a precision multi-pulse generator for energy calibration and performance monitoring, and general-purpose digital interfaces for detection and control of auxiliary external events are included. Both hardware and software are modular to facilitate continued optimization. The Phase II remote analyzer is completely controlled from a central installation. Primary functions of the central controller include erase, start, stop and transmit, and read and set external devices. Transmitted data include elapsed and live time clocks, analyzer status, up to five windowed calibration pulse peaks, and the 4096-channel spectrum. All data will be transmitted in ASCII suppressed-zero format to provide a favorable compromise between data transmission time and a universally recognized data format.

The third phase in the development effort is to design a relatively inexpensive and reliable device, based on LSI and microprocessor technology, that is suitable for commercial production. A micro-processor prototyping, development, and debugging system has been acquired in this phase to support electronic design activities.

Use of the microprocessor development system in the design of the LSI/microprocessor version of the remotely-controlled analyzer is expected to reduce electronic design time by approximately 30%, component and fabrication costs by approximately 50%, and debugging and check-out time by similar values. The capabilities of the system permit incorporation into the design of a greater level of firmware substitution for traditional hardware functions.

A COMPUTERIZED COULTER COUNTER BLOOD ANALYSIS SYSTEM AT
JOHNSON SPACECRAFT CENTER

A. D. Bennett* , R. C. Davies, G. O. English

During manned spaceflights changes in red blood cell volume have been noted. As a result the Medical Directorate at NASA needed a method to quickly and accurately measure red blood cell volume distribution and to store and analyze the data. These analyses are useful in determining the reasons for the cell volume changes that occur during spaceflight.

The Coulter counter system is a real-time system written in a nested interrupt mode, allowing the user to execute a variety of tasks simultaneously. The system is designed to acquire data from the Coulter counter and to display the data as it is acquired. Peak areas, centroids, and other parameters may be calculated while acquiring data. When not acquiring data, previously acquired spectra stored on DECTape may be displayed and analyzed. The system is designed to store data on DECTape in the same manner that it would be stored had the data been acquired on the PDP-9 in NASA's RADIATION COUNTING LABORATORY. As a result, the blood cell spectral data may be analyzed on the PDP-9 using the versatile analysis routines developed for processing NaI gamma-ray spectra (1).

Basic hardware of the system consists of a PDP-8I, oscilloscope, DECTapes, teletype and Coulter counter.

* Member of Programming and Analysis Branch, Technical Services Division.

(1) R. C. Davies, R. S. Clark, J. E. Keith, RALPH-An Online Computer Program for Acquisition and Reduction of Pulse Height Data, ANCR-1103, (April 1973).

TEMPERATURE CHARACTERISTICS OF A SODIUM IODIDE DETECTOR WITH A LIGHT EMITTING DIODE

J. W. Mandler

It is well known that the output pulse amplitude from a NaI(Tl) detector varies with temperature. The observed effect is a combination of two components, one arising from the crystal and the other from the photomultiplier tube (PMT). Because of this temperature response, if a NaI(Tl) detector is to be used under varying temperature conditions it either must be stabilized in some manner (e.g., by keeping its temperature constant or by using a reference source to stabilize the gain of the system) or the system must be recalibrated frequently.

One method of stabilization which has recently been developed is to use the pulses produced by a light emitting diode (LED) as a reference source and keeping the amplitudes of the reference pulses constant by altering the gain of the system. The LED source has the advantages of giving a Compton-less peak with a resolution slightly better than an equal energy gamma-ray peak that can be varied in intensity and energy. It also has the capability of being turned on and off.

Since a NaI(Tl) system for bulk monitoring of soil that must operate under widely varying temperature conditions (about 40° F to 100° F) is currently being developed, the LED stabilization system is of interest. Discussions with the Bicron Corporation (a detector manufacturer that currently produces detectors containing LED pulses) indicated that these devices had been tested only in a limited temperature range under laboratory conditions. To date, primary interest has been in long term stability under laboratory conditions. Since the current application requires knowledge of the temperature characteristics in a much wider range, a 3 inch x 3 inch NaI(Tl) detector containing an LED pulser together with a Bicron type P-14 tube base and Bicron's Electric Gamma Source Driver Circuit was obtained on loan from the Bicron Corporation. This detector was temperature cycled from -18° F to +122° F.

The tests consisted of placing the detector which was plugged into the P-14 base in an environmental chamber with a collimated ^{88}Y source, adjusting the LED driver circuit so that the LED "gamma" peak fell between the two ^{88}Y peaks in the gamma-ray spectrum, and cycling the temperature of the chamber. The chamber temperature was varied slowly (less than 1° F per minute) so that the detector would not be damaged. At each temperature of interest the locations of the ^{88}Y and LED peaks were measured after letting the detector soak for a time sufficient to allow the temperature of the whole crystal volume to come to equilibrium with the chamber temperature. Experiments showed that if the chamber temperature was changed by 20° F, equilibrium would be attained in about 2.5 hours.

Using the known energies of the ^{88}Y gamma rays and the measured

peak positions, the energy equivalent of the LED "gamma" peak was calculated for each temperature. This parameter is of prime interest because its behavior with temperature will indicate how the behavior of the LED "gamma" pulse differs from that of a true gamma-ray pulse in NaI. For example, a constant (with temperature) energy equivalent would indicate that the LED "gamma" behaved the same as a true gamma ray.

During initial temperature cycling, considerable pulse height variation with temperature was observed - more than had been expected. Upon further investigation, part of this temperature effect was found to be due to the coupling capacitor in the P-14 tube base. The detector was removed from the P-14 tube base, a pulse (from an ORTEC 480 pulser located outside of the environmental chamber) fed onto pin 11 (the anode position in the bleeder resistor string), and the temperature varied. The temperature characteristics of the coupling capacitor was thereby measured. The coupling capacitor was then located outside of the environmental chamber and the temperature cycling repeated. This time temperature cycling produced no apparent effect. Therefore, for final temperature cycling of the detector, only the detector and bleeder resistor string were located in the chamber. The coupling capacitor together with the rest of the electronics (preamp, amplifier, LED driver circuit, multichannel analyzer, and high voltage supply) were located outside the chamber.

The results of the temperature cycling measurements are shown in Figures 1 and 2. Figure 1 contains a plot of the peak positions for the 1836 keV ^{88}Y gamma-ray and the LED "gamma" as a function of temperature. The arrows indicate the time sequence for which the temperatures were attained. Two features are obvious: (1) the room temperature gains before and after cycling are not the same (i.e., the curves are not closed). The net gain for the 1836 keV gamma-ray pulse shows a 12.9% decrease and the LED pulse exhibited a 9.9% decrease. This indicates that something happened to the gain at high and low temperatures and the system never recovered. (2) The shapes of the two curves are not the same. This indicates that the LED pulse does not have the same temperature characteristics as a real gamma-ray pulse.

Figure 2 shows a plot of the energy equivalent of the LED pulse as a function of temperature. Here again we see that the LED pulse does not have the same temperature characteristics as a real gamma-ray pulse (i.e., the energy equivalent is not a constant with temperature). Moreover, the room temperature values before and after cycling differ by about 3.3%.

We have not yet been able to explain what happened to cause the observed decrease in gain. All that is known is that for some as yet unexplained reasons the gain decreased and that the decrease in gain for the LED pulse was about 23% less than the decrease for the gamma-ray pulses. (This gain decrease was also evident with 898 keV gamma-ray pulse.)

As a result of these experiments, we conclude that, while the LED stabilization method may be satisfactory for small temperature changes that occur under laboratory conditions, it is not adequate for our purposes in the 40° F to 100° F temperature range. We do not know whether the observed behavior is characteristic of the LED device itself or just anomalous behavior of the particular detector we tested.

Fig. 1 Peak positions as a function of temperature.

Figure 2. Energy Equivalent of LED pulse as a function of Temperature

AN ULTRASONIC DETECTOR FOR MEASURING SMALL VOLUMETRIC
FLOW RATES AT THE CHEMICAL PROCESSING PLANT (CPP)

A. E. Arave

An ultrasonic detector was designed for use in conjunction with a transient time flow meter designed by Harry Deveroux in the Chemical Research and Engineering Branch of Allied Chemical Co. at Chemical Processing Plant in Idaho.

The need is for a flow meter to measure low volumetric flows of uranian acid used in processing nuclear fuel elements. Flows vary from 5 to 25 ml/sec in a 3/8" diameter tube. The accuracy required is .5% of reading.

The objective is to design an ultrasonic transducer to transmit and receive a 8 MHz ultrasonic signal across the ID of a 3/8" stainless steel tube. A change in the acoustical impedance of the fluid flowing in the pipe will cause a change in the amplitude of the received signal. By using two sets of transmitter-receivers the transit flow time between the two points can be measured for propagation time of a bubble in the fluid in the pipe. Figure 1 shows the configuration of the detectors and process instrumentation. Figure 2 shows the transducer design.

This measurement technique has not been reduced to practice yet. In laboratory tests, the accuracy is better than $\pm 1\%$. Tests in a mockup facility will be conducted in the near future.

Figure 1. Ultrasonic transit time flowmeter block diagram.

Figure 2: Photograph of the fitting and Piezoelectric crystals that make up the transmitt and receive transducers.

A PULSED EDDY CURRENT INSPECTION SYSTEM

M. E. Yancey

As part of the Light Water Reactor safety studies being sponsored by the Nuclear Regulatory Commission, Aerojet Nuclear Company is conducting inpile tests on irradiated and unirradiated fuel rods. During the tests the fuel rods are being exposed to a variety of off-normal and accident conditions.

A pulsed eddy current system developed by Argonne National Laboratory⁽¹⁾ was used as part of a system⁽²⁾ designed to completely characterize the fuel rod. The pulsed eddy current system provides four channels of information i.e. (1) wall thickness variation, (2) outer surface defect, (3) inner surface defects and (4) inner and outer surface defect. Defect and wall thickness calibration standards were prepared from typical fuel cladding material and used to optimize the systems performance for this application.

Figure 1 shows a portion of the data recorded from an irradiated fuel rod "835". This data shows an outer surface defect indication (A), an area of apparent surface corrosion (B) and wall thinning (C) in the area of the surface corrosion. The area of surface corrosion corresponds to the fuel rod area which was subjected to the maximum time average axial power distribution.

A metallographic examination⁽³⁾ was performed on several fuel rods to evaluate the performance of the pulsed eddy current system. The destructive examination provided reasonably good confirmation of defects detected in the non-destructive examination.

-
- (1) C. J. Renken and Allen Sather, Manual of Operations, ANL-7973 (November 1972).
 - (2) M. E. Yancey, E. H. Porter, H. R. Hansen, An Inspection System for Zircaloy Clad Fuel Rods, CI 1269, To Be Released.
 - (3) W. C. Francis, M. R. Martin, W. J. Quapp, G. W. Gibson, Internal Report.

Figure 1. A portion of the data trace from irradiated fuel rod "835".

D. PROGRAM SUPPORT

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

Test Reactor Operations Support

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

REACTOR CRITICAL ELECTRICAL LOAD TRANSFER ANALYSIS

B. G. Crooks

The Sodium Loop Safety Facility (SLSF) sodium pump, at present, has potentially four sources of power supplied by the Engineering Test Reactor (ETR) Electrical Distribution System. Two power sources are supplied by the commercial bus, one source is supplied by the emergency or diesel bus and one source is a battery backed motor generator set. It is vital that power from at least one of these sources be available during the operation of the SLSF In-Pile Loop to preserve the integrity of the experiment.

If commercial power is lost for any reason, automatic transfer switches actuate to transfer the SLSF sodium pump power source to the battery backed H Bus. This configuration constitutes the emergency mode of operation and was the subject of a fault current and breaker coordination study. The main objective of the study was to determine if the SLSF sodium pump and associated protective devices were properly coordinated with the ETR Electrical Distribution system while operating in the emergency mode. Further, the effects of transient conditions due to operation of load transfer devices or high motor starting loads on the H Bus were considered.

It was determined that, in general, the emergency 480 V system at ETR is adequately protected but is not optimally coordinated. Protective device settings encroach on each other and in some cases are set too high relative to the amount of fault current available. Diesel relay settings are not coordinated with series downstream devices. Actual breaker trip tests will have to be performed in order to ascertain present selective tripping capability.

Start-up of a helium circulator on Motor Generator Set A (MG-A) results in a momentary drop in E Bus voltage. During the initial phases of testing, the only adverse effect detected was the opening of the GH Bus tie breaker via the undervoltage relay on the E Bus. This resulted in the H Bus load being transferred to Motor Generator Set No. 1. This situation was corrected by adjusting the diesel governor to compensate for the starting load of MG-A.

The transient effects on the SLSF sodium pump and other H Bus loads, due to the automatic transfer of the G-H tie breaker are limited to the response time of the field regulating circuit of MG-1 in going from an unloaded to a loaded condition. The response time is placed at less than 50 msec and appears to be no problem.

The ability of the H Bus to accept and maintain the additional load equivalent to the SLSF configuration has been demonstrated under actual tests. This test included verification of the G-H tie breaker transfer ability and established that battery bank No. 1 had sufficient capacity to supply this load for a minimum of 30 minutes.

CRITICALITY OF HOT CELL TRANSFER CASKS

T. E. Young

Criticality calculations were performed for various loadings of ETR and ATR elements in the hot cell carriers (White Elephants #2 and #3).

Calculations of the multiplication factor (k_{eff}) were made using the SCAMP⁽¹⁾ SN transport code, with four neutron groups. All constants required as input to SCAMP were calculated from the ENDF/B data files using the spectrum averaging codes PHROG⁽²⁾ and INCITE⁽³⁾. Calculations are conservative because of two assumptions: (1) the elements contain no boron; and (2) the elements and casks are of infinite length. Calculations were made for both voided and water-filled casks.

With the assumptions in the above paragraph, the highest values of k_{eff} were for two 7F-ATR elements in the water-filled Cask #2 ($k_{eff} = 0.755$), two 7F-ATR elements in the water-filled Cask #3 ($k_{eff} = 0.712$), and two ETR elements in the water-filled Cask #2 ($k_{eff} = 0.849$). (Two ETR elements in Cask #3 will have a lower k_{eff} than two ETR elements in Cask #2 because of the effect of the lead reflector and the difference in metal-water ratio.)

-
- (1) G. E. Putnam, J. B. Fussell, and C. L. Beek; Private Communication.
 - (2) R. L. Curtis, et. al., PHROG - A FORTRAN IV Program to Generate Fast Spectra and Average Multigroup Constants, IN-1435, (April 1971).
 - (3) R. L. Curtis and R. A. Grimesey, INCITE - A FORTRAN IV Program to Generate Thermal Neutron Spectra and Multigroup Constants Using Arbitrary Scattering Kernels, IN-1062, (November 1967).

TRA FUEL STORAGE

R. R. Jones, J. H. Lofthouse

A safety evaluation, including criticality calculations, has been performed to expand the scope of the Preliminary Safety Analysis Report for the Test Reactor Area unirradiated enriched uranium fuel storage facilities.⁽¹⁾ With this additional analysis, it is intended that ANC's required fuel storage which is now in several areas, will be consolidated in the present fuel storage facilities at TRA. Only limited modifications are required to these facilities, resulting in effective cost savings. This SAR is being prepared to comply with "Criteria for Storage of Unirradiated Enriched Uranium" issued by the U. S. Atomic Energy Commission, Division of Construction, May 10, 1972.

The previous safety analysis⁽¹⁾ provided limits and safety margins for storage of ATR and ETR fuel elements, fuel element plates and odd lot material (other than fuel elements). Expanding on the original safety analysis, provides for the efficient storage of UO₂ fuel rods and pellets in the existing ATR and ETR fuel racks at TRA with only minor modifications to the racks. The UO₂ rod calculations were performed to increase the storage limit of these rods over that of odd-lot material. Criticality calculations were performed to determine safe storage limits for UO₂ rods of various diameters and U-235 enrichments to 93%. All degrees of moderation were evaluated to provide safe storage limits in the event of flooding, or spraying caused by fire suppression activities. The most reactive rod storage configurations were evaluated. The evaluation also provided for establishing storage limits for UO₂ pellets when these pellets are confined to rod configuration and stored with moderator material. The calculations were performed using the Monte Carlo computer code KENO-II, Version 5, with Hansen-Roach 16-group cross-section set.

The ATR and ETR fuel storage racks in the TRA storage vaults are cadmium poisoned and are of two construction types. One type of construction incorporates only wood moderator and the other includes wood and polyethylene. These racks were evaluated for fire safety considerations and criticality.

With the storage limits established in the evaluation both types of racks were found to provide safe storage with their present construction materials provided quick response fire detector systems and automatic fire sprinkler systems are installed in the storage vaults.

It is intended that the expansion of the evaluations for the Preliminary Safety Analysis Report⁽¹⁾ for the TRA unirradiated fuels storage facilities will result in considerable cost savings in upgrading the ATR, ETR and #2 vaults to meet ERDA and Aerojet Nuclear Company requirements. These savings will come from not requiring extensive modification or addition to the present fuel storage racks. Also, fuel material now stored in other facilities, particularly UO₂ rods at PBF, can be consolidated at TRA, thus eliminating a detailed safety analysis and upgrading costs of those facilities.

(1) R. R. Jones, J. H. Lofthouse, Nuclear Technology Division Annual Progress Report, ANCR-1177, (1974), 209.

REACTOR PHYSICS CALCULATIONS IN SUPPORT OF THE ETR TECHNICAL SPECIFICATIONS

J. E. Brasier, A. W. Brown

Two-dimensional neutron diffusion theory calculations were made for the Engineering Test Reactor (ETR) and the Engineering Test Reactor Critical Facility (ETRC). These calculations provide a technical basis for the ETR Technical Specifications document. This document identifies credible reactor accidents, provides analysis of the associated consequences, and specifies guidelines for safe operation of the ETR. Some 2-D calculations were also compared to measured ETRC data to verify the accuracy of the analytical models. Different PDQ analytical models were set up for each reactor due to physical dissimilarities in reflectors, core filler blocks, shim guide tubes, control rod poison sections, grid spacing, and moderator temperature.

ETR data were calculated for discrete time steps at a power of 175 MW from beginning-of-core life to 20 days of operation. At each time step, these data included core power distributions, neutron generation lifetimes, delayed neutron fractions, eigenvalues (used to calculate critical rod positions at that particular time step), and void coefficients. Individual and ganged control rod worths for several rod configurations were also calculated for some of the time steps.

ETRC benchmark data (consisting of core power distributions and void coefficients) were calculated at xenon equilibrium conditions and then compared to ETRC measured data. In general, comparisons of ETRC measured and PDQ calculated data were very good.

The two-dimensional calculations for the ETR and for the ETRC benchmark problems utilized the PDQ-7⁽¹⁾ diffusion theory code in four energy groups, the PERP⁽²⁾ perturbation code, and the detailed core models described in two spacial dimensions at an "average" horizontal plane through the core. The vertical direction was approximated by using a core buckling. The ETR model used a larger mesh than the ETRC model due to dissimilar reflectors. The SLSF loop was described in considerable detail, with less detail for other core and reflector components.

Diffusion-theory cross sections were obtained with the PHROG⁽³⁾ fast-spectrum code and the INCITE⁽⁴⁾ thermal-spectrum code. The SCRABLE⁽⁵⁾ code was used to obtain hafnium resonance cross sections. The SCAMP⁽⁶⁾ one-dimensional multigroup (26 groups) transport code was used along with the MONA⁽⁷⁾ code for highly absorbing regions and collapsed to the 4-group structure before use in the PDQ calculations. Vertically averaged cross sections were obtained for regions with large variations in the vertical direction. Microscopic cross sections were used in fueled regions of the cores in order to study ETR core behavior with fuel depletion. Thermal-group self-shielding factors were obtained from multigroup cell problems with the SCAMP code.

Figure 1 compares the PDQ calculated and ETRC measured power distribution at xenon equilibrium conditions. Xenon poisoning in the ETRC is simulated by uniformly inserting boron-impregnated plastic wands into the coolant channels of fuel elements and control rod fuel sections. The ETRC core contained fourteen 6-inch-long hafnium tailoring devices around the SLSF loop near reactor midplane and also, aluminum strips were placed in predetermined fuel coolant channels to simulate voids. As shown, the calculated power is, in general, low around the SLSF loop and high away from the SLSF loop which is probably due to the method used to represent the tailoring devices in the two-dimensional calculations. The PDQ calculations apparently give distributions which are more nearly representative of the power at the reactor midplane where the poison sections of the tailoring devices are located, rather than vertically averaged power distributions.

Table I compares PDQ calculated and ETRC measured reactivity values when the aluminum void simulators are inserted into the fuel coolant channels to simulate voiding. The calculated reactivity values are in general about 15% more negative than the measured values and agree with the measured values quite well in spite of calculational difficulties such as:

- (a) mesh not fine enough to allow precise location of void simulator,
- (b) the calculated power distribution is slightly different from the measured power distribution, and
- (c) no change was made in the thermal self-shielding factor of the fuel meat from the case with aluminum strips to the case with water in the fuel coolant channels.

The neutron generation time, Λ , was computed at each time step by using an absorption perturbation equal to $1/v$ in each energy group and each region of the reactor. The effective delayed neutron fraction β was also computed at each time step by using a perturbation to the neutron yield in each energy group of each fueled region equal to βX_d^g , where β is the unweighted delayed neutron fraction (taken as .0065) and X_d^g is the fractional yield of delayed neutrons in group g . The use of four-group perturbation theory to obtain β does not adequately account for neutron spectral effects. However, ETR measured β/Λ ($185 \pm 4 \text{ sec}^{-1}$) compares very well with the PDQ calculated value of 182.2 sec^{-1} .

In general, comparisons of PDQ calculated and measured reactor physics data were in good agreement even though refinement of the calculational models is obviously necessary in certain core regions.

REFERENCES:

1. A. W. Brown et. al., Summary of PDQ-7 (IBM-360-370 Version) Input Data Requirements and Operating Procedures, ANCR-1061 (March 1972).
2. G. E. Putnam, Private Communication, (December 1974).
3. R. L. Curtis, et. al., PHROG - A Fortran IV Program to Generate Fast Neutron Spectra and Average Multigroup Constants, IN-1435 (April 1971).
4. R. L. Curtis, et. al., INCITE - A Fortran IV Program to Generate Thermal Neutron Spectra and Multigroup Constants Using Arbitrary Scattering Kernels, IN-1062 (November 1967).
5. F. J. Wheeler, Private Communication, and P. H. Pier, et. al., RABBLE, A Program for Computation of Resonance Absorption in Multigroup Reactor Cells, ANC-7326 (April 1967).
6. J. B. Fussell, Private Communication, (August 1970) and C. L. Beck, Private Communication, (May 1968).
7. G. E. Putnam, MONA-A Multigroup One-Dimensional Neutronics Analysis Code, ANCR-1051 (March 1972).

TABLE I

REACTIVITY WORTH OF ALUMINUM VOID SIMULATORS IN ETRC

Position	Channel	Measured Reactivity (β)	Calculated Reactivity and Problem Number		
			1 (β)	2 (β)	3 (β)
K12	3	-.78	-.74	-.77	-.78
K12	16	-.59	-.52	-.52	-.54
L5	3	-1.12	-.93	-.99	-.95
L5	16	-1.93	-2.52	-2.52	-2.40
L9	3	-1.47	-1.25	-1.16	-1.12
L9	16	-2.04	-1.88	-1.93	-1.87
J5(S#6)	3	-.31	-.34	-.36	-.34
J5 (S#6)	13	-.67	-1.19	-1.19	-1.15
G7	3	-1.52	-2.09	-2.09	-2.04
G7	16	-1.36	-1.60	-1.62	-1.62
I7	3	-2.20	-2.67	-2.75	-2.67
I7	16	-1.91	-2.10	-2.18	-2.12
M7	3	-2.19	-2.98	-2.94	-2.80
M7	16	-2.09	-2.87	-2.79	-2.66
M9 (S#11)	3	-1.19	-1.57	-1.58	-1.52
M9 (S#11)	13	-1.14	-1.88	-1.90	-1.83
E10	3	-.09	-.07	-.08	-.08
E10	16	-.16	-.20	-.20	-.22
H10	3	-1.46	-1.89	-1.89	-1.92
H10	16	-1.26	-1.57	-1.58	-1.67
E11 (S#12)	3	-.009	-.12	-.12	-.14
E11 (S#12)	13	-.003	-.05	-.06	-.05
N11	3	-1.82	-2.43	-2.42	-2.34
N11	16	-.92	-.87	-.85	-.82
I13	3	-.78	-.97	-.96	-1.20
I13	16	-.27	-.30	-.29	-.42

Top: ETRC Measured Percent of Core Power (Reference d)

Middle: ETRC PDQ-Calculated Percent of Core Power(Problem AWB204)

Bottom: Fractional Difference = (calc-meas.)/meas.

Figure 1. ETRC calculated versus ETRC measured percent core powers at xenon equilibrium conditions.

EXPERIMENTAL TECHNICAL SUPPORT FOR THE
ETR REQUALIFICATION TESTS

W. Serrano, D. W. Knight

The startup of the ETR with the SLSF core configuration was monitored by personnel from the Reactor Experiments Section. Each Nuclear Requalifying test, labeled NT-1 through 5, had specific objectives and required technical support as follows:

NT-1: The objective for the test was to load the reactor with fuel and make the reactor critical. A fuel charge was selected whose overall characteristics were nearly identical to those of the fuel used for SLSF reactor physics measurements in the ETR critical facility. A critical rod position was predicted with consideration of the built-in reactivity difference between the ETR and ETRC and the neutron poison that has formed in the beryllium reflector during the two-year shutdown. The predicted critical position for the NT-1 core was 6 inches on the 5-9-14-15 control rod bank. The actual position was at the upper limit of the 6-12 control bank resulting in an error of 0.23\$. The approach to critical was monitored using inverse multiplication techniques. The resultant data followed the predicted data quite accurately. A ten-wire flux run was also made in the ETR during the NT-1 test for preliminary calibration of the ETR's nuclear instrumentation. Data from the ten-wire flux run indicated the ETR was at a power level of approximately 316 watts. Thus, a preliminary calibration of the Log-N and level recorders was made.

NT-2: The primary objectives for the NT-2 test were to:

1. Make a flux run in the ETR for a power distribution comparison between the ETR and the ETRC.
2. Irradiate silver wires at 3000 watts for more precise calibration of the reactor's instrumentation.

The ETR core with the P-1 fuel was loaded with uranium activation wires attached to aluminum wands. The 20-minute flux run was to be made at a predicted reactor power of 3000 watts based on the power calibration from NT-1. The actual power was calculated to be 3039 watts. The power distribution comparison will be made after obtaining the ETRC power distribution data. Silver wires were irradiated during the NT-2 flux run for additional nuclear instrumentation calibration. A linear relationship is assumed between the silver wire activation and the reactor's power level. This calibration provided a basis for the NT-3 test.

NT-3: The primary objective for NT-3 was to calibrate the nuclear instrumentation at a power level of N_L . Silver wires were again irradiated at a reactor power of approximately N_L . The Log-N and level recordings expected at N_L were predicted using the calibration data from NT-2. The silver wire activations from NT-3 were compared to the corresponding data from NT-2 providing instrument calibration at N_L .

NT-4: The primary objective for NT-4 was to measure reactivity worths of four safety rods and to determine β/λ from the neutron noise spectrum. With the reactor at $\sim N_L$ (based on the NT-3 calibration data) the control rod worths of four safety rods were determined using rod drop techniques. Preliminary data was obtained with a reactivity meter while more refined worths will be calculated using inverse kinetic techniques. Preliminary results for the control rod worths approach the predicted values with one exception. The deviation for the single rod can be partially explained by the fission chamber location with respect to the rod location.

The preliminary value for β/λ is 185 sec^{-1} . A better value will be obtained using computer curve fitting techniques.

NT-5: The primary objective of the NT-5 test was the qualification of ETR for power operation. A "getter" core replaced the P-1 core for the NT-5 tests. A substitute loop designed by the ETRC Group was used. The core was operated at several power levels up to 80 MW. Neutron noise measurements were made at several power levels as a reference for future ETR operations and to monitor reactor stability as the reactor power was increased.

THE NUCLEAR KINETICS ANALYSIS FOR THE ETR TECHNICAL SPECIFICATIONS

W. R. Carpenter

This analysis was performed using the PARET Neutron Kinetics Code. The procedures employed can be divided into three steps:

- (a) Setup and checkout of the ETR core kinetics model.
- (b) Determination of model sensitivity to the various kinetics input parameters.
- (c) Determination and analysis of the damage parameters for the postulated ETR faults.

During the model setup, no unusual occurrences were experienced. Most of the input data were experimentally determined in ETRC. When a choice of data existed, the data which would provide the most conservative results were always chosen. All of the input data were subsequently subjected to calculational verification by the Reactor Technology Branch Reactor Physics Section. During checkout of the model, several reactivity oscillations were observed on the back side of the power burst. Analysis of the PARET output showed these oscillations to be caused by sudden and complete collapse of all voids in the nucleate boiling regime. Several attempts to eliminate this phenomenon were unsuccessful and, finally, all subcooled voiding was disallowed. In view of the care exercised in the model setup, such a drastic cure was unfortunate. However, the ultimate result is a very conservative estimate of the ETR damage parameters.

Nothing surprising was encountered in the sensitivity study. The standard, or reference, burst was chosen to be a \$1.25 step insertion at an initial power of 175 MW. As would be expected, the calculated ETR burst characteristics are more sensitive to changes in those parameters appearing directly in the neutron kinetics equations (λ , β_{eff} , ρ) than those parameters of a more indirect nature such as power distribution and reactivity weighting.

In the ETR fault analysis for the three fault categories (anticipated, unlikely, unlikely faults) the following results were obtained:

(a) Anticipated Faults. It was found that the damage parameters (power, integrated power) calculated for those postulated events falling within the definition of anticipated faults are conservatively bounded and predicted by ramp reactivity addition rates of up to 18¢/sec, or a step reactivity addition of 22¢.

(b) Unlikely Faults. It was found that the damage parameters calculated for those postulated events falling within the definition of unlikely faults are conservatively bounded and predicted by ramp reactivity addition rates of up to 25¢/sec, or a step reactivity addition of 75¢ followed by immediate experiment cascading of an additional 25¢.

(c) Extremely Unlikely Faults. It was found that the damage parameters calculated for those postulated events falling within the definition of extremely unlikely faults are conservatively bounded and predicted by ramp reactivity addition rates of up to 35¢/sec, or a step reactivity addition of \$0.95 followed by immediate experiment cascading of an additional 25¢.

All damage parameters were within acceptable limits for the respective fault categories.

NEUTRON NOISE MEASUREMENTS FOR THE REQUALIFICATION OF ETR

D. R. Chick

During the requalification of ETR, neutron signals were recorded on magnetic tape. At a power level of N_L , signals from a compensated ion chamber and a fission chamber were recorded and analyzed to determine β/λ . At N_L , 10 MW, 20 MW, and 40 MW signals were recorded from Level 2 and Level 3. These signals were analyzed on the TIME/DATA 100. Power spectral density (PSD) and cross power spectral density (CPSD) plots were made and analyzed. The plots did not indicate any stability problems. The data obtained and analyzed at the 60 MW power level indicated no instability. The data obtained and analyzed at the 80 MW power level indicated no instability.

Neutron noise signals were recorded on magnetic tape during the requalification of the ETR. Data were taken from neutron level channel No. 2, neutron level channel No. 3, a temporary ion chamber and a temporary fission chamber. These signals were subsequently analyzed on the Time/Data 100 computer to provide power spectral density (PSD) and cross power spectral density (CPSP) results. The spectral composition of the temporary channel data at zero power was used to determine the reactor kinetics parameter β/λ . The spectral composition of the level channel data was used to evaluate reactor stability as the reactor power was slowly escalated to full rated power. Level channel data was taken at 1 MW, 10 MW, 20 MW, 40 MW, 60 MW and 80 MW. The data at each successive power level indicated no reactor stability problems.

The recorded data was also analyzed to determine the RMS values of the fluctuations of the level signals. A plot of the RMS values versus power level showed a linearly increasing RMS value with increasing power level. Again, there was no indication of instability.

The PSD and CPSD plots made at these power levels will be used as reference for future testing after the SLSF loop is inserted into the reactor.

SAFETY ASSURANCE CALCULATIONS IN SUPPORT OF THE ATR

A. C. Smith, W. C. Cook, J. E. Brasier

The Advanced Test Reactor (ATR) is operated near the maximum heat flux and fuel burnup limits which are consistent with the safety requirements. All cycles operated this year included some recycle fuel elements. Utilization of these recycle fuel elements allows the most economical mode of operation for the ATR since recycle fuel elements generate lower power density distributions thereby reducing the critical heat flux. Additional recycle fuel elements allow higher relative lobe powers to be available to the sponsor's tests while remaining within the safety requirements.

Calculations of critical power density distributions and fission density concentrations were made with a full-core PDQ-7 XY model of the ATR for the several cycles operated during the year. Conservative fission density buildup rates for the center lobe core positions were used for some cycles without explicit calculations being made for the cycle. Utilization of these conservative buildup rates allows operation of the ATR without PDQ analysis, however, at the expense of poor fuel utilization. The combination of recycle fuel and new fuel provides near optimum cycle fuel loadings without compromising sponsor requirements on cycle life.

Reshuffle of the fuel elements between different core positions allows for more uniform fuel burnup. This is accomplished with the use of the RECYCLE computer program which allows the transformation of fuel from one core position to another in a mode acceptable to the PDQ-7 code for further calculations. Reshuffle of the fuel during its full irradiation history increases its lobe MWd burnup exposure level by approximately 300 MWd.

A SUMMARY OF ATR SHIM PREDICTIONS

W. D. Gregory

Predicted ATR shim positions for criticality are provided to ATR Operations for each cycle and, upon request, for xenon restarts. The ATR core may consist of all new fuel elements, all fuel elements recycled from the previous cycle or a mixture of new fuel elements and fuel elements recycled from previous cycles.

Predicted ATR shim positions for criticality for a new fuel loading are determined from the ATRC mock-up shim positions at criticality as well as from critical shim positions in an earlier and similar ATR startup. The two values obtained are averaged for the prediction. Also, where a PDQ-7 model calculation has been run on a new fuel loading, the PDQ-7 calculated shim positions for criticality are averaged with the ATRC empirical calculations for the final shim prediction provided to ATR Operations.

The predicted ATR shim positions for criticality for fuel elements recycled from the previous cycle and for xenon restarts are calculated using the ATR mid-cycle shim prediction program⁽¹⁾.

Predicted ATR shim positions for criticality for a mixed fuel loading are calculated from critical shim positions in two or three earlier and similar ATR startups. Also, where a PDQ-7 model calculation has been run on the mixed fuel loading the PDQ-7 calculated shim positions for criticality are averaged with the ATRC empirical calculations for the final shim prediction provided to ATR Operations.

A revision in the ATR mid-cycle shim prediction program has been incorporated in all predictions since Cycle 12B involving fission-product poisoning. The PDQ-7 model calculational procedure was revised and has been incorporated in predictions since Cycle 18A. PDQ-7 model calculations are not made if the ATR new fuel loading, relative power division, and flux trap composition are the same as or similar to a previous ATR cycle.

A summary of the standard deviation expressed in dollars of reactivity for the predicted ATR shim positions for criticality from Core II through Cycle 26A-1 startup are given below:

<u>Condition</u>	<u>1σ (\$)</u>
New-fuel startups	0.28
Recycled-fuel startups	0.55
Mixed-fuel startups	0.41

A comparison of the standard deviation presented here and in Reference 2 shows improvement in the predicted ATR shim positions for both the new-fuel startups and recycled-fuel startups.

-
- (1) P. R. Napper, Prediction of Shim Positions for Criticality for ATR Startups, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1971, ANCR-1016 (October 1971) 178.
 - (2) W. D. Gregory, ATR Cycle Mock-ups in ATRC, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1973, ANCR-1129 (December 1973) 167.

ATR POWER VARIATION SURVEILLANCE

P. R. Napper

Power variation surveillance is performed on the ATR to assist in identifying sources of any power variation and to prevent excessive reactor power variations in the ATR core.

There are basically five methods used for power variation monitoring and detection: Brush recordings, frequency scans, rms measurements and digital analysis producing both power spectral density and cross power spectral density. The data used for the analysis are the level channel currents, the spare servo chamber current and accelerometer signals from transducers mounted at various locations on the ATR pressure vessel. The Brush recording method is used on a daily basis. The other methods are only used if the Brush recordings show significant changes in power variation or if special tests are scheduled.

In addition to the daily measurements, all five methods were used in a special series of measurements during Cycle 24B. The data resulting from the Cycle 24B series of measurements shows that the frequency spectrum of the ATR noise is very complex and is probably caused by a combination of mechanically induced reactivity variations and mechanical noise on the chambers and their cabling. The complex noise spectra and results of the Cycle 24B measurements show that Brush recordings are suitable for detecting major variation problems. However, several techniques e.g., frequency scans and digital analysis using both ion chamber signals and accelerometer signals must be employed to identify the source of the variation.

The ATR power variation surveillance program is a continuing program and has demonstrated its usefulness in monitoring and detecting changes in the level of the ATR power variation. The equipment and methods used for ATR power surveillance will also be used for ETR power surveillance and for other reactors on an as-needed basis.

ETR PLANT PROTECTION SYSTEM UPGRADE

L.F. Hunt

The Engineering Test Reactor (ETR) facility was evaluated and Title I engineering proposal prepared and approved to upgrade the Plant Protection System (PPS) in accordance to ERDA-RDT Standards. In conjunction with the preparation, completion and approval of the Title II System Design Description (SDD), detailed procurement specification were prepared and, after experiencing some delay, instrumentation was purchased and delivered which conformed to the specified standards.

The Title II design phase was followed by the physical modification and installation of the second channel of instrumentation within each of the 13 protective subsystems. The installation was completed within the constraints specified in the approved SDD's and in accordance with detailed installation instructions.

Following installation, and prior to starting the reactor requalification program the modules within each channel of a two channel subsystem were individually inspected, calibrated, and tested for proper response time, using approved Detailed Operating Procedures (DOP). In addition to the module testing, end-to-end System Operational (SO) and response time tests were completed on each channel of each subsystem. In concert with the testing phase the installation drawings and maintenance manuals were verified and corrected as necessary to reflect the as-installed condition of the facility.

The PPS requalification testing phase was completed without experiencing any major design difficulties and on July 18, 1975 the ETR successfully completed the reactor requalification program thus bringing this design project to a successful conclusion.

Power Burst Facility

**THIS PAGE
WAS INTENTIONALLY
LEFT BLANK**

UPGRADING THE ATR CLAD GAGE INSPECTION SYSTEM

M. E. Yancey

The ATR clad gage inspection system had been developed in connection with an earlier ATR fuel contract in order to ensure that a minimum fuel plate clad thickness was maintained during the fabrication process. Experience in the production of ATR fuel plates has shown that during the rolling process a fuel build up occurs in an area near the ends of the core resulting in a thinning of the fuel cladding. Because of past operational and maintenance problems, it was necessary to upgrade this inspection system prior to use in connection with a new ATR contract.

Figure 1 shows a block diagram of the ATR clad gage inspection system. A fuel plate is located in the inspection tank under the ultrasonic transducer. The Z axis control module is used to automatically maintain the correct water path between the transducer and the fuel plate during the scanning process. The XY scanner provides a scanning motion across the width of the fuel plate, while incrementally positioning the transducer along the length of the fuel plates at specified intervals. An ultrasonic micrometer developed by Erdman Instruments was used to condition the transducers output and provide an alarm signal output when the clad thickness was below an acceptable level.

The system upgrade consisted of the following changes:

1. Improvement of the XY scanning system.
2. Elimination of the bulky inspection tank.
3. Changes in the Z axis control module and recorder alarm interface.
4. Modification of the alarm counting system.

Improvement of the XY scanning system and the elimination of the bulky inspection tank was achieved by using a modified laboratory scanner produced by Automation Industries. This scanner provided a sinusoidal scan rate across the width of the fuel plate instead of a linear scan rate. Therefore, a position encoder was added to the scanning system in order to provide a means of externally triggering the ultrasonic transducer at a rate proportional to the distance across the fuel plate. This permits a uniform inspection of the fuel plate surface while scanning at a sinusoidal rate. The ultrasonic micrometer was modified to interface with the position encoder.

A new Z axis control module and recorder alarm interface system were designed and fabricated for use in upgrading the system. The Z axis control module was also designed such that an alarm signal would be recorded should the proper water path be lost. The recorder alarm interface was designed to provide a +200 VDC alarm signal to the recording

pen when an alarm condition was received from the ultrasonic micrometer.

In the previous design an alarm counting scheme had been used in which several alarms had to be received in succession before an actual alarm was recorded. This counting scheme was modified to give an alarm indication on the recorder for every alarm received.

Personnel from Automation Industries, the ANC Quality Division and the Instrumentation and Measurements Branch worked together to implement this upgrade.

Figure 1. ATR Clad gage inspection system.

DIGITAL CONTROL FOR A SOLID STATE MOR

J. L. Morrison

This report describes a proposed digital control system for a solid state replacement for the Advanced Test Reactor (ATR) servo control system Motor Operated Rheostat (MOR). The existing system is a motor driven rheostat with two hundred fifty positions that vary the electrical output from position to position in a logarithmic manner. A study was undertaken to try to upgrade the existing mechanical system with a solid state system that had better control features, less granularity and eliminated the mechanical contacts in the MOR. The proposed replacement would store the log function in one thousand positions in a memory which would provide solid state switch settings to a weighted resistor array. The system block diagram is shown in Figure 1.

The digital control system consists of the following subsystems. Operator input control position switches that consist of three decade switches that allow a count of zero to 999 to be input as a setpoint by the operator. A decade to binary convertor that converts the decade switch input into a ten bit binary number. Bit comparison logic that compares the operator's control position with the actual setpoint position in the up/down counter and disables the clock when they agree. It also determines if it is an up or down count. The up/down counter is a ten bit binary counter that can count through 1000 positions at a fast count of 90 sec or a slow count of 480 sec. This count provides the address to the read only memory system. The counter can count up or down and can be preloaded. The read only memory system stores the log function of the MOR and as the counter goes through 1000 positions, the memory system will output coded words to the analog switches in the solid state MOR causing it to assume the proper value of resistance. The control unit receives input from the operational mode select switch and orders the counter to count up or down. The control unit also generates the various system clocks and the jump enable pulse (JEN) for the counter. The digital display is a 3 digit 7 segment display that displays a base 10 number showing the output of the counter.

Operation of the system would be as follows. The power is controlled by changing a function called "position." The digital display shows the actual setpoint of the function position. A low value of position corresponds to a low power setting. A high value in position is a high power setpoint. The control position switch is a decade array of switches similar to that of the switches on a decade resistance box. Through these switches the new setpoint would be entered by the operator. After entering the new setpoint, the operator would then position the gain mode select switch (a four-position spring loaded to off switch) to any of the three (3) modes of changing the setpoint for power. If he positions it to "slow" the actual setpoint will change at the slow rate (480 seconds to traverse full scale) until the actual position agrees with the position the operator set on the decade switches or, if the operator

releases the gain mode selector switch to the off position, then the actual position will stay where it was when the switch was released. If he had positioned the switch to fast, the change would occur at the fast rate (90 seconds to traverse full scale); otherwise it will operate the same way as in the slow speed. A jump position is available that will allow instantaneous changes in setpoint in the decreasing power direction. For example, the setpoint loaded into the decade switches is in the decrease in power direction. The operator could position the gain mode selector switch to jump and the feedback resistor unit will jump its setting to the new setting for a lower power. This function will not operate in the increase power direction.

This digital control system was proposed for use at ATR on a new solid state MOR for the servo system. The system provides decreased granularity (1000 positions vs. 250 positions), unique operating features, and solid state switching in the programmable gain operational amplifier.

Figure 1. Block diagram of digital system.

R-2R LADDER NETWORK FOR DIGITALLY CONTROLLED PROGRAMMABLE GAIN FOR AN OPERATIONAL AMPLIFIER

J. L. Morrison

As a result of the study to upgrade the Advanced Test Reactor (ATR) Servo Control System Motor Operated Rheostat (MOR) alternatives to the weighted resistor array for the programmable gain amplifier were studied. The goal of the study was to reduce the variety of resistor values needed and simplify the switching requirements. The application of the simple R-2R ladder and analog switches with an operational amplifier will provide the capability of a digitally controlled programmable gain. By using a memory to store the program of gain encoded in analog switch positions, a variety of time varying gain functions can be discretely fitted. A digital counter will address the memory and the discrete points of the gain function will be read out of memory at the frequency of the counter clock. The word read out of memory will change the analog switch settings on the R-2R ladder and thus, change the operational amplifier gain.

Characteristics of the R-2R ladder that lend themselves to a variable gain element are its constant output impedance, its binarily variable output voltage, and its analog switches are all referenced to the same voltages (ground and V_{IN}). A 4 bit ladder shown in Figure 1 illustrates these characteristics. The 4 bit ladder will divide the input voltage up in 16 parts in a binary manner.

The ladder switches S_1 through S_4 are switches in a binary sequence where a "1" is the switch indexed to V_{IN} and a "0" is the switch indexed to ground. S_1 is the most significant bit and S_4 is the least significant bit.

The transfer function of the ladder is given in Equation (1).

$$F(S_1, S_2, S_3, S_4) = \frac{V_0}{V_{IN}} = [S_1(\frac{1}{2}) + S_2(\frac{1}{2})^2 + S_3(\frac{1}{2})^3 + S_4(\frac{1}{2})^4] \quad (1)$$

As seen in Equation (1), as the binary array is inserted in bits S_1 through S_4 , the input voltage will be counted up in steps of $1/16$ from 0 to $15/16$. The characteristic of constant output impedance lends the ladder an excellent device as an input network on the inverting configuration of the operational amplifier. Equation (2) gives the resultant transfer function.

$$\frac{V_0}{V_{IN}} = \frac{R_F}{R} \times f(S_1, S_2, S_3, S_4) \quad (2)$$

The operational amplifier gain of $-R_F/R$ is divided into 16 parts and can be adjusted discretely with a resolution of $1/16 R_F/R$ from 0 to $-15/16 R_F/R$. Figure 2 shows the actual operational amplifier ladder hookup. The ladder can be extended to provide any desired

degree of bit resolution.

A block diagram of a digitally controlled ladder providing gain adjust for an operational amplifier is shown in Figure 3.

The ROM (Read Only Memory) would store the function of programmed gain. The counter would generate an address for the ROM. The control unit would initialize the counter and determine up or down count. It would also stop and start the count and determine count rate with the clock.

By placing the R-2R ladder in feedback for the operational amplifier and just using a straight counter for switch settings, the inverse function will be generated. Figure 4 shows the circuit configuration with a 4 bit R-2R ladder.

Solving for V_0 for feedback configuration yields Equation (3). Equation (3) can be reconfigured in Equation 4.

$$I_{IN} = \frac{V_0}{R} S_1(\frac{1}{2}) = S_2(\frac{1}{2})^2 + S_3(\frac{1}{2})^3 + S_4(\frac{1}{2})^4$$

$$V_0 = \frac{I_{IN} R}{[S_1(\frac{1}{2}) + S_2(\frac{1}{2})^2 + S_3(\frac{1}{2})^3 + S_4(\frac{1}{2})^4]} \quad (3)$$

V_0 has 15 values where $1 \leq K \leq 15$

$$V_{0K} = I_{IN} R \times \frac{\overbrace{16}^F}{\sum_{i=1}^K i} \quad (4)$$

where $S_1, S_2, S_3, S_4 = \text{binary } 1 \rightarrow 15$

Table 1 shows the relation between the binary inputs to the switches and the resultant function f . As seen in the table, all that is needed to generate this function is a straight counter operating at the desired frequency of clock. Figure 5 illustrates the configuration of this system. Cascading this system with two stages will simply square the inverse function. Cascading the system with the Figure 3 will doubly invert and result in unity gain.

TABLE 1
INVERSE FUNCTION f

Binary				Numeric Eq.	Inverse Function f
S ₁	S ₂	S ₃	S ₄		
0	0	0	0	0	∞
0	0	0	1	1/16	16/1
0	0	1	0	2/16	16/2
0	0	1	1	3/16	16/3
0	1	0	0	4/16	16/4
0	1	0	1	5/16	16/5
0	1	1	0	6/16	16/6
0	1	1	1	7/16	16/7
1	0	0	0	8/16	16/8
1	0	0	1	9/16	16/9
1	0	1	0	10/16	16/10
1	0	1	1	11/16	16/11
1	1	0	0	12/16	16/12
1	1	0	1	13/16	16/13
1	1	1	0	14/16	16/14
1	1	1	1	15/16	16/15

The first technique presented using the R-2R ladder as an input element for an operational amplifier was considered for possible application as a programmable gain amplifier with the proposed digital control system for a solid state MOR replacement in the Servo Control System at the ATR. Its simplified switching requirements, reduced variety of resistor values, and other unique characteristics lends itself for this application.

Figure 1. 4 bit R-2R ladder.

Figure 2. R-2R ladder hookup with inverting operational amplifier.

Figure 3. System of digitally programmed gain change.

Figure 4. R-2R in feedback.

Figure 5. R-2R Ladder for generating inverse function.

RELIABILITY STUDY FOR ATR PLANT PROTECTION SYSTEM UPGRADE

P. D. Ahlstrom, G. L. Hunt

Two measures of system reliability were calculated for a representative Advanced Test Reactor (ATR) Plant Protection System (PPS) configuration. These values were used to specify reasonable reliability requirements for the new ATR PPS. System unavailability, Q_S , is the probability that the PPS is incapable of performing all its intended protective functions at any specified point in time, and can be interpreted correctly as the probability of failure on demand. Unsafe failure rates are used to calculate system unavailability to obtain an estimate of PPS operational certainty. System unreliability, $\bar{R}_S$, is the probability that a system failure has occurred up to a specified point in time. Safe failure rates are used to calculate system unreliability to obtain an estimate of plant availability using the PPS spurious actuation rate.

System reliability figures are calculated in terms of failure modes, or minimal cut sets. A failure mode is defined as a necessary and sufficient collection of primary failures needed to produce a system failure. A primary failure is a failure, either safe or unsafe, of a component or group of components which, if subdivided further, would not affect system failure calculations. A constant component failure rate, λ , which is the reciprocal of component mean-time-to-failure (MTTF), is an input value to the calculations. Since the system is testable on-line, an input value for the testing interval, T , defined as the operating interval between tests, is required. Also needed is a value for component mean-time-to-repair, τ , defined as the time between the occurrence of the failure and restoration of the system to original operating conditions. For component MTTF's much greater than T , τ can be approximated by half the testing interval, if the repair time is much less than T .

The general approximate equations for system reliability figures were derived using the method of J. B. Fussell,⁽¹⁾ with the following results.

$$Q_S = \frac{1}{T} \int_0^T \sum_{k=1}^N \prod_{i=1}^{n_k} \lambda_{ik} t \, dt; \lambda_{ik} t < 0.1$$

$$= \frac{1}{T} \int_0^T \sum_{k=1}^N (\lambda_k t)^{n_k} dt; \lambda_{ik} = \lambda_k$$

$$\bar{R}_S = \sum_{k=1}^N t \prod_{i=1}^{n_k} \lambda_{ik} \tau_{ik} \sum_{j=1}^{n_k} \frac{1}{\tau_{jk}}; \lambda_{ik} \tau_{ik} \ll 0.1, t \text{ large}$$

$$= t \sum_{k=1}^N n_k \lambda_k^{n_k} \tau_k^{n_k-1} ; \lambda_{ik} \tau_{ik} = \lambda_k \tau_k$$

where:

N = number of failure modes

λ_{ik} = constant failure rate for i^{th} component of k^{th} failure mode

n_k = number of primary failures in k^{th} failure mode

τ_{ik} = mean-time-to-repair for i^{th} component of k^{th} failure mode

t = given time (usually the length of an operating cycle for $\bar{R}_S$ calculations)

The above approximations are valid for reasonable and likely values of λ , τ , and t , and always give conservative results, although usually only slightly conservative.

A block diagram of a representative PPS configuration is shown in Figure 1. To demonstrate the method, unavailability and unreliability figures will be calculated for a single 2/3 subsystem of the PPS. The failure modes of the subsystem for unsafe failures must be determined to obtain Q_S . Each subdivision of the subsystem (channels, subsystem logic, division logic, actuator controllers) is examined for possible unsafe failure modes which could disable the subsystem's protective function. The failure modes include interactive combinations among subdivisions.

In specifying the equation for Q_S , it is convenient to assume a common mean-time-to-repair, τ , for all subsystem components. Similarly, all components in each subdivision of the subsystem are assumed to have the same failure rates. The resulting equation is:

$$\begin{aligned} Q_S = & (\lambda_{ch} T)^2 + (\lambda_{2/3} T)^3 + (\lambda_{DL} T)^3 \\ & + \frac{4}{5} (\lambda_{act} T)^4 + 3 \lambda_{2/3} \lambda_{DL}^2 T^3 + 3 \lambda_{2/3}^2 \lambda_{DL} T^3 \\ & + \lambda_{DL} \lambda_{act}^2 T^3 + \lambda_{2/3} \lambda_{act}^2 T^3 + \lambda_{DL}^2 \lambda_{act} T^3 \\ & + \frac{4}{5} \lambda_{DL}^2 \lambda_{act}^2 T^4 + \lambda_{2/3}^2 \lambda_{act} T^3 + \frac{4}{5} \lambda_{2/3}^2 \lambda_{act}^2 T^4 \\ & + 2 \lambda_{2/3} \lambda_{DL} \lambda_{act} T^3 + \frac{8}{5} \lambda_{2/3} \lambda_{DL} \lambda_{act}^2 T^4 \end{aligned}$$

where:

λ_{ch} = constant failure rate for channels

$\lambda_{2/3}$ = constant failure rate for subsystem logic

λ_{DL} = constant failure rate for division logic

λ_{act} = constant failure rate for rod clutch coil controllers

As an example, consider a testing interval of eight hours and an MTTF of 20,000 hours for all components of the system. This results in a Q_S of 1.61×10^{-7} , with channel failure the dominant factor.

To calculate subsystem unreliability, $\bar{R}_S$, the procedure is similar to the above, with the failure modes for safe failures tabulated. Using the same assumptions as before, the following equation is obtained.

$$\begin{aligned} \bar{R}_S = t(6\lambda_{ch}^2\tau + 12\lambda_{2/3}^2\tau + 12\lambda_{DL}^2\tau + 16\lambda_{act}^2\tau \\ + 24\lambda_{2/3}\lambda_{DL}\tau + 16\lambda_{DL}\lambda_{act}\tau + 16\lambda_{2/3}\lambda_{act}\tau) \end{aligned}$$

For $\tau = 1$ hour, $T = 8$ hours, MTTF = 5,000 hours for safe failures, and a 50-day operating cycle ($t = 1200$ hours), the results are $\bar{R}_S = 4.896 \times 10^{-3}$, assuming the time required for testing is much less than T . This number is also an estimate of the expected number of spurious trips during a cycle. The above calculations are an example of the method used to determine reasonable reliability requirements for the new ATR PPS.

-
- (1) J. B. Fussell, "How to Hand-Calculate System Reliability and Safety Characteristics."

Figure 1. Typical PPS configuration.

ATR RESISTANCE TEMPERATURE DETECTOR RESPONSE STUDY

P. D. Ahlstrom

The ramp response of the existing resistance temperature detectors (RTD's) used in the Advanced Test Reactor (ATR) quadrant outlet temperature subsystems was needed to determine the adequacy of those subsystems for inclusion in the new ATR Plant Protection System (PPS). The time response of the existing platinum RTD's and thermowells is considered representative of currently available devices. Quadrant temperature subsystems are needed for protection against the slow lobe power increase due to withdrawal of selected outer shim cylinders, an anticipated fault. The neutron level subsystem does not provide adequate primary mitigation for this event, due to the unbalanced power conditions generated.

The ideal (exponential) response characteristic of the RTD's and thermowells was measured using step-change temperature baths to obtain a 63% response time. For the combination, the response time was between 9 and 12 seconds; for the RTD alone, the range was 5 to 7 seconds. The accident curves showing the temperature increase corresponding to the power increase were supplied by S. A. Atkinson and are shown in Figure 1. The limiting version of this accident is determined by the power in the critical lobe, which is the lobe operated under conditions closest to critical heat flux conditions. The expected range of critical lobe power is 40 MW to 75 MW.

The trip points in Figure 1 were chosen to assure that the maximum critical lobe power would not exceed 125% of the normal power in that lobe, in accordance with core safety assurance requirements. Figure 1 also gives an indication of the increase in temperature at the subsystem sensors, as delayed by the estimated 5 second transport time of the primary water from the core. The numbers on the ordinate scale are multipliers to be applied to the normal quadrant differential temperature, rather than quadrant outlet temperature.

Using Laplace transform techniques, the ramp response of the RTD-thermowell combination can be generated from the measured step response. The resulting normalized equation is:

$$r(t) = K[t - \frac{1}{\alpha} (1 - e^{-\alpha t})]$$

where α varies from 1/12 to 1/9, and K varies from .00352 to .00533, according to the ramp chosen from Figure 1. Plots of this equation are shown in Figure 2. The outlet temperature, as indicated by the RTD output, can be obtained by multiplying graph readings by the normal quadrant ΔT , and adding the normal quadrant outlet temperature for the critical lobe. Figure 2 also shows the required setpoints for adequate mitigation of this accident.

It was concluded that, for the worst case critical lobe power, quadrant outlet temperature subsystems did not provide adequate PPS

response to this accident. With a 5% setpoint accuracy, the required setpoint for these subsystems would have to be less than normal operating level. However, quadrant differential temperature subsystems could provide adequate response with a setpoint margin of at least 10% above operating levels, including setpoint accuracy effects. The PPS conceptual design was, therefore, modified by replacing quadrant outlet temperature with quadrant differential temperature subsystems.

Figure 1. Shim withdrawal accident.

Figure 2. RTD response to shim withdrawal accident.

COMPUTATION OF TEMPERATURE COEFFICIENTS,
BORON WORTH, AND CONTROL ROD WORTH AT BOL AND 1000
EFPH USING XYZ SYNTHESIS IN PDQ-7

T. E. Young

Temperature coefficients and boron worth at beginning-of-life (BOL) had previously been computed for LOFT-I(1,2). The maximum and minimum values of moderator- and fuel-temperature coefficients for accident analysis were based on that data. In this study, the effects on these parameters of depletion to 1000 effective-full-power-hours (1000 EFPH) were determined. The effect of depletion on rod worth was also computed.

Computations were performed using PDQ-7⁽³⁾ with the XYZ-synthesis model described in LTR-111-60⁽²⁾. In order to isolate the effects of depletion, temperature coefficients were computed at BOL and 1000 EFPH (full power = 55 MW) for constant boron concentration *800 ppm) and constant rod position (54-inches withdrawn).

For the reactor at a uniform temperature of 584°F, the overall-temperature coefficient (moderator & fuel) changes from $-34.9 \times 10^{-5} \Delta\rho/\Delta F$ at BOL to $-37.0 \times 10^{-5} \Delta\rho/\Delta F$ at 1000 EFPH. The corresponding fuel-temperature coefficient changes from $-1.23 \times 10^{-5} \Delta\rho/\Delta F$ at BOL to $-1.27 \times 10^{-5} \Delta\rho/\Delta F$ at 1000 EFPH. The corresponding moderator-temperature coefficient changes from $-33.7 \times 10^{-5} \Delta\rho/\Delta F$ at 1000 EFPH. The limits set on the temperature coefficients for accident analysis adequately account for such small percentage changes. Comparison with Reference 1 data for BOL showed that differences effected by changes in the calculational model were larger than those caused by depletion. The XYZ-synthesis model predicts temperature coefficients 10% less negative than the Reference 1 values. Accident analysis that uses minimum values for the temperature coefficients should, therefore, reduce limits based on previous data by 10%.

Inverse boron worth at hot operating conditions after depletion to 1000 EFPH is 128.63 ppm/% $\Delta\rho$. The corresponding value at BOL is 127.18 ppm/% $\Delta\rho$, from Reference 2. For the reactor at a uniform 680°F after depletion to 100 EFPH, the inverse boron worth is 100.30 ppm/% $\Delta\rho$. The corresponding value at BOL is 99.5 ppm/% $\Delta\rho$, from Reference 1. Control rod worths, determined for the cold (680°F) reactor were 11.84% at BOL and 11.76% at 1000 EFPH. It is seen from these values that depletion (and fission product buildup) produced by operation of LOFT-I to 1000 EFPH has negligible effect on the magnitude of computed values of boron worth and rod worth.

-
- (1) A. J. Scott, Internal Report, (August 31, 1973).
 - (2) B. L. Rushton, Internal Report, (November 21, 1974).
 - (3) W. R. Cadwell, PDQ Reference Manual, WAPD-TM-698, (January 1967).

PBF REACTOR RESPONSES TO ROD MOTION

J. W. Sielinsky

The responses of the Power Burst Facility (PBF) neutron power for ramp and sinusoidal reactivity driving functions were measured and compared to calculated responses as part of the program to try to identify the cause of the power fluctuations. The objective was to try to determine whether the power fluctuations are caused by a direct reactor kinetics feedback mechanism or whether they are caused by a reactivity driving source. The power fluctuations start at a nominal power of about 6 MW with a dominant frequency component in the region of 0.065 Hz. As the nominal power is increased the amplitude of the fluctuations increases until the nominal power is about 20 MW; then the amplitude of the fluctuations remains about the same as the power is increased. As the nominal power is increased the dominant frequency of the power fluctuation decreases. At a nominal power of 10 MW it is about 0.05 Hz and at 25 MW it is about 0.045 Hz.

Figure 1 presents the neutron power responses for approximate ramp reactivity insertions generated by inserting the control rods. The power was established at a nominal steady-state level of 16 MW; then the control rods were inserted to their respective positions for the lower nominal power levels. The points present the measured responses from the reactor and the solid curves present the calculated responses from the PBF Reactor Kinetics Simulator. The upper curve is the 16-to 12-MW transient, the middle curve is the 16-to 8-MW transient, and the lower curve is the 16-to 6-MW transient. When the control rod insertions are stopped the power continues to decrease; then as the fuel cools the magnitude of the Doppler feedback decreases, and the power increases up to a new level. The measured and calculated responses agree reasonably well which shows that the simulator models are a reasonable representation of the reactor kinetics. The responses do not show any oscillations with periods in the order of 20 seconds which would indicate that the source of the power fluctuations is a direct feedback mechanism which could cause the reactor to go unstable as the power is increased.

Figures 2, 3 and 4 present the frequency responses of neutron power for sinusoidal reactivity inputs for nominal powers of 0.46, 4.0 and 7.6 MW, respectively. The measured responses were obtained by driving the reactor with approximate sinusoidal reactivity functions using the transient rod drive system, then measuring the amplitude of the power and the phase shift between the power and the transient rod positions. The amplitude of the frequency response was then normalized to the nominal power and plotted. The points present the measured responses and the solid curves present the calculated responses.

The measured responses for nominal powers of 0.46 and 4.0 MW (Figures 2 and 3) agree very well with the calculated responses. Since these were made below the nominal power at which the power fluctuations are observed, they show that the model for the reactor kinetics is a reasonable representation of the actual reactor kinetics. The amplitude of the measured response at the nominal power of 7.6 MW

(Figure 4) does not show a peak in the region of 0.06 Hz. A peak in the amplitude in this frequency region would indicate a resonance in the reactor and would also indicate that the power fluctuations are caused by a direct feedback mechanism.

The objective of these measurements was to try to determine whether the power fluctuations are caused by a direct reactor kinetics feedback mechanism or whether they are caused by a reactivity driving source. Neither the ramp responses or the frequency responses indicate that the power fluctuations are caused by a direct feedback mechanism which would cause the power to go unstable as the nominal power is increased. The responses indicate that the power fluctuations are caused by a reactivity driving source.

Figure 1. Comparison of PBF power reduction transients of run 75B with simulated transients.

Figure 2. PBF frequency at a nominal power of 0.46 MW.

Figure 3. PBF frequency response at a nominal power of 5.0 MW.

Figure 4. PBF frequency response at a nominal power of 7.6 MW.

PBF POWER FLUCTUATION DIAGNOSTICS

J. W. Sielinsky

The neutron power signals and fuel pin temperature signals were analyzed as part of the program to try to determine the cause of the neutron power fluctuation in the Power Burst Facility (PBF). The neutron power signals were analyzed to estimate the power spectral density (PSD) functions and the rms-to-mean ratios of the fluctuations at nominal power levels up to 25 MW. The fuel pin clad temperature signals were analyzed to estimate their fundamental frequencies and to estimate the phase shift between temperature signals from four thermocouples spaced 90 degrees around the instrumented fuel pins.

Figure 1 presents the estimates of the PSD's for nominal reactor powers of 6, 8, 10, 12, 14, 20 and 25 MW. The PSD's present an estimate of the power of the neutron power fluctuations as a function of frequency. This figure shows that as the nominal power is increased the dominate frequency of the power fluctuations tends to decrease. At 6 MW the dominate frequency is about 0.065 Hz and at 25 MW it has decreased to about 0.045 Hz. Also as the nominal power is increased, the amplitude of the peak increases and the peak becomes narrower. Note the increase in the peak amplitude of the PSD's between 6 and 12 MW is larger than the increase in the peak amplitude from 12 to 25 MW. This indicates that the change in amplitude of the fluctuations as a function of nominal power is decreasing as the nominal power is increased. The PSD for a nominal power of 25 MW for servo control with two control rods shows that the servo controller is capable of significantly decreasing the amplitude of the power fluctuations.

Figure 2 presents the RMS/MEAN ratios of the power fluctuations as a function of nominal reactor power. The points are the measured values from the diagnostic tests and the solid curve is estimated from these points. Because of the random characteristics of the power fluctuations, the measured values varied significantly from one test to the next; therefore, the intent of the solid curve is to show the trend of the RMS/MEAN ratio as the nominal power is increased. The trend is for the ratio to increase up to the region of 15 MW then it decreases as the nominal power is increased up to about 26 MW. If it is assumed that the fluctuations are caused by a reactivity driving function, then this figure indicates that the amplitude of the reactivity driving function continues to increase up to a nominal power of about 15 MW and then decreases as the nominal power increases up to about 26 MW. Figure 2 also shows that the control rod drive system power level controller is capable of significantly decreasing the fluctuations. The point at 14 MW shows that the ratio is decreased from 1.25% to about 0.3% using the controller with one control rod drive. The point at 26 MW shows that the ratio is decreased from about 0.9% to about 0.25% using the controller with two control rod drives.

During diagnostic Run 72 fuel pin centerline, clad surface, and coolant channel temperatures were measured as part of the program to

try to identify the source of the neutron power fluctuations. Previous measurements showed that some of the coolant channel outlet temperatures were fluctuating. Fuel pins were instrumented in fuel assemblies A2, B1, B12 and C4. The fuel pins were instrumented with a centerline temperature detector, four clad temperature thermocouples spaced 90 degrees apart at about the axial center of the fuel pins, and a coolant channel thermocouple. Also one of the adjacent fuel pins was instrumented with one clad thermocouple. Table 1 presents a summary of the amplitudes and frequencies of the temperatures at nominal powers of 6, 8 and 10 MW. The instrumented fuel pins in assemblies A2 and B12 used ultrasonic thermometers to measure the fuel centerline temperatures, and thermocouples to measure the clad surface and coolant channel temperatures. In Table 1 both the ultrasonic thermometers and the clad thermocouples are identified by UT's. The sensors for the fuel pins with centerline thermocouples are identified by TC's in Table 1. Table 1 shows that the fundamental frequencies of the temperature signals range from 0.082 to 0.1 Hz for a nominal power of 6 MW, from 0.055 to 0.069 for a nominal power of 8 MW and from 0.044 to 0.084 Hz for a nominal power of 10 MW. These show that the fundamental frequencies of the temperature signals decrease as the nominal power increases. Figure 1 shows the dominant frequency of the power fluctuations also decreased as the nominal power was increased. Also note that the fundamental frequencies of the clad temperature fluctuations are different for each fuel pin. This indicates that the clad surface temperatures are not being driven by the reactor power fluctuations. The temperature fluctuations from the instrumented fuel pins started at different power levels. For example, temperature fluctuations were observed on fuel pin UT 0002 in assembly B12 at 6 MW but none were observed on UT 0001 in assembly A2 until 10 MW. This indicates that there is a different threshold for each fuel pin at which the temperature fluctuations begin.

Table 1 shows that the amplitudes of the clad temperature signals for a particular fuel pin are not the same for each side of the pin. It also shows that the clad signals are shifted in phase with respect to each other. The temperature signal time traces for fuel pin TC 0005 in assembly B1 are shown in Figure 3. Clad TC 0005-1 and -3 show large amplitudes compared to TC 0005-2 and -4. TC 0005-1 is shifted in phase by about 180° from TC 0005-3. Also note that the TC 0005-1 and -3 signals are the same frequency but the adjacent rod, 2823-2, clad signal is at a different frequency. The information from these temperature signals indicated that the clad temperature fluctuations are caused by fuel pin movement with the fuel pellets shifting within the insulator.

Because of the clad temperature fluctuations measured during diagnostic Run 72, additional tests were run. These included tests to determine the movement of the top of fuel pins, to determine the effects on the clad surface temperature fluctuations of controlling the amplitude of the power fluctuations, to determine if the clad temperature fluctuations would occur on PBF fuel pins in the test space, and to determine if the clad temperature fluctuations could be decreased by cracking the fuel pellets.

Two of the PBF fuel pins were instrumented with displacement transducers to measure the movement of the top of the pins. The instrumented fuel pin in assembly A1 showed that movement started at a nominal power of about 6 MW, the amplitude increased with power, the movement was roughly in a clockwise elliptical pattern, had a frequency of about 0.04 Hz, and a peak to peak amplitude of about 60 mils at about 10 MW nominal power. The instrumented fuel pin in assembly B12 showed that movement started at about 8 MW, the amplitude increased with power, the movement was roughly in a single plane, had periods of time in which little movement occurred, had a frequency of about 0.035 Hz when it was moving, and a peak to peak amplitude of roughly 60 mils at 10 MW nominal power.

The control rod power level controller was modified to incorporate a variable deadband in order to determine the effects on the clad temperature fluctuations of controlling the power fluctuations. At a nominal power of 14 MW, the amplitude of the power fluctuations was decreased by about a factor of five by decreasing the deadband of the power level controller, but the amplitude and frequency of the clad temperature fluctuations were essentially unchanged. This agreed with the indications from previous tests that the clad temperature fluctuations are not caused directly by the power fluctuations.

In order to determine if clad temperature fluctuations would occur on PBF fuel pins in the test space, the Nine-Rod Lead Rod cluster was installed in the inpile tube with some of the fuel pins instrumented with clad thermocouples. Clad temperature fluctuations similar to those observed on the driver core fuel pins did occur. Also two of the test fuel pins placed in essentially identical environments showed that the clad temperature fluctuations varied considerably. This indicated that the fluctuations are a characteristic of the individual fuel pins rather than the local environmental conditions.

Because the previous test strongly indicated that the clad temperature fluctuations are caused by a fuel pin movement problem with the fuel pellets shifting periodically within the insulator, additional tests were run to determine if the clad temperature fluctuations could be significantly decreased by cracking the fuel pellets. Two methods of cracking the fuel pellets during reactor operation were postulated, burst operation and high-power steady-state operation. The high-power steady-state operation was used with the Nine-Rod Lead Rod cluster installed in the inpile tube with fuel pins instrumented with clad thermocouples. With the nominal reactor power at about 16 MW the PBF fuel pins in the inpile tube were subjected to equivalent power densities of about 32 MW. Figure 4 presents the power history for this test. The nominal power was increased to 16 MW, shutdown, increased to 16 MW, decreased to 8 MW, increased to 16 MW, decreased to 12 MW, increased to 16 MW, and then shutdown. Figure 5 summarizes the amplitude of the clad temperature fluctuations measured on test rod 9 in the inpile tube as a function of core nominal power for the four power cycles. During the first power cycle the fluctuations started at about 4 MW and increased in amplitude to about 17° F peak to peak at about 12 MW, then decreased in amplitude as the core power was increased

to 16 MW. For the second power cycle, the amplitude was between 7 and 8° F from 8 to 16 MW. For the third and fourth power cycles the amplitude was about 4° F from 10 to 16 MW. Figure 6 shows a comparison of the clad temperature fluctuations for test rod 9 for the various power cycles. Neutron radiographs of the test rods showed that fuel pellet cracking did occur. The pellet cracks were mainly in the radial direction with one and, in some instances, two major cracks extending the full length of the pellet. It was concluded from this test that the cracking of the fuel pellets significantly decreased the amplitude of the clad temperature fluctuations.

The results of the PBF Power Fluctuation Diagnostic Test strongly support a postulated mechanism of fuel pin movement as the reactivity fluctuation source which causes the neutron power fluctuations. Tests have demonstrated that fuel pellet cracking will significantly decrease the fuel clad temperature fluctuations, and hence could provide a solution to the neutron power fluctuations.

TABLE 1

SUMMARY OF RUN 72 TC TEMPERATURE DATA

10 MW				8 MW			6MW			Comments	
Temperature Sensor Identification	Peak to Peak Amp. (°F)	Period (Sec)	Freq. (HZ)	Peak to Peak Amp. (°F)	Period (Sec)	Freq. (HZ)	Peak to Peak Amp. (°F)	Period (Sec)	Freq. (HZ)		
<u>Assembly A2</u>											
Fuel	UT 0001										
Clad	UT 0001-1			No Fluctuations			No Fluctuations			TC Bad 180° Phase w/3 90° Phase w/4	
	UT 0001-2	3.5	12.6								.08
	UT 0001-3	5.2	12.6								.08
	UT 0001-4	2.1	12.6								.08
Clad	2825-2	8.8	16.7	.06						<90° Phase w/coolant	
Coolant	2825-1	2.0	16.7	.06							
<u>Assembly B1</u>											
Fuel	TC 0005	3.1	19.2	.052	2.0	17.7	.057	< 1		Crude Approx.	
Clad	TC 0005-1	9.0	15.7	.064	No Fluctuations		No Fluctuations			180° Phase w/3	
	TC 0005-2										
	TC 0005-3	11.4	15.7	.064							
	TC 0005-4										
Clad	2823-2	12.3	20.0	.05	12.3	18.3	.055	5.2	12.1	.082	45° Phase w/coolant (Crude Approx.)
Coolant	2823-1	2.0	20.0	.05							
Fuel	TC 0006	4.0			2.5						
Clad	TC 0006-1	14.0	18.6	.055	8.0	16.1	.062	No Fluctuations			} In Phase { 180° Phase; } In Phase { 1 & 3 Highest Amp
	TC 0006-2	5.2	18.6	.055	3.5						
	TC 0006-3	10.5	18.6	.055	7.0						
	TC 0006-4	5.2	18.6	.055	5.2						
Clad	2824-1	9.7	20.2	.05	7.0	~16.1	~.062				
Coolant	2824-2		20.2	.05							
<u>Assembly B12</u>											
Fuel	UT 0002										
Clad	UT 0002-1	7.0	16.6	.06	3.5	14.4	.069	1.0	10	.1	180° Phase w/4 Highest Amp W/2
	UT 0002-2	14.0	16.6	.06	10.5	14.4	.069	5.3	10	.1	
	UT 0002-3	7.0	16.6	.06	3.5	14.4	.069	3.5	10	.1	
	UT 0002-4	35.0	16.6	.06	21.0	14.4	.069	7.0	10	.1	
<u>Assembly C4</u>											
	TC 0004-1	5.2	12	.084	No Fluctuations		No Fluctuations			} In Phase { 180° Phase } In Phase {	
	TC 0004-2	5.2	12	.084							
	TC 0004-3	7.0	12	.084							
	TC 0004-4	5.2	12	.084							
<u>Assembly D8</u>											
	No Fluctuations			No Fluctuations			No Fluctuations				
<u>Assembly D2</u>											
	TC 6	16.0	23	.044	11.7	16.7	.06	No Fluctuations			
<u>Peak Frequency of Neutron Spectral Density Function (HZ)</u>											
			.05			.06		.06

Figure 1. Power spectral density functions of PBF neutron power fluctuations.

Figure 2. PBF power fluctuation RMS/mean ratios as a function of nominal power.

Figure 3. Time traces of temperature signal from instrumented fuel pin in PBF reactor.

Figure 4. Run 75 power history.

Figure 5. Summary of cladding temperature fluctuations on Test Rod 9 as measured by TC #6 during Run 75.

Figure 6. Comparison of the cladding surface fluctuations on test rod 9 at various power levels.

PBF GAP CONDUCTANCE MEASUREMENTS

J. W. Sielinsky

The Gap Conductance Thermal Oscillator Feasibility Test (1-1) was performed in the Power Burst Facility to determine the feasibility of this technique for obtaining information on the magnitude of the gap conductance between the fuel pellets and the clad in typical power reactor fuel rods. The thermal oscillator technique is based on the relationship between the magnitude of the gap conductance and the frequency response of the fuel pin cladding surface temperature for fuel power oscillations. Therefore, the primary objective of the test was to oscillate the reactor power and measure the amplitude and phase shift of the test fuel cladding surface temperature.

The transient rod servo control system was modified to use the Supplemental Linear 2 neutron power signal for the controller power feedback signal; the input to the controller was modified so that an external oscillator could be connected for the sinusoidal power command signal; and the control logic was modified to manually switch to closed loop power control instead of using the program timer. The test procedures were written for the operation of the modified system and then the test was dry run using the PBF Reactor Kinetics Simulator with a simplified dynamics model of the test fuel pin.

A Weston Transfer Function Analyzer was used to provide the sinusoidal reactor power demand signal and the on-line amplitude and phase measurement of one of the clad temperature signals. For most of the on-line measurements, the clad temperature signal used was from the thermocouple identified as TC 1. For the case of the nominal power at 11.0 MW and the sinusoidal amplitude of 20%, measurements were also made from the thermocouple TC 3 in order to compare the measurements on the opposite sides of the fuel pin. The data from the on-line measurements are presented in Table 1.

The signals recorded on magnetic tape were the neutron power signal from Supplemental Linear 2 neutron power channel, the oscillator signal from the Transfer Function Analyzer, the four test fuel pin clad surface temperature signals (TC 1, TC 2, TC 3, and TC 4), the experiment inlet and outlet temperature signals, the experiment inlet flow rate, and the sum of the transient rod position signals. From the magnetic tape recordings the amplitude and phase of the four clad surface temperature signals with respect to the neutron power signal were calculated using the Time/Data 100 Digital Analyzer. The data from these analyses is also present in Table 1 and compared with the on-line data. The comparison shows that the measurements made on line agree reasonably well with the data from analyzing the recorded signals with the Time/Data 100 Digital Analyzer.

From the data obtained from this test, the Fuels Behavior Program personnel are estimating the gap conductances. Preliminary results of this test indicate that:

1. The PBF reactor can be oscillated at the desired amplitudes and frequencies in an exceptionally stable manner.
2. The clad temperature signals are sufficient to measure the amplitude and phase for power signal amplitudes of 10 and 20% for the record lengths recorded. For the 5% power amplitudes, longer record lengths are needed to average out the "noise" effects of the test loop flow variations caused by the loop flow control valve cycling.
3. The preliminary results indicate that the gap conductance can be measured using the thermal oscillator technique, and it was felt the test was highly successful.

TABLE I

DATA FROM THE THERMAL OSCILLATOR FEASIBILITY TEST

NOMINAL POWER (MW)	AMP. (%)	FREQ. (HZ)	TC #	PHASE LAG T/D 100 (°)	PHASE LAG ON LINE (°)	PHASE DIFF. (T/D100-ON LINE) (°)	TEMP. AMP. T/D 100 (°F)	TEMP. AMP. ON LINE (°F)
5.3	5	0.033	1	37.72	34.4	+3.32	1.45	1.56
			3	40.70			0.89	
			2	38.92			0.97	
			4	39.05			1.82	
	10	0.033	1	39.03	38.0	+1.03	2.94	3.05
			3	43.18			1.78	
			2	39.59			2.06	
			4	39.80			3.66	
		0.05	1	47.81	48.0	-0.19	2.34	2.33
			3	51.45			1.32	
			2	49.22			1.63	
			4	47.99			2.99	
		0.10	1	57.07	60.0	-2.93	1.57	1.54
			3	58.11			0.84	
			2	54.85			1.14	
			4	60.02			1.90	
	20	0.033	1	39.27	39.0	+0.27	5.58	5.98
			3	40.21			3.43	
			2	41.54			4.02	
			4	39.17			7.24	
		0.05	1	48.38	48.1	+0.28	4.63	4.76
			3	49.53			2.81	
			2	47.84			3.37	
			4	49.10			5.81	
		0.10	1	58.16	57.4	+0.78	3.10	3.13
			3	61.56			1.83	
			2	58.77			2.26	
			4	59.89			3.76	
	30	0.033	1	39.62	40.9	-1.28	8.60	8.6
			3	40.62			5.29	
			2	40.38			6.25	
			4	40.24			10.94	
		0.05	1	47.77	47.3	+0.47	6.83	6.9
			3	48.46			4.34	
			2	50.41			4.87	
			4	46.76			8.88	
		0.10	1	58.55	58.0	+0.55	4.46	4.3
			3	58.92			2.92	
			2	58.39			3.28	
			4	59.41			5.76	

TABLE I (Contd.)

NOMINAL POWER (MW)	AMP. (%)	FREQ. (HZ)	TC #	PHASE LAG T/D 100 (°)	PHASE LAG ON LINE (°)	PHASE DIFF. (T/D100 ON LINE (°)	TEMP. AMP T/D 100 (°F)	TEMP. AMP. ON LINE (°F)
11.0	5	0.033	1	34.95	31.6	+3.35	1.7	2.0
			3	35.19			1.1	
			2	38.49			1.1	
			4	30.45			2.7	
		0.05	1	40.69	43.2	-2.51	1.37	1.4
			3	43.16			1.04	
			2	38.52			0.85	
			4	39.36			2.25	
		0.10	1	47.66	50.0	-2.34	0.96	0.9
			3	54.25			0.68	
			2	49.50			0.57	
			4	44.85			1.61	
	10	0.033	1	36.17	37.4	-1.23	3.6	3.6
			3	34.15			2.3	
			2	36.74			2.4	
			4	33.04			5.1	
		0.05	1	42.70	40.30	+2.40	2.8	2.9
			3	44.86			1.9	
			2	45.08			1.9	
			4	39.19			4.3	
		0.10	1	48.49	50.60	-2.11	2.0	2.0
			3	50.70			1.3	
			2	49.15			1.3	
			4	45.41			3.2	
	20	0.033	1	35.05	36.6	-1.55	7.4	7.4
			3	34.98			4.6	
			2	34.84			5.0	
			4	33.50			10.3	
		0.05	1	41.75	40.8	+0.95	6.0	6.1
			3	43.05			3.7	
			2	40.95			4.0	
			4	39.53			8.4	
		0.10	1	49.36	50.9	-1.54	4.1	4.2
			3	53.55			2.5	
			2	48.42			2.7	
			4	48.28			6.0	

POWER DISTRIBUTION FOR THE NINE-ROD LEAD TEST IN PBF

A. J. Scott, E. Fast

As part of ANC's Thermal Fuel Behavior Program, a number of tests will be conducted in PBF with various clusters of test fuel pins. Experiment planning and design requires an accurate prediction of the power distribution within each cluster. To provide this information, reactor physics calculations have relied on full energy range, general geometry Monte Carlo methods using the RAFFLE code(1). To test the accuracy of the calculational methods, the model has been applied to one cluster for which experimentally determined power distribution data was available. The test cluster consisted of nine PBF type pins in the geometry shown in Figure 1. The computed and measured relative fission rates differed by less than 2% for all pins in the cluster. The good agreement lends considerable confidence to the accuracy of the calculational model to predict test pin cluster power distributions.

The test geometry shown in Figure 1 was represented exactly in RAFFLE. Neutron currents entering the test space were computed with S_N transport theory and input as a cylindrical surface source in RAFFLE. The S_N reactor calculations were done in radial geometry with 32 neutron energy groups using the SCAMP code(2). Except for calcium, all cross sections were based on ENDF/B Version 3 data. The resulting relative power distribution is compared with experimental results in Table 1.

TABLE 1
COMPARISON OF ROD POWER FRACTIONS
FOR NINE-ROD LEAD TEST

<u>Rod Location</u>	<u>Calculated</u>	<u>Measured</u>
Center	11.3+ .3*	11.3+ .2
Side	10.4+ .1	10.2+ .1
Corner	11.8+ .1	12.0+ .1

* Statistical uncertainty corresponds to 90% confidence interval.

- (1) W. E. Vesely, F. J. Wheeler and R. S. Marsden, RAFFLE - A Multipurpose Monte Carlo Code, ANCR-1022, (1973).
- (2) SCAMP is a multigroup version of TOPIC. G. E. Putnam, TOPIC -- FORTRAN Program for Calculating Transport of Particles in Cylinders, IDO-16968, Phillips Petroleum Company, (April 1964).

Figure 1. Nine-rod PBF experiment

SINGLE ROD POWER LEVELS IN PBF FOR THE PCM-20 TEST SERIES

A. J. Scott, T. E. Young

The Thermal Fuel Behavior Program includes a test series to investigate power-cooling-mismatch (PCM) conditions that could lead to failure of thermal reactor fuel rods. The first test of this series (PCM-20) has been performed with a single PWR type fuel rod in the PBF test space. Reactor physics calculations were done to predict the PCM-20 rod power level under steady state PBF operating conditions. The results were found to be in good agreement with the experimentally determined rod powers.

The test rod was a 20% enriched UO_2 zircaloy-clad rod. The test geometry is shown in Figure 1. To predict the test pin fission rate, SCAMP⁽¹⁾ transport theory calculations were made in radial geometry with an S_4 approximation and 32 neutron energy groups (25 fast, 7 thermal). Since the one-dimensional radial model could not represent partially inserted control rods, 4-group PDQ⁽²⁾ calculations were made in RZ geometry to account for their effect on the pin fission rate. Fifteen-group gamma transport calculations were also done with SCAMP to determine the gamma energy deposition distribution to allow conversion from fission rate to heat generation rate (i.e., power).

The computed PCM-20 test rod power density at the axial flux peak was 1.22 kW/ft per MW of core power. The experimental rod power based on calorimetric or heat balance measurements was $1.26 \pm .23$ kW/ft/core MW. The rod power was also determined from rad-chem measurements of the fissions that occurred in the rod. This gave a measured power of $1.3 \pm .18$ kW/ft/core MW.

-
- (1) SCAMP has not been published but it is essentially a multigroup version of TOPIC: G. E. Putnam, TOPIC -- FORTRAN Program for Calculating Transport of Particles in Cylinders, IDO-16968, Phillips Petroleum Company, (April 1964).
- (2) A. W. Brown, et. al., Summary of PDQ-7 (IBM-360-75 Version) Input Data Requirements and Operating Procedures, ANCR-1061, (March 1972).

Figure 1. Test space portion of the SCAMP model (single rod tests).

Loss of Fluid Test

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

COMPUTATION OF THE UNIFORM MODERATOR VOID
COEFFICIENT (LOFT-I: BEGINNING OF CORE LIFE)

T. E. Young

Several changes have been made in the design of the LOFT reactor since the uniform moderator void coefficient was calculated previously (1). It was anticipated that the void coefficient might be significantly different from that calculated for the earlier design. The purpose of the present calculations was to obtain the beginning-of-life uniform moderator void coefficient applicable to the current reactor design for void fractions up to 50%. These data are used primarily for accident analysis.

The as-built LOFT reactor design, upon which the present calculations were based, differs from the design used for the previous calculations in various respects. The differences are summarized in Table I.

TABLE I
COMPARISON OF PRESENT LOFT DESIGN WITH DESIGN USED IN PREVIOUS CALCULATIONS

<u>QUANTITY</u>	<u>Previous Design</u>	<u>Present Design</u>
Pellet O.D.	0.3669 in.	0.3659 in.
Fuel Pin Diametrical Gap	0.0065 in.	0.0075 in.
Fuel Density	10.3 g/cm ³	9.989 g/cm ³
Fuel Enrichment in U-235	3.45%	4.029%
Barrel Filler Composition:	Moderator	10%
	SSt1	90%
Vessel Filler Composition:	Moderator	5.265%
	SSt1	94.735%
Downcomer Temperature	10%	0.0%
	90%	100%
PPM Natural Boron in Moderator	Not explicit	557.0°F
Fuel Temperature	1120.0	1231.7
Moderator Temperature	1522.0°F	1589.0°F
Cladding Temperature	590.0°F	581.9°F
	656.0°F	581.9°F

The results of the present calculations are shown on Figure 1 along with data from the previous calculations. There are no significant differences in the two sets of data.

Figure 1 Reactivity of LOFT Reactor as a function of Moderator Void Fraction.

The reactivity notation (ρ_{RTC}) on Figure 1 stands for referred-to-critical and is defined by;

$$\rho_{RTC}(\%) = \frac{\lambda - \lambda_0}{\lambda} (100),$$

where λ_0 = the eigenvalue computed with no voiding.

Due to changes in the LOFT reactor design since earlier calculations, the uniform moderator void coefficient at beginning of life has been recalculated. There were no significant changes in the effects of voiding and it was recommended that the void coefficients previously reported continue to be used for LOFT accident analysis.

(1) E. C. Anderson, Internal Report, October 20, 1970.

ENERGY DEPOSITION IN THE LOFT REACTOR AT 54.71 MW

T. E. Young

The energy depositions in various components of the LOFT reactor have been calculated for the reactor operating at 54.71 MW. These rates will be used as input for the heat transfer calculations to insure that the proper temperatures are maintained within the reactor. Each fission event was determined to cause 203.7 MeV to be deposited in the system. Of this 203.7 MeV, 192.9 MeV comes directly from the fission process and 10.8 MeV from (n,γ) reactions in the reactor materials. For each fission event, 193.7 MeV is deposited in the fuel pins, 4.7 MeV in other core materials, and 5.3 MeV in the reflector. The ratio of energy absorbed in any given fuel pin to the energy produced in the associated fuel pin cell is 0.971, regardless of the location of the pin.

Four and forty-one group neutron distributions for the reactor were calculated using the SCAMP S_N code⁽¹⁾ with a radial model consisting of 20 regions. Similar calculations were made for a typical fuel pin cell. The same SCAMP geometrical models were used to calculate gamma ray energy absorption rates. Prompt fission gamma and fission product decay gamma sources were obtained from the literature. Neutron capture (n,γ) sources were calculated using the GAMSOR code⁽²⁾, cross sections from the literature, and neutron fluxes from the four-group SCAMP neutron calculations. Gamma reaction cross sections were calculated with the GAMLEG code⁽³⁾, using additional cross sections from the literature.

Gamma ray dose rates (averaged over the length of the core) are between 1×10^9 and 2×10^9 rads/hr, depending on the atomic number of the material in which the dose rate is calculated.

(1) C. L. Beck, Private Communication, (May 17, 1968); J. B. Fussell, Private Communication, (August 7, 1970).

(2) F. J. Wheeler, Private Communication.

(3) K. D. Lathrop, GAMLEG-A Fortran Code to Produce Multigroup Cross Sections for Photon Transport Calculations, (April 23, 1975).

THREE-DIMENSIONAL PDQ-7 CALCULATIONS WITH THERMAL FEEDBACK FOR
LOFT-I WITH DEPLETION TO 2000 EFPH

B. L. Rushton

In the operating LOFT reactor, the nonuniform spatial distributions of moderator density, moderator temperature, and fuel temperature have an important effect on the overall power distribution and on the magnitude of the power peaking. With the implementation of thermal-hydraulic feedback routines in the Aerojet version of PDQ-7(1), a method was available to include these important feedback effects in the computation of LOFT power distributions as a function of operating time. A three-dimensional model of LOFT-I was developed and the core was depleted from beginning of life (BOL) to 2000 effective full power hours (EFPH) under high flow conditions.

The depletion to 2000 EFPH (end-of-core-life) was accomplished in eight time steps and after each time interval the critical boron concentration was determined. Reactivity lost due to fuel depletion in LOFT is offset by diluting the soluble poison (natural boron) in the coolant. The control rods are held in a banked position 54 inches withdrawn. The analysis provided LOFT support groups with the following information:

1. Three-dimensional power distributions based on high-flow conditions (3.4×10^6 lb/hr) as a function of time ($BOL \leq TIME \leq 2000$ EFPH),
2. Three-dimensional power distribution based on low-flow conditions (2.0×10^6 lb/hr) and 200 - EFPH nuclide concentrations;
3. Reactivity loss rates over the time interval;
4. Parts per million boron required for 55-MW operation over the time interval (control rods withdrawn 54 inches); and,
5. Three-dimensional power distributions for the following combinations of control rod position and reactor power level:
 - a) Control rods withdrawn 24 inches; power level at 70% of full power.
 - b) Control rods withdrawn 36 inches; power level at 90% of full power.
 - c) Control rods withdrawn 45 inches; power level at 107% of full power.

The 200-EFPH results provide information for the point in time when LOFT experiments will probably be initiated. The computed peak-to-average power in the hot pin at BOL was 2.50 with the peak located 7.5 inches below core midplane (control rods withdrawn 54 inches). After 200-EFPH operation, the computed peak-to-average power was 2.43 and the peak location did not shift. With 200-EFPH nuclide concentrations, low-flow conditions were assumed and the computed peak-to-average power was 2.45 with the peak located approximately 10.0 inches below core midplane. The computed peak-linear power density was approximately 19.0 kW/ft for both flow conditions. These are acceptable peaking factors and 19.0 Kw/ft is the specified linear power density.

The LOFT-I has been modeled for three-dimensional analysis using PDQ-7 with thermal-hydraulic feedback routines. Previous cumbersome methods that required iteration by hand between PDQ and the THETA(2) heat transfer code

for thermal feedback effects have been eliminated. The three-dimensional model can be viewed as the best representation available for LOFT reactor physics analysis.

-
- (1) W. R. Cadwell et al., PDQ-7 Reference Manual, WAPD-TM-698, January 1967.
 - (2) C. J. Hocevar, T. M. Wineinger, THETA1-B, A Computer Code for Nuclear Reactor Core Thermal Analysis, IN-1445, February 1971.

THREE-DIMENSIONAL SYNTHESIS CALCULATIONS FOR THE LOFT-I
STUCK ROD ACCIDENT (SHUTDOWN MARGINS, POWER DISTRIBUTIONS
AND RECRITICAL TEMPERATURES)

E. F. Aber

Calculations were performed to provide LOFT support groups with shutdown margins, power distributions, and recritical temperatures for a control-rod configuration having three rod clusters inserted and one rod cluster stuck in the operating band (54 inches withdrawn). Calculations were made for BOL (beginning-of-life), 200 EFPH (effective full power hours), 1000 EFPH, and 2000 EFPH. The information was required for accident analysis.

The shutdown margins (percent shutdown) and power distributions were calculated for the hot-standby condition (540°F uniform-core temperature). The computed shutdown margins were 7.0% ρ at BOL, 6.7% ρ at 2000 EFPH, and 6.5% ρ at 1000 EFPH. Computed values for the peak-to-average power were 3.38 at BOL, 3.27 at 200 EFPH, and 3.12 at 1000 EFPH.

The recritical temperatures following steam-line or feedwater-line rupture were calculated for each depletion time-point. The computed recritical temperatures were 68°F at BOL, 235°F at 200 EFPH, 277°F at 1000 EFPH, and 325°F at 2000 EFPH. The increase during depletion is due to an increase in the negative moderator-temperature coefficients as the boron concentration is reduced. The reactivity with stuck rod is shown in Figure 1.

In the event of a stuck-rod accident, the hot shutdown margin will be greater than 1% ρ for at least 1000 EFPH. If a scram is initiated by a steam-line or feedwater-line rupture, a recritical temperature will be reached during cooldown.

Figure 1. LOFT reactivity with stuck rod.

COMPUTATION OF k_{eff} AS A FUNCTION OF
THE FUEL LOADING SEQUENCE IN LOFT-I

T. Watanabe

The k_{eff} values were computed for two loading sequences to provide initial physics input for LOFT startup. Uniform core temperature of 680°F and a natural boron concentration of 3000 ppm were assumed. The computations were made using the two-dimensional diffusion code PDQ-7 in XY geometry.

The calculated values of k_{eff} are given in the table below. It may be seen that once the center position is loaded, the resulting values for k_{eff} for the subsequent incremental loadings are not affected very much by what sequence is followed.

<u>Sequence</u>	<u>Core Position Loaded</u>	<u>Incremental Number of Pins Loaded</u>	<u>Total Number of Pins Loaded</u>	<u>k_{eff}</u>
1	3	70	70	.397
	5	204	274	.620
	4	204	478	.669
	8	204	682	.715
	1	70	752	.730
	9	70	822	.743
	2	204	1026	.779
	6	204	1230	.809
	7	70	1300	.820
2	3	70	70	.397
	5	204	274	.620
	7	70	344	.636
	4	204	548	.694
	8	204	752	.742
	2	204	956	.768
	6	204	1160	.797
	1	70	1230	.809
	9	70	1300	.820

N

CORE POSITION INDEX

CRITICAL BORON CONCENTRATION VERSUS CONTROL
ROD POSITION IN LOFT-I

D. R. Cooper

For LOFT-1, the critical boron concentrations in the reactor coolant as a function of uniform lattice temperature and control rod position were required input to the LOFT-1 Technical Specifications Report. This information provides data for initial startup and low power physics testing. Additional data for the Technical Specifications Report were computed and provide the boron concentrations that give k_{eff} values of .99 and .90 with all control rod clusters inserted. Also, the calculations showed that the refueling concentration of 3000 ppm was adequate to meet the $k_{eff} = .90$ criteria with the control rods fully withdrawn as set forth in the Technical Specifications.

The calculations were performed using the PDQ-7 code⁽¹⁾ and the "window shade" technique in which radial bucklings are first computed for the control rods fully inserted and fully withdrawn. These configurations are computed in the X-Y geometry for the necessary temperatures and boron concentrations. These resulting radial bucklings provide leakage terms when input to the PDQ calculation in the Z direction. This approximation to the three-dimensional solution provides a means for computing a large number of configurations economically. Using this technique, the critical boron concentrations as a function of banked control rod position and uniform lattice temperature were determined. A subsequent check on the accuracy of the "window shade" approach in LOFT was made using the XYZ flux synthesis technique⁽²⁾. The agreement was within 0.5 percent in reactivity or 50 parts-per million natural boron in the coolant. This is good agreement and is typical for such comparisons.

A series of calculations was completed to support the LOFT Technical Specifications Report, and the initial startup. Data were reported in graphical form for general use⁽³⁾.

-
- (1) W. R. Cadwell, et al, PDQ-7 Reference Manual , WAPD-TM-698, January 1967.
 - (2) T. E. Young, Internal Report, to be published.
 - (3) M. N. Munson, Internal Report, March 1975.

THREE-DIMENSIONAL PDQ-7 CALCULATIONS FOR REPLACEMENT OF
THE LOFT-I CENTRAL FUEL MODULE AFTER 200 EFPH

E. F. Aber

After completion of a LOFT-I test, one or more fuel modules may be removed for inspection. The purpose of this study was to determine if replacement of the central assembly after 200 EFPH (effective full power hours) would significantly change reactivity coefficients, rod worth, or power distributions.

The depleted assembly was replaced with a fresh 15 X 15 fuel module, identical to the original assembly. The remaining fuel modules had nuclide concentrations based on 200 EFPH and a long shutdown time (42 days). Control rod worth, temperature coefficients, boron worth, and power distribution were determined after replacement of the central assembly. Previous work has established the effect of depletion upon these parameters(1).

The computer inverse boron worth under hot operating conditions was 131.6 $\Delta\text{ppm}/\% \Delta\rho$. For comparison, the 200 EFPH value before replacement of the central assembly was 127.4 $\Delta\text{ppm}/\% \Delta\rho$. Temperature coefficients were computed at constant boron concentration (800 ppm) and constant rod position (54 inches withdrawn). The coefficients were well within the limits set for accident analysis. Control rod worth was computed for the cold (68°F) reactor. The net rod worth from the operating band (54 inches withdrawn) was 11.5% ρ . For comparison, the BOL and 1000 EFPH values were both 11.8% ρ . The computed power distribution was not significantly different from the BOL distribution.

The replacement of the central fuel assembly after 200 EFPH has no significant effect upon the magnitude of computed values of temperature coefficients, boron worth, or rod worth. The power distribution is essentially the same as the BOL and additional thermal analysis should not be required.

(1) T. E. Young, Internal Report, April 25, 1975.

EFFECT OF FUEL BURNUP ON LOFT TEMPERATURE COEFFICIENTS,
BORON WORTH, AND CONTROL ROD WORTH

T. E. Young

The purpose of the present investigation was to determine the effect of 1000 effective-full-power-hours (1000 EFPH) operation on the temperature coefficients, boron worths, and rod worths computed for LOFT-I. After depletion to 1000 EFPH, there will be changes in fuel and fission product concentrations, and a resulting change in the critical boron concentration. The effects of changes in boron concentration on moderator- and fuel-temperature coefficients and boron worth have been reported⁽¹⁾. The present calculations were performed to determine if the previous beginning-of-life (BOL) results are applicable after 1000-EFPH of operation. These data are used primarily for accident analysis.

In order to isolate the effects of depletion, temperature coefficients were computed at BOL and 1000 EFPH (full power = 55 MW) for constant boron concentration (800 ppm) and constant rod position (54-inches withdrawn). For the reactor at a uniform temperature of 580°F, the overall-temperature coefficient (moderator + fuel) changes from $-34.9 \times 10^{-5} \Delta\rho/\Delta^\circ\text{F}$ at BOL to $-37.0 \times 10^{-5} \Delta\rho/\Delta^\circ\text{F}$ at 1000 EFPH. The corresponding fuel-temperature coefficient changes from $-1.23 \times 10^{-5} \Delta\rho/\Delta^\circ\text{F}$ at BOL to $-1.27 \times 10^{-5} \Delta\rho/\Delta^\circ\text{F}$ at 1000 EFPH. The corresponding moderator-temperature coefficient changes from $-33.7 \times 10^{-5} \Delta\rho/\Delta^\circ\text{F}$ at BOL to $35.7 \times 10^{-5} \Delta\rho/\Delta^\circ\text{F}$ at 1000 EFPH. The limits for such small percentage changes.

Inverse boron worth at hot operating conditions after depletion to 1000 EFPH is 128.63 ppm/% $\Delta\rho$. The corresponding value at BOL is 127.18 ppm/% $\Delta\rho$.⁽²⁾ For the reactor at a uniform 68°F after depletion to 1000 EFPH, the inverse boron worth is 100.30 ppm/% $\Delta\rho$. The corresponding value at BOL is 99.5 ppm/% $\Delta\rho$, from Reference 1.

Control rod worths were determined for the cold (68°F) reactor. At BOL the reactivity worth is 11.84%, and at 1000 EFPH it is 11.76%.

These results show that depletion (and fission-product buildup) produced by operation of LOFT-I to 1000 EFPH has little effect on the magnitude of computed values of temperature coefficients, boron worth, and rod worth. The largest percentage changes are in the moderator- and overall-temperature coefficients, which increase 6% in absolute magnitude as the result of depletion to 1000 EFPH.

Temperature coefficients, control rod worth, and inverse boron worth have previously been computed for LOFT-I at beginning-of-life. The maximum and minimum values of moderator- and fuel-temperature coefficients for accident analysis were based on that data. In this study, the effects on these parameters of depletion to 1000-effective-full-power-hours (1000 EFPH) were determined. Depletion over this time interval had very little effect on the magnitude of the parameters.

(1) A. J. Scott, Internal Report, August 31, 1973.

(2) B. L. Rushton, Internal Report, November 21, 1974.

PBF FUEL ROD MOTION SENSORS

G. D. Lassahn

Two devices were constructed to measure the motion of the top ends of two PBF fuel pins relative to the canister walls in two directions.

The devices were installed on fuel pin B2 in canister B12 and on pin F2 in canister A1. These sensitivities are expected to be applicable over a position range of ± 0.1 inch, corresponding to an output voltage in the range 0 to 1 volt. In each of the sensors, a more positive output voltage indicates that the fuel pin is closer to the canister wall.

The sensors are linear variable differential transformers (LVDT's) Model 100 MHR, made by Schaevitz Engineering. They are used with electronic modules GPM-105, also from Schaevitz.

The sensor mounting assembly is designed to be installed while the water in the reactor is at the normal operating depths. An installation tool was supplied with the sensor assemblies. It consists of a long metal rod threaded at one end, so that it can be screwed into the top of the sensor assembly. The installation procedure consists of pushing the sensor firmly down over the fuel pin end cap, and then unscrewing the installation tool from the sensor assembly.

FABRICATION OF INTERNALLY INSTRUMENTED ZIRCALOY CLAD FUEL RODS

J. D. Schmutz

A vital part of any fuel behavior study program is the measurement of internal conditions in individual fuel rods during reactor operation. To do this, instruments and/or methods must be developed to instrument fuel rods while keeping their characteristics as nearly typical of normal fuel rods as possible. Since most PWR fuel rods have Zircaloy cladding, it becomes necessary to find ways of working with this material.

The greatest single problem encountered in instrumenting Zircaloy clad fuel rods is that of penetrating the cladding. Most available instruments and instrument leads are stainless or Inconel, neither of which is compatible with Zircaloy. A silver braze joint between a Zircaloy end cap and a stainless steel tube that previously appeared to be a good solution to the problem⁽¹⁾ proved to be unreliable in the reactor environment. A new design of the end cap employing titanium explosively bonded to Inconel proved to be an acceptable solution. This material was used to form a transition between Zircaloy cladding and the stainless steel lead penetrations. The titanium can be welded very readily to the Zircaloy and stainless steel welds nicely to Inconel. The present configuration of the fuel rod is shown in Figure 1. An Inconel pressure transducer⁽²⁾ at the top of the rod measures internal gas pressure. It is welded to an adapter of stainless steel that contains penetrations for the signal leads of a centerline temperature sensor, a gas plenum TC, and for the gas fill tube. The penetration is made by brazing a small weld adapter onto the lead at the point of penetration, and then, after installation, welding the adapter into the fuel rod end cap as shown. Not shown in the figure is a .020" O.D. thermocouple which is to measure the temperature in the gas plenum above the fuel. It passes through a similar penetration in the plane perpendicular to the page. The stainless steel part of the assembly is welded to the Inconel end of the transition piece which is welded to the Zircaloy fuel rod as shown. To reduce the void volume to that more typical of a standard fuel rod, the space in the upper part of the assembly is occupied by filler blocks. The centerline temperature sensor may be either a high temperature thermocouple⁽³⁾ or an ultrasonic thermometer.⁽⁴⁾

After the fuel rod is assembled, the void volume of the rod is measured. This is done by allowing the gas in the fuel rod, originally at atmospheric pressure, to expand into an evacuated, calibrated volume. The resultant pressure is measured, and assuming the perfect gas law, the fuel rod void volume is calculated.

The fuel rod is then backfilled with helium to the desired pressure, the fill tube is pinched, and while pinched, the end is seal welded.

One fuel rod assembled in this manner has been tested with satisfactory results and a second is ready for test. In conclusion, Zircaloy clad fuel rods have been fabricated with pressure and temperature sensors that

measure internal pressure and temperature satisfactorily. While work remains to be done to increase the number and kind of measurements that can be made, it has been demonstrated that the instrumentation of Zircaloy clad fuel rods is possible without jeopardizing the integrity of the fuel rod or reactor.

-
- (1) J. D. Schmutz, S. C. Wilkins, A. E. Arave, Nuclear Technology Division Annual Progress Report for Period Ending June 30, 1974, ANCR 1177 (Jan. 1975) 272.
 - (2) T. C. Piper, Nuclear Technology Division Annual Progress Report for Period ending June 30, 1974, ANCR-1177 (Jan. 1975) 300.
 - (3) S. C. Wilkins, "An Improved Ta/SST Transition Thermocouple" This Report.
 - (4) A. E. Arave and R. H. Meservey, Internal Report (August 1970):

Figure 1. Schematic diagram of PCM-20 fuel rod end cap.

TI/INCONEL FUEL ROD END CAP TESTING

J. D. Schmutz

One of the greatest problems in instrumenting Zircaloy clad fuel rods is the transition from Zircaloy to stainless steel to allow the penetration of stainless steel sheathed leads or the attachment of stainless steel transducers. Because titanium and Zircaloy are compatible and Inconel and stainless steel are compatible, it was decided to use the explosively bonded Ti/Inconel plate that was available. Before using it in a fuel rod end cap assembly, however, it was necessary to verify that it would survive the environment and the loads that would be placed upon it.

The material was available in blocks from which finished end caps could be machined. To verify that the material would meet requirements for fuel rod end cap use, sixteen pieces were cut from a block of the material. At the same time a 1/32" thick wafer of material was cut from between each two adjacent end cap pieces. These wafers were checked with dye penetrant for evidence of cracks or porosity in the bond area. They were then retained for future testing should that be desirable.

Each of the sixteen end caps were also dye-checked. Then seven pieces were chosen at random for further testing. Each of the seven was sealed to form a capsule with 550 psi internal helium pressure as they would be when used in fuel rods. These capsules were then placed in an autoclave which operated at 650°F and 2250 psi for a total of 200 hours. The autoclave test was interrupted at 50 and 100 hours to leak check the samples. The samples were then vented to atmosphere and thermally cycled from <100°F to 650°F for a total of 40 cycles*. The samples were again leak checked and dye checked. No failures, i.e., cracks or leaks, were detected. The samples were checked for yielding or creep in the area of the explosion bond, but no changes in diameter were detectable.

After considering the data obtained from these tests, it was concluded that this material is acceptable for use in the Zircaloy clad fuel rods. Actual use in reactor tests⁽¹⁾ subsequent to the tests has born this conclusion out.

* There was one exception. One sample was left pressurized so that it had in excess of 550 psi inside with atmospheric pressure outside. No difference in its behavior was observed.

(1) J. D. Schmutz, Internally Instrumented Zircaloy Fuel Rods.

THERMAL CYCLING AND CALIBRATION OF
ZIRCALOY-SHEATHED CLADDING THERMOCOUPLE

S. C. Wilkins

The accuracy and reliability of any thermocouple are major criteria for its adoption in a particular application. Testing of a Zircaloy-sheathed, BeO-insulated fuel rod cladding thermocouple with tungsten-5% rhenium and tungsten-26% rhenium thermoelements has been carried out. Calibration to approximately 3000°F (1650°C) and thermal cycling from ambient to as high as 2800°F (1540°C) were conducted.

The thermocouple is constructed with a plug-type junction. A short length of Zircaloy wire is inserted in the end of the swaged cable prior to welding the grounded junction closed. The brittleness of the tungsten-rhenium wires after an initial thermal cycle was a source of concern with regard to the thermal cycling ability of the sensor. In addition, the possibility of a shift in calibration after once being at temperature was to be checked. The test thermocouple output during three calibration cycles up to approximately 3000°F (1650°C), did not vary more than $\pm 1.5\%$ from the standard calibration curve for W5Re/W26Re, referenced to a bare-wire thermocouple of the same type. The continuity of the thermocouple, as indicated by changes in wire-wire and wire-sheath resistances, was monitored during twelve additional cycles up to 2800°F (1540°C). No open circuits or resistance degradation was found during cycling.

Confidence in the thermal cycling ability of Zircaloy-sheathed cladding thermocouples and in the repeatability of their output has been enhanced through test results. Such thermocouples have subsequently been used successfully in the Power Burst Facility (PBF).

Semiscale

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

EFFECTS OF CABLE LENGTH ON LOFT DTT PERFORMANCE

G. D. Lassahn

The drag-disk part of the LOFT drag-disk turbine transducer (DTT) has on occasion exhibited some temperature dependence. This work was undertaken to determine whether this temperature dependence was due to the cables between the transducer and the electronics module, and what the effects of these cables are in general.

The pertinent aspects of the system studied are indicated schematically in Figure 1. This system has been described by T. C. Piper and J. B. Colson.⁽¹⁾

The variable reluctance transducer (VRT) consists of a solenoid with a center tap and a movable magnetic core shorter than the solenoid. When the core is displaced from the center of the solenoid, the inductive impedance is not equal in the two halves of the coil. There then appears at the coil center tap a voltage with amplitude approximately proportional to the core displacement.

Five cable segments in series connect the VRT to the electronics module. The properties of these five cable segments are listed in Table 1. The various cable lengths are different for different installations, and the values in Table 1 represent the greatest cable lengths. In this sense, the calculations based on these values represent the worst case of cable effects.

The driving circuit is arranged so that there is a constant amplitude 3000 Hz current through the secondary of transformer T1, independent of normal impedance variations in the VRT. In operation, the position of the tap on resistor R1 is adjusted to minimize the amplitude of the voltage D, to compensate for whatever resistive imbalance there may be in the probe. Then the phase of the reference voltage into the demodulator is adjusted so that there is no change in the demodulator output when switch S1 is opened. This is to eliminate the effects of variations in resistive imbalance in the VRT, such as might result from uneven heating of the VRT coils.

There are three distinct effects that the cables can have on the operation of this system:

1. The input impedance into the cable - VRT combination is different from the input impedance into the VRT without the cable.
2. There could be current attenuation in the cable; that is, the current at the electronics end of the cable could have a different amplitude than the current at the VRT end of the cable.
3. There could be a phase shift in the cable; that is, the current at the electronics end of the cable could have a different phase than the current at the VRT end of the cable.

It was analytically determined that the most significant cable effect was the input impedance into the cable - VRT combination is different from the input impedance into the VRT without the cable. The input values for the extreme cases can be used in a mathematical analysis to estimate the effects of the impedance changes on the VRT system performance.

The system sensitivity changes by -1.8% when the cable is added to a cold probe. Thus, we see that the first significant effect of the cables is to decrease by about 1.8% the sensitivity of the system. The second significant effect is that it introduces a change in the temperature dependence of the system, which can cause errors of about 1.6%.

It is not possible to use one resistance value to optimally compensate for temperature changes both with and without the cable in the system. Furthermore, the correction with the cable will be different for different transducer installations, because cable lengths are different. One reasonable procedure would be to calculate the temperature sensitivity for each installation and to correct for the temperature sensitivity in the data analysis.

(1) T. C. Piper and J. B. Colson, Internal Report (November 1963).

TABLE 1: CABLE PROPERTIES

Cable Location	Cable Length (meters)	r (ohm/meter)	C _s (farad/meter)	C _g (farad/meter)	L (henry/meter)	Comments
VRT to reactor vessel penetration	6.1	0.677 at 75°F 1.317 at 600°F	2.21x10 ⁻¹⁰ at 75°F 2.38x10 ⁻¹⁰ at 600°F	3.36x10 ⁻¹⁰ at 75°F 3.52x10 ⁻¹⁰ at 600°F	2.52x10 ⁻⁷	r, C _s , & C _g measured directly L estimated.
inside reactor vessel penetration	1.2	0.106 at 75°F 0.16 average at 600°F	1.4x10 ⁻¹⁰	2.1x10 ⁻¹⁰	2.0x10 ⁻⁷	r calculated from wire gauge and composition; L, C _s , & C _g estimated.
reactor vessel penetration to MTA terminal box	3.05	0.066	1.3x10 ⁻¹⁰	1.9x10 ⁻¹⁰	2.1x10 ⁻⁷	r calculated from wire gauge and composition; L, C _s , C _g estimated.
MTA terminal box to containment penetration	6.1	0.021	1.17x10 ⁻¹⁰	1.8x10 ⁻¹⁰	2.4x10 ⁻⁷	r calculated from wire gauge and composition; C _s , & C _g estimated from specification E-109; L estimated.
containment penetration to room 219	45.7	0.021	1.17x10 ⁻¹⁰	1.8x10 ⁻¹⁰	2.4x10 ⁻⁷	r calculated from wire gauge and composition; C _s & C _g estimated from specification E-109; L estimated.

NOTE: In all cases the conductance across the cable insulation is negligible compared with the capacitance term.

Figure 1. Schematic of DTT VRT system.

LOFT SUPPRESSION TANK SIMULATION
TESTING IN SEMISCALE FACILITY

J. M. Strong

The LOFT Program Branch required an additional data system at Semiscale for testing of the LOFT suppression tank simulation. Parameters to be monitored were tank loads, internal pressures and temperatures, and external strains of the vessel. The responsibility was for the total system—sensors, signal conditioning, acquisition and useable data. The data was to be recorded on magnetic tape and reduced at the LOFT facility computer.

The original system consisted of 15 channels of strain gage instrumentation fed to the tape recorders. Eighteen thermocouples on an internal rack were amplified and fed to a Visicorder. Four load cells of the piezoelectric type were recorded on the tape recorder. Six piezoelectric type pressure transducers were also recorded. Timing was accomplished by using the IRIG signal from the Semiscale data system to the tape recorders. Some signals were recorded on a Visicorder and timing reference was provided from rupture disc pressure.

Testing during blowdowns as selected by LOFT Program to obtain data to be extrapolated to the LOFT suppression tank. Several tests were conducted and modifications were made to obtain the data wanted. In place calibration of the load cells was also made to verify the calibration data.

The latest configuration of the system that is still in operation employs four load channels, ten pressure channels (nine are of the piezoelectric and one of the strain gage type), and selected thermocouple channels as the two recorders will permit.

Data have been taken on several tests and are continuing. Several problems have been met and successfully overcome such as signal noise, loading effects, and scheduling. Conclusive results have not been deduced as yet, but the system appears to be giving adequate information.

SEMISCALE HEATER POWER MONITOR SYSTEM

J. G. Richardson

The Semiscale Heater Power Monitor System was developed to prevent a sequential burnout of the semiscale core by automatically monitoring the current through each of the forty heaters. If an excessively low heater current is detected, the monitor system will automatically remove power from the entire core.

The current through each of the forty heaters is monitored via a hall-effect device. Each channel has a comparator set for the lowest acceptable heater current level. During normal operation, a very low heater current indicates an open heating element. Because the core heaters are paralleled in a constant current configuration, an open failure of one heater causes a rise in current through each of the remaining heaters, thus increasing their probability of their failure.

If low heater current is detected, the Heater Power Monitor System will remove power from the entire core. The defective heater can then be readily identified by repowering the core at a low level and observing the heater monitor panel on the unit.

In addition to its primary function of heater power monitoring, the system also observes total core power following a 6% core power trip. If actual core power has not decayed below the 6% level after a preset time following a trip, the system will automatically remove all power from the core and raise an audible alarm.

The Semiscale Heater Power Monitor System is performing satisfactorily and has, under normal operating conditions, successfully detected a heater failure and shut down the core.

SEMISCALE TEST OPERATIONAL MODIFICATIONS AND START UP

K.A. Ward and A.D. Hill

The power and control system for the Semi-Scale test program was designed by personnel from the Electrical & Instrumentation Design Section. They also closely supervised installation and checkout in the EBOR facility. The first test was successfully conducted in September 1974. Immediately a program was initiated to upgrade the system to improve flexibility, shorten turn around time, and to provide additional control capability in the conduct of the tests. The principle control and hardware modifications completed during FY-1975 are as follows:

1. Load tested core power supply system and prepared system for 1.6MW power core.
2. Redesigned the core power control system to include additional safety trips and separation of 13.8 KV breaker trip cables to meet SFA criteria. All power adjustments designed to control power to the core heaters are effected by the adjustment of a 0 to -9 volt control signal. Redundant safety trips that were added to interrupt this control signal are: 1250°F Preblowdown, 1800°F, variable temperature-power, loss of control console and DAS power (non-redundant), low primary coolant flow, low primary coolant pressure, high primary coolant pressure, high primary coolant temperature (non-redundant), and operating loop pump interlock (non-redundant).
3. 220 volt pressurizer heaters were replaced with 480 volt units and the power supply system modified to handle the increased power requirements. This was done to facilitate a faster heat-up and thus permit a shorter test turn around.
4. Addition of a Data Trak controller to the control system that enables the core power to be continuously varied as a function of time in accordance with pre-programmed plot.
5. Completed design of the new pressure suppression system steam controls to be used in controlling the flow and pressure of steam entering the pressure suppression tank.
6. Added a second pump speed control circuit to the operating loop pump.
7. Modified nitrogen valve control circuit and relocated control of N₂ and Heise valves from panel 190 to panel 200.

The above modifications have been made, checked out, and placed into operation. Each of these jobs were completed without interruption to the overall Semiscale test schedule.

INFRARED SCAN EVALUATION OF SEMISCALE HEATER RODS

J. M. Strong

An infrared scanner system was to be used to scan the heater rods for integrity and to locate any anomalies which would terminate Semiscale testing prematurely. This nondestructive type of testing had been employed at other national laboratories, but needed to be perfected for our particular usage.

The equipment consisted of an infrared scanner which made a horizontal line scan. The signal output was transferred to an oscilloscope which was monitored by a closed circuit TV camera. The camera output was fed to a video tape recorder for a permanent record of the test. The heater rods were mounted in an insulated jig that allowed vertical alignment. The testing was accomplished by applying a DC current of several hundred amperes to the heater coils on the clad for a one second interval. This current was derived from ordinary automotive batteries in series to give the proper current for the desired temperature gradient. The switching was accomplished by a heavy duty circuit breaker type switch actuated by an oscillator controlled timer. The block diagram is shown in Figure 1.

The project consisted of accumulating the necessary components, installing and checking out the system, familiarization by use of various techniques, writing a set up and test procedure, and actually testing the Semiscale rods.

In preparing the procedures several techniques were employed using light sources and "hot" bodies to acquaint the personnel with the capabilities of the system. Vertical and horizontal positions with their limits were necessary to evaluate the data. Several "old" heater rods and mock up devices were heated and viewed before actual operation could take place with confidence.

Testing was carried out successfully on 60 low power heater rods in the fall of 1974. The speed with which these rods were tested was a pleasant surprise. No obvious anomalies were observed so that further investigations were unnecessary. In the late spring of 1975 ten high power heater rods were tested. These also had good results. A typical scan is shown in Figure 2. The trace shows a typical temperature profile as obtained with this means of testing.

Figure 1. Transient tests.

Figure 2: Representative scan of high power heater

SEMISCALE DOWNCOMER ECC PERFORMANCE

C. J. Shaffer

Analytical support to the Semiscale Blowdown and Emergency Core Cooling (ECC) Project's first test series of the MOD-1 system consisted of analyzing the downcomer-related ECC performance. The MOD-1 system is a small-scale experimental program whose purpose is to investigate the behavior of a light-water nuclear reactor during a loss-of-coolant accident. Understanding of the performance of the ECC in the downcomer region of the MOD-1 system is necessary for predicting ECC delivery to the core.

The analysis consisted of predicting the downcomer ECC performance prior to the test, examining the test data, and explaining deviations from theory. The hot-wall countercurrent flow-predictive-method previously developed was used to predict the ECC performance. The ECC performance involves a delay in ECC delivery to the lower plenum due to countercurrent steam flow caused by blowdown and hot-wall generated steam. The forces exerted on the ECC flow by this countercurrent steam flow may be large enough to partially or fully negate the gravitational force acting on the ECC flow. RELAP 4 calculated input to the predictive model and by downcomer insulator leakage. Analysis has verified the countercurrent flow hot-wall predictive theory as a valid method for predicting downcomer ECC performance in the semiscale vessel.

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

Non-Nuclear Programs

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

CONCEPTUAL DESIGN OF LIQUID FUEL AND TEMPERATURE MEASUREMENT
SYSTEM FOR THE CPP WASTE STORAGE TANK FARM

T. B. Klingler

A conceptual design was performed for a new instrumentation system to continuously monitor the level and temperature of the liquid waste in the eleven tanks in the CPP Liquid Waste Storage Tank Farm. The design concept was to provide a system which would have high accuracy and reliability and would remain operable in the liquid waste environment for a period of several years. A block diagram of the design concept is shown in Figure 1.

Liquid level in each of the eleven tanks will be measured with a resonant cavity detector. The theory of operation of this detector is based on the relationship that exists between the length of a cavity and its resonant frequencies. By immersing a perforated cavity in a highly conductive liquid, cavity length will be defined by the liquid level. By measuring the resonant frequencies of the cavity, its length can be determined, thus defining liquid level. A model of the system has been evaluated in the laboratory giving detectable changes in level of as little as 0.005 inches in a twenty-eight foot column.

The power to the level detector is an RF frequency in the range of 500 to 1000 MHz. The RF frequencies are generated and controlled by an RF synthesizer and an automatic measurement and control system. The control system can be programmed to perform the following functions:

1. Select a particular waste storage tank to be monitored.
2. Set at a preprogrammed value the level of RF power to be inserted into the system by the synthesizer and RF amplifier. The greatest power requirement for each channel is to compensate for insertion losses of the RF cable. The length of line to each tank is different, thus establishing a unique power requirement for each tank level measurement.
3. The system controls a synthesizer frequency scan through a pre-selected spectrum in selected increments for each tank level measurement. The level detector output data resulting from these frequency scans will be used to calculate the resonant frequency of the cavity and subsequently the liquid level. If the scan frequency is broad enough to require RF power level adjustment during the frequency scan to compensate for variance in cable insertion losses, the system has the capability of programming to compensate for such losses.
4. The system has built-in alarm capability with programmable limits on the parameters of each channel.
5. The system possesses self-check capability. It is not under

constant personnel surveillance; therefore, it has been designed to check its own system vital signs and sound an alarm if adverse conditions are detected.

The liquid waste temperature will be measured in each of the eleven storage tanks with thermocouples inserted in the tube constituting the center electrode of the level detector. The thermocouples are designed for high reliability and longevity. The thermocouples are chromel-alumel (Type K calibration) with swaged stainless steel sheath and magnesium oxide insulation. The thermocouple installation will provide spring loading to hold the thermocouple against the wall of the tube, thus assuring good thermal conductivity between the liquid waste and the thermocouple hot junction.

The proposed design will provide very rugged measurement components in the liquid waste environment. This is essentially due to the contaminants involved which makes repair of components after insertion extremely difficult. The liquid level system has displayed high accuracy, and even if a factor of 10 increase is allowed over the laboratory tests due to less ideal conditions, the 0.05-inch sensitivity would equate to 60 gallons of volumetric change in the 300,000 gallon storage tank, which is well within established requirements.

Figure 2-1. Conceptual design of CPP tank farm instrumentation system.

Figure 2-1 continued

CONVERSION OF A 400-IN³ I.C. ENGINE TO OPERATE ON HYDROGEN

F. B. Simpson, D. R. Swope, J. H. Lofthouse

The fuel shortage has stimulated much interest in the development of synthetic fuels for transportation. Because of the different characteristics of synthetic fuels a training program to convert conventional internal combustion engines to operate on hydrogen was initiated at Billings Energy Research Corporation. This program is in support of the joint proposal between Aerojet Nuclear Company and Billings Energy Research Corporation to operate part of the INEL bus fleet on hydrogen fuel as a demonstration program.

This project includes the conversion of a 400-cubic-inch 1975 Pontiac engine to operate on hydrogen and testing its performance on a dynamometer.

GEOHERMAL STEAM PLANT MODELING AND POWER TRADE-OFF STUDIES

C. J. Shaffer

Analytical support to the geothermal project consisted of modeling a multistage steam-flash electric generating plant and performing power trade off studies to determine optimum operating conditions. The model will provide calculational capability to plant designers and provide insight as to the more sensitive and significant parameters.

The model contains the flashers (up to 4 stages), preflasher, turbine, condensers, air ejectors, cooling tower, and pumps. The model is capable of tracking nitrogen and carbon-dioxide which are initially dissolved in the geothermal brine throughout the plant in both the dissolved and free states and then computes the steam flow necessary to drive the air ejectors to remove the gases from the condensers. The model also computes the significant frictional piping pressure drops throughout the plant. The model has been programmed for the IBM-360 and is fully operational.

Sensitivity studies were performed on significant parameters such as the initial dissolved gas concentrations, air ejector effectiveness, condenser pressure, brine temperature, number of flashes, flash pressures, relative humidity and atmospheric air temperature. The results are correlated according to the brine flow rate necessary to generate 10 MW net electricity. These sensitivity studies shed light on power trade-off options such as the optimum number of flash stages, uses of a preflasher, and condenser pressure which will be useful in an actual plant design.

HEAT FLOW MEASUREMENTS IN SNOW FIELDS COVERING PROSPECTIVE GEOTHERMAL AREAS

J. A. Close and P. R. Napper

A major geothermal exploration effort is commencing in the United States. New techniques will improve the efficiency of this work. A quick and inexpensive method for determining geothermal heat flux has been devised for areas which have substantial snowfall.

Snow is an excellent insulator and serves as an excellent medium in which to make heat flow measurements. Fourier's law of heat conduction in a slab can be applied to a snow field to determine the heat flow. Fourier's Law is:

$$q = k_{\text{eff}} \frac{(T_2 - T_1)}{(Z_2 - Z_1)}$$

where q is the heat flow in $\text{cal/cm}^2\text{-sec.}$, $T_2 - T_1$ is the measured temperature difference and $Z_2 - Z_1$ is the elevation increment in which the temperature difference occurs. k_{eff} is the effective thermal conductivity of the snow. The thermal conductivity of the snow is determined by relating thermal conductivity to snow density⁽¹⁾.

Portable lightweight equipment was designed and constructed for field tests. A temperature probe using a battery-operated temperature transducer was built which gives a reading proportional to the snow temperature. Snow density values were obtained from samples cut from a column of snow at the location of the temperature measurements using a lightweight snow sectioning device. The separate snow cores were placed in sample containers for determination of water content at a later time. The complete set of equipment fits in a small sled or pack for transportation to the area of interest.

Field tests were conducted in the Raft River area of southern Idaho during the early part of January 1975. This location was chosen to test the method because of the relatively heavy snow accumulation at that time and because the area is a known geothermal area.

Three sets of data were obtained, two sets in one area and one set in another area. Both areas are suspected of having higher than normal heat flows (normal heat flow is from 1 to 2 $\mu\text{cal/cm}^2\text{-sec}^{(2)}$). The temperature profiles through the snow pack in these areas are shown in Figure 1 and exhibit temperatures around 0°C at ground level to as low as -9°C within the snow pack. The measured snow densities at the two areas ranged from 0.233 gm/cm^3 to 0.256 gm/cm^3 which correspond to a thermal conductivity of about $4.6 \times 10^{-4} \text{ cal/sec-cm-}^\circ\text{C}$.

The heat flow calculated from the three sets of data averaged about $170 \mu\text{cal/sec-cm}^2$, almost 100 times greater than the normal heat flow for a nongeothermal area.

The results of these preliminary field tests indicate that the method is applicable but probably produces higher values of heat flow than are actually present. Additional tests are needed in other areas along with independent heat flow measurements using other methods of heat flow determination to determine the accuracy of this new method.

-
- (1) Thermal conductivity of snow at a density of 0.25 g/cm^3 is $4.6 \times 10^{-4} \text{ cal/sec-cm-}^\circ\text{C}$ according to D. Pitnam and B. Zuckerman, "Effective Thermal Conductivity of Snow at -88° , -27° , and -5°C " in Journal of Applied Physics 38(6) 1967, pp. 2698-9.
 - (2) The average heat flow on continents is $1.2 \mu\text{cal/cm}^2\text{-sec.}$ according to L. J. P. Muffler and D. E. White, "Geothermal Energy" in The Science Teacher, Vol. 39. No. 3, March 1972.

Figure 1. Temperature profiles at the three test sites.

RADON EMISSION DISTRIBUTION NEAR RAFT RIVER GEOTHERMAL AREAS

J. H. Lofthouse, C. G. Cooper, F. B. Simpson

The advent of the "energy crisis" which has brought about greater interest in geothermal energy development has resulted in an accelerated interest in techniques for locating promising drill site locations. One technique which shows promise is mapping of the radon emission rate from the ground surface around known geothermal areas such as hot springs. It has been found that radon, the gaseous daughter product of radium which lies in the uranium decay chain, is emitted from the ground surface in much higher concentrations near some geothermal areas than would normally be expected.⁽¹⁾

An inexperienced method has been devised to obtain the relative radon emission rate at many mapping locations utilizing alpha track counting techniques.⁽²⁾ Briefly the method consists of placing small plastic detectors in inverted cups at locations of interest in the field. Radioactive radon gas is collected in the inverted cup at the ground surface. When the radon decays with its characteristic alpha emission a certain number of the alpha particles will impinge on the plastic detector surface causing minute molecular dislocations (holes). After a suitable exposure period the plastic detectors are collected and chemically etched with a strong base which enlarges the holes to a size suitable for counting under a microscope.

This mapping technique was tried in the Raft River Valley at locations near the present geothermal drill site in an effort to get experience and perfect the technique at INEL. Approximately 300 detectors were placed in the field during the winter month of February 1975 and collected six to eight weeks later. The detectors used were small chips of Lexan about 1 inch square, secured with two-sided sticky tape to the bottom of a plastic dish about 2-1/2 inches deep and 3 inches in diameter. The dishes were placed in an inverted position at the bottom of a hole drilled in the top soil to penetrate the frost layer.

After some experimentation with Lexan chips exposed to known alpha sources, a suitable concentration of the potassium hydroxide etching solution and the etching time was established, after which the detectors exposed in the field were processed. The results were not entirely satisfactory. Large variations in track density from location to location existed where rather uniform densities would be expected. The suspected cause of this anomaly was the condensation of water droplets on the detector surface due to soil moisture and large daily variations of temperature during the wet spring months when the detectors were in the field. Future experiments should be conducted during the dry summer months. Also a survey of literature suggests that plastic films other than Lexan have been used which are more sensitive, but also more fragile. These films should be evaluated for possible field use.

(1) H. A. Wollenberg, Radon Alpha-Track Survey of a Potential Geothermal Resource Area, (October 28, 1974).

(2) H. W. Alter, P. B. Price, Radon Detection, U.S. Patent # 3,665,194, (May 23, 1972).

EFFECTS OF GEOTHERMAL POWER PLANT COOLING WATER
WELLS OF RAFT RIVER BASIN COLD WATER AQUIFER HYDROLOGY

J. H. Lofthouse

Either large air cooling towers or substantial quantities of cold water, or a combination of both will be required to condense the working fluid for a geothermal driven power plant in the Raft River Basin of southern Idaho. The cooling water requirements are estimated to be about 15,000 gallons per minute for a nominal 10-megawatt electrical generating plant. Since all of this water would have to be pumped from the cold water aquifer in the region near the power plant it could have significant effects on other water users, mainly agricultural irrigation pumping, in the basin. Since several production and re-injection wells would be required, their placement with respect to each other and other wells in the area is an important design feature.

An investigation of these problems was initiated with the aid of a computer code obtained from the Idaho Bureau of Mines and Geology which models the hydrology of the Raft River valley(1). This code solves by finite difference methods a two-dimensional parabolic equation describing the mass transfer of water in an aquifer. The model allows for the natural elevation gradient of the aquifer and for boundary and steam recharge on a seasonal basis. The code, as received, was set up with a 1/2-mile mesh spacing. Pumping and re-injection wells, which are handled as sinks and sources in the model, can be modeled at discrete mesh points. Data for the existing pumping wells along with the permeability, initial hydraulic head, and saturated thickness of the aquifer were received with the code. The method by which these data were developed is described in Reference 1.

Some modifications were made to the FORTRAN Code to allow easy input of additional pumping and re-injection wells at selected mesh points to simulate wells required for a 10-MW geothermal power plant. Modifications were also made to the output routine to provide monitoring the hydraulic head at mesh locations for selected periods of pumping. Meshpoints are identified by row and column numbers. Figure 1 shows the modeled aquifer boundary and the approximate location of the geothermal well site on the grid.

Trial data on the effects of pumping for a geothermal power plant are shown in Tables 1 and 2 for two different well arrangements. The numbers in the tables represent the change in the water table height at the indicated meshpoints after 10 years of continuous pumping for a power plant.

The data is obtained by subtracting from a base computer run (without the power plant cooling wells), a run which includes the production and re-injection wells.

These trial data indicate that no severe perturbation will exist if proper well arrangements are designed. Further studies are planned using finer meshpoint spacing and transmissibility data obtained from actual well pump-down tests performed in that region of the valley. No consideration has yet been given to the problem of mixing in the aquifer in which water from production wells could be raised in temperature by the heated water being re-injected. This problem must be considered in any well field design.

-
- (1) D. Goldman, Application of a Mathematical Ground-Water Modeling Technique, 1974, M.S. Thesis, University of Idaho.

Fig. 1 Grid overlay of Raft River Valley defining the aquifer boundary and the approximate location of a proposed 10 megawatt power station.

TABLE I

CHANGE IN WATER TABLE HEIGHT AFTER 10 YEARS OF PUMPING
AND RE-INJECTION AT 3000 GAL/MIN AT EACH INDICATED WELL LOCATION

COL ROW	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28
76					0	1	2	3	4	5	5	5	5	6	5	6	5	5	5	3	1
77					0	2	3	4	4	5	6	6	6	6	6	6	5	5	4	4	1
78					0	3	4	4	5	5	6	6	6	7	6	7	7	6	5	4	1
79					0	3	4	4	5	5	7	7	8	7	7	7	7	6	6	4	1
80					0	2	3	4	5	6	7	7	8	8	8	7	8	7	6	4	2
81					1	2	2	4	4	6	7	8	9	9	9	9	8	8	6	5	2
82					0	0	1	2	4	6	7	9	11	11	10	9	10	8	7	5	1
83				-2	-2	-1	0	1	3	5	7	10	12	13	12	11	10	9	8	6	2
84				-3	-3	-3	-3	-1	1	3	7	11	13	16	14	12	10	10	7	5	2
85				-6	-6	-7	-5	-4	-1	2	6	11	16	18	14	12	11	9	8	4	2
86			-7	-9	-10	-10	-8	-7	-5	-2	3	11	14	14	13	11	10	8	7	4	2
87		-6	-10	-11	-12	-13	-13	-12	-11	-8	-2	4	8	9	9	9	7	7	5	4	2
88		-8	-11	-13	-13	-15	-16	-17	-18	-16	-8	-2	3	5	6	6	5	5	4	3	2
89	-5	-9	-11	-13	-15	-16	-19	-22	-24	-22	-12	-5	-2	1	3	4	4	4	3	3	2
90	-7	-9	-11	-12	-15	-17	-20	-24	-27	-21	-14	-8	-3	-1	2	2	2	2	2	1	1
91	-8	-9	-10	-12	-14	-16	-19	-21	-22	-19	-13	-9	-4	-1	0	1	2	2	2	1	1
92	-6	-8	-10	-11	-13	-15	-16	-18	-18	-15	-11	-8	-5	-2	-1	0	1	1	1	1	0
93	-6	-7	-8	-9	-11	-12	-13	-14	-14	-12	-9	-6	-4	-2	-1	0	0	1	1	1	0
94	-6	-6	-7	-8	-8	-9	-10	-10	-10	-9	-6	-5	-4	-2	-1	-1	0	0	0	0	0
95	-5	-5	-5	-6	-6	-6	-7	-6	-6	-5	-5	-4	-3	-2	-1	-1	0	0	0	1	1
96	-4	-4	-5	-4	-4	-4	-5	-5	-4	-4	-3	-2	-2	-1	-1	-1	0	0	0	0	0

Pump Locations

Production

Row	Col
90	15
90	16
89	16
89	17
88	17

Re-Injection

Row	Col
86	19
86	20
85	20
85	21
84	21

TABLE II

CHANGE IN WATER TABLE HEIGHT AFTER 10 YEARS OF PUMPING
AND RE-INJECTION AT 3000 GAL/MIN AT EACH INDICATED WELL LOCATION

COL ROW	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28
76					0	0	0	1	1	1	2	1	1	1	1	1	1	1	1	0	0
77					0	1	1	1	1	1	2	1	1	2	1	1	1	1	1	1	0
78					0	1	1	1	1	1	1	2	1	2	1	2	2	1	1	1	0
79					0	1	1	1	2	1	2	2	2	2	1	2	2	2	1	1	0
80					0	1	1	2	1	2	2	2	2	1	1	1	2	1	1	0	1
81					1	1	1	2	2	2	2	2	2	2	2	2	1	1	1	0	1
82				0	1	1	1	2	2	3	2	2	3	2	2	2	2	2	1	1	0
83				0	1	2	2	2	3	3	3	2	3	2	2	3	1	1	1	1	0
84				0	1	1	1	2	2	2	3	3	2	3	2	3	2	2	1	1	0
85				-1	0	0	2	2	3	3	3	3	3	3	3	2	2	1	2	0	0
86			-2	-2	-1	-1	1	2	3	4	4	4	4	3	3	2	2	2	1	1	1
87		-2	-3	-2	-3	-2	-1	2	4	5	5	5	4	3	3	2	2	2	1	1	0
88		-3	-4	-4	-4	-3	-2	2	4	7	6	5	4	3	3	2	2	1	1	1	0
89	-2	-4	-5	-5	-6	-6	-7	-8	-4	7	6	5	3	3	2	2	2	2	1	1	1
90	-3	-4	-5	-6	-7	-8	-10	-12	-10	6	5	4	3	3	3	2	1	1	1	0	0
91	-4	-5	-5	-6	-7	-8	-10	-16	-10	-1	2	2	3	3	2	1	1	1	1	1	0
92	-3	-4	-5	-6	-7	-8	-9	-11	-8	-3	0	1	1	1	2	1	1	1	1	0	0
93	-3	-4	-4	-5	-6	-7	-7	-8	-6	-4	-1	0	0	1	1	1	1	1	1	0	0
94	-3	-3	-3	-5	-4	-5	-6	-5	-4	-2	-1	0	0	1	1	0	1	1	0	0	0
95	-3	-2	-3	-3	-4	-4	-4	-3	-3	-2	-1	-1	0	0	0	0	0	0	0	1	1
96	-2	-2	-3	-2	-3	-2	-3	-3	-2	-1	-1	0	0	0	0	0	0	0	0	0	0

Pump Locations

Production

Row Col

91 15
90 15
90 16
89 15
89 16

Re-Injection

Row Col

90 17
89 17
88 17
88 16
88 15

SOUTHEASTERN IDAHO WIND POWER SCOPING CALCULATION

C. J. Shaffer

A wind power scoping calculation for Southeastern Idaho was performed to investigate the feasibility of producing electricity from wind as a source of power. This calculation included reducing the hourly wind velocity data for a year at several locations to determine the approximate power which could be generated by a windmill. Wind data obtained from the National Oceanic and Atmospheric Administration was reduced with a small computer program obtaining the total available wind power for a given windmill diameter as a function of wind velocity for each month of the year 1974. The largest yearly average power computed for a 100-ft diameter windmill was a yearly average 33.5 kW assuming 30% utilization of the total wind power. At this power rate, it would require over 20,000 wind stations to produce the annual output of one large nuclear plant assuming a 1000 MW plant on line 80% of the time. Conclusive results will require more extensive research of wind velocities specifically areas where the winds are naturally much higher than average such as mountain tops or valley and canyon channeling.

The methodology for making the site selection is developed from decision modeling techniques. Briefly it consists of determining a figure of merit for each siting alternative. The figure of merit is the weighted sum of the impacts and parameters for each site, which are displayed in a comparison matrix. The weighting is the measure of importance given to each impact or parameter and is a subjective value judgment.

While all techniques for site selection necessarily contain subjective factors, not all permit evaluating the effect of subjectivity on the outcome. This methodology employs sensitivity analysis to show how much error is allowed in a value judgment or in the estimate of an impact or parameter before a different site exhibits a higher figure of merit. The sensitivity analysis can be performed quite easily with a computer and plots of the figure of merit as a function of the error in value judgment, impact, or other parameter can be generated.

The optimization studies consider using a computerized model to study alternate ways of combining processes to determine the combination that would meet demands in a cost effective manner. The combined processes include those that convert coal to substitute natural gas, oil, electricity or other forms of energy suitable for industrial use.

Some of the criteria to be evaluated that have been identified are:

1. Processing costs, - annual costs due to capital, operation, maintenance, raw material costs and other direct material costs, all replaceable materials, catalyst, refractory liners, etc. (should be estimated for each process combination).
2. Mix capability for customer load variations - The diversity of the system and its performance under load factor and hourly or peak performance should be evaluated. The efficiency of the processes under part load operation should be compared.
3. Utilization efficiency - Thermal efficiencies and carbon efficiencies should be determined. Various process combinations should be simulated to optimize this step.
4. System Reliability - Failure rate of the different combinations should be calculated from the historical failure frequency of the components used in a subsystem. The cost of reserve equipment needed for scheduled shutdowns, failed equipment and peak loads should be determined for all combinations.
5. Scaling economics - Studies apply a general static model to generate costs/unit output as a function of output.

The criteria used for the optimization studies are also used for process comparison studies.

The high cost of synthetic fuels from coal require an examination of the cost details of processes under development. A systematic search of each process using a general static model can:

1. Point out the high cost areas of each process

SYNTHETIC FUELS FROM COAL STUDIES

K. D. Bulmahn, J. A. Close, S. Cohen
A. C. Crail, K. L. Smith, I. E. Stepan

Before a synthetic fuel from coal industry can contribute substantially to our natural liquid and gaseous fuels, many complex problems must be solved in a research, development and demonstration phase. A systems approach has been used in addressing the following specific synfuel problems which are of immediate interest to ERDA:

Site selection for pilot and demonstration plants

Optimization of processes and process comparison

Economic production of synfuels in large coalplexes (energy parks).

The site selection methodology places the many and diverse impacts which must be considered in siting studies on a common basis and generates a figure of merit for each siting alternative. The approach can be extended for siting of commercial plants as well. The major impacts and siting parameters which are considered are:

Economic (related to financing, operating costs, etc.)

Socio-Economic

Environmental

Resource Utilization

Site Suitability

Identification and interrelation of the impacts and parameters are accomplished in a formal manner through the use of event trees. After a preliminary investigation the important impacts, parameters and interrelationships are selected for use in the site selection.

The impacts are formulated with three considerations in mind:

1. Magnitude of impact
2. Duration of impact
3. Value or cost of impact

The major effort in developing a method for site evaluation is defining the impacts and other parameters, determining which should be included in the evaluation, and developing the algorithms to calculate them.

2. Determine the feasibility of applying cost effective alternative sub-processes.
3. Point out areas for the application of cost effective research and development.

One of the principal goals of the fossil energy park studies is to examine in detail the disadvantages and benefits of using coalplexes rather than dispersed plants. The methodology for site selection discussed above can be adapted quite readily to make these comparisons. Extension of the optimization and process comparison studies previously discussed can also contribute, particularly in analyses of product mix, load matching to reduce costly equipment idle-time, and reliability. An event tree has been developed which identifies important aspects of coalplex development and operation which deserve detailed study.

SCHLUMBERGER MEASUREMENT FIELD PACK

J. G. Richardson

Two Schlumberger Measurement Field Packs have been developed to aid in studies being conducted by Boise State University in conjunction with Aerojet's geothermal effort in the Boise area. The portable, battery-powered instruments are used to obtain earth resistivity data that will aid in the location of potentially useful reservoirs of geothermal water.

Each Field Pack consists of an earth potential nulling network, a high-gain DC amplifier and low-pass filter, and a strip chart recorder. Common-mode earth potentials up to 4.5 volts can be nulled out and the unit can detect induced Schlumberger signals as low as $10\mu\text{v}$.

Because many of the measurements are made in or near the Boise metropolitan area, 1.6 HZ low-pass filter was included in the instrument to provide sufficient rejection of 60 HZ and other man-made and natural noise sources.

Both Schlumberger Measurement Field Packs have been used successfully in the field for some time. The data obtained from them has been a valuable contribution to the Boise geothermal project.

RELATED ACTIVITIES OF DIVISION PERSONNEL

THIS PAGE
WAS INTENTIONALLY
LEFT BLANK

PROFESSIONAL ACTIVITIES OF DIVISION PERSONNEL

Besides their direct research accomplishments and their activities in support of education, Division personnel are often called upon to assume other professional responsibilities and duties. During the past year the following staff members have been so engaged:

A. E. Arave: ASTM Committee, E-20.6 Committee on Acoustic Thermometry.

W. R. Carpenter: Reviewer for Nuclear Technology; Member of ANS Standards Subcommittee (ANS-8.9).

R. C. Davies: President-Elect of Digital Equipment Computer User Society.

N. C. Dyer: Health Physics Society Task Committee on Airline Shipment of Radioactive Packages; Advisory Group for EPRI Program on In-plant Radioiodine and Other Radionuclide Measurements.

E. Fast: Reviewer for Nuclear Technology.

R. C. Greenwood: Brookhaven National Laboratory (1-year appointment); Member of Special Publication Committee ANS.

Y. D. Harker: Member of Fission Product Subcommittee of Cross-Sections Evaluations Working Group (CSEWG); Contributor to Data Testing Subcommittee of CSEWG; Participant in Interlaboratory LMFBR Reactor Rates (ILRR) program.

R. L. Heath: Member of the U. S. Nuclear Data Committee Reviewer for Nuclear Science and Engineering, Physical Review, Nuclear Instruments and Methods, and Journal of Analytical and Nuclear Chemistry; U. S. Delegate to I.A.E.A. Panel concerned with "Applications of Modern Technology in the Emerging African Nations" - ACCRN, Ghana, Africa, July 1-5, 1975.

J. W. Henscheid: Secretary, Eastern Idaho Section, ANS.

R. G. Helmer: Review for Physical Review; Member of IUPAP Task Group on Gamma-Ray Calibration Energies.

C. W. Reich: Review for Physical Review; Member of Fission Product Subcommittee, Cross-Sections Evaluation Working Group, ERDA; Adjoint Professor of Physics and Collaborator, Utah State University.

J. W. Rogers: Participant in Interlaboratory LMFBR Reaction Rate (ILRR) program.

F. B. Simpson: Ex-officio Member of Transplutonium Committee, AEC.

S. C. Wilkins: ASTM Committee, E-20 Committee on Temperature Measurement.

NUCLEAR TECHNOLOGY DIVISION
Reports Issued During FY 1975

<u>Author(s)</u>	<u>Report No.</u>	<u>Title</u>	<u>Issue Date</u>
C. W. Reich R. G. Helmer M. H. Putnam	ANCR-1157 (ENDF-210)	Radioactive-Nuclide Decay Data for ENDF,B	August, 1974
E. B. Nieschmidt N. C. Dyer E. W. Killian R. A. Coates	ANCR-1171	The Application of a Real-Time Stack Monitor Using a Ge(Li) Detector and a PDP-9 Processor	November, 1974
C. W. Reich R. C. Greenwood R. G. Helmer R. J. Gehrke R. L. Heath	ANCR-1200	Annual Progress Report - Nuclear Structure Studies Utilizing LAMPF	January, 1975
G. D. Lassahn	ANCR-1201	Mathematical Analysis of a Two-Beam Gamma Densitometer	February, 1975
R. S. Marsden F. J. Wheeler D. E. Wessol	ANCR-1206	A Mixed-Zone Geometry Option for the RAFFLE General Purpose Monte Carlo Code	February, 1975
G. D. Lassahn	ANCR-1216	Two-Phase Flow Velocity Measurement with Radiation Intensity Correlation	June, 1975
A. E. Arave	ANCR-1225	Comparison of Four Tungsten Alloys for use as Ultrasonic Thermometer Sensors	June, 1975

NUCLEAR TECHNOLOGY DIVISION

Presentation of Technical Papers

Author(s)	Subject	Group	Place, Date
W. C. Dyer R. J. Schultz E. W. Killian J. E. Baston	Calculation of the Radiation Dose from an Upset Condition in the Off-Gas System for a Boiling Water Power Reactor	13th USAEC Air Cleaning Conference	Springfield, VA 1974
R. L. Heath N. C. Dyer	Application of Gamma-Ray Spectrometry in Real-Time Environmental Monitoring	Conference on Nuclear Methods in Environmental Research	Columbia, MO 1974
E. B. Nieschmidt N. C. Dyer E. W. Killian R. A. Coates	The Application of a Real-Time Stack Monitor Using a Ge(Li) Detector and a PDP-9 Processor	Health Physics Society	Houston, Texas July, 1974
J. E. Brasier	Axial Flux Tailoring Methods in Test Reactors	ANS Conference on Research, Test & Training Reactors	University of VA Charlottesville, VA August, 1974
R. C. Greenwood C. W. Reich R. E. Chrien K. Rimawi	Energy Levels of ^{155}Gd and ^{157}Gd Populated by the (n,γ) Reaction Using 24.5-keV Neutrons	International Symposium on Neutron Capture Gamma-ray Spectroscopy and Related Topics	Petten, The Netherlands, September 2-6, 1974
J. A. Close K. L. Smith	A Systems Model to Evaluate the Production of Synthetic Fuels from Coal	First National Topical Meeting on Nuclear Process Heat Applications	Los Alamos Scientific Lab. Los Alamos, NM October 1-3, 1974
J. R. Chick G. E. Morris	Applications of Interactive Simulation Language	EAI Computer User's Group	Coeur d'Alene, Ida October, 1974

NUCLEAR TECHNOLOGY DIVISION

Presentation of Technical Papers

Author(s)	Subject	Group	Place, Date
R. G. Helmer R. C. Greenwood R. J. Gehrke C. W. Reich	Gamma-Ray Studies of the Decay of ^{128}Ba and ^{128}Cs	Fall Meeting, Division of Nuclear Physics, American Physics Society	Pittsburgh, PA Oct. 31, Nov. 2, 1974
R. C. Greenwood C. W. Reich ¹ R. C. Crien ¹ K. Rimawi	Energy Levels of ^{155}Gd and ^{157}Gd Populated by the (n, γ) Reaction Using 24-keV Neutrons	Fall Meeting, Division of Nuclear Physics, American Physics Society	Pittsburgh, PA Oct. 31, Nov. 2, 1974
J. J. Feeley	A Digital Simulation of the LOFT Reactor Coolant Pumping System	ANS Annual Meeting	Washington, D. C. November, 1974
A. E. Arave	Use of Tungsten - 2% Thoria Ultrasonic Transmission Line and Sensor to Improve the Performance of High Temperature Ultrasonic Thermometry	Joint J.R.C. Petten International Colloquium on High Temp. In-Pile Thermometry	The Netherlands December, 1974
F. J. Wheeler	Sn Analysis of the TRX Metal Lattices with ENDF/B Version III Data	Seminar on ^{238}U Resonance Capture	Brookhaven Nat. Lab. March, 1975
R. A. Anderl Y. D. Harker E. H. Turk ² R. G. Nisle ³ J. R. Berreth	Integral Capture Cross-Section Measurements in the CFRMF for LMFBR Control Materials	Conference on Nuclear Cross Sections and Technology	Washington, D. C. Mar. 3-7, 1975
C. W. Reich R. G. Helmer	Radioactive-Nuclide Decay Data in Science and Technology	Conference on Nuclear Cross Sections and Technology	Washington, D.C. Mar. 3-7, 1975

NUCLEAR TECHNOLOGY DIVISION

Presentation of Technical Papers

Author(s)	Subject	Group	Place, Date
R. G. Helmer R. C. Greenwood	Evaluated Decay-Scheme Data for the ILRR Program	Conference on Nuclear Cross Sections and Technology	Washington, D. C. Mar. 3-7, 1975
R. C. Greenwood ¹ R. E. Crien	Radiative Capture of Neutrons in the keV Region	Conference on Nuclear Cross Sections and Technology	Washington, D. C. Mar. 3-7, 1975
E. W. Killian R. L. Heath	Remote Acquisition of Gamma-Ray Pulse- Height Spectra	Digital Equipment Computer User Society	Miami, Florida April, 1975
W. R. Myers	Multiple-Task Real-Time PDP-15 Operating System for Data Acquisition and Analysis	Digital Equipment Computer User Society	Miami, Florida April, 1975
405 M. S. Cole W. R. Myers	Preparation of Minicomputer Software Using Large Computer Systems	Digital Equipment Computer User Society	Miami, Florida April, 1975
R. C. Davies	Basic Interrupt and Command Structures and Applications	Digital Equipment Computer User Society	Miami, Florida April, 1975
T. C. Piper	Variable Reluctance Displacement Trans- ducer Temperature Compensated to 650°F	Eighth Transducer Workshop in Dayton,	Dayton, Ohio April, 21, 1975
R. L. Heath	Developments in Architecture for Real- Time Data Systems	IEEE International Confer- ence on Nuclear Electronics	Ispra, Italy May, 1975
R. G. Helmer R. C. Greenwood R. J. Gehrke	Gamma-Ray Energies for Calibration of Ge(Li) Spectrometers	Fifth International Confer- ence on Atomic Masses and Fundamental Constants	Paris, France June 2-6, 1975
J-D. Schmutz	Fabrication of Internally Instrumented Reactor Fuel Rods	ANS Meeting	New Orleans, LA June 13, 1975

NUCLEAR TECHNOLOGY DIVISION
Presentation of Technical Papers

¹Brookhaven National Laboratory

²Retired

³Allied Chemical Corporation - ICPP Idaho National Engineering Laboratory

NUCLEAR TECHNOLOGY DIVISION

Papers Published in the Open Literature

Author(s)	Title	Publication
N. C. Dyer R. J. Schultz E. W. Killian J. E. Baston	Radiation Dose Calculation to Off-Site Personnel from a Delay Line Break for a Boiling Water Nuclear Power Reactor	<u>Health Physics 27 (1974)</u>
E. B. Nieschmidt N. C. Dyer E. W. Killian R. A. Coates	The Application of a Real-Time Stack Monitor Using a Ge(Li) Detector and PDP-9 Processor	<u>Health Physics 27 (1974)</u>
M. M. Mansour N. C. Dyer L. H. Hoffman J. Davies A. B. Brill	Placental Transfer of Mercuric Nitrate and Methyl Mercury in the Rat	<u>American Journal of Ob. and Gyn. 119 (1974)</u>
R. J. Baglan A. B. Brill A. R. Schulert D. Wilson K. Larsen N. C. Dyer M. M. Mansour W. Schaffner L. H. Hoffmar J. Davies	Utility of Placental Tissue as an Indicator of Trace Element Exposure to Adult and Fetus	<u>Environmental Research 8 (1974)</u>

NUCLEAR TECHNOLOGY DIVISION

Papers Published in the Open Literature

Author(s)	Title	Publication
¹ D. J. McMillan R. C. Greenwood C. W. Reich R. G. Helmer	Level Structure of ^{184}W from the Decay of $^{184\text{m}}\text{Re}$ and $^{184\text{g}}\text{Re}$	<u>Nuclear Physics A223</u> (1974)
R. C. Greenwood C. W. Reich	Level Structure of ^{184}W from the $^{183}\text{W}(\text{r},\gamma)$ Reaction	<u>Nuclear Physics A233</u> (1974)
C. W. Reich R. C. Greenwood ¹ R. A. Lokken	Decay of ^{172}Tm : The Mixing of $K\pi=0^+$ and 2^+ Bands in ^{172}Yb	<u>Nuclear Physics A228</u> (1974)
J. E. Brasier	Axial Flux Tailoring Methods in Test Reactors	<u>Transactions of the</u> <u>ANS Conference on</u> <u>Research, Test & Training</u> <u>Reactors, August, 1974</u>
J. A. Close	A Systems Model to Evaluate the Production of Synthetic Fuels from Coal	LA-5795-C, (Conf-74 1032) October 1974
J. J. Feeley	A Digital Simulation of the LOFT Reactor Coolant Pumping System	<u>Transactions of 1974</u> <u>Winter Meeting of ANS,</u> October, 1974
N. C. Dyer A. B. Brill W. S. Lyon	Biomedical Studies Using Nuclear Activation Tech.	<u>American Nuclear Society</u> <u>Transactions 21 (1975)</u>
R. J. Gehrke R. G. Helmer	Nickel-59 Excitation Source for X-Ray Fluorescence Analysis of Carbon and Low Alloy Steel	<u>X-Ray Spectrometry 4</u> (1975)

NUCLEAR TECHNOLOGY DIVISION

Papers Published in the Open Literature

Author(s)	Title	Publication
R. J. Gehrke R. C. Davies	Spectrum Fitting Technique for Energy Dispersive X-Ray Analysis of Oxides and Silicates with Electron Micro-beam Excitations	<u>Analytical Chemistry 47</u> (1975)
R. G. Helmer R. J. Gehrke R. C. Greenwood	Peak Position Variation with Source Geometry in Ge(Li) Detector Spectra	<u>Nuclear Instruments and Methods 123</u> (1975)
J. W. Rogers D. A. Millsap Y. D. Harker	CFRME Neutron Field Flux Spectral Characterization	<u>Nuclear Technology 25</u> (1975)
2,3 L. A. Kroger C. W. Reich	Nuclear Data Sheets for A-155	<u>Nuclear Data Sheets 15</u> (1975)
R. G. Helmer R. C. Greenwood	Evaluated Decay Scheme Data	<u>Nuclear Technology 25</u> (1975)
R. C. Greenwood R. G. Helmer J. W. Rogers 4N. D. Dudey 4R. J. Popek 5L. S. Kellogg 6W. H. Zimmer	Nonfission Reaction Rate Measurements	<u>Nuclear Technology 25</u> (1975)
4N. D. Dudey 4R. J. Popek R. C. Greenwood R. G. Helmer J. W. Rogers 5L. S. Kellogg 6W. H. Zimmer	Fission-Product Rate Measurements and Yields	<u>Nuclear Technology 25</u> (1975)

NUCLEAR TECHNOLOGY DIVISION

Papers Published in the Open Literature

Author(s)	Title	Publication
F. J. Wheeler	Sn Analysis of the TRX Metal Lattices with END= /B Version III Data	Seminar on ^{238}U Resonance Capture, BNL-NCS-50451, (March, 1975)
J. R. Smith	Manganese Bath Systematic Effects of NuBar and Eta	Wash. D. C. Conference on Nuclear Cross Sections and Technology, (Mar. 1975)

¹Physics Department, University of Wisconsin - Stevens Point, Stevens Point, Wisconsin.

²Nuclear Information Research Associate, Work Supported by the National Science Foundation through the National Academy of Sciences - National Research Council, Committee on Nuclear Science.

³Present address: The Emergency Care Research Institute, 913 Walnut Street, Philadelphia, Pa.

⁴Argonne National Laboratory

⁵Hanford Engineering Development Laboratory

⁶Atlantic-Richfield Hanford Company

DISTRIBUTION RECORD FOR ANCR-1255

External

171 - UC-2, General, Miscellaneous, and Progress Reports (Nuclear)
TID-4500, R63

Internal

1 - Chicago Patent Group - ERDA
9800 South Cass Avenue
Argonne, Illinois 60439

3 - A. T. Morphew, Classification and Technical Information Officer
ERDA-ID
Idaho Falls, Idaho 83401

31 - INEL Technical Library

20 - R. L. Heath

20 - J. W. Henscheid

20 - G. L. Smith

Total Copies Printed - 266