CHARACTERIZATION OF OIL AND GAS RESERVOIR HETEROGENEITY

Cooperative Agreement DE-FG07-90ID12839

DOE/ID/12839--8

Petroleum Development Laboratory
University of Alaska Fairbanks
437 Duckering Building
Fairbanks, AK 99775-1260

DE93 000517

Contract Date: November 1, 1989
Anticipated Completion: March 31, 1993
Total Project Cost:

DOE Funding for FY 1992:	\$195,000
Contractor:	<u>\$195,000</u>

Total	\$390,000
-------	-----------

Principal Investigator:
G. D. Sharma

Project Manager:
Idaho Operations Office

Reporting Period: April 1, 1992 - June 30, 1992

OBJECTIVE

The ultimate objective of this cooperative research project is to characterize Alaskan petroleum reservoirs in terms of their reserves, physical and chemical properties, geologic configuration in relation to lithofacies and structure, and development potential.

The project has two tasks: Task 1 is a geological description of the reservoirs including petrophysical properties, i.e., porosity, permeability, permeability variation, formation depth, temperature, and net pay, facies changes and reservoir structures as drawn from cores, well logs, and other geological data. Task 2 is reservoir fluid characterization—determination of physical properties of reservoir fluids including density, viscosity, phase distributions and composition as well as petrogenesis—source rock identification; and the study of asphaltene precipitation for Alaskan crude oils.

SUMMARY OF TECHNICAL PROGRESS

MILNE POINT

The Milne Point field lies in the northeastern part of the Kuparuk River Unit. The Kuparuk River formation is distributed throughout most of northern Alaska. The sediments were deposited during the Jurassic and Lower Cretaceous rifting episode in the Arctic. Silts and shale of the Jurassic Kingak formation overlain by Miluveach and Kuparuk formations represent the synrift sequence. The bottom Kingak shale of northern source were deposited on the shelf and the slope while the Miluveach shales and Kuparuk sandstones were derived from the adjacent Barrow Arch. The clastics of Kuparuk formation consist of deltaic-fluvial dominated shelf deposits. Facies include channel sandstones, shelf shales and siltstones.

The structural map of the top of Middle Kuparuk at Milne Point field (Figures 1 and 2) suggests a northwest oriented anticlinal structure with a steep plunge towards the northeast and with a prominent saddle at the crest. The anticline also has a slight plunge to the northwest (Figure 3). The structural geometry of the Milne Point field appears to be a faulted anticline with a northwesterly plunge. The Milne Point hydrocarbon accumulation is trapped along the crest of the anticlinal structure.

Major faults trending northwest-southeast may also occur on either side of the main field. Such faults could have provided the major structural impetus for the concentration of oil at Milne Point, in that an uplifted and tilted block with limits defined by these faults may have developed there. Analysis of well test and pressure data may provide insight as to whether any such existing faults are sealing or not. Faulting of this type occurs elsewhere on the North Slope, and was instrumental in the development of reservoirs at Endicott and Prudhoe Bay.

Continued structural analysis and mapping of the Middle and Lower Kuparuk at Milne Point, including placement of major faults, will be integrated with stratigraphic analysis. Utilization of dip meter data and isopach mapping from shallow horizons down to the Kuparuk should yield a greater understanding of faulting at Milne Point and how faulting may have affected reservoir development. Evaluation of well log trace character, dip meter data, and other available data will continue as part of the stratigraphic analysis.

Figure 1. Structure Map of the Top Middle Kuperuk at Milne Point Field.
(A-A' and B-B' are cross section lines for Figures 2 and 3, respectively)

**Figure 2. Northeast-Southwest Stratigraphic Cross Section (strike line)
of the Lower and Middle Kuparuk Formations
Illustrating Subzone Thickness Variations in Milne Point Field.**

**Figure 3. Northwest-Southeast Stratigraphic Cross Section
of the Lower and Middle Kuparuk Formation
Illustrating Subzone Thickness Variations in Milne Point Field.**

RESERVOIR FLUID CHARACTERIZATION

Under the reservoir fluid characterization task, work on two subtasks were conducted which include: 1) characterization of fluid properties of oils from Alaskan North Slope reservoirs; and 2) study of effect of asphaltene deposition on rock-fluid properties.

a) Fluid Property Characterization

All the available oil PVT and fluid property data for Prudhoe Bay, Kuparuk, Endicott and West Sak reservoirs has been compiled for the generation of fluid property data base. Additional fluid property data for 15 regions of Prudhoe Bay reservoir and 3 regions of Kuparuk River reservoir have been requested from BP Exploration (Alaska) Inc. and ARCO Alaska (Inc.). With the availability of such data, the variation in fluid properties can be better understood.

b) Effect of Asphaltene Deposition on Rock-Fluid Properties

The understanding of the effect of asphaltene deposition during miscible displacement processes on the rock-fluid properties is important since the asphaltene deposition will affect the sweep and displacement efficiencies of such processes. Very little is understood about the dynamic effects of asphaltene deposition on the rock-fluid properties as well as on the oil recovery efficiency. The in-situ precipitated asphaltenes from oil due to interaction between the miscible solvent and oil will result in adsorption of asphaltenes on the rock surfaces and cause alteration of the wettability of the rock surfaces. The larger size asphaltene particles will partially block the pore space causing permeability reduction and the smaller size asphaltene particles may get transported along with the oil through larger size pores.

The objective of this experimental work was to quantify the effect of asphaltene deposition on the absolute permeability reduction, the oil-water relative permeability changes, the displacement performance and the oil recovery for different types of porous media. Unsteady-state dynamic displacement tests (water displacing oil under varying degree of asphaltene deposition) were conducted for three different types of cores. The first sets of experiments were conducted with consoli-

dated Berea Sandstone core. The next two sets of experiments were conducted with two different unconsolidated sand cores of different original absolute permeability, porosity and sand grain size distribution.

Table 1 gives the properties of each of the cores used. Table 2 gives the sand grain size distributions for the two unconsolidated cores (core number 2 and 3). After measuring the core properties such as porosity and absolute permeability prior to asphaltene deposition, asphaltenes were deposited into the cores by simultaneous injection of solvents such as n-pentane or n-heptane and West Sak oil. The degree of asphaltenes deposited for each run was varied by varying the solvent/oil injection ratio. For each core, four unsteady-state dynamic displacements were conducted. The amount of asphaltene deposited for runs 1 through 4 were 0.0, 5.1, 9.9 and 12.8 wt% asphaltenes, respectively. The dynamic oil displacements were conducted by injecting brine at a constant rate of 0.019 cc/min for all the runs. The pressure drop, oil recovery and water production at various pore volumes of water injected were continuously monitored throughout each run.

Table 1. Properties of Cores Used for Study of Asphaltene Deposition Effect.

PROPERTY	CORE NO. 1	CORE NO. 2	CORE NO. 3
Core Type	Consolidated Berea Sandstone	Unconsolidated Sand (20-42 mesh)	Unconsolidated Sand (60-150 mesh)
Length (cm)	25.20	25.38	27.07
Diameter (cm)	2.527	2.667	2.667
Porosity (%)	27.86	32.67	31.25
Absolute Permeability (MD)	236	2380	1520
Initial Irreducible Water Saturation (%)	19.98	24.80	15.60

Table 2. Sand Grain Size Distribution for Unconsolidated Sand Cores (Weight %).

MESH	GRAIN DIAMETER (INCHES)	CORE NO. 2	CORE NO. 3
16	0.0390	0.00	0.00
20	0.0328	4.95	0.00
24	0.0276	42.66	0.00
32	0.0195	42.78	0.00
35	0.0164	7.32	0.00
42	0.0138	2.29	0.00
60	0.0097	0.00	1.94
65	0.0082	0.00	69.66
100	0.0058	0.00	22.86
115	0.0049	0.00	4.73
150	0.0041	0.00	0.93

Figure 4 shows the ratio of absolute permeability of the core after asphaltene deposition to the original absolute permeability the core (K_i/K_o) for all three cores at various degrees of asphaltene deposition. For core number 1 with lowest initial absolute permeability ($K_o = 236$ md), the permeability reduction is highest (about 50% at 12.8% asphaltene deposited), whereas for core number 2 with the highest initial absolute permeability ($K_o = 2380$ md), the permeability reduction is lowest (about 26% at 12.8% asphaltene deposited). This can be explained by traditional capillary model of porous media. The figure shows that the degree of permeability reduction increases with the increase in the degree of asphaltene deposition and increases with the decrease in the original absolute permeability of the core. Figures 5, 6 and 7 give the cumulative fractional oil recovery (N_p) versus pore volumes of water injected (Q_i) at various degrees of asphaltene deposition for cores 1, 2 and 3,

respectively. These figures clearly indicate that asphaltene deposition has resulted in the improved displacement performance and oil recovery. Figures 8, 9 and 10 show the ratio of relative oil permeability to relative water permeability (K_{ro}/K_{rw}) as a function of water saturation at various degrees of asphaltene deposition for cores 1, 2 and 3, respectively. These plots also clearly indicate that the asphaltene deposition causes increase in relative permeability of oil and decrease in relative permeability of water and results in improved fractional flow of oil, displacement performance and oil recovery. Although the wettability changes due to asphaltene deposition were not measured in these experiments, we believe that asphaltene deposition resulted in the wettability alterations and also affected the irreducible water saturation and residual oil saturations.

Figure 4. The Ratio of Absolute Core Permeability After Asphaltene Deposition to the Original Absolute Permeability (K_i/K_o) as a Function of Degree of Asphaltene Deposition.

**Figure 5. Cumulative Fractional Oil Recovery (N_p)
Versus Pore Volumes of Water Injected (Q_i) for Core No. 1.**

**Figure 6. Cumulative Fractional Oil Recovery (N_p)
Versus Pore Volumes of Water Injected (Q_i) for Core No. 2.**

**Figure 7. Cumulative Fractional Oil Recovery (N_p)
Versus Pore Volumes of Water Injected (N_p) for Core No. 3.**

**Figure 8. Effect of Asphaltene Deposition
on Ratio of Relative Permeabilities (Core No. 1).**

**Figure 9. Effect of Asphaltene Deposition
on Ratio of Relative Permeabilities (Core No. 2).**

Figure 10. Effect of Asphaltene Deposition on Ratio of Relative Permeabilities (Core No. 3).

END

DATE
FILMED

11 / 19 / 92